

Gateway Documentation - FCUBSRMService
Oracle FLEXCUBE Universal Banking
Release FCUBS_12.1.0.0.0
[October][2015]



Table Of Contents

1. Background	1
2. FCUBSRMSERVICE	2
2.1. AuthorizeReportParam	2
2.1.1. ST-AuthorizeReportParam-Req-Full-MSG.xsd	2
2.1.2. ST-AuthorizeReportParam-Req-IO-MSG.xsd	13
2.1.3. ST-AuthorizeReportParam-Res-Full-MSG.xsd	21
2.1.4. ST-AuthorizeReportParam-Res-PK-MSG.xsd	34
2.2. AuthorizeRMHierarchy	43
2.2.1. ST-AuthorizeRMHierarchy-Req-Full-MSG.xsd	43
2.2.2. ST-AuthorizeRMHierarchy-Req-IO-MSG.xsd	53
2.2.3. ST-AuthorizeRMHierarchy-Res-Full-MSG.xsd	60
2.2.4. ST-AuthorizeRMHierarchy-Res-PK-MSG.xsd	71
2.3. AuthorizeRMMassAmend	80
2.3.1. ST-AuthorizeRMMassAmend-Req-Full-MSG.xsd	80
2.3.2. ST-AuthorizeRMMassAmend-Req-IO-MSG.xsd	92
2.3.3. ST-AuthorizeRMMassAmend-Res-Full-MSG.xsd	99
2.3.4. ST-AuthorizeRMMassAmend-Res-PK-MSG.xsd	112
2.4. CloseRMHierarchy	121
2.4.1. ST-CloseRMHierarchy-Req-Full-MSG.xsd	121
2.4.2. ST-CloseRMHierarchy-Req-IO-MSG.xsd	131
2.4.3. ST-CloseRMHierarchy-Res-Full-MSG.xsd	138
2.4.4. ST-CloseRMHierarchy-Res-PK-MSG.xsd	149
2.5. CreateReportParam	158
2.5.1. ST-CreateReportParam-Req-Full-MSG.xsd	158
2.5.2. ST-CreateReportParam-Req-IO-MSG.xsd	170
2.5.3. ST-CreateReportParam-Res-Full-MSG.xsd	180
2.5.4. ST-CreateReportParam-Res-PK-MSG.xsd	193
2.6. CreateRMHierarchy	204
2.6.1. ST-CreateRMHierarchy-Req-Full-MSG.xsd	204
2.6.2. ST-CreateRMHierarchy-Req-IO-MSG.xsd	213
2.6.3. ST-CreateRMHierarchy-Res-Full-MSG.xsd	220
2.6.4. ST-CreateRMHierarchy-Res-PK-MSG.xsd	231
2.7. CreateRMMassAmend	240
2.7.1. ST-CreateRMMassAmend-Req-Full-MSG.xsd	240
2.7.2. ST-CreateRMMassAmend-Req-IO-MSG.xsd	251
2.7.3. ST-CreateRMMassAmend-Res-Full-MSG.xsd	259
2.7.4. ST-CreateRMMassAmend-Res-PK-MSG.xsd	272
2.8. DeleteRMHierarchy	282
2.8.1. ST-DeleteRMHierarchy-Req-Full-MSG.xsd	282
2.8.2. ST-DeleteRMHierarchy-Req-IO-MSG.xsd	291
2.8.3. ST-DeleteRMHierarchy-Res-Full-MSG.xsd	298
2.8.4. ST-DeleteRMHierarchy-Res-PK-MSG.xsd	309
2.9. DeleteRMMassAmend	317
2.9.1. ST-DeleteRMMassAmend-Req-Full-MSG.xsd	317
2.9.2. ST-DeleteRMMassAmend-Req-IO-MSG.xsd	329
2.9.3. ST-DeleteRMMassAmend-Res-Full-MSG.xsd	335
2.9.4. ST-DeleteRMMassAmend-Res-PK-MSG.xsd	348
2.10. ModifyReportParam	357

2.10.1.ST-ModifyReportParam-Req-Full-MSG.xsd	357
2.10.2.ST-ModifyReportParam-Req-IO-MSG.xsd	368
2.10.3.ST-ModifyReportParam-Res-Full-MSG.xsd	378
2.10.4.ST-ModifyReportParam-Res-PK-MSG.xsd	391
2.11.ModifyRMHierarchy	403
2.11.1.ST-ModifyRMHierarchy-Req-Full-MSG.xsd	403
2.11.2.ST-ModifyRMHierarchy-Req-IO-MSG.xsd	413
2.11.3.ST-ModifyRMHierarchy-Res-Full-MSG.xsd	420
2.11.4.ST-ModifyRMHierarchy-Res-PK-MSG.xsd	431
2.12.ModifyRMMassAmend	440
2.12.1.ST-ModifyRMMassAmend-Req-Full-MSG.xsd	440
2.12.2.ST-ModifyRMMassAmend-Req-IO-MSG.xsd	452
2.12.3.ST-ModifyRMMassAmend-Res-Full-MSG.xsd	461
2.12.4.ST-ModifyRMMassAmend-Res-PK-MSG.xsd	474
2.13.QueryReportParam	486
2.13.1.ST-QueryReportParam-Req-IO-MSG.xsd	486
2.13.2.ST-QueryReportParam-Res-Full-MSG.xsd	492
2.14.QueryRMHierarchy	506
2.14.1.ST-QueryRMHierarchy-Req-IO-MSG.xsd	506
2.14.2.ST-QueryRMHierarchy-Res-Full-MSG.xsd	512
2.15.QueryRMMassAmend	524
2.15.1.ST-QueryRMMassAmend-Req-IO-MSG.xsd	524
2.15.2.ST-QueryRMMassAmend-Res-Full-MSG.xsd	530
2.16.ReopenRMHierarchy	543
2.16.1.ST-ReopenRMHierarchy-Req-Full-MSG.xsd	543
2.16.2.ST-ReopenRMHierarchy-Req-IO-MSG.xsd	553
2.16.3.ST-ReopenRMHierarchy-Res-Full-MSG.xsd	560
2.16.4.ST-ReopenRMHierarchy-Res-PK-MSG.xsd	571

1. Background

Integration of different applications and solutions is a key area in today's systems. A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data. The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs. The integration needs supported by the Gateway can be broadly categorized from the perspective of Gateway as follows

1. Inbound application integration :

This is used when any external system needs to add, modify or query information within FLEXCUBE UBS

2. Outbound application integration :

This is used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS

The following sections provide detailed XSD documentation of all operations available in FCUBSRMService of Core Module

2. FCUBSRMSERVICE

2.1. AuthorizeReportParam

2.1.1. ST-AuthorizeReportParam-Req-Full-MSG.xsd

AUTHORIZEREPORTPARAM_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Report-Params-Full

LIEN_LIMIT_PERCENT

WITHDRAWAL_THRESHOLD

DEPOSIT_THRESHOLD

NEGATIVE_BAL_THRESHOLD

UTIL_PERCENT

CUST_DUE_FOR_COLL_REV

CUST_DUE_FOR_CR_LINE_EXP

TD_MATDAYS

LOAN_MATDAYS

BANKCODE

WAKALA_EXPIRE_DAYS

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

AUTHORIZEReportParam_FSFS_REQ

Attribute	Description
Name	AUTHORIZEReportParam_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	string

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

MSGID

Attribute	Description					
Name	MSGID					
Datatype	string					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	string					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
------------------	--------------------

Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute		Description
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	
	minOccurs	0

DESTINATION

Attribute		Description
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute		Description
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Request of AuthorizeReportParam	

Report-Params-Full

Attribute	Description
Name	Report-Params-Full
Datatype	
Description	

LIEN_LIMIT_PERCENT

Attribute	Description				
Name	LIEN_LIMIT_PERCENT				
Datatype	decimal				
Description	Indicates Lien Limit Percentage				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

WITHDRAWAL_THRESHOLD

Attribute	Description				
Name	WITHDRAWAL_THRESHOLD				
Datatype	decimal				
Description	Indicates Withdrawal Threshold				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

DEPOSIT_THRESHOLD

Attribute	Description				
Name	DEPOSIT_THRESHOLD				
Datatype	decimal				
Description	Indicates Deposit Threshold				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

NEGATIVE_BAL_THRESHOLD

Attribute	Description				
Name	NEGATIVE_BAL_THRESHOLD				
Datatype	decimal				
Description	Indicates Negative Balance Threshold				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	totalDigits	22

UTIL_PERCENT

Attribute	Description	
Name	UTIL_PERCENT	
Datatype	decimal	
Description	Indicates Utilization Percentage	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

CUST_DUE_FOR_COLL_REV

Attribute	Description	
Name	CUST_DUE_FOR_COLL_REV	
Datatype	decimal	
Description	Indicates Customers Due For Collateral Revaluation	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

CUST_DUE_FOR_CR_LINE_EXP

Attribute	Description	
Name	CUST_DUE_FOR_CR_LINE_EXP	
Datatype	decimal	
Description	Indicates Customers Due For Credit Line Expiry	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

TD_MATDAYS

Attribute	Description	
Name	TD_MATDAYS	
Datatype	decimal	
Description	Indicates TD mature days	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

LOAN_MATDAYS

Attribute	Description	
Name	LOAN_MATDAYS	
Datatype	decimal	
Description	Indicates Loan mature days	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

BANKCODE

Attribute	Description	
Name	BANKCODE	
Datatype	string	
Description	Indicates Bank Code	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

WAKALA_EXPIRE_DAYS

Attribute	Description	
Name	WAKALA_EXPIRE_DAYS	
Datatype	decimal	
Description	Indicates Wakala Expire Days	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

2.1.2.ST-AuthorizeReportParam-Req-IO-MSG.xsd

AUTHORIZEREPORTPARAM_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
 NAME
 VALUE
FCUBS_BODY
 Report-Params-IO
 BANKCODE
 CHECKER
 CHECKERSTAMP
 MODNO

AUTHORIZEREPORTPARAM_IOPK_REQ

Attribute	Description
Name	AUTHORIZEREPORTPARAM_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description

Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of AuthorizeReportParam

Report-Params-IO

Attribute	Description
Name	Report-Params-IO
Datatype	
Description	

BANKCODE

Attribute	Description				
Name	BANKCODE				
Datatype	string				
Description	Indicates Bank Code				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>4</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	4
Restrictions	Description				
maxLength	4				

CHECKER

Attribute	Description				
Name	CHECKER				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

CHECKERSTAMP

Attribute	Description				
Name	CHECKERSTAMP				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

2.1.3.ST-AuthorizeReportParam-Res-Full-MSG.xsd

AUTHORIZEREPORTPARAM_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Report-Params-Full

LIEN_LIMIT_PERCENT

WITHDRAWAL_THRESHOLD

DEPOSIT_THRESHOLD

NEGATIVE_BAL_THRESHOLD

UTIL_PERCENT

CUST_DUE_FOR_COLL_REV

CUST_DUE_FOR_CR_LINE_EXP

TD_MATDAYS

LOAN_MATDAYS

BANKCODE

WAKALA_EXPIRE_DAYS

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEREPORTPARAM_FSFS_RES

Attribute	Description
-----------	-------------

Name	AUTHORIZEREPORTPARAM_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	
	Description	
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	
	Description	
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	

Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description
------------------	--------------------

Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

Report-Params-Full

Attribute	Description
Name	Report-Params-Full
Datatype	
Description	

LIEN_LIMIT_PERCENT

Attribute	Description	
Name	LIEN_LIMIT_PERCENT	
Datatype	decimal	
Description	Indicates Lien Limit Percentage	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

WITHDRAWAL_THRESHOLD

Attribute	Description	
Name	WITHDRAWAL_THRESHOLD	
Datatype	decimal	
Description	Indicates Withdrawal Threshold	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	totalDigits	22

DEPOSIT_THRESHOLD

Attribute	Description	
Name	DEPOSIT_THRESHOLD	
Datatype	decimal	
Description	Indicates Deposit Threshold	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

NEGATIVE_BAL_THRESHOLD

Attribute	Description	
Name	NEGATIVE_BAL_THRESHOLD	
Datatype	decimal	
Description	Indicates Negative Balance Threshold	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

UTIL_PERCENT

Attribute	Description	
Name	UTIL_PERCENT	
Datatype	decimal	
Description	Indicates Utilization Percentage	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

CUST_DUE_FOR_COLL_REV

Attribute	Description	
Name	CUST_DUE_FOR_COLL_REV	
Datatype	decimal	
Description	Indicates Customers Due For Collateral Revaluation	

Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	totalDigits	22
	Description	

CUST_DUE_FOR_CR_LINE_EXP

Attribute	Description	
Name	CUST_DUE_FOR_CR_LINE_EXP	
Datatype	decimal	
Description	Indicates Customers Due For Credit Line Expiry	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	totalDigits	22
	Description	

TD_MATDAYS

Attribute	Description	
Name	TD_MATDAYS	
Datatype	decimal	
Description	Indicates TD mature days	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	totalDigits	22
	Description	

LOAN_MATDAYS

Attribute	Description	
Name	LOAN_MATDAYS	
Datatype	decimal	
Description	Indicates Loan mature days	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	totalDigits	22
	Description	

BANKCODE

Attribute	Description	
Name	BANKCODE	
Datatype	string	
Description	Indicates Bank Code	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

WAKALA_EXPIRE_DAYS

Attribute	Description	
Name	WAKALA_EXPIRE_DAYS	
Datatype	decimal	
Description	Indicates Wakala Expire Days	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description
------------------	--------------------

Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.1.4.ST-AuthorizeReportParam-Res-PK-MSG.xsd

AUTHORIZEREPORTPARAM_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM
NAME
VALUE
FCUBS_BODY
Report-Params-PK
BANKCODE
Report-Params-IO
BANKCODE
CHECKER
CHECKERSTAMP
MODNO
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

AUTHORIZEREPORTPARAM_IOPK_RES

Attribute	Description
Name	AUTHORIZEREPORTPARAM_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description

Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

Report-Params-PK

Attribute	Description
Name	Report-Params-PK
Datatype	
Description	

BANKCODE

Attribute	Description				
Name	BANKCODE				
Datatype	string				
Description	Indicates Bank Code				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>4</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	4
Restrictions	Description				
maxLength	4				

Report-Params-IO

Attribute	Description
Name	Report-Params-IO
Datatype	
Description	

BANKCODE

Attribute	Description				
Name	BANKCODE				
Datatype	string				
Description	Indicates Bank Code				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>4</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	4
Restrictions	Description				
maxLength	4				

CHECKER

Attribute	Description
Name	CHECKER
Datatype	string
Description	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.2.AuthorizeRMHierarchy

2.2.1.ST-AuthorizeRMHierarchy-Req-Full-MSG.xsd

[AUTHORIZERMHIERARCHY_FSFS_REQ](#)

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rm-Hierarchy-Full

RM_ID

RMNAME

PARENT_RM_ID

PARENTRMNAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

AUTHORIZERMHIERARCHY_FSFS_REQ

Attribute	Description
Name	AUTHORIZERMHIERARCHY_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	string				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	string
Description	This is the user id in the Source system who is performing the action.

Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Request of AuthorizeRMHierarchy	

Rm-Hierarchy-Full

Attribute	Description	
Name	Rm-Hierarchy-Full	
Datatype		
Description		

RM_ID

Attribute	Description	
Name	RM_ID	
Datatype	string	
Description	Indicates RM ID	
Restrictions	Restrictions	Description
	maxLength	12

RMNAME

Attribute	Description	
Name	RMNAME	
Datatype	string	
Description	Indicates RM Name	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

PARENT_RM_ID

Attribute	Description	
Name	PARENT_RM_ID	
Datatype	string	
Description	Indicates Parent RM ID	
Restrictions	Restrictions	Description
	maxLength	12

PARENTRMNAME

Attribute	Description	
Name	PARENTRMNAME	
Datatype	string	
Description	Indicates Parent RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

2.2.2.ST-AuthorizeRMHierarchy-Req-IO-MSG.xsd

AUTHORIZERMHIERARCHY_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rm-Hierarchy-IO

RM_ID

CHECKER

CHECKERSTAMP

MODNO

AUTHORIZERMHIERARCHY_IOPK_REQ

Attribute	Description
Name	AUTHORIZERMHIERARCHY_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

ADDL

Attribute		Description	
Name	ADDL		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

FCUBS_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description	This XSD Gives Information about IO Request of AuthorizeRMHierarchy		

Rm-Hierarchy-IO

Attribute		Description	
Name	Rm-Hierarchy-IO		
Datatype			
Description			

RM_ID

Attribute		Description	
Name	RM_ID		
Datatype	string		
Description	Indicates RM ID		

Restrictions	Restrictions	Description
	maxLength	12

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

2.2.3.ST-AuthorizeRMHierarchy-Res-Full-MSG.xsd

AUTHORIZERMHIERARCHY_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Rm-Hierarchy-Full
RM_ID
RMNAME
PARENT_RM_ID
PARENTRMNAME
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZERMHIERARCHY_FSFS_RES

Attribute	Description
Name	AUTHORIZERMHIERARCHY_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
-----------	-------------

Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
	Restrictions	Description
Restrictions	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	string				
Description	This is the user id in the Source system who is performing the action.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	string				
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

FUNCTIONID

Attribute	Description				
Name	FUNCTIONID				
Datatype	string				
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

Rm-Hierarchy-Full

Attribute	Description
Name	Rm-Hierarchy-Full
Datatype	
Description	

RM_ID

Attribute	Description				
Name	RM_ID				
Datatype	string				
Description	Indicates RM ID				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

RMNAME

Attribute	Description	
Name	RMNAME	
Datatype	string	
Description	Indicates RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

PARENT_RM_ID

Attribute	Description	
Name	PARENT_RM_ID	
Datatype	string	
Description	Indicates Parent RM ID	
Restrictions	Restrictions	Description
	maxLength	12

PARENTRMNAME

Attribute	Description	
Name	PARENTRMNAME	
Datatype	string	
Description	Indicates Parent RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.2.4.ST-AuthorizeRMHierarchy-Res-PK-MSG.xsd

AUTHORIZERMHIERARCHY_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
 NAME
 VALUE
FCUBS_BODY
 Rm-Hierarchy-PK
 RM_ID
 Rm-Hierarchy-IO
 RM_ID
 CHECKER
 CHECKERSTAMP
 MODNO
FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

AUTHORIZERMHIERARCHY_IOPK_RES

Attribute	Description
Name	AUTHORIZERMHIERARCHY_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

Rm-Hierarchy-PK

Attribute	Description
Name	Rm-Hierarchy-PK
Datatype	
Description	

RM_ID

Attribute	Description				
Name	RM_ID				
Datatype	string				
Description	Indicates RM ID				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

Rm-Hierarchy-IO

Attribute	Description
Name	Rm-Hierarchy-IO
Datatype	
Description	

RM_ID

Attribute	Description				
Name	RM_ID				
Datatype	string				
Description	Indicates RM ID				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

CHECKER

Attribute	Description
Name	CHECKER
Datatype	string
Description	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.3.AuthorizeRMMassAmend

2.3.1.ST-AuthorizeRMMassAmend-Req-Full-MSG.xsd

AUTHORIZERMMASSAMEND_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rm-Amend-Full

REFNO

FRMRMID

TORMID

RESTRLIST

EFFDT

STATUS

FRMRMNAME

TORMNAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Restriction

CUSTNO

CUSTNAME

AUTHORIZERMMASSAMEND_FSFS_REQ

Attribute	Description
Name	AUTHORIZERMMASSAMEND_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	string
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	string
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of AuthorizeRMMassAmend

Rm-Amend-Full

Attribute	Description
Name	Rm-Amend-Full
Datatype	
Description	

REFNO

Attribute	Description
------------------	--------------------

Name	REFNO	
Datatype	string	
Description	Indicates Reference Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

FRMRMID

Attribute	Description	
Name	FRMRMID	
Datatype	string	
Description	Indicates From RM ID	
Restrictions	Restrictions	Description
	maxLength	12

TORMID

Attribute	Description	
Name	TORMID	
Datatype	string	
Description	Indicates To RM ID	
Restrictions	Restrictions	Description
	maxLength	12

RESTRLIST

Attribute	Description	
Name	RESTRLIST	
Datatype	string	
Description	Indicates Customer Restrictions L - Allowed Customers R - Restrictive Customers A - All Customers	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	L,R,A

EFFDT

Attribute	Description	
Name	EFFDT	
Datatype	String	
Description	Indicates Effective Date	

STATUS

Attribute	Description
------------------	--------------------

Name	STATUS	
Datatype	string	
Description	Indicates Status N - Not Started C - Completed F - Failed	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	N,C,F

FRMRMNAME

Attribute	Description	
Name	FRMRMNAME	
Datatype	string	
Description	Indicates From RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TORMNAME

Attribute	Description	
Name	TORMNAME	
Datatype	string	
Description	Indicates To RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description
------------------	--------------------

Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description
------------------	--------------------

Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Restriction

Attribute	Description	
Name	Restriction	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	string	
Description	Indicates Customer No	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	11

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	string	
Description	Indicates Customer Name	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

2.3.2.ST-AuthorizeRMMassAmend-Req-IO-MSG.xsd

AUTHORIZERMMASSAMEND_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rm-Amend-IO

REFNO

CHECKER

CHECKERSTAMP

MODNO

AUTHORIZERMMASSAMEND_IOPK_REQ

Attribute	Description
Name	AUTHORIZERMMASSAMEND_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	string				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	string
Description	This is the user id in the Source system who is performing the action.

Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

FCUBS_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description	This XSD Gives Information about IO Request of AuthorizeRMMassAmend		

Rm-Amend-IO

Attribute		Description	
Name	Rm-Amend-IO		
Datatype			
Description			

REFNO

Attribute		Description	
Name	REFNO		
Datatype	string		
Description	Indicates Reference Number		
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	16	

CHECKER

Attribute		Description	
Name	CHECKER		
Datatype	string		

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

2.3.3.ST-AuthorizeRMMassAmend-Res-Full-MSG.xsd

AUTHORIZERMMASSAMEND_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTIRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Rm-Amend-Full
REFNO
FRMRMID
TORMID
RESTRLIST
EFFDT
STATUS
FRMRMNAME
TORMNAME
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Restriction
CUSTNO
CUSTNAME

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZERMMASSAMEND_FSFS_RES

Attribute	Description
Name	AUTHORIZERMMASSAMEND_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

Attribute	Description					
Name	MSGID					
Datatype	string					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	string					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

USERID

Attribute	Description							
Name	USERID							
Datatype	string							
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description							
maxLength	12							
pattern	[A-Z_0-9]*							

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

ADDL

Attribute		Description	
Name	ADDL		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

FCUBS_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description	This XSD Gives Information about Full Response		

Rm-Amend-Full

Attribute		Description	
Name	Rm-Amend-Full		
Datatype			
Description			

REFNO

Attribute		Description	
Name	REFNO		
Datatype	string		
Description	Indicates Reference Number		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

FRMRMID

Attribute	Description	
Name	FRMRMID	
Datatype	string	
Description	Indicates From RM ID	
Restrictions	Restrictions	Description
	maxLength	12

TORMID

Attribute	Description	
Name	TORMID	
Datatype	string	
Description	Indicates To RM ID	
Restrictions	Restrictions	Description
	maxLength	12

RESTRLIST

Attribute	Description	
Name	RESTRLIST	
Datatype	string	
Description	Indicates Customer Restrictions L - Allowed Customers R - Restrictive Customers A - All Customers	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	L,R,A

EFFDT

Attribute	Description	
Name	EFFDT	
Datatype	String	
Description	Indicates Effective Date	

STATUS

Attribute	Description	
Name	STATUS	
Datatype	string	
Description	Indicates Status N - Not Started C - Completed F - Failed	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	N,C,F

FRMRMNAME

Attribute	Description	
Name	FRMRMNAME	
Datatype	string	
Description	Indicates From RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TORMNAME

Attribute	Description	
Name	TORMNAME	
Datatype	string	
Description	Indicates To RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Restriction

Attribute	Description	
Name	Restriction	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	string	
Description	Indicates Customer No	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	11

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	string	
Description	Indicates Customer Name	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description
------------------	--------------------

Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.3.4.ST-AuthorizeRMMassAmend-Res-PK-MSG.xsd

AUTHORIZERMMASSAMEND_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM
NAME
VALUE
FCUBS_BODY
Rm-Amend-PK
REFNO
Rm-Amend-IO
REFNO
CHECKER
CHECKERSTAMP
MODNO
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

AUTHORIZERMMASSAMEND_IOPK_RES

Attribute	Description
Name	AUTHORIZERMMASSAMEND_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description

Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

Rm-Amend-PK

Attribute	Description
Name	Rm-Amend-PK
Datatype	
Description	

REFNO

Attribute	Description				
Name	REFNO				
Datatype	string				
Description	Indicates Reference Number				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

Rm-Amend-IO

Attribute	Description
Name	Rm-Amend-IO
Datatype	
Description	

REFNO

Attribute	Description				
Name	REFNO				
Datatype	string				
Description	Indicates Reference Number				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

CHECKER

Attribute	Description
Name	CHECKER
Datatype	string
Description	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.4.CloseRMHierarchy

2.4.1.ST-CloseRMHierarchy-Req-Full-MSG.xsd

[CLOSERMHIERARCHY_FSFS_REQ](#)

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rm-Hierarchy-Full

RM_ID

RMNAME

PARENT_RM_ID

PARENTRMNAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

CLOSERMHIERARCHY_FSFS_REQ

Attribute	Description
Name	CLOSERMHIERARCHY_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	string				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	string
Description	This is the user id in the Source system who is performing the action.

Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Request of CloseRMHierarchy	

Rm-Hierarchy-Full

Attribute	Description	
Name	Rm-Hierarchy-Full	
Datatype		
Description		

RM_ID

Attribute	Description	
Name	RM_ID	
Datatype	string	
Description	Indicates RM ID	
Restrictions	Restrictions	Description
	maxLength	12

RMNAME

Attribute	Description	
Name	RMNAME	
Datatype	string	
Description	Indicates RM Name	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

PARENT_RM_ID

Attribute	Description	
Name	PARENT_RM_ID	
Datatype	string	
Description	Indicates Parent RM ID	
Restrictions	Restrictions	Description
	maxLength	12

PARENTRMNAME

Attribute	Description	
Name	PARENTRMNAME	
Datatype	string	
Description	Indicates Parent RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

2.4.2.ST-CloseRMHierarchy-Req-IO-MSG.xsd

CLOSERMHIERARCHY_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rm-Hierarchy-IO

RM_ID

MAKER

MAKERSTAMP

MODNO

CLOSERMHIERARCHY_IOPK_REQ

Attribute	Description
Name	CLOSERMHIERARCHY_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*
	Description	

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*
	Description	

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	enumeration	SUCCESS,WARNING,FAILURE
	Description	

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*
	Description	

ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0

PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0
	maxOccurs		unbounded

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description		This XSD Gives Information about IO Request of CloseRMHierarchy	

Rm-Hierarchy-IO

Attribute		Description	
Name		Rm-Hierarchy-IO	
Datatype			
Description			

RM_ID

Attribute		Description	
Name		RM_ID	
Datatype		string	
Description		Indicates RM ID	

Restrictions		
	Restrictions	Description
	maxLength	12

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

2.4.3.ST-CloseRMHierarchy-Res-Full-MSG.xsd

CLOSERMHIERARCHY_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Rm-Hierarchy-Full
RM_ID
RMNAME
PARENT_RM_ID
PARENTRMNAME
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CLOSERMHIERARCHY_FSFS_RES

Attribute	Description
Name	CLOSERMHIERARCHY_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
-----------	-------------

Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	string				
Description	This is the user id in the Source system who is performing the action.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	string				
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

FUNCTIONID

Attribute	Description				
Name	FUNCTIONID				
Datatype	string				
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

Rm-Hierarchy-Full

Attribute	Description
Name	Rm-Hierarchy-Full
Datatype	
Description	

RM_ID

Attribute	Description				
Name	RM_ID				
Datatype	string				
Description	Indicates RM ID				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

RMNAME

Attribute	Description	
Name	RMNAME	
Datatype	string	
Description	Indicates RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

PARENT_RM_ID

Attribute	Description	
Name	PARENT_RM_ID	
Datatype	string	
Description	Indicates Parent RM ID	
Restrictions	Restrictions	Description
	maxLength	12

PARENTRMNAME

Attribute	Description	
Name	PARENTRMNAME	
Datatype	string	
Description	Indicates Parent RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.4.4.ST-CloseRMHierarchy-Res-PK-MSG.xsd

CLOSERMHIERARCHY_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Rm-Hierarchy-PK
RM_ID
Rm-Hierarchy-IO
RM_ID
MAKER
MAKERSTAMP
MODNO
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

CLOSERMHIERARCHY_IOPK_RES

Attribute	Description
Name	CLOSERMHIERARCHY_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

Rm-Hierarchy-PK

Attribute	Description
Name	Rm-Hierarchy-PK
Datatype	
Description	

RM_ID

Attribute	Description				
Name	RM_ID				
Datatype	string				
Description	Indicates RM ID				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

Rm-Hierarchy-IO

Attribute	Description
Name	Rm-Hierarchy-IO
Datatype	
Description	

RM_ID

Attribute	Description				
Name	RM_ID				
Datatype	string				
Description	Indicates RM ID				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKER

Attribute	Description
Name	MAKER
Datatype	string
Description	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.5.CreateReportParam

2.5.1.ST-CreateReportParam-Req-Full-MSG.xsd

[CREATEREPORTPARAM_FSFS_REQ](#)

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Report-Params-Full

LIEN_LIMIT_PERCENT

WITHDRAWAL_THRESHOLD

DEPOSIT_THRESHOLD

NEGATIVE_BAL_THRESHOLD

UTIL_PERCENT

CUST_DUE_FOR_COLL_REV

CUST_DUE_FOR_CR_LINE_EXP

TD_MATDAYS

LOAN_MATDAYS

BANKCODE

WAKALA_EXPIRE_DAYS

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

CREATEREPORTPARAM_FSFS_REQ

Attribute	Description
Name	CREATEREPORTPARAM_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	string
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	string
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Request of CreateReportParam	

Report-Params-Full

Attribute	Description	
Name	Report-Params-Full	
Datatype		
Description		

LIEN_LIMIT_PERCENT

Attribute	Description	
------------------	--------------------	--

Name	LIEN_LIMIT_PERCENT	
Datatype	decimal	
Description	Indicates Lien Limit Percentage	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	totalDigits	22

WITHDRAWAL_THRESHOLD

Attribute	Description	
Name	WITHDRAWAL_THRESHOLD	
Datatype	decimal	
Description	Indicates Withdrawal Threshold	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	totalDigits	22

DEPOSIT_THRESHOLD

Attribute	Description	
Name	DEPOSIT_THRESHOLD	
Datatype	decimal	
Description	Indicates Deposit Threshold	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	totalDigits	22

NEGATIVE_BAL_THRESHOLD

Attribute	Description	
Name	NEGATIVE_BAL_THRESHOLD	
Datatype	decimal	
Description	Indicates Negative Balance Threshold	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	totalDigits	22

UTIL_PERCENT

Attribute	Description
------------------	--------------------

Name	UTIL_PERCENT	
Datatype	decimal	
Description	Indicates Utilization Percentage	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

CUST_DUE_FOR_COLL_REV

Attribute	Description	
Name	CUST_DUE_FOR_COLL_REV	
Datatype	decimal	
Description	Indicates Customers Due For Collateral Revaluation	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

CUST_DUE_FOR_CR_LINE_EXP

Attribute	Description	
Name	CUST_DUE_FOR_CR_LINE_EXP	
Datatype	decimal	
Description	Indicates Customers Due For Credit Line Expiry	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

TD_MATDAYS

Attribute	Description	
Name	TD_MATDAYS	
Datatype	decimal	
Description	Indicates TD mature days	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

LOAN_MATDAYS

Attribute	Description
------------------	--------------------

Name	LOAN_MATDAYS	
Datatype	decimal	
Description	Indicates Loan mature days	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	totalDigits	22

BANKCODE

Attribute	Description	
Name	BANKCODE	
Datatype	string	
Description	Indicates Bank Code	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	4

WAKALA_EXPIRE_DAYS

Attribute	Description	
Name	WAKALA_EXPIRE_DAYS	
Datatype	decimal	
Description	Indicates Wakala Expire Days	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	12

MAKERSTAMP

Attribute	Description
------------------	--------------------

Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description
------------------	--------------------

Name	TXNSTAT	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

2.5.2.ST-CreateReportParam-Req-IO-MSG.xsd

CREATEREPORTPARAM_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Report-Params-IO

LIEN_LIMIT_PERCENT

WITHDRAWAL_THRESHOLD

DEPOSIT_THRESHOLD

NEGATIVE_BAL_THRESHOLD

UTIL_PERCENT

CUST_DUE_FOR_COLL_REV

CUST_DUE_FOR_CR_LINE_EXP

TD_MATDAYS

LOAN_MATDAYS

BANKCODE

WAKALA_EXPIRE_DAYS

CREATEREPORTPARAM_IOPK_REQ

Attribute	Description
Name	CREATEREPORTPARAM_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description

Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of CreateReportParam

Report-Params-IO

Attribute	Description
Name	Report-Params-IO
Datatype	
Description	

LIEN_LIMIT_PERCENT

Attribute	Description				
Name	LIEN_LIMIT_PERCENT				
Datatype	decimal				
Description	Indicates Lien Limit Percentage				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

WITHDRAWAL_THRESHOLD

Attribute	Description				
Name	WITHDRAWAL_THRESHOLD				
Datatype	decimal				
Description	Indicates Withdrawal Threshold				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

DEPOSIT_THRESHOLD

Attribute	Description				
Name	DEPOSIT_THRESHOLD				
Datatype	decimal				
Description	Indicates Deposit Threshold				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	totalDigits	22

NEGATIVE_BAL_THRESHOLD

Attribute	Description	
Name	NEGATIVE_BAL_THRESHOLD	
Datatype	decimal	
Description	Indicates Negative Balance Threshold	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

UTIL_PERCENT

Attribute	Description	
Name	UTIL_PERCENT	
Datatype	decimal	
Description	Indicates Utilization Percentage	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

CUST_DUE_FOR_COLL_REV

Attribute	Description	
Name	CUST_DUE_FOR_COLL_REV	
Datatype	decimal	
Description	Indicates Customers Due For Collateral Revaluation	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

CUST_DUE_FOR_CR_LINE_EXP

Attribute	Description	
Name	CUST_DUE_FOR_CR_LINE_EXP	
Datatype	decimal	
Description	Indicates Customers Due For Credit Line Expiry	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

TD_MATDAYS

Attribute	Description	
Name	TD_MATDAYS	
Datatype	decimal	
Description	Indicates TD mature days	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

LOAN_MATDAYS

Attribute	Description	
Name	LOAN_MATDAYS	
Datatype	decimal	
Description	Indicates Loan mature days	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

BANKCODE

Attribute	Description	
Name	BANKCODE	
Datatype	string	
Description	Indicates Bank Code	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

WAKALA_EXPIRE_DAYS

Attribute	Description	
Name	WAKALA_EXPIRE_DAYS	
Datatype	decimal	
Description	Indicates Wakala Expire Days	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

2.5.3.ST-CreateReportParam-Res-Full-MSG.xsd

CREATEREPORTPARAM_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Report-Params-Full

LIEN_LIMIT_PERCENT

WITHDRAWAL_THRESHOLD

DEPOSIT_THRESHOLD
NEGATIVE_BAL_THRESHOLD
UTIL_PERCENT
CUST_DUE_FOR_COLL_REV
CUST_DUE_FOR_CR_LINE_EXP
TD_MATDAYS
LOAN_MATDAYS
BANKCODE
WAKALA_EXPIRE_DAYS
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

CREATEREPORTPARAM_FSFS_RES

Attribute	Description
Name	CREATEREPORTPARAM_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

Report-Params-Full

Attribute	Description
Name	Report-Params-Full
Datatype	
Description	

LIEN_LIMIT_PERCENT

Attribute	Description				
Name	LIEN_LIMIT_PERCENT				
Datatype	decimal				
Description	Indicates Lien Limit Percentage				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

WITHDRAWAL_THRESHOLD

Attribute	Description				
Name	WITHDRAWAL_THRESHOLD				
Datatype	decimal				
Description	Indicates Withdrawal Threshold				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

DEPOSIT_THRESHOLD

Attribute	Description
Name	DEPOSIT_THRESHOLD
Datatype	decimal
Description	Indicates Deposit Threshold

Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	totalDigits	22

NEGATIVE_BAL_THRESHOLD

Attribute	Description	
Name	NEGATIVE_BAL_THRESHOLD	
Datatype	decimal	
Description	Indicates Negative Balance Threshold	
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	totalDigits	22

UTIL_PERCENT

Attribute	Description	
Name	UTIL_PERCENT	
Datatype	decimal	
Description	Indicates Utilization Percentage	
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	totalDigits	22

CUST_DUE_FOR_COLL_REV

Attribute	Description	
Name	CUST_DUE_FOR_COLL_REV	
Datatype	decimal	
Description	Indicates Customers Due For Collateral Revaluation	
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	totalDigits	22

CUST_DUE_FOR_CR_LINE_EXP

Attribute	Description	
Name	CUST_DUE_FOR_CR_LINE_EXP	
Datatype	decimal	

Description	Indicates Customers Due For Credit Line Expiry	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

TD_MATDAYS

Attribute	Description	
Name	TD_MATDAYS	
Datatype	decimal	
Description	Indicates TD mature days	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

LOAN_MATDAYS

Attribute	Description	
Name	LOAN_MATDAYS	
Datatype	decimal	
Description	Indicates Loan mature days	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

BANKCODE

Attribute	Description	
Name	BANKCODE	
Datatype	string	
Description	Indicates Bank Code	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

WAKALA_EXPIRE_DAYS

Attribute	Description	
Name	WAKALA_EXPIRE_DAYS	
Datatype	decimal	

Description	Indicates Wakala Expire Days	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		

Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	

Description	
-------------	--

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.5.4.ST-CreateReportParam-Res-PK-MSG.xsd

CREATEREPORTPARAM_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Report-Params-PK

BANKCODE

Report-Params-IO

LIEN_LIMIT_PERCENT
WITHDRAWAL_THRESHOLD
DEPOSIT_THRESHOLD
NEGATIVE_BAL_THRESHOLD
UTIL_PERCENT
CUST_DUE_FOR_COLL_REV
CUST_DUE_FOR_CR_LINE_EXP
TD_MATDAYS
LOAN_MATDAYS
BANKCODE
WAKALA_EXPIRE_DAYS
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

CREATEREPORTPARAM_IOPK_RES

Attribute	Description
Name	CREATEREPORTPARAM_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description

Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

Report-Params-PK

Attribute	Description
Name	Report-Params-PK
Datatype	
Description	

BANKCODE

Attribute	Description				
Name	BANKCODE				
Datatype	string				
Description	Indicates Bank Code				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>4</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	4
Restrictions	Description				
maxLength	4				

Report-Params-IO

Attribute	Description
Name	Report-Params-IO
Datatype	
Description	

LIEN_LIMIT_PERCENT

Attribute	Description				
Name	LIEN_LIMIT_PERCENT				
Datatype	decimal				
Description	Indicates Lien Limit Percentage				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

WITHDRAWAL_THRESHOLD

Attribute	Description
Name	WITHDRAWAL_THRESHOLD
Datatype	decimal
Description	Indicates Withdrawal Threshold

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

DEPOSIT_THRESHOLD

Attribute	Description	
Name	DEPOSIT_THRESHOLD	
Datatype	decimal	
Description	Indicates Deposit Threshold	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

NEGATIVE_BAL_THRESHOLD

Attribute	Description	
Name	NEGATIVE_BAL_THRESHOLD	
Datatype	decimal	
Description	Indicates Negative Balance Threshold	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

UTIL_PERCENT

Attribute	Description	
Name	UTIL_PERCENT	
Datatype	decimal	
Description	Indicates Utilization Percentage	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

CUST_DUE_FOR_COLL_REV

Attribute	Description	
Name	CUST_DUE_FOR_COLL_REV	
Datatype	decimal	
Description	Indicates Customers Due For Collateral Revaluation	

Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	totalDigits	22
	Description	

CUST_DUE_FOR_CR_LINE_EXP

Attribute	Description	
Name	CUST_DUE_FOR_CR_LINE_EXP	
Datatype	decimal	
Description	Indicates Customers Due For Credit Line Expiry	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	totalDigits	22
	Description	

TD_MATDAYS

Attribute	Description	
Name	TD_MATDAYS	
Datatype	decimal	
Description	Indicates TD mature days	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	totalDigits	22
	Description	

LOAN_MATDAYS

Attribute	Description	
Name	LOAN_MATDAYS	
Datatype	decimal	
Description	Indicates Loan mature days	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	totalDigits	22
	Description	

BANKCODE

Attribute	Description	
Name	BANKCODE	
Datatype	string	
Description	Indicates Bank Code	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

WAKALA_EXPIRE_DAYS

Attribute	Description	
Name	WAKALA_EXPIRE_DAYS	
Datatype	decimal	
Description	Indicates Wakala Expire Days	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.6.CreateRMHierarchy

2.6.1.ST-CreateRMHierarchy-Req-Full-MSG.xsd

CREATERMHIERARCHY_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
 NAME
 VALUE
FCUBS_BODY
 Rm-Hierarchy-Full
 RM_ID
 RMNAME
 PARENT_RM_ID
 PARENTRMNAME
 MAKER
 MAKERSTAMP
 CHECKER
 CHECKERSTAMP
 MODNO
 TXNSTAT
 AUTHSTAT

CREATERMHIERARCHY_FSFS_REQ

Attribute	Description
Name	CREATERMHIERARCHY_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	
-------------	--

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of CreateRMHierarchy

Rm-Hierarchy-Full

Attribute	Description
Name	Rm-Hierarchy-Full
Datatype	
Description	

RM_ID

Attribute	Description				
Name	RM_ID				
Datatype	string				
Description	Indicates RM ID				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

RMNAME

Attribute	Description				
Name	RMNAME				
Datatype	string				
Description	Indicates RM Name				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

PARENT_RM_ID

Attribute	Description				
Name	PARENT_RM_ID				
Datatype	string				
Description	Indicates Parent RM ID				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

PARENTRMNAME

Attribute	Description	
Name	PARENTRMNAME	
Datatype	string	
Description	Indicates Parent RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rm-Hierarchy-IO

RM_ID

PARENT_RM_ID

CREATERMHIERARCHY_IOPK_REQ

Attribute	Description
Name	CREATERMHIERARCHY_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
------------------	--------------------

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	string	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of CreateRMHierarchy

Rm-Hierarchy-IO

Attribute	Description
Name	Rm-Hierarchy-IO
Datatype	
Description	

RM_ID

Attribute	Description				
Name	RM_ID				
Datatype	string				
Description	Indicates RM ID				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

PARENT_RM_ID

Attribute	Description				
Name	PARENT_RM_ID				
Datatype	string				
Description	Indicates Parent RM ID				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

2.6.3.ST-CreateRMHierarchy-Res-Full-MSG.xsd

CREATERMHIERARCHY_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Rm-Hierarchy-Full
RM_ID
RMNAME
PARENT_RM_ID
PARENTRMNAME
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATERMHIERARCHY_FSFS_RES

Attribute	Description
Name	CREATERMHIERARCHY_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	string				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	string
Description	This is the user id in the Source system who is performing the action.

Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

Rm-Hierarchy-Full

Attribute	Description
Name	Rm-Hierarchy-Full
Datatype	
Description	

RM_ID

Attribute	Description				
Name	RM_ID				
Datatype	string				
Description	Indicates RM ID				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

RMNAME

Attribute	Description
Name	RMNAME
Datatype	string
Description	Indicates RM Name

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

PARENT_RM_ID

Attribute	Description	
Name	PARENT_RM_ID	
Datatype	string	
Description	Indicates Parent RM ID	
Restrictions	Restrictions	Description
	maxLength	12

PARENTRMNAME

Attribute	Description	
Name	PARENTRMNAME	
Datatype	string	
Description	Indicates Parent RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
------------------	--------------------	--

Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

2.6.4.ST-CreateRMHierarchy-Res-PK-MSG.xsd

CREATERMHIERARCHY_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rm-Hierarchy-PK

RM_ID

Rm-Hierarchy-IO

RM_ID

PARENT_RM_ID

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATERMHIERARCHY_IOPK_RES

Attribute	Description
Name	CREATERMHIERARCHY_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	string	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

Rm-Hierarchy-PK

Attribute	Description
Name	Rm-Hierarchy-PK
Datatype	
Description	

RM_ID

Attribute	Description				
Name	RM_ID				
Datatype	string				
Description	Indicates RM ID				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

Rm-Hierarchy-IO

Attribute	Description
Name	Rm-Hierarchy-IO
Datatype	
Description	

RM_ID

Attribute	Description				
Name	RM_ID				
Datatype	string				
Description	Indicates RM ID				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

PARENT_RM_ID

Attribute	Description
Name	PARENT_RM_ID
Datatype	string
Description	Indicates Parent RM ID

Restrictions		
	Restrictions	Description
	maxLength	12

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.7.CreateRMMassAmend

2.7.1.ST-CreateRMMassAmend-Req-Full-MSG.xsd

CREATERMMASSAMEND_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rm-Amend-Full

REFNO

FRMRMID

TORMID

RESTRLIST

EFFDT

STATUS

FRMRMNAME

TORMNAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Restriction

CUSTNO

CUSTNAME

CREATERMMASSAMEND_FSFS_REQ

Attribute	Description
Name	CREATERMMASSAMEND_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE

Datatype	string	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of CreateRMMassAmend

Rm-Amend-Full

Attribute	Description
Name	Rm-Amend-Full
Datatype	
Description	

REFNO

Attribute	Description				
Name	REFNO				
Datatype	string				
Description	Indicates Reference Number				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

FRMRMID

Attribute	Description				
Name	FRMRMID				
Datatype	string				
Description	Indicates From RM ID				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

TORMID

Attribute	Description				
Name	TORMID				
Datatype	string				
Description	Indicates To RM ID				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

RESTRLIST

Attribute	Description	
Name	RESTRLIST	
Datatype	string	
Description	Indicates Customer Restrictions L - Allowed Customers R - Restrictive Customers A - All Customers	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	L,R,A

EFFDT

Attribute	Description	
Name	EFFDT	
Datatype	String	
Description	Indicates Effective Date	

STATUS

Attribute	Description	
Name	STATUS	
Datatype	string	
Description	Indicates Status N - Not Started C - Completed F - Failed	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	N,C,F

FRMRMNAME

Attribute	Description	
Name	FRMRMNAME	
Datatype	string	
Description	Indicates From RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TORMNAME

Attribute	Description	
Name	TORMNAME	
Datatype	string	
Description	Indicates To RM Name	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Restriction

Attribute	Description	
Name	Restriction	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	string	
Description	Indicates Customer No	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	string	
Description	Indicates Customer Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

2.7.2.ST-CreateRMMassAmend-Req-IO-MSG.xsd

CREATERMMASSAMEND_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTIRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rm-Amend-IO

REFNO

FRMRMID

TORMID

RESTRLIST

EFFDT

Restriction

CUSTNO

CREATERMMASSAMEND_IOPK_REQ

Attribute	Description
Name	CREATERMMASSAMEND_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description

Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of CreateRMMassAmend

Rm-Amend-IO

Attribute	Description
Name	Rm-Amend-IO
Datatype	
Description	

REFNO

Attribute	Description				
Name	REFNO				
Datatype	string				
Description	Indicates Reference Number				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

FRMRMID

Attribute	Description				
Name	FRMRMID				
Datatype	string				
Description	Indicates From RM ID				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

TORMID

Attribute	Description				
Name	TORMID				
Datatype	string				
Description	Indicates To RM ID				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

RESTRLIST

Attribute	Description
Name	RESTRLIST
Datatype	string
Description	Indicates Customer Restrictions L - Allowed Customers R - Restrictive Customers A - All Customers

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	L,R,A

EFFDT

Attribute	Description
Name	EFFDT
Datatype	String
Description	Indicates Effective Date

Restriction

Attribute	Description	
Name	Restriction	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	string	
Description	Indicates Customer No	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

2.7.3.ST-CreateRMMassAmend-Res-Full-MSG.xsd

CREATERMMASSAMEND_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Rm-Amend-Full
REFNO
FRMRMID
TORMID
RESTRLIST
EFFDT
STATUS
FRMRMNAME
TORMNAME
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Restriction

CUSTNO

CUSTNAME

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATERMMASSAMEND_FSFS_RES

Attribute	Description
Name	CREATERMMASSAMEND_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	string
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	string
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

Rm-Amend-Full

Attribute	Description
Name	Rm-Amend-Full
Datatype	
Description	

REFNO

Attribute	Description
------------------	--------------------

Name	REFNO	
Datatype	string	
Description	Indicates Reference Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

FRMRMID

Attribute	Description	
Name	FRMRMID	
Datatype	string	
Description	Indicates From RM ID	
Restrictions	Restrictions	Description
	maxLength	12

TORMID

Attribute	Description	
Name	TORMID	
Datatype	string	
Description	Indicates To RM ID	
Restrictions	Restrictions	Description
	maxLength	12

RESTRLIST

Attribute	Description	
Name	RESTRLIST	
Datatype	string	
Description	Indicates Customer Restrictions L - Allowed Customers R - Restrictive Customers A - All Customers	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	L,R,A

EFFDT

Attribute	Description	
Name	EFFDT	
Datatype	String	
Description	Indicates Effective Date	

STATUS

Attribute	Description
------------------	--------------------

Name	STATUS	
Datatype	string	
Description	Indicates Status N - Not Started C - Completed F - Failed	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	N,C,F

FRMRMNAME

Attribute	Description	
Name	FRMRMNAME	
Datatype	string	
Description	Indicates From RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TORMNAME

Attribute	Description	
Name	TORMNAME	
Datatype	string	
Description	Indicates To RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description
------------------	--------------------

Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description
------------------	--------------------

Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Restriction

Attribute	Description	
Name	Restriction	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	string	
Description	Indicates Customer No	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	11

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	string	
Description	Indicates Customer Name	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description
------------------	--------------------

Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.7.4.ST-CreateRMMassAmend-Res-PK-MSG.xsd

CREATERMMASSAMEND_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM
NAME
VALUE
FCUBS_BODY
Rm-Amend-PK
REFNO
Rm-Amend-IO
REFNO
FRMRMID
TORMID
RESTRLIST
EFFDT
Restriction
CUSTNO
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

CREATERMMASSAMEND_IOPK_RES

Attribute	Description
Name	CREATERMMASSAMEND_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE

Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

Rm-Amend-PK

Attribute	Description
Name	Rm-Amend-PK
Datatype	
Description	

REFNO

Attribute	Description				
Name	REFNO				
Datatype	string				
Description	Indicates Reference Number				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

Rm-Amend-IO

Attribute	Description
Name	Rm-Amend-IO
Datatype	
Description	

REFNO

Attribute	Description				
Name	REFNO				
Datatype	string				
Description	Indicates Reference Number				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

FRMRMID

Attribute	Description	
Name	FRMRMID	
Datatype	string	
Description	Indicates From RM ID	
Restrictions		
	Restrictions	Description
	maxLength	12

TORMID

Attribute	Description	
Name	TORMID	
Datatype	string	
Description	Indicates To RM ID	
Restrictions		
	Restrictions	Description
	maxLength	12

RESTRLIST

Attribute	Description	
Name	RESTRLIST	
Datatype	string	
Description	Indicates Customer Restrictions L - Allowed Customers R - Restrictive Customers A - All Customers	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	L,R,A

EFFDT

Attribute	Description	
Name	EFFDT	
Datatype	String	
Description	Indicates Effective Date	

Restriction

Attribute	Description	
Name	Restriction	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	string	

Description	Indicates Customer No	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

2.8.DeleteRMHierarchy

2.8.1.ST-DeleteRMHierarchy-Req-Full-MSG.xsd

DELETERMHIERARCHY_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rm-Hierarchy-Full

RM_ID

RMNAME

PARENT_RM_ID

PARENTRMNAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

DELETERMHIERARCHY_FSFS_REQ

Attribute	Description
Name	DELETERMHIERARCHY_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description

Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of DeleteRMHierarchy

Rm-Hierarchy-Full

Attribute	Description
Name	Rm-Hierarchy-Full
Datatype	
Description	

RM_ID

Attribute	Description				
Name	RM_ID				
Datatype	string				
Description	Indicates RM ID				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

RMNAME

Attribute	Description				
Name	RMNAME				
Datatype	string				
Description	Indicates RM Name				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>255</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

PARENT_RM_ID

Attribute	Description				
Name	PARENT_RM_ID				
Datatype	string				
Description	Indicates Parent RM ID				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

PARENTRMNAME

Attribute	Description
Name	PARENTRMNAME
Datatype	string
Description	Indicates Parent RM Name

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

2.8.2.ST-DeleteRMHierarchy-Req-IO-MSG.xsd

DELETERMHIERARCHY_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Rm-Hierarchy-IO
RM_ID

DELETERMHIERARCHY_IOPK_REQ

Attribute	Description
Name	DELETERMHIERARCHY_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	string	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of DeleteRMHierarchy

Rm-Hierarchy-IO

Attribute	Description
Name	Rm-Hierarchy-IO
Datatype	
Description	

RM_ID

Attribute	Description				
Name	RM_ID				
Datatype	string				
Description	Indicates RM ID				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

2.8.3.ST-DeleteRMHierarchy-Res-Full-MSG.xsd

DELETERMHIERARCHY_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rm-Hierarchy-Full

RM_ID

RMNAME

PARENT_RM_ID

PARENTRMNAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETERMHIERARCHY_FSFS_RES

Attribute	Description
-----------	-------------

Name	DELETERMHIERARCHY_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	
	Description	
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	
	Description	
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	

Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description
------------------	--------------------

Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

Rm-Hierarchy-Full

Attribute	Description
Name	Rm-Hierarchy-Full
Datatype	
Description	

RM_ID

Attribute	Description	
Name	RM_ID	
Datatype	string	
Description	Indicates RM ID	
Restrictions	Restrictions	Description
	maxLength	12

RMNAME

Attribute	Description	
Name	RMNAME	
Datatype	string	
Description	Indicates RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

PARENT_RM_ID

Attribute	Description				
Name	PARENT_RM_ID				
Datatype	string				
Description	Indicates Parent RM ID				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

PARENTRMNAME

Attribute	Description				
Name	PARENTRMNAME				
Datatype	string				
Description	Indicates Parent RM Name				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
	Restrictions	Description			
maxLength	255				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
	Restrictions	Description			
maxLength	35				

CHECKER

Attribute	Description
Name	CHECKER

Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	

Datatype	string	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	1
	Description	

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	
	maxOccurs	unbounded
	Description	

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

2.8.4.ST-DeleteRMHierarchy-Res-PK-MSG.xsd

DELETERMHIERARCHY_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rm-Hierarchy-PK

RM_ID

Rm-Hierarchy-IO

RM_ID

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETERMHIERARCHY_IOPK_RES

Attribute	Description
Name	DELETERMHIERARCHY_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	string				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description
-----------	-------------

Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
pattern	[A-Z_0-9]*	

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
pattern	[a-zA-Z_0-9]{3}	

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

Rm-Hierarchy-PK

Attribute	Description
Name	Rm-Hierarchy-PK
Datatype	
Description	

RM_ID

Attribute	Description				
Name	RM_ID				
Datatype	string				
Description	Indicates RM ID				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

Rm-Hierarchy-IO

Attribute	Description
Name	Rm-Hierarchy-IO
Datatype	
Description	

RM_ID

Attribute	Description				
Name	RM_ID				
Datatype	string				
Description	Indicates RM ID				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

FCUBS_ERROR_RESP

Attribute	Description						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.9.DeleteRMMassAmend

2.9.1.ST-DeleteRMMassAmend-Req-Full-MSG.xsd

DELETERMMASSAMEND_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Rm-Amend-Full
REFNO
FRMRMID
TORMID
RESTRLIST
EFFDT
STATUS
FRMRMNAME
TORMNAME
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Restriction

CUSTNO

CUSTNAME

DELETERMMASSAMEND_FSFS_REQ

Attribute	Description
Name	DELETERMMASSAMEND_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	string

Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	string				
Description	This is the user id in the Source system who is performing the action.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	string				
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

FUNCTIONID

Attribute	Description				
Name	FUNCTIONID				
Datatype	string				
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of DeleteRMMassAmend

Rm-Amend-Full

Attribute	Description
Name	Rm-Amend-Full
Datatype	
Description	

REFNO

Attribute	Description				
Name	REFNO				
Datatype	string				
Description	Indicates Reference Number				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	16

FRMRMID

Attribute	Description	
Name	FRMRMID	
Datatype	string	
Description	Indicates From RM ID	
Restrictions		
	Restrictions	Description
	maxLength	12

TORMID

Attribute	Description	
Name	TORMID	
Datatype	string	
Description	Indicates To RM ID	
Restrictions		
	Restrictions	Description
	maxLength	12

RESTRLIST

Attribute	Description	
Name	RESTRLIST	
Datatype	string	
Description	Indicates Customer Restrictions L - Allowed Customers R - Restrictive Customers A - All Customers	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	L,R,A

EFFDT

Attribute	Description	
Name	EFFDT	
Datatype	String	
Description	Indicates Effective Date	

STATUS

Attribute	Description	
Name	STATUS	
Datatype	string	
Description	Indicates Status N - Not Started C - Completed F - Failed	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	N,C,F

FRMRMNAME

Attribute	Description	
Name	FRMRMNAME	
Datatype	string	
Description	Indicates From RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TORMNAME

Attribute	Description	
Name	TORMNAME	
Datatype	string	
Description	Indicates To RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Restriction

Attribute	Description	
Name	Restriction	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	string	
Description	Indicates Customer No	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	11

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	string	
Description	Indicates Customer Name	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

2.9.2.ST-DeleteRMMassAmend-Req-IO-MSG.xsd

DELETERMMASSAMEND_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rm-Amend-IO

REFNO

Attribute	Description
Name	DELETERMMASSAMEND_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	string					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

USERID

Attribute	Description							
Name	USERID							
Datatype	string							
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description							
maxLength	12							
pattern	[A-Z_0-9]*							

BRANCH

Attribute	Description							
Name	BRANCH							
Datatype	string							
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>		Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description							
length	3							
pattern	[a-zA-Z_0-9]{3}							

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	

Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description
------------------	--------------------

Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of DeleteRMMassAmend

Rm-Amend-IO

Attribute	Description
Name	Rm-Amend-IO
Datatype	
Description	

REFNO

Attribute	Description	
Name	REFNO	
Datatype	string	
Description	Indicates Reference Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

2.9.3.ST-DeleteRMMassAmend-Res-Full-MSG.xsd

DELETERMMASSAMEND_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Rm-Amend-Full
REFNO
FRMRMID
TORMID
RESTRLIST
EFFDT
STATUS
FRMRMNAME
TORMNAME
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Restriction

CUSTNO

CUSTNAME

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETERMMASSAMEND_FSFS_RES

Attribute	Description
Name	DELETERMMASSAMEND_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	string

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

MSGID

Attribute	Description					
Name	MSGID					
Datatype	string					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	string					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
------------------	--------------------

Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

Rm-Amend-Full

Attribute	Description
Name	Rm-Amend-Full
Datatype	
Description	

REFNO

Attribute	Description				
Name	REFNO				
Datatype	string				
Description	Indicates Reference Number				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

FRMRMID

Attribute	Description				
Name	FRMRMID				
Datatype	string				
Description	Indicates From RM ID				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

TORMID

Attribute	Description				
Name	TORMID				
Datatype	string				
Description	Indicates To RM ID				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

RESTRLIST

Attribute	Description				
Name	RESTRLIST				
Datatype	string				
Description	Indicates Customer Restrictions L - Allowed Customers R - Restrictive Customers A - All Customers				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>L,R,A</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	L,R,A
Restrictions	Description				
enumeration	L,R,A				

EFFDT

Attribute	Description
Name	EFFDT
Datatype	String
Description	Indicates Effective Date

STATUS

Attribute	Description	
Name	STATUS	
Datatype	string	
Description	Indicates Status N - Not Started C - Completed F - Failed	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	N,C,F

FRMRMNAME

Attribute	Description	
Name	FRMRMNAME	
Datatype	string	
Description	Indicates From RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TORMNAME

Attribute	Description	
Name	TORMNAME	
Datatype	string	
Description	Indicates To RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description
Name	MAKER
Datatype	string
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

Restriction

Attribute	Description	
Name	Restriction	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	string	
Description	Indicates Customer No	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	string	
Description	Indicates Customer Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.9.4.ST-DeleteRMMassAmend-Res-PK-MSG.xsd

DELETERMMASSAMEND_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rm-Amend-PK

REFNO

Rm-Amend-IO

REFNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETERMMASSAMEND_IOPK_RES

Attribute	Description
Name	DELETERMMASSAMEND_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

Rm-Amend-PK

Attribute	Description
Name	Rm-Amend-PK
Datatype	
Description	

REFNO

Attribute	Description				
Name	REFNO				
Datatype	string				
Description	Indicates Reference Number				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

Rm-Amend-IO

Attribute	Description
Name	Rm-Amend-IO
Datatype	
Description	

REFNO

Attribute	Description				
Name	REFNO				
Datatype	string				
Description	Indicates Reference Number				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

FCUBS_ERROR_RESP

Attribute		Description	
Name	FCUBS_ERROR_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

ERROR

Attribute		Description	
Name	ERROR		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

ECODE

Attribute		Description	
Name	ECODE		
Datatype	String		
Description			

EDESC

Attribute		Description	
Name	EDESC		
Datatype	String		
Description			

FCUBS_WARNING_RESP

Attribute		Description	
Name	FCUBS_WARNING_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

WARNING

Attribute		Description	
Name	WARNING		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.10.ModifyReportParam

2.10.1.ST-ModifyReportParam-Req-Full-MSG.xsd

MODIFYREPORTPARAM_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Report-Params-Full

LIEN_LIMIT_PERCENT
WITHDRAWAL_THRESHOLD
DEPOSIT_THRESHOLD
NEGATIVE_BAL_THRESHOLD
UTIL_PERCENT
CUST_DUE_FOR_COLL_REV
CUST_DUE_FOR_CR_LINE_EXP
TD_MATDAYS
LOAN_MATDAYS
BANKCODE
WAKALA_EXPIRE_DAYS
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT

MODIFYREPORTPARAM_FSFS_REQ

Attribute	Description
Name	MODIFYREPORTPARAM_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description

Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of ModifyReportParam

Report-Params-Full

Attribute	Description
Name	Report-Params-Full
Datatype	
Description	

LIEN_LIMIT_PERCENT

Attribute	Description				
Name	LIEN_LIMIT_PERCENT				
Datatype	decimal				
Description	Indicates Lien Limit Percentage				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

WITHDRAWAL_THRESHOLD

Attribute	Description				
Name	WITHDRAWAL_THRESHOLD				
Datatype	decimal				
Description	Indicates Withdrawal Threshold				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

DEPOSIT_THRESHOLD

Attribute	Description				
Name	DEPOSIT_THRESHOLD				
Datatype	decimal				
Description	Indicates Deposit Threshold				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	totalDigits	22

NEGATIVE_BAL_THRESHOLD

Attribute	Description	
Name	NEGATIVE_BAL_THRESHOLD	
Datatype	decimal	
Description	Indicates Negative Balance Threshold	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

UTIL_PERCENT

Attribute	Description	
Name	UTIL_PERCENT	
Datatype	decimal	
Description	Indicates Utilization Percentage	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

CUST_DUE_FOR_COLL_REV

Attribute	Description	
Name	CUST_DUE_FOR_COLL_REV	
Datatype	decimal	
Description	Indicates Customers Due For Collateral Revaluation	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

CUST_DUE_FOR_CR_LINE_EXP

Attribute	Description	
Name	CUST_DUE_FOR_CR_LINE_EXP	
Datatype	decimal	
Description	Indicates Customers Due For Credit Line Expiry	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

TD_MATDAYS

Attribute	Description	
Name	TD_MATDAYS	
Datatype	decimal	
Description	Indicates TD mature days	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

LOAN_MATDAYS

Attribute	Description	
Name	LOAN_MATDAYS	
Datatype	decimal	
Description	Indicates Loan mature days	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

BANKCODE

Attribute	Description	
Name	BANKCODE	
Datatype	string	
Description	Indicates Bank Code	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

WAKALA_EXPIRE_DAYS

Attribute	Description	
Name	WAKALA_EXPIRE_DAYS	
Datatype	decimal	
Description	Indicates Wakala Expire Days	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

2.10.2.ST-ModifyReportParam-Req-IO-MSG.xsd

MODIFYREPORTPARAM_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Report-Params-IO
LIEN_LIMIT_PERCENT
WITHDRAWAL_THRESHOLD
DEPOSIT_THRESHOLD
NEGATIVE_BAL_THRESHOLD
UTIL_PERCENT
CUST_DUE_FOR_COLL_REV
CUST_DUE_FOR_CR_LINE_EXP
TD_MATDAYS
LOAN_MATDAYS
BANKCODE

WAKALA_EXPIRE_DAYS

MAKER

MAKERSTAMP

MODIFYREPORTPARAM_IOPK_REQ

Attribute	Description
Name	MODIFYREPORTPARAM_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	string				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	string
Description	This is the user id in the Source system who is performing the action.

Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about IO Request of ModifyReportParam	

Report-Params-IO

Attribute	Description	
Name	Report-Params-IO	
Datatype		
Description		

LIEN_LIMIT_PERCENT

Attribute	Description	
Name	LIEN_LIMIT_PERCENT	
Datatype	decimal	
Description	Indicates Lien Limit Percentage	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

WITHDRAWAL_THRESHOLD

Attribute	Description	
Name	WITHDRAWAL_THRESHOLD	
Datatype	decimal	

Description	Indicates Withdrawal Threshold	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

DEPOSIT_THRESHOLD

Attribute	Description	
Name	DEPOSIT_THRESHOLD	
Datatype	decimal	
Description	Indicates Deposit Threshold	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

NEGATIVE_BAL_THRESHOLD

Attribute	Description	
Name	NEGATIVE_BAL_THRESHOLD	
Datatype	decimal	
Description	Indicates Negative Balance Threshold	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

UTIL_PERCENT

Attribute	Description	
Name	UTIL_PERCENT	
Datatype	decimal	
Description	Indicates Utilization Percentage	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

CUST_DUE_FOR_COLL_REV

Attribute	Description	
Name	CUST_DUE_FOR_COLL_REV	
Datatype	decimal	

Description	Indicates Customers Due For Collateral Revaluation	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

CUST_DUE_FOR_CR_LINE_EXP

Attribute	Description	
Name	CUST_DUE_FOR_CR_LINE_EXP	
Datatype	decimal	
Description	Indicates Customers Due For Credit Line Expiry	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

TD_MATDAYS

Attribute	Description	
Name	TD_MATDAYS	
Datatype	decimal	
Description	Indicates TD mature days	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

LOAN_MATDAYS

Attribute	Description	
Name	LOAN_MATDAYS	
Datatype	decimal	
Description	Indicates Loan mature days	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

BANKCODE

Attribute	Description
Name	BANKCODE

Datatype	string	
Description	Indicates Bank Code	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

WAKALA_EXPIRE_DAYS

Attribute	Description	
Name	WAKALA_EXPIRE_DAYS	
Datatype	decimal	
Description	Indicates Wakala Expire Days	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

2.10.3.ST-ModifyReportParam-Res-Full-MSG.xsd

MODIFYREPORTPARAM_FSFS_RES

FCUBS_HEADER

SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Report-Params-Full
LIEN_LIMIT_PERCENT
WITHDRAWAL_THRESHOLD
DEPOSIT_THRESHOLD
NEGATIVE_BAL_THRESHOLD
UTIL_PERCENT
CUST_DUE_FOR_COLL_REV
CUST_DUE_FOR_CR_LINE_EXP
TD_MATDAYS
LOAN_MATDAYS

BANKCODE

WAKALA_EXPIRE_DAYS

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYREPORTPARAM_FSFS_RES

Attribute	Description
Name	MODIFYREPORTPARAM_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
-----------	-------------

Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

Report-Params-Full

Attribute	Description
Name	Report-Params-Full
Datatype	
Description	

LIEN_LIMIT_PERCENT

Attribute	Description				
Name	LIEN_LIMIT_PERCENT				
Datatype	decimal				
Description	Indicates Lien Limit Percentage				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

WITHDRAWAL_THRESHOLD

Attribute	Description				
Name	WITHDRAWAL_THRESHOLD				
Datatype	decimal				
Description	Indicates Withdrawal Threshold				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

DEPOSIT_THRESHOLD

Attribute	Description				
Name	DEPOSIT_THRESHOLD				
Datatype	decimal				
Description	Indicates Deposit Threshold				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

NEGATIVE_BAL_THRESHOLD

Attribute	Description
Name	NEGATIVE_BAL_THRESHOLD
Datatype	decimal
Description	Indicates Negative Balance Threshold

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

UTIL_PERCENT

Attribute	Description	
Name	UTIL_PERCENT	
Datatype	decimal	
Description	Indicates Utilization Percentage	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

CUST_DUE_FOR_COLL_REV

Attribute	Description	
Name	CUST_DUE_FOR_COLL_REV	
Datatype	decimal	
Description	Indicates Customers Due For Collateral Revaluation	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

CUST_DUE_FOR_CR_LINE_EXP

Attribute	Description	
Name	CUST_DUE_FOR_CR_LINE_EXP	
Datatype	decimal	
Description	Indicates Customers Due For Credit Line Expiry	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

TD_MATDAYS

Attribute	Description	
Name	TD_MATDAYS	
Datatype	decimal	

Description	Indicates TD mature days	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

LOAN_MATDAYS

Attribute	Description	
Name	LOAN_MATDAYS	
Datatype	decimal	
Description	Indicates Loan mature days	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

BANKCODE

Attribute	Description	
Name	BANKCODE	
Datatype	string	
Description	Indicates Bank Code	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

WAKALA_EXPIRE_DAYS

Attribute	Description	
Name	WAKALA_EXPIRE_DAYS	
Datatype	decimal	
Description	Indicates Wakala Expire Days	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	

Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.10.4.ST-ModifyReportParam-Res-PK-MSG.xsd

MODIFYREPORTPARAM_IOPK_RES

FCUBS_HEADER

SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Report-Params-PK
BANKCODE
Report-Params-IO
LIEN_LIMIT_PERCENT
WITHDRAWAL_THRESHOLD
DEPOSIT_THRESHOLD
NEGATIVE_BAL_THRESHOLD
UTIL_PERCENT
CUST_DUE_FOR_COLL_REV
CUST_DUE_FOR_CR_LINE_EXP

TD_MATDAYS

LOAN_MATDAYS

BANKCODE

WAKALA_EXPIRE_DAYS

MAKER

MAKERSTAMP

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYREPORTPARAM_IOPK_RES

Attribute	Description
Name	MODIFYREPORTPARAM_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	string

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

MSGID

Attribute	Description					
Name	MSGID					
Datatype	string					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	string					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
------------------	--------------------

Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about PK Response	

Report-Params-PK

Attribute	Description
Name	Report-Params-PK
Datatype	
Description	

BANKCODE

Attribute	Description				
Name	BANKCODE				
Datatype	string				
Description	Indicates Bank Code				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>4</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	4
Restrictions	Description				
maxLength	4				

Report-Params-IO

Attribute	Description
Name	Report-Params-IO
Datatype	
Description	

LIEN_LIMIT_PERCENT

Attribute	Description				
Name	LIEN_LIMIT_PERCENT				
Datatype	decimal				
Description	Indicates Lien Limit Percentage				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

WITHDRAWAL_THRESHOLD

Attribute	Description				
Name	WITHDRAWAL_THRESHOLD				
Datatype	decimal				
Description	Indicates Withdrawal Threshold				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

DEPOSIT_THRESHOLD

Attribute	Description
-----------	-------------

Name	DEPOSIT_THRESHOLD	
Datatype	decimal	
Description	Indicates Deposit Threshold	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	totalDigits	22

NEGATIVE_BAL_THRESHOLD

Attribute	Description	
Name	NEGATIVE_BAL_THRESHOLD	
Datatype	decimal	
Description	Indicates Negative Balance Threshold	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	totalDigits	22

UTIL_PERCENT

Attribute	Description	
Name	UTIL_PERCENT	
Datatype	decimal	
Description	Indicates Utilization Percentage	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	totalDigits	22

CUST_DUE_FOR_COLL_REV

Attribute	Description	
Name	CUST_DUE_FOR_COLL_REV	
Datatype	decimal	
Description	Indicates Customers Due For Collateral Revaluation	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	totalDigits	22

CUST_DUE_FOR_CR_LINE_EXP

Attribute	Description
------------------	--------------------

Name	CUST_DUE_FOR_CR_LINE_EXP	
Datatype	decimal	
Description	Indicates Customers Due For Credit Line Expiry	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	totalDigits	22

TD_MATDAYS

Attribute	Description	
Name	TD_MATDAYS	
Datatype	decimal	
Description	Indicates TD mature days	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	totalDigits	22

LOAN_MATDAYS

Attribute	Description	
Name	LOAN_MATDAYS	
Datatype	decimal	
Description	Indicates Loan mature days	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	totalDigits	22

BANKCODE

Attribute	Description	
Name	BANKCODE	
Datatype	string	
Description	Indicates Bank Code	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	4

WAKALA_EXPIRE_DAYS

Attribute	Description
------------------	--------------------

Name	WAKALA_EXPIRE_DAYS	
Datatype	decimal	
Description	Indicates Wakala Expire Days	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.11.ModifyRMHierarchy

2.11.1.ST-ModifyRMHierarchy-Req-Full-MSG.xsd

[MODIFYRMHIERARCHY_FSFS_REQ](#)

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rm-Hierarchy-Full

RM_ID

RMNAME

PARENT_RM_ID

PARENTRMNAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

MODIFYRMHIERARCHY_FSFS_REQ

Attribute	Description
Name	MODIFYRMHIERARCHY_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	string				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	string
Description	This is the user id in the Source system who is performing the action.

Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Request of ModifyRMHierarchy	

Rm-Hierarchy-Full

Attribute	Description	
Name	Rm-Hierarchy-Full	
Datatype		
Description		

RM_ID

Attribute	Description	
Name	RM_ID	
Datatype	string	
Description	Indicates RM ID	
Restrictions	Restrictions	
	Description	
	maxLength	12

RMNAME

Attribute	Description	
Name	RMNAME	
Datatype	string	
Description	Indicates RM Name	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

PARENT_RM_ID

Attribute	Description	
Name	PARENT_RM_ID	
Datatype	string	
Description	Indicates Parent RM ID	
Restrictions	Restrictions	Description
	maxLength	12

PARENTRMNAME

Attribute	Description	
Name	PARENTRMNAME	
Datatype	string	
Description	Indicates Parent RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

2.11.2.ST-ModifyRMHierarchy-Req-IO-MSG.xsd

MODIFYRMHIERARCHY_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rm-Hierarchy-IO

RM_ID

PARENT_RM_ID

MAKER

MAKERSTAMP

MODIFYRMHIERARCHY_IOPK_REQ

Attribute	Description
Name	MODIFYRMHIERARCHY_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

ADDL

Attribute		Description	
Name	ADDL		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

FCUBS_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description	This XSD Gives Information about IO Request of ModifyRMHierarchy		

Rm-Hierarchy-IO

Attribute		Description	
Name	Rm-Hierarchy-IO		
Datatype			
Description			

RM_ID

Attribute		Description	
Name	RM_ID		
Datatype	string		
Description	Indicates RM ID		

Restrictions		
	Restrictions	Description
	maxLength	12

PARENT_RM_ID

Attribute	Description	
Name	PARENT_RM_ID	
Datatype	string	
Description	Indicates Parent RM ID	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

2.11.3.ST-ModifyRMHierarchy-Res-Full-MSG.xsd

MODIFYRMHIERARCHY_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Rm-Hierarchy-Full
RM_ID
RMNAME
PARENT_RM_ID
PARENTRMNAME
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYRMHIERARCHY_FSFS_RES

Attribute	Description
Name	MODIFYRMHIERARCHY_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
-----------	-------------

Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	string				
Description	This is the user id in the Source system who is performing the action.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	string				
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

FUNCTIONID

Attribute	Description				
Name	FUNCTIONID				
Datatype	string				
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

Rm-Hierarchy-Full

Attribute	Description
Name	Rm-Hierarchy-Full
Datatype	
Description	

RM_ID

Attribute	Description				
Name	RM_ID				
Datatype	string				
Description	Indicates RM ID				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

RMNAME

Attribute	Description	
Name	RMNAME	
Datatype	string	
Description	Indicates RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

PARENT_RM_ID

Attribute	Description	
Name	PARENT_RM_ID	
Datatype	string	
Description	Indicates Parent RM ID	
Restrictions	Restrictions	Description
	maxLength	12

PARENTRMNAME

Attribute	Description	
Name	PARENTRMNAME	
Datatype	string	
Description	Indicates Parent RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.11.4.ST-ModifyRMHierarchy-Res-PK-MSG.xsd

MODIFYRMHIERARCHY_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
 NAME
 VALUE
FCUBS_BODY
 Rm-Hierarchy-PK
 RM_ID
 Rm-Hierarchy-IO
 RM_ID
 PARENT_RM_ID
 MAKER
 MAKERSTAMP
FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

MODIFYRMHIERARCHY_IOPK_RES

Attribute	Description
Name	MODIFYRMHIERARCHY_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

Rm-Hierarchy-PK

Attribute	Description
Name	Rm-Hierarchy-PK
Datatype	
Description	

RM_ID

Attribute	Description				
Name	RM_ID				
Datatype	string				
Description	Indicates RM ID				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

Rm-Hierarchy-IO

Attribute	Description
Name	Rm-Hierarchy-IO
Datatype	
Description	

RM_ID

Attribute	Description				
Name	RM_ID				
Datatype	string				
Description	Indicates RM ID				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

PARENT_RM_ID

Attribute	Description
Name	PARENT_RM_ID
Datatype	string
Description	Indicates Parent RM ID

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.12.ModifyRMMassAmend

2.12.1.ST-ModifyRMMassAmend-Req-Full-MSG.xsd

[MODIFYRMMASSAMEND_FSFS_REQ](#)

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rm-Amend-Full

REFNO

FRMRMID

TORMID

RESTRLIST

EFFDT

STATUS

FRMRMNAME

TORMNAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Restriction

CUSTNO

CUSTNAME

MODIFYRMMASSAMEND_FSFS_REQ

Attribute	Description
Name	MODIFYRMMASSAMEND_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	string
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	string
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Request of ModifyRMMassAmend	

Rm-Amend-Full

Attribute	Description	
Name	Rm-Amend-Full	
Datatype		
Description		

REFNO

Attribute	Description	
------------------	--------------------	--

Name	REFNO	
Datatype	string	
Description	Indicates Reference Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

FRMRMID

Attribute	Description	
Name	FRMRMID	
Datatype	string	
Description	Indicates From RM ID	
Restrictions	Restrictions	Description
	maxLength	12

TORMID

Attribute	Description	
Name	TORMID	
Datatype	string	
Description	Indicates To RM ID	
Restrictions	Restrictions	Description
	maxLength	12

RESTRLIST

Attribute	Description	
Name	RESTRLIST	
Datatype	string	
Description	Indicates Customer Restrictions L - Allowed Customers R - Restrictive Customers A - All Customers	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	L,R,A

EFFDT

Attribute	Description	
Name	EFFDT	
Datatype	String	
Description	Indicates Effective Date	

STATUS

Attribute	Description
------------------	--------------------

Name	STATUS	
Datatype	string	
Description	Indicates Status N - Not Started C - Completed F - Failed	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	N,C,F

FRMRMNAME

Attribute	Description	
Name	FRMRMNAME	
Datatype	string	
Description	Indicates From RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TORMNAME

Attribute	Description	
Name	TORMNAME	
Datatype	string	
Description	Indicates To RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description
------------------	--------------------

Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description
------------------	--------------------

Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Restriction

Attribute	Description	
Name	Restriction	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	string	
Description	Indicates Customer No	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	11

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	string	
Description	Indicates Customer Name	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

2.12.2.ST-ModifyRMMassAmend-Req-IO-MSG.xsd

MODIFYRMMASSAMEND_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rm-Amend-IO

REFNO

FRMRMID

TORMID

RESTRLIST

EFFDT

FRMRMNAME

TORMNAME

MAKER

MAKERSTAMP

Restriction

CUSTNO

CUSTNAME

MODIFYRMMASSAMEND_IOPK_REQ

Attribute	Description
Name	MODIFYRMMASSAMEND_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	string
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	string
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of ModifyRMMassAmend

Rm-Amend-IO

Attribute	Description
Name	Rm-Amend-IO
Datatype	
Description	

REFNO

Attribute	Description
------------------	--------------------

Name	REFNO	
Datatype	string	
Description	Indicates Reference Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

FRMRMID

Attribute	Description	
Name	FRMRMID	
Datatype	string	
Description	Indicates From RM ID	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TORMID

Attribute	Description	
Name	TORMID	
Datatype	string	
Description	Indicates To RM ID	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

RESTRLIST

Attribute	Description	
Name	RESTRLIST	
Datatype	string	
Description	Indicates Customer Restrictions L - Allowed Customers R - Restrictive Customers A - All Customers	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	L,R,A

EFFDT

Attribute	Description
------------------	--------------------

Name	EFFDT	
Datatype	String	
Description	Indicates Effective Date	
Attribute		
	Attribute	Description
	minOccurs	0

FRMRMNAME

Attribute	Description	
Name	FRMRMNAME	
Datatype	string	
Description	Indicates From RM Name	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

TORMNAME

Attribute	Description	
Name	TORMNAME	
Datatype	string	
Description	Indicates To RM Name	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

Restriction

Attribute	Description	
Name	Restriction	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxOccurs	unbounded

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	string	
Description	Indicates Customer No	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	string	
Description	Indicates Customer Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

2.12.3.ST-ModifyRMMassAmend-Res-Full-MSG.xsd

MODIFYRMMASSAMEND_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Rm-Amend-Full
REFNO
FRMRMID
TORMID
RESTRLIST
EFFDT
STATUS
FRMRMNAME
TORMNAME
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Restriction

CUSTNO

CUSTNAME

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYRMMASSAMEND_FSFS_RES

Attribute	Description
Name	MODIFYRMMASSAMEND_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	string

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

MSGID

Attribute	Description					
Name	MSGID					
Datatype	string					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	string					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
------------------	--------------------

Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

Rm-Amend-Full

Attribute	Description
Name	Rm-Amend-Full
Datatype	
Description	

REFNO

Attribute	Description				
Name	REFNO				
Datatype	string				
Description	Indicates Reference Number				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

FRMRMID

Attribute	Description				
Name	FRMRMID				
Datatype	string				
Description	Indicates From RM ID				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

TORMID

Attribute	Description				
Name	TORMID				
Datatype	string				
Description	Indicates To RM ID				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

RESTRLIST

Attribute	Description				
Name	RESTRLIST				
Datatype	string				
Description	Indicates Customer Restrictions L - Allowed Customers R - Restrictive Customers A - All Customers				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>L,R,A</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	L,R,A
Restrictions	Description				
enumeration	L,R,A				

EFFDT

Attribute	Description
Name	EFFDT
Datatype	String
Description	Indicates Effective Date

STATUS

Attribute	Description				
Name	STATUS				
Datatype	string				
Description	Indicates Status N - Not Started C - Completed F - Failed				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>N,C,F</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	N,C,F
Restrictions	Description				
enumeration	N,C,F				

FRMRMNAME

Attribute	Description				
Name	FRMRMNAME				
Datatype	string				
Description	Indicates From RM Name				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>255</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

TORMNAME

Attribute	Description				
Name	TORMNAME				
Datatype	string				
Description	Indicates To RM Name				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>255</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

MAKER

Attribute	Description
Name	MAKER
Datatype	string
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

Restriction

Attribute	Description	
Name	Restriction	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	string	
Description	Indicates Customer No	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	string	
Description	Indicates Customer Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.12.4.ST-ModifyRMMassAmend-Res-PK-MSG.xsd

MODIFYRMMASSAMEND_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Rm-Amend-PK
REFNO
Rm-Amend-IO
REFNO
FRMRMID
TORMID
RESTRLIST
EFFDT
FRMRMNAME
TORMNAME
MAKER
MAKERSTAMP
Restriction
CUSTNO
CUSTNAME
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYRMMASSAMEND_IOPK_RES

Attribute	Description
Name	MODIFYRMMASSAMEND_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	string				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	string
Description	This is the user id in the Source system who is performing the action.

Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

FCUBS_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description	This XSD Gives Information about PK Response		

Rm-Amend-PK

Attribute		Description	
Name	Rm-Amend-PK		
Datatype			
Description			

REFNO

Attribute		Description	
Name	REFNO		
Datatype	string		
Description	Indicates Reference Number		
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	16	

Rm-Amend-IO

Attribute		Description	
Name	Rm-Amend-IO		
Datatype			

Description	
-------------	--

REFNO

Attribute	Description	
Name	REFNO	
Datatype	string	
Description	Indicates Reference Number	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	16

FRMRMID

Attribute	Description	
Name	FRMRMID	
Datatype	string	
Description	Indicates From RM ID	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

TORMID

Attribute	Description	
Name	TORMID	
Datatype	string	
Description	Indicates To RM ID	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

RESTRLIST

Attribute	Description	
Name	RESTRLIST	
Datatype	string	
Description	Indicates Customer Restrictions L - Allowed Customers R - Restrictive Customers A - All Customers	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	L,R,A

EFFDT

Attribute	Description	
Name	EFFDT	
Datatype	String	
Description	Indicates Effective Date	
Attribute		
	Attribute	Description
	minOccurs	0

FRMRMNAME

Attribute	Description	
Name	FRMRMNAME	
Datatype	string	
Description	Indicates From RM Name	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

TORMNAME

Attribute	Description	
Name	TORMNAME	
Datatype	string	
Description	Indicates To RM Name	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

Restriction

Attribute	Description						
Name	Restriction						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

CUSTNO

Attribute	Description				
Name	CUSTNO				
Datatype	string				
Description	Indicates Customer No				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>11</td></tr></tbody></table>	Restrictions	Description	maxLength	11
Restrictions	Description				
maxLength	11				

CUSTNAME

Attribute	Description				
Name	CUSTNAME				
Datatype	string				
Description	Indicates Customer Name				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

FCUBS_ERROR_RESP

Attribute	Description
-----------	-------------

Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	
	Description	
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	
	Description	
	maxOccurs	unbounded

WCODE

Attribute	Description
------------------	--------------------

Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.13.QueryReportParam

2.13.1.ST-QueryReportParam-Req-IO-MSG.xsd

QUERYREPORTPARAM_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Report-Params-IO

BANKCODE

QUERYREPORTPARAM_IOFS_REQ

Attribute	Description
Name	QUERYREPORTPARAM_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	

Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about IO Request of QueryReportParam	

Report-Params-IO

Attribute	Description	
Name	Report-Params-IO	
Datatype		
Description		

BANKCODE

Attribute	Description	
Name	BANKCODE	
Datatype	string	
Description	Indicates Bank Code	
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	maxLength	4

2.13.2.ST-QueryReportParam-Res-Full-MSG.xsd

QUERYREPORTPARAM_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Report-Params-IO
BANKCODE
Report-Params-Full
LIEN_LIMIT_PERCENT
WITHDRAWAL_THRESHOLD
DEPOSIT_THRESHOLD
NEGATIVE_BAL_THRESHOLD
UTIL_PERCENT
CUST_DUE_FOR_COLL_REV
CUST_DUE_FOR_CR_LINE_EXP
TD_MATDAYS

LOAN_MATDAYS

BANKCODE

WAKALA_EXPIRE_DAYS

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYREPORTPARAM_IOFS_RES

Attribute	Description
Name	QUERYREPORTPARAM_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description

Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

Report-Params-IO

Attribute	Description
Name	Report-Params-IO
Datatype	
Description	

BANKCODE

Attribute	Description				
Name	BANKCODE				
Datatype	string				
Description	Indicates Bank Code				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>4</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	4
Restrictions	Description				
maxLength	4				

Report-Params-Full

Attribute	Description
Name	Report-Params-Full
Datatype	
Description	

LIEN_LIMIT_PERCENT

Attribute	Description				
Name	LIEN_LIMIT_PERCENT				
Datatype	decimal				
Description	Indicates Lien Limit Percentage				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

WITHDRAWAL_THRESHOLD

Attribute	Description
Name	WITHDRAWAL_THRESHOLD
Datatype	decimal
Description	Indicates Withdrawal Threshold

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

DEPOSIT_THRESHOLD

Attribute	Description	
Name	DEPOSIT_THRESHOLD	
Datatype	decimal	
Description	Indicates Deposit Threshold	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

NEGATIVE_BAL_THRESHOLD

Attribute	Description	
Name	NEGATIVE_BAL_THRESHOLD	
Datatype	decimal	
Description	Indicates Negative Balance Threshold	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

UTIL_PERCENT

Attribute	Description	
Name	UTIL_PERCENT	
Datatype	decimal	
Description	Indicates Utilization Percentage	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

CUST_DUE_FOR_COLL_REV

Attribute	Description	
Name	CUST_DUE_FOR_COLL_REV	
Datatype	decimal	
Description	Indicates Customers Due For Collateral Revaluation	

Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	totalDigits	22
	Description	

CUST_DUE_FOR_CR_LINE_EXP

Attribute	Description	
Name	CUST_DUE_FOR_CR_LINE_EXP	
Datatype	decimal	
Description	Indicates Customers Due For Credit Line Expiry	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	totalDigits	22
	Description	

TD_MATDAYS

Attribute	Description	
Name	TD_MATDAYS	
Datatype	decimal	
Description	Indicates TD mature days	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	totalDigits	22
	Description	

LOAN_MATDAYS

Attribute	Description	
Name	LOAN_MATDAYS	
Datatype	decimal	
Description	Indicates Loan mature days	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	totalDigits	22
	Description	

BANKCODE

Attribute	Description	
Name	BANKCODE	
Datatype	string	
Description	Indicates Bank Code	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

WAKALA_EXPIRE_DAYS

Attribute	Description	
Name	WAKALA_EXPIRE_DAYS	
Datatype	decimal	
Description	Indicates Wakala Expire Days	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description
------------------	--------------------

Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.14.QueryRMHierarchy

2.14.1.ST-QueryRMHierarchy-Req-IO-MSG.xsd

QUERYRMHIERARCHY_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rm-Hierarchy-IO

RM_ID

QUERYRMHIERARCHY_IOFS_REQ

Attribute	Description
Name	QUERYRMHIERARCHY_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
-----------	-------------

Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
	Restrictions	Description
Restrictions	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	string				
Description	This is the user id in the Source system who is performing the action.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	string				
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

FUNCTIONID

Attribute	Description				
Name	FUNCTIONID				
Datatype	string				
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of QueryRMHierarchy

Rm-Hierarchy-IO

Attribute	Description
Name	Rm-Hierarchy-IO
Datatype	
Description	

RM_ID

Attribute	Description				
Name	RM_ID				
Datatype	string				
Description	Indicates RM ID				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

QUERYRMHIERARCHY_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rm-Hierarchy-IO

RM_ID

Rm-Hierarchy-Full

RM_ID

RMNAME

PARENT_RM_ID

PARENTRMNAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYRMHIERARCHY_IOFS_RES

Attribute	Description
Name	QUERYRMHIERARCHY_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	string
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	string
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

Rm-Hierarchy-IO

Attribute	Description	
Name	Rm-Hierarchy-IO	
Datatype		
Description		

RM_ID

Attribute	Description	
------------------	--------------------	--

Name	RM_ID	
Datatype	string	
Description	Indicates RM ID	
Restrictions		
	Restrictions	Description
	maxLength	12

Rm-Hierarchy-Full

Attribute	Description
Name	Rm-Hierarchy-Full
Datatype	
Description	

RM_ID

Attribute	Description	
Name	RM_ID	
Datatype	string	
Description	Indicates RM ID	
Restrictions		
	Restrictions	Description
	maxLength	12

RMNAME

Attribute	Description	
Name	RMNAME	
Datatype	string	
Description	Indicates RM Name	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

PARENT_RM_ID

Attribute	Description	
Name	PARENT_RM_ID	
Datatype	string	
Description	Indicates Parent RM ID	
Restrictions		
	Restrictions	Description
	maxLength	12

PARENTRMNAME

Attribute	Description
Name	PARENTRMNAME
Datatype	string
Description	Indicates Parent RM Name

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		

Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.15.QueryRMMassAmend

2.15.1.ST-QueryRMMassAmend-Req-IO-MSG.xsd

QUERYRMMASSAMEND_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rm-Amend-IO

REFNO

Attribute	Description
Name	QUERYRMMASSAMEND_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	string				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description						
Name	USERID						
Datatype	string						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description
Name	MODULEID
Datatype	string
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description
------------------	--------------------

Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of QueryRMMassAmend

Rm-Amend-IO

Attribute	Description
Name	Rm-Amend-IO
Datatype	
Description	

REFNO

Attribute	Description	
Name	REFNO	
Datatype	string	
Description	Indicates Reference Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

2.15.2.ST-QueryRMMassAmend-Res-Full-MSG.xsd

QUERYRMMASSAMEND_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Rm-Amend-IO
REFNO
Rm-Amend-Full
REFNO
FRMRMID
TORMID
RESTRLIST
EFFDT
STATUS
FRMRMNAME
TORMNAME
MAKER
MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Restriction

CUSTNO

CUSTNAME

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYRMMASSAMEND_IOFS_RES

Attribute	Description
Name	QUERYRMMASSAMEND_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	string				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description
Name	USERID

Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
pattern	[A-Z_0-9]*	

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
pattern	[a-zA-Z_0-9]{3}	

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

Rm-Amend-IO

Attribute	Description
Name	Rm-Amend-IO
Datatype	
Description	

REFNO

Attribute	Description				
Name	REFNO				
Datatype	string				
Description	Indicates Reference Number				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

Rm-Amend-Full

Attribute	Description
Name	Rm-Amend-Full
Datatype	
Description	

REFNO

Attribute	Description				
Name	REFNO				
Datatype	string				
Description	Indicates Reference Number				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

FRMRMID

Attribute	Description				
Name	FRMRMID				
Datatype	string				
Description	Indicates From RM ID				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

TORMID

Attribute	Description
Name	TORMID
Datatype	string
Description	Indicates To RM ID

Restrictions		
	Restrictions	Description
	maxLength	12

RESTRLIST

Attribute	Description	
Name	RESTRLIST	
Datatype	string	
Description	Indicates Customer Restrictions L - Allowed Customers R - Restrictive Customers A - All Customers	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	L,R,A

EFFDT

Attribute	Description	
Name	EFFDT	
Datatype	String	
Description	Indicates Effective Date	

STATUS

Attribute	Description	
Name	STATUS	
Datatype	string	
Description	Indicates Status N - Not Started C - Completed F - Failed	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	N,C,F

FRMRMNAME

Attribute	Description	
Name	FRMRMNAME	
Datatype	string	
Description	Indicates From RM Name	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

TORMNAME

Attribute	Description	
Name	TORMNAME	
Datatype	string	
Description	Indicates To RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Restriction

Attribute	Description	
Name	Restriction	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	string	
Description	Indicates Customer No	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	11

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	string	
Description	Indicates Customer Name	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.16.ReopenRMHierarchy

2.16.1.ST-ReopenRMHierarchy-Req-Full-MSG.xsd

[REOPENRMHIERARCHY_FSFS_REQ](#)

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rm-Hierarchy-Full

RM_ID

RMNAME

PARENT_RM_ID

PARENTRMNAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

REOPENRMHIERARCHY_FSFS_REQ

Attribute	Description
Name	REOPENRMHIERARCHY_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	string				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	string
Description	This is the user id in the Source system who is performing the action.

Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

FCUBS_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description	This XSD Gives Information about Full Request of ReopenRMHierarchy		

Rm-Hierarchy-Full

Attribute		Description	
Name	Rm-Hierarchy-Full		
Datatype			
Description			

RM_ID

Attribute		Description	
Name	RM_ID		
Datatype	string		
Description	Indicates RM ID		
Restrictions	Restrictions		Description
	maxLength	12	

RMNAME

Attribute		Description	
Name	RMNAME		
Datatype	string		
Description	Indicates RM Name		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

PARENT_RM_ID

Attribute	Description	
Name	PARENT_RM_ID	
Datatype	string	
Description	Indicates Parent RM ID	
Restrictions	Restrictions	Description
	maxLength	12

PARENTRMNAME

Attribute	Description	
Name	PARENTRMNAME	
Datatype	string	
Description	Indicates Parent RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

2.16.2.ST-ReopenRMHierarchy-Req-IO-MSG.xsd

REOPENRMHIERARCHY_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rm-Hierarchy-IO

RM_ID

MAKER

MAKERSTAMP

MODNO

REOPENRMHIERARCHY_IOPK_REQ

Attribute	Description
Name	REOPENRMHIERARCHY_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

ADDL

Attribute		Description	
Name	ADDL		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

FCUBS_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description	This XSD Gives Information about IO Request of ReopenRMHierarchy		

Rm-Hierarchy-IO

Attribute		Description	
Name	Rm-Hierarchy-IO		
Datatype			
Description			

RM_ID

Attribute		Description	
Name	RM_ID		
Datatype	string		
Description	Indicates RM ID		

Restrictions		
	Restrictions	Description
	maxLength	12

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

2.16.3.ST-ReopenRMHierarchy-Res-Full-MSG.xsd

REOPENRMHIERARCHY_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Rm-Hierarchy-Full
RM_ID
RMNAME
PARENT_RM_ID
PARENTRMNAME
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

REOPENRMHIERARCHY_FSFS_RES

Attribute	Description
Name	REOPENRMHIERARCHY_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
-----------	-------------

Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	string				
Description	This is the user id in the Source system who is performing the action.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	string				
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

FUNCTIONID

Attribute	Description				
Name	FUNCTIONID				
Datatype	string				
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

Rm-Hierarchy-Full

Attribute	Description
Name	Rm-Hierarchy-Full
Datatype	
Description	

RM_ID

Attribute	Description				
Name	RM_ID				
Datatype	string				
Description	Indicates RM ID				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

RMNAME

Attribute	Description	
Name	RMNAME	
Datatype	string	
Description	Indicates RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

PARENT_RM_ID

Attribute	Description	
Name	PARENT_RM_ID	
Datatype	string	
Description	Indicates Parent RM ID	
Restrictions	Restrictions	Description
	maxLength	12

PARENTRMNAME

Attribute	Description	
Name	PARENTRMNAME	
Datatype	string	
Description	Indicates Parent RM Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.16.4.ST-ReopenRMHierarchy-Res-PK-MSG.xsd

REOPENRMHIERARCHY_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rm-Hierarchy-PK

RM_ID

Rm-Hierarchy-IO

RM_ID

MAKER

MAKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

REOPENRMHIERARCHY_IOPK_RES

Attribute	Description
Name	REOPENRMHIERARCHY_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

Rm-Hierarchy-PK

Attribute	Description
Name	Rm-Hierarchy-PK
Datatype	
Description	

RM_ID

Attribute	Description				
Name	RM_ID				
Datatype	string				
Description	Indicates RM ID				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

Rm-Hierarchy-IO

Attribute	Description
Name	Rm-Hierarchy-IO
Datatype	
Description	

RM_ID

Attribute	Description				
Name	RM_ID				
Datatype	string				
Description	Indicates RM ID				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKER

Attribute	Description
Name	MAKER
Datatype	string
Description	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	



FINANCIAL SERVICES

Gateway Documentation - FCUBSRMSservice
[October] [2015]

Oracle Financial services Software Limited
Oracle Park
Off western Express Highway
Goregaon(East)
Mumbai,Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax:+91 22 6718 3001
www.oracle.com/financialservices/

Copyright © [2013], [2015], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.