

Gateway Documentation - FCUBSSMService  
Oracle FLEXCUBE Universal Banking  
Release FCUBS\_12.1.0.0.0  
[October][2015]



# Table Of Contents

<b>1. Background</b>	<b>1</b>
<b>2. FCUBSSMService</b>	<b>2</b>
<b>2.1. AuthorizeSMDBANKP</b>	<b>2</b>
2.1.1. SM-AuthorizeSMDBANKP-Req-Full-MSG.xsd	2
2.1.2. SM-AuthorizeSMDBANKP-Req-IO-MSG.xsd	19
2.1.3. SM-AuthorizeSMDBANKP-Res-Full-MSG.xsd	26
2.1.4. SM-AuthorizeSMDBANKP-Res-PK-MSG.xsd	45
<b>2.2. AuthorizeSMDRLMNE</b>	<b>54</b>
2.2.1. SM-AuthorizeSMDRLMNE-Req-Full-MSG.xsd	54
2.2.2. SM-AuthorizeSMDRLMNE-Req-IO-MSG.xsd	65
2.2.3. SM-AuthorizeSMDRLMNE-Res-Full-MSG.xsd	72
2.2.4. SM-AuthorizeSMDRLMNE-Res-PK-MSG.xsd	84
<b>2.3. AuthorizeUserMaint</b>	<b>93</b>
2.3.1. SM-AuthorizeUserMaint-Req-Full-MSG.xsd	93
2.3.2. SM-AuthorizeUserMaint-Req-IO-MSG.xsd	145
2.3.3. SM-AuthorizeUserMaint-Res-Full-MSG.xsd	153
2.3.4. SM-AuthorizeUserMaint-Res-PK-MSG.xsd	206
<b>2.4. CloseSMDBANKP</b>	<b>215</b>
2.4.1. SM-CloseSMDBANKP-Req-Full-MSG.xsd	215
2.4.2. SM-CloseSMDBANKP-Req-IO-MSG.xsd	233
2.4.3. SM-CloseSMDBANKP-Res-Full-MSG.xsd	240
2.4.4. SM-CloseSMDBANKP-Res-PK-MSG.xsd	259
<b>2.5. CloseSMDRLMNE</b>	<b>268</b>
2.5.1. SM-CloseSMDRLMNE-Req-Full-MSG.xsd	268
2.5.2. SM-CloseSMDRLMNE-Req-IO-MSG.xsd	279
2.5.3. SM-CloseSMDRLMNE-Res-Full-MSG.xsd	286
2.5.4. SM-CloseSMDRLMNE-Res-PK-MSG.xsd	298
<b>2.6. CloseUserMaint</b>	<b>307</b>
2.6.1. SM-CloseUserMaint-Req-Full-MSG.xsd	307
2.6.2. SM-CloseUserMaint-Req-IO-MSG.xsd	359
2.6.3. SM-CloseUserMaint-Res-Full-MSG.xsd	367
2.6.4. SM-CloseUserMaint-Res-PK-MSG.xsd	420
<b>2.7. CreateSMDBANKP</b>	<b>429</b>
2.7.1. SM-CreateSMDBANKP-Req-Full-MSG.xsd	429
2.7.2. SM-CreateSMDBANKP-Req-IO-MSG.xsd	447
2.7.3. SM-CreateSMDBANKP-Res-Full-MSG.xsd	462
2.7.4. SM-CreateSMDBANKP-Res-PK-MSG.xsd	480
<b>2.8. CreateSMDRLMNE</b>	<b>497</b>
2.8.1. SM-CreateSMDRLMNE-Req-Full-MSG.xsd	497
2.8.2. SM-CreateSMDRLMNE-Req-IO-MSG.xsd	507
2.8.3. SM-CreateSMDRLMNE-Res-Full-MSG.xsd	516
2.8.4. SM-CreateSMDRLMNE-Res-PK-MSG.xsd	527
<b>2.9. CreateSMRole</b>	<b>537</b>
2.9.1. SM-CreateSMRole-Req-Full-MSG.xsd	537
2.9.2. SM-CreateSMRole-Req-IO-MSG.xsd	592
2.9.3. SM-CreateSMRole-Res-Full-MSG.xsd	644
2.9.4. SM-CreateSMRole-Res-PK-MSG.xsd	700
<b>2.10. CreateUserMaint</b>	<b>753</b>

2.10.1.SM-CreateUserMaint-Req-Full-MSG.xsd	753
2.10.2.SM-CreateUserMaint-Req-IO-MSG.xsd	805
2.10.3.SM-CreateUserMaint-Res-Full-MSG.xsd	851
2.10.4.SM-CreateUserMaint-Res-PK-MSG.xsd	904
<b>2.11.DeleteSMDBANKP</b>	<b>951</b>
2.11.1.SM-DeleteSMDBANKP-Req-Full-MSG.xsd	951
2.11.2.SM-DeleteSMDBANKP-Req-IO-MSG.xsd	968
2.11.3.SM-DeleteSMDBANKP-Res-Full-MSG.xsd	975
2.11.4.SM-DeleteSMDBANKP-Res-PK-MSG.xsd	994
<b>2.12.DeleteSMDRLMNE</b>	<b>1002</b>
2.12.1.SM-DeleteSMDRLMNE-Req-Full-MSG.xsd	1002
2.12.2.SM-DeleteSMDRLMNE-Req-IO-MSG.xsd	1013
2.12.3.SM-DeleteSMDRLMNE-Res-Full-MSG.xsd	1019
2.12.4.SM-DeleteSMDRLMNE-Res-PK-MSG.xsd	1031
<b>2.13.DeleteSMRole</b>	<b>1039</b>
2.13.1.SM-DeleteSMRole-Req-Full-MSG.xsd	1039
2.13.2.SM-DeleteSMRole-Req-IO-MSG.xsd	1094
2.13.3.SM-DeleteSMRole-Res-Full-MSG.xsd	1101
2.13.4.SM-DeleteSMRole-Res-PK-MSG.xsd	1157
<b>2.14.DeleteUserMaint</b>	<b>1166</b>
2.14.1.SM-DeleteUserMaint-Req-Full-MSG.xsd	1166
2.14.2.SM-DeleteUserMaint-Req-IO-MSG.xsd	1218
2.14.3.SM-DeleteUserMaint-Res-Full-MSG.xsd	1224
2.14.4.SM-DeleteUserMaint-Res-PK-MSG.xsd	1278
<b>2.15.ModifySMDBANKP</b>	<b>1286</b>
2.15.1.SM-ModifySMDBANKP-Req-Full-MSG.xsd	1286
2.15.2.SM-ModifySMDBANKP-Req-IO-MSG.xsd	1303
2.15.3.SM-ModifySMDBANKP-Res-Full-MSG.xsd	1319
2.15.4.SM-ModifySMDBANKP-Res-PK-MSG.xsd	1338
<b>2.16.ModifySMDRLMNE</b>	<b>1355</b>
2.16.1.SM-ModifySMDRLMNE-Req-Full-MSG.xsd	1355
2.16.2.SM-ModifySMDRLMNE-Req-IO-MSG.xsd	1366
2.16.3.SM-ModifySMDRLMNE-Res-Full-MSG.xsd	1375
2.16.4.SM-ModifySMDRLMNE-Res-PK-MSG.xsd	1386
<b>2.17.ModifySMRole</b>	<b>1397</b>
2.17.1.SM-ModifySMRole-Req-Full-MSG.xsd	1397
2.17.2.SM-ModifySMRole-Req-IO-MSG.xsd	1452
2.17.3.SM-ModifySMRole-Res-Full-MSG.xsd	1512
2.17.4.SM-ModifySMRole-Res-PK-MSG.xsd	1568
<b>2.18.ModifyUserMaint</b>	<b>1630</b>
2.18.1.SM-ModifyUserMaint-Req-Full-MSG.xsd	1630
2.18.2.SM-ModifyUserMaint-Req-IO-MSG.xsd	1682
2.18.3.SM-ModifyUserMaint-Res-Full-MSG.xsd	1724
2.18.4.SM-ModifyUserMaint-Res-PK-MSG.xsd	1778
<b>2.19.QuerySMDBANKP</b>	<b>1822</b>
2.19.1.SM-QuerySMDBANKP-Req-IO-MSG.xsd	1822
2.19.2.SM-QuerySMDBANKP-Res-Full-MSG.xsd	1829
<b>2.20.QuerySMDRLMNE</b>	<b>1847</b>
2.20.1.SM-QuerySMDRLMNE-Req-IO-MSG.xsd	1847
2.20.2.SM-QuerySMDRLMNE-Res-Full-MSG.xsd	1854
<b>2.21.QuerySMRole</b>	<b>1866</b>
2.21.1.SM-QuerySMRole-Req-IO-MSG.xsd	1866

2.21.2.SM-QuerySMRole-Res-Full-MSG.xsd	1873
<b>2.22.QueryUserMaint</b>	<b>1929</b>
2.22.1.SM-QueryUserMaint-Req-IO-MSG.xsd	1929
2.22.2.SM-QueryUserMaint-Res-Full-MSG.xsd	1937
<b>2.23.ReopenSMDBANKP</b>	<b>1991</b>
2.23.1.SM-ReopenSMDBANKP-Req-Full-MSG.xsd	1991
2.23.2.SM-ReopenSMDBANKP-Req-IO-MSG.xsd	2008
2.23.3.SM-ReopenSMDBANKP-Res-Full-MSG.xsd	2016
2.23.4.SM-ReopenSMDBANKP-Res-PK-MSG.xsd	2035
<b>2.24.ReopenSMDRLMNE</b>	<b>2044</b>
2.24.1.SM-ReopenSMDRLMNE-Req-Full-MSG.xsd	2044
2.24.2.SM-ReopenSMDRLMNE-Req-IO-MSG.xsd	2054
2.24.3.SM-ReopenSMDRLMNE-Res-Full-MSG.xsd	2062
2.24.4.SM-ReopenSMDRLMNE-Res-PK-MSG.xsd	2074
<b>2.25.ReopenUserMaint</b>	<b>2083</b>
2.25.1.SM-ReopenUserMaint-Req-Full-MSG.xsd	2083
2.25.2.SM-ReopenUserMaint-Req-IO-MSG.xsd	2135
2.25.3.SM-ReopenUserMaint-Res-Full-MSG.xsd	2142
2.25.4.SM-ReopenUserMaint-Res-PK-MSG.xsd	2196

## 1. Background

Integration of different applications and solutions is a key area in today's systems. A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data. The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs. The integration needs supported by the Gateway can be broadly categorized from the perspective of Gateway as follows

### 1. Inbound application integration :

This is used when any external system needs to add, modify or query information within FLEXCUBE UBS

### 2. Outbound application integration :

This is used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS

The following sections provide detailed XSD documentation of all operations available in FCUBSSMService of SMS Module

## 2. FCUBSSMService

### 2.1.AuthorizeSMDBANKP

2.1.1.SM-AuthorizeSMDBANKP-Req-Full-MSG.xsd

*AUTHORIZESMDBANKP\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Parameters-Full*

*HEAD\_OFFICE*

*SITE\_CODE*

*ACTIVATION\_KEY*

*INVALID\_LOGINS\_CUM*

*INVALID\_LOGINS\_SUC*  
*PWD\_PREVENT\_REUSE*  
*PWD\_CHANGE\_AFTER*  
*MAXIMUM*  
*MINIMUM*  
*PWD\_EXPIRY\_MSG\_DAYS*  
*ARCHIVAL\_PERIOD*  
*CONCHAR\_PWD\_NUM*  
*FREQ\_PWD\_CHG*  
*MIN\_PWD\_NUMERIC\_LENGTH*  
*LEGAL\_NOTICE*  
*DORMANCY\_DAYS*  
*DISPLAY\_LEGAL\_NOTICE*  
*MIN\_SPECIALCHAR\_LENGTH*  
*MIN\_LOWERCASE\_CHAR*  
*MIN\_UPPERCASE\_CHAR*  
*SCREESAVERREQUIRED*  
*SCREESAVERTIMEOUTINSECONDS*  
*SCREESAVERMODIFIABLEBYUSER*  
*PASSWORDEXTERNAL*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*Smtbs-Branch-Restr*  
*RESTR\_TYPE*  
*DESCRIPTION*  
*Smtbs-Restrictive-Passwd*  
*PASSWORD*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

**AUTHORIZESMDBANKP\_FSFS\_REQ**

Attribute	Description
Name	AUTHORIZESMDBANKP_FSFS_REQ
Datatype	
Description	

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

**SOURCE**

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

**UBSCOMP**

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

**MSGID**

Attribute	Description
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	string				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	string
Description	This is the user id in the Source system who is performing the action.

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

## FCUBS\_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Request of AuthorizeSMD BANKP	

## Smtbs-Parameters-Full

Attribute	Description	
Name	Smtbs-Parameters-Full	
Datatype		
Description		

## HEAD\_OFFICE

Attribute	Description	
Name	HEAD_OFFICE	
Datatype	string	
Description	Indicates Head Office	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

## SITE\_CODE

Attribute	Description	
Name	SITE_CODE	
Datatype	string	

Description	Indicates Site Code	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

### ACTIVATION\_KEY

<b>Attribute</b>	<b>Description</b>	
Name	ACTIVATION_KEY	
Datatype	string	
Description	Indicates Activation Key	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	24

### INVALID\_LOGINS\_CUM

<b>Attribute</b>	<b>Description</b>	
Name	INVALID_LOGINS_CUM	
Datatype	decimal	
Description	Indicates Cumulative	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	6
	maxInclusive	99

### INVALID\_LOGINS\_SUC

<b>Attribute</b>	<b>Description</b>	
Name	INVALID_LOGINS_SUC	
Datatype	decimal	
Description	Indicates Successive	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	1
	minInclusive	3
	maxInclusive	5

### PWD\_PREVENT\_REUSE

<b>Attribute</b>	<b>Description</b>	
Name	PWD_PREVENT_REUSE	
Datatype	decimal	

Description	Indicates Password Repetitions	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## PWD\_CHANGE\_AFTER

<b>Attribute</b>	<b>Description</b>	
Name	PWD_CHANGE_AFTER	
Datatype	decimal	
Description	Indicates Force Password Change After	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	3
	minInclusive	15
	maxInclusive	180

## MAXIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MAXIMUM	
Datatype	decimal	
Description	Indicates Maximum	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	12
	maxInclusive	30

## MINIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MINIMUM	
Datatype	decimal	
Description	Indicates Minimum	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	6
	maxInclusive	11

## PWD\_EXPIRY\_MSG\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	PWD_EXPIRY_MSG_DAYS	
Datatype	decimal	
Description	Indicates Intimate User (Before Password Expiry)	

Attribute	<b>Attribute</b>		<b>Description</b>	
	minOccurs		0	
Restrictions	<b>Restrictions</b>		<b>Description</b>	
	totalDigits		2	
	minInclusive		1	
	maxInclusive		5	

## ARCHIVAL\_PERIOD

<b>Attribute</b>		<b>Description</b>		
Name		ARCHIVAL_PERIOD		
Datatype		decimal		
Description		Indicates Archival Period (in days)		
Attribute	<b>Attribute</b>		<b>Description</b>	
	minOccurs		0	
Restrictions	<b>Restrictions</b>		<b>Description</b>	
	totalDigits		3	

## CONCHAR\_PWD\_NUM

<b>Attribute</b>		<b>Description</b>		
Name		CONCHAR_PWD_NUM		
Datatype		decimal		
Description		Indicates Maximum Consecutive Repetitive Characters		
Attribute	<b>Attribute</b>		<b>Description</b>	
	minOccurs		0	
Restrictions	<b>Restrictions</b>		<b>Description</b>	
	totalDigits		2	

## FREQ\_PWD\_CHG

<b>Attribute</b>		<b>Description</b>		
Name		FREQ_PWD_CHG		
Datatype		decimal		
Description		Indicates Minimum Days Between Password Changes		
Attribute	<b>Attribute</b>		<b>Description</b>	
	minOccurs		0	
Restrictions	<b>Restrictions</b>		<b>Description</b>	
	totalDigits		2	
	minInclusive		0	

## MIN\_PWD\_NUMERIC\_LENGTH



Attribute	Description						
Name	MIN_PWD_NUMERIC_LENGTH						
Datatype	decimal						
Description	Indicates Minimum Number Of Numeric Characters In Password						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>2</td> </tr> <tr> <td>minInclusive</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	2	minInclusive	1
Restrictions	Description						
totalDigits	2						
minInclusive	1						

## LEGAL\_NOTICE

Attribute	Description				
Name	LEGAL_NOTICE				
Datatype	string				
Description	Indicates Warning Screen Text				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>4000</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	4000
Restrictions	Description				
maxLength	4000				

## DORMANCY\_DAYS

Attribute	Description						
Name	DORMANCY_DAYS						
Datatype	decimal						
Description	Indicates Dormancy Days						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>2</td> </tr> <tr> <td>minInclusive</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	2	minInclusive	1
Restrictions	Description						
totalDigits	2						
minInclusive	1						

## DISPLAY\_LEGAL\_NOTICE

Attribute	Description				
Name	DISPLAY_LEGAL_NOTICE				
Datatype	string				
Description	Indicates Display Legal Notice Y - on N - Off				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Y,N</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## MIN\_SPECIALCHAR\_LENGTH

Attribute	Description
-----------	-------------

Name	MIN_SPECIALCHAR_LENGTH	
Datatype	decimal	
Description	Indicates Minimum Number Of Special Characters In Password	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## MIN\_LOWERCASE\_CHAR

<b>Attribute</b>	<b>Description</b>	
Name	MIN_LOWERCASE_CHAR	
Datatype	decimal	
Description	Indicates Minimum Number of LowerCase Characters in Password	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## MIN\_UPPERCASE\_CHAR

<b>Attribute</b>	<b>Description</b>	
Name	MIN_UPPERCASE_CHAR	
Datatype	decimal	
Description	Indicates Minimum Number of UpperCase Characters in Password	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## SCRENSAVERREQUIRED

<b>Attribute</b>	<b>Description</b>	
Name	SCRENSAVERREQUIRED	
Datatype	string	
Description	Indicates Screensaver Required Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SCRENSAVERTIMEOUTINSECONDS

<b>Attribute</b>	<b>Description</b>	
Name	SCRENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description	Indicates Screensaver Interval (in seconds)	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

### SCREENSAVERMODIFIABLEBYUSER

<b>Attribute</b>	<b>Description</b>	
Name	SCREENSAVERMODIFIABLEBYUSER	
Datatype	string	
Description	Indicates Screensaver Interval Modifiable at User Level Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### PASSWORDEXTERNAL

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORDEXTERNAL	
Datatype	string	
Description	Indicates Password External Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	

Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	

Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## Smtbs-Branch-Restr

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Branch-Restr	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## RESTR\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_TYPE	
Datatype	string	
Description	Indicates Restriction Type	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Restriction Type Description	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

### Smtbs-Restrictive-Passwd

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Restrictive-Passwd	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description	Indicates Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

### FLDVAL

<b>Attribute</b>	<b>Description</b>
Name	FLDVAL

Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

2.1.2.SM-AuthorizeSMDBANKP-Req-IO-MSG.xsd

*AUTHORIZESMDBANKP\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Parameters-IO*

*SITE\_CODE*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

## AUTHORIZESMDBANKP\_IOPK\_REQ

Attribute	Description
Name	AUTHORIZESMDBANKP_IOPK_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.



Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	string				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	string
Description	This is the user id in the Source system who is performing the action.

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

## FCUBS\_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about IO Request of AuthorizeSMDBANKP	

## Smtbs-Parameters-IO

Attribute	Description	
Name	Smtbs-Parameters-IO	
Datatype		
Description		

## SITE\_CODE

Attribute	Description	
Name	SITE_CODE	
Datatype	string	
Description	Indicates Site Code	
Restrictions	Restrictions	Description
	maxLength	4

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

### 2.1.3.SM-AuthorizeSMDBANKP-Res-Full-MSG.xsd

*AUTHORIZESMDBANKP\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Smtbs-Parameters-Full*  
*HEAD\_OFFICE*  
*SITE\_CODE*  
*ACTIVATION\_KEY*  
*INVALID\_LOGINS\_CUM*  
*INVALID\_LOGINS\_SUC*  
*PWD\_PREVENT\_REUSE*  
*PWD\_CHANGE\_AFTER*  
*MAXIMUM*  
*MINIMUM*  
*PWD\_EXPIRY\_MSG\_DAYS*  
*ARCHIVAL\_PERIOD*  
*CONCHAR\_PWD\_NUM*  
*FREQ\_PWD\_CHG*  
*MIN\_PWD\_NUMERIC\_LENGTH*  
*LEGAL\_NOTICE*  
*DORMANCY\_DAYS*  
*DISPLAY\_LEGAL\_NOTICE*  
*MIN\_SPECIALCHAR\_LENGTH*

MIN\_LOWERCASE\_CHAR  
 MIN\_UPPERCASE\_CHAR  
 SCREENSAVERREQUIRED  
 SCREENSAVERTIMEOUTINSECONDS  
 SCREENSAVERMODIFIABLEBYUSER  
 PASSWORDEXTERNAL  
 MAKER  
 MAKERSTAMP  
 CHECKER  
 CHECKERSTAMP  
 MODNO  
 TXNSTAT  
 AUTHSTAT  
 Smtbs-Branch-Restr  
     RESTR\_TYPE  
     DESCRIPTION  
 Smtbs-Restrictive-Passwd  
     PASSWORD  
 UDFDETAILS  
     FLDNAM  
     FLDVAL  
 FCUBS\_ERROR\_RESP  
     ERROR  
     ECODE  
     EDESC  
 FCUBS\_WARNING\_RESP  
     WARNING  
     WCODE  
     WDESC

**AUTHORIZESMDBANKP\_FSFS\_RES**

Attribute	Description
Name	AUTHORIZESMDBANKP_FSFS_RES



Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

## Smtbs-Parameters-Full

<b>Attribute</b>	<b>Description</b>
Name	Smtbs-Parameters-Full
Datatype	
Description	

## HEAD\_OFFICE

<b>Attribute</b>	<b>Description</b>	
Name	HEAD_OFFICE	
Datatype	string	
Description	Indicates Head Office	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## SITE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	SITE_CODE	
Datatype	string	
Description	Indicates Site Code	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

## ACTIVATION\_KEY

Attribute	Description				
Name	ACTIVATION_KEY				
Datatype	string				
Description	Indicates Activation Key				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>24</td></tr></tbody></table>	Restrictions	Description	maxLength	24
Restrictions	Description				
maxLength	24				

## INVALID\_LOGINS\_CUM

Attribute	Description								
Name	INVALID_LOGINS_CUM								
Datatype	decimal								
Description	Indicates Cumulative								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>6</td></tr><tr><td>maxInclusive</td><td>99</td></tr></tbody></table>	Restrictions	Description	totalDigits	2	minInclusive	6	maxInclusive	99
Restrictions	Description								
totalDigits	2								
minInclusive	6								
maxInclusive	99								

## INVALID\_LOGINS\_SUC

Attribute	Description								
Name	INVALID_LOGINS_SUC								
Datatype	decimal								
Description	Indicates Successive								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>1</td></tr><tr><td>minInclusive</td><td>3</td></tr><tr><td>maxInclusive</td><td>5</td></tr></tbody></table>	Restrictions	Description	totalDigits	1	minInclusive	3	maxInclusive	5
Restrictions	Description								
totalDigits	1								
minInclusive	3								
maxInclusive	5								

## PWD\_PREVENT\_REUSE

Attribute	Description				
Name	PWD_PREVENT_REUSE				
Datatype	decimal				
Description	Indicates Password Repetitions				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## PWD\_CHANGE\_AFTER

<b>Attribute</b>	<b>Description</b>	
Name	PWD_CHANGE_AFTER	
Datatype	decimal	
Description	Indicates Force Password Change After	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	3
	minInclusive	15
	maxInclusive	180

## MAXIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MAXIMUM	
Datatype	decimal	
Description	Indicates Maximum	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	12
	maxInclusive	30

## MINIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MINIMUM	
Datatype	decimal	
Description	Indicates Minimum	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	6
	maxInclusive	11

## PWD\_EXPIRY\_MSG\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	PWD_EXPIRY_MSG_DAYS	
Datatype	decimal	
Description	Indicates Intimate User (Before Password Expiry)	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	2
	minInclusive	1
	maxInclusive	5

## ARCHIVAL\_PERIOD

<b>Attribute</b>	<b>Description</b>	
Name	ARCHIVAL_PERIOD	
Datatype	decimal	
Description	Indicates Archival Period (in days)	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	3

## CONCHAR\_PWD\_NUM

<b>Attribute</b>	<b>Description</b>	
Name	CONCHAR_PWD_NUM	
Datatype	decimal	
Description	Indicates Maximum Consecutive Repetitive Characters	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	2

## FREQ\_PWD\_CHG

<b>Attribute</b>	<b>Description</b>	
Name	FREQ_PWD_CHG	
Datatype	decimal	
Description	Indicates Minimum Days Between Password Changes	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	2
	minInclusive	0

## MIN\_PWD\_NUMERIC\_LENGTH

<b>Attribute</b>	<b>Description</b>	
Name	MIN_PWD_NUMERIC_LENGTH	
Datatype	decimal	

Description	Indicates Minimum Number Of Numeric Characters In Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## LEGAL\_NOTICE

<b>Attribute</b>	<b>Description</b>	
Name	LEGAL_NOTICE	
Datatype	string	
Description	Indicates Warning Screen Text	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

## DORMANCY\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	DORMANCY_DAYS	
Datatype	decimal	
Description	Indicates Dormancy Days	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## DISPLAY\_LEGAL\_NOTICE

<b>Attribute</b>	<b>Description</b>	
Name	DISPLAY_LEGAL_NOTICE	
Datatype	string	
Description	Indicates Display Legal Notice Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MIN\_SPECIALCHAR\_LENGTH

<b>Attribute</b>	<b>Description</b>	
Name	MIN_SPECIALCHAR_LENGTH	
Datatype	decimal	
Description	Indicates Minimum Number Of Special Characters In Password	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### MIN\_LOWERCASE\_CHAR

<b>Attribute</b>	<b>Description</b>	
Name	MIN_LOWERCASE_CHAR	
Datatype	decimal	
Description	Indicates Minimum Number of LowerCase Characters in Password	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### MIN\_UPPERCASE\_CHAR

<b>Attribute</b>	<b>Description</b>	
Name	MIN_UPPERCASE_CHAR	
Datatype	decimal	
Description	Indicates Minimum Number of UpperCase Characters in Password	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### SCRENSAVERREQUIRED

<b>Attribute</b>	<b>Description</b>	
Name	SCRENSAVERREQUIRED	
Datatype	string	
Description	Indicates Screensaver Required Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### SCRENSAVERTIMEOUTINSECONDS

<b>Attribute</b>	<b>Description</b>	
Name	SCRENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description	Indicates Screensaver Interval (in seconds)	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

### SCREENSAVERMODIFIABLEBYUSER

<b>Attribute</b>	<b>Description</b>	
Name	SCREENSAVERMODIFIABLEBYUSER	
Datatype	string	
Description	Indicates Screensaver Interval Modifiable at User Level Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### PASSWORDEXTERNAL

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORDEXTERNAL	
Datatype	string	
Description	Indicates Password External Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## Smtbs-Branch-Restr

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Branch-Restr	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## RESTR\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_TYPE	
Datatype	string	
Description	Indicates Restriction Type	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Restriction Type Description	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

### Smtbs-Restrictive-Passwd

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Restrictive-Passwd	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description	Indicates Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

### FLDVAL

<b>Attribute</b>	<b>Description</b>
Name	FLDVAL

Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	150
	minLength	0
	<b>Description</b>	

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	maxOccurs	unbounded
	<b>Description</b>	

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	



## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

### 2.1.4.SM-AuthorizeSMDBANKP-Res-PK-MSG.xsd

*AUTHORIZESMDBANKP\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Parameters-PK*

*SITE\_CODE*

*Smtbs-Parameters-IO*

*SITE\_CODE*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## **AUTHORIZESMDBANKP\_IOPK\_RES**

<b>Attribute</b>	<b>Description</b>
Name	AUTHORIZESMDBANKP_IOPK_RES
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

<b>Attribute</b>	<b>Description</b>
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within EL EXCLUDE LIBS. In

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

Attribute	Description

Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

## Smtbs-Parameters-PK

Attribute	Description
Name	Smtbs-Parameters-PK
Datatype	
Description	

## SITE\_CODE

Attribute	Description	
Name	SITE_CODE	
Datatype	string	
Description	Indicates Site Code	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

## Smtbs-Parameters-IO

Attribute	Description
Name	Smtbs-Parameters-IO
Datatype	
Description	

## SITE\_CODE

Attribute	Description	
Name	SITE_CODE	
Datatype	string	
Description	Indicates Site Code	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12



## CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

## 2.2.AuthorizeSMDRLMNE

2.2.1.SM-AuthorizeSMDRLMNE-Req-Full-MSG.xsd

*AUTHORIZESMDRLMNE\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Smtbs-Role-Limit-Full*  
*ROLEID2*  
*DESCRIPTION*  
*LIMIT\_CCY*  
*INPUT\_LIMIT*  
*AUTHORIZATION\_LIMIT*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*UDFDETAILS*  
*FLDNAM*  
*FLDVAL*

## AUTHORIZESMDRLMNE\_FSFS\_REQ

Attribute	Description
Name	AUTHORIZESMDRLMNE_FSFS_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>
Name	MODULEID

Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM



Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

## FCUBS\_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Request of AuthorizeSMDRLMNE	

## Smtbs-Role-Limit-Full

Attribute	Description	
Name	Smtbs-Role-Limit-Full	
Datatype		
Description		

## ROLEID2

Attribute	Description	
Name	ROLEID2	
Datatype	string	
Description	Indicates Role Id	
Restrictions	Restrictions	Description
	maxLength	15

## DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Description	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

### LIMIT\_CCY

<b>Attribute</b>	<b>Description</b>	
Name	LIMIT_CCY	
Datatype	string	
Description	Indicates Limit Currency	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### INPUT\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	INPUT_LIMIT	
Datatype	decimal	
Description	Indicates Input Limit	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0

### AUTHORIZATION\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHORIZATION_LIMIT	
Datatype	decimal	
Description	Indicates Authorization Limit	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0

### MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

## CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

2.2.2.SM-AuthorizeSMDRLMNE-Req-IO-MSG.xsd

*AUTHORIZESMDRLMNE\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Role-Limit-IO*

*ROLEID2*

CHECKER

CHECKERSTAMP

MODNO

### AUTHORIZESMDRLMNE\_IOPK\_REQ

Attribute	Description
Name	AUTHORIZESMDRLMNE_IOPK_REQ
Datatype	
Description	

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

### SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

### UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

### MSGID

Attribute	Description
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	string				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	string
Description	This is the user id in the Source system who is performing the action.



Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

## FCUBS\_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about IO Request of AuthorizeSMDRLMNE	

## Smtbs-Role-Limit-IO

Attribute	Description	
Name	Smtbs-Role-Limit-IO	
Datatype		
Description		

## ROLEID2

Attribute	Description	
Name	ROLEID2	
Datatype	string	
Description	Indicates Role Id	
Restrictions	Restrictions	Description
	maxLength	15

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

### 2.2.3.SM-AuthorizeSMDRLMNE-Res-Full-MSG.xsd

*AUTHORIZESMDRLMNE\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTIRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Smtbs-Role-Limit-Full*  
*ROLEID2*  
*DESCRIPTION*  
*LIMIT\_CCY*  
*INPUT\_LIMIT*  
*AUTHORIZATION\_LIMIT*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*UDFDETAILS*  
*FLDNAM*  
*FLDVAL*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*

EDESC

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## AUTHORIZESMDRLMNE\_FSFS\_RES

Attribute	Description
Name	AUTHORIZESMDRLMNE_FSFS_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	string				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	string
Description	This is the user id in the Source system who is performing the action.



Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
	maxOccurs	unbounded	

## NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

## VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

## FCUBS\_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description	This XSD Gives Information about Full Response		

## Smtbs-Role-Limit-Full

Attribute		Description	
Name	Smtbs-Role-Limit-Full		
Datatype			
Description			

## ROLEID2

Attribute		Description	
Name	ROLEID2		
Datatype	string		
Description	Indicates Role Id		
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	15	

## DESCRIPTION

Attribute		Description	
Name	DESCRIPTION		
Datatype	string		
Description	Indicates Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

### LIMIT\_CCY

<b>Attribute</b>	<b>Description</b>	
Name	LIMIT_CCY	
Datatype	string	
Description	Indicates Limit Currency	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### INPUT\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	INPUT_LIMIT	
Datatype	decimal	
Description	Indicates Input Limit	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0

### AUTHORIZATION\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHORIZATION_LIMIT	
Datatype	decimal	
Description	Indicates Authorization Limit	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0

### MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

## CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

## WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

## WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

### 2.2.4.SM-AuthorizeSMDRLMNE-Res-PK-MSG.xsd

*AUTHORIZESMDRLMNE\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*



*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Role-Limit-PK*

*ROLEID2*

*Smtbs-Role-Limit-IO*

*ROLEID2*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## **AUTHORIZESMDRLMNE\_IOPK\_RES**

<b>Attribute</b>	<b>Description</b>
Name	AUTHORIZESMDRLMNE_IOPK_RES
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

<b>Attribute</b>	<b>Description</b>
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

Attribute	Description

Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

## Smtbs-Role-Limit-PK

Attribute	Description
Name	Smtbs-Role-Limit-PK
Datatype	
Description	

## ROLEID2

Attribute	Description				
Name	ROLEID2				
Datatype	string				
Description	Indicates Role Id				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>15</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## Smtbs-Role-Limit-IO

Attribute	Description
Name	Smtbs-Role-Limit-IO
Datatype	
Description	

## ROLEID2

Attribute	Description				
Name	ROLEID2				
Datatype	string				
Description	Indicates Role Id				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>15</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## CHECKER

Attribute	Description				
Name	CHECKER				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## CHECKERSTAMP

Attribute	Description				
Name	CHECKERSTAMP				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

## MODNO

Attribute	Description				
Name	MODNO				
Datatype	decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>4</td></tr></tbody></table>	Restrictions	Description	totalDigits	4
Restrictions	Description				
totalDigits	4				

## FCUBS\_ERROR\_RESP

Attribute	Description						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

## EDESC



Attribute	Description
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

## 2.3.AuthorizeUserMaint

### 2.3.1.SM-AuthorizeUserMaint-Req-Full-MSG.xsd

*AUTHORIZEUSERMAINT\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*USR-Full*  
*STRTDATE*  
*USRNAME*  
*USRPWD*  
*ENDDT*  
*USRLANG*  
*HOMEBRN*  
*CUSTNO*  
*LDAPUSR*  
*TIMELEVEL*  
*AUTOAUTH*  
*USRSTAT*  
*USRID*  
*EXTUSRREF*  
*USRCATEG*  
*TILLALLOW*

*ACCCLSALLOW*  
*GLALLOW*  
*USRTXNLMT*  
*LMTSCCY*  
*MAXTXNAMT*  
*MAXAUTHAMT*  
*BRNSALLOW*  
*PRDSALLOW*  
*PRDSACCESALLOW*  
*TAX\_IDENTIFIER*  
*AMOUNT\_FORMAT*  
*DATE\_FORMAT*  
*STAFFACCRESTR*  
*DEPT\_CODE*  
*DEPT\_DESC*  
*USRML*  
*ELCMUSER*  
*GROUP\_CODE*  
*MULTIBRN\_ACCESS*  
*OTH\_RM\_CUST\_ACC\_ALLOW*  
*SUPERVISOR\_ID*  
*SUPERVISOR\_NAME*  
*DASHBOARD\_REQD*  
*ALERTS\_ON\_HOME*  
*REFERENCE\_NO*  
*NO\_CUMULATIVE\_LOGINS*  
*NO\_SUCESSIVE\_LOGINS*  
*SCREENSAVERTIMEOUTINSECONDS*  
*NUMBER\_FORMAT\_MASK*  
*FRONTEND\_DEBUG\_ENABLED*  
*F10\_REQD*  
*F11\_REQD*

*F12\_REQD*  
*MFI\_USER*  
*MFAENABLED*  
*MFAID*  
*ACCESS\_CONTROL*  
*EXTN\_ALERTS*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*RESTR\_PWD*  
*PWD*  
*MSGRIGHTS*  
*GEN*  
*HLD*  
*CNL*  
*TSTINP*  
*CHGNODE*  
*CHGADDR*  
*REL*  
*REINS*  
*CHGMEDIA*  
*CHGPRIOR*  
*BRNMOV*  
*PRNT*  
*TSTCHK*  
*HLDAUTH*  
*CNLAUTH*  
*TSTINPAUTH*

*CHGNODEAUTH*  
*CHGADDRAUTH*  
*RELAUTH*  
*REINSAUTH*  
*CHGMEDIAAUTH*  
*BRNMOVAUTH*  
*CHGPRIORAUTH*  
*FTUPL*  
*LNKCONT*  
*MOVQ*  
*CHGBRNIN*  
*CHGADDRIN*  
*AUTHRGHTS*  
*CHGMSG*  
*CHGMSGAUTH*  
*CHGFORCCOVMATCH*  
*CHANGE\_FORCE\_RELEASE\_FUND*  
*SUPPRESS*  
*DELMSG*  
*QUEUERIGHTS*  
*QUEUE*  
*USERTILLS*  
*TILLID*  
*TILLBRNCD*  
*DESCRIPTION*  
*USERACCCLASS*  
*ACCCLS*  
*USERGLREST*  
*NODEGL*  
*USERGLEXCEPT*  
*EXCEPLEAFGL*  
*USERLIMITSROLE*

*LMTBRN*

*LMTSROLE*

*QLMTCCY*

*QINPLMT*

*QAUTHLMT*

*USERBRANCHES*

*BRNSBRN*

*BRNNAME*

*USERPRODUCTS*

*PRDPRDCD*

*PRDDESC*

*USERACCESSPRODUCTS*

*PRDACCESSPRDCD*

*PRDDESC*

*USERFUNCDISALLOW*

*FUNCDISALLOWFUNCID*

*USERROLE*

*ROLEBRNCD*

*USRROLEID*

*MASTERROLEDESC*

*USERSFUNCTIONS*

*USERFUNCBRNCD*

*USERFUNCFUNCID*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*USERFUNCCTRL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CONTROL15*

*CONTROL16*

*Grp-Restriction*

*GROUP\_CODE*

*GROUP\_DESC*

*Centralisation*

*USRROLEID*

*ROLDESC*

*Dshmst*

*USRID*

*USRNAME*

*Dshdet*

*FUNCTIONID*

*DESCRIPTION*

*SEQUENCE\_NO*

*DBWHERECLAUSE*

*SHOW\_IN\_DASHBOARD*

*Where-Master*

*COLUMN\_NAME*

*WHERE\_CL*

*CONDITION*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

## **AUTHORIZEUSERMAINT\_FSFS\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	AUTHORIZEUSERMAINT_FSFS_REQ

Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## CORRELID



Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of AuthorizeUserMaint

## USR-Full

<b>Attribute</b>	<b>Description</b>
Name	USR-Full
Datatype	
Description	

## STRTDATE

<b>Attribute</b>	<b>Description</b>
Name	STRTDATE
Datatype	String
Description	

## USRNAME

<b>Attribute</b>	<b>Description</b>	
Name	USRNAME	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## USRPWD

<b>Attribute</b>	<b>Description</b>
Name	USRPWD
Datatype	string
Description	

Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	32

## ENDDT

<b>Attribute</b>	<b>Description</b>	
Name	ENDDT	
Datatype	String	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0

## USRLANG

<b>Attribute</b>	<b>Description</b>	
Name	USRLANG	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	3

## HOMEBRN

<b>Attribute</b>	<b>Description</b>	
Name	HOMEBRN	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	3

## CUSTNO

<b>Attribute</b>	<b>Description</b>	
Name	CUSTNO	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	9

## LDAPUSR

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	LDAPUSR	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	500

## TIMELEVEL

<b>Attribute</b>	<b>Description</b>	
Name	TIMELEVEL	
Datatype	decimal	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	9

## AUTOAUTH

<b>Attribute</b>	<b>Description</b>	
Name	AUTOAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## USRSTAT

<b>Attribute</b>	<b>Description</b>	
Name	USRSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	E,H,D,L

## USRID

<b>Attribute</b>	<b>Description</b>	
Name	USRID	
Datatype	string	

Description					
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>maxLength</td> <td>12</td> </tr> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## EXTUSRREF

Attribute	Description				
Name	EXTUSRREF				
Datatype	string				
Description					
Attribute	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>maxLength</td> <td>20</td> </tr> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

## USRCATEG

Attribute	Description				
Name	USRCATEG				
Datatype	string				
Description					
Attribute	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>enumeration</td> <td>S,B</td> </tr> </table>	Restrictions	Description	enumeration	S,B
Restrictions	Description				
enumeration	S,B				

## TILLALLOW

Attribute	Description				
Name	TILLALLOW				
Datatype	string				
Description					
Attribute	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>enumeration</td> <td>A,D</td> </tr> </table>	Restrictions	Description	enumeration	A,D
Restrictions	Description				
enumeration	A,D				

## ACCCLSALLOW

Attribute	Description
Name	ACCCLSALLOW
Datatype	string
Description	



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## GLALLOW

<b>Attribute</b>	<b>Description</b>	
Name	GLALLOW	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## USRTXNLMT

<b>Attribute</b>	<b>Description</b>	
Name	USRTXNLMT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,R,N

## LMTSCCY

<b>Attribute</b>	<b>Description</b>	
Name	LMTSCCY	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## MAXTXNAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXTXNAMT	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### MAXAUTHAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXAUTHAMT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### BRNSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	BRNSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### PRDSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### PRDSACCESALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSACCESALLOW	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## TAX\_IDENTIFIER

<b>Attribute</b>	<b>Description</b>	
Name	TAX_IDENTIFIER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

## AMOUNT\_FORMAT

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_FORMAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	****.***

## DATE\_FORMAT

<b>Attribute</b>	<b>Description</b>	
Name	DATE_FORMAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	M/d/yyyy

## STAFFACCRESTR

<b>Attribute</b>	<b>Description</b>	
Name	STAFFACCRESTR	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### DEPT\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	DEPT_CODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### DEPT\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	DEPT_DESC	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### USRML

<b>Attribute</b>	<b>Description</b>	
Name	USRML	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ELCMUSER

<b>Attribute</b>	<b>Description</b>	
Name	ELCMUSER	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### GROUP\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_CODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### MULTIBRN\_ACCESS

<b>Attribute</b>	<b>Description</b>	
Name	MULTIBRN_ACCESS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### OTH\_RM\_CUST\_ACC\_ALLOW

<b>Attribute</b>	<b>Description</b>	
Name	OTH_RM_CUST_ACC_ALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### SUPERVISOR\_ID

<b>Attribute</b>	<b>Description</b>	
Name	SUPERVISOR_ID	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	80

## SUPERVISOR\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	SUPERVISOR_NAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## DASHBOARD\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	DASHBOARD_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## ALERTS\_ON\_HOME

<b>Attribute</b>	<b>Description</b>	
Name	ALERTS_ON_HOME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REFERENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	REFERENCE_NO	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	20
	<b>Description</b>	

### NO\_CUMULATIVE\_LOGINS

<b>Attribute</b>		<b>Description</b>
Name	NO_CUMULATIVE_LOGINS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	<b>Description</b>	

### NO\_SUCCESSIVE\_LOGINS

<b>Attribute</b>		<b>Description</b>
Name	NO_SUCCESSIVE_LOGINS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	<b>Description</b>	

### SCREENSAVERTIMEOUTINSECONDS

<b>Attribute</b>		<b>Description</b>
Name	SCREENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	<b>Description</b>	

### NUMBER\_FORMAT\_MASK

<b>Attribute</b>		<b>Description</b>
Name	NUMBER_FORMAT_MASK	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	M,L

### FRONTEND\_DEBUG\_ENABLED

<b>Attribute</b>	<b>Description</b>	
Name	FRONTEND_DEBUG_ENABLED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F10\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F10_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F11\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F11_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F12\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F12_REQD	
Datatype	string	
Description		



Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MFI\_USER

<b>Attribute</b>	<b>Description</b>	
Name	MFI_USER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MFAENABLED

<b>Attribute</b>	<b>Description</b>	
Name	MFAENABLED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	N,Y,L

## MFAID

<b>Attribute</b>	<b>Description</b>	
Name	MFAID	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

## ACCESS\_CONTROL

<b>Attribute</b>	<b>Description</b>	
Name	ACCESS_CONTROL	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,G,B

## EXTN\_ALERTS

<b>Attribute</b>	<b>Description</b>	
Name	EXTN_ALERTS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## RESTR\_PWD

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_PWD	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PWD

<b>Attribute</b>	<b>Description</b>	
Name	PWD	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MSGSRIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	MSGSRIGHTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## GEN

<b>Attribute</b>	<b>Description</b>	
Name	GEN	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLD

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	HLD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNL

<b>Attribute</b>	<b>Description</b>	
Name	CNL	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINP

<b>Attribute</b>	<b>Description</b>	
Name	TSTINP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODE

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDR

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CHGADDR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REL

<b>Attribute</b>	<b>Description</b>	
Name	REL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINS

<b>Attribute</b>	<b>Description</b>	
Name	REINS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIA

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIA	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIOR

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CHGPRIOR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOV

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOV	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PRNT

<b>Attribute</b>	<b>Description</b>	
Name	PRNT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTCHK

<b>Attribute</b>	<b>Description</b>	
Name	TSTCHK	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLDAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	HLDAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNLAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CNLAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINPAUTH

<b>Attribute</b>	<b>Description</b>	
Name	TSTINPAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODEAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	CHGADDRAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## RELAUTH

<b>Attribute</b>	<b>Description</b>	
Name	RELAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINSAUTH

<b>Attribute</b>	<b>Description</b>	
Name	REINSAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIAAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIAAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOVAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	BRNMOVAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIORAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIORAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## FTUPL

<b>Attribute</b>	<b>Description</b>	
Name	FTUPL	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## LNKCONT

<b>Attribute</b>	<b>Description</b>	
Name	LNKCONT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MOVQ

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	MOVQ	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGBRNIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGBRNIN	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRIN	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## AUTHRGHTS

<b>Attribute</b>	<b>Description</b>	
Name	AUTHRGHTS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSG

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CHGMSG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHGMSGAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSGAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHGFORCCOVMATCH

<b>Attribute</b>	<b>Description</b>	
Name	CHGFORCCOVMATCH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHANGE\_FORCE\_RELEASE\_FUND

<b>Attribute</b>	<b>Description</b>	
Name	CHANGE_FORCE_RELEASE_FUND	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### SUPPRESS

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	SUPPRESS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	enumeration	Y,N
	<b>Description</b>	

## DELMSG

<b>Attribute</b>	<b>Description</b>	
Name	DELMSG	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	enumeration	Y,N
	<b>Description</b>	

## QUEUERIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	QUEUERIGHTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## QUEUE

<b>Attribute</b>	<b>Description</b>	
Name	QUEUE	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	10
	<b>Description</b>	

## USERTILLS

<b>Attribute</b>	<b>Description</b>	
Name	USERTILLS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## TILLID

Attribute	Description				
Name	TILLID				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## TILLBRNCD

Attribute	Description				
Name	TILLBRNCD				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## DESCRIPTION

Attribute	Description				
Name	DESCRIPTION				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

## USERACCCLASS

Attribute	Description						
Name	USERACCCLASS						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## ACCCLS

Attribute	Description				
Name	ACCCLS				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>6</td></tr></tbody></table>	Restrictions	Description	maxLength	6
Restrictions	Description				
maxLength	6				

## USERGLREST

Attribute		Description	
Name	USERGLREST		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
	maxOccurs	unbounded	

## NODEGL

Attribute		Description	
Name	NODEGL		
Datatype	string		
Description			
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	9	

## USERGLEXCEPT

Attribute		Description	
Name	USERGLEXCEPT		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
	maxOccurs	unbounded	

## EXCEPLEAFGL

Attribute		Description	
Name	EXCEPLEAFGL		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	9	

## USERLIMITSROLE

Attribute		Description	
Name	USERLIMITSROLE		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
	maxOccurs	unbounded	

**LMTBRN**

Attribute	Description	
Name	LMTBRN	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

**LMTSROLE**

Attribute	Description	
Name	LMTSROLE	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	15

**QLMTCCY**

Attribute	Description	
Name	QLMTCCY	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

**QINPLMT**

Attribute	Description	
Name	QINPLMT	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

**QAUTHLMT**

Attribute	Description	
Name	QAUTHLMT	



Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	<b>Description</b>	

## USERBRANCHES

<b>Attribute</b>	<b>Description</b>	
Name	USERBRANCHES	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## BRNSBRN

<b>Attribute</b>	<b>Description</b>	
Name	BRNSBRN	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	3
	<b>Description</b>	

## BRNNAME

<b>Attribute</b>	<b>Description</b>	
Name	BRNNAME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	105
	<b>Description</b>	

## USERPRODUCTS

<b>Attribute</b>	<b>Description</b>	
Name	USERPRODUCTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## PRDPRDCD

Attribute	Description	
Name	PRDPRDCD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

## PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## USERACCESSPRODUCTS

Attribute	Description	
Name	USERACCESSPRODUCTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PRDACCESSPRDCD

Attribute	Description	
Name	PRDACCESSPRDCD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

## PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## USERFUNCDISALLOW

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCDISALLOW	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FUNCDISALLOWFUNCID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCDISALLOWFUNCID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## USERROLE

<b>Attribute</b>	<b>Description</b>	
Name	USERROLE	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEBRNCD

<b>Attribute</b>	<b>Description</b>	
Name	ROLEBRNCD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## USRROLEID

<b>Attribute</b>	<b>Description</b>	
Name	USRROLEID	
Datatype	string	
Description		

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## MASTERROLEDESC

<b>Attribute</b>	<b>Description</b>	
Name	MASTERROLEDESC	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	45

## USERSFUNCTIONS

<b>Attribute</b>	<b>Description</b>	
Name	USERSFUNCTIONS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## USERFUNCBRNCD

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCBRNCD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## USERFUNCFUNCID

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCFUNCID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## CONTROL1

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL1	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL2	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL4

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL4	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL6

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL6	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL8

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL8	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### USERFUNCCTRL10

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCCTRL10	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL11

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL11	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL12

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL12	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL13

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL13	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

#### CONTROL14

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL14	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

#### CONTROL15

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL15	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

#### CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

#### Grp-Restriction

<b>Attribute</b>	<b>Description</b>	
Name	Grp-Restriction	
Datatype		
Description		



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## GROUP\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_CODE	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

## GROUP\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_DESC	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

## Centralisation

<b>Attribute</b>	<b>Description</b>	
Name	Centralisation	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## USRROLEID

<b>Attribute</b>	<b>Description</b>	
Name	USRROLEID	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## ROLDESC

<b>Attribute</b>	<b>Description</b>	
Name	ROLDESC	
Datatype	string	

Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

### Dshmst

<b>Attribute</b>	<b>Description</b>	
Name	Dshmst	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

### USRID

<b>Attribute</b>	<b>Description</b>	
Name	USRID	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

### USRNAME

<b>Attribute</b>	<b>Description</b>	
Name	USRNAME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

### Dshdet

<b>Attribute</b>	<b>Description</b>	
Name	Dshdet	
Datatype		
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1000

## SEQUENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	SEQUENCE_NO	
Datatype	decimal	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## DBWHERECLAUSE

<b>Attribute</b>	<b>Description</b>	
Name	DBWHERECLAUSE	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

## SHOW\_IN\_DASHBOARD

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	SHOW_IN_DASHBOARD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## Where-Master

<b>Attribute</b>	<b>Description</b>	
Name	Where-Master	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## COLUMN\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	COLUMN_NAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	2000

## WHERE\_CL

<b>Attribute</b>	<b>Description</b>	
Name	WHERE_CL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	500

## CONDITION

<b>Attribute</b>	<b>Description</b>	
Name	CONDITION	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
Restrictions	<b>Restrictions</b>	<b>Description</b>
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
Restrictions	<b>Restrictions</b>	<b>Description</b>
	minLength	0

### 2.3.2.SM-AuthorizeUserMaint-Req-IO-MSG.xsd

*AUTHORIZEUSERMAINT\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
     *PARAM*  
         *NAME*  
         *VALUE*  
*FCUBS\_BODY*  
*USR-IO*  
     *USRID*  
     *CHECKER*  
     *CHECKERSTAMP*  
     *MODNO*

#### **AUTHORIZEUSERMAINT\_IOPK\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	AUTHORIZEUSERMAINT_IOPK_REQ
Datatype	
Description	

#### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

#### **SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	string	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of AuthorizeUserMaint

## USR-IO

Attribute	Description
Name	USR-IO
Datatype	
Description	

## USRID

Attribute	Description				
Name	USRID				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## CHECKER

Attribute	Description				
Name	CHECKER				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## CHECKERSTAMP

Attribute	Description				
Name	CHECKERSTAMP				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

### 2.3.3.SM-AuthorizeUserMaint-Res-Full-MSG.xsd

*AUTHORIZEUSERMAINT\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*USR-Full*  
*STRTDATE*  
*USRNAME*  
*USRPWD*  
*ENDDT*  
*USRLANG*  
*HOMEBRN*  
*CUSTNO*  
*LDAPUSR*  
*TIMELEVEL*  
*AUTOAUTH*  
*USRSTAT*  
*USRID*  
*EXTUSRREF*  
*USRCATEG*  
*TILLALLOW*  
*ACCCLSALLOW*  
*GLALLOW*  
*USRTXNLMT*  
*LMTSCCY*  
*MAXTXNAMT*  
*MAXAUTHAMT*  
*BRNSALLOW*  
*PRDSALLOW*  
*PRDSACCESALLOW*  
*TAX\_IDENTIFIER*  
*AMOUNT\_FORMAT*  
*DATE\_FORMAT*  
*STAFFACCRESTR*

*DEPT\_CODE*  
*DEPT\_DESC*  
*USRML*  
*ELCMUSER*  
*GROUP\_CODE*  
*MULTIBRN\_ACCESS*  
*OTH\_RM\_CUST\_ACC\_ALLOW*  
*SUPERVISOR\_ID*  
*SUPERVISOR\_NAME*  
*DASHBOARD\_REQD*  
*ALERTS\_ON\_HOME*  
*REFERENCE\_NO*  
*NO\_CUMULATIVE\_LOGINS*  
*NO\_SUCESSIVE\_LOGINS*  
*SCREENSAVERTIMEOUTINSECONDS*  
*NUMBER\_FORMAT\_MASK*  
*FRONTEND\_DEBUG\_ENABLED*  
*F10\_REQD*  
*F11\_REQD*  
*F12\_REQD*  
*MFI\_USER*  
*MFAENABLED*  
*MFAID*  
*ACCESS\_CONTROL*  
*EXTN\_ALERTS*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*

*RESTR\_PWD*  
*PWD*  
*MSGSRIGHTS*  
*GEN*  
*HLD*  
*CNL*  
*TSTINP*  
*CHGNODE*  
*CHGADDR*  
*REL*  
*REINS*  
*CHGMEDIA*  
*CHGPRIOR*  
*BRNMOV*  
*PRNT*  
*TSTCHK*  
*HLDAUTH*  
*CNLAUTH*  
*TSTINPAUTH*  
*CHGNODEAUTH*  
*CHGADDRAUTH*  
*RELAUTH*  
*REINSAUTH*  
*CHGMEDIAAUTH*  
*BRNMOVAUTH*  
*CHGPRIORAUTH*  
*FTUPL*  
*LNKCONT*  
*MOVQ*  
*CHGBRNIN*  
*CHGADDRIN*  
*AUTHRGHTS*



*CHGMSG*  
*CHGMSGAUTH*  
*CHGFORCCOVMATCH*  
*CHANGE\_FORCE\_RELEASE\_FUND*  
*SUPPRESS*  
*DELMSG*  
*QUEUERIGHTS*  
*QUEUE*  
*USERTILLS*  
*TILLID*  
*TILLBRNCD*  
*DESCRIPTION*  
*USERACCCLASS*  
*ACCCLS*  
*USERGLREST*  
*NODEGL*  
*USERGLEXCEPT*  
*EXCEPLEAFGL*  
*USERLIMITSROLE*  
*LMTBRN*  
*LMTSROLE*  
*QLMTCCY*  
*QINPLMT*  
*QAUTHLMT*  
*USERBRANCHES*  
*BRNSBRN*  
*BRNNAME*  
*USERPRODUCTS*  
*PRDPRDCD*  
*PRDDESC*  
*USERACCESSPRODUCTS*  
*PRDACCESSPRDCD*

*PRDESC*

*USERFUNCDISALLOW*

*FUNCDISALLOWFUNCID*

*USERROLE*

*ROLEBRNCD*

*USRROLEID*

*MASTERROLEDESC*

*USERSFUNCTIONS*

*USERFUNCBRNCD*

*USERFUNCFUNCID*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*USERFUNCCTRL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CONTROL15*

*CONTROL16*

*Grp-Restriction*

*GROUP\_CODE*

*GROUP\_DESC*

*Centralisation*

*USRROLEID*

*ROLDESC*

*Dshmst*

*USRID*

*USRNAME*

*Dshdet*

*FUNCTIONID*

*DESCRIPTION*

*SEQUENCE\_NO*

*DBWHERECLAUSE*

*SHOW\_IN\_DASHBOARD*

*Where-Master*

*COLUMN\_NAME*

*WHERE\_CL*

*CONDITION*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## **AUTHORIZEUSERMAINT\_FSFS\_RES**

<b>Attribute</b>	<b>Description</b>
Name	AUTHORIZEUSERMAINT_FSFS_RES
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	string	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		



## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

## USR-Full

Attribute	Description
Name	USR-Full
Datatype	
Description	

## STRDATE

Attribute	Description
Name	STRDATE
Datatype	String
Description	

## USRNAME

Attribute	Description				
Name	USRNAME				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

## USRPWD

Attribute	Description				
Name	USRPWD				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>32</td></tr></tbody></table>	Restrictions	Description	maxLength	32
Restrictions	Description				
maxLength	32				

## ENDDT

Attribute	Description
Name	ENDDT
Datatype	String

Description					
Attribute					
	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## USRLANG

Attribute	Description				
Name	USRLANG				
Datatype	string				
Description					
Restrictions					
	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>maxLength</td> <td>3</td> </tr> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## HOMEBRN

Attribute	Description				
Name	HOMEBRN				
Datatype	string				
Description					
Restrictions					
	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>maxLength</td> <td>3</td> </tr> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## CUSTNO

Attribute	Description				
Name	CUSTNO				
Datatype	string				
Description					
Attribute					
	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>maxLength</td> <td>9</td> </tr> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

## LDAPUSR

Attribute	Description				
Name	LDAPUSR				
Datatype	string				
Description					
Attribute					
	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>maxLength</td> <td>500</td> </tr> </table>	Restrictions	Description	maxLength	500
Restrictions	Description				
maxLength	500				

## TIMELEVEL

Attribute	Description
-----------	-------------

Name	TIMELEVEL	
Datatype	decimal	
Description		
Restrictions	<b>Restrictions</b>	
		<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	9

## AUTOAUTH

<b>Attribute</b>		<b>Description</b>
Name	AUTOAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
		<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
		<b>Description</b>
	enumeration	Y,N

## USRSTAT

<b>Attribute</b>		<b>Description</b>
Name	USRSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
		<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
		<b>Description</b>
	enumeration	E,H,D,L

## USRID

<b>Attribute</b>		<b>Description</b>
Name	USRID	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
		<b>Description</b>
	maxLength	12

## EXTUSRREF

<b>Attribute</b>		<b>Description</b>
Name	EXTUSRREF	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## USRCATEG

<b>Attribute</b>	<b>Description</b>	
Name	USRCATEG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	S,B

## TILLALLOW

<b>Attribute</b>	<b>Description</b>	
Name	TILLALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## ACCCLSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## GLALLOW

<b>Attribute</b>	<b>Description</b>	
Name	GLALLOW	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### USRTXNLMT

<b>Attribute</b>	<b>Description</b>	
Name	USRTXNLMT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,R,N

### LMTSCCY

<b>Attribute</b>	<b>Description</b>	
Name	LMTSCCY	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### MAXTXNAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXTXNAMT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### MAXAUTHAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXAUTHAMT	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### BRNSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	BRNSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### PRDSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### PRDSACCESALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSACCESALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### TAX\_IDENTIFIER

<b>Attribute</b>	<b>Description</b>	
Name	TAX_IDENTIFIER	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

## AMOUNT\_FORMAT

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_FORMAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	*****

## DATE\_FORMAT

<b>Attribute</b>	<b>Description</b>	
Name	DATE_FORMAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	M/d/yyyy

## STAFFACCRESTR

<b>Attribute</b>	<b>Description</b>	
Name	STAFFACCRESTR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DEPT\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	DEPT_CODE	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## DEPT\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	DEPT_DESC	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## USRML

<b>Attribute</b>	<b>Description</b>	
Name	USRML	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## ELCMUSER

<b>Attribute</b>	<b>Description</b>	
Name	ELCMUSER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## GROUP\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_CODE	
Datatype	string	
Description		



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### MULTIBRN\_ACCESS

<b>Attribute</b>	<b>Description</b>	
Name	MULTIBRN_ACCESS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### OTH\_RM\_CUST\_ACC\_ALLOW

<b>Attribute</b>	<b>Description</b>	
Name	OTH_RM_CUST_ACC_ALLOW	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### SUPERVISOR\_ID

<b>Attribute</b>	<b>Description</b>	
Name	SUPERVISOR_ID	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	80

### SUPERVISOR\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	SUPERVISOR_NAME	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## DASHBOARD\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	DASHBOARD_REQD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## ALERTS\_ON\_HOME

<b>Attribute</b>	<b>Description</b>	
Name	ALERTS_ON_HOME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REFERENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	REFERENCE_NO	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## NO\_CUMULATIVE\_LOGINS

<b>Attribute</b>	<b>Description</b>	
Name	NO_CUMULATIVE_LOGINS	
Datatype	decimal	
Description		

Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	<b>Description</b>	

### NO\_SUCESSIVE\_LOGINS

<b>Attribute</b>		<b>Description</b>
Name	NO_SUCESSIVE_LOGINS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	<b>Description</b>	

### SCREENSAVERTIMEOUTINSECONDS

<b>Attribute</b>		<b>Description</b>
Name	SCREENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	<b>Description</b>	

### NUMBER\_FORMAT\_MASK

<b>Attribute</b>		<b>Description</b>
Name	NUMBER_FORMAT_MASK	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	enumeration	M,L
	<b>Description</b>	

### FRONTEND\_DEBUG\_ENABLED

<b>Attribute</b>		<b>Description</b>
Name	FRONTEND_DEBUG_ENABLED	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F10\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F10_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F11\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F11_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F12\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F12_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### MFI\_USER

<b>Attribute</b>	<b>Description</b>	
Name	MFI_USER	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MFAENABLED

<b>Attribute</b>	<b>Description</b>	
Name	MFAENABLED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	N,Y,L

## MFAID

<b>Attribute</b>	<b>Description</b>	
Name	MFAID	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

## ACCESS\_CONTROL

<b>Attribute</b>	<b>Description</b>	
Name	ACCESS_CONTROL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,G,B

## EXTN\_ALERTS

<b>Attribute</b>	<b>Description</b>	
Name	EXTN_ALERTS	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## RESTR\_PWD

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_PWD	
Datatype		
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PWD

<b>Attribute</b>	<b>Description</b>	
Name	PWD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MSGSRIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	MSGSRIGHTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## GEN

<b>Attribute</b>	<b>Description</b>	
Name	GEN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLD

<b>Attribute</b>	<b>Description</b>	
Name	HLD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNL

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	CNL	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINP

<b>Attribute</b>	<b>Description</b>	
Name	TSTINP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODE

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDR

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDR	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REL

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	REL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINS

<b>Attribute</b>	<b>Description</b>	
Name	REINS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIA

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIA	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIOR

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIOR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOV

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	BRNMOV	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PRNT

<b>Attribute</b>	<b>Description</b>	
Name	PRNT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTCHK

<b>Attribute</b>	<b>Description</b>	
Name	TSTCHK	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLDAUTH

<b>Attribute</b>	<b>Description</b>	
Name	HLDAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNLAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CNLAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINPAUTH

<b>Attribute</b>	<b>Description</b>	
Name	TSTINPAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODEAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## RELAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	RELAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINSAUTH

<b>Attribute</b>	<b>Description</b>	
Name	REINSAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIAAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIAAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOVAUTH

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOVAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIORAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CHGPRIORAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## FTUPL

<b>Attribute</b>	<b>Description</b>	
Name	FTUPL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## LNKCONT

<b>Attribute</b>	<b>Description</b>	
Name	LNKCONT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MOVQ

<b>Attribute</b>	<b>Description</b>	
Name	MOVQ	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGBRNIN

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CHGBRNIN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRIN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## AUTHRGHTS

<b>Attribute</b>	<b>Description</b>	
Name	AUTHRGHTS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSG

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSGAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CHGMSGAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHGFORCCOVMATCH

<b>Attribute</b>	<b>Description</b>	
Name	CHGFORCCOVMATCH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHANGE\_FORCE\_RELEASE\_FUND

<b>Attribute</b>	<b>Description</b>	
Name	CHANGE_FORCE_RELEASE_FUND	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### SUPPRESS

<b>Attribute</b>	<b>Description</b>	
Name	SUPPRESS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### DELMSG

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	DELMSG	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	enumeration	Y,N
	<b>Description</b>	

## QUEUERIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	QUEUERIGHTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## QUEUE

<b>Attribute</b>	<b>Description</b>	
Name	QUEUE	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	10
	<b>Description</b>	

## USERTILLS

<b>Attribute</b>	<b>Description</b>	
Name	USERTILLS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## TILLID

<b>Attribute</b>	<b>Description</b>	
Name	TILLID	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	12
	<b>Description</b>	

## TILLBRNCD

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	TILLBRNCD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

## USERACCCLASS

<b>Attribute</b>	<b>Description</b>	
Name	USERACCCLASS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ACCCLS

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLS	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

## USERGLREST

<b>Attribute</b>	<b>Description</b>	
Name	USERGLREST	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NODEGL

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	NODEGL	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## USERGLEXCEPT

<b>Attribute</b>	<b>Description</b>	
Name	USERGLEXCEPT	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## EXCEPLEAFGL

<b>Attribute</b>	<b>Description</b>	
Name	EXCEPLEAFGL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## USERLIMITSROLE

<b>Attribute</b>	<b>Description</b>	
Name	USERLIMITSROLE	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## LMTBRN

<b>Attribute</b>	<b>Description</b>	
Name	LMTBRN	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## LMTSROLE

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	LMTSROLE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

### QLMTCCY

<b>Attribute</b>	<b>Description</b>	
Name	QLMTCCY	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### QINPLMT

<b>Attribute</b>	<b>Description</b>	
Name	QINPLMT	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### QAUHLMT

<b>Attribute</b>	<b>Description</b>	
Name	QAUHLMT	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### USERBRANCHES

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	USERBRANCHES	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	maxOccurs	unbounded

## BRNSBRN

<b>Attribute</b>	<b>Description</b>	
Name	BRNSBRN	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	3

## BRNNAME

<b>Attribute</b>	<b>Description</b>	
Name	BRNNAME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	105

## USERPRODUCTS

<b>Attribute</b>	<b>Description</b>	
Name	USERPRODUCTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	maxOccurs	unbounded

## PRDPRDCD

<b>Attribute</b>	<b>Description</b>	
Name	PRDPRDCD	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	4

## PRDDESC

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	PRDESC	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	105
	<b>Description</b>	

## USERACCESSPRODUCTS

<b>Attribute</b>	<b>Description</b>	
Name	USERACCESSPRODUCTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## PRDACCESSPRDCD

<b>Attribute</b>	<b>Description</b>	
Name	PRDACCESSPRDCD	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	4
	<b>Description</b>	

## PRDESC

<b>Attribute</b>	<b>Description</b>	
Name	PRDESC	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	105
	<b>Description</b>	

## USERFUNCDISALLOW

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCDISALLOW	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## FUNCDISALLOWFUNCID

Attribute	Description				
Name	FUNCDISALLOWFUNCID				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr></tbody></table>	Restrictions	Description	maxLength	8
Restrictions	Description				
maxLength	8				

## USERROLE

Attribute	Description						
Name	USERROLE						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## ROLEBRNCD

Attribute	Description				
Name	ROLEBRNCD				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## USRROLEID

Attribute	Description				
Name	USRROLEID				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## MASTERROLEDESC

Attribute	Description				
Name	MASTERROLEDESC				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>45</td></tr></tbody></table>	Restrictions	Description	maxLength	45
Restrictions	Description				
maxLength	45				

## USERSFUNCTIONS

Attribute	Description	
Name	USERSFUNCTIONS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## USERFUNCBRNCD

Attribute	Description	
Name	USERFUNCBRNCD	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

## USERFUNCFUNCID

Attribute	Description	
Name	USERFUNCFUNCID	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	8

## CONTROL1

Attribute	Description	
Name	CONTROL1	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

## CONTROL2

Attribute	Description	
Name	CONTROL2	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL4

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL4	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL6

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL6	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL8

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL8	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### USERFUNCCTRL10

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCCTRL10	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL11

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL11	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL12

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL12	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL13

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL13	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL14

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL14	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL15

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL15	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### Grp-Restriction

<b>Attribute</b>	<b>Description</b>	
Name	Grp-Restriction	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### GROUP\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_CODE	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

### GROUP\_DESC

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	GROUP_DESC	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	255
	<b>Description</b>	

## Centralisation

<b>Attribute</b>	<b>Description</b>	
Name	Centralisation	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## USRROLEID

<b>Attribute</b>	<b>Description</b>	
Name	USRROLEID	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	15
	<b>Description</b>	

## ROLDESC

<b>Attribute</b>	<b>Description</b>	
Name	ROLDESC	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	20
	<b>Description</b>	

## Dshmst

<b>Attribute</b>	<b>Description</b>	
Name	Dshmst	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	

## USRID

Attribute	Description	
Name	USRID	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	15

## USRNAME

Attribute	Description	
Name	USRNAME	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

## Dshdet

Attribute	Description	
Name	Dshdet	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	15

## DESCRIPTION

Attribute	Description
-----------	-------------

Name	DESCRIPTION	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1000

## SEQUENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	SEQUENCE_NO	
Datatype	decimal	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## DBWHERECLAUSE

<b>Attribute</b>	<b>Description</b>	
Name	DBWHERECLAUSE	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

## SHOW\_IN\_DASHBOARD

<b>Attribute</b>	<b>Description</b>	
Name	SHOW_IN_DASHBOARD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## Where-Master

<b>Attribute</b>	<b>Description</b>	
Name	Where-Master	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## COLUMN\_NAME

Attribute		Description	
Name	COLUMN_NAME		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	2000	

## WHERE\_CL

Attribute		Description	
Name	WHERE_CL		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	500	

## CONDITION

Attribute		Description	
Name	CONDITION		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	30	

## UDFDETAILS

Attribute		Description	
Name	UDFDETAILS		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
	maxOccurs	unbounded	

## FLDNAM

Attribute		Description	
Name	FLDNAM		



Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

### 2.3.4.SM-AuthorizeUserMaint-Res-PK-MSG.xsd

*AUTHORIZEUSERMAINT\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*USR-PK*  
*USRID*  
*USR-IO*  
*USRID*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*  
*WCODE*  
*WDESC*

**AUTHORIZEUSERMAINT\_IOPK\_RES**

<b>Attribute</b>	<b>Description</b>
Name	AUTHORIZEUSERMAINT_IOPK_RES
Datatype	
Description	

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		



## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

## USR-PK

Attribute	Description
Name	USR-PK
Datatype	
Description	

## USRID

Attribute	Description				
Name	USRID				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## USR-IO

Attribute	Description
Name	USR-IO
Datatype	
Description	

## USRID

Attribute	Description				
Name	USRID				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## CHECKER

Attribute	Description
Name	CHECKER
Datatype	string
Description	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

## WDESC

<b>Attribute</b>	<b>Description</b>
Name	WDESC
Datatype	String
Description	

## 2.4.CloseSMDBANKP

### 2.4.1.SM-CloseSMDBANKP-Req-Full-MSG.xsd

[CLOSESMDBANKP\\_FSFS\\_REQ](#)

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Parameters-Full*

*HEAD\_OFFICE*

*SITE\_CODE*

*ACTIVATION\_KEY*

*INVALID\_LOGINS\_CUM*

*INVALID\_LOGINS\_SUC*

*PWD\_PREVENT\_REUSE*

*PWD\_CHANGE\_AFTER*

*MAXIMUM*

*MINIMUM*

*PWD\_EXPIRY\_MSG\_DAYS*

*ARCHIVAL\_PERIOD*

*CONCHAR\_PWD\_NUM*

*FREQ\_PWD\_CHG*

*MIN\_PWD\_NUMERIC\_LENGTH*

*LEGAL\_NOTICE*

*DORMANCY\_DAYS*

*DISPLAY\_LEGAL\_NOTICE*

*MIN\_SPECIALCHAR\_LENGTH*

*MIN\_LOWERCASE\_CHAR*

*MIN\_UPPERCASE\_CHAR*

*SCREENSAVERREQUIRED*

*SCREENSAVERTIMEOUTINSECONDS*

*SCREENSAVERMODIFIABLEBYUSER*

*PASSWORDEXTERNAL*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Smtbs-Branch-Restr*

*RESTR\_TYPE*

*DESCRIPTION*

*Smtbs-Restrictive-Passwd*

*PASSWORD*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

Attribute	Description
Name	CLOSESMDBANKP_FSFS_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	string				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## USERID

Attribute	Description						
Name	USERID						
Datatype	string						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

Attribute	Description
Name	MODULEID
Datatype	string
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of CloseSMDBANKP

## Smtbs-Parameters-Full

<b>Attribute</b>	<b>Description</b>
Name	Smtbs-Parameters-Full
Datatype	
Description	

## HEAD\_OFFICE

<b>Attribute</b>	<b>Description</b>	
Name	HEAD_OFFICE	
Datatype	string	
Description	Indicates Head Office	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## SITE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	SITE_CODE	
Datatype	string	
Description	Indicates Site Code	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

## ACTIVATION\_KEY

Attribute	Description				
Name	ACTIVATION_KEY				
Datatype	string				
Description	Indicates Activation Key				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>24</td></tr></tbody></table>	Restrictions	Description	maxLength	24
Restrictions	Description				
maxLength	24				

## INVALID\_LOGINS\_CUM

Attribute	Description								
Name	INVALID_LOGINS_CUM								
Datatype	decimal								
Description	Indicates Cumulative								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>6</td></tr><tr><td>maxInclusive</td><td>99</td></tr></tbody></table>	Restrictions	Description	totalDigits	2	minInclusive	6	maxInclusive	99
Restrictions	Description								
totalDigits	2								
minInclusive	6								
maxInclusive	99								

## INVALID\_LOGINS\_SUC

Attribute	Description								
Name	INVALID_LOGINS_SUC								
Datatype	decimal								
Description	Indicates Successive								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>1</td></tr><tr><td>minInclusive</td><td>3</td></tr><tr><td>maxInclusive</td><td>5</td></tr></tbody></table>	Restrictions	Description	totalDigits	1	minInclusive	3	maxInclusive	5
Restrictions	Description								
totalDigits	1								
minInclusive	3								
maxInclusive	5								

## PWD\_PREVENT\_REUSE

Attribute	Description				
Name	PWD_PREVENT_REUSE				
Datatype	decimal				
Description	Indicates Password Repetitions				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## PWD\_CHANGE\_AFTER

<b>Attribute</b>	<b>Description</b>	
Name	PWD_CHANGE_AFTER	
Datatype	decimal	
Description	Indicates Force Password Change After	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	3
	minInclusive	15
	maxInclusive	180

## MAXIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MAXIMUM	
Datatype	decimal	
Description	Indicates Maximum	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	12
	maxInclusive	30

## MINIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MINIMUM	
Datatype	decimal	
Description	Indicates Minimum	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	6
	maxInclusive	11

## PWD\_EXPIRY\_MSG\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	PWD_EXPIRY_MSG_DAYS	
Datatype	decimal	
Description	Indicates Intimate User (Before Password Expiry)	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	2
	minInclusive	1
	maxInclusive	5

## ARCHIVAL\_PERIOD

<b>Attribute</b>	<b>Description</b>	
Name	ARCHIVAL_PERIOD	
Datatype	decimal	
Description	Indicates Archival Period (in days)	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	3

## CONCHAR\_PWD\_NUM

<b>Attribute</b>	<b>Description</b>	
Name	CONCHAR_PWD_NUM	
Datatype	decimal	
Description	Indicates Maximum Consecutive Repetitive Characters	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	2

## FREQ\_PWD\_CHG

<b>Attribute</b>	<b>Description</b>	
Name	FREQ_PWD_CHG	
Datatype	decimal	
Description	Indicates Minimum Days Between Password Changes	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	2
	minInclusive	0

## MIN\_PWD\_NUMERIC\_LENGTH

<b>Attribute</b>	<b>Description</b>	
Name	MIN_PWD_NUMERIC_LENGTH	
Datatype	decimal	

Description	Indicates Minimum Number Of Numeric Characters In Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## LEGAL\_NOTICE

<b>Attribute</b>	<b>Description</b>	
Name	LEGAL_NOTICE	
Datatype	string	
Description	Indicates Warning Screen Text	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

## DORMANCY\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	DORMANCY_DAYS	
Datatype	decimal	
Description	Indicates Dormancy Days	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## DISPLAY\_LEGAL\_NOTICE

<b>Attribute</b>	<b>Description</b>	
Name	DISPLAY_LEGAL_NOTICE	
Datatype	string	
Description	Indicates Display Legal Notice Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MIN\_SPECIALCHAR\_LENGTH

<b>Attribute</b>	<b>Description</b>	
Name	MIN_SPECIALCHAR_LENGTH	
Datatype	decimal	
Description	Indicates Minimum Number Of Special Characters In Password	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### MIN\_LOWERCASE\_CHAR

<b>Attribute</b>	<b>Description</b>	
Name	MIN_LOWERCASE_CHAR	
Datatype	decimal	
Description	Indicates Minimum Number of LowerCase Characters in Password	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### MIN\_UPPERCASE\_CHAR

<b>Attribute</b>	<b>Description</b>	
Name	MIN_UPPERCASE_CHAR	
Datatype	decimal	
Description	Indicates Minimum Number of UpperCase Characters in Password	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### SCREENSAVERREQUIRED

<b>Attribute</b>	<b>Description</b>	
Name	SCREENSAVERREQUIRED	
Datatype	string	
Description	Indicates Screensaver Required Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### SCREENSAVERTIMEOUTINSECONDS

<b>Attribute</b>	<b>Description</b>	
Name	SCREENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description	Indicates Screensaver Interval (in seconds)	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## SCREENSAVERMODIFIABLEBYUSER

<b>Attribute</b>	<b>Description</b>	
Name	SCREENSAVERMODIFIABLEBYUSER	
Datatype	string	
Description	Indicates Screensaver Interval Modifiable at User Level Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PASSWORDEXTERNAL

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORDEXTERNAL	
Datatype	string	
Description	Indicates Password External Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## Smtbs-Branch-Restr

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Branch-Restr	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## RESTR\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_TYPE	
Datatype	string	
Description	Indicates Restriction Type	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Restriction Type Description	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

### Smtbs-Restrictive-Passwd

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Restrictive-Passwd	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description	Indicates Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

### FLDVAL

<b>Attribute</b>	<b>Description</b>
Name	FLDVAL

Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

#### 2.4.2.SM-CloseSMDBANKP-Req-IO-MSG.xsd

##### *CLOSESMDBANKP\_IOPK\_REQ*

###### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

###### *FCUBS\_BODY*

*Smtbs-Parameters-IO*

*SITE\_CODE*

*MAKER*

*MAKERSTAMP*

*MODNO*

## CLOSESMDBANKP\_IOPK\_REQ

Attribute	Description
Name	CLOSESMDBANKP_IOPK_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field. 234

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	string				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	string
Description	This is the user id in the Source system who is performing the action.



Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

## FCUBS\_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about IO Request of CloseSMDBANKP	

## Smtbs-Parameters-IO

Attribute	Description	
Name	Smtbs-Parameters-IO	
Datatype		
Description		

## SITE\_CODE

Attribute	Description	
Name	SITE_CODE	
Datatype	string	
Description	Indicates Site Code	
Restrictions	Restrictions	Description
	maxLength	4

## MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

### 2.4.3.SM-CloseSMDBANKP-Res-Full-MSG.xsd

*CLOSESMDBANKP\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Smtbs-Parameters-Full*  
*HEAD\_OFFICE*  
*SITE\_CODE*  
*ACTIVATION\_KEY*  
*INVALID\_LOGINS\_CUM*  
*INVALID\_LOGINS\_SUC*  
*PWD\_PREVENT\_REUSE*  
*PWD\_CHANGE\_AFTER*  
*MAXIMUM*  
*MINIMUM*  
*PWD\_EXPIRY\_MSG\_DAYS*  
*ARCHIVAL\_PERIOD*  
*CONCHAR\_PWD\_NUM*  
*FREQ\_PWD\_CHG*  
*MIN\_PWD\_NUMERIC\_LENGTH*  
*LEGAL\_NOTICE*  
*DORMANCY\_DAYS*  
*DISPLAY\_LEGAL\_NOTICE*  
*MIN\_SPECIALCHAR\_LENGTH*

*MIN\_LOWERCASE\_CHAR*  
*MIN\_UPPERCASE\_CHAR*  
*SCREENSAVERREQUIRED*  
*SCREENSAVERTIMEOUTINSECONDS*  
*SCREENSAVERMODIFIABLEBYUSER*  
*PASSWORDEXTERNAL*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*Smtbs-Branch-Restr*  
     *RESTR\_TYPE*  
     *DESCRIPTION*  
*Smtbs-Restrictive-Passwd*  
     *PASSWORD*  
*UDFDETAILS*  
     *FLDNAM*  
     *FLDVAL*  
*FCUBS\_ERROR\_RESP*  
     *ERROR*  
     *ECODE*  
     *EDESC*  
*FCUBS\_WARNING\_RESP*  
     *WARNING*  
     *WCODE*  
     *WDESC*

**CLOSESMDBANKP\_FSFS\_RES**

<b>Attribute</b>	<b>Description</b>
Name	CLOSESMDBANKP_FSFS_RES

Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

## Smtbs-Parameters-Full

<b>Attribute</b>	<b>Description</b>
Name	Smtbs-Parameters-Full
Datatype	
Description	

## HEAD\_OFFICE

<b>Attribute</b>	<b>Description</b>	
Name	HEAD_OFFICE	
Datatype	string	
Description	Indicates Head Office	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## SITE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	SITE_CODE	
Datatype	string	
Description	Indicates Site Code	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

## ACTIVATION\_KEY

Attribute	Description				
Name	ACTIVATION_KEY				
Datatype	string				
Description	Indicates Activation Key				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>24</td></tr></tbody></table>	Restrictions	Description	maxLength	24
Restrictions	Description				
maxLength	24				

## INVALID\_LOGINS\_CUM

Attribute	Description								
Name	INVALID_LOGINS_CUM								
Datatype	decimal								
Description	Indicates Cumulative								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>6</td></tr><tr><td>maxInclusive</td><td>99</td></tr></tbody></table>	Restrictions	Description	totalDigits	2	minInclusive	6	maxInclusive	99
Restrictions	Description								
totalDigits	2								
minInclusive	6								
maxInclusive	99								

## INVALID\_LOGINS\_SUC

Attribute	Description								
Name	INVALID_LOGINS_SUC								
Datatype	decimal								
Description	Indicates Successive								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>1</td></tr><tr><td>minInclusive</td><td>3</td></tr><tr><td>maxInclusive</td><td>5</td></tr></tbody></table>	Restrictions	Description	totalDigits	1	minInclusive	3	maxInclusive	5
Restrictions	Description								
totalDigits	1								
minInclusive	3								
maxInclusive	5								

## PWD\_PREVENT\_REUSE

Attribute	Description				
Name	PWD_PREVENT_REUSE				
Datatype	decimal				
Description	Indicates Password Repetitions				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## PWD\_CHANGE\_AFTER

<b>Attribute</b>	<b>Description</b>	
Name	PWD_CHANGE_AFTER	
Datatype	decimal	
Description	Indicates Force Password Change After	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	3
	minInclusive	15
	maxInclusive	180

## MAXIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MAXIMUM	
Datatype	decimal	
Description	Indicates Maximum	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	12
	maxInclusive	30

## MINIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MINIMUM	
Datatype	decimal	
Description	Indicates Minimum	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	6
	maxInclusive	11

## PWD\_EXPIRY\_MSG\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	PWD_EXPIRY_MSG_DAYS	
Datatype	decimal	
Description	Indicates Intimate User (Before Password Expiry)	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	2
	minInclusive	1
	maxInclusive	5

## ARCHIVAL\_PERIOD

<b>Attribute</b>	<b>Description</b>	
Name	ARCHIVAL_PERIOD	
Datatype	decimal	
Description	Indicates Archival Period (in days)	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	3

## CONCHAR\_PWD\_NUM

<b>Attribute</b>	<b>Description</b>	
Name	CONCHAR_PWD_NUM	
Datatype	decimal	
Description	Indicates Maximum Consecutive Repetitive Characters	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	2

## FREQ\_PWD\_CHG

<b>Attribute</b>	<b>Description</b>	
Name	FREQ_PWD_CHG	
Datatype	decimal	
Description	Indicates Minimum Days Between Password Changes	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	2
	minInclusive	0

## MIN\_PWD\_NUMERIC\_LENGTH

<b>Attribute</b>	<b>Description</b>	
Name	MIN_PWD_NUMERIC_LENGTH	
Datatype	decimal	

Description	Indicates Minimum Number Of Numeric Characters In Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## LEGAL\_NOTICE

<b>Attribute</b>	<b>Description</b>	
Name	LEGAL_NOTICE	
Datatype	string	
Description	Indicates Warning Screen Text	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
Restrictions	maxLength	4000

## DORMANCY\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	DORMANCY_DAYS	
Datatype	decimal	
Description	Indicates Dormancy Days	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
Restrictions	totalDigits	2
	minInclusive	1

## DISPLAY\_LEGAL\_NOTICE

<b>Attribute</b>	<b>Description</b>	
Name	DISPLAY_LEGAL_NOTICE	
Datatype	string	
Description	Indicates Display Legal Notice Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
Restrictions	enumeration	Y,N

## MIN\_SPECIALCHAR\_LENGTH

<b>Attribute</b>	<b>Description</b>	
Name	MIN_SPECIALCHAR_LENGTH	
Datatype	decimal	
Description	Indicates Minimum Number Of Special Characters In Password	



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### MIN\_LOWERCASE\_CHAR

<b>Attribute</b>	<b>Description</b>	
Name	MIN_LOWERCASE_CHAR	
Datatype	decimal	
Description	Indicates Minimum Number of LowerCase Characters in Password	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### MIN\_UPPERCASE\_CHAR

<b>Attribute</b>	<b>Description</b>	
Name	MIN_UPPERCASE_CHAR	
Datatype	decimal	
Description	Indicates Minimum Number of UpperCase Characters in Password	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### SCREENSAVERREQUIRED

<b>Attribute</b>	<b>Description</b>	
Name	SCREENSAVERREQUIRED	
Datatype	string	
Description	Indicates Screensaver Required Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### SCREENSAVERTIMEOUTINSECONDS

<b>Attribute</b>	<b>Description</b>	
Name	SCREENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description	Indicates Screensaver Interval (in seconds)	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## SCREENSAVERMODIFIABLEBYUSER

<b>Attribute</b>	<b>Description</b>	
Name	SCREENSAVERMODIFIABLEBYUSER	
Datatype	string	
Description	Indicates Screensaver Interval Modifiable at User Level Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PASSWORDEXTERNAL

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORDEXTERNAL	
Datatype	string	
Description	Indicates Password External Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## Smtbs-Branch-Restr

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Branch-Restr	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## RESTR\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_TYPE	
Datatype	string	
Description	Indicates Restriction Type	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Restriction Type Description	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

### Smtbs-Restrictive-Passwd

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Restrictive-Passwd	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description	Indicates Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

### FLDVAL

<b>Attribute</b>	<b>Description</b>
Name	FLDVAL

Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	150
	minLength	0
	<b>Description</b>	

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	maxOccurs	unbounded
	<b>Description</b>	

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

### 2.4.4.SM-CloseSMDBANKP-Res-PK-MSG.xsd

*CLOSESMDBANKP\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Parameters-PK*

*SITE\_CODE*

*Smtbs-Parameters-IO*

*SITE\_CODE*

*MAKER*

*MAKERSTAMP*

*MODNO*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## **CLOSESMDBANKP\_IOPK\_RES**

<b>Attribute</b>	<b>Description</b>
Name	CLOSESMDBANKP_IOPK_RES
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

<b>Attribute</b>	<b>Description</b>
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within EL EXCLUDE UBS. In



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

Attribute	Description

Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

### FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

### Smtbs-Parameters-PK

Attribute	Description
Name	Smtbs-Parameters-PK
Datatype	
Description	

### SITE\_CODE

Attribute	Description	
Name	SITE_CODE	
Datatype	string	
Description	Indicates Site Code	
Restrictions		
	Restrictions	Description
	maxLength	4

### Smtbs-Parameters-IO

Attribute	Description
Name	Smtbs-Parameters-IO
Datatype	
Description	

### SITE\_CODE

Attribute	Description	
Name	SITE_CODE	
Datatype	string	
Description	Indicates Site Code	
Restrictions		
	Restrictions	Description
	maxLength	4

### MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

## MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

## 2.5.CloseSMDRLMNE

### 2.5.1.SM-CloseSMDRLMNE-Req-Full-MSG.xsd

*CLOSESMDRLMNE\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*



*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Smtbs-Role-Limit-Full*  
*ROLEID2*  
*DESCRIPTION*  
*LIMIT\_CCY*  
*INPUT\_LIMIT*  
*AUTHORIZATION\_LIMIT*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*UDFDETAILS*  
*FLDNAM*  
*FLDVAL*

## CLOSESMOURLMNE\_FSFS\_REQ

Attribute	Description
Name	CLOSESMOURLMNE_FSFS_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>
Name	MODULEID

Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
	maxOccurs	unbounded	

## NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

## VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

## FCUBS\_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description	This XSD Gives Information about Full Request of CloseSMDRLMNE		

## Smtbs-Role-Limit-Full

Attribute		Description	
Name	Smtbs-Role-Limit-Full		
Datatype			
Description			

## ROLEID2

Attribute		Description	
Name	ROLEID2		
Datatype	string		
Description	Indicates Role Id		
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	15	

## DESCRIPTION

Attribute		Description	
Name	DESCRIPTION		
Datatype	string		
Description	Indicates Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

### LIMIT\_CCY

<b>Attribute</b>	<b>Description</b>	
Name	LIMIT_CCY	
Datatype	string	
Description	Indicates Limit Currency	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### INPUT\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	INPUT_LIMIT	
Datatype	decimal	
Description	Indicates Input Limit	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0

### AUTHORIZATION\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHORIZATION_LIMIT	
Datatype	decimal	
Description	Indicates Authorization Limit	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0

### MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### MAKERSTAMP



Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

## CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	1
	<b>Description</b>	

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	1
	<b>Description</b>	

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	
	maxLength	105
	minLength	1
	<b>Description</b>	

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

2.5.2.SM-CloseSMDRLMNE-Req-IO-MSG.xsd

*CLOSESMDRLMNE\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Role-Limit-IO*

*ROLEID2*

*MAKER*

*MAKERSTAMP*

*MODNO*

## CLOSESMDRLMNE\_IOPK\_REQ

Attribute	Description
Name	CLOSESMDRLMNE_IOPK_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	string				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	string
Description	This is the user id in the Source system who is performing the action.

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM



Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

## FCUBS\_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about IO Request of CloseSMDRLMNE	

## Smtbs-Role-Limit-IO

Attribute	Description	
Name	Smtbs-Role-Limit-IO	
Datatype		
Description		

## ROLEID2

Attribute	Description	
Name	ROLEID2	
Datatype	string	
Description	Indicates Role Id	
Restrictions	Restrictions	Description
	maxLength	15

## MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

### 2.5.3.SM-CloseSMDRLMNE-Res-Full-MSG.xsd

*CLOSESMDRLMNE\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTIRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Smtbs-Role-Limit-Full*  
*ROLEID2*  
*DESCRIPTION*  
*LIMIT\_CCY*  
*INPUT\_LIMIT*  
*AUTHORIZATION\_LIMIT*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*UDFDETAILS*  
*FLDNAM*  
*FLDVAL*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*

EDESC

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## CLOSESMDRLMNE\_FSFS\_RES

Attribute	Description
Name	CLOSESMDRLMNE_FSFS_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	string				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	string
Description	This is the user id in the Source system who is performing the action.

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM



Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

## FCUBS\_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

## Smtbs-Role-Limit-Full

Attribute	Description	
Name	Smtbs-Role-Limit-Full	
Datatype		
Description		

## ROLEID2

Attribute	Description	
Name	ROLEID2	
Datatype	string	
Description	Indicates Role Id	
Restrictions	Restrictions	Description
	maxLength	15

## DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Description	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

### LIMIT\_CCY

<b>Attribute</b>	<b>Description</b>	
Name	LIMIT_CCY	
Datatype	string	
Description	Indicates Limit Currency	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### INPUT\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	INPUT_LIMIT	
Datatype	decimal	
Description	Indicates Input Limit	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0

### AUTHORIZATION\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHORIZATION_LIMIT	
Datatype	decimal	
Description	Indicates Authorization Limit	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0

### MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

## CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	1
	<b>Description</b>	

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	1
	<b>Description</b>	

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	
	maxLength	105
	minLength	1
	<b>Description</b>	

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

### 2.5.4.SM-CloseSMDRLMNE-Res-PK-MSG.xsd

*CLOSESMDRLMNE\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Role-Limit-PK*

*ROLEID2*

*Smtbs-Role-Limit-IO*

*ROLEID2*

*MAKER*

*MAKERSTAMP*

*MODNO*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## **CLOSESMDRLMNE\_IOPK\_RES**

<b>Attribute</b>	<b>Description</b>
Name	CLOSESMDRLMNE_IOPK_RES
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

<b>Attribute</b>	<b>Description</b>
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

Attribute	Description

Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

## Smtbs-Role-Limit-PK

Attribute	Description
Name	Smtbs-Role-Limit-PK
Datatype	
Description	

## ROLEID2

Attribute	Description				
Name	ROLEID2				
Datatype	string				
Description	Indicates Role Id				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>15</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## Smtbs-Role-Limit-IO

Attribute	Description
Name	Smtbs-Role-Limit-IO
Datatype	
Description	

## ROLEID2

Attribute	Description				
Name	ROLEID2				
Datatype	string				
Description	Indicates Role Id				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>15</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## MAKER

Attribute	Description				
Name	MAKER				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

## 2.6.CloseUserMaint

### 2.6.1.SM-CloseUserMaint-Req-Full-MSG.xsd

*CLOSEUSERMAINT\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*USR-Full*  
*STRTDATE*  
*USRNAME*  
*USRPWD*  
*ENDDT*  
*USRLANG*  
*HOMEBRN*  
*CUSTNO*  
*LDAPUSR*  
*TIMELEVEL*  
*AUTOAUTH*  
*USRSTAT*  
*USRID*  
*EXTUSRREF*  
*USRCATEG*  
*TILLALLOW*



*ACCCLSALLOW*  
*GLALLOW*  
*USRTXNLMT*  
*LMTSCCY*  
*MAXTXNAMT*  
*MAXAUTHAMT*  
*BRNSALLOW*  
*PRDSALLOW*  
*PRDSACCESALLOW*  
*TAX\_IDENTIFIER*  
*AMOUNT\_FORMAT*  
*DATE\_FORMAT*  
*STAFFACCRESTR*  
*DEPT\_CODE*  
*DEPT\_DESC*  
*USRML*  
*ELCMUSER*  
*GROUP\_CODE*  
*MULTIBRN\_ACCESS*  
*OTH\_RM\_CUST\_ACC\_ALLOW*  
*SUPERVISOR\_ID*  
*SUPERVISOR\_NAME*  
*DASHBOARD\_REQD*  
*ALERTS\_ON\_HOME*  
*REFERENCE\_NO*  
*NO\_CUMULATIVE\_LOGINS*  
*NO\_SUCESSIVE\_LOGINS*  
*SCREENSAVERTIMEOUTINSECONDS*  
*NUMBER\_FORMAT\_MASK*  
*FRONTEND\_DEBUG\_ENABLED*  
*F10\_REQD*  
*F11\_REQD*

*F12\_REQD*  
*MFI\_USER*  
*MFAENABLED*  
*MFAID*  
*ACCESS\_CONTROL*  
*EXTN\_ALERTS*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*RESTR\_PWD*  
*PWD*  
*MSGRIGHTS*  
*GEN*  
*HLD*  
*CNL*  
*TSTINP*  
*CHGNODE*  
*CHGADDR*  
*REL*  
*REINS*  
*CHGMEDIA*  
*CHGPRIOR*  
*BRNMOV*  
*PRNT*  
*TSTCHK*  
*HLDAUTH*  
*CNLAUTH*  
*TSTINPAUTH*

*CHGNODEAUTH*  
*CHGADDRAUTH*  
*RELAUTH*  
*REINSAUTH*  
*CHGMEDIAAUTH*  
*BRNMOVAUTH*  
*CHGPRIORAUTH*  
*FTUPL*  
*LNKCONT*  
*MOVQ*  
*CHGBRNIN*  
*CHGADDRIN*  
*AUTHRGHTS*  
*CHGMSG*  
*CHGMSGAUTH*  
*CHGFORCCOVMATCH*  
*CHANGE\_FORCE\_RELEASE\_FUND*  
*SUPPRESS*  
*DELMSG*  
*QUEUERIGHTS*  
*QUEUE*  
*USERTILLS*  
*TILLID*  
*TILLBRNCD*  
*DESCRIPTION*  
*USERACCCLASS*  
*ACCCLS*  
*USERGLREST*  
*NODEGL*  
*USERGLEXCEPT*  
*EXCEPLEAFGL*  
*USERLIMITSROLE*

*LMTBRN*

*LMTSROLE*

*QLMTCCY*

*QINPLMT*

*QAUTHLMT*

*USERBRANCHES*

*BRNSBRN*

*BRNNAME*

*USERPRODUCTS*

*PRDPRDCD*

*PRDDESC*

*USERACCESSPRODUCTS*

*PRDACCESSPRDCD*

*PRDDESC*

*USERFUNCDISALLOW*

*FUNCDISALLOWFUNCID*

*USERROLE*

*ROLEBRNCD*

*USRROLEID*

*MASTERROLEDESC*

*USERSFUNCTIONS*

*USERFUNCBRNCD*

*USERFUNCFUNCID*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*USERFUNCCTRL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CONTROL15*

*CONTROL16*

*Grp-Restriction*

*GROUP\_CODE*

*GROUP\_DESC*

*Centralisation*

*USRROLEID*

*ROLDESC*

*Dshmst*

*USRID*

*USRNAME*

*Dshdet*

*FUNCTIONID*

*DESCRIPTION*

*SEQUENCE\_NO*

*DBWHERECLAUSE*

*SHOW\_IN\_DASHBOARD*

*Where-Master*

*COLUMN\_NAME*

*WHERE\_CL*

*CONDITION*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

**CLOSEUSERMAINT\_FSFS\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	CLOSEUSERMAINT_FSFS_REQ

Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of CloseUserMaint

## USR-Full

<b>Attribute</b>	<b>Description</b>
Name	USR-Full
Datatype	
Description	

## STRDATE

<b>Attribute</b>	<b>Description</b>
Name	STRDATE
Datatype	String
Description	

## USRNAME

<b>Attribute</b>	<b>Description</b>	
Name	USRNAME	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## USRPWD

<b>Attribute</b>	<b>Description</b>
Name	USRPWD
Datatype	string
Description	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	32

## ENDDT

<b>Attribute</b>	<b>Description</b>	
Name	ENDDT	
Datatype	String	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## USRLANG

<b>Attribute</b>	<b>Description</b>	
Name	USRLANG	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## HOMEBRN

<b>Attribute</b>	<b>Description</b>	
Name	HOMEBRN	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## CUSTNO

<b>Attribute</b>	<b>Description</b>	
Name	CUSTNO	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## LDAPUSR

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	LDAPUSR	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	500

## TIMELEVEL

<b>Attribute</b>	<b>Description</b>	
Name	TIMELEVEL	
Datatype	decimal	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	9

## AUTOAUTH

<b>Attribute</b>	<b>Description</b>	
Name	AUTOAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## USRSTAT

<b>Attribute</b>	<b>Description</b>	
Name	USRSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	E,H,D,L

## USRID

<b>Attribute</b>	<b>Description</b>	
Name	USRID	
Datatype	string	

Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## EXTUSRREF

Attribute	Description				
Name	EXTUSRREF				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

## USRCATEG

Attribute	Description				
Name	USRCATEG				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>S,B</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	S,B
Restrictions	Description				
enumeration	S,B				

## TILLALLOW

Attribute	Description				
Name	TILLALLOW				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>A,D</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	A,D
Restrictions	Description				
enumeration	A,D				

## ACCCLSALLOW

Attribute	Description
Name	ACCCLSALLOW
Datatype	string
Description	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## GLALLOW

<b>Attribute</b>	<b>Description</b>	
Name	GLALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## USRTXNLMT

<b>Attribute</b>	<b>Description</b>	
Name	USRTXNLMT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,R,N

## LMTSCCY

<b>Attribute</b>	<b>Description</b>	
Name	LMTSCCY	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## MAXTXNAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXTXNAMT	
Datatype	decimal	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### MAXAUTHAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXAUTHAMT	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### BRNSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	BRNSALLOW	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### PRDSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSALLOW	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### PRDSACCESALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSACCESALLOW	
Datatype	string	
Description		



Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## TAX\_IDENTIFIER

<b>Attribute</b>	<b>Description</b>	
Name	TAX_IDENTIFIER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

## AMOUNT\_FORMAT

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_FORMAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	****.99

## DATE\_FORMAT

<b>Attribute</b>	<b>Description</b>	
Name	DATE_FORMAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	M/d/yyyy

## STAFFACCRESTR

<b>Attribute</b>	<b>Description</b>	
Name	STAFFACCRESTR	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### DEPT\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	DEPT_CODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### DEPT\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	DEPT_DESC	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### USRML

<b>Attribute</b>	<b>Description</b>	
Name	USRML	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ELCMUSER

<b>Attribute</b>	<b>Description</b>	
Name	ELCMUSER	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### GROUP\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_CODE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### MULTIBRN\_ACCESS

<b>Attribute</b>	<b>Description</b>	
Name	MULTIBRN_ACCESS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### OTH\_RM\_CUST\_ACC\_ALLOW

<b>Attribute</b>	<b>Description</b>	
Name	OTH_RM_CUST_ACC_ALLOW	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### SUPERVISOR\_ID

<b>Attribute</b>	<b>Description</b>	
Name	SUPERVISOR_ID	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	80

## SUPERVISOR\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	SUPERVISOR_NAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## DASHBOARD\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	DASHBOARD_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## ALERTS\_ON\_HOME

<b>Attribute</b>	<b>Description</b>	
Name	ALERTS_ON_HOME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REFERENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	REFERENCE_NO	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	20
	<b>Description</b>	

### NO\_CUMULATIVE\_LOGINS

<b>Attribute</b>		<b>Description</b>
Name	NO_CUMULATIVE_LOGINS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	<b>Description</b>	

### NO\_SUCCESSIVE\_LOGINS

<b>Attribute</b>		<b>Description</b>
Name	NO_SUCCESSIVE_LOGINS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	<b>Description</b>	

### SCREENSAVERTIMEOUTINSECONDS

<b>Attribute</b>		<b>Description</b>
Name	SCREENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	<b>Description</b>	

### NUMBER\_FORMAT\_MASK

<b>Attribute</b>		<b>Description</b>
Name	NUMBER_FORMAT_MASK	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	M,L

### FRONTEND\_DEBUG\_ENABLED

<b>Attribute</b>	<b>Description</b>	
Name	FRONTEND_DEBUG_ENABLED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F10\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F10_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F11\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F11_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F12\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F12_REQD	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MFI\_USER

<b>Attribute</b>	<b>Description</b>	
Name	MFI_USER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MFAENABLED

<b>Attribute</b>	<b>Description</b>	
Name	MFAENABLED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	N,Y,L

## MFAID

<b>Attribute</b>	<b>Description</b>	
Name	MFAID	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

## ACCESS\_CONTROL

<b>Attribute</b>	<b>Description</b>	
Name	ACCESS_CONTROL	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,G,B

## EXTN\_ALERTS

<b>Attribute</b>	<b>Description</b>	
Name	EXTN_ALERTS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## RESTR\_PWD

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_PWD	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PWD

<b>Attribute</b>	<b>Description</b>	
Name	PWD	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MSGSRIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	MSGSRIGHTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## GEN

<b>Attribute</b>	<b>Description</b>	
Name	GEN	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLD

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	HLD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNL

<b>Attribute</b>	<b>Description</b>	
Name	CNL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINP

<b>Attribute</b>	<b>Description</b>	
Name	TSTINP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODE

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDR

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CHGADDR	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REL

<b>Attribute</b>	<b>Description</b>	
Name	REL	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINS

<b>Attribute</b>	<b>Description</b>	
Name	REINS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIA

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIA	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIOR

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CHGPRIOR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOV

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOV	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PRNT

<b>Attribute</b>	<b>Description</b>	
Name	PRNT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTCHK

<b>Attribute</b>	<b>Description</b>	
Name	TSTCHK	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLDAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	HLDAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNLAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CNLAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINPAUTH

<b>Attribute</b>	<b>Description</b>	
Name	TSTINPAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODEAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CHGADDRAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## RELAUTH

<b>Attribute</b>	<b>Description</b>	
Name	RELAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINSAUTH

<b>Attribute</b>	<b>Description</b>	
Name	REINSAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIAAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIAAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOVAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	BRNMOVAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIORAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIORAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## FTUPL

<b>Attribute</b>	<b>Description</b>	
Name	FTUPL	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## LNKCONT

<b>Attribute</b>	<b>Description</b>	
Name	LNKCONT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MOVQ

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	MOVQ	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGBRNIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGBRNIN	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRIN	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## AUTHRGHTS

<b>Attribute</b>	<b>Description</b>	
Name	AUTHRGHTS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSG

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CHGMSG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHGMSGAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSGAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHGFORCCOVMATCH

<b>Attribute</b>	<b>Description</b>	
Name	CHGFORCCOVMATCH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHANGE\_FORCE\_RELEASE\_FUND

<b>Attribute</b>	<b>Description</b>	
Name	CHANGE_FORCE_RELEASE_FUND	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### SUPPRESS

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	SUPPRESS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DELMSG

<b>Attribute</b>	<b>Description</b>	
Name	DELMSG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## QUEUERIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	QUEUERIGHTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## QUEUE

<b>Attribute</b>	<b>Description</b>	
Name	QUEUE	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## USERTILLS

<b>Attribute</b>	<b>Description</b>	
Name	USERTILLS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## TILLID

Attribute	Description				
Name	TILLID				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## TILLBRNCD

Attribute	Description				
Name	TILLBRNCD				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## DESCRIPTION

Attribute	Description				
Name	DESCRIPTION				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

## USERACCCLASS

Attribute	Description						
Name	USERACCCLASS						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## ACCCLS

Attribute	Description				
Name	ACCCLS				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>6</td></tr></tbody></table>	Restrictions	Description	maxLength	6
Restrictions	Description				
maxLength	6				

## USERGLREST

Attribute		Description	
Name	USERGLREST		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
	maxOccurs	unbounded	

## NODEGL

Attribute		Description	
Name	NODEGL		
Datatype	string		
Description			
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	9	

## USERGLEXCEPT

Attribute		Description	
Name	USERGLEXCEPT		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
	maxOccurs	unbounded	

## EXCEPLEAFGL

Attribute		Description	
Name	EXCEPLEAFGL		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	9	

## USERLIMITSROLE

Attribute		Description	
Name	USERLIMITSROLE		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
	maxOccurs	unbounded	

**LMTBRN**

Attribute	Description	
Name	LMTBRN	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

**LMTSROLE**

Attribute	Description	
Name	LMTSROLE	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	15

**QLMTCCY**

Attribute	Description	
Name	QLMTCCY	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

**QINPLMT**

Attribute	Description	
Name	QINPLMT	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

**QAUTHLMT**

Attribute	Description	
Name	QAUTHLMT	

Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	<b>Description</b>	

## USERBRANCHES

<b>Attribute</b>	<b>Description</b>	
Name	USERBRANCHES	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## BRNSBRN

<b>Attribute</b>	<b>Description</b>	
Name	BRNSBRN	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	3
	<b>Description</b>	

## BRNNAME

<b>Attribute</b>	<b>Description</b>	
Name	BRNNAME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	105
	<b>Description</b>	

## USERPRODUCTS

<b>Attribute</b>	<b>Description</b>	
Name	USERPRODUCTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## PRDPRDCD

Attribute	Description				
Name	PRDPRDCD				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>4</td></tr></tbody></table>	Restrictions	Description	maxLength	4
Restrictions	Description				
maxLength	4				

## PRDDESC

Attribute	Description				
Name	PRDDESC				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

## USERACCESSPRODUCTS

Attribute	Description						
Name	USERACCESSPRODUCTS						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## PRDACCESSPRDCD

Attribute	Description				
Name	PRDACCESSPRDCD				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>4</td></tr></tbody></table>	Restrictions	Description	maxLength	4
Restrictions	Description				
maxLength	4				

## PRDDESC

Attribute	Description				
Name	PRDDESC				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## USERFUNCDISALLOW

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCDISALLOW	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FUNCDISALLOWFUNCID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCDISALLOWFUNCID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## USERROLE

<b>Attribute</b>	<b>Description</b>	
Name	USERROLE	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEBRNCD

<b>Attribute</b>	<b>Description</b>	
Name	ROLEBRNCD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## USRROLEID

<b>Attribute</b>	<b>Description</b>	
Name	USRROLEID	
Datatype	string	
Description		

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## MASTERROLEDESC

<b>Attribute</b>	<b>Description</b>	
Name	MASTERROLEDESC	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	45

## USERSFUNCTIONS

<b>Attribute</b>	<b>Description</b>	
Name	USERSFUNCTIONS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## USERFUNCBRNCD

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCBRNCD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## USERFUNCFUNCID

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCFUNCID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## CONTROL1

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL1	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL2	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL4

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL4	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL6

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL6	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL8

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL8	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## USERFUNCCTRL10

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCCTRL10	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL11

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL11	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL12

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL12	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL13

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL13	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

#### CONTROL14

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL14	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

#### CONTROL15

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL15	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

#### CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

#### Grp-Restriction

<b>Attribute</b>	<b>Description</b>	
Name	Grp-Restriction	
Datatype		
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## GROUP\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_CODE	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

## GROUP\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_DESC	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

## Centralisation

<b>Attribute</b>	<b>Description</b>	
Name	Centralisation	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## USRROLEID

<b>Attribute</b>	<b>Description</b>	
Name	USRROLEID	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## ROLDESC

<b>Attribute</b>	<b>Description</b>	
Name	ROLDESC	
Datatype	string	

Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

### Dshmst

<b>Attribute</b>	<b>Description</b>	
Name	Dshmst	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

### USRID

<b>Attribute</b>	<b>Description</b>	
Name	USRID	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

### USRNAME

<b>Attribute</b>	<b>Description</b>	
Name	USRNAME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

### Dshdet

<b>Attribute</b>	<b>Description</b>	
Name	Dshdet	
Datatype		
Description		



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1000

## SEQUENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	SEQUENCE_NO	
Datatype	decimal	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## DBWHERECLAUSE

<b>Attribute</b>	<b>Description</b>	
Name	DBWHERECLAUSE	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

## SHOW\_IN\_DASHBOARD

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	SHOW_IN_DASHBOARD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## Where-Master

<b>Attribute</b>	<b>Description</b>	
Name	Where-Master	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## COLUMN\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	COLUMN_NAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	2000

## WHERE\_CL

<b>Attribute</b>	<b>Description</b>	
Name	WHERE_CL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	500

## CONDITION

<b>Attribute</b>	<b>Description</b>	
Name	CONDITION	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
Restrictions	<b>Restrictions</b>	<b>Description</b>
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
Restrictions	<b>Restrictions</b>	<b>Description</b>
	minLength	0

### 2.6.2.SM-CloseUserMaint-Req-IO-MSG.xsd

*CLOSEUSERMAINT\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
     *PARAM*  
         *NAME*  
         *VALUE*  
*FCUBS\_BODY*  
*USR-IO*  
     *USRID*  
     *MAKER*  
     *MAKERSTAMP*  
     *MODNO*

**CLOSEUSERMAINT\_IOPK\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	CLOSEUSERMAINT_IOPK_REQ
Datatype	
Description	

**FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	string	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT



Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of CloseUserMaint

## USR-IO

Attribute	Description
Name	USR-IO
Datatype	
Description	

## USRID

Attribute	Description				
Name	USRID				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## MAKER

Attribute	Description				
Name	MAKER				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

### 2.6.3.SM-CloseUserMaint-Res-Full-MSG.xsd

*CLOSEUSERMAINT\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*USR-Full*  
*STRTDATE*  
*USRNAME*  
*USRPWD*  
*ENDDT*  
*USRLANG*  
*HOMEBRN*  
*CUSTNO*  
*LDAPUSR*  
*TIMELEVEL*  
*AUTOAUTH*  
*USRSTAT*  
*USRID*  
*EXTUSRREF*  
*USRCATEG*  
*TILLALLOW*  
*ACCCLSALLOW*  
*GLALLOW*  
*USRTXNLMT*  
*LMTSCCY*  
*MAXTXNAMT*  
*MAXAUTHAMT*  
*BRNSALLOW*  
*PRDSALLOW*  
*PRDSACCESALLOW*  
*TAX\_IDENTIFIER*  
*AMOUNT\_FORMAT*  
*DATE\_FORMAT*  
*STAFFACCRESTR*

*DEPT\_CODE*  
*DEPT\_DESC*  
*USRML*  
*ELCMUSER*  
*GROUP\_CODE*  
*MULTIBRN\_ACCESS*  
*OTH\_RM\_CUST\_ACC\_ALLOW*  
*SUPERVISOR\_ID*  
*SUPERVISOR\_NAME*  
*DASHBOARD\_REQD*  
*ALERTS\_ON\_HOME*  
*REFERENCE\_NO*  
*NO\_CUMULATIVE\_LOGINS*  
*NO\_SUCESSIVE\_LOGINS*  
*SCREENSAVERTIMEOUTINSECONDS*  
*NUMBER\_FORMAT\_MASK*  
*FRONTEND\_DEBUG\_ENABLED*  
*F10\_REQD*  
*F11\_REQD*  
*F12\_REQD*  
*MFI\_USER*  
*MFAENABLED*  
*MFAID*  
*ACCESS\_CONTROL*  
*EXTN\_ALERTS*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*

*RESTR\_PWD*  
*PWD*  
*MSGSRIGHTS*  
*GEN*  
*HLD*  
*CNL*  
*TSTINP*  
*CHGNODE*  
*CHGADDR*  
*REL*  
*REINS*  
*CHGMEDIA*  
*CHGPRIOR*  
*BRNMOV*  
*PRNT*  
*TSTCHK*  
*HLDAUTH*  
*CNLAUTH*  
*TSTINPAUTH*  
*CHGNODEAUTH*  
*CHGADDRAUTH*  
*RELAUTH*  
*REINSAUTH*  
*CHGMEDIAAUTH*  
*BRNMOVAUTH*  
*CHGPRIORAUTH*  
*FTUPL*  
*LNKCONT*  
*MOVQ*  
*CHGBRNIN*  
*CHGADDRIN*  
*AUTHRGHTS*

*CHGMSG*  
*CHGMSGAUTH*  
*CHGFORCCOVMATCH*  
*CHANGE\_FORCE\_RELEASE\_FUND*  
*SUPPRESS*  
*DELMSG*  
*QUEUERIGHTS*  
*QUEUE*  
*USERTILLS*  
*TILLID*  
*TILLBRNCD*  
*DESCRIPTION*  
*USERACCCLASS*  
*ACCCLS*  
*USERGLREST*  
*NODEGL*  
*USERGLEXCEPT*  
*EXCEPLEAFGL*  
*USERLIMITSROLE*  
*LMTBRN*  
*LMTSROLE*  
*QLMTCCY*  
*QINPLMT*  
*QAUTHLMT*  
*USERBRANCHES*  
*BRNSBRN*  
*BRNNAME*  
*USERPRODUCTS*  
*PRDPRDCD*  
*PRDDESC*  
*USERACCESSPRODUCTS*  
*PRDACCESSPRDCD*

*PRDESC*

*USERFUNCDISALLOW*

*FUNCDISALLOWFUNCID*

*USERROLE*

*ROLEBRNCD*

*USRROLEID*

*MASTERROLEDESC*

*USERSFUNCTIONS*

*USERFUNCBRNCD*

*USERFUNCFUNCID*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*USERFUNCSCTRL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CONTROL15*

*CONTROL16*

*Grp-Restriction*

*GROUP\_CODE*

*GROUP\_DESC*

*Centralisation*

*USRROLEID*

*ROLDESC*



*Dshmst*

*USRID*

*USRNAME*

*Dshdet*

*FUNCTIONID*

*DESCRIPTION*

*SEQUENCE\_NO*

*DBWHERECLAUSE*

*SHOW\_IN\_DASHBOARD*

*Where-Master*

*COLUMN\_NAME*

*WHERE\_CL*

*CONDITION*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## **CLOSEUSERMAINT\_FSFS\_RES**

<b>Attribute</b>	<b>Description</b>
Name	CLOSEUSERMAINT_FSFS_RES
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

Attribute	Description	
Name	SOURCE	
Datatype	string	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

## USR-Full

Attribute	Description
Name	USR-Full
Datatype	
Description	

## STRDATE

Attribute	Description
Name	STRDATE
Datatype	String
Description	

## USRNAME

Attribute	Description				
Name	USRNAME				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

## USRPWD

Attribute	Description				
Name	USRPWD				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>32</td></tr></tbody></table>	Restrictions	Description	maxLength	32
Restrictions	Description				
maxLength	32				

## ENDDT

Attribute	Description
Name	ENDDT
Datatype	String

Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## USRLANG

<b>Attribute</b>	<b>Description</b>	
Name	USRLANG	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## HOMEBRN

<b>Attribute</b>	<b>Description</b>	
Name	HOMEBRN	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## CUSTNO

<b>Attribute</b>	<b>Description</b>	
Name	CUSTNO	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## LDAPUSR

<b>Attribute</b>	<b>Description</b>	
Name	LDAPUSR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	500

## TIMELEVEL

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	TIMELEVEL	
Datatype	decimal	
Description		
Restrictions	<b>Restrictions</b>	
		<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	9

## AUTOAUTH

<b>Attribute</b>	<b>Description</b>	
Name	AUTOAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
		<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
		<b>Description</b>
	enumeration	Y,N

## USRSTAT

<b>Attribute</b>	<b>Description</b>	
Name	USRSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
		<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
		<b>Description</b>
	enumeration	E,H,D,L

## USRID

<b>Attribute</b>	<b>Description</b>	
Name	USRID	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
		<b>Description</b>
	maxLength	12

## EXTUSRREF

<b>Attribute</b>	<b>Description</b>	
Name	EXTUSRREF	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## USRCATEG

<b>Attribute</b>	<b>Description</b>	
Name	USRCATEG	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	S,B

## TILLALLOW

<b>Attribute</b>	<b>Description</b>	
Name	TILLALLOW	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## ACCCLSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLSALLOW	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## GLALLOW

<b>Attribute</b>	<b>Description</b>	
Name	GLALLOW	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### USRTXNLMT

<b>Attribute</b>	<b>Description</b>	
Name	USRTXNLMT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,R,N

### LMTSCCY

<b>Attribute</b>	<b>Description</b>	
Name	LMTSCCY	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### MAXTXNAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXTXNAMT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### MAXAUTHAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXAUTHAMT	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### BRNSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	BRNSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### PRDSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### PRDSACCESALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSACCESALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### TAX\_IDENTIFIER

<b>Attribute</b>	<b>Description</b>	
Name	TAX_IDENTIFIER	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

## AMOUNT\_FORMAT

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_FORMAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	*****

## DATE\_FORMAT

<b>Attribute</b>	<b>Description</b>	
Name	DATE_FORMAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	M/d/yyyy

## STAFFACCRESTR

<b>Attribute</b>	<b>Description</b>	
Name	STAFFACCRESTR	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DEPT\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	DEPT_CODE	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## DEPT\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	DEPT_DESC	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## USRML

<b>Attribute</b>	<b>Description</b>	
Name	USRML	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## ELCMUSER

<b>Attribute</b>	<b>Description</b>	
Name	ELCMUSER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## GROUP\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_CODE	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### MULTIBRN\_ACCESS

<b>Attribute</b>	<b>Description</b>	
Name	MULTIBRN_ACCESS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### OTH\_RM\_CUST\_ACC\_ALLOW

<b>Attribute</b>	<b>Description</b>	
Name	OTH_RM_CUST_ACC_ALLOW	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### SUPERVISOR\_ID

<b>Attribute</b>	<b>Description</b>	
Name	SUPERVISOR_ID	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	80

### SUPERVISOR\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	SUPERVISOR_NAME	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	35
	<b>Description</b>	

### DASHBOARD\_REQD

<b>Attribute</b>		<b>Description</b>
Name	DASHBOARD_REQD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	enumeration	Y,N
	<b>Description</b>	

### ALERTS\_ON\_HOME

<b>Attribute</b>		<b>Description</b>
Name	ALERTS_ON_HOME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	enumeration	Y,N
	<b>Description</b>	

### REFERENCE\_NO

<b>Attribute</b>		<b>Description</b>
Name	REFERENCE_NO	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	20
	<b>Description</b>	

### NO\_CUMULATIVE\_LOGINS

<b>Attribute</b>		<b>Description</b>
Name	NO_CUMULATIVE_LOGINS	
Datatype	decimal	
Description		



Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	<b>Description</b>	

## NO\_SUCCESSIVE\_LOGINS

<b>Attribute</b>		<b>Description</b>
Name	NO_SUCCESSIVE_LOGINS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	<b>Description</b>	

## SCREENSAVERTIMEOUTINSECONDS

<b>Attribute</b>		<b>Description</b>
Name	SCREENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	<b>Description</b>	

## NUMBER\_FORMAT\_MASK

<b>Attribute</b>		<b>Description</b>
Name	NUMBER_FORMAT_MASK	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	enumeration	M,L
	<b>Description</b>	

## FRONTEND\_DEBUG\_ENABLED

<b>Attribute</b>		<b>Description</b>
Name	FRONTEND_DEBUG_ENABLED	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F10\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F10_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F11\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F11_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F12\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F12_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### MFI\_USER

<b>Attribute</b>	<b>Description</b>	
Name	MFI_USER	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MFAENABLED

<b>Attribute</b>	<b>Description</b>	
Name	MFAENABLED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	N,Y,L

## MFAID

<b>Attribute</b>	<b>Description</b>	
Name	MFAID	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

## ACCESS\_CONTROL

<b>Attribute</b>	<b>Description</b>	
Name	ACCESS_CONTROL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,G,B

## EXTN\_ALERTS

<b>Attribute</b>	<b>Description</b>	
Name	EXTN_ALERTS	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	35
	<b>Description</b>	

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	4
	<b>Description</b>	

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	1
	<b>Description</b>	

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	1
	<b>Description</b>	

## RESTR\_PWD

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_PWD	
Datatype		
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PWD

<b>Attribute</b>	<b>Description</b>	
Name	PWD	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MSGSRIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	MSGSRIGHTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## GEN

<b>Attribute</b>	<b>Description</b>	
Name	GEN	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLD

<b>Attribute</b>	<b>Description</b>	
Name	HLD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNL

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CNL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINP

<b>Attribute</b>	<b>Description</b>	
Name	TSTINP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODE

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDR

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REL

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	REL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINS

<b>Attribute</b>	<b>Description</b>	
Name	REINS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIA

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIA	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIOR

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIOR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOV

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	BRNMOV	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PRNT

<b>Attribute</b>	<b>Description</b>	
Name	PRNT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTCHK

<b>Attribute</b>	<b>Description</b>	
Name	TSTCHK	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLDAUTH

<b>Attribute</b>	<b>Description</b>	
Name	HLDAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNLAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CNLAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINPAUTH

<b>Attribute</b>	<b>Description</b>	
Name	TSTINPAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODEAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## RELAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	RELAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINSAUTH

<b>Attribute</b>	<b>Description</b>	
Name	REINSAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIAAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIAAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOVAUTH

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOVAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIORAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CHGPRIORAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## FTUPL

<b>Attribute</b>	<b>Description</b>	
Name	FTUPL	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## LNKCONT

<b>Attribute</b>	<b>Description</b>	
Name	LNKCONT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MOVQ

<b>Attribute</b>	<b>Description</b>	
Name	MOVQ	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGBRNIN

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CHGBRNIN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRIN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## AUTHRGHTS

<b>Attribute</b>	<b>Description</b>	
Name	AUTHRGHTS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSG

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSGAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CHGMSGAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHGFORCCOVMATCH

<b>Attribute</b>	<b>Description</b>	
Name	CHGFORCCOVMATCH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHANGE\_FORCE\_RELEASE\_FUND

<b>Attribute</b>	<b>Description</b>	
Name	CHANGE_FORCE_RELEASE_FUND	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### SUPPRESS

<b>Attribute</b>	<b>Description</b>	
Name	SUPPRESS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### DELMSG

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	DELMSG	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	enumeration	Y,N
	<b>Description</b>	

## QUEUERIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	QUEUERIGHTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## QUEUE

<b>Attribute</b>	<b>Description</b>	
Name	QUEUE	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	10
	<b>Description</b>	

## USERTILLS

<b>Attribute</b>	<b>Description</b>	
Name	USERTILLS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## TILLID

<b>Attribute</b>	<b>Description</b>	
Name	TILLID	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	12
	<b>Description</b>	

## TILLBRNCD

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	TILLBRNCD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

## USERACCCLASS

<b>Attribute</b>	<b>Description</b>	
Name	USERACCCLASS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ACCCLS

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLS	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

## USERGLREST

<b>Attribute</b>	<b>Description</b>	
Name	USERGLREST	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NODEGL

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	NODEGL	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## USERGLEXCEPT

<b>Attribute</b>	<b>Description</b>	
Name	USERGLEXCEPT	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## EXCEPLEAFGL

<b>Attribute</b>	<b>Description</b>	
Name	EXCEPLEAFGL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## USERLIMITSROLE

<b>Attribute</b>	<b>Description</b>	
Name	USERLIMITSROLE	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## LMTBRN

<b>Attribute</b>	<b>Description</b>	
Name	LMTBRN	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## LMTSROLE

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	LMTSROLE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

### QLMTCCY

<b>Attribute</b>	<b>Description</b>	
Name	QLMTCCY	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### QINPLMT

<b>Attribute</b>	<b>Description</b>	
Name	QINPLMT	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### QAUHLMT

<b>Attribute</b>	<b>Description</b>	
Name	QAUHLMT	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### USERBRANCHES

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	USERBRANCHES	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### BRNSBRN

<b>Attribute</b>	<b>Description</b>	
Name	BRNSBRN	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### BRNNAME

<b>Attribute</b>	<b>Description</b>	
Name	BRNNAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

### USERPRODUCTS

<b>Attribute</b>	<b>Description</b>	
Name	USERPRODUCTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### PRDPRDCD

<b>Attribute</b>	<b>Description</b>	
Name	PRDPRDCD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

### PRDDESC

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	PRDESC	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## USERACCESSPRODUCTS

<b>Attribute</b>	<b>Description</b>	
Name	USERACCESSPRODUCTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PRDACCESSPRDCD

<b>Attribute</b>	<b>Description</b>	
Name	PRDACCESSPRDCD	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

## PRDESC

<b>Attribute</b>	<b>Description</b>	
Name	PRDESC	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## USERFUNCDISALLOW

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCDISALLOW	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FUNCDISALLOWFUNCID

Attribute	Description				
Name	FUNCDISALLOWFUNCID				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr></tbody></table>	Restrictions	Description	maxLength	8
Restrictions	Description				
maxLength	8				

## USERROLE

Attribute	Description						
Name	USERROLE						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## ROLEBRNCD

Attribute	Description				
Name	ROLEBRNCD				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## USRROLEID

Attribute	Description				
Name	USRROLEID				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## MASTERROLEDESC

Attribute	Description				
Name	MASTERROLEDESC				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>45</td></tr></tbody></table>	Restrictions	Description	maxLength	45
Restrictions	Description				
maxLength	45				

## USERSFUNCTIONS

Attribute	Description	
Name	USERSFUNCTIONS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## USERFUNCBRNCD

Attribute	Description	
Name	USERFUNCBRNCD	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

## USERFUNCFUNCID

Attribute	Description	
Name	USERFUNCFUNCID	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	8

## CONTROL1

Attribute	Description	
Name	CONTROL1	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

## CONTROL2

Attribute	Description	
Name	CONTROL2	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL4

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL4	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL6

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL6	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL8

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL8	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### USERFUNCCTRL10

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCCTRL10	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL11

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL11	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL12

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL12	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL13

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL13	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL14

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL14	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL15

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL15	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### Grp-Restriction

<b>Attribute</b>	<b>Description</b>	
Name	Grp-Restriction	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### GROUP\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_CODE	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

### GROUP\_DESC

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	GROUP_DESC	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

## Centralisation

<b>Attribute</b>	<b>Description</b>	
Name	Centralisation	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## USRROLEID

<b>Attribute</b>	<b>Description</b>	
Name	USRROLEID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## ROLDESC

<b>Attribute</b>	<b>Description</b>	
Name	ROLDESC	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## Dshmst

<b>Attribute</b>	<b>Description</b>	
Name	Dshmst	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## USRID

Attribute	Description	
Name	USRID	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

## USRNAME

Attribute	Description	
Name	USRNAME	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

## Dshdet

Attribute	Description	
Name	Dshdet	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

## DESCRIPTION

Attribute	Description
-----------	-------------

Name	DESCRIPTION	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1000

## SEQUENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	SEQUENCE_NO	
Datatype	decimal	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## DBWHERECLAUSE

<b>Attribute</b>	<b>Description</b>	
Name	DBWHERECLAUSE	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

## SHOW\_IN\_DASHBOARD

<b>Attribute</b>	<b>Description</b>	
Name	SHOW_IN_DASHBOARD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## Where-Master

<b>Attribute</b>	<b>Description</b>	
Name	Where-Master	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## COLUMN\_NAME

Attribute		Description	
Name	COLUMN_NAME		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	2000	

## WHERE\_CL

Attribute		Description	
Name	WHERE_CL		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	500	

## CONDITION

Attribute		Description	
Name	CONDITION		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	30	

## UDFDETAILS

Attribute		Description	
Name	UDFDETAILS		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
	maxOccurs	unbounded	

## FLDNAM

Attribute		Description	
Name	FLDNAM		

Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

### 2.6.4.SM-CloseUserMaint-Res-PK-MSG.xsd

*CLOSEUSERMAINT\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*



*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*USR-PK*  
*USRID*  
*USR-IO*  
*USRID*  
*MAKER*  
*MAKERSTAMP*  
*MODNO*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*  
*WCODE*  
*WDESC*

**CLOSEUSERMAINT\_IOPK\_RES**

<b>Attribute</b>	<b>Description</b>
Name	CLOSEUSERMAINT_IOPK_RES
Datatype	
Description	

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

## USR-PK

Attribute	Description
Name	USR-PK
Datatype	
Description	

## USRID

Attribute	Description				
Name	USRID				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## USR-IO

Attribute	Description
Name	USR-IO
Datatype	
Description	

## USRID

Attribute	Description				
Name	USRID				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## MAKER

Attribute	Description
Name	MAKER
Datatype	string
Description	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		



Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

## WDESC

<b>Attribute</b>	<b>Description</b>
Name	WDESC
Datatype	String
Description	

## 2.7.CreateSMD BANKP

### 2.7.1.SM-CreateSMD BANKP-Req-Full-MSG.xsd

[CREATESMDBANKP\\_FSFS\\_REQ](#)

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Parameters-Full*

*HEAD\_OFFICE*

*SITE\_CODE*

*ACTIVATION\_KEY*

*INVALID\_LOGINS\_CUM*

*INVALID\_LOGINS\_SUC*

*PWD\_PREVENT\_REUSE*

*PWD\_CHANGE\_AFTER*

*MAXIMUM*

*MINIMUM*

*PWD\_EXPIRY\_MSG\_DAYS*

*ARCHIVAL\_PERIOD*

*CONCHAR\_PWD\_NUM*

*FREQ\_PWD\_CHG*

*MIN\_PWD\_NUMERIC\_LENGTH*

*LEGAL\_NOTICE*

*DORMANCY\_DAYS*

*DISPLAY\_LEGAL\_NOTICE*

*MIN\_SPECIALCHAR\_LENGTH*

*MIN\_LOWERCASE\_CHAR*

*MIN\_UPPERCASE\_CHAR*

*SCREENSAVERREQUIRED*

*SCREENSAVERTIMEOUTINSECONDS*

*SCREENSAVERMODIFIABLEBYUSER*

*PASSWORDEXTERNAL*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Smtbs-Branch-Restr*

*RESTR\_TYPE*

*DESCRIPTION*

*Smtbs-Restrictive-Passwd*

*PASSWORD*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

Attribute	Description
Name	CREATESMDBANKP_FSFS_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	string				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## USERID

Attribute	Description						
Name	USERID						
Datatype	string						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

Attribute	Description
Name	MODULEID
Datatype	string
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of CreateSMDBANKP

## Smtbs-Parameters-Full

<b>Attribute</b>	<b>Description</b>
Name	Smtbs-Parameters-Full
Datatype	
Description	

## HEAD\_OFFICE

<b>Attribute</b>	<b>Description</b>	
Name	HEAD_OFFICE	
Datatype	string	
Description	Indicates Head Office	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## SITE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	SITE_CODE	
Datatype	string	
Description	Indicates Site Code	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

## ACTIVATION\_KEY

Attribute	Description				
Name	ACTIVATION_KEY				
Datatype	string				
Description	Indicates Activation Key				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>24</td></tr></tbody></table>	Restrictions	Description	maxLength	24
Restrictions	Description				
maxLength	24				

## INVALID\_LOGINS\_CUM

Attribute	Description								
Name	INVALID_LOGINS_CUM								
Datatype	decimal								
Description	Indicates Cumulative								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>6</td></tr><tr><td>maxInclusive</td><td>99</td></tr></tbody></table>	Restrictions	Description	totalDigits	2	minInclusive	6	maxInclusive	99
Restrictions	Description								
totalDigits	2								
minInclusive	6								
maxInclusive	99								

## INVALID\_LOGINS\_SUC

Attribute	Description								
Name	INVALID_LOGINS_SUC								
Datatype	decimal								
Description	Indicates Successive								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>1</td></tr><tr><td>minInclusive</td><td>3</td></tr><tr><td>maxInclusive</td><td>5</td></tr></tbody></table>	Restrictions	Description	totalDigits	1	minInclusive	3	maxInclusive	5
Restrictions	Description								
totalDigits	1								
minInclusive	3								
maxInclusive	5								

## PWD\_PREVENT\_REUSE

Attribute	Description				
Name	PWD_PREVENT_REUSE				
Datatype	decimal				
Description	Indicates Password Repetitions				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## PWD\_CHANGE\_AFTER

<b>Attribute</b>	<b>Description</b>	
Name	PWD_CHANGE_AFTER	
Datatype	decimal	
Description	Indicates Force Password Change After	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	3
	minInclusive	15
	maxInclusive	180

## MAXIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MAXIMUM	
Datatype	decimal	
Description	Indicates Maximum	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	12
	maxInclusive	30

## MINIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MINIMUM	
Datatype	decimal	
Description	Indicates Minimum	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	6
	maxInclusive	11

## PWD\_EXPIRY\_MSG\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	PWD_EXPIRY_MSG_DAYS	
Datatype	decimal	
Description	Indicates Intimate User (Before Password Expiry)	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	2
	minInclusive	1
	maxInclusive	5

## ARCHIVAL\_PERIOD

<b>Attribute</b>	<b>Description</b>	
Name	ARCHIVAL_PERIOD	
Datatype	decimal	
Description	Indicates Archival Period (in days)	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	3

## CONCHAR\_PWD\_NUM

<b>Attribute</b>	<b>Description</b>	
Name	CONCHAR_PWD_NUM	
Datatype	decimal	
Description	Indicates Maximum Consecutive Repetitive Characters	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	2

## FREQ\_PWD\_CHG

<b>Attribute</b>	<b>Description</b>	
Name	FREQ_PWD_CHG	
Datatype	decimal	
Description	Indicates Minimum Days Between Password Changes	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	2
	minInclusive	0

## MIN\_PWD\_NUMERIC\_LENGTH

<b>Attribute</b>	<b>Description</b>	
Name	MIN_PWD_NUMERIC_LENGTH	
Datatype	decimal	

Description	Indicates Minimum Number Of Numeric Characters In Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## LEGAL\_NOTICE

<b>Attribute</b>	<b>Description</b>	
Name	LEGAL_NOTICE	
Datatype	string	
Description	Indicates Warning Screen Text	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

## DORMANCY\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	DORMANCY_DAYS	
Datatype	decimal	
Description	Indicates Dormancy Days	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## DISPLAY\_LEGAL\_NOTICE

<b>Attribute</b>	<b>Description</b>	
Name	DISPLAY_LEGAL_NOTICE	
Datatype	string	
Description	Indicates Display Legal Notice Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MIN\_SPECIALCHAR\_LENGTH

<b>Attribute</b>	<b>Description</b>	
Name	MIN_SPECIALCHAR_LENGTH	
Datatype	decimal	
Description	Indicates Minimum Number Of Special Characters In Password	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### MIN\_LOWERCASE\_CHAR

<b>Attribute</b>	<b>Description</b>	
Name	MIN_LOWERCASE_CHAR	
Datatype	decimal	
Description	Indicates Minimum Number of LowerCase Characters in Password	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### MIN\_UPPERCASE\_CHAR

<b>Attribute</b>	<b>Description</b>	
Name	MIN_UPPERCASE_CHAR	
Datatype	decimal	
Description	Indicates Minimum Number of UpperCase Characters in Password	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### SCREENSAVERREQUIRED

<b>Attribute</b>	<b>Description</b>	
Name	SCREENSAVERREQUIRED	
Datatype	string	
Description	Indicates Screensaver Required Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### SCREENSAVERTIMEOUTINSECONDS

<b>Attribute</b>	<b>Description</b>	
Name	SCREENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description	Indicates Screensaver Interval (in seconds)	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## SCREENSAVERMODIFIABLEBYUSER

<b>Attribute</b>	<b>Description</b>	
Name	SCREENSAVERMODIFIABLEBYUSER	
Datatype	string	
Description	Indicates Screensaver Interval Modifiable at User Level Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PASSWORDEXTERNAL

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORDEXTERNAL	
Datatype	string	
Description	Indicates Password External Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		



Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## Smtbs-Branch-Restr

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Branch-Restr	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## RESTR\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_TYPE	
Datatype	string	
Description	Indicates Restriction Type	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Restriction Type Description	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

### Smtbs-Restrictive-Passwd

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Restrictive-Passwd	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description	Indicates Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

### FLDVAL

<b>Attribute</b>	<b>Description</b>
Name	FLDVAL

Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

## 2.7.2.SM-CreateSMDBANKP-Req-IO-MSG.xsd

### *CREATESMDBANKP\_IOPK\_REQ*

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

*Smtbs-Parameters-IO*

*HEAD\_OFFICE*  
*SITE\_CODE*  
*ACTIVATION\_KEY*  
*INVALID\_LOGINS\_CUM*  
*INVALID\_LOGINS\_SUC*  
*PWD\_PREVENT\_REUSE*  
*PWD\_CHANGE\_AFTER*  
*MAXIMUM*  
*MINIMUM*  
*PWD\_EXPIRY\_MSG\_DAYS*  
*ARCHIVAL\_PERIOD*  
*CONCHAR\_PWD\_NUM*  
*FREQ\_PWD\_CHG*  
*MIN\_PWD\_NUMERIC\_LENGTH*  
*LEGAL\_NOTICE*  
*DORMANCY\_DAYS*  
*DISPLAY\_LEGAL\_NOTICE*  
*MIN\_SPECIALCHAR\_LENGTH*  
*MIN\_LOWERCASE\_CHAR*  
*MIN\_UPPERCASE\_CHAR*  
*SCREESAVERREQUIRED*  
*SCREESAVERTIMEOUTINSECONDS*  
*SCREESAVERMODIFIABLEBYUSER*  
*Smtbs-Branch-Restr*  
*RESTR\_TYPE*  
*DESCRIPTION*  
*Smtbs-Restrictive-Passwd*  
*PASSWORD*  
*UDFDETAILS*  
*FLDNAM*  
*FLDVAL*

Attribute	Description
Name	CREATESMDBANKP_IOPK_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	string				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## USERID

Attribute	Description						
Name	USERID						
Datatype	string						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

Attribute	Description
Name	MODULEID
Datatype	string
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	



Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of CreateSMDBANKP

## Smtbs-Parameters-IO

<b>Attribute</b>	<b>Description</b>
Name	Smtbs-Parameters-IO
Datatype	
Description	

## HEAD\_OFFICE

<b>Attribute</b>	<b>Description</b>	
Name	HEAD_OFFICE	
Datatype	string	
Description	Indicates Head Office	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## SITE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	SITE_CODE	
Datatype	string	
Description	Indicates Site Code	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

## ACTIVATION\_KEY

Attribute	Description				
Name	ACTIVATION_KEY				
Datatype	string				
Description	Indicates Activation Key				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>24</td></tr></tbody></table>	Restrictions	Description	maxLength	24
Restrictions	Description				
maxLength	24				

## INVALID\_LOGINS\_CUM

Attribute	Description								
Name	INVALID_LOGINS_CUM								
Datatype	decimal								
Description	Indicates Cumulative								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>6</td></tr><tr><td>maxInclusive</td><td>99</td></tr></tbody></table>	Restrictions	Description	totalDigits	2	minInclusive	6	maxInclusive	99
Restrictions	Description								
totalDigits	2								
minInclusive	6								
maxInclusive	99								

## INVALID\_LOGINS\_SUC

Attribute	Description								
Name	INVALID_LOGINS_SUC								
Datatype	decimal								
Description	Indicates Successive								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>1</td></tr><tr><td>minInclusive</td><td>3</td></tr><tr><td>maxInclusive</td><td>5</td></tr></tbody></table>	Restrictions	Description	totalDigits	1	minInclusive	3	maxInclusive	5
Restrictions	Description								
totalDigits	1								
minInclusive	3								
maxInclusive	5								

## PWD\_PREVENT\_REUSE

Attribute	Description				
Name	PWD_PREVENT_REUSE				
Datatype	decimal				
Description	Indicates Password Repetitions				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## PWD\_CHANGE\_AFTER

<b>Attribute</b>	<b>Description</b>	
Name	PWD_CHANGE_AFTER	
Datatype	decimal	
Description	Indicates Force Password Change After	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	3
	minInclusive	15
	maxInclusive	180

## MAXIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MAXIMUM	
Datatype	decimal	
Description	Indicates Maximum	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	12
	maxInclusive	30

## MINIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MINIMUM	
Datatype	decimal	
Description	Indicates Minimum	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	6
	maxInclusive	11

## PWD\_EXPIRY\_MSG\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	PWD_EXPIRY_MSG_DAYS	
Datatype	decimal	
Description	Indicates Intimate User (Before Password Expiry)	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	2
	minInclusive	1
	maxInclusive	5

## ARCHIVAL\_PERIOD

<b>Attribute</b>	<b>Description</b>	
Name	ARCHIVAL_PERIOD	
Datatype	decimal	
Description	Indicates Archival Period (in days)	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	3

## CONCHAR\_PWD\_NUM

<b>Attribute</b>	<b>Description</b>	
Name	CONCHAR_PWD_NUM	
Datatype	decimal	
Description	Indicates Maximum Consecutive Repetitive Characters	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	2

## FREQ\_PWD\_CHG

<b>Attribute</b>	<b>Description</b>	
Name	FREQ_PWD_CHG	
Datatype	decimal	
Description	Indicates Minimum Days Between Password Changes	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	2
	minInclusive	0

## MIN\_PWD\_NUMERIC\_LENGTH

<b>Attribute</b>	<b>Description</b>	
Name	MIN_PWD_NUMERIC_LENGTH	
Datatype	decimal	

Description	Indicates Minimum Number Of Numeric Characters In Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## LEGAL\_NOTICE

<b>Attribute</b>	<b>Description</b>	
Name	LEGAL_NOTICE	
Datatype	string	
Description	Indicates Warning Screen Text	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

## DORMANCY\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	DORMANCY_DAYS	
Datatype	decimal	
Description	Indicates Dormancy Days	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## DISPLAY\_LEGAL\_NOTICE

<b>Attribute</b>	<b>Description</b>	
Name	DISPLAY_LEGAL_NOTICE	
Datatype	string	
Description	Indicates Display Legal Notice Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MIN\_SPECIALCHAR\_LENGTH

<b>Attribute</b>	<b>Description</b>	
Name	MIN_SPECIALCHAR_LENGTH	
Datatype	decimal	
Description	Indicates Minimum Number Of Special Characters In Password	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### MIN\_LOWERCASE\_CHAR

<b>Attribute</b>	<b>Description</b>	
Name	MIN_LOWERCASE_CHAR	
Datatype	decimal	
Description	Indicates Minimum Number of LowerCase Characters in Password	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### MIN\_UPPERCASE\_CHAR

<b>Attribute</b>	<b>Description</b>	
Name	MIN_UPPERCASE_CHAR	
Datatype	decimal	
Description	Indicates Minimum Number of UpperCase Characters in Password	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### SCREENSAVERREQUIRED

<b>Attribute</b>	<b>Description</b>	
Name	SCREENSAVERREQUIRED	
Datatype	string	
Description	Indicates Screensaver Required Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### SCREENSAVERTIMEOUTINSECONDS

<b>Attribute</b>	<b>Description</b>	
Name	SCREENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description	Indicates Screensaver Interval (in seconds)	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## SCRENSAVERMODIFIABLEBYUSER

<b>Attribute</b>	<b>Description</b>	
Name	SCRENSAVERMODIFIABLEBYUSER	
Datatype	string	
Description	Indicates Screensaver Interval Modifiable at User Level Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## Smtbs-Branch-Restr

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Branch-Restr	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## RESTR\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_TYPE	
Datatype	string	
Description	Indicates Restriction Type	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Restriction Type Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

### Smtbs-Restrictive-Passwd

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Restrictive-Passwd	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description	Indicates Password	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

### FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

2.7.3.SM-CreateSMDBANKP-Res-Full-MSG.xsd

*CREATESMDBANKP\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Parameters-Full*

*HEAD\_OFFICE*

*SITE\_CODE*

*ACTIVATION\_KEY*

*INVALID\_LOGINS\_CUM*

*INVALID\_LOGINS\_SUC*

*PWD\_PREVENT\_REUSE*

*PWD\_CHANGE\_AFTER*

*MAXIMUM*

*MINIMUM*

*PWD\_EXPIRY\_MSG\_DAYS*

*ARCHIVAL\_PERIOD*

*CONCHAR\_PWD\_NUM*

*FREQ\_PWD\_CHG*

*MIN\_PWD\_NUMERIC\_LENGTH*

*LEGAL\_NOTICE*

*DORMANCY\_DAYS*

*DISPLAY\_LEGAL\_NOTICE*

*MIN\_SPECIALCHAR\_LENGTH*

*MIN\_LOWERCASE\_CHAR*

*MIN\_UPPERCASE\_CHAR*

*SCREESAVERREQUIRED*

*SCREESAVERTIMEOUTINSECONDS*

*SCREESAVERMODIFIABLEBYUSER*

*PASSWORDEXTERNAL*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Smtbs-Branch-Restr*

*RESTR\_TYPE*

*DESCRIPTION*

*Smtbs-Restrictive-Passwd*

*PASSWORD*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

**CREATESMDBANKP\_FSFS\_RES**

Attribute	Description
Name	CREATESMDBANKP_FSFS_RES
Datatype	
Description	

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

**SOURCE**

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

**UBSCOMP**

Attribute	Description
Name	UBSCOMP
Datatype	string

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

## MSGID

Attribute	Description					
Name	MSGID					
Datatype	string					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

## CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	string					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

## USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

## Smtbs-Parameters-Full

Attribute	Description
Name	Smtbs-Parameters-Full
Datatype	
Description	

## HEAD\_OFFICE

Attribute	Description				
Name	HEAD_OFFICE				
Datatype	string				
Description	Indicates Head Office				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## SITE\_CODE

Attribute	Description				
Name	SITE_CODE				
Datatype	string				
Description	Indicates Site Code				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>4</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	4
Restrictions	Description				
maxLength	4				

## ACTIVATION\_KEY

Attribute	Description				
Name	ACTIVATION_KEY				
Datatype	string				
Description	Indicates Activation Key				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>24</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	24
Restrictions	Description				
maxLength	24				

## INVALID\_LOGINS\_CUM

Attribute	Description								
Name	INVALID_LOGINS_CUM								
Datatype	decimal								
Description	Indicates Cumulative								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>2</td> </tr> <tr> <td>minInclusive</td> <td>6</td> </tr> <tr> <td>maxInclusive</td> <td>99</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	2	minInclusive	6	maxInclusive	99
Restrictions	Description								
totalDigits	2								
minInclusive	6								
maxInclusive	99								

## INVALID\_LOGINS\_SUC

Attribute	Description								
Name	INVALID_LOGINS_SUC								
Datatype	decimal								
Description	Indicates Successive								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>1</td></tr><tr><td>minInclusive</td><td>3</td></tr><tr><td>maxInclusive</td><td>5</td></tr></tbody></table>	Restrictions	Description	totalDigits	1	minInclusive	3	maxInclusive	5
Restrictions	Description								
totalDigits	1								
minInclusive	3								
maxInclusive	5								

## PWD\_PREVENT\_REUSE

Attribute	Description						
Name	PWD_PREVENT_REUSE						
Datatype	decimal						
Description	Indicates Password Repetitions						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	2	minInclusive	1
Restrictions	Description						
totalDigits	2						
minInclusive	1						

## PWD\_CHANGE\_AFTER

Attribute	Description								
Name	PWD_CHANGE_AFTER								
Datatype	decimal								
Description	Indicates Force Password Change After								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>3</td></tr><tr><td>minInclusive</td><td>15</td></tr><tr><td>maxInclusive</td><td>180</td></tr></tbody></table>	Restrictions	Description	totalDigits	3	minInclusive	15	maxInclusive	180
Restrictions	Description								
totalDigits	3								
minInclusive	15								
maxInclusive	180								

## MAXIMUM

Attribute	Description								
Name	MAXIMUM								
Datatype	decimal								
Description	Indicates Maximum								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>12</td></tr><tr><td>maxInclusive</td><td>30</td></tr></tbody></table>	Restrictions	Description	totalDigits	2	minInclusive	12	maxInclusive	30
Restrictions	Description								
totalDigits	2								
minInclusive	12								
maxInclusive	30								

## MINIMUM

Attribute	Description								
Name	MINIMUM								
Datatype	decimal								
Description	Indicates Minimum								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>6</td></tr><tr><td>maxInclusive</td><td>11</td></tr></tbody></table>	Restrictions	Description	totalDigits	2	minInclusive	6	maxInclusive	11
Restrictions	Description								
totalDigits	2								
minInclusive	6								
maxInclusive	11								

## PWD\_EXPIRY\_MSG\_DAYS

Attribute	Description								
Name	PWD_EXPIRY_MSG_DAYS								
Datatype	decimal								
Description	Indicates Intimate User (Before Password Expiry)								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>1</td></tr><tr><td>maxInclusive</td><td>5</td></tr></tbody></table>	Restrictions	Description	totalDigits	2	minInclusive	1	maxInclusive	5
Restrictions	Description								
totalDigits	2								
minInclusive	1								
maxInclusive	5								

## ARCHIVAL\_PERIOD

Attribute	Description				
Name	ARCHIVAL_PERIOD				
Datatype	decimal				
Description	Indicates Archival Period (in days)				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>3</td></tr></tbody></table>	Restrictions	Description	totalDigits	3
Restrictions	Description				
totalDigits	3				

## CONCHAR\_PWD\_NUM

Attribute	Description				
Name	CONCHAR_PWD_NUM				
Datatype	decimal				
Description	Indicates Maximum Consecutive Repetitive Characters				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>2</td></tr></tbody></table>	Restrictions	Description	totalDigits	2
Restrictions	Description				
totalDigits	2				

## FREQ\_PWD\_CHG

Attribute	Description						
Name	FREQ_PWD_CHG						
Datatype	decimal						
Description	Indicates Minimum Days Between Password Changes						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>0</td></tr></tbody></table>	Restrictions	Description	totalDigits	2	minInclusive	0
Restrictions	Description						
totalDigits	2						
minInclusive	0						

## MIN\_PWD\_NUMERIC\_LENGTH

Attribute	Description						
Name	MIN_PWD_NUMERIC_LENGTH						
Datatype	decimal						
Description	Indicates Minimum Number Of Numeric Characters In Password						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	2	minInclusive	1
Restrictions	Description						
totalDigits	2						
minInclusive	1						

## LEGAL\_NOTICE

Attribute	Description				
Name	LEGAL_NOTICE				
Datatype	string				
Description	Indicates Warning Screen Text				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>4000</td></tr></tbody></table>	Restrictions	Description	maxLength	4000
Restrictions	Description				
maxLength	4000				

## DORMANCY\_DAYS

Attribute	Description						
Name	DORMANCY_DAYS						
Datatype	decimal						
Description	Indicates Dormancy Days						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	2	minInclusive	1
Restrictions	Description						
totalDigits	2						
minInclusive	1						

## DISPLAY\_LEGAL\_NOTICE

Attribute	Description				
Name	DISPLAY_LEGAL_NOTICE				
Datatype	string				
Description	Indicates Display Legal Notice Y - on N - Off				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>Y,N</td></tr></tbody></table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## MIN\_SPECIALCHAR\_LENGTH

Attribute	Description						
Name	MIN_SPECIALCHAR_LENGTH						
Datatype	decimal						
Description	Indicates Minimum Number Of Special Characters In Password						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	2	minInclusive	1
Restrictions	Description						
totalDigits	2						
minInclusive	1						

## MIN\_LOWERCASE\_CHAR

Attribute	Description						
Name	MIN_LOWERCASE_CHAR						
Datatype	decimal						
Description	Indicates Minimum Number of LowerCase Characters in Password						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	2	minInclusive	1
Restrictions	Description						
totalDigits	2						
minInclusive	1						

## MIN\_UPPERCASE\_CHAR

Attribute	Description						
Name	MIN_UPPERCASE_CHAR						
Datatype	decimal						
Description	Indicates Minimum Number of UpperCase Characters in Password						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	2	minInclusive	1
Restrictions	Description						
totalDigits	2						
minInclusive	1						

## SCREENSAVERREQUIRED

Attribute	Description
Name	SCREENSAVERREQUIRED
Datatype	string
Description	Indicates Screensaver Required Y - on N - Off

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SCREENSAVERTIMEOUTINSECONDS

<b>Attribute</b>	<b>Description</b>	
Name	SCREENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description	Indicates Screensaver Interval (in seconds)	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## SCREENSAVERMODIFIABLEBYUSER

<b>Attribute</b>	<b>Description</b>	
Name	SCREENSAVERMODIFIABLEBYUSER	
Datatype	string	
Description	Indicates Screensaver Interval Modifiable at User Level Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PASSWORDEXTERNAL

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORDEXTERNAL	
Datatype	string	
Description	Indicates Password External Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	

Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	



Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## Smtbs-Branch-Restr

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Branch-Restr	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## RESTR\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_TYPE	
Datatype	string	
Description	Indicates Restriction Type	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Restriction Type Description	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

## Smtbs-Restrictive-Passwd

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Restrictive-Passwd	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description	Indicates Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

## EDESC

Attribute	Description	
Name	EDESC	

Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

### 2.7.4.SM-CreateSMDBANKP-Res-PK-MSG.xsd

*CREATESMDBANKP\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Smtbs-Parameters-PK*  
*SITE\_CODE*  
*Smtbs-Parameters-IO*  
*HEAD\_OFFICE*  
*SITE\_CODE*  
*ACTIVATION\_KEY*  
*INVALID\_LOGINS\_CUM*  
*INVALID\_LOGINS\_SUC*  
*PWD\_PREVENT\_REUSE*  
*PWD\_CHANGE\_AFTER*  
*MAXIMUM*  
*MINIMUM*  
*PWD\_EXPIRY\_MSG\_DAYS*  
*ARCHIVAL\_PERIOD*  
*CONCHAR\_PWD\_NUM*  
*FREQ\_PWD\_CHG*  
*MIN\_PWD\_NUMERIC\_LENGTH*  
*LEGAL\_NOTICE*  
*DORMANCY\_DAYS*

*DISPLAY\_LEGAL\_NOTICE*

*MIN\_SPECIALCHAR\_LENGTH*

*MIN\_LOWERCASE\_CHAR*

*MIN\_UPPERCASE\_CHAR*

*SCREENSAVERREQUIRED*

*SCREENSAVERTIMEOUTINSECONDS*

*SCREENSAVERMODIFIABLEBYUSER*

*Smtbs-Branch-Restr*

*RESTR\_TYPE*

*DESCRIPTION*

*Smtbs-Restrictive-Passwd*

*PASSWORD*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## **CREATESMDBANKP\_IOPK\_RES**

<b>Attribute</b>	<b>Description</b>
Name	CREATESMDBANKP_IOPK_RES
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	string	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

## Smtbs-Parameters-PK

Attribute	Description
Name	Smtbs-Parameters-PK
Datatype	
Description	

## SITE\_CODE

Attribute	Description				
Name	SITE_CODE				
Datatype	string				
Description	Indicates Site Code				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>4</td></tr></tbody></table>	Restrictions	Description	maxLength	4
Restrictions	Description				
maxLength	4				

## Smtbs-Parameters-IO

Attribute	Description
Name	Smtbs-Parameters-IO
Datatype	
Description	

## HEAD\_OFFICE

Attribute	Description				
Name	HEAD_OFFICE				
Datatype	string				
Description	Indicates Head Office				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## SITE\_CODE

Attribute	Description
Name	SITE_CODE
Datatype	string

Description	Indicates Site Code	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

## ACTIVATION\_KEY

<b>Attribute</b>	<b>Description</b>	
Name	ACTIVATION_KEY	
Datatype	string	
Description	Indicates Activation Key	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	24

## INVALID\_LOGINS\_CUM

<b>Attribute</b>	<b>Description</b>	
Name	INVALID_LOGINS_CUM	
Datatype	decimal	
Description	Indicates Cumulative	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	6
	maxInclusive	99

## INVALID\_LOGINS\_SUC

<b>Attribute</b>	<b>Description</b>	
Name	INVALID_LOGINS_SUC	
Datatype	decimal	
Description	Indicates Successive	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	1
	minInclusive	3
	maxInclusive	5

## PWD\_PREVENT\_REUSE

<b>Attribute</b>	<b>Description</b>	
Name	PWD_PREVENT_REUSE	
Datatype	decimal	

Description	Indicates Password Repetitions	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## PWD\_CHANGE\_AFTER

<b>Attribute</b>	<b>Description</b>	
Name	PWD_CHANGE_AFTER	
Datatype	decimal	
Description	Indicates Force Password Change After	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	3
	minInclusive	15
	maxInclusive	180

## MAXIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MAXIMUM	
Datatype	decimal	
Description	Indicates Maximum	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	12
	maxInclusive	30

## MINIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MINIMUM	
Datatype	decimal	
Description	Indicates Minimum	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	6
	maxInclusive	11

## PWD\_EXPIRY\_MSG\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	PWD_EXPIRY_MSG_DAYS	
Datatype	decimal	
Description	Indicates Intimate User (Before Password Expiry)	

Attribute	<b>Attribute</b>		<b>Description</b>	
	minOccurs		0	
Restrictions	<b>Restrictions</b>		<b>Description</b>	
	totalDigits		2	
	minInclusive		1	
	maxInclusive		5	

## ARCHIVAL\_PERIOD

<b>Attribute</b>		<b>Description</b>		
Name		ARCHIVAL_PERIOD		
Datatype		decimal		
Description		Indicates Archival Period (in days)		
Attribute	<b>Attribute</b>		<b>Description</b>	
	minOccurs		0	
Restrictions	<b>Restrictions</b>		<b>Description</b>	
	totalDigits		3	

## CONCHAR\_PWD\_NUM

<b>Attribute</b>		<b>Description</b>		
Name		CONCHAR_PWD_NUM		
Datatype		decimal		
Description		Indicates Maximum Consecutive Repetitive Characters		
Attribute	<b>Attribute</b>		<b>Description</b>	
	minOccurs		0	
Restrictions	<b>Restrictions</b>		<b>Description</b>	
	totalDigits		2	

## FREQ\_PWD\_CHG

<b>Attribute</b>		<b>Description</b>		
Name		FREQ_PWD_CHG		
Datatype		decimal		
Description		Indicates Minimum Days Between Password Changes		
Attribute	<b>Attribute</b>		<b>Description</b>	
	minOccurs		0	
Restrictions	<b>Restrictions</b>		<b>Description</b>	
	totalDigits		2	
	minInclusive		0	

## MIN\_PWD\_NUMERIC\_LENGTH

Attribute	Description						
Name	MIN_PWD_NUMERIC_LENGTH						
Datatype	decimal						
Description	Indicates Minimum Number Of Numeric Characters In Password						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>2</td> </tr> <tr> <td>minInclusive</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	2	minInclusive	1
Restrictions	Description						
totalDigits	2						
minInclusive	1						

## LEGAL\_NOTICE

Attribute	Description				
Name	LEGAL_NOTICE				
Datatype	string				
Description	Indicates Warning Screen Text				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>4000</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	4000
Restrictions	Description				
maxLength	4000				

## DORMANCY\_DAYS

Attribute	Description						
Name	DORMANCY_DAYS						
Datatype	decimal						
Description	Indicates Dormancy Days						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>2</td> </tr> <tr> <td>minInclusive</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	2	minInclusive	1
Restrictions	Description						
totalDigits	2						
minInclusive	1						

## DISPLAY\_LEGAL\_NOTICE

Attribute	Description				
Name	DISPLAY_LEGAL_NOTICE				
Datatype	string				
Description	Indicates Display Legal Notice Y - on N - Off				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Y,N</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## MIN\_SPECIALCHAR\_LENGTH

Attribute	Description
-----------	-------------



Name	MIN_SPECIALCHAR_LENGTH	
Datatype	decimal	
Description	Indicates Minimum Number Of Special Characters In Password	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## MIN\_LOWERCASE\_CHAR

<b>Attribute</b>	<b>Description</b>	
Name	MIN_LOWERCASE_CHAR	
Datatype	decimal	
Description	Indicates Minimum Number of LowerCase Characters in Password	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## MIN\_UPPERCASE\_CHAR

<b>Attribute</b>	<b>Description</b>	
Name	MIN_UPPERCASE_CHAR	
Datatype	decimal	
Description	Indicates Minimum Number of UpperCase Characters in Password	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## SCRENSAVERREQUIRED

<b>Attribute</b>	<b>Description</b>	
Name	SCRENSAVERREQUIRED	
Datatype	string	
Description	Indicates Screensaver Required Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SCRENSAVERTIMEOUTINSECONDS

<b>Attribute</b>	<b>Description</b>	
Name	SCRENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description	Indicates Screensaver Interval (in seconds)	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## SCRENSAVERMODIFIABLEBYUSER

<b>Attribute</b>	<b>Description</b>	
Name	SCRENSAVERMODIFIABLEBYUSER	
Datatype	string	
Description	Indicates Screensaver Interval Modifiable at User Level Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## Smtbs-Branch-Restr

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Branch-Restr	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## RESTR\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_TYPE	
Datatype	string	
Description	Indicates Restriction Type	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Restriction Type Description	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

### Smtbs-Restrictive-Passwd

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Restrictive-Passwd	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description	Indicates Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

### FLDVAL

<b>Attribute</b>	<b>Description</b>
Name	FLDVAL

Datatype	string	
Description	Indicates Field Value	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

## 2.8.CreateSMDRLMNE

### 2.8.1.SM-CreateSMDRLMNE-Req-Full-MSG.xsd

*CREATESMDRLMNE\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Role-Limit-Full*

*ROLEID2*

*DESCRIPTION*

*LIMIT\_CCY*

*INPUT\_LIMIT*

*AUTHORIZATION\_LIMIT*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

#### **CREATESMDRLMNE\_FSFS\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	CREATESMDRLMNE_FSFS_REQ
Datatype	
Description	

#### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

#### **SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	string	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of CreateSMDRLMNE

## Smtbs-Role-Limit-Full

Attribute	Description
Name	Smtbs-Role-Limit-Full
Datatype	
Description	

## ROLEID2

Attribute	Description				
Name	ROLEID2				
Datatype	string				
Description	Indicates Role Id				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## DESCRIPTION

Attribute	Description				
Name	DESCRIPTION				
Datatype	string				
Description	Indicates Description				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

## LIMIT\_CCY

Attribute	Description				
Name	LIMIT_CCY				
Datatype	string				
Description	Indicates Limit Currency				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## INPUT\_LIMIT

Attribute	Description	
Name	INPUT_LIMIT	
Datatype	decimal	
Description	Indicates Input Limit	
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	22
	minInclusive	0

## AUTHORIZATION\_LIMIT

Attribute	Description	
Name	AUTHORIZATION_LIMIT	
Datatype	decimal	
Description	Indicates Authorization Limit	
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	22
	minInclusive	0

## MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	12

## MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	35

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
Restrictions	<b>Restrictions</b>	<b>Description</b>
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
Restrictions	<b>Restrictions</b>	<b>Description</b>
	minLength	0

### 2.8.2.SM-CreateSMDRLMNE-Req-IO-MSG.xsd

*CREATESMDRLMNE\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
     *PARAM*  
         *NAME*  
         *VALUE*  
*FCUBS\_BODY*  
     *Smtbs-Role-Limit-IO*  
         *ROLEID2*  
         *DESCRIPTION*  
         *LIMIT\_CCY*  
         *INPUT\_LIMIT*  
         *AUTHORIZATION\_LIMIT*  
         *UDFDETAILS*  
             *FLDNAM*  
             *FLDVAL*

**CREATESMDRLMNE\_IOPK\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	CREATESMDRLMNE_IOPK_REQ
Datatype	
Description	

**FCUBS\_HEADER**



Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of CreateSMDRLMNE

## Smtbs-Role-Limit-IO

Attribute	Description
Name	Smtbs-Role-Limit-IO
Datatype	
Description	

## ROLEID2

Attribute	Description				
Name	ROLEID2				
Datatype	string				
Description	Indicates Role Id				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## DESCRIPTION

Attribute	Description				
Name	DESCRIPTION				
Datatype	string				
Description	Indicates Description				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

## LIMIT\_CCY

Attribute	Description				
Name	LIMIT_CCY				
Datatype	string				
Description	Indicates Limit Currency				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## INPUT\_LIMIT

Attribute	Description	
Name	INPUT_LIMIT	
Datatype	decimal	
Description	Indicates Input Limit	
Restrictions	Restrictions	Description
	totalDigits	22
	minInclusive	0

## AUTHORIZATION\_LIMIT

Attribute	Description	
Name	AUTHORIZATION_LIMIT	
Datatype	decimal	
Description	Indicates Authorization Limit	
Restrictions	Restrictions	Description
	totalDigits	22
	minInclusive	0

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

*CREATESMDRLMNE\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Role-Limit-Full*

*ROLEID2*

*DESCRIPTION*

*LIMIT\_CCY*

*INPUT\_LIMIT*

*AUTHORIZATION\_LIMIT*

*MAKER*

*MAKERSTAMP*



CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS\_ERROR\_RESP

ERROR

ECODE

EDESC

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## CREATESMDRLMNE\_FSFS\_RES

Attribute	Description
Name	CREATESMDRLMNE_FSFS_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	string				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## USERID

Attribute	Description
Name	USERID

Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
pattern	[A-Z_0-9]*	

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
pattern	[a-zA-Z_0-9]{3}	

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

## Smtbs-Role-Limit-Full

Attribute	Description
Name	Smtbs-Role-Limit-Full
Datatype	
Description	

## ROLEID2

Attribute	Description				
Name	ROLEID2				
Datatype	string				
Description	Indicates Role Id				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>15</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	15
	Restrictions	Description			
maxLength	15				

## DESCRIPTION

Attribute	Description				
Name	DESCRIPTION				
Datatype	string				
Description	Indicates Description				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>105</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	105
	Restrictions	Description			
maxLength	105				

## LIMIT\_CCY

Attribute	Description				
Name	LIMIT_CCY				
Datatype	string				
Description	Indicates Limit Currency				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

## INPUT\_LIMIT

Attribute	Description						
Name	INPUT_LIMIT						
Datatype	decimal						
Description	Indicates Input Limit						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> <tr> <td>minInclusive</td> <td>0</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22	minInclusive	0
	Restrictions	Description					
	totalDigits	22					
minInclusive	0						

## AUTHORIZATION\_LIMIT

Attribute	Description
Name	AUTHORIZATION_LIMIT
Datatype	decimal
Description	Indicates Authorization Limit

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		



Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	ECODE
Datatype	String
Description	

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

### 2.8.4.SM-CreateSMDRLMNE-Res-PK-MSG.xsd

*CREATESMDRLMNE\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Smtbs-Role-Limit-PK*  
*ROLEID2*  
*Smtbs-Role-Limit-IO*  
*ROLEID2*  
*DESCRIPTION*  
*LIMIT\_CCY*  
*INPUT\_LIMIT*  
*AUTHORIZATION\_LIMIT*  
*UDFDETAILS*  
*FLDNAM*  
*FLDVAL*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*

EDESC

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

### CREATESMDRLMNE\_IOPK\_RES

Attribute	Description
Name	CREATESMDRLMNE_IOPK_RES
Datatype	
Description	

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

### SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

### UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

### MSGID

Attribute	Description
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	string				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	string
Description	This is the user id in the Source system who is performing the action.

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION



Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

## FCUBS\_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about PK Response	

## Smtbs-Role-Limit-PK

Attribute	Description	
Name	Smtbs-Role-Limit-PK	
Datatype		
Description		

## ROLEID2

Attribute	Description	
Name	ROLEID2	
Datatype	string	
Description	Indicates Role Id	
Restrictions	Restrictions	Description
	maxLength	15

## Smtbs-Role-Limit-IO

Attribute	Description	
Name	Smtbs-Role-Limit-IO	
Datatype		
Description		

## ROLEID2

Attribute	Description	

Name	ROLEID2	
Datatype	string	
Description	Indicates Role Id	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## LIMIT\_CCY

<b>Attribute</b>	<b>Description</b>	
Name	LIMIT_CCY	
Datatype	string	
Description	Indicates Limit Currency	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## INPUT\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	INPUT_LIMIT	
Datatype	decimal	
Description	Indicates Input Limit	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0

## AUTHORIZATION\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHORIZATION_LIMIT	
Datatype	decimal	
Description	Indicates Authorization Limit	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
		<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	
		<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	
		<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
		<b>Description</b>
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	
		<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	
		<b>Description</b>
	maxOccurs	unbounded

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

## 2.9.CreateSMRole

### 2.9.1.SM-CreateSMRole-Req-Full-MSG.xsd

[\*CREATESMROLE\\_FSFS\\_REQ\*](#)

[\*FCUBS\\_HEADER\*](#)

[\*SOURCE\*](#)

[\*UBSCOMP\*](#)

*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*ROLEMASTER-Full*  
*ROLEIDENTIFICATION*  
*MASTERROLEDESC*  
*AUTHORISERROLE*  
*BRANCH\_RES*  
*ACCCLASSALLOWED*  
*CENTRALISATIONROLE*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*

*TXNSTAT*

*AUTHSTAT*

*ROLEDETAIL*

*ROLEFUN*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*CONTROL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CONTROL15*

*CONTROL16*

*ROLEDETAILB*

*ROLEFUN*

*CONT1*

*CONT2*

*CONT3*

*CONT4*

*CONT5*

*CONT6*

*CONTROL7*

*CONT8*

*CONT9*

*CONT10*

*CONT11*

*CONT12*

*CONT13*

*CONT14*

*CONT15*

*CONTROL16*

*ROLEDETAILC*

*ROLEFUN*

*CNTRL1*

*CNTRL2*

*CNTRL3*

*CNTRL4*

*CNTRL5*

*CNTRL6*

*CNTRL7*

*CNTRL8*

*CNTRL9*

*CNTRL10*

*CNTRL11*

*CNTRL12*

*CNTRL13*

*CNTRL14*

*CNTRL15*

*CNTRL16*

*ROLEDETAILD*

*ROLEFUN*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*



*CONTROL7*

*CONTROL8*

*CONTROL9*

*CONTROL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CNTRL15*

*CNTRL16*

*ROLEBRANCHES*

*BRANCH*

*BRNNAME*

*ROLEACCCLASS*

*ACCCLS*

*DESCRIPTION*

*MSGCRIGHTS*

*CNL*

*CHGNODE*

*REL*

*CHGMEDIA*

*BRNMOV*

*HLD*

*TSTINP*

*CHGADDR*

*REINS*

*CHGPRIOR*

*CNLAUTH*

*CHGNODEAUTH*

*RELAUTH*

*CHGMEDIAAUTH*

*BRNMOVAUTH*

*HLDAUTH*  
*TSTINPAUTH*  
*CHGADDRAUTH*  
*REINSAUTH*  
*CHGPRIORAUTH*  
*GEN*  
*TSTCHK*  
*LNKCONT*  
*CHGBRNIN*  
*CHGMSG*  
*CHGFORCRELFUND*  
*SUPPRESS*  
*DELMSG*  
*PRNT*  
*FTUPL*  
*MOVQ*  
*CHGADDRIN*  
*CHGMSGAUTH*  
*AUTHRGHTS*  
*CHGFORCCOVMATCH*  
*QUEUERIGHTS*  
*QUEUE*  
*RESTRICTIVEPASSWD*  
*PWD*  
*PWDID*  
*ROLEBRANCHLIMITS*  
*LMTCCY*  
*BRHUSERLMT*  
*Roledetaile*  
*ROLEFUN*  
*BRANCHCODE*  
*EDITABLE*

*CNTRLSTR*

*Roledetailf*

*ROLEID*

*ROLEFUN*

*CNTRLSTR*

*CNTRL1*

*CNTRL10*

*CNTRL11*

*CNTRL12*

*CNTRL13*

*CNTRL14*

*CNTRL15*

*CNTRL16*

*CNTRL2*

*CNTRL3*

*CNTRL4*

*CNTRL5*

*CNTRL6*

*CNTRL7*

*CNTRL8*

*CNTRL9*

*ATHSTAT*

*BRNCHCODE*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

**CREATESMROLE\_FSFS\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	CREATESMROLE_FSFS_REQ
Datatype	
Description	

**FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		



## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of CreateSMRole

## ROLEMASTER-Full

Attribute	Description
Name	ROLEMASTER-Full
Datatype	
Description	

## ROLEIDENTIFICATION

Attribute	Description				
Name	ROLEIDENTIFICATION				
Datatype	string				
Description	Indicates Role Id				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## MASTERROLEDESC

Attribute	Description				
Name	MASTERROLEDESC				
Datatype	string				
Description	Indicates Role Description				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

## AUTHORISERROLE

Attribute	Description				
Name	AUTHORISERROLE				
Datatype	string				
Description	Indicates Authorizer Role Y - on N - Off				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRANCH\_RES

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_RES	
Datatype	string	
Description	Indicates Branch Restriction A - Allowed D - Disallowed	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## ACCCLASSALLOWED

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLASSALLOWED	
Datatype	string	
Description	Indicates Account Class Restriction A - Allowed D - Disallowed	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## CENTRALISATIONROLE

<b>Attribute</b>	<b>Description</b>	
Name	CENTRALISATIONROLE	
Datatype	string	
Description	Indicates Centralisation Role Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## ROLEDETAIL

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAIL	
Datatype		
Description	Maintenance	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

### CONTROL1

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL4

<b>Attribute</b>	<b>Description</b>
Name	CONTROL4

Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL6

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL8

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL8	
Datatype	decimal	
Description	Indicates Auth 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL10

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL11

Attribute		Description	
Name		CONTROL11	
Datatype		decimal	
Description		Indicates Confirm 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL12

Attribute		Description	
Name		CONTROL12	
Datatype		decimal	
Description		Indicates Liquidate 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL13

Attribute		Description	
Name		CONTROL13	
Datatype		decimal	
Description		Indicates Hold 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL14

Attribute		Description	
Name		CONTROL14	
Datatype		decimal	
Description		Indicates Template 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL15

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEDETAILB

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILB	
Datatype		
Description	Roles	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

### CONT1

<b>Attribute</b>	<b>Description</b>	
Name	CONT1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT2

<b>Attribute</b>	<b>Description</b>	
Name	CONT2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT3

<b>Attribute</b>	<b>Description</b>	
Name	CONT3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT4

<b>Attribute</b>	<b>Description</b>
Name	CONT4

Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT5

<b>Attribute</b>	<b>Description</b>	
Name	CONT5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT6

<b>Attribute</b>	<b>Description</b>	
Name	CONT6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT8

<b>Attribute</b>	<b>Description</b>	
Name	CONT8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT9

<b>Attribute</b>	<b>Description</b>	
Name	CONT9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT10

<b>Attribute</b>	<b>Description</b>	
Name	CONT10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT11

Attribute		Description	
Name		CONT11	
Datatype		decimal	
Description		Indicates Confirm 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONT12

Attribute		Description	
Name		CONT12	
Datatype		decimal	
Description		Indicates Liquidate 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONT13

Attribute		Description	
Name		CONT13	
Datatype		decimal	
Description		Indicates Hold 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONT14

Attribute		Description	
Name		CONT14	
Datatype		decimal	
Description		Indicates Template 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT15

<b>Attribute</b>	<b>Description</b>	
Name	CONT15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEDETAILC

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILC	
Datatype		
Description	Batch	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

### CNTRL1

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL2

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL3

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL4

<b>Attribute</b>	<b>Description</b>
Name	CNTRL4

Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL5

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL6

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL7

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL8

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL9

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL10

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL11

Attribute		Description	
Name		CNTRL11	
Datatype		decimal	
Description		Indicates Confirm 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CNTRL12

Attribute		Description	
Name		CNTRL12	
Datatype		decimal	
Description		Indicates Liquidate 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CNTRL13

Attribute		Description	
Name		CNTRL13	
Datatype		decimal	
Description		Indicates Hold 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CNTRL14

Attribute		Description	
Name		CNTRL14	
Datatype		decimal	
Description		Indicates Template 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL15

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL16

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEDETAILD

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILD	
Datatype		
Description	Roles	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

### CONTROL1

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL4

<b>Attribute</b>	<b>Description</b>
Name	CONTROL4

Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL6

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL8

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL8	
Datatype	decimal	
Description	Indicates Auth 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL10

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL11

Attribute		Description	
Name		CONTROL11	
Datatype		decimal	
Description		Indicates Confirm 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL12

Attribute		Description	
Name		CONTROL12	
Datatype		decimal	
Description		Indicates Liquidate 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL13

Attribute		Description	
Name		CONTROL13	
Datatype		decimal	
Description		Indicates Hold 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL14

Attribute		Description	
Name		CONTROL14	
Datatype		decimal	
Description		Indicates Template 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL15

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL16

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEBRANCHES

<b>Attribute</b>	<b>Description</b>	
Name	ROLEBRANCHES	
Datatype		
Description	Branches	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	Indicates Branch	



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## BRNNAME

<b>Attribute</b>	<b>Description</b>	
Name	BRNNAME	
Datatype	string	
Description	Indicates Branch Name	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## ROLEACCCLASS

<b>Attribute</b>	<b>Description</b>	
Name	ROLEACCCLASS	
Datatype		
Description	Acc Class Restriction	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ACCCLS

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLS	
Datatype	string	
Description	Indicates Account Class	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Account Class Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## MSGCRIGHTS

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	MSGCRIGHTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## CNL

<b>Attribute</b>	<b>Description</b>	
Name	CNL	
Datatype	string	
Description	Indicates Cancel Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODE

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODE	
Datatype	string	
Description	Indicates Change Node Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REL

<b>Attribute</b>	<b>Description</b>	
Name	REL	
Datatype	string	
Description	Indicates Release Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIA

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIA	
Datatype	string	
Description	Indicates Change Media Y - on N - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOV

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOV	
Datatype	string	
Description	Indicates Branch Move Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLD

<b>Attribute</b>	<b>Description</b>	
Name	HLD	
Datatype	string	
Description	Indicates Hold Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINP

<b>Attribute</b>	<b>Description</b>	
Name	TSTINP	
Datatype	string	
Description	Indicates Test Input Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDR

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDR	
Datatype	string	
Description	Indicates Change Address Y - on N - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINS

<b>Attribute</b>	<b>Description</b>	
Name	REINS	
Datatype	string	
Description	Indicates Reinstatement Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIOR

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIOR	
Datatype	string	
Description	Indicates Change Priority Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNLAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CNLAUTH	
Datatype	string	
Description	Indicates Auth Cancel Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODEAUTH	
Datatype	string	
Description	Indicates Auth Change Node Y - on N - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## RELAUTH

<b>Attribute</b>	<b>Description</b>	
Name	RELAUTH	
Datatype	string	
Description	Indicates Release Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIAAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIAAUTH	
Datatype	string	
Description	Indicates Change Media Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOVAUTH

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOVAUTH	
Datatype	string	
Description	Indicates Auth Branch Move Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLDAUTH

<b>Attribute</b>	<b>Description</b>
Name	HLDAUTH
Datatype	string

Description	Indicates Hold Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINPAUTH

<b>Attribute</b>	<b>Description</b>	
Name	TSTINPAUTH	
Datatype	string	
Description	Indicates Auth Test Input Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRAUTH	
Datatype	string	
Description	Indicates Change Address Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINSAUTH

<b>Attribute</b>	<b>Description</b>	
Name	REINSAUTH	
Datatype	string	
Description	Indicates Auth Reinstate Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIORAUTH

<b>Attribute</b>	<b>Description</b>
Name	CHGPRIORAUTH

Datatype	string	
Description	Indicates Change Priority Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## GEN

<b>Attribute</b>	<b>Description</b>	
Name	GEN	
Datatype	string	
Description	Indicates Install Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTCHK

<b>Attribute</b>	<b>Description</b>	
Name	TSTCHK	
Datatype	string	
Description	Indicates Test Check Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## LNKCONT

<b>Attribute</b>	<b>Description</b>	
Name	LNKCONT	
Datatype	string	
Description	Indicates Link Contract Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGBRNIN

<b>Attribute</b>	<b>Description</b>
Name	CHGBRNIN

Datatype	string	
Description	Indicates Change Branch In Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSG

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSG	
Datatype	string	
Description	Indicates Change Message Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGFORCRELFUND

<b>Attribute</b>	<b>Description</b>	
Name	CHGFORCRELFUND	
Datatype	string	
Description	Indicates Change Force Release Fund Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SUPPRESS

<b>Attribute</b>	<b>Description</b>	
Name	SUPPRESS	
Datatype	string	
Description	Indicates Suppress Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DELMSG



Attribute	Description	
Name	DELMSG	
Datatype	string	
Description	Indicates Delete Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PRNT

Attribute	Description	
Name	PRNT	
Datatype	string	
Description	Indicates Print Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## FTUPL

Attribute	Description	
Name	FTUPL	
Datatype	string	
Description	Indicates FT Upload Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MOVQ

Attribute	Description	
Name	MOVQ	
Datatype	string	
Description	Indicates Move To Queue Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRIN

Attribute	Description	
Name	CHGADDRIN	
Datatype	string	
Description	Indicates Change Address In Y - on N - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGMSGAUTH

Attribute	Description	
Name	CHGMSGAUTH	
Datatype	string	
Description	Indicates Auth Change Message Y - on N - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## AUTHRGHTS

Attribute	Description	
Name	AUTHRGHTS	
Datatype	string	
Description	Indicates Auth Rights Y - on N - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGFORCCOVMATCH

Attribute	Description	
Name	CHGFORCCOVMATCH	
Datatype	string	
Description	Indicates Change Force Cover Match Y - on N - Off	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## QUEUERIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	QUEUERIGHTS	
Datatype		
Description	Queues	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## QUEUE

<b>Attribute</b>	<b>Description</b>	
Name	QUEUE	
Datatype	string	
Description	Indicates Queue	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## RESTRICTIVEPASSWD

<b>Attribute</b>	<b>Description</b>	
Name	RESTRICTIVEPASSWD	
Datatype		
Description	Restricted Password	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PWD

<b>Attribute</b>	<b>Description</b>	
Name	PWD	
Datatype	string	
Description	Indicates Password	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## PWDID

<b>Attribute</b>	<b>Description</b>	
Name	PWDID	
Datatype	string	
Description	Indicates Id	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## ROLEBRANCHLIMITS

<b>Attribute</b>	<b>Description</b>	
Name	ROLEBRANCHLIMITS	
Datatype		
Description	User Limits	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxOccurs	unbounded

## LMTCCY

<b>Attribute</b>	<b>Description</b>	
Name	LMTCCY	
Datatype	string	
Description	Indicates Limit Currency	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## BRHUSERLMT

<b>Attribute</b>	<b>Description</b>	
Name	BRHUSERLMT	
Datatype	decimal	
Description	Indicates User Limit	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## Roledetaile

<b>Attribute</b>	<b>Description</b>	
Name	Roledetaile	
Datatype		
Description	Process Stage Rights	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxOccurs	unbounded

## ROLEFUN

Attribute	Description	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	string	
Description	Indicates Branch Code	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## EDITABLE

Attribute	Description	
Name	EDITABLE	
Datatype	decimal	
Description	Indicates Editable 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CNTRLSTR

Attribute	Description	
Name	CNTRLSTR	
Datatype	string	
Description	Indicates Control String	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

## Roledetailf

Attribute	Description	
Name	Roledetailf	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded

## ROLEID

Attribute	Description	
Name	ROLEID	
Datatype	string	
Description	Indicates Role Function	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	15

## ROLEFUN

Attribute	Description	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	8

## CNTRLSTR

Attribute	Description	
Name	CNTRLSTR	
Datatype	string	
Description	Indicates Control String	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	16

## CNTRL1

Attribute	Description
Name	CNTRL1
Datatype	decimal

Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL10

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL11

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL12

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL12	
Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL13**

Attribute	Description	
Name	CNTRL13	
Datatype	decimal	
Description	Indicates Hold 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL14**

Attribute	Description	
Name	CNTRL14	
Datatype	decimal	
Description	Indicates Template 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL15**

Attribute	Description	
Name	CNTRL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL16**

Attribute	Description	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	



Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL2

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL3

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL4

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL5**

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL6**

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL7**

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL8**

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL9

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ATHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	ATHSTAT	
Datatype	string	
Description	Indicates Authorization Status	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## BRNCHCODE

<b>Attribute</b>	<b>Description</b>	
Name	BRNCHCODE	
Datatype	string	
Description	Indicates Branch Code	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

### 2.9.2.SM-CreateSMRole-Req-IO-MSG.xsd

*CREATESMROLE\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*ROLEMASTER-IO*  
*ROLEIDENTIFICATION*  
*MASTERROLEDESC*  
*AUTHORISERROLE*  
*BRANCH\_RES*  
*ACCCLASSALLOWED*  
*CENTRALISATIONROLE*  
*ROLEDETAIL*  
*ROLEFUN*  
*CONTROL1*  
*CONTROL2*  
*CONTROL3*  
*CONTROL4*  
*CONTROL5*  
*CONTROL6*  
*CONTROL7*  
*CONTROL8*  
*CONTROL9*  
*CONTROL10*  
*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CONTROL15*

*CONTROL16*

*ROLEDETAILB*

*ROLEFUN*

*CONT1*

*CONT2*

*CONT3*

*CONT4*

*CONT5*

*CONT6*

*CONTROL7*

*CONT8*

*CONT9*

*CONT10*

*CONT11*

*CONT12*

*CONT13*

*CONT14*

*CONT15*

*CONTROL16*

*ROLEDETAILC*

*ROLEFUN*

*CNTRL1*

*CNTRL2*

*CNTRL3*

*CNTRL4*

*CNTRL5*

*CNTRL6*

*CNTRL7*

*CNTRL8*

*CNTRL9*

*CNTRL10*

*CNTRL11*

*CNTRL12*

*CNTRL13*

*CNTRL14*

*CNTRL15*

*CNTRL16*

*ROLEDETAILED*

*ROLEFUN*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*CONTROL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*ROLEBRANCHES*

*BRANCH*

*ROLEACCCLASS*

*ACCCLS*

*MSGCRIGHTS*

*CNL*

*CHGNODE*

*REL*  
*CHGMEDIA*  
*BRNMOV*  
*HLD*  
*TSTINP*  
*CHGADDR*  
*REINS*  
*CHGPRIOR*  
*CNLAUTH*  
*CHGNODEAUTH*  
*RELAUTH*  
*CHGMEDIAAUTH*  
*BRNMOVAUTH*  
*HLDAUTH*  
*TSTINPAUTH*  
*CHGADDRAUTH*  
*REINSAUTH*  
*CHGPRIORAUTH*  
*GEN*  
*TSTCHK*  
*LNKCONT*  
*CHGBRNIN*  
*CHGMSG*  
*CHGFORCRELFUND*  
*SUPPRESS*  
*DELMSG*  
*PRNT*  
*FTUPL*  
*MOVQ*  
*CHGADDRIN*  
*CHGMSGAUTH*  
*AUTHRGHTS*



*CHGFORCCOVMATCH*

*QUEUERIGHTS*

*QUEUE*

*RESTRICTIVEPASSWD*

*PWD*

*PWDID*

*ROLEBRANCHLIMITS*

*LMTCCY*

*BRHUSERLMT*

*Roledetaile*

*ROLEFUN*

*BRANCHCODE*

*EDITABLE*

*CNTRLSTR*

*Roledetailf*

*ROLEID*

*ROLEFUN*

*CNTRLSTR*

*CNTRL1*

*CNTRL10*

*CNTRL11*

*CNTRL12*

*CNTRL13*

*CNTRL14*

*CNTRL15*

*CNTRL16*

*CNTRL2*

*CNTRL3*

*CNTRL4*

*CNTRL5*

*CNTRL6*

*CNTRL7*

*CNTRL8*

*CNTRL9*

*ATHSTAT*

*BRNCHCODE*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

## CREATESMROLE\_IOPK\_REQ

Attribute	Description
Name	CREATESMROLE_IOPK_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description
-----------	-------------

Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	string				
Description	This is the user id in the Source system who is performing the action.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	string				
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## FUNCTIONID

Attribute	Description				
Name	FUNCTIONID				
Datatype	string				
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

## ADDL

<b>Attribute</b>	<b>Description</b>
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of CreateSMRole

## ROLEMASTER-IO

Attribute	Description
Name	ROLEMASTER-IO
Datatype	
Description	

## ROLEIDENTIFICATION

Attribute	Description				
Name	ROLEIDENTIFICATION				
Datatype	string				
Description	Indicates Role Id				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>15</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## MASTERROLEDESC

Attribute	Description	
Name	MASTERROLEDESC	
Datatype	string	
Description	Indicates Role Description	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## AUTHORISERROLE

Attribute	Description	
Name	AUTHORISERROLE	
Datatype	string	
Description	Indicates Authorizer Role Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRANCH\_RES

Attribute	Description	
Name	BRANCH_RES	
Datatype	string	
Description	Indicates Branch Restriction A - Allowed D - Disallowed	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## ACCCLASSALLOWED

Attribute	Description	
Name	ACCCLASSALLOWED	
Datatype	string	
Description	Indicates Account Class Restriction A - Allowed D - Disallowed	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## CENTRALISATIONROLE



Attribute	Description	
Name	CENTRALISATIONROLE	
Datatype	string	
Description	Indicates Centralisation Role Y - on N - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## ROLEDETAIL

Attribute	Description	
Name	ROLEDETAIL	
Datatype		
Description	Maintenance	
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

Attribute	Description	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Restrictions		
	Restrictions	Description
	maxLength	8

## CONTROL1

Attribute	Description	
Name	CONTROL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL2

Attribute	Description	
Name	CONTROL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL4

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL6

Attribute	Description								
Name	CONTROL6								
Datatype	decimal								
Description	Indicates Reopen 1 - on 0 - Off								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
	Attribute	Description							
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0	maxInclusive	1
	Restrictions	Description							
	totalDigits	22							
	minInclusive	0							
maxInclusive	1								

## CONTROL7

Attribute	Description								
Name	CONTROL7								
Datatype	decimal								
Description	Indicates Print 1 - on 0 - Off								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
	Attribute	Description							
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0	maxInclusive	1
	Restrictions	Description							
	totalDigits	22							
	minInclusive	0							
maxInclusive	1								

## CONTROL8

Attribute	Description								
Name	CONTROL8								
Datatype	decimal								
Description	Indicates Auth 1 - on 0 - Off								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
	Attribute	Description							
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0	maxInclusive	1
	Restrictions	Description							
	totalDigits	22							
	minInclusive	0							
maxInclusive	1								

## CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	decimal
Description	Indicates Reverse 1 - on 0 - Off

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL10

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL11

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL12

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL12	
Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL13

Attribute	Description								
Name	CONTROL13								
Datatype	decimal								
Description	Indicates Hold 1 - on 0 - Off								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
	Attribute	Description							
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0	maxInclusive	1
	Restrictions	Description							
	totalDigits	22							
	minInclusive	0							
maxInclusive	1								

## CONTROL14

Attribute	Description								
Name	CONTROL14								
Datatype	decimal								
Description	Indicates Template 1 - on 0 - Off								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
	Attribute	Description							
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0	maxInclusive	1
	Restrictions	Description							
	totalDigits	22							
	minInclusive	0							
maxInclusive	1								

## CONTROL15

Attribute	Description								
Name	CONTROL15								
Datatype	decimal								
Description	Indicates View 1 - on 0 - Off								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
	Attribute	Description							
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0	maxInclusive	1
	Restrictions	Description							
	totalDigits	22							
	minInclusive	0							
maxInclusive	1								

## CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	decimal
Description	Indicates Generate 1 - on 0 - Off

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEDETAILB

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILB	
Datatype		
Description	Roles	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## CONT1

<b>Attribute</b>	<b>Description</b>	
Name	CONT1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT2

<b>Attribute</b>	<b>Description</b>	
Name	CONT2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT3

<b>Attribute</b>	<b>Description</b>	
Name	CONT3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT4

<b>Attribute</b>	<b>Description</b>	
Name	CONT4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT5

<b>Attribute</b>	<b>Description</b>	
Name	CONT5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONT6**

Attribute	Description	
Name	CONT6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONTROL7**

Attribute	Description	
Name	CONTROL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONT8**

Attribute	Description	
Name	CONT8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONT9**

Attribute	Description	
Name	CONT9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	



Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT10

<b>Attribute</b>	<b>Description</b>	
Name	CONT10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT11

<b>Attribute</b>	<b>Description</b>	
Name	CONT11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT12

<b>Attribute</b>	<b>Description</b>	
Name	CONT12	
Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONT13**

Attribute	Description	
Name	CONT13	
Datatype	decimal	
Description	Indicates Hold 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONT14**

Attribute	Description	
Name	CONT14	
Datatype	decimal	
Description	Indicates Template 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONT15**

Attribute	Description	
Name	CONT15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONTROL16**

Attribute	Description	
Name	CONTROL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	

Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEDETAILC

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILC	
Datatype		
Description	Batch	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	8

## CNTRL1

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL2

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	

Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1
	<b>Description</b>	

### CNTRL3

<b>Attribute</b>		
Name	CNTRL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1
	<b>Description</b>	

### CNTRL4

<b>Attribute</b>		
Name	CNTRL4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1
	<b>Description</b>	

### CNTRL5

<b>Attribute</b>		
Name	CNTRL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1
	<b>Description</b>	

**CNTRL6**

Attribute	Description	
Name	CNTRL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL7**

Attribute	Description	
Name	CNTRL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL8**

Attribute	Description	
Name	CNTRL8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL9**

Attribute	Description	
Name	CNTRL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL10

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL11

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL12

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL12	
Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL13**

Attribute	Description	
Name	CNTRL13	
Datatype	decimal	
Description	Indicates Hold 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL14**

Attribute	Description	
Name	CNTRL14	
Datatype	decimal	
Description	Indicates Template 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL15**

Attribute	Description	
Name	CNTRL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL16**

Attribute	Description	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	

Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEDETAILD

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILD	
Datatype		
Description	Roles	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	8

## CONTROL1

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL4

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONTROL6**

Attribute	Description	
Name	CONTROL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONTROL7**

Attribute	Description	
Name	CONTROL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONTROL8**

Attribute	Description	
Name	CONTROL8	
Datatype	decimal	
Description	Indicates Auth 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONTROL9**

Attribute	Description	
Name	CONTROL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL10

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL11

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL12

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL12	
Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL13

Attribute	Description								
Name	CONTROL13								
Datatype	decimal								
Description	Indicates Hold 1 - on 0 - Off								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0	maxInclusive	1
Restrictions	Description								
totalDigits	22								
minInclusive	0								
maxInclusive	1								

## CONTROL14

Attribute	Description								
Name	CONTROL14								
Datatype	decimal								
Description	Indicates Template 1 - on 0 - Off								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0	maxInclusive	1
Restrictions	Description								
totalDigits	22								
minInclusive	0								
maxInclusive	1								

## ROLEBRANCHES

Attribute	Description						
Name	ROLEBRANCHES						
Datatype							
Description	Branches						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## BRANCH

Attribute	Description				
Name	BRANCH				
Datatype	string				
Description	Indicates Branch				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## ROLEACCCLASS

Attribute	Description
-----------	-------------

Name	ROLEACCCLASS	
Datatype		
Description	Acc Class Restriction	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ACCCLS

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLS	
Datatype	string	
Description	Indicates Account Class	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

## MSGCRIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	MSGCRIGHTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## CNL

<b>Attribute</b>	<b>Description</b>	
Name	CNL	
Datatype	string	
Description	Indicates Cancel Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODE

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODE	
Datatype	string	
Description	Indicates Change Node Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

**REL**

Attribute	Description	
Name	REL	
Datatype	string	
Description	Indicates Release Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

**CHGMEDIA**

Attribute	Description	
Name	CHGMEDIA	
Datatype	string	
Description	Indicates Change Media Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

**BRNMOV**

Attribute	Description	
Name	BRNMOV	
Datatype	string	
Description	Indicates Branch Move Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

**HLD**

Attribute	Description	
Name	HLD	
Datatype	string	
Description	Indicates Hold Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

**TSTINP**

Attribute	Description	
Name	TSTINP	
Datatype	string	
Description	Indicates Test Input Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDR

Attribute	Description	
Name	CHGADDR	
Datatype	string	
Description	Indicates Change Address Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINS

Attribute	Description	
Name	REINS	
Datatype	string	
Description	Indicates Reinstate Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIOR

Attribute	Description	
Name	CHGPRIOR	
Datatype	string	
Description	Indicates Change Priority Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNLAUTH

Attribute	Description	
Name	CNLAUTH	
Datatype	string	
Description	Indicates Auth Cancel Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODEAUTH

Attribute	Description	
Name	CHGNODEAUTH	
Datatype	string	
Description	Indicates Auth Change Node Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## RELAUTH

Attribute	Description	
Name	RELAUTH	
Datatype	string	
Description	Indicates Release Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIAAUTH

Attribute	Description	
Name	CHGMEDIAAUTH	
Datatype	string	
Description	Indicates Change Media Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOVAUTH



<b>Attribute</b>	<b>Description</b>	
Name	BRNMOVAUTH	
Datatype	string	
Description	Indicates Auth Branch Move Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLDAUTH

<b>Attribute</b>	<b>Description</b>	
Name	HLDAUTH	
Datatype	string	
Description	Indicates Hold Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINPAUTH

<b>Attribute</b>	<b>Description</b>	
Name	TSTINPAUTH	
Datatype	string	
Description	Indicates Auth Test Input Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRAUTH	
Datatype	string	
Description	Indicates Change Address Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINSAUTH

Attribute	Description				
Name	REINSAUTH				
Datatype	string				
Description	Indicates Auth Reinstate Y - on N - Off				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>Y,N</td></tr></tbody></table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## CHGPRIORAUTH

Attribute	Description				
Name	CHGPRIORAUTH				
Datatype	string				
Description	Indicates Change Priority Y - on N - Off				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>Y,N</td></tr></tbody></table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## GEN

Attribute	Description				
Name	GEN				
Datatype	string				
Description	Indicates Install Y - on N - Off				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>Y,N</td></tr></tbody></table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## TSTCHK

Attribute	Description				
Name	TSTCHK				
Datatype	string				
Description	Indicates Test Check Y - on N - Off				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>Y,N</td></tr></tbody></table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## LNKCONT

Attribute		Description	
Name	LNKCONT		
Datatype	string		
Description	Indicates Link Contract Y - on N - Off		
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	Y,N	

### CHGBRNIN

Attribute		Description	
Name	CHGBRNIN		
Datatype	string		
Description	Indicates Change Branch In Y - on N - Off		
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	Y,N	

### CHGMSG

Attribute		Description	
Name	CHGMSG		
Datatype	string		
Description	Indicates Change Message Y - on N - Off		
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	Y,N	

### CHGFORCREFUND

Attribute		Description	
Name	CHGFORCREFUND		
Datatype	string		
Description	Indicates Change Force Release Fund Y - on N - Off		
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SUPPRESS

<b>Attribute</b>	<b>Description</b>	
Name	SUPPRESS	
Datatype	string	
Description	Indicates Suppress Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DELMMSG

<b>Attribute</b>	<b>Description</b>	
Name	DELMMSG	
Datatype	string	
Description	Indicates Delete Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PRNT

<b>Attribute</b>	<b>Description</b>	
Name	PRNT	
Datatype	string	
Description	Indicates Print Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## FTUPL

<b>Attribute</b>	<b>Description</b>	
Name	FTUPL	
Datatype	string	
Description	Indicates FT Upload Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MOVQ

<b>Attribute</b>	<b>Description</b>	
Name	MOVQ	
Datatype	string	
Description	Indicates Move To Queue Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRIN	
Datatype	string	
Description	Indicates Change Address In Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSGAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSGAUTH	
Datatype	string	
Description	Indicates Auth Change Message Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## AUTHRGHTS

<b>Attribute</b>	<b>Description</b>	
Name	AUTHRGHTS	
Datatype	string	
Description	Indicates Auth Rights Y - on N - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGFORCCOVMATCH

<b>Attribute</b>	<b>Description</b>	
Name	CHGFORCCOVMATCH	
Datatype	string	
Description	Indicates Change Force Cover Match Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## QUEUERIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	QUEUERIGHTS	
Datatype		
Description	Queues	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## QUEUE

<b>Attribute</b>	<b>Description</b>	
Name	QUEUE	
Datatype	string	
Description	Indicates Queue	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## RESTRICTIVEPASSWD

<b>Attribute</b>	<b>Description</b>	
Name	RESTRICTIVEPASSWD	
Datatype		
Description	Restricted Password	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PWD

Attribute	Description	
Name	PWD	
Datatype	string	
Description	Indicates Password	
Restrictions		
	Restrictions	Description
	maxLength	12

## PWDID

Attribute	Description	
Name	PWDID	
Datatype	string	
Description	Indicates Id	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	15

## ROLEBRANCHLIMITS

Attribute	Description	
Name	ROLEBRANCHLIMITS	
Datatype		
Description	User Limits	
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## LMTCCY

Attribute	Description	
Name	LMTCCY	
Datatype	string	
Description	Indicates Limit Currency	
Restrictions		
	Restrictions	Description
	maxLength	3

## BRHUSERLMT

Attribute	Description	
Name	BRHUSERLMT	
Datatype	decimal	
Description	Indicates User Limit	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## Roledetaile

<b>Attribute</b>	<b>Description</b>	
Name	Roledetaile	
Datatype		
Description	Process Stage Rights	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## BRANCHCODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCHCODE	
Datatype	string	
Description	Indicates Branch Code	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## EDITABLE

<b>Attribute</b>	<b>Description</b>	
Name	EDITABLE	
Datatype	decimal	
Description	Indicates Editable 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CNTRLSTR

<b>Attribute</b>	<b>Description</b>	
Name	CNTRLSTR	
Datatype	string	
Description	Indicates Control String	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

## Roledetailf

<b>Attribute</b>	<b>Description</b>	
Name	Roledetailf	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEID

<b>Attribute</b>	<b>Description</b>	
Name	ROLEID	
Datatype	string	
Description	Indicates Role Function	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## CNTRLSTR

<b>Attribute</b>	<b>Description</b>	
Name	CNTRLSTR	
Datatype	string	
Description	Indicates Control String	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

## CNTRL1

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL10

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL11

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL12

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL12	
Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL13

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL13	
Datatype	decimal	
Description	Indicates Hold 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL14

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL14	
Datatype	decimal	
Description	Indicates Template 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL15**

Attribute	Description	
Name	CNTRL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL16**

Attribute	Description	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL2**

Attribute	Description	
Name	CNTRL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL3**

Attribute	Description	
Name	CNTRL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

#### CNTRL4

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

#### CNTRL5

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

#### CNTRL6

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL7**

Attribute	Description	
Name	CNTRL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL8**

Attribute	Description	
Name	CNTRL8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL9**

Attribute	Description	
Name	CNTRL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**ATHSTAT**

Attribute	Description	
Name	ATHSTAT	
Datatype	string	
Description	Indicates Authorization Status	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## BRNCHCODE

<b>Attribute</b>	<b>Description</b>	
Name	BRNCHCODE	
Datatype	string	
Description	Indicates Branch Code	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

### 2.9.3.SM-CreateSMRole-Res-Full-MSG.xsd

*CREATESMROLE\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*ROLEMASTER-Full*

*ROLEIDENTIFICATION*

*MASTERROLEDESC*

*AUTHORISERROLE*



*BRANCH\_RES*  
*ACCCLASSALLOWED*  
*CENTRALISATIONROLE*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*ROLEDETAIL*  
*ROLEFUN*  
*CONTROL1*  
*CONTROL2*  
*CONTROL3*  
*CONTROL4*  
*CONTROL5*  
*CONTROL6*  
*CONTROL7*  
*CONTROL8*  
*CONTROL9*  
*CONTROL10*  
*CONTROL11*  
*CONTROL12*  
*CONTROL13*  
*CONTROL14*  
*CONTROL15*  
*CONTROL16*  
*ROLEDETAILB*  
*ROLEFUN*  
*CONT1*  
*CONT2*  
*CONT3*

*CONT4*

*CONT5*

*CONT6*

*CONTROL7*

*CONT8*

*CONT9*

*CONT10*

*CONT11*

*CONT12*

*CONT13*

*CONT14*

*CONT15*

*CONTROL16*

*ROLEDETAILC*

*ROLEFUN*

*CNTRL1*

*CNTRL2*

*CNTRL3*

*CNTRL4*

*CNTRL5*

*CNTRL6*

*CNTRL7*

*CNTRL8*

*CNTRL9*

*CNTRL10*

*CNTRL11*

*CNTRL12*

*CNTRL13*

*CNTRL14*

*CNTRL15*

*CNTRL16*

*ROLEDETAILD*

*ROLEFUN*  
*CONTROL1*  
*CONTROL2*  
*CONTROL3*  
*CONTROL4*  
*CONTROL5*  
*CONTROL6*  
*CONTROL7*  
*CONTROL8*  
*CONTROL9*  
*CONTROL10*  
*CONTROL11*  
*CONTROL12*  
*CONTROL13*  
*CONTROL14*  
*CNTRL15*  
*CNTRL16*  
*ROLEBRANCHES*  
*BRANCH*  
*BRNNAME*  
*ROLEACCCLASS*  
*ACCCLS*  
*DESCRIPTION*  
*MSGCRIGHTS*  
*CNL*  
*CHGNODE*  
*REL*  
*CHGMEDIA*  
*BRNMOV*  
*HLD*  
*TSTINP*  
*CHGADDR*

*REINS*  
*CHGPRIOR*  
*CNLAUTH*  
*CHGNODEAUTH*  
*RELAUTH*  
*CHGMEDIAAUTH*  
*BRNMOVAUTH*  
*HLDAUTH*  
*TSTINPAUTH*  
*CHGADDRAUTH*  
*REINSAUTH*  
*CHGPRIORAUTH*  
*GEN*  
*TSTCHK*  
*LNKCONT*  
*CHGBRNIN*  
*CHGMSG*  
*CHGFORCRELFUND*  
*SUPPRESS*  
*DELMSG*  
*PRNT*  
*FTUPL*  
*MOVQ*  
*CHGADDRIN*  
*CHGMSGAUTH*  
*AUTHRGHTS*  
*CHGFORCCOVMATCH*  
*QUEUERIGHTS*  
*QUEUE*  
*RESTRICTIVEPASSWD*  
*PWD*  
*PWDID*

*ROLEBRANCHLIMITS*

*LMTCCY*

*BRHUSERLMT*

*Roledetaile*

*ROLEFUN*

*BRANCHCODE*

*EDITABLE*

*CNTRLSTR*

*Roledetailf*

*ROLEID*

*ROLEFUN*

*CNTRLSTR*

*CNTRL1*

*CNTRL10*

*CNTRL11*

*CNTRL12*

*CNTRL13*

*CNTRL14*

*CNTRL15*

*CNTRL16*

*CNTRL2*

*CNTRL3*

*CNTRL4*

*CNTRL5*

*CNTRL6*

*CNTRL7*

*CNTRL8*

*CNTRL9*

*ATHSTAT*

*BRNCHCODE*

*UDFDETAILS*

*FLDNAM*

FLDVAL

FCUBS\_ERROR\_RESP

ERROR

ECODE

EDESC

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

### CREATESMROLE\_FSFS\_RES

Attribute	Description
Name	CREATESMROLE_FSFS_RES
Datatype	
Description	

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

### SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

### UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	string				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## USERID

Attribute	Description						
Name	USERID						
Datatype	string						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

## BRANCH

Attribute	Description
Name	BRANCH

Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	string				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

## ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute			
		Attribute	Description
	minOccurs		0

## PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute			
		Attribute	Description
	minOccurs		0
	maxOccurs		unbounded

## NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

## VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

## FCUBS\_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description		This XSD Gives Information about Full Response	

## ROLEMASTER-Full

Attribute		Description	
Name		ROLEMASTER-Full	
Datatype			
Description			

## ROLEIDENTIFICATION

Attribute		Description	
Name		ROLEIDENTIFICATION	
Datatype		string	
Description		Indicates Role Id	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## MASTERROLEDESC

<b>Attribute</b>	<b>Description</b>	
Name	MASTERROLEDESC	
Datatype	string	
Description	Indicates Role Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## AUTHORISERROLE

<b>Attribute</b>	<b>Description</b>	
Name	AUTHORISERROLE	
Datatype	string	
Description	Indicates Authorizer Role Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRANCH\_RES

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_RES	
Datatype	string	
Description	Indicates Branch Restriction A - Allowed D - Disallowed	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## ACCCLASSALLOWED

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLASSALLOWED	
Datatype	string	
Description	Indicates Account Class Restriction A - Allowed D - Disallowed	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## CENTRALISATIONROLE

<b>Attribute</b>	<b>Description</b>	
Name	CENTRALISATIONROLE	
Datatype	string	
Description	Indicates Centralisation Role Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## ROLEDETAIL

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAIL	
Datatype		
Description	Maintenance	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## CONTROL1

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL4

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL6



Attribute	Description	
Name	CONTROL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL7

Attribute	Description	
Name	CONTROL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL8

Attribute	Description	
Name	CONTROL8	
Datatype	decimal	
Description	Indicates Auth 1 - on 0 - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL9

Attribute	Description	
Name	CONTROL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL10

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL11

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL12

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL12	
Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL13

Attribute	Description	
Name	CONTROL13	
Datatype	decimal	
Description	Indicates Hold 1 - on 0 - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22
	minInclusive	0
	maxInclusive	1

#### CONTROL14

Attribute	Description	
Name	CONTROL14	
Datatype	decimal	
Description	Indicates Template 1 - on 0 - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22
	minInclusive	0
	maxInclusive	1

#### CONTROL15

Attribute	Description	
Name	CONTROL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22
	minInclusive	0
	maxInclusive	1

#### CONTROL16

Attribute	Description	
Name	CONTROL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEDETAILB

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILB	
Datatype		
Description	Roles	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## CONT1

<b>Attribute</b>	<b>Description</b>	
Name	CONT1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT2

<b>Attribute</b>	<b>Description</b>	
Name	CONT2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT3

<b>Attribute</b>	<b>Description</b>	
Name	CONT3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT4

<b>Attribute</b>	<b>Description</b>	
Name	CONT4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT5

<b>Attribute</b>	<b>Description</b>	
Name	CONT5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT6

Attribute		Description	
Name		CONT6	
Datatype		decimal	
Description		Indicates Reopen 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL7

Attribute		Description	
Name		CONTROL7	
Datatype		decimal	
Description		Indicates Print 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONT8

Attribute		Description	
Name		CONT8	
Datatype		decimal	
Description		Indicates Authorize 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONT9

Attribute		Description	
Name		CONT9	
Datatype		decimal	
Description		Indicates Reverse 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT10

<b>Attribute</b>	<b>Description</b>	
Name	CONT10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT11

<b>Attribute</b>	<b>Description</b>	
Name	CONT11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT12

<b>Attribute</b>	<b>Description</b>	
Name	CONT12	
Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT13

Attribute	Description	
Name	CONT13	
Datatype	decimal	
Description	Indicates Hold 1 - on 0 - Off	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22
	minInclusive	0
	maxInclusive	1

#### CONT14

Attribute	Description	
Name	CONT14	
Datatype	decimal	
Description	Indicates Template 1 - on 0 - Off	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22
	minInclusive	0
	maxInclusive	1

#### CONT15

Attribute	Description	
Name	CONT15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22
	minInclusive	0
	maxInclusive	1

#### CONTROL16

Attribute	Description	
Name	CONTROL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	Attribute	Description
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEDETAILC

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILC	
Datatype		
Description	Batch	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## CNTRL1

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL2

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL3

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL4

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL5

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL6

Attribute		Description	
Name		CNTRL6	
Datatype		decimal	
Description		Indicates Reopen 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

### CNTRL7

Attribute		Description	
Name		CNTRL7	
Datatype		decimal	
Description		Indicates Print 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

### CNTRL8

Attribute		Description	
Name		CNTRL8	
Datatype		decimal	
Description		Indicates Authorize 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

### CNTRL9

Attribute		Description	
Name		CNTRL9	
Datatype		decimal	
Description		Indicates Reverse 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL10

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL11

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL12

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL12	
Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL13

Attribute		Description	
Name		CNTRL13	
Datatype		decimal	
Description		Indicates Hold 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

#### CNTRL14

Attribute		Description	
Name		CNTRL14	
Datatype		decimal	
Description		Indicates Template 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

#### CNTRL15

Attribute		Description	
Name		CNTRL15	
Datatype		decimal	
Description		Indicates View 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

#### CNTRL16

Attribute		Description	
Name		CNTRL16	
Datatype		decimal	
Description		Indicates Generate 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEDETAILD

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILD	
Datatype		
Description	Roles	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## CONTROL1

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL4

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL6

Attribute	Description	
Name	CONTROL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL7

Attribute	Description	
Name	CONTROL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL8

Attribute	Description	
Name	CONTROL8	
Datatype	decimal	
Description	Indicates Auth 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL9

Attribute	Description	
Name	CONTROL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL10

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL11

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL12

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL12	
Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL13

Attribute		Description	
Name		CONTROL13	
Datatype		decimal	
Description		Indicates Hold 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

#### CONTROL14

Attribute		Description	
Name		CONTROL14	
Datatype		decimal	
Description		Indicates Template 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

#### CNTRL15

Attribute		Description	
Name		CNTRL15	
Datatype		decimal	
Description		Indicates View 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

#### CNTRL16

Attribute		Description	
Name		CNTRL16	
Datatype		decimal	
Description		Indicates Generate 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEBRANCHES

<b>Attribute</b>	<b>Description</b>	
Name	ROLEBRANCHES	
Datatype		
Description	Branches	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	Indicates Branch	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## BRNNAME

<b>Attribute</b>	<b>Description</b>	
Name	BRNNAME	
Datatype	string	
Description	Indicates Branch Name	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## ROLEACCCLASS

<b>Attribute</b>	<b>Description</b>	
Name	ROLEACCCLASS	
Datatype		
Description	Acc Class Restriction	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ACCCLS

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	ACCCLS	
Datatype	string	
Description	Indicates Account Class	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Account Class Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## MSGRIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	MSGRIGHTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## CNL

<b>Attribute</b>	<b>Description</b>	
Name	CNL	
Datatype	string	
Description	Indicates Cancel Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODE

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODE	
Datatype	string	
Description	Indicates Change Node Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REL

<b>Attribute</b>	<b>Description</b>	
Name	REL	
Datatype	string	
Description	Indicates Release Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIA

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIA	
Datatype	string	
Description	Indicates Change Media Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOV

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOV	
Datatype	string	
Description	Indicates Branch Move Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLD

<b>Attribute</b>	<b>Description</b>	
Name	HLD	
Datatype	string	
Description	Indicates Hold Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINP

<b>Attribute</b>	<b>Description</b>	
Name	TSTINP	
Datatype	string	
Description	Indicates Test Input Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDR

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDR	
Datatype	string	
Description	Indicates Change Address Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINS

<b>Attribute</b>	<b>Description</b>	
Name	REINS	
Datatype	string	
Description	Indicates Reinstate Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIOR

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIOR	
Datatype	string	
Description	Indicates Change Priority Y - on N - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNLAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CNLAUTH	
Datatype	string	
Description	Indicates Auth Cancel Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODEAUTH	
Datatype	string	
Description	Indicates Auth Change Node Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## RELAUTH

<b>Attribute</b>	<b>Description</b>	
Name	RELAUTH	
Datatype	string	
Description	Indicates Release Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIAAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIAAUTH	
Datatype	string	

Description	Indicates Change Media Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOVAUTH

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOVAUTH	
Datatype	string	
Description	Indicates Auth Branch Move Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLDAUTH

<b>Attribute</b>	<b>Description</b>	
Name	HLDAUTH	
Datatype	string	
Description	Indicates Hold Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINPAUTH

<b>Attribute</b>	<b>Description</b>	
Name	TSTINPAUTH	
Datatype	string	
Description	Indicates Auth Test Input Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRAUTH	



Datatype	string	
Description	Indicates Change Address Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINSAUTH

<b>Attribute</b>	<b>Description</b>	
Name	REINSAUTH	
Datatype	string	
Description	Indicates Auth Reinstate Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIORAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIORAUTH	
Datatype	string	
Description	Indicates Change Priority Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## GEN

<b>Attribute</b>	<b>Description</b>	
Name	GEN	
Datatype	string	
Description	Indicates Install Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTCHK

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	TSTCHK	
Datatype	string	
Description	Indicates Test Check Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## LNKCONT

<b>Attribute</b>	<b>Description</b>	
Name	LNKCONT	
Datatype	string	
Description	Indicates Link Contract Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGBRNIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGBRNIN	
Datatype	string	
Description	Indicates Change Branch In Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSG

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSG	
Datatype	string	
Description	Indicates Change Message Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGFORCREFUND

Attribute	Description	
Name	CHGFORCRELFUND	
Datatype	string	
Description	Indicates Change Force Release Fund Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SUPPRESS

Attribute	Description	
Name	SUPPRESS	
Datatype	string	
Description	Indicates Suppress Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DELMSG

Attribute	Description	
Name	DELMSG	
Datatype	string	
Description	Indicates Delete Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PRNT

Attribute	Description	
Name	PRNT	
Datatype	string	
Description	Indicates Print Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## FTUPL

Attribute	Description	
Name	FTUPL	
Datatype	string	
Description	Indicates FT Upload Y - on N - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## MOVQ

Attribute	Description	
Name	MOVQ	
Datatype	string	
Description	Indicates Move To Queue Y - on N - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGADDRIN

Attribute	Description	
Name	CHGADDRIN	
Datatype	string	
Description	Indicates Change Address In Y - on N - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGMSGAUTH

Attribute	Description	
Name	CHGMSGAUTH	
Datatype	string	
Description	Indicates Auth Change Message Y - on N - Off	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## AUTHRGHTS

<b>Attribute</b>	<b>Description</b>	
Name	AUTHRGHTS	
Datatype	string	
Description	Indicates Auth Rights Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGFORCCOVMATCH

<b>Attribute</b>	<b>Description</b>	
Name	CHGFORCCOVMATCH	
Datatype	string	
Description	Indicates Change Force Cover Match Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## QUEUERIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	QUEUERIGHTS	
Datatype		
Description	Queues	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## QUEUE

<b>Attribute</b>	<b>Description</b>	
Name	QUEUE	
Datatype	string	
Description	Indicates Queue	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## RESTRICTIVEPASSWD

Attribute	Description	
Name	RESTRICTIVEPASSWD	
Datatype		
Description	Restricted Password	
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## PWD

Attribute	Description	
Name	PWD	
Datatype	string	
Description	Indicates Password	
Restrictions		
	Restrictions	Description
	maxLength	12

## PWDID

Attribute	Description	
Name	PWDID	
Datatype	string	
Description	Indicates Id	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	15

## ROLEBRANCLIMITS

Attribute	Description	
Name	ROLEBRANCLIMITS	
Datatype		
Description	User Limits	
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## LMTCCY

Attribute	Description	
Name	LMTCCY	
Datatype	string	
Description	Indicates Limit Currency	
Restrictions		
	Restrictions	Description
	maxLength	3

## BRHUSERLMT

Attribute	Description	
Name	BRHUSERLMT	
Datatype	decimal	
Description	Indicates User Limit	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### Roledetaile

Attribute	Description	
Name	Roledetaile	
Datatype		
Description	Process Stage Rights	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### ROLEFUN

Attribute	Description	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

### BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	string	
Description	Indicates Branch Code	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### EDITABLE

Attribute	Description
Name	EDITABLE

Datatype	decimal	
Description	Indicates Editable 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CNTRLSTR

<b>Attribute</b>	<b>Description</b>	
Name	CNTRLSTR	
Datatype	string	
Description	Indicates Control String	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

## Roledetailf

<b>Attribute</b>	<b>Description</b>	
Name	Roledetailf	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEID

<b>Attribute</b>	<b>Description</b>	
Name	ROLEID	
Datatype	string	
Description	Indicates Role Function	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	



Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## CNTRLSTR

<b>Attribute</b>	<b>Description</b>	
Name	CNTRLSTR	
Datatype	string	
Description	Indicates Control String	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

## CNTRL1

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL10

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL11

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CNTRL11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL12

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL12	
Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL13

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL13	
Datatype	decimal	
Description	Indicates Hold 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL14

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL14	
Datatype	decimal	
Description	Indicates Template 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL15

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL16

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL2

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL3

Attribute		Description	
Name		CNTRL3	
Datatype		decimal	
Description		Indicates Delete 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

#### CNTRL4

Attribute		Description	
Name		CNTRL4	
Datatype		decimal	
Description		Indicates Close 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

#### CNTRL5

Attribute		Description	
Name		CNTRL5	
Datatype		decimal	
Description		Indicates Unlock 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

#### CNTRL6

Attribute		Description	
Name		CNTRL6	
Datatype		decimal	
Description		Indicates Reopen 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL7

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL8

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL9

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ATHSTAT

Attribute	Description	
Name	ATHSTAT	
Datatype	string	
Description	Indicates Authorization Status	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

## BRNCHCODE

Attribute	Description	
Name	BRNCHCODE	
Datatype	string	
Description	Indicates Branch Code	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

## WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

## WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

### 2.9.4.SM-CreateSMRole-Res-PK-MSG.xsd

*CREATESMROLE\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*



*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*ROLEMASTER-PK*

*ROLEIDENTIFICATION*

*ROLEMASTER-IO*

*ROLEIDENTIFICATION*

*MASTERROLEDESC*

*AUTHORISERROLE*

*BRANCH\_RES*

*ACCCLASSALLOWED*

*CENTRALISATIONROLE*

*ROLEDETAIL*

*ROLEFUN*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*CONTROL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CONTROL15*

*CONTROL16*

*ROLEDETAILB*

*ROLEFUN*

*CONT1*

*CONT2*

*CONT3*

*CONT4*

*CONT5*

*CONT6*

*CONTROL7*

*CONT8*

*CONT9*

*CONT10*

*CONT11*

*CONT12*

*CONT13*

*CONT14*

*CONT15*

*CONTROL16*

*ROLEDETAILC*

*ROLEFUN*

*CNTRL1*

*CNTRL2*

*CNTRL3*

*CNTRL4*

*CNTRL5*

*CNTRL6*

*CNTRL7*

*CNTRL8*

*CNTRL9*

*CNTRL10*

*CNTRL11*

*CNTRL12*

*CNTRL13*

*CNTRL14*

*CNTRL15*

*CNTRL16*

*ROLEDETAILED*

*ROLEFUN*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*CONTROL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*ROLEBRANCHES*

*BRANCH*

*ROLEACCCLASS*

*ACCCLS*

*MSGCRIGHTS*

*CNL*

*CHGNODE*

*REL*

*CHGMEDIA*

*BRNMOV*

*HLD*

*TSTINP*

*CHGADDR*  
*REINS*  
*CHGPRIOR*  
*CNLAUTH*  
*CHGNODEAUTH*  
*RELAUTH*  
*CHGMEDIAAUTH*  
*BRNMOVAUTH*  
*HLDAUTH*  
*TSTINPAUTH*  
*CHGADDRAUTH*  
*REINSAUTH*  
*CHGPRIORAUTH*  
*GEN*  
*TSTCHK*  
*LNKCONT*  
*CHGBRNIN*  
*CHGMSG*  
*CHGFORCRELFUND*  
*SUPPRESS*  
*DELMSG*  
*PRNT*  
*FTUPL*  
*MOVQ*  
*CHGADDRIN*  
*CHGMSGAUTH*  
*AUTHRGHTS*  
*CHGFORCCOVMATCH*  
*QUEUERIGHTS*  
*QUEUE*  
*RESTRICTIVEPASSWD*  
*PWD*

*PWDID*

*ROLEBRANCHLIMITS*

*LMTCCY*

*BRHUSERLMT*

*Roledetaile*

*ROLEFUN*

*BRANCHCODE*

*EDITABLE*

*CNTRLSTR*

*Roledetailf*

*ROLEID*

*ROLEFUN*

*CNTRLSTR*

*CNTRL1*

*CNTRL10*

*CNTRL11*

*CNTRL12*

*CNTRL13*

*CNTRL14*

*CNTRL15*

*CNTRL16*

*CNTRL2*

*CNTRL3*

*CNTRL4*

*CNTRL5*

*CNTRL6*

*CNTRL7*

*CNTRL8*

*CNTRL9*

*ATHSTAT*

*BRNCHCODE*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## CREATESMROLE\_IOPK\_RES

Attribute	Description
Name	CREATESMROLE_IOPK_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	string
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	string
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	

Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

## ROLEMASTER-PK

<b>Attribute</b>	<b>Description</b>
Name	ROLEMASTER-PK
Datatype	
Description	

## ROLEIDENTIFICATION

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	ROLEIDENTIFICATION	
Datatype	string	
Description	Indicates Role Id	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## ROLEMASTER-IO

<b>Attribute</b>	<b>Description</b>
Name	ROLEMASTER-IO
Datatype	
Description	

## ROLEIDENTIFICATION

<b>Attribute</b>	<b>Description</b>	
Name	ROLEIDENTIFICATION	
Datatype	string	
Description	Indicates Role Id	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## MASTERROLEDESC

<b>Attribute</b>	<b>Description</b>	
Name	MASTERROLEDESC	
Datatype	string	
Description	Indicates Role Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## AUTHORISERROLE

<b>Attribute</b>	<b>Description</b>	
Name	AUTHORISERROLE	
Datatype	string	
Description	Indicates Authorizer Role Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRANCH\_RES

<b>Attribute</b>	<b>Description</b>
Name	BRANCH_RES

Datatype	string	
Description	Indicates Branch Restriction A - Allowed D - Disallowed	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## ACCCLASSALLOWED

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLASSALLOWED	
Datatype	string	
Description	Indicates Account Class Restriction A - Allowed D - Disallowed	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## CENTRALISATIONROLE

<b>Attribute</b>	<b>Description</b>	
Name	CENTRALISATIONROLE	
Datatype	string	
Description	Indicates Centralisation Role Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## ROLEDETAIL

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAIL	
Datatype		
Description	Maintenance	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	

Description	Indicates Role Function	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

### CONTROL1

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL4

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CONTROL4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL6

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL8

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL8	
Datatype	decimal	
Description	Indicates Auth 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL10

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL11



Attribute		Description	
Name		CONTROL11	
Datatype		decimal	
Description		Indicates Confirm 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL12

Attribute		Description	
Name		CONTROL12	
Datatype		decimal	
Description		Indicates Liquidate 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL13

Attribute		Description	
Name		CONTROL13	
Datatype		decimal	
Description		Indicates Hold 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL14

Attribute		Description	
Name		CONTROL14	
Datatype		decimal	
Description		Indicates Template 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL15

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEDETAILB

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILB	
Datatype		
Description	Roles	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

### CONT1

<b>Attribute</b>	<b>Description</b>	
Name	CONT1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT2

<b>Attribute</b>	<b>Description</b>	
Name	CONT2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT3

<b>Attribute</b>	<b>Description</b>	
Name	CONT3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT4

<b>Attribute</b>	<b>Description</b>
Name	CONT4

Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT5

<b>Attribute</b>	<b>Description</b>	
Name	CONT5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT6

<b>Attribute</b>	<b>Description</b>	
Name	CONT6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT8

<b>Attribute</b>	<b>Description</b>	
Name	CONT8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT9

<b>Attribute</b>	<b>Description</b>	
Name	CONT9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT10

<b>Attribute</b>	<b>Description</b>	
Name	CONT10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT11

Attribute		Description	
Name	CONT11		
Datatype	decimal		
Description	Indicates Confirm 1 - on 0 - Off		
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	
	minInclusive	0	
	maxInclusive	1	

## CONT12

Attribute		Description	
Name	CONT12		
Datatype	decimal		
Description	Indicates Liquidate 1 - on 0 - Off		
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	
	minInclusive	0	
	maxInclusive	1	

## CONT13

Attribute		Description	
Name	CONT13		
Datatype	decimal		
Description	Indicates Hold 1 - on 0 - Off		
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	
	minInclusive	0	
	maxInclusive	1	

## CONT14

Attribute		Description	
Name	CONT14		
Datatype	decimal		
Description	Indicates Template 1 - on 0 - Off		
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT15

<b>Attribute</b>	<b>Description</b>	
Name	CONT15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEDETAILC

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILC	
Datatype		
Description	Batch	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

### CNTRL1

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL2

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL3

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL4

<b>Attribute</b>	<b>Description</b>
Name	CNTRL4



Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL5

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL6

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL7

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL8

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL9

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL10

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL11

Attribute		Description	
Name		CNTRL11	
Datatype		decimal	
Description		Indicates Confirm 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CNTRL12

Attribute		Description	
Name		CNTRL12	
Datatype		decimal	
Description		Indicates Liquidate 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CNTRL13

Attribute		Description	
Name		CNTRL13	
Datatype		decimal	
Description		Indicates Hold 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CNTRL14

Attribute		Description	
Name		CNTRL14	
Datatype		decimal	
Description		Indicates Template 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL15

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL16

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEDETAILD

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILD	
Datatype		
Description	Roles	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

### CONTROL1

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL4

<b>Attribute</b>	<b>Description</b>
Name	CONTROL4

Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL6

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL8

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL8	
Datatype	decimal	
Description	Indicates Auth 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL10

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL11

Attribute		Description	
Name		CONTROL11	
Datatype		decimal	
Description		Indicates Confirm 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL12

Attribute		Description	
Name		CONTROL12	
Datatype		decimal	
Description		Indicates Liquidate 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL13

Attribute		Description	
Name		CONTROL13	
Datatype		decimal	
Description		Indicates Hold 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL14

Attribute		Description	
Name		CONTROL14	
Datatype		decimal	
Description		Indicates Template 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEBRANCHES

<b>Attribute</b>	<b>Description</b>	
Name	ROLEBRANCHES	
Datatype		
Description	Branches	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	Indicates Branch	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## ROLEACCCLASS

<b>Attribute</b>	<b>Description</b>	
Name	ROLEACCCLASS	
Datatype		
Description	Acc Class Restriction	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ACCCLS

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLS	
Datatype	string	
Description	Indicates Account Class	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

## MSGCRIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	MSGCRIGHTS	
Datatype		
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## CNL

<b>Attribute</b>	<b>Description</b>	
Name	CNL	
Datatype	string	
Description	Indicates Cancel Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODE

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODE	
Datatype	string	
Description	Indicates Change Node Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REL

<b>Attribute</b>	<b>Description</b>	
Name	REL	
Datatype	string	
Description	Indicates Release Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIA

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIA	
Datatype	string	
Description	Indicates Change Media Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOV

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOV	
Datatype	string	
Description	Indicates Branch Move Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLD

<b>Attribute</b>	<b>Description</b>	
Name	HLD	
Datatype	string	
Description	Indicates Hold Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINP

<b>Attribute</b>	<b>Description</b>	
Name	TSTINP	
Datatype	string	
Description	Indicates Test Input Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDR

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDR	
Datatype	string	
Description	Indicates Change Address Y - on N - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINS

<b>Attribute</b>	<b>Description</b>	
Name	REINS	
Datatype	string	
Description	Indicates Reinstatement Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIOR

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIOR	
Datatype	string	
Description	Indicates Change Priority Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNLAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CNLAUTH	
Datatype	string	
Description	Indicates Auth Cancel Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODEAUTH	
Datatype	string	
Description	Indicates Auth Change Node Y - on N - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## RELAUTH

<b>Attribute</b>	<b>Description</b>	
Name	RELAUTH	
Datatype	string	
Description	Indicates Release Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIAAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIAAUTH	
Datatype	string	
Description	Indicates Change Media Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOVAUTH

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOVAUTH	
Datatype	string	
Description	Indicates Auth Branch Move Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLDAUTH

<b>Attribute</b>	<b>Description</b>	
Name	HLDAUTH	
Datatype	string	

Description	Indicates Hold Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINPAUTH

<b>Attribute</b>	<b>Description</b>	
Name	TSTINPAUTH	
Datatype	string	
Description	Indicates Auth Test Input Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRAUTH	
Datatype	string	
Description	Indicates Change Address Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINSAUTH

<b>Attribute</b>	<b>Description</b>	
Name	REINSAUTH	
Datatype	string	
Description	Indicates Auth Reinstate Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIORAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIORAUTH	

Datatype	string	
Description	Indicates Change Priority Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## GEN

<b>Attribute</b>	<b>Description</b>	
Name	GEN	
Datatype	string	
Description	Indicates Install Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTCHK

<b>Attribute</b>	<b>Description</b>	
Name	TSTCHK	
Datatype	string	
Description	Indicates Test Check Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## LNKCONT

<b>Attribute</b>	<b>Description</b>	
Name	LNKCONT	
Datatype	string	
Description	Indicates Link Contract Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGBRNIN

<b>Attribute</b>	<b>Description</b>
Name	CHGBRNIN

Datatype	string	
Description	Indicates Change Branch In Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSG

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSG	
Datatype	string	
Description	Indicates Change Message Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGFORCRELFUND

<b>Attribute</b>	<b>Description</b>	
Name	CHGFORCRELFUND	
Datatype	string	
Description	Indicates Change Force Release Fund Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SUPPRESS

<b>Attribute</b>	<b>Description</b>	
Name	SUPPRESS	
Datatype	string	
Description	Indicates Suppress Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DELMSG



Attribute	Description	
Name	DELMSG	
Datatype	string	
Description	Indicates Delete Y - on N - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## PRNT

Attribute	Description	
Name	PRNT	
Datatype	string	
Description	Indicates Print Y - on N - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## FTUPL

Attribute	Description	
Name	FTUPL	
Datatype	string	
Description	Indicates FT Upload Y - on N - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## MOVQ

Attribute	Description	
Name	MOVQ	
Datatype	string	
Description	Indicates Move To Queue Y - on N - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGADDRIN

Attribute	Description	
Name	CHGADDRIN	
Datatype	string	
Description	Indicates Change Address In Y - on N - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGMSGAUTH

Attribute	Description	
Name	CHGMSGAUTH	
Datatype	string	
Description	Indicates Auth Change Message Y - on N - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## AUTHRGHTS

Attribute	Description	
Name	AUTHRGHTS	
Datatype	string	
Description	Indicates Auth Rights Y - on N - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGFORCCOVMATCH

Attribute	Description	
Name	CHGFORCCOVMATCH	
Datatype	string	
Description	Indicates Change Force Cover Match Y - on N - Off	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## QUEUERIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	QUEUERIGHTS	
Datatype		
Description	Queues	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## QUEUE

<b>Attribute</b>	<b>Description</b>	
Name	QUEUE	
Datatype	string	
Description	Indicates Queue	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## RESTRICTIVEPASSWD

<b>Attribute</b>	<b>Description</b>	
Name	RESTRICTIVEPASSWD	
Datatype		
Description	Restricted Password	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PWD

<b>Attribute</b>	<b>Description</b>	
Name	PWD	
Datatype	string	
Description	Indicates Password	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## PWDID

<b>Attribute</b>	<b>Description</b>	
Name	PWDID	
Datatype	string	
Description	Indicates Id	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## ROLEBRANCHLIMITS

<b>Attribute</b>	<b>Description</b>	
Name	ROLEBRANCHLIMITS	
Datatype		
Description	User Limits	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxOccurs	unbounded

## LMTCCY

<b>Attribute</b>	<b>Description</b>	
Name	LMTCCY	
Datatype	string	
Description	Indicates Limit Currency	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## BRHUSERLMT

<b>Attribute</b>	<b>Description</b>	
Name	BRHUSERLMT	
Datatype	decimal	
Description	Indicates User Limit	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## Roledetaile

<b>Attribute</b>	<b>Description</b>	
Name	Roledetaile	
Datatype		
Description	Process Stage Rights	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxOccurs	unbounded

## ROLEFUN

Attribute	Description	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	string	
Description	Indicates Branch Code	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## EDITABLE

Attribute	Description	
Name	EDITABLE	
Datatype	decimal	
Description	Indicates Editable 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CNTRLSTR

Attribute	Description	
Name	CNTRLSTR	
Datatype	string	
Description	Indicates Control String	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

## Roledetailf

Attribute	Description	
Name	Roledetailf	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded

## ROLEID

Attribute	Description	
Name	ROLEID	
Datatype	string	
Description	Indicates Role Function	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	15

## ROLEFUN

Attribute	Description	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	8

## CNTRLSTR

Attribute	Description	
Name	CNTRLSTR	
Datatype	string	
Description	Indicates Control String	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	16

## CNTRL1

Attribute	Description
Name	CNTRL1
Datatype	decimal

Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL10

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL11

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL12

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL12	
Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL13**

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL13	
Datatype	decimal	
Description	Indicates Hold 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL14**

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL14	
Datatype	decimal	
Description	Indicates Template 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL15**

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL16**

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	



Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL2

<b>Attribute</b>		<b>Description</b>
Name	CNTRL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL3

<b>Attribute</b>		<b>Description</b>
Name	CNTRL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL4

<b>Attribute</b>		<b>Description</b>
Name	CNTRL4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL5**

Attribute	Description	
Name	CNTRL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL6**

Attribute	Description	
Name	CNTRL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL7**

Attribute	Description	
Name	CNTRL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL8**

Attribute	Description	
Name	CNTRL8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL9

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ATHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	ATHSTAT	
Datatype	string	
Description	Indicates Authorization Status	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## BRNCHCODE

<b>Attribute</b>	<b>Description</b>	
Name	BRNCHCODE	
Datatype	string	
Description	Indicates Branch Code	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
		<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	
		<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	
		<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
		<b>Description</b>
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	
		<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	
		<b>Description</b>
	maxOccurs	unbounded

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

## 2.10.CreateUserMaint

### 2.10.1.SM-CreateUserMaint-Req-Full-MSG.xsd

*CREATEUSERMAINT\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*USR-Full*  
*STRTDATE*  
*USRNAME*  
*USRPWD*  
*ENDDT*  
*USRLANG*  
*HOMEBRN*  
*CUSTNO*  
*LDAPUSR*  
*TIMELEVEL*  
*AUTOAUTH*  
*USRSTAT*

*USRID*  
*EXTUSRREF*  
*USRCATEG*  
*TILLALLOW*  
*ACCCLSALLOW*  
*GLALLOW*  
*USRTXNLMT*  
*LMTSCCY*  
*MAXTXNAMT*  
*MAXAUTHAMT*  
*BRNSALLOW*  
*PRDSALLOW*  
*PRDSACCESALLOW*  
*TAX\_IDENTIFIER*  
*AMOUNT\_FORMAT*  
*DATE\_FORMAT*  
*STAFFACCRESTR*  
*DEPT\_CODE*  
*DEPT\_DESC*  
*USRML*  
*ELCMUSER*  
*GROUP\_CODE*  
*MULTIBRN\_ACCESS*  
*OTH\_RM\_CUST\_ACC\_ALLOW*  
*SUPERVISOR\_ID*  
*SUPERVISOR\_NAME*  
*DASHBOARD\_REQD*  
*ALERTS\_ON\_HOME*  
*REFERENCE\_NO*  
*NO\_CUMULATIVE\_LOGINS*  
*NO\_SUCCESSIVE\_LOGINS*  
*SCREENSAVERTIMEOUTINSECONDS*

*NUMBER\_FORMAT\_MASK*  
*FRONTEND\_DEBUG\_ENABLED*  
*F10\_REQD*  
*F11\_REQD*  
*F12\_REQD*  
*MFI\_USER*  
*MFAENABLED*  
*MFAID*  
*ACCESS\_CONTROL*  
*EXTN\_ALERTS*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*RESTR\_PWD*  
*PWD*  
*MSGSRIGHTS*  
*GEN*  
*HLD*  
*CNL*  
*TSTINP*  
*CHGNODE*  
*CHGADDR*  
*REL*  
*REINS*  
*CHGMEDIA*  
*CHGPRIOR*  
*BRNMOV*  
*PRNT*



*TSTCHK*  
*HLDAUTH*  
*CNLAUTH*  
*TSTINPAUTH*  
*CHGNODEAUTH*  
*CHGADDRAUTH*  
*RELAUTH*  
*REINSAUTH*  
*CHGMEDIAAUTH*  
*BRNMOVAUTH*  
*CHGPRIORAUTH*  
*FTUPL*  
*LNKCONT*  
*MOVQ*  
*CHGBRNIN*  
*CHGADDRIN*  
*AUTHRGHTS*  
*CHGMSG*  
*CHGMSGAUTH*  
*CHGFORCCOVMATCH*  
*CHANGE\_FORCE\_RELEASE\_FUND*  
*SUPPRESS*  
*DELMSG*  
*QUEUERIGHTS*  
    *QUEUE*  
*USERTILLS*  
    *TILLID*  
    *TILLBRNCD*  
    *DESCRIPTION*  
*USERACCCLASS*  
    *ACCCLS*  
*USERGLREST*

*NODEGL*  
*USERGLEXCEPT*  
*EXCEPLEAFGL*  
*USERLIMITSROLE*  
*LMTBRN*  
*LMTSROLE*  
*QLMTCCY*  
*QINPLMT*  
*QAUTHLMT*  
*USERBRANCHES*  
*BRNSBRN*  
*BRNNAME*  
*USERPRODUCTS*  
*PRDPRDCD*  
*PRDDESC*  
*USERACCESSPRODUCTS*  
*PRDACCESSPRDCD*  
*PRDDESC*  
*USERFUNCDISALLOW*  
*FUNCDISALLOWFUNCID*  
*USERROLE*  
*ROLEBRNCD*  
*USRROLEID*  
*MASTERROLEDESC*  
*USERSFUNCTIONS*  
*USERFUNCBRNCD*  
*USERFUNCFUNCID*  
*CONTROL1*  
*CONTROL2*  
*CONTROL3*  
*CONTROL4*  
*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*USERFUNCSCTRL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CONTROL15*

*CONTROL16*

*Grp-Restriction*

*GROUP\_CODE*

*GROUP\_DESC*

*Centralisation*

*USRROLEID*

*ROLDESC*

*Dshmst*

*USRID*

*USRNAME*

*Dshdet*

*FUNCTIONID*

*DESCRIPTION*

*SEQUENCE\_NO*

*DBWHERECLAUSE*

*SHOW\_IN\_DASHBOARD*

*Where-Master*

*COLUMN\_NAME*

*WHERE\_CL*

*CONDITION*

*UDFDETAILS*

*FLDNAM*

**CREATEUSERMAINT\_FSFS\_REQ**

Attribute	Description
Name	CREATEUSERMAINT_FSFS_REQ
Datatype	
Description	

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

**SOURCE**

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

**UBSCOMP**

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

**MSGID**

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>
Name	MODULEID

Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM



Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

## FCUBS\_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Request of CreateUserMaint	

## USR-Full

Attribute	Description	
Name	USR-Full	
Datatype		
Description		

## STRTDATE

Attribute	Description	
Name	STRTDATE	
Datatype	String	
Description		

## USRNAME

Attribute	Description	
Name	USRNAME	
Datatype	string	
Description		
Restrictions	Restrictions	Description
	maxLength	35

## USRPWD

Attribute	Description	

Name	USRPWD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	32

## ENDDT

<b>Attribute</b>	<b>Description</b>	
Name	ENDDT	
Datatype	String	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0

## USRLANG

<b>Attribute</b>	<b>Description</b>	
Name	USRLANG	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	3

## HOMEBRN

<b>Attribute</b>	<b>Description</b>	
Name	HOMEBRN	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	3

## CUSTNO

<b>Attribute</b>	<b>Description</b>	
Name	CUSTNO	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	9

## LDAPUSR

Attribute	Description	
Name	LDAPUSR	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	500

## TIMELEVEL

Attribute	Description	
Name	TIMELEVEL	
Datatype	decimal	
Description		
Restrictions	Restrictions	Description
	totalDigits	22
	minInclusive	0
	maxInclusive	9

## AUTOAUTH

Attribute	Description	
Name	AUTOAUTH	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

## USRSTAT

Attribute	Description	
Name	USRSTAT	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	E,H,D,L

## USRID

Attribute	Description
-----------	-------------

Name	USRID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## EXTUSRREF

<b>Attribute</b>	<b>Description</b>	
Name	EXTUSRREF	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## USRCATEG

<b>Attribute</b>	<b>Description</b>	
Name	USRCATEG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	S,B

## TILLALLOW

<b>Attribute</b>	<b>Description</b>	
Name	TILLALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## ACCCLSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLSALLOW	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## GLALLOW

<b>Attribute</b>	<b>Description</b>	
Name	GLALLOW	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## USRTXNLMT

<b>Attribute</b>	<b>Description</b>	
Name	USRTXNLMT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,R,N

## LMTSCCY

<b>Attribute</b>	<b>Description</b>	
Name	LMTSCCY	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## MAXTXNAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXTXNAMT	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### MAXAUTHAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXAUTHAMT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### BRNSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	BRNSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### PRDSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### PRDSACCESALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSACCESALLOW	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## TAX\_IDENTIFIER

<b>Attribute</b>	<b>Description</b>	
Name	TAX_IDENTIFIER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

## AMOUNT\_FORMAT

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_FORMAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	******

## DATE\_FORMAT

<b>Attribute</b>	<b>Description</b>	
Name	DATE_FORMAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	M/d/yyyy

## STAFFACCRESTR

<b>Attribute</b>	<b>Description</b>	
Name	STAFFACCRESTR	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### DEPT\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	DEPT_CODE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### DEPT\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	DEPT_DESC	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### USRML

<b>Attribute</b>	<b>Description</b>	
Name	USRML	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ELCMUSER

<b>Attribute</b>	<b>Description</b>	
Name	ELCMUSER	
Datatype	string	
Description		



Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	12
	<b>Description</b>	

### GROUP\_CODE

<b>Attribute</b>		<b>Description</b>
Name	GROUP_CODE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	enumeration	A,D
	<b>Description</b>	

### MULTIBRN\_ACCESS

<b>Attribute</b>		<b>Description</b>
Name	MULTIBRN_ACCESS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	enumeration	Y,N
	<b>Description</b>	

### OTH\_RM\_CUST\_ACC\_ALLOW

<b>Attribute</b>		<b>Description</b>
Name	OTH_RM_CUST_ACC_ALLOW	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	enumeration	Y,N
	<b>Description</b>	

### SUPERVISOR\_ID

<b>Attribute</b>		<b>Description</b>
Name	SUPERVISOR_ID	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	80

## SUPERVISOR\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	SUPERVISOR_NAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## DASHBOARD\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	DASHBOARD_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## ALERTS\_ON\_HOME

<b>Attribute</b>	<b>Description</b>	
Name	ALERTS_ON_HOME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REFERENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	REFERENCE_NO	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	20
	<b>Description</b>	

### NO\_CUMULATIVE\_LOGINS

<b>Attribute</b>		<b>Description</b>
Name	NO_CUMULATIVE_LOGINS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	<b>Description</b>	

### NO\_SUCCESSIVE\_LOGINS

<b>Attribute</b>		<b>Description</b>
Name	NO_SUCCESSIVE_LOGINS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	<b>Description</b>	

### SCREENSAVERTIMEOUTINSECONDS

<b>Attribute</b>		<b>Description</b>
Name	SCREENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	<b>Description</b>	

### NUMBER\_FORMAT\_MASK

<b>Attribute</b>		<b>Description</b>
Name	NUMBER_FORMAT_MASK	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	M,L

### FRONTEND\_DEBUG\_ENABLED

<b>Attribute</b>	<b>Description</b>	
Name	FRONTEND_DEBUG_ENABLED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F10\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F10_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F11\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F11_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F12\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F12_REQD	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MFI\_USER

<b>Attribute</b>	<b>Description</b>	
Name	MFI_USER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MFAENABLED

<b>Attribute</b>	<b>Description</b>	
Name	MFAENABLED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	N,Y,L

## MFAID

<b>Attribute</b>	<b>Description</b>	
Name	MFAID	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

## ACCESS\_CONTROL

<b>Attribute</b>	<b>Description</b>	
Name	ACCESS_CONTROL	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,G,B

## EXTN\_ALERTS

<b>Attribute</b>	<b>Description</b>	
Name	EXTN_ALERTS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## RESTR\_PWD

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_PWD	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PWD

<b>Attribute</b>	<b>Description</b>	
Name	PWD	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MSGSRIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	MSGSRIGHTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## GEN

<b>Attribute</b>	<b>Description</b>	
Name	GEN	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLD

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	HLD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNL

<b>Attribute</b>	<b>Description</b>	
Name	CNL	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINP

<b>Attribute</b>	<b>Description</b>	
Name	TSTINP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODE

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDR

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CHGADDR	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REL

<b>Attribute</b>	<b>Description</b>	
Name	REL	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINS

<b>Attribute</b>	<b>Description</b>	
Name	REINS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIA

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIA	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIOR

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CHGPRIOR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOV

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOV	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PRNT

<b>Attribute</b>	<b>Description</b>	
Name	PRNT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTCHK

<b>Attribute</b>	<b>Description</b>	
Name	TSTCHK	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLDAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	HLDAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNLAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CNLAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINPAUTH

<b>Attribute</b>	<b>Description</b>	
Name	TSTINPAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODEAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CHGADDRAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## RELAUTH

<b>Attribute</b>	<b>Description</b>	
Name	RELAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINSAUTH

<b>Attribute</b>	<b>Description</b>	
Name	REINSAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIAAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIAAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOVAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	BRNMOVAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHGPRIORAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIORAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### FTUPL

<b>Attribute</b>	<b>Description</b>	
Name	FTUPL	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### LNKCONT

<b>Attribute</b>	<b>Description</b>	
Name	LNKCONT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### MOVQ

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	MOVQ	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGBRNIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGBRNIN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRIN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## AUTHRGHTS

<b>Attribute</b>	<b>Description</b>	
Name	AUTHRGHTS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSG

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CHGMSG	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHGMSGAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSGAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHGFORCCOVMATCH

<b>Attribute</b>	<b>Description</b>	
Name	CHGFORCCOVMATCH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHANGE\_FORCE\_RELEASE\_FUND

<b>Attribute</b>	<b>Description</b>	
Name	CHANGE_FORCE_RELEASE_FUND	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### SUPPRESS

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	SUPPRESS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DELMSG

<b>Attribute</b>	<b>Description</b>	
Name	DELMSG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## QUEUERIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	QUEUERIGHTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## QUEUE

<b>Attribute</b>	<b>Description</b>	
Name	QUEUE	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## USERTILLS

<b>Attribute</b>	<b>Description</b>	
Name	USERTILLS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## TILLID

Attribute	Description				
Name	TILLID				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## TILLBRNCD

Attribute	Description				
Name	TILLBRNCD				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## DESCRIPTION

Attribute	Description				
Name	DESCRIPTION				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

## USERACCCLASS

Attribute	Description						
Name	USERACCCLASS						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## ACCCLS

Attribute	Description				
Name	ACCCLS				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>6</td></tr></tbody></table>	Restrictions	Description	maxLength	6
Restrictions	Description				
maxLength	6				

## USERGLREST

Attribute		Description	
Name	USERGLREST		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
	maxOccurs	unbounded	

## NODEGL

Attribute		Description	
Name	NODEGL		
Datatype	string		
Description			
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	9	

## USERGLEXCEPT

Attribute		Description	
Name	USERGLEXCEPT		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
	maxOccurs	unbounded	

## EXCEPLEAFGL

Attribute		Description	
Name	EXCEPLEAFGL		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	9	

## USERLIMITSROLE

Attribute		Description	
Name	USERLIMITSROLE		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
	maxOccurs	unbounded	

## LMTBRN

Attribute	Description				
Name	LMTBRN				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## LMTSROLE

Attribute	Description				
Name	LMTSROLE				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## QLMTCCY

Attribute	Description				
Name	QLMTCCY				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## QINPLMT

Attribute	Description				
Name	QINPLMT				
Datatype	decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## QAUTHLMT

Attribute	Description
Name	QAUTHLMT

Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	<b>Description</b>	

## USERBRANCHES

<b>Attribute</b>	<b>Description</b>	
Name	USERBRANCHES	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## BRNSBRN

<b>Attribute</b>	<b>Description</b>	
Name	BRNSBRN	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	3
	<b>Description</b>	

## BRNNAME

<b>Attribute</b>	<b>Description</b>	
Name	BRNNAME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	105
	<b>Description</b>	

## USERPRODUCTS

<b>Attribute</b>	<b>Description</b>	
Name	USERPRODUCTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## PRDPRDCD

Attribute	Description				
Name	PRDPRDCD				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>4</td></tr></tbody></table>	Restrictions	Description	maxLength	4
Restrictions	Description				
maxLength	4				

## PRDDESC

Attribute	Description				
Name	PRDDESC				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

## USERACCESSPRODUCTS

Attribute	Description						
Name	USERACCESSPRODUCTS						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## PRDACCESSPRDCD

Attribute	Description				
Name	PRDACCESSPRDCD				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>4</td></tr></tbody></table>	Restrictions	Description	maxLength	4
Restrictions	Description				
maxLength	4				

## PRDDESC

Attribute	Description				
Name	PRDDESC				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## USERFUNCDISALLOW

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCDISALLOW	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FUNCDISALLOWFUNCID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCDISALLOWFUNCID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## USERROLE

<b>Attribute</b>	<b>Description</b>	
Name	USERROLE	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEBRNCD

<b>Attribute</b>	<b>Description</b>	
Name	ROLEBRNCD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## USRROLEID

<b>Attribute</b>	<b>Description</b>	
Name	USRROLEID	
Datatype	string	
Description		

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## MASTERROLEDESC

<b>Attribute</b>	<b>Description</b>	
Name	MASTERROLEDESC	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	45

## USERSFUNCTIONS

<b>Attribute</b>	<b>Description</b>	
Name	USERSFUNCTIONS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## USERFUNCBRNCD

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCBRNCD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## USERFUNCFUNCID

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCFUNCID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## CONTROL1

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL1	
Datatype	decimal	
Description		



Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL2	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL4

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL4	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL6

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL6	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL8

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL8	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## USERFUNCCTRL10

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCCTRL10	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL11

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL11	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL12

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL12	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL13

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL13	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

#### CONTROL14

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL14	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

#### CONTROL15

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL15	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

#### CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

#### Grp-Restriction

<b>Attribute</b>	<b>Description</b>	
Name	Grp-Restriction	
Datatype		
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### GROUP\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_CODE	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

### GROUP\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_DESC	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

### Centralisation

<b>Attribute</b>	<b>Description</b>	
Name	Centralisation	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### USRROLEID

<b>Attribute</b>	<b>Description</b>	
Name	USRROLEID	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

### ROLDESC

<b>Attribute</b>	<b>Description</b>	
Name	ROLDESC	
Datatype	string	

Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

### Dshmst

<b>Attribute</b>	<b>Description</b>	
Name	Dshmst	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

### USRID

<b>Attribute</b>	<b>Description</b>	
Name	USRID	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

### USRNAME

<b>Attribute</b>	<b>Description</b>	
Name	USRNAME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

### Dshdet

<b>Attribute</b>	<b>Description</b>	
Name	Dshdet	
Datatype		
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1000

## SEQUENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	SEQUENCE_NO	
Datatype	decimal	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## DBWHERECLAUSE

<b>Attribute</b>	<b>Description</b>	
Name	DBWHERECLAUSE	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

## SHOW\_IN\_DASHBOARD

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	SHOW_IN_DASHBOARD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## Where-Master

<b>Attribute</b>	<b>Description</b>	
Name	Where-Master	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## COLUMN\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	COLUMN_NAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	2000

## WHERE\_CL

<b>Attribute</b>	<b>Description</b>	
Name	WHERE_CL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	500

## CONDITION

<b>Attribute</b>	<b>Description</b>	
Name	CONDITION	
Datatype	string	
Description		



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
Restrictions	<b>Restrictions</b>	<b>Description</b>
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
Restrictions	<b>Restrictions</b>	<b>Description</b>
	minLength	0

### 2.10.2.SM-CreateUserMaint-Req-IO-MSG.xsd

*CREATEUSERMAINT\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*USR-IO*  
*STRTDATE*  
*USRNAME*  
*USRPWD*  
*ENDDT*  
*USRLANG*  
*HOMEBRN*  
*CUSTNO*  
*LDAPUSR*  
*TIMELEVEL*  
*AUTOAUTH*  
*USRSTAT*  
*USRID*  
*EXTUSRREF*

*USRCATEG*  
*TILLALLOW*  
*ACCCLSALLOW*  
*GLALLOW*  
*USRTXNLMT*  
*LMTSCCY*  
*MAXTXNAMT*  
*MAXAUTHAMT*  
*BRNSALLOW*  
*PRDSALLOW*  
*PRDSACCESALLOW*  
*TAX\_IDENTIFIER*  
*AMOUNT\_FORMAT*  
*DATE\_FORMAT*  
*STAFFACCRESTR*  
*DEPT\_CODE*  
*USRML*  
*ELCMUSER*  
*GROUP\_CODE*  
*MULTIBRN\_ACCESS*  
*OTH\_RM\_CUST\_ACC\_ALLOW*  
*SUPERVISOR\_ID*  
*DASHBOARD\_REQD*  
*ALERTS\_ON\_HOME*  
*NO\_CUMULATIVE\_LOGINS*  
*NO\_SUCESSIVE\_LOGINS*  
*SCREENSAVERTIMEOUTINSECONDS*  
*NUMBER\_FORMAT\_MASK*  
*FRONTEND\_DEBUG\_ENABLED*  
*F10\_REQD*  
*F11\_REQD*  
*F12\_REQD*

*MFI\_USER*  
*MFAENABLED*  
*MFAID*  
*ACCESS\_CONTROL*  
*EXTN\_ALERTS*  
*RESTR\_PWD*  
*PWD*  
*MSGSRIGHTS*  
*GEN*  
*HLD*  
*CNL*  
*TSTINP*  
*CHGNODE*  
*CHGADDR*  
*REL*  
*REINS*  
*CHGMEDIA*  
*CHGPRIOR*  
*BRNMOV*  
*PRNT*  
*TSTCHK*  
*HLDAUTH*  
*CNLAUTH*  
*TSTINPAUTH*  
*CHGNODEAUTH*  
*CHGADDRAUTH*  
*RELAUTH*  
*REINSAUTH*  
*CHGMEDIAAUTH*  
*BRNMOVAUTH*  
*CHGPRIORAUTH*  
*FTUPL*

*LNKCONT*  
*MOVQ*  
*CHGBRNIN*  
*CHGADDRIN*  
*AUTHRGHTS*  
*CHGMSG*  
*CHGMSGAUTH*  
*CHGFORCCOVMATCH*  
*CHANGE\_FORCE\_RELEASE\_FUND*  
*SUPPRESS*  
*DELMSG*  
*QUEUERIGHTS*  
    *QUEUE*  
*USERTILLS*  
    *TILLID*  
    *TILLBRNCD*  
    *DESCRIPTION*  
*USERACCCLASS*  
    *ACCCLS*  
*USERGLREST*  
    *NODEGL*  
    *USERGLEXCEPT*  
        *EXCEPLEAFGL*  
*USERLIMITSROLE*  
    *LMTBRN*  
    *LMTSROLE*  
*USERBRANCHES*  
    *BRNSBRN*  
*USERPRODUCTS*  
    *PRDPRDCD*  
*USERACCESSPRODUCTS*  
    *PRDACCESSPRDCD*

*USERFUNCDISALLOW*

*FUNCDISALLOWFUNCID*

*USERROLE*

*ROLEBRNCD*

*USRROLEID*

*USERSFUNCTIONS*

*USERFUNCBRNCD*

*USERFUNCFUNCID*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*USERFUNCSCTRL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CONTROL15*

*CONTROL16*

*Grp-Restriction*

*GROUP\_CODE*

*Centralisation*

*USRROLEID*

*Dshdet*

*SEQUENCE\_NO*

*DBWHERECLAUSE*

*SHOW\_IN\_DASHBOARD*

*Where-Master*

*COLUMN\_NAME*

*WHERE\_CL*

*CONDITION*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

## CREATEUSERMAINT\_IOPK\_REQ

Attribute	Description
Name	CREATEUSERMAINT_IOPK_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description
-----------	-------------

Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	



Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	string				
Description	This is the user id in the Source system who is performing the action.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	string				
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## FUNCTIONID

Attribute	Description				
Name	FUNCTIONID				
Datatype	string				
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

## ADDL

<b>Attribute</b>	<b>Description</b>
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of CreateUserMaint

## USR-IO

Attribute	Description
Name	USR-IO
Datatype	
Description	

## STRTDATE

Attribute	Description
Name	STRTDATE
Datatype	String
Description	

## USRNAME

Attribute	Description
Name	USRNAME
Datatype	string

Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## USRPWD

<b>Attribute</b>	<b>Description</b>	
Name	USRPWD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	32

## ENDDT

<b>Attribute</b>	<b>Description</b>	
Name	ENDDT	
Datatype	String	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## USRLANG

<b>Attribute</b>	<b>Description</b>	
Name	USRLANG	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## HOMEBRN

<b>Attribute</b>	<b>Description</b>	
Name	HOMEBRN	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## CUSTNO

<b>Attribute</b>	<b>Description</b>	
Name	CUSTNO	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## LDAPUSR

<b>Attribute</b>	<b>Description</b>	
Name	LDAPUSR	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	500

## TIMELEVEL

<b>Attribute</b>	<b>Description</b>	
Name	TIMELEVEL	
Datatype	decimal	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	9

## AUTOAUTH

<b>Attribute</b>	<b>Description</b>	
Name	AUTOAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## USRSTAT

<b>Attribute</b>	<b>Description</b>	
Name	USRSTAT	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	E,H,D,L

## USRID

<b>Attribute</b>	<b>Description</b>	
Name	USRID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## EXTUSRREF

<b>Attribute</b>	<b>Description</b>	
Name	EXTUSRREF	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## USRCATEG

<b>Attribute</b>	<b>Description</b>	
Name	USRCATEG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	S,B

## TILLALLOW

<b>Attribute</b>	<b>Description</b>	
Name	TILLALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## ACCCLSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## GLALLOW

<b>Attribute</b>	<b>Description</b>	
Name	GLALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## USRTXNLMT

<b>Attribute</b>	<b>Description</b>	
Name	USRTXNLMT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,R,N

## LMTSCCY

<b>Attribute</b>	<b>Description</b>	
Name	LMTSCCY	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### MAXTXNAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXTXNAMT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### MAXAUTHAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXAUTHAMT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### BRNSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	BRNSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### PRDSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## PRDSACCESALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSACCESALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## TAX\_IDENTIFIER

<b>Attribute</b>	<b>Description</b>	
Name	TAX_IDENTIFIER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

## AMOUNT\_FORMAT

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_FORMAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	.....

## DATE\_FORMAT

<b>Attribute</b>	<b>Description</b>	
Name	DATE_FORMAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	M/d/yyyy

## STAFFACCRESTR

<b>Attribute</b>	<b>Description</b>	
Name	STAFFACCRESTR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DEPT\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	DEPT_CODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## USRML

<b>Attribute</b>	<b>Description</b>	
Name	USRML	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## ELCMUSER

<b>Attribute</b>	<b>Description</b>	
Name	ELCMUSER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## GROUP\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_CODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## MULTIBRN\_ACCESS

<b>Attribute</b>	<b>Description</b>	
Name	MULTIBRN_ACCESS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## OTH\_RM\_CUST\_ACC\_ALLOW

<b>Attribute</b>	<b>Description</b>	
Name	OTH_RM_CUST_ACC_ALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SUPERVISOR\_ID

<b>Attribute</b>	<b>Description</b>	
Name	SUPERVISOR_ID	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	80

## DASHBOARD\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	DASHBOARD_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## ALERTS\_ON\_HOME

<b>Attribute</b>	<b>Description</b>	
Name	ALERTS_ON_HOME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## NO\_CUMULATIVE\_LOGINS

<b>Attribute</b>	<b>Description</b>	
Name	NO_CUMULATIVE_LOGINS	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## NO\_SUCCESSIVE\_LOGINS

<b>Attribute</b>	<b>Description</b>	
Name	NO_SUCCESSIVE_LOGINS	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### SCREENSAVERTIMEOUTINSECONDS

<b>Attribute</b>	<b>Description</b>	
Name	SCREENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### NUMBER\_FORMAT\_MASK

<b>Attribute</b>	<b>Description</b>	
Name	NUMBER_FORMAT_MASK	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	M,L

### FRONTEND\_DEBUG\_ENABLED

<b>Attribute</b>	<b>Description</b>	
Name	FRONTEND_DEBUG_ENABLED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F10\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F10_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F11\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F11_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F12\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F12_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### MFI\_USER

<b>Attribute</b>	<b>Description</b>	
Name	MFI_USER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### MFAENABLED

<b>Attribute</b>	<b>Description</b>	
Name	MFAENABLED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	N,Y,L

## MFAID

<b>Attribute</b>	<b>Description</b>	
Name	MFAID	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

## ACCESS\_CONTROL

<b>Attribute</b>	<b>Description</b>	
Name	ACCESS_CONTROL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,G,B

## EXTN\_ALERTS

<b>Attribute</b>	<b>Description</b>	
Name	EXTN_ALERTS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## RESTR\_PWD

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_PWD	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded



**PWD**

Attribute	Description	
Name	PWD	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	12

**MSGSRIGHTS**

Attribute	Description	
Name	MSGSRIGHTS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

**GEN**

Attribute	Description	
Name	GEN	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

**HLD**

Attribute	Description	
Name	HLD	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

**CNL**

Attribute	Description	
Name	CNL	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINP

<b>Attribute</b>	<b>Description</b>	
Name	TSTINP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODE

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDR

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REL

<b>Attribute</b>	<b>Description</b>	
Name	REL	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINS

<b>Attribute</b>	<b>Description</b>	
Name	REINS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIA

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIA	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIOR

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIOR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOV

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOV	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PRNT

<b>Attribute</b>	<b>Description</b>	
Name	PRNT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTCHK

<b>Attribute</b>	<b>Description</b>	
Name	TSTCHK	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLDAUTH

<b>Attribute</b>	<b>Description</b>	
Name	HLDAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNLAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CNLAUTH	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINPAUTH

<b>Attribute</b>	<b>Description</b>	
Name	TSTINPAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODEAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## RELAUTH

<b>Attribute</b>	<b>Description</b>	
Name	RELAUTH	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINSAUTH

<b>Attribute</b>	<b>Description</b>	
Name	REINSAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIAAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIAAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOVAUTH

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOVAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIORAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIORAUTH	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## FTUPL

<b>Attribute</b>	<b>Description</b>	
Name	FTUPL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## LNKCONT

<b>Attribute</b>	<b>Description</b>	
Name	LNKCONT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MOVQ

<b>Attribute</b>	<b>Description</b>	
Name	MOVQ	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGBRNIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGBRNIN	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRIN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## AUTHRGHTS

<b>Attribute</b>	<b>Description</b>	
Name	AUTHRGHTS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSG

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSGAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSGAUTH	
Datatype	string	
Description		



Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	enumeration	Y,N

### CHGFORCCOVMATCH

<b>Attribute</b>	<b>Description</b>	
Name	CHGFORCCOVMATCH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	enumeration	Y,N

### CHANGE\_FORCE\_RELEASE\_FUND

<b>Attribute</b>	<b>Description</b>	
Name	CHANGE_FORCE_RELEASE_FUND	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	enumeration	Y,N

### SUPPRESS

<b>Attribute</b>	<b>Description</b>	
Name	SUPPRESS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	enumeration	Y,N

### DELMSG

<b>Attribute</b>	<b>Description</b>	
Name	DELMSG	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## QUEUERIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	QUEUERIGHTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## QUEUE

<b>Attribute</b>	<b>Description</b>	
Name	QUEUE	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## USERTILLS

<b>Attribute</b>	<b>Description</b>	
Name	USERTILLS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## TILLID

<b>Attribute</b>	<b>Description</b>	
Name	TILLID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## TILLBRNCD

<b>Attribute</b>	<b>Description</b>	
Name	TILLBRNCD	
Datatype	string	

Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## DESCRIPTION

Attribute	Description				
Name	DESCRIPTION				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>255</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

## USERACCCLASS

Attribute	Description						
Name	USERACCCLASS						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## ACCCLS

Attribute	Description				
Name	ACCCLS				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>6</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	6
Restrictions	Description				
maxLength	6				

## USERGLREST

Attribute	Description						
Name	USERGLREST						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## NODEGL

Attribute	Description
Name	NODEGL

Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## USERGLEXCEPT

<b>Attribute</b>	<b>Description</b>	
Name	USERGLEXCEPT	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## EXCEPLEAFGL

<b>Attribute</b>	<b>Description</b>	
Name	EXCEPLEAFGL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## USERLIMITSROLE

<b>Attribute</b>	<b>Description</b>	
Name	USERLIMITSROLE	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## LMTBRN

<b>Attribute</b>	<b>Description</b>	
Name	LMTBRN	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## LMTSROLE

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	LMTSROLE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## USERBRANCHES

<b>Attribute</b>	<b>Description</b>	
Name	USERBRANCHES	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## BRNSBRN

<b>Attribute</b>	<b>Description</b>	
Name	BRNSBRN	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## USERPRODUCTS

<b>Attribute</b>	<b>Description</b>	
Name	USERPRODUCTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PRDPRDCD

<b>Attribute</b>	<b>Description</b>	
Name	PRDPRDCD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

## USERACCESSPRODUCTS

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	USERACCESSPRODUCTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	maxOccurs	unbounded

### PRDACCESSPRDCD

<b>Attribute</b>	<b>Description</b>	
Name	PRDACCESSPRDCD	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	4

### USERFUNCDISALLOW

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCDISALLOW	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	maxOccurs	unbounded

### FUNCDISALLOWFUNCID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCDISALLOWFUNCID	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	8

### USERROLE

<b>Attribute</b>	<b>Description</b>	
Name	USERROLE	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	maxOccurs	unbounded

### ROLEBRNCD

<b>Attribute</b>	<b>Description</b>	
Name	ROLEBRNCD	
Datatype	string	

Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## USRROLEID

Attribute	Description				
Name	USRROLEID				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>15</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## USERSFUNCTIONS

Attribute	Description						
Name	USERSFUNCTIONS						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## USERFUNCBRNCD

Attribute	Description				
Name	USERFUNCBRNCD				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## USERFUNCFUNCID

Attribute	Description				
Name	USERFUNCFUNCID				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>8</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	8
Restrictions	Description				
maxLength	8				

## CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	decimal
Description	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL2	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL4

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL4	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description		



Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL6

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL6	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL8

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL8	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### USERFUNCCTRL10

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCCTRL10	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL11

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL11	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL12

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL12	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL13

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL13	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

#### CONTROL14

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL14	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

#### CONTROL15

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL15	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

#### CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

#### Grp-Restriction

<b>Attribute</b>	<b>Description</b>	
Name	Grp-Restriction	
Datatype		
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## GROUP\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_CODE	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

## Centralisation

<b>Attribute</b>	<b>Description</b>	
Name	Centralisation	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## USRROLEID

<b>Attribute</b>	<b>Description</b>	
Name	USRROLEID	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## Dshdet

<b>Attribute</b>	<b>Description</b>	
Name	Dshdet	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## SEQUENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	SEQUENCE_NO	
Datatype	decimal	
Description		

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## DBWHERECLAUSE

<b>Attribute</b>	<b>Description</b>	
Name	DBWHERECLAUSE	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

## SHOW\_IN\_DASHBOARD

<b>Attribute</b>	<b>Description</b>	
Name	SHOW_IN_DASHBOARD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## Where-Master

<b>Attribute</b>	<b>Description</b>	
Name	Where-Master	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## COLUMN\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	COLUMN_NAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	2000

## WHERE\_CL

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	WHERE_CL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	500

## CONDITION

<b>Attribute</b>	<b>Description</b>	
Name	CONDITION	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

### 2.10.3.SM-CreateUserMaint-Res-Full-MSG.xsd

*CREATEUSERMAINT\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*USR-Full*

*STRDATE*

*USRNAME*  
*USRPWD*  
*ENDDT*  
*USRLANG*  
*HOMEBRN*  
*CUSTNO*  
*LDAPUSR*  
*TIMELEVEL*  
*AUTOAUTH*  
*USRSTAT*  
*USRID*  
*EXTUSRREF*  
*USRCATEG*  
*TILLALLOW*  
*ACCCLSALLOW*  
*GLALLOW*  
*USRTXNLMT*  
*LMTSCCY*  
*MAXTXNAMT*  
*MAXAUTHAMT*  
*BRNSALLOW*  
*PRDSALLOW*  
*PRDSACCESALLOW*  
*TAX\_IDENTIFIER*  
*AMOUNT\_FORMAT*  
*DATE\_FORMAT*  
*STAFFACCRESTR*  
*DEPT\_CODE*  
*DEPT\_DESC*  
*USRML*  
*ELCMUSER*  
*GROUP\_CODE*



*MULTIBRN\_ACCESS*  
*OTH\_RM\_CUST\_ACC\_ALLOW*  
*SUPERVISOR\_ID*  
*SUPERVISOR\_NAME*  
*DASHBOARD\_REQD*  
*ALERTS\_ON\_HOME*  
*REFERENCE\_NO*  
*NO\_CUMULATIVE\_LOGINS*  
*NO\_SUCESSIVE\_LOGINS*  
*SCREENSAVERTIMEOUTINSECONDS*  
*NUMBER\_FORMAT\_MASK*  
*FRONTEND\_DEBUG\_ENABLED*  
*F10\_REQD*  
*F11\_REQD*  
*F12\_REQD*  
*MFI\_USER*  
*MFAENABLED*  
*MFAID*  
*ACCESS\_CONTROL*  
*EXTN\_ALERTS*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*RESTR\_PWD*  
*PWD*  
*MSGSRIGHTS*  
*GEN*  
*HLD*

*CNL*  
*TSTINP*  
*CHGNODE*  
*CHGADDR*  
*REL*  
*REINS*  
*CHGMEDIA*  
*CHGPRIOR*  
*BRNMOV*  
*PRNT*  
*TSTCHK*  
*HLDAUTH*  
*CNLAUTH*  
*TSTINPAUTH*  
*CHGNODEAUTH*  
*CHGADDRAUTH*  
*RELAUTH*  
*REINSAUTH*  
*CHGMEDIAAUTH*  
*BRNMOVAUTH*  
*CHGPRIORAUTH*  
*FTUPL*  
*LNKCONT*  
*MOVQ*  
*CHGBRNIN*  
*CHGADDRIN*  
*AUTHRGHTS*  
*CHGMSG*  
*CHGMSGAUTH*  
*CHGFORCCOVMATCH*  
*CHANGE\_FORCE\_RELEASE\_FUND*  
*SUPPRESS*

*DELMSG*  
*QUEUERIGHTS*  
    *QUEUE*  
*USERTILLS*  
    *TILLID*  
    *TILLBRNCD*  
    *DESCRIPTION*  
*USERACCCLASS*  
    *ACCCLS*  
*USERGLREST*  
    *NODEGL*  
    *USERGLEXCEPT*  
        *EXCEPLEAFGL*  
*USERLIMITSROLE*  
    *LMTBRN*  
    *LMTSROLE*  
    *QLMTCCY*  
    *QINPLMT*  
    *QAUTHLMT*  
*USERBRANCHES*  
    *BRNSBRN*  
    *BRNNAME*  
*USERPRODUCTS*  
    *PRDPRDCD*  
    *PRDDESC*  
*USERACCESSPRODUCTS*  
    *PRDACCESSPRDCD*  
    *PRDDESC*  
*USERFUNCDISALLOW*  
    *FUNCDISALLOWFUNCID*  
*USERROLE*  
    *ROLEBRNCD*

*USRROLEID*

*MASTERROLEDESC*

*USERSFUNCTIONS*

*USERFUNCBRNCD*

*USERFUNCFUNCID*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*USERFUNCSCTRL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CONTROL15*

*CONTROL16*

*Grp-Restriction*

*GROUP\_CODE*

*GROUP\_DESC*

*Centralisation*

*USRROLEID*

*ROLDESC*

*Dshmst*

*USRID*

*USRNAME*

*Dshdet*

*FUNCTIONID*

*DESCRIPTION*

*SEQUENCE\_NO*

*DBWHERECLAUSE*

*SHOW\_IN\_DASHBOARD*

*Where-Master*

*COLUMN\_NAME*

*WHERE\_CL*

*CONDITION*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## **CREATEUSERMAINT\_FSFS\_RES**

<b>Attribute</b>	<b>Description</b>
Name	CREATEUSERMAINT_FSFS_RES
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

<b>Attribute</b>	<b>Description</b>
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

Attribute	Description



Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

## USR-Full

Attribute	Description
Name	USR-Full
Datatype	
Description	

## STRTDATE

Attribute	Description
Name	STRTDATE
Datatype	String
Description	

## USRNAME

Attribute	Description				
Name	USRNAME				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

## USRPWD

Attribute	Description				
Name	USRPWD				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>32</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	32
Restrictions	Description				
maxLength	32				

## ENDDT

Attribute	Description				
Name	ENDDT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## USRLANG

Attribute	Description	
Name	USRLANG	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## HOMEBRN

Attribute	Description	
Name	HOMEBRN	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## LDAPUSR

Attribute	Description	
Name	LDAPUSR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	500

## TIMELEVEL

Attribute	Description
Name	TIMELEVEL
Datatype	decimal
Description	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	9

## AUTOAUTH

<b>Attribute</b>	<b>Description</b>	
Name	AUTOAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## USRSTAT

<b>Attribute</b>	<b>Description</b>	
Name	USRSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	E,H,D,L

## USRID

<b>Attribute</b>	<b>Description</b>	
Name	USRID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## EXTUSRREF

<b>Attribute</b>	<b>Description</b>	
Name	EXTUSRREF	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## USRCATEG

<b>Attribute</b>	<b>Description</b>	
Name	USRCATEG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	S,B

## TILLALLOW

<b>Attribute</b>	<b>Description</b>	
Name	TILLALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## ACCCLSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## GLALLOW

<b>Attribute</b>	<b>Description</b>	
Name	GLALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### USRTXNLMT

<b>Attribute</b>	<b>Description</b>	
Name	USRTXNLMT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,R,N

### LMTSCCY

<b>Attribute</b>	<b>Description</b>	
Name	LMTSCCY	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### MAXTXNAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXTXNAMT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### MAXAUTHAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXAUTHAMT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### BRNSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	BRNSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### PRDSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### PRDSACCESALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSACCESALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### TAX\_IDENTIFIER

<b>Attribute</b>	<b>Description</b>	
Name	TAX_IDENTIFIER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

## AMOUNT\_FORMAT

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_FORMAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	****.***

## DATE\_FORMAT

<b>Attribute</b>	<b>Description</b>	
Name	DATE_FORMAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	M/d/yyyy

## STAFFACCRESTR

<b>Attribute</b>	<b>Description</b>	
Name	STAFFACCRESTR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DEPT\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	DEPT_CODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## DEPT\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	DEPT_DESC	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## USRML

<b>Attribute</b>	<b>Description</b>	
Name	USRML	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## ELCMUSER

<b>Attribute</b>	<b>Description</b>	
Name	ELCMUSER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## GROUP\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_CODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### MULTIBRN\_ACCESS

<b>Attribute</b>	<b>Description</b>	
Name	MULTIBRN_ACCESS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### OTH\_RM\_CUST\_ACC\_ALLOW

<b>Attribute</b>	<b>Description</b>	
Name	OTH_RM_CUST_ACC_ALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### SUPERVISOR\_ID

<b>Attribute</b>	<b>Description</b>	
Name	SUPERVISOR_ID	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	80

### SUPERVISOR\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	SUPERVISOR_NAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## DASHBOARD\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	DASHBOARD_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## ALERTS\_ON\_HOME

<b>Attribute</b>	<b>Description</b>	
Name	ALERTS_ON_HOME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REFERENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	REFERENCE_NO	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## NO\_CUMULATIVE\_LOGINS

<b>Attribute</b>	<b>Description</b>	
Name	NO_CUMULATIVE_LOGINS	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### NO\_SUCCESSIVE\_LOGINS

<b>Attribute</b>	<b>Description</b>	
Name	NO_SUCCESSIVE_LOGINS	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### SCREENSAVERTIMEOUTINSECONDS

<b>Attribute</b>	<b>Description</b>	
Name	SCREENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### NUMBER\_FORMAT\_MASK

<b>Attribute</b>	<b>Description</b>	
Name	NUMBER_FORMAT_MASK	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	M,L

### FRONTEND\_DEBUG\_ENABLED

<b>Attribute</b>	<b>Description</b>	
Name	FRONTEND_DEBUG_ENABLED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F10\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F10_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F11\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F11_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F12\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F12_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### MFI\_USER

<b>Attribute</b>	<b>Description</b>	
Name	MFI_USER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MFAENABLED

<b>Attribute</b>	<b>Description</b>	
Name	MFAENABLED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	N,Y,L

## MFAID

<b>Attribute</b>	<b>Description</b>	
Name	MFAID	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

## ACCESS\_CONTROL

<b>Attribute</b>	<b>Description</b>	
Name	ACCESS_CONTROL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,G,B

## EXTN\_ALERTS

<b>Attribute</b>	<b>Description</b>	
Name	EXTN_ALERTS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## RESTR\_PWD

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_PWD	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

**PWD**

Attribute	Description	
Name	PWD	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	12

**MSGSRIGHTS**

Attribute	Description	
Name	MSGSRIGHTS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

**GEN**

Attribute	Description	
Name	GEN	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

**HLD**

Attribute	Description	
Name	HLD	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

**CNL**

Attribute	Description	
Name	CNL	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINP

<b>Attribute</b>	<b>Description</b>	
Name	TSTINP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODE

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDR

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REL

<b>Attribute</b>	<b>Description</b>	
Name	REL	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINS

<b>Attribute</b>	<b>Description</b>	
Name	REINS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIA

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIA	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIOR

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIOR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOV

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOV	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PRNT

<b>Attribute</b>	<b>Description</b>	
Name	PRNT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTCHK

<b>Attribute</b>	<b>Description</b>	
Name	TSTCHK	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLDAUTH

<b>Attribute</b>	<b>Description</b>	
Name	HLDAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNLAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CNLAUTH	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINPAUTH

<b>Attribute</b>	<b>Description</b>	
Name	TSTINPAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODEAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## RELAUTH

<b>Attribute</b>	<b>Description</b>	
Name	RELAUTH	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINSAUTH

<b>Attribute</b>	<b>Description</b>	
Name	REINSAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIAAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIAAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOVAUTH

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOVAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIORAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIORAUTH	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## FTUPL

<b>Attribute</b>	<b>Description</b>	
Name	FTUPL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## LNKCONT

<b>Attribute</b>	<b>Description</b>	
Name	LNKCONT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MOVQ

<b>Attribute</b>	<b>Description</b>	
Name	MOVQ	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGBRNIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGBRNIN	
Datatype	string	
Description		



Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRIN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## AUTHRGHTS

<b>Attribute</b>	<b>Description</b>	
Name	AUTHRGHTS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSG

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSGAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSGAUTH	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHGFORCCOVMATCH

<b>Attribute</b>	<b>Description</b>	
Name	CHGFORCCOVMATCH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHANGE\_FORCE\_RELEASE\_FUND

<b>Attribute</b>	<b>Description</b>	
Name	CHANGE_FORCE_RELEASE_FUND	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### SUPPRESS

<b>Attribute</b>	<b>Description</b>	
Name	SUPPRESS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### DELMSG

<b>Attribute</b>	<b>Description</b>	
Name	DELMSG	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## QUEUERIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	QUEUERIGHTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## QUEUE

<b>Attribute</b>	<b>Description</b>	
Name	QUEUE	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## USERTILLS

<b>Attribute</b>	<b>Description</b>	
Name	USERTILLS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## TILLID

<b>Attribute</b>	<b>Description</b>	
Name	TILLID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## TILLBRNCD

<b>Attribute</b>	<b>Description</b>	
Name	TILLBRNCD	
Datatype	string	

Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## DESCRIPTION

Attribute	Description				
Name	DESCRIPTION				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>255</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

## USERACCCLASS

Attribute	Description						
Name	USERACCCLASS						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## ACCCLS

Attribute	Description				
Name	ACCCLS				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>6</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	6
Restrictions	Description				
maxLength	6				

## USERGLREST

Attribute	Description						
Name	USERGLREST						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## NODEGL

Attribute	Description
Name	NODEGL

Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## USERGLEXCEPT

<b>Attribute</b>	<b>Description</b>	
Name	USERGLEXCEPT	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## EXCEPLEAFGL

<b>Attribute</b>	<b>Description</b>	
Name	EXCEPLEAFGL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## USERLIMITSROLE

<b>Attribute</b>	<b>Description</b>	
Name	USERLIMITSROLE	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## LMTBRN

<b>Attribute</b>	<b>Description</b>	
Name	LMTBRN	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## LMTSROLE

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	LMTSROLE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## QLMTCCY

<b>Attribute</b>	<b>Description</b>	
Name	QLMTCCY	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## QINPLMT

<b>Attribute</b>	<b>Description</b>	
Name	QINPLMT	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## QAUHLMT

<b>Attribute</b>	<b>Description</b>	
Name	QAUHLMT	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## USERBRANCHES

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	USERBRANCHES	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## BRNSBRN

<b>Attribute</b>	<b>Description</b>	
Name	BRNSBRN	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## BRNNAME

<b>Attribute</b>	<b>Description</b>	
Name	BRNNAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## USERPRODUCTS

<b>Attribute</b>	<b>Description</b>	
Name	USERPRODUCTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PRDPRDCD

<b>Attribute</b>	<b>Description</b>	
Name	PRDPRDCD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

## PRDDESC

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	PRDESC	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	105
	<b>Description</b>	

## USERACCESSPRODUCTS

<b>Attribute</b>	<b>Description</b>	
Name	USERACCESSPRODUCTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## PRDACCESSPRDCD

<b>Attribute</b>	<b>Description</b>	
Name	PRDACCESSPRDCD	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	4
	<b>Description</b>	

## PRDESC

<b>Attribute</b>	<b>Description</b>	
Name	PRDESC	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	105
	<b>Description</b>	

## USERFUNCDISALLOW

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCDISALLOW	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	



## FUNCDISALLOWFUNCID

Attribute	Description				
Name	FUNCDISALLOWFUNCID				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr></tbody></table>	Restrictions	Description	maxLength	8
Restrictions	Description				
maxLength	8				

## USERROLE

Attribute	Description						
Name	USERROLE						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## ROLEBRNCD

Attribute	Description				
Name	ROLEBRNCD				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## USRROLEID

Attribute	Description				
Name	USRROLEID				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## MASTERROLEDESC

Attribute	Description				
Name	MASTERROLEDESC				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>45</td></tr></tbody></table>	Restrictions	Description	maxLength	45
Restrictions	Description				
maxLength	45				

## USERSFUNCTIONS

Attribute	Description	
Name	USERSFUNCTIONS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## USERFUNCBRNCD

Attribute	Description	
Name	USERFUNCBRNCD	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

## USERFUNCFUNCID

Attribute	Description	
Name	USERFUNCFUNCID	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	8

## CONTROL1

Attribute	Description	
Name	CONTROL1	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

## CONTROL2

Attribute	Description	
Name	CONTROL2	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL4

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL4	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL6

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL6	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL8

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL8	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### USERFUNCCTRL10

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCCTRL10	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL11

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL11	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL12

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL12	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL13

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL13	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL14

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL14	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL15

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL15	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### Grp-Restriction

<b>Attribute</b>	<b>Description</b>	
Name	Grp-Restriction	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### GROUP\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_CODE	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

### GROUP\_DESC

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	GROUP_DESC	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

## Centralisation

<b>Attribute</b>	<b>Description</b>	
Name	Centralisation	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## USRROLEID

<b>Attribute</b>	<b>Description</b>	
Name	USRROLEID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## ROLDESC

<b>Attribute</b>	<b>Description</b>	
Name	ROLDESC	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## Dshmst

<b>Attribute</b>	<b>Description</b>	
Name	Dshmst	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## USRID

Attribute	Description				
Name	USRID				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## USRNAME

Attribute	Description				
Name	USRNAME				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

## Dshdet

Attribute	Description						
Name	Dshdet						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## FUNCTIONID

Attribute	Description				
Name	FUNCTIONID				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## DESCRIPTION

Attribute	Description
-----------	-------------



Name	DESCRIPTION	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1000

## SEQUENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	SEQUENCE_NO	
Datatype	decimal	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## DBWHERECLAUSE

<b>Attribute</b>	<b>Description</b>	
Name	DBWHERECLAUSE	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

## SHOW\_IN\_DASHBOARD

<b>Attribute</b>	<b>Description</b>	
Name	SHOW_IN_DASHBOARD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## Where-Master

<b>Attribute</b>	<b>Description</b>	
Name	Where-Master	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## COLUMN\_NAME

Attribute		Description	
Name	COLUMN_NAME		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	2000	

## WHERE\_CL

Attribute		Description	
Name	WHERE_CL		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	500	

## CONDITION

Attribute		Description	
Name	CONDITION		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	30	

## UDFDETAILS

Attribute		Description	
Name	UDFDETAILS		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
	maxOccurs	unbounded	

## FLDNAM

Attribute		Description	
Name	FLDNAM		

Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

### 2.10.4.SM-CreateUserMaint-Res-PK-MSG.xsd

*CREATEUSERMAINT\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*USR-PK*  
*USRID*  
*USR-IO*  
*STRDATE*  
*USRNAME*  
*USRPWD*  
*ENDDT*  
*USRLANG*  
*HOMEBRN*  
*CUSTNO*  
*LDAPUSR*  
*TIMELEVEL*  
*AUTOAUTH*  
*USRSTAT*  
*USRID*  
*EXTUSRREF*  
*USRCATEG*  
*TILLALLOW*  
*ACCCLSALLOW*  
*GLALLOW*

*USRTXNLMT*  
*LMTSCCY*  
*MAXTXNAMT*  
*MAXAUTHAMT*  
*BRNSALLOW*  
*PRDSALLOW*  
*PRDSACCESALLOW*  
*TAX\_IDENTIFIER*  
*AMOUNT\_FORMAT*  
*DATE\_FORMAT*  
*STAFFACCRESTR*  
*DEPT\_CODE*  
*USRML*  
*ELCMUSER*  
*GROUP\_CODE*  
*MULTIBRN\_ACCESS*  
*OTH\_RM\_CUST\_ACC\_ALLOW*  
*SUPERVISOR\_ID*  
*DASHBOARD\_REQD*  
*ALERTS\_ON\_HOME*  
*NO\_CUMULATIVE\_LOGINS*  
*NO\_SUCESSIVE\_LOGINS*  
*SCREENSAVERTIMEOUTINSECONDS*  
*NUMBER\_FORMAT\_MASK*  
*FRONTEND\_DEBUG\_ENABLED*  
*F10\_REQD*  
*F11\_REQD*  
*F12\_REQD*  
*MFI\_USER*  
*MFAENABLED*  
*MFAID*  
*ACCESS\_CONTROL*

*EXTN\_ALERTS*

*RESTR\_PWD*

*PWD*

*MSGSRIGHTS*

*GEN*

*HLD*

*CNL*

*TSTINP*

*CHGNODE*

*CHGADDR*

*REL*

*REINS*

*CHGMEDIA*

*CHGPRIOR*

*BRNMOV*

*PRNT*

*TSTCHK*

*HLDAUTH*

*CNLAUTH*

*TSTINPAUTH*

*CHGNODEAUTH*

*CHGADDRAUTH*

*RELAUTH*

*REINSAUTH*

*CHGMEDIAAUTH*

*BRNMOVAUTH*

*CHGPRIORAUTH*

*FTUPL*

*LNKCONT*

*MOVQ*

*CHGBRNIN*

*CHGADDRIN*

*AUTHRGHTS*

*CHGMSG*

*CHGMSGAUTH*

*CHGFORCCOVMATCH*

*CHANGE\_FORCE\_RELEASE\_FUND*

*SUPPRESS*

*DELMSG*

*QUEUERIGHTS*

*QUEUE*

*USERTILLS*

*TILLID*

*TILLBRNCD*

*DESCRIPTION*

*USERACCCLASS*

*ACCCLS*

*USERGLREST*

*NODEGL*

*USERGLEXCEPT*

*EXCEPLEAFGL*

*USERLIMITSROLE*

*LMTBRN*

*LMTSROLE*

*USERBRANCHES*

*BRNSBRN*

*USERPRODUCTS*

*PRDPRDCD*

*USERACCESSPRODUCTS*

*PRDACCESSPRDCD*

*USERFUNCDISALLOW*

*FUNCDISALLOWFUNCID*

*USERROLE*

*ROLEBRNCD*



*USRROLEID*

*USERSFUNCTIONS*

*USERFUNCBRNCD*

*USERFUNCFUNCID*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*USERFUNCSCTRL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CONTROL15*

*CONTROL16*

*Grp-Restriction*

*GROUP\_CODE*

*Centralisation*

*USRROLEID*

*Dshdet*

*SEQUENCE\_NO*

*DBWHERECLAUSE*

*SHOW\_IN\_DASHBOARD*

*Where-Master*

*COLUMN\_NAME*

*WHERE\_CL*

*CONDITION*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## CREATEUSERMAINT\_IOPK\_RES

Attribute	Description
Name	CREATEUSERMAINT_IOPK_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	string
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	string
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	

Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

## USR-PK

<b>Attribute</b>	<b>Description</b>
Name	USR-PK
Datatype	
Description	

## USRID

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	USRID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## USR-IO

<b>Attribute</b>	<b>Description</b>
Name	USR-IO
Datatype	
Description	

## STRTDATE

<b>Attribute</b>	<b>Description</b>
Name	STRTDATE
Datatype	String
Description	

## USRNAME

<b>Attribute</b>	<b>Description</b>	
Name	USRNAME	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## USRPWD

<b>Attribute</b>	<b>Description</b>	
Name	USRPWD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	32

## ENDDT

<b>Attribute</b>	<b>Description</b>	
Name	ENDDT	
Datatype	String	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## USRLANG



Attribute	Description	
Name	USRLANG	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

## HOMEBRN

Attribute	Description	
Name	HOMEBRN	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

## CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9

## LDAPUSR

Attribute	Description	
Name	LDAPUSR	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	500

## TIMELEVEL

Attribute	Description	
Name	TIMELEVEL	
Datatype	decimal	
Description		
Restrictions		
	Restrictions	Description
	totalDigits	22
	minInclusive	0
	maxInclusive	9

## AUTOAUTH

Attribute	Description	
Name	AUTOAUTH	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

## USRSTAT

Attribute	Description	
Name	USRSTAT	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	E,H,D,L

## USRID

Attribute	Description	
Name	USRID	
Datatype	string	
Description		
Restrictions	Restrictions	Description
	maxLength	12

## EXTUSRREF

Attribute	Description	
Name	EXTUSRREF	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

## USRCATEG

Attribute	Description
Name	USRCATEG

Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	S,B

## TILLALLOW

<b>Attribute</b>	<b>Description</b>	
Name	TILLALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## ACCCLSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## GLALLOW

<b>Attribute</b>	<b>Description</b>	
Name	GLALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## USRTXNLMT

<b>Attribute</b>	<b>Description</b>	
Name	USRTXNLMT	

Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,R,N

### LMTSCCY

<b>Attribute</b>	<b>Description</b>	
Name	LMTSCCY	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### MAXTXNAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXTXNAMT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### MAXAUTHAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXAUTHAMT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### BRNSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	BRNSALLOW	

Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## PRDSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## PRDSACCESALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSACCESALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## TAX\_IDENTIFIER

<b>Attribute</b>	<b>Description</b>	
Name	TAX_IDENTIFIER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

## AMOUNT\_FORMAT

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_FORMAT	

Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	.....

## DATE\_FORMAT

<b>Attribute</b>	<b>Description</b>	
Name	DATE_FORMAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	M/d/yyyy

## STAFFACCRESTR

<b>Attribute</b>	<b>Description</b>	
Name	STAFFACCRESTR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DEPT\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	DEPT_CODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## USRML

<b>Attribute</b>	<b>Description</b>
Name	USRML

Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## ELCMUSER

<b>Attribute</b>	<b>Description</b>	
Name	ELCMUSER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## GROUP\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_CODE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## MULTIBRN\_ACCESS

<b>Attribute</b>	<b>Description</b>	
Name	MULTIBRN_ACCESS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## OTH\_RM\_CUST\_ACC\_ALLOW

<b>Attribute</b>	<b>Description</b>	
Name	OTH_RM_CUST_ACC_ALLOW	

Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SUPERVISOR\_ID

<b>Attribute</b>	<b>Description</b>	
Name	SUPERVISOR_ID	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	80

## DASHBOARD\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	DASHBOARD_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## ALERTS\_ON\_HOME

<b>Attribute</b>	<b>Description</b>	
Name	ALERTS_ON_HOME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## NO\_CUMULATIVE\_LOGINS

<b>Attribute</b>	<b>Description</b>	
Name	NO_CUMULATIVE_LOGINS	



Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## NO\_SUCESSIVE\_LOGINS

<b>Attribute</b>	<b>Description</b>	
Name	NO_SUCESSIVE_LOGINS	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## SCREENSAVERTIMEOUTINSECONDS

<b>Attribute</b>	<b>Description</b>	
Name	SCREENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## NUMBER\_FORMAT\_MASK

<b>Attribute</b>	<b>Description</b>	
Name	NUMBER_FORMAT_MASK	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	M,L

## FRONTEND\_DEBUG\_ENABLED

<b>Attribute</b>	<b>Description</b>	
Name	FRONTEND_DEBUG_ENABLED	

Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F10\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F10_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F11\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F11_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F12\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F12_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### MFI\_USER

<b>Attribute</b>	<b>Description</b>
Name	MFI_USER

Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MFAENABLED

<b>Attribute</b>	<b>Description</b>	
Name	MFAENABLED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	N,Y,L

## MFAID

<b>Attribute</b>	<b>Description</b>	
Name	MFAID	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

## ACCESS\_CONTROL

<b>Attribute</b>	<b>Description</b>	
Name	ACCESS_CONTROL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,G,B

## EXTN\_ALERTS

<b>Attribute</b>	<b>Description</b>	
Name	EXTN_ALERTS	

Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	enumeration	Y,N
	<b>Description</b>	

## RESTR\_PWD

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_PWD	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## PWD

<b>Attribute</b>	<b>Description</b>	
Name	PWD	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	12
	<b>Description</b>	

## MSGSRIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	MSGSRIGHTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	

## GEN

<b>Attribute</b>	<b>Description</b>	
Name	GEN	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	enumeration	Y,N
	<b>Description</b>	

Attribute	Description	
Name	HLD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNL

Attribute	Description	
Name	CNL	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINP

Attribute	Description	
Name	TSTINP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODE

Attribute	Description	
Name	CHGNODE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDR

Attribute	Description	
Name	CHGADDR	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## REL

Attribute	Description	
Name	REL	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## REINS

Attribute	Description	
Name	REINS	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGMEDIA

Attribute	Description	
Name	CHGMEDIA	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGPRIOR

Attribute	Description	
Name	CHGPRIOR	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## BRNMOV

Attribute	Description	
Name	BRNMOV	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## PRNT

Attribute	Description	
Name	PRNT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## TSTCHK

Attribute	Description	
Name	TSTCHK	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## HLDAUTH

Attribute	Description	
Name	HLDAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNLAUTH

Attribute	Description	
Name	CNLAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINPAUTH

Attribute	Description	
Name	TSTINPAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODEAUTH

Attribute	Description	
Name	CHGNODEAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRAUTH



Attribute	Description	
Name	CHGADDRAUTH	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## RELAUTH

Attribute	Description	
Name	RELAUTH	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## REINSAUTH

Attribute	Description	
Name	REINSAUTH	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGMEDIAAUTH

Attribute	Description	
Name	CHGMEDIAAUTH	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## BRNMOVAUTH

Attribute	Description	
Name	BRNMOVAUTH	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGPRIORAUTH

Attribute	Description	
Name	CHGPRIORAUTH	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## FTUPL

Attribute	Description	
Name	FTUPL	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## LNKCONT

Attribute	Description	
Name	LNKCONT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## MOVQ

Attribute	Description	
Name	MOVQ	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGBRNIN

Attribute	Description	
Name	CHGBRNIN	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGADDRIN

Attribute	Description	
Name	CHGADDRIN	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## AUTHRGHTS

Attribute	Description	
Name	AUTHRGHTS	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGMSG

Attribute	Description	
Name	CHGMSG	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGMSGAUTH

Attribute	Description	
Name	CHGMSGAUTH	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGFORCCOVMATCH

Attribute	Description	
Name	CHGFORCCOVMATCH	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHANGE\_FORCE\_RELEASE\_FUND

Attribute	Description	
Name	CHANGE_FORCE_RELEASE_FUND	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## SUPPRESS

Attribute	Description	
Name	SUPPRESS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DELMSG

Attribute	Description	
Name	DELMSG	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## QUEUERIGHTS

Attribute	Description	
Name	QUEUERIGHTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## QUEUE

Attribute	Description	
Name	QUEUE	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## USERTILLS

Attribute	Description	
Name	USERTILLS	
Datatype		
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## TILLID

<b>Attribute</b>	<b>Description</b>	
Name	TILLID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## TILLBRNCD

<b>Attribute</b>	<b>Description</b>	
Name	TILLBRNCD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

## USERACCCLASS

<b>Attribute</b>	<b>Description</b>	
Name	USERACCCLASS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ACCCLS

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLS	
Datatype	string	

Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>6</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	6
Restrictions	Description				
maxLength	6				

## USERGLREST

Attribute	Description						
Name	USERGLREST						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## NODEGL

Attribute	Description				
Name	NODEGL				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

## USERGLEXCEPT

Attribute	Description						
Name	USERGLEXCEPT						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## EXCEPLEAFGL

Attribute	Description				
Name	EXCEPLEAFGL				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

## USERLIMITSROLE

Attribute	Description
Name	USERLIMITSROLE

Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## LMTBRN

<b>Attribute</b>	<b>Description</b>				
Name	LMTBRN				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## LMTSROLE

<b>Attribute</b>	<b>Description</b>				
Name	LMTSROLE				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>15</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## USERBRANCHES

<b>Attribute</b>	<b>Description</b>						
Name	USERBRANCHES						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## BRNSBRN

<b>Attribute</b>	<b>Description</b>				
Name	BRNSBRN				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## USERPRODUCTS

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	USERPRODUCTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	maxOccurs	unbounded

### PRDPRDCD

<b>Attribute</b>	<b>Description</b>	
Name	PRDPRDCD	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	4

### USERACCESSPRODUCTS

<b>Attribute</b>	<b>Description</b>	
Name	USERACCESSPRODUCTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	maxOccurs	unbounded

### PRDACCESSPRDCD

<b>Attribute</b>	<b>Description</b>	
Name	PRDACCESSPRDCD	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	4

### USERFUNCDISALLOW

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCDISALLOW	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	maxOccurs	unbounded

### FUNCDISALLOWFUNCID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCDISALLOWFUNCID	
Datatype	string	

Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>8</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	8
Restrictions	Description				
maxLength	8				

## USERROLE

Attribute	Description						
Name	USERROLE						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## ROLEBRNCD

Attribute	Description				
Name	ROLEBRNCD				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## USRROLEID

Attribute	Description				
Name	USRROLEID				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>15</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## USERSFUNCTIONS

Attribute	Description						
Name	USERSFUNCTIONS						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## USERFUNCBRNCD

Attribute	Description
Name	USERFUNCBRNCD
Datatype	string
Description	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## USERFUNCFUNCID

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCFUNCID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## CONTROL1

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL1	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL2	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL4

Attribute	Description	
Name	CONTROL4	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL5

Attribute	Description	
Name	CONTROL5	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL6

Attribute	Description	
Name	CONTROL6	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL7

Attribute	Description	
Name	CONTROL7	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL8

Attribute		Description	
Name	CONTROL8		
Datatype	decimal		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	

### CONTROL9

Attribute		Description	
Name	CONTROL9		
Datatype	decimal		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	

### USERFUNCSCTRL10

Attribute		Description	
Name	USERFUNCSCTRL10		
Datatype	decimal		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	

### CONTROL11

Attribute		Description	
Name	CONTROL11		
Datatype	decimal		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	

### CONTROL12

Attribute	Description	
Name	CONTROL12	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL13

Attribute	Description	
Name	CONTROL13	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL14

Attribute	Description	
Name	CONTROL14	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL15

Attribute	Description	
Name	CONTROL15	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL16

Attribute	Description	
Name	CONTROL16	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

### Grp-Restriction

Attribute	Description	
Name	Grp-Restriction	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

### GROUP\_CODE

Attribute	Description	
Name	GROUP_CODE	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	40

### Centralisation

Attribute	Description	
Name	Centralisation	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

### USRROLEID

Attribute	Description	
Name	USRROLEID	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	15

Attribute	Description	
Name	Dshdet	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## SEQUENCE\_NO

Attribute	Description	
Name	SEQUENCE_NO	
Datatype	decimal	
Description		
Restrictions		
	Restrictions	Description
	totalDigits	22

## DBWHERECLAUSE

Attribute	Description	
Name	DBWHERECLAUSE	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	4000

## SHOW\_IN\_DASHBOARD

Attribute	Description	
Name	SHOW_IN_DASHBOARD	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## Where-Master

Attribute	Description	
Name	Where-Master	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

## COLUMN\_NAME



Attribute	Description	
Name	COLUMN_NAME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	2000
	<b>Description</b>	

## WHERE\_CL

Attribute	Description	
Name	WHERE_CL	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	500
	<b>Description</b>	

## CONDITION

Attribute	Description	
Name	CONDITION	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	30
	<b>Description</b>	

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	string	

Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

Attribute		Description	
Name	FCUBS_WARNING_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

## WARNING

Attribute		Description	
Name	WARNING		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

## WCODE

Attribute		Description	
Name	WCODE		
Datatype	String		
Description			

## WDESC

Attribute		Description	
Name	WDESC		
Datatype	String		
Description			

## 2.11.DeleteSMD BANKP

2.11.1.SM-DeleteSMD BANKP-Req-Full-MSG.xsd

*DELETESMD BANKP\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Smtbs-Parameters-Full*  
*HEAD\_OFFICE*  
*SITE\_CODE*  
*ACTIVATION\_KEY*  
*INVALID\_LOGINS\_CUM*  
*INVALID\_LOGINS\_SUC*  
*PWD\_PREVENT\_REUSE*  
*PWD\_CHANGE\_AFTER*  
*MAXIMUM*  
*MINIMUM*  
*PWD\_EXPIRY\_MSG\_DAYS*  
*ARCHIVAL\_PERIOD*  
*CONCHAR\_PWD\_NUM*  
*FREQ\_PWD\_CHG*  
*MIN\_PWD\_NUMERIC\_LENGTH*  
*LEGAL\_NOTICE*  
*DORMANCY\_DAYS*  
*DISPLAY\_LEGAL\_NOTICE*  
*MIN\_SPECIALCHAR\_LENGTH*  
*MIN\_LOWERCASE\_CHAR*

*MIN\_UPPERCASE\_CHAR*  
*SCRENSAVERREQUIRED*  
*SCRENSAVERTIMEOUTINSECONDS*  
*SCRENSAVERMODIFIABLEBYUSER*  
*PASSWORDEXTERNAL*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*Smtbs-Branch-Restr*  
*RESTR\_TYPE*  
*DESCRIPTION*  
*Smtbs-Restrictive-Passwd*  
*PASSWORD*  
*UDFDETAILS*  
*FLDNAM*  
*FLDVAL*

#### DELETESMDBANKP\_FSFS\_REQ

Attribute	Description
Name	DELETESMDBANKP_FSFS_REQ
Datatype	
Description	

#### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

#### SOURCE

Attribute	Description
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

Attribute	Description



Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of DeleteSMD BANKP

## Smtbs-Parameters-Full

Attribute	Description
Name	Smtbs-Parameters-Full
Datatype	
Description	

## HEAD\_OFFICE

Attribute	Description				
Name	HEAD_OFFICE				
Datatype	string				
Description	Indicates Head Office				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## SITE\_CODE

Attribute	Description				
Name	SITE_CODE				
Datatype	string				
Description	Indicates Site Code				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>4</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	4
Restrictions	Description				
maxLength	4				

## ACTIVATION\_KEY

Attribute	Description				
Name	ACTIVATION_KEY				
Datatype	string				
Description	Indicates Activation Key				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>24</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	24
Restrictions	Description				
maxLength	24				

## INVALID\_LOGINS\_CUM

Attribute	Description

Name	INVALID_LOGINS_CUM	
Datatype	decimal	
Description	Indicates Cumulative	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	6
	maxInclusive	99

## INVALID\_LOGINS\_SUC

<b>Attribute</b>	<b>Description</b>	
Name	INVALID_LOGINS_SUC	
Datatype	decimal	
Description	Indicates Successive	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	1
	minInclusive	3
	maxInclusive	5

## PWD\_PREVENT\_REUSE

<b>Attribute</b>	<b>Description</b>	
Name	PWD_PREVENT_REUSE	
Datatype	decimal	
Description	Indicates Password Repetitions	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## PWD\_CHANGE\_AFTER

<b>Attribute</b>	<b>Description</b>	
Name	PWD_CHANGE_AFTER	
Datatype	decimal	
Description	Indicates Force Password Change After	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	3
	minInclusive	15
	maxInclusive	180

## MAXIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MAXIMUM	
Datatype	decimal	
Description	Indicates Maximum	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	12
	maxInclusive	30

## MINIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MINIMUM	
Datatype	decimal	
Description	Indicates Minimum	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	6
	maxInclusive	11

## PWD\_EXPIRY\_MSG\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	PWD_EXPIRY_MSG_DAYS	
Datatype	decimal	
Description	Indicates Intimate User (Before Password Expiry)	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1
	maxInclusive	5

## ARCHIVAL\_PERIOD

<b>Attribute</b>	<b>Description</b>	
Name	ARCHIVAL_PERIOD	
Datatype	decimal	
Description	Indicates Archival Period (in days)	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	3

### CONCHAR\_PWD\_NUM

<b>Attribute</b>	<b>Description</b>	
Name	CONCHAR_PWD_NUM	
Datatype	decimal	
Description	Indicates Maximum Consecutive Repetitive Characters	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2

### FREQ\_PWD\_CHG

<b>Attribute</b>	<b>Description</b>	
Name	FREQ_PWD_CHG	
Datatype	decimal	
Description	Indicates Minimum Days Between Password Changes	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	0

### MIN\_PWD\_NUMERIC\_LENGTH

<b>Attribute</b>	<b>Description</b>	
Name	MIN_PWD_NUMERIC_LENGTH	
Datatype	decimal	
Description	Indicates Minimum Number Of Numeric Characters In Password	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### LEGAL\_NOTICE

<b>Attribute</b>	<b>Description</b>	
Name	LEGAL_NOTICE	
Datatype	string	
Description	Indicates Warning Screen Text	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

## DORMANCY\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	DORMANCY_DAYS	
Datatype	decimal	
Description	Indicates Dormancy Days	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## DISPLAY\_LEGAL\_NOTICE

<b>Attribute</b>	<b>Description</b>	
Name	DISPLAY_LEGAL_NOTICE	
Datatype	string	
Description	Indicates Display Legal Notice Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MIN\_SPECIALCHAR\_LENGTH

<b>Attribute</b>	<b>Description</b>	
Name	MIN_SPECIALCHAR_LENGTH	
Datatype	decimal	
Description	Indicates Minimum Number Of Special Characters In Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## MIN\_LOWERCASE\_CHAR

<b>Attribute</b>	<b>Description</b>	
Name	MIN_LOWERCASE_CHAR	
Datatype	decimal	
Description	Indicates Minimum Number of LowerCase Characters in Password	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### MIN\_UPPERCASE\_CHAR

<b>Attribute</b>	<b>Description</b>	
Name	MIN_UPPERCASE_CHAR	
Datatype	decimal	
Description	Indicates Minimum Number of UpperCase Characters in Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### SCRENSAVERREQUIRED

<b>Attribute</b>	<b>Description</b>	
Name	SCRENSAVERREQUIRED	
Datatype	string	
Description	Indicates Screensaver Required Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### SCRENSAVERTIMEOUTINSECONDS

<b>Attribute</b>	<b>Description</b>	
Name	SCRENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description	Indicates Screensaver Interval (in seconds)	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

### SCRENSAVERMODIFIABLEBYUSER

<b>Attribute</b>	<b>Description</b>	
Name	SCRENSAVERMODIFIABLEBYUSER	
Datatype	string	
Description	Indicates Screensaver Interval Modifiable at User Level Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PASSWORDEXTERNAL

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORDEXTERNAL	
Datatype	string	
Description	Indicates Password External Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

### Smtbs-Branch-Restr

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Branch-Restr	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### RESTR\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_TYPE	
Datatype	string	
Description	Indicates Restriction Type	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Restriction Type Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

### Smtbs-Restrictive-Passwd

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Restrictive-Passwd	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description	Indicates Password	
Restrictions		
	Restrictions	Description
	maxLength	12

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.11.2.SM-DeleteSMD BANKP-Req-IO-MSG.xsd

*DELETESMDBANKP\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Smtbs-Parameters-IO*  
*SITE\_CODE*

**DELETESMDBANKP\_IOPK\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	DELETESMDBANKP_IOPK_REQ
Datatype	
Description	

**FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

**SOURCE**

<b>Attribute</b>	<b>Description</b>
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

Attribute	Description



Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of DeleteSMD BANKP

## Smtbs-Parameters-IO

Attribute	Description
Name	Smtbs-Parameters-IO
Datatype	
Description	

## SITE\_CODE

Attribute	Description				
Name	SITE_CODE				
Datatype	string				
Description	Indicates Site Code				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>4</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	4
Restrictions	Description				
maxLength	4				

### 2.11.3.SM-DeleteSMD BANKP-Res-Full-MSG.xsd

#### *DELETESMD BANKP\_FSFS\_RES*

##### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Parameters-Full*

*HEAD\_OFFICE*

*SITE\_CODE*

*ACTIVATION\_KEY*

*INVALID\_LOGINS\_CUM*

*INVALID\_LOGINS\_SUC*

*PWD\_PREVENT\_REUSE*

*PWD\_CHANGE\_AFTER*

*MAXIMUM*

*MINIMUM*

*PWD\_EXPIRY\_MSG\_DAYS*

*ARCHIVAL\_PERIOD*

*CONCHAR\_PWD\_NUM*

*FREQ\_PWD\_CHG*

*MIN\_PWD\_NUMERIC\_LENGTH*

*LEGAL\_NOTICE*

*DORMANCY\_DAYS*

*DISPLAY\_LEGAL\_NOTICE*

*MIN\_SPECIALCHAR\_LENGTH*

*MIN\_LOWERCASE\_CHAR*

*MIN\_UPPERCASE\_CHAR*

*SCREESAVERREQUIRED*

*SCREESAVERTIMEOUTINSECONDS*

*SCREESAVERMODIFIABLEBYUSER*

*PASSWORDEXTERNAL*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Smtbs-Branch-Restr*

*RESTR\_TYPE*

*DESCRIPTION*

*Smtbs-Restrictive-Passwd*

*PASSWORD*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

#### **DELETESMDBANKP\_FSFS\_RES**

<b>Attribute</b>	<b>Description</b>
Name	DELETESMDBANKP_FSFS_RES
Datatype	
Description	

#### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

#### **SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	string	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

## Smtbs-Parameters-Full

Attribute	Description
Name	Smtbs-Parameters-Full
Datatype	
Description	

## HEAD\_OFFICE

Attribute	Description				
Name	HEAD_OFFICE				
Datatype	string				
Description	Indicates Head Office				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## SITE\_CODE

Attribute	Description				
Name	SITE_CODE				
Datatype	string				
Description	Indicates Site Code				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>4</td></tr></tbody></table>	Restrictions	Description	maxLength	4
Restrictions	Description				
maxLength	4				

## ACTIVATION\_KEY

Attribute	Description				
Name	ACTIVATION_KEY				
Datatype	string				
Description	Indicates Activation Key				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	24

### INVALID\_LOGINS\_CUM

<b>Attribute</b>	<b>Description</b>	
Name	INVALID_LOGINS_CUM	
Datatype	decimal	
Description	Indicates Cumulative	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	6
	maxInclusive	99

### INVALID\_LOGINS\_SUC

<b>Attribute</b>	<b>Description</b>	
Name	INVALID_LOGINS_SUC	
Datatype	decimal	
Description	Indicates Successive	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	1
	minInclusive	3
	maxInclusive	5

### PWD\_PREVENT\_REUSE

<b>Attribute</b>	<b>Description</b>	
Name	PWD_PREVENT_REUSE	
Datatype	decimal	
Description	Indicates Password Repetitions	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### PWD\_CHANGE\_AFTER

<b>Attribute</b>	<b>Description</b>	
Name	PWD_CHANGE_AFTER	
Datatype	decimal	

Description	Indicates Force Password Change After	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	3
	minInclusive	15
	maxInclusive	180

## MAXIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MAXIMUM	
Datatype	decimal	
Description	Indicates Maximum	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	12
	maxInclusive	30

## MINIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MINIMUM	
Datatype	decimal	
Description	Indicates Minimum	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	6
	maxInclusive	11

## PWD\_EXPIRY\_MSG\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	PWD_EXPIRY_MSG_DAYS	
Datatype	decimal	
Description	Indicates Intimate User (Before Password Expiry)	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1
	maxInclusive	5

## ARCHIVAL\_PERIOD

<b>Attribute</b>	<b>Description</b>	
Name	ARCHIVAL_PERIOD	
Datatype	decimal	

Description	Indicates Archival Period (in days)	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	3

### CONCHAR\_PWD\_NUM

<b>Attribute</b>	<b>Description</b>	
Name	CONCHAR_PWD_NUM	
Datatype	decimal	
Description	Indicates Maximum Consecutive Repetitive Characters	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2

### FREQ\_PWD\_CHG

<b>Attribute</b>	<b>Description</b>	
Name	FREQ_PWD_CHG	
Datatype	decimal	
Description	Indicates Minimum Days Between Password Changes	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	0

### MIN\_PWD\_NUMERIC\_LENGTH

<b>Attribute</b>	<b>Description</b>	
Name	MIN_PWD_NUMERIC_LENGTH	
Datatype	decimal	
Description	Indicates Minimum Number Of Numeric Characters In Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### LEGAL\_NOTICE

<b>Attribute</b>	<b>Description</b>
Name	LEGAL_NOTICE

Datatype	string	
Description	Indicates Warning Screen Text	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

## DORMANCY\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	DORMANCY_DAYS	
Datatype	decimal	
Description	Indicates Dormancy Days	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## DISPLAY\_LEGAL\_NOTICE

<b>Attribute</b>	<b>Description</b>	
Name	DISPLAY_LEGAL_NOTICE	
Datatype	string	
Description	Indicates Display Legal Notice Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MIN\_SPECIALCHAR\_LENGTH

<b>Attribute</b>	<b>Description</b>	
Name	MIN_SPECIALCHAR_LENGTH	
Datatype	decimal	
Description	Indicates Minimum Number Of Special Characters In Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## MIN\_LOWERCASE\_CHAR

<b>Attribute</b>	<b>Description</b>	
Name	MIN_LOWERCASE_CHAR	
Datatype	decimal	

Description	Indicates Minimum Number of LowerCase Characters in Password	
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	2
	minInclusive	1

## MIN\_UPPERCASE\_CHAR

<b>Attribute</b>	<b>Description</b>	
Name	MIN_UPPERCASE_CHAR	
Datatype	decimal	
Description	Indicates Minimum Number of UpperCase Characters in Password	
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	2
	minInclusive	1

## SCREENSAVERREQUIRED

<b>Attribute</b>	<b>Description</b>	
Name	SCREENSAVERREQUIRED	
Datatype	string	
Description	Indicates Screensaver Required Y - on N - Off	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	enumeration	Y,N

## SCREENSAVERTIMEOUTINSECONDS

<b>Attribute</b>	<b>Description</b>	
Name	SCREENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description	Indicates Screensaver Interval (in seconds)	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	4

## SCREENSAVERMODIFIABLEBYUSER

<b>Attribute</b>	<b>Description</b>	
Name	SCREENSAVERMODIFIABLEBYUSER	
Datatype	string	
Description	Indicates Screensaver Interval Modifiable at User Level Y - on N - Off	



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PASSWORDEXTERNAL

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORDEXTERNAL	
Datatype	string	
Description	Indicates Password External Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

### Smtbs-Branch-Restr

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Branch-Restr	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### RESTR\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_TYPE	
Datatype	string	
Description	Indicates Restriction Type	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Restriction Type Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

### Smtbs-Restrictive-Passwd

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Restrictive-Passwd	
Datatype		
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description	Indicates Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	maxOccurs	unbounded

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	maxOccurs	unbounded

## WCODE

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

### 2.11.4.SM-DeleteSMDBANKP-Res-PK-MSG.xsd

*DELETESMDBANKP\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Parameters-PK*

*SITE\_CODE*

*Smtbs-Parameters-IO*

*SITE\_CODE*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

**DELETESMDBANKP\_IOPK\_RES**

<b>Attribute</b>	<b>Description</b>
Name	DELETESMDBANKP_IOPK_RES
Datatype	
Description	

**FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

**SOURCE**

<b>Attribute</b>	<b>Description</b>				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

**UBSCOMP**

<b>Attribute</b>	<b>Description</b>
Name	UBSCOMP
Datatype	string
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*



## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	string
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	

Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

## Smtbs-Parameters-PK

<b>Attribute</b>	<b>Description</b>
Name	Smtbs-Parameters-PK
Datatype	
Description	

## SITE\_CODE

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	SITE_CODE	
Datatype	string	
Description	Indicates Site Code	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

### Smtbs-Parameters-IO

<b>Attribute</b>	<b>Description</b>
Name	Smtbs-Parameters-IO
Datatype	
Description	

### SITE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	SITE_CODE	
Datatype	string	
Description	Indicates Site Code	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

### FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

### ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

### EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC

Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

## 2.12.DeleteSMDRLMNE

2.12.1.SM-DeleteSMDRLMNE-Req-Full-MSG.xsd

*DELETESMDRLMNE\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Smtbs-Role-Limit-Full*  
*ROLEID2*  
*DESCRIPTION*  
*LIMIT\_CCY*  
*INPUT\_LIMIT*  
*AUTHORIZATION\_LIMIT*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*UDFDETAILS*  
*FLDNAM*  
*FLDVAL*

**DELETESMDRLMNE\_FSFS\_REQ**

Attribute	Description
Name	DELETESMDRLMNE_FSFS_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				



Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	pattern	[a-zA-Z_0-9]*

## USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	12
pattern	[A-Z_0-9]*	

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	length	3
pattern	[a-zA-Z_0-9]{3}	

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of DeleteSMDRLMNE

## Smtbs-Role-Limit-Full

<b>Attribute</b>	<b>Description</b>
Name	Smtbs-Role-Limit-Full
Datatype	
Description	

## ROLEID2

<b>Attribute</b>	<b>Description</b>	
Name	ROLEID2	
Datatype	string	
Description	Indicates Role Id	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Description	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## LIMIT\_CCY

Attribute	Description				
Name	LIMIT_CCY				
Datatype	string				
Description	Indicates Limit Currency				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

## INPUT\_LIMIT

Attribute	Description						
Name	INPUT_LIMIT						
Datatype	decimal						
Description	Indicates Input Limit						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0
	Restrictions	Description					
	totalDigits	22					
minInclusive	0						

## AUTHORIZATION\_LIMIT

Attribute	Description						
Name	AUTHORIZATION_LIMIT						
Datatype	decimal						
Description	Indicates Authorization Limit						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0
	Restrictions	Description					
	totalDigits	22					
minInclusive	0						

## MAKER

Attribute	Description				
Name	MAKER				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

## MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0



*DELETESMDRLMNE\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Role-Limit-IO*

*ROLEID2*

**DELETESMDRLMNE\_IOPK\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	DELETESMDRLMNE_IOPK_REQ
Datatype	
Description	

**FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	string	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of DeleteSMDRLMNE

## Smtbs-Role-Limit-IO

Attribute	Description
Name	Smtbs-Role-Limit-IO
Datatype	
Description	

## ROLEID2

Attribute	Description				
Name	ROLEID2				
Datatype	string				
Description	Indicates Role Id				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

### 2.12.3.SM-DeleteSMDRLMNE-Res-Full-MSG.xsd

*DELETESMDRLMNE\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Role-Limit-Full*

*ROLEID2*

*DESCRIPTION*

*LIMIT\_CCY*

*INPUT\_LIMIT*

*AUTHORIZATION\_LIMIT*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*



WCODE

WDESC

### DELETESMDRLMNE\_FSFS\_RES

Attribute	Description
Name	DELETESMDRLMNE_FSFS_RES
Datatype	
Description	

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

### SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

### UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

### MSGID

Attribute	Description
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	string				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	string
Description	This is the user id in the Source system who is performing the action.

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
	maxOccurs	unbounded	

## NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

## VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

## FCUBS\_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description	This XSD Gives Information about Full Response		

## Smtbs-Role-Limit-Full

Attribute		Description	
Name	Smtbs-Role-Limit-Full		
Datatype			
Description			

## ROLEID2

Attribute		Description	
Name	ROLEID2		
Datatype	string		
Description	Indicates Role Id		
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	15	

## DESCRIPTION

Attribute		Description	
Name	DESCRIPTION		
Datatype	string		
Description	Indicates Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

### LIMIT\_CCY

<b>Attribute</b>	<b>Description</b>	
Name	LIMIT_CCY	
Datatype	string	
Description	Indicates Limit Currency	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### INPUT\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	INPUT_LIMIT	
Datatype	decimal	
Description	Indicates Input Limit	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0

### AUTHORIZATION\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHORIZATION_LIMIT	
Datatype	decimal	
Description	Indicates Authorization Limit	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0

### MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

## CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

## TXNSTAT



Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	1
	<b>Description</b>	

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	1
	<b>Description</b>	

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	
	maxLength	105
	minLength	1
	<b>Description</b>	

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

## WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

## WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

### 2.12.4.SM-DeleteSMDRLMNE-Res-PK-MSG.xsd

*DELETESMDRLMNE\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Role-Limit-PK*

*ROLEID2*

*Smtbs-Role-Limit-IO*

*ROLEID2*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## DELETESMDRLMNE\_IOPK\_RES

Attribute	Description
Name	DELETESMDRLMNE_IOPK_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## USERID

Attribute	Description
-----------	-------------

Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE



## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

**Smtbs-Role-Limit-PK**

Attribute	Description
Name	Smtbs-Role-Limit-PK
Datatype	
Description	

**ROLEID2**

Attribute	Description				
Name	ROLEID2				
Datatype	string				
Description	Indicates Role Id				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>15</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

**Smtbs-Role-Limit-IO**

Attribute	Description
Name	Smtbs-Role-Limit-IO
Datatype	
Description	

**ROLEID2**

Attribute	Description				
Name	ROLEID2				
Datatype	string				
Description	Indicates Role Id				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>15</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

**FCUBS\_ERROR\_RESP**

Attribute	Description						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

**ERROR**

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

**ECODE**

Attribute	Description
Name	ECODE
Datatype	String
Description	

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

## 2.13.DeleteSMRole

### 2.13.1.SM-DeleteSMRole-Req-Full-MSG.xsd

*DELETESMROLE\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*ROLEMASTER-Full*  
*ROLEIDENTIFICATION*  
*MASTERROLEDESC*  
*AUTHORISERROLE*  
*BRANCH\_RES*  
*ACCCLASSALLOWED*  
*CENTRALISATIONROLE*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*

*AUTHSTAT*

*ROLEDETAIL*

*ROLEFUN*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*CONTROL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CONTROL15*

*CONTROL16*

*ROLEDETAILB*

*ROLEFUN*

*CONT1*

*CONT2*

*CONT3*

*CONT4*

*CONT5*

*CONT6*

*CONTROL7*

*CONT8*

*CONT9*

*CONT10*

*CONT11*

*CONT12*

*CONT13*

*CONT14*

*CONT15*

*CONTROL16*

*ROLEDETAILC*

*ROLEFUN*

*CNTRL1*

*CNTRL2*

*CNTRL3*

*CNTRL4*

*CNTRL5*

*CNTRL6*

*CNTRL7*

*CNTRL8*

*CNTRL9*

*CNTRL10*

*CNTRL11*

*CNTRL12*

*CNTRL13*

*CNTRL14*

*CNTRL15*

*CNTRL16*

*ROLEDETAILD*

*ROLEFUN*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*CONTROL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CNTRL15*

*CNTRL16*

*ROLEBRANCHES*

*BRANCH*

*BRNNAME*

*ROLEACCCLASS*

*ACCCLS*

*DESCRIPTION*

*MSGCRIGHTS*

*CNL*

*CHGNODE*

*REL*

*CHGMEDIA*

*BRNMOV*

*HLD*

*TSTINP*

*CHGADDR*

*REINS*

*CHGPRIOR*

*CNLAUTH*

*CHGNODEAUTH*

*RELAUTH*

*CHGMEDIAAUTH*

*BRNMOVAUTH*

*HLDAUTH*

*TSTINPAUTH*  
*CHGADDRAUTH*  
*REINSAUTH*  
*CHGPRIORAUTH*  
*GEN*  
*TSTCHK*  
*LNKCONT*  
*CHGBRNIN*  
*CHGMSG*  
*CHGFORCRELFUND*  
*SUPPRESS*  
*DELMSG*  
*PRNT*  
*FTUPL*  
*MOVQ*  
*CHGADDRIN*  
*CHGMSGAUTH*  
*AUTHRGHTS*  
*CHGFORCCOVMATCH*  
*QUEUERIGHTS*  
*QUEUE*  
*RESTRICTIVEPASSWD*  
*PWD*  
*PWDID*  
*ROLEBRANCHLIMITS*  
*LMTCCY*  
*BRUSERLMT*  
*Roledetaile*  
*ROLEFUN*  
*BRANCHCODE*  
*EDITABLE*  
*CNTRLSTR*



*Roledetailf*

*ROLEID*

*ROLEFUN*

*CNTRLSTR*

*CNTRL1*

*CNTRL10*

*CNTRL11*

*CNTRL12*

*CNTRL13*

*CNTRL14*

*CNTRL15*

*CNTRL16*

*CNTRL2*

*CNTRL3*

*CNTRL4*

*CNTRL5*

*CNTRL6*

*CNTRL7*

*CNTRL8*

*CNTRL9*

*ATHSTAT*

*BRNCHCODE*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

**DELETESMROLE\_FSFS\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	DELETESMROLE_FSFS_REQ
Datatype	
Description	

**FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	

Description	
-------------	--

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	string	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of DeleteSMRole

## ROLEMASTER-Full

Attribute	Description
Name	ROLEMASTER-Full
Datatype	
Description	

## ROLEIDENTIFICATION

Attribute	Description				
Name	ROLEIDENTIFICATION				
Datatype	string				
Description	Indicates Role Id				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## MASTERROLEDESC

Attribute	Description				
Name	MASTERROLEDESC				
Datatype	string				
Description	Indicates Role Description				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

## AUTHORISERROLE

Attribute	Description				
Name	AUTHORISERROLE				
Datatype	string				
Description	Indicates Authorizer Role Y - on N - Off				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRANCH\_RES

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_RES	
Datatype	string	
Description	Indicates Branch Restriction A - Allowed D - Disallowed	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## ACCCLASSALLOWED

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLASSALLOWED	
Datatype	string	
Description	Indicates Account Class Restriction A - Allowed D - Disallowed	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## CENTRALISATIONROLE

<b>Attribute</b>	<b>Description</b>	
Name	CENTRALISATIONROLE	
Datatype	string	
Description	Indicates Centralisation Role Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

### TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

### AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

### ROLEDETAIL

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAIL	
Datatype		
Description	Maintenance	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

### CONTROL1

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL4

<b>Attribute</b>	<b>Description</b>
Name	CONTROL4

Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL6

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL8

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL8	
Datatype	decimal	
Description	Indicates Auth 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL10

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL11

Attribute		Description	
Name		CONTROL11	
Datatype		decimal	
Description		Indicates Confirm 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL12

Attribute		Description	
Name		CONTROL12	
Datatype		decimal	
Description		Indicates Liquidate 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL13

Attribute		Description	
Name		CONTROL13	
Datatype		decimal	
Description		Indicates Hold 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL14

Attribute		Description	
Name		CONTROL14	
Datatype		decimal	
Description		Indicates Template 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL15

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEDETAILB

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILB	
Datatype		
Description	Roles	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

### CONT1

<b>Attribute</b>	<b>Description</b>	
Name	CONT1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT2

<b>Attribute</b>	<b>Description</b>	
Name	CONT2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT3

<b>Attribute</b>	<b>Description</b>	
Name	CONT3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT4

<b>Attribute</b>	<b>Description</b>
Name	CONT4



Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT5

<b>Attribute</b>	<b>Description</b>	
Name	CONT5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT6

<b>Attribute</b>	<b>Description</b>	
Name	CONT6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT8

<b>Attribute</b>	<b>Description</b>	
Name	CONT8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT9

<b>Attribute</b>	<b>Description</b>	
Name	CONT9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT10

<b>Attribute</b>	<b>Description</b>	
Name	CONT10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT11

Attribute		Description	
Name		CONT11	
Datatype		decimal	
Description		Indicates Confirm 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONT12

Attribute		Description	
Name		CONT12	
Datatype		decimal	
Description		Indicates Liquidate 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONT13

Attribute		Description	
Name		CONT13	
Datatype		decimal	
Description		Indicates Hold 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONT14

Attribute		Description	
Name		CONT14	
Datatype		decimal	
Description		Indicates Template 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT15

<b>Attribute</b>	<b>Description</b>	
Name	CONT15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEDETAILC

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILC	
Datatype		
Description	Batch	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

### CNTRL1

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL2

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL3

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL4

<b>Attribute</b>	<b>Description</b>
Name	CNTRL4

Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL5

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL6

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL7

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL8

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL9

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL10

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL11

Attribute		Description	
Name		CNTRL11	
Datatype		decimal	
Description		Indicates Confirm 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CNTRL12

Attribute		Description	
Name		CNTRL12	
Datatype		decimal	
Description		Indicates Liquidate 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CNTRL13

Attribute		Description	
Name		CNTRL13	
Datatype		decimal	
Description		Indicates Hold 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CNTRL14

Attribute		Description	
Name		CNTRL14	
Datatype		decimal	
Description		Indicates Template 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL15

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL16

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEDETAILD

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILD	
Datatype		
Description	Roles	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

### CONTROL1

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL4

<b>Attribute</b>	<b>Description</b>
Name	CONTROL4

Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL6

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL8

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL8	
Datatype	decimal	
Description	Indicates Auth 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL10

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL11

Attribute	Description	
Name	CONTROL11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL12

Attribute	Description	
Name	CONTROL12	
Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL13

Attribute	Description	
Name	CONTROL13	
Datatype	decimal	
Description	Indicates Hold 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL14

Attribute	Description	
Name	CONTROL14	
Datatype	decimal	
Description	Indicates Template 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL15

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL16

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEBRANCHES

<b>Attribute</b>	<b>Description</b>	
Name	ROLEBRANCHES	
Datatype		
Description	Branches	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	Indicates Branch	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## BRNNAME

<b>Attribute</b>	<b>Description</b>	
Name	BRNNAME	
Datatype	string	
Description	Indicates Branch Name	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## ROLEACCCLASS

<b>Attribute</b>	<b>Description</b>	
Name	ROLEACCCLASS	
Datatype		
Description	Acc Class Restriction	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ACCCLS

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLS	
Datatype	string	
Description	Indicates Account Class	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Account Class Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## MSGCRIGHTS

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	MSGCRIGHTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## CNL

<b>Attribute</b>	<b>Description</b>	
Name	CNL	
Datatype	string	
Description	Indicates Cancel Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODE

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODE	
Datatype	string	
Description	Indicates Change Node Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REL

<b>Attribute</b>	<b>Description</b>	
Name	REL	
Datatype	string	
Description	Indicates Release Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIA

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIA	
Datatype	string	
Description	Indicates Change Media Y - on N - Off	



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOV

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOV	
Datatype	string	
Description	Indicates Branch Move Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLD

<b>Attribute</b>	<b>Description</b>	
Name	HLD	
Datatype	string	
Description	Indicates Hold Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINP

<b>Attribute</b>	<b>Description</b>	
Name	TSTINP	
Datatype	string	
Description	Indicates Test Input Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDR

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDR	
Datatype	string	
Description	Indicates Change Address Y - on N - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINS

<b>Attribute</b>	<b>Description</b>	
Name	REINS	
Datatype	string	
Description	Indicates Reinststate Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIOR

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIOR	
Datatype	string	
Description	Indicates Change Priority Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNLAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CNLAUTH	
Datatype	string	
Description	Indicates Auth Cancel Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODEAUTH	
Datatype	string	
Description	Indicates Auth Change Node Y - on N - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## RELAUTH

<b>Attribute</b>	<b>Description</b>	
Name	RELAUTH	
Datatype	string	
Description	Indicates Release Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIAAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIAAUTH	
Datatype	string	
Description	Indicates Change Media Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOVAUTH

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOVAUTH	
Datatype	string	
Description	Indicates Auth Branch Move Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLDAUTH

<b>Attribute</b>	<b>Description</b>
Name	HLDAUTH
Datatype	string

Description	Indicates Hold Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINPAUTH

<b>Attribute</b>	<b>Description</b>	
Name	TSTINPAUTH	
Datatype	string	
Description	Indicates Auth Test Input Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRAUTH	
Datatype	string	
Description	Indicates Change Address Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINSAUTH

<b>Attribute</b>	<b>Description</b>	
Name	REINSAUTH	
Datatype	string	
Description	Indicates Auth Reinstate Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIORAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIORAUTH	

Datatype	string	
Description	Indicates Change Priority Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## GEN

<b>Attribute</b>	<b>Description</b>	
Name	GEN	
Datatype	string	
Description	Indicates Install Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTCHK

<b>Attribute</b>	<b>Description</b>	
Name	TSTCHK	
Datatype	string	
Description	Indicates Test Check Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## LNKCONT

<b>Attribute</b>	<b>Description</b>	
Name	LNKCONT	
Datatype	string	
Description	Indicates Link Contract Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGBRNIN

<b>Attribute</b>	<b>Description</b>
Name	CHGBRNIN

Datatype	string	
Description	Indicates Change Branch In Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSG

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSG	
Datatype	string	
Description	Indicates Change Message Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGFORCRELFUND

<b>Attribute</b>	<b>Description</b>	
Name	CHGFORCRELFUND	
Datatype	string	
Description	Indicates Change Force Release Fund Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SUPPRESS

<b>Attribute</b>	<b>Description</b>	
Name	SUPPRESS	
Datatype	string	
Description	Indicates Suppress Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DELMSG

Attribute	Description	
Name	DELMSG	
Datatype	string	
Description	Indicates Delete Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PRNT

Attribute	Description	
Name	PRNT	
Datatype	string	
Description	Indicates Print Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## FTUPL

Attribute	Description	
Name	FTUPL	
Datatype	string	
Description	Indicates FT Upload Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MOVQ

Attribute	Description	
Name	MOVQ	
Datatype	string	
Description	Indicates Move To Queue Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRIN

Attribute		Description	
Name	CHGADDRIN		
Datatype	string		
Description	Indicates Change Address In Y - on N - Off		
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	Y,N	

## CHGMSGAUTH

Attribute		Description	
Name	CHGMSGAUTH		
Datatype	string		
Description	Indicates Auth Change Message Y - on N - Off		
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	Y,N	

## AUTHRGHTS

Attribute		Description	
Name	AUTHRGHTS		
Datatype	string		
Description	Indicates Auth Rights Y - on N - Off		
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	Y,N	

## CHGFORCCOVMATCH

Attribute		Description	
Name	CHGFORCCOVMATCH		
Datatype	string		
Description	Indicates Change Force Cover Match Y - on N - Off		
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## QUEUERIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	QUEUERIGHTS	
Datatype		
Description	Queues	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## QUEUE

<b>Attribute</b>	<b>Description</b>	
Name	QUEUE	
Datatype	string	
Description	Indicates Queue	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## RESTRICTIVEPASSWD

<b>Attribute</b>	<b>Description</b>	
Name	RESTRICTIVEPASSWD	
Datatype		
Description	Restricted Password	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PWD

<b>Attribute</b>	<b>Description</b>	
Name	PWD	
Datatype	string	
Description	Indicates Password	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## PWDID

<b>Attribute</b>	<b>Description</b>	
Name	PWDID	
Datatype	string	
Description	Indicates Id	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## ROLEBRANCHLIMITS

<b>Attribute</b>	<b>Description</b>	
Name	ROLEBRANCHLIMITS	
Datatype		
Description	User Limits	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxOccurs	unbounded

## LMTCCY

<b>Attribute</b>	<b>Description</b>	
Name	LMTCCY	
Datatype	string	
Description	Indicates Limit Currency	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## BRHUSERLMT

<b>Attribute</b>	<b>Description</b>	
Name	BRHUSERLMT	
Datatype	decimal	
Description	Indicates User Limit	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## Roledetaile

<b>Attribute</b>	<b>Description</b>	
Name	Roledetaile	
Datatype		
Description	Process Stage Rights	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxOccurs	unbounded

## ROLEFUN

Attribute	Description	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8

## BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	string	
Description	Indicates Branch Code	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

## EDITABLE

Attribute	Description	
Name	EDITABLE	
Datatype	decimal	
Description	Indicates Editable 1 - on 0 - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

## CNTRLSTR

Attribute	Description	
Name	CNTRLSTR	
Datatype	string	
Description	Indicates Control String	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	16

## Roledetailf

Attribute	Description	
Name	Roledetailf	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## ROLEID

Attribute	Description	
Name	ROLEID	
Datatype	string	
Description	Indicates Role Function	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	15

## ROLEFUN

Attribute	Description	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8

## CNTRLSTR

Attribute	Description	
Name	CNTRLSTR	
Datatype	string	
Description	Indicates Control String	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	16

## CNTRL1

Attribute	Description
Name	CNTRL1
Datatype	decimal

Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL10

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL11

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL12

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL12	
Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL13**

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL13	
Datatype	decimal	
Description	Indicates Hold 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL14**

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL14	
Datatype	decimal	
Description	Indicates Template 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL15**

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL16**

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	

Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL2

<b>Attribute</b>		<b>Description</b>
Name	CNTRL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL3

<b>Attribute</b>		<b>Description</b>
Name	CNTRL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL4

<b>Attribute</b>		<b>Description</b>
Name	CNTRL4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL5**

Attribute	Description	
Name	CNTRL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL6**

Attribute	Description	
Name	CNTRL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL7**

Attribute	Description	
Name	CNTRL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL8**

Attribute	Description	
Name	CNTRL8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL9

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ATHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	ATHSTAT	
Datatype	string	
Description	Indicates Authorization Status	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## BRNCHCODE

<b>Attribute</b>	<b>Description</b>	
Name	BRNCHCODE	
Datatype	string	
Description	Indicates Branch Code	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

### 2.13.2.SM-DeleteSMRole-Req-IO-MSG.xsd

*DELETESMROLE\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*ROLEMASTER-IO*

*ROLEIDENTIFICATION*

#### DELETESMROLE\_IOPK\_REQ

Attribute	Description
Name	DELETESMROLE_IOPK_REQ
Datatype	
Description	

#### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

#### SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

#### UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	string

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

## MSGID

Attribute	Description					
Name	MSGID					
Datatype	string					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

## CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	string					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

## USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about IO Request of DeleteSMRole	

## ROLEMASTER-IO



Attribute	Description
Name	ROLEMASTER-IO
Datatype	
Description	

## ROLEIDENTIFICATION

Attribute	Description	
Name	ROLEIDENTIFICATION	
Datatype	string	
Description	Indicates Role Id	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

### 2.13.3.SM-DeleteSMRole-Res-Full-MSG.xsd

*DELETESMROLE\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*ROLEMASTER-Full*

*ROLEIDENTIFICATION*

*MASTERROLEDESC*

*AUTHORISERROLE*

*BRANCH\_RES*

*ACCCLASSALLOWED*

*CENTRALISATIONROLE*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*ROLEDETAIL*

*ROLEFUN*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*CONTROL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CONTROL15*

*CONTROL16*

*ROLEDETAILB*

*ROLEFUN*

*CONT1*

*CONT2*

*CONT3*

*CONT4*

*CONT5*

*CONT6*

*CONTROL7*

*CONT8*

*CONT9*

*CONT10*

*CONT11*

*CONT12*

*CONT13*

*CONT14*

*CONT15*

*CONTROL16*

*ROLEDETAILC*

*ROLEFUN*

*CNTRL1*

*CNTRL2*

*CNTRL3*

*CNTRL4*

*CNTRL5*

*CNTRL6*

*CNTRL7*

*CNTRL8*

*CNTRL9*

*CNTRL10*

*CNTRL11*

*CNTRL12*

*CNTRL13*

*CNTRL14*

*CNTRL15*

*CNTRL16*

*ROLEDETAILED*

*ROLEFUN*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*CONTROL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CNTRL15*

*CNTRL16*

*ROLEBRANCHES*

*BRANCH*

*BRNNAME*

*ROLEACCCLASS*

*ACCCLS*

*DESCRIPTION*

*MSGCRIGHTS*

*CNL*

*CHGNODE*

*REL*  
*CHGMEDIA*  
*BRNMOV*  
*HLD*  
*TSTINP*  
*CHGADDR*  
*REINS*  
*CHGPRIOR*  
*CNLAUTH*  
*CHGNODEAUTH*  
*RELAUTH*  
*CHGMEDIAAUTH*  
*BRNMOVAUTH*  
*HLDAUTH*  
*TSTINPAUTH*  
*CHGADDRAUTH*  
*REINSAUTH*  
*CHGPRIORAUTH*  
*GEN*  
*TSTCHK*  
*LNKCONT*  
*CHGBRNIN*  
*CHGMSG*  
*CHGFORCRELFUND*  
*SUPPRESS*  
*DELMSG*  
*PRNT*  
*FTUPL*  
*MOVQ*  
*CHGADDRIN*  
*CHGMSGAUTH*  
*AUTHRGHTS*

*CHGFORCCOVMATCH*

*QUEUERIGHTS*

*QUEUE*

*RESTRICTIVEPASSWD*

*PWD*

*PWDID*

*ROLEBRANCHLIMITS*

*LMTCCY*

*BRHUSERLMT*

*Roledetaile*

*ROLEFUN*

*BRANCHCODE*

*EDITABLE*

*CNTRLSTR*

*Roledetailf*

*ROLEID*

*ROLEFUN*

*CNTRLSTR*

*CNTRL1*

*CNTRL10*

*CNTRL11*

*CNTRL12*

*CNTRL13*

*CNTRL14*

*CNTRL15*

*CNTRL16*

*CNTRL2*

*CNTRL3*

*CNTRL4*

*CNTRL5*

*CNTRL6*

*CNTRL7*

*CNTRL8*

*CNTRL9*

*ATHSTAT*

*BRNCHCODE*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## DELETESMROLE\_FSFS\_RES

Attribute	Description
Name	DELETESMROLE_FSFS_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description
-----------	-------------

Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE. <sup>1108</sup>	



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	<b>Description</b>	

## ADDL

<b>Attribute</b>		<b>Description</b>
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	

## PARAM

<b>Attribute</b>		<b>Description</b>
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## NAME

<b>Attribute</b>		<b>Description</b>
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>		<b>Description</b>
Name	VALUE	
Datatype	String	
Description		

## FCUBS\_BODY

<b>Attribute</b>		<b>Description</b>
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

## ROLEMASTER-Full

Attribute	Description
Name	ROLEMASTER-Full
Datatype	
Description	

## ROLEIDENTIFICATION

Attribute	Description				
Name	ROLEIDENTIFICATION				
Datatype	string				
Description	Indicates Role Id				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>15</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## MASTERROLEDESC

Attribute	Description				
Name	MASTERROLEDESC				
Datatype	string				
Description	Indicates Role Description				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

## AUTHORISERROLE

Attribute	Description				
Name	AUTHORISERROLE				
Datatype	string				
Description	Indicates Authorizer Role Y - on N - Off				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Y,N</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## BRANCH\_RES

Attribute	Description				
Name	BRANCH_RES				
Datatype	string				
Description	Indicates Branch Restriction A - Allowed D - Disallowed				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## ACCCLASSALLOWED

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLASSALLOWED	
Datatype	string	
Description	Indicates Account Class Restriction A - Allowed D - Disallowed	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## CENTRALISATIONROLE

<b>Attribute</b>	<b>Description</b>	
Name	CENTRALISATIONROLE	
Datatype	string	
Description	Indicates Centralisation Role Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## ROLEDETAIL

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAIL	
Datatype		
Description	Maintenance	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## CONTROL1

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL4

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL5

Attribute	Description	
Name	CONTROL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL6

Attribute	Description	
Name	CONTROL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL7

Attribute	Description	
Name	CONTROL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL8

Attribute	Description	
Name	CONTROL8	
Datatype	decimal	
Description	Indicates Auth 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL10

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL11

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL12

Attribute		Description	
Name		CONTROL12	
Datatype		decimal	
Description		Indicates Liquidate 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

### CONTROL13

Attribute		Description	
Name		CONTROL13	
Datatype		decimal	
Description		Indicates Hold 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

### CONTROL14

Attribute		Description	
Name		CONTROL14	
Datatype		decimal	
Description		Indicates Template 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

### CONTROL15

Attribute		Description	
Name		CONTROL15	
Datatype		decimal	
Description		Indicates View 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEDETAILB

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILB	
Datatype		
Description	Roles	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## CONT1

<b>Attribute</b>	<b>Description</b>	
Name	CONT1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT2

<b>Attribute</b>	<b>Description</b>	
Name	CONT2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT3

<b>Attribute</b>	<b>Description</b>	
Name	CONT3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT4

<b>Attribute</b>	<b>Description</b>	
Name	CONT4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT5

Attribute		Description	
Name		CONT5	
Datatype		decimal	
Description		Indicates Unlock 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONT6

Attribute		Description	
Name		CONT6	
Datatype		decimal	
Description		Indicates Reopen 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL7

Attribute		Description	
Name		CONTROL7	
Datatype		decimal	
Description		Indicates Print 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONT8

Attribute		Description	
Name		CONT8	
Datatype		decimal	
Description		Indicates Authorize 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT9

<b>Attribute</b>	<b>Description</b>	
Name	CONT9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT10

<b>Attribute</b>	<b>Description</b>	
Name	CONT10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT11

<b>Attribute</b>	<b>Description</b>	
Name	CONT11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT12



Attribute	Description	
Name	CONT12	
Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT13

Attribute	Description	
Name	CONT13	
Datatype	decimal	
Description	Indicates Hold 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT14

Attribute	Description	
Name	CONT14	
Datatype	decimal	
Description	Indicates Template 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT15

Attribute	Description	
Name	CONT15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEDETAILC

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILC	
Datatype		
Description	Batch	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## CNTRL1

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL2

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL3

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL4

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL5

Attribute		Description	
Name		CNTRL5	
Datatype		decimal	
Description		Indicates Unlock 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CNTRL6

Attribute		Description	
Name		CNTRL6	
Datatype		decimal	
Description		Indicates Reopen 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CNTRL7

Attribute		Description	
Name		CNTRL7	
Datatype		decimal	
Description		Indicates Print 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CNTRL8

Attribute		Description	
Name		CNTRL8	
Datatype		decimal	
Description		Indicates Authorize 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL9

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL10

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL11

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL12

Attribute		Description	
Name		CNTRL12	
Datatype		decimal	
Description		Indicates Liquidate 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

### CNTRL13

Attribute		Description	
Name		CNTRL13	
Datatype		decimal	
Description		Indicates Hold 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

### CNTRL14

Attribute		Description	
Name		CNTRL14	
Datatype		decimal	
Description		Indicates Template 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

### CNTRL15

Attribute		Description	
Name		CNTRL15	
Datatype		decimal	
Description		Indicates View 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL16

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEDETAILD

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILD	
Datatype		
Description	Roles	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## CONTROL1

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL4

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL5



Attribute		Description	
Name		CONTROL5	
Datatype		decimal	
Description		Indicates Unlock 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL6

Attribute		Description	
Name		CONTROL6	
Datatype		decimal	
Description		Indicates Reopen 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL7

Attribute		Description	
Name		CONTROL7	
Datatype		decimal	
Description		Indicates Print 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL8

Attribute		Description	
Name		CONTROL8	
Datatype		decimal	
Description		Indicates Auth 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL10

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL11

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL12

Attribute		Description	
Name		CONTROL12	
Datatype		decimal	
Description		Indicates Liquidate 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

### CONTROL13

Attribute		Description	
Name		CONTROL13	
Datatype		decimal	
Description		Indicates Hold 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

### CONTROL14

Attribute		Description	
Name		CONTROL14	
Datatype		decimal	
Description		Indicates Template 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

### CNTRL15

Attribute		Description	
Name		CNTRL15	
Datatype		decimal	
Description		Indicates View 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL16

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEBRANCHES

<b>Attribute</b>	<b>Description</b>	
Name	ROLEBRANCHES	
Datatype		
Description	Branches	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	Indicates Branch	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## BRNNAME

<b>Attribute</b>	<b>Description</b>	
Name	BRNNAME	
Datatype	string	
Description	Indicates Branch Name	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## ROLEACCCLASS

<b>Attribute</b>	<b>Description</b>	
Name	ROLEACCCLASS	
Datatype		
Description	Acc Class Restriction	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ACCCLS

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLS	
Datatype	string	
Description	Indicates Account Class	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Account Class Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## MSGCRIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	MSGCRIGHTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## CNL

<b>Attribute</b>	<b>Description</b>	
Name	CNL	
Datatype	string	
Description	Indicates Cancel Y - on N - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODE

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODE	
Datatype	string	
Description	Indicates Change Node Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REL

<b>Attribute</b>	<b>Description</b>	
Name	REL	
Datatype	string	
Description	Indicates Release Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIA

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIA	
Datatype	string	
Description	Indicates Change Media Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOV

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOV	
Datatype	string	
Description	Indicates Branch Move Y - on N - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLD

<b>Attribute</b>	<b>Description</b>	
Name	HLD	
Datatype	string	
Description	Indicates Hold Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINP

<b>Attribute</b>	<b>Description</b>	
Name	TSTINP	
Datatype	string	
Description	Indicates Test Input Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDR

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDR	
Datatype	string	
Description	Indicates Change Address Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINS

<b>Attribute</b>	<b>Description</b>	
Name	REINS	
Datatype	string	

Description	Indicates Reinstate Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIOR

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIOR	
Datatype	string	
Description	Indicates Change Priority Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNLAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CNLAUTH	
Datatype	string	
Description	Indicates Auth Cancel Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODEAUTH	
Datatype	string	
Description	Indicates Auth Change Node Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## RELAUTH

<b>Attribute</b>	<b>Description</b>
Name	RELAUTH



Datatype	string	
Description	Indicates Release Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIAAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIAAUTH	
Datatype	string	
Description	Indicates Change Media Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOVAUTH

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOVAUTH	
Datatype	string	
Description	Indicates Auth Branch Move Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLDAUTH

<b>Attribute</b>	<b>Description</b>	
Name	HLDAUTH	
Datatype	string	
Description	Indicates Hold Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINPAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	TSTINPAUTH	
Datatype	string	
Description	Indicates Auth Test Input Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRAUTH	
Datatype	string	
Description	Indicates Change Address Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINSAUTH

<b>Attribute</b>	<b>Description</b>	
Name	REINSAUTH	
Datatype	string	
Description	Indicates Auth Reinstate Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIORAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIORAUTH	
Datatype	string	
Description	Indicates Change Priority Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## GEN

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	GEN	
Datatype	string	
Description	Indicates Install Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTCHK

<b>Attribute</b>	<b>Description</b>	
Name	TSTCHK	
Datatype	string	
Description	Indicates Test Check Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## LNKCONT

<b>Attribute</b>	<b>Description</b>	
Name	LNKCONT	
Datatype	string	
Description	Indicates Link Contract Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGBRNIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGBRNIN	
Datatype	string	
Description	Indicates Change Branch In Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSG

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CHGMSG	
Datatype	string	
Description	Indicates Change Message Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGFORCREFUND

<b>Attribute</b>	<b>Description</b>	
Name	CHGFORCREFUND	
Datatype	string	
Description	Indicates Change Force Release Fund Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SUPPRESS

<b>Attribute</b>	<b>Description</b>	
Name	SUPPRESS	
Datatype	string	
Description	Indicates Suppress Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DELMSG

<b>Attribute</b>	<b>Description</b>	
Name	DELMSG	
Datatype	string	
Description	Indicates Delete Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PRNT

Attribute	Description	
Name	PRNT	
Datatype	string	
Description	Indicates Print Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## FTUPL

Attribute	Description	
Name	FTUPL	
Datatype	string	
Description	Indicates FT Upload Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MOVQ

Attribute	Description	
Name	MOVQ	
Datatype	string	
Description	Indicates Move To Queue Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRIN

Attribute	Description	
Name	CHGADDRIN	
Datatype	string	
Description	Indicates Change Address In Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSGAUTH

Attribute	Description	
Name	CHGMSGAUTH	
Datatype	string	
Description	Indicates Auth Change Message Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## AUTHRGHTS

Attribute	Description	
Name	AUTHRGHTS	
Datatype	string	
Description	Indicates Auth Rights Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGFORCCOVMATCH

Attribute	Description	
Name	CHGFORCCOVMATCH	
Datatype	string	
Description	Indicates Change Force Cover Match Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## QUEUERIGHTS

Attribute	Description	
Name	QUEUERIGHTS	
Datatype		
Description	Queues	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## QUEUE

Attribute	Description
-----------	-------------

Name	QUEUE	
Datatype	string	
Description	Indicates Queue	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## RESTRICTIVEPASSWD

<b>Attribute</b>	<b>Description</b>	
Name	RESTRICTIVEPASSWD	
Datatype		
Description	Restricted Password	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PWD

<b>Attribute</b>	<b>Description</b>	
Name	PWD	
Datatype	string	
Description	Indicates Password	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## PWDID

<b>Attribute</b>	<b>Description</b>	
Name	PWDID	
Datatype	string	
Description	Indicates Id	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## ROLEBRANCLIMITS

<b>Attribute</b>	<b>Description</b>	
Name	ROLEBRANCLIMITS	
Datatype		
Description	User Limits	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## LMTCCY

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	LMTCCY	
Datatype	string	
Description	Indicates Limit Currency	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## BRHUSERLMT

<b>Attribute</b>	<b>Description</b>	
Name	BRHUSERLMT	
Datatype	decimal	
Description	Indicates User Limit	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## Roledetaile

<b>Attribute</b>	<b>Description</b>	
Name	Roledetaile	
Datatype		
Description	Process Stage Rights	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## BRANCHCODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCHCODE	
Datatype	string	
Description	Indicates Branch Code	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## EDITABLE

<b>Attribute</b>	<b>Description</b>	
Name	EDITABLE	
Datatype	decimal	
Description	Indicates Editable 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CNTRLSTR

<b>Attribute</b>	<b>Description</b>	
Name	CNTRLSTR	
Datatype	string	
Description	Indicates Control String	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

## Roledetailf

<b>Attribute</b>	<b>Description</b>	
Name	Roledetailf	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEID

<b>Attribute</b>	<b>Description</b>	
Name	ROLEID	
Datatype	string	
Description	Indicates Role Function	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## CNTRLSTR

<b>Attribute</b>	<b>Description</b>	
Name	CNTRLSTR	
Datatype	string	
Description	Indicates Control String	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

## CNTRL1

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL10

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL11

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL12

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL12	
Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL13

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL13	
Datatype	decimal	
Description	Indicates Hold 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL14**

Attribute	Description	
Name	CNTRL14	
Datatype	decimal	
Description	Indicates Template 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL15**

Attribute	Description	
Name	CNTRL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL16**

Attribute	Description	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL2**

Attribute	Description	
Name	CNTRL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	

Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL3

<b>Attribute</b>		<b>Description</b>
Name	CNTRL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL4

<b>Attribute</b>		<b>Description</b>
Name	CNTRL4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL5

<b>Attribute</b>		<b>Description</b>
Name	CNTRL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL6**

Attribute	Description	
Name	CNTRL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL7**

Attribute	Description	
Name	CNTRL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL8**

Attribute	Description	
Name	CNTRL8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL9**

Attribute	Description	
Name	CNTRL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ATHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	ATHSTAT	
Datatype	string	
Description	Indicates Authorization Status	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## BRNCHCODE

<b>Attribute</b>	<b>Description</b>	
Name	BRNCHCODE	
Datatype	string	
Description	Indicates Branch Code	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP



Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

## WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

## WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

### 2.13.4.SM-DeleteSMRole-Res-PK-MSG.xsd

*DELETESMROLE\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*ROLEMASTER-PK*

*ROLEIDENTIFICATION*

*ROLEMASTER-IO*

*ROLEIDENTIFICATION*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## **DELETESMROLE\_IOPK\_RES**

<b>Attribute</b>	<b>Description</b>
Name	DELETESMROLE_IOPK_RES
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	string	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

## ROLEMASTER-PK

Attribute	Description
Name	ROLEMASTER-PK
Datatype	
Description	

## ROLEIDENTIFICATION

Attribute	Description				
Name	ROLEIDENTIFICATION				
Datatype	string				
Description	Indicates Role Id				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## ROLEMASTER-IO

Attribute	Description
Name	ROLEMASTER-IO
Datatype	
Description	

## ROLEIDENTIFICATION

Attribute	Description				
Name	ROLEIDENTIFICATION				
Datatype	string				
Description	Indicates Role Id				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## FCUBS\_ERROR\_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

### 2.14.DeleteUserMaint

#### 2.14.1.SM-DeleteUserMaint-Req-Full-MSG.xsd

*DELETEUSERMAINT\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*USR-Full*

*STRDATE*

*USRNAME*

*USRPWD*  
*ENDDT*  
*USRLANG*  
*HOMEBRN*  
*CUSTNO*  
*LDAPUSR*  
*TIMELEVEL*  
*AUTOAUTH*  
*USRSTAT*  
*USRID*  
*EXTUSRREF*  
*USRCATEG*  
*TILLALLOW*  
*ACCCLSALLOW*  
*GLALLOW*  
*USRTXNLMT*  
*LMTSCCY*  
*MAXTXNAMT*  
*MAXAUTHAMT*  
*BRNSALLOW*  
*PRDSALLOW*  
*PRDSACCESALLOW*  
*TAX\_IDENTIFIER*  
*AMOUNT\_FORMAT*  
*DATE\_FORMAT*  
*STAFFACCRESTR*  
*DEPT\_CODE*  
*DEPT\_DESC*  
*USRML*  
*ELCMUSER*  
*GROUP\_CODE*  
*MULTIBRN\_ACCESS*

*OTH\_RM\_CUST\_ACC\_ALLOW*  
*SUPERVISOR\_ID*  
*SUPERVISOR\_NAME*  
*DASHBOARD\_REQD*  
*ALERTS\_ON\_HOME*  
*REFERENCE\_NO*  
*NO\_CUMULATIVE\_LOGINS*  
*NO\_SUCESSIVE\_LOGINS*  
*SCREENSAVERTIMEOUTINSECONDS*  
*NUMBER\_FORMAT\_MASK*  
*FRONTEND\_DEBUG\_ENABLED*  
*F10\_REQD*  
*F11\_REQD*  
*F12\_REQD*  
*MFI\_USER*  
*MFAENABLED*  
*MFAID*  
*ACCESS\_CONTROL*  
*EXTN\_ALERTS*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*RESTR\_PWD*  
*PWD*  
*MSGSRIGHTS*  
*GEN*  
*HLD*  
*CNL*

*TSTINP*  
*CHGNODE*  
*CHGADDR*  
*REL*  
*REINS*  
*CHGMEDIA*  
*CHGPRIOR*  
*BRNMOV*  
*PRNT*  
*TSTCHK*  
*HLDAUTH*  
*CNLAUTH*  
*TSTINPAUTH*  
*CHGNODEAUTH*  
*CHGADDRAUTH*  
*RELAUTH*  
*REINSAUTH*  
*CHGMEDIAAUTH*  
*BRNMOVAUTH*  
*CHGPRIORAUTH*  
*FTUPL*  
*LNKCONT*  
*MOVQ*  
*CHGBRNIN*  
*CHGADDRIN*  
*AUTHRGHTS*  
*CHGMSG*  
*CHGMSGAUTH*  
*CHGFORCCOVMATCH*  
*CHANGE\_FORCE\_RELEASE\_FUND*  
*SUPPRESS*  
*DELMSG*

*QUEUERIGHTS*  
*QUEUE*  
*USERTILLS*  
*TILLID*  
*TILLBRNCD*  
*DESCRIPTION*  
*USERACCCLASS*  
*ACCCLS*  
*USERGLREST*  
*NODEGL*  
*USERGLEXCEPT*  
*EXCEPLEAFGL*  
*USERLIMITSROLE*  
*LMTBRN*  
*LMTSROLE*  
*QLMTCCY*  
*QINPLMT*  
*QAUTHLMT*  
*USERBRANCHES*  
*BRNSBRN*  
*BRNNAME*  
*USERPRODUCTS*  
*PRDPRDCD*  
*PRDDESC*  
*USERACCESSPRODUCTS*  
*PRDACCESSPRDCD*  
*PRDDESC*  
*USERFUNCDISALLOW*  
*FUNCDISALLOWFUNCID*  
*USERROLE*  
*ROLEBRNCD*  
*USRROLEID*

*MASTERROLEDESC*

*USERSFUNCTIONS*

*USERFUNCBRNCD*

*USERFUNCFUNCID*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*USERFUNCSCTRL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CONTROL15*

*CONTROL16*

*Grp-Restriction*

*GROUP\_CODE*

*GROUP\_DESC*

*Centralisation*

*USRROLEID*

*ROLDESC*

*Dshmst*

*USRID*

*USRNAME*

*Dshdet*

*FUNCTIONID*

*DESCRIPTION*

*SEQUENCE\_NO*

*DBWHERECLAUSE*

*SHOW\_IN\_DASHBOARD*

*Where-Master*

*COLUMN\_NAME*

*WHERE\_CL*

*CONDITION*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

## DELETEUSERMAINT\_FSFS\_REQ

Attribute	Description
Name	DELETEUSERMAINT_FSFS_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	string
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.



Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	string
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	

Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of DeleteUserMaint

## USR-Full

<b>Attribute</b>	<b>Description</b>
Name	USR-Full
Datatype	
Description	

## STRTDATE

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	STRTDATE
Datatype	String
Description	

## USRNAME

Attribute	Description	
Name	USRNAME	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## USRPWD

Attribute	Description	
Name	USRPWD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	32

## ENDDT

Attribute	Description	
Name	ENDDT	
Datatype	String	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## USRLANG

Attribute	Description	
Name	USRLANG	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## HOMEBRN

Attribute	Description	
Name	HOMEBRN	
Datatype	string	
Description		

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## CUSTNO

<b>Attribute</b>	<b>Description</b>	
Name	CUSTNO	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## LDAPUSR

<b>Attribute</b>	<b>Description</b>	
Name	LDAPUSR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	500

## TIMELEVEL

<b>Attribute</b>	<b>Description</b>	
Name	TIMELEVEL	
Datatype	decimal	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	9

## AUTOAUTH

<b>Attribute</b>	<b>Description</b>	
Name	AUTOAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## USRSTAT

<b>Attribute</b>	<b>Description</b>	
Name	USRSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	E,H,D,L

## USRID

<b>Attribute</b>	<b>Description</b>	
Name	USRID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## EXTUSRREF

<b>Attribute</b>	<b>Description</b>	
Name	EXTUSRREF	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## USRCATEG

<b>Attribute</b>	<b>Description</b>	
Name	USRCATEG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	S,B



## TILLALLOW

Attribute	Description	
Name	TILLALLOW	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## ACCCLSALLOW

Attribute	Description	
Name	ACCCLSALLOW	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## GLALLOW

Attribute	Description	
Name	GLALLOW	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## USRTXNLMT

Attribute	Description	
Name	USRTXNLMT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,R,N

## LMTSCCY

Attribute		Description	
Name	LMTSCCY		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	3	

### MAXTXNAMT

Attribute		Description	
Name	MAXTXNAMT		
Datatype	decimal		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	

### MAXAUTHAMT

Attribute		Description	
Name	MAXAUTHAMT		
Datatype	decimal		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	

### BRNSALLOW

Attribute		Description	
Name	BRNSALLOW		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	A,D	

### PRDSALLOW

Attribute	Description	
Name	PRDSALLOW	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	A,D

## PRDSACCESALLOW

Attribute	Description	
Name	PRDSACCESALLOW	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	A,D

## TAX\_IDENTIFIER

Attribute	Description	
Name	TAX_IDENTIFIER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	11

## AMOUNT\_FORMAT

Attribute	Description	
Name	AMOUNT_FORMAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	.....

## DATE\_FORMAT

Attribute	Description	
Name	DATE_FORMAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	M/d/yyyy

## STAFFACCRESTR

Attribute	Description	
Name	STAFFACCRESTR	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DEPT\_CODE

Attribute	Description	
Name	DEPT_CODE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## DEPT\_DESC

Attribute	Description	
Name	DEPT_DESC	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## USRML

Attribute	Description	
Name	USRML	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	50

## ELCMUSER

Attribute	Description	
Name	ELCMUSER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

## GROUP\_CODE

Attribute	Description	
Name	GROUP_CODE	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	A,D

## MULTIBRN\_ACCESS

Attribute	Description	
Name	MULTIBRN_ACCESS	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## OTH\_RM\_CUST\_ACC\_ALLOW

Attribute	Description	
Name	OTH_RM_CUST_ACC_ALLOW	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## SUPERVISOR\_ID

Attribute	Description	
Name	SUPERVISOR_ID	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	80

## SUPERVISOR\_NAME

Attribute	Description	
Name	SUPERVISOR_NAME	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

## DASHBOARD\_REQD

Attribute	Description	
Name	DASHBOARD_REQD	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## ALERTS\_ON\_HOME

Attribute	Description	
Name	ALERTS_ON_HOME	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## REFERENCE\_NO

Attribute	Description	
Name	REFERENCE_NO	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	20

## NO\_CUMULATIVE\_LOGINS

Attribute	Description	
Name	NO_CUMULATIVE_LOGINS	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

## NO\_SUCCESSIVE\_LOGINS

Attribute	Description	
Name	NO_SUCCESSIVE_LOGINS	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

## SCREENSAVERTIMEOUTINSECONDS

Attribute	Description	
Name	SCREENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## NUMBER\_FORMAT\_MASK

Attribute	Description	
Name	NUMBER_FORMAT_MASK	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	M,L

## FRONTEND\_DEBUG\_ENABLED

Attribute	Description	
Name	FRONTEND_DEBUG_ENABLED	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## F10\_REQD

Attribute	Description	
Name	F10_REQD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## F11\_REQD



Attribute	Description	
Name	F11_REQD	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## F12\_REQD

Attribute	Description	
Name	F12_REQD	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## MFI\_USER

Attribute	Description	
Name	MFI_USER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## MFAENABLED

Attribute	Description	
Name	MFAENABLED	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	N,Y,L

## MFAID

Attribute	Description	
Name	MFAID	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

## ACCESS\_CONTROL

Attribute	Description	
Name	ACCESS_CONTROL	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,G,B

## EXTN\_ALERTS

Attribute	Description	
Name	EXTN_ALERTS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

## CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

## TXNSTAT

Attribute		Description	
Name	TXNSTAT		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	1	

## AUTHSTAT

Attribute		Description	
Name	AUTHSTAT		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	1	

## RESTR\_PWD

Attribute		Description	
Name	RESTR_PWD		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
	maxOccurs	unbounded	

## PWD

Attribute		Description	
Name	PWD		
Datatype	string		
Description			
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	12	

## MSGSRIGHTS

Attribute		Description	
Name	MSGSRIGHTS		
Datatype			
Description			

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## GEN

<b>Attribute</b>	<b>Description</b>	
Name	GEN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLD

<b>Attribute</b>	<b>Description</b>	
Name	HLD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNL

<b>Attribute</b>	<b>Description</b>	
Name	CNL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINP

<b>Attribute</b>	<b>Description</b>	
Name	TSTINP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODE

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDR

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REL

<b>Attribute</b>	<b>Description</b>	
Name	REL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINS

<b>Attribute</b>	<b>Description</b>	
Name	REINS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIA

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIA	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIOR

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIOR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOV

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOV	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PRNT

<b>Attribute</b>	<b>Description</b>	
Name	PRNT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTCHK

<b>Attribute</b>	<b>Description</b>	
Name	TSTCHK	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLDAUTH

<b>Attribute</b>	<b>Description</b>	
Name	HLDAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNLAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CNLAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINPAUTH

<b>Attribute</b>	<b>Description</b>	
Name	TSTINPAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODEAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## RELAUTH

<b>Attribute</b>	<b>Description</b>	
Name	RELAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINSAUTH

<b>Attribute</b>	<b>Description</b>	
Name	REINSAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIAAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIAAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOVAUTH

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOVAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIORAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIORAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## FTUPL

<b>Attribute</b>	<b>Description</b>	
Name	FTUPL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## LNKCONT

<b>Attribute</b>	<b>Description</b>	
Name	LNKCONT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MOVQ

<b>Attribute</b>	<b>Description</b>	
Name	MOVQ	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGBRNIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGBRNIN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRIN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## AUTHRGHTS

<b>Attribute</b>	<b>Description</b>	
Name	AUTHRGHTS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSG

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSGAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSGAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGFORCCOVMATCH

<b>Attribute</b>	<b>Description</b>	
Name	CHGFORCCOVMATCH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHANGE\_FORCE\_RELEASE\_FUND

<b>Attribute</b>	<b>Description</b>	
Name	CHANGE_FORCE_RELEASE_FUND	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SUPPRESS

<b>Attribute</b>	<b>Description</b>	
Name	SUPPRESS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DELMSG

<b>Attribute</b>	<b>Description</b>	
Name	DELMSG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## QUEUERIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	QUEUERIGHTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## QUEUE

Attribute	Description				
Name	QUEUE				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

## USERTILLS

Attribute	Description						
Name	USERTILLS						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## TILLID

Attribute	Description				
Name	TILLID				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## TILLBRNCD

Attribute	Description				
Name	TILLBRNCD				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## DESCRIPTION

Attribute	Description				
Name	DESCRIPTION				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

## USERACCCLASS

Attribute		Description	
Name	USERACCCLASS		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
	maxOccurs	unbounded	

## ACCCLS

Attribute		Description	
Name	ACCCLS		
Datatype	string		
Description			
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	6	

## USERGLREST

Attribute		Description	
Name	USERGLREST		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
	maxOccurs	unbounded	

## NODEGL

Attribute		Description	
Name	NODEGL		
Datatype	string		
Description			
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	9	

## USERGLEXCEPT

Attribute		Description	
Name	USERGLEXCEPT		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
	maxOccurs	unbounded	

## EXCEPLEAFGL

Attribute	Description

Name	EXCEPLEAFGL	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## USERLIMITSROLE

<b>Attribute</b>	<b>Description</b>	
Name	USERLIMITSROLE	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## LMTBRN

<b>Attribute</b>	<b>Description</b>	
Name	LMTBRN	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## LMTSROLE

<b>Attribute</b>	<b>Description</b>	
Name	LMTSROLE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## QLMTCCY

<b>Attribute</b>	<b>Description</b>	
Name	QLMTCCY	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### QINPLMT

<b>Attribute</b>	<b>Description</b>	
Name	QINPLMT	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### QAUTHLMT

<b>Attribute</b>	<b>Description</b>	
Name	QAUTHLMT	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### USERBRANCHES

<b>Attribute</b>	<b>Description</b>	
Name	USERBRANCHES	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### BRNSBRN

<b>Attribute</b>	<b>Description</b>	
Name	BRNSBRN	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### BRNNAME

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	BRNNAME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	105
	<b>Description</b>	

## USERPRODUCTS

<b>Attribute</b>	<b>Description</b>	
Name	USERPRODUCTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## PRDPRDCD

<b>Attribute</b>	<b>Description</b>	
Name	PRDPRDCD	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	4
	<b>Description</b>	

## PRDESC

<b>Attribute</b>	<b>Description</b>	
Name	PRDESC	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	105
	<b>Description</b>	

## USERACCESSPRODUCTS

<b>Attribute</b>	<b>Description</b>	
Name	USERACCESSPRODUCTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## PRDACCESSPRDCD

Attribute	Description				
Name	PRDACCESSPRDCD				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>4</td></tr></tbody></table>	Restrictions	Description	maxLength	4
Restrictions	Description				
maxLength	4				

## PRDDESC

Attribute	Description				
Name	PRDDESC				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

## USERFUNCDISALLOW

Attribute	Description						
Name	USERFUNCDISALLOW						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## FUNCDISALLOWFUNCID

Attribute	Description				
Name	FUNCDISALLOWFUNCID				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr></tbody></table>	Restrictions	Description	maxLength	8
Restrictions	Description				
maxLength	8				

## USERROLE

Attribute	Description						
Name	USERROLE						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## ROLEBRNCD

Attribute	Description				
Name	ROLEBRNCD				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## USRROLEID

Attribute	Description				
Name	USRROLEID				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## MASTERROLEDESC

Attribute	Description				
Name	MASTERROLEDESC				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>45</td></tr></tbody></table>	Restrictions	Description	maxLength	45
Restrictions	Description				
maxLength	45				

## USERSFUNCTIONS

Attribute	Description						
Name	USERSFUNCTIONS						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## USERFUNCBRNCD

Attribute	Description				
Name	USERFUNCBRNCD				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## USERFUNCFUNCID

Attribute		Description	
Name	USERFUNCFUNCID		
Datatype	string		
Description			
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	8	

### CONTROL1

Attribute		Description	
Name	CONTROL1		
Datatype	decimal		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	

### CONTROL2

Attribute		Description	
Name	CONTROL2		
Datatype	decimal		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	

### CONTROL3

Attribute		Description	
Name	CONTROL3		
Datatype	decimal		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	

### CONTROL4

Attribute		Description	
Name	CONTROL4		
Datatype	decimal		

Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL6

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL6	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL8

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL8	
Datatype	decimal	

Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## USERFUNCCTRL10

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCCTRL10	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL11

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL11	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL12

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL12	
Datatype	decimal	

Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL13

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL13	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL14

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL14	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL15

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL15	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	



Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### Grp-Restriction

<b>Attribute</b>	<b>Description</b>	
Name	Grp-Restriction	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### GROUP\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_CODE	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

### GROUP\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_DESC	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

### Centralisation

<b>Attribute</b>	<b>Description</b>	
Name	Centralisation	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

Attribute		Description	
Name	USRROLEID		
Datatype	string		
Description			
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	15	

## ROLDESC

Attribute		Description	
Name	ROLDESC		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	20	

## Dshmst

Attribute		Description	
Name	Dshmst		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	

## USRID

Attribute		Description	
Name	USRID		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	15	

## USRNAME

Attribute		Description	
Name	USRNAME		
Datatype	string		
Description			

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## Dshdet

<b>Attribute</b>	<b>Description</b>	
Name	Dshdet	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxOccurs	unbounded

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1000

## SEQUENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	SEQUENCE_NO	
Datatype	decimal	
Description		

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## DBWHERECLAUSE

<b>Attribute</b>	<b>Description</b>	
Name	DBWHERECLAUSE	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

## SHOW\_IN\_DASHBOARD

<b>Attribute</b>	<b>Description</b>	
Name	SHOW_IN_DASHBOARD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## Where-Master

<b>Attribute</b>	<b>Description</b>	
Name	Where-Master	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## COLUMN\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	COLUMN_NAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	2000

## WHERE\_CL

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	WHERE_CL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	500

## CONDITION

<b>Attribute</b>	<b>Description</b>	
Name	CONDITION	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

2.14.2.SM-DeleteUserMaint-Req-IO-MSG.xsd

*DELETEUSERMAINT\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*USR-IO*

*USRID*

## DELETEUSERMAINT\_IOPK\_REQ

Attribute	Description
Name	DELETEUSERMAINT_IOPK_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>
Name	MODULEID



Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

## FCUBS\_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about IO Request of DeleteUserMaint	

## USR-IO

Attribute	Description	
Name	USR-IO	
Datatype		
Description		

## USRID

Attribute	Description	
Name	USRID	
Datatype	string	
Description		
Restrictions	Restrictions	Description
	maxLength	12

### 2.14.3.SM-DeleteUserMaint-Res-Full-MSG.xsd

*DELETEUSERMAINT\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*USR-Full*  
*STRTDATE*  
*USRNAME*  
*USRPWD*  
*ENDDT*  
*USRLANG*  
*HOMEBRN*  
*CUSTNO*  
*LDAPUSR*  
*TIMELEVEL*  
*AUTOAUTH*  
*USRSTAT*  
*USRID*

*EXTUSRREF*  
*USRCATEG*  
*TILLALLOW*  
*ACCCLSALLOW*  
*GLALLOW*  
*USRTXNLMT*  
*LMTSCCY*  
*MAXTXNAMT*  
*MAXAUTHAMT*  
*BRNSALLOW*  
*PRDSALLOW*  
*PRDSACCESALLOW*  
*TAX\_IDENTIFIER*  
*AMOUNT\_FORMAT*  
*DATE\_FORMAT*  
*STAFFACCRESTR*  
*DEPT\_CODE*  
*DEPT\_DESC*  
*USRML*  
*ELCMUSER*  
*GROUP\_CODE*  
*MULTIBRN\_ACCESS*  
*OTH\_RM\_CUST\_ACC\_ALLOW*  
*SUPERVISOR\_ID*  
*SUPERVISOR\_NAME*  
*DASHBOARD\_REQD*  
*ALERTS\_ON\_HOME*  
*REFERENCE\_NO*  
*NO\_CUMULATIVE\_LOGINS*  
*NO\_SUCESSIVE\_LOGINS*  
*SCREENSAVERTIMEOUTINSECONDS*  
*NUMBER\_FORMAT\_MASK*

*FRONTEND\_DEBUG\_ENABLED*

*F10\_REQD*

*F11\_REQD*

*F12\_REQD*

*MFI\_USER*

*MFAENABLED*

*MFAID*

*ACCESS\_CONTROL*

*EXTN\_ALERTS*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*RESTR\_PWD*

*PWD*

*MSGSRIGHTS*

*GEN*

*HLD*

*CNL*

*TSTINP*

*CHGNODE*

*CHGADDR*

*REL*

*REINS*

*CHGMEDIA*

*CHGPRIOR*

*BRNMOV*

*PRNT*

*TSTCHK*

*HLDAUTH*  
*CNLAUTH*  
*TSTINPAUTH*  
*CHGNODEAUTH*  
*CHGADDRAUTH*  
*RELAUTH*  
*REINSAUTH*  
*CHGMEDIAAUTH*  
*BRNMOVAUTH*  
*CHGPRIORAUTH*  
*FTUPL*  
*LNKCONT*  
*MOVQ*  
*CHGBRNIN*  
*CHGADDRIN*  
*AUTHRGHTS*  
*CHGMSG*  
*CHGMSGAUTH*  
*CHGFORCCOVMATCH*  
*CHANGE\_FORCE\_RELEASE\_FUND*  
*SUPPRESS*  
*DELMSG*  
*QUEUERIGHTS*  
    *QUEUE*  
*USERTILLS*  
    *TILLID*  
    *TILLBRNCD*  
    *DESCRIPTION*  
*USERACCCLASS*  
    *ACCCLS*  
*USERGLREST*  
    *NODEGL*



*USERGLEXCEPT*

*EXCEPLEAFGL*

*USERLIMITSROLE*

*LMTBRN*

*LMTSROLE*

*QLMTCCY*

*QINPLMT*

*QAUTHLMT*

*USERBRANCHES*

*BRNSBRN*

*BRNNAME*

*USERPRODUCTS*

*PRDPRDCD*

*PRDDESC*

*USERACCESSPRODUCTS*

*PRDACCESSPRDCD*

*PRDDESC*

*USERFUNCDISALLOW*

*FUNCDISALLOWFUNCID*

*USERROLE*

*ROLEBRNCD*

*USRROLEID*

*MASTERROLEDESC*

*USERSFUNCTIONS*

*USERFUNCBRNCD*

*USERFUNCFUNCID*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*USERFUNCSCTRL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CONTROL15*

*CONTROL16*

*Grp-Restriction*

*GROUP\_CODE*

*GROUP\_DESC*

*Centralisation*

*USRROLEID*

*ROLDESC*

*Dshmst*

*USRID*

*USRNAME*

*Dshdet*

*FUNCTIONID*

*DESCRIPTION*

*SEQUENCE\_NO*

*DBWHERECLAUSE*

*SHOW\_IN\_DASHBOARD*

*Where-Master*

*COLUMN\_NAME*

*WHERE\_CL*

*CONDITION*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

**DELETEUSERMAINT\_FSFS\_RES**

<b>Attribute</b>	<b>Description</b>
Name	DELETEUSERMAINT_FSFS_RES
Datatype	
Description	

**FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

**SOURCE**

<b>Attribute</b>	<b>Description</b>				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

**UBSCOMP**

<b>Attribute</b>	<b>Description</b>				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	<b>Restrictions</b>	<b>Description</b>	enumeration	FCUBS,FCIS
<b>Restrictions</b>	<b>Description</b>				
enumeration	FCUBS,FCIS				

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

## ADDL

Attribute		Description	
Name	ADDL		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

## PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

## NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

## VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

## FCUBS\_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description	This XSD Gives Information about Full Response		

## USR-Full

Attribute		Description	
Name	USR-Full		
Datatype			
Description			

## STRTDATE

Attribute		Description	
Name	STRTDATE		
Datatype	String		
Description			

## USRNAME

Attribute		Description	



Name	USRNAME	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## USRPWD

<b>Attribute</b>	<b>Description</b>	
Name	USRPWD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	32

## ENDDT

<b>Attribute</b>	<b>Description</b>	
Name	ENDDT	
Datatype	String	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## USRLANG

<b>Attribute</b>	<b>Description</b>	
Name	USRLANG	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## HOMEBRN

<b>Attribute</b>	<b>Description</b>	
Name	HOMEBRN	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## CUSTNO

<b>Attribute</b>	<b>Description</b>	
Name	CUSTNO	

Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## LDAPUSR

<b>Attribute</b>	<b>Description</b>	
Name	LDAPUSR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	500

## TIMELEVEL

<b>Attribute</b>	<b>Description</b>	
Name	TIMELEVEL	
Datatype	decimal	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	9

## AUTOAUTH

<b>Attribute</b>	<b>Description</b>	
Name	AUTOAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## USRSTAT

<b>Attribute</b>	<b>Description</b>	
Name	USRSTAT	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	E,H,D,L

## USRID

<b>Attribute</b>	<b>Description</b>	
Name	USRID	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## EXTUSRREF

<b>Attribute</b>	<b>Description</b>	
Name	EXTUSRREF	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## USRCATEG

<b>Attribute</b>	<b>Description</b>	
Name	USRCATEG	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	S,B

## TILLALLOW

<b>Attribute</b>	<b>Description</b>	
Name	TILLALLOW	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## ACCCLSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## GLALLOW

<b>Attribute</b>	<b>Description</b>	
Name	GLALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## USRTXNLMT

<b>Attribute</b>	<b>Description</b>	
Name	USRTXNLMT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,R,N

## LMTSCCY

<b>Attribute</b>	<b>Description</b>	
Name	LMTSCCY	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### MAXTXNAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXTXNAMT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### MAXAUTHAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXAUTHAMT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### BRNSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	BRNSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### PRDSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## PRDSACCESALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSACCESALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## TAX\_IDENTIFIER

<b>Attribute</b>	<b>Description</b>	
Name	TAX_IDENTIFIER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

## AMOUNT\_FORMAT

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_FORMAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	.....

## DATE\_FORMAT

<b>Attribute</b>	<b>Description</b>	
Name	DATE_FORMAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	M/d/yyyy

## STAFFACCRESTR

<b>Attribute</b>	<b>Description</b>	
Name	STAFFACCRESTR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DEPT\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	DEPT_CODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## DEPT\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	DEPT_DESC	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## USRML

<b>Attribute</b>	<b>Description</b>	
Name	USRML	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## ELCMUSER

<b>Attribute</b>	<b>Description</b>	
Name	ELCMUSER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## GROUP\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_CODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## MULTIBRN\_ACCESS

<b>Attribute</b>	<b>Description</b>	
Name	MULTIBRN_ACCESS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## OTH\_RM\_CUST\_ACC\_ALLOW

<b>Attribute</b>	<b>Description</b>	
Name	OTH_RM_CUST_ACC_ALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SUPERVISOR\_ID

<b>Attribute</b>	<b>Description</b>	
Name	SUPERVISOR_ID	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	80

## SUPERVISOR\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	SUPERVISOR_NAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## DASHBOARD\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	DASHBOARD_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## ALERTS\_ON\_HOME

<b>Attribute</b>	<b>Description</b>	
Name	ALERTS_ON_HOME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REFERENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	REFERENCE_NO	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## NO\_CUMULATIVE\_LOGINS

<b>Attribute</b>	<b>Description</b>	
Name	NO_CUMULATIVE_LOGINS	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## NO\_SUCCESSIVE\_LOGINS

<b>Attribute</b>	<b>Description</b>	
Name	NO_SUCCESSIVE_LOGINS	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## SCREENSAVERTIMEOUTINSECONDS

<b>Attribute</b>	<b>Description</b>	
Name	SCREENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## NUMBER\_FORMAT\_MASK

<b>Attribute</b>	<b>Description</b>	
Name	NUMBER_FORMAT_MASK	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	M,L

## FRONTEND\_DEBUG\_ENABLED

<b>Attribute</b>	<b>Description</b>	
Name	FRONTEND_DEBUG_ENABLED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## F10\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F10_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## F11\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F11_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## F12\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F12_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MFI\_USER

<b>Attribute</b>	<b>Description</b>	
Name	MFI_USER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MFAENABLED

<b>Attribute</b>	<b>Description</b>	
Name	MFAENABLED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	N,Y,L

## MFAID

<b>Attribute</b>	<b>Description</b>	
Name	MFAID	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

## ACCESS\_CONTROL

<b>Attribute</b>	<b>Description</b>	
Name	ACCESS_CONTROL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,G,B

## EXTN\_ALERTS

<b>Attribute</b>	<b>Description</b>	
Name	EXTN_ALERTS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## RESTR\_PWD

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_PWD	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PWD

<b>Attribute</b>	<b>Description</b>	
Name	PWD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MSGSRIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	MSGSRIGHTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## GEN

<b>Attribute</b>	<b>Description</b>	
Name	GEN	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLD

<b>Attribute</b>	<b>Description</b>	
Name	HLD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNL

<b>Attribute</b>	<b>Description</b>	
Name	CNL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINP

<b>Attribute</b>	<b>Description</b>	
Name	TSTINP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODE

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODE	
Datatype	string	
Description		



Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDR

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REL

<b>Attribute</b>	<b>Description</b>	
Name	REL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINS

<b>Attribute</b>	<b>Description</b>	
Name	REINS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIA

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIA	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHGPRIOR

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIOR	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### BRNMOV

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOV	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### PRNT

<b>Attribute</b>	<b>Description</b>	
Name	PRNT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### TSTCHK

<b>Attribute</b>	<b>Description</b>	
Name	TSTCHK	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLDAUTH

<b>Attribute</b>	<b>Description</b>	
Name	HLDAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNLAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CNLAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINPAUTH

<b>Attribute</b>	<b>Description</b>	
Name	TSTINPAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODEAUTH	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## RELAUTH

<b>Attribute</b>	<b>Description</b>	
Name	RELAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINSAUTH

<b>Attribute</b>	<b>Description</b>	
Name	REINSAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIAAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIAAUTH	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### BRNMOVAUTH

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOVAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHGPRIORAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIORAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### FTUPL

<b>Attribute</b>	<b>Description</b>	
Name	FTUPL	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### LNKCONT

<b>Attribute</b>	<b>Description</b>	
Name	LNKCONT	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MOVQ

<b>Attribute</b>	<b>Description</b>	
Name	MOVQ	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGBRNIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGBRNIN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRIN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## AUTHRGHTS

<b>Attribute</b>	<b>Description</b>	
Name	AUTHRGHTS	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHGMSG

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHGMSGAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSGAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHGFORCCOVMATCH

<b>Attribute</b>	<b>Description</b>	
Name	CHGFORCCOVMATCH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHANGE\_FORCE\_RELEASE\_FUND

<b>Attribute</b>	<b>Description</b>	
Name	CHANGE_FORCE_RELEASE_FUND	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SUPPRESS

<b>Attribute</b>	<b>Description</b>	
Name	SUPPRESS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DELMSG

<b>Attribute</b>	<b>Description</b>	
Name	DELMSG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## QUEUERIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	QUEUERIGHTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## QUEUE

<b>Attribute</b>	<b>Description</b>	
Name	QUEUE	
Datatype	string	
Description		



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## USERTILLS

<b>Attribute</b>	<b>Description</b>	
Name	USERTILLS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## TILLID

<b>Attribute</b>	<b>Description</b>	
Name	TILLID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## TILLBRNCD

<b>Attribute</b>	<b>Description</b>	
Name	TILLBRNCD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

## USERACCCCLASS

<b>Attribute</b>	<b>Description</b>	
Name	USERACCCCLASS	
Datatype		
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ACCCLS

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLS	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

## USERGLREST

<b>Attribute</b>	<b>Description</b>	
Name	USERGLREST	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NODEGL

<b>Attribute</b>	<b>Description</b>	
Name	NODEGL	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## USERGLEXCEPT

<b>Attribute</b>	<b>Description</b>	
Name	USERGLEXCEPT	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## EXCEPLEAFGL

<b>Attribute</b>	<b>Description</b>	
Name	EXCEPLEAFGL	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## USERLIMITSROLE

<b>Attribute</b>	<b>Description</b>	
Name	USERLIMITSROLE	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxOccurs	unbounded

## LMTBRN

<b>Attribute</b>	<b>Description</b>	
Name	LMTBRN	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## LMTSROLE

<b>Attribute</b>	<b>Description</b>	
Name	LMTSROLE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## QLMTCCY

<b>Attribute</b>	<b>Description</b>	
Name	QLMTCCY	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## QINPLMT

<b>Attribute</b>	<b>Description</b>	
Name	QINPLMT	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## QAUTHLMT

<b>Attribute</b>	<b>Description</b>	
Name	QAUTHLMT	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## USERBRANCHES

<b>Attribute</b>	<b>Description</b>	
Name	USERBRANCHES	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## BRNSBRN

<b>Attribute</b>	<b>Description</b>	
Name	BRNSBRN	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## BRNNAME

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	BRNNAME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	105
	<b>Description</b>	

## USERPRODUCTS

<b>Attribute</b>	<b>Description</b>	
Name	USERPRODUCTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## PRDPRDCD

<b>Attribute</b>	<b>Description</b>	
Name	PRDPRDCD	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	4
	<b>Description</b>	

## PRDESC

<b>Attribute</b>	<b>Description</b>	
Name	PRDESC	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	105
	<b>Description</b>	

## USERACCESSPRODUCTS

<b>Attribute</b>	<b>Description</b>	
Name	USERACCESSPRODUCTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## PRDACCESSPRDCD

Attribute	Description				
Name	PRDACCESSPRDCD				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>4</td></tr></tbody></table>	Restrictions	Description	maxLength	4
Restrictions	Description				
maxLength	4				

## PRDDESC

Attribute	Description				
Name	PRDDESC				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

## USERFUNCDISALLOW

Attribute	Description						
Name	USERFUNCDISALLOW						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## FUNCDISALLOWFUNCID

Attribute	Description				
Name	FUNCDISALLOWFUNCID				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr></tbody></table>	Restrictions	Description	maxLength	8
Restrictions	Description				
maxLength	8				

## USERROLE

Attribute	Description						
Name	USERROLE						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## ROLEBRNCD

Attribute	Description				
Name	ROLEBRNCD				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## USRROLEID

Attribute	Description				
Name	USRROLEID				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## MASTERROLEDESC

Attribute	Description				
Name	MASTERROLEDESC				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>45</td></tr></tbody></table>	Restrictions	Description	maxLength	45
Restrictions	Description				
maxLength	45				

## USERSFUNCTIONS

Attribute	Description						
Name	USERSFUNCTIONS						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## USERFUNCBRNCD

Attribute	Description				
Name	USERFUNCBRNCD				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## USERFUNCFUNCID

Attribute	Description	
Name	USERFUNCFUNCID	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	8

## CONTROL1

Attribute	Description	
Name	CONTROL1	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

## CONTROL2

Attribute	Description	
Name	CONTROL2	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

## CONTROL3

Attribute	Description	
Name	CONTROL3	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

## CONTROL4

Attribute	Description	
Name	CONTROL4	
Datatype	decimal	



Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL6

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL6	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL8

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL8	
Datatype	decimal	

Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### USERFUNCCTRL10

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCCTRL10	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL11

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL11	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL12

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL12	
Datatype	decimal	

Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL13

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL13	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL14

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL14	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL15

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL15	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	

Description	
Attribute	<b>Attribute</b>
	minOccurs
Restrictions	<b>Description</b>
	totalDigits

### Grp-Restriction

<b>Attribute</b>	<b>Description</b>
Name	Grp-Restriction
Datatype	
Description	
Attribute	<b>Attribute</b>
	minOccurs
Restrictions	<b>Description</b>
	maxOccurs

### GROUP\_CODE

<b>Attribute</b>	<b>Description</b>
Name	GROUP_CODE
Datatype	string
Description	
Restrictions	<b>Restrictions</b>
	maxLength

### GROUP\_DESC

<b>Attribute</b>	<b>Description</b>
Name	GROUP_DESC
Datatype	string
Description	
Attribute	<b>Attribute</b>
	minOccurs
Restrictions	<b>Description</b>
	maxLength

### Centralisation

<b>Attribute</b>	<b>Description</b>
Name	Centralisation
Datatype	
Description	
Attribute	<b>Attribute</b>
	minOccurs
Restrictions	<b>Description</b>
	maxOccurs

Attribute		Description	
Name	USRROLEID		
Datatype	string		
Description			
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	15	

## ROLDESC

Attribute		Description	
Name	ROLDESC		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	20	

## Dshmst

Attribute		Description	
Name	Dshmst		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	

## USRID

Attribute		Description	
Name	USRID		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	15	

## USRNAME

Attribute		Description	
Name	USRNAME		
Datatype	string		
Description			

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## Dshdet

<b>Attribute</b>	<b>Description</b>	
Name	Dshdet	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1000

## SEQUENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	SEQUENCE_NO	
Datatype	decimal	
Description		

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## DBWHERECLAUSE

<b>Attribute</b>	<b>Description</b>	
Name	DBWHERECLAUSE	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

## SHOW\_IN\_DASHBOARD

<b>Attribute</b>	<b>Description</b>	
Name	SHOW_IN_DASHBOARD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## Where-Master

<b>Attribute</b>	<b>Description</b>	
Name	Where-Master	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## COLUMN\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	COLUMN_NAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	2000

## WHERE\_CL

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	WHERE_CL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	500

## CONDITION

<b>Attribute</b>	<b>Description</b>	
Name	CONDITION	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

## WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

## WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

### 2.14.4.SM-DeleteUserMaint-Res-PK-MSG.xsd

*DELETEUSERMAINT\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*USR-PK*

*USRID*

*USR-IO*

*USRID*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## DELETEUSERMAINT\_IOPK\_RES

Attribute	Description
Name	DELETEUSERMAINT_IOPK_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## USERID

Attribute	Description

Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response



## USR-PK

Attribute	Description
Name	USR-PK
Datatype	
Description	

## USRID

Attribute	Description				
Name	USRID				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## USR-IO

Attribute	Description
Name	USR-IO
Datatype	
Description	

## USRID

Attribute	Description				
Name	USRID				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## FCUBS\_ERROR\_RESP

Attribute	Description						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

## 2.15.ModifySMDBANKP

2.15.1.SM-ModifySMDBANKP-Req-Full-MSG.xsd

*MODIFYSMDBANKP\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Smtbs-Parameters-Full*  
*HEAD\_OFFICE*  
*SITE\_CODE*  
*ACTIVATION\_KEY*  
*INVALID\_LOGINS\_CUM*  
*INVALID\_LOGINS\_SUC*  
*PWD\_PREVENT\_REUSE*  
*PWD\_CHANGE\_AFTER*  
*MAXIMUM*  
*MINIMUM*  
*PWD\_EXPIRY\_MSG\_DAYS*  
*ARCHIVAL\_PERIOD*  
*CONCHAR\_PWD\_NUM*

*FREQ\_PWD\_CHG*  
*MIN\_PWD\_NUMERIC\_LENGTH*  
*LEGAL\_NOTICE*  
*DORMANCY\_DAYS*  
*DISPLAY\_LEGAL\_NOTICE*  
*MIN\_SPECIALCHAR\_LENGTH*  
*MIN\_LOWERCASE\_CHAR*  
*MIN\_UPPERCASE\_CHAR*  
*SCREESAVERREQUIRED*  
*SCREESAVERTIMEOUTINSECONDS*  
*SCREESAVERMODIFIABLEBYUSER*  
*PASSWORDEXTERNAL*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*Smtbs-Branch-Restr*  
     *RESTR\_TYPE*  
     *DESCRIPTION*  
*Smtbs-Restrictive-Passwd*  
     *PASSWORD*  
*UDFDETAILS*  
     *FLDNAM*  
     *FLDVAL*

**MODIFYSMDBANKP\_FSFS\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	MODIFYSMDBANKP_FSFS_REQ
Datatype	
Description	

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT



Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of ModifySMDBANKP

## Smtbs-Parameters-Full

Attribute	Description
Name	Smtbs-Parameters-Full
Datatype	
Description	

## HEAD\_OFFICE

Attribute	Description				
Name	HEAD_OFFICE				
Datatype	string				
Description	Indicates Head Office				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## SITE\_CODE

Attribute	Description				
Name	SITE_CODE				
Datatype	string				
Description	Indicates Site Code				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>4</td></tr></tbody></table>	Restrictions	Description	maxLength	4
Restrictions	Description				
maxLength	4				

## ACTIVATION\_KEY

Attribute	Description				
Name	ACTIVATION_KEY				
Datatype	string				
Description	Indicates Activation Key				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	24

### INVALID\_LOGINS\_CUM

<b>Attribute</b>	<b>Description</b>	
Name	INVALID_LOGINS_CUM	
Datatype	decimal	
Description	Indicates Cumulative	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	6
	maxInclusive	99

### INVALID\_LOGINS\_SUC

<b>Attribute</b>	<b>Description</b>	
Name	INVALID_LOGINS_SUC	
Datatype	decimal	
Description	Indicates Successive	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	1
	minInclusive	3
	maxInclusive	5

### PWD\_PREVENT\_REUSE

<b>Attribute</b>	<b>Description</b>	
Name	PWD_PREVENT_REUSE	
Datatype	decimal	
Description	Indicates Password Repetitions	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### PWD\_CHANGE\_AFTER

<b>Attribute</b>	<b>Description</b>	
Name	PWD_CHANGE_AFTER	
Datatype	decimal	

Description	Indicates Force Password Change After	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	3
	minInclusive	15
	maxInclusive	180

## MAXIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MAXIMUM	
Datatype	decimal	
Description	Indicates Maximum	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	12
	maxInclusive	30

## MINIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MINIMUM	
Datatype	decimal	
Description	Indicates Minimum	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	6
	maxInclusive	11

## PWD\_EXPIRY\_MSG\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	PWD_EXPIRY_MSG_DAYS	
Datatype	decimal	
Description	Indicates Intimate User (Before Password Expiry)	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1
	maxInclusive	5

## ARCHIVAL\_PERIOD

<b>Attribute</b>	<b>Description</b>	
Name	ARCHIVAL_PERIOD	
Datatype	decimal	

Description	Indicates Archival Period (in days)	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	3

### CONCHAR\_PWD\_NUM

<b>Attribute</b>	<b>Description</b>	
Name	CONCHAR_PWD_NUM	
Datatype	decimal	
Description	Indicates Maximum Consecutive Repetitive Characters	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2

### FREQ\_PWD\_CHG

<b>Attribute</b>	<b>Description</b>	
Name	FREQ_PWD_CHG	
Datatype	decimal	
Description	Indicates Minimum Days Between Password Changes	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	0

### MIN\_PWD\_NUMERIC\_LENGTH

<b>Attribute</b>	<b>Description</b>	
Name	MIN_PWD_NUMERIC_LENGTH	
Datatype	decimal	
Description	Indicates Minimum Number Of Numeric Characters In Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### LEGAL\_NOTICE

<b>Attribute</b>	<b>Description</b>
Name	LEGAL_NOTICE

Datatype	string	
Description	Indicates Warning Screen Text	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

## DORMANCY\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	DORMANCY_DAYS	
Datatype	decimal	
Description	Indicates Dormancy Days	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## DISPLAY\_LEGAL\_NOTICE

<b>Attribute</b>	<b>Description</b>	
Name	DISPLAY_LEGAL_NOTICE	
Datatype	string	
Description	Indicates Display Legal Notice Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MIN\_SPECIALCHAR\_LENGTH

<b>Attribute</b>	<b>Description</b>	
Name	MIN_SPECIALCHAR_LENGTH	
Datatype	decimal	
Description	Indicates Minimum Number Of Special Characters In Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## MIN\_LOWERCASE\_CHAR

<b>Attribute</b>	<b>Description</b>	
Name	MIN_LOWERCASE_CHAR	
Datatype	decimal	

Description	Indicates Minimum Number of LowerCase Characters in Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### MIN\_UPPERCASE\_CHAR

<b>Attribute</b>	<b>Description</b>	
Name	MIN_UPPERCASE_CHAR	
Datatype	decimal	
Description	Indicates Minimum Number of UpperCase Characters in Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### SCRENSAVERREQUIRED

<b>Attribute</b>	<b>Description</b>	
Name	SCRENSAVERREQUIRED	
Datatype	string	
Description	Indicates Screensaver Required Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### SCRENSAVERTIMEOUTINSECONDS

<b>Attribute</b>	<b>Description</b>	
Name	SCRENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description	Indicates Screensaver Interval (in seconds)	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

### SCRENSAVERMODIFIABLEBYUSER

<b>Attribute</b>	<b>Description</b>	
Name	SCRENSAVERMODIFIABLEBYUSER	
Datatype	string	
Description	Indicates Screensaver Interval Modifiable at User Level Y - on N - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PASSWORDEXTERNAL

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORDEXTERNAL	
Datatype	string	
Description	Indicates Password External Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

### Smtbs-Branch-Restr

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Branch-Restr	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### RESTR\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_TYPE	
Datatype	string	
Description	Indicates Restriction Type	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Restriction Type Description	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

### Smtbs-Restrictive-Passwd

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Restrictive-Passwd	
Datatype		
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description	Indicates Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

2.15.2.SM-ModifySMDBANKP-Req-IO-MSG.xsd

[MODIFYSMDBANKP\\_IOPK\\_REQ](#)

[FCUBS\\_HEADER](#)

*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Smtbs-Parameters-IO*  
*SITE\_CODE*  
*INVALID\_LOGINS\_CUM*  
*INVALID\_LOGINS\_SUC*  
*PWD\_PREVENT\_REUSE*  
*PWD\_CHANGE\_AFTER*  
*MAXIMUM*  
*MINIMUM*  
*PWD\_EXPIRY\_MSG\_DAYS*  
*ARCHIVAL\_PERIOD*

*CONCHAR\_PWD\_NUM*  
*FREQ\_PWD\_CHG*  
*MIN\_PWD\_NUMERIC\_LENGTH*  
*LEGAL\_NOTICE*  
*DORMANCY\_DAYS*  
*DISPLAY\_LEGAL\_NOTICE*  
*MIN\_SPECIALCHAR\_LENGTH*  
*MIN\_LOWERCASE\_CHAR*  
*MIN\_UPPERCASE\_CHAR*  
*SCREESAVERREQUIRED*  
*SCREESAVERTIMEOUTINSECONDS*  
*SCREESAVERMODIFIABLEBYUSER*  
*PASSWORDEXTERNAL*  
*MAKER*  
*MAKERSTAMP*  
*Smtbs-Branch-Restr*  
*RESTR\_TYPE*  
*DESCRIPTION*  
*Smtbs-Restrictive-Passwd*  
*PASSWORD*  
*UDFDETAILS*  
*FLDNAM*  
*FLDVAL*

#### **MODIFYSMDBANKP\_IOPK\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	MODIFYSMDBANKP_IOPK_REQ
Datatype	
Description	

#### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

#### **SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	string	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of ModifySMDBANKP

## Smtbs-Parameters-IO

Attribute	Description
Name	Smtbs-Parameters-IO
Datatype	
Description	

## SITE\_CODE

Attribute	Description				
Name	SITE_CODE				
Datatype	string				
Description	Indicates Site Code				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>4</td></tr></tbody></table>	Restrictions	Description	maxLength	4
Restrictions	Description				
maxLength	4				

## INVALID\_LOGINS\_CUM

Attribute	Description								
Name	INVALID_LOGINS_CUM								
Datatype	decimal								
Description	Indicates Cumulative								
Attribute									
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions									
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>6</td></tr><tr><td>maxInclusive</td><td>99</td></tr></tbody></table>	Restrictions	Description	totalDigits	2	minInclusive	6	maxInclusive	99
Restrictions	Description								
totalDigits	2								
minInclusive	6								
maxInclusive	99								

## INVALID\_LOGINS\_SUC

Attribute	Description				
Name	INVALID_LOGINS_SUC				
Datatype	decimal				
Description	Indicates Successive				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	1
	minInclusive	3
	maxInclusive	5

## PWD\_PREVENT\_REUSE

<b>Attribute</b>	<b>Description</b>	
Name	PWD_PREVENT_REUSE	
Datatype	decimal	
Description	Indicates Password Repetitions	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	2
	minInclusive	1

## PWD\_CHANGE\_AFTER

<b>Attribute</b>	<b>Description</b>	
Name	PWD_CHANGE_AFTER	
Datatype	decimal	
Description	Indicates Force Password Change After	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	3
	minInclusive	15
	maxInclusive	180

## MAXIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MAXIMUM	
Datatype	decimal	
Description	Indicates Maximum	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	2
	minInclusive	12
	maxInclusive	30

## MINIMUM

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	MINIMUM	
Datatype	decimal	
Description	Indicates Minimum	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	6
	maxInclusive	11

## PWD\_EXPIRY\_MSG\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	PWD_EXPIRY_MSG_DAYS	
Datatype	decimal	
Description	Indicates Intimate User (Before Password Expiry)	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1
	maxInclusive	5

## ARCHIVAL\_PERIOD

<b>Attribute</b>	<b>Description</b>	
Name	ARCHIVAL_PERIOD	
Datatype	decimal	
Description	Indicates Archival Period (in days)	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	3

## CONCHAR\_PWD\_NUM

<b>Attribute</b>	<b>Description</b>	
Name	CONCHAR_PWD_NUM	
Datatype	decimal	
Description	Indicates Maximum Consecutive Repetitive Characters	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2

### FREQ\_PWD\_CHG

<b>Attribute</b>	<b>Description</b>	
Name	FREQ_PWD_CHG	
Datatype	decimal	
Description	Indicates Minimum Days Between Password Changes	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	0

### MIN\_PWD\_NUMERIC\_LENGTH

<b>Attribute</b>	<b>Description</b>	
Name	MIN_PWD_NUMERIC_LENGTH	
Datatype	decimal	
Description	Indicates Minimum Number Of Numeric Characters In Password	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### LEGAL\_NOTICE

<b>Attribute</b>	<b>Description</b>	
Name	LEGAL_NOTICE	
Datatype	string	
Description	Indicates Warning Screen Text	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

### DORMANCY\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	DORMANCY_DAYS	
Datatype	decimal	
Description	Indicates Dormancy Days	

Attribute	<b>Attribute</b>		<b>Description</b>	
	minOccurs		0	
Restrictions	<b>Restrictions</b>		<b>Description</b>	
	totalDigits		2	
	minInclusive		1	

## DISPLAY\_LEGAL\_NOTICE

<b>Attribute</b>		<b>Description</b>		
Name		DISPLAY_LEGAL_NOTICE		
Datatype		string		
Description		Indicates Display Legal Notice Y - on N - Off		
Attribute	<b>Attribute</b>		<b>Description</b>	
	minOccurs		0	
Restrictions	<b>Restrictions</b>		<b>Description</b>	
	enumeration		Y,N	

## MIN\_SPECIALCHAR\_LENGTH

<b>Attribute</b>		<b>Description</b>		
Name		MIN_SPECIALCHAR_LENGTH		
Datatype		decimal		
Description		Indicates Minimum Number Of Special Characters In Password		
Attribute	<b>Attribute</b>		<b>Description</b>	
	minOccurs		0	
Restrictions	<b>Restrictions</b>		<b>Description</b>	
	totalDigits		2	
	minInclusive		1	

## MIN\_LOWERCASE\_CHAR

<b>Attribute</b>		<b>Description</b>		
Name		MIN_LOWERCASE_CHAR		
Datatype		decimal		
Description		Indicates Minimum Number of LowerCase Characters in Password		
Attribute	<b>Attribute</b>		<b>Description</b>	
	minOccurs		0	
Restrictions	<b>Restrictions</b>		<b>Description</b>	
	totalDigits		2	
	minInclusive		1	

## MIN\_UPPERCASE\_CHAR

Attribute	Description							
Name	MIN_UPPERCASE_CHAR							
Datatype	decimal							
Description	Indicates Minimum Number of UpperCase Characters in Password							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>2</td> </tr> <tr> <td>minInclusive</td> <td>1</td> </tr> </tbody> </table>		Restrictions	Description	totalDigits	2	minInclusive	1
Restrictions	Description							
totalDigits	2							
minInclusive	1							

## SCRENSAVERREQUIRED

Attribute	Description					
Name	SCRENSAVERREQUIRED					
Datatype	string					
Description	Indicates Screensaver Required Y - on N - Off					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Y,N</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	Y,N
Restrictions	Description					
enumeration	Y,N					

## SCRENSAVERTIMEOUTINSECONDS

Attribute	Description					
Name	SCRENSAVERTIMEOUTINSECONDS					
Datatype	decimal					
Description	Indicates Screensaver Interval (in seconds)					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>4</td> </tr> </tbody> </table>		Restrictions	Description	totalDigits	4
Restrictions	Description					
totalDigits	4					

## SCRENSAVERMODIFIABLEBYUSER

Attribute	Description					
Name	SCRENSAVERMODIFIABLEBYUSER					
Datatype	string					
Description	Indicates Screensaver Interval Modifiable at User Level Y - on N - Off					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Y,N</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	Y,N
Restrictions	Description					
enumeration	Y,N					



**PASSWORDEXTERNAL**

Attribute	Description	
Name	PASSWORDEXTERNAL	
Datatype	string	
Description	Indicates Password External Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

**MAKER**

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

**MAKERSTAMP**

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

**Smtbs-Branch-Restr**

Attribute	Description	
Name	Smtbs-Branch-Restr	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

**RESTR\_TYPE**

Attribute	Description
-----------	-------------

Name	RESTR_TYPE	
Datatype	string	
Description	Indicates Restriction Type	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Restriction Type Description	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

## Smtbs-Restrictive-Passwd

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Restrictive-Passwd	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description	Indicates Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

### 2.15.3.SM-ModifySMDBANKP-Res-Full-MSG.xsd

#### *MODIFYSMDBANKP\_FSFS\_RES*

##### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Parameters-Full*

*HEAD\_OFFICE*

*SITE\_CODE*

*ACTIVATION\_KEY*

*INVALID\_LOGINS\_CUM*

*INVALID\_LOGINS\_SUC*

*PWD\_PREVENT\_REUSE*

*PWD\_CHANGE\_AFTER*

*MAXIMUM*

*MINIMUM*

*PWD\_EXPIRY\_MSG\_DAYS*

*ARCHIVAL\_PERIOD*

*CONCHAR\_PWD\_NUM*

*FREQ\_PWD\_CHG*

*MIN\_PWD\_NUMERIC\_LENGTH*

*LEGAL\_NOTICE*

*DORMANCY\_DAYS*

*DISPLAY\_LEGAL\_NOTICE*

*MIN\_SPECIALCHAR\_LENGTH*

*MIN\_LOWERCASE\_CHAR*

*MIN\_UPPERCASE\_CHAR*

*SCREESAVERREQUIRED*

*SCREESAVERTIMEOUTINSECONDS*

*SCREESAVERMODIFIABLEBYUSER*

*PASSWORDEXTERNAL*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Smtbs-Branch-Restr*

*RESTR\_TYPE*

*DESCRIPTION*

*Smtbs-Restrictive-Passwd*

*PASSWORD*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## **MODIFYSMDBANKP\_FSFS\_RES**

<b>Attribute</b>	<b>Description</b>
Name	MODIFYSMDBANKP_FSFS_RES
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	string	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

## Smtbs-Parameters-Full

Attribute	Description
Name	Smtbs-Parameters-Full
Datatype	
Description	

## HEAD\_OFFICE

Attribute	Description				
Name	HEAD_OFFICE				
Datatype	string				
Description	Indicates Head Office				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## SITE\_CODE

Attribute	Description				
Name	SITE_CODE				
Datatype	string				
Description	Indicates Site Code				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>4</td></tr></tbody></table>	Restrictions	Description	maxLength	4
Restrictions	Description				
maxLength	4				

## ACTIVATION\_KEY

Attribute	Description				
Name	ACTIVATION_KEY				
Datatype	string				
Description	Indicates Activation Key				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	24

### INVALID\_LOGINS\_CUM

<b>Attribute</b>	<b>Description</b>	
Name	INVALID_LOGINS_CUM	
Datatype	decimal	
Description	Indicates Cumulative	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	6
	maxInclusive	99

### INVALID\_LOGINS\_SUC

<b>Attribute</b>	<b>Description</b>	
Name	INVALID_LOGINS_SUC	
Datatype	decimal	
Description	Indicates Successive	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	1
	minInclusive	3
	maxInclusive	5

### PWD\_PREVENT\_REUSE

<b>Attribute</b>	<b>Description</b>	
Name	PWD_PREVENT_REUSE	
Datatype	decimal	
Description	Indicates Password Repetitions	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### PWD\_CHANGE\_AFTER

<b>Attribute</b>	<b>Description</b>	
Name	PWD_CHANGE_AFTER	
Datatype	decimal	

Description	Indicates Force Password Change After	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	3
	minInclusive	15
	maxInclusive	180

## MAXIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MAXIMUM	
Datatype	decimal	
Description	Indicates Maximum	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	12
	maxInclusive	30

## MINIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MINIMUM	
Datatype	decimal	
Description	Indicates Minimum	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	6
	maxInclusive	11

## PWD\_EXPIRY\_MSG\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	PWD_EXPIRY_MSG_DAYS	
Datatype	decimal	
Description	Indicates Intimate User (Before Password Expiry)	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1
	maxInclusive	5

## ARCHIVAL\_PERIOD

<b>Attribute</b>	<b>Description</b>	
Name	ARCHIVAL_PERIOD	
Datatype	decimal	

Description	Indicates Archival Period (in days)	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	3

### CONCHAR\_PWD\_NUM

<b>Attribute</b>	<b>Description</b>	
Name	CONCHAR_PWD_NUM	
Datatype	decimal	
Description	Indicates Maximum Consecutive Repetitive Characters	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2

### FREQ\_PWD\_CHG

<b>Attribute</b>	<b>Description</b>	
Name	FREQ_PWD_CHG	
Datatype	decimal	
Description	Indicates Minimum Days Between Password Changes	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	0

### MIN\_PWD\_NUMERIC\_LENGTH

<b>Attribute</b>	<b>Description</b>	
Name	MIN_PWD_NUMERIC_LENGTH	
Datatype	decimal	
Description	Indicates Minimum Number Of Numeric Characters In Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### LEGAL\_NOTICE

<b>Attribute</b>	<b>Description</b>
Name	LEGAL_NOTICE

Datatype	string	
Description	Indicates Warning Screen Text	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

## DORMANCY\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	DORMANCY_DAYS	
Datatype	decimal	
Description	Indicates Dormancy Days	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## DISPLAY\_LEGAL\_NOTICE

<b>Attribute</b>	<b>Description</b>	
Name	DISPLAY_LEGAL_NOTICE	
Datatype	string	
Description	Indicates Display Legal Notice Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MIN\_SPECIALCHAR\_LENGTH

<b>Attribute</b>	<b>Description</b>	
Name	MIN_SPECIALCHAR_LENGTH	
Datatype	decimal	
Description	Indicates Minimum Number Of Special Characters In Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## MIN\_LOWERCASE\_CHAR

<b>Attribute</b>	<b>Description</b>	
Name	MIN_LOWERCASE_CHAR	
Datatype	decimal	

Description	Indicates Minimum Number of LowerCase Characters in Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## MIN\_UPPERCASE\_CHAR

<b>Attribute</b>	<b>Description</b>	
Name	MIN_UPPERCASE_CHAR	
Datatype	decimal	
Description	Indicates Minimum Number of UpperCase Characters in Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## SCREENSAVERREQUIRED

<b>Attribute</b>	<b>Description</b>	
Name	SCREENSAVERREQUIRED	
Datatype	string	
Description	Indicates Screensaver Required Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SCREENSAVERTIMEOUTINSECONDS

<b>Attribute</b>	<b>Description</b>	
Name	SCREENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description	Indicates Screensaver Interval (in seconds)	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## SCREENSAVERMODIFIABLEBYUSER

<b>Attribute</b>	<b>Description</b>	
Name	SCREENSAVERMODIFIABLEBYUSER	
Datatype	string	
Description	Indicates Screensaver Interval Modifiable at User Level Y - on N - Off	



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PASSWORDEXTERNAL

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORDEXTERNAL	
Datatype	string	
Description	Indicates Password External Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

### Smtbs-Branch-Restr

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Branch-Restr	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### RESTR\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_TYPE	
Datatype	string	
Description	Indicates Restriction Type	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Restriction Type Description	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

### Smtbs-Restrictive-Passwd

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Restrictive-Passwd	
Datatype		
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description	Indicates Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	maxOccurs	unbounded

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	maxOccurs	unbounded

## WCODE

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

### 2.15.4.SM-ModifySMDBANKP-Res-PK-MSG.xsd

#### *MODIFYSMDBANKP\_IOPK\_RES*

##### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

##### *FCUBS\_BODY*

*Smtbs-Parameters-PK*

*SITE\_CODE*

*Smtbs-Parameters-IO*

*SITE\_CODE*

*INVALID\_LOGINS\_CUM*

*INVALID\_LOGINS\_SUC*

*PWD\_PREVENT\_REUSE*

*PWD\_CHANGE\_AFTER*

*MAXIMUM*

*MINIMUM*

*PWD\_EXPIRY\_MSG\_DAYS*

*ARCHIVAL\_PERIOD*

*CONCHAR\_PWD\_NUM*

*FREQ\_PWD\_CHG*

*MIN\_PWD\_NUMERIC\_LENGTH*

*LEGAL\_NOTICE*

*DORMANCY\_DAYS*

*DISPLAY\_LEGAL\_NOTICE*

*MIN\_SPECIALCHAR\_LENGTH*

*MIN\_LOWERCASE\_CHAR*

*MIN\_UPPERCASE\_CHAR*

*SCRENSAVERREQUIRED*

*SCRENSAVERTIMEOUTINSECONDS*

*SCRENSAVERMODIFIABLEBYUSER*

*PASSWORDEXTERNAL*

*MAKER*

*MAKERSTAMP*

*Smtbs-Branch-Restr*

*RESTR\_TYPE*

*DESCRIPTION*

*Smtbs-Restrictive-Passwd*

*PASSWORD*

*UDFDETAILS*

*FLDNAM*

FLDVAL

FCUBS\_ERROR\_RESP

ERROR

ECODE

EDESC

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

### MODIFYSMDBANKP\_IOPK\_RES

Attribute	Description
Name	MODIFYSMDBANKP_IOPK_RES
Datatype	
Description	

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

### SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

### UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				



## MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

## CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	string				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

## USERID

Attribute	Description						
Name	USERID						
Datatype	string						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	12					
pattern	[A-Z_0-9]*						

## BRANCH

Attribute	Description
Name	BRANCH

Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

## ADDL

Attribute		Description	
Name	ADDL		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

## PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

## NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

## VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

## FCUBS\_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description	This XSD Gives Information about PK Response		

## Smtbs-Parameters-PK

Attribute		Description	
Name	Smtbs-Parameters-PK		
Datatype			
Description			

## SITE\_CODE

Attribute		Description	
Name	SITE_CODE		
Datatype	string		
Description	Indicates Site Code		

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

### Smtbs-Parameters-IO

Attribute	Description
Name	Smtbs-Parameters-IO
Datatype	
Description	

### SITE\_CODE

Attribute	Description	
Name	SITE_CODE	
Datatype	string	
Description	Indicates Site Code	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

### INVALID\_LOGINS\_CUM

Attribute	Description	
Name	INVALID_LOGINS_CUM	
Datatype	decimal	
Description	Indicates Cumulative	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	6
	maxInclusive	99

### INVALID\_LOGINS\_SUC

Attribute	Description	
Name	INVALID_LOGINS_SUC	
Datatype	decimal	
Description	Indicates Successive	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	1
	minInclusive	3
	maxInclusive	5

### PWD\_PREVENT\_REUSE

Attribute	Description
-----------	-------------

Name	PWD_PREVENT_REUSE	
Datatype	decimal	
Description	Indicates Password Repetitions	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## PWD\_CHANGE\_AFTER

<b>Attribute</b>	<b>Description</b>	
Name	PWD_CHANGE_AFTER	
Datatype	decimal	
Description	Indicates Force Password Change After	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	3
	minInclusive	15
	maxInclusive	180

## MAXIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MAXIMUM	
Datatype	decimal	
Description	Indicates Maximum	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	12
	maxInclusive	30

## MINIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MINIMUM	
Datatype	decimal	
Description	Indicates Minimum	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	2
	minInclusive	6
	maxInclusive	11

### PWD\_EXPIRY\_MSG\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	PWD_EXPIRY_MSG_DAYS	
Datatype	decimal	
Description	Indicates Intimate User (Before Password Expiry)	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	2
	minInclusive	1
	maxInclusive	5

### ARCHIVAL\_PERIOD

<b>Attribute</b>	<b>Description</b>	
Name	ARCHIVAL_PERIOD	
Datatype	decimal	
Description	Indicates Archival Period (in days)	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	3

### CONCHAR\_PWD\_NUM

<b>Attribute</b>	<b>Description</b>	
Name	CONCHAR_PWD_NUM	
Datatype	decimal	
Description	Indicates Maximum Consecutive Repetitive Characters	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	2

### FREQ\_PWD\_CHG

<b>Attribute</b>	<b>Description</b>	
Name	FREQ_PWD_CHG	
Datatype	decimal	



Description	Indicates Minimum Days Between Password Changes	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	0

## MIN\_PWD\_NUMERIC\_LENGTH

<b>Attribute</b>	<b>Description</b>	
Name	MIN_PWD_NUMERIC_LENGTH	
Datatype	decimal	
Description	Indicates Minimum Number Of Numeric Characters In Password	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## LEGAL\_NOTICE

<b>Attribute</b>	<b>Description</b>	
Name	LEGAL_NOTICE	
Datatype	string	
Description	Indicates Warning Screen Text	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

## DORMANCY\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	DORMANCY_DAYS	
Datatype	decimal	
Description	Indicates Dormancy Days	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## DISPLAY\_LEGAL\_NOTICE

Attribute		Description	
Name	DISPLAY_LEGAL_NOTICE		
Datatype	string		
Description	Indicates Display Legal Notice Y - on N - Off		
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	Y,N	

### MIN\_SPECIALCHAR\_LENGTH

Attribute		Description	
Name	MIN_SPECIALCHAR_LENGTH		
Datatype	decimal		
Description	Indicates Minimum Number Of Special Characters In Password		
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	2	
	minInclusive	1	

### MIN\_LOWERCASE\_CHAR

Attribute		Description	
Name	MIN_LOWERCASE_CHAR		
Datatype	decimal		
Description	Indicates Minimum Number of LowerCase Characters in Password		
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	2	
	minInclusive	1	

### MIN\_UPPERCASE\_CHAR

Attribute		Description	
Name	MIN_UPPERCASE_CHAR		
Datatype	decimal		
Description	Indicates Minimum Number of UpperCase Characters in Password		
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## SCRENSAVERREQUIRED

<b>Attribute</b>	<b>Description</b>	
Name	SCRENSAVERREQUIRED	
Datatype	string	
Description	Indicates Screensaver Required Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SCRENSAVERTIMEOUTINSECONDS

<b>Attribute</b>	<b>Description</b>	
Name	SCRENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description	Indicates Screensaver Interval (in seconds)	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## SCRENSAVERMODIFIABLEBYUSER

<b>Attribute</b>	<b>Description</b>	
Name	SCRENSAVERMODIFIABLEBYUSER	
Datatype	string	
Description	Indicates Screensaver Interval Modifiable at User Level Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PASSWORDEXTERNAL

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORDEXTERNAL	
Datatype	string	
Description	Indicates Password External Y - on N - Off	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## Smtbs-Branch-Restr

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Branch-Restr	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## RESTR\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_TYPE	
Datatype	string	
Description	Indicates Restriction Type	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Restriction Type Description	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

## Smtbs-Restrictive-Passwd

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Restrictive-Passwd	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description	Indicates Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

## EDESC

Attribute	Description	
Name	EDESC	

Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

## 2.16.ModifySMDRLMNE

2.16.1.SM-ModifySMDRLMNE-Req-Full-MSG.xsd

*MODIFYSMOURLMNE\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Smtbs-Role-Limit-Full*  
*ROLEID2*  
*DESCRIPTION*  
*LIMIT\_CCY*  
*INPUT\_LIMIT*  
*AUTHORIZATION\_LIMIT*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*UDFDETAILS*  
*FLDNAM*  
*FLDVAL*



Attribute	Description
Name	MODIFYSMOBSMNE_FSFS_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	pattern	[a-zA-Z_0-9]*

## USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of ModifySMDRLMNE

## Smtbs-Role-Limit-Full

<b>Attribute</b>	<b>Description</b>
Name	Smtbs-Role-Limit-Full
Datatype	
Description	

## ROLEID2

<b>Attribute</b>	<b>Description</b>	
Name	ROLEID2	
Datatype	string	
Description	Indicates Role Id	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Description	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## LIMIT\_CCY

Attribute	Description				
Name	LIMIT_CCY				
Datatype	string				
Description	Indicates Limit Currency				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## INPUT\_LIMIT

Attribute	Description						
Name	INPUT_LIMIT						
Datatype	decimal						
Description	Indicates Input Limit						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0
Restrictions	Description						
totalDigits	22						
minInclusive	0						

## AUTHORIZATION\_LIMIT

Attribute	Description						
Name	AUTHORIZATION_LIMIT						
Datatype	decimal						
Description	Indicates Authorization Limit						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0
Restrictions	Description						
totalDigits	22						
minInclusive	0						

## MAKER

Attribute	Description				
Name	MAKER				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

*MODIFYSMOBSMNE\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Role-Limit-IO*

*ROLEID2*

*DESCRIPTION*

*LIMIT\_CCY*

*INPUT\_LIMIT*

*AUTHORIZATION\_LIMIT*

*MAKER*

*MAKERSTAMP*

## UDFDETAILS

### FLDNAM

### FLDVAL

## MODIFYSMDRLMNE\_IOPK\_REQ

Attribute	Description
Name	MODIFYSMDRLMNE_IOPK_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	string				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	string
Description	This is the user id in the Source system who is performing the action.

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
	maxOccurs	unbounded	

## NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

## VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

## FCUBS\_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description	This XSD Gives Information about IO Request of ModifySMDRLMNE		

## Smtbs-Role-Limit-IO

Attribute		Description	
Name	Smtbs-Role-Limit-IO		
Datatype			
Description			

## ROLEID2

Attribute		Description	
Name	ROLEID2		
Datatype	string		
Description	Indicates Role Id		
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	15	

## DESCRIPTION

Attribute		Description	
Name	DESCRIPTION		
Datatype	string		
Description	Indicates Description		



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

### LIMIT\_CCY

<b>Attribute</b>	<b>Description</b>	
Name	LIMIT_CCY	
Datatype	string	
Description	Indicates Limit Currency	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### INPUT\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	INPUT_LIMIT	
Datatype	decimal	
Description	Indicates Input Limit	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0

### AUTHORIZATION\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHORIZATION_LIMIT	
Datatype	decimal	
Description	Indicates Authorization Limit	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0

### MAKER

<b>Attribute</b>	<b>Description</b>
Name	MAKER

Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

2.16.3.SM-ModifySMDRLMNE-Res-Full-MSG.xsd

*MODIFYSMOURLMNE\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Role-Limit-Full*

*ROLEID2*

*DESCRIPTION*

*LIMIT\_CCY*

*INPUT\_LIMIT*

*AUTHORIZATION\_LIMIT*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## **MODIFYSMOVLNNE\_FSFS\_RES**

<b>Attribute</b>	<b>Description</b>
Name	MODIFYSMOVLNNE_FSFS_RES
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

<b>Attribute</b>	<b>Description</b>
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

Attribute	Description

Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

## Smtbs-Role-Limit-Full

Attribute	Description
Name	Smtbs-Role-Limit-Full
Datatype	
Description	

## ROLEID2

Attribute	Description				
Name	ROLEID2				
Datatype	string				
Description	Indicates Role Id				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>15</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## DESCRIPTION

Attribute	Description				
Name	DESCRIPTION				
Datatype	string				
Description	Indicates Description				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>105</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

## LIMIT\_CCY

Attribute	Description				
Name	LIMIT_CCY				
Datatype	string				
Description	Indicates Limit Currency				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## INPUT\_LIMIT

Attribute	Description
Name	INPUT_LIMIT
Datatype	decimal
Description	Indicates Input Limit

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0

## AUTHORIZATION\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHORIZATION_LIMIT	
Datatype	decimal	
Description	Indicates Authorization Limit	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	ERROR	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

## WDESC

<b>Attribute</b>	<b>Description</b>
Name	WDESC
Datatype	String
Description	

*MODIFYSMDRLMNE\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Role-Limit-PK*

*ROLEID2*

*Smtbs-Role-Limit-IO*

*ROLEID2*

*DESCRIPTION*

*LIMIT\_CCY*

*INPUT\_LIMIT*

*AUTHORIZATION\_LIMIT*

*MAKER*

*MAKERSTAMP*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## MODIFYSMDRMNE\_IOPK\_RES

Attribute	Description
Name	MODIFYSMDRMNE_IOPK_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	string
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.



Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	string
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	

Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about PK Response	

## Smtbs-Role-Limit-PK

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Role-Limit-PK	
Datatype		
Description		

## ROLEID2

<b>Attribute</b>	<b>Description</b>	
------------------	--------------------	--

Name	ROLEID2	
Datatype	string	
Description	Indicates Role Id	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

### Smtbs-Role-Limit-IO

<b>Attribute</b>	<b>Description</b>
Name	Smtbs-Role-Limit-IO
Datatype	
Description	

### ROLEID2

<b>Attribute</b>	<b>Description</b>	
Name	ROLEID2	
Datatype	string	
Description	Indicates Role Id	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

### DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

### LIMIT\_CCY

<b>Attribute</b>	<b>Description</b>	
Name	LIMIT_CCY	
Datatype	string	
Description	Indicates Limit Currency	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### INPUT\_LIMIT

<b>Attribute</b>	<b>Description</b>
Name	INPUT_LIMIT

Datatype	decimal	
Description	Indicates Input Limit	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0

## AUTHORIZATION\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHORIZATION_LIMIT	
Datatype	decimal	
Description	Indicates Authorization Limit	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	maxOccurs	unbounded

## ECODE



Attribute	Description
Name	ECODE
Datatype	String
Description	

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

## 2.17.ModifySMRole

### 2.17.1.SM-ModifySMRole-Req-Full-MSG.xsd

*MODIFYSMROLE\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*ROLEMASTER-Full*  
*ROLEIDENTIFICATION*  
*MASTERROLEDESC*  
*AUTHORISEROLE*  
*BRANCH\_RES*  
*ACCCLASSALLOWED*  
*CENTRALISATIONROLE*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*

*TXNSTAT*

*AUTHSTAT*

*ROLEDETAIL*

*ROLEFUN*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*CONTROL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CONTROL15*

*CONTROL16*

*ROLEDETAILB*

*ROLEFUN*

*CONT1*

*CONT2*

*CONT3*

*CONT4*

*CONT5*

*CONT6*

*CONTROL7*

*CONT8*

*CONT9*

*CONT10*

*CONT11*

*CONT12*

*CONT13*

*CONT14*

*CONT15*

*CONTROL16*

*ROLEDETAILC*

*ROLEFUN*

*CNTRL1*

*CNTRL2*

*CNTRL3*

*CNTRL4*

*CNTRL5*

*CNTRL6*

*CNTRL7*

*CNTRL8*

*CNTRL9*

*CNTRL10*

*CNTRL11*

*CNTRL12*

*CNTRL13*

*CNTRL14*

*CNTRL15*

*CNTRL16*

*ROLEDETAILD*

*ROLEFUN*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*CONTROL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CNTRL15*

*CNTRL16*

*ROLEBRANCHES*

*BRANCH*

*BRNNAME*

*ROLEACCCLASS*

*ACCCLS*

*DESCRIPTION*

*MSGCRIGHTS*

*CNL*

*CHGNODE*

*REL*

*CHGMEDIA*

*BRNMOV*

*HLD*

*TSTINP*

*CHGADDR*

*REINS*

*CHGPRIOR*

*CNLAUTH*

*CHGNODEAUTH*

*RELAUTH*

*CHGMEDIAAUTH*

*BRNMOVAUTH*

*HLDAUTH*  
*TSTINPAUTH*  
*CHGADDRAUTH*  
*REINSAUTH*  
*CHGPRIORAUTH*  
*GEN*  
*TSTCHK*  
*LNKCONT*  
*CHGBRNIN*  
*CHGMSG*  
*CHGFORCRELFUND*  
*SUPPRESS*  
*DELMSG*  
*PRNT*  
*FTUPL*  
*MOVQ*  
*CHGADDRIN*  
*CHGMSGAUTH*  
*AUTHRGHTS*  
*CHGFORCCOVMATCH*  
*QUEUERIGHTS*  
*QUEUE*  
*RESTRICTIVEPASSWD*  
*PWD*  
*PWDID*  
*ROLEBRANCHLIMITS*  
*LMTCCY*  
*BRHUSERLMT*  
*Roledetaile*  
*ROLEFUN*  
*BRANCHCODE*  
*EDITABLE*

*CNTRLSTR*

*Roledetailf*

*ROLEID*

*ROLEFUN*

*CNTRLSTR*

*CNTRL1*

*CNTRL10*

*CNTRL11*

*CNTRL12*

*CNTRL13*

*CNTRL14*

*CNTRL15*

*CNTRL16*

*CNTRL2*

*CNTRL3*

*CNTRL4*

*CNTRL5*

*CNTRL6*

*CNTRL7*

*CNTRL8*

*CNTRL9*

*ATHSTAT*

*BRNCHCODE*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

**MODIFYSMROLE\_FSFS\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	MODIFYSMROLE_FSFS_REQ
Datatype	
Description	

**FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	string	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to	



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of ModifySMRole

## ROLEMASTER-Full

Attribute	Description
Name	ROLEMASTER-Full
Datatype	
Description	

## ROLEIDENTIFICATION

Attribute	Description				
Name	ROLEIDENTIFICATION				
Datatype	string				
Description	Indicates Role Id				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## MASTERROLEDESC

Attribute	Description				
Name	MASTERROLEDESC				
Datatype	string				
Description	Indicates Role Description				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

## AUTHORISERROLE

Attribute	Description				
Name	AUTHORISERROLE				
Datatype	string				
Description	Indicates Authorizer Role Y - on N - Off				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRANCH\_RES

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_RES	
Datatype	string	
Description	Indicates Branch Restriction A - Allowed D - Disallowed	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## ACCCLASSALLOWED

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLASSALLOWED	
Datatype	string	
Description	Indicates Account Class Restriction A - Allowed D - Disallowed	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## CENTRALISATIONROLE

<b>Attribute</b>	<b>Description</b>	
Name	CENTRALISATIONROLE	
Datatype	string	
Description	Indicates Centralisation Role Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

### TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

### AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

### ROLEDETAIL

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAIL	
Datatype		
Description	Maintenance	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

### CONTROL1

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL4

<b>Attribute</b>	<b>Description</b>
Name	CONTROL4

Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL6

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL8

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL8	
Datatype	decimal	
Description	Indicates Auth 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL10

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL11

Attribute		Description	
Name		CONTROL11	
Datatype		decimal	
Description		Indicates Confirm 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL12

Attribute		Description	
Name		CONTROL12	
Datatype		decimal	
Description		Indicates Liquidate 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL13

Attribute		Description	
Name		CONTROL13	
Datatype		decimal	
Description		Indicates Hold 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL14

Attribute		Description	
Name		CONTROL14	
Datatype		decimal	
Description		Indicates Template 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL15

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEDETAILB

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILB	
Datatype		
Description	Roles	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

### CONT1

<b>Attribute</b>	<b>Description</b>	
Name	CONT1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT2

<b>Attribute</b>	<b>Description</b>	
Name	CONT2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT3

<b>Attribute</b>	<b>Description</b>	
Name	CONT3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT4

<b>Attribute</b>	<b>Description</b>
Name	CONT4

Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT5

<b>Attribute</b>	<b>Description</b>	
Name	CONT5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT6

<b>Attribute</b>	<b>Description</b>	
Name	CONT6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT8

<b>Attribute</b>	<b>Description</b>	
Name	CONT8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT9

<b>Attribute</b>	<b>Description</b>	
Name	CONT9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT10

<b>Attribute</b>	<b>Description</b>	
Name	CONT10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT11



Attribute		Description	
Name		CONT11	
Datatype		decimal	
Description		Indicates Confirm 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONT12

Attribute		Description	
Name		CONT12	
Datatype		decimal	
Description		Indicates Liquidate 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONT13

Attribute		Description	
Name		CONT13	
Datatype		decimal	
Description		Indicates Hold 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONT14

Attribute		Description	
Name		CONT14	
Datatype		decimal	
Description		Indicates Template 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT15

<b>Attribute</b>	<b>Description</b>	
Name	CONT15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEDETAILC

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILC	
Datatype		
Description	Batch	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

### CNTRL1

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL2

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL3

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL4

<b>Attribute</b>	<b>Description</b>
Name	CNTRL4

Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL5

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL6

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL7

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL8

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL9

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL10

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL11

Attribute		Description	
Name		CNTRL11	
Datatype		decimal	
Description		Indicates Confirm 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CNTRL12

Attribute		Description	
Name		CNTRL12	
Datatype		decimal	
Description		Indicates Liquidate 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CNTRL13

Attribute		Description	
Name		CNTRL13	
Datatype		decimal	
Description		Indicates Hold 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CNTRL14

Attribute		Description	
Name		CNTRL14	
Datatype		decimal	
Description		Indicates Template 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL15

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL16

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEDETAILD

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILD	
Datatype		
Description	Roles	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

### CONTROL1

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL4

<b>Attribute</b>	<b>Description</b>
Name	CONTROL4



Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL6

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL8

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL8	
Datatype	decimal	
Description	Indicates Auth 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL10

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL11

Attribute		Description	
Name		CONTROL11	
Datatype		decimal	
Description		Indicates Confirm 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL12

Attribute		Description	
Name		CONTROL12	
Datatype		decimal	
Description		Indicates Liquidate 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL13

Attribute		Description	
Name		CONTROL13	
Datatype		decimal	
Description		Indicates Hold 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL14

Attribute		Description	
Name		CONTROL14	
Datatype		decimal	
Description		Indicates Template 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL15

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL16

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEBRANCHES

<b>Attribute</b>	<b>Description</b>	
Name	ROLEBRANCHES	
Datatype		
Description	Branches	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	Indicates Branch	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## BRNNAME

<b>Attribute</b>	<b>Description</b>	
Name	BRNNAME	
Datatype	string	
Description	Indicates Branch Name	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## ROLEACCCLASS

<b>Attribute</b>	<b>Description</b>	
Name	ROLEACCCLASS	
Datatype		
Description	Acc Class Restriction	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ACCCLS

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLS	
Datatype	string	
Description	Indicates Account Class	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Account Class Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## MSGCRIGHTS

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	MSGCRIGHTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## CNL

<b>Attribute</b>	<b>Description</b>	
Name	CNL	
Datatype	string	
Description	Indicates Cancel Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODE

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODE	
Datatype	string	
Description	Indicates Change Node Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REL

<b>Attribute</b>	<b>Description</b>	
Name	REL	
Datatype	string	
Description	Indicates Release Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIA

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIA	
Datatype	string	
Description	Indicates Change Media Y - on N - Off	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOV

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOV	
Datatype	string	
Description	Indicates Branch Move Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLD

<b>Attribute</b>	<b>Description</b>	
Name	HLD	
Datatype	string	
Description	Indicates Hold Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINP

<b>Attribute</b>	<b>Description</b>	
Name	TSTINP	
Datatype	string	
Description	Indicates Test Input Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDR

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDR	
Datatype	string	
Description	Indicates Change Address Y - on N - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINS

<b>Attribute</b>	<b>Description</b>	
Name	REINS	
Datatype	string	
Description	Indicates Reinststate Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIOR

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIOR	
Datatype	string	
Description	Indicates Change Priority Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNLAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CNLAUTH	
Datatype	string	
Description	Indicates Auth Cancel Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODEAUTH	
Datatype	string	
Description	Indicates Auth Change Node Y - on N - Off	



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## RELAUTH

<b>Attribute</b>	<b>Description</b>	
Name	RELAUTH	
Datatype	string	
Description	Indicates Release Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIAAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIAAUTH	
Datatype	string	
Description	Indicates Change Media Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOVAUTH

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOVAUTH	
Datatype	string	
Description	Indicates Auth Branch Move Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLDAUTH

<b>Attribute</b>	<b>Description</b>
Name	HLDAUTH
Datatype	string

Description	Indicates Hold Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINPAUTH

<b>Attribute</b>	<b>Description</b>	
Name	TSTINPAUTH	
Datatype	string	
Description	Indicates Auth Test Input Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRAUTH	
Datatype	string	
Description	Indicates Change Address Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINSAUTH

<b>Attribute</b>	<b>Description</b>	
Name	REINSAUTH	
Datatype	string	
Description	Indicates Auth Reinstate Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIORAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIORAUTH	

Datatype	string	
Description	Indicates Change Priority Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## GEN

<b>Attribute</b>	<b>Description</b>	
Name	GEN	
Datatype	string	
Description	Indicates Install Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTCHK

<b>Attribute</b>	<b>Description</b>	
Name	TSTCHK	
Datatype	string	
Description	Indicates Test Check Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## LNKCONT

<b>Attribute</b>	<b>Description</b>	
Name	LNKCONT	
Datatype	string	
Description	Indicates Link Contract Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGBRNIN

<b>Attribute</b>	<b>Description</b>
Name	CHGBRNIN

Datatype	string	
Description	Indicates Change Branch In Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSG

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSG	
Datatype	string	
Description	Indicates Change Message Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGFORCRELFUND

<b>Attribute</b>	<b>Description</b>	
Name	CHGFORCRELFUND	
Datatype	string	
Description	Indicates Change Force Release Fund Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SUPPRESS

<b>Attribute</b>	<b>Description</b>	
Name	SUPPRESS	
Datatype	string	
Description	Indicates Suppress Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DELMSG

Attribute	Description	
Name	DELMSG	
Datatype	string	
Description	Indicates Delete Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PRNT

Attribute	Description	
Name	PRNT	
Datatype	string	
Description	Indicates Print Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## FTUPL

Attribute	Description	
Name	FTUPL	
Datatype	string	
Description	Indicates FT Upload Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MOVQ

Attribute	Description	
Name	MOVQ	
Datatype	string	
Description	Indicates Move To Queue Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRIN

Attribute	Description	
Name	CHGADDRIN	
Datatype	string	
Description	Indicates Change Address In Y - on N - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGMSGAUTH

Attribute	Description	
Name	CHGMSGAUTH	
Datatype	string	
Description	Indicates Auth Change Message Y - on N - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## AUTHRGHTS

Attribute	Description	
Name	AUTHRGHTS	
Datatype	string	
Description	Indicates Auth Rights Y - on N - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGFORCCOVMATCH

Attribute	Description	
Name	CHGFORCCOVMATCH	
Datatype	string	
Description	Indicates Change Force Cover Match Y - on N - Off	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## QUEUERIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	QUEUERIGHTS	
Datatype		
Description	Queues	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## QUEUE

<b>Attribute</b>	<b>Description</b>	
Name	QUEUE	
Datatype	string	
Description	Indicates Queue	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## RESTRICTIVEPASSWD

<b>Attribute</b>	<b>Description</b>	
Name	RESTRICTIVEPASSWD	
Datatype		
Description	Restricted Password	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PWD

<b>Attribute</b>	<b>Description</b>	
Name	PWD	
Datatype	string	
Description	Indicates Password	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## PWDID

<b>Attribute</b>	<b>Description</b>	
Name	PWDID	
Datatype	string	
Description	Indicates Id	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## ROLEBRANCHLIMITS

<b>Attribute</b>	<b>Description</b>	
Name	ROLEBRANCHLIMITS	
Datatype		
Description	User Limits	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxOccurs	unbounded

## LMTCCY

<b>Attribute</b>	<b>Description</b>	
Name	LMTCCY	
Datatype	string	
Description	Indicates Limit Currency	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## BRHUSERLMT

<b>Attribute</b>	<b>Description</b>	
Name	BRHUSERLMT	
Datatype	decimal	
Description	Indicates User Limit	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## Roledetaile

<b>Attribute</b>	<b>Description</b>	
Name	Roledetaile	
Datatype		
Description	Process Stage Rights	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxOccurs	unbounded

## ROLEFUN



Attribute	Description	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	string	
Description	Indicates Branch Code	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## EDITABLE

Attribute	Description	
Name	EDITABLE	
Datatype	decimal	
Description	Indicates Editable 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CNTRLSTR

Attribute	Description	
Name	CNTRLSTR	
Datatype	string	
Description	Indicates Control String	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

## Roledetailf

Attribute	Description	
Name	Roledetailf	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## ROLEID

Attribute	Description	
Name	ROLEID	
Datatype	string	
Description	Indicates Role Function	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	15

## ROLEFUN

Attribute	Description	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8

## CNTRLSTR

Attribute	Description	
Name	CNTRLSTR	
Datatype	string	
Description	Indicates Control String	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	16

## CNTRL1

Attribute	Description
Name	CNTRL1
Datatype	decimal

Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL10

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL11

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL12

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL12	
Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL13**

Attribute	Description	
Name	CNTRL13	
Datatype	decimal	
Description	Indicates Hold 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL14**

Attribute	Description	
Name	CNTRL14	
Datatype	decimal	
Description	Indicates Template 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL15**

Attribute	Description	
Name	CNTRL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL16**

Attribute	Description	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL2

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL3

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL4

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL5**

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL6**

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL7**

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL8**

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL9

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ATHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	ATHSTAT	
Datatype	string	
Description	Indicates Authorization Status	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## BRNCHCODE

<b>Attribute</b>	<b>Description</b>	
Name	BRNCHCODE	
Datatype	string	
Description	Indicates Branch Code	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

### 2.17.2.SM-ModifySMRole-Req-IO-MSG.xsd

*MODIFYSMROLE\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*



*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*ROLEMASTER-IO*  
*ROLEIDENTIFICATION*  
*MASTERROLEDESC*  
*BRANCHROLE*  
*BRANCHROLELEVEL*  
*BRANCHPWDRESETFREQ*  
*AUTHORISERROLE*  
*BRANCHVLTROLE*  
*BRANCH\_RES*  
*ACCCLASSALLOWED*  
*CENTRALISATIONROLE*  
*MAKER*  
*MAKERSTAMP*  
*ROLEDETAIL*  
*CONTROLSTRING*  
*ROLEFUN*  
*CONTROL1*  
*CONTROL2*  
*CONTROL3*  
*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*CONTROL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CONTROL15*

*CONTROL16*

*ATHSTAT*

*BRNCHCODE*

*ROLEDETAILB*

*CNTRLSTR*

*ROLEFUN*

*CONT1*

*CONT2*

*CONT3*

*CONT4*

*CONT5*

*CONT6*

*CONTROL7*

*CONT8*

*CONT9*

*CONT10*

*CONT11*

*CONT12*

*CONT13*

*CONT14*

*CONT15*

*CONTROL16*  
*ATHATAT*  
*BRHCODE*  
*ROLEDETAILC*  
*CNTRLSTR*  
*ROLEFUN*  
*CNTRL1*  
*CNTRL2*  
*CNTRL3*  
*CNTRL4*  
*CNTRL5*  
*CNTRL6*  
*CNTRL7*  
*CNTRL8*  
*CNTRL9*  
*CNTRL10*  
*CNTRL11*  
*CNTRL12*  
*CNTRL13*  
*CNTRL14*  
*CNTRL15*  
*CNTRL16*  
*ATHSTAT*  
*ROLEDETAILD*  
*CNTRLSTRING*  
*ROLEFUN*  
*CONTROL1*  
*CONTROL2*  
*CONTROL3*  
*CONTROL4*  
*CONTROL5*  
*CONTROL6*

*CONTROL7*  
*CONTROL8*  
*CONTROL9*  
*CONTROL10*  
*CONTROL11*  
*CONTROL12*  
*CONTROL13*  
*CONTROL14*  
*CNTRL15*  
*CNTRL16*  
*ROLEBRANCHES*  
*BRANCH*  
*ROLEACCCLASS*  
*ACCCLS*  
*MSGCRIGHTS*  
*CNL*  
*CHGNODE*  
*REL*  
*CHGMEDIA*  
*BRNMOV*  
*HLD*  
*TSTINP*  
*CHGADDR*  
*REINS*  
*CHGPRIOR*  
*CNLAUTH*  
*CHGNODEAUTH*  
*RELAUTH*  
*CHGMEDIAAUTH*  
*BRNMOVAUTH*  
*HLDAUTH*  
*TSTINPAUTH*

*CHGADDRAUTH*  
*REINSAUTH*  
*CHGPRIORAUTH*  
*GEN*  
*TSTCHK*  
*LNKCONT*  
*CHGBRNIN*  
*CHGMSG*  
*CHGFORCRELFUND*  
*SUPPRESS*  
*DELMSG*  
*PRNT*  
*FTUPL*  
*MOVQ*  
*CHGADDRIN*  
*CHGMSGAUTH*  
*AUTHRGHTS*  
*CHGFORCCOVMATCH*  
*QUEUERIGHTS*  
*QUEUE*  
*RESTRICTIVEPASSWD*  
*PWD*  
*ROLEBRANCHLIMITS*  
*LMTCCY*  
*EXRATE*  
*BRHLOWERLMT*  
*BRHUPPRLMT*  
*BRHUSERLMT*  
*Roledetaile*  
*ROLEFUN*  
*EDITABLE*  
*CNTRLSTR*

*CONTROL\_1*  
*CONTROL\_10*  
*CONTROL\_11*  
*CONTROL\_12*  
*CONTROL\_13*  
*CONTROL\_14*  
*CONTROL\_15*  
*CONTROL\_16*  
*CONTROL\_2*  
*CONTROL\_3*  
*CONTROL\_4*  
*CONTROL\_6*  
*CONTROL\_7*  
*CONTROL\_8*  
*CONTROL\_9*

*Roledetailf*

*ROLEFUN*  
*CNTRLSTR*  
*CNTRL1*  
*CNTRL10*  
*CNTRL11*  
*CNTRL12*  
*CNTRL13*  
*CNTRL14*  
*CNTRL15*  
*CNTRL16*  
*CNTRL2*  
*CNTRL3*  
*CNTRL4*  
*CNTRL5*  
*CNTRL6*  
*CNTRL7*

CNTRL8

CNTRL9

UDFDETAILS

FLDNAM

FLDVAL

## MODIFYSMROLE\_IOPK\_REQ

Attribute	Description
Name	MODIFYSMROLE_IOPK_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID



Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	string				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	string
Description	This is the user id in the Source system who is performing the action.

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

## FCUBS\_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about IO Request of ModifySMRole	

## ROLEMASTER-IO

Attribute	Description	
Name	ROLEMASTER-IO	
Datatype		
Description		

## ROLEIDENTIFICATION

Attribute	Description	
Name	ROLEIDENTIFICATION	
Datatype	string	
Description	Indicates Role Id	
Restrictions	Restrictions	Description
	maxLength	15

## MASTERROLEDESC

Attribute	Description	
Name	MASTERROLEDESC	
Datatype	string	
Description	Indicates Role Description	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## BRANCHROLE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCHROLE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRANCHROLELEVEL

<b>Attribute</b>	<b>Description</b>	
Name	BRANCHROLELEVEL	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## BRANCHPWDRESETREQ

<b>Attribute</b>	<b>Description</b>	
Name	BRANCHPWDRESETREQ	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## AUTHORISEROLE

<b>Attribute</b>	<b>Description</b>	
Name	AUTHORISEROLE	
Datatype	string	
Description	Indicates Authorizer Role Y - on N - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRANCHVLTROLE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCHVLTROLE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRANCH\_RES

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_RES	
Datatype	string	
Description	Indicates Branch Restriction A - Allowed D - Disallowed	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## ACCCLASSALLOWED

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLASSALLOWED	
Datatype	string	
Description	Indicates Account Class Restriction A - Allowed D - Disallowed	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## CENTRALISATIONROLE

<b>Attribute</b>	<b>Description</b>
Name	CENTRALISATIONROLE

Datatype	string	
Description	Indicates Centralisation Role Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## ROLEDETAIL

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAIL	
Datatype		
Description	Maintenance	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## CONTROLSTRING

<b>Attribute</b>	<b>Description</b>	
Name	CONTROLSTRING	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## CONTROL1

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

#### CONTROL4

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

#### CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

#### CONTROL6

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONTROL7**

Attribute	Description	
Name	CONTROL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONTROL8**

Attribute	Description	
Name	CONTROL8	
Datatype	decimal	
Description	Indicates Auth 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONTROL9**

Attribute	Description	
Name	CONTROL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONTROL10**

Attribute	Description	
Name	CONTROL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL11

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL12

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL12	
Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL13

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL13	
Datatype	decimal	
Description	Indicates Hold 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL14

Attribute	Description								
Name	CONTROL14								
Datatype	decimal								
Description	Indicates Template 1 - on 0 - Off								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0	maxInclusive	1
Restrictions	Description								
totalDigits	22								
minInclusive	0								
maxInclusive	1								

## CONTROL15

Attribute	Description								
Name	CONTROL15								
Datatype	decimal								
Description	Indicates View 1 - on 0 - Off								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0	maxInclusive	1
Restrictions	Description								
totalDigits	22								
minInclusive	0								
maxInclusive	1								

## CONTROL16

Attribute	Description								
Name	CONTROL16								
Datatype	decimal								
Description	Indicates Generate 1 - on 0 - Off								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0	maxInclusive	1
Restrictions	Description								
totalDigits	22								
minInclusive	0								
maxInclusive	1								

## ATHSTAT

Attribute	Description
Name	ATHSTAT
Datatype	string
Description	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## BRNCHCODE

<b>Attribute</b>	<b>Description</b>	
Name	BRNCHCODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## ROLEDETAILB

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILB	
Datatype		
Description	Roles	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## CNTRLSTR

<b>Attribute</b>	<b>Description</b>	
Name	CNTRLSTR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

**CONT1**

Attribute	Description	
Name	CONT1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONT2**

Attribute	Description	
Name	CONT2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONT3**

Attribute	Description	
Name	CONT3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONT4**

Attribute	Description	
Name	CONT4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT5

<b>Attribute</b>	<b>Description</b>	
Name	CONT5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT6

<b>Attribute</b>	<b>Description</b>	
Name	CONT6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONT8**

<b>Attribute</b>	<b>Description</b>	
Name	CONT8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONT9**

<b>Attribute</b>	<b>Description</b>	
Name	CONT9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONT10**

<b>Attribute</b>	<b>Description</b>	
Name	CONT10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONT11**

<b>Attribute</b>	<b>Description</b>	
Name	CONT11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT12

<b>Attribute</b>	<b>Description</b>	
Name	CONT12	
Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT13

<b>Attribute</b>	<b>Description</b>	
Name	CONT13	
Datatype	decimal	
Description	Indicates Hold 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT14

<b>Attribute</b>	<b>Description</b>	
Name	CONT14	
Datatype	decimal	
Description	Indicates Template 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONT15**

Attribute	Description	
Name	CONT15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONTROL16**

Attribute	Description	
Name	CONTROL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**ATHATAT**

Attribute	Description	
Name	ATHATAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**BRHCODE**

Attribute	Description	
Name	BRHCODE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## ROLEDETAILC

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILC	
Datatype		
Description	Batch	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## CNTRLSTR

<b>Attribute</b>	<b>Description</b>	
Name	CNTRLSTR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## CNTRL1

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL2

Attribute		Description	
Name		CNTRL2	
Datatype		decimal	
Description		Indicates Copy 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

### CNTRL3

Attribute		Description	
Name		CNTRL3	
Datatype		decimal	
Description		Indicates Delete 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

### CNTRL4

Attribute		Description	
Name		CNTRL4	
Datatype		decimal	
Description		Indicates Close 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

### CNTRL5

Attribute		Description	
Name		CNTRL5	
Datatype		decimal	
Description		Indicates Unlock 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL6

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL7

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL8

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL9

Attribute		Description	
Name		CNTRL9	
Datatype		decimal	
Description		Indicates Reverse 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

### CNTRL10

Attribute		Description	
Name		CNTRL10	
Datatype		decimal	
Description		Indicates Rollover 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

### CNTRL11

Attribute		Description	
Name		CNTRL11	
Datatype		decimal	
Description		Indicates Confirm 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

### CNTRL12

Attribute		Description	
Name		CNTRL12	
Datatype		decimal	
Description		Indicates Liquidate 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL13

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL13	
Datatype	decimal	
Description	Indicates Hold 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL14

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL14	
Datatype	decimal	
Description	Indicates Template 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL15

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL16

Attribute	Description	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ATHSTAT

Attribute	Description	
Name	ATHSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## ROLEDETAILD

Attribute	Description	
Name	ROLEDETAILD	
Datatype		
Description	Roles	
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## CNTRLSTRING

Attribute	Description	
Name	CNTRLSTRING	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

## ROLEFUN

Attribute	Description
Name	ROLEFUN



Datatype	string	
Description	Indicates Role Function	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

### CONTROL1

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
Restrictions	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
Restrictions	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
Restrictions	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL4

Attribute	Description	
Name	CONTROL4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL5

Attribute	Description	
Name	CONTROL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL6

Attribute	Description	
Name	CONTROL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL7

Attribute	Description	
Name	CONTROL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL8

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL8	
Datatype	decimal	
Description	Indicates Auth 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL10

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL11

<b>Attribute</b>		<b>Description</b>	
Name		CONTROL11	
Datatype		decimal	
Description		Indicates Confirm 1 - on 0 - Off	
Attribute			
		<b>Attribute</b>	<b>Description</b>
		minOccurs	0
Restrictions			
		<b>Restrictions</b>	<b>Description</b>
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL12

<b>Attribute</b>		<b>Description</b>	
Name		CONTROL12	
Datatype		decimal	
Description		Indicates Liquidate 1 - on 0 - Off	
Attribute			
		<b>Attribute</b>	<b>Description</b>
		minOccurs	0
Restrictions			
		<b>Restrictions</b>	<b>Description</b>
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL13

<b>Attribute</b>		<b>Description</b>	
Name		CONTROL13	
Datatype		decimal	
Description		Indicates Hold 1 - on 0 - Off	
Attribute			
		<b>Attribute</b>	<b>Description</b>
		minOccurs	0
Restrictions			
		<b>Restrictions</b>	<b>Description</b>
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL14

<b>Attribute</b>		<b>Description</b>	
Name		CONTROL14	
Datatype		decimal	
Description		Indicates Template 1 - on 0 - Off	
Attribute			
		<b>Attribute</b>	<b>Description</b>
		minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL15

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL16

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEBRANCHES

<b>Attribute</b>	<b>Description</b>	
Name	ROLEBRANCHES	
Datatype		
Description	Branches	
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	Indicates Branch	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## ROLEACCCLASS

<b>Attribute</b>	<b>Description</b>	
Name	ROLEACCCLASS	
Datatype		
Description	Acc Class Restriction	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ACCCLS

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLS	
Datatype	string	
Description	Indicates Account Class	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

## MSGCRIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	MSGCRIGHTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## CNL

<b>Attribute</b>	<b>Description</b>	
Name	CNL	
Datatype	string	
Description	Indicates Cancel Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODE

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODE	
Datatype	string	
Description	Indicates Change Node Y - on N - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REL

<b>Attribute</b>	<b>Description</b>	
Name	REL	
Datatype	string	
Description	Indicates Release Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIA

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIA	
Datatype	string	
Description	Indicates Change Media Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOV

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOV	
Datatype	string	
Description	Indicates Branch Move Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLD

<b>Attribute</b>	<b>Description</b>	
Name	HLD	
Datatype	string	
Description	Indicates Hold Y - on N - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINP

<b>Attribute</b>	<b>Description</b>	
Name	TSTINP	
Datatype	string	
Description	Indicates Test Input Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDR

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDR	
Datatype	string	
Description	Indicates Change Address Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINS

<b>Attribute</b>	<b>Description</b>	
Name	REINS	
Datatype	string	
Description	Indicates Reinstate Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIOR

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIOR	
Datatype	string	



Description	Indicates Change Priority Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNLAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CNLAUTH	
Datatype	string	
Description	Indicates Auth Cancel Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODEAUTH	
Datatype	string	
Description	Indicates Auth Change Node Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## RELAUTH

<b>Attribute</b>	<b>Description</b>	
Name	RELAUTH	
Datatype	string	
Description	Indicates Release Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIAAUTH

<b>Attribute</b>	<b>Description</b>
Name	CHGMEDIAAUTH

Datatype	string	
Description	Indicates Change Media Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOVAUTH

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOVAUTH	
Datatype	string	
Description	Indicates Auth Branch Move Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLDAUTH

<b>Attribute</b>	<b>Description</b>	
Name	HLDAUTH	
Datatype	string	
Description	Indicates Hold Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINPAUTH

<b>Attribute</b>	<b>Description</b>	
Name	TSTINPAUTH	
Datatype	string	
Description	Indicates Auth Test Input Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CHGADDRAUTH	
Datatype	string	
Description	Indicates Change Address Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINSAUTH

<b>Attribute</b>	<b>Description</b>	
Name	REINSAUTH	
Datatype	string	
Description	Indicates Auth Reinstate Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIORAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIORAUTH	
Datatype	string	
Description	Indicates Change Priority Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## GEN

<b>Attribute</b>	<b>Description</b>	
Name	GEN	
Datatype	string	
Description	Indicates Install Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTCHK

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	TSTCHK	
Datatype	string	
Description	Indicates Test Check Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## LNKCONT

<b>Attribute</b>	<b>Description</b>	
Name	LNKCONT	
Datatype	string	
Description	Indicates Link Contract Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGBRNIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGBRNIN	
Datatype	string	
Description	Indicates Change Branch In Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSG

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSG	
Datatype	string	
Description	Indicates Change Message Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGFORCREFUND

Attribute		Description	
Name	CHGFORCRELFUND		
Datatype	string		
Description	Indicates Change Force Release Fund Y - on N - Off		
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	Y,N	

## SUPPRESS

Attribute		Description	
Name	SUPPRESS		
Datatype	string		
Description	Indicates Suppress Y - on N - Off		
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	Y,N	

## DELMSG

Attribute		Description	
Name	DELMSG		
Datatype	string		
Description	Indicates Delete Y - on N - Off		
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	Y,N	

## PRNT

Attribute		Description	
Name	PRNT		
Datatype	string		
Description	Indicates Print Y - on N - Off		
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	Y,N	

## FTUPL

Attribute	Description	
Name	FTUPL	
Datatype	string	
Description	Indicates FT Upload Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MOVQ

Attribute	Description	
Name	MOVQ	
Datatype	string	
Description	Indicates Move To Queue Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRIN

Attribute	Description	
Name	CHGADDRIN	
Datatype	string	
Description	Indicates Change Address In Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSGAUTH

Attribute	Description	
Name	CHGMSGAUTH	
Datatype	string	
Description	Indicates Auth Change Message Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## AUTHRGHTS

<b>Attribute</b>	<b>Description</b>	
Name	AUTHRGHTS	
Datatype	string	
Description	Indicates Auth Rights Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGFORCCOVMATCH

<b>Attribute</b>	<b>Description</b>	
Name	CHGFORCCOVMATCH	
Datatype	string	
Description	Indicates Change Force Cover Match Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## QUEUERIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	QUEUERIGHTS	
Datatype		
Description	Queues	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## QUEUE

<b>Attribute</b>	<b>Description</b>	
Name	QUEUE	
Datatype	string	
Description	Indicates Queue	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## RESTRICTIVEPASSWD

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	RESTRICTIVEPASSWD	
Datatype		
Description	Restricted Password	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## PWD

<b>Attribute</b>	<b>Description</b>	
Name	PWD	
Datatype	string	
Description	Indicates Password	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## ROLEBRANCHLIMITS

<b>Attribute</b>	<b>Description</b>	
Name	ROLEBRANCHLIMITS	
Datatype		
Description	User Limits	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## LMTCCY

<b>Attribute</b>	<b>Description</b>	
Name	LMTCCY	
Datatype	string	
Description	Indicates Limit Currency	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## EXRATE

<b>Attribute</b>	<b>Description</b>	
Name	EXRATE	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## BRHLOWERLMT

<b>Attribute</b>	<b>Description</b>	
Name	BRHLOWERLMT	



Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## BRHUPRLMT

<b>Attribute</b>	<b>Description</b>	
Name	BRHUPRLMT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## BRUSERLMT

<b>Attribute</b>	<b>Description</b>	
Name	BRUSERLMT	
Datatype	decimal	
Description	Indicates User Limit	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## Roledetaile

<b>Attribute</b>	<b>Description</b>	
Name	Roledetaile	
Datatype		
Description	Process Stage Rights	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## EDITABLE

<b>Attribute</b>	<b>Description</b>	
Name	EDITABLE	
Datatype	decimal	
Description	Indicates Editable 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CNTRLSTR

<b>Attribute</b>	<b>Description</b>	
Name	CNTRLSTR	
Datatype	string	
Description	Indicates Control String	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

## CONTROL\_1

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_1	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL\_10

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_10	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL\_11

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_11	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL\_12

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_12	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL\_13

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_13	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL\_14

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_14	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL\_15

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_15	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL\_16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_16	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL\_2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_2	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL\_3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_3	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

#### CONTROL\_4

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_4	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

#### CONTROL\_6

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_6	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

#### CONTROL\_7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_7	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

#### CONTROL\_8

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_8	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL\_9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_9	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## Roledetailf

<b>Attribute</b>	<b>Description</b>	
Name	Roledetailf	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## CNTRLSTR

<b>Attribute</b>	<b>Description</b>	
Name	CNTRLSTR	
Datatype	string	
Description	Indicates Control String	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

### CNTRL1

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL10

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL11

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL12

<b>Attribute</b>	<b>Description</b>
Name	CNTRL12

Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL13

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL13	
Datatype	decimal	
Description	Indicates Hold 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL14

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL14	
Datatype	decimal	
Description	Indicates Template 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL15

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL16

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL2

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL3

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL4

Attribute		Description	
Name		CNTRL4	
Datatype		decimal	
Description		Indicates Close 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CNTRL5

Attribute		Description	
Name		CNTRL5	
Datatype		decimal	
Description		Indicates Unlock 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CNTRL6

Attribute		Description	
Name		CNTRL6	
Datatype		decimal	
Description		Indicates Reopen 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CNTRL7

Attribute		Description	
Name		CNTRL7	
Datatype		decimal	
Description		Indicates Print 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL8

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL9

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>
Name	FLDNAM
Datatype	string
Description	Indicates Field Name

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

### 2.17.3.SM-ModifySMRole-Res-Full-MSG.xsd

#### *MODIFYSMROLE\_FSFS\_RES*

##### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*ROLEMASTER-Full*

*ROLEIDENTIFICATION*

*MASTERROLEDESC*

*AUTHORISERROLE*

*BRANCH\_RES*

*ACCCLASSALLOWED*

*CENTRALISATIONROLE*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*ROLEDETAIL*

*ROLEFUN*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*CONTROL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CONTROL15*

*CONTROL16*

*ROLEDETAILB*

*ROLEFUN*

*CONT1*

*CONT2*

*CONT3*

*CONT4*

*CONT5*

*CONT6*

*CONTROL7*

*CONT8*

*CONT9*

*CONT10*

*CONT11*

*CONT12*

*CONT13*

*CONT14*

*CONT15*

*CONTROL16*

*ROLEDETAILC*

*ROLEFUN*

*CNTRL1*

*CNTRL2*

*CNTRL3*

*CNTRL4*

*CNTRL5*

*CNTRL6*

*CNTRL7*

*CNTRL8*

*CNTRL9*

*CNTRL10*

*CNTRL11*

*CNTRL12*

*CNTRL13*

*CNTRL14*

*CNTRL15*

*CNTRL16*

*ROLEDETAILED*

*ROLEFUN*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*CONTROL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CNTRL15*

*CNTRL16*

*ROLEBRANCHES*

*BRANCH*

*BRNNAME*

*ROLEACCCLASS*

*ACCCLS*

*DESCRIPTION*

*MSGCRIGHTS*

*CNL*

*CHGNODE*

*REL*

*CHGMEDIA*

*BRNMOV*

*HLD*

*TSTINP*

*CHGADDR*

*REINS*

*CHGPRIOR*

*CNLAUTH*

*CHGNODEAUTH*

*RELAUTH*

*CHGMEDIAAUTH*

*BRNMOVAUTH*

*HLDAUTH*

*TSTINPAUTH*

*CHGADDRAUTH*

*REINSAUTH*

*CHGPRIORAUTH*

*GEN*

*TSTCHK*

*LNKCONT*

*CHGBRNIN*

*CHGMSG*

*CHGFORCRELFUND*

*SUPPRESS*

*DELMSG*

*PRNT*

*FTUPL*

*MOVQ*



*CHGADDRIN*

*CHGMSGAUTH*

*AUTHRGHTS*

*CHGFORCCOVMATCH*

*QUEUERIGHTS*

*QUEUE*

*RESTRICTIVEPASSWD*

*PWD*

*PWDID*

*ROLEBRANCHLIMITS*

*LMTCCY*

*BRHUSERLMT*

*Roledetaile*

*ROLEFUN*

*BRANCHCODE*

*EDITABLE*

*CNTRLSTR*

*Roledetailf*

*ROLEID*

*ROLEFUN*

*CNTRLSTR*

*CNTRL1*

*CNTRL10*

*CNTRL11*

*CNTRL12*

*CNTRL13*

*CNTRL14*

*CNTRL15*

*CNTRL16*

*CNTRL2*

*CNTRL3*

*CNTRL4*

*CNTRL5*

*CNTRL6*

*CNTRL7*

*CNTRL8*

*CNTRL9*

*ATHSTAT*

*BRNCHCODE*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## **MODIFYSMROLE\_FSFS\_RES**

<b>Attribute</b>	<b>Description</b>
Name	MODIFYSMROLE_FSFS_RES
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

<b>Attribute</b>	<b>Description</b>
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

Attribute	Description

Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

## ROLEMASTER-Full

Attribute	Description
Name	ROLEMASTER-Full
Datatype	
Description	

## ROLEIDENTIFICATION

Attribute	Description				
Name	ROLEIDENTIFICATION				
Datatype	string				
Description	Indicates Role Id				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>15</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## MASTERROLEDESC

Attribute	Description				
Name	MASTERROLEDESC				
Datatype	string				
Description	Indicates Role Description				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

## AUTHORISERROLE

Attribute	Description				
Name	AUTHORISERROLE				
Datatype	string				
Description	Indicates Authorizer Role Y - on N - Off				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Y,N</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## BRANCH\_RES

Attribute	Description



Name	BRANCH_RES	
Datatype	string	
Description	Indicates Branch Restriction A - Allowed D - Disallowed	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## ACCCLASSALLOWED

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLASSALLOWED	
Datatype	string	
Description	Indicates Account Class Restriction A - Allowed D - Disallowed	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## CENTRALISATIONROLE

<b>Attribute</b>	<b>Description</b>	
Name	CENTRALISATIONROLE	
Datatype	string	
Description	Indicates Centralisation Role Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

## CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	1
	<b>Description</b>	

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	1
	<b>Description</b>	

## ROLEDETAIL

Attribute	Description	
Name	ROLEDETAIL	
Datatype		
Description	Maintenance	
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## ROLEFUN

Attribute	Description	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Restrictions	<b>Restrictions</b>	
	maxLength	8
	<b>Description</b>	

## CONTROL1

Attribute	Description	
Name	CONTROL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL4

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL5

Attribute	Description								
Name	CONTROL5								
Datatype	decimal								
Description	Indicates Unlock 1 - on 0 - Off								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
	Attribute	Description							
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0	maxInclusive	1
	Restrictions	Description							
	totalDigits	22							
	minInclusive	0							
maxInclusive	1								

## CONTROL6

Attribute	Description								
Name	CONTROL6								
Datatype	decimal								
Description	Indicates Reopen 1 - on 0 - Off								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
	Attribute	Description							
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0	maxInclusive	1
	Restrictions	Description							
	totalDigits	22							
	minInclusive	0							
maxInclusive	1								

## CONTROL7

Attribute	Description								
Name	CONTROL7								
Datatype	decimal								
Description	Indicates Print 1 - on 0 - Off								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
	Attribute	Description							
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0	maxInclusive	1
	Restrictions	Description							
	totalDigits	22							
	minInclusive	0							
maxInclusive	1								

## CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	decimal
Description	Indicates Auth 1 - on 0 - Off

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL10

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL11

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONTROL12**

Attribute	Description	
Name	CONTROL12	
Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONTROL13**

Attribute	Description	
Name	CONTROL13	
Datatype	decimal	
Description	Indicates Hold 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONTROL14**

Attribute	Description	
Name	CONTROL14	
Datatype	decimal	
Description	Indicates Template 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONTROL15**

Attribute	Description	
Name	CONTROL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEDETAILB

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILB	
Datatype		
Description	Roles	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## CONT1

<b>Attribute</b>	<b>Description</b>	
Name	CONT1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT2

<b>Attribute</b>	<b>Description</b>	
Name	CONT2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT3

<b>Attribute</b>	<b>Description</b>	
Name	CONT3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT4

<b>Attribute</b>	<b>Description</b>	
Name	CONT4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONT5**

Attribute	Description	
Name	CONT5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONT6**

Attribute	Description	
Name	CONT6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONTROL7**

Attribute	Description	
Name	CONTROL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONT8**

Attribute	Description	
Name	CONT8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT9

<b>Attribute</b>	<b>Description</b>	
Name	CONT9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT10

<b>Attribute</b>	<b>Description</b>	
Name	CONT10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT11

<b>Attribute</b>	<b>Description</b>	
Name	CONT11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONT12**

<b>Attribute</b>	<b>Description</b>	
Name	CONT12	
Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONT13**

<b>Attribute</b>	<b>Description</b>	
Name	CONT13	
Datatype	decimal	
Description	Indicates Hold 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONT14**

<b>Attribute</b>	<b>Description</b>	
Name	CONT14	
Datatype	decimal	
Description	Indicates Template 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONT15**

<b>Attribute</b>	<b>Description</b>	
Name	CONT15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEDETAILC

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILC	
Datatype		
Description	Batch	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## CNTRL1

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	

Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL2

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL3

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL4

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL5**

Attribute	Description	
Name	CNTRL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL6**

Attribute	Description	
Name	CNTRL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL7**

Attribute	Description	
Name	CNTRL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL8**

Attribute	Description	
Name	CNTRL8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL9

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL10

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL11

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1



**CNTRL12**

Attribute	Description	
Name	CNTRL12	
Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL13**

Attribute	Description	
Name	CNTRL13	
Datatype	decimal	
Description	Indicates Hold 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL14**

Attribute	Description	
Name	CNTRL14	
Datatype	decimal	
Description	Indicates Template 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL15**

Attribute	Description	
Name	CNTRL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL16

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEDETAILD

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILD	
Datatype		
Description	Roles	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## CONTROL1

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL4

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL5

Attribute	Description								
Name	CONTROL5								
Datatype	decimal								
Description	Indicates Unlock 1 - on 0 - Off								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
	Attribute	Description							
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0	maxInclusive	1
	Restrictions	Description							
	totalDigits	22							
	minInclusive	0							
maxInclusive	1								

## CONTROL6

Attribute	Description								
Name	CONTROL6								
Datatype	decimal								
Description	Indicates Reopen 1 - on 0 - Off								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
	Attribute	Description							
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0	maxInclusive	1
	Restrictions	Description							
	totalDigits	22							
	minInclusive	0							
maxInclusive	1								

## CONTROL7

Attribute	Description								
Name	CONTROL7								
Datatype	decimal								
Description	Indicates Print 1 - on 0 - Off								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
	Attribute	Description							
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0	maxInclusive	1
	Restrictions	Description							
	totalDigits	22							
	minInclusive	0							
maxInclusive	1								

## CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	decimal
Description	Indicates Auth 1 - on 0 - Off

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL10

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL11

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONTROL12**

Attribute	Description	
Name	CONTROL12	
Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONTROL13**

Attribute	Description	
Name	CONTROL13	
Datatype	decimal	
Description	Indicates Hold 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CONTROL14**

Attribute	Description	
Name	CONTROL14	
Datatype	decimal	
Description	Indicates Template 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL15**

Attribute	Description	
Name	CNTRL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	

Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL16

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEBRANCHES

<b>Attribute</b>	<b>Description</b>	
Name	ROLEBRANCHES	
Datatype		
Description	Branches	
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	Indicates Branch	
Restrictions	<b>Restrictions</b>	
	maxLength	3

## BRNNAME

<b>Attribute</b>	<b>Description</b>	
Name	BRNNAME	
Datatype	string	
Description	Indicates Branch Name	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## ROLEACCCLASS

<b>Attribute</b>	<b>Description</b>	
Name	ROLEACCCLASS	
Datatype		
Description	Acc Class Restriction	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ACCCLS

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLS	
Datatype	string	
Description	Indicates Account Class	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Account Class Description	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## MSGCRIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	MSGCRIGHTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## CNL

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	CNL	
Datatype	string	
Description	Indicates Cancel Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODE

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODE	
Datatype	string	
Description	Indicates Change Node Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REL

<b>Attribute</b>	<b>Description</b>	
Name	REL	
Datatype	string	
Description	Indicates Release Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIA

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIA	
Datatype	string	
Description	Indicates Change Media Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOV

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	BRNMOV	
Datatype	string	
Description	Indicates Branch Move Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLD

<b>Attribute</b>	<b>Description</b>	
Name	HLD	
Datatype	string	
Description	Indicates Hold Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINP

<b>Attribute</b>	<b>Description</b>	
Name	TSTINP	
Datatype	string	
Description	Indicates Test Input Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDR

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDR	
Datatype	string	
Description	Indicates Change Address Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINS

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	REINS	
Datatype	string	
Description	Indicates Reinststate Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIOR

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIOR	
Datatype	string	
Description	Indicates Change Priority Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNLAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CNLAUTH	
Datatype	string	
Description	Indicates Auth Cancel Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODEAUTH	
Datatype	string	
Description	Indicates Auth Change Node Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## RELAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	RELAUTH	
Datatype	string	
Description	Indicates Release Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIAAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIAAUTH	
Datatype	string	
Description	Indicates Change Media Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOVAUTH

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOVAUTH	
Datatype	string	
Description	Indicates Auth Branch Move Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLDAUTH

<b>Attribute</b>	<b>Description</b>	
Name	HLDAUTH	
Datatype	string	
Description	Indicates Hold Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINPAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	TSTINPAUTH	
Datatype	string	
Description	Indicates Auth Test Input Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRAUTH	
Datatype	string	
Description	Indicates Change Address Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINSAUTH

<b>Attribute</b>	<b>Description</b>	
Name	REINSAUTH	
Datatype	string	
Description	Indicates Auth Reinstate Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIORAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIORAUTH	
Datatype	string	
Description	Indicates Change Priority Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## GEN

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	GEN	
Datatype	string	
Description	Indicates Install Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTCHK

<b>Attribute</b>	<b>Description</b>	
Name	TSTCHK	
Datatype	string	
Description	Indicates Test Check Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## LNKCONT

<b>Attribute</b>	<b>Description</b>	
Name	LNKCONT	
Datatype	string	
Description	Indicates Link Contract Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGBRNIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGBRNIN	
Datatype	string	
Description	Indicates Change Branch In Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSG

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CHGMSG	
Datatype	string	
Description	Indicates Change Message Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGFORCRELFUND

<b>Attribute</b>	<b>Description</b>	
Name	CHGFORCRELFUND	
Datatype	string	
Description	Indicates Change Force Release Fund Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SUPPRESS

<b>Attribute</b>	<b>Description</b>	
Name	SUPPRESS	
Datatype	string	
Description	Indicates Suppress Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DELMSG

<b>Attribute</b>	<b>Description</b>	
Name	DELMSG	
Datatype	string	
Description	Indicates Delete Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PRNT

Attribute	Description	
Name	PRNT	
Datatype	string	
Description	Indicates Print Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## FTUPL

Attribute	Description	
Name	FTUPL	
Datatype	string	
Description	Indicates FT Upload Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MOVQ

Attribute	Description	
Name	MOVQ	
Datatype	string	
Description	Indicates Move To Queue Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRIN

Attribute	Description	
Name	CHGADDRIN	
Datatype	string	
Description	Indicates Change Address In Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSGAUTH



Attribute	Description	
Name	CHGMSGAUTH	
Datatype	string	
Description	Indicates Auth Change Message Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## AUTHRGHTS

Attribute	Description	
Name	AUTHRGHTS	
Datatype	string	
Description	Indicates Auth Rights Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGFORCCOVMATCH

Attribute	Description	
Name	CHGFORCCOVMATCH	
Datatype	string	
Description	Indicates Change Force Cover Match Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## QUEUERIGHTS

Attribute	Description	
Name	QUEUERIGHTS	
Datatype		
Description	Queues	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## QUEUE

Attribute	Description
-----------	-------------

Name	QUEUE	
Datatype	string	
Description	Indicates Queue	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## RESTRICTIVEPASSWD

<b>Attribute</b>	<b>Description</b>	
Name	RESTRICTIVEPASSWD	
Datatype		
Description	Restricted Password	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PWD

<b>Attribute</b>	<b>Description</b>	
Name	PWD	
Datatype	string	
Description	Indicates Password	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## PWDID

<b>Attribute</b>	<b>Description</b>	
Name	PWDID	
Datatype	string	
Description	Indicates Id	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## ROLEBRANCLIMITS

<b>Attribute</b>	<b>Description</b>	
Name	ROLEBRANCLIMITS	
Datatype		
Description	User Limits	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## LMTCCY

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	LMTCCY	
Datatype	string	
Description	Indicates Limit Currency	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## BRHUSERLMT

<b>Attribute</b>	<b>Description</b>	
Name	BRHUSERLMT	
Datatype	decimal	
Description	Indicates User Limit	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## Roledetaile

<b>Attribute</b>	<b>Description</b>	
Name	Roledetaile	
Datatype		
Description	Process Stage Rights	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## BRANCHCODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCHCODE	
Datatype	string	
Description	Indicates Branch Code	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## EDITABLE

<b>Attribute</b>	<b>Description</b>	
Name	EDITABLE	
Datatype	decimal	
Description	Indicates Editable 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CNTRLSTR

<b>Attribute</b>	<b>Description</b>	
Name	CNTRLSTR	
Datatype	string	
Description	Indicates Control String	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

## Roledetailf

<b>Attribute</b>	<b>Description</b>	
Name	Roledetailf	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEID

<b>Attribute</b>	<b>Description</b>	
Name	ROLEID	
Datatype	string	
Description	Indicates Role Function	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## CNTRLSTR

<b>Attribute</b>	<b>Description</b>	
Name	CNTRLSTR	
Datatype	string	
Description	Indicates Control String	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

## CNTRL1

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL10

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL11

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL12

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL12	
Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL13

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL13	
Datatype	decimal	
Description	Indicates Hold 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL14**

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL14	
Datatype	decimal	
Description	Indicates Template 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL15**

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL16**

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL2**

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL3

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL4

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL5

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1



**CNTRL6**

Attribute	Description	
Name	CNTRL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL7**

Attribute	Description	
Name	CNTRL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL8**

Attribute	Description	
Name	CNTRL8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL9**

Attribute	Description	
Name	CNTRL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ATHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	ATHSTAT	
Datatype	string	
Description	Indicates Authorization Status	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## BRNCHCODE

<b>Attribute</b>	<b>Description</b>	
Name	BRNCHCODE	
Datatype	string	
Description	Indicates Branch Code	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

### 2.17.4.SM-ModifySMRole-Res-PK-MSG.xsd

*MODIFYSMROLE\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*  
*MULTIRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*ROLEMASTER-PK*  
*ROLEIDENTIFICATION*  
*ROLEMASTER-IO*  
*ROLEIDENTIFICATION*  
*MASTERROLEDESC*  
*BRANCHROLE*  
*BRANCHROLELEVEL*  
*BRANCHPWDRESETFREQ*  
*AUTHORISERROLE*  
*BRANCHVLTROLE*  
*BRANCH\_RES*  
*ACCCLASSALLOWED*  
*CENTRALISATIONROLE*  
*MAKER*  
*MAKERSTAMP*  
*ROLEDETAIL*  
*CONTROLSTRING*  
*ROLEFUN*  
*CONTROL1*  
*CONTROL2*  
*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*CONTROL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CONTROL15*

*CONTROL16*

*ATHSTAT*

*BRNCHCODE*

*ROLEDETAILB*

*CNTRLSTR*

*ROLEFUN*

*CONT1*

*CONT2*

*CONT3*

*CONT4*

*CONT5*

*CONT6*

*CONTROL7*

*CONT8*

*CONT9*

*CONT10*

*CONT11*

*CONT12*

*CONT13*

*CONT14*

*CONT15*

*CONTROL16*

*ATHATAT*

*BRHCODE*

*ROLEDETAILC*

*CNTRLSTR*

*ROLEFUN*

*CNTRL1*

*CNTRL2*

*CNTRL3*

*CNTRL4*

*CNTRL5*

*CNTRL6*

*CNTRL7*

*CNTRL8*

*CNTRL9*

*CNTRL10*

*CNTRL11*

*CNTRL12*

*CNTRL13*

*CNTRL14*

*CNTRL15*

*CNTRL16*

*ATHSTAT*

*ROLEDETAILD*

*CNTRLSTRING*

*ROLEFUN*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*  
*CONTROL7*  
*CONTROL8*  
*CONTROL9*  
*CONTROL10*  
*CONTROL11*  
*CONTROL12*  
*CONTROL13*  
*CONTROL14*  
*CNTRL15*  
*CNTRL16*  
*ROLEBRANCHES*  
    *BRANCH*  
*ROLEACCCLASS*  
    *ACCCLS*  
*MSGCRIGHTS*  
    *CNL*  
    *CHGNODE*  
    *REL*  
    *CHGMEDIA*  
    *BRNMOV*  
    *HLD*  
    *TSTINP*  
    *CHGADDR*  
    *REINS*  
    *CHGPRIOR*  
    *CNLAUTH*  
    *CHGNODEAUTH*  
    *RELAUTH*  
    *CHGMEDIAAUTH*  
    *BRNMOVAUTH*  
    *HLDAUTH*



*TSTINPAUTH*  
*CHGADDRAUTH*  
*REINSAUTH*  
*CHGPRIORAUTH*  
*GEN*  
*TSTCHK*  
*LNKCONT*  
*CHGBRNIN*  
*CHGMSG*  
*CHGFORCRELFUND*  
*SUPPRESS*  
*DELMSG*  
*PRNT*  
*FTUPL*  
*MOVQ*  
*CHGADDRIN*  
*CHGMSGAUTH*  
*AUTHRGHTS*  
*CHGFORCCOVMATCH*  
*QUEUERIGHTS*  
*QUEUE*  
*RESTRICTIVEPASSWD*  
*PWD*  
*ROLEBRANCHLIMITS*  
*LMTCCY*  
*EXRATE*  
*BRHLOWERLMT*  
*BRHUPPRLMT*  
*BRHUSERLMT*  
*Roledetaile*  
*ROLEFUN*  
*EDITABLE*

*CNTRLSTR*

*CONTROL\_1*

*CONTROL\_10*

*CONTROL\_11*

*CONTROL\_12*

*CONTROL\_13*

*CONTROL\_14*

*CONTROL\_15*

*CONTROL\_16*

*CONTROL\_2*

*CONTROL\_3*

*CONTROL\_4*

*CONTROL\_6*

*CONTROL\_7*

*CONTROL\_8*

*CONTROL\_9*

*Roledetailf*

*ROLEFUN*

*CNTRLSTR*

*CNTRL1*

*CNTRL10*

*CNTRL11*

*CNTRL12*

*CNTRL13*

*CNTRL14*

*CNTRL15*

*CNTRL16*

*CNTRL2*

*CNTRL3*

*CNTRL4*

*CNTRL5*

*CNTRL6*

*CNTRL7*

*CNTRL8*

*CNTRL9*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## MODIFYSMROLE\_IOPK\_RES

Attribute	Description
Name	MODIFYSMROLE_IOPK_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	string

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

## MSGID

Attribute	Description					
Name	MSGID					
Datatype	string					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

## CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	string					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

## USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	<b>Description</b>	

## ADDL

<b>Attribute</b>		<b>Description</b>
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	

## PARAM

<b>Attribute</b>		<b>Description</b>
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## NAME

<b>Attribute</b>		<b>Description</b>
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>		<b>Description</b>
Name	VALUE	
Datatype	String	
Description		

## FCUBS\_BODY

<b>Attribute</b>		<b>Description</b>
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about PK Response	

## ROLEMASTER-PK



Attribute	Description
Name	ROLEMASTER-PK
Datatype	
Description	

## ROLEIDENTIFICATION

Attribute	Description	
Name	ROLEIDENTIFICATION	
Datatype	string	
Description	Indicates Role Id	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## ROLEMASTER-IO

Attribute	Description
Name	ROLEMASTER-IO
Datatype	
Description	

## ROLEIDENTIFICATION

Attribute	Description	
Name	ROLEIDENTIFICATION	
Datatype	string	
Description	Indicates Role Id	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## MASTERROLEDESC

Attribute	Description	
Name	MASTERROLEDESC	
Datatype	string	
Description	Indicates Role Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## BRANCHROLE

Attribute	Description	
Name	BRANCHROLE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRANCHROLELEVEL

<b>Attribute</b>	<b>Description</b>	
Name	BRANCHROLELEVEL	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## BRANCHPWDRESETFREQ

<b>Attribute</b>	<b>Description</b>	
Name	BRANCHPWDRESETFREQ	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## AUTHORISERROLE

<b>Attribute</b>	<b>Description</b>	
Name	AUTHORISERROLE	
Datatype	string	
Description	Indicates Authorizer Role Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRANCHVLTROLE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCHVLTROLE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRANCH\_RES

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_RES	
Datatype	string	
Description	Indicates Branch Restriction A - Allowed D - Disallowed	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## ACCCLASSALLOWED

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLASSALLOWED	
Datatype	string	
Description	Indicates Account Class Restriction A - Allowed D - Disallowed	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## CENTRALISATIONROLE

<b>Attribute</b>	<b>Description</b>	
Name	CENTRALISATIONROLE	
Datatype	string	
Description	Indicates Centralisation Role Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	12
	<b>Description</b>	

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	35
	<b>Description</b>	

## ROLEDETAIL

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAIL	
Datatype		
Description	Maintenance	
Attribute	<b>Attribute</b>	
	maxOccurs	unbounded
	<b>Description</b>	

## CONTROLSTRING

<b>Attribute</b>	<b>Description</b>	
Name	CONTROLSTRING	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	16
	<b>Description</b>	

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Restrictions	<b>Restrictions</b>	
	maxLength	8
	<b>Description</b>	

## CONTROL1

Attribute	Description								
Name	CONTROL1								
Datatype	decimal								
Description	Indicates New 1 - on 0 - Off								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
	Attribute	Description							
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0	maxInclusive	1
	Restrictions	Description							
	totalDigits	22							
	minInclusive	0							
maxInclusive	1								

## CONTROL2

Attribute	Description								
Name	CONTROL2								
Datatype	decimal								
Description	Indicates Copy 1 - on 0 - Off								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
	Attribute	Description							
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0	maxInclusive	1
	Restrictions	Description							
	totalDigits	22							
	minInclusive	0							
maxInclusive	1								

## CONTROL3

Attribute	Description								
Name	CONTROL3								
Datatype	decimal								
Description	Indicates Delete 1 - on 0 - Off								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
	Attribute	Description							
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0	maxInclusive	1
	Restrictions	Description							
	totalDigits	22							
	minInclusive	0							
maxInclusive	1								

## CONTROL4

Attribute	Description
Name	CONTROL4
Datatype	decimal
Description	Indicates Close 1 - on 0 - Off

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL6

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL8

Attribute	Description								
Name	CONTROL8								
Datatype	decimal								
Description	Indicates Auth 1 - on 0 - Off								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0	maxInclusive	1
Restrictions	Description								
totalDigits	22								
minInclusive	0								
maxInclusive	1								

## CONTROL9

Attribute	Description								
Name	CONTROL9								
Datatype	decimal								
Description	Indicates Reverse 1 - on 0 - Off								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0	maxInclusive	1
Restrictions	Description								
totalDigits	22								
minInclusive	0								
maxInclusive	1								

## CONTROL10

Attribute	Description								
Name	CONTROL10								
Datatype	decimal								
Description	Indicates Rollover 1 - on 0 - Off								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0	maxInclusive	1
Restrictions	Description								
totalDigits	22								
minInclusive	0								
maxInclusive	1								

## CONTROL11

Attribute	Description
Name	CONTROL11
Datatype	decimal
Description	Indicates Confirm 1 - on 0 - Off

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL12

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL12	
Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL13

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL13	
Datatype	decimal	
Description	Indicates Hold 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL14

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL14	
Datatype	decimal	
Description	Indicates Template 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1



## CONTROL15

Attribute	Description								
Name	CONTROL15								
Datatype	decimal								
Description	Indicates View 1 - on 0 - Off								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0	maxInclusive	1
Restrictions	Description								
totalDigits	22								
minInclusive	0								
maxInclusive	1								

## CONTROL16

Attribute	Description								
Name	CONTROL16								
Datatype	decimal								
Description	Indicates Generate 1 - on 0 - Off								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0	maxInclusive	1
Restrictions	Description								
totalDigits	22								
minInclusive	0								
maxInclusive	1								

## ATHSTAT

Attribute	Description				
Name	ATHSTAT				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

## BRNCHCODE

Attribute	Description				
Name	BRNCHCODE				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## ROLEDETAILB

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILB	
Datatype		
Description	Roles	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## CNTRLSTR

<b>Attribute</b>	<b>Description</b>	
Name	CNTRLSTR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## CONT1

<b>Attribute</b>	<b>Description</b>	
Name	CONT1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT2

Attribute	Description	
Name	CONT2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT3

Attribute	Description	
Name	CONT3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT4

Attribute	Description	
Name	CONT4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT5

Attribute	Description	
Name	CONT5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT6

<b>Attribute</b>	<b>Description</b>	
Name	CONT6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT8

<b>Attribute</b>	<b>Description</b>	
Name	CONT8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT9

Attribute		Description	
Name		CONT9	
Datatype		decimal	
Description		Indicates Reverse 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

### CONT10

Attribute		Description	
Name		CONT10	
Datatype		decimal	
Description		Indicates Rollover 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

### CONT11

Attribute		Description	
Name		CONT11	
Datatype		decimal	
Description		Indicates Confirm 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

### CONT12

Attribute		Description	
Name		CONT12	
Datatype		decimal	
Description		Indicates Liquidate 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT13

<b>Attribute</b>	<b>Description</b>	
Name	CONT13	
Datatype	decimal	
Description	Indicates Hold 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT14

<b>Attribute</b>	<b>Description</b>	
Name	CONT14	
Datatype	decimal	
Description	Indicates Template 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT15

<b>Attribute</b>	<b>Description</b>	
Name	CONT15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL16

Attribute	Description	
Name	CONTROL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ATHATAT

Attribute	Description	
Name	ATHATAT	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

## BRHCODE

Attribute	Description	
Name	BRHCODE	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

## ROLEDETAILC

Attribute	Description	
Name	ROLEDETAILC	
Datatype		
Description	Batch	
Attribute	Attribute	Description
	maxOccurs	unbounded

## CNTRLSTR

Attribute	Description
Name	CNTRLSTR

Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## CNTRL1

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL2

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL3

<b>Attribute</b>	<b>Description</b>
Name	CNTRL3



Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

#### CNTRL4

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

#### CNTRL5

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

#### CNTRL6

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL7

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL8

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL9

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL10

Attribute		Description	
Name		CNTRL10	
Datatype		decimal	
Description		Indicates Rollover 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

### CNTRL11

Attribute		Description	
Name		CNTRL11	
Datatype		decimal	
Description		Indicates Confirm 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

### CNTRL12

Attribute		Description	
Name		CNTRL12	
Datatype		decimal	
Description		Indicates Liquidate 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

### CNTRL13

Attribute		Description	
Name		CNTRL13	
Datatype		decimal	
Description		Indicates Hold 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

#### CNTRL14

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL14	
Datatype	decimal	
Description	Indicates Template 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

#### CNTRL15

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

#### CNTRL16

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

#### ATHSTAT

Attribute	Description	
Name	ATHSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## ROLEDETAILD

Attribute	Description	
Name	ROLEDETAILD	
Datatype		
Description	Roles	
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## CNTRLSTRING

Attribute	Description	
Name	CNTRLSTRING	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

## ROLEFUN

Attribute	Description	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## CONTROL1

Attribute	Description	
Name	CONTROL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL4

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL5

Attribute		Description	
Name		CONTROL5	
Datatype		decimal	
Description		Indicates Unlock 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL6

Attribute		Description	
Name		CONTROL6	
Datatype		decimal	
Description		Indicates Reopen 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL7

Attribute		Description	
Name		CONTROL7	
Datatype		decimal	
Description		Indicates Print 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL8

Attribute		Description	
Name		CONTROL8	
Datatype		decimal	
Description		Indicates Auth 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL10

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL11

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL12



Attribute	Description	
Name	CONTROL12	
Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL13

Attribute	Description	
Name	CONTROL13	
Datatype	decimal	
Description	Indicates Hold 1 - on 0 - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL14

Attribute	Description	
Name	CONTROL14	
Datatype	decimal	
Description	Indicates Template 1 - on 0 - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL15

Attribute	Description	
Name	CNTRL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL16

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEBRANCHES

<b>Attribute</b>	<b>Description</b>	
Name	ROLEBRANCHES	
Datatype		
Description	Branches	
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	Indicates Branch	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## ROLEACCCCLASS

<b>Attribute</b>	<b>Description</b>	
Name	ROLEACCCCLASS	
Datatype		
Description	Acc Class Restriction	
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ACCCLS

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	ACCCLS	
Datatype	string	
Description	Indicates Account Class	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

## MSGCRIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	MSGCRIGHTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## CNL

<b>Attribute</b>	<b>Description</b>	
Name	CNL	
Datatype	string	
Description	Indicates Cancel Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODE

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODE	
Datatype	string	
Description	Indicates Change Node Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REL

<b>Attribute</b>	<b>Description</b>	
Name	REL	
Datatype	string	
Description	Indicates Release Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIA

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIA	
Datatype	string	
Description	Indicates Change Media Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOV

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOV	
Datatype	string	
Description	Indicates Branch Move Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLD

<b>Attribute</b>	<b>Description</b>	
Name	HLD	
Datatype	string	
Description	Indicates Hold Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINP

<b>Attribute</b>	<b>Description</b>	
Name	TSTINP	
Datatype	string	
Description	Indicates Test Input Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDR

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDR	
Datatype	string	
Description	Indicates Change Address Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINS

<b>Attribute</b>	<b>Description</b>	
Name	REINS	
Datatype	string	
Description	Indicates Reinstate Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIOR

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIOR	
Datatype	string	
Description	Indicates Change Priority Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNLAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CNLAUTH	
Datatype	string	
Description	Indicates Auth Cancel Y - on N - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHGNODEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODEAUTH	
Datatype	string	
Description	Indicates Auth Change Node Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### RELAUTH

<b>Attribute</b>	<b>Description</b>	
Name	RELAUTH	
Datatype	string	
Description	Indicates Release Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHGMEDIAAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIAAUTH	
Datatype	string	
Description	Indicates Change Media Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### BRNMOVAUTH

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOVAUTH	
Datatype	string	

Description	Indicates Auth Branch Move Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLDAUTH

<b>Attribute</b>	<b>Description</b>	
Name	HLDAUTH	
Datatype	string	
Description	Indicates Hold Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINPAUTH

<b>Attribute</b>	<b>Description</b>	
Name	TSTINPAUTH	
Datatype	string	
Description	Indicates Auth Test Input Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRAUTH	
Datatype	string	
Description	Indicates Change Address Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINSAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	REINSAUTH	
Datatype	string	
Description	Indicates Auth Reinstate Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIORAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIORAUTH	
Datatype	string	
Description	Indicates Change Priority Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## GEN

<b>Attribute</b>	<b>Description</b>	
Name	GEN	
Datatype	string	
Description	Indicates Install Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTCHK

<b>Attribute</b>	<b>Description</b>	
Name	TSTCHK	
Datatype	string	
Description	Indicates Test Check Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## LNKCONT

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	LNKCONT	
Datatype	string	
Description	Indicates Link Contract Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHGBRNIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGBRNIN	
Datatype	string	
Description	Indicates Change Branch In Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHGMSG

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSG	
Datatype	string	
Description	Indicates Change Message Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHGFORCREFUND

<b>Attribute</b>	<b>Description</b>	
Name	CHGFORCREFUND	
Datatype	string	
Description	Indicates Change Force Release Fund Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### SUPPRESS

Attribute		Description	
Name	SUPPRESS		
Datatype	string		
Description	Indicates Suppress Y - on N - Off		
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	Y,N	

## DELMSG

Attribute		Description	
Name	DELMSG		
Datatype	string		
Description	Indicates Delete Y - on N - Off		
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	Y,N	

## PRNT

Attribute		Description	
Name	PRNT		
Datatype	string		
Description	Indicates Print Y - on N - Off		
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	Y,N	

## FTUPL

Attribute		Description	
Name	FTUPL		
Datatype	string		
Description	Indicates FT Upload Y - on N - Off		
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	Y,N	

## MOVQ

Attribute	Description	
Name	MOVQ	
Datatype	string	
Description	Indicates Move To Queue Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRIN

Attribute	Description	
Name	CHGADDRIN	
Datatype	string	
Description	Indicates Change Address In Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSGAUTH

Attribute	Description	
Name	CHGMSGAUTH	
Datatype	string	
Description	Indicates Auth Change Message Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## AUTHRGHTS

Attribute	Description	
Name	AUTHRGHTS	
Datatype	string	
Description	Indicates Auth Rights Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGFORCCOVMATCH

Attribute	Description	
Name	CHGFORCCOVMATCH	
Datatype	string	
Description	Indicates Change Force Cover Match Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## QUEUERIGHTS

Attribute	Description	
Name	QUEUERIGHTS	
Datatype		
Description	Queues	
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## QUEUE

Attribute	Description	
Name	QUEUE	
Datatype	string	
Description	Indicates Queue	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## RESTRICTIVEPASSWD

Attribute	Description	
Name	RESTRICTIVEPASSWD	
Datatype		
Description	Restricted Password	
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## PWD

Attribute	Description	
Name	PWD	
Datatype	string	
Description	Indicates Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## ROLEBRANCHLIMITS

Attribute		Description	
Name	ROLEBRANCHLIMITS		
Datatype			
Description	User Limits		
Attribute	<b>Attribute</b>		<b>Description</b>
	maxOccurs	unbounded	

### LMTCCY

Attribute		Description	
Name	LMTCCY		
Datatype	string		
Description	Indicates Limit Currency		
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	3	

### EXRATE

Attribute		Description	
Name	EXRATE		
Datatype	decimal		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	

### BRHLOWERLMT

Attribute		Description	
Name	BRHLOWERLMT		
Datatype	decimal		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	

### BRHUPPRLMT

Attribute		Description	
Name	BRHUPPRLMT		
Datatype	decimal		
Description			

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## BRHUSERLMT

<b>Attribute</b>	<b>Description</b>	
Name	BRHUSERLMT	
Datatype	decimal	
Description	Indicates User Limit	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## Roledetaile

<b>Attribute</b>	<b>Description</b>	
Name	Roledetaile	
Datatype		
Description	Process Stage Rights	
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## EDITABLE

<b>Attribute</b>	<b>Description</b>	
Name	EDITABLE	
Datatype	decimal	
Description	Indicates Editable 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CNTRLSTR

<b>Attribute</b>	<b>Description</b>	
Name	CNTRLSTR	
Datatype	string	
Description	Indicates Control String	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

## CONTROL\_1

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_1	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL\_10

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_10	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL\_11

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_11	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL\_12

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_12	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL\_13

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_13	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL\_14

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_14	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL\_15

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_15	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL\_16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_16	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL\_2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_2	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL\_3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_3	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL\_4

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_4	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL\_6

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_6	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL\_7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_7	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL\_8

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_8	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL\_9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL_9	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### Roledetailf

<b>Attribute</b>	<b>Description</b>	
Name	Roledetailf	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

### ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

### CNTRLSTR

<b>Attribute</b>	<b>Description</b>	
Name	CNTRLSTR	
Datatype	string	
Description	Indicates Control String	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

### CNTRL1

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL10**

Attribute	Description	
Name	CNTRL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL11**

Attribute	Description	
Name	CNTRL11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL12**

Attribute	Description	
Name	CNTRL12	
Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL13**

Attribute	Description	
Name	CNTRL13	
Datatype	decimal	
Description	Indicates Hold 1 - on 0 - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

#### CNTRL14

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL14	
Datatype	decimal	
Description	Indicates Template 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

#### CNTRL15

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

#### CNTRL16

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL2**

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL3**

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL4**

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL5**

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL6

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL7

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL8

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL9

Attribute	Description								
Name	CNTRL9								
Datatype	decimal								
Description	Indicates Reverse 1 - on 0 - Off								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	minInclusive	0	maxInclusive	1
Restrictions	Description								
totalDigits	22								
minInclusive	0								
maxInclusive	1								

## UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## FLDNAM

Attribute	Description						
Name	FLDNAM						
Datatype	string						
Description	Indicates Field Name						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	105	minLength	1
Restrictions	Description						
maxLength	105						
minLength	1						

## FLDVAL

Attribute	Description						
Name	FLDVAL						
Datatype	string						
Description	Indicates Field Value						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></tbody></table>	Restrictions	Description	maxLength	150	minLength	0
Restrictions	Description						
maxLength	150						
minLength	0						

## FCUBS\_ERROR\_RESP

Attribute	Description
-----------	-------------



Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	maxOccurs	unbounded

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	maxOccurs	unbounded

## WCODE

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

## 2.18.ModifyUserMaint

### 2.18.1.SM-ModifyUserMaint-Req-Full-MSG.xsd

*MODIFYUSERMAINT\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*USR-Full*

*STRTDATE*  
*USRNAME*  
*USRPWD*  
*ENDDT*  
*USRLANG*  
*HOMEBRN*  
*CUSTNO*  
*LDAPUSR*  
*TIMELEVEL*  
*AUTOAUTH*  
*USRSTAT*  
*USRID*  
*EXTUSRREF*  
*USRCATEG*  
*TILLALLOW*  
*ACCCLSALLOW*  
*GLALLOW*  
*USRTXNLMT*  
*LMTSCCY*  
*MAXTXNAMT*  
*MAXAUTHAMT*  
*BRNSALLOW*  
*PRDSALLOW*  
*PRDSACCESALLOW*  
*TAX\_IDENTIFIER*  
*AMOUNT\_FORMAT*  
*DATE\_FORMAT*  
*STAFFACCRESTR*  
*DEPT\_CODE*  
*DEPT\_DESC*  
*USRML*  
*ELCMUSER*

*GROUP\_CODE*  
*MULTIBRN\_ACCESS*  
*OTH\_RM\_CUST\_ACC\_ALLOW*  
*SUPERVISOR\_ID*  
*SUPERVISOR\_NAME*  
*DASHBOARD\_REQD*  
*ALERTS\_ON\_HOME*  
*REFERENCE\_NO*  
*NO\_CUMULATIVE\_LOGINS*  
*NO\_SUCESSIVE\_LOGINS*  
*SCREENSAVERTIMEOUTINSECONDS*  
*NUMBER\_FORMAT\_MASK*  
*FRONTEND\_DEBUG\_ENABLED*  
*F10\_REQD*  
*F11\_REQD*  
*F12\_REQD*  
*MFI\_USER*  
*MFAENABLED*  
*MFAID*  
*ACCESS\_CONTROL*  
*EXTN\_ALERTS*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*RESTR\_PWD*  
*PWD*  
*MSGSRIGHTS*  
*GEN*

*HLD*  
*CNL*  
*TSTINP*  
*CHGNODE*  
*CHGADDR*  
*REL*  
*REINS*  
*CHGMEDIA*  
*CHGPRIOR*  
*BRNMOV*  
*PRNT*  
*TSTCHK*  
*HLDAUTH*  
*CNLAUTH*  
*TSTINPAUTH*  
*CHGNODEAUTH*  
*CHGADDRAUTH*  
*RELAUTH*  
*REINSAUTH*  
*CHGMEDIAAUTH*  
*BRNMOVAUTH*  
*CHGPRIORAUTH*  
*FTUPL*  
*LNKCONT*  
*MOVQ*  
*CHGBRNIN*  
*CHGADDRIN*  
*AUTHRGHTS*  
*CHGMSG*  
*CHGMSGAUTH*  
*CHGFORCCOVMATCH*  
*CHANGE\_FORCE\_RELEASE\_FUND*

*SUPPRESS*

*DELMSG*

*QUEUERIGHTS*

*QUEUE*

*USERTILLS*

*TILLID*

*TILLBRNCD*

*DESCRIPTION*

*USERACCCLASS*

*ACCCLS*

*USERGLREST*

*NODEGL*

*USERGLEXCEPT*

*EXCEPLEAFGL*

*USERLIMITSROLE*

*LMTBRN*

*LMTSROLE*

*QLMTCCY*

*QINPLMT*

*QAUTHLMT*

*USERBRANCHES*

*BRNSBRN*

*BRNNAME*

*USERPRODUCTS*

*PRDPRDCD*

*PRDDESC*

*USERACCESSPRODUCTS*

*PRDACCESSPRDCD*

*PRDDESC*

*USERFUNCDISALLOW*

*FUNCDISALLOWFUNCID*

*USERROLE*

*ROLEBRNCD*

*USRROLEID*

*MASTERROLEDESC*

*USERSFUNCTIONS*

*USERFUNCBRNCD*

*USERFUNCFUNCID*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*USERFUNCCTRL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CONTROL15*

*CONTROL16*

*Grp-Restriction*

*GROUP\_CODE*

*GROUP\_DESC*

*Centralisation*

*USRROLEID*

*ROLDESC*

*Dshmst*

*USRID*

*USRNAME*

*Dshdet*

*FUNCTIONID*

*DESCRIPTION*

*SEQUENCE\_NO*

*DBWHERECLAUSE*

*SHOW\_IN\_DASHBOARD*

*Where-Master*

*COLUMN\_NAME*

*WHERE\_CL*

*CONDITION*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

## MODIFYUSERMAINT\_FSFS\_REQ

Attribute	Description
Name	MODIFYUSERMAINT_FSFS_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	string
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.



Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	string
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	

Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Request of ModifyUserMaint	

## USR-Full

<b>Attribute</b>	<b>Description</b>	
Name	USR-Full	
Datatype		
Description		

## STRTDATE

<b>Attribute</b>	<b>Description</b>	
------------------	--------------------	--

Name	STRTDATE
Datatype	String
Description	

## USRNAME

Attribute	Description	
Name	USRNAME	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## USRPWD

Attribute	Description	
Name	USRPWD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	32

## ENDDT

Attribute	Description	
Name	ENDDT	
Datatype	String	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## USRLANG

Attribute	Description	
Name	USRLANG	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## HOMEBRN

Attribute	Description	
Name	HOMEBRN	
Datatype	string	
Description		

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## CUSTNO

<b>Attribute</b>	<b>Description</b>	
Name	CUSTNO	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## LDAPUSR

<b>Attribute</b>	<b>Description</b>	
Name	LDAPUSR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	500

## TIMELEVEL

<b>Attribute</b>	<b>Description</b>	
Name	TIMELEVEL	
Datatype	decimal	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	9

## AUTOAUTH

<b>Attribute</b>	<b>Description</b>	
Name	AUTOAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## USRSTAT

<b>Attribute</b>	<b>Description</b>	
Name	USRSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	E,H,D,L

## USRID

<b>Attribute</b>	<b>Description</b>	
Name	USRID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## EXTUSRREF

<b>Attribute</b>	<b>Description</b>	
Name	EXTUSRREF	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## USRCATEG

<b>Attribute</b>	<b>Description</b>	
Name	USRCATEG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	S,B



## TILLALLOW

Attribute	Description	
Name	TILLALLOW	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## ACCCLSALLOW

Attribute	Description	
Name	ACCCLSALLOW	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## GLALLOW

Attribute	Description	
Name	GLALLOW	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## USRTXNLMT

Attribute	Description	
Name	USRTXNLMT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,R,N

## LMTSCCY

Attribute		Description	
Name	LMTSCCY		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	3	

### MAXTXNAMT

Attribute		Description	
Name	MAXTXNAMT		
Datatype	decimal		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	

### MAXAUTHAMT

Attribute		Description	
Name	MAXAUTHAMT		
Datatype	decimal		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	

### BRNSALLOW

Attribute		Description	
Name	BRNSALLOW		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	A,D	

### PRDSALLOW

Attribute	Description	
Name	PRDSALLOW	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	A,D

## PRDSACCESALLOW

Attribute	Description	
Name	PRDSACCESALLOW	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	A,D

## TAX\_IDENTIFIER

Attribute	Description	
Name	TAX_IDENTIFIER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	11

## AMOUNT\_FORMAT

Attribute	Description	
Name	AMOUNT_FORMAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	.....

## DATE\_FORMAT

Attribute	Description	
Name	DATE_FORMAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	M/d/yyyy

## STAFFACCRESTR

Attribute	Description	
Name	STAFFACCRESTR	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DEPT\_CODE

Attribute	Description	
Name	DEPT_CODE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## DEPT\_DESC

Attribute	Description	
Name	DEPT_DESC	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## USRML

Attribute	Description	
Name	USRML	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	50

## ELCMUSER

Attribute	Description	
Name	ELCMUSER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

## GROUP\_CODE

Attribute	Description	
Name	GROUP_CODE	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	A,D

## MULTIBRN\_ACCESS

Attribute	Description	
Name	MULTIBRN_ACCESS	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## OTH\_RM\_CUST\_ACC\_ALLOW

Attribute	Description	
Name	OTH_RM_CUST_ACC_ALLOW	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## SUPERVISOR\_ID

Attribute	Description	
Name	SUPERVISOR_ID	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	80

## SUPERVISOR\_NAME

Attribute	Description	
Name	SUPERVISOR_NAME	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

## DASHBOARD\_REQD

Attribute	Description	
Name	DASHBOARD_REQD	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## ALERTS\_ON\_HOME

Attribute	Description	
Name	ALERTS_ON_HOME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REFERENCE\_NO

Attribute	Description	
Name	REFERENCE_NO	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## NO\_CUMULATIVE\_LOGINS

Attribute	Description	
Name	NO_CUMULATIVE_LOGINS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## NO\_SUCCESSIVE\_LOGINS

Attribute	Description	
Name	NO_SUCCESSIVE_LOGINS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## SCREENSAVERTIMEOUTINSECONDS

Attribute	Description	
Name	SCREENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### NUMBER\_FORMAT\_MASK

Attribute	Description	
Name	NUMBER_FORMAT_MASK	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	M,L

### FRONTEND\_DEBUG\_ENABLED

Attribute	Description	
Name	FRONTEND_DEBUG_ENABLED	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F10\_REQD

Attribute	Description	
Name	F10_REQD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F11\_REQD



Attribute	Description	
Name	F11_REQD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## F12\_REQD

Attribute	Description	
Name	F12_REQD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MFI\_USER

Attribute	Description	
Name	MFI_USER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MFAENABLED

Attribute	Description	
Name	MFAENABLED	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	N,Y,L

## MFAID

Attribute	Description	
Name	MFAID	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	30

## ACCESS\_CONTROL

Attribute	Description	
Name	ACCESS_CONTROL	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	U,G,B

## EXTN\_ALERTS

Attribute	Description	
Name	EXTN_ALERTS	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

## MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

## CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	1
	<b>Description</b>	

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	1
	<b>Description</b>	

## RESTR\_PWD

Attribute	Description	
Name	RESTR_PWD	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## PWD

Attribute	Description	
Name	PWD	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	12
	<b>Description</b>	

## MSGSRIGHTS

Attribute	Description	
Name	MSGSRIGHTS	
Datatype		
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## GEN

<b>Attribute</b>	<b>Description</b>	
Name	GEN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLD

<b>Attribute</b>	<b>Description</b>	
Name	HLD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNL

<b>Attribute</b>	<b>Description</b>	
Name	CNL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINP

<b>Attribute</b>	<b>Description</b>	
Name	TSTINP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODE

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDR

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REL

<b>Attribute</b>	<b>Description</b>	
Name	REL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINS

<b>Attribute</b>	<b>Description</b>	
Name	REINS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIA

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIA	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIOR

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIOR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOV

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOV	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PRNT

<b>Attribute</b>	<b>Description</b>	
Name	PRNT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTCHK

<b>Attribute</b>	<b>Description</b>	
Name	TSTCHK	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLDAUTH

<b>Attribute</b>	<b>Description</b>	
Name	HLDAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNLAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CNLAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINPAUTH

<b>Attribute</b>	<b>Description</b>	
Name	TSTINPAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODEAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## RELAUTH

<b>Attribute</b>	<b>Description</b>	
Name	RELAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINSAUTH

<b>Attribute</b>	<b>Description</b>	
Name	REINSAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIAAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIAAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOVAUTH

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOVAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIORAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIORAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## FTUPL

<b>Attribute</b>	<b>Description</b>	
Name	FTUPL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## LNKCONT

<b>Attribute</b>	<b>Description</b>	
Name	LNKCONT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MOVQ

<b>Attribute</b>	<b>Description</b>	
Name	MOVQ	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGBRNIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGBRNIN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRIN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## AUTHRGHTS

<b>Attribute</b>	<b>Description</b>	
Name	AUTHRGHTS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSG

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSGAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSGAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGFORCCOVMATCH

<b>Attribute</b>	<b>Description</b>	
Name	CHGFORCCOVMATCH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHANGE\_FORCE\_RELEASE\_FUND

<b>Attribute</b>	<b>Description</b>	
Name	CHANGE_FORCE_RELEASE_FUND	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### SUPPRESS

<b>Attribute</b>	<b>Description</b>	
Name	SUPPRESS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### DELMSG

<b>Attribute</b>	<b>Description</b>	
Name	DELMSG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### QUEUERIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	QUEUERIGHTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## QUEUE

Attribute	Description				
Name	QUEUE				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

## USERTILLS

Attribute	Description						
Name	USERTILLS						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## TILLID

Attribute	Description				
Name	TILLID				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## TILLBRNCD

Attribute	Description				
Name	TILLBRNCD				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## DESCRIPTION

Attribute	Description				
Name	DESCRIPTION				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

## USERACCCLASS

Attribute	Description	
Name	USERACCCLASS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## ACCCLS

Attribute	Description	
Name	ACCCLS	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	6

## USERGLREST

Attribute	Description	
Name	USERGLREST	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## NODEGL

Attribute	Description	
Name	NODEGL	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

## USERGLEXCEPT

Attribute	Description	
Name	USERGLEXCEPT	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## EXCEPLEAFGL

Attribute	Description
-----------	-------------

Name	EXCEPLEAFGL	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## USERLIMITSROLE

<b>Attribute</b>	<b>Description</b>	
Name	USERLIMITSROLE	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## LMTBRN

<b>Attribute</b>	<b>Description</b>	
Name	LMTBRN	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## LMTSROLE

<b>Attribute</b>	<b>Description</b>	
Name	LMTSROLE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## QLMTCCY

<b>Attribute</b>	<b>Description</b>	
Name	QLMTCCY	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## QINPLMT

<b>Attribute</b>	<b>Description</b>	
Name	QINPLMT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## QAUTHLMT

<b>Attribute</b>	<b>Description</b>	
Name	QAUTHLMT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## USERBRANCHES

<b>Attribute</b>	<b>Description</b>	
Name	USERBRANCHES	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## BRNSBRN

<b>Attribute</b>	<b>Description</b>	
Name	BRNSBRN	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## BRNNAME

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	BRNNAME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	105
	<b>Description</b>	

## USERPRODUCTS

<b>Attribute</b>	<b>Description</b>	
Name	USERPRODUCTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## PRDPRDCD

<b>Attribute</b>	<b>Description</b>	
Name	PRDPRDCD	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	4
	<b>Description</b>	

## PRDESC

<b>Attribute</b>	<b>Description</b>	
Name	PRDESC	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	105
	<b>Description</b>	

## USERACCESSPRODUCTS

<b>Attribute</b>	<b>Description</b>	
Name	USERACCESSPRODUCTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## PRDACCESSPRDCD

Attribute	Description	
Name	PRDACCESSPRDCD	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	4

## PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

## USERFUNCDISALLOW

Attribute	Description	
Name	USERFUNCDISALLOW	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded
Restrictions		
	Restrictions	Description
	maxLength	8

## FUNCDISALLOWFUNCID

Attribute	Description	
Name	FUNCDISALLOWFUNCID	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	8

## USERROLE

Attribute	Description	
Name	USERROLE	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded
Restrictions		
	Restrictions	Description
	maxLength	8

## ROLEBRNCD

Attribute	Description				
Name	ROLEBRNCD				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## USRROLEID

Attribute	Description				
Name	USRROLEID				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## MASTERROLEDESC

Attribute	Description				
Name	MASTERROLEDESC				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>45</td></tr></tbody></table>	Restrictions	Description	maxLength	45
Restrictions	Description				
maxLength	45				

## USERSFUNCTIONS

Attribute	Description						
Name	USERSFUNCTIONS						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## USERFUNCBRNCD

Attribute	Description				
Name	USERFUNCBRNCD				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## USERFUNCFUNCID

Attribute		Description	
Name	USERFUNCFUNCID		
Datatype	string		
Description			
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	8	

### CONTROL1

Attribute		Description	
Name	CONTROL1		
Datatype	decimal		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	

### CONTROL2

Attribute		Description	
Name	CONTROL2		
Datatype	decimal		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	

### CONTROL3

Attribute		Description	
Name	CONTROL3		
Datatype	decimal		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	

### CONTROL4

Attribute		Description	
Name	CONTROL4		
Datatype	decimal		

Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL6

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL6	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL8

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL8	
Datatype	decimal	

Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## USERFUNCCTRL10

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCCTRL10	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL11

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL11	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL12

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL12	
Datatype	decimal	

Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL13

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL13	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL14

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL14	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL15

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL15	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	



Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### Grp-Restriction

<b>Attribute</b>	<b>Description</b>	
Name	Grp-Restriction	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### GROUP\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_CODE	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

### GROUP\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_DESC	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

### Centralisation

<b>Attribute</b>	<b>Description</b>	
Name	Centralisation	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

Attribute		Description	
Name	USRROLEID		
Datatype	string		
Description			
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	15	

## ROLDESC

Attribute		Description	
Name	ROLDESC		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	20	

## Dshmst

Attribute		Description	
Name	Dshmst		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	

## USRID

Attribute		Description	
Name	USRID		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	15	

## USRNAME

Attribute		Description	
Name	USRNAME		
Datatype	string		
Description			

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## Dshdet

<b>Attribute</b>	<b>Description</b>	
Name	Dshdet	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxOccurs	unbounded

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1000

## SEQUENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	SEQUENCE_NO	
Datatype	decimal	
Description		

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## DBWHERECLAUSE

<b>Attribute</b>	<b>Description</b>	
Name	DBWHERECLAUSE	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

## SHOW\_IN\_DASHBOARD

<b>Attribute</b>	<b>Description</b>	
Name	SHOW_IN_DASHBOARD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## Where-Master

<b>Attribute</b>	<b>Description</b>	
Name	Where-Master	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## COLUMN\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	COLUMN_NAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	2000

## WHERE\_CL

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	WHERE_CL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	500

## CONDITION

<b>Attribute</b>	<b>Description</b>	
Name	CONDITION	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

2.18.2.SM-ModifyUserMaint-Req-IO-MSG.xsd

*MODIFYUSERMAINT\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*USR-IO*

*STRDATE*

*USRNAME*  
*USRPWD*  
*ENDDT*  
*USRLANG*  
*HOMEBRN*  
*CUSTNO*  
*LDAPUSR*  
*TIMELEVEL*  
*AUTOAUTH*  
*USRSTAT*  
*USRID*  
*FORCPWDCHG*  
*USRCATEG*  
*TILLALLOW*  
*ACCCLSALLOW*  
*GLALLOW*  
*USRTXNLMT*  
*LMTSCCY*  
*MAXTXNAMT*  
*MAXAUTHAMT*  
*BRNSALLOW*  
*PRDSALLOW*  
*PRDSACCESALLOW*  
*TAX\_IDENTIFIER*  
*STAFFACCRESTR*  
*DEPT\_CODE*  
*USRML*  
*ELCMUSER*  
*GROUP\_CODE*  
*MULTIBRN\_ACCESS*  
*OTH\_RM\_CUST\_ACC\_ALLOW*  
*SUPERVISOR\_ID*

*SUPERVISOR\_NAME*  
*DASHBOARD\_REQD*  
*ALERTS\_ON\_HOME*  
*FRONTEND\_DEBUG\_ENABLED*  
*F10\_REQD*  
*F11\_REQD*  
*F12\_REQD*  
*MFAENABLED*  
*MFAID*  
*ACCESS\_CONTROL*  
*EXTN\_ALERTS*  
*MAKER*  
*MAKERSTAMP*  
*RESTR\_PWD*  
*PWD*  
*MSGRIGHTS*  
*GEN*  
*HLD*  
*CNL*  
*TSTINP*  
*CHGNODE*  
*CHGADDR*  
*REL*  
*REINS*  
*CHGMEDIA*  
*CHGPRIOR*  
*BRNMOV*  
*PRNT*  
*TSTCHK*  
*HLDAUTH*  
*CNLAUTH*  
*TSTINPAUTH*



*CHGNODEAUTH*  
*CHGADDRAUTH*  
*RELAUTH*  
*REINSAUTH*  
*CHGMEDIAAUTH*  
*BRNMOVAUTH*  
*CHGPRIORAUTH*  
*FTUPL*  
*LNKCONT*  
*MOVQ*  
*CHGBRNIN*  
*CHGADDRIN*  
*AUTHRGHTS*  
*CHGMSG*  
*CHGMSGAUTH*  
*CHGFORCCOVMATCH*  
*CHANGE\_FORCE\_RELEASE\_FUND*  
*SUPPRESS*  
*DELMSG*  
*QUEUERIGHTS*  
*QUEUE*  
*USERTILLS*  
*TILLID*  
*USERACCCLASS*  
*ACCCLS*  
*USERGLREST*  
*NODEGL*  
*USERGLEXCEPT*  
*EXPNODEGL*  
*EXCEPLEAFGL*  
*USERLIMITSROLE*  
*LMTBRN*

*LMTSROLE*  
*USERBRANCHES*  
*BRNSBRN*  
*USERPRODUCTS*  
*PRDPRDCD*  
*USERACCESSPRODUCTS*  
*PRDACCESSPRDCD*  
*USERFUNCDISALLOW*  
*FUNCDISALLOWFUNCID*  
*USERROLE*  
*ROLEBRNCD*  
*USRROLEID*  
*USERSFUNCTIONS*  
*USERFUNCBRNCD*  
*USERFUNCFUNCID*  
*CONTROL1*  
*CONTROL2*  
*CONTROL3*  
*CONTROL4*  
*CONTROL5*  
*CONTROL6*  
*CONTROL7*  
*CONTROL8*  
*CONTROL9*  
*USERFUNCCTRL10*  
*CONTROL11*  
*CONTROL12*  
*CONTROL13*  
*CONTROL14*  
*CONTROL15*  
*CONTROL16*  
*USERFUNCCTRSTR*

*Grp-Restriction*

*GROUP\_CODE*

*Centralisation*

*USRROLEID*

*Dshdet*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

## MODIFYUSERMAINT\_IOPK\_REQ

Attribute	Description
Name	MODIFYUSERMAINT_IOPK_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description					
Name	MSGID					
Datatype	string					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

## CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	string					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

## USERID

Attribute	Description							
Name	USERID							
Datatype	string							
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description							
maxLength	12							
pattern	[A-Z_0-9]*							

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

## ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute			
		Attribute	Description
		minOccurs	0

## PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute			
		Attribute	Description
		minOccurs	0
		maxOccurs	unbounded

## NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

## VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

## FCUBS\_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description		This XSD Gives Information about IO Request of ModifyUserMaint	

## USR-IO

Attribute		Description	
Name		USR-IO	
Datatype			
Description			

## STRTDATE

Attribute		Description	
Name		STRTDATE	
Datatype		String	
Description			



Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## USRNAME

<b>Attribute</b>	<b>Description</b>	
Name	USRNAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## USRPWD

<b>Attribute</b>	<b>Description</b>	
Name	USRPWD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	32

## ENDDT

<b>Attribute</b>	<b>Description</b>	
Name	ENDDT	
Datatype	String	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## USRLANG

<b>Attribute</b>	<b>Description</b>	
Name	USRLANG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## HOMEBRN

Attribute	Description	
Name	HOMEBRN	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## LDAPUSR

Attribute	Description	
Name	LDAPUSR	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	500

## TIMELEVEL

Attribute	Description	
Name	TIMELEVEL	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	9

## AUTOAUTH

Attribute	Description	
Name	AUTOAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## USRSTAT

Attribute	Description	
Name	USRSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	E,H,D,L

## USRID

Attribute	Description	
Name	USRID	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## FORCPWDCHG

Attribute	Description	
Name	FORCPWDCHG	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## USRCATEG

Attribute	Description	
Name	USRCATEG	

Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	S,B

## TILLALLOW

<b>Attribute</b>	<b>Description</b>	
Name	TILLALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## ACCCLSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## GLALLOW

<b>Attribute</b>	<b>Description</b>	
Name	GLALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## USRTXNLMT

<b>Attribute</b>	<b>Description</b>	
Name	USRTXNLMT	

Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,R,N

### LMTSCCY

<b>Attribute</b>	<b>Description</b>	
Name	LMTSCCY	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### MAXTXNAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXTXNAMT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### MAXAUTHAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXAUTHAMT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### BRNSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	BRNSALLOW	

Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## PRDSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## PRDSACCESALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSACCESALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## TAX\_IDENTIFIER

<b>Attribute</b>	<b>Description</b>	
Name	TAX_IDENTIFIER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

## STAFFACCRESTR

<b>Attribute</b>	<b>Description</b>	
Name	STAFFACCRESTR	

Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DEPT\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	DEPT_CODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## USRML

<b>Attribute</b>	<b>Description</b>	
Name	USRML	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## ELCMUSER

<b>Attribute</b>	<b>Description</b>	
Name	ELCMUSER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## GROUP\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_CODE	

Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### MULTIBRN\_ACCESS

<b>Attribute</b>	<b>Description</b>	
Name	MULTIBRN_ACCESS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### OTH\_RM\_CUST\_ACC\_ALLOW

<b>Attribute</b>	<b>Description</b>	
Name	OTH_RM_CUST_ACC_ALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### SUPERVISOR\_ID

<b>Attribute</b>	<b>Description</b>	
Name	SUPERVISOR_ID	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	80

### SUPERVISOR\_NAME

<b>Attribute</b>	<b>Description</b>
Name	SUPERVISOR_NAME



Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

### DASHBOARD\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	DASHBOARD_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### ALERTS\_ON\_HOME

<b>Attribute</b>	<b>Description</b>	
Name	ALERTS_ON_HOME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### FRONTEND\_DEBUG\_ENABLED

<b>Attribute</b>	<b>Description</b>	
Name	FRONTEND_DEBUG_ENABLED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F10\_REQD

<b>Attribute</b>	<b>Description</b>
Name	F10_REQD

Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F11\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F11_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F12\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F12_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### MFAENABLED

<b>Attribute</b>	<b>Description</b>	
Name	MFAENABLED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	N,Y,L

### MFAID

<b>Attribute</b>	<b>Description</b>	
Name	MFAID	

Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

## ACCESS\_CONTROL

<b>Attribute</b>	<b>Description</b>	
Name	ACCESS_CONTROL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,G,B

## EXTN\_ALERTS

<b>Attribute</b>	<b>Description</b>	
Name	EXTN_ALERTS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	

Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## RESTR\_PWD

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_PWD	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## PWD

<b>Attribute</b>	<b>Description</b>	
Name	PWD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MSGSRIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	MSGSRIGHTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## GEN

<b>Attribute</b>	<b>Description</b>	
Name	GEN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLD

Attribute	Description	
Name	HLD	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CNL

Attribute	Description	
Name	CNL	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## TSTINP

Attribute	Description	
Name	TSTINP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGNODE

Attribute	Description	
Name	CHGNODE	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGADDR

Attribute	Description	
Name	CHGADDR	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## REL

Attribute	Description	
Name	REL	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## REINS

Attribute	Description	
Name	REINS	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGMEDIA

Attribute	Description	
Name	CHGMEDIA	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGPRIOR

Attribute	Description	
Name	CHGPRIOR	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## BRNMOV

Attribute	Description	
Name	BRNMOV	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## PRNT

Attribute	Description	
Name	PRNT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## TSTCHK

Attribute	Description	
Name	TSTCHK	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## HLDAUTH

Attribute	Description	
Name	HLDAUTH	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CNLAUTH

Attribute	Description	
Name	CNLAUTH	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## TSTINPAUTH

Attribute	Description	
Name	TSTINPAUTH	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGNODEAUTH

Attribute	Description	
Name	CHGNODEAUTH	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGADDRAUTH



Attribute	Description	
Name	CHGADDRAUTH	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## RELAUTH

Attribute	Description	
Name	RELAUTH	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## REINSAUTH

Attribute	Description	
Name	REINSAUTH	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGMEDIAAUTH

Attribute	Description	
Name	CHGMEDIAAUTH	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## BRNMOVAUTH

Attribute	Description	
Name	BRNMOVAUTH	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGPRIORAUTH

Attribute	Description	
Name	CHGPRIORAUTH	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## FTUPL

Attribute	Description	
Name	FTUPL	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## LNKCONT

Attribute	Description	
Name	LNKCONT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## MOVQ

Attribute	Description	
Name	MOVQ	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGBRNIN

Attribute	Description	
Name	CHGBRNIN	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGADDRIN

Attribute	Description	
Name	CHGADDRIN	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## AUTHRGHTS

Attribute	Description	
Name	AUTHRGHTS	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGMSG

Attribute	Description	
Name	CHGMSG	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

### CHGMSGAUTH

Attribute	Description	
Name	CHGMSGAUTH	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

### CHGFORCCOVMATCH

Attribute	Description	
Name	CHGFORCCOVMATCH	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

### CHANGE\_FORCE\_RELEASE\_FUND

Attribute	Description	
Name	CHANGE_FORCE_RELEASE_FUND	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

### SUPPRESS

Attribute	Description	
Name	SUPPRESS	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## DELMSG

Attribute	Description	
Name	DELMSG	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## QUEUERIGHTS

Attribute	Description	
Name	QUEUERIGHTS	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

## QUEUE

Attribute	Description	
Name	QUEUE	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	10

## USERTILLS

Attribute	Description	
Name	USERTILLS	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

## TILLID

Attribute	Description				
Name	TILLID				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## USERACCCLASS

Attribute	Description				
Name	USERACCCLASS				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## ACCCLS

Attribute	Description				
Name	ACCCLS				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>6</td></tr></tbody></table>	Restrictions	Description	maxLength	6
Restrictions	Description				
maxLength	6				

## USERGLREST

Attribute	Description				
Name	USERGLREST				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## NODEGL

Attribute	Description				
Name	NODEGL				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

## USERGLEXCEPT

Attribute	Description
Name	USERGLEXCEPT
Datatype	

Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## EXPNODEGL

Attribute	Description				
Name	EXPNODEGL				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

## EXCEPLEAFGL

Attribute	Description				
Name	EXCEPLEAFGL				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

## USERLIMITSROLE

Attribute	Description				
Name	USERLIMITSROLE				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## LMTBRN

Attribute	Description				
Name	LMTBRN				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## LMTSROLE

Attribute	Description
Name	LMTSROLE
Datatype	string
Description	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## USERBRANCHES

<b>Attribute</b>	<b>Description</b>	
Name	USERBRANCHES	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## BRNSBRN

<b>Attribute</b>	<b>Description</b>	
Name	BRNSBRN	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## USERPRODUCTS

<b>Attribute</b>	<b>Description</b>	
Name	USERPRODUCTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## PRDPRDCD

<b>Attribute</b>	<b>Description</b>	
Name	PRDPRDCD	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

## USERACCESSPRODUCTS

<b>Attribute</b>	<b>Description</b>	
Name	USERACCESSPRODUCTS	
Datatype		
Description		



Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## PRDACCESSPRDCD

<b>Attribute</b>	<b>Description</b>	
Name	PRDACCESSPRDCD	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

## USERFUNCDISALLOW

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCDISALLOW	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## FUNCDISALLOWFUNCID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCDISALLOWFUNCID	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## USERROLE

<b>Attribute</b>	<b>Description</b>	
Name	USERROLE	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ROLEBRNCD

<b>Attribute</b>	<b>Description</b>	
Name	ROLEBRNCD	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## USRROLEID

Attribute	Description	
Name	USRROLEID	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	15

## USERSFUNCTIONS

Attribute	Description	
Name	USERSFUNCTIONS	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

## USERFUNCBRNCD

Attribute	Description	
Name	USERFUNCBRNCD	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

## USERFUNCFUNCID

Attribute	Description	
Name	USERFUNCFUNCID	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	8

## CONTROL1

Attribute	Description	
Name	CONTROL1	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

## CONTROL2

Attribute	Description

Name	CONTROL2	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL4

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL4	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL6

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CONTROL6	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL8

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL8	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## USERFUNCCTRL10

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	USERFUNCCTRL10	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL11

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL11	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL12

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL12	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL13

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL13	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL14

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CONTROL14	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL15

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL15	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## USERFUNCSTR

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCSTR	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

## Grp-Restriction

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	Grp-Restriction	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	maxOccurs	unbounded

## GROUP\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_CODE	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	40

## Centralisation

<b>Attribute</b>	<b>Description</b>	
Name	Centralisation	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	maxOccurs	unbounded

## USRROLEID

<b>Attribute</b>	<b>Description</b>	
Name	USRROLEID	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	15

## Dshdet

<b>Attribute</b>	<b>Description</b>	
Name	Dshdet	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	maxOccurs	unbounded

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		

Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

### 2.18.3.SM-ModifyUserMaint-Res-Full-MSG.xsd

*MODIFYUSERMAINT\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*



*DESTINATION*  
*MULTIRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*USR-Full*  
*STRDATE*  
*USRNAME*  
*USRPWD*  
*ENDDT*  
*USRLANG*  
*HOMEBRN*  
*CUSTNO*  
*LDAPUSR*  
*TIMELEVEL*  
*AUTOAUTH*  
*USRSTAT*  
*USRID*  
*EXTUSRREF*  
*USRCATEG*  
*TILLALLOW*  
*ACCCLSALLOW*  
*GLALLOW*  
*USRTXNLMT*  
*LMTSCCY*  
*MAXTXNAMT*

*MAXAUTHAMT*  
*BRNSALLOW*  
*PRDSALLOW*  
*PRDSACCESALLOW*  
*TAX\_IDENTIFIER*  
*AMOUNT\_FORMAT*  
*DATE\_FORMAT*  
*STAFFACCRESTR*  
*DEPT\_CODE*  
*DEPT\_DESC*  
*USRML*  
*ELCMUSER*  
*GROUP\_CODE*  
*MULTIBRN\_ACCESS*  
*OTH\_RM\_CUST\_ACC\_ALLOW*  
*SUPERVISOR\_ID*  
*SUPERVISOR\_NAME*  
*DASHBOARD\_REQD*  
*ALERTS\_ON\_HOME*  
*REFERENCE\_NO*  
*NO\_CUMULATIVE\_LOGINS*  
*NO\_SUCESSIVE\_LOGINS*  
*SCREENSAVERTIMEOUTINSECONDS*  
*NUMBER\_FORMAT\_MASK*  
*FRONTEND\_DEBUG\_ENABLED*  
*F10\_REQD*  
*F11\_REQD*  
*F12\_REQD*  
*MFI\_USER*  
*MFAENABLED*  
*MFAID*  
*ACCESS\_CONTROL*

*EXTN\_ALERTS*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*RESTR\_PWD*  
*PWD*  
*MSGSRIGHTS*  
*GEN*  
*HLD*  
*CNL*  
*TSTINP*  
*CHGNODE*  
*CHGADDR*  
*REL*  
*REINS*  
*CHGMEDIA*  
*CHGPRIOR*  
*BRNMOV*  
*PRNT*  
*TSTCHK*  
*HLDAUTH*  
*CNLAUTH*  
*TSTINPAUTH*  
*CHGNODEAUTH*  
*CHGADDRAUTH*  
*RELAUTH*  
*REINSAUTH*  
*CHGMEDIAAUTH*

*BRNMOVAUTH*  
*CHGPRIORAUTH*  
*FTUPL*  
*LNKCONT*  
*MOVQ*  
*CHGBRNIN*  
*CHGADDRIN*  
*AUTHRGHTS*  
*CHGMSG*  
*CHGMSGAUTH*  
*CHGFORCCOVMATCH*  
*CHANGE\_FORCE\_RELEASE\_FUND*  
*SUPPRESS*  
*DELMSG*  
*QUEUERIGHTS*  
    *QUEUE*  
*USERTILLS*  
    *TILLID*  
    *TILLBRNCD*  
    *DESCRIPTION*  
*USERACCCLASS*  
    *ACCCLS*  
*USERGLREST*  
    *NODEGL*  
    *USERGLEXCEPT*  
        *EXCEPLEAFGL*  
*USERLIMITSROLE*  
    *LMTBRN*  
    *LMTSROLE*  
    *QLMTCCY*  
    *QINPLMT*  
    *QAUTHLMT*

*USERBRANCHES*

*BRNSBRN*

*BRNNAME*

*USERPRODUCTS*

*PRDPRDCD*

*PRDDESC*

*USERACCESSPRODUCTS*

*PRDACCESSPRDCD*

*PRDDESC*

*USERFUNCDISALLOW*

*FUNCDISALLOWFUNCID*

*USERROLE*

*ROLEBRNCD*

*USRROLEID*

*MASTERROLEDESC*

*USERSFUNCTIONS*

*USERFUNCBRNCD*

*USERFUNCFUNCID*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*USERFUNCCTRL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CONTROL15*

*CONTROL16*

*Grp-Restriction*

*GROUP\_CODE*

*GROUP\_DESC*

*Centralisation*

*USRROLEID*

*ROLDESC*

*Dshmst*

*USRID*

*USRNAME*

*Dshdet*

*FUNCTIONID*

*DESCRIPTION*

*SEQUENCE\_NO*

*DBWHERECLAUSE*

*SHOW\_IN\_DASHBOARD*

*Where-Master*

*COLUMN\_NAME*

*WHERE\_CL*

*CONDITION*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## MODIFYUSERMAINT\_FSFS\_RES

Attribute	Description
Name	MODIFYUSERMAINT_FSFS_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>
Name	MODULEID



Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs		0
	maxOccurs		unbounded

## NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

## VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

## FCUBS\_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description		This XSD Gives Information about Full Response	

## USR-Full

Attribute		Description	
Name		USR-Full	
Datatype			
Description			

## STRTDAT

Attribute		Description	
Name		STRTDAT	
Datatype		String	
Description			

## USRNAME

Attribute		Description	
Name		USRNAME	
Datatype		string	
Description			
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength		35

## USRPWD

Attribute		Description	

Name	USRPWD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	32

## ENDDT

<b>Attribute</b>	<b>Description</b>	
Name	ENDDT	
Datatype	String	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0

## USRLANG

<b>Attribute</b>	<b>Description</b>	
Name	USRLANG	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	3

## HOMEBRN

<b>Attribute</b>	<b>Description</b>	
Name	HOMEBRN	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	3

## CUSTNO

<b>Attribute</b>	<b>Description</b>	
Name	CUSTNO	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	9

## LDAPUSR

Attribute	Description	
Name	LDAPUSR	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	500

## TIMELEVEL

Attribute	Description	
Name	TIMELEVEL	
Datatype	decimal	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	9

## AUTOAUTH

Attribute	Description	
Name	AUTOAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## USRSTAT

Attribute	Description	
Name	USRSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	E,H,D,L

## USRID

Attribute	Description

Name	USRID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## EXTUSRREF

<b>Attribute</b>	<b>Description</b>	
Name	EXTUSRREF	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## USRCATEG

<b>Attribute</b>	<b>Description</b>	
Name	USRCATEG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	S,B

## TILLALLOW

<b>Attribute</b>	<b>Description</b>	
Name	TILLALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## ACCCLSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLSALLOW	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## GLALLOW

<b>Attribute</b>	<b>Description</b>	
Name	GLALLOW	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## USRTXNLMT

<b>Attribute</b>	<b>Description</b>	
Name	USRTXNLMT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,R,N

## LMTSCCY

<b>Attribute</b>	<b>Description</b>	
Name	LMTSCCY	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## MAXTXNAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXTXNAMT	
Datatype	decimal	
Description		



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### MAXAUTHAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXAUTHAMT	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### BRNSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	BRNSALLOW	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### PRDSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSALLOW	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### PRDSACCESALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSACCESALLOW	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## TAX\_IDENTIFIER

<b>Attribute</b>	<b>Description</b>	
Name	TAX_IDENTIFIER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

## AMOUNT\_FORMAT

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_FORMAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	******

## DATE\_FORMAT

<b>Attribute</b>	<b>Description</b>	
Name	DATE_FORMAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	M/d/yyyy

## STAFFACCRESTR

<b>Attribute</b>	<b>Description</b>	
Name	STAFFACCRESTR	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### DEPT\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	DEPT_CODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### DEPT\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	DEPT_DESC	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### USRML

<b>Attribute</b>	<b>Description</b>	
Name	USRML	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ELCMUSER

<b>Attribute</b>	<b>Description</b>	
Name	ELCMUSER	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### GROUP\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_CODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### MULTIBRN\_ACCESS

<b>Attribute</b>	<b>Description</b>	
Name	MULTIBRN_ACCESS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### OTH\_RM\_CUST\_ACC\_ALLOW

<b>Attribute</b>	<b>Description</b>	
Name	OTH_RM_CUST_ACC_ALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### SUPERVISOR\_ID

<b>Attribute</b>	<b>Description</b>	
Name	SUPERVISOR_ID	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	80

## SUPERVISOR\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	SUPERVISOR_NAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## DASHBOARD\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	DASHBOARD_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## ALERTS\_ON\_HOME

<b>Attribute</b>	<b>Description</b>	
Name	ALERTS_ON_HOME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REFERENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	REFERENCE_NO	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	20
	<b>Description</b>	

### NO\_CUMULATIVE\_LOGINS

<b>Attribute</b>		<b>Description</b>
Name	NO_CUMULATIVE_LOGINS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	<b>Description</b>	

### NO\_SUCCESSIVE\_LOGINS

<b>Attribute</b>		<b>Description</b>
Name	NO_SUCCESSIVE_LOGINS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	<b>Description</b>	

### SCREENSAVERTIMEOUTINSECONDS

<b>Attribute</b>		<b>Description</b>
Name	SCREENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	<b>Description</b>	

### NUMBER\_FORMAT\_MASK

<b>Attribute</b>		<b>Description</b>
Name	NUMBER_FORMAT_MASK	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	M,L

### FRONTEND\_DEBUG\_ENABLED

<b>Attribute</b>	<b>Description</b>	
Name	FRONTEND_DEBUG_ENABLED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F10\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F10_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F11\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F11_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F12\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F12_REQD	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MFI\_USER

<b>Attribute</b>	<b>Description</b>	
Name	MFI_USER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MFAENABLED

<b>Attribute</b>	<b>Description</b>	
Name	MFAENABLED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	N,Y,L

## MFAID

<b>Attribute</b>	<b>Description</b>	
Name	MFAID	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

## ACCESS\_CONTROL

<b>Attribute</b>	<b>Description</b>	
Name	ACCESS_CONTROL	
Datatype	string	
Description		



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,G,B

## EXTN\_ALERTS

<b>Attribute</b>	<b>Description</b>	
Name	EXTN_ALERTS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## RESTR\_PWD

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_PWD	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PWD

<b>Attribute</b>	<b>Description</b>	
Name	PWD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MSGSRIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	MSGSRIGHTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## GEN

<b>Attribute</b>	<b>Description</b>	
Name	GEN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLD

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	HLD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNL

<b>Attribute</b>	<b>Description</b>	
Name	CNL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINP

<b>Attribute</b>	<b>Description</b>	
Name	TSTINP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODE

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDR

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CHGADDR	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REL

<b>Attribute</b>	<b>Description</b>	
Name	REL	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINS

<b>Attribute</b>	<b>Description</b>	
Name	REINS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIA

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIA	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIOR

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CHGPRIOR	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOV

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOV	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PRNT

<b>Attribute</b>	<b>Description</b>	
Name	PRNT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTCHK

<b>Attribute</b>	<b>Description</b>	
Name	TSTCHK	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLDAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	HLDAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNLAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CNLAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINPAUTH

<b>Attribute</b>	<b>Description</b>	
Name	TSTINPAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODEAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CHGADDRAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## RELAUTH

<b>Attribute</b>	<b>Description</b>	
Name	RELAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINSAUTH

<b>Attribute</b>	<b>Description</b>	
Name	REINSAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIAAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIAAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOVAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	BRNMOVAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIORAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIORAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## FTUPL

<b>Attribute</b>	<b>Description</b>	
Name	FTUPL	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## LNKCONT

<b>Attribute</b>	<b>Description</b>	
Name	LNKCONT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MOVQ

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	MOVQ	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGBRNIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGBRNIN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRIN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## AUTHRGHTS

<b>Attribute</b>	<b>Description</b>	
Name	AUTHRGHTS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSG

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CHGMSG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHGMSGAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSGAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHGFORCCOVMATCH

<b>Attribute</b>	<b>Description</b>	
Name	CHGFORCCOVMATCH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHANGE\_FORCE\_RELEASE\_FUND

<b>Attribute</b>	<b>Description</b>	
Name	CHANGE_FORCE_RELEASE_FUND	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### SUPPRESS

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	SUPPRESS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DELMSG

<b>Attribute</b>	<b>Description</b>	
Name	DELMSG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## QUEUERIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	QUEUERIGHTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## QUEUE

<b>Attribute</b>	<b>Description</b>	
Name	QUEUE	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## USERTILLS

<b>Attribute</b>	<b>Description</b>	
Name	USERTILLS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## TILLID

Attribute	Description				
Name	TILLID				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## TILLBRNCD

Attribute	Description				
Name	TILLBRNCD				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## DESCRIPTION

Attribute	Description				
Name	DESCRIPTION				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

## USERACCCLASS

Attribute	Description						
Name	USERACCCLASS						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## ACCCLS

Attribute	Description				
Name	ACCCLS				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>6</td></tr></tbody></table>	Restrictions	Description	maxLength	6
Restrictions	Description				
maxLength	6				

## USERGLREST

Attribute		Description	
Name	USERGLREST		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
	maxOccurs	unbounded	

## NODEGL

Attribute		Description	
Name	NODEGL		
Datatype	string		
Description			
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	9	

## USERGLEXCEPT

Attribute		Description	
Name	USERGLEXCEPT		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
	maxOccurs	unbounded	

## EXCEPLEAFGL

Attribute		Description	
Name	EXCEPLEAFGL		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	9	

## USERLIMITSROLE

Attribute		Description	
Name	USERLIMITSROLE		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
	maxOccurs	unbounded	

## LMTBRN

Attribute	Description				
Name	LMTBRN				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## LMTSROLE

Attribute	Description				
Name	LMTSROLE				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## QLMTCCY

Attribute	Description				
Name	QLMTCCY				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## QINPLMT

Attribute	Description				
Name	QINPLMT				
Datatype	decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## QAUTHLMT

Attribute	Description
Name	QAUTHLMT

Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	<b>Description</b>	

## USERBRANCHES

<b>Attribute</b>	<b>Description</b>	
Name	USERBRANCHES	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## BRNSBRN

<b>Attribute</b>	<b>Description</b>	
Name	BRNSBRN	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	3
	<b>Description</b>	

## BRNNAME

<b>Attribute</b>	<b>Description</b>	
Name	BRNNAME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	105
	<b>Description</b>	

## USERPRODUCTS

<b>Attribute</b>	<b>Description</b>	
Name	USERPRODUCTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	



## PRDPRDCD

Attribute	Description	
Name	PRDPRDCD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

## PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## USERACCESSPRODUCTS

Attribute	Description	
Name	USERACCESSPRODUCTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PRDACCESSPRDCD

Attribute	Description	
Name	PRDACCESSPRDCD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

## PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## USERFUNCDISALLOW

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCDISALLOW	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FUNCDISALLOWFUNCID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCDISALLOWFUNCID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## USERROLE

<b>Attribute</b>	<b>Description</b>	
Name	USERROLE	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEBRNCD

<b>Attribute</b>	<b>Description</b>	
Name	ROLEBRNCD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## USRROLEID

<b>Attribute</b>	<b>Description</b>	
Name	USRROLEID	
Datatype	string	
Description		

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## MASTERROLEDESC

<b>Attribute</b>	<b>Description</b>	
Name	MASTERROLEDESC	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	45

## USERSFUNCTIONS

<b>Attribute</b>	<b>Description</b>	
Name	USERSFUNCTIONS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## USERFUNCBRNCD

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCBRNCD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## USERFUNCFUNCID

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCFUNCID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## CONTROL1

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL1	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL2	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL4

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL4	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL6

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL6	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL8

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL8	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### USERFUNCCTRL10

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCCTRL10	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL11

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL11	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL12

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL12	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL13

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL13	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

#### CONTROL14

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL14	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

#### CONTROL15

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL15	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

#### CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

#### Grp-Restriction

<b>Attribute</b>	<b>Description</b>	
Name	Grp-Restriction	
Datatype		
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## GROUP\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_CODE	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

## GROUP\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_DESC	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

## Centralisation

<b>Attribute</b>	<b>Description</b>	
Name	Centralisation	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## USRROLEID

<b>Attribute</b>	<b>Description</b>	
Name	USRROLEID	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## ROLDESC

<b>Attribute</b>	<b>Description</b>	
Name	ROLDESC	
Datatype	string	



Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

### Dshmst

<b>Attribute</b>	<b>Description</b>	
Name	Dshmst	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

### USRID

<b>Attribute</b>	<b>Description</b>	
Name	USRID	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

### USRNAME

<b>Attribute</b>	<b>Description</b>	
Name	USRNAME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

### Dshdet

<b>Attribute</b>	<b>Description</b>	
Name	Dshdet	
Datatype		
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1000

## SEQUENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	SEQUENCE_NO	
Datatype	decimal	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## DBWHERECLAUSE

<b>Attribute</b>	<b>Description</b>	
Name	DBWHERECLAUSE	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

## SHOW\_IN\_DASHBOARD

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	SHOW_IN_DASHBOARD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### Where-Master

<b>Attribute</b>	<b>Description</b>	
Name	Where-Master	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

### COLUMN\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	COLUMN_NAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	2000

### WHERE\_CL

<b>Attribute</b>	<b>Description</b>	
Name	WHERE_CL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	500

### CONDITION

<b>Attribute</b>	<b>Description</b>	
Name	CONDITION	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxOccurs	unbounded

## ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String

Description	
-------------	--

#### 2.18.4.SM-ModifyUserMaint-Res-PK-MSG.xsd

### *MODIFYUSERMAINT\_IOPK\_RES*

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

*USR-PK*

*USRID*

*USR-IO*

*STRTDATE*

*USRNAME*

*USRPWD*

*ENDDT*

*USRLANG*  
*HOMEBRN*  
*CUSTNO*  
*LDAPUSR*  
*TIMELEVEL*  
*AUTOAUTH*  
*USRSTAT*  
*USRID*  
*FORCPWDCHG*  
*USRCATEG*  
*TILLALLOW*  
*ACCCLSALLOW*  
*GLALLOW*  
*USRTXNLMT*  
*LMTSCCY*  
*MAXTXNAMT*  
*MAXAUTHAMT*  
*BRNSALLOW*  
*PRDSALLOW*  
*PRDSACCESALLOW*  
*TAX\_IDENTIFIER*  
*STAFFACCRESTR*  
*DEPT\_CODE*  
*USRML*  
*ELCMUSER*  
*GROUP\_CODE*  
*MULTIBRN\_ACCESS*  
*OTH\_RM\_CUST\_ACC\_ALLOW*  
*SUPERVISOR\_ID*  
*SUPERVISOR\_NAME*  
*DASHBOARD\_REQD*  
*ALERTS\_ON\_HOME*

*FRONTEND\_DEBUG\_ENABLED*

*F10\_REQD*

*F11\_REQD*

*F12\_REQD*

*MFAENABLED*

*MFAID*

*ACCESS\_CONTROL*

*EXTN\_ALERTS*

*MAKER*

*MAKERSTAMP*

*RESTR\_PWD*

*PWD*

*MSGSRIGHTS*

*GEN*

*HLD*

*CNL*

*TSTINP*

*CHGNODE*

*CHGADDR*

*REL*

*REINS*

*CHGMEDIA*

*CHGPRIOR*

*BRNMOV*

*PRNT*

*TSTCHK*

*HLDAUTH*

*CNLAUTH*

*TSTINPAUTH*

*CHGNODEAUTH*

*CHGADDRAUTH*

*RELAUTH*



*REINSAUTH*  
*CHGMEDIAAUTH*  
*BRNMOVAUTH*  
*CHGPRIORAUTH*  
*FTUPL*  
*LNKCONT*  
*MOVQ*  
*CHGBRNIN*  
*CHGADDRIN*  
*AUTHRGHTS*  
*CHGMSG*  
*CHGMSGAUTH*  
*CHGFORCCOVMATCH*  
*CHANGE\_FORCE\_RELEASE\_FUND*  
*SUPPRESS*  
*DELMSG*  
*QUEUERIGHTS*  
    *QUEUE*  
*USERTILLS*  
    *TILLID*  
*USERACCCLASS*  
    *ACCCLS*  
*USERGLREST*  
    *NODEGL*  
    *USERGLEXCEPT*  
        *EXPNODEGL*  
        *EXCEPLEAFGL*  
*USERLIMITSROLE*  
    *LMTBRN*  
    *LMTSROLE*  
*USERBRANCHES*  
    *BRNSBRN*

*USERPRODUCTS*

*PRDPRDCD*

*USERACCESSPRODUCTS*

*PRDACCESSPRDCD*

*USERFUNCDISALLOW*

*FUNCDISALLOWFUNCID*

*USERROLE*

*ROLEBRNCD*

*USRROLEID*

*USERSFUNCTIONS*

*USERFUNCBRNCD*

*USERFUNCFUNCID*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*USERFUNCCTRL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CONTROL15*

*CONTROL16*

*USERFUNCSTRSTR*

*Grp-Restriction*

*GROUP\_CODE*

*Centralisation*

*USRROLEID*

*Dshdet*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## MODIFYUSERMAINT\_IOPK\_RES

Attribute	Description
Name	MODIFYUSERMAINT_IOPK_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	string
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	string
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>
Name	FUNCTIONID

Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

## USR-PK

<b>Attribute</b>	<b>Description</b>
Name	USR-PK
Datatype	
Description	

## USRID

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	USRID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## USR-IO

<b>Attribute</b>	<b>Description</b>
Name	USR-IO
Datatype	
Description	

## STRTDATE

<b>Attribute</b>	<b>Description</b>	
Name	STRTDATE	
Datatype	String	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## USRNAME

<b>Attribute</b>	<b>Description</b>	
Name	USRNAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## USRPWD

<b>Attribute</b>	<b>Description</b>	
Name	USRPWD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	32

## ENDDT

<b>Attribute</b>	<b>Description</b>
Name	ENDDT

Datatype	String	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## USRLANG

<b>Attribute</b>	<b>Description</b>	
Name	USRLANG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## HOMEBRN

<b>Attribute</b>	<b>Description</b>	
Name	HOMEBRN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## CUSTNO

<b>Attribute</b>	<b>Description</b>	
Name	CUSTNO	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## LDAPUSR

<b>Attribute</b>	<b>Description</b>	
Name	LDAPUSR	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	500

## TIMELEVEL

<b>Attribute</b>	<b>Description</b>	
Name	TIMELEVEL	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	9

## AUTOAUTH

<b>Attribute</b>	<b>Description</b>	
Name	AUTOAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## USRSTAT

<b>Attribute</b>	<b>Description</b>	
Name	USRSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	E,H,D,L

## USRID

<b>Attribute</b>	<b>Description</b>
Name	USRID

Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### FORCPWDCHG

<b>Attribute</b>	<b>Description</b>	
Name	FORCPWDCHG	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### USRCATEG

<b>Attribute</b>	<b>Description</b>	
Name	USRCATEG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	S,B

### TILLALLOW

<b>Attribute</b>	<b>Description</b>	
Name	TILLALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### ACCCLSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLSALLOW	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## GLALLOW

<b>Attribute</b>	<b>Description</b>	
Name	GLALLOW	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## USRTXNLMT

<b>Attribute</b>	<b>Description</b>	
Name	USRTXNLMT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,R,N

## LMTSCCY

<b>Attribute</b>	<b>Description</b>	
Name	LMTSCCY	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## MAXTXNAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXTXNAMT	
Datatype	decimal	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### MAXAUTHAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXAUTHAMT	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### BRNSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	BRNSALLOW	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### PRDSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSALLOW	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### PRDSACCESALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSACCESALLOW	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## TAX\_IDENTIFIER

<b>Attribute</b>	<b>Description</b>	
Name	TAX_IDENTIFIER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

## STAFFACCRESTR

<b>Attribute</b>	<b>Description</b>	
Name	STAFFACCRESTR	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DEPT\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	DEPT_CODE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## USRML

<b>Attribute</b>	<b>Description</b>	
Name	USRML	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	50
	<b>Description</b>	

## ELCMUSER

<b>Attribute</b>	<b>Description</b>	
Name	ELCMUSER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	12
	<b>Description</b>	

## GROUP\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_CODE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	enumeration	A,D
	<b>Description</b>	

## MULTIBRN\_ACCESS

<b>Attribute</b>	<b>Description</b>	
Name	MULTIBRN_ACCESS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	enumeration	Y,N
	<b>Description</b>	

## OTH\_RM\_CUST\_ACC\_ALLOW

<b>Attribute</b>	<b>Description</b>	
Name	OTH_RM_CUST_ACC_ALLOW	
Datatype	string	
Description		



Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### SUPERVISOR\_ID

<b>Attribute</b>	<b>Description</b>	
Name	SUPERVISOR_ID	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	80

### SUPERVISOR\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	SUPERVISOR_NAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

### DASHBOARD\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	DASHBOARD_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### ALERTS\_ON\_HOME

<b>Attribute</b>	<b>Description</b>	
Name	ALERTS_ON_HOME	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### FRONTEND\_DEBUG\_ENABLED

<b>Attribute</b>	<b>Description</b>	
Name	FRONTEND_DEBUG_ENABLED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F10\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F10_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F11\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F11_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F12\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F12_REQD	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MFAENABLED

<b>Attribute</b>	<b>Description</b>	
Name	MFAENABLED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	N,Y,L

## MFAID

<b>Attribute</b>	<b>Description</b>	
Name	MFAID	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

## ACCESS\_CONTROL

<b>Attribute</b>	<b>Description</b>	
Name	ACCESS_CONTROL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,G,B

## EXTN\_ALERTS

<b>Attribute</b>	<b>Description</b>	
Name	EXTN_ALERTS	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## RESTR\_PWD

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_PWD	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## PWD

<b>Attribute</b>	<b>Description</b>	
Name	PWD	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MSGSRIGHTS

Attribute		Description	
Name	MSGSRIGHTS		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	

## GEN

Attribute		Description	
Name	GEN		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	Y,N	

## HLD

Attribute		Description	
Name	HLD		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	Y,N	

## CNL

Attribute		Description	
Name	CNL		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	Y,N	

## TSTINP

Attribute		Description	
Name	TSTINP		

Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODE

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDR

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REL

<b>Attribute</b>	<b>Description</b>	
Name	REL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINS

<b>Attribute</b>	<b>Description</b>
Name	REINS

Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIA

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIA	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIOR

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIOR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOV

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOV	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PRNT

<b>Attribute</b>	<b>Description</b>	
Name	PRNT	

Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTCHK

<b>Attribute</b>	<b>Description</b>	
Name	TSTCHK	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLDAUTH

<b>Attribute</b>	<b>Description</b>	
Name	HLDAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNLAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CNLAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINPAUTH

<b>Attribute</b>	<b>Description</b>	
Name	TSTINPAUTH	



Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODEAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## RELAUTH

<b>Attribute</b>	<b>Description</b>	
Name	RELAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINSAUTH

<b>Attribute</b>	<b>Description</b>	
Name	REINSAUTH	

Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIAAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIAAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOVAUTH

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOVAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIORAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIORAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## FTUPL

<b>Attribute</b>	<b>Description</b>
Name	FTUPL

Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## LNKCONT

<b>Attribute</b>	<b>Description</b>	
Name	LNKCONT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MOVQ

<b>Attribute</b>	<b>Description</b>	
Name	MOVQ	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGBRNIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGBRNIN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRIN	

Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## AUTHRGHTS

<b>Attribute</b>	<b>Description</b>	
Name	AUTHRGHTS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSG

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSGAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSGAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGFORCCOVMATCH

<b>Attribute</b>	<b>Description</b>
Name	CHGFORCCOVMATCH

Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHANGE\_FORCE\_RELEASE\_FUND

<b>Attribute</b>	<b>Description</b>	
Name	CHANGE_FORCE_RELEASE_FUND	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SUPPRESS

<b>Attribute</b>	<b>Description</b>	
Name	SUPPRESS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DELMSG

<b>Attribute</b>	<b>Description</b>	
Name	DELMSG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## QUEUERIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	QUEUERIGHTS	

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## QUEUE

Attribute	Description				
Name	QUEUE				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>10</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

## USERTILLS

Attribute	Description				
Name	USERTILLS				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## TILLID

Attribute	Description				
Name	TILLID				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## USERACCCLASS

Attribute	Description				
Name	USERACCCLASS				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	string
Description	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

## USERGLREST

<b>Attribute</b>	<b>Description</b>	
Name	USERGLREST	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## NODEGL

<b>Attribute</b>	<b>Description</b>	
Name	NODEGL	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## USERGLEXCEPT

<b>Attribute</b>	<b>Description</b>	
Name	USERGLEXCEPT	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## EXPNODEGL

<b>Attribute</b>	<b>Description</b>	
Name	EXPNODEGL	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## EXCEPLEAFGL

<b>Attribute</b>	<b>Description</b>	
Name	EXCEPLEAFGL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## USERLIMITSROLE

<b>Attribute</b>	<b>Description</b>	
Name	USERLIMITSROLE	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## LMTBRN

<b>Attribute</b>	<b>Description</b>	
Name	LMTBRN	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## LMTSROLE

<b>Attribute</b>	<b>Description</b>	
Name	LMTSROLE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## USERBRANCHES

<b>Attribute</b>	<b>Description</b>	
Name	USERBRANCHES	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## BRNSBRN

<b>Attribute</b>	<b>Description</b>	
Name	BRNSBRN	
Datatype	string	
Description		



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## USERPRODUCTS

<b>Attribute</b>	<b>Description</b>	
Name	USERPRODUCTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## PRDPRDCD

<b>Attribute</b>	<b>Description</b>	
Name	PRDPRDCD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

## USERACCESSPRODUCTS

<b>Attribute</b>	<b>Description</b>	
Name	USERACCESSPRODUCTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## PRDACCESSPRDCD

<b>Attribute</b>	<b>Description</b>	
Name	PRDACCESSPRDCD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

## USERFUNCDISALLOW

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCDISALLOW	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## FUNCDISALLOWFUNCID

Attribute	Description	
Name	FUNCDISALLOWFUNCID	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	8

## USERROLE

Attribute	Description	
Name	USERROLE	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

## ROLEBRNCD

Attribute	Description	
Name	ROLEBRNCD	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

## USRROLEID

Attribute	Description	
Name	USRROLEID	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	15

## USERSFUNCTIONS

Attribute	Description	
Name	USERSFUNCTIONS	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

## USERFUNCBRNCD

Attribute	Description	
Name	USERFUNCBRNCD	
Datatype	string	
Description		

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## USERFUNCFUNCID

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCFUNCID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## CONTROL1

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL1	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL2	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL4

Attribute	Description	
Name	CONTROL4	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL5

Attribute	Description	
Name	CONTROL5	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL6

Attribute	Description	
Name	CONTROL6	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL7

Attribute	Description	
Name	CONTROL7	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL8

Attribute		Description	
Name	CONTROL8		
Datatype	decimal		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	

### CONTROL9

Attribute		Description	
Name	CONTROL9		
Datatype	decimal		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	

### USERFUNCCTRL10

Attribute		Description	
Name	USERFUNCCTRL10		
Datatype	decimal		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	

### CONTROL11

Attribute		Description	
Name	CONTROL11		
Datatype	decimal		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	

### CONTROL12

Attribute	Description	
Name	CONTROL12	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL13

Attribute	Description	
Name	CONTROL13	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL14

Attribute	Description	
Name	CONTROL14	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL15

Attribute	Description	
Name	CONTROL15	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL16

Attribute	Description	
Name	CONTROL16	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	<b>Description</b>	

## USERFUNCSTR

Attribute	Description	
Name	USERFUNCSTR	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	16
	<b>Description</b>	

## Grp-Restriction

Attribute	Description	
Name	Grp-Restriction	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## GROUP\_CODE

Attribute	Description	
Name	GROUP_CODE	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	40
	<b>Description</b>	

## Centralisation

Attribute	Description	
Name	Centralisation	
Datatype		
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## USRROLEID

<b>Attribute</b>	<b>Description</b>	
Name	USRROLEID	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## Dshdet

<b>Attribute</b>	<b>Description</b>	
Name	Dshdet	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

## WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

## WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

## 2.19.QuerySMDBANKP

### 2.19.1.SM-QuerySMDBANKP-Req-IO-MSG.xsd

*QUERYSMDBANKP\_IOFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS\_BODY

Smtbs-Parameters-IO

SITE\_CODE

## QUERYSMDBANKP\_IOFS\_REQ

Attribute	Description
Name	QUERYSMDBANKP_IOFS_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

## ADDL

Attribute		Description	
Name	ADDL		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

## PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

## NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

## VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

## FCUBS\_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description	This XSD Gives Information about IO Request of QuerySMDBANKP		

## Smtbs-Parameters-IO

Attribute		Description	
Name	Smtbs-Parameters-IO		
Datatype			
Description			

## SITE\_CODE

Attribute		Description	
Name	SITE_CODE		
Datatype	string		
Description	Indicates Site Code		



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

2.19.2.SM-QuerySMDBANKP-Res-Full-MSG.xsd

*QUERYSMDBANKP\_IOFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Parameters-IO*

*SITE\_CODE*

*Smtbs-Parameters-Full*

*HEAD\_OFFICE*

*SITE\_CODE*

*ACTIVATION\_KEY*  
*INVALID\_LOGINS\_CUM*  
*INVALID\_LOGINS\_SUC*  
*PWD\_PREVENT\_REUSE*  
*PWD\_CHANGE\_AFTER*  
*MAXIMUM*  
*MINIMUM*  
*PWD\_EXPIRY\_MSG\_DAYS*  
*ARCHIVAL\_PERIOD*  
*CONCHAR\_PWD\_NUM*  
*FREQ\_PWD\_CHG*  
*MIN\_PWD\_NUMERIC\_LENGTH*  
*LEGAL\_NOTICE*  
*DORMANCY\_DAYS*  
*DISPLAY\_LEGAL\_NOTICE*  
*MIN\_SPECIALCHAR\_LENGTH*  
*MIN\_LOWERCASE\_CHAR*  
*MIN\_UPPERCASE\_CHAR*  
*SCREESAVERREQUIRED*  
*SCREESAVERTIMEOUTINSECONDS*  
*SCREESAVERMODIFIABLEBYUSER*  
*PASSWORDEXTERNAL*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*Smtbs-Branch-Restr*  
*RESTR\_TYPE*  
*DESCRIPTION*

*Smtbs-Restrictive-Passwd*

*PASSWORD*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

**QUERYSMDBANKP\_IOFS\_RES**

Attribute	Description
Name	QUERYSMDBANKP_IOFS_RES
Datatype	
Description	

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

**SOURCE**

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

**UBSCOMP**

Attribute	Description
Name	UBSCOMP
Datatype	string
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	string
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	

Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

## Smtbs-Parameters-IO

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Parameters-IO	
Datatype		
Description		

## SITE\_CODE

<b>Attribute</b>	<b>Description</b>	
------------------	--------------------	--



Name	SITE_CODE	
Datatype	string	
Description	Indicates Site Code	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

### Smtbs-Parameters-Full

<b>Attribute</b>	<b>Description</b>
Name	Smtbs-Parameters-Full
Datatype	
Description	

### HEAD\_OFFICE

<b>Attribute</b>	<b>Description</b>	
Name	HEAD_OFFICE	
Datatype	string	
Description	Indicates Head Office	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### SITE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	SITE_CODE	
Datatype	string	
Description	Indicates Site Code	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

### ACTIVATION\_KEY

<b>Attribute</b>	<b>Description</b>	
Name	ACTIVATION_KEY	
Datatype	string	
Description	Indicates Activation Key	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	24

### INVALID\_LOGINS\_CUM

<b>Attribute</b>	<b>Description</b>
Name	INVALID_LOGINS_CUM

Datatype	decimal	
Description	Indicates Cumulative	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	6
	maxInclusive	99

## INVALID\_LOGINS\_SUC

<b>Attribute</b>	<b>Description</b>	
Name	INVALID_LOGINS_SUC	
Datatype	decimal	
Description	Indicates Successive	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	1
	minInclusive	3
	maxInclusive	5

## PWD\_PREVENT\_REUSE

<b>Attribute</b>	<b>Description</b>	
Name	PWD_PREVENT_REUSE	
Datatype	decimal	
Description	Indicates Password Repetitions	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## PWD\_CHANGE\_AFTER

<b>Attribute</b>	<b>Description</b>	
Name	PWD_CHANGE_AFTER	
Datatype	decimal	
Description	Indicates Force Password Change After	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	3
	minInclusive	15
	maxInclusive	180

## MAXIMUM

Attribute	Description								
Name	MAXIMUM								
Datatype	decimal								
Description	Indicates Maximum								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>12</td></tr><tr><td>maxInclusive</td><td>30</td></tr></tbody></table>	Restrictions	Description	totalDigits	2	minInclusive	12	maxInclusive	30
	Restrictions	Description							
	totalDigits	2							
	minInclusive	12							
maxInclusive	30								

## MINIMUM

Attribute	Description								
Name	MINIMUM								
Datatype	decimal								
Description	Indicates Minimum								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>6</td></tr><tr><td>maxInclusive</td><td>11</td></tr></tbody></table>	Restrictions	Description	totalDigits	2	minInclusive	6	maxInclusive	11
	Restrictions	Description							
	totalDigits	2							
	minInclusive	6							
maxInclusive	11								

## PWD\_EXPIRY\_MSG\_DAYS

Attribute	Description								
Name	PWD_EXPIRY_MSG_DAYS								
Datatype	decimal								
Description	Indicates Intimate User (Before Password Expiry)								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0				
	Attribute	Description							
minOccurs	0								
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>1</td></tr><tr><td>maxInclusive</td><td>5</td></tr></tbody></table>	Restrictions	Description	totalDigits	2	minInclusive	1	maxInclusive	5
	Restrictions	Description							
	totalDigits	2							
	minInclusive	1							
maxInclusive	5								

## ARCHIVAL\_PERIOD

Attribute	Description				
Name	ARCHIVAL_PERIOD				
Datatype	decimal				
Description	Indicates Archival Period (in days)				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>3</td></tr></tbody></table>	Restrictions	Description	totalDigits	3
	Restrictions	Description			
totalDigits	3				

## CONCHAR\_PWD\_NUM

Attribute	Description					
Name	CONCHAR_PWD_NUM					
Datatype	decimal					
Description	Indicates Maximum Consecutive Repetitive Characters					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>2</td> </tr> </tbody> </table>		Restrictions	Description	totalDigits	2
Restrictions	Description					
totalDigits	2					

## FREQ\_PWD\_CHG

Attribute	Description							
Name	FREQ_PWD_CHG							
Datatype	decimal							
Description	Indicates Minimum Days Between Password Changes							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>2</td> </tr> <tr> <td>minInclusive</td> <td>0</td> </tr> </tbody> </table>		Restrictions	Description	totalDigits	2	minInclusive	0
Restrictions	Description							
totalDigits	2							
minInclusive	0							

## MIN\_PWD\_NUMERIC\_LENGTH

Attribute	Description							
Name	MIN_PWD_NUMERIC_LENGTH							
Datatype	decimal							
Description	Indicates Minimum Number Of Numeric Characters In Password							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>2</td> </tr> <tr> <td>minInclusive</td> <td>1</td> </tr> </tbody> </table>		Restrictions	Description	totalDigits	2	minInclusive	1
Restrictions	Description							
totalDigits	2							
minInclusive	1							

## LEGAL\_NOTICE

Attribute	Description					
Name	LEGAL_NOTICE					
Datatype	string					
Description	Indicates Warning Screen Text					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>4000</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	4000
Restrictions	Description					
maxLength	4000					

## DORMANCY\_DAYS

Attribute		Description	
Name	DORMANCY_DAYS		
Datatype	decimal		
Description	Indicates Dormancy Days		
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	2	
	minInclusive	1	

## DISPLAY\_LEGAL\_NOTICE

Attribute		Description	
Name	DISPLAY_LEGAL_NOTICE		
Datatype	string		
Description	Indicates Display Legal Notice Y - on N - Off		
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	Y,N	

## MIN\_SPECIALCHAR\_LENGTH

Attribute		Description	
Name	MIN_SPECIALCHAR_LENGTH		
Datatype	decimal		
Description	Indicates Minimum Number Of Special Characters In Password		
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	2	
	minInclusive	1	

## MIN\_LOWERCASE\_CHAR

Attribute		Description	
Name	MIN_LOWERCASE_CHAR		
Datatype	decimal		
Description	Indicates Minimum Number of LowerCase Characters in Password		
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	2	
	minInclusive	1	

## MIN\_UPPERCASE\_CHAR

Attribute		Description	
Name	MIN_UPPERCASE_CHAR		

Datatype	decimal						
Description	Indicates Minimum Number of UpperCase Characters in Password						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>2</td> </tr> <tr> <td>minInclusive</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	2	minInclusive	1
	Restrictions	Description					
	totalDigits	2					
minInclusive	1						

## SCRENSAVERREQUIRED

<b>Attribute</b>	<b>Description</b>	
Name	SCRENSAVERREQUIRED	
Datatype	string	
Description	Indicates Screensaver Required Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SCRENSAVERTIMEOUTINSECONDS

<b>Attribute</b>	<b>Description</b>	
Name	SCRENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description	Indicates Screensaver Interval (in seconds)	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## SCRENSAVERMODIFIABLEBYUSER

<b>Attribute</b>	<b>Description</b>	
Name	SCRENSAVERMODIFIABLEBYUSER	
Datatype	string	
Description	Indicates Screensaver Interval Modifiable at User Level Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PASSWORDEXTERNAL

<b>Attribute</b>	<b>Description</b>
Name	PASSWORDEXTERNAL
Datatype	string

Description	Indicates Password External Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	

Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## Smtbs-Branch-Restr

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Branch-Restr	
Datatype		



Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## RESTR\_TYPE

Attribute	Description				
Name	RESTR_TYPE				
Datatype	string				
Description	Indicates Restriction Type				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## DESCRIPTION

Attribute	Description				
Name	DESCRIPTION				
Datatype	string				
Description	Indicates Restriction Type Description				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>255</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

## Smtbs-Restrictive-Passwd

Attribute	Description						
Name	Smtbs-Restrictive-Passwd						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## PASSWORD

Attribute	Description				
Name	PASSWORD				
Datatype	string				
Description	Indicates Password				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

## WDESC

<b>Attribute</b>	<b>Description</b>
Name	WDESC
Datatype	String
Description	

## 2.20.QuerySMDRLMNE

### 2.20.1.SM-QuerySMDRLMNE-Req-IO-MSG.xsd

[QUERYSMDRLMNE\\_IOFS\\_REQ](#)

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Role-Limit-IO*

*ROLEID2*

**QUERYSMDRLMNE\_IOFS\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	QUERYSMDRLMNE_IOFS_REQ
Datatype	
Description	

**FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	

Description	
-------------	--

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	string	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT



Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of QuerySMDRLMNE

## Smtbs-Role-Limit-IO

Attribute	Description
Name	Smtbs-Role-Limit-IO
Datatype	
Description	

## ROLEID2

Attribute	Description				
Name	ROLEID2				
Datatype	string				
Description	Indicates Role Id				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

### 2.20.2.SM-QuerySMDRLMNE-Res-Full-MSG.xsd

#### *QUERYSMDRLMNE\_IOFS\_RES*

##### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Role-Limit-IO*

*ROLEID2*

*Smtbs-Role-Limit-Full*

*ROLEID2*

*DESCRIPTION*

*LIMIT\_CCY*

*INPUT\_LIMIT*

*AUTHORIZATION\_LIMIT*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

**QUERYSMDRLMNE\_IOFS\_RES**

Attribute	Description
Name	QUERYSMDRLMNE_IOFS_RES
Datatype	
Description	

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

**SOURCE**

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

**UBSCOMP**

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

**MSGID**

Attribute	Description
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field. 1856

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	string				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	string
Description	This is the user id in the Source system who is performing the action.

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM



Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

## FCUBS\_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

## Smtbs-Role-Limit-IO

Attribute	Description	
Name	Smtbs-Role-Limit-IO	
Datatype		
Description		

## ROLEID2

Attribute	Description	
Name	ROLEID2	
Datatype	string	
Description	Indicates Role Id	
Restrictions	Restrictions	Description
	maxLength	15

## Smtbs-Role-Limit-Full

Attribute	Description	
Name	Smtbs-Role-Limit-Full	
Datatype		
Description		

## ROLEID2

Attribute	Description	

Name	ROLEID2	
Datatype	string	
Description	Indicates Role Id	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## LIMIT\_CCY

<b>Attribute</b>	<b>Description</b>	
Name	LIMIT_CCY	
Datatype	string	
Description	Indicates Limit Currency	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## INPUT\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	INPUT_LIMIT	
Datatype	decimal	
Description	Indicates Input Limit	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0

## AUTHORIZATION\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHORIZATION_LIMIT	
Datatype	decimal	
Description	Indicates Authorization Limit	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0

## MAKER

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

## 2.21.QuerySMRole

### 2.21.1.SM-QuerySMRole-Req-IO-MSG.xsd

*QUERYSMROLE\_IOFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*ROLEMASTER-IO*

*ROLEIDENTIFICATION*

#### QUERYSMROLE\_IOFS\_REQ

Attribute	Description
Name	QUERYSMROLE_IOFS_REQ
Datatype	
Description	

#### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

#### SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

#### UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	string

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

## MSGID

Attribute	Description					
Name	MSGID					
Datatype	string					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

## CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	string					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

## USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	<b>Description</b>	

## ADDL

<b>Attribute</b>		<b>Description</b>
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	

## PARAM

<b>Attribute</b>		<b>Description</b>
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## NAME

<b>Attribute</b>		<b>Description</b>
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>		<b>Description</b>
Name	VALUE	
Datatype	String	
Description		

## FCUBS\_BODY

<b>Attribute</b>		<b>Description</b>
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about IO Request of QuerySMRole	

## ROLEMASTER-IO

Attribute	Description
Name	ROLEMASTER-IO
Datatype	
Description	

## ROLEIDENTIFICATION

Attribute	Description	
Name	ROLEIDENTIFICATION	
Datatype	string	
Description	Indicates Role Id	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

### 2.21.2.SM-QuerySMRole-Res-Full-MSG.xsd

#### *QUERYSMROLE\_IOFS\_RES*

##### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*ROLEMASTER-IO*

*ROLEIDENTIFICATION*

*ROLEMASTER-Full*

*ROLEIDENTIFICATION*

*MASTERROLEDESC*

*AUTHORISERROLE*

*BRANCH\_RES*

*ACCCLASSALLOWED*

*CENTRALISATIONROLE*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*ROLEDETAIL*

*ROLEFUN*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*CONTROL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CONTROL15*

*CONTROL16*

*ROLEDETAILB*

*ROLEFUN*

*CONT1*

*CONT2*

*CONT3*

*CONT4*

*CONT5*

*CONT6*

*CONTROL7*

*CONT8*

*CONT9*

*CONT10*

*CONT11*

*CONT12*

*CONT13*

*CONT14*

*CONT15*

*CONTROL16*

*ROLEDETAILC*

*ROLEFUN*

*CNTRL1*

*CNTRL2*

*CNTRL3*

*CNTRL4*

*CNTRL5*

*CNTRL6*

*CNTRL7*

*CNTRL8*

*CNTRL9*

*CNTRL10*

*CNTRL11*

*CNTRL12*

*CNTRL13*

*CNTRL14*

*CNTRL15*

*CNTRL16*

*ROLEDETAILED*

*ROLEFUN*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*CONTROL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CNTRL15*

*CNTRL16*

*ROLEBRANCHES*

*BRANCH*

*BRNNAME*

*ROLEACCCLASS*

*ACCCLS*

*DESCRIPTION*

*MSGCRIGHTS*



*CNL*  
*CHGNODE*  
*REL*  
*CHGMEDIA*  
*BRNMOV*  
*HLD*  
*TSTINP*  
*CHGADDR*  
*REINS*  
*CHGPRIOR*  
*CNLAUTH*  
*CHGNODEAUTH*  
*RELAUTH*  
*CHGMEDIAAUTH*  
*BRNMOVAUTH*  
*HLDAUTH*  
*TSTINPAUTH*  
*CHGADDRAUTH*  
*REINSAUTH*  
*CHGPRIORAUTH*  
*GEN*  
*TSTCHK*  
*LNKCONT*  
*CHGBRNIN*  
*CHGMSG*  
*CHGFORCRELFUND*  
*SUPPRESS*  
*DELMSG*  
*PRNT*  
*FTUPL*  
*MOVQ*  
*CHGADDRIN*

*CHGMSGAUTH*

*AUTHRGHTS*

*CHGFORCCOVMATCH*

*QUEUERIGHTS*

*QUEUE*

*RESTRICTIVEPASSWD*

*PWD*

*PWDID*

*ROLEBRANCHLIMITS*

*LMTCCY*

*BRHUSERLMT*

*Roledetaile*

*ROLEFUN*

*BRANCHCODE*

*EDITABLE*

*CNTRLSTR*

*Roledetailf*

*ROLEID*

*ROLEFUN*

*CNTRLSTR*

*CNTRL1*

*CNTRL10*

*CNTRL11*

*CNTRL12*

*CNTRL13*

*CNTRL14*

*CNTRL15*

*CNTRL16*

*CNTRL2*

*CNTRL3*

*CNTRL4*

*CNTRL5*

*CNTRL6*

*CNTRL7*

*CNTRL8*

*CNTRL9*

*ATHSTAT*

*BRNCHCODE*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## QUERYSMROLE\_IOFS\_RES

Attribute	Description
Name	QUERYSMROLE_IOFS_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	string				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## USERID

Attribute	Description
-----------	-------------

Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response



## ROLEMASTER-IO

Attribute	Description
Name	ROLEMASTER-IO
Datatype	
Description	

## ROLEIDENTIFICATION

Attribute	Description				
Name	ROLEIDENTIFICATION				
Datatype	string				
Description	Indicates Role Id				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## ROLEMASTER-Full

Attribute	Description
Name	ROLEMASTER-Full
Datatype	
Description	

## ROLEIDENTIFICATION

Attribute	Description				
Name	ROLEIDENTIFICATION				
Datatype	string				
Description	Indicates Role Id				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## MASTERROLEDESC

Attribute	Description				
Name	MASTERROLEDESC				
Datatype	string				
Description	Indicates Role Description				
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

## AUTHORISERROLE

Attribute	Description
Name	AUTHORISERROLE
Datatype	string
Description	Indicates Authorizer Role Y - on N - Off

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRANCH\_RES

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_RES	
Datatype	string	
Description	Indicates Branch Restriction A - Allowed D - Disallowed	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## ACCCLASSALLOWED

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLASSALLOWED	
Datatype	string	
Description	Indicates Account Class Restriction A - Allowed D - Disallowed	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## CENTRALISATIONROLE

<b>Attribute</b>	<b>Description</b>	
Name	CENTRALISATIONROLE	
Datatype	string	
Description	Indicates Centralisation Role Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>
Name	MAKER

Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>
Name	MODNO

Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## ROLEDETAIL

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAIL	
Datatype		
Description	Maintenance	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

### CONTROL1

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL4

<b>Attribute</b>	<b>Description</b>
Name	CONTROL4

Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL6

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL8

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL8	
Datatype	decimal	
Description	Indicates Auth 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL10

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL11

Attribute		Description	
Name		CONTROL11	
Datatype		decimal	
Description		Indicates Confirm 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL12

Attribute		Description	
Name		CONTROL12	
Datatype		decimal	
Description		Indicates Liquidate 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL13

Attribute		Description	
Name		CONTROL13	
Datatype		decimal	
Description		Indicates Hold 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL14

Attribute		Description	
Name		CONTROL14	
Datatype		decimal	
Description		Indicates Template 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL15

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEDETAILB

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILB	
Datatype		
Description	Roles	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

### CONT1

<b>Attribute</b>	<b>Description</b>	
Name	CONT1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT2

<b>Attribute</b>	<b>Description</b>	
Name	CONT2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT3

<b>Attribute</b>	<b>Description</b>	
Name	CONT3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT4

<b>Attribute</b>	<b>Description</b>
Name	CONT4

Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT5

<b>Attribute</b>	<b>Description</b>	
Name	CONT5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONT6

<b>Attribute</b>	<b>Description</b>	
Name	CONT6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT8

<b>Attribute</b>	<b>Description</b>	
Name	CONT8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT9

<b>Attribute</b>	<b>Description</b>	
Name	CONT9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT10

<b>Attribute</b>	<b>Description</b>	
Name	CONT10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT11

Attribute		Description	
Name		CONT11	
Datatype		decimal	
Description		Indicates Confirm 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONT12

Attribute		Description	
Name		CONT12	
Datatype		decimal	
Description		Indicates Liquidate 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONT13

Attribute		Description	
Name		CONT13	
Datatype		decimal	
Description		Indicates Hold 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONT14

Attribute		Description	
Name		CONT14	
Datatype		decimal	
Description		Indicates Template 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONT15

<b>Attribute</b>	<b>Description</b>	
Name	CONT15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEDETAILC

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILC	
Datatype		
Description	Batch	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

### CNTRL1

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL2

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL3

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL4

<b>Attribute</b>	<b>Description</b>
Name	CNTRL4

Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL5

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL6

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL7

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL8

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL9

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL10

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL11

Attribute		Description	
Name		CNTRL11	
Datatype		decimal	
Description		Indicates Confirm 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CNTRL12

Attribute		Description	
Name		CNTRL12	
Datatype		decimal	
Description		Indicates Liquidate 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CNTRL13

Attribute		Description	
Name		CNTRL13	
Datatype		decimal	
Description		Indicates Hold 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CNTRL14

Attribute		Description	
Name		CNTRL14	
Datatype		decimal	
Description		Indicates Template 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL15

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL16

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEDETAILD

<b>Attribute</b>	<b>Description</b>	
Name	ROLEDETAILD	
Datatype		
Description	Roles	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ROLEFUN

<b>Attribute</b>	<b>Description</b>	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

### CONTROL1

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL1	
Datatype	decimal	
Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL2

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL4

<b>Attribute</b>	<b>Description</b>
Name	CONTROL4

Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL6

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL8

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL8	
Datatype	decimal	
Description	Indicates Auth 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL10

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CONTROL11

Attribute		Description	
Name		CONTROL11	
Datatype		decimal	
Description		Indicates Confirm 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL12

Attribute		Description	
Name		CONTROL12	
Datatype		decimal	
Description		Indicates Liquidate 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL13

Attribute		Description	
Name		CONTROL13	
Datatype		decimal	
Description		Indicates Hold 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0
Restrictions		<b>Restrictions</b>	
		<b>Description</b>	
		totalDigits	22
		minInclusive	0
		maxInclusive	1

## CONTROL14

Attribute		Description	
Name		CONTROL14	
Datatype		decimal	
Description		Indicates Template 1 - on 0 - Off	
Attribute		<b>Attribute</b>	
		<b>Description</b>	
		minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL15

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL16

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ROLEBRANCHES

<b>Attribute</b>	<b>Description</b>	
Name	ROLEBRANCHES	
Datatype		
Description	Branches	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	Indicates Branch	



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## BRNNAME

<b>Attribute</b>	<b>Description</b>	
Name	BRNNAME	
Datatype	string	
Description	Indicates Branch Name	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## ROLEACCCLASS

<b>Attribute</b>	<b>Description</b>	
Name	ROLEACCCLASS	
Datatype		
Description	Acc Class Restriction	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ACCCLS

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLS	
Datatype	string	
Description	Indicates Account Class	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Account Class Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## MSGCRIGHTS

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	MSGCRIGHTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## CNL

<b>Attribute</b>	<b>Description</b>	
Name	CNL	
Datatype	string	
Description	Indicates Cancel Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODE

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODE	
Datatype	string	
Description	Indicates Change Node Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REL

<b>Attribute</b>	<b>Description</b>	
Name	REL	
Datatype	string	
Description	Indicates Release Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIA

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIA	
Datatype	string	
Description	Indicates Change Media Y - on N - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOV

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOV	
Datatype	string	
Description	Indicates Branch Move Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLD

<b>Attribute</b>	<b>Description</b>	
Name	HLD	
Datatype	string	
Description	Indicates Hold Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINP

<b>Attribute</b>	<b>Description</b>	
Name	TSTINP	
Datatype	string	
Description	Indicates Test Input Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDR

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDR	
Datatype	string	
Description	Indicates Change Address Y - on N - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINS

<b>Attribute</b>	<b>Description</b>	
Name	REINS	
Datatype	string	
Description	Indicates Reinstatement Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIOR

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIOR	
Datatype	string	
Description	Indicates Change Priority Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNLAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CNLAUTH	
Datatype	string	
Description	Indicates Auth Cancel Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODEAUTH	
Datatype	string	
Description	Indicates Auth Change Node Y - on N - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## RELAUTH

<b>Attribute</b>	<b>Description</b>	
Name	RELAUTH	
Datatype	string	
Description	Indicates Release Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIAAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIAAUTH	
Datatype	string	
Description	Indicates Change Media Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOVAUTH

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOVAUTH	
Datatype	string	
Description	Indicates Auth Branch Move Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLDAUTH

<b>Attribute</b>	<b>Description</b>	
Name	HLDAUTH	
Datatype	string	

Description	Indicates Hold Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINPAUTH

<b>Attribute</b>	<b>Description</b>	
Name	TSTINPAUTH	
Datatype	string	
Description	Indicates Auth Test Input Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRAUTH	
Datatype	string	
Description	Indicates Change Address Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINSAUTH

<b>Attribute</b>	<b>Description</b>	
Name	REINSAUTH	
Datatype	string	
Description	Indicates Auth Reinstate Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIORAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIORAUTH	

Datatype	string	
Description	Indicates Change Priority Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## GEN

<b>Attribute</b>	<b>Description</b>	
Name	GEN	
Datatype	string	
Description	Indicates Install Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTCHK

<b>Attribute</b>	<b>Description</b>	
Name	TSTCHK	
Datatype	string	
Description	Indicates Test Check Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## LNKCONT

<b>Attribute</b>	<b>Description</b>	
Name	LNKCONT	
Datatype	string	
Description	Indicates Link Contract Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGBRNIN

<b>Attribute</b>	<b>Description</b>
Name	CHGBRNIN

Datatype	string	
Description	Indicates Change Branch In Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSG

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSG	
Datatype	string	
Description	Indicates Change Message Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGFORCRELFUND

<b>Attribute</b>	<b>Description</b>	
Name	CHGFORCRELFUND	
Datatype	string	
Description	Indicates Change Force Release Fund Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SUPPRESS

<b>Attribute</b>	<b>Description</b>	
Name	SUPPRESS	
Datatype	string	
Description	Indicates Suppress Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DELMSG



Attribute	Description	
Name	DELMSG	
Datatype	string	
Description	Indicates Delete Y - on N - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## PRNT

Attribute	Description	
Name	PRNT	
Datatype	string	
Description	Indicates Print Y - on N - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## FTUPL

Attribute	Description	
Name	FTUPL	
Datatype	string	
Description	Indicates FT Upload Y - on N - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## MOVQ

Attribute	Description	
Name	MOVQ	
Datatype	string	
Description	Indicates Move To Queue Y - on N - Off	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## CHGADDRIN

Attribute	Description	
Name	CHGADDRIN	
Datatype	string	
Description	Indicates Change Address In Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSGAUTH

Attribute	Description	
Name	CHGMSGAUTH	
Datatype	string	
Description	Indicates Auth Change Message Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## AUTHRGHTS

Attribute	Description	
Name	AUTHRGHTS	
Datatype	string	
Description	Indicates Auth Rights Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGFORCCOVMATCH

Attribute	Description	
Name	CHGFORCCOVMATCH	
Datatype	string	
Description	Indicates Change Force Cover Match Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## QUEUERIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	QUEUERIGHTS	
Datatype		
Description	Queues	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## QUEUE

<b>Attribute</b>	<b>Description</b>	
Name	QUEUE	
Datatype	string	
Description	Indicates Queue	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## RESTRICTIVEPASSWD

<b>Attribute</b>	<b>Description</b>	
Name	RESTRICTIVEPASSWD	
Datatype		
Description	Restricted Password	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PWD

<b>Attribute</b>	<b>Description</b>	
Name	PWD	
Datatype	string	
Description	Indicates Password	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## PWDID

<b>Attribute</b>	<b>Description</b>	
Name	PWDID	
Datatype	string	
Description	Indicates Id	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## ROLEBRANCHLIMITS

<b>Attribute</b>	<b>Description</b>	
Name	ROLEBRANCHLIMITS	
Datatype		
Description	User Limits	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxOccurs	unbounded

## LMTCCY

<b>Attribute</b>	<b>Description</b>	
Name	LMTCCY	
Datatype	string	
Description	Indicates Limit Currency	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## BRHUSERLMT

<b>Attribute</b>	<b>Description</b>	
Name	BRHUSERLMT	
Datatype	decimal	
Description	Indicates User Limit	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## Roledetaile

<b>Attribute</b>	<b>Description</b>	
Name	Roledetaile	
Datatype		
Description	Process Stage Rights	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxOccurs	unbounded

## ROLEFUN

Attribute	Description	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	string	
Description	Indicates Branch Code	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## EDITABLE

Attribute	Description	
Name	EDITABLE	
Datatype	decimal	
Description	Indicates Editable 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CNTRLSTR

Attribute	Description	
Name	CNTRLSTR	
Datatype	string	
Description	Indicates Control String	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

## Roledetailf

Attribute	Description	
Name	Roledetailf	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## ROLEID

Attribute	Description	
Name	ROLEID	
Datatype	string	
Description	Indicates Role Function	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	15

## ROLEFUN

Attribute	Description	
Name	ROLEFUN	
Datatype	string	
Description	Indicates Role Function	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8

## CNTRLSTR

Attribute	Description	
Name	CNTRLSTR	
Datatype	string	
Description	Indicates Control String	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	16

## CNTRL1

Attribute	Description
Name	CNTRL1
Datatype	decimal

Description	Indicates New 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL10

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL10	
Datatype	decimal	
Description	Indicates Rollover 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL11

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL11	
Datatype	decimal	
Description	Indicates Confirm 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

### CNTRL12

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL12	
Datatype	decimal	
Description	Indicates Liquidate 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL13**

Attribute	Description	
Name	CNTRL13	
Datatype	decimal	
Description	Indicates Hold 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL14**

Attribute	Description	
Name	CNTRL14	
Datatype	decimal	
Description	Indicates Template 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL15**

Attribute	Description	
Name	CNTRL15	
Datatype	decimal	
Description	Indicates View 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL16**

Attribute	Description	
Name	CNTRL16	
Datatype	decimal	
Description	Indicates Generate 1 - on 0 - Off	



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL2

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL2	
Datatype	decimal	
Description	Indicates Copy 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL3

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL3	
Datatype	decimal	
Description	Indicates Delete 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL4

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL4	
Datatype	decimal	
Description	Indicates Close 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL5**

Attribute	Description	
Name	CNTRL5	
Datatype	decimal	
Description	Indicates Unlock 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL6**

Attribute	Description	
Name	CNTRL6	
Datatype	decimal	
Description	Indicates Reopen 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL7**

Attribute	Description	
Name	CNTRL7	
Datatype	decimal	
Description	Indicates Print 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

**CNTRL8**

Attribute	Description	
Name	CNTRL8	
Datatype	decimal	
Description	Indicates Authorize 1 - on 0 - Off	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## CNTRL9

<b>Attribute</b>	<b>Description</b>	
Name	CNTRL9	
Datatype	decimal	
Description	Indicates Reverse 1 - on 0 - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	1

## ATHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	ATHSTAT	
Datatype	string	
Description	Indicates Authorization Status	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## BRNCHCODE

<b>Attribute</b>	<b>Description</b>	
Name	BRNCHCODE	
Datatype	string	
Description	Indicates Branch Code	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	maxOccurs	unbounded

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

## 2.22.QueryUserMaint

### 2.22.1.SM-QueryUserMaint-Req-IO-MSG.xsd

[\*QUERYUSERMAINT\\_IOFS\\_REQ\*](#)

[\*FCUBS\\_HEADER\*](#)

[\*SOURCE\*](#)

[\*UBSCOMP\*](#)

*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
     *NAME*  
     *VALUE*  
*FCUBS\_BODY*  
*USR-IO*  
     *USRID*  
     *DASHBOARD\_REQD*  
     *ALERTS\_ON\_HOME*  
     *Grp-Restriction*

**QUERYUSERMAINT\_IOFS\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	QUERYUSERMAINT_IOFS_REQ
Datatype	
Description	

**FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	

Description	
-------------	--

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of QueryUserMaint

## USR-IO

Attribute	Description
Name	USR-IO
Datatype	
Description	

## USRID

Attribute	Description				
Name	USRID				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## DASHBOARD\_REQD

Attribute	Description				
Name	DASHBOARD_REQD				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>Y,N</td></tr></tbody></table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## ALERTS\_ON\_HOME

Attribute	Description				
Name	ALERTS_ON_HOME				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### Grp-Restriction

<b>Attribute</b>	<b>Description</b>	
Name	Grp-Restriction	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### 2.22.2.SM-QueryUserMaint-Res-Full-MSG.xsd

*QUERYUSERMAINT\_IOFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*USR-IO*

*USRID*

*DASHBOARD\_REQD*

*ALERTS\_ON\_HOME*

*Grp-Restriction*

*USR-Full*

*STRTDATE*

*USRNAME*

*USRPWD*

*ENDDT*

*USRLANG*

*HOMEBRN*

*CUSTNO*

*LDAPUSR*

*TIMELEVEL*

*AUTOAUTH*

*USRSTAT*

*USRID*

*EXTUSRREF*

*USRCATEG*

*TILLALLOW*

*ACCCLSALLOW*

*GLALLOW*

*USRTXNLMT*

*LMTSCCY*

*MAXTXNAMT*

*MAXAUTHAMT*

*BRNSALLOW*

*PRDSALLOW*

*PRDSACCESALLOW*

*TAX\_IDENTIFIER*

*AMOUNT\_FORMAT*  
*DATE\_FORMAT*  
*STAFFACCRESR*  
*DEPT\_CODE*  
*DEPT\_DESC*  
*USRML*  
*ELCMUSER*  
*GROUP\_CODE*  
*MULTIBRN\_ACCESS*  
*OTH\_RM\_CUST\_ACC\_ALLOW*  
*SUPERVISOR\_ID*  
*SUPERVISOR\_NAME*  
*DASHBOARD\_REQD*  
*ALERTS\_ON\_HOME*  
*REFERENCE\_NO*  
*NO\_CUMULATIVE\_LOGINS*  
*NO\_SUCESSIVE\_LOGINS*  
*SCREENSAVERTIMEOUTINSECONDS*  
*NUMBER\_FORMAT\_MASK*  
*FRONTEND\_DEBUG\_ENABLED*  
*F10\_REQD*  
*F11\_REQD*  
*F12\_REQD*  
*MFI\_USER*  
*MFAENABLED*  
*MFAID*  
*ACCESS\_CONTROL*  
*EXTN\_ALERTS*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*

*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*RESTR\_PWD*  
*PWD*  
*MSGSRIGHTS*  
*GEN*  
*HLD*  
*CNL*  
*TSTINP*  
*CHGNODE*  
*CHGADDR*  
*REL*  
*REINS*  
*CHGMEDIA*  
*CHGPRIOR*  
*BRNMOV*  
*PRNT*  
*TSTCHK*  
*HLDAUTH*  
*CNLAUTH*  
*TSTINPAUTH*  
*CHGNODEAUTH*  
*CHGADDRAUTH*  
*RELAUTH*  
*REINSAUTH*  
*CHGMEDIAAUTH*  
*BRNMOVAUTH*  
*CHGPRIORAUTH*  
*FTUPL*  
*LNKCONT*  
*MOVQ*



*CHGBRNIN*  
*CHGADDRIN*  
*AUTHRGHTS*  
*CHGMSG*  
*CHGMSGAUTH*  
*CHGFORCCOVMATCH*  
*CHANGE\_FORCE\_RELEASE\_FUND*  
*SUPPRESS*  
*DELMSG*  
*QUEUERIGHTS*  
    *QUEUE*  
*USERTILLS*  
    *TILLID*  
    *TILLBRNCD*  
    *DESCRIPTION*  
*USERACCCLASS*  
    *ACCCLS*  
*USERGLREST*  
    *NODEGL*  
    *USERGLEXCEPT*  
        *EXCEPLEAFGL*  
*USERLIMITSROLE*  
    *LMTBRN*  
    *LMTSROLE*  
    *QLMTCCY*  
    *QINPLMT*  
    *QAUTHLMT*  
*USERBRANCHES*  
    *BRNSBRN*  
    *BRNNAME*  
*USERPRODUCTS*  
    *PRDPRDCD*

*PRDDESC*

*USERACCESSPRODUCTS*

*PRDACCESSPRDCD*

*PRDDESC*

*USERFUNCDISALLOW*

*FUNCDISALLOWFUNCID*

*USERROLE*

*ROLEBRNCD*

*USRROLEID*

*MASTERROLEDESC*

*USERSFUNCTIONS*

*USERFUNCBRNCD*

*USERFUNCFUNCID*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*USERFUNCSCTRL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CONTROL15*

*CONTROL16*

*Grp-Restriction*

*GROUP\_CODE*

*GROUP\_DESC*

*Centralisation*

*USRROLEID*

*ROLDESC*

*Dshmst*

*USRID*

*USRNAME*

*Dshdet*

*FUNCTIONID*

*DESCRIPTION*

*SEQUENCE\_NO*

*DBWHERECLAUSE*

*SHOW\_IN\_DASHBOARD*

*Where-Master*

*COLUMN\_NAME*

*WHERE\_CL*

*CONDITION*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

**QUERYUSERMAINT\_IOFS\_RES**

<b>Attribute</b>	<b>Description</b>
Name	QUERYUSERMAINT_IOFS_RES
Datatype	
Description	

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		



## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

## USR-IO

Attribute	Description
Name	USR-IO
Datatype	
Description	

## USRID

Attribute	Description				
Name	USRID				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## DASHBOARD\_REQD

Attribute	Description				
Name	DASHBOARD_REQD				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>Y,N</td></tr></tbody></table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## ALERTS\_ON\_HOME

Attribute	Description				
Name	ALERTS_ON_HOME				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### Grp-Restriction

<b>Attribute</b>	<b>Description</b>	
Name	Grp-Restriction	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### USR-Full

<b>Attribute</b>	<b>Description</b>
Name	USR-Full
Datatype	
Description	

### STRTDATE

<b>Attribute</b>	<b>Description</b>
Name	STRTDATE
Datatype	String
Description	

### USRNAME

<b>Attribute</b>	<b>Description</b>	
Name	USRNAME	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

### USRPWD

<b>Attribute</b>	<b>Description</b>	
Name	USRPWD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	32

### ENDDT

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	ENDDT	
Datatype	String	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## USRLANG

<b>Attribute</b>	<b>Description</b>	
Name	USRLANG	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## HOMEBRN

<b>Attribute</b>	<b>Description</b>	
Name	HOMEBRN	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## CUSTNO

<b>Attribute</b>	<b>Description</b>	
Name	CUSTNO	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## LDAPUSR

<b>Attribute</b>	<b>Description</b>	
Name	LDAPUSR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	500

## TIMELEVEL

Attribute	Description	
Name	TIMELEVEL	
Datatype	decimal	
Description		
Restrictions		
	Restrictions	Description
	totalDigits	22
	minInclusive	0
	maxInclusive	9

## AUTOAUTH

Attribute	Description	
Name	AUTOAUTH	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

## USRSTAT

Attribute	Description	
Name	USRSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	E,H,D,L

## USRID

Attribute	Description	
Name	USRID	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	12

## EXTUSRREF

Attribute	Description	
Name	EXTUSRREF	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## USRCATEG

<b>Attribute</b>	<b>Description</b>	
Name	USRCATEG	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	S,B

## TILLALLOW

<b>Attribute</b>	<b>Description</b>	
Name	TILLALLOW	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## ACCCLSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLSALLOW	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## GLALLOW

<b>Attribute</b>	<b>Description</b>	
Name	GLALLOW	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## USRTXNLMT

<b>Attribute</b>	<b>Description</b>	
Name	USRTXNLMT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,R,N

## LMTSCCY

<b>Attribute</b>	<b>Description</b>	
Name	LMTSCCY	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## MAXTXNAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXTXNAMT	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## MAXAUTHAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXAUTHAMT	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### BRNSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	BRNSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### PRDSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### PRDSACCESALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSACCESALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### TAX\_IDENTIFIER

<b>Attribute</b>	<b>Description</b>	
Name	TAX_IDENTIFIER	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

## AMOUNT\_FORMAT

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_FORMAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	*****

## DATE\_FORMAT

<b>Attribute</b>	<b>Description</b>	
Name	DATE_FORMAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	M/d/yyyy

## STAFFACCRESTR

<b>Attribute</b>	<b>Description</b>	
Name	STAFFACCRESTR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DEPT\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	DEPT_CODE	
Datatype	string	
Description		



Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## DEPT\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	DEPT_DESC	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## USRML

<b>Attribute</b>	<b>Description</b>	
Name	USRML	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## ELCMUSER

<b>Attribute</b>	<b>Description</b>	
Name	ELCMUSER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## GROUP\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_CODE	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### MULTIBRN\_ACCESS

<b>Attribute</b>	<b>Description</b>	
Name	MULTIBRN_ACCESS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### OTH\_RM\_CUST\_ACC\_ALLOW

<b>Attribute</b>	<b>Description</b>	
Name	OTH_RM_CUST_ACC_ALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### SUPERVISOR\_ID

<b>Attribute</b>	<b>Description</b>	
Name	SUPERVISOR_ID	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	80

### SUPERVISOR\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	SUPERVISOR_NAME	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## DASHBOARD\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	DASHBOARD_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## ALERTS\_ON\_HOME

<b>Attribute</b>	<b>Description</b>	
Name	ALERTS_ON_HOME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REFERENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	REFERENCE_NO	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## NO\_CUMULATIVE\_LOGINS

<b>Attribute</b>	<b>Description</b>	
Name	NO_CUMULATIVE_LOGINS	
Datatype	decimal	
Description		

Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	<b>Description</b>	

## NO\_SUCCESSIVE\_LOGINS

<b>Attribute</b>		<b>Description</b>
Name	NO_SUCCESSIVE_LOGINS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	<b>Description</b>	

## SCREENSAVERTIMEOUTINSECONDS

<b>Attribute</b>		<b>Description</b>
Name	SCREENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	totalDigits	22
	<b>Description</b>	

## NUMBER\_FORMAT\_MASK

<b>Attribute</b>		<b>Description</b>
Name	NUMBER_FORMAT_MASK	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	enumeration	M,L
	<b>Description</b>	

## FRONTEND\_DEBUG\_ENABLED

<b>Attribute</b>		<b>Description</b>
Name	FRONTEND_DEBUG_ENABLED	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F10\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F10_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F11\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F11_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F12\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F12_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### MFI\_USER

<b>Attribute</b>	<b>Description</b>	
Name	MFI_USER	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MFAENABLED

<b>Attribute</b>	<b>Description</b>	
Name	MFAENABLED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	N,Y,L

## MFAID

<b>Attribute</b>	<b>Description</b>	
Name	MFAID	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

## ACCESS\_CONTROL

<b>Attribute</b>	<b>Description</b>	
Name	ACCESS_CONTROL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,G,B

## EXTN\_ALERTS

<b>Attribute</b>	<b>Description</b>	
Name	EXTN_ALERTS	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## RESTR\_PWD

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_PWD	
Datatype		
Description		



Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

**PWD**

<b>Attribute</b>	<b>Description</b>	
Name	PWD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

**MSGSRIGHTS**

<b>Attribute</b>	<b>Description</b>	
Name	MSGSRIGHTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

**GEN**

<b>Attribute</b>	<b>Description</b>	
Name	GEN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

**HLD**

<b>Attribute</b>	<b>Description</b>	
Name	HLD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

**CNL**

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CNL	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINP

<b>Attribute</b>	<b>Description</b>	
Name	TSTINP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODE

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDR

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDR	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REL

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	REL	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINS

<b>Attribute</b>	<b>Description</b>	
Name	REINS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIA

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIA	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIOR

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIOR	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOV

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	BRNMOV	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PRNT

<b>Attribute</b>	<b>Description</b>	
Name	PRNT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTCHK

<b>Attribute</b>	<b>Description</b>	
Name	TSTCHK	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLDAUTH

<b>Attribute</b>	<b>Description</b>	
Name	HLDAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNLAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CNLAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINPAUTH

<b>Attribute</b>	<b>Description</b>	
Name	TSTINPAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODEAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## RELAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	RELAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINSAUTH

<b>Attribute</b>	<b>Description</b>	
Name	REINSAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIAAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIAAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOVAUTH

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOVAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIORAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CHGPRIORAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## FTUPL

<b>Attribute</b>	<b>Description</b>	
Name	FTUPL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## LNKCONT

<b>Attribute</b>	<b>Description</b>	
Name	LNKCONT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MOVQ

<b>Attribute</b>	<b>Description</b>	
Name	MOVQ	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGBRNIN

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	CHGBRNIN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRIN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## AUTHRGHTS

<b>Attribute</b>	<b>Description</b>	
Name	AUTHRGHTS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSG

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSGAUTH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	CHGMSGAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHGFORCCOVMATCH

<b>Attribute</b>	<b>Description</b>	
Name	CHGFORCCOVMATCH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHANGE\_FORCE\_RELEASE\_FUND

<b>Attribute</b>	<b>Description</b>	
Name	CHANGE_FORCE_RELEASE_FUND	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### SUPPRESS

<b>Attribute</b>	<b>Description</b>	
Name	SUPPRESS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### DELMSG

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	DELMSG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## QUEUERIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	QUEUERIGHTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## QUEUE

<b>Attribute</b>	<b>Description</b>	
Name	QUEUE	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## USERTILLS

<b>Attribute</b>	<b>Description</b>	
Name	USERTILLS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## TILLID

<b>Attribute</b>	<b>Description</b>	
Name	TILLID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## TILLBRNCD

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	TILLBRNCD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

## USERACCCLASS

<b>Attribute</b>	<b>Description</b>	
Name	USERACCCLASS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ACCCLS

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLS	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

## USERGLREST

<b>Attribute</b>	<b>Description</b>	
Name	USERGLREST	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NODEGL

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	NODEGL	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## USERGLEXCEPT

<b>Attribute</b>	<b>Description</b>	
Name	USERGLEXCEPT	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## EXCEPLEAFGL

<b>Attribute</b>	<b>Description</b>	
Name	EXCEPLEAFGL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## USERLIMITSROLE

<b>Attribute</b>	<b>Description</b>	
Name	USERLIMITSROLE	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## LMTBRN

<b>Attribute</b>	<b>Description</b>	
Name	LMTBRN	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## LMTSROLE

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	LMTSROLE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

### QLMTCCY

<b>Attribute</b>	<b>Description</b>	
Name	QLMTCCY	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### QINPLMT

<b>Attribute</b>	<b>Description</b>	
Name	QINPLMT	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### QAUHLMT

<b>Attribute</b>	<b>Description</b>	
Name	QAUHLMT	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### USERBRANCHES

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	USERBRANCHES	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	maxOccurs	unbounded

### BRNSBRN

<b>Attribute</b>	<b>Description</b>	
Name	BRNSBRN	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	3

### BRNNAME

<b>Attribute</b>	<b>Description</b>	
Name	BRNNAME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	105

### USERPRODUCTS

<b>Attribute</b>	<b>Description</b>	
Name	USERPRODUCTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	maxOccurs	unbounded

### PRDPRDCD

<b>Attribute</b>	<b>Description</b>	
Name	PRDPRDCD	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	4

### PRDDESC

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	PRDESC	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## USERACCESSPRODUCTS

<b>Attribute</b>	<b>Description</b>	
Name	USERACCESSPRODUCTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PRDACCESSPRDCD

<b>Attribute</b>	<b>Description</b>	
Name	PRDACCESSPRDCD	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

## PRDESC

<b>Attribute</b>	<b>Description</b>	
Name	PRDESC	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## USERFUNCDISALLOW

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCDISALLOW	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FUNCDISALLOWFUNCID

Attribute	Description				
Name	FUNCDISALLOWFUNCID				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr></tbody></table>	Restrictions	Description	maxLength	8
Restrictions	Description				
maxLength	8				

## USERROLE

Attribute	Description						
Name	USERROLE						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## ROLEBRNCD

Attribute	Description				
Name	ROLEBRNCD				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## USRROLEID

Attribute	Description				
Name	USRROLEID				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## MASTERROLEDESC

Attribute	Description				
Name	MASTERROLEDESC				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>45</td></tr></tbody></table>	Restrictions	Description	maxLength	45
Restrictions	Description				
maxLength	45				

## USERSFUNCTIONS



Attribute	Description	
Name	USERSFUNCTIONS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## USERFUNCBRNCD

Attribute	Description	
Name	USERFUNCBRNCD	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

## USERFUNCFUNCID

Attribute	Description	
Name	USERFUNCFUNCID	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	8

## CONTROL1

Attribute	Description	
Name	CONTROL1	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

## CONTROL2

Attribute	Description	
Name	CONTROL2	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL4

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL4	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL6

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL6	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL8

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL8	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## USERFUNCCTRL10

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCCTRL10	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL11

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL11	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL12

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL12	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL13

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL13	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL14

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL14	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL15

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL15	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## Grp-Restriction

<b>Attribute</b>	<b>Description</b>	
Name	Grp-Restriction	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## GROUP\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_CODE	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

## GROUP\_DESC

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	GROUP_DESC	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	255
	<b>Description</b>	

## Centralisation

<b>Attribute</b>	<b>Description</b>	
Name	Centralisation	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## USRROLEID

<b>Attribute</b>	<b>Description</b>	
Name	USRROLEID	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	15
	<b>Description</b>	

## ROLDESC

<b>Attribute</b>	<b>Description</b>	
Name	ROLDESC	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	20
	<b>Description</b>	

## Dshmst

<b>Attribute</b>	<b>Description</b>	
Name	Dshmst	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	

## USRID

Attribute	Description	
Name	USRID	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## USRNAME

Attribute	Description	
Name	USRNAME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## Dshdet

Attribute	Description	
Name	Dshdet	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## DESCRIPTION

Attribute	Description
-----------	-------------

Name	DESCRIPTION	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1000

## SEQUENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	SEQUENCE_NO	
Datatype	decimal	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## DBWHERECLAUSE

<b>Attribute</b>	<b>Description</b>	
Name	DBWHERECLAUSE	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

## SHOW\_IN\_DASHBOARD

<b>Attribute</b>	<b>Description</b>	
Name	SHOW_IN_DASHBOARD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## Where-Master

<b>Attribute</b>	<b>Description</b>	
Name	Where-Master	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## COLUMN\_NAME



Attribute		Description	
Name	COLUMN_NAME		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	2000	

## WHERE\_CL

Attribute		Description	
Name	WHERE_CL		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	500	

## CONDITION

Attribute		Description	
Name	CONDITION		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	30	

## UDFDETAILS

Attribute		Description	
Name	UDFDETAILS		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
	maxOccurs	unbounded	

## FLDNAM

Attribute		Description	
Name	FLDNAM		

Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

## 2.23.ReopenSMDBANKP

### 2.23.1.SM-ReopenSMDBANKP-Req-Full-MSG.xsd

*REOPENSMDBANKP\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Smtbs-Parameters-Full*  
*HEAD\_OFFICE*  
*SITE\_CODE*  
*ACTIVATION\_KEY*  
*INVALID\_LOGINS\_CUM*  
*INVALID\_LOGINS\_SUC*  
*PWD\_PREVENT\_REUSE*  
*PWD\_CHANGE\_AFTER*  
*MAXIMUM*  
*MINIMUM*  
*PWD\_EXPIRY\_MSG\_DAYS*  
*ARCHIVAL\_PERIOD*  
*CONCHAR\_PWD\_NUM*  
*FREQ\_PWD\_CHG*  
*MIN\_PWD\_NUMERIC\_LENGTH*  
*LEGAL\_NOTICE*  
*DORMANCY\_DAYS*  
*DISPLAY\_LEGAL\_NOTICE*  
*MIN\_SPECIALCHAR\_LENGTH*

*MIN\_LOWERCASE\_CHAR*  
*MIN\_UPPERCASE\_CHAR*  
*SCRENSAVERREQUIRED*  
*SCRENSAVERTIMEOUTINSECONDS*  
*SCRENSAVERMODIFIABLEBYUSER*  
*PASSWORDEXTERNAL*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*Smtbs-Branch-Restr*  
*RESTR\_TYPE*  
*DESCRIPTION*  
*Smtbs-Restrictive-Passwd*  
*PASSWORD*  
*UDFDETAILS*  
*FLDNAM*  
*FLDVAL*

## REOPENSMDBANKP\_FSFS\_REQ

Attribute	Description
Name	REOPENSMDBANKP_FSFS_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages this field has to contain the source code for the partner system as maintained within EL EXCLUDE UBS. In

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

Attribute	Description



Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of ReopenSMDBANKP

## Smtbs-Parameters-Full

Attribute	Description
Name	Smtbs-Parameters-Full
Datatype	
Description	

## HEAD\_OFFICE

Attribute	Description				
Name	HEAD_OFFICE				
Datatype	string				
Description	Indicates Head Office				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## SITE\_CODE

Attribute	Description				
Name	SITE_CODE				
Datatype	string				
Description	Indicates Site Code				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>4</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	4
Restrictions	Description				
maxLength	4				

## ACTIVATION\_KEY

Attribute	Description				
Name	ACTIVATION_KEY				
Datatype	string				
Description	Indicates Activation Key				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>24</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	24
Restrictions	Description				
maxLength	24				

## INVALID\_LOGINS\_CUM

Attribute	Description

Name	INVALID_LOGINS_CUM	
Datatype	decimal	
Description	Indicates Cumulative	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	6
	maxInclusive	99

## INVALID\_LOGINS\_SUC

<b>Attribute</b>	<b>Description</b>	
Name	INVALID_LOGINS_SUC	
Datatype	decimal	
Description	Indicates Successive	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	1
	minInclusive	3
	maxInclusive	5

## PWD\_PREVENT\_REUSE

<b>Attribute</b>	<b>Description</b>	
Name	PWD_PREVENT_REUSE	
Datatype	decimal	
Description	Indicates Password Repetitions	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## PWD\_CHANGE\_AFTER

<b>Attribute</b>	<b>Description</b>	
Name	PWD_CHANGE_AFTER	
Datatype	decimal	
Description	Indicates Force Password Change After	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	3
	minInclusive	15
	maxInclusive	180

## MAXIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MAXIMUM	
Datatype	decimal	
Description	Indicates Maximum	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	12
	maxInclusive	30

## MINIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MINIMUM	
Datatype	decimal	
Description	Indicates Minimum	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	6
	maxInclusive	11

## PWD\_EXPIRY\_MSG\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	PWD_EXPIRY_MSG_DAYS	
Datatype	decimal	
Description	Indicates Intimate User (Before Password Expiry)	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1
	maxInclusive	5

## ARCHIVAL\_PERIOD

<b>Attribute</b>	<b>Description</b>	
Name	ARCHIVAL_PERIOD	
Datatype	decimal	
Description	Indicates Archival Period (in days)	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	3

### CONCHAR\_PWD\_NUM

<b>Attribute</b>	<b>Description</b>	
Name	CONCHAR_PWD_NUM	
Datatype	decimal	
Description	Indicates Maximum Consecutive Repetitive Characters	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2

### FREQ\_PWD\_CHG

<b>Attribute</b>	<b>Description</b>	
Name	FREQ_PWD_CHG	
Datatype	decimal	
Description	Indicates Minimum Days Between Password Changes	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	0

### MIN\_PWD\_NUMERIC\_LENGTH

<b>Attribute</b>	<b>Description</b>	
Name	MIN_PWD_NUMERIC_LENGTH	
Datatype	decimal	
Description	Indicates Minimum Number Of Numeric Characters In Password	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### LEGAL\_NOTICE

<b>Attribute</b>	<b>Description</b>	
Name	LEGAL_NOTICE	
Datatype	string	
Description	Indicates Warning Screen Text	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

## DORMANCY\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	DORMANCY_DAYS	
Datatype	decimal	
Description	Indicates Dormancy Days	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## DISPLAY\_LEGAL\_NOTICE

<b>Attribute</b>	<b>Description</b>	
Name	DISPLAY_LEGAL_NOTICE	
Datatype	string	
Description	Indicates Display Legal Notice Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MIN\_SPECIALCHAR\_LENGTH

<b>Attribute</b>	<b>Description</b>	
Name	MIN_SPECIALCHAR_LENGTH	
Datatype	decimal	
Description	Indicates Minimum Number Of Special Characters In Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## MIN\_LOWERCASE\_CHAR

<b>Attribute</b>	<b>Description</b>	
Name	MIN_LOWERCASE_CHAR	
Datatype	decimal	
Description	Indicates Minimum Number of LowerCase Characters in Password	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### MIN\_UPPERCASE\_CHAR

<b>Attribute</b>	<b>Description</b>	
Name	MIN_UPPERCASE_CHAR	
Datatype	decimal	
Description	Indicates Minimum Number of UpperCase Characters in Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### SCRENSAVERREQUIRED

<b>Attribute</b>	<b>Description</b>	
Name	SCRENSAVERREQUIRED	
Datatype	string	
Description	Indicates Screensaver Required Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### SCRENSAVERTIMEOUTINSECONDS

<b>Attribute</b>	<b>Description</b>	
Name	SCRENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description	Indicates Screensaver Interval (in seconds)	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

### SCRENSAVERMODIFIABLEBYUSER

<b>Attribute</b>	<b>Description</b>	
Name	SCRENSAVERMODIFIABLEBYUSER	
Datatype	string	
Description	Indicates Screensaver Interval Modifiable at User Level Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PASSWORDEXTERNAL

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORDEXTERNAL	
Datatype	string	
Description	Indicates Password External Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

### Smtbs-Branch-Restr

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Branch-Restr	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### RESTR\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_TYPE	
Datatype	string	
Description	Indicates Restriction Type	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Restriction Type Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

### Smtbs-Restrictive-Passwd

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Restrictive-Passwd	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description	Indicates Password	
Restrictions		
	Restrictions	Description
	maxLength	12

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.23.2.SM-ReopenSMDBANKP-Req-IO-MSG.xsd

*REOPENSMDBANKP\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Smtbs-Parameters-IO*  
*SITE\_CODE*  
*MAKER*  
*MAKERSTAMP*  
*MODNO*

**REOPENSMDBANKP\_IOPK\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	REOPENSMDBANKP_IOPK_REQ
Datatype	
Description	

**FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	string	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of ReopenSMD BANKP

## Smtbs-Parameters-IO

Attribute	Description
Name	Smtbs-Parameters-IO
Datatype	
Description	

## SITE\_CODE

Attribute	Description				
Name	SITE_CODE				
Datatype	string				
Description	Indicates Site Code				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>4</td></tr></tbody></table>	Restrictions	Description	maxLength	4
Restrictions	Description				
maxLength	4				

## MAKER

Attribute	Description				
Name	MAKER				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

### 2.23.3.SM-ReopenSMDBANKP-Res-Full-MSG.xsd

*REOPENSMDBANKP\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Parameters-Full*

*HEAD\_OFFICE*

*SITE\_CODE*

*ACTIVATION\_KEY*

*INVALID\_LOGINS\_CUM*

*INVALID\_LOGINS\_SUC*

*PWD\_PREVENT\_REUSE*

*PWD\_CHANGE\_AFTER*

*MAXIMUM*

*MINIMUM*

*PWD\_EXPIRY\_MSG\_DAYS*

*ARCHIVAL\_PERIOD*

*CONCHAR\_PWD\_NUM*

*FREQ\_PWD\_CHG*

*MIN\_PWD\_NUMERIC\_LENGTH*

*LEGAL\_NOTICE*

*DORMANCY\_DAYS*

*DISPLAY\_LEGAL\_NOTICE*

*MIN\_SPECIALCHAR\_LENGTH*

*MIN\_LOWERCASE\_CHAR*

*MIN\_UPPERCASE\_CHAR*

*SCREESAVERREQUIRED*

*SCREESAVERTIMEOUTINSECONDS*

*SCREESAVERMODIFIABLEBYUSER*

*PASSWORDEXTERNAL*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Smtbs-Branch-Restr*

*RESTR\_TYPE*

*DESCRIPTION*

*Smtbs-Restrictive-Passwd*

*PASSWORD*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## **REOPENSMDBANKP\_FSFS\_RES**

<b>Attribute</b>	<b>Description</b>
Name	REOPENSMDBANKP_FSFS_RES
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

<b>Attribute</b>	<b>Description</b>
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION



Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

Attribute	Description

Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

## Smtbs-Parameters-Full

Attribute	Description
Name	Smtbs-Parameters-Full
Datatype	
Description	

## HEAD\_OFFICE

Attribute	Description				
Name	HEAD_OFFICE				
Datatype	string				
Description	Indicates Head Office				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## SITE\_CODE

Attribute	Description				
Name	SITE_CODE				
Datatype	string				
Description	Indicates Site Code				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>4</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	4
Restrictions	Description				
maxLength	4				

## ACTIVATION\_KEY

Attribute	Description				
Name	ACTIVATION_KEY				
Datatype	string				
Description	Indicates Activation Key				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>24</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	24
Restrictions	Description				
maxLength	24				

## INVALID\_LOGINS\_CUM

Attribute	Description

Name	INVALID_LOGINS_CUM	
Datatype	decimal	
Description	Indicates Cumulative	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	6
	maxInclusive	99

## INVALID\_LOGINS\_SUC

<b>Attribute</b>	<b>Description</b>	
Name	INVALID_LOGINS_SUC	
Datatype	decimal	
Description	Indicates Successive	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	1
	minInclusive	3
	maxInclusive	5

## PWD\_PREVENT\_REUSE

<b>Attribute</b>	<b>Description</b>	
Name	PWD_PREVENT_REUSE	
Datatype	decimal	
Description	Indicates Password Repetitions	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## PWD\_CHANGE\_AFTER

<b>Attribute</b>	<b>Description</b>	
Name	PWD_CHANGE_AFTER	
Datatype	decimal	
Description	Indicates Force Password Change After	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	3
	minInclusive	15
	maxInclusive	180

## MAXIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MAXIMUM	
Datatype	decimal	
Description	Indicates Maximum	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	12
	maxInclusive	30

## MINIMUM

<b>Attribute</b>	<b>Description</b>	
Name	MINIMUM	
Datatype	decimal	
Description	Indicates Minimum	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	6
	maxInclusive	11

## PWD\_EXPIRY\_MSG\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	PWD_EXPIRY_MSG_DAYS	
Datatype	decimal	
Description	Indicates Intimate User (Before Password Expiry)	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1
	maxInclusive	5

## ARCHIVAL\_PERIOD

<b>Attribute</b>	<b>Description</b>	
Name	ARCHIVAL_PERIOD	
Datatype	decimal	
Description	Indicates Archival Period (in days)	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	3

### CONCHAR\_PWD\_NUM

<b>Attribute</b>	<b>Description</b>	
Name	CONCHAR_PWD_NUM	
Datatype	decimal	
Description	Indicates Maximum Consecutive Repetitive Characters	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2

### FREQ\_PWD\_CHG

<b>Attribute</b>	<b>Description</b>	
Name	FREQ_PWD_CHG	
Datatype	decimal	
Description	Indicates Minimum Days Between Password Changes	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	0

### MIN\_PWD\_NUMERIC\_LENGTH

<b>Attribute</b>	<b>Description</b>	
Name	MIN_PWD_NUMERIC_LENGTH	
Datatype	decimal	
Description	Indicates Minimum Number Of Numeric Characters In Password	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### LEGAL\_NOTICE

<b>Attribute</b>	<b>Description</b>	
Name	LEGAL_NOTICE	
Datatype	string	
Description	Indicates Warning Screen Text	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

## DORMANCY\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	DORMANCY_DAYS	
Datatype	decimal	
Description	Indicates Dormancy Days	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## DISPLAY\_LEGAL\_NOTICE

<b>Attribute</b>	<b>Description</b>	
Name	DISPLAY_LEGAL_NOTICE	
Datatype	string	
Description	Indicates Display Legal Notice Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MIN\_SPECIALCHAR\_LENGTH

<b>Attribute</b>	<b>Description</b>	
Name	MIN_SPECIALCHAR_LENGTH	
Datatype	decimal	
Description	Indicates Minimum Number Of Special Characters In Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

## MIN\_LOWERCASE\_CHAR

<b>Attribute</b>	<b>Description</b>	
Name	MIN_LOWERCASE_CHAR	
Datatype	decimal	
Description	Indicates Minimum Number of LowerCase Characters in Password	



Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### MIN\_UPPERCASE\_CHAR

<b>Attribute</b>	<b>Description</b>	
Name	MIN_UPPERCASE_CHAR	
Datatype	decimal	
Description	Indicates Minimum Number of UpperCase Characters in Password	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	2
	minInclusive	1

### SCRENSAVERREQUIRED

<b>Attribute</b>	<b>Description</b>	
Name	SCRENSAVERREQUIRED	
Datatype	string	
Description	Indicates Screensaver Required Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### SCRENSAVERTIMEOUTINSECONDS

<b>Attribute</b>	<b>Description</b>	
Name	SCRENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description	Indicates Screensaver Interval (in seconds)	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

### SCRENSAVERMODIFIABLEBYUSER

<b>Attribute</b>	<b>Description</b>	
Name	SCRENSAVERMODIFIABLEBYUSER	
Datatype	string	
Description	Indicates Screensaver Interval Modifiable at User Level Y - on N - Off	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PASSWORDEXTERNAL

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORDEXTERNAL	
Datatype	string	
Description	Indicates Password External Y - on N - Off	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

### Smtbs-Branch-Restr

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Branch-Restr	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### RESTR\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_TYPE	
Datatype	string	
Description	Indicates Restriction Type	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description	Indicates Restriction Type Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

### Smtbs-Restrictive-Passwd

<b>Attribute</b>	<b>Description</b>	
Name	Smtbs-Restrictive-Passwd	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description	Indicates Password	
Restrictions	Restrictions	Description
	maxLength	12

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String

*2.23.4.SM-ReopenSMDBANKP-Res-PK-MSG.xsd**REOPENSMDBANKP\_IOPK\_RES**FCUBS\_HEADER**SOURCE**UBSCOMP**MSGID**CORRELID**USERID**BRANCH**MODULEID**SERVICE**OPERATION**SOURCE\_OPERATION**SOURCE\_USERID**DESTINATION**MULTITRIPID**FUNCTIONID**ACTION**MSGSTAT**PASSWORD**ADDL**PARAM**NAME**VALUE**FCUBS\_BODY**Smtbs-Parameters-PK**SITE\_CODE**Smtbs-Parameters-IO**SITE\_CODE**MAKER**MAKERSTAMP**MODNO*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## REOPENSMDBANKP\_IOPK\_RES

Attribute	Description
Name	REOPENSMDBANKP_IOPK_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				



Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

Attribute		Description	
Name	ADDL		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

## PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

## NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

## VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

## FCUBS\_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description	This XSD Gives Information about PK Response		

## Smtbs-Parameters-PK

Attribute		Description	
Name	Smtbs-Parameters-PK		
Datatype			
Description			

## SITE\_CODE

Attribute		Description	
Name	SITE_CODE		
Datatype	string		
Description	Indicates Site Code		

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

### Smtbs-Parameters-IO

<b>Attribute</b>	<b>Description</b>
Name	Smtbs-Parameters-IO
Datatype	
Description	

### SITE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	SITE_CODE	
Datatype	string	
Description	Indicates Site Code	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

### MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

### MODNO

<b>Attribute</b>	<b>Description</b>
Name	MODNO
Datatype	decimal
Description	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## WARNING

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	WARNING	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

## 2.24.ReopenSMDRLMNE

### 2.24.1.SM-ReopenSMDRLMNE-Req-Full-MSG.xsd

*REOPENSMDRLMNE\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*



*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Role-Limit-Full*

*ROLEID2*

*DESCRIPTION*

*LIMIT\_CCY*

*INPUT\_LIMIT*

*AUTHORIZATION\_LIMIT*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

## **REOPENSMDRLMNE\_FSFS\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	REOPENSMDRLMNE_FSFS_REQ
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

<b>Attribute</b>	<b>Description</b>
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages this field has to contain the source code for the partner system as maintained within EL EXCLUDE LIBS. In

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

Attribute	Description

Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of ReopenSMDRLMNE

## Smtbs-Role-Limit-Full

Attribute	Description
Name	Smtbs-Role-Limit-Full
Datatype	
Description	

## ROLEID2

Attribute	Description				
Name	ROLEID2				
Datatype	string				
Description	Indicates Role Id				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>15</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## DESCRIPTION

Attribute	Description				
Name	DESCRIPTION				
Datatype	string				
Description	Indicates Description				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>105</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

## LIMIT\_CCY

Attribute	Description				
Name	LIMIT_CCY				
Datatype	string				
Description	Indicates Limit Currency				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## INPUT\_LIMIT

Attribute	Description
Name	INPUT_LIMIT
Datatype	decimal
Description	Indicates Input Limit

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0

## AUTHORIZATION\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHORIZATION_LIMIT	
Datatype	decimal	
Description	Indicates Authorization Limit	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

### 2.24.2.SM-ReopenSMDRLMNE-Req-IO-MSG.xsd

*REOPENSMDRLMNE\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Role-Limit-IO*

*ROLEID2*

*MAKER*

*MAKERSTAMP*

*MODNO*

## REOPENSMDRLMNE\_IOPK\_REQ

Attribute	Description
Name	REOPENSMDRLMNE_IOPK_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages this field has to contain the source code for the partner system as maintained within EL EXCLUDE UBS. In

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

Attribute	Description

Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	



Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of ReopenSMDRLMNE

## Smtbs-Role-Limit-IO

Attribute	Description
Name	Smtbs-Role-Limit-IO
Datatype	
Description	

## ROLEID2

Attribute	Description				
Name	ROLEID2				
Datatype	string				
Description	Indicates Role Id				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>15</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## MAKER

Attribute	Description				
Name	MAKER				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

## MODNO

Attribute	Description

Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

2.24.3.SM-ReopenSMDRLMNE-Res-Full-MSG.xsd

*REOPENSMDRLMNE\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Smtbs-Role-Limit-Full*

*ROLEID2*

*DESCRIPTION*

*LIMIT\_CCY*

*INPUT\_LIMIT*

*AUTHORIZATION\_LIMIT*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## **REOPENSMDRLMNE\_FSFS\_RES**

<b>Attribute</b>	<b>Description</b>
Name	REOPENSMDRLMNE_FSFS_RES
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	string	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		



## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

## Smtbs-Role-Limit-Full

Attribute	Description
Name	Smtbs-Role-Limit-Full
Datatype	
Description	

## ROLEID2

Attribute	Description				
Name	ROLEID2				
Datatype	string				
Description	Indicates Role Id				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## DESCRIPTION

Attribute	Description				
Name	DESCRIPTION				
Datatype	string				
Description	Indicates Description				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

## LIMIT\_CCY

Attribute	Description				
Name	LIMIT_CCY				
Datatype	string				
Description	Indicates Limit Currency				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## INPUT\_LIMIT

Attribute	Description	
Name	INPUT_LIMIT	
Datatype	decimal	
Description	Indicates Input Limit	
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	22
	minInclusive	0

## AUTHORIZATION\_LIMIT

Attribute	Description	
Name	AUTHORIZATION_LIMIT	
Datatype	decimal	
Description	Indicates Authorization Limit	
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	totalDigits	22
	minInclusive	0

## MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	12

## MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	35

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxOccurs	unbounded

## ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String

Description	
-------------	--

#### 2.24.4.SM-ReopenSMDRLMNE-Res-PK-MSG.xsd

### *REOPENSMDRLMNE\_IOPK\_RES*

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

*Smtbs-Role-Limit-PK*

*ROLEID2*

*Smtbs-Role-Limit-IO*

*ROLEID2*

*MAKER*

*MAKERSTAMP*

*MODNO*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

**REOPENSMDRLMNE\_IOPK\_RES**

<b>Attribute</b>	<b>Description</b>
Name	REOPENSMDRLMNE_IOPK_RES
Datatype	
Description	

**FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

**SOURCE**

<b>Attribute</b>	<b>Description</b>				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

**UBSCOMP**

<b>Attribute</b>	<b>Description</b>				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	<b>Restrictions</b>	<b>Description</b>	enumeration	FCUBS,FCIS
<b>Restrictions</b>	<b>Description</b>				
enumeration	FCUBS,FCIS				

Attribute	Description					
Name	MSGID					
Datatype	string					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

## CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	string					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

## USERID

Attribute	Description							
Name	USERID							
Datatype	string							
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description							
maxLength	12							
pattern	[A-Z_0-9]*							

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	



Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

## ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute		Attribute	
		Description	
		minOccurs	0

## PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute		Attribute	
		Description	
		minOccurs	0
		maxOccurs	unbounded

## NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

## VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

## FCUBS\_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description		This XSD Gives Information about PK Response	

## Smtbs-Role-Limit-PK

Attribute		Description	
Name		Smtbs-Role-Limit-PK	
Datatype			
Description			

## ROLEID2

Attribute		Description	
Name		ROLEID2	
Datatype		string	
Description		Indicates Role Id	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

### Smtbs-Role-Limit-IO

<b>Attribute</b>	<b>Description</b>
Name	Smtbs-Role-Limit-IO
Datatype	
Description	

### ROLEID2

<b>Attribute</b>	<b>Description</b>	
Name	ROLEID2	
Datatype	string	
Description	Indicates Role Id	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

### MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

### MODNO

<b>Attribute</b>	<b>Description</b>
Name	MODNO
Datatype	decimal
Description	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## WARNING

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	WARNING	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

## 2.25.ReopenUserMaint

### 2.25.1.SM-ReopenUserMaint-Req-Full-MSG.xsd

*REOPENUSERMAINT\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*USR-Full*

*STRDATE*

*USRNAME*

*USRPWD*

*ENDDT*

*USRLANG*

*HOMEBRN*

*CUSTNO*

*LDAPUSR*

*TIMELEVEL*

*AUTOAUTH*

*USRSTAT*

*USRID*

*EXTUSRREF*

*USRCATEG*

*TILLALLOW*

*ACCCLSALLOW*

*GLALLOW*

*USRTXNLMT*

*LMTSCCY*

*MAXTXNAMT*

*MAXAUTHAMT*

*BRNSALLOW*

*PRDSALLOW*

*PRDSACCESALLOW*

*TAX\_IDENTIFIER*

*AMOUNT\_FORMAT*



*DATE\_FORMAT*  
*STAFFACCRESTR*  
*DEPT\_CODE*  
*DEPT\_DESC*  
*USRML*  
*ELCMUSER*  
*GROUP\_CODE*  
*MULTIBRN\_ACCESS*  
*OTH\_RM\_CUST\_ACC\_ALLOW*  
*SUPERVISOR\_ID*  
*SUPERVISOR\_NAME*  
*DASHBOARD\_REQD*  
*ALERTS\_ON\_HOME*  
*REFERENCE\_NO*  
*NO\_CUMULATIVE\_LOGINS*  
*NO\_SUCESSIVE\_LOGINS*  
*SCREENSAVERTIMEOUTINSECONDS*  
*NUMBER\_FORMAT\_MASK*  
*FRONTEND\_DEBUG\_ENABLED*  
*F10\_REQD*  
*F11\_REQD*  
*F12\_REQD*  
*MFI\_USER*  
*MFAENABLED*  
*MFAID*  
*ACCESS\_CONTROL*  
*EXTN\_ALERTS*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*

*TXNSTAT*  
*AUTHSTAT*  
*RESTR\_PWD*  
*PWD*  
*MSGSRIGHTS*  
*GEN*  
*HLD*  
*CNL*  
*TSTINP*  
*CHGNODE*  
*CHGADDR*  
*REL*  
*REINS*  
*CHGMEDIA*  
*CHGPRIOR*  
*BRNMOV*  
*PRNT*  
*TSTCHK*  
*HLDAUTH*  
*CNLAUTH*  
*TSTINPAUTH*  
*CHGNODEAUTH*  
*CHGADDRAUTH*  
*RELAUTH*  
*REINSAUTH*  
*CHGMEDIAAUTH*  
*BRNMOVAUTH*  
*CHGPRIORAUTH*  
*FTUPL*  
*LNKCONT*  
*MOVQ*  
*CHGBRNIN*

*CHGADDRIN*  
*AUTHRGHTS*  
*CHGMSG*  
*CHGMSGAUTH*  
*CHGFORCCOVMATCH*  
*CHANGE\_FORCE\_RELEASE\_FUND*  
*SUPPRESS*  
*DELMSG*  
*QUEUERIGHTS*  
    *QUEUE*  
*USERTILLS*  
    *TILLID*  
    *TILLBRNCD*  
    *DESCRIPTION*  
*USERACCCLASS*  
    *ACCCLS*  
*USERGLREST*  
    *NODEGL*  
    *USERGLEXCEPT*  
        *EXCEPLEAFGL*  
*USERLIMITSROLE*  
    *LMTBRN*  
    *LMTSROLE*  
    *QLMTCCY*  
    *QINPLMT*  
    *QAUTHLMT*  
*USERBRANCHES*  
    *BRNSBRN*  
    *BRNNAME*  
*USERPRODUCTS*  
    *PRDPRDCD*  
    *PRDDESC*

*USERACCESSPRODUCTS*

*PRDACCESSPRDCD*

*PRDDESC*

*USERFUNCDISALLOW*

*FUNCDISALLOWFUNCID*

*USERROLE*

*ROLEBRNCD*

*USRROLEID*

*MASTERROLEDESC*

*USERSFUNCTIONS*

*USERFUNCBRNCD*

*USERFUNCFUNCID*

*CONTROL1*

*CONTROL2*

*CONTROL3*

*CONTROL4*

*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*USERFUNCSCTRL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CONTROL15*

*CONTROL16*

*Grp-Restriction*

*GROUP\_CODE*

*GROUP\_DESC*

*Centralisation*

*USRROLEID*

*ROLDESC*

*Dshmst*

*USRID*

*USRNAME*

*Dshdet*

*FUNCTIONID*

*DESCRIPTION*

*SEQUENCE\_NO*

*DBWHERECLAUSE*

*SHOW\_IN\_DASHBOARD*

*Where-Master*

*COLUMN\_NAME*

*WHERE\_CL*

*CONDITION*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

## REOPENUSERMAINT\_FSFS\_REQ

Attribute	Description
Name	REOPENUSERMAINT_FSFS_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

Attribute	Description



Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of ReopenUserMaint

## USR-Full

Attribute	Description
Name	USR-Full
Datatype	
Description	

## STRTDATE

Attribute	Description
Name	STRTDATE
Datatype	String
Description	

## USRNAME

Attribute	Description				
Name	USRNAME				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

## USRPWD

Attribute	Description				
Name	USRPWD				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>32</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	32
Restrictions	Description				
maxLength	32				

## ENDDT

Attribute	Description				
Name	ENDDT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## USRLANG

Attribute	Description				
Name	USRLANG				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

## HOMEBRN

Attribute	Description				
Name	HOMEBRN				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

## CUSTNO

Attribute	Description				
Name	CUSTNO				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
	Restrictions	Description			
maxLength	9				

## LDAPUSR

Attribute	Description				
Name	LDAPUSR				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>500</td></tr></tbody></table>	Restrictions	Description	maxLength	500
	Restrictions	Description			
maxLength	500				

## TIMELEVEL

Attribute	Description
Name	TIMELEVEL
Datatype	decimal
Description	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	9

## AUTOAUTH

<b>Attribute</b>	<b>Description</b>	
Name	AUTOAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## USRSTAT

<b>Attribute</b>	<b>Description</b>	
Name	USRSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	E,H,D,L

## USRID

<b>Attribute</b>	<b>Description</b>	
Name	USRID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## EXTUSRREF

<b>Attribute</b>	<b>Description</b>	
Name	EXTUSRREF	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## USRCATEG

<b>Attribute</b>	<b>Description</b>	
Name	USRCATEG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	S,B

## TILLALLOW

<b>Attribute</b>	<b>Description</b>	
Name	TILLALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## ACCCLSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## GLALLOW

<b>Attribute</b>	<b>Description</b>	
Name	GLALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## USRTXNLMT

<b>Attribute</b>	<b>Description</b>	
Name	USRTXNLMT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,R,N

## LMTSCCY

<b>Attribute</b>	<b>Description</b>	
Name	LMTSCCY	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## MAXTXNAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXTXNAMT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## MAXAUTHAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXAUTHAMT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### BRNSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	BRNSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### PRDSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### PRDSACCESALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSACCESALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### TAX\_IDENTIFIER

<b>Attribute</b>	<b>Description</b>	
Name	TAX_IDENTIFIER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

## AMOUNT\_FORMAT

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_FORMAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	*****

## DATE\_FORMAT

<b>Attribute</b>	<b>Description</b>	
Name	DATE_FORMAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	M/d/yyyy

## STAFFACCRESTR

<b>Attribute</b>	<b>Description</b>	
Name	STAFFACCRESTR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DEPT\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	DEPT_CODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## DEPT\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	DEPT_DESC	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## USRML

<b>Attribute</b>	<b>Description</b>	
Name	USRML	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## ELCMUSER

<b>Attribute</b>	<b>Description</b>	
Name	ELCMUSER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## GROUP\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_CODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## MULTIBRN\_ACCESS

<b>Attribute</b>	<b>Description</b>	
Name	MULTIBRN_ACCESS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## OTH\_RM\_CUST\_ACC\_ALLOW

<b>Attribute</b>	<b>Description</b>	
Name	OTH_RM_CUST_ACC_ALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SUPERVISOR\_ID

<b>Attribute</b>	<b>Description</b>	
Name	SUPERVISOR_ID	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	80

## SUPERVISOR\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	SUPERVISOR_NAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## DASHBOARD\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	DASHBOARD_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## ALERTS\_ON\_HOME

<b>Attribute</b>	<b>Description</b>	
Name	ALERTS_ON_HOME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REFERENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	REFERENCE_NO	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## NO\_CUMULATIVE\_LOGINS

<b>Attribute</b>	<b>Description</b>	
Name	NO_CUMULATIVE_LOGINS	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### NO\_SUCCESSIVE\_LOGINS

<b>Attribute</b>	<b>Description</b>	
Name	NO_SUCCESSIVE_LOGINS	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### SCREENSAVERTIMEOUTINSECONDS

<b>Attribute</b>	<b>Description</b>	
Name	SCREENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### NUMBER\_FORMAT\_MASK

<b>Attribute</b>	<b>Description</b>	
Name	NUMBER_FORMAT_MASK	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	M,L

### FRONTEND\_DEBUG\_ENABLED

<b>Attribute</b>	<b>Description</b>	
Name	FRONTEND_DEBUG_ENABLED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F10\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F10_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F11\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F11_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F12\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F12_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### MFI\_USER

<b>Attribute</b>	<b>Description</b>	
Name	MFI_USER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MFAENABLED

<b>Attribute</b>	<b>Description</b>	
Name	MFAENABLED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	N,Y,L

## MFAID

<b>Attribute</b>	<b>Description</b>	
Name	MFAID	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

## ACCESS\_CONTROL

<b>Attribute</b>	<b>Description</b>	
Name	ACCESS_CONTROL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,G,B

## EXTN\_ALERTS

<b>Attribute</b>	<b>Description</b>	
Name	EXTN_ALERTS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## RESTR\_PWD

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_PWD	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

**PWD**

Attribute	Description	
Name	PWD	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	12

**MSGSRIGHTS**

Attribute	Description	
Name	MSGSRIGHTS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

**GEN**

Attribute	Description	
Name	GEN	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

**HLD**

Attribute	Description	
Name	HLD	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

**CNL**

Attribute	Description	
Name	CNL	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINP

<b>Attribute</b>	<b>Description</b>	
Name	TSTINP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODE

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDR

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REL

<b>Attribute</b>	<b>Description</b>	
Name	REL	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINS

<b>Attribute</b>	<b>Description</b>	
Name	REINS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIA

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIA	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIOR

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIOR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOV

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOV	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## PRNT

<b>Attribute</b>	<b>Description</b>	
Name	PRNT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTCHK

<b>Attribute</b>	<b>Description</b>	
Name	TSTCHK	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLDAUTH

<b>Attribute</b>	<b>Description</b>	
Name	HLDAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNLAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CNLAUTH	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINPAUTH

<b>Attribute</b>	<b>Description</b>	
Name	TSTINPAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODEAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## RELAUTH

<b>Attribute</b>	<b>Description</b>	
Name	RELAUTH	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINSAUTH

<b>Attribute</b>	<b>Description</b>	
Name	REINSAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIAAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIAAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## BRNMOVAUTH

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOVAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGPRIORAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIORAUTH	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## FTUPL

<b>Attribute</b>	<b>Description</b>	
Name	FTUPL	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## LNKCONT

<b>Attribute</b>	<b>Description</b>	
Name	LNKCONT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MOVQ

<b>Attribute</b>	<b>Description</b>	
Name	MOVQ	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGBRNIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGBRNIN	
Datatype	string	
Description		



Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRIN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## AUTHRGHTS

<b>Attribute</b>	<b>Description</b>	
Name	AUTHRGHTS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSG

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMSGAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSGAUTH	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	enumeration	Y,N

### CHGFORCCOVMATCH

<b>Attribute</b>	<b>Description</b>	
Name	CHGFORCCOVMATCH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	enumeration	Y,N

### CHANGE\_FORCE\_RELEASE\_FUND

<b>Attribute</b>	<b>Description</b>	
Name	CHANGE_FORCE_RELEASE_FUND	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	enumeration	Y,N

### SUPPRESS

<b>Attribute</b>	<b>Description</b>	
Name	SUPPRESS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	enumeration	Y,N

### DELMSG

<b>Attribute</b>	<b>Description</b>	
Name	DELMSG	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## QUEUERIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	QUEUERIGHTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## QUEUE

<b>Attribute</b>	<b>Description</b>	
Name	QUEUE	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## USERTILLS

<b>Attribute</b>	<b>Description</b>	
Name	USERTILLS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## TILLID

<b>Attribute</b>	<b>Description</b>	
Name	TILLID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## TILLBRNCD

<b>Attribute</b>	<b>Description</b>	
Name	TILLBRNCD	
Datatype	string	

Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## DESCRIPTION

Attribute	Description				
Name	DESCRIPTION				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>255</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

## USERACCCLASS

Attribute	Description						
Name	USERACCCLASS						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## ACCCLS

Attribute	Description				
Name	ACCCLS				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>6</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	6
Restrictions	Description				
maxLength	6				

## USERGLREST

Attribute	Description						
Name	USERGLREST						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## NODEGL

Attribute	Description
Name	NODEGL

Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## USERGLEXCEPT

<b>Attribute</b>	<b>Description</b>	
Name	USERGLEXCEPT	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## EXCEPLEAFGL

<b>Attribute</b>	<b>Description</b>	
Name	EXCEPLEAFGL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## USERLIMITSROLE

<b>Attribute</b>	<b>Description</b>	
Name	USERLIMITSROLE	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## LMTBRN

<b>Attribute</b>	<b>Description</b>	
Name	LMTBRN	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## LMTSROLE

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	LMTSROLE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## QLMTCCY

<b>Attribute</b>	<b>Description</b>	
Name	QLMTCCY	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## QINPLMT

<b>Attribute</b>	<b>Description</b>	
Name	QINPLMT	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## QAUHLMT

<b>Attribute</b>	<b>Description</b>	
Name	QAUHLMT	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## USERBRANCHES

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	USERBRANCHES	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### BRNSBRN

<b>Attribute</b>	<b>Description</b>	
Name	BRNSBRN	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### BRNNAME

<b>Attribute</b>	<b>Description</b>	
Name	BRNNAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

### USERPRODUCTS

<b>Attribute</b>	<b>Description</b>	
Name	USERPRODUCTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### PRDPRDCD

<b>Attribute</b>	<b>Description</b>	
Name	PRDPRDCD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

### PRDDESC

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	PRDESC	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## USERACCESSPRODUCTS

<b>Attribute</b>	<b>Description</b>	
Name	USERACCESSPRODUCTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PRDACCESSPRDCD

<b>Attribute</b>	<b>Description</b>	
Name	PRDACCESSPRDCD	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

## PRDESC

<b>Attribute</b>	<b>Description</b>	
Name	PRDESC	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## USERFUNCDISALLOW

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCDISALLOW	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded



## FUNCDISALLOWFUNCID

Attribute	Description				
Name	FUNCDISALLOWFUNCID				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr></tbody></table>	Restrictions	Description	maxLength	8
Restrictions	Description				
maxLength	8				

## USERROLE

Attribute	Description						
Name	USERROLE						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## ROLEBRNCD

Attribute	Description				
Name	ROLEBRNCD				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## USRROLEID

Attribute	Description				
Name	USRROLEID				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## MASTERROLEDESC

Attribute	Description				
Name	MASTERROLEDESC				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>45</td></tr></tbody></table>	Restrictions	Description	maxLength	45
Restrictions	Description				
maxLength	45				

## USERSFUNCTIONS

Attribute	Description	
Name	USERSFUNCTIONS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## USERFUNCBRNCD

Attribute	Description	
Name	USERFUNCBRNCD	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

## USERFUNCFUNCID

Attribute	Description	
Name	USERFUNCFUNCID	
Datatype	string	
Description		
Restrictions		
	Restrictions	Description
	maxLength	8

## CONTROL1

Attribute	Description	
Name	CONTROL1	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

## CONTROL2

Attribute	Description	
Name	CONTROL2	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL3

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL3	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL4

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL4	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL6

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL6	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL8

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL8	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### USERFUNCCTRL10

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCCTRL10	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL11

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL11	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL12

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL12	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL13

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL13	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL14

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL14	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL15

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL15	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### Grp-Restriction

<b>Attribute</b>	<b>Description</b>	
Name	Grp-Restriction	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### GROUP\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_CODE	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

### GROUP\_DESC

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	GROUP_DESC	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

## Centralisation

<b>Attribute</b>	<b>Description</b>	
Name	Centralisation	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## USRROLEID

<b>Attribute</b>	<b>Description</b>	
Name	USRROLEID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## ROLDESC

<b>Attribute</b>	<b>Description</b>	
Name	ROLDESC	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## Dshmst

<b>Attribute</b>	<b>Description</b>	
Name	Dshmst	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## USRID

Attribute	Description	
Name	USRID	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	15

## USRNAME

Attribute	Description	
Name	USRNAME	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

## Dshdet

Attribute	Description	
Name	Dshdet	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	15

## DESCRIPTION

Attribute	Description
-----------	-------------



Name	DESCRIPTION	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1000

## SEQUENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	SEQUENCE_NO	
Datatype	decimal	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## DBWHERECLAUSE

<b>Attribute</b>	<b>Description</b>	
Name	DBWHERECLAUSE	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

## SHOW\_IN\_DASHBOARD

<b>Attribute</b>	<b>Description</b>	
Name	SHOW_IN_DASHBOARD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## Where-Master

<b>Attribute</b>	<b>Description</b>	
Name	Where-Master	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## COLUMN\_NAME

Attribute		Description	
Name	COLUMN_NAME		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	2000	

## WHERE\_CL

Attribute		Description	
Name	WHERE_CL		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	500	

## CONDITION

Attribute		Description	
Name	CONDITION		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	30	

## UDFDETAILS

Attribute		Description	
Name	UDFDETAILS		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
	maxOccurs	unbounded	

## FLDNAM

Attribute		Description	
Name	FLDNAM		

Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

### 2.25.2.SM-ReopenUserMaint-Req-IO-MSG.xsd

#### *REOPENUSERMAINT\_IOPK\_REQ*

##### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*USR-IO*

*USRID*

*MAKER*

*MAKERSTAMP*

*MODNO*

## REOPENUSERMAINT\_IOPK\_REQ

Attribute	Description
Name	REOPENUSERMAINT_IOPK_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	string
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	string				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	string
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	

Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of ReopenUserMaint

## USR-IO

<b>Attribute</b>	<b>Description</b>
Name	USR-IO
Datatype	
Description	

## USRID

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	USRID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

2.25.3.SM-ReopenUserMaint-Res-Full-MSG.xsd

*REOPENUSERMAINT\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*USR-Full*  
*STRTDATE*  
*USRNAME*  
*USRPWD*  
*ENDDT*  
*USRLANG*  
*HOMEBRN*  
*CUSTNO*  
*LDAPUSR*  
*TIMELEVEL*  
*AUTOAUTH*  
*USRSTAT*

*USRID*  
*EXTUSRREF*  
*USRCATEG*  
*TILLALLOW*  
*ACCCLSALLOW*  
*GLALLOW*  
*USRTXNLMT*  
*LMTSCCY*  
*MAXTXNAMT*  
*MAXAUTHAMT*  
*BRNSALLOW*  
*PRDSALLOW*  
*PRDSACCESALLOW*  
*TAX\_IDENTIFIER*  
*AMOUNT\_FORMAT*  
*DATE\_FORMAT*  
*STAFFACCRESTR*  
*DEPT\_CODE*  
*DEPT\_DESC*  
*USRML*  
*ELCMUSER*  
*GROUP\_CODE*  
*MULTIBRN\_ACCESS*  
*OTH\_RM\_CUST\_ACC\_ALLOW*  
*SUPERVISOR\_ID*  
*SUPERVISOR\_NAME*  
*DASHBOARD\_REQD*  
*ALERTS\_ON\_HOME*  
*REFERENCE\_NO*  
*NO\_CUMULATIVE\_LOGINS*  
*NO\_SUCCESSIVE\_LOGINS*  
*SCREENSAVERTIMEOUTINSECONDS*

*NUMBER\_FORMAT\_MASK*  
*FRONTEND\_DEBUG\_ENABLED*  
*F10\_REQD*  
*F11\_REQD*  
*F12\_REQD*  
*MFI\_USER*  
*MFAENABLED*  
*MFAID*  
*ACCESS\_CONTROL*  
*EXTN\_ALERTS*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*RESTR\_PWD*  
*PWD*  
*MSGSRIGHTS*  
*GEN*  
*HLD*  
*CNL*  
*TSTINP*  
*CHGNODE*  
*CHGADDR*  
*REL*  
*REINS*  
*CHGMEDIA*  
*CHGPRIOR*  
*BRNMOV*  
*PRNT*

*TSTCHK*  
*HLDAUTH*  
*CNLAUTH*  
*TSTINPAUTH*  
*CHGNODEAUTH*  
*CHGADDRAUTH*  
*RELAUTH*  
*REINSAUTH*  
*CHGMEDIAAUTH*  
*BRNMOVAUTH*  
*CHGPRIORAUTH*  
*FTUPL*  
*LNKCONT*  
*MOVQ*  
*CHGBRNIN*  
*CHGADDRIN*  
*AUTHRGHTS*  
*CHGMSG*  
*CHGMSGAUTH*  
*CHGFORCCOVMATCH*  
*CHANGE\_FORCE\_RELEASE\_FUND*  
*SUPPRESS*  
*DELMSG*  
*QUEUERIGHTS*  
    *QUEUE*  
*USERTILLS*  
    *TILLID*  
    *TILLBRNCD*  
    *DESCRIPTION*  
*USERACCCLASS*  
    *ACCCLS*  
*USERGLREST*

*NODEGL*  
*USERGLEXCEPT*  
*EXCEPLEAFGL*  
*USERLIMITSROLE*  
*LMTBRN*  
*LMTSROLE*  
*QLMTCCY*  
*QINPLMT*  
*QAUTHLMT*  
*USERBRANCHES*  
*BRNSBRN*  
*BRNNAME*  
*USERPRODUCTS*  
*PRDPRDCD*  
*PRDDESC*  
*USERACCESSPRODUCTS*  
*PRDACCESSPRDCD*  
*PRDDESC*  
*USERFUNCDISALLOW*  
*FUNCDISALLOWFUNCID*  
*USERROLE*  
*ROLEBRNCD*  
*USRROLEID*  
*MASTERROLEDESC*  
*USERSFUNCTIONS*  
*USERFUNCBRNCD*  
*USERFUNCFUNCID*  
*CONTROL1*  
*CONTROL2*  
*CONTROL3*  
*CONTROL4*  
*CONTROL5*

*CONTROL6*

*CONTROL7*

*CONTROL8*

*CONTROL9*

*USERFUNCSCTRL10*

*CONTROL11*

*CONTROL12*

*CONTROL13*

*CONTROL14*

*CONTROL15*

*CONTROL16*

*Grp-Restriction*

*GROUP\_CODE*

*GROUP\_DESC*

*Centralisation*

*USRROLEID*

*ROLDESC*

*Dshmst*

*USRID*

*USRNAME*

*Dshdet*

*FUNCTIONID*

*DESCRIPTION*

*SEQUENCE\_NO*

*DBWHERECLAUSE*

*SHOW\_IN\_DASHBOARD*

*Where-Master*

*COLUMN\_NAME*

*WHERE\_CL*

*CONDITION*

*UDFDETAILS*

*FLDNAM*



*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## REOPENUSERMAINT\_FSFS\_RES

Attribute	Description
Name	REOPENUSERMAINT_FSFS_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	string				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	string				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## USERID

Attribute	Description						
Name	USERID						
Datatype	string						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

## BRANCH

Attribute	Description
Name	BRANCH

Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

## ADDL

Attribute		Description	
Name	ADDL		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

## PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

## NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

## VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

## FCUBS\_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description	This XSD Gives Information about Full Response		

## USR-Full

Attribute		Description	
Name	USR-Full		
Datatype			
Description			

## STRTDATE

Attribute		Description	
Name	STRTDATE		
Datatype	String		
Description			

## USRNAME

Attribute		Description	

Name	USRNAME	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## USRPWD

<b>Attribute</b>	<b>Description</b>	
Name	USRPWD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	32

## ENDDT

<b>Attribute</b>	<b>Description</b>	
Name	ENDDT	
Datatype	String	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## USRLANG

<b>Attribute</b>	<b>Description</b>	
Name	USRLANG	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## HOMEBRN

<b>Attribute</b>	<b>Description</b>	
Name	HOMEBRN	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## CUSTNO

<b>Attribute</b>	<b>Description</b>	
Name	CUSTNO	

Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## LDAPUSR

<b>Attribute</b>	<b>Description</b>	
Name	LDAPUSR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	500

## TIMELEVEL

<b>Attribute</b>	<b>Description</b>	
Name	TIMELEVEL	
Datatype	decimal	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22
	minInclusive	0
	maxInclusive	9

## AUTOAUTH

<b>Attribute</b>	<b>Description</b>	
Name	AUTOAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## USRSTAT

<b>Attribute</b>	<b>Description</b>	
Name	USRSTAT	
Datatype	string	
Description		



Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	E,H,D,L

## USRID

<b>Attribute</b>	<b>Description</b>	
Name	USRID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## EXTUSRREF

<b>Attribute</b>	<b>Description</b>	
Name	EXTUSRREF	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## USRCATEG

<b>Attribute</b>	<b>Description</b>	
Name	USRCATEG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	S,B

## TILLALLOW

<b>Attribute</b>	<b>Description</b>	
Name	TILLALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## ACCCLSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## GLALLOW

<b>Attribute</b>	<b>Description</b>	
Name	GLALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## USRTXNLMT

<b>Attribute</b>	<b>Description</b>	
Name	USRTXNLMT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,R,N

## LMTSCCY

<b>Attribute</b>	<b>Description</b>	
Name	LMTSCCY	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### MAXTXNAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXTXNAMT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### MAXAUTHAMT

<b>Attribute</b>	<b>Description</b>	
Name	MAXAUTHAMT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### BRNSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	BRNSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### PRDSALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### PRDSACCESALLOW

<b>Attribute</b>	<b>Description</b>	
Name	PRDSACCESALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

### TAX\_IDENTIFIER

<b>Attribute</b>	<b>Description</b>	
Name	TAX_IDENTIFIER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

### AMOUNT\_FORMAT

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_FORMAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	.....

### DATE\_FORMAT

<b>Attribute</b>	<b>Description</b>	
Name	DATE_FORMAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	M/d/yyyy

## STAFFACCRESTR

<b>Attribute</b>	<b>Description</b>	
Name	STAFFACCRESTR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DEPT\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	DEPT_CODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## DEPT\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	DEPT_DESC	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## USRML

<b>Attribute</b>	<b>Description</b>	
Name	USRML	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## ELCMUSER

<b>Attribute</b>	<b>Description</b>	
Name	ELCMUSER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## GROUP\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_CODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

## MULTIBRN\_ACCESS

<b>Attribute</b>	<b>Description</b>	
Name	MULTIBRN_ACCESS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## OTH\_RM\_CUST\_ACC\_ALLOW

<b>Attribute</b>	<b>Description</b>	
Name	OTH_RM_CUST_ACC_ALLOW	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SUPERVISOR\_ID

<b>Attribute</b>	<b>Description</b>	
Name	SUPERVISOR_ID	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	80

## SUPERVISOR\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	SUPERVISOR_NAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## DASHBOARD\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	DASHBOARD_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## ALERTS\_ON\_HOME

<b>Attribute</b>	<b>Description</b>	
Name	ALERTS_ON_HOME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REFERENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	REFERENCE_NO	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## NO\_CUMULATIVE\_LOGINS

<b>Attribute</b>	<b>Description</b>	
Name	NO_CUMULATIVE_LOGINS	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## NO\_SUCCESSIVE\_LOGINS

<b>Attribute</b>	<b>Description</b>	
Name	NO_SUCCESSIVE_LOGINS	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## SCREENSAVERTIMEOUTINSECONDS

<b>Attribute</b>	<b>Description</b>	
Name	SCREENSAVERTIMEOUTINSECONDS	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### NUMBER\_FORMAT\_MASK

<b>Attribute</b>	<b>Description</b>	
Name	NUMBER_FORMAT_MASK	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	M,L

### FRONTEND\_DEBUG\_ENABLED

<b>Attribute</b>	<b>Description</b>	
Name	FRONTEND_DEBUG_ENABLED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F10\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F10_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### F11\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F11_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## F12\_REQD

<b>Attribute</b>	<b>Description</b>	
Name	F12_REQD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MFI\_USER

<b>Attribute</b>	<b>Description</b>	
Name	MFI_USER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MFAENABLED

<b>Attribute</b>	<b>Description</b>	
Name	MFAENABLED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	N,Y,L

## MFAID

<b>Attribute</b>	<b>Description</b>	
Name	MFAID	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

## ACCESS\_CONTROL

<b>Attribute</b>	<b>Description</b>	
Name	ACCESS_CONTROL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	U,G,B

## EXTN\_ALERTS

<b>Attribute</b>	<b>Description</b>	
Name	EXTN_ALERTS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## RESTR\_PWD

<b>Attribute</b>	<b>Description</b>	
Name	RESTR_PWD	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## PWD

<b>Attribute</b>	<b>Description</b>	
Name	PWD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MSGSRIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	MSGSRIGHTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## GEN

<b>Attribute</b>	<b>Description</b>	
Name	GEN	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLD

<b>Attribute</b>	<b>Description</b>	
Name	HLD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNL

<b>Attribute</b>	<b>Description</b>	
Name	CNL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINP

<b>Attribute</b>	<b>Description</b>	
Name	TSTINP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODE

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODE	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDR

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDR	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REL

<b>Attribute</b>	<b>Description</b>	
Name	REL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINS

<b>Attribute</b>	<b>Description</b>	
Name	REINS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIA

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIA	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHGPRIOR

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIOR	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### BRNMOV

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOV	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### PRNT

<b>Attribute</b>	<b>Description</b>	
Name	PRNT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### TSTCHK

<b>Attribute</b>	<b>Description</b>	
Name	TSTCHK	
Datatype	string	
Description		



Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## HLDAUTH

<b>Attribute</b>	<b>Description</b>	
Name	HLDAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CNLAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CNLAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## TSTINPAUTH

<b>Attribute</b>	<b>Description</b>	
Name	TSTINPAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGNODEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGNODEAUTH	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## RELAUTH

<b>Attribute</b>	<b>Description</b>	
Name	RELAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## REINSAUTH

<b>Attribute</b>	<b>Description</b>	
Name	REINSAUTH	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGMEDIAAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMEDIAAUTH	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### BRNMOVAUTH

<b>Attribute</b>	<b>Description</b>	
Name	BRNMOVAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHGPRIORAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGPRIORAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### FTUPL

<b>Attribute</b>	<b>Description</b>	
Name	FTUPL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### LNKCONT

<b>Attribute</b>	<b>Description</b>	
Name	LNKCONT	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## MOVQ

<b>Attribute</b>	<b>Description</b>	
Name	MOVQ	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGBRNIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGBRNIN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CHGADDRIN

<b>Attribute</b>	<b>Description</b>	
Name	CHGADDRIN	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## AUTHRGHTS

<b>Attribute</b>	<b>Description</b>	
Name	AUTHRGHTS	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHGMSG

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHGMSGAUTH

<b>Attribute</b>	<b>Description</b>	
Name	CHGMSGAUTH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHGFORCCOVMATCH

<b>Attribute</b>	<b>Description</b>	
Name	CHGFORCCOVMATCH	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

### CHANGE\_FORCE\_RELEASE\_FUND

<b>Attribute</b>	<b>Description</b>	
Name	CHANGE_FORCE_RELEASE_FUND	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SUPPRESS

<b>Attribute</b>	<b>Description</b>	
Name	SUPPRESS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## DELMSG

<b>Attribute</b>	<b>Description</b>	
Name	DELMSG	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## QUEUERIGHTS

<b>Attribute</b>	<b>Description</b>	
Name	QUEUERIGHTS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## QUEUE

<b>Attribute</b>	<b>Description</b>	
Name	QUEUE	
Datatype	string	
Description		

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## USERTILLS

<b>Attribute</b>	<b>Description</b>	
Name	USERTILLS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## TILLID

<b>Attribute</b>	<b>Description</b>	
Name	TILLID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## TILLBRNCD

<b>Attribute</b>	<b>Description</b>	
Name	TILLBRNCD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

## USERACCCCLASS

<b>Attribute</b>	<b>Description</b>	
Name	USERACCCCLASS	
Datatype		
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ACCCLS

<b>Attribute</b>	<b>Description</b>	
Name	ACCCLS	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

## USERGLREST

<b>Attribute</b>	<b>Description</b>	
Name	USERGLREST	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NODEGL

<b>Attribute</b>	<b>Description</b>	
Name	NODEGL	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## USERGLEXCEPT

<b>Attribute</b>	<b>Description</b>	
Name	USERGLEXCEPT	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## EXCEPLEAFGL

<b>Attribute</b>	<b>Description</b>	
Name	EXCEPLEAFGL	
Datatype	string	
Description		



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## USERLIMITSROLE

<b>Attribute</b>	<b>Description</b>	
Name	USERLIMITSROLE	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxOccurs	unbounded

## LMTBRN

<b>Attribute</b>	<b>Description</b>	
Name	LMTBRN	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## LMTSROLE

<b>Attribute</b>	<b>Description</b>	
Name	LMTSROLE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## QLMTCCY

<b>Attribute</b>	<b>Description</b>	
Name	QLMTCCY	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## QINPLMT

<b>Attribute</b>	<b>Description</b>	
Name	QINPLMT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## QAUTHLMT

<b>Attribute</b>	<b>Description</b>	
Name	QAUTHLMT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## USERBRANCHES

<b>Attribute</b>	<b>Description</b>	
Name	USERBRANCHES	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## BRNSBRN

<b>Attribute</b>	<b>Description</b>	
Name	BRNSBRN	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## BRNNAME

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	BRNNAME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	105
	<b>Description</b>	

## USERPRODUCTS

<b>Attribute</b>	<b>Description</b>	
Name	USERPRODUCTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## PRDPRDCD

<b>Attribute</b>	<b>Description</b>	
Name	PRDPRDCD	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	4
	<b>Description</b>	

## PRDESC

<b>Attribute</b>	<b>Description</b>	
Name	PRDESC	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	105
	<b>Description</b>	

## USERACCESSPRODUCTS

<b>Attribute</b>	<b>Description</b>	
Name	USERACCESSPRODUCTS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## PRDACCESSPRDCD

Attribute	Description	
Name	PRDACCESSPRDCD	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

## PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## USERFUNCDISALLOW

Attribute	Description	
Name	USERFUNCDISALLOW	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## FUNCDISALLOWFUNCID

Attribute	Description	
Name	FUNCDISALLOWFUNCID	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## USERROLE

Attribute	Description	
Name	USERROLE	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8

## ROLEBRNCD

Attribute	Description				
Name	ROLEBRNCD				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## USRROLEID

Attribute	Description				
Name	USRROLEID				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

## MASTERROLEDESC

Attribute	Description				
Name	MASTERROLEDESC				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>45</td></tr></tbody></table>	Restrictions	Description	maxLength	45
Restrictions	Description				
maxLength	45				

## USERSFUNCTIONS

Attribute	Description						
Name	USERSFUNCTIONS						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## USERFUNCBRNCD

Attribute	Description				
Name	USERFUNCBRNCD				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## USERFUNCFUNCID

Attribute		Description	
Name	USERFUNCFUNCID		
Datatype	string		
Description			
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	8	

### CONTROL1

Attribute		Description	
Name	CONTROL1		
Datatype	decimal		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	

### CONTROL2

Attribute		Description	
Name	CONTROL2		
Datatype	decimal		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	

### CONTROL3

Attribute		Description	
Name	CONTROL3		
Datatype	decimal		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	

### CONTROL4

Attribute		Description	
Name	CONTROL4		
Datatype	decimal		

Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL5

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL5	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL6

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL6	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL7

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL7	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL8

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL8	
Datatype	decimal	

Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL9

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL9	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## USERFUNCCTRL10

<b>Attribute</b>	<b>Description</b>	
Name	USERFUNCCTRL10	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL11

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL11	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CONTROL12

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL12	
Datatype	decimal	



Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL13

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL13	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL14

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL14	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL15

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL15	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### CONTROL16

<b>Attribute</b>	<b>Description</b>	
Name	CONTROL16	
Datatype	decimal	

Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### Grp-Restriction

<b>Attribute</b>	<b>Description</b>	
Name	Grp-Restriction	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### GROUP\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_CODE	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

### GROUP\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	GROUP_DESC	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

### Centralisation

<b>Attribute</b>	<b>Description</b>	
Name	Centralisation	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

Attribute		Description	
Name	USRROLEID		
Datatype	string		
Description			
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	15	

## ROLDESC

Attribute		Description	
Name	ROLDESC		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	20	

## Dshmst

Attribute		Description	
Name	Dshmst		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	

## USRID

Attribute		Description	
Name	USRID		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	15	

## USRNAME

Attribute		Description	
Name	USRNAME		
Datatype	string		
Description			

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

## Dshdet

<b>Attribute</b>	<b>Description</b>	
Name	Dshdet	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1000

## SEQUENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	SEQUENCE_NO	
Datatype	decimal	
Description		

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## DBWHERECLAUSE

<b>Attribute</b>	<b>Description</b>	
Name	DBWHERECLAUSE	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

## SHOW\_IN\_DASHBOARD

<b>Attribute</b>	<b>Description</b>	
Name	SHOW_IN_DASHBOARD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## Where-Master

<b>Attribute</b>	<b>Description</b>	
Name	Where-Master	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## COLUMN\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	COLUMN_NAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	2000

## WHERE\_CL

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	WHERE_CL	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	500

## CONDITION

<b>Attribute</b>	<b>Description</b>	
Name	CONDITION	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

## WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

### 2.25.4.SM-ReopenUserMaint-Res-PK-MSG.xsd

*REOPENUSERMAINT\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*



*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*USR-PK*

*USRID*

*USR-IO*

*USRID*

*MAKER*

*MAKERSTAMP*

*MODNO*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## REOPENUSERMAINT\_IOPK\_RES

Attribute	Description
Name	REOPENUSERMAINT_IOPK_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

Attribute	Description

Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

## USR-PK

Attribute	Description
Name	USR-PK
Datatype	
Description	

## USRID

Attribute	Description				
Name	USRID				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## USR-IO

Attribute	Description
Name	USR-IO
Datatype	
Description	

## USRID

Attribute	Description				
Name	USRID				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## MAKER

Attribute	Description				
Name	MAKER				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

## EDESC



Attribute	Description
Name	EDESC
Datatype	String
Description	

### FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

### WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

### WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

### WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	



## FINANCIAL SERVICES

Gateway Documentation - FCUBSSMSservice  
[October] [2015]

Oracle Financial services Software Limited  
Oracle Park  
Off western Express Highway  
Goregaon(East)  
Mumbai, Maharashtra 400 063  
India

Worldwide Inquiries:  
Phone: +91 22 6718 3000  
Fax: +91 22 6718 3001  
[www.oracle.com/financialservices/](http://www.oracle.com/financialservices/)

Copyright © [2013], [2015], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.