

Oracle® Communications Calendar Server

WCAP Developer's Guide

Release 7.0.4

July 2015

ORACLE®

Oracle Communications Calendar Server WCAP Developer's Guide, Release 7.0.4

Copyright © 2007, 2015, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

1. Web Calendar Access Protocol Overview	4
check_id.wcap	9
createcalendar.wcap	11
deletecalendar.wcap	14
deleteevents_by_id.wcap	16
deleteevents_by_range.wcap	19
deletetodos_by_id.wcap	22
deletetodos_by_range.wcap	25
export.wcap	28
fetchattachment.wcap	32
fetchcomponents_by_lastmod.wcap	34
fetchcomponents_by_range.wcap	38
fetchevents_by_id.wcap	46
fetchtodos_by_id.wcap	49
get_accountprops.wcap	52
get_all_timezones.wcap	57
get_calprops.wcap	97
get_capabilities.wcap	99
get_freebusy.wcap	101
get_guids.wcap	105
get_userprefs.wcap	107
import.wcap	111
list_subscribed.wcap	114
list.wcap	116
login.wcap	118
logout.wcap	120
search_calprops.wcap	122
set_accountprops.wcap	125
set_calprops.wcap	129
storeevents.wcap	132
storetodos.wcap	140
subscribe_calendars.wcap	148
unsubscribe_calendars.wcap	150
version.wcap	152
2. Oracle Communications Calendar Server WCAP Common Topics	154
3. WCAP Design Changes Between Oracle Communications Calendar Server and Sun Java System Calendar Server	166

Chapter 1. Web Calendar Access Protocol Overview

WCAP 7.0 (WCAPbis) Overview



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

This information describes the Web Calendar Access Protocol 7.0 (WCAPbis), which is a high level command-based protocol used to communicate with Calendar Server 7.

Topics:

- [Before You Use This Information](#)
- [Introduction to WCAP 7.0 \(WCAPbis\)](#)
- [Calendar Server WCAP 7.0 \(WCAPbis\) Command Overview](#)
- [Command Formats](#)

Before You Use This Information

This information assumes that you have a general understanding of the following:

- The Internet and the World Wide Web
- Calendaring concepts
- Calendaring Standards - RFC 5545, RFC 2446, RFC 2447
These RFC's describe in detail the format and definition for times, strings, parameters, and so forth used in WCAP commands. The RFC's can be found at the IETF web site:
 - <http://tools.ietf.org/html/rfc5545>
 - <http://tools.ietf.org/html/rfc2446>
 - <http://tools.ietf.org/html/rfc2447>

Introduction to WCAP 7.0 (WCAPbis)

Calendar data is stored in Standard iCal format in the calendar database. You can retrieve this calendar data by using WCAP commands with the `fmt-out` parameter set to `text/calendar`, `text/json`, or `text/xml`. `text/calendar` is the default format and outputs in Standard iCal format as defined in RFC5545.

WCAP is a command-based system consisting of client requests and server responses for transmitting calendaring data. WCAP returns calendaring data using the HTTP protocol. In most cases, Calendar

Server receives data through URL-encoded arguments to the commands.

WCAP commands consist of five general categories of usage:

- Creating calendars
- Storing, retrieving, and managing calendar properties
- Storing, retrieving, and managing calendar data
- Retrieving calendar Information of other users
- Scheduling



Note

WCAP 7.0 (WCAPbis) is based on WCAP in Calendar Server 6 and prior but has undergone many changes to increase usability, to better work with the new server model, and so on. For more information, see [WCAP Design Changes Between Oracle Communications Calendar Server and Sun Java System Calendar Server](#).

Calendar Server WCAP 7.0 (WCAPbis) Command Overview

Topics in this section:

- [List of WCAP 7.0 Commands](#)
- [Session Identifiers](#)
- [Hosted \(Virtual\) Domain](#)

List of WCAP 7.0 Commands

The following table lists the commands supported in WCAP 7.0.

WCAP 7.0 Command Overview

WCAP 7.0 Command	Description
check_id.wcap	Checks session id for validity.
createcalendar.wcap	Creates a new calendar.
deletecalendar.wcap	Deletes an existing calendar.
deleteevents_by_id.wcap	Deletes events given a specific calid and uid or uid and rid pair.
deleteevents_by_range.wcap	Deletes events in calendar(s) over a specific time period.
deletetodos_by_id.wcap	Deletes todos given a specific calid and uid or uid and rid pair.
deletetodos_by_range.wcap	Deletes todos in calendar(s) over a specific time period.
export.wcap	Exports a calendar to a file.
fetchattachment.wcap	Fetches an attachment of specified attachid.
fetchcomponents_by_lastmod.wcap	Fetches a list of components that have changed since a specified time.
fetchcomponents_by_range.wcap	Queries for components over a specific time period, with filtering attributes.

fetchevents_by_id.wcap	Queries for one or more events by a unique identifier (UID, Recurrence ID, modifier).
fetchtodos_by_id.wcap	Queries for one or more todos by a unique identifier (UID, Recurrence ID, modifier).
get_accountprops.wcap	Returns account properties.
get_all_timezones.wcap	Returns all the time zones the server supports.
get_calprops.wcap	Returns properties of requested calendars.
get_capabilities.wcap	Determines if the attachment store been enabled for Calendar Server.
get_freebusy.wcap	Returns free/busy information of requested users.
import.wcap	Imports a calendar from a file to a user's specified calendar.
list.wcap	Lists all calendars owned by a user.
list_subscribed.wcap	Lists all subscribed calendars of a user.
login.wcap	Authenticates a user and generates a session id.
logout.wcap	Logs out of a session.
search_calprops.wcap	Searches for a user with the specified parameter values and returns his calendars.
set_accountprops.wcap	Sets the account properties of a user.
set_calprops.wcap	Sets calendar properties.
storeevents.wcap	Creates or modifies events, including inviting attendees for the event.
storetodos.wcap	Creates or modifies todos.
subscribe_calendars.wcap	Adds calendars to a user's subscription list.
unsubscribe_calendars.wcap	Removes calendars from a user's subscription list.
version.wcap	Prints server and WCAP version.

See [Calendar Server WCAP Error Codes](#) for error codes returned by WCAP commands.

Session Identifiers

For many WCAP commands, you must specify the session identifier (`id`) that is returned by the `login` command. The session identifier ensures that data is accessible only to authenticated users with the required level of privilege or ownership.

When logging into the system, a user provides identity information for authentication. The default authentication mechanism uses plain-text passwords and user names. Calendar Server generates the session identifier only when authentication is successful. The identifier then serves as proof of authentication in subsequent calendaring operations.



Note

For more information about how to configure authentication, see the [Calendar Server 7 Administration Guide](#).

Hosted (Virtual) Domain

WCAP commands work the same for users in default and non-default domains in a hosted domain environment. For non-default domains, WCAP commands you issue must have fully qualified login IDs to properly identify the domain of the user, for example, `jdoh@example.com`.

Command Formats

WCAP uses HTTP and follows the standards defined by the WC3 URL specifications.



Note

On some HTTP client implementations, the request URI length is limited to 1024. Thus, always use HTTP POST (with an `application/x-www-form-urlencoded` body part containing all the parameters) when sending a request where the total size of parameters is unbounded (for example, in the case of `storeevents.wcap`).

Topics in this section:

- [Client Request Formats](#)
- [Server Response Formats](#)
- [Reducing Network Traffic](#)

Client Request Formats

Clients submit command requests to the Calendar Server in Universal Resource Identifier (URI) data format.

Use the following format to submit a URI request:

```
http://<webcalendarserver>:<port>/wcap/COMMAND?PARAM=VAL&PARAM=VAL...
```

- Newlines in values must be represented by `\n`.
- Semi-colons in values must be escaped: `\;`
- Carats in a value can be used as is. No doubling is needed, as the other separator carats occur only in the parameter name part.
- Property values can contain a colon. The code evaluates each `PROPERTY_NAME:PROPERTY_VALUE` up to the first ":" as `PROPERTY_NAME` (including parameters), and the rest as `PROPERTY_VALUE`.

The following example shows how to represent the string "gh;i" in a list of IDs:

```
http://<webcalendarserver>:<port>/wcap/fetchcomponents_by_range.wcap?uid=abc;def;gh\;i;jkl
```

Server Response Formats

Calendar Server responds to client requests in iCalendar, JSON, or XML objects. You can configure a response format preference per request by using the `fmt-out` parameter.

Starting with **Calendar Server 7.0.4.14.0**, all JSON formatted output is prefixed by `"{}&&"`. This is to help combat JSON hijacking. You can change the prefix value by setting the

`davcore.serverdefaults.jsonprefix` configuration parameter. The default value is "{}&&".

Reducing Network Traffic

Starting with **Calendar Server 7 Update 2 Patch 5**, the server accepts compressed requests (indicated by a "Content-Encoding:gzip" HTTP header in the request). Additionally, the server can return compressed responses (requested through an "Accept-Encoding:gzip" HTTP header in the request). This helps reduce overall network traffic between client and server.

check_id.wcap

check_id.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

Check validity of specified session ID.

Parameters

check_id Parameter

Parameter	Types	Multi-valued?	Purposes	Required?	Default
fmt-out	string	N	The format for the returned data. The three format types are: text/calendar text/json text/xml	N	text/calendar
id	unique identifier string	N	The session identifier.	Y	N/A

Description

Use this command to check if a specified session id string is still valid.

Returns

X-NSCP-WCAP-CHECK-ID property with value set to 1, if session is valid. It is set to 0 for an invalid session ID string.

Error Codes

Returns WCAP_ERRNO 0. For a complete list of error codes, see [Calendar Server WCAP 7.0 \(WCAPbis\) Error Codes](#).

Examples

The following example is for a valid session identifier and using text/calendar format:

```
http://<host>:<port>/wcap/check_id.wcap?fmt-out=text/calendar&id=<session-id>
Corporation/CS 7u2-5.05//EN
X-NSCP-WCAP-CHECK-ID:1
X-NSCP-WCAP-ERRNO:0
END:VCALENDAR
```

The following example shows an invalid session identifier:

```
http://<host>:<port>/davserver/wcap/check_id.wcap

BEGIN:VCALENDAR
VERSION:2.0
PRODID:-//Oracle Corporation/CS 7u2-5.05//EN
X-NSCP-WCAP-CHECK-ID:0
X-NSCP-WCAP-ERRNO:0
END:VCALENDAR
```

createcalendar.wcap

createcalendar.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:


<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

Create a new calendar.

Parameters

createcalendar **Parameter**

Parameter	Types	Multi-valued?	Purposes	Required	Default
acl	string	N	A semicolon-separated list of strings specifying the new value of the access control entries. <div style="border: 1px solid #add8e6; padding: 5px; width: fit-content; margin: 10px auto;">  See Administering Calendar Server Access for more information. </div>	N	Uses server default
desc	string	N	The description of the calendar.	N	N/A
id	unique identifier string	N	The session identifier.	Y	N/A
fbinclude	integer (0 or 1)	N	A boolean indicating whether the calendar can be used in any free/busy lookup. 1 = Include the calendar 0 = Do not include the calendar	N	1
fmt-out	string		The format for the returned data. The three format types: text/calendar text/json text/xml	N	text/calendar
name	string	N	The name of the calendar.	Y	N/A
set_calprops	integer (0 or 1)	N	A boolean indicating whether to set the properties of the new calendar. 1 = Set properties 0 = Do not set properties	N	0
tzid	string	N	Timezone identifier for the calendar	N	Uses server default

Description

Use this command to create a new calendar for the current user.

Setting Calendar Properties

The calendar properties `desc`, `fbinclude`, and `tzid` can be set during creation of a calendar. If they are supplied and the `set_calprops` parameter has a value of 1, these properties are set in the new calendar. If `set_calprops` has a value of 0, even if they are supplied, these properties are not set. These properties can also be set on an existing calendar via the `set_calprops.wcap` command.

At calendar creation, if you do not specify calendar properties or `set_calprops` has a value of 1, the defaults, set by the server configuration, are used.

Returns

The returned output shows the properties of the newly created calendar, formatted according to the `fmt-out` value.

Error Codes

If the operation is successful, the error number of 0 is returned. If the requested calendar already exists in the database, an error code of 25, `CREATECALENDAR_ALREADY_EXISTS_FAILED` is returned. If the command fails due to any other reasons like insufficient rights, an error code of 10, `CREATECALENDAR_FAILED` is returned.

For a complete list of error codes, see [Calendar Server WCAP 7.0 \(WCAPbis\) Error Codes](#).

Example

The following example shows a successful attempt to create a calendar:

```
http://<host>:<port>/wcap/createcalendar.wcap?fmt-out=text/calendar&id=<session-id>
Corporation/CS 7u2-5.06//EN
X-NSCP-CALPROPS-RELATIVE-CALID;X-S1CS-EMAIL=john.doe@example.com:/home/John
```

The following example shows a failed attempt to create a calendar:

```
http://<host>:<port>/wcap/createcalendar.wcap?fmt-out=text/calendar&name=fr
Corporation/CS 7u2-5.06//EN
X-NSCP-WCAP-ERRNO:75
X-NSCP-WCAP-ERRNO-MESSAGE:Command cannot be executed by anonymous
X-NSCP-WCAP-ERRNO-DETAILED-MESSAGE:forbidden
END:VCALENDAR
```

deletecalendar.wcap

deletecalendar.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

This command deletes specified calendars.

Parameters

deletecalendars Parameter

Parameter	Types	Multi-valued?	Purposes	Required	Default
calid	string	Y	The calids of the calendars to delete. Semi-colon separated list if more than one calendar needs to be deleted.	Y	N/A
id	unique identifier string	N	The session identifier.	Y	N/A
fmt-out	string	N	The format for the returned data. Three format types: text/calendar text/json text/xml	N	text/calendar

Description

Use this command to delete specified calendars. You must pass in the `calid` of each calendar to be deleted, in a semi-colon separated list. `calid` is the value provided by the server for the option `X-NSCP-CALPROPS-RELATIVE-CALID`, when the calendar was created.

Returns

The returned output is the formatted output of the delete execution status.

Error Codes

If the operation is successful, the error number of 0 is returned in the error string, X-NSCP-WCAP-ERRNO. If the operation fails, an error code of 11, DELETECALENDAR_FAILED is returned.

For a complete list of error codes, see [Calendar Server WCAP 7.0 \(WCAPbis\) Error Codes](#).

Examples

The following command sends a URL that deletes the calendar with calid /home/jdoe/newcal/:

```
http://<host>:<port>/wcap/deletecalendar.wcap?calid=/home/jdoe/newcal/&fmt-  
Corporation/CS 7u2-5.06//EN  
X-NSCP-CALPROPS-RELATIVE-CALID;X-S1CS-EMAIL=john.doe@sun.com:/home/jdoe/new
```

The following command is unsuccessful in its attempt to delete the calendar:

```
http://<host>:<port>/wcap/deletecalendar.wcap?fmt-out=text/calendar&id=<see  
Corporation/CS 7u2-5.06//EN  
X-NSCP-CALPROPS-RELATIVE-CALID;X-S1CS-EMAIL=john.doe@example.com:/home/john  
delete the default calendar.  
END:VCALENDAR
```

deleteevents_by_id.wcap

deleteevents_by_id.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

Deletes one or more events from a calendar specified by event identifier list.

Parameters

deleteevents_by_id Parameters

Parameter	Type	Multi-valued?	Purpose	Required	Default
calid	string	N	Calendar identifier of calendar from which to delete. The calid is the value given by the server as X-NSCP-CALPROPS-RELATIVE-CALID	N	Current user's default calendar calid
fmt-out	string	N	The format for the returned data. Three format types: text/calendar text/json text/xml	N	text/calendar
id	unique identifier string	N	The session identifier.	Y	NULL
mod	integer 1,2,3,4	Y	Recurrence modifier or semi-colon separated list of recurrence modifiers, indicating which instances to delete, for each event series. If a list, it must have same number of elements as the uid list. Values: 1 = THISINSTANCE 2 = THISANDFUTURE 3 = THISANDPRIOR 4 = THISANDALL	N	1
rid	string	Y	Recurrence identifier of the event, or semicolon-separated list of recurrence identifiers. If a list, it must have same number of elements as the uid list.	N	0
uid	string	Y	Unique identifier of an event to be deleted, or semicolon-separated list of unique identifiers.	Y	N/A

Description

Use this command to delete the specified event or events from the specified calendar.

Error Codes

If the operation is successful, the error number of 0 is appended to the error string. On failure, it returns the error code 6, `DELETE_EVENTS_BY_ID_FAILED`.

For a complete list of error codes, see [Calendar Server WCAP 7.0 \(WCAPbis\) Error Codes](#).

Recurrences

If the `rid` parameter is passed, the command also deletes recurrences, as specified by the `mod` parameter. To delete multiple events, specify a semicolon-separated list for the `uid`, `rid`, and `mod` parameters. The three lists must have the same number of elements. Each list element corresponds to the same number element in the other two lists.

Example

The following example deletes an instance (specified by `rid`) of an event specified by `uid`.

```
http://<host>:<port>/wcap/deleteevents_by_id.wcap?fmt-out=text/calendar
  &id=<session-id>
  &mod=1&rid=20111210T120000Z
  &uid=691a9af3-a3d4-4c19-966b-4cc1684d1faa
  &calid=/home/jdoe/calendar/

BEGIN:VCALENDAR
VERSION:2.0
PRODID:-//Oracle Corporation/CS 7u2-5.06//EN
BEGIN:VEVENT
UID:691a9af3-a3d4-4c19-966b-4cc1684d1faa
RECURRENCE-ID:RANGE:THISINSTANCE:20111210T120000Z
REQUEST-STATUS:2.0;Success. Delete successful.
END:VEVENT
X-NSCP-WCAP-ERRNO:0
END:VCALENDAR
```

deleteevents_by_range.wcap

deleteevents_by_range.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

Delete events from a calendar in a specified time range.

Parameters

deleteevents_by_range Parameters

Parameter	Type	Multi-valued?	Purpose	Required	Default
calid	string	Y	Semicolon-separated list of calendar identifiers from which to delete events. The calid is the value given by the server as X-NSCP-CALPROPS-RELATIVE-CALID.	N	Current user's default calendar calid
dtend	Date Time string	N	End time and date of events to be deleted. A value of 0 means delete all events until the end of time, since dtstart if specified.	N	0
dtstart	Date Time string	N	Start time and date of events to be deleted. A value of 0 means delete all events from the beginning of time, until dtend, if specified.	N	0
fmt-out	string	N	The format for the returned data. Format types: text/calendar text/json text/xml	N	text/calendar
id	unique identifier string	N	The session identifier.	Y	N/A
tzid	string	N	Default time zone to use if dtstart or dtend parameters are not in Zulu time. If not provided, the server's default time zone is used.	N	N/A

Description

Use this command to delete the events that fall completely within the specified range from the specified calendars. If a range is not specified (`dtstart` and `dtend`), this command deletes all events from the specified calendars.

You must specify the `id` parameter with the command unless the specified calendar is editable by anonymous users. The server returns data in the format specified by the `fmt-out` parameter. If this parameter is not passed, the data is returned in the default `text/calendar` format.

Error Codes

If the operation is successful, the error number of 0 is appended to the error string, X-NSCP-WCAP-ERRNO.

For a complete list of error codes, see [Calendar Server WCAP 7.0 \(WCAPbis\) Error Codes](#).

Example

The following example deletes events for the range specified by the `dtstart` and `dtend` parameters:

```
http://<host>:<port>/wcap/deletetodos_by_range.wcap
?id=<sessionid>
&calid=/home/jdoe/mycal/&fmt-out=text/calendar
&dtstart=20111113T110000Z&dtend=20111114T010000Z

BEGIN:VCALENDAR
VERSION:2.0
PRODID:-//Oracle Corporation/CS 7u2-5.06//EN
X-NSCP-CALPROPS-RELATIVE-CALID;X-SICS-EMAIL=john.doe@sun.com:/home/jdoe/myc
[20111113T110000Z---20111114T010000Z]
REQUEST-STATUS:2.0;Delete by range successful on calendar.
END:VTODO
BEGIN:VTODO
UID:e2f3536c-37b8-44e8-a269-eec060elfeac
RECURRENCE-ID:RANGE: [20111113T110000Z---20111114T010000Z]
REQUEST-STATUS:2.0;Delete by range successful on calendar.
END:VTODO
BEGIN:VTODO
UID:6155c5a9-cbbd-4351-a94b-144b71029978
RECURRENCE-ID:RANGE: [20111113T110000Z---20111114T010000Z]
REQUEST-STATUS:2.0;Delete by range successful on calendar.
END:VTODO
X-NSCP-WCAP-ERRNO:0
END:VCALENDAR
```

deletetodos_by_id.wcap

deletetodos_by_id.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

Deletes one or more todos (tasks) from a calendar specified by todo identifier list.

Parameters

deletetodos_by_id Parameter

Parameter	Types	Multi-valued?	Purposes	Required	Default
calid	string	N	Calendar identifier of calendar from which to delete. The calid is the value given by the server as X-NSCP-CALPROPS-RELATIVE-CALID	N	Current user's default calendar calid
fmt-out	string	N	The format for the returned data. Three format types: text/calendar text/json text/xml	N	text/calendar
id	unique identifier string	N	The session identifier.	Y	NULL
mod	integer 1,2,3,4	Y	Recurrence modifier or semi-colon separated list of recurrence modifiers, indicating which instances to delete, for each todo series. If a list, it must have same number of elements as the uid list. Values: 1 = THISINSTANCE 2 = THISANDFUTURE 3 = THISANDPRIOR 4 = THISANDALL	N	1
rid	string	Y	Recurrence identifier of the todo, or semicolon-separated list of recurrence identifiers. If a list, it must have same number of elements as the uid list.	N	0
uid	string	Y	Unique identifier of a todo to be deleted, or semicolon-separated list of unique identifiers.	Y	N/A

Description

Use this command to delete the specified todo or todos from the specified calendar.

Error Codes

If the operation is successful, the error number of 0 is appended to the error string. On failure, it returns the error code 16, `DELETE_TODOS_BY_ID_FAILED`.

For a complete list of error codes, see [Calendar Server WCAP 7.0 \(WCAPbis\) Error Codes](#).

Recurrences

If the `rid` parameter is passed, the command also deletes recurrences, as specified by the `mod`

parameter. To delete multiple todos, specify a semicolon-separated list for the `uid`, `rid`, and `mod` parameters. The three lists must have the same number of elements. Each list element corresponds to the same number element in the other two lists.

Example

The example deletes a todo with uid `be0b4804-541b-4c2e-a0a6-b6a44cc344ab`:

```
http://<host>:<port>/wcap/deletetodos_by_id.wcap
?id=<sessionid>&calid=/home/jdoe/mynewcal/
&fmt-out=text/calendar
&uid=be0b4804-541b-4c2e-a0a6-b6a44cc344ab

BEGIN:VCALENDAR
VERSION:2.0
PRODID:-//Oracle Corporation/CS 7u2-5.06//EN
BEGIN:VTODO
UID:be0b4804-541b-4c2e-a0a6-b6a44cc344ab
RECURRENCE-ID:RANGE:THISINSTANCE:0
REQUEST-STATUS:2.0;Success. Delete successful.
END:VTODO
X-NSCP-WCAP-ERRNO:0
END:VCALENDAR
```


deletetodos_by_range.wcap

deletetodos_by_range.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

Delete todos (tasks) from a calendar in a specified time range.

Parameters

deletetodos_by_range **Parameter**

Parameter	Types	Multi-valued?	Purposes	Required?	Default
calid	string	Y	Semicolon-separated list of calendar identifiers from which to delete todos. The calid is the value given by the server as X-NSCP-CALPROPS-RELATIVE-CALID.	N	Current user's default calendar calid
dtend	Date Time string	N	End time and date of todos to be deleted. A value of 0 means delete all todos until the end of time, since dtstart if specified.	N	0
dtstart	Date Time string	N	Start time and date of todos to be deleted. A value of 0 means delete all todos from the beginning of time, until dtend, if specified.	N	0
fmt-out	string	N	The format for the returned data. Format types: text/calendar text/json text/xml	N	text/calendar
id	unique identifier string	N	The session identifier.	Y	N/A
tzid	string	N	Default time zone to use if dtstart or dtend parameters are not in Zulu time. If not provided, the server's default time zone is used.	N	N/A

Description

Use this command to delete the todos that fall completely within the specified range from the specified calendars. If a range is not specified (`dtstart` and `dtend`), this command deletes all todos from the specified calendars.

You must specify the `id` parameter with the command unless the specified calendar is editable by anonymous users. The server returns data in the format specified by the `fmt-out` parameter. If this parameter is not passed, the data is returned in the default `text/calendar` format.

Error Codes

If the operation is successful, the error number of 0 is appended to the error string, X-NSCP-WCAP-ERRNO.

See also [Calendar Server WCAP 7.0 \(WCAPbis\) Error Codes](#).

Example

For example, assuming the user has write access to the calendars `/home/jdoe/calendar/` and `/home/john/calendar/`, the following URL would result in deleting **all** todos from the calendars `/home/jdoe/calendar/` and `/home/john/calendar/`:

```
http://<calendarserver>:<port>/wcap/deletetodos_by_range.wcap
      ?id=<session-id>
      &calid=/home/jdoe/calendar;/home/john/calendar/
      &dtstart=0
      &dtend=0
```

export.wcap

export.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

Export events and todos from a calendar to a file.

Parameters

export Parameters

Parameter	Type	Multi-valued?	Purpose	Required?	Default
calid	string	Y	A semicolon-separated list of calendar identifiers from which to export events and todos. The <code>calid</code> is the value given by the server as X-NSCP-CALPROPS-RELATIVE-CALID	N	Current user's default calendar <code>calid</code> .
content-out	string	N	Content type for output file. Currently only <code>text/calendar</code> is supported	N	<code>text/calendar</code>
dtend	Date Time string in UTC	N	End time and date of the events and todos to export. A value of 0 means export all components from the start date to the latest date.	N	0
dtstart	Date Time string in UTC	N	Start time and date of events and todos to export. A value of 0 means export all components from the earliest date to the end date.	N	0
fetchattach	integer (0, 1)	N	A boolean indicating if attachments must be returned with the calendar data. 0 = Return information about attachments 1 = Return entire attachments	N	0
id	unique identifier string	N	The session identifier.	Y	N/A

Description

Use this command to export events and todos from one or more specified calendars to a file. The contents of the file can later be imported to a calendar by using the `import` command.

Range

If you do not specify either the starting or ending date, all events and todos in the calendars are added to the file. If you specify a starting and ending date, the command exports only events and todos in the calendars that fall within the time range. Specify starting and ending dates in UTC time, which is indicated by `Z` at the end of the date-time string.

HTTP Post Examples

You must use this command with an HTTP `POST`. This is unlike other commands, which can be used

with an HTTP GET.

Example 1

The following HTTP POST message exports all components of the calendars `/home/jdoe/calendar/` and `/home/john/calendar/` to an iCalendar file named `export.ics`:

```
POST
http://<calendarserver>:<port>/wcap/export.wcap?id=<session-id>
      &calid=/home/jdoe/calendar;/home/john/calendar/
      &dtstart=0
      &dtend=0
      &content-out=text/calendar
```

Example 2

The following HTML generates a POST message using the `export` command, producing files in both iCalendar format:

```
<form METHOD=POST ENCTYPE="multipart/form-data"
NAME="john.ics"
ACTION="http://<calendarserver>:<port>/wcap/export.wcap
?id=t9u9m0eh8x5pu9b&calid=/home/john/calendar/&dtstart=0&dtend=0
      &content-out=text/calendar"\>
<ul\>
  <li\>Press Export ICAL Now:<input type="submit"
      value="Export ICAL now"\>
</li\> </ul\> </form\>
```

This is the output generated:

```
HTTP/1.0 200
Date: Thu, 03 Jun 2002 22:15:52 GMT
Content-type: text/calendar
Content-disposition: attachment; filename="john.ics"
Content-length: 7004
BEGIN:VCALENDAR
METHOD:PUBLISH
VERSION:6.0
BEGIN:VEVENT
UID:tm-001
RECURRENCE-ID:20020519T010000Z
DTSTAMP:20020603T221548Z
SUMMARY:Calendar Staff
DTSTART:20020518T170000Z
DTEND:20020518T190000Z
CREATED:20020603T024254Z
LAST-MODIFIED:20020603T024254Z
PRIORITY:1
SEQ:1
GEO:37.463581;-121.897606
DESC:This is the description for event with UID = tm-001
URL:http://calendarserver/susan?uid=tm-001
LOCATION:Green Conference Room
STATUS:CONFIRMED
TRANSP:OPAQUE
END:VEVENT
BEGIN:VEVENT
UID:tm-001
RECURRENCE-ID:20020526T010000Z
DTSTAMP:20020603T221548Z
SUMMARY:Calendar Staff
DTSTART:20020525T170000Z
DTEND:20020525T190000Z
CREATED:20020603T024254Z
LAST-MODIFIED:20020603T024254Z
PRIORITY:1
SEQ:1
GEO:37.463581;-121.897606
DESC:This is the description for event with UID = tm-001
URL:http://calendarserver/susan?uid=tm-001
LOCATION:Green Conference Room
STATUS:CONFIRMED
TRANSP:OPAQUE
END:VEVENT
END:VCALENDAR
```

fetchattachment.wcap

fetchattachment.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

Fetch attachment given a specific attachment identifier.

Parameters

fetchattachment Parameter

Parameter	Types	Multi-valued?	Purposes	Required	Default
attachid	string	N	Attachment identifier. This is the value of X-S1CS-ATTACH-ID which can be found in the output of the fetch commands.	Y	N/A
fmt-out	string	N	The format for the returned WCAP data. The three format types: text/calendar text/json text/xml Does not affect the attachment data.	N	text/calendar
id	unique identifier string	N	The session identifier.	Y	N/A

Description

Use this command to fetch the attachment specified by the attachment id.

Returns

Returns the specified attachment.

Error Codes

Returns WCAP_ERRNO 0 on success, and ATTACHMENT_NOT_FOUND 87 if specified attachment was not found. For a complete list of error codes, see [Calendar Server WCAP 7.0 \(WCAPbis\) Error Codes](#).

Example

The following example fetches an attachment named `attach1.txt`:

```
http://<host><port>/wcap/fetchattachment.wcap?id=<sessionid>
&attachid=/home/caluser1@example.com/calendar/dropbox/2e484927-faa0-434b-98
&fmt-out=text/json HTTP/1.1
```

fetchcomponents_by_lastmod.wcap

fetchcomponents_by_lastmod.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

Fetch a list of components that have changed since a specified time

Parameters.

fetchcomponents_by_lastmod Parameters

Parameter	Type	Multi-valued?	Purpose	Required?	Default
calid	string	Y	A semicolon-separated list of calendar identifiers. The calid is the value given by the server as X-NSCP-CALPROPS-RELATIVE-CALID	N	Current user's default calendar calid.
component-type	keyword (event, todo, all)	N	Indicates which components to return: event returns only events. todo returns only todos. all returns both events and todos. If an invalid value is passed in, the system assumes all.	N	all

<code>fetchattach</code>	integer (0, 1)	N	A boolean indicating if attachments must be returned with the calendar data. 0 = Return information about attachments 1 = Return entire attachments	N	0
<code>fmt-out</code>	string	N	The format for the returned data. The three format types are: <code>text/calendar</code> <code>text/json</code> <code>text/xml</code>	N	<code>text/calendar</code>
<code>id</code>	unique identifier string		The session identifier.	Y	N/A
<code>lastmod</code>	string	N	The sync token, value of <code>X-S1CS-SYNCTOKEN</code> returned by a previous execution of this command.	N	N/A
<code>maxResults</code>	integer	N	The maximum number of events and todos to be returned. When 0, no maximum is applied and the command returns all events and todos found.	N	0
<code>tzidout</code>	time zone ID string	N	Time zone in which to report returned data.	N	Zulu time

Description

Use this command to retrieve a list of events and todos that have changed (created, modified, or deleted) since a specific time, indicated by a sync-token.

Output Format

The server returns data in the format specified by the `fmt-out` parameter. If this parameter is not passed, the data is returned in the default `text/calendar` format.

maxResults Value

If you specify a maximum `n`, the command returns up to the first `n` events and todos. The response contains the `X-S1CS-PARTIAL-RESULT-COUNT` property if the result was partial due to the `maxResults` setting.

If the `maxResults` parameter is set to 0 or is not passed, then all relevant data is returned.

Returns

For each calendar specified in `calid`, the server returns the calendar's events and todos that changed since `lastmod`. The status of the event or todo is indicated by the `X-S1CS-MODSTATUS` property. The possible values are :

```
HTTP/1.1 201 CREATED
HTTP/1.1 200 OK
HTTP/1.1 404 Not Found
```

The command also returns a sync-token, `X-S1CS-SYNCTOKEN` that can be used as the value for the `lastmod` parameter for the next fetch command.

If no `lastmod` is specified, the server returns all events and todos that have changed, up to the specified maximum.

Error Codes

If the operation is successful, the error number of 0 is appended to the error string `X-WCAP-ERRNO`. For a complete list of error codes, see [Calendar Server WCAP 7.0 \(WCAPbis\) Error Codes](#).

Examples

The following example shows `fetchcomponents_by_lastmod` fetching tasks only, with no sync token (so full sync) requesting a maximum of ten results.

```
http://<host>:<port>/wcap/fetchcomponents_by_lastmod.wcap?fmt-out=text/calendar
&id=<session-id>
    &component-type=todo
    &maxResults=10
    &calid=/home/jdoe/calendar/

BEGIN:VCALENDAR
VERSION:2.0
PRODID:-//Oracle Corporation/CS 7u2-5.06//EN
X-NSCP-CALPROPS-RELATIVE-CALID;X-S1CS-EMAIL=John.doe@example.com:/home/jdoe
200 OK
UID:e701c8a9-69a1-4ccb-85ba-24fd6142
DTSTAMP:20111116T081648Z
REQUEST-STATUS:2.0;Success
END:VTODO
X-S1CS-SYNCTOKEN:1323174999000
X-NSCP-WCAP-ERRNO:0
END:VCALENDAR
```

The following example shows `fetchcomponents_by_lastmod` fetching tasks and events, with a sync token (so request changes since last sync). Nothing is returned as as nothing has changed.

```
http://<host>:<port>/wcap/fetchcomponents_by_lastmod.wcap?fmt-out=text/cale
&id=<session-id>
    &component-type=all
    &calid=/home/jdoe/calendar/
    &lastmod=1323067828000
```

```
BEGIN:VCALENDAR
```

```
VERSION:2.0
```

```
PRODID:-//Oracle Corporation/CS 7u2-5.06//EN
```

```
X-NSCP-CALPROPS-RELATIVE-CALID;X-S1CS-EMAIL=john.doe@example.com:/home/jdoe
```

fetchcomponents_by_range.wcap

fetchcomponents_by_range.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

Retrieve calendar events and todos from specified calendars, in a specified range.

Parameters

fetchcomponents_by_range Parameters

Parameter	Type	Multi-valued?	Purpose	Required?	Default
calid	string	Y	A semicolon-separated list of calendar identifiers. The <code>calid</code> is the value given by the server as X-NSCP-CALPROPS-RELATIVE-CALID.	N	Current default value is <code>calid</code>
component-type	keyword (event, todo, all)	N	Indicates which components to return: event returns only events. todo returns only todos. all returns both events and todos. If an invalid value is passed in, the system assumes <code>all</code> .	N	<code>all</code>

compressed	integer (0,1)	N	Boolean. compressed=0 returns less data if expansion is requested with recurring=0. Specifically, it does not return the following parameters: rrules, rdates, exrules, and exdates. For compressed=1, all recurrence data is returned.	N	0
dtend	Date Time string	N	End time and date of events or Due time and date of todos to be returned. A value of 0 means fetch all events and todos since dtstart, if specified. Start and end timings are required unless the recurring=1 parameter is passed in. The dtend=0 default is invalid if recurring=0.	N (if recurring=1 parameter is passed in) Y (if recurring=0 is passed in or no recurring parameter is passed in)	0
dtstart	Date Time string	N	Start time and date of events or tasks to be returned. A value of 0 means fetch all events and tasks from the beginning of time until dtend, if specified. Start and end timings are required unless the recurring=1 parameter is passed in. The dtstart=0 default is invalid if recurring=0.	N (if recurring=1 parameter is passed in) Y (if recurring=0 is passed in or no recurring parameter is passed in)	0
fetchattach	integer (0, 1)	N	A boolean indicating if attachments must be returned with the calendar data. 0 = Return information about attachments 1 = Return entire attachments	N	0

filter	string	N	<p>A string containing a filter that follows the XPath Syntax. The property names that can be used in the filter are:</p> <ul style="list-style-type: none"> • ATTENDEE • ORGANIZER • SUMMARY • DESCRIPTION • LOCATION • CLASS • CATEGORIES • ALL <p>ALL searches all property names.</p> <p>Filter Strings can be constructed using:</p> <ul style="list-style-type: none"> • Binary equality operators: '=' ; '!=' <p>Only the binary equality operator (=) is supported with ALL.</p> <p>Note: Enclose literal strings with single or double quotation marks; encode special URL characters.</p> <ul style="list-style-type: none"> • Binary logical operators: 'and' ; 'or' • Functional calls: <ul style="list-style-type: none"> • contains (PropertyName, aArg) • starts-with (PropertyName, aArg) • ends-with (PropertyName, aArg) • equals (PropertyName, aArg) 	N	NULL
fmt-out	string		<p>The format for the returned data.</p> <p>The three format types are: text/calendar text/json text/xml</p>	N	text/calendar
id	unique identifier string	N	The session identifier.	N	N/A

maxResults	integer	N	The maximum number of events and todos to be returned. When 0 or a negative number, no maximum is applied and the command returns all events and todos found.	N	0
recurring	integer (0, 1)	N	1 = Return all components in compressed form. The compressed form has master entry plus exceptions. 0 = Return components as individual instances, without master record and exceptions.	N	0 (not compressed)
tzid	time zone ID string	N	Default time zone to use if dtstart, or dtend parameters are not in Zulu time. For example: "America/Los_Angeles"	N	Server's time zone
tzidout	time zone ID string	N	Time zone in which to report returned data.	N	Zulu time

Description

Use this command to retrieve events and todos from one or more specified calendars.

Filter Parameter

Filter strings can be constructed using the following:


- Binary equality operators: '=' ; '!='
Note: Enclose literal strings with single or double quotation marks; encode special URL characters.
- Binary logical operators: 'and' ; 'or'
- Functional calls:
 - contains(PropertyName, aArg)
 - starts-with(PropertyName, aArg)
 - ends-with(PropertyName, aArg)
 - equals(PropertyName, aArg)
- Search by All='string' searches if any of the following properties contains the string passed:
 - "ATTENDEE"
 - "ORGANIZER"
 - "DESCRIPTION"
 - "CATEGORIES"
 - "CLASS"
 - "LOCATION"
 - "SUMMARY"

Only the binary equality operator (=) is supported with ALL. For example, (ALL!='string') is an invalid search. The binary logical operators and the function calls are not supported with ALL either.

Returns

For each calendar specified in calid, the server returns the events and todos of that calendar that fall

within the range specified by `dtstart` and `dtend`. Todos with no due date and overdue incomplete todos are also returned. If a filter is specified, additional filtering is done based on that.

 Tasks returned by this WCAP Command:

- Tasks due within the date range
- Overdue tasks
- Tasks that are never due

If the times specified in the `dtstart` and `dtend` parameters are not Zulu time, the system uses the time zone specified in the `tzid` parameter to translate the times into Zulu time for data retrieval. If the `tzid` parameter is missing, the system uses the server's default time zone.

The system uses the `tzidout` parameter to determine into what time zone to translate retrieved data before returning it. If the `tzidout` parameter is missing, the system returns the data in Zulu time.

If neither the starting nor ending date-time is specified, the server returns all events and todos, up to the specified maximum. Start and end timings are required unless the `recurring=1` parameter is passed in.

Output Format

The server returns data in the format specified by the `fmt-out` parameter. If this parameter is not passed, the data is returned in the default `text/calendar` format.

maxResults Value

If you specify a maximum `n`, the command returns up to the first `n` events and todos in the specified range. The response contains the `X-SICS-PARTIAL-RESULT-COUNT` property if the result was partial due to the `maxResults` setting.

If the `maxResults` parameter is set to 0 or a negative number, no maximum is applied and the command returns all events and todos found.

Error Codes

If the operation is successful, the error number 0 is appended to the error string. If a calendar cannot be accessed or is missing, the error number is appended to the error string. For a complete list of error codes, see [Calendar Server WCAP 7.0 \(WCAPbis\) Error Codes](#).

Examples

This example searches for all events with `jdoe` as attendee in a given time period.

```

http://<hostname>:<port>/wcap/fetchcomponents_by_range.wcap?id=<session-id>
&content-type=event
    &calid=/home/jdoe/calendar;/home/jdoe@example.com/Testcalendar/
    &fmt-out=text/calendar
    &tzidout=Europe/Paris&recurring=1

&dtstart=20120716T000000Z&dtend=20120728T000000Z&filter=%28starts-with%28AT
Corporation/CS 7u2-5.06//EN
X-NSCP-CALPROPS-RELATIVE-CALID;X-S1CS-EMAIL=jdoe@example.com:/home/jdoe/cal
Events
DTSTART;TZID=Europe/Paris:20120727T070000
DTEND;TZID=Europe/Paris:20120727T080000
CREATED:20120726T161511Z
LAST-MODIFIED:20120726T161559Z
CATEGORIES:Business
ORGANIZER;PARTSTAT=ACCEPTED;ROLE=CHAIR;RSVP=TRUE:mailto:jdoe@example.com
TRANSP:OPAQUE
LOCATION:IDC Bangalore
DESCRIPTION:Test events.
ATTENDEE;CN=caluser13;PARTSTAT=ACCEPTED;ROLE=REQ-PARTICIPANT;SCHEDULE-STATU
Corporation/CS 7u2-5.06//EN
X-NSCP-CALPROPS-RELATIVE-CALID;X-S1CS-EMAIL=jdoe@example.com:/home/jdoe/exa

```

This example searches for all events with given description and in the given time period, in expanded format.

```

http://<host>:<port>/wcap/fetchcomponents_by_range.wcap?fmt-out=text/calendar
&id=<session-id>
    &content-type=event
    &filter=contains%28DESCRIPTION,%20%27event%27%29
    &calid=/home/jdoe/calendar;/home/jdoe/calendar/
    &dtstart=20111101T010000Z&&dtend=20111230T120000Z
    &recurring=0

BEGIN:VCALENDAR
VERSION:2.0
PRODID:-//Oracle Corporation/CS 7u2-5.06//EN
X-NSCP-CALPROPS-RELATIVE-CALID;X-S1CS-EMAIL=john.doe@example.com:/home/jdoe
Corporation/CS 7u2-5.06//EN
X-NSCP-CALPROPS-RELATIVE-CALID;X-S1CS-EMAIL=john.doe@example.com:/home/jdoe
December Calculator
DTSTART:20111202T010000Z
DTEND:20111203T120000Z
CREATED:20111202T091551Z
LAST-MODIFIED:20111202T091551Z
PRIORITY:5
CLASS:PRIVATE
ORGANIZER;CN=John Doe:mailto:john.doe@example.com
STATUS:CONFIRMED
LOCATION:Asia/Kolkatta
DESCRIPTION:December Event
ATTENDEE;CN=jsmith;SCHEDULE-STATUS=1.2:mailto:john.smith@example.com
ATTENDEE:mailto:john.doe@example.com
CONTACT:john.doe@example.com
END:VEVENT

BEGIN:VEVENT
UID:45fb3076-df47-4fbb-9c28-3484f36178de
DTSTAMP:20111202T091724Z
SUMMARY:New December Calculator
DTSTART:20111202T010000Z
DTEND:20111203T120000Z
CREATED:20111202T091724Z
LAST-MODIFIED:20111202T091724Z
PRIORITY:5
CLASS:PRIVATE
ORGANIZER;CN=John Doe:mailto:john.doe@example.com
STATUS:CONFIRMED
LOCATION:Asia/Kolkatta
DESCRIPTION:December Event
ATTENDEE;CN=jsmith;SCHEDULE-STATUS=1.2:mailto:john.smith@example.com
ATTENDEE:mailto:john.doe@example.com
CONTACT:john.doe@example.com
END:VEVENT
X-S1CS-PARTIAL-RESULT-COUNT:2
X-NSCP-WCAP-ERRNO:0
END:VCALENDAR

```

This example searches for all events with `jsmith` as attendee in a given time period with maximum results accepted set to 1. The response contains the `X-S1CS-PARTIAL-RESULT-COUNT` property that

indicates the result was partial due to the `maxResults` setting.

```
http://<host>:<port>/wcap/fetchcomponents_by_range.wcap?fmt-out=text/calend
&id=<session-id>
    &content-type=event
    &filter=contains%28ATTENDEE,%20%27jsmith%27%29
    &calid=/home/jdoe/calendar/
    &dtstart=20111101T010000Z&maxResults=1
    &dtend=20111230T120000Z
    &recurring=1

BEGIN:VCALENDAR
VERSION:2.0
PRODID:-//Oracle Corporation/CS 7u2-5.06//EN
X-NSCP-CALPROPS-RELATIVE-CALID;X-S1CS-EMAIL=john.doe@example.com:/home/jdoe
December Calendar
DTSTART:20111202T010000Z
DTEND:20111203T120000Z
CREATED:20111202T091551Z
LAST-MODIFIED:20111202T091551Z
PRIORITY:5
CLASS:PRIVATE
ORGANIZER;CN=John Doe:mailto:john.doe@example.com
STATUS:CONFIRMED
LOCATION:Asia/Kolkatta
DESCRIPTION:December Event
ATTENDEE;CN=jsmith;SCHEDULE-STATUS=1.2:mailto:john.smith@example.com
ATTENDEE:mailto:john.doe@example.com
CONTACT:john.doe@example.com
END:VEVENT
X-S1CS-PARTIAL-RESULT-COUNT:1
X-NSCP-WCAP-ERRNO:0
END:VCALENDAR
```

fetchevents_by_id.wcap

fetchevents_by_id.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

This command retrieves specific calendar events.

Parameters

fetchevents_by_id Parameters

Parameter	Type	Multi-valued?	Purpose	Required?	Default
calid	string	N	Calendar identifier of calendar from which to fetch. The calid is the value given by the server as X-NSCP-CALPROPS-RELATIVE-CALID .	N	Current user's default calendar calid
compressed	integer (0,1)	N	compressed=0, returns less data of recurring events in expanded mode. Specifically, it does not return the following parameters: rrules, rdates, exrules, and exdates. For compressed=1, all recurrence data is returned.	N	0

fmt-out	string	N	The format for the returned data. The three format types are: text/calendar text/json text/xml	N	text/calendar
id	unique identifier string	N	The session identifier.	Y	N/A
recurring	integer (0, 1)	N	1 = Returns all components in compressed form, which contains a master entry plus exceptions. 0 = Returns components expanded into individual instances. The rid parameter is also required.	N	0 Not compressed
rid	RFC5545 Date Time string	N	The recurrence identifier for the event. For a nonrecurring event or entire recurring series, set to 0.	N	0
tzid	time zone ID string	N	Time zone to use if the rid parameter is not in Zulu time. For example, "America/Los_Angeles."	N	Server's default time zone
tzidout	time zone ID string	N	Time zone that returned data should be translated to. Special value X-S1CS-TZNATIVE will return data in the original timezone it was created in.	N	Returns data in Zulu time
uid	string	N	The unique identifier for the event.	Y	N/A

Description

Use this command to retrieve the specified event or event series from the specified calendar. You must specify the `id` parameter with the command unless the specified calendar is a publicly readable calendar. The command returns recurrences as specified by the `mod` parameter.

Output Format

The server returns data in the format specified by the `fmt-out` parameter. If this parameter is not passed, the data is returned in the default format.

Returns

The system uses the `tzidout` parameter to determine what time zone into which to translate retrieved data before returning it. If the `tzidout` parameter is missing, the system returns the data in Zulu time. Special value `X-S1CS-TZNATIVE` for `tzidout` will return data in the original timezone it was created in.

Error Codes

If the operation is successful, the error number of 0 is appended to the WCAP error string. `COMPONENT_NOT_FOUND`, 59 is returned if a matching event is not found. For a complete list of error codes, see [Calendar Server WCAP 7.0 \(WCAPbis\) Error Codes](#).

Example

This query retrieves an event with a specific id.

```
http://<host>:<port>/wcap/fetchevents_by_id.wcap
  ?fmt-out=text/calendar
  &id=<session-id>
  &compressed=0
  &recurring=1&rid=0
  &calid=/home/jdoe/calendar/

BEGIN:VCALENDAR
VERSION:2.0
PRODID:-//Oracle Corporation/CS 7u2-5.06//EN
X-NSCP-CALPROPS-RELATIVE-CALID;X-S1CS-EMAIL=john.doe@example.com:/home/jdoe
Doe:mailto:john.doe@example.com
STATUS:TENTATIVE
LOCATION:Asia/Kolkatta
ATTENDEE;CN=jsmith;SCHEDULE-STATUS=1.2:mailto:john.smith@example.com
ATTENDEE:mailto:john.doe@example.com
END:VEVENT
X-NSCP-WCAP-ERRNO:0
END:VCALENDAR
```


fetchtodos_by_id.wcap

fetchtodos_by_id.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

Retrieve specific calendar todos.

Parameters

fetchtodos_by_id Parameters

Parameter	Type	Multi-valued?	Purpose	Required?	Default
calid	string	N	Calendar identifier of calendar from which to fetch. The calid is the value given by the server as X-NSCP-CALPROPS-RELATIVE-CALID	N	Current user's default calendar calid
compressed	integer (0,1)	N	compressed=0, returns less data of recurring todos in expanded mode. Specifically, it does not return the following parameters: rrules, rdates, exrules, and exdates. For compressed=1, all recurrence data is returned.	N	0

<code>fmt-out</code>	string	N	The format for the returned data. The three format types are: <code>text/calendar</code> <code>text/json</code> <code>text/xml</code>	N	<code>text/calendar</code>
<code>id</code>	unique identifier string	N	The session identifier.	Y	N/A
<code>recurring</code>	integer (0, 1)		1 = Returns all components in compressed form, which contains a master entry plus exceptions. 0 = Returns components expanded into individual instances. The <code>rid</code> parameter is also required.	N	0 Not compressed
<code>rid</code>	RFC5545 Date Time string	N	The recurrence identifier for the todo. For a nonrecurring todo, set to 0.	N	0
<code>tzid</code>	time zone ID string	N	Time zone to use if the <code>rid</code> parameter is not in Zulu time. For example, "America/Los_Angeles."	N	Server's default time zone
<code>tzidout</code>	time zone ID string	N	Time zone to which returned data should be translated. Special value X-S1CS-TZNATIVE will return data in the original timezone it was created in.	N	Returns data in Zulu time
<code>uid</code>	string	N	The unique identifier for the todo.	Y	N/A

Description

Use this command to retrieve the specified todo or todo series from the specified calendar. You must specify the `id` parameter with the command unless the specified calendar is a publicly readable calendar. The command returns recurrences as specified by the `mod` parameter.

Output Format

The server returns data in the format specified by the `fmt-out` parameter. If this parameter is not passed, the data is returned in the default format.

Returns

The system uses the `tzidout` parameter to determine into what time zone to translate retrieved data

before returning it. If the `tzidout` parameter is missing, the system returns the data in Zulu time. Special value `X-S1CS-TZNATIVE` for `tzidout` will return data in the original timezone it was created in.

Error Codes

If the operation is successful, the error number of 0 is appended to the WCAP error string. `COMPONENT_NOT_FOUND`, 59 is returned if a matching todo is not found. For a complete list of error codes, see [Calendar Server WCAP 7.0 \(WCAPbis\) Error Codes](#).

Example

This query retrieves a specific instance by requesting a specific rid and uid.

```
http://<host>:<port>/wcap/fetchtodos_by_id.wcap?fmt-out=text/calendar
    &id=<session-id>
    &compressed=1&recurring=0
    &rid=20111210T120000Z

&uid=6b32f245-44bb-4f7c-8bcd-9b6e520d8a52&calid=/home/jdoe/calendar/

BEGIN:VCALENDAR
VERSION:2.0
PRODID:-//Oracle Corporation/CS 7u2-5.06//EN
X-NSCP-CALPROPS-RELATIVE-CALID;X-S1CS-EMAIL=john.doe@example.com:/home/jdoe
Doe:mailto:john.doe@example.com
STATUS:NEEDS-ACTION
LOCATION:Asia/Kolkatta
ATTENDEE;CN=jsmith;SCHEDULE-STATUS=1.2:mailto:john.smith@example.com
ATTENDEE:mailto:john.doe@example.com
ATTENDEE;CN=jsmith;SCHEDULE-STATUS=1.2:mailto:john.smith@example.com
ATTENDEE:mailto:john.doe@example.com
END:VTODO
X-NSCP-WCAP-ERRNO:0
END:VCALENDAR
```

get_accountprops.wcap

get_accountprops.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

Retrieve account properties. The properties include the scheduling permissions, the access rights the executor of the command has on the account, the email notification flag, the list of recipients of email notifications, and the attendance flag and the owner of the resource.

Parameters

get_accountprops Parameters

Parameter	Type	Multi-valued?	Purpose	Required?	Default
fmt-out	string	N	The format for the returned data. Three format types are: text/calendar text/json text/xml	N	text/calendar
id	unique identifier string	N	The session identifier.	Y	Not applicable
account	string	Y	Semicolon separated list of account identifiers provided as email addresses, for users or resources for which the account properties are being retrieved.	N	Logged in user's account
onbehalfof	string	N	A single account identifier (email address). The authenticated user executing the <code>get_accountprops</code> command is requesting "myrights" information about the accounts listed in the <code>account</code> parameter. The request is made from the viewpoint of the "onbehalfof" account.	N	Not applicable

Description

Use this command to retrieve the account properties for the specified account(s), as available to the logged in user.

In reference to the "onbehalfof" parameter, the delegator is the user who gives authorization to a delegate to manage the user's account. In other words, delegators give 'a' (all) rights on any of their calendars to the delegates. When a delegate requests information about other accounts on behalf of a delegator's account, the delegate receives type, status, and myrights settings for those accounts from the viewpoint of the delegator.

Returns

The command returns the account properties.

Property	Description	Possible Values
X-NSCP-WCAP-PREF-mail	Email address of the resource	An email address
X-S1CS-ACCOUNT-STATUS	LDAP information of type and status	ACTIVE, INACTIVE, or DELETED
X-S1CS-ACCOUNT TYPE	Type of account	USER, RESOURCE, or GROUP
X-S1CS-MYRIGHTS	User's current rights	Any of the privilege settings (see Retrieving Access Control Information for more information)
X-NSCP-CALPROPS-ACCESS-CONTROL-ENTRY	Current ACL settings (need manage rights to get the ACL string)	ACL settings (see Retrieving Access Control Information for more information)
X-S1CS-NOTIF-EMAIL-ENABLED	Email notification flag	0 = no email notification. 1 = email notification enabled.
X-S1CS-NOTIF-EMAIL-RECIPIENTS	List of recipients of email notifications	list of email addresses
X-S1CS-ATTENDANCE-FLAG	A flag that controls the behavior of an invitation	0 - Does not perform autoaccept, does not check booking conflict, does not check recurrence on invitations 1 - Automatically accepts invitations 2 - Automatically declines if invitation results in booking conflict 3 - Automatically accepts invitation and automatically declines on booking conflict 4 - Automatically declines recurring meeting invitations 5 - Automatically accepts invitations and automatically declines recurring meeting invitations 6 - Automatically declines recurring invitations and invitations that cause a booking conflict 7 - Automatically accepts invitations, automatically declines recurring invitations and invitations that cause a booking conflict
X-NSCP-CALPROPS-PRIMARY-OWNER	The owner of the resource	An email address.

Error Codes

The command returns:

```
X-NSCP-WCAP-ERRNO=0: No errors
X-NSCP-WCAP-ERRNO=93: Get failed because of an invalid userid
X-NSCP-WCAP-ERRNO=94: User has no schedule permissions
```

In a co-deployment setup with both Calendar Server 7 and Calendar Server 6, the `get_accountprops` command returns error code 93 for Calendar Server 6 indicating it is an external user as far as the Calendar Server 7 deployment is concerned.

For a complete list of error codes, see [Calendar Server WCAP 7.0 \(WCAPbis\) Error Codes](#).

Examples

This example shows how to retrieve the account properties for another user:

```
http://<host>:<port>/wcap/get_accountprops.wcap?account=caluser2@sun.com&fr
Corporation/CS 7u2-5.06//EN
X-NSCP-WCAP-PREF-mail:caluser2@sun.com
X-S1CS-ACCOUNT-TYPE:USER
X-S1CS-ACCOUNT-STATUS:ACTIVE
X-S1CS-MYRIGHTS:n
X-NSCP-WCAP-ERRNO:0
END:VCALENDAR
```

This example shows how to get account properties for the logged-in user:

```
http://<host>:<port>/wcap/get_accountprops.wcap?fmt-out=text/calendar&id=<e
Corporation/CS 7u2-5.06//EN
X-NSCP-WCAP-PREF-mail:john.doe@example.com
X-S1CS-ACCOUNT-TYPE:USER
X-S1CS-ACCOUNT-STATUS:ACTIVE
X-NSCP-CALPROPS-ACCESS-CONTROL-ENTRY:@:s
X-S1CS-MYRIGHTS:m
X-S1CS-NOTIF-EMAIL-ENABLED:1
X-S1CS-NOTIF-EMAIL-RECIPIENTS:john.doe@example.com
X-S1CS-NOTIF-EMAIL-RECIPIENTS:john.smith@example.com
X-S1CS-ATTENDANCE-FLAG:5
X-NSCP-CALPROPS-PRIMARY-OWNER:john.doe@example.com
X-NSCP-WCAP-ERRNO:0
END:VCALENDAR
```

This example shows some possible output using the `onbehalfof` parameter. It gets the "myrights" values for `userB` and `userC` from the viewpoint of `userA`. In this example, `userA` is the delegator, `userX` is the delegate, and `userB` and `userC` are the target accounts. The `get_accountprops` command is run by `userX` to see what scheduling rights `userA` has for `userB` and `userC`.

```
http://<host>:<port>/wcap/get_accountprops.wcap?onbehalfof=userA@example.co
Corporation/CS 8-0.04//EN",
"METHOD": "PUBLISH",
"iCal": [
{
"X-NSCP-WCAP-PREF-mail": "userB@sun.com",
"X-S1CS-ACCOUNT-TYPE": "USER",
"X-S1CS-ACCOUNT-STATUS": "ACTIVE",
"X-S1CS-MYRIGHTS": "s",
"X-NSCP-WCAP-ERRNO": "0"
},
{
"X-NSCP-WCAP-PREF-mail": "userC@sun.com",
"X-S1CS-ACCOUNT-TYPE": "USER",
"X-S1CS-ACCOUNT-STATUS": "ACTIVE",
"X-S1CS-MYRIGHTS": "n",
"X-NSCP-WCAP-ERRNO": "0"
}
]
```


get_all_timezones.wcap

get_all_timezones.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

Retrieve data about all time zones supported by the server as VTIMEZONE components.

Parameters

get_all_timezones Parameters

Parameter	Type	Multi-valued?	Purpose	Required	Default
fmt-out	string	N	The format for the returned data. Three format types: text/calendar text/json text/xml	N	text/calendar
id	unique identifier string	N	The session identifier.	N	N/A

Description

Use this command to retrieve data about all time zones that are supported by the server in VTIMEZONE format.

The server returns data in the format specified by the `fmt-out` parameter. If you do not pass in the `fmt-out` parameter, the server uses the default `text/calendar` format.

Error Codes

Server returns error code 0 on success. For a complete list of error codes, see [Calendar Server WCAP 7.0 \(WCAPbis\) Error Codes](#).

Example

This example gets all time zones.

```
http://<host>:<port>/wcap/get_all_timezones.wcap?fmt-out=text/calendar&id=<
Corporation/CS 7u2-5.06//EN
BEGIN:VTIMEZONE
TZID:Africa/Cairo
X-S1CS-TZID-ALIAS:Egypt Standard Time
X-S1CS-TZID-ALIAS:Egypt
BEGIN:STANDARD
TZOFFSETFROM:+0300
TZOFFSETTO:+0200
TZNAME:EET
DTSTART:20101001T000000
RRULE:FREQ=YEARLY;BYYEARDAY=-92,-93,-94,-95,-96,-97,-98;BYDAY=FR
END:STANDARD
BEGIN:STANDARD
TZOFFSETFROM:+0200
TZOFFSETTO:+0200
TZNAME:EET
DTSTART:20030925T230000
RDATE:20030925T230000
RDATE:20040930T230000
RDATE:20050929T230000
RDATE:20060921T230000
RDATE:20070906T230000
RDATE:20080828T230000
RDATE:20090820T230000
RDATE:20100811T000000
END:STANDARD
BEGIN:DAYLIGHT
TZOFFSETFROM:+0200
TZOFFSETTO:+0300
TZNAME:EEST
DTSTART:19950428T000000
RRULE:FREQ=YEARLY;BYMONTH=4;BYDAY=-1FR
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0300
TZOFFSETTO:+0200
TZNAME:EET
DTSTART:19400930T233640
RDATE:20020927T000000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Africa/Casablanca
X-S1CS-TZID-ALIAS:Greenwich Standard Time
BEGIN:DAYLIGHT
TZOFFSETFROM:+0000
TZOFFSETTO:+0100
TZNAME:WEST
DTSTART:19390911T233640
RDATE:20080601T000000
RDATE:20090601T000000
RDATE:20100502T000000
```

```

END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0000
TZOFFSETTO:+0100
TZNAME:CET
DTSTART:19840316T000000
RDATE:19840316T000000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Africa/Johannesburg
X-S1CS-TZID-ALIAS:South Africa Standard Time
BEGIN:DAYLIGHT
TZOFFSETFROM:+0200
TZOFFSETTO:+0300
TZNAME:SAST
DTSTART:19420920T010000
RDATE:19430919T000000
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0300
TZOFFSETTO:+0200
TZNAME:SAST
DTSTART:19430321T010000
RDATE:19440319T000000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Africa/Lagos
X-S1CS-TZID-ALIAS:W. Central Africa Standard Time
BEGIN:STANDARD
TZOFFSETFROM:+001336
TZOFFSETTO:+0100
TZNAME:WAT
DTSTART:19190831T233640
RDATE:19190831T231320
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Africa/Tripoli
X-S1CS-TZID-ALIAS:Libya
BEGIN:STANDARD
TZOFFSETFROM:+0200
TZOFFSETTO:+0200
TZNAME:EET
DTSTART:19971004T000000
RDATE:19971004T000000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Africa/Windhoek
BEGIN:DAYLIGHT
TZOFFSETFROM:+0100
TZOFFSETTO:+0200
TZNAME:WAST
DTSTART:19940904T020000

```

```

RRULE:FREQ=YEARLY;BYMONTH=9;BYDAY=1SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0200
TZOFFSETTO:+0100
TZNAME:WAT
DTSTART:19950402T020000
RRULE:FREQ=YEARLY;BYMONTH=4;BYDAY=1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:America/Adak
X-S1CS-TZID-ALIAS:US/Aleutian
X-S1CS-TZID-ALIAS:America/Atka
BEGIN:DAYLIGHT
TZOFFSETFROM:-1000
TZOFFSETTO:-0900
TZNAME:HADT
DTSTART:20070311T020000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=2SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:-0900
TZOFFSETTO:-1000
TZNAME:HAST
DTSTART:20071104T020000
RRULE:FREQ=YEARLY;BYMONTH=11;BYDAY=1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:America/Anchorage
X-S1CS-TZID-ALIAS:Alaskan Standard Time
X-S1CS-TZID-ALIAS:US/Alaska
BEGIN:DAYLIGHT
TZOFFSETFROM:-0900
TZOFFSETTO:-0800
TZNAME:AKDT
DTSTART:20070311T020000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=2SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:-0800
TZOFFSETTO:-0900
TZNAME:AKST
DTSTART:20071104T020000
RRULE:FREQ=YEARLY;BYMONTH=11;BYDAY=1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:America/Argentina/Buenos_Aires
X-S1CS-TZID-ALIAS:SA Eastern Standard Time
BEGIN:STANDARD
TZOFFSETFROM:-0300
TZOFFSETTO:-0300
TZNAME:ART
DTSTART:20000303T000000

```

```

RDATE:20000303T000000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:America/Caracas
BEGIN:STANDARD
TZOFFSETFROM:-0400
TZOFFSETTO:-0430
TZNAME:VET
DTSTART:20071209T030000
RDATE:20071209T030000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:America/Chicago
X-S1CS-TZID-ALIAS:Central Standard Time
X-S1CS-TZID-ALIAS:US/Central
BEGIN:DAYLIGHT
TZOFFSETFROM:-0600
TZOFFSETTO:-0500
TZNAME:CDT
DTSTART:20070311T020000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=2SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:-0500
TZOFFSETTO:-0600
TZNAME:CST
DTSTART:20071104T020000
RRULE:FREQ=YEARLY;BYMONTH=11;BYDAY=1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:America/Costa_Rica
X-S1CS-TZID-ALIAS:Canada Central Standard Time
X-S1CS-TZID-ALIAS:Central America Standard Time
BEGIN:DAYLIGHT
TZOFFSETFROM:-0600
TZOFFSETTO:-0500
TZNAME:CDT
DTSTART:19790225T000000
RDATE:19920118T000000
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:-0500
TZOFFSETTO:-0600
TZNAME:CST
DTSTART:19790603T000000
RDATE:19920315T000000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:America/Cuiaba
BEGIN:DAYLIGHT
TZOFFSETFROM:-0400
TZOFFSETTO:-0300

```

```

TZNAME:AMST
DTSTART:20081019T000000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=3SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:-0400
TZOFFSETTO:-0400
TZNAME:AMT
DTSTART:20380221T000000
RRULE:FREQ=YEARLY;BYMONTH=2;BYDAY=3SU
END:STANDARD
BEGIN:STANDARD
TZOFFSETFROM:-0300
TZOFFSETTO:-0400
TZNAME:AMT
DTSTART:19320331T233640
RDATE:20020217T000000
RDATE:20030216T000000
RDATE:20050220T000000
RDATE:20060219T000000
RDATE:20070225T000000
RDATE:20080217T000000
RDATE:20090215T000000
RDATE:20100221T000000
RDATE:20110220T000000
END:STANDARD
BEGIN:STANDARD
TZOFFSETFROM:-0400
TZOFFSETTO:-0400
TZNAME:AMT
DTSTART:20030924T000000
RDATE:20030924T000000
RDATE:20041001T000000
RDATE:20120226T000000
RDATE:20130217T000000
RDATE:20140216T000000
RDATE:20150222T000000
RDATE:20160221T000000
RDATE:20170219T000000
RDATE:20180218T000000
RDATE:20190217T000000
RDATE:20200216T000000
RDATE:20210221T000000
RDATE:20220220T000000
RDATE:20230226T000000
RDATE:20240218T000000
RDATE:20250216T000000
RDATE:20260222T000000
RDATE:20270221T000000
RDATE:20280220T000000
RDATE:20290218T000000
RDATE:20300217T000000
RDATE:20310216T000000
RDATE:20320215T000000
RDATE:20330220T000000
RDATE:20340226T000000

```

```

RDATE:20350218T000000
RDATE:20360217T000000
RDATE:20370222T000000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:America/Denver
X-S1CS-TZID-ALIAS:Mountain Standard Time
X-S1CS-TZID-ALIAS:US/Mountain
BEGIN:DAYLIGHT
TZOFFSETFROM:-0700
TZOFFSETTO:-0600
TZNAME:MDT
DTSTART:20070311T020000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=2SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:-0600
TZOFFSETTO:-0700
TZNAME:MST
DTSTART:20071104T020000
RRULE:FREQ=YEARLY;BYMONTH=11;BYDAY=1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:America/Grand_Turk
BEGIN:DAYLIGHT
TZOFFSETFROM:-0500
TZOFFSETTO:-0400
TZNAME:EDT
DTSTART:20070311T020000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=2SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:-0400
TZOFFSETTO:-0500
TZNAME:EST
DTSTART:20071104T020000
RRULE:FREQ=YEARLY;BYMONTH=11;BYDAY=1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:America/Godthab
BEGIN:DAYLIGHT
TZOFFSETFROM:-0300
TZOFFSETTO:-0200
TZNAME:WGST
DTSTART:19810328T220000
RRULE:FREQ=YEARLY;BYMONTH=3;BYMONTHDAY=24,25,26,27,28,29,30;BYDAY=SA
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:-0200
TZOFFSETTO:-0300
TZNAME:WGT
DTSTART:19961026T230000
RRULE:FREQ=YEARLY;BYMONTH=10;BYMONTHDAY=24,25,26,27,28,29,30;BYDAY=SA

```

```

END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:America/Halifax
X-S1CS-TZID-ALIAS:Atlantic Standard Time
X-S1CS-TZID-ALIAS:Canada/Atlantic
BEGIN:DAYLIGHT
TZOFFSETFROM:-0400
TZOFFSETTO:-0300
TZNAME:ADT
DTSTART:20070311T020000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=2SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:-0300
TZOFFSETTO:-0400
TZNAME:AST
DTSTART:20071104T020000
RRULE:FREQ=YEARLY;BYMONTH=11;BYDAY=1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:America/Havana
X-S1CS-TZID-ALIAS:Cuba
BEGIN:STANDARD
TZOFFSETFROM:-0400
TZOFFSETTO:-0500
TZNAME:CST
DTSTART:20061029T010000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=-1SU
END:STANDARD
BEGIN:DAYLIGHT
TZOFFSETFROM:-0500
TZOFFSETTO:-0400
TZNAME:CDT
DTSTART:20120311T000000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=2SU
END:DAYLIGHT
BEGIN:DAYLIGHT
TZOFFSETFROM:-0500
TZOFFSETTO:-0400
TZNAME:CDT
DTSTART:19280609T233640
RDATE:20020407T000000
RDATE:20030406T000000
RDATE:20040404T000000
RDATE:20070311T000000
RDATE:20080316T000000
RDATE:20090308T000000
RDATE:20100314T000000
RDATE:20110320T000000
END:DAYLIGHT
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:America/Indiana/Indianapolis
X-S1CS-TZID-ALIAS:US Eastern Standard Time

```



```

X-S1CS-TZID-ALIAS:SA Pacific Standard Time
X-S1CS-TZID-ALIAS:US/East-Indiana
BEGIN:DAYLIGHT
TZOFFSETFROM:-0500
TZOFFSETTO:-0400
TZNAME:EDT
DTSTART:20070311T020000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=2SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:-0400
TZOFFSETTO:-0500
TZNAME:EST
DTSTART:20071104T020000
RRULE:FREQ=YEARLY;BYMONTH=11;BYDAY=1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:America/La_Paz
X-S1CS-TZID-ALIAS:SA Western Standard Time
BEGIN:DAYLIGHT
TZOFFSETFROM:-043236
TZOFFSETTO:-033236
TZNAME:BOST
DTSTART:19311014T233640
RDATE:19311014T231320
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:-033236
TZOFFSETTO:-0400
TZNAME:BOT
DTSTART:19320320T233640
RDATE:19320320T231320
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:America/Los_Angeles
X-S1CS-TZID-ALIAS:Pacific Standard Time
X-S1CS-TZID-ALIAS:US/Pacific
BEGIN:DAYLIGHT
TZOFFSETFROM:-0800
TZOFFSETTO:-0700
TZNAME:PDT
DTSTART:20070311T020000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=2SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:-0700
TZOFFSETTO:-0800
TZNAME:PST
DTSTART:20071104T020000
RRULE:FREQ=YEARLY;BYMONTH=11;BYDAY=1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:America/Mexico_City

```

```

X-S1CS-TZID-ALIAS:Mexico Standard Time
X-S1CS-TZID-ALIAS:Mexico/General
BEGIN:DAYLIGHT
TZOFFSETFROM:-0600
TZOFFSETTO:-0500
TZNAME:CDT
DTSTART:20020407T020000
RRULE:FREQ=YEARLY;BYMONTH=4;BYDAY=1SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:-0500
TZOFFSETTO:-0600
TZNAME:CST
DTSTART:20021027T020000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=-1SU
END:STANDARD
BEGIN:STANDARD
TZOFFSETFROM:-0600
TZOFFSETTO:-0600
TZNAME:CST
DTSTART:20020220T000000
RDATE:20020220T000000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:America/Miquelon
X-S1CS-TZID-ALIAS:Greenland Standard Time
BEGIN:DAYLIGHT
TZOFFSETFROM:-0300
TZOFFSETTO:-0200
TZNAME:PMDT
DTSTART:20070311T020000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=2SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:-0200
TZOFFSETTO:-0300
TZNAME:PMST
DTSTART:20071104T020000
RRULE:FREQ=YEARLY;BYMONTH=11;BYDAY=1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:America/New_York
X-S1CS-TZID-ALIAS:Eastern Standard Time
X-S1CS-TZID-ALIAS:US/Eastern
BEGIN:DAYLIGHT
TZOFFSETFROM:-0500
TZOFFSETTO:-0400
TZNAME:EDT
DTSTART:20070311T020000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=2SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:-0400
TZOFFSETTO:-0500

```

```

TZNAME:EST
DTSTART:20071104T020000
RRULE:FREQ=YEARLY;BYMONTH=11;BYDAY=1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:America/Phoenix
X-S1CS-TZID-ALIAS:US Mountain Standard Time
X-S1CS-TZID-ALIAS:US/Arizona
BEGIN:STANDARD
TZOFFSETFROM:-0700
TZOFFSETTO:-0700
TZNAME:MST
DTSTART:19670101T000000
RDATE:19680321T000000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:America/Port-au-Prince
BEGIN:DAYLIGHT
TZOFFSETFROM:-0500
TZOFFSETTO:-0400
TZNAME:EDT
DTSTART:19830508T000000
RDATE:20050403T000000
RDATE:20060402T000000
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:-0400
TZOFFSETTO:-0500
TZNAME:EST
DTSTART:19831030T000000
RDATE:20051030T000000
RDATE:20061029T000000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:America/Santiago
X-S1CS-TZID-ALIAS:Pacific SA Standard Time
X-S1CS-TZID-ALIAS:Chile/Continental
BEGIN:STANDARD
TZOFFSETFROM:-0400
TZOFFSETTO:-0400
TZNAME:CLT
DTSTART:20120310T230000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=2SA
END:STANDARD
BEGIN:STANDARD
TZOFFSETFROM:-0300
TZOFFSETTO:-0400
TZNAME:CLT
DTSTART:19690330T000000
RDATE:20020310T000000
RDATE:20030309T000000
RDATE:20040314T000000
RDATE:20050313T000000

```

```

RDATE:20060312T000000
RDATE:20070311T000000
RDATE:20080330T000000
RDATE:20090315T000000
RDATE:20100404T000000
RDATE:20110403T000000
END:STANDARD
BEGIN:DAYLIGHT
TZOFFSETFROM:-0400
TZOFFSETTO:-0300
TZNAME:CLST
DTSTART:19991010T000000
RRULE:FREQ=YEARLY;BYMONTH=10;BYMONTHDAY=9,10,11,12,13,14,15;BYDAY=SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:-0300
TZOFFSETTO:-0400
TZNAME:CLT
DTSTART:19690330T000000
RDATE:20020310T000000
RDATE:20030309T000000
RDATE:20040314T000000
RDATE:20050313T000000
RDATE:20060312T000000
RDATE:20070311T000000
RDATE:20080330T000000
RDATE:20090315T000000
RDATE:20100404T000000
RDATE:20110403T000000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:America/Sao_Paulo
X-S1CS-TZID-ALIAS:E. South America Standard Time
X-S1CS-TZID-ALIAS:Brazil/East
BEGIN:DAYLIGHT
TZOFFSETFROM:-0300
TZOFFSETTO:-0200
TZNAME:BRST
DTSTART:20081019T000000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=3SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:-0300
TZOFFSETTO:-0300
TZNAME:BRT
DTSTART:20380221T000000
RRULE:FREQ=YEARLY;BYMONTH=2;BYDAY=3SU
END:STANDARD
BEGIN:STANDARD
TZOFFSETFROM:-0200
TZOFFSETTO:-0300
TZNAME:BRT
DTSTART:19320331T233640
RDATE:20020217T000000
RDATE:20030216T000000

```

```

RDATE:20040215T000000
RDATE:20050220T000000
RDATE:20060219T000000
RDATE:20070225T000000
RDATE:20080217T000000
RDATE:20090215T000000
RDATE:20100221T000000
RDATE:20110220T000000
END:STANDARD
BEGIN:STANDARD
TZOFFSETFROM:-0300
TZOFFSETTO:-0300
TZNAME:BRT
DTSTART:20120226T000000
RDATE:20120226T000000
RDATE:20130217T000000
RDATE:20140216T000000
RDATE:20150222T000000
RDATE:20160221T000000
RDATE:20170219T000000
RDATE:20180218T000000
RDATE:20190217T000000
RDATE:20200216T000000
RDATE:20210221T000000
RDATE:20220220T000000
RDATE:20230226T000000
RDATE:20240218T000000
RDATE:20250216T000000
RDATE:20260222T000000
RDATE:20270221T000000
RDATE:20280220T000000
RDATE:20290218T000000
RDATE:20300217T000000
RDATE:20310216T000000
RDATE:20320215T000000
RDATE:20330220T000000
RDATE:20340226T000000
RDATE:20350218T000000
RDATE:20360217T000000
RDATE:20370222T000000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:America/St_Johns
X-S1CS-TZID-ALIAS:Newfoundland Standard Time
X-S1CS-TZID-ALIAS:Canada/Newfoundland
BEGIN:DAYLIGHT
TZOFFSETFROM:-0330
TZOFFSETTO:-0230
TZNAME:NDT
DTSTART:20070311T000100
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=2SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:-0230
TZOFFSETTO:-0330

```

```

TZNAME:NST
DTSTART:20071104T000100
RRULE:FREQ=YEARLY;BYMONTH=11;BYDAY=1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Anadyr
BEGIN:STANDARD
TZOFFSETFROM:+1200
TZOFFSETTO:+1100
TZNAME:ANAT
DTSTART:20101031T030000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=-1SU
END:STANDARD
BEGIN:DAYLIGHT
TZOFFSETFROM:+1100
TZOFFSETTO:+1200
TZNAME:ANAST
DTSTART:20110327T020000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=-1SU
END:DAYLIGHT
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Amman
BEGIN:DAYLIGHT
TZOFFSETFROM:+0200
TZOFFSETTO:+0300
TZNAME:EEST
DTSTART:20020328T235959
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=-1TH
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0300
TZOFFSETTO:+0200
TZNAME:EET
DTSTART:20061027T010000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=-1FR
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Aqtau
BEGIN:STANDARD
TZOFFSETFROM:+0400
TZOFFSETTO:+0500
TZNAME:AQTT
DTSTART:20050315T000000
RDATE:20050315T000000
END:STANDARD
BEGIN:DAYLIGHT
TZOFFSETFROM:+0400
TZOFFSETTO:+0500
TZNAME:AQTST
DTSTART:19960331T020000
RDATE:20020331T020000
RDATE:20030330T020000
RDATE:20040328T020000

```

```

END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0500
TZOFFSETTO:+0400
TZNAME:AQTT
DTSTART:19950924T030000
RDATE:20021027T030000
RDATE:20031026T030000
RDATE:20041031T030000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Aqtobe
X-S1CS-TZID-ALIAS:Ekaterinburg Standard Time
BEGIN:DAYLIGHT
TZOFFSETFROM:+0500
TZOFFSETTO:+0600
TZNAME:AQTST
DTSTART:19920328T230000
RDATE:20020331T020000
RDATE:20030330T020000
RDATE:20040328T020000
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0600
TZOFFSETTO:+0500
TZNAME:AQTT
DTSTART:19920926T230000
RDATE:20021027T030000
RDATE:20031026T030000
RDATE:20041031T030000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Baghdad
X-S1CS-TZID-ALIAS:Arabic Standard Time
BEGIN:DAYLIGHT
TZOFFSETFROM:+0300
TZOFFSETTO:+0400
TZNAME:ADT
DTSTART:19820501T000000
RDATE:20020401T030000
RDATE:20030401T030000
RDATE:20040401T030000
RDATE:20050401T030000
RDATE:20060401T030000
RDATE:20070401T030000
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0400
TZOFFSETTO:+0300
TZNAME:AST
DTSTART:19821001T000000
RDATE:20021001T040000
RDATE:20031001T040000
RDATE:20041001T040000

```

```

RDATE:20051001T040000
RDATE:20061001T040000
RDATE:20071001T040000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Baku
X-S1CS-TZID-ALIAS:Caucasus Standard Time
BEGIN:DAYLIGHT
TZOFFSETFROM:+0400
TZOFFSETTO:+0500
TZNAME:AZST
DTSTART:19970330T040000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=-1SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0500
TZOFFSETTO:+0400
TZNAME:AZT
DTSTART:19971026T050000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=-1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Bangkok
X-S1CS-TZID-ALIAS:SE Asia Standard Time
BEGIN:STANDARD
TZOFFSETFROM:+064204
TZOFFSETTO:+0700
TZNAME:ICT
DTSTART:19200331T233640
RDATE:19200331T231320
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Beirut
BEGIN:DAYLIGHT
TZOFFSETFROM:+0200
TZOFFSETTO:+0300
TZNAME:EEST
DTSTART:19930328T000000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=-1SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0300
TZOFFSETTO:+0200
TZNAME:EET
DTSTART:19991031T000000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=-1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Bishkek
BEGIN:STANDARD
TZOFFSETFROM:+0600
TZOFFSETTO:+0600

```



```

TZNAME:KGT
DTSTART:20050812T000000
RDATE:20050812T000000
END:STANDARD
BEGIN:DAYLIGHT
TZOFFSETFROM:+0500
TZOFFSETTO:+0600
TZNAME:KGST
DTSTART:19920412T000000
RDATE:20020331T023000
RDATE:20030330T023000
RDATE:20040328T023000
RDATE:20050327T023000
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0600
TZOFFSETTO:+0500
TZNAME:KGT
DTSTART:19910831T020000
RDATE:20021027T023000
RDATE:20031026T023000
RDATE:20041031T023000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Dhaka
X-S1CS-TZID-ALIAS:Asia/Dacca
X-S1CS-TZID-ALIAS:Central Asia Standard Time
X-S1CS-TZID-ALIAS:Sri Lanka Standard Time
BEGIN:DAYLIGHT
TZOFFSETFROM:+0600
TZOFFSETTO:+0700
TZNAME:BDST
DTSTART:20090619T230000
RDATE:20090619T230000
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0700
TZOFFSETTO:+0600
TZNAME:BDT
DTSTART:20091231T235900
RDATE:20091231T235900
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Irkutsk
X-S1CS-TZID-ALIAS:North Asia East Standard Time
BEGIN:DAYLIGHT
TZOFFSETFROM:+0800
TZOFFSETTO:+0900
TZNAME:IRKST
DTSTART:19930328T020000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=-1SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0900

```

```

TZOFFSETTO:+0800
TZNAME:IRKT
DTSTART:19961027T030000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=-1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Jerusalem
X-S1CS-TZID-ALIAS:Israel Standard Time
X-S1CS-TZID-ALIAS:Asia/Tel_Aviv
X-S1CS-TZID-ALIAS:Israel
BEGIN:DAYLIGHT
TZOFFSETFROM:+0200
TZOFFSETTO:+0300
TZNAME:IDT
DTSTART:19400531T233640
RDATE:20020329T010000
RDATE:20030328T010000
RDATE:20040407T010000
RDATE:20050401T020000
RDATE:20060331T020000
RDATE:20070330T020000
RDATE:20080328T020000
RDATE:20090327T020000
RDATE:20100326T020000
RDATE:20110401T020000
RDATE:20120330T020000
RDATE:20130329T020000
RDATE:20140328T020000
RDATE:20150327T020000
RDATE:20160401T020000
RDATE:20170331T020000
RDATE:20180330T020000
RDATE:20190329T020000
RDATE:20200327T020000
RDATE:20210326T020000
RDATE:20220401T020000
RDATE:20230331T020000
RDATE:20240329T020000
RDATE:20250328T020000
RDATE:20260327T020000
RDATE:20270326T020000
RDATE:20280331T020000
RDATE:20290330T020000
RDATE:20300329T020000
RDATE:20310328T020000
RDATE:20320326T020000
RDATE:20330401T020000
RDATE:20340331T020000
RDATE:20350330T020000
RDATE:20360328T020000
RDATE:20370327T020000
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0300
TZOFFSETTO:+0200

```

```

TZNAME: IST
DTSTART:19421031T230000
RDATE:20021007T010000
RDATE:20031003T010000
RDATE:20040922T010000
RDATE:20051009T020000
RDATE:20061001T020000
RDATE:20070916T020000
RDATE:20081005T020000
RDATE:20090927T020000
RDATE:20100912T020000
RDATE:20111002T020000
RDATE:20120923T020000
RDATE:20130908T020000
RDATE:20140928T020000
RDATE:20150920T020000
RDATE:20161009T020000
RDATE:20170924T020000
RDATE:20180916T020000
RDATE:20191006T020000
RDATE:20200927T020000
RDATE:20210912T020000
RDATE:20221002T020000
RDATE:20230924T020000
RDATE:20241006T020000
RDATE:20250928T020000
RDATE:20260920T020000
RDATE:20271010T020000
RDATE:20280924T020000
RDATE:20290916T020000
RDATE:20301006T020000
RDATE:20310921T020000
RDATE:20320912T020000
RDATE:20331002T020000
RDATE:20340917T020000
RDATE:20351007T020000
RDATE:20360928T020000
RDATE:20370913T020000
END: STANDARD
END: VTIMEZONE
BEGIN: VTIMEZONE
TZID: Asia/Kabul
X-SLCS-TZID-ALIAS: Afghanistan Standard Time
BEGIN: STANDARD
TZOFFSETFROM: +0400
TZOFFSETTO: +0430
TZNAME: AFT
DTSTART: 19441231T230000
RDATE: 19441231T220000
END: STANDARD
END: VTIMEZONE
BEGIN: VTIMEZONE
TZID: Asia/Kamchatka
BEGIN: STANDARD
TZOFFSETFROM: +1200
TZOFFSETTO: +1100

```

```

TZNAME:PETT
DTSTART:20101031T030000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=-1SU
END:STANDARD
BEGIN:DAYLIGHT
TZOFFSETFROM:+1100
TZOFFSETTO:+1200
TZNAME:PETST
DTSTART:20110327T020000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=-1SU
END:DAYLIGHT
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Kathmandu
X-S1CS-TZID-ALIAS:Nepal Standard Time
X-S1CS-TZID-ALIAS:Asia/Katmandu
BEGIN:STANDARD
TZOFFSETFROM:+0530
TZOFFSETTO:+0545
TZNAME:NPT
DTSTART:19860101T000000
RDATE:19860101T000000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Karachi
X-S1CS-TZID-ALIAS:West Asia Standard Time
BEGIN:DAYLIGHT
TZOFFSETFROM:+0500
TZOFFSETTO:+0600
TZNAME:PKST
DTSTART:20020407T000100
RDATE:20020407T000100
RDATE:20080601T000000
RDATE:20090415T000000
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0600
TZOFFSETTO:+0500
TZNAME:PKT
DTSTART:20021006T000100
RDATE:20021006T000100
RDATE:20081101T000000
RDATE:20091101T000000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Kolkata
X-S1CS-TZID-ALIAS:India Standard Time
X-S1CS-TZID-ALIAS:Asia/Calcutta
BEGIN:DAYLIGHT
TZOFFSETFROM:+0530
TZOFFSETTO:+0630
TZNAME:IST
DTSTART:19420901T000000
RDATE:19420901T000000

```

```

END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0630
TZOFFSETTO:+0530
TZNAME:IST
DTSTART:19420515T000000
RDATE:19451015T000000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Krasnoyarsk
X-S1CS-TZID-ALIAS:North Asia Standard Time
BEGIN:DAYLIGHT
TZOFFSETFROM:+0700
TZOFFSETTO:+0800
TZNAME:KRAST
DTSTART:19930328T020000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=-1SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0800
TZOFFSETTO:+0700
TZNAME:KRAT
DTSTART:19961027T030000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=-1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Kuwait
X-S1CS-TZID-ALIAS:Kuwait\, Riyadh
BEGIN:STANDARD
TZOFFSETFROM:+031156
TZOFFSETTO:+0300
TZNAME:AST
DTSTART:19500101T000000
RDATE:19500101T000000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Magadan
BEGIN:DAYLIGHT
TZOFFSETFROM:+1100
TZOFFSETTO:+1200
TZNAME:MAGST
DTSTART:19930328T020000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=-1SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+1200
TZOFFSETTO:+1100
TZNAME:MAGT
DTSTART:19961027T030000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=-1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE

```

```

TZID:Asia/Novosibirsk
X-S1CS-TZID-ALIAS:N. Central Asia Standard Time
BEGIN:DAYLIGHT
TZOFFSETFROM:+0600
TZOFFSETTO:+0700
TZNAME:NOVST
DTSTART:19940327T020000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=-1SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0700
TZOFFSETTO:+0600
TZNAME:NOVT
DTSTART:19961027T030000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=-1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Rangoon
X-S1CS-TZID-ALIAS:Myanmar Standard Time
BEGIN:STANDARD
TZOFFSETFROM:+0900
TZOFFSETTO:+0630
TZNAME:MMT
DTSTART:19450502T230000
RDATE:19450502T220000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Riyadh
X-S1CS-TZID-ALIAS:Arab Standard Time
X-S1CS-TZID-ALIAS:E. Africa Standard Time
BEGIN:STANDARD
TZOFFSETFROM:+030652
TZOFFSETTO:+0300
TZNAME:AST
DTSTART:19500101T000000
RDATE:19500101T000000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Seoul
X-S1CS-TZID-ALIAS:Korea Standard Time
X-S1CS-TZID-ALIAS:ROK
BEGIN:DAYLIGHT
TZOFFSETFROM:+0900
TZOFFSETTO:+1000
TZNAME:KDT
DTSTART:19870510T000000
RDATE:19880508T000000
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+1000
TZOFFSETTO:+0900
TZNAME:KST
DTSTART:19871011T000000

```

```

RDATE:19881009T000000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Shanghai
X-S1CS-TZID-ALIAS:China Standard Time
X-S1CS-TZID-ALIAS:PRC
BEGIN:STANDARD
TZOFFSETFROM:+0800
TZOFFSETTO:+0800
TZNAME:CST
DTSTART:19490101T000000
RDATE:19490101T000000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Taipei
X-S1CS-TZID-ALIAS:Singapore Standard Time
X-S1CS-TZID-ALIAS:Taipei Standard Time
X-S1CS-TZID-ALIAS:ROC
BEGIN:DAYLIGHT
TZOFFSETFROM:+0800
TZOFFSETTO:+0900
TZNAME:CDT
DTSTART:19450430T230000
RDATE:19790630T000000
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0900
TZOFFSETTO:+0800
TZNAME:CST
DTSTART:19450930T230000
RDATE:19790930T000000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Tehran
X-S1CS-TZID-ALIAS:Iran Standard Time
X-S1CS-TZID-ALIAS:Iran
BEGIN:DAYLIGHT
TZOFFSETFROM:+0330
TZOFFSETTO:+0430
TZNAME:IRDT
DTSTART:19790321T000000
RDATE:20020322T000000
RDATE:20030322T000000
RDATE:20040321T000000
RDATE:20050322T000000
RDATE:20080321T000000
RDATE:20090322T000000
RDATE:20100322T000000
RDATE:20110322T000000
RDATE:20120321T000000
RDATE:20130322T000000
RDATE:20140322T000000
RDATE:20150322T000000

```

```
RDATE:20160321T000000
RDATE:20170322T000000
RDATE:20180322T000000
RDATE:20190322T000000
RDATE:20200321T000000
RDATE:20210322T000000
RDATE:20220322T000000
RDATE:20230322T000000
RDATE:20240321T000000
RDATE:20250322T000000
RDATE:20260322T000000
RDATE:20270322T000000
RDATE:20280321T000000
RDATE:20290321T000000
RDATE:20300322T000000
RDATE:20310322T000000
RDATE:20320321T000000
RDATE:20330321T000000
RDATE:20340322T000000
RDATE:20350322T000000
RDATE:20360321T000000
RDATE:20370321T000000
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0430
TZOFFSETTO:+0330
TZNAME:IRST
DTSTART:19790919T000000
RDATE:20020922T000000
RDATE:20030922T000000
RDATE:20040921T000000
RDATE:20050922T000000
RDATE:20080921T000000
RDATE:20090922T000000
RDATE:20100922T000000
RDATE:20110922T000000
RDATE:20120921T000000
RDATE:20130922T000000
RDATE:20140922T000000
RDATE:20150922T000000
RDATE:20160921T000000
RDATE:20170922T000000
RDATE:20180922T000000
RDATE:20190922T000000
RDATE:20200921T000000
RDATE:20210922T000000
RDATE:20220922T000000
RDATE:20230922T000000
RDATE:20240921T000000
RDATE:20250922T000000
RDATE:20260922T000000
RDATE:20270922T000000
RDATE:20280921T000000
RDATE:20290921T000000
RDATE:20300922T000000
RDATE:20310922T000000
```



```

RDATE:20320921T000000
RDATE:20330921T000000
RDATE:20340922T000000
RDATE:20350922T000000
RDATE:20360921T000000
RDATE:20370921T000000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Tokyo
X-S1CS-TZID-ALIAS:Tokyo Standard Time
X-S1CS-TZID-ALIAS:Japan
BEGIN:DAYLIGHT
TZOFFSETFROM:+0900
TZOFFSETTO:+1000
TZNAME:JDT
DTSTART:19480502T020000
RDATE:19510506T020000
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+1000
TZOFFSETTO:+0900
TZNAME:JST
DTSTART:19480911T020000
RDATE:19510908T020000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Ulaanbaatar
X-S1CS-TZID-ALIAS:Asia/Ulan_Bator
BEGIN:DAYLIGHT
TZOFFSETFROM:+0800
TZOFFSETTO:+0900
TZNAME:ULAST
DTSTART:19830401T000000
RDATE:20020330T020000
RDATE:20030329T020000
RDATE:20040327T020000
RDATE:20050326T020000
RDATE:20060325T020000
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0900
TZOFFSETTO:+0800
TZNAME:ULAT
DTSTART:19831001T000000
RDATE:20020928T020000
RDATE:20030927T020000
RDATE:20040925T020000
RDATE:20050924T020000
RDATE:20060930T020000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Vladivostok
X-S1CS-TZID-ALIAS:Vladivostok Standard Time

```

```

BEGIN:DAYLIGHT
TZOFFSETFROM:+1000
TZOFFSETTO:+1100
TZNAME:VLAST
DTSTART:19930328T020000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=-1SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+1100
TZOFFSETTO:+1000
TZNAME:VLAT
DTSTART:19961027T030000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=-1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Yakutsk
X-S1CS-TZID-ALIAS:Yakutsk Standard Time
BEGIN:DAYLIGHT
TZOFFSETFROM:+0900
TZOFFSETTO:+1000
TZNAME:YAKST
DTSTART:19930328T020000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=-1SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+1000
TZOFFSETTO:+0900
TZNAME:YAKT
DTSTART:19961027T030000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=-1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Yekaterinburg
X-S1CS-TZID-ALIAS:Ekaterinburg Standard Time
BEGIN:DAYLIGHT
TZOFFSETFROM:+0500
TZOFFSETTO:+0600
TZNAME:YEKST
DTSTART:19930328T020000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=-1SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0600
TZOFFSETTO:+0500
TZNAME:YEKT
DTSTART:19961027T030000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=-1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Asia/Yerevan
BEGIN:DAYLIGHT
TZOFFSETFROM:+0400
TZOFFSETTO:+0500

```

```

TZNAME:AMST
DTSTART:19970330T020000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=-1SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0500
TZOFFSETTO:+0400
TZNAME:AMT
DTSTART:19971026T030000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=-1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Atlantic/Azores
X-S1CS-TZID-ALIAS:Azores Standard Time
BEGIN:DAYLIGHT
TZOFFSETFROM:-0100
TZOFFSETTO:+0000
TZNAME:AZOST
DTSTART:19940327T000000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=-1SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0000
TZOFFSETTO:-0100
TZNAME:AZOT
DTSTART:19961027T010000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=-1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Atlantic/Cape_Verde
X-S1CS-TZID-ALIAS:Cape Verde Standard Time
BEGIN:DAYLIGHT
TZOFFSETFROM:-0200
TZOFFSETTO:-0100
TZNAME:CVST
DTSTART:19420901T000000
RDATE:19420901T000000
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:-0200
TZOFFSETTO:-0100
TZNAME:CVT
DTSTART:19751125T020000
RDATE:19751125T020000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Atlantic/Stanley
BEGIN:DAYLIGHT
TZOFFSETFROM:-0400
TZOFFSETTO:-0300
TZNAME:FKST
DTSTART:20010902T020000
RRULE:FREQ=YEARLY;BYMONTH=9;BYDAY=1SU

```

```

END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:-0300
TZOFFSETTO:-0400
TZNAME:FKT
DTSTART:20010415T020000
RRULE:FREQ=YEARLY;BYMONTH=4;BYDAY=3SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Atlantic/South_Georgia
BEGIN:STANDARD
TZOFFSETFROM:-022608
TZOFFSETTO:-0200
TZNAME:GST
DTSTART:18900101T000000
RDATE:18900101T000000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Australia/Adelaide
X-S1CS-TZID-ALIAS: Cen. Australia Standard Time
X-S1CS-TZID-ALIAS: Australia/South
BEGIN:STANDARD
TZOFFSETFROM:+1030
TZOFFSETTO:+0930
TZNAME:CST
DTSTART:20080406T030000
RRULE:FREQ=YEARLY;BYMONTH=4;BYDAY=1SU
END:STANDARD
BEGIN:DAYLIGHT
TZOFFSETFROM:+0930
TZOFFSETTO:+1030
TZNAME:CST
DTSTART:20081005T020000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=1SU
END:DAYLIGHT
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Australia/Brisbane
X-S1CS-TZID-ALIAS: E. Australia Standard Time
X-S1CS-TZID-ALIAS: West Pacific Standard Time
X-S1CS-TZID-ALIAS: Australia/Queensland
BEGIN:STANDARD
TZOFFSETFROM:+1000
TZOFFSETTO:+1000
TZNAME:EST
DTSTART:19710101T000000
RDATE:19710101T000000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Australia/Darwin
X-S1CS-TZID-ALIAS: AUS Central Standard Time
X-S1CS-TZID-ALIAS: Australia/North
BEGIN:DAYLIGHT

```

```

TZOFFSETFROM:+0930
TZOFFSETTO:+1030
TZNAME:CST
DTSTART:19161231T233740
RDATE:19431003T000000
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+1030
TZOFFSETTO:+0930
TZNAME:CST
DTSTART:19170325T013640
RDATE:19440326T000000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Australia/Hobart
X-S1CS-TZID-ALIAS:Tasmania Standard Time
X-S1CS-TZID-ALIAS:Australia/Tasmania
BEGIN:STANDARD
TZOFFSETFROM:+1100
TZOFFSETTO:+1000
TZNAME:EST
DTSTART:20080406T030000
RRULE:FREQ=YEARLY;BYMONTH=4;BYDAY=1SU
END:STANDARD
BEGIN:DAYLIGHT
TZOFFSETFROM:+1000
TZOFFSETTO:+1100
TZNAME:EST
DTSTART:20011007T020000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=1SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+1000
TZOFFSETTO:+1000
TZNAME:EST
DTSTART:19670101T000000
RDATE:19670101T000000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Australia/Lord_Howe
X-S1CS-TZID-ALIAS:Australia/LHI
BEGIN:STANDARD
TZOFFSETFROM:+1100
TZOFFSETTO:+1030
TZNAME:LHST
DTSTART:20080406T020000
RRULE:FREQ=YEARLY;BYMONTH=4;BYDAY=1SU
END:STANDARD
BEGIN:DAYLIGHT
TZOFFSETFROM:+1030
TZOFFSETTO:+1100
TZNAME:LHST
DTSTART:20081005T020000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=1SU

```

```

END:DAYLIGHT
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Australia/Perth
X-S1CS-TZID-ALIAS:W. Australia Standard Time
X-S1CS-TZID-ALIAS:Australia/West
BEGIN:STANDARD
TZOFFSETFROM:+0800
TZOFFSETTO:+0800
TZNAME:WST
DTSTART:19430630T230000
RDATE:19430630T220000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Australia/Sydney
X-S1CS-TZID-ALIAS:AUS Eastern Standard Time
X-S1CS-TZID-ALIAS:Australia/ACT
X-S1CS-TZID-ALIAS:Australia/Canberra
X-S1CS-TZID-ALIAS:Australia/NSW
BEGIN:STANDARD
TZOFFSETFROM:+1100
TZOFFSETTO:+1000
TZNAME:EST
DTSTART:20080406T030000
RRULE:FREQ=YEARLY;BYMONTH=4;BYDAY=1SU
END:STANDARD
BEGIN:DAYLIGHT
TZOFFSETFROM:+1000
TZOFFSETTO:+1100
TZNAME:EST
DTSTART:20081005T020000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=1SU
END:DAYLIGHT
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Europe/Bucharest
X-S1CS-TZID-ALIAS:E. Europe Standard Time
BEGIN:DAYLIGHT
TZOFFSETFROM:+0200
TZOFFSETTO:+0300
TZNAME:EEST
DTSTART:19970330T030000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=-1SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0300
TZOFFSETTO:+0200
TZNAME:EET
DTSTART:19971026T040000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=-1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Europe/Istanbul
X-S1CS-TZID-ALIAS:GTB Standard Time

```

```

X-S1CS-TZID-ALIAS:E. Europe Standard Time
X-S1CS-TZID-ALIAS:Turkey
X-S1CS-TZID-ALIAS:Asia/Istanbul
BEGIN:STANDARD
TZOFFSETFROM:+0300
TZOFFSETTO:+0200
TZNAME:EET
DTSTART:20071028T040000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=-1SU
END:STANDARD
BEGIN:DAYLIGHT
TZOFFSETFROM:+0200
TZOFFSETTO:+0300
TZNAME:EEST
DTSTART:20120325T030000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=-1SU
END:DAYLIGHT
BEGIN:DAYLIGHT
TZOFFSETFROM:+0200
TZOFFSETTO:+0300
TZNAME:EEST
DTSTART:19160430T233640
RDATE:20020331T010000
RDATE:20030330T010000
RDATE:20040328T010000
RDATE:20050327T010000
RDATE:20060326T010000
RDATE:20070325T030000
RDATE:20080330T030000
RDATE:20090329T030000
RDATE:20100328T030000
RDATE:20110328T030000
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0200
TZOFFSETTO:+0200
TZNAME:EET
DTSTART:20070101T000000
RDATE:20070101T000000
RDATE:20110327T030000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Europe/London
X-S1CS-TZID-ALIAS:GMT Standard Time
X-S1CS-TZID-ALIAS:GB
X-S1CS-TZID-ALIAS:Europe/Guernsey
X-S1CS-TZID-ALIAS:Europe/Isle_of_Man
X-S1CS-TZID-ALIAS:Europe/Jersey
X-S1CS-TZID-ALIAS:Europe/Belfast
BEGIN:DAYLIGHT
TZOFFSETFROM:+0000
TZOFFSETTO:+0100
TZNAME:BST
DTSTART:19810329T010000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=-1SU

```

```

END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0100
TZOFFSETTO:+0000
TZNAME:GMT
DTSTART:19961027T020000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=-1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Europe/Minsk
BEGIN:DAYLIGHT
TZOFFSETFROM:+0200
TZOFFSETTO:+0300
TZNAME:EEST
DTSTART:19930328T020000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=-1SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0300
TZOFFSETTO:+0200
TZNAME:EET
DTSTART:19961027T030000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=-1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Europe/Moscow
X-S1CS-TZID-ALIAS:Russian Standard Time
X-S1CS-TZID-ALIAS:W-SU
BEGIN:DAYLIGHT
TZOFFSETFROM:+0300
TZOFFSETTO:+0400
TZNAME:MSD
DTSTART:19930328T020000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=-1SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0400
TZOFFSETTO:+0300
TZNAME:MSK
DTSTART:19961027T030000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=-1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Europe/Paris
X-S1CS-TZID-ALIAS:Central Europe Standard Time
X-S1CS-TZID-ALIAS:Central European Standard Time
X-S1CS-TZID-ALIAS:Romance Standard Time
X-S1CS-TZID-ALIAS:W. Europe Standard Time
BEGIN:DAYLIGHT
TZOFFSETFROM:+0100
TZOFFSETTO:+0200
TZNAME:CEST
DTSTART:19810329T020000

```



```

RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=-1SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0200
TZOFFSETTO:+0100
TZNAME:CET
DTSTART:19961027T030000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=-1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Europe/Riga
X-S1CS-TZID-ALIAS:FLE Standard Time
BEGIN:DAYLIGHT
TZOFFSETFROM:+0200
TZOFFSETTO:+0300
TZNAME:EEST
DTSTART:20010325T030000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=-1SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0300
TZOFFSETTO:+0200
TZNAME:EET
DTSTART:20011028T040000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=-1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Europe/Samara
BEGIN:STANDARD
TZOFFSETFROM:+0400
TZOFFSETTO:+0300
TZNAME:SAMT
DTSTART:20101031T030000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=-1SU
END:STANDARD
BEGIN:DAYLIGHT
TZOFFSETFROM:+0300
TZOFFSETTO:+0400
TZNAME:SAMST
DTSTART:20110327T020000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=-1SU
END:DAYLIGHT
BEGIN:DAYLIGHT
TZOFFSETFROM:+0400
TZOFFSETTO:+0400
TZNAME:SAMST
DTSTART:20100328T020000
RDATE:20100328T020000
END:DAYLIGHT
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Europe/Simferopol
BEGIN:DAYLIGHT
TZOFFSETFROM:+0200

```

```

TZOFFSETTO:+0300
TZNAME:EEST
DTSTART:19980329T030000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=-1SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0300
TZOFFSETTO:+0200
TZNAME:EET
DTSTART:19971026T040000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=-1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Europe/Warsaw
X-S1CS-TZID-ALIAS:Central Europe Standard Time
X-S1CS-TZID-ALIAS:Poland
BEGIN:DAYLIGHT
TZOFFSETFROM:+0100
TZOFFSETTO:+0200
TZNAME:CEST
DTSTART:19880327T020000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=-1SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+0200
TZOFFSETTO:+0100
TZNAME:CET
DTSTART:19961027T030000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=-1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Pacific/Apia
X-S1CS-TZID-ALIAS:Samoa Standard Time
BEGIN:DAYLIGHT
TZOFFSETFROM:-1100
TZOFFSETTO:-1000
TZNAME:WSDT
DTSTART:20100926T000000
RDATE:20100926T000000
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:-1000
TZOFFSETTO:-1100
TZNAME:WST
DTSTART:20110402T040000
RDATE:20110402T040000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Pacific/Auckland
X-S1CS-TZID-ALIAS:New Zealand Standard Time
X-S1CS-TZID-ALIAS:NZ
BEGIN:DAYLIGHT
TZOFFSETFROM:+1200

```

```

TZOFFSETTO:+1300
TZNAME:NZDT
DTSTART:20070930T020000
RRULE:FREQ=YEARLY;BYMONTH=9;BYDAY=-1SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+1300
TZOFFSETTO:+1200
TZNAME:NZST
DTSTART:20080406T030000
RRULE:FREQ=YEARLY;BYMONTH=4;BYDAY=1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Pacific/Chatham
X-S1CS-TZID-ALIAS:NZ-CHAT
BEGIN:DAYLIGHT
TZOFFSETFROM:+1245
TZOFFSETTO:+1345
TZNAME:CHADT
DTSTART:20070930T024500
RRULE:FREQ=YEARLY;BYMONTH=9;BYDAY=-1SU
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+1345
TZOFFSETTO:+1245
TZNAME:CHAST
DTSTART:20080406T034500
RRULE:FREQ=YEARLY;BYMONTH=4;BYDAY=1SU
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Pacific/Easter
X-S1CS-TZID-ALIAS:Chile/EasterIsland
BEGIN:STANDARD
TZOFFSETFROM:-0600
TZOFFSETTO:-0600
TZNAME:EAST
DTSTART:20120310T210000
RRULE:FREQ=YEARLY;BYMONTH=3;BYDAY=2SA
END:STANDARD
BEGIN:STANDARD
TZOFFSETFROM:-0500
TZOFFSETTO:-0600
TZNAME:EAST
DTSTART:19830312T220000
RDATE:20020309T220000
RDATE:20030308T220000
RDATE:20040313T220000
RDATE:20050312T220000
RDATE:20060311T220000
RDATE:20070310T220000
RDATE:20080329T220000
RDATE:20090314T220000
RDATE:20100403T220000
RDATE:20110402T220000

```

```

END:STANDARD
BEGIN:DAYLIGHT
TZOFFSETFROM:-0600
TZOFFSETTO:-0500
TZNAME:EASST
DTSTART:19991009T220000
RRULE:FREQ=YEARLY;BYMONTH=10;BYDAY=2SA
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:-0500
TZOFFSETTO:-0600
TZNAME:EAST
DTSTART:19830312T220000
RDATE:20020309T220000
RDATE:20030308T220000
RDATE:20040313T220000
RDATE:20050312T220000
RDATE:20060311T220000
RDATE:20070310T220000
RDATE:20080329T220000
RDATE:20090314T220000
RDATE:20100403T220000
RDATE:20110402T220000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Pacific/Fiji
X-S1CS-TZID-ALIAS:Fiji Standard Time
BEGIN:STANDARD
TZOFFSETFROM:+1300
TZOFFSETTO:+1200
TZNAME:FJT
DTSTART:19990228T030000
RDATE:20100328T030000
RDATE:20110306T030000
END:STANDARD
BEGIN:DAYLIGHT
TZOFFSETFROM:+1200
TZOFFSETTO:+1300
TZNAME:FJST
DTSTART:19981101T020000
RDATE:20091129T020000
RDATE:20101024T020000
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+1300
TZOFFSETTO:+1200
TZNAME:FJT
DTSTART:19990228T030000
RDATE:20100328T030000
RDATE:20110306T030000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Pacific/Gambier
BEGIN:STANDARD

```

```

TZOFFSETFROM:-085948
TZOFFSETTO:-0900
TZNAME:GAMT
DTSTART:19120930T233640
RDATE:19120930T231320
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Pacific/Guadalcanal
X-S1CS-TZID-ALIAS:Central Pacific Standard Time
BEGIN:STANDARD
TZOFFSETFROM:+103948
TZOFFSETTO:+1100
TZNAME:SBT
DTSTART:19120930T233640
RDATE:19120930T231320
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Pacific/Honolulu
X-S1CS-TZID-ALIAS:Hawaiian Standard Time
X-S1CS-TZID-ALIAS:US/Hawaii
BEGIN:DAYLIGHT
TZOFFSETFROM:-1030
TZOFFSETTO:-0930
TZNAME:HDT
DTSTART:19330430T013640
RDATE:19420209T000000
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:-1030
TZOFFSETTO:-1000
TZNAME:HST
DTSTART:19470608T020000
RDATE:19470608T020000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Pacific/Kiritimati
BEGIN:STANDARD
TZOFFSETFROM:-1000
TZOFFSETTO:+1400
TZNAME:LINT
DTSTART:19950101T000000
RDATE:19950101T000000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Pacific/Marquesas
BEGIN:STANDARD
TZOFFSETFROM:-0918
TZOFFSETTO:-0930
TZNAME:MART
DTSTART:19120930T233640
RDATE:19120930T231320
END:STANDARD

```

```

END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Pacific/Noumea
BEGIN:DAYLIGHT
TZOFFSETFROM:+1100
TZOFFSETTO:+1200
TZNAME:NCST
DTSTART:19771204T000000
RDATE:19961201T020000
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+1200
TZOFFSETTO:+1100
TZNAME:NCT
DTSTART:19780227T000000
RDATE:19970302T030000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Pacific/Norfolk
BEGIN:STANDARD
TZOFFSETFROM:+1112
TZOFFSETTO:+1130
TZNAME:NFT
DTSTART:19510101T000000
RDATE:19510101T000000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Pacific/Pitcairn
BEGIN:STANDARD
TZOFFSETFROM:-0830
TZOFFSETTO:-0800
TZNAME:PST
DTSTART:19980427T000000
RDATE:19980427T000000
END:STANDARD
END:VTIMEZONE
BEGIN:VTIMEZONE
TZID:Pacific/Tongatapu
X-S1CS-TZID-ALIAS:Tonga Standard Time
BEGIN:DAYLIGHT
TZOFFSETFROM:+1300
TZOFFSETTO:+1400
TZNAME:TOST
DTSTART:19991007T020000
RDATE:20011104T020000
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:+1400
TZOFFSETTO:+1300
TZNAME:TOT
DTSTART:20000319T030000
RDATE:20020127T020000
END:STANDARD
END:VTIMEZONE

```

```
BEGIN:VTIMEZONE
TZID:Pacific/Rarotonga
BEGIN:DAYLIGHT
TZOFFSETFROM:-1000
TZOFFSETTO:-0930
TZNAME:CKHST
DTSTART:19791028T000000
RDATE:19901028T000000
END:DAYLIGHT
BEGIN:STANDARD
TZOFFSETFROM:-0930
TZOFFSETTO:-1000
TZNAME:CKT
DTSTART:19790304T000000
RDATE:19910303T000000
END:STANDARD
END:VTIMEZONE
```

```
X-NSCP-WCAP-ERRNO: 0  
END: VCALENDAR
```


get_calprops.wcap

get_calprops.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

Retrieve calendar properties of specified calendars.

Parameters

get_calprops Parameters

Parameter	Type	Multi-valued?	Purpose	Required	Default
calid	semicolon-separated list of strings	Y	Specifies a semicolon-separated list of calendar identifiers from which to retrieve properties. The calid is the value given by the server as X-NSCP-CALPROPS-RELATIVE-CALID	N	Current user's default calendar calid
fmt-out	string	N	The format for the returned data. The three format types are: text/calendar text/json text/xml	N	text/calenda
id	unique identifier string	N	The session identifier.	N	N/A

Description

Use this command to retrieve the calendar properties for the specified calendar(s).

Returns

The command returns the access control settings, display name, owner information, and so on, for each of the specified calendars.

Error Codes

If the fetch fails for any calendar, its error number, X-NSCP-WCAP-ERRNO, is set to FAILED: GET_CALPROPS_FAILED (20). For a complete list of error codes, see [Calendar Server WCAP 7.0 \(WCAPbis\) Error Codes](#).

Example

In the following example, you want to retrieve the calendar properties for the calendars /home/jdoe/calendar/ and /home/jsmith/calendar/, and /home/jjones/calendar/:

```
http://<host>:<port>/wcap/get_calprops.wcap?fmt-out=text/calendar
    &id=<session-id>

&calid=/home/jdoe/calendar;/home/jsmith/calendar;/home/jjones/calendar/
Corporation/CS 7u2-5.06//EN
X-NSCP-CALPROPS-RELATIVE-CALID;X-S1CS-EMAIL=john.doe@example.com:/home/jdoe
Doe
X-S1CS-MYRIGHTS:a
X-NSCP-WCAP-ERRNO:0
END:VCALENDAR
BEGIN:VCALENDAR
VERSION:2.0
PROPID:-//Oracle Corporation/CS 7u2-5.06//EN
X-NSCP-CALPROPS-RELATIVE-CALID;X-S1CS-EMAIL=john.smith@example.com:/home/js
Corporation/CS 7u2-5.06//EN
X-NSCP-CALPROPS-RELATIVE-CALID;X-S1CS-EMAIL=john.doe@example.com:/home/jjor
Jones
X-S1CS-MYRIGHTS:a
X-NSCP-WCAP-ERRNO:0
END:VCALENDAR
```

get_capabilities.wcap

get_capabilities.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

This command was introduced in **Calendar Server 7 Update 2**.

Purpose

Determines the status of features that can be enabled or disabled in a deployment. Use this command to determine the server capability so as to present the right user interface to end users. Currently this command determines the status of the attachment store, and ability to do virus scanning on calendar data.

Parameters

get_capabilities Parameters

Parameter	Type	Multi-valued?	Purpose	Required	Default
fmt-out	string	N	The format for the returned data. The three format types are: text/calendar text/json text/xml	N	text/calendar
id	unique identifier string	N	The session identifier.	Y	N/A

Description

Use this command to retrieve the settings (enabled or disabled) for the attachment store and virus scanning.

Returns

The command returns:

```
X-S1CS-SERVER-ATTACHMENT-ENABLED:TRUE  
or  
X-S1CS-SERVER-ATTACHMENT-ENABLED:FALSE  
and  
X-S1CS-SERVER-VIRUSCHECK-ENABLED:TRUE  
or  
X-S1CS-SERVER-VIRUSCHECK-ENABLED:FALSE
```

Error Codes

For a complete list of error codes, see [Calendar Server WCAP 7.0 \(WCAPbis\) Error Codes](#).

Example

This example returns that Calendar Server is enabled for attachments but not for virus scanning.

```
http://<host>:<port>/davserver/wcap/get_capabilities.wcap?fmt-out=text/calendar  
Corporation/CS_7u2-5.06//EN  
X-S1CS-SERVER-ATTACHMENT-ENABLED:TRUE  
X-S1CS-SERVER-VIRUSCHECK-ENABLED:FALSE  
X-NSCP-WCAP-ERRNO:0  
END:VCALENDAR
```

get_freebusy.wcap

get_freebusy.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

Get the calendar free-busy information for users.

Parameters

get_freebusy Parameters

Parameter	Type	Multi-valued?	Purpose	Required	Default
mail	string	Y	Semi-colon separated list of email addresses. Each email address is used to compute free/busy time for each user. The address must be present in the Directory Server. All of the user's eligible calendars are used in computing free/busy time. Eligible calendars are those for which this user has fbinclude=1.	Y	N/A
dtstart	Date Time string	N	Start time of free/busy search.	N	freebusybegin days before today.
dtend	Date Time string	N	End time of free/busy search.	N	freebusyend days after today
fmt-out	string	N	The format for the returned data. Three format types: text/calendar text/json text/xml	N	text/calendar
freebusybegin	integer	N	Offset in number of days from today, if dtstart is not specified. Backs off the date range by the value of this parameter. For example, a value of 30 would start the free/busy range 30 days before the current time.	N	Default value is 30 (days)
freebusyend	integer	N	Offset in number of days from today to calculate the end of the free-busy range, if dtend is not specified. For example, a value of 30 would put the end date 30 days beyond the current time.	N	Default value is 30 (days)
id	unique identifier string	N	The session identifier.	N	N/A

Description

This command retrieves the calendar free/busy information for specified users for a specified time range. Free/busy calendar information indicates which times have been scheduled on the user's calendars. Free/busy calendar information does not include any details of the scheduled time. Session-id is not

required if anonymous free/busy information access is allowed by the user.

Determining Free/busy

The busy information for all day and floating events should be presented to reflect the user's intention; that is, the exact 24 hours of the day in the user's timezone for all-day and the time-slot from start to end in the user's timezone for floating events. For this, the all day and floating events are converted to timed events in the calendar's timezone before calculating the free/busy information, which is the best guess of the user's timezone.

Calculating the Free-Busy Value

At fetch time, the server calculates the free-busy information based on events in the user's calendars. Only busy and busy-tentative information is given in the output.

PARSTAT Value	TRANSPARENCY Value	
	None specified, or OPAQUE	TRANSPARENT
TENTATIVE	Busy-tentative	Free
ACCEPTED	Busy	Free
DECLINED	Free	Free
NEEDS-ACTION	Busy-tentative	Free



Tip

For overlapping events that do not have the same free-busy types, the system returns the value based on the following precedence rules: Busy overrides Busy-tentative, Busy-tentative overrides Free.

Error Codes

If this command fails for any reason, `errno` is set to 39. For a complete list of error codes, see [Calendar Server WCAP 7.0 \(WCAPbis\) Error Codes](#).

Examples

The following URL generates free-busy information found for the users `john.smith`, `user1`, and `caluser1`, beginning 45 days before the current time and ending 60 days after the current time. The output is returned in `text/calendar` format.

```

http://<host>:<port>/wcap/get_freebusy.wcap?fmt-out=text/calendar
    &id=<session-id>
    &mail=john.smith@example.com;user1@example.com;caluser1@sun.com
    &freebusybegin=45
    &freebusyend=60

BEGIN:VCALENDAR
VERSION:2.0
PRODID:-//Oracle Corporation/CS 7u2-5.06//EN
X-NSCP-CALPROPS-RELATIVE-CALID;X-S1CS-EMAIL=john.smith@example.com:mailto:john.smith@example.com:Oracle Corporation/CS 7u2-5.06//EN
X-NSCP-CALPROPS-RELATIVE-CALID;X-S1CS-EMAIL=user1@example.com:mailto:user1@example.com:Oracle Corporation/CS 7u2-5.06//EN
X-NSCP-CALPROPS-RELATIVE-CALID;X-S1CS-EMAIL=caluser1@sun.com:mailto:caluser1@sun.com:Oracle Corporation/CS 7u2-5.06//EN

```

The following URL generates free-busy information found for the users john.doe, john.smith, user1, and caluser1 between October 21, 2011 and November 30, 2011. The output is returned in text/calendar format.

```

http://<host>:<port>/wcap/get_freebusy.wcap?fmt-out=text/calendar
    &id=<session-id>

    &mail=john.doe@example.com;john.smith@example.com;user1@example.com;caluser1@sun.com
    &dtstart=20111021T120000
    &dtend=20111130T120000

BEGIN:VCALENDAR
VERSION:2.0
PRODID:-//Oracle Corporation/CS 7u2-5.06//EN
X-NSCP-CALPROPS-RELATIVE-CALID;X-S1CS-EMAIL=john.doe@example.com:mailto:john.doe@example.com:Oracle Corporation/CS 7u2-5.06//EN
X-NSCP-CALPROPS-RELATIVE-CALID;X-S1CS-EMAIL=john.smith@example.com:mailto:john.smith@example.com:Oracle Corporation/CS 7u2-5.06//EN
X-NSCP-CALPROPS-RELATIVE-CALID;X-S1CS-EMAIL=user1@example.com:mailto:user1@example.com:Oracle Corporation/CS 7u2-5.06//EN
X-NSCP-CALPROPS-RELATIVE-CALID;X-S1CS-EMAIL=caluser1@sun.com:mailto:caluser1@sun.com:Oracle Corporation/CS 7u2-5.06//EN

```


get_guids.wcap

get_guids.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

Generate a set of globally unique identifiers.

Parameters

get_guids Parameters

Parameter	Type	Purpose	Required	Default
fmt-out	string	The format for the returned data. Two format types: text/calendar text/xml	Y	text/calendar
guidCount	integer	Number of GUID's to return.	N	1

Description

This command returns the specified number of globally unique identifiers, GUID's. The client need not be authenticated to call this command.

Example

```
http://calendarserver/get_guids.wcap
    ?guidCount=10
    &fmt-out=text/calendar
```

```
BEGIN:VCALENDAR
VERSION:6.0
  PRODID:SunONE Calendar Server 6.0
X-NSCP-GUID0:e5e4b53746560000b000000c3000000
X-NSCP-GUID1:e5e4b537d47900000c000000c3000000
X-NSCP-GUID2:e5e4b537961400000d000000c3000000
X-NSCP-GUID3:e5e4b5373d3a00000e000000c3000000
X-NSCP-GUID4:e5e4b537f31400000f000000c3000000
X-NSCP-GUID5:e5e4b5378259000010000000c3000000
X-NSCP-GUID6:e5e4b537b026000011000000c3000000
X-NSCP-GUID7:e5e4b537c263000012002002c3000000
X-NSCP-GUID8:e5e4b537241f000013000000c3000000
X-NSCP-GUID9:e5e4b537e733000014000000c3000000
END:VCALENDAR
```

get_userprefs.wcap

get_userprefs.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

Retrieve the calendar preferences for the current user.

Parameters

get_userprefs Parameters

Parameter	Type	Purpose	Required	Default
fmt-out	string	The format for the returned data. Two format types: text/calendar text/xml	Y	text/calendar
id	unique identifier string	The session identifier.	Y	N/A
userid	string	Indicates which user's preferences to get.	N	N/A

Description

This command retrieves all the calendar preferences for the current user, and the following server preferences relating to this user:

- allowchangepassword-- Users can change the password{{.}}
- allowcreatecalendars-- Users can create calendars.
- allowdeletecalendars-- Users can delete calendars.
- allowpublicwritablecalendars-- Users can have publicly writable calendars.
- validateowners-- If set to 1, the server must validate that each owner of a calendar exists in the LDAP directory.
- allowsetprefs-- If set to 1, allow set_userprefs.wcap to modify the user preferences.

See the [Sun Java System Calendar Server 6.3 Administration Guide](#) for more information about server preferences.

Access Control Information (ACI)

The Calendar Server configuration program adds new ACI's. If you are upgrading from an earlier version of Java Enterprise System, you must rerun the configuration program to have the new ACI's added. Or you can use the Directory Server `ldapmodify` command to add them yourself as follows.

In this example, the ACI is added to the root suffix, `o=usergroup`:

```
dn: o=usergroup
changetype: modify
add: aci
aci: (targetattr="icscalendar || cn || givenName || sn || uid || mail")
      (targetfilter=(objectClass=icscalendaruser))
      (version 3.0; acl "Allow calendar administrators to
proxy-product=ics,
      class=admin,num=2,version=1"; allow (proxy)
      groupdn="ldap:///cn=Calendar
Administrators,ou=Groups,o=usergroup";)
```



Note

All nodes under the `basedn` must be set to allow anyone read and search access rights in order for this command to work. For more information, see [WCAP Common Topics](#).

```
dn: o=sesta.com,o=usergroup
changetype: modify
add: aci
aci:(targetattr="icscalendar || cn || givenName || sn || uid || mail")
      (targetfilter=(objectClass=icscalendaruser))
      (version 3.0; acl "Allow calendar users to read and search other
users-product=ics,
      class=admin,num=3,version=1"; allow (search,read)
      userdn="ldap:///uid=*,ou=People, o=sesta.com, o=usergroup";)
```



Note

If there is no `basedn` domain node, add the preceding ACI to the root suffix itself by changing the `dn:` value to `o=usergroup`.

Example

The following URL retrieves user preferences for the current user:

```
http://calendarserver/get_userprefs.wcap
      ?id=b5q2o8ve2rk02nv9t6
      &calid=jdoe
      &fmt-out=text/calendar
```

This is the data returned:

```

BEGIN:VCALENDAR
PRODID:-//SunONE/Calendar Hosting Server//EN
METHOD:PUBLISH
VERSION:6.0
X-NSCP-WCAP-PREF-cn:John Doe
X-NSCP-WCAP-PREF-givenName:John
X-NSCP-WCAP-PREF-mail:jdoe@sesta.com
X-NSCP-WCAP-PREF-preferredlanguage:
X-NSCP-WCAP-PREF-sn:Doe
X-NSCP-WCAP-PREF-icsCalendar:jdoe
X-NSCP-WCAP-PREF-icsTimezone:Europe/London
X-NSCP-WCAP-PREF-icsDefaultSet:
X-NSCP-WCAP-PREF-icsFirstDay:
X-NSCP-WCAP-PREF-icsSet:name=mygroup$calendar=lucy\\;jjones
\\
;jdoe
TimeZone$tzmode=specify$tz=America/Denver$mergeInDayView=true
$description=
X-NSCP-WCAP-PREF-icsSubscribed:lucy$,jjones$,jsmith:jdoe
X-NSCP-WCAP-PREF-icsFreeBusy:jdoe
X-NSCP-WCAP-PREF-ceInterval:PT0H30M
X-NSCP-WCAP-PREF-ceDayTail:19
X-NSCP-WCAP-PREF-ceDefaultView:overview
X-NSCP-WCAP-PREF-ceColorSet:pref_group4
X-NSCP-WCAP-PREF-ceToolText:1
X-NSCP-WCAP-PREF-ceToolImage:1
X-NSCP-WCAP-PREF-ceFontFace:PrimSansBT,Verdana,sans-serif
X-NSCP-WCAP-PREF-ceExcludeSatSun:0
X-NSCP-WCAP-PREF-ceGroupInviteAll:1
X-NSCP-WCAP-PREF-ceSingleCalendarTZID:0z
X-NSCP-WCAP-PREF-ceAllCalendarTZIDs:0
X-NSCP-WCAP-PREF-ceNotifyEnable:0
X-NSCP-WCAP-PREF-ceNotifyEmail:jdoe@sesta.com
X-NSCP-WCAP-PREF-ceDefaultAlarmStart:p 15M
X-NSCP-WCAP-PREF-ceDefaultAlarmEmail:jdoe@sesta.com
X-NSCP-WCAP-PREF-nswcalCALID:jdoe
X-NSCP-WCAP-PREF-icsDWPHost:DWPserver1
X-NSCP-WCAP-PREF-icsCalendarOwned:jdoe
$John's Calendar,jdoe:personal$John's Personal Calendar
X-NSCP-WCAP-SERVER-PREF-allowchange-password:no
X-NSCP-WCAP-SERVER-PREF-allowcreatecalendars:yes
X-NSCP-WCAP-SERVER-PREF-allowdeletecalendars:
X-NSCP-WCAP-SERVER-PREF-allowpublicwritablecalendars:
X-NSCP-WCAP-SERVER-PREF-validateowners:no
X-NSCP-WCAP-ERRNO:0
END:VCALENDAR

```

The following string of commands generates the output shown:

```
http://calendarserver/get_userprefs.wcap
    ?id=t95qm0n0es3bo35r
    &fmt-out=text/calendar
    &userid=jdoe
http://calendarserver/get_userprefs.wcap
    ?id=t95qm0n0es3bo35r
    &fmt-out=text/calendar
    &userid=mailto:sue@sesta.com
http://calendarserver/get_userprefs.wcap
    ?id=t95qm0n0es3bo35r
    &fmt-out=text/calendar
    &userid=john123abc
```

```
BEGIN:VCALENDAR
PRODID:-//SunONE/Calendar Hosting Server//EN
METHOD:PUBLISH
VERSION:2.0
X-NSCP-WCAP-PREF-cn:JohnDoe,TEST TEST-2
X-NSCP-WCAP-PREF-uid:jdoe
X-NSCP-WCAP-PREF-mail:jdoe@sesta.com
X-NSCP-WCAP-PREF-givenName:John
X-NSCP-WCAP-PREF-sn:Doe
X-NSCP-WCAP-PREF-icsCalendar:jdoe
X-NSCP-WCAP-ERRNO:0
END:VCALENDAR
GET /get_userprefs.wcap?id=eo38ue2q2rq6r68u
    &fmt-out=text/calendar&userid=mailto:sue@sesta.com
BEGIN:VCALENDAR
PRODID:-//SunONE/Calendar Hosting Server//EN
METHOD:PUBLISH
VERSION:2.0
X-NSCP-WCAP-PREF-cn:Sue Smith
X-NSCP-WCAP-PREF-uid:Sue
X-NSCP-WCAP-PREF-mail:sue@sesta.com
X-NSCP-WCAP-PREF-givenName:Sue
X-NSCP-WCAP-PREF-sn:Smith
X-NSCP-WCAP-PREF-icsCalendar:sue
X-NSCP-WCAP-ERRNO:0
END:VCALENDAR
GET /get_userprefs.wcap?id=eo38ue2q2rq6r68u
    &fmt-out=text/calendar&userid=john123abc
BEGIN:VCALENDAR
PRODID:-//SunONE/Calendar Hosting Server//EN
METHOD:PUBLISHx
VERSION:2.0
X-NSCP-WCAP-ERRNO:61
END:VCALENDAR
```

import.wcap

import.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

Import events and todos in iCalendar format in to a calendar.

Parameters

import Parameters

Parameter	Type	Multi-valued?	Purpose	Required	Default
calid	string	N	Identifier of a calendar to which to import events and todos. The <code>calid</code> is the value given by the server as X-NSCP-CALPROPS-RELATIVE-CALID	N	Current user's default calendar <code>calid</code>
content-in	string	N	Content type of input data. Only <code>text/calendar</code> is supported.	N	<code>text/calendar</code>
dtend	Date Time string in UTC	N	End time and date of the events and todos to import. A value of 0 means import all components from the start date to the last date in the file.	N	0
dtstart	Date Time string in UTC	N	Start time and date of events and todos to import. A value of 0 means import all components from the earliest date in the file to the end date.	N	0
id	unique identifier string	N	The session identifier. Required unless the calendar is public.	Y	N/A

Description

Use this command to import to the specified calendar events and todos that have previously been exported to a file using the `export` command.

You must use this command with an HTTP `POST` message, unlike other commands that can be used with an HTTP `GET` message. You attach the file containing the exported events and todos to the `POST` message. This file must be in iCalendar (`.ics`) format.

Range

If you do not specify either the starting or ending date, or you pass in 0 as the value for `dtstart` and `dtend`, the command adds all events and todos in the file to the specified calendar. If you specify a starting and ending date, the command imports only events and todos in the file that fall within the time range. Specify starting and ending dates in UTC time, which is indicated by the `Z` at the end of the date-time string.

Error Codes

If the operation is successful, the error number of 0 is appended to the error string. On failure, it returns the error code 77, `BAD_IMPORT_ARGUMENTS`. For a complete list of error codes, see [Calendar Server WCAP 7.0 \(WCAPbis\) Error Codes](#).

Example

The following POST message imports the attached iCalendar file to the calendar /home/jdoe/calendar/ using the import command. The session ID is required:

```
POST
http://<calendarserver>:<port>/wcap//import.wcap?id=<session-id>&calid=/home/jdoe/calendar/
multipart/form-data;boundary=-----33111928916708
Content-Length: 679
-----33111928916708
Content-Disposition: form-data; name="file"; filename="/tmp/ical1.ics"
Content-Type: text/calendar

BEGIN:VCALENDAR
BEGIN:VEVENT
DTSTART:20020105T100000Z
DTEND:20020105T110000Z
DTSTAMP:20010104T120020Z
CREATED:20010105T110000Z
LAST-MODIFIED:20010104T120020Z
SUMMARY:Weekly QA Meeting
UID:random-uid001
END:VEVENT
BEGIN:VEVENT
DTSTART:20020106T100000Z
DTEND:20020106T110000Z
DTSTAMP:20010104T120020Z
CREATED:20010105T110000Z
LAST-MODIFIED:20010104T120020Z
SUMMARY:Weekly QA Meeting 2
UID:random-uid002
END:VEVENT
END:VCALENDAR
-----33111928916708--
```

The following HTML form creates such a POST message, attaching a file that the user specifies:

```
<FORM METHOD=POST ENCTYPE="multipart/form-data"
ACTION="http://<calendarserver>:<port>/wcap/import.wcap
?id=<session-id>
&calid=/home/jdoe/calendar/
&dtstart=0
&dtend=0
&content-in=text/calendar"\>
<ol\>
<li\>file to import:<input type="file" accept="text" name="file"\>
</li\>
<li\>Press Import Now:<input type="submit" value="Import Now"\></li\>
</ol\>
</FORM\>
```

list_subscribed.wcap

list_subscribed.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

List all calendars subscribed by current user.

Parameters

list_subscribed Parameters

Parameter	Type	Multi-valued?	Purpose	Required?	Default
id	unique identifier string	N	The session identifier. Required unless the calendar is public.	Y	N/A
fmt-out	string	N	The format for the returned data. The three format types are: text/calendar text/json text/xml	N	text/calendar

Description

Returns list of calendars the user is subscribed to.

Example

```
http://<host>:<port>/wcap/list_subscribed.wcap?fmt-out=text/calendar&id=<session-id>  
Corporation/CS_7u2-5.06//EN  
X-NSCP-WCAP-USER-ID:john.doe@example.com  
X-S1CS-CALPROPS-SUBSCRIBED-CALENDAR:/home/john.doe@example.com/calendar/  
X-S1CS-CALPROPS-SUBSCRIBED-CALENDAR:/home/john.doe@example.com/november-cal
```


list.wcap

list.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

List all calendars owned by current user.

Parameters

list Parameters

Parameter	Type	Multi-valued?	Purpose	Required?	Default
id	unique identifier string	N	The session identifier. Required unless the calendar is public.	Y	N/A
fmt-out	string	N	The format for the returned data. The three format types are: text/calendar text/json text/xml	N	text/calendar

Description

Returns list of calendars the user owns.

Examples

The following example shows subscribed calendars:

```
http://<host>:<port>/davserver/wcap/list.wcap?fmt-out=text/calendar&id=<sess  
Corporation/CS 7u2-5.06//EN  
X-NSCP-WCAP-USER-ID:john.doe@example.com  
X-S1CS-CALPROPS-SUBSCRIBED-CALENDAR:/home/john.doe@example.com/calendar/  
X-S1CS-CALPROPS-SUBSCRIBED-CALENDAR:/home/john.doe@example.com/november-cal
```

The following example shows owned calendars:

```
http://host:port/davserver/wcap/list.wcap?fmt-out=text/calendar&id=<session  
Corporation/CS 7u2-5.06//EN  
X-NSCP-WCAP-USER-ID:John.Doe@example.com  
X-S1CS-CALPROPS-OWNED-CALENDAR:/home/John.Doe@example.com/calendar/  
X-S1CS-CALPROPS-OWNED-CALENDAR:/home/John.Doe@example.com/newcal/  
X-S1CS-CALPROPS-OWNED-CALENDAR:/home/John.Doe@example.com/november-cal  
%2F/  
X-S1CS-CALPROPS-OWNED-CALENDAR:/home/John.Doe@example.com/mynewcal/  
X-S1CS-CALPROPS-OWNED-CALENDAR:/home/John.Doe@example.com/mycal/  
X-NSCP-WCAP-ERRNO:0  
END:VCALENDAR
```

login.wcap

login.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

Authenticate a specific user.

Parameters

login Parameters

Parameter	Type	Multi-valued?	Purpose	Required?	Default
fmt-out	string	N	The format for the returned data. The three format types are: text/calendar text/json text/xml	N	text/calendar
password	string	N	The user's password.	Y	N/A
proxyauth	string	N	User to proxy-auth as. Used by calendar administrators.	N	N/A
user	string	N	The user's login ID.	Y	NULL

Description

This command logs a specific user into Calendar Server, authenticating the user to the server with a user name and password convention, and returns a session-id that can be used for further commands.

The user login ID is a plain-text string that uniquely identifies the user to the server. This user login ID could, for example, be the same as a user's email address. The password is also plain-text.

Authentication

Authentication is done against the user information stored in the Directory Server LDAP. In case of

proxyauth, the user and password provided must be that of a calendar administrator, `calmaster`. The admin user is authenticated and then proxied as the user specified in the proxyauth parameter.

If the user fails to authenticate correctly, HTTP Unauthorized failure status (401) is returned. For a complete list of error codes, see [Calendar Server WCAP 7.0 \(WCAPbis\) Error Codes](#).

Examples

The following URL attempts to log in user `jdoue`:

```
http://<host>:<port>/wcap/login.wcap?user=jdoue&password=mypword  
  
BEGIN:VCALENDAR  
VERSION:2.0  
PRODID:-//Sun Microsystems/CS 7u1-1.01//EN  
X-NSCP-WCAPVERSION:7.0.0  
X-NSCP-WCAP-SESSION-ID:124cb5bab770  
X-NSCP-WCAP-CALENDAR-ID:/home/jdoue@example.com/calendar/  
X-NSCP-WCAP-USER-ID:jdoue@example.com  
X-NSCP-WCAP-ERRNO:0  
END:VCALENDAR
```

The following example shows a failed login:

```
http://<host>:<port>/wcap/login.wcap?fmt-out=text/calendar  
  
BEGIN:VCALENDAR  
VERSION:2.0  
PRODID:-//Oracle Corporation/CS 7u2-5.06//EN  
X-NSCP-WCAP-ERRNO:1  
X-NSCP-WCAP-ERRNO-MESSAGE:login failed, session-id timed out. invalid  
session-id  
END:VCALENDAR
```

logout.wcap

logout.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

Logs out a user and invalidates a session id.

Parameters

Logout Parameters

Parameter	Type	Multi-valued?	Purpose	Required?	Default
id	unique identifier string	N	The session identifier.	Y	N/A
fmt-out	string	N	The format for the returned data. The three format types are: text/calendar text/json text/xml	N	text/calendar

Description

This command logs out a specific user and invalidates the specified session-id.

Returns

The command returns a `WCAP_ERRNO` of `-1` on success. For a complete list of error codes, see [Calendar Server WCAP 7.0 \(WCAPbis\) Error Codes](#).

Example

The following URL logs out the user:


```
http://host:port/davserver/wcap/logout.wcap?fmt-out=text/calendar&id=<sessi  
Corporation/CS 7u2-5.06//EN  
X-NSCP-WCAP-ERRNO:-1  
END:VCALENDAR
```

search_calprops.wcap

search_calprops.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

Search for calendars.

Parameters

search_calprops Parameters

Parameter	Type	Multi-valued?	Purpose	Required?	Default
fmt-out	string	N	The format for the returned data. The three format types are: text/calendar text/json text/xml	N	text/calendar
id	unique identifier string	N	The session identifier.	Y	N/A
maxResults	integer	N	The maximum number of results to return. If maxResults is 0, return all available calendars that match the search.	N	200
search-string	string	N	String to use for the search. All characters in the string are treated as characters and not as search tokens. For example, using an asterisk (*) will be treated as that character and not as a wildcard for the search.	Y	" "

Description

This command searches for calendars belonging to users specified by the search string. The search-string is substituted in the server search filter defined by the server configuration option `davcore.uriinfo.subjectsearchfilter` and a query is made to the Directory Server. The query is governed by the LDAP ACLs. It returns the list of users, groups, or resources matching the search string, for which the authenticated user has access. The results of the LDAP search are then checked to make sure that active calendars exist for each and that the requesting user has both domain and calendar ACL access to these calendars. The information about the calendars that survived the filtering is outputted.

Beginning with **Calendar Server 7 Update 2 Patch 5**, the `search_calprops.wcap` command does not return calendars belonging to accounts which have a status of 'inactive,' 'removed,' or 'deleted.'

maxResults Value

If you specify a maximum `n`, the command returns up to the first `n` events and todos.

If the `maxResults` parameter is set to 0, all relevant data is returned.

If results are truncated due to `maxResults`, the property `X-S1CS-PARTIAL-RESULT-COUNT` is included in the result to indicate truncation.

Configuring LDAP Search Limit

The amount of data returned by the `search_calprops.wcap` command is dependent upon the Directory Server search limit attribute, `nsslapd-sizelimit`. When `nsslapd-sizelimit` is configured for a high value, you might experience a long wait time for the `search_calprops.wcap` command to complete. If so, use a more specific search string the next time. You could also adjust the value of `nsslapd-sizelimit` accordingly, but this changes the search limit for all applications using the Directory Server.

Error Codes

If the operation is successful, the error number of 0 is appended to the error string `X-WCAP-ERRNO`. If the search-string is too short, error 88, `BAD_SEARCH_STRING_LENGTH` is returned. For any other failure, error 19, `SEARCH_CALPROPS_FAILED` is returned.

For a complete list of error codes, see [Calendar Server WCAP 7.0 \(WCAPbis\) Error Codes](#).

Example

Here is a sample search. The search is looking for all the calendars owned by user `john.doe` and it returns `john.doe`'s default calendar and "personal" calendar.

```
http://<calendarserver>:<port>/wcap/search_calprops.wcap
      ?id=<session-id>
      &search-string=jdoe

BEGIN:VCALENDAR
VERSION:2.0
PRODID:-//Oracle Corporation/CS 7u2-4.17//EN
X-NSCP-CALPROPS-RELATIVE-CALID;X-S1CS-EMAIL=John.Doe@example.com:/home/john
Doe
X-NSCP-CALPROPS-TZID:America/Los_Angeles
X-S1CS-CALPROPS-FB-INCLUDE:1
X-S1CS-CALPROPS-ALLOW-DOUBLEBOOKING:0
X-NSCP-CALPROPS-PRIMARY-OWNER:john.doe@example.com
X-S1CS-CALPROPS-COMMON-NAME:John Doe
X-NSCP-CALPROPS-ACCESS-CONTROL-ENTRY:Jane.Doe@example.com:w
X-NSCP-CALPROPS-ACCESS-CONTROL-ENTRY:@:r
X-S1CS-MYRIGHTS:a
X-S1CS-DEFAULTCALENDAR:1
X-NSCP-WCAP-ERRNO:0
END:VCALENDAR
BEGIN:VCALENDAR
VERSION:2.0
PRODID:-//Oracle Corporation/CS 7u2-4.17//EN
X-NSCP-CALPROPS-RELATIVE-CALID;X-S1CS-EMAIL=john.doe@example.com:/home/john
Calendar
X-NSCP-CALPROPS-TZID:America/Los_Angeles
X-S1CS-CALPROPS-FB-INCLUDE:1
X-S1CS-CALPROPS-ALLOW-DOUBLEBOOKING:0
X-NSCP-CALPROPS-PRIMARY-OWNER:john.doe@example.com
X-S1CS-CALPROPS-COMMON-NAME:John Doe
X-S1CS-MYRIGHTS:a
X-NSCP-WCAP-ERRNO:0
END:VCALENDAR
```

set_accountprops.wcap

set_accountprops.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

This command specifies users' and resources' account properties that are exposed to other users.

Parameters

set_accountprops.wcap Parameter

Parameter	Types	Multi-valued?	Purposes	Required?	Default
account	unique identifier string	N	Specifies the user or resource account for which properties are to be set.	N	Logged-in user.
acl	string	N	Specifies the scheduling permissions. See ACL Description . If this value is empty, all permissions will be removed.	N	N/A.
attendanceflag	integer	N	Specifies the following behavior when an invitation occurs. See Description of attendanceflag .	N	N/A.

<code>delegate_notifaddr</code>	string	Y	A semicolon-separated list of email addresses indicating the notification addresses for the delegates for an account.	N	N/A.
<code>fmt-out</code>	string	N	The format for the returned data. The three format types are: text/calendar text/json text/xml	N	text/calendar
<code>maxbookingwindow</code>	integer	N	Specifies the end of a booking window, in days, from the time of scheduling, from which a calendar can be booked in advance.	N	Defaults to using the corresponding system-wide booking window configuration.
<code>minbookingwindow</code>	integer	N	Specifies the start of a booking window, in days, from the time of scheduling, from which a calendar can be booked in advance.	N	Defaults to using the corresponding system-wide booking window configuration.
<code>notifemail</code>	integer	N	Specifies if notification via email is enabled. 0 = notification disabled. 1 = notification enabled.	N	N/A.
<code>notifrecipients</code>	string	Y	Specifies the semicolon separated list of email addresses that should receive email notifications.	N	N/A.
<code>owner</code>	string	N	Specifies the owner of the resource. This parameter cannot be used on user accounts, only resource accounts.	N	N/A.

Description

Use this command to set the account properties for a user or resource.

ACL Description

The ACL is a semicolon separated list of access control entries (ACE). Each ACE consists of a user ID and a privilege level. The user ID is the user's email address or the special token @. @ is used to indicate all users or all authenticated users, depending on the `davcore.acl.schedulinganonymousall` configuration parameter.

The following table shows the permission levels.

Permission Levels

Privilege Level	Permission Description
n	No scheduling privileges
f	Free/busy lookup
s	Free/busy lookup and scheduling of events
m	Free/busy lookup, scheduling of events and management of the scheduling ACL

If not explicitly set, each user has the permissions defined by the server default. See [Calendar Server Access Control Lists \(ACL\)](#).

Description of attendanceflag

Specifies the behavior when an invitation occurs. The number can be between 0 and 7. The following table shows the behavior settings:

Flag Options

Option Value	Description
0	Does not perform autoaccept, does not check booking conflict, does not check recurrence on invitations
1	Automatically accepts invitations
2	Automatically declines if invitation results in booking conflict
3	Automatically accepts invitation and automatically declines on booking conflict
4	Automatically declines recurring meeting invitations
5	Automatically accepts invitations and automatically declines recurring meeting invitations
6	Automatically declines recurring invitations and invitations that cause a booking conflict
7	Automatically accepts invitations, automatically declines recurring invitations and invitations that cause a booking conflict



Note

At the system-wide level, if the `davcore.scheduling.allowownerdoublebooking` parameter is set to `true` (the default value is `false`), then resource calendar owners can double book the resource even if an attendant flag is set that prevents double booking.

Returns

The command returns an error code indicating success or failure.

Error Codes

The command returns:

```
X-NSCP-WCAP-ERRNO=0: No errors
X-NSCP-WCAP-ERRNO=89: Set failed.
```

For a complete list of error codes, see [Calendar Server WCAP 7.0 \(WCAPbis\) Error Codes](#).

Example

This example sets properties on the `john.doe@example.com` account.

```
http://<host>:<port>/wcap/set_accountprops.wcap
  ?fmt-out=text/calendar
  &id=<session-id>
  &account=john.doe@example.com
  &acl=@:s&notifemail=1
  &notifrecipients=john.doe@example.com;john.smith@example.com
  &attendanceflag=5

BEGIN:VCALENDAR
VERSION:2.0
PRODID:-//Oracle Corporation/CS 7u2-5.06//EN
X-NSCP-WCAP-ERRNO:0
END:VCALENDAR
```


set_calprops.wcap

set_calprops.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

Sets the calendar properties of a specified calendar.

Parameters

set_calprops Parameters

Parameter	Type	Multi-valued?	Purpose	Required?	Default
acl	string	N	A semicolon-separated list of strings specifying the new value of the access control entries. See Administering Calendar Server Access for more information.	N	" "
calid	string	N	Calendar identifier of calendar to modify. The calid is the value given by the server as X-NSCP-CALPROPS-RELATIVE-CALID.	N	Current user's default calendar calid
desc	string	N	The description of the calendar.	N	N/A
fbinclude	integer	N	Specifies whether the calendar should be used in any free/busy lookup. 1 = Include the calendar. 0 = Do not include the calendar. If you want to remove the calendar from the free/busy lookup list, pass in fbinclude=0.	N	N/A
fmt-out	string	N	The format for the returned data. The three format types are: text/calendar text/json text/xml	N	text/calendar
id	unique identifier string	N	The session identifier.	Y	N/A
name	string	N	The new display name of the calendar.	N	N/A
tzid	String	N	Time zone identifier of the calendar.	N	Server's default time zone

Description

Calendar properties are special states of a calendar, which includes the calendar's name, read and write permission values (acl parameter), and so on. You can use the `set_calprops.wcap` command to change these properties of a calendar. This command is an update command, that is, it only changes the values of the parameters you specify. It is not necessary to supply all parameters in the command, only the ones you want to change. On update, it replaces the existing value of the same property. Thus, when modifying the properties, especially access control entries, make sure to specify all required values in the set command.

Use `set_calprops` to:

- Change the display name of the calendar
- Change read permission of calendar's events
- Change write permission of calendar's events
- Change description of calendar
- Change the time zone-identifier of the calendar
- Allow or disallow double booking for this calendar

Example

This example sets a new display name, `mynewcalendar`, for the `/home/jdoe/mynewcal` calendar.

```
http://<host>:<port>/davserver/wcap/set_calprops.wcap?calid=/home/jdoe/mynewca  
Corporation/CS_7u2-5.06//EN  
X-NSCP-CALPROPS-RELATIVE-CALID;X-S1CS-EMAIL=john.doe@example.com:/home/jdoe/my
```

Access Control Entries

See [Calendar Access Control Information \(ACI\)](#).

Free/busy Access

See [Free/busy Information Handling in Calendar Server WCAP 7.0 \(WCAPbis\)](#).

storeevents.wcap

storeevents.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

Add events to a calendar.

Parameters

storeevents Parameters

Parameter	Type	Multi-valued?	Purpose	Required?
alarms	semicolon-separated list of alarm strings	N	Specify alarms or reminders for the event. See WCAP Alarms Parameter for details	N
attendees	semicolon-separated list of strings	Y	An event's iCalendar RFC 5545 ATTENDEE properties. For a list of the parameters understood by Calendar Server, see Calendar Server WCAP Attendee Parameter .	N
calid	string	N	Calendar identifier, or email address of the calendar, in which to store the event.	Y
categories	semicolon-separated list of strings	Y	Categories to which the event belongs.	N

compressed	integer (0,1)	N	Used in conjunction with <code>fetch=1</code> and <code>recurring=0</code> . . <code>compressed=0</code> returns less data. Specifically, it does not return the following parameters: <code>rrules</code> , <code>rdates</code> , <code>exrules</code> , and <code>exdates</code> . For <code>compressed=1</code> , all recurrence data is returned.	N
contacts	semicolon-separated list of strings	Y	Contacts for the event.	N
desc	string	N	Event purpose description. A string of any length.	N
deleteattach	semicolon-separated list of strings	Y	List of attachment ids to delete.	N
dtend	Date Time string	N	Event end time and date.	N
dtstart	Date Time string	N	Event start time and date. Required to create or modify events.	N
duration	string	N	Event duration in ISO8601 format. Ignored if <code>dtend</code> is also provided.	N
excludedtstart	integer (0,1)	N	A boolean indicating whether or not to include the <code>dtstart</code> date in a recurring series if it does not fall within the <code>rrules</code> dates. 1 = exclude the <code>dtstart</code> date. 0 = include the <code>dtstart</code> date.	N
expandend	Date Time string	N	Expansion end time and date. Required with <code>fetch=1</code> and <code>recurring=0</code> , for recurring event.	N
expandstart	Date Time string	N	Expansion start time and date. Used with <code>fetch=1</code> and <code>recurring=0</code> , for recurring event.	N
fetch	integer (0,1)	N	A boolean indicating whether or not to fetch and return newly stored event(s). 1 = Fetch and return newly stored event. 0 = Do not fetch.	N
file	MIME body part	Y	Add attachment files.	N

fmt-out	string	N	The format for the returned data. The three format types are: text/calendar text/json text/xml	N
icsClass	string	N	Event class. One of the following values: PUBLIC - Others can see time and text. PRIVATE - Others can see nothing. CONFIDENTIAL - Others can see time and date only. (Set transparent = 1 to make it invisible to free/busy queries).	N
id	unique identifier string	N	The session identifier.	Y
location	string	N	Event location.	N
method	integer (1,2,4,8,256)	N	ITIP methods for group scheduling. The organizer issues the following ITIP methods: <ul style="list-style-type: none"> • 1 = PUBLISH • 2 = REQUEST • 8 = CANCEL The attendee issues these ITIP methods: 4 = REPLY or 256 = UPDATE	Y
priority	integer (0-9)	N	Event priority. Follows RFC 5545. 0 = undefined 1= highest 9= lowest	N
orgEmail This parameter is available starting in Calendar Server 7 Update 3 Patch 9.	string	N	Sets organizer email if different from calendar owner.	N
orgCN This parameter is available starting in Calendar Server 7 Update 3 Patch 9.	string	N	Sets organizer CN if organizer is different from calendar owner. Use only in conjunction with orgEmail	N

recurring	integer (0, 1)	N	1 = Returns all components in compressed form, which contains a master entry plus exceptions. 0 = Returns components expanded into individual instances.	N
replace	integer (0,1)	N	A boolean. For parameters with semicolon-separated values, except alarms: 1 = update (Replace the old values with the new passed-in values.) 0 = append (Add the new passed-in values to the old ones.)	N
resources	semicolon-separated list of strings	Y	The resources associated with the event.	N
rid	RFC5545 Date Time string	N	Event recurrence identifier. Not required to create events. If this parameter is not set when trying to modify events, the whole series of events is modified.	N
rrules	String	N	Event recurrence rules. A recurrence rule string as defined in RFC5545. See Recurring Components in Calendar Server WCAP .	N
seq	integer	N	Revision sequence number of the event.	N
smtp	integer boolean (0 or 1)	N	Send email invitation to external attendees 0 => NO 1 => YES	N
smtpNotify	integer boolean (0 or 1)	N	Send invitation notifications to attendees, if they have notification enabled. 0 => NO 1 => YES	N
status Available starting with Calendar Server 7 Update 1 Patch 3	string	N	Specify the status of the event: cancelled - event has been cancelled confirmed - event is definite tentative - event is tentative	N

storetype	integer	N	Designates whether an explicit "create" or "modify" is attempted on an event. An error results if an attempt is made to create an event that already exists, or to modify an event that does not exist. The following values are valid: 0 WCAP_STORE_TYPE_NONE 1 WCAP_STORE_TYPE_CREATE 2 WCAP_STORE_TYPE_MODIFY If the attribute is not passed or has a value of 0, no error conditions are reported and the server does the right thing.	N
summary	string	N	Event summary. A string of any length.	N
transparent	integer 0, 1	N	A boolean indicating if the event should be included in free/busy calculations.	N
tzid	time zone ID string	N	The time zone associated with passed in dates. If this parameter is missing, and the time string has no Z after it, the calendar server time zone ID is used.	N
tzidout	time zone ID string	N	Time zone returned data should be translated to.	N
uid	string	N	Unique identifier of the event to be stored. System generated for new events. Required to modify events.	N (create) Y (modify)
xprops	A <CR NL> or a <%0D%0A> - separated list of iCalendar xprops components	Y	Input additional xprops.	N

Description

Use this command to create or modify events with the specified attributes and store them in the specified calendar in the database.

The command creates and stores recurrences as specified by the recurrence parameters. See [Recurring Components in Calendar Server WCAP](#).

For an explanation of how to use the `attendee` and `method` parameters to do group scheduling, see the Common Topics section [Calendar Server WCAP Attendee Parameter](#).

For an explanation of how to replace, append or delete a parameter, see the explanation in the Common Topics section [Updating Parameter Values in Calendar Server WCAP](#).

It is possible to delete an attendee in an existing meeting by assigning the value `X-NSCP-WCAP-ATTENDEE-DELETE` to the `attendee` parameter `PARTSTAT`. For example, to delete attendee `jdoe`, the `attendee` parameter would contain the following:

```
PARTSTAT=X-NSCP-WCAP-ATTENDEE-DELETE^jdoe
```

Required Parameters

This command creates new events and modifies existing events. You can not add and modify events in the same command. You must do one or the other.

Each case requires a different set of parameters:

- To create new events requires only the `dtstart` parameter. Every other parameter is optional. The server generates the `uid`.
- To modify existing events `uid` parameter is required.

All other parameters are optional. If a parameter is not specified, the event retains the previous value of the property.

Attachments

Attachments can be stored as data for an event.

The actual attachments will follow the `store` command as multipart form-data for the POST. Following example shows how attachments can be stored by passing arguments to `storeevents` in the URI itself and the actual attachments in the data.

```
POST
http://<calendarserver>:<port>/wcap/storeevents.wcap?id=${SESSIONID}&calid=
Keep-Alive
Content-Type    multipart/form-data;
boundary=-----abcdefghijklmnopqrstuvwxyz
Content-Length  444

-----abcdefghijklmnopqrstuvwxyz
Content-Disposition: form-data; name="file"; filename="birthday.jpeg"
Content-Type: application/octet-stream

<raw content of birthday.jpeg>
-----abcdefghijklmnopqrstuvwxyz
Content-Disposition: form-data; name="file"; filename="birthday.gif"
Content-Type: application/octet-stream

<raw content of birthday.gif>
-----abcdefghijklmnopqrstuvwxyz--
```

See [Calendar Server WCAP Attachment Support](#) for more details.

Duration

If you specify both `duration` and `dtend`, the `store` command fails.

Specify the `duration` in iCal format. For example:

- `P3DT1H30M10S` represents a duration of 3 days, 1 hour, 30 minutes, 10 seconds
- `PT1H30M` represents a duration of 1 hour, 30 minutes
- `P1D` represents a duration of 1 day
- `PT15M` represents a duration of 15 minutes

Notice that the `T` in the string separates the date information from the time information.

Returns

The command returns the error value. To have the command return the stored event data, specify `fetch=1`. In addition, use the `tzidout` parameter to specify the time zone to which the returned data should be translated. If the `tzidout` parameter is missing, the data is returned in Zulu time.

Error Codes

If you set `storetype` for creation, possible error codes are `CALENDAR_DOES_NOT_EXIST` (29) or `WCAP_CREATE_EXISTS` (63).

On modification, possible error codes are `CALENDAR_DOES_NOT_EXIST` (29) or `WCAP_MODIFY_NO_EVENT` (62).

If double booking is disallowed, when you try to store an event in a time slot that is already scheduled, the command fails, and returns: `FAILED: STORE_FAILED_DOUBLE_BOOKED` (40).

For a complete list of error codes, see [Calendar Server WCAP 7.0 \(WCAPbis\) Error Codes](#).

Upfront Free/busy Check for Control of Doublebooking and Booking Window During Scheduling

A scheduling attempt requested for an account that has the attendance flag set to "decline on conflict" (the attendance flag is set either by a `set_accountsprops.wcap` command or `davadmin account` command), triggers Calendar Server to perform a special free/busy check. This check happens as part of the scheduling process for both CalDAV and WCAP clients. Because scheduling is an asynchronous process, the event organizers are made aware of an error only after they have made the booking. However, for clients that use the WCAP protocol, the same check is performed upfront if the scheduled attendee is a resource. This enables the organizer to get an immediate error if the event request results in a conflict for the resource.

Example

This example creates a daily recurring private event with five instances, inviting two attendees, and fetches back instances that fall between `expandstart` and `expandend`.

```
http://<host>:<port>/wcap/storeevents.wcap?fmt-out=text/calendar&id=<sessio
attendees=john.smith@example.com;john.doe@example.com&

calid=/home/jdoe/calendar/&compressed=1&contacts=john.doe@example.com&

desc=December%20Event&tzid=America/Los_Angeles&dtstart=20120601T150000&dter
location=Conf_Room&method=2&priority=5&recurring=0&rrules:count=5;freq=dail
summary=New%20December%20Calculator&expandstart=20120601T150000&expandend=2
Corporation/CS 7u2-5.06//EN
X-NSCP-CALPROPS-RELATIVE-CALID;X-S1CS-EMAIL=john.doe@example.com:/home/jdoe
December Calculator
DTSTART;TZID=America/Los_Angeles:20120601T150000
DTEND;TZID=America/Los_Angeles:20120601T160000
CREATED:20120601T210558Z
LAST-MODIFIED:20120601T210558Z
PRIORITY:5
CLASS:PRIVATE
ORGANIZER;CN=John Doe:mailto:john.doe@example.com
STATUS:CONFIRMED
LOCATION:Conf_Room
DESCRIPTION:December Event
ATTENDEE;CN=jsmith;SCHEDULE-STATUS=1.2:mailto:john.smith@example.com
ATTENDEE:mailto:john.doe@example.com
CONTACT:john.doe@example.com
END:VEVENT
END:VCALENDAR
```

storetodos.wcap

storetodos.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

Add todos to a calendar or modify existing ones.

Parameters

storetodos Parameters

Parameter	Type	Multi-valued?	Purpose	Required?
alarms	semicolon-separated list of alarm strings	N	Specify alarms or reminders for the todo. See WCAP Calendar Server Alarms for details.	N
attendees	semicolon-separated list of strings	Y	A todo's iCalendar RFC 5545 ATTENDEE properties. For a list of the parameters understood by Calendar Server, see Calendar Server WCAP Attendee Parameter .	N
calid	string	N	Calendar identifier, or email address of the calendar, in which to store the todo.	Y
categories	semicolon-separated list of strings	Y	Categories to which the todo belongs.	N
completed	Date Time String	N	Date and time of completion.	N

compressed	integer (0,1)	N	Used in conjunction with <code>fetch=1</code> and <code>recurring=0</code> . <code>compressed=0</code> returns less data. Specifically, it does not return the following parameters: <code>rrules</code> , <code>rdates</code> , <code>exrules</code> , and <code>exdates</code> . For <code>compressed=1</code> , all recurrence data is returned.	N
contacts	semicolon-separated list of strings	Y	Contacts for the todo.	N
desc	string	N	Todo purpose description. A string of any length.	N
deleteattach	semicolon-separated list of strings	Y	List of attachment ids to delete.	N
dtstart	Date Time string	N	Todo start time and date. Required to create or modify todos.	N
due	Date Time string	N	Todo due time and date.	N
duration	string	N	Task duration in ISO8601 format. Ignored if <code>due</code> is also provided.	N
excludedtstart	integer (0,1)	N	A boolean indicating whether or not to include the <code>dtstart</code> date in a recurring series if it does not fall within the <code>rrules</code> dates. 1 = exclude the <code>dtstart</code> date. 0 = include the <code>dtstart</code> date.	N
expandend	Date Time string	N	Expansion end time and date. Required with <code>fetch=1</code> and <code>recurring=0</code> , for recurring todo.	N
expandstart	Date Time string	N	Expansion start time and date. Used with <code>fetch=1</code> and <code>recurring=0</code> , for recurring todo.	N
fetch	integer (0,1)	N	A boolean indicating whether or not to fetch and return newly stored todo(s). 1 = Fetch and return newly stored todo. 0 = Do not fetch.	N
fmt-out	string	N	The format for the returned data. The three format types are: <code>text/calendar</code> <code>text/json</code> <code>text/xml</code>	N

icsClass	string	N	Todo class. One of the following values: PUBLIC - Others can see time and text. PRIVATE - Others can see nothing. CONFIDENTIAL - Others can see time and date only.	N
id	unique identifier string	N	The session identifier.	Y
location	string	N	Todo location.	N
method	integer (1,2,4,8,256)	N	ITIP methods for group scheduling. The organizer issues the following ITIP methods: <ul style="list-style-type: none"> • 1 = PUBLISH • 2 = REQUEST • 8 = CANCEL The attendee issues these ITIP methods: 4 = REPLY or 256 = UPDATE	Y
orgEmail This parameter is available starting in Calendar Server 7 Update 3 Patch 9.	string	N	Sets organizer email if different from calendar owner.	N
orgCN This parameter is available starting in Calendar Server 7 Update 3 Patch 9.	string	N	Sets organizer CN if organizer is different from calendar owner. Use only in conjunction with orgEmail	N
percent	integer (0-100)	N	Percentage of task done.	N
priority	integer (0-9)	N	Todo priority. Follows RFC 5545. 0 = undefined 1= highest 9= lowest	N
recurring	integer (0, 1)	N	1 = Returns all components in compressed form , which contains a master entry plus exceptions. 0 = Returns components expanded into individual instances.	N

replace	integer (0,1)	N	A boolean. For parameters with semicolon-separated values, except alarms: 1 = update (Replace the old values with the new passed-in values). 0 = append (Add the new passed-in values to the old ones).	N
resources	semicolon-separated list of strings	Y	The resources associated with the todo.	N
rid	RFC5545 Date Time string	N	Todo recurrence identifier. Not required to create todos. If this parameter is not set when trying to modify todos, the whole series of todos is modified.	N
rrules	String	N	Todo recurrence rules. A recurrence rule string as defined in RFC5545. See Recurring Components in Calendar Server WCAP .	N
seq	integer	N	Revision sequence number of the todo.	N
smtp	integer boolean (0 or 1)	N	send email invitation to external attendees 0 => NO 1 => YES	N
smtpNotify	integer boolean (0 or 1)	N	send invitation notifications to attendees, if they have notification enabled. 0 => NO 1 => YES	N
status Available starting in Calendar Server 7 Update 1 Patch 3.	String	N	Specify the status of the task: cancelled - task has been cancelled completed - task has been completed in-process - task is in progress needs-action - task needs action	N

storetype	integer	N	Designates whether an explicit "create" or "modify" is attempted on a todo. An error results if an attempt is made to create a todo that already exists, or to modify a todo that does not exist. The following values are valid: 0 WCAP_STORE_TYPE_NONE 1 WCAP_STORE_TYPE_CREATE 2 WCAP_STORE_TYPE_MODIFY If the attribute is not passed or has a value of 0, no error conditions are reported and the server does the right thing.	N
summary	string	N	Todo summary. A string of any length.	N
tzid	time zone ID string	N	The time zone associated with passed in dates. If this parameter is missing, and the time string has no Z after it, the calendar server time zone ID is used.	N
tzidout	time zone ID string	N	Time zone returned to which data should be translated.	N
uid	string	N	Unique identifier of the todo to be stored. System generated for new todos. Required to modify todos.	N (create) Y (modify)

Description

Use this command to create or modify todos with the specified attributes and store them in the specified calendar in the database.

The command creates and stores recurrences as specified by the recurrence parameters. See [Recurring Components in Calendar Server WCAP](#).

For an explanation of how to use the `attendee` and `method` parameters to do group scheduling, see the Common Topics section [Calendar Server WCAP Attendee Parameter](#).

For an explanation of how to replace, append or delete a parameter, see the explanation in the Common Topics section [Updating Parameter Values in Calendar Server WCAP](#).

It is possible to delete an attendee in an existing task by assigning the value `X-NSCP-WCAP-ATTENDEE-DELETE` to the `attendee` parameter `PARTSTAT`. For example, to delete attendee `jdoe`, the `attendee` parameter would contain the following:


```
PARTSTAT=X-NSCP-WCAP-ATTENDEE-DELETE^jdoe
```

Required Parameters

This command creates new todos and modifies existing todos. You cannot add and modify todos in the same command. You must do one or the other.

To modify existing todos the `uid` parameter is required.

All other parameters are optional. If a parameter is not specified, the todo retains the previous value of the property.

Attachments

Attachments can be stored as data for a todo.

The actual attachments follow the `store` command as multipart form-data for the POST.

The following example shows how attachments can be stored by passing arguments to `storetodos` in the URI itself and the actual attachments in the data.

```
POST
http://<calendarserver>:<port>/wcap/storetodos.wcap?id=${SESSIONID}&calid=,
Keep-Alive
Content-Type    multipart/form-data;
boundary=-----abcdefghijklmnopqrstuvwxyz
Content-Length  444

-----abcdefghijklmnopqrstuvwxyz
Content-Disposition: form-data; name="file"; filename="birthday.jpeg"
Content-Type: application/octet-stream

<raw content of birthday.jpeg>
-----abcdefghijklmnopqrstuvwxyz
Content-Disposition: form-data; name="file"; filename="birthday.gif"
Content-Type: application/octet-stream

<raw content of birthday.gif>
-----abcdefghijklmnopqrstuvwxyz--
```

See [Calendar Server WCAP Attachment Support](#) for more details.

Duration

If you specify both `duration` and `dtend`, the `store` command fails.

Specify the `duration` in iCal format. For example:

- `P1Y2M3DT1H30M10S` represents a duration of 1 year, 2 months, 3 days, 1 hour, 30 minutes, 10 seconds
- `PT1H30M` represents a duration of 1 hour, 30 minutes
- `P1D` represents a duration of 1 day
- `PT15M` represents a duration of 15 minutes

Notice that the T in the string separates the date information from the time information.

Returns

The command returns the error value. To have the command return the stored todo data, specify `fetch=1`. In addition, use the `tzidout` parameter to specify the time zone to which the returned data should be translated. If the `tzidout` parameter is missing, the data is returned in Zulu time.

Error Codes

If you set `storetype` for creation, possible error codes are `CALENDAR_DOES_NOT_EXIST (29)` or `WCAP_CREATE_EXISTS (63)`.

On modification, possible error codes are `CALENDAR_DOES_NOT_EXIST (29)` or `WCAP_MODIFY_NO_EVENT (62)`.

If double booking is disallowed, when you try to store a todo in a time slot that is already scheduled, the command fails, and returns `FAILED: STORE_FAILED_DOUBLE_BOOKED(40)`.

For a complete list of error codes, see [Calendar Server WCAP 7.0 \(WCAPbis\) Error Codes](#).

Examples

The following URL calls `storetodos.wcap` and results in storing a todo in the calendar `/home/jdoe/calendar/`:

```
http://<host>:<port>/wcap/storetodos.wcap
?fmt-out=text/calendar&id=<session-id>
&compressed=1&attendees=john.smith@example.com;john.doe@example.com
&dtstart=20111206T120000Z&dtend=20111220T120000Z
&expandend=20111220T120000Z&summary=store-event
&recurring=0&fetch=1&status=needs-action
&priority=9&calid=/home/jdoe/calendar/
&icsClass=PRIVATE&location=Asia/Kolkatta&method=1
&rrules:freq=weekly;count=7;until=20111220T120000Z
&rid=20111210T120000Z&mod=1&smtp=1&smtpNotify=1
&storetype=1&resource=/home/jdoe/calendar/

BEGIN:VCALENDAR
VERSION:2.0
PRODID:-//Oracle Corporation/CS 7u2-5.06//EN
X-NSCP-CALPROPS-RELATIVE-CALID;X-S1CS-EMAIL=john.doe@example.com:/home/jdoe
Doe:mailto:john.doe@example.com
STATUS:NEEDS-ACTION
LOCATION:Asia/Kolkatta
ATTENDEE;CN=jsmith;SCHEDULE-STATUS=1.2:mailto:john.smith@example.com
ATTENDEE:mailto:john.doe@example.com
END:VTODO
END:VCALENDAR
```

The following example modifies an existing todo:

```
http://<host>:<port>/wcap/storetodos.wcap
?fmt-out=text/calendar
&id=<session-id>&compressed=1
&attendees=john.smith@example.com;john.doe@example.com
&dtstart=20111206T120000Z&dtend=20111220T120000Z
&expandend=20111220T120000Z&summary=store-todo
&recurring=0&fetch=1&status=needs-action
&priority=9&calid=/home/jdoe/calendar/
&icsClass=PRIVATE&location=Asia/Kolkatta
&method=1&rrules:freq=weekly;count=7;until=20111220T120000Z
&rid=20111210T120000Z&mod=1&smtp=1&smtpNotify=1
&storetype=2&resource=/home/jdoe/calendar/
&uid=6b32f245-44bb-4f7c-8bcd-9b6e520d8a52

BEGIN:VCALENDAR
VERSION:2.0
PRODID:-//Oracle Corporation/CS 7u2-5.06//EN
X-NSCP-CALPROPS-RELATIVE-CALID;X-S1CS-EMAIL=john.doe@example.com:/home/jdoe
Doe:mailto:john.doe@example.com
STATUS:NEEDS-ACTION
LOCATION:Asia/Kolkatta
ATTENDEE;CN=jsmith;SCHEDULE-STATUS=1.2:mailto:john.smith@example.com
ATTENDEE:mailto:john.doe@example.com
ATTENDEE;CN=jsmith;SCHEDULE-STATUS=1.2:mailto:john.smith@example.com
ATTENDEE:mailto:john.doe@example.com
END:VTODO
END:VCALENDAR
```

subscribe_calendars.wcap

subscribe_calendars.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

Add the specified calendars to the user's calendar subscription list.

Parameters

subscribe_calendars Parameters

Parameter	Type	Multi-valued?	Purpose	Required?	Default
calid	string	Y	Semi-colon separated list of calendars to be added to subscription list. The calid is the value given by the server as X-NSCP-CALPROPS-RELATIVE-CALID	Y	N/A
fmt-out	string	N	The format for the returned data. The three format types are: text/calendar text/json text/xml	N	text/calendar
id	unique identifier string	N	The session identifier.	Y	N/A

Description

Adds the calendar(s) specified in the `calid` parameter to the user's subscription list. The command checks that the calendar(s) exist and that the logged-in user has at least "read" access to those calendars. If not, error code 73, `SUBSCRIBE_FAILED`, is returned. For a complete list of error codes, see [Calendar Server WCAP 7.0 \(WCAPbis\) Error Codes](#).

Examples

The following example shows a successful calendar subscription.

```
http://<host>:<port>//davserver/wcap/subscribe_calendars.wcap?calid=/home/;  
&fmt-out=text/calendar  
    &id=<sessionid>  
  
BEGIN:VCALENDAR  
VERSION:2.0  
PRODID:-//Oracle Corporation/CS 7u2-5.06//EN  
X-NSCP-WCAP-ERRNO:0  
END:VCALENDAR
```

The following example shows a calendar subscription attempt, but the logged-in user does not have at least read access to the requested calendar.

```
http://<host>:<port>/wcap/subscribe_calendars.wcap?fmt-out=text/calendar  
    &calid=/home/jsmith/calendar;/home/caluser/calendar/  
    &id=<session-id>  
  
BEGIN:VCALENDAR  
VERSION:2.0  
PRODID:-//Oracle Corporation/CS 7u2-5.06//EN  
X-NSCP-WCAP-ERRNO:73  
END:VCALENDAR
```

The following example shows that anonymous access is not permitted when attempting to subscribe to a calendar.

```
http://<host>:<port>/wcap/subscribe_calendars.wcap?fmt-out=text/calendar  
    &calid=/home/jsmith/calendar;/home/caluser/calendar/  
  
BEGIN:VCALENDAR  
VERSION:2.0  
PRODID:-//Oracle Corporation/CS 7u2-5.06//EN  
X-NSCP-WCAP-ERRNO:75  
X-NSCP-WCAP-ERRNO-MESSAGE:Command cannot be executed by anonymous  
X-NSCP-WCAP-ERRNO-DETAILED-MESSAGE:forbidden  
END:VCALENDAR
```

unsubscribe_calendars.wcap

unsubscribe_calendars.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

Remove the specified calendar(s) from the user's calendar subscription list.

Parameters

unsubscribe_calendars Parameters

Parameter	Type	Multi-valued?	Purpose	Required?	Default
calid	string	Y	Semi-colon separated list of calendars to be removed from subscription list. The calid is the value given by the server as X-NSCP-CALPROPS-RELATIVE-CALID.	Y	N/A
fmt-out	string	N	The format for the returned data. The three format types are: text/calendar text/json text/xml	N	text/calendar
id	unique identifier string	N	The session identifier.	Y	N/A

Description

Removes the calendar(s) specified in the calid parameter from the user's subscription list. The command does not check to see if the calendar(s) exists. Returns error code 74, UNSUBSCRIBE_FAILED, if the command fails. For a complete list of error codes, see [Calendar Server WCAP 7.0 \(WCAPbis\) Error Codes](#).

Example

This example removes the `/home/jdoe/mynewcal` calendar from the subscription list.

```
http://<host>:<port>//davserver/wcap/unsubscribe_calendars.wcap?calid=/home
&fmt-out=text/calendar
    &id=<sessionid>

BEGIN:VCALENDAR
VERSION:2.0
PRODID:-//Oracle Corporation/CS 7u2-5.06//EN
X-NSCP-WCAP-ERRNO:0
END:VCALENDAR
```

version.wcap

version.wcap



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

Purpose

Print server and WCAP version.

Parameters

version Parameter

Parameter	Types	Multi-valued?	Purposes	Required?	Default
fmt-out	string	N	The format for the returned data. The three format types are: text/calendar text/json text/xml	N	text/calendar

Description

Prints server version and wcap version in requested format.

Returns

Version information.

Error Codes

Returns WCAP_ERRNO 0. For a complete list of error codes, see [Calendar Server WCAP 7.0 \(WCAPbis\) Error Codes](#).

Example

This example returns a version of 7u2-5.05 for Calendar Server, which corresponds to Calendar Server 7 Update 2 Patch 5.


```
http://<host>:<port>/davserver/wcap/version.wcap?fmt-out=text/calendar
BEGIN:VCALENDAR
VERSION:2.0
PRODID:-//Oracle Corporation/CS 7u2-5.05//EN
X-NSCP-WCAPVERSION:7.0.0
X-NSCP-SERVERVERSION:7u2-5.05
END:VCALENDAR
```

Chapter 2. Oracle Communications Calendar Server WCAP Common Topics

Oracle Communications Calendar Server WCAP 7.0 (WCAPbis) Common Topics



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

This information contains topics of common interest that span multiple commands.

Topics:

- Calendar Server Access Control Lists (ACL)
- Calendar Server WCAP 7.0 (WCAPbis) Attachment Support
- Calendar Server WCAP 7.0 (WCAPbis) Attendee Parameter
- Calendar Server WCAP 7.0 (WCAPbis) Method Parameter
- Calendar Server WCAP 7.0 (WCAPbis) Encoded Characters
- Calendar Server WCAP 7.0 (WCAPbis) Error Handling
- Fetching Component Data Using Calendar Server WCAP 7.0 (WCAPbis)
- Fetching Recurrence Data Using Calendar Server WCAP 7.0 (WCAPbis)
- Free/busy Information Handling in Calendar Server WCAP 7.0 (WCAPbis)
- Output Format Used by Calendar Server WCAP 7.0 (WCAPbis)
- Recurring Components in Calendar Server WCAP 7.0 (WCAPbis)
- Calendar Server WCAP 7.0 (WCAPbis) Time Zones
- Updating Parameter Values in Calendar Server WCAP 7.0 (WCAPbis)
- X-Tokens Used by Calendar Server WCAP 7.0 (WCAPbis)
- WCAP 7.0 (WCAPbis) Calendar Server Alarms
- Filter Parameter in WCAP 7.0 (WCAPbis) Fetch

Calendar Server Access Control Lists (ACL)

See [Administering Calendar Server Access](#).

Calendar Server WCAP 7.0 (WCAPbis) Attachment Support

Attachments can be stored as part of an event by providing it as a MIME part in either the WCAP `storeevents.wcap` or `storetodos.wcap` command over the `http post` command. Each user calendar has a special collection called a *dropbox*. The dropbox stores calendar attachments. Attachments are not stored as part of the event or task itself. In the case of group scheduled events, the

attachments are stored in the organizer's dropbox, and attendee's events refer to the organizer's attachment. The location of the attachment is stored in the event or the task's `X-S1CS-ATTACH-ID` property value.

- Attachments can be fetched by using the `fetchattachment.wcap` command.

```
http://calendarserver:port/wcap/fetchattachment.wcap?
fmt-out=text/xml
&attachid=/home/jdoe/calendar/dropbox/D1E96253-FD32-4E6A-BA92-0637D8F
```

- Using the `storeevents.wcap` or `storetodos.wcap` command, you can delete the attachments for an event or todo, by sending the attachment url (`X-S1CS-ATTACH-ID` value) as value of the `deleteattach` parameter. The value can be a semicolon separated list of attachment urls. Attachments will be automatically deleted if the events or tasks referring to it are deleted.
- Attachments will not be sent to external invitees or as part of iMIP.

Calendar Server WCAP 7.0 (WCAPbis) Attendee Parameter

Each attendee entry can contain several sub-parameters, such as invitation participation status, whether attendance is required or not, type of the attendee, and so forth. All such sub-parameters are encapsulated in a syntax very similar to the parameters for the `ATTENDEE` property defined in the iCalendar Specification (RFC 5545). Read the entire document to have the necessary background information to understand the WCAP attendee syntax. Some differences exist, for example, WCAP uses a different delimiter, `^`, to set apart these sub-parameters. (However, WCAP uses the standard iCalendar semicolon delimiter for separating attendees.)

For example, where iCalendar uses the following:

```
PARSTAT=ACCEPTED;RSVP=TRUE;mailto:abc@xyz.com
```

WCAP formats it this way:

```
PARSTAT=ACCEPTED^RSVP=TRUE^mailto:abc@xyz.com
```

The default setting for the `PARTSTAT` sub-parameter on creation of an event is `NEEDS-ACTION`, except for Organizer itself. It is changed to `ACCEPTED` or `DECLINED` when the attendee replies to the invitation. The `PARTSTAT` sub-parameter is reset to `NEEDS-ACTION` on any significant update from the Organizer. An attendee can be removed from an existing event by the Organizer, by storing the event again with the `replace` parameter value set to 1, and either not specifying the attendee in the attendee list or changing the attendee `PARTSTAT` sub-parameter value to `X-NSCP-WCAP-ATTENDEE-DELETE`.

Calendar Server WCAP 7.0 (WCAPbis) Method Parameter

The `method` parameter describes the type of store: invitation, response, cancellation. The value is used in the construction of the iTIP message only. The actual required action is interpreted by the server from all other provided parameters.

Calendar Server WCAP 7.0 (WCAPbis) Encoded Characters

In the example, the encoded list of parameters for `cal` includes some encoded characters. Here are some examples of characters and their encoding:

=	%3D
&	%26
"	%22

The %xx string is the hexadecimal value of the character. For example, the & character is 26 in hexadecimal.

Calendar Server WCAP 7.0 (WCAPbis) Error Handling

Each call to a WCAP command also returns an error number in the property `X-NSCP-WCAP-ERRNO`. The value is 0 if the command succeeded. In some failure cases more detailed error messages are also included using the properties `X-NSCP-WCAP-ERRNO-MESSAGE` and `X-NSCP-WCAP-ERRNO-DETAILED-MESSAGE`.

Topic in this section:

- [Calendar Server WCAP 7.0 \(WCAPbis\) Error Codes](#)

Calendar Server WCAP 7.0 (WCAPbis) Error Codes

The following table lists error codes returned by WCAP commands.

Error Names, Values, and Meanings

Error Name	Value	Meaning
LOGOUT / UNKNOWN	-1	Successful logout for logout command. Unknown internal server error for other commands.
OK	0	Command successful.
LOGIN_FAILED	1	Login failed, session ID timed out. Invalid session ID
DELETE_EVENTS_BY_ID_FAILED	6	Delete by event id command failed.
SETCALPROPS_FAILED	8	Set calprops command failed.
FETCH_EVENTS_BY_ID_FAILED	9	Fetch by event id command failed.
CREATECALENDAR_FAILED	10	Create calendar command failed.
DELETECALENDAR_FAILED	11	Delete calendar command failed.
STOREEVENTS_FAILED	14	Store command for an event failed.
STORETODOS_FAILED	15	Store command for a todo failed.
DELETE_TODOS_BY_ID_FAILED	16	Delete by todo id command failed.
FETCH_TODOS_BY_ID_FAILED	17	Fetch by todo id command failed.
SEARCH_CALPROPS_FAILED	19	Search calprops command failed.
GET_CALPROPS_FAILED	20	Get calprops command failed.
DELETEEVENTS_BY_RANGE_FAILED	22	Delete events by time range command failed.
DELETETODOS_BY_RANGE_FAILED	23	Delete todos by time range command failed.
CREATECALENDAR_ALREADY_EXISTS_FAILED	25	The command <code>createcalendar.wcap</code> failed because a calendar with that name already exists in the database.
ACCESS_DENIED_TO_CALENDAR	28	The user is denied access to a calendar.
CALENDAR_DOES_NOT_EXIST	29	The requested calendar does not exist in the database.
GET_FREEBUSY_FAILED	39	Get free/busy command failed.

STORE_FAILED_DOUBLE_BOOKED	40	If double booking is not allowed in this calendar, <code>storeevents</code> fails with this error when attempting to store an event in a time slot that was already filled.
WCAP_NO_SUCH_FORMAT	58	Specified output format not recognized.
COMPONENT_NOT_FOUND	59	Returned when a fetch or delete is attempted on a resource that does not exist.
BAD_ARGUMENTS	60	Invalid arguments passed in such as invalid email address, invalid date, and so on.
WCAP_MODIFY_NO_EVENT	62	<code>storeevents.wcap</code> issued with <code>storetype</code> set to 2 (<code>WCAP_STORE_TYPE_MODIFY</code>) and the event doesn't exist.
WCAP_CREATE_EXISTS	63	<code>storeevents.wcap</code> issued with <code>storetype</code> set to 1 (<code>WCAP_STORE_TYPE_CREATE</code>) and the event already exists.
LIST_SUBSCRIBED_FAILED	72	<code>list_subscribed.wcap</code> failed.
SUBSCRIBE_FAILED	73	<code>subscribe.wcap</code> failed.
UNSUBSCRIBE_FAILED	74	<code>unsubscribe.wcap</code> failed.
ANONYMOUS_NOT_ALLOWED	75	Command cannot be executed without a valid sessionid.
BAD_IMPORT_ARGUMENTS	77	Incorrect parameter received by <code>import.wcap</code> .
IMPORT_FAILURE	78	Some events and todos were not imported successfully. (Available starting in Calendar Server 7 Update 2).
ATTACHMENT_NOT_FOUND	87	The attachment requested to be fetched from the server was not found.
BAD_SEARCH_STRING_LENGTH	88	Length of search string for <code>search_calprops</code> is less than required minimum.
SET_ACCOUNTPROPS_FAILED	89	<code>set_accountprops</code> command failed.
GET_ACCOUNTPROPS_FAILED	90	<code>get_accountprops</code> command failed.
GET_FREEBUSY_EXTERNAL_FAILED	91	Unable to retrieve the free/busy info from external service.
STOREEVENTS_WITH_ATTACHMENT_FAILED	92	<code>storeevents.wcap</code> with attachment failed. (Available starting in Calendar Server 7 Update 2.)
GET_ACCOUNTPROPS_NOT_FOUND	93	Account not found.
GET_ACCOUNTPROPS_NO_CALENDAR	94	Calendar for account not found.
FETCH_COMPONENTS_BY_LAST_MOD_INVALID_SYNC_TOKEN_FAILED	99	Invalid sync token.
VIRUS_DETECTED	100	Attachment rejected due to virus detected by virus scanning. (Available starting in Calendar Server 7 Update 2.)
VIRUS_DETECTION_SERVICE_FAILURE	101	Attachment rejected due to virus scanning service being unavailable. (Available starting in Calendar Server 7 Update 2.)

Fetching Component Data Using Calendar Server WCAP 7.0 (WCAPbis)

The `component-type` parameter directs WCAP to return either only events, only todos, or both events and todos. The keyword arguments, respectively, are: `event`, `todo`, or `all`. The parameter is not required. Its default is `all`, returning both events and todos.

This parameter can be used with the `fetchcomponents_by_range` and `fetchcomponents_by_lastmod` commands.

Fetching Recurrence Data Using Calendar Server WCAP 7.0 (WCAPbis)

The `recurring` parameter specifies whether to return recurring events and todos as individual instances or in a master plus exceptions format for any fetch command. The default behavior that is equivalent to setting `recurring` to 0 is to return in expanded form for `fetchcomponents_by_range` and `store` commands. Start and end dates are required for fetching in the expanded form. This is provided by `dtstart` and `dtend` in the `fetchcomponents_by_range` command and `expandstart` and `expandend` for a `store` command that passes in the `fetch` parameter too. For the `fetch_by_id` commands expanded form is the default only if a set of `rids` are provided.

The `compressed` parameter allows you to retrieve the `RRULE` and `EXRULE` properties when in expanded mode. The parameter defaults (`compressed=0`) to the compressed format, which returns data without the `RRULE` and `EXRULE` properties. To receive all the recurrence data back use `compressed=1`. This parameter is valid only when used in conjunction with the expanded mode (`recurring=0`). This parameter is used by the `fetchcomponents_by_range` command, the `fetchevents_by_id` and `fetchtodos_by_id` commands, and the `store*` commands.

Free/busy Information Handling in Calendar Server WCAP 7.0 (WCAPbis)

Free/busy information for a user is calculated by taking into account all `opaque` events in all the user's calendars that are marked for inclusion in the free/busy calculation. A calendar can be included in the calculation list by setting its transparency value using the `fbinclude` parameter in the `set_calprops` command. Individual event transparency can be controlled by the `transparent` parameter in the `storeevents` command. Default value for the `transparent` parameter is 0, which indicates an opaque event included in free/busy calculation.

Whether another user can fetch the free/busy information using the `get_freebusy` command also depends on whether the user has been granted the scheduling free/busy permissions.

The `get_freebusy` command returns the busy data only. The rest of the time slots are presumed to be free.

Topic in this section:

- [Upfront Free/busy Check for Control of Doublebooking and Booking Window During Scheduling](#)

Upfront Free/busy Check for Control of Doublebooking and Booking Window During Scheduling

A scheduling attempt requested for an account that has the attendance flag set to "decline on conflict" (the attendance flag is set either by a `set_accountsprops.wcap` command or `davadmin account` command), triggers Calendar Server to perform a special free/busy check. This check happens as part of the scheduling process for both CalDAV and WCAP clients. Because scheduling is an asynchronous process, the event organizers are made aware of an error only after they have made the booking. However, for clients that use the WCAP protocol, the same check is performed upfront if the scheduled attendee is a resource. This enables the organizer to get an immediate error if the event request results in a conflict for the resource.

Output Format Used by Calendar Server WCAP 7.0 (WCAPbis)

WCAP commands can request the output format in three content types: `text/calendar`, `text/json`, and `text/xml`.

To change the output format, set `fmt-out` to the target value. If `fmt-out` is not specified, the default

format of `text/calendar` is returned.

Recurring Components in Calendar Server WCAP 7.0 (WCAPbis)

Topics in this section:

- [Calendar Server WCAP 7.0 \(WCAPbis\) Recurrence Overview](#)
- [Calendar Server WCAP 7.0 \(WCAPbis\) Creating and Modifying Recurring Components](#)
- [Calendar Server WCAP 7.0 \(WCAPbis\) Deleting Recurring Components](#)
- [Calendar Server WCAP 7.0 \(WCAPbis\) Fetching Recurring Components](#)

Calendar Server WCAP 7.0 (WCAPbis) Recurrence Overview

Recurrence handling occurs as follows:

- A recurring series of events or todos has a master entry plus entries for exceptions.
- Changing the `rrules` of a single instance returns an error. When `rrules` are modified for a recurring series, the whole series is deleted and recreated.
- Changing `dtstart` of a recurring series entry causes the whole series to be recreated with the new `dtstart` thereby losing all exceptions.
- Inserting a `rid` that was not part of the original rule is not supported.
- Multiple `rrules` for any component are not supported.

Calendar Server WCAP 7.0 (WCAPbis) Creating and Modifying Recurring Components

The following parameters are used with the `storeevents` and `storetodos` commands to create and modify recurring components:

- `rules` - Recurrence-rule string for recurring events.
- `rid` - RFC5545 Date-Time String giving the recurrence ID of an event. If this parameter is not set when trying to modify a component, the whole series is modified.
- `excludedtstart`-- An integer specifying whether or not to include the `dtstart` date in a recurring series if the date does not follow the `rrule`.

Topics in this section:

- [rules](#)
- [rid](#)
- [excludedtstart](#)

rules

The `rrules` parameter takes a semicolon-separated list of recurrence rule sub-parameter strings. Each string represents a part of the recurrence rule for the event. Many sub-parameters are possible for recurrence rules. (See [RFC 5545](#) for a complete description of the syntax.)

Three example sub-parameters used by Calendar Server for specifying recurrence are `FREQ`, `COUNT` and `UNTIL`:

- The `FREQ` parameter in a rule defines the periodicity of the event, and has the following possible values:
- [FREQ Parameter Values*](#)

Parameter	Description
DAILY	The event recurs daily.
WEEKLY	The event recurs weekly.
MONTHLY	The event recurs monthly.
YEARLY	The event recurs yearly.

- The `COUNT` parameter in a rule defines how many times the meeting repeats.
- The `UNTIL` parameter in a rule specifies using an end date as opposed to using the `count` to limit the number of instances created.

In the event that neither the `COUNT` nor the `UNTIL` parameter are specified, the series is considered a never ending series.

The following example shows a `rrules` parameter that specifies the event is to occur daily for 10 instances (`COUNT=10;FREQ=DAILY`):

```
rrules="COUNT%3D10%3BFREQ%3DDAILY"
```

The following example URL passes the example `rrules` parameter:

```
http://<calendarserver>:<port>/wcap/storeevents.wcap
?id=<sessionid>
&calid=jdoe
&uid=333
&dtstart=20020301T112233Z
&rrules="COUNT%3D10%3BFREQ%3DDAILY"
&dtend=20020301T112233
&summary=uuuu
```

rid

This parameter specifies a unique recurrence date of an event or todo. Use `rid` parameter to specify the instance of a recurring event or todo to be modified.

For example:

```
http://<calendarserver>:<port>/wcap/storeevents.wcap
?id=<sessionid>
&calid=jdoe
&uid=333
&dtstart=20020301T112233Z
&rid=20020331T112233Z
&dtend=20020301T112233
&summary=uuuu&mod=1
```

excludedtstart

When creating a recurring series according to the `rrule`, this integer specifies whether to include the `dtstart` date if the date does not follow the `rrules`. For example, if on a Monday, you were creating a recurring series of meetings that were to be held every Wednesday, the `dtstart` would be Monday, but that does not fit the set of dates (all Wednesdays) generated using the `rrules`. Therefore the server must decide whether to include the `dtstart` date or not based on the value of `excludedtstart`.

A value of 0 indicates the `dtstart` date is included in the recurring series and a value of 1 indicates the

`dtstart` date is not included in the recurring series. The default is 0.

Calendar Server WCAP 7.0 (WCAPbis) Deleting Recurring Components

When you delete a recurring component, specify the recurrence ID and whether to delete the recurrences as well as the original event or todo.

Use the `mod` parameter to select which occurrences to delete:

mod Parameter Values

Value	Option
1	Delete or modify this instance only.
2	Delete specified instance and all future instances.
3	Delete specified instance and all prior instances.
4	Delete or modify all instances.

Examples Using `deleteevents_by_id`

To delete just the single instance of the event, the `mod` parameter should be set to 1. For example, this URL would delete just the event that occurs on the date March 1, 2002 11:22:33 AM GMT.

```
http://<calendarserver>:<port>/wcap/deleteevents_by_id.wcap
?id=<sessionid>
&calid=jdoe
&uid=001
&rid=20020301T112233Z
&mod=1
```

To delete all instances of the event, the `mod` parameter should be set to 4. For example, this URL would delete ALL instances of the event (`uid 001`).

```
http://<calendarserver>:<port>/wcap/deleteevents_by_id.wcap
?id=<sessionid>
&calid=jdoe
&uid=001
&mod=4
```

Calendar Server WCAP 7.0 (WCAPbis) Fetching Recurring Components

The following parameters are found in the `fetchcomponents_by_*` commands, and the `fetchevents_by_id` and `fetchtodos_by_id` commands:

- `compressed`-- A boolean specifying whether to return all of the recurring entry's data, or to exclude the following parameters: `rrules`, `rdates`, `exrules`, `exdates`.
- `recurring`-- A boolean parameter specifying whether or not to return all components in compressed form (master entry and exceptions).

Calendar Server WCAP 7.0 (WCAPbis) Time Zones

Calendar Server supports almost all known time zones. The time zones accepted by the WCAP commands are restricted to those recognized by Convergence. WCAP time zones and its aliases are

listed in the file `timezoneids.txt` in the Calendar Server configuration directory.

Zulu time corresponds to Greenwich Mean Time (GMT) or Coordinated Universal Time (UTC).

WCAP converts the time values to the appropriate time zone settings on input and output depending upon the value of the `tzid` and `tzidout` parameters. Starting with **Calendar Server 7 Update 2 Patch 5**, the default for `tzid` is Zulu.

The `tzid` parameter is used for date and time strings passed in with the WCAP command, that is, values of parameters such as `dtstart`, `dtend`, and `rid`, which are not provided in Zulu time. If the `tzid` parameter is not passed in, the server's default time zone is assumed.

For commands that return events and todos, the data is returned in Zulu time, unless the `tzidout` parameter is passed in. In this case the Zulu time is translated into the time zone specified in the `tzidout` parameter. A special value of `X-S1CS-TZNATIVE` for `tzidout` outputs date strings in the time zone they were originally created in.

For example, if the `fetch_components_by_range` command specifies a date range of `20020506T100000` to `20020507T100000`, with `tzid=America/Los_Angeles`, WCAP translates that to Zulu time for database lookup. If the `tzidout` parameter was also passed in (for our example, `tzidout=America/New_York`), then the resulting output is translated to that time zone and returned. If the `tzidout` parameter is missing, the component data is returned in Zulu time.

The `tzidout` parameter can be used with the `storeevents` and `storetodos` command when the `fetch` parameter is set to 1 (`fetch=1`).

The following commands use both the `tzid` and `tzidout` parameters:

- `fetchcomponents_by_range.wcap`
- `fetchevents_by_id.wcap`
- `fetchtodos_by_id.wcap`
- `storeevents.wcap`
- `storetodos.wcap`

In addition, the following commands use the `tzid` parameter (but not the `tzidout` parameter):

- `deleteevents_by_id.wcap`
- `deletetodos_by_id.wcap`
- `get_freebusy.wcap`
- `set_calprops.wcap`
- `createcalendar.wcap`
- `deleteevents_by_range.wcap`
- `deletetodos_by_range.wcap`

The following command uses `tzidout` only:

- `fetchcomponents_by_lastmod.wcap`

Updating Parameter Values in Calendar Server WCAP 7.0 (WCAPbis)

Two commands, `storeevents` and `storetodos`, allow you to update (replace, append, or delete) parameter values. When updating current values for a component, you can either replace the current values with the new ones being passed in, append the new values to the current values, or pass in empty parameter values to delete the parameter.

The ability to append parameter values applies only to parameters that can accommodate multiple values (that is, parameters that use semicolon-separated values, such as the `attendees` parameter). The default is to append (`replace=0`) the new values to the current values. If you want to replace the

current values with the new values being passed in, include the `replace` parameter in the command, with the value set to 1 (`replace=1`). If you do not include the `replace` parameter in the command, the system assumes the default setting (`replace=0`) and appends the new values to the old values. Exceptions are the recurrence and alarm parameters that can only be replaced, not appended though their value is a semicolon separated string. Specifically, the parameters are: `rrules` and `alarms`.

X-Tokens Used by Calendar Server WCAP 7.0 (WCAPbis)

The following table shows the X-tokens used by Calendar Server.

X-Tokens Returned by WCAP Commands

Token Name	Type	WCAP Command	Description
X-NSCP-CALPROPS-ACCESS-CONTROL-ENTRY	string	get_calprops & get_accountprops commands	Access control String
X-NSCP-CALPROPS-DESCRIPTION	string	get_calprops commands	Calendar description
X-NSCP-CALPROPS-NAME	string	get_calprops commands	Calendar display name
X-NSCP-CALPROPS-PRIMARY-OWNER	string	all fetch commands	Primary Owner of the Calendar
X-NSCP-CALPROPS-RELATIVE-CALID	string	all fetch/create/delete commands	Calendar identifier
X-NSCP-CALPROPS-TZID	string	all fetch commands	Time Zone identifier
X-NSCP-WCAP-CALENDAR-ID	string	login command	Default calendar id
X-NSCP-WCAP-ERRNO	integer	all	Error number
X-NSCP-WCAP-ERRNO-MESSAGE	String	all	Error Message
X-NSCP-WCAP-ERRNO-DETAILED-MESSAGE	String	all	Detailed error message
X-NSCP-WCAP-SESSION-ID	string	login, check_id	Session ID
X-NSCP-WCAP-USER-ID	string	login, list	Logged in user id
X-NSCP-WCAPVERSION	string	all	WCAP protocol version. Currently 7.0.0
X-S1CS-ATTACH-ID	string	store command	attachment ID
X-S1CS-ATTENDANCE-FLAG	integer	get_accountprops	A flag that controls the behavior of an invitation.
X-S1CS-CALPROPS-ALLOW-DOUBLEBOOKING	string	get_calprops set_calprops	Doublebooking setting for the calendar
X-S1CS-CALPROPS-COMMON-NAME	string	get_calprops	Name of Calendar owner
X-S1CS-CALPROPS-FB-INCLUDE	integer	get_calprops	Freebusy inclusion of calendar
X-S1CS-CALPROPS-OWNED-CALENDAR	string	list	ID of calendars owned by specified user
X-S1CS-CALPROPS-SUBSCRIBED-CALENDAR	string	list_subscribed	ID of calendars specified user is subscribed to
X-S1CS-EMAIL	string	all fetch commands	Email address associated with calendar
X-S1CS-FILENAME	string	fetch	attachment filename
X-S1CS-NOTIF-EMAIL-ENABLED	integer	get_accountprops	Enable email notification flag.
X-S1CS-NOTIF-EMAIL-RECIPIENTS	string	get_accountprops	Recipients of email notifications.
X-S1CS-RECURRENCE-COUNT	integer	all fetch commands	rrule recurrence count
X-S1CS-RECURRENCE-UNTIL	string	all fetch commands	rrule recurrence until
X-S1CS-RESOURCE-OWNER	string	get_accountprops	Email address of the resource owner.
X-S1CS-TZID-ALIAS	string	get_all_timezones command	timezone alias

WCAP 7.0 (WCAPbis) Calendar Server Alarms

WCAP 7.0 (WCAPbis) enables you to configure multiple alarms by using a single alarms parameter that takes multiple VALARMS information in a semicolon separated string value, that is, `alarms=alarm1;alarm2` and so on.

Each alarm value has multiple properties separated by a newline (CRLF). Each value is represented as `PROPERTY_NAME:PROPERTY_VALUE%0D%0APROPERTY_NAME:PROPERTY_VALUE` and so on.

PROPERTY_NAME can contain PARAMETERS, which are separated by the caret character and represented by the following string:

```
^PARAM_NAME=PARAM_VALUE^PARAM_NAME=PARAM_VALUE
```

A PROPERTY can be any valid VALARM property as defined in the iCal standard or X-Properties. The ACTION and TRIGGER properties MUST be present for the alarm to have any effect. An "EMAIL" alarm must include the following properties:

- "DESCRIPTION" property: Contains the text to be used as the message body
- "SUMMARY" property: Contains the text to be used as the message subject
- One or more "ATTENDEE" properties: Contains the address of attendees to receive the message.

The ATTENDEE address value can be an email address represented by `mailto:valid_email_address` or an SMS address represented by `sms:valid_sms_address`.

For more details on alarm properties see <http://tools.ietf.org/html/rfc5545#section-3.6.6>.

Starting with **version 7.0.4.14.0**, Calendar Server supports the Alarm-Agent Property. This property specifies whether a client, server, both client and server, or none, is responsible for processing an alarm when it is triggered. This is in accordance with the [Extended VALARM draft](#).

Example

```
alarms=TRIGGER:-PT30M%0D%0AREPEAT:2%0D%0ADURATION:PT15M%0D%0AACTION:DISPLAY
meeting with executive\nteam at 8:30 AM EST;TRIGGER^VALUE=DATE-
TIME:19970317T133000Z%0D%0AREPEAT:4%0D%0ADURATION:PT15M%0D%0AATTACH^FMPTYPE
SEND AGENDA FOR WEEKLY STAFF
MEETING\; BY MAIL%0D%0ADESCRIPTION:A draft agenda needs to be sent out
to the attendees to the
weekly managers meeting (MGR-LIST). \nAttached is a pointer to the
document template for the
agenda file%0D%0AACTION:EMAIL
```

Filter Parameter in WCAP 7.0 (WCAPbis) Fetch

See [Filter Parameter](#).

Chapter 3. WCAP Design Changes Between Oracle Communications Calendar Server and Sun Java System Calendar Server

WCAP Design Changes Between Oracle Communications Calendar Server and Sun Java System Calendar Server



This page contains information for Calendar Server 7.0.4.15.0 and will not be updated in the future. For documentation beginning with Calendar Server 7.0.5.17.0, see the Oracle Technology Network site at:

<http://www.oracle.com/technetwork/documentation/oracle-communications-185806.html>

This information describes design changes in the Web Calendar Access Protocol (WCAP) between Oracle Communications Calendar Server and Sun Java System Calendar Server.

Topics:

- Overview of Differences
- calid Format
- Access Control and WCAP ACL Parameter
- Time Zones File
- Alarms Parameters
- Filter Parameter
- fetchbylastmod Command
- search_calprops Command
- org* Parameters for storeevents and storetodos Commands
- Error Codes
- LDAP Schema Changes

Overview of Differences

The major differences in WCAP design changes between Calendar Server 7 and Calendar Server 6 include the following:

- Not all Calendar Server 6 WCAP commands are supported by Calendar Server 7 WCAPbis. Even for supported commands, not all parameters are supported.
- The `calid` format, `fetch_by_lastmod` command, `acl` parameter, `filter` parameter, and `alarms` parameter have changed.
- The XML tags used by Calendar Server 7 for XML output format are different from that of Calendar Server 6.
- The `text/json` format was supported (and used by Convergence) in Calendar Server 6.3, with patch 121657-24, but was never documented. Beginning with Calendar Server 7, it is officially

supported and documented.

calid Format

Calendar Server 6 WCAP had specific restrictions on `calendarid`. In Calendar Server 7, `calid` is just part of the `CalendarCollection` URI. This is not constructed by WCAP clients. In `createcalendar`, the server constructs the `calid` for a given calendar name. As a result, `createcalendar` no longer accepts the `calid` parameter. Instead, it has the `name` parameter as a required parameter. The `calid` itself is returned in a `create`, `login`, or `list` commands' response, so clients can use it for commands like `deletecalendar`, `get_calprops`, `set_calprops`, and so on. A new X-prop `X-S1CS-DEFAULTCALENDAR` is returned on `get_calprops` of the default calendar.

Access Control and WCAP ACL Parameter

The getting and setting of ACLs has been simplified in Calendar Server 7. The scheduling and free/busy ACLs for a user and read/write ACLs for a calendar are completely separated. The `acl` parameter for `set_calprops` or `create_calendar` commands is still used to set read/write/manage acls of a particular calendar. Access control list still consists of a semicolon separated list of ACEs. Each ACE consists of `user/group-identifier:rights-token`. The rights tokens can be one of the following:

- n: none
- r: read
- w: read+write+delete
- a: read+write+delete+manage

Two new commands, `get_accountprops` and `set_accountprops`, have been introduced to get and set account properties, including scheduling ACLs. Scheduling ACLs are also set as a semicolon separated list of ACEs, where each ACE is a `user/group-identifier:rights-token`. The rights-token can be:

- f: free/busy
- s: free/busy and invite
- m: all scheduling rights including manage

@ is a special `user/group-identifier` that can be used for all users. Whether all users includes anonymous users is determined by a server configuration option.

Rights not granted are denied by default. In an ACL string, more specific rights override other rights. That is, rights granted to a specific user are more specific than rights granted to a user as member of a group. Rights granted as part of "all" users setting are considered least specific. If a user is a member of multiple groups, the highest level of access granted individually by any one of the groups is the access level of the user. Levels of nesting within each group are not taken into consideration. A default ACL for all calendar collections are defined by the configuration option `davcore.acl.defaultcalendaracl`.

The access-control string is returned on a get request only if the user has manage access to the ACLs. If not, related information is returned in the X-PROP `X-S1CS-MYRIGHTS`. The value for this property is computed from the ACL string to return the access rights pertaining to the logged in user only. Value tokens are the same as those used in calendar and scheduling ACEs.

Time Zones File

The `get_all_timezones` command still returns the same list of time zones returned by Calendar Server 6. But the `VTIMEZONE` values themselves are not an exact match with those in Calendar Server 6. The server maintains a list of time zone IDs and aliases to be used when generating this information in the `timezoneids.txt` file.

When events and tasks are stored, the `datetime` components are no longer converted to Zulu for storing. Instead the passed-in `tzid` value is tagged to the `datetime`, if not there already, and the corresponding `VTIMEZONE` is added to the resource, while storing. On retrieval, the timezone information stored with the resource is used to convert all `datetime` values to the timezone requested by `tzidout` parameter or Zulu time.

Alarms Parameters

To support multiple alarms, all the Calendar Server 6 `alarm` parameters were replaced by a single `alarms` parameter that takes a compound value.

```
alarms=VALUE;VALUE
```

where `VALUE` will have multiple properties separated by CRLF. For example:

```
PROPERTY_NAME:PROPERTY_VALUE%0D%0APROPERTY_NAME:PROPERTY_VALUE and so on.
```

`PROPERTY_NAME` might contain `PARAMETERS`, which are separated by carat and represented by `^PARAM_NAME=PARAM_VALUE^PARAM_NAME=PARAM_VALUE`.

Newlines in value are represented by `/n`. Semicolons in value are escaped by using `\;` characters.

Example:

```
alarms=TRIGGER:-PT30M%0D%0AREPEAT:2%0D%0ADURATION:PT15M%0D%0AACTION:DISPLAY
meeting with executive\nnteam at 8:30 AM EST;
TRIGGER^VALUE=DATE-TIME:19970317T133000Z%0D%0AREPEAT:4%0D%0ADURATION:PT15M%
SEND AGENDA FOR WEEKLY STAFF
MEETING%0D%0ADESCRIPTION:A draft agenda needs to be sent out to the
attendees to the weekly managers meeting (MGR-LIST). \nAttached is a
pointer to
the document template for the agenda file%0D%0AACTION:EMAIL
```

Clients return all the alarms fetched plus the ones they want to add on in a `Store` command. To delete all alarms, the `alarms` parameter with empty value is used. To delete a particular alarm, just the remaining list of the alarms are stored.

Filter Parameter

Calendar Server 6 did not offer the complicated ANDed and ORed filters required by some customers. To support the complicated filters, the `filter param` value in `fetch` is being modified to use a XPATH like syntax. List of attributes that can be searched on will be `ATTENDEE`, `ORGANIZER`, `SUMMARY`, `DESCRIPTION`, `LOCATION`, `CLASS`, `CATEGORIES` just like in Calendar Server 6.

Searching in `ALL` will mean a search in the whole Resource `CONTENT`. No attachment searching.

Sample filter strings:


```
Organizer is ciny, and category is 1009 or 1000 - ((ORGANIZER='ciny')
and ((CATEGORIES='1009') or (CATEGORIES='1000')))
Summary contains new - (contains(SUMMARY, 'new'))
Organizer is ciny and location starts with Andro - ((ORGANIZER='ciny)
and (starts-with(LOCATION, 'Andro'))
Attendee is ciny and partstat needs-action -
(ATTENDEE[@PARTSTAT='NEEDS-ACTION']='ciny')
Attendee contains ciny and partstat is needs-action -
(contains(ATTENDEE[@PARTSTAT='NEEDS-ACTION'], 'ciny'))
```

fetchbylastmod Command

This command was used by Connector for Outlook in conjunction with `gettime` and `fetch_deleted`. To do it more accurately and efficiently, `fetchcomponents_by_lastmod` in Calendar Server 7 has been written to provide the same information in one command. A sync token (X-S1CS-SYNCTOKEN) is also returned to be used for the next sync. The date parameters in `fetchcomponents_by_lastmod` have been removed in favor of the `synctoken` param. If `synctoken` is null, a full sync is done. Deleted resources are returned in restricted `VEVENT` or `VTODOS` components with deleted status indicated in the `X-S1CS-MODSTATUS` property. (In this instance, the `VEVENT` component is modified to be just a container that returns status.)

search_calprops Command

This command no longer directly searches for calendars. It searches for users and groups in LDAP that match the search string and then returns the calendars of those entries. As a result, the `calid`, `name`, `primaryOwner`, and `searchOpts` parameters have been deprecated. The LDAP attributes filter used is configured server-wide. A new error code has been introduced to indicate invalid search string (88). A new X-PROP was introduced to indicate partial results due to search limit exceeding:
X-S1CS-PARTIAL-RESULT-COUNT

org* Parameters for storeevents and storetodos Commands

Calendar Server 6 WCAP supports the `orgCalid`, `orgEmail`, `orgCN`, and `orgUID` parameters. Connector for Microsoft Outlook mainly uses these parameters to set the organizer information when a delegatee creates events and tasks on behalf of someone else or to store an invitation from an external organizer. Starting with version 7 Update 3 Patch 9, Calendar Server supports `orgEmail` and `orgCN` parameters, which are required to support storing of external invitations from Connector for Microsoft Outlook. Calendar Server 7 does not support `orgCalid` and `orgUId` parameters because they are redundant. Additionally, the server fills in the correct organizer information as long as the client sets the correct calendar information by using the `calid` parameter. That is, if a delegatee is creating on behalf of someone else, the client needs to set the `calid` value to that of the person on whose behalf the event or task is being created.

Error Codes

Calendar Server does not use all of the older WCAP error codes. Calendar Server 7 includes some new error codes. Failed login and badly constructed commands return an HTTP error and not a WCAP error.

LDAP Schema Changes

Calendar Server 7 works with the Calendar Server 6 LDAP schema with some exceptions. See [LDAP](#)

Schema Changes for Oracle Communications Calendar Server 7.