

**Oracle Functional Testing Advanced
Pack for Oracle Utilities
Reference Guide for Oracle Utilities Mobile
Workforce Management and Oracle Real-Time
Scheduler**

Release 5.0.0

E67846-01

October 2015

Oracle Functional Testing Advanced Pack for Oracle Utilities Reference Guide for Oracle Utilities Mobile Workforce Management and Oracle Real-Time Scheduler, Release 5.0.0

E67846-01

Copyright © 2015 Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are “commercial computer software” pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Contents

Preface	i
Audience	i
Related Documents	i
Notational Conventions	ii
Chapter 1	
Component Reference	1-1
Overview	1-1
Components	1-2
Chapter 2	
Function Library Reference	2-1
OUMWMLIB.....	2-1
OUMWMCONNECTEDMCPLIB.....	2-4
OUMWMMCPLIB	2-8
Chapter 3	
Sample Work Flows	3-1
Sample Flows.....	3-1
Non-MDT Flow.....	3-1
MDT Flow	3-2
M2 Non-MDT Flow.....	3-3
MDT Flow Using NextGen MCP.....	3-3
Executing Sample Flows.....	3-4
Pre-requisites.....	3-4
Setting Up Sample Flows	3-4
Appendix A	
Inbound Web Services	A-1
List of Inbound Web Services	A-1

Preface

This guide describes the Oracle Utilities Mobile Workforce Management (MWM) v2.2.0.3 and Oracle Real-Time Scheduler (ORS) v2.2.0.3 components and the function libraries used to create those components in Oracle Functional Testing Advanced Pack for Oracle Utilities (OFTAPOU) v5.0.0. These components are used to build test flows in Oracle Flow Builder (OFB).

This preface includes the following sections:

- [Audience](#)
- [Related Documents](#)
- [Notational Conventions](#)

Audience

This guide is intended for QA/Test Engineers and Automation Developers to understand the various components and libraries available for them to automate the business test flows for Oracle Utilities Mobile Workforce Management using Oracle Functional Testing Advanced Pack for Oracle Utilities (OFTAPOU) for Oracle Utilities Mobile Workforce Management and Oracle Real-Time Scheduler.

Related Documents

For more information, see the following documents:

- *Oracle Functional Testing Advanced Pack for Oracle Utilities Release Notes*
- *Oracle Functional Testing Advanced Pack for Oracle Utilities Installation and Administration Guide*
- *Oracle Functional Testing Advanced Pack for Oracle Utilities User's Guide*

See also:

- Oracle Utilities Mobile Workforce Management Documentation Library
- Oracle Real-Time Scheduler Documentation Library

Notational Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

Chapter 1

Component Reference

This chapter lists the Oracle Utilities Mobile Workforce Management starter components available to create flows in Oracle Flow Builder for testing the Oracle Utilities Mobile Workforce Management and Oracle Real-Time Scheduler applications.

The chapter includes the following sections:

- [Overview](#)
- [Components](#)

Overview

Oracle Functional Testing Advanced Pack for Oracle Utilities for Oracle Utilities Mobile Workforce Management and Oracle Real-Time Scheduler is a test starter pack built on top of Oracle Functional Testing Advanced Pack for Oracle Utilities that generates test automation scripts using Oracle Flow Builder.

Oracle Functional Testing Advanced Pack for Oracle Utilities for Oracle Utilities Mobile Workforce Management and Oracle Real-Time Scheduler contains out-of-the-box product-specific components used to build new test flows in Oracle Flow Builder to test the Oracle Utilities Mobile Workforce Management and Oracle Real-Time Scheduler applications. These out-of-the-box components correspond to specific business entities, such as business objects, service scripts, or business services used for interfacing with the application. Users can use these components as available or can extend them. Users can also create new components to be used to create flows. This starter pack also contains a set of function libraries that can be used for creating custom components.

Note: See [Chapter 2: Function Library Reference](#) for detailed information about using these function libraries.

Consider this pack to be a starter kit which can be expanded and built upon. A few sample flows are included as an example.

Note: See the *Oracle Functional Testing Advanced Pack for Oracle Utilities User's Guide* for information about creating components and flows.

The components are categorized under the following functional areas:

- Administration Data
- Connected MCP Processing
- Contractor Portal
- Resource Management
- Scheduling

- Service Management
- Next Generation MCP Processing

Components

The following table lists the starter components available in Oracle Utilities Mobile Workforce Management.

Pre-requisites: The Inbound Web Service service using the respective business object should be available in the application.

Additional Notes: Failure while creating, reading, or updating the component is logged in the test execution report, thus facilitating debugging/analysis of the problem.

Component	Functional Area	Description
M1-ActivityType	Administration Data	Used to create, read, or update M1 Activity Type via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-ActivityType business object.
M1-AlertType	Administration Data	Used to create, read, or update an M1 Alert Type via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-AlertType business object.
M1-AppointmentBookingGroup	Administration Data	Used to create, read, or update an M1 Appointment Booking Group via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-AppointmentBookingGroup business object.
M1-BreakTaskType	Administration Data	Used to create, read, or update an M1 Break Task Type via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-BreakTaskType business object.
M1-CapacityType	Administration Data	Used to create, read, or update an M1 Capacity Type via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-CapacityType business object.

Component	Functional Area	Description
M1-ComplexActivityType	Administration Data	Used to create, read, or update an M1 Complex Activity Type via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-ComplexActivityType business object.
M1-CrewHierarchy	Administration Data	Used to create, read, or update an M1-CrewHierarchy via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-CrewHierarchy business object.
M1-ContractorType	Administration Data	Used to create, read, or update an M1 Contractor Type via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-ContractorType business object.
M1-CrewShiftType	Administration Data	Used to create, read, or update an M1 Crew Shift Type via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-CrewShiftType business object.
M1-CrewType	Administration Data	Used to create, read, or update an M1 Crew Type via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-CrewType business object.
M1-Deployment	Administration Data	Used to activate or deactivate a deployment via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-Deployment business object.
M1-DeploymentPart	Administration Data	Used to create, read, or update a deployment part via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-DeploymentPart business object.

Component	Functional Area	Description
M1-DeploymentType	Administration Data	Used to create, read, or update a deployment type via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-DeploymentType business object.
M1-Depot	Administration Data	Used to create, read, or update a depot via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-Depot business object.
M1-DepotProfile	Administration Data	Used to create, read, or update a depot profile via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-DepotProfile business object.
M1-DepotTaskType	Administration Data	Used to create, read, or update a depot task type via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-DepotTaskType business object.
M1-DispatchArea	Administration Data	Used to create, read, or update an M1 Dispatch Area via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-DispatchArea business object.
M1-DispatcherType	Administration Data	Used to create, read, or update an M1 Dispatcher Type via a Web service. the CRUD operations can be performed through these components against the M1-DispatcherType business object.
M1-Equipment	Administration Data	Used to create, read, or update an M1 Equipment via a Web service. the CRUD operations can be performed through these components against the M1-Equipment business object.

Component	Functional Area	Description
M1-GeographicArea	Administration Data	Used to create, read, or update an M1 Geographic Area via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-GeographicArea business object.
M1-GlobalConfig	Administration Data	Used to create, read, or update M1 Global Configurations via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-GlobalConfigurations business object.
M1-KPI	Administration Data	Used to create, read, or update an M1 KPI via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-KPI business object.
M1-Location	Administration Data	Used to create, read, or update an M1 Location via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-Location business object.
M1-MobileDeviceTerminal	Administration Data	Used to create, read, or update an M1 Mobile Device Terminal via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-MobileDeviceTerminal business object.
M1-MobileWorkerType	Administration Data	Used to create, read, or update an M1 Mobile Worker Type via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-MobileWorkerType business object.
M1-MobileDeviceTerminalType	Administration Data	Used to create, read, or update an M1 MobileDeviceTerminalType via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-MobileDeviceTerminalType business object.

Component	Functional Area	Description
M1-NPTTaskType	Administration Data	Used to create, read, or update an M1 Non Prd Task Type via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-NonPrdTaskType business object.
M1-POUTaskType	Administration Data	Used to create, read, or update an M1 POU Task Type via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-POUTaskType business object.
M1-POUType	Administration Data	Used to create, read, or update an M1 POU Type via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-POUType business object.
M1-PriorityProfile	Administration Data	Used to create, read, or update an M1 Priority Profile via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-PriorityProfile business object.
M1-ProcedureType	Administration Data	Used to create, read, or update an M1 Procedure Type via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-ProcedureType business object.
M1-RemarkType	Administration Data	Used to create, read, or update an M1 Remark Type via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-RemarkType business object.
M1-ResTimesheetType	Administration Data	Used to create, read, or update an M1 Resource TimesheetType. via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-Resource TimesheetType business object.

Component	Functional Area	Description
M1-Scheduler	Administration Data	Used to create, read, or update an M1 Scheduler via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-Scheduler business object.
M1-SchedulerArea	Administration Data	Used to create, read, or update an M1 Scheduler Area via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-SchedulerArea business object.
M1-SchedulerConfig	Administration Data	Used to create, read, or update an M1 Scheduler Config via a Web service. the CRUD operations can be performed through these components against the M1-SchedulerConfig business object.
M1-ServiceArea	Administration Data	Used to create, read, or update an M1 Service Area via a Web service. the CRUD operations can be performed through these components against the M1-ServiceArea business object.
M1-ServiceAreaHierarchy	Administration Data	Used to create, read, or update an M1 Service Area Hierarchy via a Web service. the CRUD operations can be performed through these components against the M1-ServiceAreaHierarchy business object.
M1-ServiceClass	Administration Data	Used to create, read, or update an M1 Service Class via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-ServiceClass business object.
M1-ShiftCostProfile	Administration Data	Used to create, read, or update an M1 Shift Cost Profile via a Web service. The CRUD operations can be performed through these components against the M1-ShiftCostProfile business object.

Component	Functional Area	Description
M1-SpeedProfileGeoArea	Administration Data	Used to create, read, or update an M1-SpeedProfileGeoArea via a Web service. The CRUD operations can be performed through these components against the M1-SpeedProfileGeoArea business object.
M1-Skill	Administration Data	Used to create, read, or update an M1 Skill via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-Skill business object.
M1-StatusReason	Administration Data	Used to create, read, or update an M1 Status Reason via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-StatusReason business object.
M1-WorkCalendar	Administration Data	Used to create, read, or update an M1-WorkCalendar via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-WorkCalendar business object.
M1-VehicleType	Administration Data	Used to create, read, or update an M1 Vehicle Type via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-VehicleType business object.
M1-WorkProfile	Administration Data	Used to create, read, or update an M1 Work Profile via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-WorkProfile business object.
M1-WorkerAttribute	Administration Data	Used to create, read, or update an M1 WorkerAttribute via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-WorkerAttribute business object.

Component	Functional Area	Description
M1_BatchExecuteBS	Administration Data	Used to create, read, or update an M1 BatchExecuteBS via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-BatchExecuteBS business object.
M1-Capacity	Contractor Portal	Used to create, read, or update an M1 Capacity via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-Capacity business object.
M1-CapacityTemplate	Contractor Portal	Used to create, read, or update an M1 Capacity Template via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-CapacityTemplate business object.
M1-CapacityWeeklyTemplate	Contractor Portal	Used to create, read, or update an M1-CapacityWeeklyTemplate via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-CapacityWeeklyTemplate business object.
M1-Company	Contractor Portal	Used to create, read, or update an M1 Company via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-Company business object.
M1-Contractor	Contractor Portal	Used to create, read, or update an M1 Contractor via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-Contractor business object.
M1-ContractorEligibility	Contractor Portal	Used to create, read, or update an M1 Contractor Eligibility via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-ContractorEligibility business object.

Component	Functional Area	Description
M1-Alert	Service Management	Used to create, read, or update an M1 General Alert via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-GeneralAlert business object.
M1-BreakTask	Resource Management	Used to create, read, or update an M1 Break Task via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-BreakTask business object.
M1-CommonShiftWeekly Template	Resource Management	Used to create, read, or update an M1 Common Shift Weekly Template via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-CommonShiftWeeklyTemplate business object.
M1-CrewShftCloseOpenAllocate	Resource Management	Used to close or open a shift using M1-CrShfClAl via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-CrShfClAl service script.
M1-CrewShift	Resource Management	Used to create, read, or update an M1 Crew Shift via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-CrewShift business object.
M1-CrewShiftTemplate	Resource Management	Used to create, read, or update an M1 Crew Shift Template via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-CrewShiftTemplate business object.
M1-DeactivateMobileWorker	Resource Management	Used to deactivate an active mobile worker via a Web service. After the creation, the mobile worker can be deactivated. The business object used for this component is M1-MobileWorker.

Component	Functional Area	Description
M1-DeactivateVehicle	Resource Management	Used to deactivate an active vehicle via a Web service. After the creation, the vehicle can be deactivated. The business object used for this component is M1-Vehicle.
M1-DeactivateCrew	Resource Management	Used to deactivate an active crew via a Web service. After the creation, crew can be deactivated. The business object used for this component is M1-Crew.
M1-DeleteResourceLeavePOU	Resource Management	Used for deleting M1 Resource Leave POU
M1-DepotRelatedShift	Resource Management	Used to create, read, or update an M1 Depot Related Shift via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-DepotRelatedShift business object.
M1-DepotSinglePersonCrew	Resource Management	Used to create, read, or update an M1 Depot Single Person Crew via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-DepotSinglePersonCrew business object.
M1-Dispatcher	Resource Management	Used to create, read, or update an M1 Dispatcher via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-Dispatcher business object.
M1-DispatcherShift	Resource Management	Used to create, read, or update an M1 Dispatcher Shift via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-DispatcherShift business object.
M1-ForceLogOffCrewShift	Resource Management	Used to force logging off an MDT crew shift
M1-GetShiftCapabilities	Resource Management	Used to retrieve the capabilities of a crew shift

Component	Functional Area	Description
M1-HazardArea	Resource Management	Used to create, read, or update an M1 Hazard Area via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-HazardArea business object.
M1-MailingList	Resource Management	Used to create, read, or update an M1 Mailing List via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-MailingList business object.
M1-MainMail	Resource Management	Used to create M1 MainMail
M1-MobileWorker	Resource Management	Used to create, read, or update an M1 Mobile Worker via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-MobileWorker business object.
M1-NonProductiveTask	Resource Management	Used to create, read, or update an M1 NonPrdTask via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-NonPrdTask business object.
M1-POUTask	Resource Management	Used to create, read, or update an M1 POU Task via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-POUTask business object.
M1-RealPOU	Resource Management	Used to create, read, or update an M1 Real POU via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-RealPOU business object.
M1-ResourceTimesheet	Resource Management	Used to create, read, or update an M1 Res Time Sheet via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-ResTimesheet business object.

Component	Functional Area	Description
M1-Resourceleave	Resource Management	Used to create, read, or update an M1 Resource Leave via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-ResourceLeave business object.
M1-ShiftWeeklyTemplate	Resource Management	Used to create, read, or update an M1 Shift Weekly Template via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-ShiftWeeklyTemplate business object.
M1-SimpleProcedure	Resource Management	Used to create, read, or update an M1 Simple Procedure via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-SimpleProcedure business object.
M1-SinglePersonCrew	Resource Management	Used to create, read, or update an M1 Single Person Crew via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-SinglePersonCrew business object.
M1-SubscriptionWeeklyTemplate	Resource Management	Used to create, read, or update an M1 Subscription Weekly Template via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-SubscriptionWeeklyTemp business object.
M1-TemplateMail	Resource Management	Used to create, read, or update an M1 Template Mail via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-TemplateMail business object.
M1-TemplatePOU	Resource Management	Used to create, read, or update an M1 Template POU via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-TemplatePOU business object.

Component	Functional Area	Description
M1-Vehicle	Resource Management	Used to create, read, or update an M1 Vehicle via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-Vehicle business object.
M1-VehicleLeaveArea	Resource Management	Used to create, read, or update an M1 Vehicle Leave Area via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-VehicleLeaveArea business object.
M1-getPOUTaskIdForPOUId	Resource Management	Used to retrieve the POU task ID (the task scheduled to a crew shift) for a given real POU ID.
M1-getdeactivateMWId	Resource Management	Used to retrieve the mobile worker ID for the given user whose BO status is 'Active'.
M1-getdeactivateVehicleId	Resource Management	Used to retrieve the vehicle ID for the given user whose BO status is 'Active'.
M1-getdeactivateCrewId	Resource Management	Used to retrieve the crew ID for the given user whose BO status is 'Active'.
M1-AllocateActivityToAShift	Scheduling	Used to manually allocate an activity to a crew shift.
M1-AppointmentBookingRequest	Scheduling	Used to trigger an M1 Appointment Booking Request.
M1-CheckIfActivityIsScheduled	Scheduling	Verifies if an activity is scheduled to a crew shift.
M1-DailySpeedTemplate	Scheduling	Used to create, read, or update an M1 Daily Speed Template via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-DailySpeedTemplate business object.
M1-FixToCrew	Scheduling	Used to fix an activity to be scheduled to a particular crew
M1-SchedulerRegistryRead	Scheduling	Used to retrieve the scheduler registry details for an entity

Component	Functional Area	Description
M1-SpeedProfileTemplate	Scheduling	Used to create, read, or update an M1 Speed Profile Template via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-SpeedProfileTemplate business object.
M1-TaskScheduleDetails	Scheduling	Used for reading an M1 Task Schedule entity.
M1-UnAssignActivity	Scheduling	Used to unassign an activity from the crew shift.
M1-WaitForTime	Scheduling	Used to wait for certain amount of time. The unit of measure is minutes.
M1-Activity	Service Management	Used to create, read, or update an M1 Activity via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-Activity business object.
M1-Assignment	Service Management	Used to create, read, or update an M1 Assignment via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-Assignment business object.
M1-ComplexActivity	Service Management	Used to create, read, or update an M1 Complex Activity via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-ComplexActivity business object.
M1-DeferActivity	Service Management	Used to defer an activity
M1-DepotRelatedActivity	Service Management	Used to create, read, or update an M1 Depot Related Activity via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-DepotRelatedActivity business object.
M1-DepotTask	Service Management	Used to create, read, or update an M1 Depot Task via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-DepotTask business object.

Component	Functional Area	Description
M1-GetAssignmentIdForTaskId	Service Management	Used to retrieve the assignment ID of a dispatched task
M1-GetDepotTaskId	Service Management	Used to retrieve the depot task ID associated to a given depot related or a pre-requisite activity.
M1-GetDeploymentId	Service Management	Used to retrieve the deployment ID for the given deployment type.
M1-OverrideTimeWindow	Service Management	Used to create, read, or update an M1 Override Time Window via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-OverrideTimeWindow business object.
M2-InstallMeterActivity	M2 Activity	Used to create, read, or update an M2 Install Meter Activity via a Web service. After the creation, the CRUD operations can be performed through these components against the M1-InstallMeterActivity business object.
M2-InstallMeterAssignment	M2 Activity	Used to create, read, or update an M2 Install Meter Assignment via a Web service. After creation, the CRUD operations can be performed through these components against the M2-InstallMeterAssignment business object.
M2-BasicItemActivity	M2 Activity	Used to create, read, or update an M2 Basic Item Activity via a Web service. After creation, the CRUD operations can be performed through these components against the M2-BasicItemActivity business object.
M2-BasicItemAssignment	M2 Activity	Used to create, read, or update a basic item assignment via a Web service. After creation, the CRUD operations can be performed through these components against the M2-BasicItemAssignment business object.
M2- ConnectSPActivity	M2 Activity	Used to create, read, or update an M2 Connect Service Point Activity via a Web service. After creation, the CRUD operations can be performed through these components against the M2- ConnectSPActivity business object.

Component	Functional Area	Description
M2-ConnectSPAssignment	M2 Activity	Used to create, read, or update a connect service point assignment via a Web service. After creation, the CRUD operations can be performed through these components against the M2-ConnectSPAAssignment business object.
M2-CutNonPayItemActivity	M2 Activity	Used to create, read, or update an M2 Cut For Non Payment Item Activity via a Web service. After the creation, the CRUD operations can be performed through these components against the M2-CutNonPayItemActivity business object.
M2-CutNonPayItemAssignment	M2 Activity	Used to create, read, or update a cut for non payment item assignment via a Web service. After creation, the CRUD operations can be performed through these components against the M2-CutNonPayItemAssignment business object.
M2-DisconnectMeterActivity	M2 Activity	Used to create, read, or update a disconnect meter activity via a Web service. After the creation, the CRUD operations can be performed through these components against the M2- DisconnectMeterActivity business object.
M2-DisconnectMeterAssignment	M2 Activity	Used to create, read, or update a disconnect meter assignment via a Web service. After creation, the CRUD operations can be performed through these components against the M2- DisconnectMeterAssignment business object.
M2-DisconnectSPActivity	M2 Activity	Used to create, read, or update a disconnect service point activity via a Web service. After the creation, the CRUD operations can be performed through these components against the M2-DisconnectSPActivity business object.

Component	Functional Area	Description
M2-DisconnectSPAssignment	M2 Activity	Used to create, read, or update a disconnect service point assignment via a Web service. After creation, the CRUD operations can be performed through these components against the M2- DisconnectSPAssignment business object.
M2-ExchangeItemActivity	M2 Activity	Used to create, read, or update an exchange item activity via a Web service. After the creation, the CRUD operations can be performed through these components against the M2- ExchangeItemActivity business object.
M2-ExchangeItemAssignment	M2 Activity	Used to create, read, or update an exchange item assignment via a Web service. After creation, the CRUD operations can be performed through these components against the M2- ExchangeItemAssignment business object.
M2-InstallItemActivity	M2 Activity	Used to create, read, or update an install item activity via a Web service. After creation, the CRUD operations can be performed through these components against the M2- InstallItemActivity business object.
M2-InstallItemAssignment	M2 Activity	Used to create, read, or update an install item assignment via a Web service. After creation, the CRUD operations can be performed through these components against the M2-InstallItemAssignment business object.
M2-MeterReadActivity	M2 Activity	Used to create, read, or update a meter read activity via a Web service. After creation, the CRUD operations can be performed through these components against the M2- MeterReadActivity business object.
M2-MeterReadAssignment	M2 Activity	Used to create, read, or update a meter read assignment via a Web service. After creation, the CRUD operations can be performed through these components against the M2-MeterReadAssignment business object.

Component	Functional Area	Description
M2-RemoveItemActivity	M2 Activity	Used to create, read, or update a remove item activity via a Web service. After creation, the CRUD operations can be performed through these components against the M2- RemoveItemActivity business object.
M2-RemoveItemAssignment	M2 Activity	Used to create, read, or update a remove item assignment via a Web service. After creation, the CRUD operations can be performed through these components against the M2-RemoveItemAssignment business object.
M2-RemoveMeterActivity	M2 Activity	Used to create, read, or update a remove meter activity via a Web service. After the creation, the CRUD operations can be performed through these components against the M2- RemoveMeterActivity business object.
M2-RemoveMeterAssignment	M2 Activity	Used to create, read, or update a remove meter assignment via a Web service. After creation, the CRUD operations can be performed through these components against the M2-RemoveMeterAssignment business object.
M2-MaintUtilityActByHost	M2 Activity	Used to create an M2 Activity from an external system
ConnectedMCP_CompleteActivity	Connected MCP Processing	Performs the actions of a field worker for completing an M1 Activity using Connected MCP. Note: To be called only after calling the ConnectedMCP_StartActivity component.
ConnectedMCP_CompleteBreak	Connected MCP Processing	Performs the actions of a field worker for completing an M1 Break Task using Connected MCP. Note: To be called only after calling the ConnectedMCP_StartBreak component.

Component	Functional Area	Description
ConnectedMCP_ CompleteNPT	Connected MCP Processing	<p>Performs the actions of a field worker for completing an M1 Non Productive Task using Connected MCP.</p> <p>Note: To be called only after calling the ConnectedMCP_StartNPT component.</p>
ConnectedMCP_ CompletePOU	Connected MCP Processing	<p>Performs the actions of a field worker for completing an M1 POU task using Connected MCP.</p> <p>Note: To be called only after calling the ConnectedMCP_StartPOU component.</p>
ConnectedMCP_ CompleteShift	Connected MCP Processing	<p>Performs the actions of a field worker for completing a shift using Connected MCP.</p> <p>Note: To be called only after a shift is in 'start' status.</p>
ConnectedMCP_ DispatchedTask	Connected MCP Processing	<p>Performs the actions of a field worker to check if a task has been dispatched using Connected MCP. Then, click it.</p>
ConnectedMCP_ EnrouteActivity	Connected MCP Processing	<p>Performs the actions of a field worker to move the status of a task to 'En-route' using Connected MCP. Then, click it.</p> <p>Note: To be called only after calling the ConnectedMCP_DispatchedTask component.</p>
ConnectedMCP_ EnrouteNPT	Connected MCP Processing	<p>Performs the actions of a field worker to move the status of an NPT task to 'En-route' using Connected MCP. Then, click it.</p> <p>Note: To be called only after calling the ConnectedMCP_DispatchedTask component.</p>
ConnectedMCP_ EnroutePOU	Connected MCP Processing	<p>Performs the actions of a field worker to move the status of an NPT task to 'En-route' using Connected MCP. Then, click it.</p> <p>Note: To be called only after calling the ConnectedMCP_DispatchedTask component.</p>

Component	Functional Area	Description
ConnectedMCP_StartActivity	Connected MCP Processing	<p>Performs the actions of a field worker to move the status of an activity to 'Started' using Connected MCP. Then, click it.</p> <p>Note: To be called only after calling the ConnectedMCP_EnrouteActivity component.</p>
ConnectedMCP_StartBreak	Connected MCP Processing	<p>Performs the actions of a field worker to move the status of a break task to 'Started' using Connected MCP. Then, click it.</p> <p>Note: To be called only after calling the ConnectedMCP_DispatchedTask component.</p>
ConnectedMCP_StartCrewShift	Connected MCP Processing	<p>Performs the actions of a field worker to start a crew shift using Connected MCP. Then, click it.</p>
ConnectedMCP_StartNPT	Connected MCP Processing	<p>Performs the actions of a field worker to move the status of an activity to 'Started' using Connected MCP. Then, click it.</p> <p>Note: To be called only after calling the ConnectedMCP_EnrouteNPT component.</p>
ConnectedMCP_StartPOU	Connected MCP Processing	<p>Performs the actions of a field worker to move the status of a POU to 'Started' using Connected MCP. Then, click it.</p> <p>Note: To be called only after calling the ConnectedMCP_EnroutePOU component.</p>
NextGenMCP_StartShift	NextGenMCP Processing	<p>Performs the actions of a field worker to start a crew shift using NextGen MCP. Then, clicks it.</p>
NextGenMCP_EnrouteActivity	NextGenMCP Processing	<p>Performs the actions of a field worker to move the status of a task to 'En-route' using NextGen MCP. Then, clicks it.</p> <p>Note: To be called only after calling the NextGenMCP_DispatchedTask component.</p>

Component	Functional Area	Description
NextGenMCP_StartActivity	NextGenMCP Processing	<p>Performs the actions of a field worker to move the status of an activity to 'Started' using NextGen MCP. Then, clicks it.</p> <p>Note: To be called only after calling the NextGenMCP _EnrouteActivity component.</p>
NextGenMCP_CompleteActivity	NextGenMCP Processing	<p>Performs the actions of a field worker for completing an M1 Activity using NextGen MCP.</p> <p>Note: To be called only after calling the NextGenMCP _StartActivity component.</p>
NextGenMCP_StartBreak	NextGenMCP Processing	<p>Performs the actions of a field worker to move the status of a break task to 'Started' using NextGen MCP. Then, clicks it.</p> <p>Note: To be called only after calling the NextGenMCP _DispatchedTask component.</p>
NextGenMCP_CompleteBreak	NextGenMCP Processing	<p>Performs the actions of a field worker for completing an M1 Break Task using NextGen MCP.</p> <p>Note: To be called only after calling the NextGenMCP _StartBreak component.</p>
NextGenMCP_EnrouteNPT	NextGenMCP Processing	<p>Performs the actions of a field worker to move the status of an NPT task to 'En-route' using NextGen MCP. Then, clicks it.</p> <p>Note: To be called only after calling the NextGenMCP _DispatchedTask component.</p>
NextGenMCP_StartNPT	NextGenMCP Processing	<p>Performs the actions of a field worker to move the status of an activity to 'Started' using NextGen MCP. Then, clicks it.</p> <p>Note: To be called only after calling the NextGenMCP _EnrouteNPT component.</p>

Component	Functional Area	Description
NextGenMCP_CompleteNPT	NextGenMCP Processing	<p>Performs the actions of a field worker for completing an M1 Non Productive Task using NextGen MCP.</p> <p>Note: To be called only after calling the NextGenMCP_StartNPT component.</p>
NextGenMCP_EnroutePOU	NextGenMCP Processing	<p>Performs the actions of a field worker to move the status of an NPT task to 'En-route' using NextGen MCP. Then, clicks it.</p> <p>Note: To be called only after calling the NextGenMCP_DispatchedTask component.</p>
NextGenMCP_StartPOU	NextGenMCP Processing	<p>Performs the actions of a field worker to move the status of a POU to 'Started' using NextGen MCP. Then, clicks it.</p> <p>Note: To be called only after calling the NextGenMCP_EnroutePOU component.</p>
NextGenMCP_CompletePOU	NextGenMCP Processing	<p>Performs the actions of a field worker for completing an M1 POU task using ConnectedMCP.</p> <p>Note: To be called only after calling the NextGenMCP_StartPOU component.</p>
NextGenMCP_CompleteShift	NextGenMCP Processing	<p>Performs the actions of a field worker for completing a shift using NextGen MCP.</p> <p>Note: To be called only after a shift is in 'start' status.</p>

Chapter 2

Function Library Reference

This chapter lists the Oracle Utilities Mobile Workforce Management function libraries and functions available to create components and flows in Oracle Flow Builder for testing the Oracle Utilities Mobile Workforce Management application.

- [OUMWMLIB](#)
- [OUMWMCONNECTEDMCPLIB](#)
- [OUMWMMCPLIB](#)

OUMWMLIB

The OUMWMLIB library comprises functions that work on the connected MCP browser UI. These functions mimic the actions of a field worker who updates the task/shift information into the application using the connected MCP.

The library is made up of a collection of actions, such as clicking various buttons, entering text into fields, navigating through the connected MCP UI, etc., used for creating the required functions. These functions are, in turn, used for creating the connected MCP components.

The functions use the object repository “MWM_ConnectedMCP_REPOSITORY.properties” that is in the “etc” directory of the Oracle Functional Testing Advanced Pack for Oracle Utilities repository.

This section provides a list of functions included in the library, along with their usage details.

getTaskScheduledShiftId

Retrieves the Crew Shift ID to which a given task is scheduled.

This function checks continuously for the given time until it finds the crew shift that the activity is scheduled to. If the activity is not scheduled within the given time, it returns a blank string.

Example:

```
getTaskScheduledShiftId(String <timeInMinutes>, String <activityId>)
```

Input Parameters: String, String

Return Type: String

getPOUTaskIDForPOUID

Retrieves the period of unavailability Task ID for a given real-time period of unavailability ID.

This function checks continuously for the given time to retrieve the POU Task ID. If the POU Task ID is not created within the time, it returns a blank string.

Example:

```
getPOUTaskIDForPOUID(String <timeInMinutes>, String <realPOUID>)
```

Input Parameters: String, String

Return Type: String

getAssignmentIDForTaskId

Retrieves the Assignment ID for a given Activity ID. The assignment will be created when the activity is in “Assignment In Progress” state.

This function checks for the Assignment ID for a given Activity ID until the given time. If an assignment is not created within the time, it returns a blank string.

Example:

```
getAssignmentIDForTaskId(String <timeInMinutes>, String <activityId>)
```

Input Parameters: String, String

Return Type: String

getAssignmentCurrentStatus

Retrieves the current status of an assignment.

This function returns a blank string if the assignment does not exist for the given ID.

Example:

```
getAssignmentCurrentStatus (String <assignmentId>)
```

Input Parameters: String

Return Type: String

verifyIfAssignmentIsDispatched

Verifies if an assignment has been dispatched or not.

This function checks until the provided time to assert if the assignment has been dispatched. If the assignment is dispatched, it returns “Y”. Else, returns “N”.

Example:

```
verifyIfAssignmentIsDispatched (String <timeInMinutes>, String  
<assignmentId>)
```

Input Parameters: String, String

Return Type: String

checkActivityScheduledState

Verifies if an activity has been scheduled to any shift.

This function checks for the activity to be scheduled to a shift for a given time. If the activity is scheduled with in the given time, it returns “Y”, else returns “N”.

Example:

```
checkActivityScehduledState (String <timeInMinutes>, String  
<activityId>)
```

Input Parameters: String, String

Return Type: String

getProcedureId

Retrieves the Procedure ID for a given procedure name and Crew Shift ID.

This function checks for a procedure to be created for the procedure name and Crew Shift ID within the given time. If the procedure ID is not found within the given time, it returns a blank string. Else, returns the procedure ID.

Example:

```
getProcedureId(String <procedureName>,String <crewShiftId>,String
<timeInMinutes>)
```

Input Parameters: String, String, String

Return Type: String

getTimesheetIdFromShiftId

Retrieves the Timesheet ID for a given Crew Shift ID.

This function checks for a time sheet to be created for the Crew Shift ID within the given time. If Timesheet ID is not found within the given time, it returns a blank string, else returns the Timesheet ID.

Example:

```
getTimesheetIdFromShiftId(String <crewShiftId>, String
<timeInMinutes>)
```

Input Parameters: String, String

Return Type: String

getVisitIds

Retrieves the Visit IDs (comma separated) for a given Complex Activity ID.

If the Visit ID is not found, it returns a blank string. Else, it returns the Visit IDs.

Example:

```
getVisitId(String <complexActivityId>)
```

Input Parameters: String, String, String

Return Type: String

getDeploymentId

Retrieves the Deployment ID for a given Deployment Type. This function checks for the latest deployment generated for the given Deployment Type.

If the Deployment ID is not found, it returns a null. Else, it returns the Deployment ID.

Example:

```
getDeploymentId (String < deploymentType>)
```

Input Parameters: String

Return Type: String

deactivateCrew

Retrieves the Crew ID for the given Crew Name. This function checks for active Crew ID with the given Crew Name.

If the Crew ID is not found, it returns an empty string. Else, it returns the Crew ID.

Example:

```
deactivateCrew (String < crewName>)
```

Input Parameters: String

Return Type: String

deactivateMobileWorkerId

Retrieves the Mobile ID for the given User ID. This function checks for active mobile worker with the given User ID.

If the Mobile Worker ID is not found, it returns an empty string. Else, it returns the Mobile Worker ID.

Example:

```
deactivateMobileWorkerId (String < User_ID>)
```

Input Parameters: String

Return Type: String

deactivateVehicle

Retrieves the Vehicle ID for the given Vehicle Tag. This function checks for active Vehicle with the given Vehicle Tag.

If the Vehicle ID is not found, it returns an empty string. Else, it returns the Vehicle ID.

Example:

```
deactivateVehicle (String < vehicleTag>)
```

Input Parameters: String

Return Type: String

OUMWMCONNECTEDMCPLIB

The OUMWMCONNECTEDMCPLIB library contains functions that have been/can be used for creating Oracle Utilities Mobile Workforce Management components used to create the Oracle Utilities Mobile Workforce Management flows.

The library includes the Oracle Utilities Mobile Workforce Management specific functions that use the underlying framework of core functions. These functions interface with the database and read information, such as scheduling information of tasks, etc.

The library uses the UI element's xpath values specified in the MWM_ConnectedMCP_REPOSITORY.properties file in the **etc** directory of the repository.

Note: The private functions in this library are used to implement the public functions. The private functions cannot be used directly in the Oracle Flow Builder scripts.

invokeApp

Launches the Web browser, navigates to the URL provided, and then checks for the object in the Web page.

If the object is found, the function returns “Y”, else returns “N”.

Example:

```
loginToMDT (String <URL>,String <objectToCheck>)
```

Input Parameters: String, String

Return Type: String

loginToMDT

Internally calls the [invokeApp](#) function with the MCP URL that is connected.

This function inputs the User ID and password, and logs into the MCP application that is connected. It returns “Y” on the successful login, else returns “N”.

If the URL parameter is specified as “NA”, the connected MCP URL is formulated using the application URL specified in the configuration.properties file by appending “/mobility/Login.jsp” to that URL. If the connected MCP URL is specified to this function, then it is used instead.

Example:

```
loginToMDT(String <username>, String <password>, String
<connectedMCPURL>)
```

Input Parameters: String, String, String

Return Type: String

downloadDeployment

Internally calls the [loginToMDT](#) function and waits for the deployment to download.

This function verifies if the **Start Shift** page is displayed within a minute. If the page is displayed, it returns “Y”, else it returns “N”.

If the URL parameter is specified as “NA”, the connected MCP URL is formulated using the application URL specified in the configuration.properties file by appending “/mobility/Login.jsp” to that URL. If the connected MCP URL is specified to this function, then it is used instead.

Example:

```
downloadDeployment(String <username>, String <password>, String
<connectedMCPURL>)
```

Input Parameters: String, String, String

Return Type: String

startShift

Internally calls the [downloadDeployment](#) function and waits for the crew shift to start.

This function verifies if the Open Task List page is displayed. If the page is displayed, it returns “Y”, else it returns “N”. The loginError should be set as “N” for the crew shift to start successfully.

The function also verifies the negative scenarios where an error message is expected to be displayed during the shift start. The error message verification can be triggered by setting the loginError flag as “Y” as the input. If the loginError is set as “Y”, the function checks for an error message to be displayed, returns the error message, and then logs off the crew shift. If no error message is retrieved, it then returns a blank string.

If the URL parameter is specified as “NA”, the connected MCP URL is formulated using the application URL specified in the configuration.properties file by appending “/mobility/Login.jsp” to that URL. If the connected MCP URL is specified to this function, then it is used instead.

Example:

```
startShift(String <username>, String <password>, String
<connectedMCPURL>, String <loginError>)
```

Input Parameters: String, String, String, String

Return Type: String

verifyTaskDispatched

Verifies if a task has been dispatched for a given Task ID and then clicks on the task to open the UI.

This function returns a “Y” if the task has been dispatched. It checks for a task to be dispatched to the connected MCP within five minutes. If it is not dispatched, it returns a “N”.

Example:

```
verifyTaskDispatched(String <tasked>)
```

Input Parameters: String

Return Type: String

enrouteActivity

Performs the actions of a field worker and moves the task to “Enroute” status using the connected MCP.

This function returns “Y” on success, else returns “N”. To assign an activity, it has to be called after calling the [verifyTaskDispatched](#) function.

Example:

```
enrouteActivity ()
```

Input Parameters: <none>

Return Type: String

startActivityFromEnroute

Performs the actions of a field worker and moves the task to “Started” status using the connected MCP.

This function returns “Y” on success, else returns “N”. To assign an activity, it has to be called after calling the [enrouteActivity](#) function.

Example:

```
startActivityFromEnroute ()
```

Input Parameters: <none>

Return Type: String

completeActivity

Performs the actions of a field worker and moves the task to “Completed” status using the connected MCP.

This function returns “Y” on success, else returns “N”. To assign an activity, it has to be called after calling the [startActivityFromEnroute](#) function.

Example:

```
completeActivity ()
```

Input Parameters: <none>

Return Type: String

startBreak

Performs the actions of a field worker and moves the break task status to “Started” using the connected MCP.

This function returns “Y” on success, else returns “N”. To assign a break task, it has to be called after calling the [verifyTaskDispatched](#) function.

Example:

```
startBreak ()
```

Input Parameters: <none>

Return Type: String

completeBreak

Performs the actions of a field worker and moves the break task status to “Completed” using the connected MCP.

This function returns “Y” on success, else returns “N”. To assign a break task, it has to be called after calling the [startBreak](#) function.

Example:

```
completedBreak ()
```

Input Parameters: <none>

Return Type: String

enrouteNPT

Performs the actions of a field worker and moves the non productive task (NPT) status to “Enroute” using the connected MCP.

This function returns “Y” on success, else returns “N”. To assign a non productive task, it has to be called after calling the [verifyTaskDispatched](#) function.

Example:

```
enrouteNPT ()
```

Input Parameters: <none>

Return Type: String

startNPT

Performs the actions of a field worker and moves the non productive task (NPT) status to “Started” using the connected MCP.

This function returns “Y” on success, else returns “N”. To assign a non productive task, it has to be called after calling the [enrouteNPT](#) function.

Example:

```
startNPT ()
```

Input Parameters: <none>

Return Type: String

enroutePOU

Performs the actions of a field worker and moves the period of unavailability (POU) task status to “Enroute” using the connected MCP.

This function returns “Y” on success, else returns “N”. To assign a POU task, it has to be called after calling the [verifyTaskDispatched](#) function.

Example:

```
enroutePOU ()
```

Input Parameters: <none>

Return Type: String

startPOU

Performs the actions of a field worker and moves the period of unavailability (POU) task status to “Started” using the connected MCP.

This function returns “Y” on success, else returns “N”. To assign a POU task, it has to be called after calling the [enroutePOU](#) function.

Example:

```
startPOU ()
```

Input Parameters: <none>

Return Type: String

completePOU

Performs the actions of a field worker and moves the period of unavailability (POU) task status to “Completed” using the connected MCP.

This function returns “Y” on success, else returns “N”. To assign a POU task, it has to be called after calling the [startPOU](#) function.

Example:

```
completePOU()
```

Input Parameters: <none>

Return Type: String

endShift

Completes/ends the crew shift by performing the actions of a field worker to complete the current day’s crew shift using the connected MCP.

This function also closes the connected MCP application. It returns “Y” on success, else returns “N”.

Example:

```
endShift ()
```

Input Parameters: <none>

Return Type: String

OUMWMMCLIB

The OUMWMMCLIB library contains functions that have been/can be used for creating Oracle Utilities Mobile Workforce Management components. These components are later used to create the Oracle Utilities Mobile Workforce Management flows.

The library includes the Oracle Utilities Mobile Workforce Management specific functions that use the underlying framework of core functions. These functions interface with the database and read information, such as scheduling information of tasks, etc.

The library uses the UI elements’ xpath values specified in the MCP.properties file added as an asset to this functional library.

Note: The private functions in this library are used to implement the public functions. The private functions cannot be used directly in the Oracle Flow Builder scripts.

startShift

Internally calls the downloadDeployment function and waits for the crew shift to start. This Function invokes the application in Chrome browser using the URL specified in config.properties file. The URL is provided as a value to the variable gStrNewMCPURL in config.properties file.

The function fetches this URL and invokes the application, and then logs in to the application fetching user credentials from config.properties file. On successful login, it checks for the available deployments. It selects the required deployment and waits for it to be downloaded.

Once the deployment is downloaded, it starts the crew shift and waits for the tasks to get dispatched in The **Open Tasks List** screen. If in case, the user tries to launch the application for an already started shift, it directly logs into the application and waits for the activities to get dispatched in the Open Task List screen.(No start shift step is performed as it is referring to already started shift.)

The function also verifies the negative scenarios where an error message is expected to be displayed when user login fails for any of the reasons, such as invalid user credentials, etc.

Example:

```
startShift(String <username>, String <password>, String HardwareId,
String <deploymentType>)
```

Input Parameters: String, String, String, String

Return Type: String

verifyTaskDispatched

Verifies if a task has been dispatched for a given Task ID for a specified amount of time maxTimeToCheck, and then clicks on the task in UI to perform actions on it.

This function returns a "Y" if the task has been dispatched. It checks for a task to be dispatched to the new MCP browser application within specified amount of time in minutes. If it is not dispatched, it returns a "N".

Example:

```
verifyTaskDispatched(String <taskId>,String maxTimeToCheck)
```

Input Parameters: String,String

Return Type: String

enrouteActivity

Performs the actions of a field worker and moves the task to "Enroute" status using the Next Gen MCP_ EnrouteActivity component.

This function returns "Y" on success, else returns "N". To assign an activity, it has to be called after calling the verifyTaskDispatched function.

Example:

```
enrouteActivity ()
```

Input Parameters: <none>

Return Type: String

startActivityFromEnroute

Performs the actions of a field worker and moves the task to "Started" status using the NextGenMCP_StartActivity component.

This function returns "Y" on success, else returns "N". To assign an activity, it has to be called after calling the enrouteActivity function.

Example:

```
startActivityFromEnroute ()
```

Input Parameters: <none>

Return Type: String

completeActivity

Performs the actions of a field worker and moves the task to "Completed" status using the Next Gen MCP_ CompleteActivity component

This function returns "Y" on success, else returns "N". To assign an activity, it has to be called after calling the startActivityFromEnroute function.

Example:

```
completeActivity ()
```

Input Parameters: <none>

Return Type: String

startBreak

Performs the actions of a field worker and moves the break task status to "Started" using the Next Gen MCP_ StartBreak component

This function returns "Y" on success, else returns "N". To assign a break task, it has to be called after calling the verifyTaskDispatched function.

Example:

```
startBreak ()
```

Input Parameters: <none>

Return Type: String

completeBreak

Performs the actions of a field worker and moves the break task status to "Completed" using the Next Gen MCP_ CompleteBreak component

This function returns "Y" on success, else returns "N". To assign a break task, it has to be called after calling the startBreak function.

Example:

```
completedBreak ()
```

Input Parameters: <none>

Return Type: String

enrouteNPT

Performs the actions of a field worker and moves the non productive task (NPT) status to "Enroute" using the Next Gen MCP_ EnrouteNPT component.

This function returns "Y" on success, else returns "N". To assign a non productive task, it has to be called after calling the verifyTaskDispatched function.

Example:

```
enrouteNPT ()
```

Input Parameters: <none>

Return Type: String

startNPT

Performs the actions of a field worker and moves the non productive task (NPT) status to "Started" using the Next Gen MCP_StartNPT Component

This function returns "Y" on success, else returns "N". To assign a non productive task, it has to be called after calling the enroutenPT function.

Example:

```
startNPT ()
```

Input Parameters: <none>

Return Type: String

completeNPT

Performs the actions of a field worker and moves the period of unavailability (POU) task status to "Completed" using the Next Gen MCP._CompleteNPT component.

This function returns "Y" on success, else returns "N". To assign a POU task, it has to be called after calling the startPOU function.

Example:

```
completeNPT()
```

Input Parameters: <none>

Return Type: String

enroutePOU

Performs the actions of a field worker and moves the period of unavailability (POU) task status to "Enroute" using the Next Gen MCP._EnroutePOU component.

This function returns "Y" on success, else returns "N". To assign a POU task, it has to be called after calling the verifyTaskDispatched function.

Example:

```
enroutePOU ()
```

Input Parameters: <none>

Return Type: String

startPOU

Performs the actions of a field worker and moves the period of unavailability (POU) task status to "Started" using the Next Gen MCP_StartPOU component.

This function returns "Y" on success, else returns "N". To assign a POU task, it has to be called after calling the enroutenPT function.

Example:

```
startPOU ()
```

Input Parameters: <none>

Return Type: String

completePOU

Performs the actions of a field worker and moves the period of unavailability (POU) task status to "Completed" using the Next Gen MCP_CompletePOU component.

This function returns "Y" on success, else returns "N". To assign a POU task, it has to be called after calling the startPOU function.

Example:

```
completePOU()
```

Input Parameters: <none>

Return Type: String

endShift

Completes/ends the crew shift by performing the actions of a field worker to complete the current day's crew shift using the Next Gen MCP_ CompleteShift component.

This function also closes the Next Gen MCP application. It returns "Y" on success, else returns "N".

Example:

```
endShift()
```

Input Parameters: <none>

Return Type: String

CheckforAnActivityInCompletionScreen

Navigates to the **Activity Completion** screen and verifies if the activity with specified Activity ID is in completed state for a time specified as maxTimetoCheck in minutes.

If found, it returns "true", else "false".

Example:

```
CheckforAnActivityInCompletionScreen(String tasked,String  
maxTimetoCheck)
```

Input Parameters: <String,String>

Return Type: boolean

Chapter 3

Sample Work Flows

This chapter describes the Oracle Utilities Mobile Workforce Management sample flows that illustrate common use cases for Oracle Functional Testing Advanced Pack for Oracle Utilities. It also explains the procedure to execute these sample flows.

The chapter includes the following sections:

- [Sample Flows](#)
- [Executing Sample Flows](#)

Sample Flows

The sample flows delivered as part of Oracle Functional Testing Advanced Pack for Oracle Utilities for Oracle Utilities Mobile Workforce Management demonstrate how flows can be created for Web services based testing and for a combination of Web services and UI based testing using the same framework.

These flows are designed to run using the demo data, there by giving the user, the ability to deploy Oracle Functional Testing Advanced Pack for Oracle Utilities for Oracle Utilities Mobile Workforce Management and execute the sanity flows immediately. The flows perform a part of the basic sanity testing required to certify that the Oracle Utilities Mobile Workforce Management environment has been setup appropriately.

This section includes the following sample work flows:

- [Non-MDT Flow](#)
- [MDT Flow](#)
- [M2 Non-MDT Flow](#)
- [MDT Flow Using NextGen MCP](#)

Non-MDT Flow

The Non-MDT flow comprises the creation and completion life cycle of an M1 activity - break, non-productive task (NPT), and real period of unavailability (POU), along with the crew shift.

The following table lists the tasks that are created and their respective components in Oracle Utilities Mobile Workforce Management:

Task	MWM Component
Activity	M1-Activity
Break	M1-Break

Task	MWM Component
Non-productive Task	M1-NonProductiveTask
Real Period of Availability	M1-RealPOU

Activity, real POU, break, and non-productive tasks are scheduled to a planned crew shift that has the matching location, required capability, and scheduling time window. The dispatcher logs in the planned crew shift and starts the shift. Once the crew shift starts, activity, non-productive task, real POU, and break are dispatched to the crew shift. The dispatcher starts, completes the activity, real POU, break, and non-productive task.

The M1-Assignment component is used to assign a transition (to enroute --> start --> completing an activity). Similarly, M1-BreakTask, M1-NonProductiveTask, and M1-POUtask components are used to start, complete the break, non-productive tasks, and POU respectively. The dispatcher completes the crew shift after completing the dispatched tasks.

MDT Flow

The MDT flow includes the creation and completion of an activity, break, non-productive task (NPT), and real period of unavailability (POU) using connected MCP.

Task	MWM Component
Activity	M1-Activity
Break	M1-Break
Non-productive Task	M1-NonProductiveTask
Real Period of Availability	M1-RealPOU

Activity, real POU, break, and non-productive tasks are scheduled to a planned crew shift that has the matching location, required capability, and scheduling time window.

The MDT flow is as follows:

1. The dispatcher launches the connected MCP.
2. The crew logs in with the valid credentials and starts the crew shift.
3. The activity, break task, and non-productive tasks are dispatched to the crew shift.
4. Use the following components applicable for each task:

Task	MWM Component
Start the crew shift	ConnectedMCP_StartCrewShift
Verify if the tasks are dispatched	ConnectedMCP_DispatchedTask
Enroute status	ConnectedMCP_EnrouteActivity
Start activity	ConnectedMCP_StartActivity
Complete activity	ConnectedMCP_CompleteActivity

5. The crew shift is completed after completing all the dispatched tasks.

M2 Non-MDT Flow

The M2-Non-MDT flow includes the creation and completion of M-Activity (Install Meter Activity, for example).

Create an Install Meter Activity using the **M2-InstallMeterActivity** component.

The M2-Activity is scheduled to a planned crew shift that has the matching location, required capability, and the scheduling time window.

The M2 Non-MDT flow is as follows:

1. The dispatcher logs in the planned crew shift.
2. The dispatcher starts and completes the M2-Activity.
The M2-InstallMeterAssignment component is used for M2-Activity assignment transition.
3. The dispatcher completes the crew shift after completing the M2-Activity (Install Meter Activity).

MDT Flow Using NextGen MCP

The MDT flow includes the creation and completion of an activity, break, non-productive task (NPT), and real period of unavailability (POU) using NextGen MCP.

Task	MWM Component
Activity	M1-Activity
Break	M1-Break
Non-productive Task	M1-NonProductiveTask
Real Period of Availability	M1-RealPOU

Activity, real POU, break, and non-productive tasks are scheduled to a planned crew shift that has the matching location, required capability, and scheduling time window.

The MDT flow is as follows:

1. The dispatcher launches the NextGen MCP (Google Chrome Browser).
2. The crew logs in with valid credentials and starts the crew shift.
3. The activity, break task, and non-productive tasks are dispatched to the crew shift.
4. Use the following components applicable for each task:

Task	MWM Component
Start the crew shift	NextGenMCP_StartCrewShift
Verify if the tasks are dispatched	NextGenMCP_DispatchedTask
Enroute status	NextGenMCP_EnrouteActivity
Start activity	NextGenMCP_StartActivity

5. The crew shift is complete after completing all the dispatched tasks.

Note: The MDT Flow using NextGen MCP can be run/played back in OpenScript 12.5 version. OpenScript v12.5 currently does not support recording on Google Chrome at its current level. But, this is an expected feature in OpenScript v12.6 (which would soon be available).

Executing Sample Flows

This section describes the procedure to setup sample flows and execute them.

- [Pre-requisites](#)
- [Setting Up Sample Flows](#)

Pre-requisites

To execute the sample flow, ensure the following pre-requisites are met:

- Oracle Utilities Mobile Workforce Management v2.2.0.3/Oracle Real-Time Scheduler v2.2.0.3 is up and running with the demo data pack.
- OpenScript is installed in the local machine. See the *Oracle Functional Testing Advanced Pack for Oracle Utilities Installation Guide* for the version details.
- Oracle Functional Testing Advanced Pack for Oracle Utilities is installed and repository/directory is setup in the local machine appropriately. See the *Oracle Functional Testing Advanced Pack for Oracle Utilities Installation Guide* for more details.
- **Important:** Browser Playback settings of OpenScript must be set explicitly to either Mozilla Firefox or Chrome Browser for MDT flow and only "Chrome Browser" for NextGen MCP flow.

Setting Up Sample Flows

To setup a sample flow, follow these steps:

1. Login to Oracle Utilities Mobile Workforce Management/Oracle Real-Time Scheduler.
2. Import the Inbound Web services into the Oracle Utilities Mobile Workforce Management/Oracle Real-Time Scheduler application where the scenarios need to be executed.

See the [Importing Inbound Web Services](#) section in [Appendix A: Inbound Web Services](#) for steps to import the Inbound Web services.

3. Navigate to **Admin > B > Bundle Import > Add**.
4. Enter the **External Reference**, **Detailed Description**, and **Bundle Details** from the IWS Bundle Export Dump.
5. Click **Save**, and then click **Apply bundle**.
6. Launch OpenScript in the local machine and perform the following steps:
 - a. Navigate to **View > OpenScript Preferences**.
 - b. In the left tree, select **OpenScript**. In the sub tree, select **Playback**, and then select **Error Recovery**.
 - c. Click **SetAll** and select **Report Error and Continue**.
 - d. Click **Apply**, and then click **Close**.
7. Configure the **configuration.properties** file as follows:
 - a. Provide the application URL for the parameter:

```
gStrApplicationURL = http\://<%serverName%>\:<%portNumber%>/
ouaf
```

- b. Provide the additional path required for Inbound Web service URL:

```
gStrApplicationXAIServerPath=/<%webservices/
gStrApplicationURL%>/<%AppendThisToAbove gStrApplicationURL%>/
```

- c. Provide an environment name for display in the results email:
`gStrEnvironmentName= <%testEnvironmentName%>`
- d. Provide the application login user ID:
`gStrApplicationUserName= <%UserName%>`
- e. Provide the application login password:
`gStrApplicationUserPassword= <%password%>`
- f. Provide the SMTP email server and e-mail ID:
`gStrSMTP_HOST_NAME=<%SMTP ServerName%>`
`gStrSMTP_PORT=<%PortNumber%>`
`gStrTO_EMAIL_RECIPIENTS=<%e-mail Id%>`
- g. Provide the application database details as below:
`gStrApplicationDBConnectionString =<%jdbc Connectionstring%>`
eg: `jdbc\:oracle\:thin\:@<%DBserverName%>\:<%port%>\:<%DBSID%>`
`gStrApplicationDBUsername=<%DBUserID%>`
`gStrApplicationDBPassword=<%DBPassword%>`
- h. Provide the full directory path of Oracle Application Testing Suite repository directories in the local machine.
`gStrOutputFilePath=<%LogFilePath%>`
Example: `C:\OATSOUWWM_DEMO\OUTSP\Log\`
`gStrXSDFiles=<%XSD Folder path%>`
Example: `C:\OATSOUWWM_DEMO\OUTSP\Log\`
9. Create two folders (MWM and Core) in the outsp-function-libs folder in the Oracle Application Testing Suite repository directory. Copy the function libraries to the respective folders.
- MWM
 - OUMWMCONNECTEDMCPLIB
 - OUMWMLIB
 - OUMWMMCPLIB
 - Core
 - OUTSPCORELIB
 - WSCOMMONLIB
 - WSVALIDATELIB
10. Copy all the .jar files provided in the installer into the **genericJars** folder in the Oracle Application Testing Suite repository directory.

Appendix A

Inbound Web Services

The Oracle Utilities Mobile Workforce Management components are developed using Web services method, and these components require Inbound Web Services to be defined in the application.

For instructions to create, import, or search an Inbound Web Service, see the **Setting Up Inbound Web Services** appendix in *Oracle Functional Testing Advanced Pack for Oracle Utilities User's Guide*.

List of Inbound Web Services

The list of Inbound Web Services provided to use with the delivered components and flows is as follows:

- ATM1Activity
- ATM1Alert
- ATM1AllocateActivityToAShift
- ATM1AppointmentBookingRequest
- ATM1Assignment
- ATM1BreakTask
- ATM1CommonShiftWeeklyTemplate
- ATM1Company
- ATM1ComplexActivity
- ATM1Contractor
- ATM1ContractorEligibility
- ATM1Crew
- ATM1CrewShift
- ATM1CrewShiftCloseOpenAllocate
- ATM1CrewShiftTemplate
- ATM1DailySpeedTemplate
- ATM1DeferActivity
- ATM1DepotRelatedActivity
- ATM1DepotRelatedShift

- ATM1DepotSinglePersonCrew
- ATM1DepotTask
- ATM1Dispatcher
- ATM1DispatcherShift
- ATM1FixToCrew
- ATM1ForceLogOffCrewShift
- ATM1GetShiftCapabilities
- ATM1HazardArea
- ATM1MailingList
- ATM1MainMail
- ATM1MobileWorker
- ATM1NonPrdTask
- ATM1OverrideTimeWindow
- ATM1POUTask
- ATM1RealPOU
- ATM1ResTimesheet
- ATM1ResourceLeave
- ATM1SchedulerRegistryRead
- ATM1ShiftWeeklyTemplate
- ATM1SimpleProcedure
- ATM1SinglePersonCrew
- ATM1SpeedProfileTemplate
- ATM1SubscriptionWeeklyTemplate
- ATM1TaskScheduleDetails
- ATM1TemplateMail
- ATM1TemplatePOU
- ATM1UnassignActivity
- ATM1Vehicle
- ATM1VehicleLeaveArea
- ATM2InstallMeterActivity
- ATM2InstallMeterAssignment
- ATM2ConnectSPActivity
- ATM2ConnectSPAssignment
- ATM2CutNonPayItemActivity
- ATM2CutNonPayItemAssignment
- ATM2DisconnectMeterActivity
- ATM2DisconnectMeterAssignment
- ATM2ExchangeItemActivity

- ATM2ExchangeItemAssignment
- ATM2InstallMeterActivity
- ATM2InstallMeterAssignment
- ATM2MeterReadActivity
- ATM2MeterReadAssignment
- ATM2RemoveMeterActivity
- ATM2RemoveMeterAssignment
- ATM2BasicItemActivity
- ATM2BasicItemAssignment
- ATM2RemoveItemActivity
- ATM2RemoveItemAssignment
- ATM1ActivityType
- ATM1AlertType
- ATM1BreakTaskType
- ATM1Capacity
- ATM1CapacityTemplate
- ATM1CapacityType
- ATM1CapacityWeeklyTemplate
- ATM1ComplexActivityType
- ATM1ContractorType
- ATM1CrewHierarchy
- ATM1CrewShiftType
- ATM1CrewType
- ATM1Deployment
- ATM1DeploymentPart
- ATM1DeploymentType
- ATM1Depot
- ATM1DepotProfile
- ATM1DepotTaskType
- ATM1DispatchArea
- ATM1DispatcherType
- ATM1Equipment
- ATM1GeographicArea
- ATM1GlobalConfigurations
- ATM1KPI
- ATM1Location
- ATM1MobileDeviceTerminal
- ATM1MobileDeviceTerminalType

- ATM1MobileWorkerType
- ATM1NonPrdTaskType
- ATM1POUTaskType
- ATM1POUType
- ATM1PriorityProfile
- ATM1ProcedureType
- ATM1RemarkType
- ATM1ResTimesheetTyp
- ATM1Scheduler
- ATM1SchedulerArea
- ATM1SchedulerConfiguration
- ATM1ServiceArea
- ATM1ServiceAreaHierarchy
- ATM1ServiceClass
- ATM1ShiftCostProfile
- ATM1Skill
- ATM1StatusReason
- ATM1VehicleType
- ATM1WorkCalendar
- ATM1WorkProfile
- ATM2MaintainUtilityActByHost