

Oracle® Fusion Middleware

RESTful Server Runtime Reference for Oracle WebLogic
Server

12c (12.2.1)

E64955-02

November 2015

This reference describes the RESTful server runtime
resources that are used to manage WebLogic Server.

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

This documentation is in preproduction status and is intended for demonstration and preliminary use only. It may not be specific to the hardware on which you are using the software. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to this documentation and will not be responsible for any loss, costs, or damages incurred due to the use of this documentation.

The information contained in this document is for informational sharing purposes only and should be considered in your capacity as a customer advisory board member or pursuant to your beta trial agreement only. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions. The development, release, and timing of any features or functionality described in this document remains at the sole discretion of Oracle.

This document in any form, software or printed matter, contains proprietary information that is the exclusive property of Oracle. Your access to and use of this confidential material is subject to the terms and conditions of your Oracle Master Agreement, Oracle License and Services Agreement, Oracle PartnerNetwork Agreement, Oracle distribution agreement, or other license agreement which has been executed by you and Oracle and with which you agree to comply. This document and information contained herein may not be disclosed, copied, reproduced, or distributed to anyone outside Oracle without prior written consent of Oracle. This document is not part of your license agreement nor can it be incorporated into any contractual agreement with Oracle or its subsidiaries or affiliates.

Contents

Preface CXXXIX

1 Resources

/management/weblogic.....	1-2
/management/weblogic/{version}	1-5
/management/weblogic/{version}/currentUser.....	1-9
/management/weblogic/{version}/serverRuntime.....	1-12
/management/weblogic/{version}/serverRuntime/applicationRuntimes	1-19
/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name} ...	1-21
/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classLoaderRuntime	1-24
/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedeinitionRuntime	1-26
/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedeinitionRuntime/classRedeinitionTasks	1-28
/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedeinitionRuntime/classRedeinitionTasks/{name}	1-30
/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedeinitionRuntime/classRedeinitionTasks/{name}/cancel	1-32
/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedeinitionRuntime/classRedeinitionTasks/{name}/subTasks	1-34
/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedeinitionRuntime/classRedeinitionTasks/{name}/subTasks/{name}	1-36
/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedeinitionRuntime/classRedeinitionTasks/{name}/subTasks/{name}/cancel	1-38
/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedeinitionRuntime/classRedeinitionTasks/{name}/subTasks/{name}/subTasks	1-40

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRede
finitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name}
1-42

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRe
definitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name}/
cancel 1-44

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRe
definitionRuntime/redefineClasses 1-46

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/cohere
nceClusterRuntime 1-49

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/compo
nentRuntimes 1-51

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/compo
nentRuntimes/{name} 1-53

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/compo
nentRuntimes/{name}/workManagerRuntimes 1-55

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/compo
nentRuntimes/{name}/workManagerRuntimes/{name} 1-57

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/compo
nentRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime 1-59

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/compo
nentRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime
1-61

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/compo
nentRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime
1-63

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/compo
nentRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-65

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/getPers
istenceUnitRuntime 1-67

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/hasAp
plicationCache 1-69

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/library
Runtimes 1-71

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes/{name} 1-73

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes 1-75

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name} 1-77

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes 1-79

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name} 1-81

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager 1-83

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime 1-85

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime 1-87

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime 1-89

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime 1-91

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes 1-93

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name} 1-95

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager 1-97

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime 1-99

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime 1-101

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime 1-103

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime 1-105

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedThreadFactoryRuntimes 1-107

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedThreadFactoryRuntimes/{name} 1-109

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/maxThreadsConstraintRuntimes 1-111

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/maxThreadsConstraintRuntimes/{name} 1-113

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/minThreadsConstraintRuntimes 1-115

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/minThreadsConstraintRuntimes/{name} 1-117

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes 1-119

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name} 1-121

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes 1-123

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes/{name} 1-125

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/persistenceUnitRuntimes 1-127

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/persistenceUnitRuntimes/{name} 1-129

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/queryCacheRuntimes 1-131

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/queryCacheRuntimes/{name} 1-133

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/reInitializeApplicationCachesAndPools 1-135

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/requestClassRuntimes 1-137

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/requestClassRuntimes/{name} 1-139

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes 1-141

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name} 1-143

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime 1-145

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-147

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-149

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-151

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes 1-153

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name} 1-155

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/policyRuntime 1-157

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports 1-159

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} 1-161

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/aggregatedBaseOperations 1-164

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations 1-166

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations/{name} 1-168

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/clusterRouting 1-170

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers 1-172

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers/{name} 1-174

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/mc 1-176

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations 1-178

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations/{name} 1-180

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/portPolicy 1-182

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/wsrm 1-184

/management/weblogic/{version}/serverRuntime/asyncReplicationRuntime..... 1-186

/management/weblogic/{version}/serverRuntime/batchJobRepositoryRuntime ... 1-188

/management/weblogic/{version}/serverRuntime/classLoaderRuntime 1-190

/management/weblogic/{version}/serverRuntime/clusterRuntime 1-192

/management/weblogic/{version}/serverRuntime/clusterRuntime/initiateResourceGroupMigration 1-194

/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime 1-196

/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/executedJobs 1-198

/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/executedJobs/{name} 1-200

/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/executedJobs/{name}/cancel 1-202

/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/executedJobs/{name}/getJob 1-204

/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime 1-206

/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime/migrationData 1-208

/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime/migrationData/{name} 1-210

/management/weblogic/{version}/serverRuntime/clusterRuntime/unicastMessaging..... 1-212

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime.. 1-214

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes 1-216

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name} 1-218

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager 1-220

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime 1-222

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime 1-224

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime 1-226

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime 1-228

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes 1-230

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name} 1-232

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager 1-234

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime 1-236

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime 1-238

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime 1-240

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime 1-242

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes 1-244

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes/{name} 1-246

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime..... 1-248

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs 1-251

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name} 1-253

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools 1-256

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} 1-258

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections 1-261

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} 1-263

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete 1-265

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-267

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-269

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened 1-271

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectionPools/{name}/flushLog 1-273

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectionPools/{name}/forceLogRotation 1-275

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectionPools/{name}/forceReset 1-277

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectionPools/{name}/logRuntime 1-279

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-281

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectionPools/{name}/logRuntime/flushLog 1-283

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-285

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectionPools/{name}/reset 1-287

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectionPools/{name}/testPool 1-289

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime 1-291

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/getInboundConnections 1-294

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/getRA 1-296

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs 1-298

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name} 1-300

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools 1-303

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} 1-305

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/conne
ctions 1-308

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/conne
ctions/{name} 1-310

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/conne
ctions/{name}/delete 1-312

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/conne
ctions/{name}/hasError 1-314

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/conne
ctions/{name}/testConnection 1-316

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensur
eLogOpened 1-318

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flush
Log 1-320

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/force
LogRotation 1-322

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/force
Reset 1-324

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRu
netime 1-326

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRu
netime/ensureLogOpened 1-328

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRu
netime/flushLog 1-330

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRu
ntime/forceLogRotation 1-332

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset
1-334

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPo
ol 1-336

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntim
e 1-338

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration 1-340

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool 1-342

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection 1-344

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema 1-346

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections 1-348

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}
1-350

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/
MDBRuntimes 1-352

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/
MDBRuntimes/{name} 1-354

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/
MDBRuntimes/{name}/poolRuntime 1-357

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/
MDBRuntimes/{name}/poolRuntime/initializePool 1-359

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/
MDBRuntimes/{name}/resources 1-361

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/
MDBRuntimes/{name}/resources/{name} 1-363

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/
MDBRuntimes/{name}/resume 1-365

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/
MDBRuntimes/{name}/suspend 1-367

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/
MDBRuntimes/{name}/timerRuntime 1-369

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/
MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-371

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/
MDBRuntimes/{name}/transactionRuntime 1-373

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume 1-375

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll 1-377

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend 1-379

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll 1-381

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime 1-383

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacit
yRuntime 1-385

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThr
eadsConstraintRuntime 1-387

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThr
eadsConstraintRuntime 1-389

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/request
ClassRuntime 1-391

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes 1-393

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}
1-395

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}
/capacityRuntime 1-397

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}
/maxThreadsConstraintRuntime 1-399

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}
/minThreadsConstraintRuntime 1-401

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}
/requestClassRuntime 1-403

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs 1-405

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name} 1-407

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools 1-410

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} 1-412

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections
1-415

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{
name} 1-417

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{
name}/delete 1-419

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{
name}/hasError 1-421

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{
name}/testConnection 1-423

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOp
ened 1-425

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog
1-427

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRota
tion 1-429

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset
1-431

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime
1-433

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/
ensureLogOpened 1-435

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/f
lushLog 1-437

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/f
orceLogRotation 1-439

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset 1-441

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool
1-443

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime
1-445

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration 1-447

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool 1-449

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection 1-451

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/getSchema 1-453

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections 1-455

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name} 1-457

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRu
ntimes 1-459

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRu
ntimes/{name} 1-461

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRu
ntimes/{name}/poolRuntime 1-464

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRu
ntimes/{name}/poolRuntime/initializePool 1-466

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRu
ntimes/{name}/resources 1-468

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRu
ntimes/{name}/resources/{name} 1-470

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRu
ntimes/{name}/resume 1-472

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRu
ntimes/{name}/suspend 1-474

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRu
ntimes/{name}/timerRuntime 1-476

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRu
ntimes/{name}/timerRuntime/activateDisabledTimers 1-478

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRu
ntimes/{name}/transactionRuntime 1-480

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/resume 1-482

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/resumeAll 1-484

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/suspend 1-486

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/suspendAll 1-488

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime 1-490

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntim
e 1-492

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsCo
nstraintRuntime 1-494

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsCo
nstraintRuntime 1-496

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRu
ntime 1-498

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes 1-500

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} 1-502

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capaci
tyRuntime 1-504

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxT
hreadsConstraintRuntime 1-506

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minT
hreadsConstraintRuntime 1-508

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/reque
stClassRuntime 1-510

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/resume 1-512

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/resumeAll 1-514

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/suspend 1-516

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorServiceRuntime/suspendAll 1-518

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/connectorWorkManagerRuntime 1-520

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/getConfiguration 1-522

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/getConnectionPool 1-524

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/getInboundConnection 1-526

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/getSchema 1-528

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/inboundConnections 1-530

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/inboundConnections/{name} 1-532

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/inboundConnections/{name}/MDBRuntimes 1-534

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/inboundConnections/{name}/MDBRuntimes/{name} 1-536

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-539

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-541

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources 1-543

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-545

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume 1-547

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend 1-549

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-551

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-553

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime
1-555

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/resume 1-557

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/resumeAll 1-559

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/suspend 1-561

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/suspendAll 1-563

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/workManagerRuntime 1-565

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/workManagerRuntime/capacityRuntime 1-567

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-569

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-571

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/workManagerRuntime/requestClassRuntime 1-573

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/workManagerRuntimes 1-575

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/workManagerRuntimes/{name} 1-577

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/workManagerRuntimes/{name}/capacityRuntime 1-579

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-581

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-583

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs
/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-585

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/getInboundConnections 1-587

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/getRAS
1-589

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS 1-591

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name} 1-593

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/connectionPools 1-596

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/connectionPools/{name} 1-598

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/connectionPools/{name}/connections 1-601

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/connectionPools/{name}/connections/{name} 1-603

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/connectionPools/{name}/connections/{name}/delete 1-605

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/connectionPools/{name}/connections/{name}/hasError 1-607

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/connectionPools/{name}/connections/{name}/testConnection 1-609

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/connectionPools/{name}/ensureLogOpened 1-611

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/connectionPools/{name}/flushLog 1-613

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/connectionPools/{name}/forceLogRotation 1-615

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/connectionPools/{name}/forceReset 1-617

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/connectionPools/{name}/logRuntime 1-619

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-621

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-623

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-625

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset 1-627

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool 1-629

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime 1-631

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs 1-634

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} 1-636

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools 1-639

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} 1-641

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections 1-644

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} 1-646

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete 1-648

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-650

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-652

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened 1-654

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog 1-656

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation 1-658

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset 1-660

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime 1-662

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-664

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-666

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-668

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset 1-670

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool 1-672

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime 1-674

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration 1-676

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool 1-678

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection 1-680

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema 1-682

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections 1-684

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} 1-686

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/M DBRuntimes 1-688

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/M DBRuntimes/{name} 1-690

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/M DBRuntimes/{name}/poolRuntime 1-693

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/M DBRuntimes/{name}/poolRuntime/initializePool 1-695

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/M DBRuntimes/{name}/resources 1-697

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/M DBRuntimes/{name}/resources/{name} 1-699

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/M DBRuntimes/{name}/resume 1-701

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/M DBRuntimes/{name}/suspend 1-703

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/M DBRuntimes/{name}/timerRuntime 1-705

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-707

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-709

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume 1-711

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll 1-713

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend 1-715

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll 1-717

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime 1-719

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime 1-721

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-723

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-725

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime 1-727

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes 1-729

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} 1-731

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-733

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-735

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-737

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-739

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getInboundConnections 1-741

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getRA 1-743

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs 1-745

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} 1-747

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools 1-750

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} 1-752

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections 1-755

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} 1-757

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete 1-759

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-761

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-763

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened 1-765

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog 1-767

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation 1-769

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset 1-771

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime 1-773

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-775

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-777

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-779

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset 1-781

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool 1-783

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime 1-785

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration 1-787

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool 1-789

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection 1-791

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getSchema 1-793

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections 1-795

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name} 1-797

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes 1-799

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} 1-801

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-804

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-806

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources 1-808

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-810

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume 1-812

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend 1-814

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-816

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-818

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-820

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/resume 1-822

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/resumeAll 1-824

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/suspend 1-826

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/suspendAll 1-828

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime 1-830

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime 1-832

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-834

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-836

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime 1-838

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes 1-840

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} 1-842

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-844

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-846

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-848

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-850

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resume 1-852

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resumeAll 1-854

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspend 1-856

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspendAll 1-858

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime 1-860

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration 1-862

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool 1-864

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection 1-866

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/getSchema 1-868

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections 1-870

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} 1-872

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes 1-874

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/inboundConnections/{name}/MDBRuntimes/{name} 1-876

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-879

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-881

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources 1-883

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-885

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume 1-887

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend 1-889

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-891

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-893

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-895

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/resume 1-897

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/resumeAll 1-899

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/suspend 1-901

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/suspendAll 1-903

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/workManagerRuntime 1-905

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime 1-907

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-909

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-911

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime 1-913

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes 1-915

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} 1-917

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-919

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-921

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-923

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-925

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs.....
1-927

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name} 1-929

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools 1-932

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name} 1-934

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections 1-937

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} 1-939

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete 1-941

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-943

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-945

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened 1-947

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog 1-949

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation 1-951

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset 1-953

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime 1-955

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-957

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-959

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-961

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset 1-963

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool 1-965

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime 1-967

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs 1-970

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} 1-972

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools 1-975

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} 1-977

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections 1-980

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} 1-982

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete 1-984

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-986

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-988

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened 1-990

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog 1-992

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation 1-994

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset 1-996

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime 1-998

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-1000

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-1002

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-1004

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset 1-1006

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool 1-1008

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime 1-1010

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration 1-1012

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool 1-1014

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection 1-1016

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema 1-1018

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections 1-1020

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} 1-1022

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRunTimes 1-1024

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRunTimes/{name} 1-1026

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRunTimes/{name}/poolRuntime 1-1029

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRun times/{name}/poolRuntime/initializePool 1-1031

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRun times/{name}/resources 1-1033

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRun times/{name}/resources/{name} 1-1035

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRun times/{name}/resume 1-1037

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRun times/{name}/suspend 1-1039

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRun times/{name}/timerRuntime 1-1041

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRun times/{name}/timerRuntime/activateDisabledTimers 1-1043

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRun times/{name}/transactionRuntime 1-1045

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume 1-1047

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll 1-1049

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend 1-1051

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll 1-1053

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime 1-1055

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime 1-1057

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-1059

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-1061

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime 1-1063

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes 1-1065

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} 1-1067

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-1069

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-1071

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-1073

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-1075

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getInboundConnections 1-1077

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getRA 1-1079

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs 1-1081

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} 1-1083

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools 1-1086

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} 1-1088

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections 1-1091

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name} 1-1093

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete 1-1095

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-1097

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-1099

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened 1-1101

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog 1-1103

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation 1-1105

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset 1-1107

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime 1-1109

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-1111

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-1113

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-1115

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset 1-1117

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool 1-1119

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime 1-1121

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration 1-1123

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool 1-1125

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection 1-1127

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema 1-1129

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections 1-1131

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} 1-1133

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes 1-1135

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} 1-1137

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-1140

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-1142

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources 1-1144

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-1146

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume 1-1148

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend 1-1150

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-1152

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-1154

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-1156

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume 1-1158

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll 1-1160

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend 1-1162

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll 1-1164

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime 1-1166

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime 1-1168

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-1170

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-1172

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime 1-1174

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes 1-1176

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} 1-1178

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-1180

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-1182

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-1184

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-1186

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resume 1-1188

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resumeAll 1-1190

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspend 1-1192

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspendAll 1-1194

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime 1-1196

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/getConfiguration 1-1198

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/getConnectionPool 1-1200

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/getInboundConnection 1-1202

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/getSchema 1-1204

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections 1-1206

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name} 1-1208

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes 1-1210

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} 1-1212

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-1214

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-1216

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources 1-1218

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-1220

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume 1-1222

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend 1-1224

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-1226

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-1228

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-1230

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/resume 1-1232

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/resumeAll 1-1234

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/suspend 1-1236

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/suspendAll 1-1238

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime 1-1240

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime 1-1242

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-1244

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-1246

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime 1-1248

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes 1-1250

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} 1-1252

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-1254

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-1256

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-1258

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-1260
 /management/weblogic/{version}/serverRuntime/connectorServiceRuntime/resume 1-1262
 /management/weblogic/{version}/serverRuntime/connectorServiceRuntime/resumeAll 1-1264
 /management/weblogic/{version}/serverRuntime/connectorServiceRuntime/suspend ... 1-1266

 /management/weblogic/{version}/serverRuntime/connectorServiceRuntime/suspendAll 1-1268
 /management/weblogic/{version}/serverRuntime/defaultExecuteQueueRuntime..... 1-1270
 /management/weblogic/{version}/serverRuntime/entityCacheCumulativeRuntime..... 1-1272
 /management/weblogic/{version}/serverRuntime/entityCacheCurrentStateRuntime 1-1274
 /management/weblogic/{version}/serverRuntime/entityCacheHistoricalRuntime 1-1276
 /management/weblogic/{version}/serverRuntime/executeQueueRuntimes 1-1278
 /management/weblogic/{version}/serverRuntime/executeQueueRuntimes/{name} 1-1280
 /management/weblogic/{version}/serverRuntime/forceShutdown 1-1282
 /management/weblogic/{version}/serverRuntime/forceShutdownResourceGroup 1-1284
 /management/weblogic/{version}/serverRuntime/forceSuspend 1-1286
 /management/weblogic/{version}/serverRuntime/forceSuspendResourceGroup 1-1288
 /management/weblogic/{version}/serverRuntime/getIPv4URL..... 1-1290
 /management/weblogic/{version}/serverRuntime/getIPv6URL..... 1-1292
 /management/weblogic/{version}/serverRuntime/getRgState 1-1294
 /management/weblogic/{version}/serverRuntime/getURL..... 1-1296
 /management/weblogic/{version}/serverRuntime/JDBCServiceRuntime 1-1298

 /management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans 1-1300

 /management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name} 1-1302

 /management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/clearStatementCache 1-1305

 /management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPool 1-1307

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPoolProfile 1-1309

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceShutdown 1-1311

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceSuspend 1-1313

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCDriverRuntime 1-1315

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean 1-1317

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/clearStatistics 1-1319

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/refreshStatistics
1-1321

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes
1-1323

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes
/{name} 1-1325

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes
/{name}/capacityRuntime 1-1327

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes
/{name}/maxThreadsConstraintRuntime 1-1329

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes
/{name}/minThreadsConstraintRuntime 1-1331

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes
/{name}/requestClassRuntime 1-1333

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/poolExists 1-1335

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/reset 1-1337

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/resume 1-1339

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/shrink 1-1341

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/shutdown 1-1343

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/start 1-1345

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/suspend 1-1347

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/testPool 1-1349

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes 1-1351

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} 1-1353

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime 1-1355

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-1357

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-1359

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-1361

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-1361

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-1361

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-1361

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans 1-1367

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name} 1-1369

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes 1-1371

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} 1-1373

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime 1-1375

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-1377

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-1379

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-1381

/management/weblogic/{version}/serverRuntime/JMSRuntime..... 1-1383

/management/weblogic/{version}/serverRuntime/JMSRuntime/connections 1-1385

/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name} 1-1387

/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/destroy 1-1389

/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions 1-1391

/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name} 1-1393

/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/consumers 1-1395

/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/consumers/{name} 1-1397

/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/producers 1-1399

/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/producers/{name} 1-1401

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers 1-1403

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name} 1-1405

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/closeCursor 1-1408

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations 1-1410

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name} 1-1412

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/closeCursor 1-1415

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/createDurableSubscriber 1-1417

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/deleteMessages 1-1419

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers 1-1421

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name} 1-1423

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/closeCursor 1-1426

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/deleteMessages 1-1428

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime 1-1430

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor 1-1433

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/createDurableSubscriber 1-1435

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessages
1-1437

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorEndPosition 1-1439

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSize
1-1441

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorPosition 1-1443

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages
1-1445

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsumption
1-1448

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertion
1-1450

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduction
1-1452

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsumption
1-1454

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInsertion
1-1456

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProduction
1-1458

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/sort 1-1460

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorEndPosition 1-1462

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorSize 1-1464

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorStartPosition 1-1466

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getMessages 1-1468

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/sort 1-1471

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorEndPosition 1-1473

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorSize 1-1475

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorStartPosition 1-1477

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/getMessages 1-1479

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseConsumption 1-1482

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseInsertion 1-1484

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseProduction 1-1486

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeConsumption 1-1488

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeInsertion 1-1490

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeProduction 1-1492

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/sort 1-1494

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/forceCommit 1-1496

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/for
ceRollback 1-1498

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/ge
tCursorPosition 1-1500

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/ge
tCursorSize 1-1502

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/ge
tCursorPosition 1-1504

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/ge
tMessages 1-1506

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/ge
tTransactionStatus 1-1508

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/lo
gRuntime 1-1510

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/lo
gRuntime/ensureLogOpened 1-1512

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/lo
gRuntime/flushLog 1-1514

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/lo
gRuntime/forceLogRotation 1-1516

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/pa
useConsumption 1-1518

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/pa
useInsertion 1-1520

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/pa
useProduction 1-1523

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/re
sumeConsumption 1-1525

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/re
sumeInsertion 1-1527

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/re
sumeProduction 1-1529

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes 1-1531

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name} 1-1533

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers 1-1535

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers/{name} 1-1537

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer 1-1539

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/closeCursor 1-1543

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations 1-1545

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name} 1-1547

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/closeCursor 1-1550

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/createDurableSubscriber 1-1552

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/deleteMessages 1-1554

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers 1-1556

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name} 1-1558

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/closeCursor 1-1561

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/deleteMessages 1-1563

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime 1-1565

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor 1-1569

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/createDurableSubscriber 1-1571

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessages 1-1573

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorEndPosition 1-1575

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSize 1-1577

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorStartPosition 1-1579

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages 1-1581

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsumption 1-1584

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertion 1-1586

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduction 1-1588

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsumption 1-1590

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInsertion 1-1592

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProduction 1-1594

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/sort 1-1596

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorEndPosition 1-1598

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorSize 1-1600

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorStartPosition 1-1602

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getMessages 1-1604

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/sort 1-1607

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorEndPosition 1-1609

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorSize 1-1611

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorStartPosition 1-1613

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getMessages 1-1615

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseConsumption 1-1618

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseInsertion 1-1620

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseProduction 1-1622

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeConsumption 1-1624

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeInsertion 1-1626

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeProduction 1-1628

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/sort 1-1630

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/forceCommit 1-1632

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/forceRollback 1-1634

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorEndPosition 1-1636

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorSize 1-1638

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorStartPosition 1-1640

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getMessages 1-1642

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getTransactionStatus 1-1644

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime 1-1646

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/ensureLogOpened 1-1648

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/flushLog 1-1650

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/forceLogRotation 1-1652

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseConsumption 1-1654

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseInsertion 1-1656

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseProduction 1-1659

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeConsumption 1-1661

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeInsertion 1-1663

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeProduction 1-1665

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/sort 1-1667

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sort 1-1669

/management/weblogic/{version}/serverRuntime/joltRuntime 1-1671

/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools 1-1673

/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name} 1-1675

/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}/connections 1-1677

/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}/connections/{name} 1-1679

/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}/resetConnectionPool 1-1681

/management/weblogic/{version}/serverRuntime/JTARuntime 1-1683

/management/weblogic/{version}/serverRuntime/JTARuntime/getRecoveryRuntimeMBean 1-1685

/management/weblogic/{version}/serverRuntime/JTARuntime/nonXAResourceRuntimeMBeans 1-1687

/management/weblogic/{version}/serverRuntime/JTARuntime/nonXAResourceRuntimeMBeans/{name} 1-1689

/management/weblogic/{version}/serverRuntime/JTARuntime/recoveryRuntimeMBeans 1-1691

/management/weblogic/{version}/serverRuntime/JTARuntime/recoveryRuntimeMBeans/{name} 1-1693

/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean 1-1695

/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean/connections 1-1697

/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean/connections/{name} 1-1699

/management/weblogic/{version}/serverRuntime/JTARuntime/transactionNameRuntimeMBeans 1-1701

/management/weblogic/{version}/serverRuntime/JTARuntime/transactionNameRuntimeMBeans/{name} 1-1703

/management/weblogic/{version}/serverRuntime/JTARuntime/transactionResourceRuntimeMBeans 1-1705

/management/weblogic/{version}/serverRuntime/JTARuntime/transactionResourceRuntimeMBeans/{name} 1-1707

/management/weblogic/{version}/serverRuntime/JVMRuntime..... 1-1709

/management/weblogic/{version}/serverRuntime/libraryRuntimes 1-1711

/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name} 1-1713

/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name}/referencingRuntimes 1-1715

/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name}/referencingRuntimes/{name} 1-1717

/management/weblogic/{version}/serverRuntime/logBroadcasterRuntime 1-1719

/management/weblogic/{version}/serverRuntime/mailSessionRuntimes 1-1721

/management/weblogic/{version}/serverRuntime/mailSessionRuntimes/{name} 1-1723

/management/weblogic/{version}/serverRuntime/MANASyncReplicationRuntime 1-1725

/management/weblogic/{version}/serverRuntime/MANReplicationRuntime..... 1-1727

/management/weblogic/{version}/serverRuntime/maxThreadsConstraintRuntimes 1-1729

/management/weblogic/{version}/serverRuntime/maxThreadsConstraintRuntimes/{name} 1-1731
 /management/weblogic/{version}/serverRuntime/messagingBridgeRuntimes.... 1-1733
 /management/weblogic/{version}/serverRuntime/messagingBridgeRuntimes/{name}.... 1-1735
 /management/weblogic/{version}/serverRuntime/minThreadsConstraintRuntimes 1-1737

 /management/weblogic/{version}/serverRuntime/minThreadsConstraintRuntimes/{name} 1-1739
 /management/weblogic/{version}/serverRuntime/partitionRuntimes..... 1-1741
 /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}.... 1-1743

 /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes 1-1747

 /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} 1-1749

 /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classLoaderRuntime 1-1753

 /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime 1-1755

 /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks 1-1757

 /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name} 1-1759

 /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/cancel 1-1761

 /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks 1-1763

 /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name} 1-1765

 /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/cancel 1-1767

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks 1-1769

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name} 1-1771

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name}/cancel 1-1773

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/redefineClasses 1-1775

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/coherenceClusterRuntime 1-1778

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes 1-1780

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name} 1-1782

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes 1-1784

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name} 1-1786

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime 1-1788

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-1790

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-1792

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-1794

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/getPersistenceUnitRuntime 1-1796

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/hasApplicationCache 1-1798

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes 1-1800

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name} 1-1802

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes 1-1804

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name} 1-1806

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes 1-1808

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name} 1-1810

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager 1-1812

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime 1-1814

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime 1-1816

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime 1-1818

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime 1-1820

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes 1-1822

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name} 1-1824

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager 1-1826

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime 1-1828

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime 1-1830

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime 1-1832

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime 1-1834

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedThreadFactoryRuntimes 1-1836

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedThreadFactoryRuntimes/{name} 1-1838

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/maxThreadsConstraintRuntimes 1-1840

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/maxThreadsConstraintRuntimes/{name} 1-1842

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/minThreadsConstraintRuntimes 1-1844

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/minThreadsConstraintRuntimes/{name} 1-1846

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes 1-1848

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name} 1-1850

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes 1-1852

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes/{name} 1-1854

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/persistenceUnitRuntimes 1-1856

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/persistenceUnitRuntimes/{name} 1-1858

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes 1-1860

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes/{name} 1-1862

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/reInitializeApplicationCachesAndPools 1-1864

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes 1-1866

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes/{name} 1-1868

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes 1-1870

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name} 1-1872

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime 1-1874

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-1876

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-1878

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-1880

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes 1-1882

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name} 1-1884

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/policyRuntime 1-1886

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports 1-1888

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} 1-1890

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/aggregatedBaseOperations 1-1893

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations 1-1895

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations/{name} 1-1897

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/clusterRouting 1-1899

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers 1-1901

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers/{name} 1-1903

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/mc 1-1905

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations 1-1907

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations/{name} 1-1909

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/portPolicy 1-1911

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/wsrm 1-1913

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/batchJobRepositoryRuntime 1-1915

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime 1-1917

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes 1-1919

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name} 1-1921

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager
1-1923

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime 1-1925

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime 1-1927

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime 1-1929

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime 1-1931

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes 1-1933

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name} 1-1935

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager 1-1937

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime 1-1939

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime 1-1941

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime 1-1943

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime 1-1945

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes 1-1947

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes/{name} 1-1949

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime 1-1951

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs 1-1954

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name} 1-1956

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools 1-1959

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} 1-1961

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections 1-1964

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} 1-1966

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete 1-1968

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-1970

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-1972

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened 1-1974

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog 1-1976

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation 1-1978

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset 1-1980

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime 1-1982

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOp
ened 1-1984

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog
1-1986

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotat
ion 1-1988

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset 1-1990

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool 1-1992

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime 1-1994

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/getInboundConnections
1-1997

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/getRA 1-1999

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs 1-2001

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}
1-2003

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/conn
ectionPools 1-2006

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/conn
ectionPools/{name} 1-2008

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/conn
ectionPools/{name}/connections 1-2011

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name} 1-2013

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete 1-2015

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-2017

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-2019

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened 1-2021

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog 1-2023

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation 1-2025

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset 1-2027

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime 1-2029

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-2031

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-2033

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-2035

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset 1-2037

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool 1-2039

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime 1-2041

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfig 1-2043

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool 1-2045

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection 1-2047

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema 1-2049

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections 1-2051

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} 1-2053

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes 1-2055

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} 1-2057

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-2060

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-2062

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources 1-2064

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-2066

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume 1-2068

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend 1-2070

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-2072

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-2074

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-2076

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume 1-2078

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll 1-2080

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend 1-2082

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll 1-2084

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime 1-2086

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime 1-2088

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-2090

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-2092

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime 1-2094

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes 1-2096

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} 1-2098

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-2100

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-2102

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-2104

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-2106

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs 1-2108

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name} 1-2110

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools 1-2113

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} 1-2115

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections 1-2118

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} 1-2120

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete 1-2122

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-2124

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-2126

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened 1-2128

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog 1-2130

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation 1-2132

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset 1-2134

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime 1-2136

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-2138

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-2140

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-2142

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset 1-2144

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool 1-2146

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime 1-2148

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration 1-2150

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool 1-2152

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection 1-2154

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getSchema 1-2156

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections 1-2158

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name} 1-2160

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes 1-2162

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} 1-2164

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-2167

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-2169

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources 1-2171

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-2173

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume 1-2175

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend 1-2177

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-2179

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-2181

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-2183

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resume 1-2185

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resumeAll
1-2187

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspend
1-2189

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspendAll
1-2191

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime 1-2193

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime 1-2195

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-2197

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-2199

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime 1-2201

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes 1-2203

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} 1-2205

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-2207

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-2209

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-2211

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-2213

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/resume 1-2215

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/resumeAll 1-2217

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/suspend 1-2219

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/suspendAll 1-2221

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime 1-2223

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration 1-2225

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool 1-2227

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection 1-2229

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema 1-2231

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections 1-2233

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} 1-2235

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes 1-2237

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} 1-2239

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name
}/poolRuntime 1-2242

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name
}/poolRuntime/initializePool 1-2244

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name
}/resources 1-2246

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name
}/resources/{name} 1-2248

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name
}/resume 1-2250

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name
}/suspend 1-2252

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name
}/timerRuntime 1-2254

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name
}/timerRuntime/activateDisabledTimers 1-2256

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name
}/transactionRuntime 1-2258

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/resume 1-2260

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/resumeAll 1-2262

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/suspend 1-2264

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/suspendAll 1-2266

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/workManagerRuntime 1-2268

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime 1-2270

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRun-
time 1-2272

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRun-
time 1-2274

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRun-
time 1-2276

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/workManagerRuntimes 1-2278

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} 1-2280

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRun-
time 1-2282

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstr-
aintRuntime 1-2284

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstra-
intRuntime 1-2286

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRun-
time 1-2288

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/getInboundConnections 1-2290

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/getRA 1-2292

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs 1-2294

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name} 1-2296

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectionPools 1-2299

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectionPools/{name} 1-2301

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections 1-2304

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}
1-2306

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/del
ete 1-2308

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/has
Error 1-2310

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/test
Connection 1-2312

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened
1-2314

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog 1-2316

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation
1-2318

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset 1-2320

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime 1-2322

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogO
pened 1-2324

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-2326

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-2328

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset 1-2330

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool 1-2332

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime 1-2334

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs 1-2337

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} 1-2339

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools 1-2342

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} 1-2344

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections 1-2347

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} 1-2349

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete 1-2351

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-2353

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-2355

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened 1-2357

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog 1-2359

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation 1-2361

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset 1-2363

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime 1-2365

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-2367

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-2369

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-2371

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset 1-2373

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool 1-2375

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime 1-2377

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration 1-2379

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool 1-2381

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection 1-2383

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema 1-2385

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections 1-2387

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} 1-2389

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes 1-2391

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} 1-2393

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-2396

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-2398

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources 1-2400

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-2402

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume 1-2404

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend 1-2406

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-2408

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-2410

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-2412

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume 1-2414

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll 1-2416

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend 1-2418

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll 1-2420

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime 1-2422

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime 1-2424

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-2426

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-2428

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime 1-2430

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes 1-2432

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} 1-2434

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-2436

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-2438

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-2440

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-2442

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getInboundConnections 1-2444

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getRA 1-2446

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs 1-2448

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} 1-2450

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools 1-2453

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionsPools/{name} 1-2455

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionsPools/{name}/connections 1-2458

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionsPools/{name}/connections/{name} 1-2460

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionsPools/{name}/connections/{name}/delete 1-2462

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionsPools/{name}/connections/{name}/hasError 1-2464

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionsPools/{name}/connections/{name}/testConnection 1-2466

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionsPools/{name}/ensureLogOpened 1-2468

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionsPools/{name}/flushLog 1-2470

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionsPools/{name}/forceLogRotation 1-2472

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionsPools/{name}/forceReset 1-2474

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionsPools/{name}/logRuntime 1-2476

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionsPools/{name}/logRuntime/ensureLogOpened 1-2478

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-2480

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-2482

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset 1-2484

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool 1-2486

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime 1-2488

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration 1-2490

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool 1-2492

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection 1-2494

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getSchema 1-2496

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections 1-2498

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name} 1-2500

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes 1-2502

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} 1-2504

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-2507

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-2509

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources 1-2511

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-2513

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume 1-2515

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend 1-2517

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-2519

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers
1-2521

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-2523

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/resume
1-2525

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/resumeAll
1-2527

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/suspend 1-2529

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/suspendAll 1-2531

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime 1-2533

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime 1-2535

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-2537

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-2539

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime 1-2541

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes 1-2543

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} 1-2545

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-2547

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-2549

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-2551

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-2553

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resume 1-2555

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resumeAll 1-2557

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspend 1-2559

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspendAll 1-2561

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime 1-2563

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration 1-2565

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool 1-2567

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection 1-2569

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema 1-2571

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections 1-2573

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} 1-2575

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes 1-2577

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} 1-2579

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-2582

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{na
me}/poolRuntime/initializePool 1-2584

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{na
me}/resources 1-2586

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{na
me}/resources/{name} 1-2588

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{na
me}/resume 1-2590

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{na
me}/suspend 1-2592

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{na
me}/timerRuntime 1-2594

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{na
me}/timerRuntime/activateDisabledTimers 1-2596

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{na
me}/transactionRuntime 1-2598

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/resume 1-2600

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/resumeAll 1-2602

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/suspend 1-2604

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/suspendAll 1-2606

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/workManagerRuntime 1-2608

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime 1-2610

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRun
time 1-2612

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRun
time 1-2614

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime
1-2616

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/workManagerRuntimes 1-2618

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} 1-2620

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime
1-2622

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsCons
traintRuntime 1-2624

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConst
raintRuntime 1-2626

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRunt
ime 1-2628

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs 1-2630

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name} 1-2632

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectionPools 1-2635

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectionPools/{name} 1-2637

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectionPools/{name}/connections 1-2640

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} 1-2642

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete
1-2644

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError
1-2646

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnect
ion 1-2648

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened 1-2650

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog 1-2652

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation 1-2654

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset 1-2656

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime 1-2658

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened
1-2660

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-2662

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation
1-2664

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectionPools/{name}/reset 1-2666

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectionPools/{name}/testPool 1-2668

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectorServiceRuntime 1-2670

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs 1-2673

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} 1-2675

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools 1-2678

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} 1-2680

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections 1-2683

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} 1-2685

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete 1-2687

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-2689

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-2691

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened 1-2693

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog 1-2695

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation 1-2697

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset 1-2699

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime 1-2701

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-2703

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-2705

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-2707

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset 1-2709

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool 1-2711

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime 1-2713

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration 1-2715

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool 1-2717

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection 1-2719

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema 1-2721

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections 1-2723

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} 1-2725

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes 1-2727

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} 1-2729

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-2732

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-2734

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources 1-2736

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-2738

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume 1-2740

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend 1-2742

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-2744

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-2746

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-2748

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume
1-2750

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll
1-2752

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend
1-2754

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll
1-2756

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManag
erRuntime 1-2758

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManag
erRuntime/capacityRuntime 1-2760

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManag
erRuntime/maxThreadsConstraintRuntime 1-2762

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManag
erRuntime/minThreadsConstraintRuntime 1-2764

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManag
erRuntime/requestClassRuntime 1-2766

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManag
erRuntimes 1-2768

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManag
erRuntimes/{name} 1-2770

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManag
erRuntimes/{name}/capacityRuntime 1-2772

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-2774

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-2776

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-2778

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getInboundConnections 1-2780

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getRA 1-2782

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs 1-2784

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} 1-2786

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools 1-2789

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} 1-2791

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections 1-2794

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name} 1-2796

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete 1-2798

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-2800

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connections/{name}/testConnection 1-2802

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connections/{name}/ensureLogOpened 1-2804

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connections/{name}/flushLog 1-2806

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connections/{name}/forceLogRotation 1-2808

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connections/{name}/forceReset 1-2810

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connections/{name}/logRuntime 1-2812

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connections/{name}/logRuntime/ensureLogOpened 1-2814

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connections/{name}/logRuntime/flushLog 1-2816

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connections/{name}/logRuntime/forceLogRotation 1-2818

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connections/{name}/reset 1-2820

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connections/{name}/testPool 1-2822

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime 1-2824

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration 1-2826

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool 1-2828

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection 1-2830

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema 1-2832

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections 1-2834

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} 1-2836

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes 1-2838

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} 1-2840

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-2843

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-2845

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources 1-2847

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-2849

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume 1-2851

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend 1-2853

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-2855

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-2857

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-2859

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume 1-2861

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll 1-2863

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend 1-2865

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll 1-2867

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime 1-2869

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime 1-2871

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-2873

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-2875

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime 1-2877

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes 1-2879

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} 1-2881

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-2883

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-2885

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-2887

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-2889

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resume 1-2891

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resumeAll 1-2893

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspend 1-2895

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspendAll 1-2897

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime 1-2899

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration 1-2901

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/getConnectionPool 1-2903

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/getInboundConnection 1-2905

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/getSchema 1-2907

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/inboundConnections 1-2909

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/inboundConnections/{name} 1-2911

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes 1-2913

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}
1-2915

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poo
lRuntime 1-2918

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poo
lRuntime/initializePool 1-2920

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/reso
urces 1-2922

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/reso
urces/{name} 1-2924

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resu
me 1-2926

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/sus
pend 1-2928

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/tim
erRuntime 1-2930

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/tim
erRuntime/activateDisabledTimers 1-2932

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/tran
sactionRuntime 1-2934

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/resume 1-2936

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/resumeAll 1-2938

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/suspend 1-2940

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/suspendAll 1-2942

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/workManagerRuntime 1-2944

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime 1-2946

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime
1-2948

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime
1-2950

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime 1-2952

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/workManagerRuntimes 1-2954

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/workManagerRuntimes/{name} 1-2956

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-2958

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRu
ntime 1-2960

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRu
ntime 1-2962

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime
1-2964

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/resume 1-2966

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/resumeAll 1-2968

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/suspend 1-2970

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/suspendAll 1-2972

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceShut
down 1-2974

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceShut
downResourceGroup 1-2976

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceSusp
end 1-2978

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceSusp
endResourceGroup 1-2980

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/getRgStat
e 1-2982

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPart
itionRuntime 1-2984

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPart
itionRuntime/JDBCDataSourceRuntimeMBeans 1-2986

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPart
itionRuntime/JDBCDataSourceRuntimeMBeans/{name} 1-2988

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPart
itionRuntime/JDBCDataSourceRuntimeMBeans/{name}/clearStatementCache 1-2991

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPart
itionRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPool 1-2993

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPoolProfile 1-2995

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceShutdown 1-2997

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceSuspend 1-2999

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCDriverRuntime 1-3001

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean 1-3003

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/clearStatistics 1-3005

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/refreshStatistics 1-3007

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes 1-3009

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name} 1-3011

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/capacityRuntime 1-3013

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-3015

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-3017

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/requestClassRuntime 1-3019

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/poolExists 1-3021

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/reset 1-3023

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/resume 1-3025

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/shrink 1-3027

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/shutdown 1-3029

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/start 1-3031

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/suspend 1-3033

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/testPool 1-3035

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes 1-3037

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} 1-3039

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime 1-3041

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-3043

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-3045

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-3047

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans 1-3049

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name} 1-3051

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes 1-3053

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} 1-3055

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime 1-3057

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-3059

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-3061

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-3063

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime 1-3065

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections 1-3067

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name} 1-3069

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/destroy 1-3071

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions 1-3073

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name} 1-3075

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers 1-3077

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers/{name} 1-3079

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/producers 1-3081

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/producers/{name} 1-3083

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers 1-3085

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name} 1-3087

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/closeCursor 1-3090

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations 1-3092

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name} 1-3094

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/closeCursor 1-3097

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/createDurableSubscriber 1-3099

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/deleteMessages 1-3101

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers 1-3103

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name} 1-3105

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/closeCursor 1-3108

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/deleteMessages 1-3110

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime 1-3112

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor 1-3115

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/createDurableSubscriber 1-3117

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessages 1-3119

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorEndPosition 1-3121

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSize 1-3123

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorStartPosition 1-3125

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages 1-3127

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsumption 1-3130

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertion 1-3132

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduction 1-3134

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsumption 1-3136

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInsertion 1-3138

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProduction 1-3140

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/sort 1-3142

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorPosition 1-3144

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorSize 1-3146

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorStartPosition 1-3148

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getMessages 1-3150

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/sort 1-3153

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/getCursorPosition 1-3155

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/getCursorSize 1-3157

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/getCursorStartPosition 1-3159

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/getMessages 1-3161

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/pauseConsumption 1-3164

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/pauseInsertion 1-3166

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseProduction 1-3168

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeConsumption 1-3170

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeInsertion 1-3172

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeProduction 1-3174

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/sort 1-3176

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/forceCommit 1-3178

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/forceRollback 1-3180

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/getCursorEndPosition 1-3182

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/getCursorSize 1-3184

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/getCursorStartPosition 1-3186

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/getMessages 1-3188

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/getTransactionStatus 1-3190

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime 1-3192

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime/ensureLogOpened 1-3194

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime/flushLog 1-3196

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime/forceLogRotation 1-3198

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/pauseConsumption 1-3200

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/pauseInsertion 1-3202

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/pauseProduction 1-3205

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/resumeConsumption 1-3207

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/resumeInsertion 1-3209

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/resumeProduction 1-3211

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes 1-3213

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name} 1-3215

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers 1-3217

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers/{name} 1-3219

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer 1-3221

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/closeCursor 1-3225

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations 1-3227

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name} 1-3229

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/closeCursor 1-3232

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/createDurableSubscriber 1-3234

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/deleteMessages 1-3236

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers 1-3238

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name} 1-3240

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/closeCursor 1-3243

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/deleteMessages 1-3245

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime 1-3247

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor 1-3251

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/createDurableSubscriber 1-3253

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessages 1-3255

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorEndPosition 1-3257

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSize 1-3259

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorStartPosition 1-3261

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages 1-3263

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsumption 1-3266

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertion 1-3268

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduction 1-3270

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsumption 1-3272

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInsertion 1-3274

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProduction 1-3276

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/sort 1-3278

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorEndPosition 1-3280

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorSize 1-3282

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorStartPosition 1-3284

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getMessages 1-3286

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/sort 1-3289

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorEndPosition 1-3291

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorSize 1-3293

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorStartPosition 1-3295

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getMessages 1-3297

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseConsumption 1-3300

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseInsertion 1-3302

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseProduction 1-3304

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeConsumption 1-3306

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeInsertion 1-3308

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeProduction 1-3310

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/sort 1-3312

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/forceCommit 1-3314

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/forceRollback 1-3316

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorEndPosition 1-3318

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorSize 1-3320

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorStartPosition 1-3322

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getMessages 1-3324

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getTransactionStatus 1-3326

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime 1-3328

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/ensureLogOpened 1-3330

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/flushLog 1-3332

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/forceLogRotation 1-3334

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseConsumption 1-3336

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseInsertion
1-3338

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseProduction
1-3341

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeConsumption
1-3343

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeInsertion
1-3345

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeProduction
1-3347

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/sort 1-3349

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sort 1-3351

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime 1-3353

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans 1-3355

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans/{name} 1-3357

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans 1-3359

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans/{name} 1-3361

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans 1-3363

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans/{name} 1-3365

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes 1-3367

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name} 1-3369

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes 1-3371

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name} 1-3373

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes 1-3375

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes/{name} 1-3377

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes 1-3379

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes/{name} 1-3381

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes 1-3383

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes/{name} 1-3385

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes 1-3387

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes/{name} 1-3389

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionResourceMetricsRuntime 1-3391

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime 1-3393

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/fairShareRuntime 1-3395

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/maxThreadsConstraintRuntime 1-3397

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/minThreadsConstraintCapRuntime 1-3399

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes 1-3401

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name} 1-3403

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies 1-3405

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name} 1-3407

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/closeCursor 1-3409

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getCursorEndPosition 1-3411

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getCursorSize 1-3413

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getCursorStartPosition 1-3415

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getMapEntries 1-3417

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/remove 1-3419

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes 1-3421

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name} 1-3423

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections 1-3425

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections/{name} 1-3427

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes 1-3429

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes/{name} 1-3431

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resource
ManagerRuntime 1-3433

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resource
ManagerRuntime/resourceRuntimes 1-3435

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resource
ManagerRuntime/resourceRuntimes/{name} 1-3437

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resource
ManagerRuntime/resourceRuntimes/{name}/fairShareConstraintRuntime 1-3439

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resource
ManagerRuntime/resourceRuntimes/{name}/triggerRuntimes 1-3441

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resource
ManagerRuntime/resourceRuntimes/{name}/triggerRuntimes/{name} 1-3443

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resume ...
1-3445

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resumeRe
sourceGroup 1-3447

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRunti
me 1-3449

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRunti
me/agents 1-3451

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRunti
me/agents/{name} 1-3453

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRunti
me/agents/{name}/conversations 1-3456

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRunti
me/agents/{name}/conversations/{name} 1-3458

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRunti
me/agents/{name}/conversations/{name}/destroy 1-3460

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRunti
me/agents/{name}/logRuntime 1-3462

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRunti
me/agents/{name}/logRuntime/ensureLogOpened 1-3464

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRunti
me/agents/{name}/logRuntime/flushLog 1-3466

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime/forceLogRotation 1-3468

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/pauseForwarding 1-3470

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/pauseIncoming 1-3472

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/pauseReceiving 1-3474

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints 1-3476

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name} 1-3478

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/closeCursor 1-3481

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/expireAll 1-3483

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorEndPosition 1-3485

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorSize 1-3487

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorStartPosition 1-3489

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getMessages 1-3491

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/pauseForwarding 1-3493

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/pauseIncoming 1-3495

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/purge 1-3497

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/resumeForwarding 1-3499

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/resumeIncoming 1-3501

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/sort 1-3503

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/resumeForwarding 1-3505

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/resumeIncoming 1-3507

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/resumeReceiving 1-3509

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/shutdown 1-3511

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/shutdownResourceGroup 1-3514

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/startResourceGroup 1-3517

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/startResourceGroupInAdmin 1-3519

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/suspend.. 1-3521

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/suspendResourceGroup 1-3523

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime 1-3526

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime 1-3528

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes 1-3530

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name} 1-3532

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/closeCursor 1-3534

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/deleteDataRecords 1-3536

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/getDataRecordCount 1-3538

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/hasMoreData 1-3541

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/openCursor 1-3543

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/lookupWLDFDataAccessRuntime 1-3548

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes 1-3550

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes/{name} 1-3552

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes/{name}/closeArchive 1-3554

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionHarvesterRuntime 1-3556

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime 1-3558

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/captureImage 1-3560

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/clearCompletedImageCaptureTasks 1-3562

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks 1-3564

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name} 1-3566

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/cancel
1-3568

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks
1-3570

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}
1-3572

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/cancel
1-3574

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks
1-3576

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}
1-3578

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}/cancel
1-3580

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/purgeCapturedImages
1-3582

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/resetImageLockout
1-3584

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime
1-3586

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime/resetWatchAlarm
1-3588

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime/WLDFWatchJMXNotificationSource
1-3590

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes
1-3592

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}
1-3594

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime 1-3596

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-3598

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-3600

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-3602

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime 1-3604

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime/clusterRouting 1-3606

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes 1-3608
/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}.....
1-3610

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies 1-3612

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name} 1-3614

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/closeCursor 1-3616

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/getCursorEndPosition 1-3618

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/getCursorSize 1-3620

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/getCursorStartPosition 1-3622

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/getMapEntries 1-3624

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/remove 1-3626

/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes..... 1-3628

/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}.....
1-3630

/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}/connections 1-3632

/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}/connections/{name} 1-3634

/management/weblogic/{version}/serverRuntime/requestClassRuntimes..... 1-3636

/management/weblogic/{version}/serverRuntime/requestClassRuntimes/{name} 1-3638

/management/weblogic/{version}/serverRuntime/restartSSLChannels..... 1-3640

/management/weblogic/{version}/serverRuntime/resume 1-3642

/management/weblogic/{version}/serverRuntime/resumeResourceGroup 1-3644

/management/weblogic/{version}/serverRuntime/SAFRuntime 1-3646

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents..... 1-3648

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name} 1-3650

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/conversations 1-3653

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/conversations/{name} 1-3655

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/conversations/{name}/destroy 1-3657

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/logRuntime 1-3659

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/logRuntime/ensureLogOpened 1-3661

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/logRuntime/flushLog 1-3663

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/logRuntime/forceLogRotation 1-3665

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/pauseForwarding 1-3667

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/pauseIncoming 1-3669

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/pauseReceiving 1-3671

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints 1-3673

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remote
Endpoints/{name} 1-3675

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remote
Endpoints/{name}/closeCursor 1-3678

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remote
Endpoints/{name}/expireAll 1-3680

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remote
Endpoints/{name}/getCursorEndPosition 1-3682

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remote
Endpoints/{name}/getCursorSize 1-3684

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remote
Endpoints/{name}/getCursorStartPosition 1-3686

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remote
Endpoints/{name}/getMessages 1-3688

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remote
Endpoints/{name}/pauseForwarding 1-3690

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remote
Endpoints/{name}/pauseIncoming 1-3692

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remote
Endpoints/{name}/purge 1-3694

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remote
Endpoints/{name}/resumeForwarding 1-3696

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remote
Endpoints/{name}/resumeIncoming 1-3698

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remote
Endpoints/{name}/sort 1-3700

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/resume
Forwarding 1-3702

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/resume
Incoming 1-3704

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/resume
Receiving 1-3706

/management/weblogic/{version}/serverRuntime/search..... 1-3708

/management/weblogic/{version}/serverRuntime/serverChannelRuntimes 1-3710
 /management/weblogic/{version}/serverRuntime/serverChannelRuntimes/{name}
 1-3712
 /management/weblogic/{version}/serverRuntime/serverLogRuntime 1-3714

 /management/weblogic/{version}/serverRuntime/serverLogRuntime/ensureLogOpene
 d 1-3716
 /management/weblogic/{version}/serverRuntime/serverLogRuntime/flushLog 1-3718
 /management/weblogic/{version}/serverRuntime/serverLogRuntime/forceLogRotation
 1-3720
 /management/weblogic/{version}/serverRuntime/serverSecurityRuntime 1-3722

 /management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealm
 Runtime 1-3724

 /management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealm
 Runtime/authenticatorRuntimes 1-3726

 /management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealm
 Runtime/authenticatorRuntimes/{name} 1-3728

 /management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealm
 Runtime/userLockoutManagerRuntime 1-3730

 /management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealm
 Runtime/userLockoutManagerRuntime/clearLockout 1-3732

 /management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealm
 Runtime/userLockoutManagerRuntime/getLastLoginFailure 1-3734

 /management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealm
 Runtime/userLockoutManagerRuntime/getLoginFailureCount 1-3736

 /management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealm
 Runtime/userLockoutManagerRuntime/isLockedOut 1-3738

 /management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntim
 es 1-3740

 /management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntim
 es/{name} 1-3742

 /management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntim
 es/{name}/authenticatorRuntimes 1-3744

 /management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntim
 es/{name}/authenticatorRuntimes/{name} 1-3746

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntime/{name}/userLockoutManagerRuntime 1-3748

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntime/{name}/userLockoutManagerRuntime/clearLockout 1-3750

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntime/{name}/userLockoutManagerRuntime/getLastLoginFailure 1-3752

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntime/{name}/userLockoutManagerRuntime/getLoginFailureCount 1-3754

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntime/{name}/userLockoutManagerRuntime/isLockedOut 1-3756

/management/weblogic/{version}/serverRuntime/shutdown 1-3758

/management/weblogic/{version}/serverRuntime/shutdownResourceGroup 1-3761

/management/weblogic/{version}/serverRuntime/singleSignOnServicesRuntime.....
1-3764

/management/weblogic/{version}/serverRuntime/singleSignOnServicesRuntime/publish 1-3766

/management/weblogic/{version}/serverRuntime/SNMPAgentRuntime 1-3768

/management/weblogic/{version}/serverRuntime/SNMPAgentRuntime/invalidateLocalizedKeyCache 1-3770

/management/weblogic/{version}/serverRuntime/SNMPAgentRuntime/outputCustomMBeansMIBModule 1-3772

/management/weblogic/{version}/serverRuntime/startPartition..... 1-3774

/management/weblogic/{version}/serverRuntime/startPartitionInAdmin..... 1-3776

/management/weblogic/{version}/serverRuntime/startResourceGroup..... 1-3778

/management/weblogic/{version}/serverRuntime/startResourceGroupInAdmin 1-3780

/management/weblogic/{version}/serverRuntime/suspend 1-3782

/management/weblogic/{version}/serverRuntime/suspendResourceGroup..... 1-3784

/management/weblogic/{version}/serverRuntime/threadPoolRuntime 1-3787

/management/weblogic/{version}/serverRuntime/timerRuntime 1-3789

/management/weblogic/{version}/serverRuntime/WANReplicationRuntime 1-3791

/management/weblogic/{version}/serverRuntime/WANReplicationRuntime/cleanupExpiredSessionsInTheDatabase 1-3793

/management/weblogic/{version}/serverRuntime/webServerRuntimes 1-3795

/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}. 1-3797

/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}/logRuntime 1-3799

/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}/logRuntime/ensureLogOpened 1-3801

/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}/logRuntime/flushLog 1-3803

/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}/logRuntime/forceLogRotation 1-3805

/management/weblogic/{version}/serverRuntime/WLDFRuntime 1-3807

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime 1-3809

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes 1-3811

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name} 1-3813

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/closeCursor 1-3815

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/deleteDataRecords 1-3817

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/getDataRecordCount 1-3819

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/hasMoreData 1-3822

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/openCursor 1-3824

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/lookupWLDFDataAccessRuntime 1-3829

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/WLDFDataAccessRuntimes 1-3831

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/WLDFDataAccessRuntimes/{name} 1-3833

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/WLDFDataAccessRuntimes/{name}/closeArchive 1-3835

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFArchiveRuntimes 1-3837

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFArchiveRuntimes/{name} 1-3839

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime 1-3841

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls 1-3843

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name} 1-3845

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}/harvesterManagerRuntime 1-3847

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}/watchManagerRuntime 1-3849

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}/watchManagerRuntime/resetWatchAlarm 1-3851

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime 1-3853

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/activateDebugPatch 1-3855

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/clearDebugPatchTasks 1-3857

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/deactivateAllDebugPatches 1-3859

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/deactivateDebugPatches 1-3861

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks 1-3863

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name} 1-3865

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/cancel 1-3867

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks 1-3869

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatches
Runtime/debugPatchTasks/{name}/subTasks/{name} 1-3871

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatches
Runtime/debugPatchTasks/{name}/subTasks/{name}/cancel 1-3873

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatches
Runtime/debugPatchTasks/{name}/subTasks/{name}/subTasks 1-3875

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatches
Runtime/debugPatchTasks/{name}/subTasks/{name}/subTasks/{name} 1-3877

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatches
Runtime/debugPatchTasks/{name}/subTasks/{name}/subTasks/{name}/cancel 1-3879

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatches
Runtime/showDebugPatchInfo 1-3881

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFHarvesterRunt
ime 1-3883

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime
1-3885

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime
/captureImage 1-3887

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime
/clearCompletedImageCaptureTasks 1-3891

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime
/imageCaptureTasks 1-3893

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime
/imageCaptureTasks/{name} 1-3895

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime
/imageCaptureTasks/{name}/cancel 1-3897

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime
/imageCaptureTasks/{name}/subTasks 1-3899

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime
/imageCaptureTasks/{name}/subTasks/{name} 1-3901

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime
/imageCaptureTasks/{name}/subTasks/{name}/cancel 1-3903

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime
/imageCaptureTasks/{name}/subTasks/{name}/subTasks 1-3905

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime
/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name} 1-3907

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime
/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}/cancel 1-3909

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime
/purgeCapturedImages 1-3911

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime
/resetImageLockout 1-3913

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentati
onRuntimes 1-3915

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentati
onRuntimes/{name} 1-3917

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentati
onRuntimes/{name}/resetMethodInvocationStatisticsData 1-3919

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentati
onRuntimes/{name}/resetMethodMemoryAllocationStatisticsData 1-3921

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFWatchNotifica
tionRuntime 1-3923

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFWatchNotifica
tionRuntime/resetWatchAlarm 1-3925

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFWatchNotifica
tionRuntime/WLDFWatchJMXNotificationSource 1-3927

/management/weblogic/{version}/serverRuntime/workManagerRuntimes 1-3929

/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}
1-3931

/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/cap
acityRuntime 1-3933

/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/max
ThreadsConstraintRuntime 1-3935

/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/min
ThreadsConstraintRuntime 1-3937

/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/requ
estClassRuntime 1-3939

/management/weblogic/{version}/serverRuntime/wseeClusterFrontEndRuntime
 1-3941

/management/weblogic/{version}/serverRuntime/wseeClusterFrontEndRuntime/cluste
 rRouting 1-3943

/management/weblogic/{version}/serverRuntime/wseeWsruntime 1-3945

/management/weblogic/{version}/serverRuntime/WTCRuntime..... 1-3947

/management/weblogic/{version}/serverRuntime/WTCRuntime/getServiceStatus
 1-3949

/management/weblogic/{version}/serverRuntime/WTCRuntime/resumeService
 1-3953

/management/weblogic/{version}/serverRuntime/WTCRuntime/startConnection
 1-3957

/management/weblogic/{version}/serverRuntime/WTCRuntime/stopConnection
 1-3959

/management/weblogic/{version}/serverRuntime/WTCRuntime/suspendService.....
 1-3961

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntime
 MBean 1-3965

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntime
 MBean/getInboundFailReqTotalCount 1-3968

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntime
 MBean/getInboundMessageTotalCount 1-3970

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntime
 MBean/getInboundNWMMessageTotalSize 1-3973

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntime
 MBean/getInboundSuccessReqTotalCount 1-3976

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntime
 MBean/getInTransactionCommittedTotalCount 1-3978

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntime
 MBean/getInTransactionRolledBackTotalCount 1-3980

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntime
 MBean/getOutboundFailReqTotalCount 1-3982

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntime
 MBean/getOutboundMessageTotalCount 1-3984

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntime
 MBean/getOutboundNWMMessageTotalSize 1-3987

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntime
MBean/getOutboundSuccessReqTotalCount 1-3990

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntime
MBean/getOutstandingNWReqCount 1-3992

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntime
MBean/getOutTransactionCommittedTotalCount 1-3995

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntime
MBean/getOutTransactionRolledBackTotalCount 1-3997

2 Entities

[3]	com.bea.wls.redef.runtime.ClassRedefinitionRuntimeMBean	2-1
[3]	com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean	2-2
[3]	java.lang.Throwable	2-3
[3]	java.util.Date	2-4
[3]	java.util.Properties	2-4
[3]	weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean	2-4
[3]	weblogic.health.HealthState	2-5
n	weblogic.health.Symptom	2-5
n	weblogic.management.rest.bean.model.CurrentUser	2-6
n	weblogic.management.rest.bean.model.Version	2-6
n	weblogic.management.runtime.ApplicationRuntimeMBean	2-7
n	weblogic.management.runtime.AsyncReplicationRuntimeMBean	2-8
n	weblogic.management.runtime.AuthenticatorRuntimeMBean	2-9
n	weblogic.management.runtime.BatchJobRepositoryRuntimeMBean	2-10
n	weblogic.management.runtime.CapacityRuntimeMBean	2-10
n	weblogic.management.runtime.ClassLoaderRuntimeMBean	2-11
n	weblogic.management.runtime.ClusterRuntimeMBean	2-13
n	weblogic.management.runtime.CoherenceClusterRuntimeMBean	2-16
n	weblogic.management.runtime.ComponentRuntimeMBean	2-16
n	weblogic.management.runtime.ConcurrentManagedObjectsRuntimeMBean	2-17
n	weblogic.management.runtime.ConnectorComponentRuntimeMBean	2-18
n	weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean	2-22
n	weblogic.management.runtime.ConnectorConnectionRuntimeMBean	2-27
n	weblogic.management.runtime.ConnectorInboundRuntimeMBean	2-30
n	weblogic.management.runtime.ConnectorServiceRuntimeMBean	2-30
n	weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean	2-31
n	weblogic.management.runtime.EJBPoolRuntimeMBean	2-32
n	weblogic.management.runtime.EJBTimerRuntimeMBean	2-33
n	weblogic.management.runtime.EJBTransactionRuntimeMBean	2-34
n	weblogic.management.runtime.EntityCacheCumulativeRuntimeMBean	2-34
n	weblogic.management.runtime.EntityCacheCurrentStateRuntimeMBean	2-38
n	weblogic.management.runtime.ExecuteQueueRuntimeMBean	2-41
n	weblogic.management.runtime.FairShareConstraintRuntimeMBean	2-42

n	weblogic.management.runtime.JDBCDataSourceRuntimeMBean	2-42
n	weblogic.management.runtime.JDBCDriverRuntimeMBean	2-48
n	weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean	2-49
n	weblogic.management.runtime.JDBCPartitionRuntimeMBean	2-50
n	weblogic.management.runtime.JDBCReplayStatisticsRuntimeMBean	2-50
n	weblogic.management.runtime.JDBCServiceRuntimeMBean	2-52
n	weblogic.management.runtime.JMSConnectionRuntimeMBean	2-53
n	weblogic.management.runtime.JMSConsumerRuntimeMBean	2-54
n	weblogic.management.runtime.JMSDestinationRuntimeMBean	2-56
n	weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean	2-59
n	weblogic.management.runtime.JMSProducerRuntimeMBean	2-61
n	weblogic.management.runtime.JMSRuntimeMBean	2-62
n	weblogic.management.runtime.JMSServerRuntimeMBean	2-63
n	weblogic.management.runtime.JMSSessionPoolRuntimeMBean	2-67
n	weblogic.management.runtime.JMSSessionRuntimeMBean	2-68
n	weblogic.management.runtime.JTAPartitionRuntimeMBean	2-70
n	weblogic.management.runtime.JTARecoveryRuntimeMBean	2-73
n	weblogic.management.runtime.JTARuntimeMBean	2-74
n	weblogic.management.runtime.JVMRuntimeMBean	2-77
n	weblogic.management.runtime.JobRuntimeMBean	2-78
n	weblogic.management.runtime.JobSchedulerRuntimeMBean	2-80
n	weblogic.management.runtime.JoltConnectionPoolRuntimeMBean	2-80
n	weblogic.management.runtime.JoltConnectionRuntimeMBean	2-81
n	weblogic.management.runtime.JoltConnectionServiceRuntimeMBean	2-82
n	weblogic.management.runtime.LibraryRuntimeMBean	2-82
n	weblogic.management.runtime.LogBroadcasterRuntimeMBean	2-83
n	weblogic.management.runtime.LogRuntimeMBean	2-84
n	weblogic.management.runtime.MANAsyncReplicationRuntimeMBean	2-84
n	weblogic.management.runtime.MANReplicationRuntimeMBean	2-86
n	weblogic.management.runtime.MailSessionRuntimeMBean	2-87
n	weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean	2-87
n	weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean	2-89
n	weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean	2-90
n	weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean	2-91
n	weblogic.management.runtime.MessageDrivenEJBRuntimeMBean	2-92
n	weblogic.management.runtime.MessagingBridgeRuntimeMBean	2-94
n	weblogic.management.runtime.MigrationDataRuntimeMBean	2-94
n	weblogic.management.runtime.MinThreadsConstraintRuntimeMBean	2-96
n	weblogic.management.runtime.NonXAResourceRuntimeMBean	2-97
n	weblogic.management.runtime.PSAssemblyRuntimeMBean	2-98
n	weblogic.management.runtime.PartitionFairShareRuntimeMBean	2-99
n	weblogic.management.runtime.PartitionMinThreadsConstraintCapRuntimeMBean	2-100
n	weblogic.management.runtime.PartitionResourceMetricsRuntimeMBean	2-100
n	weblogic.management.runtime.PartitionRuntimeMBean	2-103
n	weblogic.management.runtime.PartitionWorkManagerRuntimeMBean	2-104
n	weblogic.management.runtime.PathServiceRuntimeMBean	2-104
n	weblogic.management.runtime.PersistenceUnitRuntimeMBean	2-105

n	weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean.....	2-105
n	weblogic.management.runtime.PersistentStoreRuntimeMBean.....	2-106
n	weblogic.management.runtime.QueryCacheRuntimeMBean.....	2-108
n	weblogic.management.runtime.RealmRuntimeMBean.....	2-109
n	weblogic.management.runtime.RequestClassRuntimeMBean.....	2-110
n	weblogic.management.runtime.ResourceManagerRuntimeMBean.....	2-111
n	weblogic.management.runtime.ResourceRuntimeMBean.....	2-111
n	weblogic.management.runtime.RuntimeMBean.....	2-112
n	weblogic.management.runtime.SAFAgentRuntimeMBean.....	2-112
n	weblogic.management.runtime.SAFConversationRuntimeMBean.....	2-115
n	weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean.....	2-116
n	weblogic.management.runtime.SAFRuntimeMBean.....	2-119
n	weblogic.management.runtime.SNMPAgentRuntimeMBean.....	2-119
n	weblogic.management.runtime.ServerChannelRuntimeMBean.....	2-122
n	weblogic.management.runtime.ServerLogRuntimeMBean.....	2-123
n	weblogic.management.runtime.ServerMigrationRuntimeMBean.....	2-123
n	weblogic.management.runtime.ServerRuntimeMBean.....	2-124
n	weblogic.management.runtime.ServerSecurityRuntimeMBean.....	2-127
n	weblogic.management.runtime.SingleSignOnServicesRuntimeMBean.....	2-128
n	weblogic.management.runtime.TaskRuntimeMBean.....	2-128
n	weblogic.management.runtime.ThreadPoolRuntimeMBean.....	2-130
n	weblogic.management.runtime.TimerRuntimeMBean.....	2-132
n	weblogic.management.runtime.TransactionNameRuntimeMBean.....	2-133
n	weblogic.management.runtime.TransactionResourceRuntimeMBean.....	2-135
n	weblogic.management.runtime.TriggerRuntimeMBean.....	2-137
n	weblogic.management.runtime.UnicastMessagingRuntimeMBean.....	2-138
n	weblogic.management.runtime.UserLockoutManagerRuntimeMBean.....	2-139
n	weblogic.management.runtime.WANReplicationRuntimeMBean.....	2-140
n	weblogic.management.runtime.WLDFAccessRuntimeMBean.....	2-141
n	weblogic.management.runtime.WLDFArchiveRuntimeMBean.....	2-141
n	weblogic.management.runtime.WLDFControlRuntimeMBean.....	2-142
n	weblogic.management.runtime.WLDFDataAccessRuntimeMBean.....	2-143
n	weblogic.management.runtime.WLDFDebugPatchTaskRuntimeMBean.....	2-143
n	weblogic.management.runtime.WLDFDebugPatchesRuntimeMBean.....	2-145
n	weblogic.management.runtime.WLDFHarvesterManagerRuntimeMBean.....	2-146
n	weblogic.management.runtime.WLDFHarvesterRuntimeMBean.....	2-147
n	weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean.....	2-148
n	weblogic.management.runtime.WLDFImageRuntimeMBean.....	2-150
n	weblogic.management.runtime.WLDFInstrumentationRuntimeMBean.....	2-150
n	weblogic.management.runtime.WLDFPartitionAccessRuntimeMBean.....	2-152
n	weblogic.management.runtime.WLDFPartitionHarvesterRuntimeMBean.....	2-152
n	weblogic.management.runtime.WLDFPartitionImageRuntimeMBean.....	2-153
n	weblogic.management.runtime.WLDFPartitionRuntimeMBean.....	2-154
n	weblogic.management.runtime.WLDFRuntimeMBean.....	2-154
n	weblogic.management.runtime.WLDFSystemResourceControlRuntimeMBean.....	2-155
n	weblogic.management.runtime.WLDFWatchManagerRuntimeMBean.....	2-155
n	weblogic.management.runtime.WLDFWatchNotificationRuntimeMBean.....	2-159

n	weblogic.management.runtime.WLDFWatchNotificationSourceRuntimeMBean	2-164
n	weblogic.management.runtime.WTCRuntimeMBean	2-164
n	weblogic.management.runtime.WTCStatisticsRuntimeMBean.....	2-165
n	weblogic.management.runtime.WebServerRuntimeMBean	2-165
n	weblogic.management.runtime.WorkManagerRuntimeMBean.....	2-166
n	weblogic.management.runtime.WseeAggregatableBaseOperationRuntimeMBean ...	2-167
n	weblogic.management.runtime.WseeBaseOperationRuntimeMBean.....	2-170
n	weblogic.management.runtime.WseeClusterFrontEndRuntimeMBean	2-174
n	weblogic.management.runtime.WseeClusterRoutingRuntimeMBean.....	2-174
n	weblogic.management.runtime.WseeHandlerRuntimeMBean	2-175
n	weblogic.management.runtime.WseeMcRuntimeMBean	2-176
n	weblogic.management.runtime.WseeOperationRuntimeMBean.....	2-176
n	weblogic.management.runtime.WseePolicyRuntimeMBean.....	2-180
n	weblogic.management.runtime.WseePortPolicyRuntimeMBean	2-180
n	weblogic.management.runtime.WseePortRuntimeMBean	2-182
n	weblogic.management.runtime.WseeV2RuntimeMBean	2-184
n	weblogic.management.runtime.WseeWsrnRuntimeMBean	2-186

Preface

This preface describes the document accessibility features and conventions used in this guide, *RESTful Server Runtime Reference for Oracle WebLogic Server*.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

Resources

This documentation describes the Oracle WebLogic Server RESTful server runtime resources that are used to monitor the Administration Server or a Managed Server.

For a complete listing of the WLS REST reference documents and descriptions of their use, see *Administering Oracle WebLogic Server with RESTful Management Services*.

/management/weblogic

This resource is used to access different versions (if applicable) of the resources that are in this domain.

For the 12.2.1 release, there are just two versions: 12.2.1 and latest, where latest is another name for 12.2.1. For future releases, latest always refers to the most recent release.

To always use the latest resources, make sure to use `latest` in the URLs. Note that this might require updating a client when moving to a newer version of WebLogic Server. To fix the version so that an update is not required, use `12.2.1` in the URLs.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.rest.bean.model.Version](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.rest.bean.model.Version](#) entities.

This method can return the following links:

- **uri=/management/weblogic rel=canonical**
This resource.
- **uri=/management/weblogic/12.2.1.0 rel=current**
Access the latest version of the WLS resources in the this domain.
- **uri=/management/weblogic rel=self**
This resource.

Example

Example 1 View the versions collection.

This example uses the GET method to display the version instances in this collection.

Example Request

```
curl -v \
--user admin:admin123 \
-H X-Requested-By:MyClient \
-H Accept:application/json \
-X GET http://localhost:7001/management/weblogic
```

Example Response

```
HTTP/1.1 200 OK
```

Response Body:

```
{
  "links": [
    {
      "rel": "self",
      "href": "http://localhost:7001/management/weblogic"
    },
    {
      "rel": "canonical",
      "href": "http://localhost:7001/management/weblogic"
    },
    {
      "rel": "current",
      "href": "http://localhost:7001/management/weblogic/12.2.1.0"
    }
  ],
  "items": [{
    "links": [
```

```
    {
      "rel": "self",
      "href": "http://localhost:7001/management/12.2.1.0"
    },
    {
      "rel": "canonical",
      "href": "http://localhost:7001/management/12.2.1.0"
    }
  ],
  "version": "12.2.1.0",
  "isLatest": true,
  "lifecycle": "active"
}]
}
```

/management/weblogic/{version}

This resource describes the resource trees that are used to manage a WebLogic Server domain and its managed servers. The resource trees mimic the bean trees in WLST and allow you to view and edit configuration and monitor runtime behavior.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.rest.bean.model.Version](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.rest.bean.model.Version](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/currentUser](#) **rel**=currentUser
- **uri**=[/management/weblogic/{version}/domainConfig](#) **rel**=domainConfig
- **uri**=[/management/weblogic/{version}/domainRuntime](#) **rel**=domainRuntime
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=edit
- **uri**=[/management/weblogic](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/serverConfig](#) **rel**=serverConfig
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=serverRuntime

Example

Example 1 View the latest version.

This example uses the GET method to display the latest version.

Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-X GET http://localhost:7001/management/weblogic/latest
```

Example Response

```
HTTP/1.1 200 OK
```

Response Body:

```
{  
  "links": [  
    {  
      "rel": "parent",  
      "href": "http://localhost:7001/management/weblogic"  
    },  
    {
```

```

        "rel": "self",
        "href": "http://localhost:7001/management/weblogic/latest"
    },
    {
        "rel": "canonical",
        "href": "http://localhost:7001/management/weblogic/latest"
    },
    {
        "rel": "edit",
        "href": "http://localhost:7001/management/weblogic/latest/edit"
    },
    {
        "rel": "domainConfig",
        "href":
"http://localhost:7001/management/weblogic/latest/domainConfig"
    },
    {
        "rel": "domainRuntime",
        "href":
"http://localhost:7001/management/weblogic/latest/domainRuntime"
    },
    {
        "rel": "serverRuntime",
        "href":
"http://localhost:7001/management/weblogic/latest/serverRuntime"
    },
    {
        "rel": "serverConfig",
        "href":
"http://localhost:7001/management/weblogic/latest/serverConfig"
    },
    {
        "rel": "currentUser",
        "href":
"http://localhost:7001/management/weblogic/latest/currentUser"
    }
],
"version": "12.2.1.0",
"isLatest": true,
"lifecycle": "active"
}

```

Example 2 View a specific version.

This example uses the GET method to display a specific version.

Example Request

```

curl -v \
--user admin:admin123 \
-H X-Requested-By:MyClient \
-H Accept:application/json \
-X GET http://localhost:7001/management/weblogic/12.2.1.0

```

Example Response

HTTP/1.1 200 OK

Response Body:

```

{
  "links": [

```

```
{
  "rel": "parent",
  "href": "http://localhost:7001/management/weblogic"
},
{
  "rel": "self",
  "href": "http://localhost:7001/management/weblogic/12.2.1.0"
},
{
  "rel": "canonical",
  "href": "http://localhost:7001/management/weblogic/12.2.1.0"
},
{
  "rel": "edit",
  "href": "http://localhost:7001/management/weblogic/12.2.1.0/edit"
},
{
  "rel": "domainConfig",
  "href":
"http://localhost:7001/management/weblogic/12.2.1.0/domainConfig"
},
{
  "rel": "domainRuntime",
  "href":
"http://localhost:7001/management/weblogic/12.2.1.0/domainRuntime"
},
{
  "rel": "serverRuntime",
  "href":
"http://localhost:7001/management/weblogic/12.2.1.0/serverRuntime"
},
{
  "rel": "serverConfig",
  "href":
"http://localhost:7001/management/weblogic/12.2.1.0/serverConfig"
},
{
  "rel": "currentUser",
  "href":
"http://localhost:7001/management/weblogic/12.2.1.0/currentUser"
}
],
"version": "12.2.1.0",
"isLatest": true,
"lifecycle": "active"
}
```


/management/weblogic/{version}/currentUser

This resource represents an authenticated user in the domain.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.rest.bean.model.CurrentUser](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.rest.bean.model.CurrentUser](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/currentUser](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/currentUser](#) **rel**=self
This resource.

Example

Example 1 Viewing the [weblogic.management.rest.bean.model.CurrentUser](#) Instance

This example uses the GET method to view this [weblogic.management.rest.bean.model.CurrentUser](#) instance.

Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-X GET http://localhost:7001/management/weblogic/latest/currentUser
```

Example Response

```
HTTP/1.1 200 OK
```

```
Response Body:
```

```
{  
  "links": [  
    {  
      "rel": "parent",  
      "href": "http://localhost:7001/management/weblogic/latest"  
    },  
    {  
      "rel": "self",  
      "href":  
"http://localhost:7001/management/weblogic/latest/currentUser"  
    },  
    {  
      "rel": "canonical",  
      "href":  
"http://localhost:7001/management/weblogic/latest/currentUser"
```

```
    }  
  ],  
  "partitionId": "0",  
  "partitionName": "DOMAIN",  
  "user": "admin"  
}
```

/management/weblogic/{version}/serverRuntime

This resource is used to monitor the administration server and managed servers.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ServerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ServerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime
rel=JDBCServiceRuntime
This resource's JDBCServiceRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime
rel=JMSRuntime
This resource's JMSRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JTARuntime
rel=JTARuntime
This resource's JTARuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JVMRuntime
rel=JVMRuntime
This resource's JVMRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/MANAsyncReplicationRuntime
rel=MANAsyncReplicationRuntime
This resource's MANAsyncReplicationRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/MANReplicationRuntime
rel=MANReplicationRuntime
This resource's MANReplicationRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime
rel=SAFRuntime
This resource's SAFRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/SNMPAgentRuntime
rel=SNMPAgentRuntime
This resource's SNMPAgentRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WANReplicationRuntime
rel=WANReplicationRuntime
This resource's WANReplicationRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime
rel=WLDFRuntime
This resource's WLDFRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WTCRuntime
rel=WTCRuntime

This resource's WTCRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/forceShutdown
rel=action **title**=forceShutdown

This resource's forceShutdown action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/forceShutdownResourceGroup
rel=action **title**=forceShutdownResourceGroup

This resource's forceShutdownResourceGroup action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/forceSuspend **rel**=action
title=forceSuspend

This resource's forceSuspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/forceSuspendResourceGroup
rel=action **title**=forceSuspendResourceGroup

This resource's forceSuspendResourceGroup action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/getIPv4URL **rel**=action
title=getIPv4URL

This resource's getIPv4URL action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/getIPv6URL **rel**=action
title=getIPv6URL

This resource's getIPv6URL action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/getRgState **rel**=action
title=getRgState

This resource's getRgState action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/getURL **rel**=action
title=getURL

This resource's getURL action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/restartSSLChannels
rel=action **title**=restartSSLChannels

This resource's restartSSLChannels action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/resume **rel**=action
title=resume

This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/resumeResourceGroup
rel=action **title**=resumeResourceGroup

This resource's resumeResourceGroup action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/shutdown **rel**=action
title=shutdown

This resource's shutdown action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/shutdownResourceGroup
rel=action **title**=shutdownResourceGroup

This resource's shutdownResourceGroup action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/startPartition **rel**=action
title=startPartition

This resource's startPartition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/startPartitionInAdmin
rel=action **title**=startPartitionInAdmin

This resource's startPartitionInAdmin action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/startResourceGroup
rel=action **title**=startResourceGroup

This resource's startResourceGroup action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/startResourceGroupInAdmin
rel=action **title**=startResourceGroupInAdmin

This resource's startResourceGroupInAdmin action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/suspend **rel**=action
title=suspend

This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/suspendResourceGroup
rel=action **title**=suspendResourceGroup

This resource's suspendResourceGroup action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes
rel=applicationRuntimes

This resource's applicationRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/asyncReplicationRuntime
rel=asyncReplicationRuntime

This resource's asyncReplicationRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/batchJobRepositoryRuntime
rel=batchJobRepositoryRuntime

This resource's batchJobRepositoryRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/classLoaderRuntime
rel=classLoaderRuntime

This resource's classLoaderRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/clusterRuntime
rel=clusterRuntime

This resource's clusterRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime
rel=concurrentManagedObjectsRuntime

This resource's concurrentManagedObjectsRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime
rel=connectorServiceRuntime

This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/defaultExecuteQueueRuntime
rel=defaultExecuteQueueRuntime

This resource's defaultExecuteQueueRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/entityCacheCumulativeRuntime **rel**=entityCacheCumulativeRuntime

This resource's entityCacheCumulativeRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/entityCacheCurrentStateRuntime **rel**=entityCacheCurrentStateRuntime

This resource's entityCacheCurrentStateRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/entityCacheHistoricalRuntime **rel**=entityCacheHistoricalRuntime

This resource's entityCacheHistoricalRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/executeQueueRuntimes **rel**=executeQueueRuntimes

This resource's executeQueueRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/joltRuntime **rel**=joltRuntime

This resource's joltRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/libraryRuntimes **rel**=libraryRuntimes

This resource's libraryRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/logBroadcasterRuntime **rel**=logBroadcasterRuntime

This resource's logBroadcasterRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/mailSessionRuntimes **rel**=mailSessionRuntimes

This resource's mailSessionRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/maxThreadsConstraintRuntimes **rel**=maxThreadsConstraintRuntimes

This resource's maxThreadsConstraintRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/messagingBridgeRuntimes **rel**=messagingBridgeRuntimes

This resource's messagingBridgeRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/minThreadsConstraintRuntimes **rel**=minThreadsConstraintRuntimes

This resource's minThreadsConstraintRuntimes collection resource.

- **uri**=/management/weblogic/{version} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes **rel**=partitionRuntimes

This resource's partitionRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/pathServiceRuntimes **rel**=pathServiceRuntimes

This resource's pathServiceRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes
rel=persistentStoreRuntimes

This resource's persistentStoreRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/requestClassRuntimes
rel=requestClassRuntimes

This resource's requestClassRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/search **rel**=search

This resource's search resource.

- **uri**=/management/weblogic/{version}/serverRuntime **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverChannelRuntimes
rel=serverChannelRuntimes

This resource's serverChannelRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverLogRuntime
rel=serverLogRuntime

This resource's serverLogRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime
rel=serverSecurityRuntime

This resource's serverSecurityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/singleSignOnServicesRuntime
rel=singleSignOnServicesRuntime

This resource's singleSignOnServicesRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/threadPoolRuntime
rel=threadPoolRuntime

This resource's threadPoolRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/timerRuntime
rel=timerRuntime

This resource's timerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/webServerRuntimes
rel=webServerRuntimes

This resource's webServerRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/workManagerRuntimes
rel=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/wseeClusterFrontEndRuntime
rel=wseeClusterFrontEndRuntime

This resource's wseeClusterFrontEndRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/wseeWsruntime
rel=wseeWsruntime

This resource's wseeWsruntime singleton resource.

Example

Example 1 Viewing the `weblogic.management.runtime.ServerRuntimeMBean` Instance

This example uses the GET method to view this `weblogic.management.runtime.ServerRuntimeMBean` instance.

Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-X GET \  
http://localhost:7001/management/weblogic/latest/serverRuntime?fields=name,openSoc  
ketsCurrentCount,overallHealthState,administrationURL&links=self
```

Example Response

HTTP/1.1 200 OK

Response Body:

```
{  
  "links": [{  
    "rel": "self",  
    "href": "http://localhost:7001/management/weblogic/latest/serverRuntime"  
  }],  
  "openSocketsCurrentCount": 1,  
  "administrationURL": "t3://localhost:7001",  
  "overallHealthState": {  
    "state": "ok",  
    "subsystemName": null,  
    "partitionName": null,  
    "symptoms": []  
  },  
  "name": "AdminServer"  
}
```

/management/weblogic/{version}/serverRuntime/applicationRuntimes

This resource manages a collection of [weblogic.management.runtime.ApplicationRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ApplicationRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ApplicationRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes](#)
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}

This resource manages a [weblogic.management.runtime.ApplicationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ApplicationRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ApplicationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/getPersistenceUnitRuntime **rel**=action **title**=getPersistenceUnitRuntime

This resource's getPersistenceUnitRuntime action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/hasApplicationCache **rel**=action **title**=hasApplicationCache

This resource's hasApplicationCache action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/reInitializeApplicationCachesAndPools **rel**=action **title**=reInitializeApplicationCachesAndPools

This resource's reInitializeApplicationCachesAndPools action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name} **rel**=canonical

This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classLoaderRuntime **rel**=classLoaderRuntime

This resource's classLoaderRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime **rel**=classRedefinitionRuntime

This resource's classRedefinitionRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/coherenceClusterRuntime **rel**=coherenceClusterRuntime

This resource's coherenceClusterRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes **rel**=componentRuntimes

This resource's componentRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes **rel**=libraryRuntimes

This resource's libraryRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes **rel**=managedExecutorServiceRuntimes

This resource's managedExecutorServiceRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes
rel=managedScheduledExecutorServiceRuntimes
This resource's managedScheduledExecutorServiceRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedThreadFactoryRuntimes **rel**=managedThreadFactoryRuntimes
This resource's managedThreadFactoryRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/maxThreadsConstraintRuntimes **rel**=maxThreadsConstraintRuntimes
This resource's maxThreadsConstraintRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/minThreadsConstraintRuntimes **rel**=minThreadsConstraintRuntimes
This resource's minThreadsConstraintRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes **rel**=optionalPackageRuntimes
This resource's optionalPackageRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes
rel=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/persistenceUnitRuntimes **rel**=persistenceUnitRuntimes
This resource's persistenceUnitRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/queryCacheRuntimes **rel**=queryCacheRuntimes
This resource's queryCacheRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/requestClassRuntimes **rel**=requestClassRuntimes
This resource's requestClassRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}
rel=self
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes **rel**=workManagerRuntimes
This resource's workManagerRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes **rel**=wseeV2Runtimes
This resource's wseeV2Runtimes collection resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classLoaderRuntime

This resource manages a [weblogic.management.runtime.ClassLoaderRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ClassLoaderRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ClassLoaderRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classLoaderRuntime **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classLoaderRuntime **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime

This resource manages a [com.bea.wls.redef.runtime.ClassRedefinitionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [com.bea.wls.redef.runtime.ClassRedefinitionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [com.bea.wls.redef.runtime.ClassRedefinitionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/redefineClasses](#) **rel=action** **title=**redefineClasses
This resource's redefineClasses action resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks](#) **rel=classRedefinitionTasks**
This resource's classRedefinitionTasks collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks

This resource manages a collection of [com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/ classRedefinitionRuntime/classRedefinitionTasks/{name}

This resource manages a [com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/cancel **rel**=action
title=cancel
This resource's cancel action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks **rel**=parent
The parent resource of this resource.
- **rel**=parentTask
This resource's parentTask reference to a weblogic.management.runtime.TaskRuntimeMBean resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks **rel**=subTasks
This resource's subTasks collection resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/ classRedefinitionRuntime/classRedefinitionTasks/{name}/cancel

The resource supports the following methods:

- [POST](#)

POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks

This resource manages a collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.TaskRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}

This resource manages a [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.TaskRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/cancel **rel**=action **title**=cancel

This resource's cancel action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks **rel**=parent

The parent resource of this resource.

- **rel**=parentTask

This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks **rel**=subTasks

This resource's subTasks collection resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/cancel

The resource supports the following methods:

- [POST](#)

POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks

This resource manages a collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.TaskRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name}

This resource manages a [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.TaskRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name}/cancel **rel**=action **title**=cancel

This resource's cancel action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks **rel**=parent

The parent resource of this resource.

- **rel**=parentTask

This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks **rel**=subTasks

This resource's subTasks collection resource.

**/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/
classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/s
ubTasks/{name}/cancel**

The resource supports the following methods:

- [POST](#)

POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/ classRedefinitionRuntime/redefineClasses

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Initiate a class redefinition cycle, which will identify classes which may have changed and then attempt to redefine them. Class redefinition will be performed asynchronously. The progress of the class redefinition process can be monitored with the returned task.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See About Synchronous and Asynchronous Operations.

Roles

Admin

Response Body

Contains a JSON object with a `com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean` reference return field.

POST

Initiate a class redefinition cycle, to redefine only the specified classes from given module. Class redefinition will be performed asynchronously. The progress of the class redefinition process can be monitored with the returned task. If specified module name is null, any classes within the application (scoped to any modules as well as globally scoped classes) which are included in the list will be redefined.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See About Synchronous and Asynchronous Operations.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

moduleName

Module from which the classes are to be redefined.

Type: string

classNames

Classes to be redefined.

Type: array of string

Response Body

Contains a JSON object with a `com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/coherenceClusterRuntime

This resource manages a [weblogic.management.runtime.CoherenceClusterRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CoherenceClusterRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CoherenceClusterRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/coherenceClusterRuntime **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/coherenceClusterRuntime **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/ componentRuntimes

This resource manages a collection of [weblogic.management.runtime.ComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ComponentRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ComponentRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/ componentRuntimes/{name}

This resource manages a [weblogic.management.runtime.ComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ComponentRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ComponentRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}](#) **rel**=self

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes](#) **rel**=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/ componentRuntimes/{name}/workManagerRuntimes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of `weblogic.management.runtime.WorkManagerRuntimeMBean` instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of `weblogic.management.runtime.WorkManagerRuntimeMBean` entities.

This method can return the following links:

- **uri**=`/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes` **rel**=canonical
This resource.
- **uri**=`/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}` **rel**=parent
The parent resource of this resource.
- **uri**=`/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes` **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/ componentRuntimes/{name}/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/ componentRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/getPersistenceUnitRuntime

The resource supports the following methods:

- [POST](#)

POST

Provides the PersistenceUnitRuntimeMBean for the application with the specified name.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

unitName
unitName
Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.PersistenceUnitRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/hasApplicationCache

The resource supports the following methods:

- [POST](#)

POST

Returns true if the application has an (EJB) Application Level Cache

Roles

Admin, Operator

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes

This resource manages a collection of [weblogic.management.runtime.LibraryRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.LibraryRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.LibraryRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/ libraryRuntimes/{name}

This resource manages a [weblogic.management.runtime.LibraryRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LibraryRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LibraryRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes](#) **rel**=referencingRuntimes

This resource's referencingRuntimes collection resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name}

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/ managedExecutorServiceRuntimes

This resource manages a collection of [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/ managedExecutorServiceRuntimes/{name}

This resource manages a [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}](#) **rel**=self

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager](#) **rel**=workManager

This resource's workManager singleton resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/ managedExecutorServiceRuntimes/{name}/workManager

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime](#)
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes

This resource manages a collection of [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/ managedScheduledExecutorServiceRuntimes/{name}

This resource manages a [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}](#) **rel**=self

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager](#) **rel**=workManager

This resource's workManager singleton resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/ managedScheduledExecutorServiceRuntimes/{name}/workManager

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime](#) **rel**=capacityRuntime
This resource's capacityRuntime singleton resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime](#) **rel**=maxThreadsConstraintRuntime
This resource's maxThreadsConstraintRuntime singleton resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime](#) **rel**=minThreadsConstraintRuntime
This resource's minThreadsConstraintRuntime singleton resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime](#) **rel**=requestClassRuntime
This resource's requestClassRuntime singleton resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedThreadFactoryRuntimes

This resource manages a collection of [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedThreadFactoryRuntimes](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedThreadFactoryRuntimes](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedThreadFactoryRuntimes/{name}

This resource manages a [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedThreadFactoryRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedThreadFactoryRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedThreadFactoryRuntimes/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/maxThreadsConstraintRuntimes

This resource manages a collection of [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/maxThreadsConstraintRuntimes](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/maxThreadsConstraintRuntimes](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/maxThreadsConstraintRuntimes/{name}

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/maxThreadsConstraintRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/maxThreadsConstraintRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/maxThreadsConstraintRuntimes/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/minThreadsConstraintRuntimes

This resource manages a collection of [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/minThreadsConstraintRuntimes](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/minThreadsConstraintRuntimes](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/minThreadsConstraintRuntimes/{name}

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/minThreadsConstraintRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/minThreadsConstraintRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/minThreadsConstraintRuntimes/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes

This resource manages a collection of [weblogic.management.runtime.LibraryRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.LibraryRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.LibraryRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name}

This resource manages a [weblogic.management.runtime.LibraryRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LibraryRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LibraryRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes](#) **rel**=referencingRuntimes

This resource's referencingRuntimes collection resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes/{name}

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes/{name}](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/persistenceUnitRuntimes

This resource manages a collection of [weblogic.management.runtime.PersistenceUnitRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.PersistenceUnitRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.PersistenceUnitRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/persistenceUnitRuntimes](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/persistenceUnitRuntimes](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/persistenceUnitRuntimes/{name}

This resource manages a [weblogic.management.runtime.PersistenceUnitRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.PersistenceUnitRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.PersistenceUnitRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/persistenceUnitRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/persistenceUnitRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/persistenceUnitRuntimes/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/queryCacheRuntimes

This resource manages a collection of [weblogic.management.runtime.QueryCacheRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.QueryCacheRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.QueryCacheRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/queryCacheRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/queryCacheRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/queryCacheRuntimes/{name}

This resource manages a [weblogic.management.runtime.QueryCacheRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.QueryCacheRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.QueryCacheRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/queryCacheRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/queryCacheRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/queryCacheRuntimes/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/reInitializeApplicationCachesAndPools

The resource supports the following methods:

- [POST](#)

POST

If the application has an (EJB) Application Level Cache, then this method will reinitialize the cache and any of its associated pools to their startup time states if possible.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/requestClassRuntimes

This resource manages a collection of [weblogic.management.runtime.RequestClassRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RequestClassRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RequestClassRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/requestClassRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/requestClassRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/requestClassRuntimes/{name}

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/requestClassRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/requestClassRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/requestClassRuntimes/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime
This resource's capacityRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime
This resource's maxThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime
This resource's minThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime
This resource's requestClassRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name} **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes

This resource manages a collection of [weblogic.management.runtime.WseeV2RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WseeV2RuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WseeV2RuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name} rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}

This resource manages a [weblogic.management.runtime.WseeV2RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WseeV2RuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WseeV2RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/policyRuntime **rel**=policyRuntime

This resource's policyRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports **rel**=ports

This resource's ports collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/policyRuntime

This resource manages a [weblogic.management.runtime.WseePolicyRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WseePolicyRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WseePolicyRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/policyRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/policyRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports

This resource manages a collection of [weblogic.management.runtime.WseePortRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WseePortRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WseePortRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}

This resource manages a [weblogic.management.runtime.WseePortRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WseePortRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WseePortRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/aggregatedBaseOperations **rel**=aggregatedBaseOperations
This resource's aggregatedBaseOperations singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations **rel**=baseOperations
This resource's baseOperations collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/clusterRouting **rel**=clusterRouting
This resource's clusterRouting singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers **rel**=handlers
This resource's handlers collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/mc **rel**=mc
This resource's mc singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations **rel**=operations
This resource's operations collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/portPolicy **rel**=portPolicy
This resource's portPolicy singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=self
This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/wsm **rel**=wsm

This resource's wsm singleton resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/aggregatedBaseOperations

This resource manages a [weblogic.management.runtime.WseeAggregatableBaseOperationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WseeAggregatableBaseOperationRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WseeAggregatableBaseOperationRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/aggregatedBaseOperations](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/aggregatedBaseOperations](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations

This resource manages a collection of [weblogic.management.runtime.WseeBaseOperationRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WseeBaseOperationRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WseeBaseOperationRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations/{name}

This resource manages a [weblogic.management.runtime.WseeBaseOperationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WseeBaseOperationRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WseeBaseOperationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations/{name} **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/clusterRouting

This resource manages a [weblogic.management.runtime.WseeClusterRoutingRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WseeClusterRoutingRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WseeClusterRoutingRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/clusterRouting **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/clusterRouting **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers

This resource manages a collection of [weblogic.management.runtime.WseeHandlerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WseeHandlerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WseeHandlerRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers/{name}

This resource manages a [weblogic.management.runtime.WseeHandlerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WseeHandlerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WseeHandlerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers/{name}](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/mc

This resource manages a [weblogic.management.runtime.WseeMcRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WseeMcRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WseeMcRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/mc **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/mc **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations

This resource manages a collection of [weblogic.management.runtime.WseeOperationRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WseeOperationRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WseeOperationRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations/{name}

This resource manages a [weblogic.management.runtime.WseeOperationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WseeOperationRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WseeOperationRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations/{name}](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/portPolicy

This resource manages a [weblogic.management.runtime.WseePortPolicyRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WseePortPolicyRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WseePortPolicyRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/portPolicy](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/portPolicy](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/wsrm

This resource manages a [weblogic.management.runtime.WseeWsruntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WseeWsruntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WseeWsruntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/wsrm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/wsrm **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/asyncReplicationRuntime

This resource manages a [weblogic.management.runtime.AsyncReplicationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.AsyncReplicationRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.AsyncReplicationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/asyncReplicationRuntime](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/asyncReplicationRuntime](#)
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/batchJobRepositoryRuntime

This resource manages a [weblogic.management.runtime.BatchJobRepositoryRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.BatchJobRepositoryRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.BatchJobRepositoryRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/batchJobRepositoryRuntime](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/batchJobRepositoryRuntime](#)
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/classLoaderRuntime

This resource manages a [weblogic.management.runtime.ClassLoaderRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ClassLoaderRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ClassLoaderRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/classLoaderRuntime](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/classLoaderRuntime](#)
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/clusterRuntime

This resource manages a [weblogic.management.runtime.ClusterRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ClusterRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ClusterRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime/initiateResourceGroupMigration](#) [rel=action](#) [title=initiateResourceGroupMigration](#)
This resource's initiateResourceGroupMigration action resource.
- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime](#) [rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime](#) [rel=jobSchedulerRuntime](#)
This resource's jobSchedulerRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime](#) [rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime](#) [rel=self](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime](#) [rel=serverMigrationRuntime](#)
This resource's serverMigrationRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime/unicastMessaging](#) [rel=unicastMessaging](#)
This resource's unicastMessaging singleton resource.

/management/weblogic/{version}/serverRuntime/clusterRuntime/initiateResourceGroupMigration

The resource supports the following methods:

- [POST](#)

POST

Provides a synchronous method for initiating resource group migration.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

partitionName

partitionName

Type: string

resourceGroupName

resourceGroupName

Type: string

targetCluster

targetCluster

Type: string

timeout

timeout

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime

This resource manages a [weblogic.management.runtime.JobSchedulerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JobSchedulerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JobSchedulerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/getJob](#) **rel=action** **title=getJob**
This resource's getJob action resource.
- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/executedJobs](#) **rel=executedJobs**
This resource's executedJobs collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/executedJobs

This resource manages a collection of [weblogic.management.runtime.JobRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JobRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JobRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/executedJobs](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/executedJobs](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/executedJobs/{name}

This resource manages a [weblogic.management.runtime.JobRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JobRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JobRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/executedJobs/{name}/cancel **rel**=action **title**=cancel
This resource's cancel action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/executedJobs/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/executedJobs **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/executedJobs/{name} **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/executedJobs/{name}/cancel

The resource supports the following methods:

- [POST](#)

POST

Cancel this job and prevent it from executing again in any server, not just this server.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/getJob

The resource supports the following methods:

- [POST](#)

POST

Return the JobRuntimeMBean corresponding to the specified ID. An ID is recorded in the WebLogic server logs whenever a new job is scheduled with the Job Scheduler.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

id
unique ID corresponding to a job
Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.JobRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime

This resource manages a [weblogic.management.runtime.ServerMigrationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ServerMigrationRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ServerMigrationRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime/migrationData](#) **rel=migrationData**
This resource's migrationData collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime/migrationData

This resource manages a collection of [weblogic.management.runtime.MigrationDataRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MigrationDataRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MigrationDataRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime/migrationData](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime/migrationData](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime/migrationData/{name}

This resource manages a [weblogic.management.runtime.MigrationDataRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MigrationDataRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MigrationDataRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime/migrationData/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime/migrationData **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime/migrationData/{name} **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/clusterRuntime/unicastMessaging

This resource manages a [weblogic.management.runtime.UnicastMessagingRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.UnicastMessagingRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.UnicastMessagingRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime/unicastMessaging rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime/unicastMessaging rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime

This resource manages a [weblogic.management.runtime.ConcurrentManagedObjectsRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConcurrentManagedObjectsRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConcurrentManagedObjectsRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes](#) **rel=managedExecutorServiceRuntimes**
This resource's managedExecutorServiceRuntimes collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes](#) **rel=managedScheduledExecutorServiceRuntimes**
This resource's managedScheduledExecutorServiceRuntimes collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes](#) **rel=managedThreadFactoryRuntimes**
This resource's managedThreadFactoryRuntimes collection resource.
- [uri=/management/weblogic/{version}/serverRuntime](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes

This resource manages a collection of [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}

This resource manages a [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}](#) **rel=self**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager](#) **rel=workManager**

This resource's workManager singleton resource.

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime
rel=capacityRuntime
This resource's capacityRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime
rel=maxThreadsConstraintRuntime
This resource's maxThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime
rel=minThreadsConstraintRuntime
This resource's minThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}
rel=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime
rel=requestClassRuntime
This resource's requestClassRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes

This resource manages a collection of [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}

This resource manages a [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}](#) **rel=self**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager](#) **rel=workManager**
This resource's workManager singleton resource.

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime](#) **rel=capacityRuntime**
This resource's capacityRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**
This resource's maxThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**
This resource's minThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime](#) **rel=requestClassRuntime**
This resource's requestClassRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/maximumThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaximumThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes

This resource manages a collection of [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes/{name}

This resource manages a [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes/{name}](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime

This resource manages a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs](#) **rel=RA**s
This resource's RAs collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/getInboundConnections](#) **rel=action** **title=getInboundConnections**
This resource's getInboundConnections action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/getRA](#) **rel=action** **title=getRA**
This resource's getRA action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/resume](#) **rel=action** **title=resume**
This resource's resume action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/resumeAll](#) **rel=action** **title=resumeAll**
This resource's resumeAll action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/suspend](#) **rel=action** **title=suspend**
This resource's suspend action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/suspendAll](#) **rel=action** **title=suspendAll**
This resource's suspendAll action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs](#) **rel=activeRAs**
This resource's activeRAs collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs](#) **rel=inactiveRAs**
This resource's inactiveRAs collection resource.
- [uri=/management/weblogic/{version}/serverRuntime](#) **rel=parent**

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime](#)
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs](#) [rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime](#) [rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs](#) [rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/getConfiguration rel=action title=getConfiguration](#)
This resource's getConfiguration action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/getConnectionPool rel=action title=getConnectionPool](#)
This resource's getConnectionPool action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/getInboundConnection rel=action title=getInboundConnection](#)
This resource's getInboundConnection action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/getSchema rel=action title=getSchema](#)
This resource's getSchema action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/resume rel=action title=resume](#)
This resource's resume action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/resumeAll rel=action title=resumeAll](#)
This resource's resumeAll action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/suspend rel=action title=suspend](#)
This resource's suspend action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/suspendAll rel=action title=suspendAll](#)
This resource's suspendAll action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name} rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools rel=connectionPools](#)
This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime
This resource's connectorServiceRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime
This resource's connectorWorkManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=inboundConnections
This resource's inboundConnections collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=workManagerRuntime
This resource's workManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes
This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened **rel**=action **title**=ensureLogOpened
This resource's ensureLogOpened action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog **rel**=action **title**=flushLog
This resource's flushLog action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation **rel**=action **title**=forceLogRotation
This resource's forceLogRotation action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset **rel**=action **title**=forceReset
This resource's forceReset action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset **rel**=action **title**=reset
This resource's reset action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool **rel**=action **title**=testPool
This resource's testPool action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=connections
This resource's connections collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime
This resource's logRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete
rel=action **title**=delete

This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError
rel=action **title**=hasError

This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection
rel=action **title**=testConnection

This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete

The resource supports the following methods:

- [POST](#)

POST

Provides a way to manually close a connection through the console.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError

The resource supports the following methods:

- [POST](#)

POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection

The resource supports the following methods:

- [POST](#)

POST

Test the connection. Returns true if the test was successful.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset

The resource supports the following methods:

- [POST](#)

POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened
rel=action **title**=ensureLogOpened
This resource's ensureLogOpened action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action
title=flushLog
This resource's flushLog action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation
rel=action **title**=forceLogRotation
This resource's forceLogRotation action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset

The resource supports the following methods:

- [POST](#)

POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool

The resource supports the following methods:

- [POST](#)

POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime

This resource manages a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs **rel**=RAs

This resource's RAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/getInboundConnections **rel**=action **title**=getInboundConnections

This resource's getInboundConnections action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/getRA **rel**=action **title**=getRA

This resource's getRA action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/resume **rel**=action **title**=resume

This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/resumeAll **rel**=action **title**=resumeAll

This resource's resumeAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/suspend **rel**=action **title**=suspend

This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/suspendAll **rel**=action **title**=suspendAll

This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/activeRAs **rel**=activeRAs

This resource's activeRAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs **rel**=inactiveRAs

This resource's inactiveRAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/getInboundConnections

The resource supports the following methods:

- [POST](#)

POST

Returns runtime information for the specified inbound connection. A null is returned if the inbound connection is not found.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

messageListenerType

Message listener type.

Type: string

Response Body

Contains a JSON object with a array of `weblogic.management.runtime.ConnectorInboundRuntimeMBean` references return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/getRA

The resource supports the following methods:

- [POST](#)

POST

Returns the runtime information of the resource adapter specified by the given JNDI name. A null is returned if the resource adapter cannot be found. This function returns the active RA if multiple versions of the resource adapters has been deployed

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

key

The JNDI name of the resource adapter.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorComponentRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration **rel**=action **title**=getConfiguration

This resource's getConfiguration action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool **rel**=action **title**=getConnectionPool

This resource's getConnectionPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection **rel**=action **title**=getInboundConnection

This resource's getInboundConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema **rel**=action **title**=getSchema

This resource's getSchema action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume **rel**=action **title**=resume

This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll **rel**=action **title**=resumeAll

This resource's resumeAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend **rel**=action **title**=suspend

This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll **rel**=action **title**=suspendAll

This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=connectionPools
This resource's connectionPools collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime
This resource's connectorServiceRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime
This resource's connectorWorkManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=inboundConnections
This resource's inboundConnections collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=workManagerRuntime
This resource's workManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes
This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened](#) **rel=action** **title=ensureLogOpened**

This resource's ensureLogOpened action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog](#) **rel=action** **title=flushLog**

This resource's flushLog action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation](#) **rel=action** **title=forceLogRotation**

This resource's forceLogRotation action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset](#) **rel=action** **title=forceReset**

This resource's forceReset action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset](#) **rel=action** **title=reset**

This resource's reset action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool](#) **rel=action** **title=testPool**

This resource's testPool action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections](#) **rel=connections**

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete

The resource supports the following methods:

- [POST](#)

POST

Provides a way to manually close a connection through the console.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError

The resource supports the following methods:

- [POST](#)

POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection

The resource supports the following methods:

- [POST](#)

POST

Test the connection. Returns true if the test was successful.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset

The resource supports the following methods:

- [POST](#)

POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened
This resource's ensureLogOpened action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog
This resource's flushLog action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation
This resource's forceLogRotation action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset

The resource supports the following methods:

- [POST](#)

POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool

The resource supports the following methods:

- [POST](#)

POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration

The resource supports the following methods:

- [POST](#)

POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool

The resource supports the following methods:

- [POST](#)

POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

key

JNDI name or resource-link name of the connection pool.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection

The resource supports the following methods:

- [POST](#)

POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

messageListenerType

Message listener type.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema

The resource supports the following methods:

- [POST](#)

POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=MDBRuntimes

This resource's MDBRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume rel=action title=resume](#)

This resource's resume action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend rel=action title=suspend](#)

This resource's suspend action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime rel=poolRuntime](#)

This resource's poolRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources rel=resources](#)

This resource's resources collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} rel=self](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime rel=timerRuntime](#)

This resource's timerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime
rel=transactionRuntime

This resource's transactionRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool

The resource supports the following methods:

- [POST](#)

POST

Instructs the Pool to initialize itself to its configured startup time size.
This is a synchronous and will wait until the pool is initialized before returning.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

Resumes the specific type of MDB by calling start on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers
rel=action **title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers

The resource supports the following methods:

- [POST](#)

POST

Activate any temporarily disabled timers.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Suspend a particular type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManager Runtime

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime rel=capacityRuntime](#)
This resource's capacityRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime rel=maxThreadsConstraintRuntime](#)
This resource's maxThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime rel=minThreadsConstraintRuntime](#)
This resource's minThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name} rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime rel=requestClassRuntime](#)
This resource's requestClassRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManager Runtimes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}](#) **rel**=canonical

This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes](#) **rel**=parent

The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration](#) **rel**=action **title**=getConfiguration
This resource's getConfiguration action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool](#) **rel**=action **title**=getConnectionPool
This resource's getConnectionPool action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection](#) **rel**=action **title**=getInboundConnection
This resource's getInboundConnection action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getSchema](#) **rel**=action **title**=getSchema
This resource's getSchema action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resume](#) **rel**=action **title**=resume
This resource's resume action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resumeAll](#) **rel**=action **title**=resumeAll
This resource's resumeAll action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspend](#) **rel**=action **title**=suspend
This resource's suspend action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspendAll](#) **rel**=action **title**=suspendAll
This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=connectionPools

This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/connectorServiceRuntime **rel**=connectorServiceRuntime

This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime

This resource's connectorWorkManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inboundConnections **rel**=inboundConnections

This resource's inboundConnections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/workManagerRuntime **rel**=workManagerRuntime

This resource's workManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/workManagerRuntimes **rel**=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset **rel**=action **title**=forceReset

This resource's forceReset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset **rel**=action **title**=reset

This resource's reset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool **rel**=action **title**=testPool

This resource's testPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=connections

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete

The resource supports the following methods:

- [POST](#)

POST

Provides a way to manually close a connection through the console.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError

The resource supports the following methods:

- [POST](#)

POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection

The resource supports the following methods:

- [POST](#)

POST

Test the connection. Returns true if the test was successful.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset

The resource supports the following methods:

- [POST](#)

POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset

The resource supports the following methods:

- [POST](#)

POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool

The resource supports the following methods:

- [POST](#)

POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration

The resource supports the following methods:

- [POST](#)

POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool

The resource supports the following methods:

- [POST](#)

POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

key

JNDI name or resource-link name of the connection pool.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection

The resource supports the following methods:

- [POST](#)

POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

messageListenerType

Message listener type.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getSchema

The resource supports the following methods:

- [POST](#)

POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections](#)
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=MDBRuntimes

This resource's MDBRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume **rel**=action **title**=resume

This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend **rel**=action **title**=suspend

This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=poolRuntime

This resource's poolRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=resources

This resource's resources collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=timerRuntime

This resource's timerRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{n

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/a
ctiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/
{name}/MDBRuntimes/{name}/transactionRuntime **rel**=transactionRuntime

This resource's transactionRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action
title=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool

The resource supports the following methods:

- [POST](#)

POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{n

POST

Resumes the specific type of MDB by calling start on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{n

POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action
title=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{n

POST

Activate any temporarily disabled timers.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resumeAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Suspend a particular type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspendAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime
rel=capacityRuntime
This resource's capacityRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime
rel=maxThreadsConstraintRuntime
This resource's maxThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime
rel=minThreadsConstraintRuntime
This resource's minThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}
rel=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime
rel=requestClassRuntime
This resource's requestClassRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime S

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime
s rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime
s rel=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime rel=capacityRuntime](#)

This resource's capacityRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime rel=maxThreadsConstraintRuntime](#)

This resource's maxThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime rel=minThreadsConstraintRuntime](#)

This resource's minThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime rel=requestClassRuntime](#)

This resource's requestClassRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} rel=self](#)

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimeS/{name}/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/resume

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes the specified type of activity for all RAs

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for all RAs.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/resumeAll

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes all activities of all resource adapters.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

props

Properties to be passed to the resource adapters or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Resumes all activities of all resource adapters.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/suspend

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends the specified type of activity for all RAs

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Suspends the specified type of activity for all RAs.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/suspendAll

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends all activities of all resource adapters.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

props

Properties to be passed to the resource adapters or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Suspends all activities of all resource adapters.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/getConfiguration

The resource supports the following methods:

- [POST](#)

POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/getConnectionPool

The resource supports the following methods:

- [POST](#)

POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

key

JNDI name or resource-link name of the connection pool.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/getInboundConnection

The resource supports the following methods:

- [POST](#)

POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

messageListenerType

Message listener type.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/getSchema

The resource supports the following methods:

- [POST](#)

POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes
rel=MDBRuntimes
This resource's MDBRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume **rel**=action **title**=resume
This resource's resume action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend **rel**=action **title**=suspend
This resource's suspend action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=poolRuntime
This resource's poolRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=resources
This resource's resources collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=timerRuntime
This resource's timerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=transactionRuntime

This resource's transactionRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool

The resource supports the following methods:

- [POST](#)

POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

Resumes the specific type of MDB by calling start on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers](#) **rel**=action **title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers

The resource supports the following methods:

- [POST](#)

POST

Activate any temporarily disabled timers.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/resumeAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Suspend a particular type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/suspendAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#)
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **e**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/getInboundConnections

The resource supports the following methods:

- [POST](#)

POST

Returns runtime information for the specified inbound connection. A null is returned if the inbound connection is not found.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

messageListenerType

Message listener type.

Type: string

Response Body

Contains a JSON object with a array of `weblogic.management.runtime.ConnectorInboundRuntimeMBean` references return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/getRA

The resource supports the following methods:

- [POST](#)

POST

Returns the runtime information of the resource adapter specified by the given JNDI name. A null is returned if the resource adapter cannot be found. This function returns the active RA if multiple versions of the resource adapters has been deployed

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

key

The JNDI name of the resource adapter.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorComponentRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs](#) [rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime](#) [rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs](#) [rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration **rel**=action **title**=getConfiguration
This resource's getConfiguration action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool **rel**=action **title**=getConnectionPool
This resource's getConnectionPool action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection **rel**=action **title**=getInboundConnection
This resource's getInboundConnection action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/getSchema **rel**=action **title**=getSchema
This resource's getSchema action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/resume **rel**=action **title**=resume
This resource's resume action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/resumeAll **rel**=action **title**=resumeAll
This resource's resumeAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/suspend **rel**=action **title**=suspend
This resource's suspend action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/suspendAll **rel**=action **title**=suspendAll
This resource's suspendAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=connectionPools

This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime

This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime

This resource's connectorWorkManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=inboundConnections

This resource's inboundConnections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=workManagerRuntime

This resource's workManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened](#) **rel=action** **title=ensureLogOpened**
This resource's ensureLogOpened action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog](#) **rel=action** **title=flushLog**
This resource's flushLog action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation](#) **rel=action** **title=forceLogRotation**
This resource's forceLogRotation action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset](#) **rel=action** **title=forceReset**
This resource's forceReset action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset](#) **rel=action** **title=reset**
This resource's reset action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool](#) **rel=action** **title=testPool**
This resource's testPool action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections](#) **rel=connections**
This resource's connections collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime](#) **rel=logRuntime**
This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inaactiveRAs/{name}/connectionPools/{name}/connections](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inaactiveRAs/{name}/connectionPools/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inaactiveRAs/{name}/connectionPools/{name}/connections](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/connectionPools/{name}/connections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete

The resource supports the following methods:

- [POST](#)

POST

Provides a way to manually close a connection through the console.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError

The resource supports the following methods:

- [POST](#)

POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection

The resource supports the following methods:

- [POST](#)

POST

Test the connection. Returns true if the test was successful.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset

The resource supports the following methods:

- [POST](#)

POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened
rel=action **title**=ensureLogOpened
This resource's ensureLogOpened action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action
title=flushLog
This resource's flushLog action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation
rel=action **title**=forceLogRotation
This resource's forceLogRotation action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset

The resource supports the following methods:

- [POST](#)

POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool

The resource supports the following methods:

- [POST](#)

POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime

This resource manages a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs **rel**=RAs
 This resource's RAs collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getInboundConnections **rel**=action **title**=getInboundConnections
 This resource's getInboundConnections action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getRA **rel**=action **title**=getRA
 This resource's getRA action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resume **rel**=action **title**=resume
 This resource's resume action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resumeAll **rel**=action **title**=resumeAll
 This resource's resumeAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspend **rel**=action **title**=suspend
 This resource's suspend action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspendAll **rel**=action **title**=suspendAll
 This resource's suspendAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs **rel**=activeRAs
 This resource's activeRAs collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime **rel**=canonical
 This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/inactiveRAs **rel**=inactiveRAs

This resource's inactiveRAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration](#) **rel=action title=getConfiguration**

This resource's `getConfiguration` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool](#) **rel=action title=getConnectionPool**

This resource's `getConnectionPool` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection](#) **rel=action title=getInboundConnection**

This resource's `getInboundConnection` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema](#) **rel=action title=getSchema**

This resource's `getSchema` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume](#) **rel=action title=resume**

This resource's `resume` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll](#) **rel=action title=resumeAll**

This resource's `resumeAll` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend](#) **rel=action title=suspend**

This resource's `suspend` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll](#) **rel=action title=suspendAll**

This resource's `suspendAll` action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=connectionPools
This resource's connectionPools collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime
This resource's connectorServiceRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime
This resource's connectorWorkManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=inboundConnections
This resource's inboundConnections collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=workManagerRuntime
This resource's workManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes
This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/innactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/innactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/innactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened](#) **rel=action** **title=ensureLogOpened**

This resource's ensureLogOpened action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog](#) **rel=action** **title=flushLog**

This resource's flushLog action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation](#) **rel=action** **title=forceLogRotation**

This resource's forceLogRotation action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset](#) **rel=action** **title=forceReset**

This resource's forceReset action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset](#) **rel=action** **title=reset**

This resource's reset action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool](#) **rel=action** **title=testPool**

This resource's testPool action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections](#) **rel=connections**

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo ols/{name}/connections

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo ols/{name}/connections/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete](#) **rel=action** **title=delete**

This resource's delete action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError](#) **rel=action** **title=hasError**

This resource's hasError action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection](#) **rel=action** **title=testConnection**

This resource's testConnection action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}](#) **rel=self**

This resource.

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in
activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo
ols/{name}/connections/{name}/delete**

The resource supports the following methods:

- [POST](#)

POST

Provides a way to manually close a connection through the console.

Roles

Admin

Response Body

Contains an empty JSON object.

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in
activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo
ols/{name}/connections/{name}/hasError**

The resource supports the following methods:

- [POST](#)

POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in
activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo
ols/{name}/connections/{name}/testConnection**

The resource supports the following methods:

- [POST](#)

POST

Test the connection. Returns true if the test was successful.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in
activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo
ols/{name}/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo ols/{name}/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo ols/{name}/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in
activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo
ols/{name}/forceReset**

The resource supports the following methods:

- [POST](#)

POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo ols/{name}/logRuntime

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=self

This resource.

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in
activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo
ols/{name}/logRuntime/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in
activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo
ols/{name}/logRuntime/flushLog**

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in
activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo
ols/{name}/logRuntime/forceLogRotation**

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in
activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo
ols/{name}/reset**

The resource supports the following methods:

- [POST](#)

POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in
activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo
ols/{name}/testPool**

The resource supports the following methods:

- [POST](#)

POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWor kManagerRuntime

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConfigurati on

The resource supports the following methods:

- [POST](#)

POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool

The resource supports the following methods:

- [POST](#)

POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

key

JNDI name or resource-link name of the connection pool.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection

The resource supports the following methods:

- [POST](#)

POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

messageListenerType

Message listener type.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema

The resource supports the following methods:

- [POST](#)

POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=MDBRuntimes

This resource's MDBRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume rel=action title=resume](#)
This resource's resume action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend rel=action title=suspend](#)
This resource's suspend action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime rel=poolRuntime](#)
This resource's poolRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources rel=resources](#)
This resource's resources collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} rel=self](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime rel=timerRuntime](#)
This resource's timerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime
rel=transactionRuntime

This resource's transactionRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool

The resource supports the following methods:

- [POST](#)

POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

Resumes the specific type of MDB by calling start on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action **title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers

The resource supports the following methods:

- [POST](#)

POST

Activate any temporarily disabled timers.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime](#) **rel**=self

This resource.

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in
activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume**

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Suspend a particular type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in
activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll**

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime rel=capacityRuntime](#)
This resource's capacityRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime rel=maxThreadsConstraintRuntime](#)
This resource's maxThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime rel=minThreadsConstraintRuntime](#)
This resource's minThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime rel=requestClassRuntime](#)
This resource's requestClassRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime rel=self](#)

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/innactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/innactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/innactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime rel=self](#)

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManager Runtimes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of `weblogic.management.runtime.WorkManagerRuntimeMBean` instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of `weblogic.management.runtime.WorkManagerRuntimeMBean` entities.

This method can return the following links:

- `uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes rel=canonical`

This resource.

- `uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} rel=parent`

The parent resource of this resource.

- `uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes rel=self`

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=canonical

This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes **rel**=parent

The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/innactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/innactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/innactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/innactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/innactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/innactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getInboundConnections

The resource supports the following methods:

- [POST](#)

POST

Returns runtime information for the specified inbound connection. A null is returned if the inbound connection is not found.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

messageListenerType

Message listener type.

Type: string

Response Body

Contains a JSON object with a array of `weblogic.management.runtime.ConnectorInboundRuntimeMBean` references return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getRA

The resource supports the following methods:

- [POST](#)

POST

Returns the runtime information of the resource adapter specified by the given JNDI name. A null is returned if the resource adapter cannot be found. This function returns the active RA if multiple versions of the resource adapters has been deployed

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

key

The JNDI name of the resource adapter.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorComponentRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration](#)
rel=action **title**=getConfiguration
This resource's getConfiguration action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool](#)
rel=action **title**=getConnectionPool
This resource's getConnectionPool action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection](#)
rel=action **title**=getInboundConnection
This resource's getInboundConnection action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getSchema](#)
rel=action **title**=getSchema
This resource's getSchema action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/resume](#) **rel**=action
title=resume
This resource's resume action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/resumeAll](#)
rel=action **title**=resumeAll
This resource's resumeAll action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/suspend](#) **rel**=action
title=suspend
This resource's suspend action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/suspendAll](#)
rel=action **title**=suspendAll
This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=connectionPools
This resource's connectionPools collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime
This resource's connectorServiceRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime
This resource's connectorWorkManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=inboundConnections
This resource's inboundConnections collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=workManagerRuntime
This resource's workManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes
This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened rel=action title=ensureLogOpened](#)

This resource's ensureLogOpened action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog rel=action title=flushLog](#)

This resource's flushLog action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation rel=action title=forceLogRotation](#)

This resource's forceLogRotation action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset rel=action title=forceReset](#)

This resource's forceReset action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset rel=action title=reset](#)

This resource's reset action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool rel=action title=testPool](#)

This resource's testPool action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections rel=connections](#)

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete

The resource supports the following methods:

- [POST](#)

POST

Provides a way to manually close a connection through the console.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError

The resource supports the following methods:

- [POST](#)

POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection

The resource supports the following methods:

- [POST](#)

POST

Test the connection. Returns true if the test was successful.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset

The resource supports the following methods:

- [POST](#)

POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened rel=action title=ensureLogOpened](#)

This resource's ensureLogOpened action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog rel=action title=flushLog](#)

This resource's flushLog action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation rel=action title=forceLogRotation](#)

This resource's forceLogRotation action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime rel=self](#)

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset

The resource supports the following methods:

- [POST](#)

POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool

The resource supports the following methods:

- [POST](#)

POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration

The resource supports the following methods:

- [POST](#)

POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool

The resource supports the following methods:

- [POST](#)

POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

key

JNDI name or resource-link name of the connection pool.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection

The resource supports the following methods:

- [POST](#)

POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

messageListenerType

Message listener type.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in
activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getSchema**

The resource supports the following methods:

- [POST](#)

POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=MDBRuntimes

This resource's MDBRuntimes collection resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume](#) **rel=action** **title=resume**

This resource's resume action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend](#) **rel=action** **title=suspend**

This resource's suspend action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel=canonical**

This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel=parent**

The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime](#) **rel=poolRuntime**

This resource's poolRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel=resources**

This resource's resources collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel=self**

This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime](#) **rel=timerRuntime**

This resource's timerRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=transactionRuntime

This resource's transactionRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action
title=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool

The resource supports the following methods:

- [POST](#)

POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{

POST

Resumes the specific type of MDB by calling start on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers
rel=action **title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{

POST

Activate any temporarily disabled timers.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resumeAll

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Suspend a particular type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspendAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRunti me

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime rel=capacityRuntime](#)
This resource's capacityRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime rel=maxThreadsConstraintRuntime](#)
This resource's maxThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime rel=minThreadsConstraintRuntime](#)
This resource's minThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime rel=requestClassRuntime](#)
This resource's requestClassRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRunti me/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRunti me/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRunti mes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRunti mes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=capacityRuntime**

This resource's capacityRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**

This resource's maxThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**

This resource's minThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=requestClassRuntime**

This resource's requestClassRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRunti mes/{name}/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resume

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes the specified type of activity for all RAs

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for all RAs.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resumeAll

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes all activities of all resource adapters.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

props

Properties to be passed to the resource adapters or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Resumes all activities of all resource adapters.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspend

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends the specified type of activity for all RAs

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Suspends the specified type of activity for all RAs.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspendAll

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends all activities of all resource adapters.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

props

Properties to be passed to the resource adapters or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Suspends all activities of all resource adapters.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration

The resource supports the following methods:

- [POST](#)

POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool

The resource supports the following methods:

- [POST](#)

POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

key

JNDI name or resource-link name of the connection pool.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection

The resource supports the following methods:

- [POST](#)

POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

messageListenerType

Message listener type.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/getSchema

The resource supports the following methods:

- [POST](#)

POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes](#)
[rel=MDBRuntimes](#)
This resource's MDBRuntimes collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}](#) [rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections](#) [rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}](#) [rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume rel=action title=resume](#)
This resource's resume action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend rel=action title=suspend](#)
This resource's suspend action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime rel=poolRuntime](#)
This resource's poolRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources rel=resources](#)
This resource's resources collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} rel=self](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime rel=timerRuntime](#)
This resource's timerRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime rel=transactionRuntime](#)

This resource's transactionRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool

The resource supports the following methods:

- [POST](#)

POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

Resumes the specific type of MDB by calling start on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers](#) **rel=action** **title=activateDisabledTimers**

This resource's activateDisabledTimers action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers

The resource supports the following methods:

- [POST](#)

POST

Activate any temporarily disabled timers.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/resumeAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Suspend a particular type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/suspendAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#)
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#)
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inaactiveRAs/{name}/workManagerRuntimes](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inaactiveRAs/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inaactiveRAs/{name}/workManagerRuntimes](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntimes/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#)
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/R](#)
[As rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime](#)
[rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/R](#)
[As rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/getConfiguration **rel**=action **title**=getConfiguration
This resource's getConfiguration action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/getConnectionPool **rel**=action **title**=getConnectionPool
This resource's getConnectionPool action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/getInboundConnection **rel**=action **title**=getInboundConnection
This resource's getInboundConnection action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/getSchema **rel**=action **title**=getSchema
This resource's getSchema action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/resume **rel**=action **title**=resume
This resource's resume action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/resumeAll **rel**=action **title**=resumeAll
This resource's resumeAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/suspend **rel**=action **title**=suspend
This resource's suspend action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/suspendAll **rel**=action **title**=suspendAll
This resource's suspendAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=connectionPools
This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime
This resource's connectorServiceRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime
This resource's connectorWorkManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=inboundConnections
This resource's inboundConnections collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=workManagerRuntime
This resource's workManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes
This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` entity.

This method can return the following links:

- **uri**=</management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened> **rel**=action **title**=ensureLogOpened
This resource's ensureLogOpened action resource.
- **uri**=</management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog> **rel**=action **title**=flushLog
This resource's flushLog action resource.
- **uri**=</management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation> **rel**=action **title**=forceLogRotation
This resource's forceLogRotation action resource.
- **uri**=</management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset> **rel**=action **title**=forceReset
This resource's forceReset action resource.
- **uri**=</management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset> **rel**=action **title**=reset
This resource's reset action resource.
- **uri**=</management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool> **rel**=action **title**=testPool
This resource's testPool action resource.
- **uri**=</management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}> **rel**=canonical
This resource.
- **uri**=</management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections> **rel**=connections
This resource's connections collection resource.
- **uri**=</management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime> **rel**=logRuntime
This resource's logRuntime singleton resource.
- **uri**=</management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools> **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete

The resource supports the following methods:

- [POST](#)

POST

Provides a way to manually close a connection through the console.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError

The resource supports the following methods:

- [POST](#)

POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection

The resource supports the following methods:

- [POST](#)

POST

Test the connection. Returns true if the test was successful.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset

The resource supports the following methods:

- [POST](#)

POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened](#) **rel**=action
title=ensureLogOpened
This resource's ensureLogOpened action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog](#) **rel**=action
title=flushLog
This resource's flushLog action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation](#) **rel**=action
title=forceLogRotation
This resource's forceLogRotation action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset

The resource supports the following methods:

- [POST](#)

POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool

The resource supports the following methods:

- [POST](#)

POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime

This resource manages a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/RAs **rel**=RAs
This resource's RAs collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getInboundConnections **rel**=action **title**=getInboundConnections
This resource's getInboundConnections action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getRA **rel**=action **title**=getRA
This resource's getRA action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resume **rel**=action **title**=resume
This resource's resume action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resumeAll **rel**=action **title**=resumeAll
This resource's resumeAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspend **rel**=action **title**=suspend
This resource's suspend action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspendAll **rel**=action **title**=suspendAll
This resource's suspendAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs **rel**=activeRAs
This resource's activeRAs collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs **rel**=inactiveRAs
This resource's inactiveRAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration](#) **rel**=action **title**=getConfiguration
This resource's getConfiguration action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool](#) **rel**=action **title**=getConnectionPool
This resource's getConnectionPool action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection](#) **rel**=action **title**=getInboundConnection
This resource's getInboundConnection action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema](#) **rel**=action **title**=getSchema
This resource's getSchema action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume](#) **rel**=action **title**=resume
This resource's resume action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll](#) **rel**=action **title**=resumeAll
This resource's resumeAll action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend](#) **rel**=action **title**=suspend
This resource's suspend action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll](#) **rel**=action **title**=suspendAll
This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=connectionPools
This resource's connectionPools collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime
This resource's connectorServiceRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime
This resource's connectorWorkManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=inboundConnections
This resource's inboundConnections collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=workManagerRuntime
This resource's workManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes
This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset **rel**=action **title**=forceReset

This resource's forceReset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset **rel**=action **title**=reset

This resource's reset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool **rel**=action **title**=testPool

This resource's testPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=connections

This resource's connections collection resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{n

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{n

POST

Provides a way to manually close a connection through the console.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError

The resource supports the following methods:

- [POST](#)

POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{n

POST

Test the connection. Returns true if the test was successful.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{n

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset

The resource supports the following methods:

- [POST](#)

POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{n

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{n

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset

The resource supports the following methods:

- [POST](#)

POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{n

POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration

The resource supports the following methods:

- [POST](#)

POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool

The resource supports the following methods:

- [POST](#)

POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

key

JNDI name or resource-link name of the connection pool.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection

The resource supports the following methods:

- [POST](#)

POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

messageListenerType

Message listener type.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema

The resource supports the following methods:

- [POST](#)

POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=MDBRuntimes

This resource's MDBRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume rel=action title=resume](#)

This resource's resume action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend rel=action title=suspend](#)

This resource's suspend action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime rel=poolRuntime](#)

This resource's poolRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources rel=resources](#)

This resource's resources collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} rel=self](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime rel=timerRuntime](#)

This resource's timerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=transactionRuntime

This resource's transactionRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action
title=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool

The resource supports the following methods:

- [POST](#)

POST

Instructs the Pool to initialize itself to its configured startup time size.
This is a synchronous and will wait until the pool is initialized before returning.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

Resumes the specific type of MDB by calling start on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers](#) **rel**=action **title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers

The resource supports the following methods:

- [POST](#)

POST

Activate any temporarily disabled timers.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Suspend a particular type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime
rel=capacityRuntime
This resource's capacityRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime
rel=maxThreadsConstraintRuntime
This resource's maxThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime
rel=minThreadsConstraintRuntime
This resource's minThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}
rel=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime
rel=requestClassRuntime
This resource's requestClassRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime S

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimeS/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimeS/{name} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimeS/{name}/capacityRuntime rel=capacityRuntime](#)

This resource's capacityRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimeS/{name}/maxThreadsConstraintRuntime rel=maxThreadsConstraintRuntime](#)

This resource's maxThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimeS/{name}/minThreadsConstraintRuntime rel=minThreadsConstraintRuntime](#)

This resource's minThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimeS rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimeS/{name}/requestClassRuntime rel=requestClassRuntime](#)

This resource's requestClassRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimeS/{name} rel=self](#)

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime rel=self](#)

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getInboundConnections

The resource supports the following methods:

- [POST](#)

POST

Returns runtime information for the specified inbound connection. A null is returned if the inbound connection is not found.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

messageListenerType

Message listener type.

Type: string

Response Body

Contains a JSON object with a array of `weblogic.management.runtime.ConnectorInboundRuntimeMBean` references return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getRA

The resource supports the following methods:

- [POST](#)

POST

Returns the runtime information of the resource adapter specified by the given JNDI name. A null is returned if the resource adapter cannot be found. This function returns the active RA if multiple versions of the resource adapters has been deployed

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

key

The JNDI name of the resource adapter.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorComponentRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration
rel=action **title**=getConfiguration
This resource's getConfiguration action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool
rel=action **title**=getConnectionPool
This resource's getConnectionPool action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection
rel=action **title**=getInboundConnection
This resource's getInboundConnection action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema
rel=action **title**=getSchema
This resource's getSchema action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume
rel=action **title**=resume
This resource's resume action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll
rel=action **title**=resumeAll
This resource's resumeAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend
rel=action **title**=suspend
This resource's suspend action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll
rel=action **title**=suspendAll
This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=connectionPools

This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime

This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime

This resource's connectorWorkManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=inboundConnections

This resource's inboundConnections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=workManagerRuntime

This resource's workManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened](#) **rel=action** **title=ensureLogOpened**

This resource's ensureLogOpened action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog](#) **rel=action** **title=flushLog**

This resource's flushLog action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation](#) **rel=action** **title=forceLogRotation**

This resource's forceLogRotation action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset](#) **rel=action** **title=forceReset**

This resource's forceReset action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset](#) **rel=action** **title=reset**

This resource's reset action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool](#) **rel=action** **title=testPool**

This resource's testPool action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections](#) **rel=connections**

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete rel=action title=delete](#)

This resource's delete action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError rel=action title=hasError](#)

This resource's hasError action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection rel=action title=testConnection](#)

This resource's testConnection action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name} rel=self](#)

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete

The resource supports the following methods:

- [POST](#)

POST

Provides a way to manually close a connection through the console.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError

The resource supports the following methods:

- [POST](#)

POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection

The resource supports the following methods:

- [POST](#)

POST

Test the connection. Returns true if the test was successful.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset

The resource supports the following methods:

- [POST](#)

POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset

The resource supports the following methods:

- [POST](#)

POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool

The resource supports the following methods:

- [POST](#)

POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration

The resource supports the following methods:

- [POST](#)

POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool

The resource supports the following methods:

- [POST](#)

POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

key

JNDI name or resource-link name of the connection pool.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection

The resource supports the following methods:

- [POST](#)

POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

messageListenerType

Message listener type.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema

The resource supports the following methods:

- [POST](#)

POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections](#)
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=MDBRuntimes

This resource's MDBRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume](#) **rel=action** **title=resume**

This resource's resume action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend](#) **rel=action** **title=suspend**

This resource's suspend action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime](#) **rel=poolRuntime**

This resource's poolRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel=resources**

This resource's resources collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel=self**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime](#) **rel=timerRuntime**

This resource's timerRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=transactionRuntime

This resource's transactionRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action
title=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool

The resource supports the following methods:

- [POST](#)

POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

Resumes the specific type of MDB by calling start on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers
rel=action **title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{

POST

Activate any temporarily disabled timers.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Suspend a particular type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel=capacityRuntime**
This resource's capacityRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**
This resource's maxThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**
This resource's minThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel=requestClassRuntime**
This resource's requestClassRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=capacityRuntime**

This resource's capacityRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**

This resource's maxThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**

This resource's minThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=requestClassRuntime**

This resource's requestClassRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resume

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes the specified type of activity for all RAs

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for all RAs.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resumeAll

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes all activities of all resource adapters.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

props

Properties to be passed to the resource adapters or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Resumes all activities of all resource adapters.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspend

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends the specified type of activity for all RAs

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Suspends the specified type of activity for all RAs.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspendAll

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends all activities of all resource adapters.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

props

Properties to be passed to the resource adapters or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Suspends all activities of all resource adapters.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/getConfiguration

The resource supports the following methods:

- [POST](#)

POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/getConnectionPool

The resource supports the following methods:

- [POST](#)

POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

key

JNDI name or resource-link name of the connection pool.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/getInboundConnection

The resource supports the following methods:

- [POST](#)

POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

messageListenerType

Message listener type.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/getSchema

The resource supports the following methods:

- [POST](#)

POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel=MDBRuntimes**
This resource's MDBRuntimes collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume
rel=action **title**=resume
This resource's resume action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend
rel=action **title**=suspend
This resource's suspend action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime
rel=poolRuntime
This resource's poolRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources
rel=resources
This resource's resources collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime
rel=timerRuntime
This resource's timerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime
rel=transactionRuntime
This resource's transactionRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool

The resource supports the following methods:

- [POST](#)

POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#)
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

Resumes the specific type of MDB by calling start on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action **title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers

The resource supports the following methods:

- [POST](#)

POST

Activate any temporarily disabled timers.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/resumeAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Suspend a particular type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/suspendAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime **rel**=capacityRuntime
This resource's capacityRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime
This resource's maxThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime
This resource's minThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime **rel**=requestClassRuntime
This resource's requestClassRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#)
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/resume

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes the specified type of activity for all RAs

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for all RAs.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/resumeAll

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes all activities of all resource adapters.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

props

Properties to be passed to the resource adapters or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Resumes all activities of all resource adapters.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/suspend

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends the specified type of activity for all RAs

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Suspends the specified type of activity for all RAs.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/suspendAll

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends all activities of all resource adapters.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

props

Properties to be passed to the resource adapters or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Suspends all activities of all resource adapters.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/defaultExecuteQueueRuntime

This resource manages a [weblogic.management.runtime.ExecuteQueueRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ExecuteQueueRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ExecuteQueueRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/defaultExecuteQueueRuntime](#) [rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime](#) [rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/defaultExecuteQueueRuntime](#) [rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/entityCacheCumulativeRuntime

This resource manages a [weblogic.management.runtime.EntityCacheCumulativeRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EntityCacheCumulativeRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EntityCacheCumulativeRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/entityCacheCumulativeRuntime rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/entityCacheCumulativeRuntime rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/entityCacheCurrentStateRuntime

This resource manages a [weblogic.management.runtime.EntityCacheCurrentStateRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EntityCacheCurrentStateRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EntityCacheCurrentStateRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/entityCacheCurrentStateRuntime rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/entityCacheCurrentStateRuntime rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/entityCacheHistoricalRuntime

This resource manages a [weblogic.management.runtime.EntityCacheCumulativeRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EntityCacheCumulativeRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EntityCacheCumulativeRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/entityCacheHistoricalRuntime rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/entityCacheHistoricalRuntime rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/executeQueueRuntimes

This resource manages a collection of [weblogic.management.runtime.ExecuteQueueRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ExecuteQueueRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ExecuteQueueRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/executeQueueRuntimes](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/executeQueueRuntimes](#)
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/executeQueueRuntimes/{name}

This resource manages a [weblogic.management.runtime.ExecuteQueueRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ExecuteQueueRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ExecuteQueueRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/executeQueueRuntimes/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/executeQueueRuntimes](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/executeQueueRuntimes/{name}](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/forceShutdown

The resource supports the following methods:

- [POST](#)

POST

Force shutdown the server. Causes the server to reject new requests and fail pending requests.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/forceShutdownResourceGroup

The resource supports the following methods:

- [POST](#)

POST

Force shutdown the resource group. Causes the resource group to reject new requests and fail pending requests.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName

resourceGroupName

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/forceSuspend

The resource supports the following methods:

- [POST](#)

POST

Transitions the server from `RUNNING` to `ADMIN` state forcefully cancelling inflight work. Work that cannot be cancelled is dropped. Applications are brought into the admin mode. This is the supported way of force suspending the server and getting it into `ADMIN` state.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/forceSuspendResourceGroup

The resource supports the following methods:

- [POST](#)

POST

Transitions the resource group from `RUNNING` to `ADMIN` state forcefully cancelling inflight work.

Work that cannot be cancelled is dropped. Applications are brought into the admin mode. This is the supported way of force suspending the resource group and getting it into `ADMIN` state.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

resourceGroupName

resourceGroupName

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/getIPv4URL

The resource supports the following methods:

- [POST](#)

POST

The URL that clients use when connecting to this server using the specified protocol.

Note: The listen address and listen port for a given protocol are persisted in the domain's `config.xml` file, however when a server instance is started, command-line options can override these persisted values. This `getURL` method returns the URL values that are currently being used, not necessarily the values that are specified in `config.xml`

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

protocol
the desired protocol
Type: string

Response Body

Contains a JSON object with a string return field.

Example

Example 1 Invoke the getIPv4URL Action

This example uses the POST method to invoke the `getIPv4URL` action.

Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-H Content-Type:application/json \  
-d "{ protocol: 'http' }" \  
-X POST http://localhost:7001/management/weblogic/latest/serverRuntime/getIPv4URL
```

Example Response

```
HTTP/1.1 200 OK
```

```
Response Body:  
{"return": "http://localhost:7001"}
```

/management/weblogic/{version}/serverRuntime/getIPv6URL

The resource supports the following methods:

- [POST](#)

POST

The URL that clients use when connecting to this server using the specified protocol.

Note: The listen address and listen port for a given protocol are persisted in the domain's `config.xml` file, however when a server instance is started, command-line options can override these persisted values. This `getURL` method returns the URL values that are currently being used, not necessarily the values that are specified in `config.xml`

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

protocol

the desired protocol

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/getRgState

The resource supports the following methods:

- [POST](#)

POST

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName

resourceGroupName

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/getURL

The resource supports the following methods:

- [POST](#)

POST

The URL that clients use when connecting to this server using the specified protocol.

Note: The listen address and listen port for a given protocol are persisted in the domain's `config.xml` file, however when a server instance is started, command-line options can override these persisted values. This `getURL` method returns the URL values that are currently being used, not necessarily the values that are specified in `config.xml`

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

protocol

the desired protocol

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime

This resource manages a [weblogic.management.runtime.JDBCServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JDBCServiceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JDBCServiceRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans](#) [rel=JDBCDataSourceRuntimeMBeans](#)
This resource's JDBCDataSourceRuntimeMBeans collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDriverRuntimeMBeans](#) [rel=JDBCDriverRuntimeMBeans](#)
This resource's JDBCDriverRuntimeMBeans collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans](#) [rel=JDBCMultiDataSourceRuntimeMBeans](#)
This resource's JDBCMultiDataSourceRuntimeMBeans collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime](#) [rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime](#) [rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime](#) [rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans

This resource manages a collection of [weblogic.management.runtime.JDBCDataSourceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JDBCDataSourceRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JDBCDataSourceRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}

This resource manages a [weblogic.management.runtime.JDBCDataSourceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JDBCDataSourceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JDBCDataSourceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JBCDriverRuntime
rel=JBCDriverRuntime
This resource's JBCDriverRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JBCReplayStatisticsRuntimeMBean
rel=JBCReplayStatisticsRuntimeMBean
This resource's JBCReplayStatisticsRuntimeMBean singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/clearStatementCache **rel**=action
title=clearStatementCache
This resource's clearStatementCache action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPool **rel**=action **title**=dumpPool
This resource's dumpPool action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPoolProfile **rel**=action
title=dumpPoolProfile
This resource's dumpPoolProfile action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceShutdown **rel**=action
title=forceShutdown
This resource's forceShutdown action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceSuspend **rel**=action **title**=forceSuspend
This resource's forceSuspend action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/poolExists **rel**=action **title**=poolExists
This resource's poolExists action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/reset **rel**=action **title**=reset
This resource's reset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/resume **rel**=action **title**=resume
This resource's resume action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/shrink **rel**=action **title**=shrink
This resource's shrink action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/shutdown **rel**=action **title**=shutdown
This resource's shutdown action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/start **rel**=action **title**=start
This resource's start action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/suspend **rel**=action **title**=suspend
This resource's suspend action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/testPool **rel**=action **title**=testPool
This resource's testPool action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name} **rel**=canonical
This resource.
- **rel**=lastTask
This resource's lastTask reference to a weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes **rel**=workManagerRuntimes
This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/clearStatementCache

The resource supports the following methods:

- [POST](#)

POST

For each connection in the connection pool, clears the statement cache of Prepared and Callable Statements.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPool

The resource supports the following methods:

- [POST](#)

POST

Prints out information about all the connections in the connection pool in the data source.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPoolProfile

The resource supports the following methods:

- [POST](#)

POST

POST

Prints out profile information about the data source.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceShutdown

The resource supports the following methods:

- [POST](#)

POST

Shuts down a data source that has a health state of `Running`, including forcing the disconnection of all current connection users.

If successful, the health state is set to `Shutdown`

This is a privileged operation that can only be invoked by an authorized user.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceSuspend

The resource supports the following methods:

- [POST](#)

POST

Suspends a data source that has the health state of `Running`, including disconnecting all current connection users. All current connections are closed and recreated.

If successful, the health state is set to `Suspended`

This is a privileged operation that can only be invoked by an authorized user.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCDriverRuntime

This resource manages a [weblogic.management.runtime.JDBCDriverRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JDBCDataSourceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JDBCDataSourceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCDataSourceRuntimeMBean](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCDataSourceRuntimeMBean](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean

This resource manages a [weblogic.management.runtime.JDBCReplayStatisticsRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JDBCReplayStatisticsRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JDBCReplayStatisticsRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/clearStatistics **rel**=action **title**=clearStatistics
This resource's clearStatistics action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/refreshStatistics **rel**=action **title**=refreshStatistics
This resource's refreshStatistics action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes **rel**=workManagerRuntimes
This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/clearStatistics

The resource supports the following methods:

- [POST](#)

POST

Clear the statistics on all connections.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/refreshStatistics

The resource supports the following methods:

- [POST](#)

POST

POST

Update the snapshot

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/capacityRuntime](#) **rel=capacityRuntime**

This resource's capacityRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**

This resource's maxThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**

This resource's minThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=requestClassRuntime**

This resource's requestClassRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/poolExists

The resource supports the following methods:

- [POST](#)

POST

Specifies whether a data source with the given name exists.

This is a privileged operation that can only be invoked by an authorized user.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

poolName

Name of the pool being looked for

Type: string

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/reset

The resource supports the following methods:

- [POST](#)

POST

Resets the connection pool in the data source by shutting down and recreating all available database connections in the pool.

Use when a data source is in the health state of `Unhealthy` and needs to be reinitialized.

This is a privileged operation that can only be invoked by an authorized user.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

Restores all access to and operations on a data source that has a health state of `Suspended`

If successful, the health state is set to `Running`

This is a privileged operation that can only be invoked by an authorized user.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/shrink

The resource supports the following methods:

- [POST](#)

POST

Shrinks the database connection pool in the data source to either the current number of reserved connections or the initial size of the connection pool, whichever is greater.

This is a privileged operation that can only be invoked by an authorized user.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/shutdown

The resource supports the following methods:

- [POST](#)

POST

Shuts down a data source that has a health state of `Running`. If any connections from the data source are currently in use, the operation fails and the health state remains `Running`

If successful, the health state is set to `Shutdown`

This is a privileged operation that can only be invoked by an authorized user.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/start

The resource supports the following methods:

- [POST](#)

POST

Starts a data source that has a health state of `Shutdown`

If successful, the health state is set to `Running`

This is a privileged operation that can only be invoked by an authorized user.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

Suspends a data source has the health state of `Running` and disables existing connections. If any connections from the data source are currently in use, the operation fails and the health state remains `Running`

If successful, the health state is set to `Suspended`

This is a privileged operation that can only be invoked by an authorized user.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/testPool

The resource supports the following methods:

- [POST](#)

POST

Tests the connection pool in the data source by reserving and releasing a connection from it.

If the pool configuration attribute `TestConnectionsOnReserve` is enabled, the acquired connection is also tested as part of the reserve operation.

Roles

Admin

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime
This resource's capacityRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime
This resource's maxThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime
This resource's minThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime
This resource's requestClassRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC DriverRuntimeMBeans

This resource manages a collection of [weblogic.management.runtime.JDBCDriverRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JDBCDriverRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JDBCDriverRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC
DriverRuntimeMBeans](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime](#)
rel=parent

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC
DriverRuntimeMBeans](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC DriverRuntimeMBeans/{name}

This resource manages a [weblogic.management.runtime.JDBCDriverRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JDBCDriverRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JDBCDriverRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC
DriverRuntimeMBeans/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC
DriverRuntimeMBeans](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC
DriverRuntimeMBeans/{name}](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans

This resource manages a collection of [weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}

This resource manages a [weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}](#) **rel**=self

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes](#) **rel**=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime
This resource's capacityRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime
This resource's maxThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime
This resource's minThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime
This resource's requestClassRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capa cityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/max ThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minT hreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requ estClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime

This resource manages a [weblogic.management.runtime.JMSRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers](#)
rel=JMSServers
This resource's JMSServers collection resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections](#)
rel=connections
This resource's connections collection resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime/connections

This resource manages a collection of [weblogic.management.runtime.JMSConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JMSConnectionRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JMSConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections](#)
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}

This resource manages a [weblogic.management.runtime.JMSConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSConnectionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/destroy](#) **rel**=action **title**=destroy
This resource's destroy action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions](#) **rel**=sessions
This resource's sessions collection resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/destroy

The resource supports the following methods:

- [POST](#)

POST

Destroys server side context for the connection.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions

This resource manages a collection of [weblogic.management.runtime.JMSSessionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JMSSessionRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JMSSessionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}

This resource manages a [weblogic.management.runtime.JMSSessionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSSessionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSSessionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/consumers](#) **rel**=consumers

This resource's consumers collection resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/producers](#) **rel**=producers

This resource's producers collection resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/consumers

This resource manages a collection of [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/consumers](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/consumers](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/consumers/{name}

This resource manages a [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/consumers/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/consumers](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/consumers/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/producers

This resource manages a collection of [weblogic.management.runtime.JMSProducerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JMSProducerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JMSProducerRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/producers](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/producers](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/producers/{name}

This resource manages a [weblogic.management.runtime.JMSProducerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSProducerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSProducerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/producers/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/producers](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/producers/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers

This resource manages a collection of [weblogic.management.runtime.JMServerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JMServerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JMServerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMServers](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMServers](#)
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}

This resource manages a [weblogic.management.runtime.JMServerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSServerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSServerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/closeCursor](#) **rel=action** **title=closeCursor**
This resource's closeCursor action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/forceCommit](#) **rel=action** **title=forceCommit**
This resource's forceCommit action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/forceRollback](#) **rel=action** **title=forceRollback**
This resource's forceRollback action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/getCursorEndPosition](#) **rel=action** **title=getCursorEndPosition**
This resource's getCursorEndPosition action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/getCursorSize](#) **rel=action** **title=getCursorSize**
This resource's getCursorSize action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/getCursorStartPosition](#) **rel=action** **title=getCursorStartPosition**
This resource's getCursorStartPosition action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/getMessages](#) **rel=action** **title=getMessages**
This resource's getMessages action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/getTransactionStatus](#) **rel=action** **title=getTransactionStatus**
This resource's getTransactionStatus action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/pauseConsumption](#) **rel=action** **title=pauseConsumption**
This resource's pauseConsumption action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/pauseInsertion](#) **rel=action** **title=pauseInsertion**
This resource's pauseInsertion action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/pauseProduction](#) **rel=action** **title=pauseProduction**

This resource's pauseProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/resumeConsumption **rel**=action **title**=resumeConsumption

This resource's resumeConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/resumeInsertion **rel**=action **title**=resumeInsertion

This resource's resumeInsertion action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/resumeProduction **rel**=action **title**=resumeProduction

This resource's resumeProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sort **rel**=action **title**=sort

This resource's sort action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations **rel**=destinations

This resource's destinations collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes **rel**=sessionPoolRuntimes

This resource's sessionPoolRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/closeCursor

The resource supports the following methods:

- [POST](#)

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations

This resource manages a collection of [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}

This resource manages a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/closeCursor](#) **rel=action** **title=closeCursor**
This resource's closeCursor action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/createDurableSubscriber](#) **rel=action** **title=createDurableSubscriber**
This resource's createDurableSubscriber action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/deleteMessages](#) **rel=action** **title=deleteMessages**
This resource's deleteMessages action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorEndPosition](#) **rel=action** **title=getCursorEndPosition**
This resource's getCursorEndPosition action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorSize](#) **rel=action** **title=getCursorSize**
This resource's getCursorSize action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorStartPosition](#) **rel=action** **title=getCursorStartPosition**
This resource's getCursorStartPosition action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/getMessages](#) **rel=action** **title=getMessages**
This resource's getMessages action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseConsumption](#) **rel=action** **title=pauseConsumption**
This resource's pauseConsumption action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseInsertion](#) **rel=action** **title=pauseInsertion**
This resource's pauseInsertion action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseProduction](#) **rel=action** **title=pauseProduction**

This resource's pauseProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeConsumption **rel**=action **title**=resumeConsumption

This resource's resumeConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeInsertion **rel**=action **title**=resumeInsertion

This resource's resumeInsertion action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeProduction **rel**=action **title**=resumeProduction

This resource's resumeProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/sort **rel**=action **title**=sort

This resource's sort action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers **rel**=durableSubscribers

This resource's durableSubscribers collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/closeCursor

The resource supports the following methods:

- [POST](#)

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/createDurableSubscriber

The resource supports the following methods:

- [POST](#)

POST

Creates a durable subscriber on the destination with the specified client ID and subscription name. A message selector and no-local flag may also be specified.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

ClientID

An identifier that uniquely identifies a client connection.

Type: string

subscriptionName

The name used to identify this subscription.

Type: string

selector

Only messages with properties matching the message selector expression are delivered. A value of null or an empty string indicates that there is no message selector for the message consumer.

Type: string

noLocal

If set, inhibits the delivery of messages published by its own connection.

Type: boolean

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/deleteMessages

The resource supports the following methods:

- [POST](#)

POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A JMS message selector to identify which messages to delete.

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers

This resource manages a collection of [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}

This resource manages a [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/closeCursor **rel**=action **title**=closeCursor
This resource's closeCursor action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/deleteMessages **rel**=action **title**=deleteMessages
This resource's deleteMessages action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorEndPosition **rel**=action **title**=getCursorEndPosition
This resource's getCursorEndPosition action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorSize **rel**=action **title**=getCursorSize
This resource's getCursorSize action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorStartPosition **rel**=action **title**=getCursorStartPosition
This resource's getCursorStartPosition action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getMessages **rel**=action **title**=getMessages
This resource's getMessages action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/sort **rel**=action **title**=sort
This resource's sort action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name} **rel**=canonical
This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime
rel=destinationRuntime

This resource's destinationRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/closeCursor

The resource supports the following methods:

- [POST](#)

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/deleteMessages

The resource supports the following methods:

- [POST](#)

POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A JMS message selector to identify which messages to delete.

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime

This resource manages a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor rel=action title=closeCursor](#)

This resource's closeCursor action resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/createDurableSubscriber rel=action title=createDurableSubscriber](#)

This resource's createDurableSubscriber action resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessages rel=action title=deleteMessages](#)

This resource's deleteMessages action resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorEndPosition rel=action title=getCursorEndPosition](#)

This resource's getCursorEndPosition action resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSize rel=action title=getCursorSize](#)

This resource's getCursorSize action resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorStartPosition rel=action title=getCursorStartPosition](#)

This resource's getCursorStartPosition action resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages rel=action title=getMessages](#)

This resource's getMessages action resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsumption rel=action title=pauseConsumption](#)

This resource's pauseConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertion **rel**=action **title**=pauseInsertion
This resource's pauseInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduction **rel**=action **title**=pauseProduction
This resource's pauseProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsumption **rel**=action **title**=resumeConsumption
This resource's resumeConsumption action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInsertion **rel**=action **title**=resumeInsertion
This resource's resumeInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProduction **rel**=action **title**=resumeProduction
This resource's resumeProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/sort **rel**=action **title**=sort
This resource's sort action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/durableSubscribers **rel**=durableSubscribers
This resource's durableSubscribers collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor

The resource supports the following methods:

- [POST](#)

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/createDurableSubscriber

The resource supports the following methods:

- [POST](#)

POST

Creates a durable subscriber on the destination with the specified client ID and subscription name. A message selector and no-local flag may also be specified.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

ClientID

An identifier that uniquely identifies a client connection.

Type: string

subscriptionName

The name used to identify this subscription.

Type: string

selector

Only messages with properties matching the message selector expression are delivered. A value of null or an empty string indicates that there is no message selector for the message consumer.

Type: string

noLocal

If set, inhibits the delivery of messages published by its own connection.

Type: boolean

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessages

The resource supports the following methods:

- [POST](#)

POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A JMS message selector to identify which messages to delete.

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSize

The resource supports the following methods:

- [POST](#)

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A valid JMS message selector.

Type: string

timeout

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

state

A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

Type: int

Response Body

Contains a JSON object with a string return field.

POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A valid JMS message selector.

Type: string

timeout

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsumption

The resource supports the following methods:

- [POST](#)

POST

Pauses the consumption on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertion

The resource supports the following methods:

- [POST](#)

POST

Pauses the insertion on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduction

The resource supports the following methods:

- [POST](#)

POST

Pauses the production on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsumption

The resource supports the following methods:

- [POST](#)

POST

Resumes the consumption operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInsertion

The resource supports the following methods:

- [POST](#)

POST

Resumes the insertion operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProduction

The resource supports the following methods:

- [POST](#)

POST

Resumes the production operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/sort

The resource supports the following methods:

- [POST](#)

POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The handle of the cursor.

Type: string

start

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

Type: long

fields

The JMS header attributes on which to sort.

Type: array of string

ascending

Determines whether the sort of the corresponding fields element is in ascending or descending order.

Type: array of boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorEndPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorSize

The resource supports the following methods:

- [POST](#)

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorStartPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getMessages

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A valid JMS message selector.

Type: string

timeout

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

state

A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

Type: int

Response Body

Contains a JSON object with a string return field.

POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A valid JMS message selector.

Type: string

timeout

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/sort

The resource supports the following methods:

- [POST](#)

POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The handle of the cursor.

Type: string

start

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

Type: long

fields

The JMS header attributes on which to sort.

Type: array of string

ascending

Determines whether the sort of the corresponding fields element is in ascending or descending order.

Type: array of boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorSize

The resource supports the following methods:

- [POST](#)

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorStartPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/getMessages

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A valid JMS message selector.

Type: string

timeout

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

state

A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

Type: int

Response Body

Contains a JSON object with a string return field.

POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A valid JMS message selector.

Type: string

timeout

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseConsumption

The resource supports the following methods:

- [POST](#)

POST

Pauses the consumption on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseInsertion

The resource supports the following methods:

- [POST](#)

POST

Pauses the insertion on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseProduction

The resource supports the following methods:

- [POST](#)

POST

Pauses the production on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeConsumption

The resource supports the following methods:

- [POST](#)

POST

Resumes the consumption operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeInsertion

The resource supports the following methods:

- [POST](#)

POST

Resumes the insertion operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeProduction

The resource supports the following methods:

- [POST](#)

POST

Resumes the production operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/sort

The resource supports the following methods:

- [POST](#)

POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The handle of the cursor.

Type: string

start

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

Type: long

fields

The JMS header attributes on which to sort.

Type: array of string

ascending

Determines whether the sort of the corresponding fields element is in ascending or descending order.

Type: array of boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/forceCommit

The resource supports the following methods:

- [POST](#)

POST

Causes the work associated with the specified transaction branch to be committed.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

xid

An xid in string representation for a JMS transaction branch.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/forceRollback

The resource supports the following methods:

- [POST](#)

POST

Causes the work associated with the specified transaction branch to be rolled back.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

xid

An xid in string representation for a JMS transaction branch.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/getCursorPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/getCursorSize

The resource supports the following methods:

- [POST](#)

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/getCursorPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/getMessages

The resource supports the following methods:

- [POST](#)

POST

Returns a set of messages that are associated with a JMS transaction branch. Note that the result set is returned to the caller in the form of a message cursor that may contain messages from several destinations on this JMS server.

The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

xid

An Xid in string representation for a JMS transaction branch.

Type: string

timeoutSeconds

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/getTransactionStatus

The resource supports the following methods:

- [POST](#)

POST

Given an Xid this method returns the JTA status of the associated JMS transaction branch.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

xid

An Xid in string representation for a JMS transaction branch.

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/logRuntime

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/logRuntime/ensureLogOpened rel=action title=ensureLogOpened](#)
This resource's ensureLogOpened action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/logRuntime/flushLog rel=action title=flushLog](#)
This resource's flushLog action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/logRuntime/forceLogRotation rel=action title=forceLogRotation](#)
This resource's forceLogRotation action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/logRuntime rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name} rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/logRuntime rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/logRuntime/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/pauseConsumption

The resource supports the following methods:

- [POST](#)

POST

Pauses the consumption operation on all the destinations hosted by the JMSServer.

When the JMSServer is paused for consumption, all of its destination's state is marked as "consumption paused" and all the new synchronous receive operations will block until the destination is resumed and there are messages available for consumption. All the synchronous receive with blocking timeout will block until the timeout happens during the consumption paused state.

All the asynchronous consumers attached to that destination will not get any messages delivered to them while the destination in "consumption paused" state.

After a successful consumption "pause" operation, the user has to explicitly "resume" the destination to allow for any further consume operations on that destination

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/pauseInsertion

The resource supports the following methods:

- [POST](#)

POST

Pauses the appearance of any messages on all the destinations of the JMSServer, that are result of the in-flight work completion on all the destinations hosted by this JMSServer.

Definition of In-Flight work

The definitions below are based on the current implementation of WebLogic JMS subsystem.

- In-flight messages associated with Producers
 - UN-BORN MESSAGES

Messages that are produced by the producer, with "birth time" (TimeToDeliver) set in future are called un-born messages and are counted as "pending" messages in the destination statistics and are not available for consumers yet.
 - UN-COMMITTED MESSAGES

These are the messages that are produced by the producer as part of the transaction (using either user transaction or transacted session) and the transaction is still not committed or rolled back. These messages are also counted as "pending" messages in the destination statistics and are not available for consumption.
 - QUOTA BLOCKING SEND

These are the messages that are produced by the producers but are not able reach the destination because of (either message or byte or both) quota limit on the destination and the producers are willing to block for a specific period of time for the quota to be available. These messages are invisible to the system and are not counted against any of the destination statistics.
- In-flight messages associated with Consumers
 - UN-ACKNOWLEDGED (CLIENT ACK PENDING) MESSAGES

These are the messages that are successfully consumed by the clients using a "client acknowledge" session, and are awaiting acknowledgements from the clients. These are "pending messages" which will be removed from the destination/system when the acknowledgement is received.
 - UN-COMMITTED MESSAGES

These are the messages that are consumed (received) by the clients within a transaction (using either user transaction or transacted session) and the transaction is still not committed or rolled back. When the clients successfully commit the transaction the messages get removed from the system.
 - ROLLED BACK MESSAGES

These are the messages that are put back on the destination because of a successful rollback of transactional receive by the consumers. These messages might or might not be ready for consumption (re-delivered) to the clients immediately, depending on the redelivery parameters, RedeliveryDelay and/or RedeliveryDelayOverride and RedeliveryLimit configured on the associated JMSConnectionFactory and JMSDestination respectively.

If there is a redelivery delay configured, then for that "delay" duration, the messages are not available for consumption and are counted as "pending" in

the destination statistics and after the "delay" period, if the redelivery limit is not exceeded, then they are delivered (made available for consumption) on that destination and are counted as "current" messages in the destination statistics. If the redelivery limit exceeds, then those messages will be moved to the ErrorDestination, if one configured.

Another parameter that controls the availability of the rolled back messages is RedeliveryLimit.

- RECOVERED MESSAGES

These messages are similar to ROLLED BACK MESSAGES except that these messages appear on the queue because of an explicit call to session "recover" by the client.

- REDELIVERED MESSAGES

These are again similar to ROLLED BACK MESSAGES except that these messages may re-appear on the destination because of an un-successful delivery attempt to the client (consumer crash, close etc.).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/pauseProduction

The resource supports the following methods:

- [POST](#)

POST

Pauses the new message production on all the destinations hosted by the JMS Server.

When the production is paused, it would prevent any new produce operations from both new and existing producers attached to the destinations. When the destination is "resumed from production pause", all the new message production is allowed from both new and existing producers attached to that destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/resumeConsumption

The resource supports the following methods:

- [POST](#)

POST

Resumes the consumption operation on all the destinations hosted by the JMSSEver.

The state of the destinations shall be marked as "consumption enabled" thus allowing all the "consuming" activity to continue normally.

Invoking this API on a JMSSEver that is currently not in "consumption paused" state has no effect.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/resumeInsertion

The resource supports the following methods:

- [POST](#)

POST

Resumes the in-flight message production operation on all the destinations hosted by the JMS Server. The state of the JMS Server shall be marked as "insertion enabled" thus allowing all the messages from in-flight work completion are allowed to appear on the destinations.

Invoking this API on a JMS Server that is currently not in "insertion paused" state has no effect.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/resumeProduction

The resource supports the following methods:

- [POST](#)

POST

Resumes the new message production operation on all the destinations hosted by the JMSServer. The state of the JMSServer shall be marked as "production enabled" thus allowing all the new "producing" activity to continue normally. Invoking this API on a JMSServer that is currently not in "production paused" state has no effect.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes

This resource manages a collection of [weblogic.management.runtime.JMSSessionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JMSSessionPoolRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JMSSessionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}

This resource manages a [weblogic.management.runtime.JMSSessionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSSessionPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSSessionPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer](#) **rel**=JMSServer

This resource's JMSServer singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers](#) **rel**=connectionConsumers

This resource's connectionConsumers collection resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers

This resource manages a collection of [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers/{name}

This resource manages a [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers/{name}](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer

This resource manages a [weblogic.management.runtime.JMSServerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSServerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSServerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/closeCursor](#) **rel**=action
title=closeCursor
This resource's closeCursor action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/forceCommit](#) **rel**=action
title=forceCommit
This resource's forceCommit action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/forceRollback](#) **rel**=action
title=forceRollback
This resource's forceRollback action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorEndPosition](#)
rel=action **title**=getCursorEndPosition
This resource's getCursorEndPosition action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorSize](#) **rel**=action
title=getCursorSize
This resource's getCursorSize action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorStartPosition](#)
rel=action **title**=getCursorStartPosition
This resource's getCursorStartPosition action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getMessages](#) **rel**=action
title=getMessages
This resource's getMessages action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getTransactionStatus](#) **rel**=action
title=getTransactionStatus
This resource's getTransactionStatus action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseConsumption **rel**=action **title**=pauseConsumption
This resource's pauseConsumption action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseInsertion **rel**=action **title**=pauseInsertion
This resource's pauseInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseProduction **rel**=action **title**=pauseProduction
This resource's pauseProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeConsumption **rel**=action **title**=resumeConsumption
This resource's resumeConsumption action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeInsertion **rel**=action **title**=resumeInsertion
This resource's resumeInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeProduction **rel**=action **title**=resumeProduction
This resource's resumeProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/sort **rel**=action **title**=sort
This resource's sort action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations **rel**=destinations
This resource's destinations collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime **rel**=logRuntime
This resource's logRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer **rel**=self
This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/sessionPoolRuntimes
rel=sessionPoolRuntimes

This resource's sessionPoolRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/closeCursor

The resource supports the following methods:

- [POST](#)

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations

This resource manages a collection of [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}

This resource manages a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/closeCursor](#) or [rel=action title=closeCursor](#)
This resource's closeCursor action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/createDurableSubscriber](#) [rel=action title=createDurableSubscriber](#)
This resource's createDurableSubscriber action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/deleteMessages](#) [rel=action title=deleteMessages](#)
This resource's deleteMessages action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorEndPosition](#) [rel=action title=getCursorEndPosition](#)
This resource's getCursorEndPosition action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorSize](#) [rel=action title=getCursorSize](#)
This resource's getCursorSize action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorStartPosition](#) [rel=action title=getCursorStartPosition](#)
This resource's getCursorStartPosition action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getMessages](#) [rel=action title=getMessages](#)
This resource's getMessages action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseConsumption](#) [rel=action title=pauseConsumption](#)
This resource's pauseConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseInsertion **rel**=action **title**=pauseInsertion

This resource's pauseInsertion action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseProduction **rel**=action **title**=pauseProduction

This resource's pauseProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeConsumption **rel**=action **title**=resumeConsumption

This resource's resumeConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeInsertion **rel**=action **title**=resumeInsertion

This resource's resumeInsertion action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeProduction **rel**=action **title**=resumeProduction

This resource's resumeProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/sort **rel**=action **title**=sort

This resource's sort action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers **rel**=durableSubscribers

This resource's durableSubscribers collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/closeCursor

The resource supports the following methods:

- [POST](#)

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/createDurableSubscriber

The resource supports the following methods:

- [POST](#)

POST

Creates a durable subscriber on the destination with the specified client ID and subscription name. A message selector and no-local flag may also be specified.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

ClientID

An identifier that uniquely identifies a client connection.

Type: string

subscriptionName

The name used to identify this subscription.

Type: string

selector

Only messages with properties matching the message selector expression are delivered. A value of null or an empty string indicates that there is no message selector for the message consumer.

Type: string

noLocal

If set, inhibits the delivery of messages published by its own connection.

Type: boolean

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/deleteMessages

The resource supports the following methods:

- [POST](#)

POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A JMS message selector to identify which messages to delete.

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers

This resource manages a collection of [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}

This resource manages a [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/closeCursor rel=action title=closeCursor](#)

This resource's closeCursor action resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/deleteMessages rel=action title=deleteMessages](#)

This resource's deleteMessages action resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorEndPosition rel=action title=getCursorEndPosition](#)

This resource's getCursorEndPosition action resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorSize rel=action title=getCursorSize](#)

This resource's getCursorSize action resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorStartPosition rel=action title=getCursorStartPosition](#)

This resource's getCursorStartPosition action resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getMessages rel=action title=getMessages](#)

This resource's getMessages action resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/sort rel=action title=sort](#)

This resource's sort action resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name} rel=canonical](#)

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime **rel**=destinationRuntime

This resource's destinationRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/closeCursor

The resource supports the following methods:

- [POST](#)

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/deleteMessages

The resource supports the following methods:

- [POST](#)

POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A JMS message selector to identify which messages to delete.

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime

This resource manages a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor **rel**=action **title**=closeCursor

This resource's closeCursor action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/createDurableSubscriber **rel**=action **title**=createDurableSubscriber

This resource's createDurableSubscriber action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessages **rel**=action **title**=deleteMessages

This resource's deleteMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorEndPosition **rel**=action **title**=getCursorEndPosition

This resource's getCursorEndPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSize **rel**=action **title**=getCursorSize

This resource's getCursorSize action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorStartPosition **rel**=action **title**=getCursorStartPosition

This resource's getCursorStartPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages **rel**=action **title**=getMessages

This resource's getMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsumption **rel**=action
title=pauseConsumption
This resource's pauseConsumption action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertion **rel**=action
title=pauseInsertion
This resource's pauseInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduction **rel**=action
title=pauseProduction
This resource's pauseProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsumption **rel**=action
title=resumeConsumption
This resource's resumeConsumption action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInsertion **rel**=action
title=resumeInsertion
This resource's resumeInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProduction **rel**=action
title=resumeProduction
This resource's resumeProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/sort **rel**=action **title**=sort
This resource's sort action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/durableSubscribers **rel**=durableSubscribers
This resource's durableSubscribers collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor

The resource supports the following methods:

- [POST](#)

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/createDurableSubscriber

The resource supports the following methods:

- [POST](#)

POST

Creates a durable subscriber on the destination with the specified client ID and subscription name. A message selector and no-local flag may also be specified.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

ClientID

An identifier that uniquely identifies a client connection.

Type: string

subscriptionName

The name used to identify this subscription.

Type: string

selector

Only messages with properties matching the message selector expression are delivered. A value of null or an empty string indicates that there is no message selector for the message consumer.

Type: string

noLocal

If set, inhibits the delivery of messages published by its own connection.

Type: boolean

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessages

The resource supports the following methods:

- [POST](#)

POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A JMS message selector to identify which messages to delete.

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSize

The resource supports the following methods:

- [POST](#)

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A valid JMS message selector.

Type: string

timeout

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

state

A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

Type: int

Response Body

Contains a JSON object with a string return field.

POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A valid JMS message selector.

Type: string

timeout

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsumption

The resource supports the following methods:

- [POST](#)

POST

Pauses the consumption on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertion

The resource supports the following methods:

- [POST](#)

POST

Pauses the insertion on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduction

The resource supports the following methods:

- [POST](#)

POST

Pauses the production on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsumption

The resource supports the following methods:

- [POST](#)

POST

Resumes the consumption operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInsertion

The resource supports the following methods:

- [POST](#)

POST

Resumes the insertion operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProduction

The resource supports the following methods:

- [POST](#)

POST

Resumes the production operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/sort

The resource supports the following methods:

- [POST](#)

POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The handle of the cursor.

Type: string

start

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

Type: long

fields

The JMS header attributes on which to sort.

Type: array of string

ascending

Determines whether the sort of the corresponding fields element is in ascending or descending order.

Type: array of boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorEndPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorSize

The resource supports the following methods:

- [POST](#)

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getMessages

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A valid JMS message selector.

Type: string

timeout

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

state

A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

Type: int

Response Body

Contains a JSON object with a string return field.

POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A valid JMS message selector.

Type: string

timeout

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/sort

The resource supports the following methods:

- [POST](#)

POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The handle of the cursor.

Type: string

start

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

Type: long

fields

The JMS header attributes on which to sort.

Type: array of string

ascending

Determines whether the sort of the corresponding fields element is in ascending or descending order.

Type: array of boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursor EndPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursor Size

The resource supports the following methods:

- [POST](#)

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getMessages

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A valid JMS message selector.

Type: string

timeout

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

state

A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

Type: int

Response Body

Contains a JSON object with a string return field.

POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A valid JMS message selector.

Type: string

timeout

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseConsumption

The resource supports the following methods:

- [POST](#)

POST

Pauses the consumption on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseInsertion

The resource supports the following methods:

- [POST](#)

POST

Pauses the insertion on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseProduction

The resource supports the following methods:

- [POST](#)

POST

Pauses the production on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeConsumption

The resource supports the following methods:

- [POST](#)

POST

Resumes the consumption operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeIns ertion

The resource supports the following methods:

- [POST](#)

POST

Resumes the insertion operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeProduction

The resource supports the following methods:

- [POST](#)

POST

Resumes the production operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/sort

The resource supports the following methods:

- [POST](#)

POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The handle of the cursor.

Type: string

start

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

Type: long

fields

The JMS header attributes on which to sort.

Type: array of string

ascending

Determines whether the sort of the corresponding fields element is in ascending or descending order.

Type: array of boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/forceCommit

The resource supports the following methods:

- [POST](#)

POST

Causes the work associated with the specified transaction branch to be committed.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

xid

An xid in string representation for a JMS transaction branch.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/forceRollback

The resource supports the following methods:

- [POST](#)

POST

Causes the work associated with the specified transaction branch to be rolled back.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

xid

An xid in string representation for a JMS transaction branch.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorSize

The resource supports the following methods:

- [POST](#)

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorStartPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getMessages

The resource supports the following methods:

- [POST](#)

POST

Returns a set of messages that are associated with a JMS transaction branch. Note that the result set is returned to the caller in the form of a message cursor that may contain messages from several destinations on this JMS server.

The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

xid

An Xid in string representation for a JMS transaction branch.

Type: string

timeoutSeconds

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getTransactionStatus

The resource supports the following methods:

- [POST](#)

POST

Given an Xid this method returns the JTA status of the associated JMS transaction branch.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

xid

An Xid in string representation for a JMS transaction branch.

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/ensureLogOpened
rel=action **title**=ensureLogOpened
This resource's ensureLogOpened action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/flushLog
rel=action **title**=flushLog
This resource's flushLog action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/forceLogRotation
rel=action **title**=forceLogRotation
This resource's forceLogRotation action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseConsumption

The resource supports the following methods:

- [POST](#)

POST

Pauses the consumption operation on all the destinations hosted by the JMSServer.

When the JMSServer is paused for consumption, all of its destination's state is marked as "consumption paused" and all the new synchronous receive operations will block until the destination is resumed and there are messages available for consumption. All the synchronous receive with blocking timeout will block until the timeout happens during the consumption paused state.

All the asynchronous consumers attached to that destination will not get any messages delivered to them while the destination in "consumption paused" state.

After a successful consumption "pause" operation, the user has to explicitly "resume" the destination to allow for any further consume operations on that destination

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseInsertion

The resource supports the following methods:

- [POST](#)

POST

Pauses the appearance of any messages on all the destinations of the JMSServer, that are result of the in-flight work completion on all the destinations hosted by this JMSServer.

Definition of In-Flight work

The definitions below are based on the current implementation of WebLogic JMS subsystem.

- In-flight messages associated with Producers
 - UN-BORN MESSAGES

Messages that are produced by the producer, with "birth time" (TimeToDeliver) set in future are called un-born messages and are counted as "pending" messages in the destination statistics and are not available for consumers yet.
 - UN-COMMITTED MESSAGES

These are the messages that are produced by the producer as part of the transaction (using either user transaction or transacted session) and the transaction is still not committed or rolled back. These messages are also counted as "pending" messages in the destination statistics and are not available for consumption.
 - QUOTA BLOCKING SEND

These are the messages that are produced by the producers but are not able reach the destination because of (either message or byte or both) quota limit on the destination and the producers are willing to block for a specific period of time for the quota to be available. These messages are invisible to the system and are not counted against any of the destination statistics.
- In-flight messages associated with Consumers
 - UN-ACKNOWLEDGED (CLIENT ACK PENDING) MESSAGES

These are the messages that are successfully consumed by the clients using a "client acknowledge" session, and are awaiting acknowledgements from the clients. These are "pending messages" which will be removed from the destination/system when the acknowledgement is received.
 - UN-COMMITTED MESSAGES

These are the messages that are consumed (received) by the clients within a transaction (using either user transaction or transacted session) and the transaction is still not committed or rolled back. When the clients successfully commit the transaction the messages get removed from the system.
 - ROLLED BACK MESSAGES

These are the messages that are put back on the destination because of a successful rollback of transactional receive by the consumers. These messages might or might not be ready for consumption (re-delivered) to the clients immediately, depending on the redelivery parameters, RedeliveryDelay and/or RedeliveryDelayOverride and RedeliveryLimit configured on the associated JMSConnectionFactory and JMSDestination respectively.

If there is a redelivery delay configured, then for that "delay" duration, the messages are not available for consumption and are counted as "pending" in

the destination statistics and after the "delay" period, if the redelivery limit is not exceeded, then they are delivered (made available for consumption) on that destination and are counted as "current" messages in the destination statistics. If the redelivery limit exceeds, then those messages will be moved to the ErrorDestination, if one configured.

Another parameter that controls the availability of the rolled back messages is RedeliveryLimit.

- RECOVERED MESSAGES

These messages are similar to ROLLED BACK MESSAGES except that these messages appear on the queue because of an explicit call to session "recover" by the client.

- REDELIVERED MESSAGES

These are again similar to ROLLED BACK MESSAGES except that these messages may re-appear on the destination because of an un-successful delivery attempt to the client (consumer crash, close etc.).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseProduction

The resource supports the following methods:

- [POST](#)

POST

Pauses the new message production on all the destinations hosted by the JMS Server.

When the production is paused, it would prevent any new produce operations from both new and existing producers attached to the destinations. When the destination is "resumed from production pause", all the new message production is allowed from both new and existing producers attached to that destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeConsumption

The resource supports the following methods:

- [POST](#)

POST

Resumes the consumption operation on all the destinations hosted by the JMSServer.

The state of the destinations shall be marked as "consumption enabled" thus allowing all the "consuming" activity to continue normally.

Invoking this API on a JMSServer that is currently not in "consumption paused" state has no effect.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeInsertion

The resource supports the following methods:

- [POST](#)

POST

Resumes the in-flight message production operation on all the destinations hosted by the JMS Server. The state of the JMS Server shall be marked as "insertion enabled" thus allowing all the messages from in-flight work completion are allowed to appear on the destinations.

Invoking this API on a JMS Server that is currently not in "insertion paused" state has no effect.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeProduction

The resource supports the following methods:

- [POST](#)

POST

Resumes the new message production operation on all the destinations hosted by the JMSServer. The state of the JMSServer shall be marked as "production enabled" thus allowing all the new "producing" activity to continue normally. Invoking this API on a JMSServer that is currently not in "production paused" state has no effect.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/sort

The resource supports the following methods:

- [POST](#)

POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The handle of the cursor.

Type: string

start

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

Type: long

fields

The JMS header attributes on which to sort.

Type: array of string

ascending

Determines whether the sort of the corresponding fields element is in ascending or descending order.

Type: array of boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sort

The resource supports the following methods:

- [POST](#)

POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The handle of the cursor.

Type: string

start

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

Type: long

fields

The JMS header attributes on which to sort.

Type: array of string

ascending

Determines whether the sort of the corresponding fields element is in ascending or descending order.

Type: array of boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/joltRuntime

This resource manages a [weblogic.management.runtime.JoltConnectionServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JoltConnectionServiceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JoltConnectionServiceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/joltRuntime](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools](#)
rel=connectionPools
This resource's connectionPools collection resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/joltRuntime](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools

This resource manages a collection of [weblogic.management.runtime.JoltConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JoltConnectionPoolRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JoltConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/joltRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}

This resource manages a [weblogic.management.runtime.JoltConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JoltConnectionPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JoltConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}/resetConnectionPool](#) **rel**=action **title**=resetConnectionPool
This resource's resetConnectionPool action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}/connections](#) **rel**=connections
This resource's connections collection resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}/connections

This resource manages a collection of [weblogic.management.runtime.JoltConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of `weblogic.management.runtime.JoltConnectionRuntimeMBean` instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of `weblogic.management.runtime.JoltConnectionRuntimeMBean` entities.

This method can return the following links:

- **uri**=`/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}/connections` **rel**=canonical
This resource.
- **uri**=`/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}` **rel**=parent
The parent resource of this resource.
- **uri**=`/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}/connections` **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}/connections/{name}

This resource manages a [weblogic.management.runtime.JoltConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JoltConnectionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JoltConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}/connections/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}/connections](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}/connections/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}/resetConnectionPool

The resource supports the following methods:

- [POST](#)

POST

POST

Resets the connection pool.

Roles

Admin

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/JTARuntime

This resource manages a [weblogic.management.runtime.JTARuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JTARuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JTARuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/getRecoveryRuntimeMBean](#) [rel=action](#) [title=getRecoveryRuntimeMBean](#)
This resource's `getRecoveryRuntimeMBean` action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime](#) [rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/nonXAResourceRuntimeMBeans](#) [rel=nonXAResourceRuntimeMBeans](#)
This resource's `nonXAResourceRuntimeMBeans` collection resource.
- [uri=/management/weblogic/{version}/serverRuntime](#) [rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/recoveryRuntimeMBeans](#) [rel=recoveryRuntimeMBeans](#)
This resource's `recoveryRuntimeMBeans` collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime](#) [rel=self](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean](#) [rel=transactionLogStoreRuntimeMBean](#)
This resource's `transactionLogStoreRuntimeMBean` singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionNameRuntimeMBeans](#) [rel=transactionNameRuntimeMBeans](#)
This resource's `transactionNameRuntimeMBeans` collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionResourceRuntimeMBeans](#) [rel=transactionResourceRuntimeMBeans](#)
This resource's `transactionResourceRuntimeMBeans` collection resource.

/management/weblogic/{version}/serverRuntime/JTARuntime/getRecoveryRuntimeMBean

The resource supports the following methods:

- [POST](#)

POST

Returns the runtime MBean for the Transaction Recovery Service of the specified server. If the Transaction Recovery Service of the specified server is not deployed on this server, null will be returned.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

serverName

serverName

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.JTARecoveryRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/JTARuntime/nonXAResourceRuntimeMBeans

This resource manages a collection of [weblogic.management.runtime.NonXAResourceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.NonXAResourceRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.NonXAResourceRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/nonXAResourceRuntimeMBeans](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/nonXAResourceRuntimeMBeans](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/JTARuntime/nonXAResourceRuntimeMBeans/{name}

This resource manages a [weblogic.management.runtime.NonXAResourceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.NonXAResourceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.NonXAResourceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JTARuntime/nonXAResourceRuntimeMBeans/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JTARuntime/nonXAResourceRuntimeMBeans](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JTARuntime/nonXAResourceRuntimeMBeans/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JTARuntime/recoveryRuntimeMBeans

This resource manages a collection of [weblogic.management.runtime.JTARecoveryRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JTARecoveryRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JTARecoveryRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/recoveryRuntimeMBeans](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/recoveryRuntimeMBeans](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/JTARuntime/recoveryRuntimeMBeans/{name}

This resource manages a [weblogic.management.runtime.JTARecoveryRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JTARecoveryRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JTARecoveryRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JTARuntime/recoveryRuntimeMBeans/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JTARuntime/recoveryRuntimeMBeans](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JTARuntime/recoveryRuntimeMBeans/{name}](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean

This resource manages a [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean/connections](#) **rel**=connections

This resource's connections collection resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JTARuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean/connections

This resource manages a collection of [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean/connections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean/connections **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean/connections/{name}

This resource manages a [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean/connections/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean/connections](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean/connections/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JTARuntime/transactionNameRuntimeMBeans

This resource manages a collection of [weblogic.management.runtime.TransactionNameRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.TransactionNameRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.TransactionNameRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionNameRuntimeMBeans rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionNameRuntimeMBeans rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/JTARuntime/transactionNameRuntimeMBeans/{name}

This resource manages a [weblogic.management.runtime.TransactionNameRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.TransactionNameRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.TransactionNameRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JTARuntime/transactionNameRuntimeMBeans/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JTARuntime/transactionNameRuntimeMBeans](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JTARuntime/transactionNameRuntimeMBeans/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/JTARuntime/transactionResourceRuntimeMBeans

This resource manages a collection of [weblogic.management.runtime.TransactionResourceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.TransactionResourceRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.TransactionResourceRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JTARuntime/transactionResourceRuntimeMBeans](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JTARuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JTARuntime/transactionResourceRuntimeMBeans](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/JTARuntime/transactionResourceRuntimeMBeans/{name}

This resource manages a [weblogic.management.runtime.TransactionResourceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.TransactionResourceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.TransactionResourceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionResourceRuntimeMBeans/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionResourceRuntimeMBeans **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionResourceRuntimeMBeans/{name} **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/JVMRuntime

This resource manages a [weblogic.management.runtime.JVMRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JVMRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JVMRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JVMRuntime](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JVMRuntime](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/libraryRuntimes

This resource manages a collection of [weblogic.management.runtime.LibraryRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.LibraryRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.LibraryRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/libraryRuntimes](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/libraryRuntimes](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name}

This resource manages a [weblogic.management.runtime.LibraryRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LibraryRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LibraryRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/libraryRuntimes](#)
rel=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name}/referencingRuntimes](#) **rel**=referencingRuntimes
This resource's referencingRuntimes collection resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name}](#)
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name}/referencingRuntimes

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name}/referencingRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name}/referencingRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name}/referencingRuntimes/{name}

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name}/referencingRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name}/referencingRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name}/referencingRuntimes/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/logBroadcasterRuntime

This resource manages a [weblogic.management.runtime.LogBroadcasterRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LogBroadcasterRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LogBroadcasterRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/logBroadcasterRuntime](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/logBroadcasterRuntime](#)
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/mailSessionRuntimes

This resource manages a collection of [weblogic.management.runtime.MailSessionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MailSessionRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MailSessionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/mailSessionRuntimes](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/mailSessionRuntimes](#)
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/mailSessionRuntimes/{name} **}**

This resource manages a [weblogic.management.runtime.MailSessionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MailSessionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MailSessionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/mailSessionRuntimes/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/mailSessionRuntimes](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/mailSessionRuntimes/{name}](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/MANAsyncReplicationRuntime

This resource manages a [weblogic.management.runtime.MANAsyncReplicationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MANAsyncReplicationRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MANAsyncReplicationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/MANAsyncReplicationRuntime](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/MANAsyncReplicationRuntime](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/MANReplicationRuntime

This resource manages a [weblogic.management.runtime.MANReplicationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MANReplicationRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MANReplicationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/MANReplicationRuntimeMBean](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/MANReplicationRuntimeMBean](#)
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/maxThreadsConstraintRuntimes

This resource manages a collection of [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/maxThreadsConstraintRuntimes](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/maxThreadsConstraintRuntimes](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/maxThreadsConstraintRuntimes/{name}

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/maxThreadsConstraintRuntimes/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/maxThreadsConstraintRuntimes](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/maxThreadsConstraintRuntimes/{name}](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/messagingBridgeRuntimes

This resource manages a collection of [weblogic.management.runtime.MessagingBridgeRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MessagingBridgeRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MessagingBridgeRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/messagingBridgeRuntimes](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/messagingBridgeRuntimes](#)
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/messagingBridgeRuntimes/{name}

This resource manages a [weblogic.management.runtime.MessagingBridgeRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MessagingBridgeRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MessagingBridgeRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/messagingBridgeRuntimes/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/messagingBridgeRuntimes](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/messagingBridgeRuntimes/{name}](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/minThreadsConstraintRuntimes

This resource manages a collection of [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/minThreadsConstraintRuntimes](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/minThreadsConstraintRuntimes](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/minThreadsConstraintRuntimes/{name}

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/minThreadsConstraintRuntimes/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/minThreadsConstraintRuntimes](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/minThreadsConstraintRuntimes/{name}](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes

This resource manages a collection of [weblogic.management.runtime.PartitionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.PartitionRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.PartitionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes](#)
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}

This resource manages a [weblogic.management.runtime.PartitionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.PartitionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.PartitionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime](#) **rel**=JDBCPartitionRuntime
This resource's JDBCPartitionRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime](#) **rel**=JMSRuntime
This resource's JMSRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime](#) **rel**=JTAPartitionRuntime
This resource's JTAPartitionRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime](#) **rel**=SAFRuntime
This resource's SAFRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime](#) **rel**=WLDFPartitionRuntime
This resource's WLDFPartitionRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceShutdown](#) **rel**=action **title**=forceShutdown
This resource's forceShutdown action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceShutdownResourceGroup](#) **rel**=action **title**=forceShutdownResourceGroup
This resource's forceShutdownResourceGroup action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceSuspend](#) **rel**=action **title**=forceSuspend
This resource's forceSuspend action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceSuspendResourceGroup](#) **rel**=action **title**=forceSuspendResourceGroup
This resource's forceSuspendResourceGroup action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/getRgState](#) **rel**=action **title**=getRgState
This resource's getRgState action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resume](#) **rel**=action **title**=resume

This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resumeResourceGroup **rel**=action **title**=resumeResourceGroup

This resource's resumeResourceGroup action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/shutdown **rel**=action **title**=shutdown

This resource's shutdown action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/shutdownResourceGroup **rel**=action **title**=shutdownResourceGroup

This resource's shutdownResourceGroup action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/startResourceGroup **rel**=action **title**=startResourceGroup

This resource's startResourceGroup action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/startResourceGroupInAdmin **rel**=action **title**=startResourceGroupInAdmin

This resource's startResourceGroupInAdmin action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/suspend **rel**=action **title**=suspend

This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/suspendResourceGroup **rel**=action **title**=suspendResourceGroup

This resource's suspendResourceGroup action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes **rel**=applicationRuntimes

This resource's applicationRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/batchJobRepositoryRuntime **rel**=batchJobRepositoryRuntime

This resource's batchJobRepositoryRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime **rel**=concurrentManagedObjectsRuntime

This resource's concurrentManagedObjectsRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime

This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes **rel**=libraryRuntimes

This resource's libraryRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes **rel**=mailSessionRuntimes

This resource's mailSessionRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes **rel**=maxThreadsConstraintRuntimes

This resource's maxThreadsConstraintRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes **rel**=messagingBridgeRuntimes

This resource's messagingBridgeRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes **rel**=minThreadsConstraintRuntimes

This resource's minThreadsConstraintRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionResourceMetricsRuntime **rel**=partitionResourceMetricsRuntime

This resource's partitionResourceMetricsRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime **rel**=partitionWorkManagerRuntime

This resource's partitionWorkManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes **rel**=pathServiceRuntimes

This resource's pathServiceRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes **rel**=persistentStoreRuntimes

This resource's persistentStoreRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes **rel**=requestClassRuntimes

This resource's requestClassRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime **rel**=resourceManagerRuntime

This resource's resourceManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes **rel**=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime **rel**=wseeClusterFrontEndRuntime

This resource's wseeClusterFrontEndRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes

This resource manages a collection of [weblogic.management.runtime.ApplicationRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ApplicationRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ApplicationRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes](#) [rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) [rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes](#) [rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}

This resource manages a [weblogic.management.runtime.ApplicationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ApplicationRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ApplicationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/getPersistenceUnitRuntime **rel**=action
title=getPersistenceUnitRuntime
This resource's getPersistenceUnitRuntime action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/hasApplicationCache **rel**=action
title=hasApplicationCache
This resource's hasApplicationCache action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/reInitializeApplicationCachesAndPools **rel**=action
title=reInitializeApplicationCachesAndPools
This resource's reInitializeApplicationCachesAndPools action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classLoaderRuntime **rel**=classLoaderRuntime
This resource's classLoaderRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime **rel**=classRedefinitionRuntime
This resource's classRedefinitionRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/coherenceClusterRuntime **rel**=coherenceClusterRuntime
This resource's coherenceClusterRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes **rel**=componentRuntimes
This resource's componentRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes **rel**=libraryRuntimes
This resource's libraryRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes
rel=managedExecutorServiceRuntimes
This resource's managedExecutorServiceRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes
rel=managedScheduledExecutorServiceRuntimes
This resource's managedScheduledExecutorServiceRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedThreadFactoryRuntimes
rel=managedThreadFactoryRuntimes
This resource's managedThreadFactoryRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/maxThreadsConstraintRuntimes
rel=maxThreadsConstraintRuntimes
This resource's maxThreadsConstraintRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/minThreadsConstraintRuntimes
rel=minThreadsConstraintRuntimes
This resource's minThreadsConstraintRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes
rel=optionalPackageRuntimes
This resource's optionalPackageRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/persistenceUnitRuntimes
rel=persistenceUnitRuntimes
This resource's persistenceUnitRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes **rel**=queryCacheRuntimes
This resource's queryCacheRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes **rel**=requestClassRuntimes
This resource's requestClassRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes
rel=workManagerRuntimes
This resource's workManagerRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes **rel**=wseeV2Runtimes

This resource's wseeV2Runtimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classLoaderRuntime

This resource manages a [weblogic.management.runtime.ClassLoaderRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ClassLoaderRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ClassLoaderRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classLoaderRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classLoaderRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime

This resource manages a [com.bea.wls.redef.runtime.ClassRedefinitionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [com.bea.wls.redef.runtime.ClassRedefinitionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [com.bea.wls.redef.runtime.ClassRedefinitionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/defineClasses](#)
rel=action **title**=defineClasses

This resource's defineClasses action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks](#)
rel=classRedefinitionTasks

This resource's classRedefinitionTasks collection resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap plicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks

This resource manages a collection of [com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks](#)
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap plicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{ name}

This resource manages a [com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/cancel **rel**=action **title**=cancel

This resource's cancel action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks **rel**=parent

The parent resource of this resource.

- **rel**=parentTask

This resource's parentTask reference to a `weblogic.management.runtime.TaskRuntimeMBean` resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks **rel**=subTasks

This resource's subTasks collection resource.

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap
plicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{
name}/cancel**

The resource supports the following methods:

- [POST](#)

POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks

This resource manages a collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.TaskRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}

This resource manages a [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.TaskRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/cancel rel=action title=cancel](#)

This resource's cancel action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks rel=parent](#)

The parent resource of this resource.

- [rel=parentTask](#)

This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name} rel=self](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks rel=subTasks](#)

This resource's subTasks collection resource.

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap
plicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{
name}/subTasks/{name}/cancel**

The resource supports the following methods:

- [POST](#)

POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap plicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{ name}/subTasks/{name}/subTasks

This resource manages a collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.TaskRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap plicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{ name}/subTasks/{name}/subTasks/{name}

This resource manages a [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.TaskRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name}/cancel](#) **rel=action** **title=cancel**

This resource's cancel action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks](#) **rel=parent**

The parent resource of this resource.

- **rel=parentTask**

This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name}](#) **rel=self**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name}/subTasks](#) **rel=subTasks**

This resource's subTasks collection resource.

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap
plicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{
name}/subTasks/{name}/subTasks/{name}/cancel**

The resource supports the following methods:

- [POST](#)

POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap plicationRuntimes/{name}/classRedefinitionRuntime/defineClasses

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Initiate a class redefinition cycle, which will identify classes which may have changed and then attempt to redefine them. Class redefinition will be performed asynchronously. The progress of the class redefinition process can be monitored with the returned task.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin

Response Body

Contains a JSON object with a `com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean` reference return field.

POST

Initiate a class redefinition cycle, to redefine only the specified classes from given module. Class redefinition will be performed asynchronously. The progress of the class redefinition process can be monitored with the returned task. If specified module name is null, any classes within the application (scoped to any modules as well as globally scoped classes) which are included in the list will be redefined.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

moduleName

Module from which the classes are to be redefined.

Type: string

classNames

Classes to be redefined.

Type: array of string

Response Body

Contains a JSON object with a `com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/coherenceClusterRuntime

This resource manages a [weblogic.management.runtime.CoherenceClusterRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CoherenceClusterRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CoherenceClusterRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/coherenceClusterRuntime](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/coherenceClusterRuntime](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes

This resource manages a collection of [weblogic.management.runtime.ComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ComponentRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ComponentRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}

This resource manages a [weblogic.management.runtime.ComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ComponentRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ComponentRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes **rel**=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntime S

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=capacityRuntime**

This resource's capacityRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**

This resource's maxThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**

This resource's minThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=requestClassRuntime**

This resource's requestClassRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntime/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntime/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntime/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/getPersistenceUnitRuntime

The resource supports the following methods:

- [POST](#)

POST

Provides the PersistenceUnitRuntimeMBean for the application with the specified name.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

unitName

unitName

Type: string

Response Body

Contains a JSON object with a
weblogic.management.runtime.PersistenceUnitRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/hasApplicationCache

The resource supports the following methods:

- [POST](#)

POST

Returns true if the application has an (EJB) Application Level Cache

Roles

Admin, Operator

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes

This resource manages a collection of [weblogic.management.runtime.LibraryRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.LibraryRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.LibraryRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}

This resource manages a [weblogic.management.runtime.LibraryRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LibraryRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LibraryRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes **rel**=referencingRuntimes

This resource's referencingRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name}

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes

This resource manages a collection of [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}

This resource manages a [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager **rel**=workManager

This resource's workManager singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes

This resource manages a collection of [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}

This resource manages a [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=workManager
This resource's workManager singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedThreadFactoryRuntimes

This resource manages a collection of [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedThreadFactoryRuntimes](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedThreadFactoryRuntimes](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedThreadFactoryRuntimes/{name}

This resource manages a [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedThreadFactoryRuntimes/{name}
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedThreadFactoryRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedThreadFactoryRuntimes/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/maxThreadsConstraintRuntimes

This resource manages a collection of [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/maxThreadsConstraintRuntimes](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/maxThreadsConstraintRuntimes](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/maxThreadsConstraintRuntimes/{name}

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/maxThreadsConstraintRuntimes/{name}
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/maxThreadsConstraintRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/maxThreadsConstraintRuntimes/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/minThreadsConstraintRuntimes

This resource manages a collection of [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/minThreadsConstraintRuntimes](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/minThreadsConstraintRuntimes](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/minThreadsConstraintRuntimes/{name}

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/minThreadsConstraintRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/minThreadsConstraintRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/minThreadsConstraintRuntimes/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes

This resource manages a collection of [weblogic.management.runtime.LibraryRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.LibraryRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.LibraryRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}

This resource manages a [weblogic.management.runtime.LibraryRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LibraryRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LibraryRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes **rel**=referencingRuntimes

This resource's referencingRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes/{name}

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/persistenceUnitRuntimes

This resource manages a collection of [weblogic.management.runtime.PersistenceUnitRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.PersistenceUnitRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.PersistenceUnitRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/persistenceUnitRuntimes](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/persistenceUnitRuntimes](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap plicationRuntimes/{name}/persistenceUnitRuntimes/{name}

This resource manages a [weblogic.management.runtime.PersistenceUnitRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.PersistenceUnitRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.PersistenceUnitRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/persistenceUnitRuntimes/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/persistenceUnitRuntimes **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/persistenceUnitRuntimes/{name} **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes

This resource manages a collection of [weblogic.management.runtime.QueryCacheRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.QueryCacheRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.QueryCacheRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes/{name}

This resource manages a [weblogic.management.runtime.QueryCacheRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.QueryCacheRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.QueryCacheRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes/{name}](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/reInitializeApplicationCachesAndPools

The resource supports the following methods:

- [POST](#)

POST

If the application has an (EJB) Application Level Cache, then this method will reinitialize the cache and any of its associated pools to their startup time states if possible.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes

This resource manages a collection of [weblogic.management.runtime.RequestClassRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RequestClassRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RequestClassRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes/{name}

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes/{name}](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=capacityRuntime**
This resource's capacityRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**
This resource's maxThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**
This resource's minThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=requestClassRuntime**
This resource's requestClassRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes

This resource manages a collection of [weblogic.management.runtime.WseeV2RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WseeV2RuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WseeV2RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}

This resource manages a [weblogic.management.runtime.WseeV2RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WseeV2RuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WseeV2RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/policyRuntime **rel**=policyRuntime
This resource's policyRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports **rel**=ports
This resource's ports collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name} **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/policyRuntime

This resource manages a [weblogic.management.runtime.WseePolicyRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WseePolicyRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WseePolicyRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/policyRuntime
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/policyRuntime **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports

This resource manages a collection of [weblogic.management.runtime.WseePortRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WseePortRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WseePortRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}

This resource manages a [weblogic.management.runtime.WseePortRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WseePortRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WseePortRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/aggregatedBaseOperations](#) **rel=aggregatedBaseOperations**
This resource's aggregatedBaseOperations singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations](#) **rel=baseOperations**
This resource's baseOperations collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/clusterRouting](#) **rel=clusterRouting**
This resource's clusterRouting singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers](#) **rel=handlers**
This resource's handlers collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/mc](#) **rel=mc**
This resource's mc singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations](#) **rel=operations**
This resource's operations collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/portPolicy](#) **rel=portPolicy**

This resource's portPolicy singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/wsm **rel**=wsm

This resource's wsm singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap plicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/aggregated BaseOperations

This resource manages a [weblogic.management.runtime.WseeAggregatableBaseOperationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WseeAggregatableBaseOperationRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WseeAggregatableBaseOperationRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/aggregateDBaseOperations rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/aggregateDBaseOperations rel=self](#)

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap plicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperati ons

This resource manages a collection of [weblogic.management.runtime.WseeBaseOperationRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WseeBaseOperationRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WseeBaseOperationRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations/{name}

This resource manages a [weblogic.management.runtime.WseeBaseOperationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WseeBaseOperationRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WseeBaseOperationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap plicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/clusterRouti ng

This resource manages a [weblogic.management.runtime.WseeClusterRoutingRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WseeClusterRoutingRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WseeClusterRoutingRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/clusterRouting](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/clusterRouting](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers

This resource manages a collection of [weblogic.management.runtime.WseeHandlerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WseeHandlerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WseeHandlerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers/{name}

This resource manages a [weblogic.management.runtime.WseeHandlerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WseeHandlerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WseeHandlerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/mc

This resource manages a [weblogic.management.runtime.WseeMcRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WseeMcRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WseeMcRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/mc
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/mc
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations

This resource manages a collection of [weblogic.management.runtime.WseeOperationRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WseeOperationRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WseeOperationRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap plicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations/{ name}

This resource manages a [weblogic.management.runtime.WseeOperationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WseeOperationRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WseeOperationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap plicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/portPolicy

This resource manages a [weblogic.management.runtime.WseePortPolicyRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WseePortPolicyRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WseePortPolicyRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/portPolicy](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/portPolicy](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap plicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/wsrcm

This resource manages a [weblogic.management.runtime.WseeWsrcmRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WseeWsruntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WseeWsruntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/wsrm
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/wsrm
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/batchJobRepositoryRuntime

This resource manages a [weblogic.management.runtime.BatchJobRepositoryRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.BatchJobRepositoryRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.BatchJobRepositoryRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/batchJobRepositoryRuntime](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/batchJobRepositoryRuntime](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime

This resource manages a [weblogic.management.runtime.ConcurrentManagedObjectsRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConcurrentManagedObjectsRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConcurrentManagedObjectsRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes](#) **rel=managedExecutorServiceRuntimes**
This resource's managedExecutorServiceRuntimes collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntime](#) **s rel=managedScheduledExecutorServiceRuntimes**
This resource's managedScheduledExecutorServiceRuntimes collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes](#) **rel=managedThreadFactoryRuntimes**
This resource's managedThreadFactoryRuntimes collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) **el=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes

This resource manages a collection of [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}

This resource manages a [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes](#)
rel=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}](#)
rel=self

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager](#) **rel**=workManager

This resource's workManager singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes

This resource manages a collection of [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}

This resource manages a [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}](#) **rel**=self

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager](#) **rel**=workManager

This resource's workManager singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime](#) **rel=capacityRuntime**

This resource's capacityRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**

This resource's maxThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**

This resource's minThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime](#) **rel=requestClassRuntime**

This resource's requestClassRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes

This resource manages a collection of [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes/{name}

This resource manages a [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes/{name}](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes/{name}](#)
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime

This resource manages a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs **rel**=RAs
This resource's RAs collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/getInboundConnections **rel**=action **title**=getInboundConnections
This resource's getInboundConnections action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/getRA **rel**=action **title**=getRA
This resource's getRA action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/resume **rel**=action **title**=resume
This resource's resume action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/resumeAll **rel**=action **title**=resumeAll
This resource's resumeAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/suspend **rel**=action **title**=suspend
This resource's suspend action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/suspendAll **rel**=action **title**=suspendAll
This resource's suspendAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs **rel**=activeRAs
This resource's activeRAs collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs **rel**=inactiveRAs
This resource's inactiveRAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration](#) **rel=action**
title=getConfiguration
This resource's getConfiguration action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool](#) **rel=action**
title=getConnectionPool
This resource's getConnectionPool action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection](#) **rel=action**
title=getInboundConnection
This resource's getInboundConnection action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema](#) **rel=action**
title=getSchema
This resource's getSchema action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/resume](#) **rel=action** **title=resume**
This resource's resume action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll](#) **rel=action**
title=resumeAll
This resource's resumeAll action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/suspend](#) **rel=action** **title=suspend**
This resource's suspend action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll](#) **rel=action**
title=suspendAll
This resource's suspendAll action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}](#) **rel=canonical**

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools
rel=connectionPools

This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime
rel=connectorServiceRuntime

This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime
rel=connectorWorkManagerRuntime

This resource's connectorWorkManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections
rel=inboundConnections

This resource's inboundConnections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime
rel=workManagerRuntime

This resource's workManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes
rel=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened rel=action title=ensureLogOpened](#)

This resource's ensureLogOpened action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog rel=action title=flushLog](#)

This resource's flushLog action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation rel=action title=forceLogRotation](#)

This resource's forceLogRotation action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset rel=action title=forceReset](#)

This resource's forceReset action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset rel=action title=reset](#)

This resource's reset action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool rel=action title=testPool](#)

This resource's testPool action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections rel=connections](#)

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete rel=action title=delete](#)

This resource's delete action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError rel=action title=hasError](#)

This resource's hasError action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection rel=action title=testConnection](#)

This resource's testConnection action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} rel=self](#)

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

POST

Provides a way to manually close a connection through the console.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError

The resource supports the following methods:

- [POST](#)

POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

POST

Test the connection. Returns true if the test was successful.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset

The resource supports the following methods:

- [POST](#)

POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened
This resource's ensureLogOpened action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog
This resource's flushLog action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation
This resource's forceLogRotation action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset

The resource supports the following methods:

- [POST](#)

POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool

The resource supports the following methods:

- [POST](#)

POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime

This resource manages a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs
rel=RAs
This resource's RAs collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/getInboundConnections **rel**=action **title**=getInboundConnections
This resource's getInboundConnections action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/getRA **rel**=action **title**=getRA
This resource's getRA action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/resume **rel**=action **title**=resume
This resource's resume action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/resumeAll **rel**=action **title**=resumeAll
This resource's resumeAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/suspend **rel**=action **title**=suspend
This resource's suspend action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/suspendAll **rel**=action **title**=suspendAll
This resource's suspendAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/activeRAs **rel**=activeRAs
This resource's activeRAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs **rel**=inactiveRAs

This resource's inactiveRAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/getInboundConnections

The resource supports the following methods:

- [POST](#)

POST

Returns runtime information for the specified inbound connection. A null is returned if the inbound connection is not found.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

messageListenerType

Message listener type.

Type: string

Response Body

Contains a JSON object with a array of `weblogic.management.runtime.ConnectorInboundRuntimeMBean` references return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/getRA

The resource supports the following methods:

- [POST](#)

POST

Returns the runtime information of the resource adapter specified by the given JNDI name. A null is returned if the resource adapter cannot be found. This function returns the active RA if multiple versions of the resource adapters has been deployed

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

key

The JNDI name of the resource adapter.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorComponentRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration **rel**=action **title**=getConfiguration

This resource's getConfiguration action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool **rel**=action **title**=getConnectionPool

This resource's getConnectionPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection **rel**=action **title**=getInboundConnection

This resource's getInboundConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema **rel**=action **title**=getSchema

This resource's getSchema action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume **rel**=action **title**=resume

This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll **rel**=action **title**=resumeAll

This resource's resumeAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend **rel**=action **title**=suspend

This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll **rel**=action **title**=suspendAll

This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=connectionPools

This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime

This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime

This resource's connectorWorkManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=inboundConnections

This resource's inboundConnections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=workManagerRuntime

This resource's workManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened rel=action title=ensureLogOpened](#)
This resource's ensureLogOpened action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog rel=action title=flushLog](#)
This resource's flushLog action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation rel=action title=forceLogRotation](#)
This resource's forceLogRotation action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset rel=action title=forceReset](#)
This resource's forceReset action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset rel=action title=reset](#)
This resource's reset action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool rel=action title=testPool](#)
This resource's testPool action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections rel=connections](#)

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete

The resource supports the following methods:

- [POST](#)

POST

Provides a way to manually close a connection through the console.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError

The resource supports the following methods:

- [POST](#)

POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection

The resource supports the following methods:

- [POST](#)

POST

Test the connection. Returns true if the test was successful.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset

The resource supports the following methods:

- [POST](#)

POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset

The resource supports the following methods:

- [POST](#)

POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool

The resource supports the following methods:

- [POST](#)

POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration

The resource supports the following methods:

- [POST](#)

POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool

The resource supports the following methods:

- [POST](#)

POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

key

JNDI name or resource-link name of the connection pool.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection

The resource supports the following methods:

- [POST](#)

POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

messageListenerType

Message listener type.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema

The resource supports the following methods:

- [POST](#)

POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=MDBRuntimes

This resource's MDBRuntimes collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}](#) **rel**=canonical

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections](#) **rel**=parent

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume](#)
rel=action title=resume

This resource's resume action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend](#)
rel=action title=suspend

This resource's suspend action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime](#)
rel=poolRuntime

This resource's poolRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#)
rel=resources

This resource's resources collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel=self**

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=timerRuntime

This resource's timerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=transactionRuntime

This resource's transactionRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool

The resource supports the following methods:

- [POST](#)

POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

Resumes the specific type of MDB by calling start on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action **title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

POST

Activate any temporarily disabled timers.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Suspend a particular type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel=capacityRuntime**
This resource's capacityRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**
This resource's maxThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**
This resource's minThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel=requestClassRuntime**
This resource's requestClassRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=capacityRuntime**

This resource's capacityRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**

This resource's maxThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**

This resource's minThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=requestClassRuntime**

This resource's requestClassRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime
rel=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration](#) **rel=action** **title=getConfiguration**

This resource's getConfiguration action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool](#) **rel=action** **title=getConnectionPool**

This resource's getConnectionPool action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection](#) **rel=action** **title=getInboundConnection**

This resource's getInboundConnection action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getSchema](#) **rel=action** **title=getSchema**

This resource's getSchema action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resume](#) **rel=action** **title=resume**

This resource's resume action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resumeAll](#) **rel=action** **title=resumeAll**

This resource's resumeAll action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspend](#) **rel=action** **title=suspend**

This resource's suspend action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspendAll](#) **rel=action** **title=suspendAll**

This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=connectionPools
This resource's connectionPools collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime
This resource's connectorServiceRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime
This resource's connectorWorkManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=inboundConnections
This resource's inboundConnections collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=workManagerRuntime
This resource's workManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes
This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset **rel**=action **title**=forceReset

This resource's forceReset action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset **rel**=action **title**=reset

This resource's reset action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool **rel**=action **title**=testPool

This resource's testPool action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=canonical

This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=connections

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete](#) **rel=action** **title=delete**

This resource's delete action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError](#) **rel=action** **title=hasError**

This resource's hasError action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection](#) **rel=action** **title=testConnection**

This resource's testConnection action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

POST

Provides a way to manually close a connection through the console.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError

The resource supports the following methods:

- [POST](#)

POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

POST

Test the connection. Returns true if the test was successful.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset

The resource supports the following methods:

- [POST](#)

POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool

The resource supports the following methods:

- [POST](#)

POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration

The resource supports the following methods:

- [POST](#)

POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool

The resource supports the following methods:

- [POST](#)

POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

key

JNDI name or resource-link name of the connection pool.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection

The resource supports the following methods:

- [POST](#)

POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

messageListenerType

Message listener type.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getSchema

The resource supports the following methods:

- [POST](#)

POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel=MDBRuntimes**

This resource's MDBRuntimes collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume **rel**=action **title**=resume
This resource's resume action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend **rel**=action **title**=suspend
This resource's suspend action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=poolRuntime
This resource's poolRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=resources
This resource's resources collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=self
This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime
rel=timerRuntime

This resource's timerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime
rel=transactionRuntime

This resource's transactionRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool

The resource supports the following methods:

- [POST](#)

POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

Resumes the specific type of MDB by calling start on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action **title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers

The resource supports the following methods:

- [POST](#)

POST

Activate any temporarily disabled timers.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resumeAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Suspend a particular type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspendAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=capacityRuntime**

This resource's capacityRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**

This resource's maxThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**

This resource's minThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=requestClassRuntime**

This resource's requestClassRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/resume

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes the specified type of activity for all RAs

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for all RAs.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/resume All

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes all activities of all resource adapters.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

props

Properties to be passed to the resource adapters or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Resumes all activities of all resource adapters.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/suspend

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends the specified type of activity for all RAs

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Suspends the specified type of activity for all RAs.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/suspendAll

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends all activities of all resource adapters.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

props

Properties to be passed to the resource adapters or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Suspends all activities of all resource adapters.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime](#)
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration

The resource supports the following methods:

- [POST](#)

POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool

The resource supports the following methods:

- [POST](#)

POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

key

JNDI name or resource-link name of the connection pool.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection

The resource supports the following methods:

- [POST](#)

POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

messageListenerType

Message listener type.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema

The resource supports the following methods:

- [POST](#)

POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=MDBRuntimes

This resource's MDBRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume](#) **rel=action** **title=resume**
This resource's resume action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend](#) **rel=action** **title=suspend**
This resource's suspend action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime](#) **rel=poolRuntime**
This resource's poolRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel=resources**
This resource's resources collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel=self**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime](#) **rel=timerRuntime**
This resource's timerRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inbound

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=transactionRuntime

This resource's transactionRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool

The resource supports the following methods:

- [POST](#)

POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

Resumes the specific type of MDB by calling start on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action
title=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers

The resource supports the following methods:

- [POST](#)

POST

Activate any temporarily disabled timers.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Suspend a particular type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime
rel=capacityRuntime
This resource's capacityRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime
rel=maxThreadsConstraintRuntime
This resource's maxThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime
rel=minThreadsConstraintRuntime
This resource's minThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}
rel=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime
rel=requestClassRuntime
This resource's requestClassRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassesRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime
This resource's capacityRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime
This resource's maxThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime
This resource's minThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime
This resource's requestClassRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/getInboundConnections

The resource supports the following methods:

- [POST](#)

POST

Returns runtime information for the specified inbound connection. A null is returned if the inbound connection is not found.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

messageListenerType

Message listener type.

Type: string

Response Body

Contains a JSON object with a array of `weblogic.management.runtime.ConnectorInboundRuntimeMBean` references return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/getRA

The resource supports the following methods:

- [POST](#)

POST

Returns the runtime information of the resource adapter specified by the given JNDI name. A null is returned if the resource adapter cannot be found. This function returns the active RA if multiple versions of the resource adapters has been deployed

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

key

The JNDI name of the resource adapter.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorComponentRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration](#) **rel**=action **title**=getConfiguration
This resource's getConfiguration action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool](#) **rel**=action **title**=getConnectionPool
This resource's getConnectionPool action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection](#) **rel**=action **title**=getInboundConnection
This resource's getInboundConnection action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema](#) **rel**=action **title**=getSchema
This resource's getSchema action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume](#) **rel**=action **title**=resume
This resource's resume action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll](#) **rel**=action **title**=resumeAll
This resource's resumeAll action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend](#) **rel**=action **title**=suspend
This resource's suspend action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll](#) **rel**=action **title**=suspendAll
This resource's suspendAll action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools
rel=connectionPools

This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime
rel=connectorServiceRuntime

This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime
rel=connectorWorkManagerRuntime

This resource's connectorWorkManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections
rel=inboundConnections

This resource's inboundConnections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime
rel=workManagerRuntime

This resource's workManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes
rel=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset **rel**=action **title**=forceReset

This resource's forceReset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset **rel**=action **title**=reset

This resource's reset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool **rel**=action **title**=testPool

This resource's testPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=connections

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete

The resource supports the following methods:

- [POST](#)

POST

Provides a way to manually close a connection through the console.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError

The resource supports the following methods:

- [POST](#)

POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/conne

POST

Test the connection. Returns true if the test was successful.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/conne

POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/conne

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset

The resource supports the following methods:

- [POST](#)

POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool

The resource supports the following methods:

- [POST](#)

POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime

This resource manages a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs](#)
rel=RAs
This resource's RAs collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getInboundConnections](#) **rel=action title=getInboundConnections**
This resource's getInboundConnections action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getRA](#)
rel=action title=getRA
This resource's getRA action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resume](#)
rel=action title=resume
This resource's resume action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resumeAll](#)
rel=action title=resumeAll
This resource's resumeAll action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspend](#)
rel=action title=suspend
This resource's suspend action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspendAll](#)
rel=action title=suspendAll
This resource's suspendAll action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs](#)
rel=activeRAs
This resource's activeRAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/inactiveRAs **rel**=inactiveRAs

This resource's inactiveRAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration](#) **rel=action** **title=getConfiguration**

This resource's `getConfiguration` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool](#) **rel=action** **title=getConnectionPool**

This resource's `getConnectionPool` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection](#) **rel=action** **title=getInboundConnection**

This resource's `getInboundConnection` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema](#) **rel=action** **title=getSchema**

This resource's `getSchema` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume](#) **rel=action** **title=resume**

This resource's `resume` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll](#) **rel=action** **title=resumeAll**

This resource's `resumeAll` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend](#) **rel=action** **title=suspend**

This resource's `suspend` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll](#) **rel=action** **title=suspendAll**

This resource's `suspendAll` action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=connectionPools

This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime

This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime

This resource's connectorWorkManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=inboundConnections

This resource's inboundConnections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=workManagerRuntime

This resource's workManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened rel=action title=ensureLogOpened](#)
This resource's ensureLogOpened action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog rel=action title=flushLog](#)
This resource's flushLog action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation rel=action title=forceLogRotation](#)
This resource's forceLogRotation action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset rel=action title=forceReset](#)
This resource's forceReset action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset rel=action title=reset](#)
This resource's reset action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool rel=action title=testPool](#)
This resource's testPool action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections rel=connections](#)

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete

The resource supports the following methods:

- [POST](#)

POST

Provides a way to manually close a connection through the console.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError

The resource supports the following methods:

- [POST](#)

POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection

The resource supports the following methods:

- [POST](#)

POST

Test the connection. Returns true if the test was successful.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset

The resource supports the following methods:

- [POST](#)

POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened](#) **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog](#) **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation](#) **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset

The resource supports the following methods:

- [POST](#)

POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool

The resource supports the following methods:

- [POST](#)

POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration

The resource supports the following methods:

- [POST](#)

POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool

The resource supports the following methods:

- [POST](#)

POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

key

JNDI name or resource-link name of the connection pool.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection

The resource supports the following methods:

- [POST](#)

POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

messageListenerType

Message listener type.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema

The resource supports the following methods:

- [POST](#)

POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=MDBRuntimes

This resource's MDBRuntimes collection resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume](#)
rel=action title=resume

This resource's resume action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend](#)
rel=action title=suspend

This resource's suspend action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime](#)
rel=poolRuntime

This resource's poolRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#)
rel=resources

This resource's resources collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel=self**

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=timerRuntime

This resource's timerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=transactionRuntime

This resource's transactionRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool

The resource supports the following methods:

- [POST](#)

POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

Resumes the specific type of MDB by calling start on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action **title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers

The resource supports the following methods:

- [POST](#)

POST

Activate any temporarily disabled timers.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Suspend a particular type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime rel=capacityRuntime](#)

This resource's capacityRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime rel=maxThreadsConstraintRuntime](#)

This resource's maxThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime rel=minThreadsConstraintRuntime](#)

This resource's minThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime rel=requestClassRuntime](#)

This resource's requestClassRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime rel=self](#)

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=capacityRuntime**

This resource's capacityRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**

This resource's maxThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**

This resource's minThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=requestClassRuntime**

This resource's requestClassRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getInboundConnections

The resource supports the following methods:

- [POST](#)

POST

Returns runtime information for the specified inbound connection. A null is returned if the inbound connection is not found.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

messageListenerType

Message listener type.

Type: string

Response Body

Contains a JSON object with a array of `weblogic.management.runtime.ConnectorInboundRuntimeMBean` references return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getRA

The resource supports the following methods:

- [POST](#)

POST

Returns the runtime information of the resource adapter specified by the given JNDI name. A null is returned if the resource adapter cannot be found. This function returns the active RA if multiple versions of the resource adapters has been deployed

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

key

The JNDI name of the resource adapter.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorComponentRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime
rel=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration](#) **rel=action** **title=getConfiguration**

This resource's `getConfiguration` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool](#) **rel=action** **title=getConnectionPool**

This resource's `getConnectionPool` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection](#) **rel=action** **title=getInboundConnection**

This resource's `getInboundConnection` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getSchema](#) **rel=action** **title=getSchema**

This resource's `getSchema` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/resume](#) **rel=action** **title=resume**

This resource's `resume` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/resumeAll](#) **rel=action** **title=resumeAll**

This resource's `resumeAll` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/suspend](#) **rel=action** **title=suspend**

This resource's `suspend` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/suspendAll](#) **rel=action** **title=suspendAll**

This resource's `suspendAll` action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=connectionPools
This resource's connectionPools collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime
This resource's connectorServiceRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime
This resource's connectorWorkManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=inboundConnections
This resource's inboundConnections collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=workManagerRuntime
This resource's workManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes
This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened **rel**=action **title**=ensureLogOpened
 This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog **rel**=action **title**=flushLog
 This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation **rel**=action **title**=forceLogRotation
 This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset **rel**=action **title**=forceReset
 This resource's forceReset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset **rel**=action **title**=reset
 This resource's reset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool **rel**=action **title**=testPool
 This resource's testPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=canonical
 This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=connections
 This resource.

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete](#) **rel=action**
title=delete

This resource's delete action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError](#) **rel=action**
title=hasError

This resource's hasError action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection](#) **rel=action**
title=testConnection

This resource's testConnection action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/conne

POST

Provides a way to manually close a connection through the console.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError

The resource supports the following methods:

- [POST](#)

POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection

The resource supports the following methods:

- [POST](#)

POST

Test the connection. Returns true if the test was successful.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/conne

POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset

The resource supports the following methods:

- [POST](#)

POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool

The resource supports the following methods:

- [POST](#)

POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration

The resource supports the following methods:

- [POST](#)

POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool

The resource supports the following methods:

- [POST](#)

POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

key

JNDI name or resource-link name of the connection pool.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection

The resource supports the following methods:

- [POST](#)

POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

messageListenerType

Message listener type.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getSchema

The resource supports the following methods:

- [POST](#)

POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=MDBRuntimes

This resource's MDBRuntimes collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel**=canonical

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections](#) **rel**=parent

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume **rel**=action **title**=resume
This resource's resume action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend **rel**=action **title**=suspend
This resource's suspend action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=poolRuntime
This resource's poolRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=resources
This resource's resources collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=self
This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime
rel=timerRuntime

This resource's timerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime
rel=transactionRuntime

This resource's transactionRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool

The resource supports the following methods:

- [POST](#)

POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#)
rel=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}](#)
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

Resumes the specific type of MDB by calling start on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action **title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activeDisabledTimers

The resource supports the following methods:

- [POST](#)

POST

Activate any temporarily disabled timers.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/resumeAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Suspend a particular type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/suspendAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resume

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes the specified type of activity for all RAs

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for all RAs.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resumeAll

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes all activities of all resource adapters.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

props

Properties to be passed to the resource adapters or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Resumes all activities of all resource adapters.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspend

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends the specified type of activity for all RAs

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Suspends the specified type of activity for all RAs.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspendAll

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends all activities of all resource adapters.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

props

Properties to be passed to the resource adapters or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Suspends all activities of all resource adapters.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime](#)
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration

The resource supports the following methods:

- [POST](#)

POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool

The resource supports the following methods:

- [POST](#)

POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

key

JNDI name or resource-link name of the connection pool.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection

The resource supports the following methods:

- [POST](#)

POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

messageListenerType

Message listener type.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema

The resource supports the following methods:

- [POST](#)

POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=MDBRuntimes

This resource's MDBRuntimes collection resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume](#) **rel=action** **title=resume**

This resource's resume action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend](#) **rel=action** **title=suspend**

This resource's suspend action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel=canonical**

This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel=parent**

The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime](#) **rel=poolRuntime**

This resource's poolRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel=resources**

This resource's resources collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel=self**

This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime](#) **rel=timerRuntime**

This resource's timerRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inbou

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/M
DBRuntimes/{name}/transactionRuntime **rel**=transactionRuntime

This resource's transactionRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool

The resource supports the following methods:

- [POST](#)

POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

Resumes the specific type of MDB by calling start on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action
title=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inbou

POST

Activate any temporarily disabled timers.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Suspend a particular type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime
rel=capacityRuntime
This resource's capacityRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime
rel=maxThreadsConstraintRuntime
This resource's maxThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime
rel=minThreadsConstraintRuntime
This resource's minThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}
rel=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime
rel=requestClassRuntime
This resource's requestClassRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime
This resource's capacityRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime
This resource's maxThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime
This resource's minThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes
rel=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime
This resource's requestClassRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration](#) **rel=action**
title=getConfiguration
This resource's getConfiguration action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool](#) **rel=action**
title=getConnectionPool
This resource's getConnectionPool action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection](#) **rel=action**
title=getInboundConnection
This resource's getInboundConnection action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getSchema](#) **rel=action** **title=getSchema**
This resource's getSchema action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/resume](#) **rel=action** **title=resume**
This resource's resume action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/resumeAll](#) **rel=action** **title=resumeAll**
This resource's resumeAll action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/suspend](#) **rel=action** **title=suspend**
This resource's suspend action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/suspendAll](#) **rel=action** **title=suspendAll**
This resource's suspendAll action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}](#) **rel=canonical**
This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=connectionPools
This resource's connectionPools collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime
This resource's connectorServiceRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime
This resource's connectorWorkManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=inboundConnections
This resource's inboundConnections collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=workManagerRuntime
This resource's workManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes
This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset **rel**=action **title**=forceReset

This resource's forceReset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset **rel**=action **title**=reset

This resource's reset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool **rel**=action **title**=testPool

This resource's testPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=connections

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime
rel=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete

The resource supports the following methods:

- [POST](#)

POST

Provides a way to manually close a connection through the console.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError

The resource supports the following methods:

- [POST](#)

POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection

The resource supports the following methods:

- [POST](#)

POST

Test the connection. Returns true if the test was successful.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset

The resource supports the following methods:

- [POST](#)

POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset

The resource supports the following methods:

- [POST](#)

POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool

The resource supports the following methods:

- [POST](#)

POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime

This resource manages a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/RAs **rel**=RAs
This resource's RAs collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getInboundConnections **rel**=action **title**=getInboundConnections
This resource's getInboundConnections action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getRA **rel**=action **title**=getRA
This resource's getRA action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resume **rel**=action **title**=resume
This resource's resume action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resumeAll **rel**=action **title**=resumeAll
This resource's resumeAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspend **rel**=action **title**=suspend
This resource's suspend action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspendAll **rel**=action **title**=suspendAll
This resource's suspendAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs **rel**=activeRAs
This resource's activeRAs collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs
rel=inactiveRAs

This resource's inactiveRAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration **rel**=action **title**=getConfiguration

This resource's getConfiguration action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool **rel**=action **title**=getConnectionPool

This resource's getConnectionPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection **rel**=action **title**=getInboundConnection

This resource's getInboundConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema **rel**=action **title**=getSchema

This resource's getSchema action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume **rel**=action **title**=resume

This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll **rel**=action **title**=resumeAll

This resource's resumeAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend **rel**=action **title**=suspend

This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll **rel**=action **title**=suspendAll

This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=connectionPools

This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime

This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime

This resource's connectorWorkManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=inboundConnections

This resource's inboundConnections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=workManagerRuntime

This resource's workManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened](#) **rel=action**
title=ensureLogOpened

This resource's ensureLogOpened action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog](#) **rel=action** **title=flushLog**

This resource's flushLog action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation](#) **rel=action**
title=forceLogRotation

This resource's forceLogRotation action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset](#) **rel=action** **title=forceReset**

This resource's forceReset action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset](#) **rel=action** **title=reset**

This resource's reset action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool](#) **rel=action** **title=testPool**

This resource's testPool action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections](#) **rel=connections**

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete

The resource supports the following methods:

- [POST](#)

POST

Provides a way to manually close a connection through the console.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError

The resource supports the following methods:

- [POST](#)

POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection

The resource supports the following methods:

- [POST](#)

POST

Test the connection. Returns true if the test was successful.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset

The resource supports the following methods:

- [POST](#)

POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset

The resource supports the following methods:

- [POST](#)

POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool

The resource supports the following methods:

- [POST](#)

POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration

The resource supports the following methods:

- [POST](#)

POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool

The resource supports the following methods:

- [POST](#)

POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

key

JNDI name or resource-link name of the connection pool.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection

The resource supports the following methods:

- [POST](#)

POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

messageListenerType

Message listener type.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema

The resource supports the following methods:

- [POST](#)

POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=MDBRuntimes

This resource's MDBRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume **rel**=action **title**=resume

This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend **rel**=action **title**=suspend

This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=poolRuntime

This resource's poolRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=resources

This resource's resources collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime
rel=timerRuntime

This resource's timerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime
rel=transactionRuntime

This resource's transactionRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool

The resource supports the following methods:

- [POST](#)

POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

Resumes the specific type of MDB by calling start on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action **title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers

The resource supports the following methods:

- [POST](#)

POST

Activate any temporarily disabled timers.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Suspend a particular type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getInboundConnections

The resource supports the following methods:

- [POST](#)

POST

Returns runtime information for the specified inbound connection. A null is returned if the inbound connection is not found.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

messageListenerType

Message listener type.

Type: string

Response Body

Contains a JSON object with a array of `weblogic.management.runtime.ConnectorInboundRuntimeMBean` references return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getRA

The resource supports the following methods:

- [POST](#)

POST

Returns the runtime information of the resource adapter specified by the given JNDI name. A null is returned if the resource adapter cannot be found. This function returns the active RA if multiple versions of the resource adapters has been deployed

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

key

The JNDI name of the resource adapter.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorComponentRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration](#) **rel=action** **title=getConfiguration**

This resource's `getConfiguration` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool](#) **rel=action** **title=getConnectionPool**

This resource's `getConnectionPool` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection](#) **rel=action** **title=getInboundConnection**

This resource's `getInboundConnection` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema](#) **rel=action** **title=getSchema**

This resource's `getSchema` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume](#) **rel=action** **title=resume**

This resource's `resume` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll](#) **rel=action** **title=resumeAll**

This resource's `resumeAll` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend](#) **rel=action** **title=suspend**

This resource's `suspend` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll](#) **rel=action** **title=suspendAll**

This resource's `suspendAll` action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=connectionPools
This resource's connectionPools collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime
This resource's connectorServiceRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime
This resource's connectorWorkManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=inboundConnections
This resource's inboundConnections collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=workManagerRuntime
This resource's workManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes
This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset **rel**=action **title**=forceReset

This resource's forceReset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset **rel**=action **title**=reset

This resource's reset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool **rel**=action **title**=testPool

This resource's testPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=connections

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete](#) **rel=action**
title=delete

This resource's delete action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError](#) **rel=action**
title=hasError

This resource's hasError action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection](#) **rel=action**
title=testConnection

This resource's testConnection action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete

The resource supports the following methods:

- [POST](#)

POST

Provides a way to manually close a connection through the console.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError

The resource supports the following methods:

- [POST](#)

POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection

The resource supports the following methods:

- [POST](#)

POST

Test the connection. Returns true if the test was successful.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset

The resource supports the following methods:

- [POST](#)

POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset

The resource supports the following methods:

- [POST](#)

POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool

The resource supports the following methods:

- [POST](#)

POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration

The resource supports the following methods:

- [POST](#)

POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool

The resource supports the following methods:

- [POST](#)

POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

key

JNDI name or resource-link name of the connection pool.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection

The resource supports the following methods:

- [POST](#)

POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

messageListenerType

Message listener type.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema

The resource supports the following methods:

- [POST](#)

POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=MDBRuntimes

This resource's MDBRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume **rel**=action **title**=resume
This resource's resume action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend **rel**=action **title**=suspend
This resource's suspend action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=poolRuntime
This resource's poolRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=resources
This resource's resources collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=self
This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime
rel=timerRuntime

This resource's timerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime
rel=transactionRuntime

This resource's transactionRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool

The resource supports the following methods:

- [POST](#)

POST

Instructs the Pool to initialize itself to its configured startup time size.
This is a synchronous and will wait until the pool is initialized before returning.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources
rel=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

Resumes the specific type of MDB by calling start on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action **title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activeDisabledTimers

The resource supports the following methods:

- [POST](#)

POST

Activate any temporarily disabled timers.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Suspend a particular type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resume

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes the specified type of activity for all RAs

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for all RAs.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resumeAll

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes all activities of all resource adapters.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

props

Properties to be passed to the resource adapters or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Resumes all activities of all resource adapters.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspend

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends the specified type of activity for all RAs

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Suspends the specified type of activity for all RAs.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspendAll

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends all activities of all resource adapters.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

props

Properties to be passed to the resource adapters or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Suspends all activities of all resource adapters.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration

The resource supports the following methods:

- [POST](#)

POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool

The resource supports the following methods:

- [POST](#)

POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

key

JNDI name or resource-link name of the connection pool.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection

The resource supports the following methods:

- [POST](#)

POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

messageListenerType

Message listener type.

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getSchema

The resource supports the following methods:

- [POST](#)

POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version

String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=MDBRuntimes

This resource's MDBRuntimes collection resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume **rel**=action **title**=resume

This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend **rel**=action **title**=suspend

This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=poolRuntime

This resource's poolRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=resources

This resource's resources collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=timerRuntime

This resource's timerRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConn

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=transactionRuntime

This resource's transactionRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool

The resource supports the following methods:

- [POST](#)

POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

Resumes the specific type of MDB by calling start on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action
title=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers

The resource supports the following methods:

- [POST](#)

POST

Activate any temporarily disabled timers.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/resumeAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Suspend a particular type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/suspendAll

The resource supports the following methods:

- [POST](#)

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime](#) **rel=capacityRuntime**
This resource's capacityRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**
This resource's maxThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**
This resource's minThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel=requestClassRuntime**
This resource's requestClassRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime
rel=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime rel=self](#)

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime
This resource's capacityRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime
This resource's maxThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime
This resource's minThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime
This resource's requestClassRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/resume

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes the specified type of activity for all RAs

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for all RAs.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/resumeAll

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Resumes all activities of all resource adapters.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

props

Properties to be passed to the resource adapters or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Resumes all activities of all resource adapters.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/suspend

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends the specified type of activity for all RAs

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

props

Properties to pass on to the RA or null

Type: `java.util.Properties`

Response Body

Contains an empty JSON object.

POST

Suspends the specified type of activity for all RAs.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/suspendAll

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends all activities of all resource adapters.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

props

Properties to be passed to the resource adapters or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Suspends all activities of all resource adapters.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceShutdown

The resource supports the following methods:

- [POST](#)

POST

Force shutdown the partition. Causes the partition to reject new requests and fail pending requests.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceShutdownResourceGroup

The resource supports the following methods:

- [POST](#)

POST

Force shutdown the resource group. Causes the resource group to reject new requests and fail pending requests.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName

resourceGroupName

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceSuspend

The resource supports the following methods:

- [POST](#)

POST

Transitions the partition from `RUNNING` to `ADMIN` state forcefully cancelling inflight work.

Work that cannot be cancelled is dropped. Applications are transitioned to admin mode. This forcefully suspends the partition and transitions it to `ADMIN` state.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceSuspendResourceGroup

The resource supports the following methods:

- [POST](#)

POST

Transitions the resource group from `RUNNING` to `ADMIN` state forcefully cancelling inflight work.

Work that cannot be cancelled is dropped. Applications are brought into the admin mode. This forcefully suspends the resource group and transitions it `ADMIN` state.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName

resourceGroupName

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/getRgState

The resource supports the following methods:

- [POST](#)

POST

The current state of the named resource group MBean

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName
the resource group name
Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime

This resource manages a [weblogic.management.runtime.JDBCPartitionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JDBCPartitionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JDBCPartitionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans](#)
[rel=JDBCDataSourceRuntimeMBeans](#)

This resource's JDBCDataSourceRuntimeMBeans collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans](#)
[rel=JDBCMultiDataSourceRuntimeMBeans](#)

This resource's JDBCMultiDataSourceRuntimeMBeans collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime](#) [rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#)
[rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime](#) [rel=self](#)

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans

This resource manages a collection of [weblogic.management.runtime.JDBCDataSourceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JDBCDataSourceRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JDBCDataSourceRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}

This resource manages a [weblogic.management.runtime.JDBCDataSourceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JDBCDataSourceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JDBCDataSourceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCDriverRuntime **rel**=JDBCDriverRuntime
This resource's JDBCDriverRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean **rel**=JDBCReplayStatisticsRuntimeMBean
This resource's JDBCReplayStatisticsRuntimeMBean singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/clearStatementCache **rel**=action **title**=clearStatementCache
This resource's clearStatementCache action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPool **rel**=action **title**=dumpPool
This resource's dumpPool action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPoolProfile **rel**=action **title**=dumpPoolProfile
This resource's dumpPoolProfile action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceShutdown **rel**=action **title**=forceShutdown
This resource's forceShutdown action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceSuspend **rel**=action **title**=forceSuspend
This resource's forceSuspend action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/poolExists **rel**=action **title**=poolExists
This resource's poolExists action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/reset **rel**=action **title**=reset
This resource's reset action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/resume **rel**=action **title**=resume
This resource's resume action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/shrink **rel**=action **title**=shrink
This resource's shrink action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/shutdown **rel**=action **title**=shutdown
This resource's shutdown action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/start **rel**=action **title**=start
This resource's start action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/suspend **rel**=action **title**=suspend
This resource's suspend action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/testPool **rel**=action **title**=testPool
This resource's testPool action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name} **rel**=canonical
This resource.
- **rel**=lastTask
This resource's lastTask reference to a weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes **rel**=workManagerRuntimes
This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/clearStatementCache

The resource supports the following methods:

- [POST](#)

POST

For each connection in the connection pool, clears the statement cache of Prepared and Callable Statements.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPool

The resource supports the following methods:

- [POST](#)

POST

Prints out information about all the connections in the connection pool in the data source.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPoolProfile

The resource supports the following methods:

- [POST](#)

POST

Prints out profile information about the data source.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceShutdown

The resource supports the following methods:

- [POST](#)

POST

Shuts down a data source that has a health state of `Running`, including forcing the disconnection of all current connection users.

If successful, the health state is set to `Shutdown`

This is a privileged operation that can only be invoked by an authorized user.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceSuspend

The resource supports the following methods:

- [POST](#)

POST

Suspends a data source that has the health state of `Running`, including disconnecting all current connection users. All current connections are closed and recreated.

If successful, the health state is set to `Suspended`

This is a privileged operation that can only be invoked by an authorized user.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCDriverRuntime

This resource manages a [weblogic.management.runtime.JDBCDriverRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JDBCDataSourceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JDBCDataSourceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCDataSourceRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCDataSourceRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean

This resource manages a [weblogic.management.runtime.JDBCReplayStatisticsRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JDBCReplayStatisticsRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JDBCReplayStatisticsRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/clearStatistics **rel**=action **title**=clearStatistics

This resource's clearStatistics action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/refreshStatistics **rel**=action **title**=refreshStatistics

This resource's refreshStatistics action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes **rel**=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/clearStatistics

The resource supports the following methods:

- [POST](#)

POST

POST

Clear the statistics on all connections.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/refreshStatistics

The resource supports the following methods:

- [POST](#)

POST

POST

Update the snapshot

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/capacityRuntime](#) **rel=capacityRuntime**

This resource's capacityRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**

This resource's maxThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**

This resource's minThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=requestClassRuntime**

This resource's requestClassRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/capacityRuntime
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/requestClassRuntime
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/requestClassRuntime
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/poolExists

The resource supports the following methods:

- [POST](#)

POST

Specifies whether a data source with the given name exists.

This is a privileged operation that can only be invoked by an authorized user.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

poolName

Name of the pool being looked for

Type: string

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/reset

The resource supports the following methods:

- [POST](#)

POST

Resets the connection pool in the data source by shutting down and recreating all available database connections in the pool.

Use when a data source is in the health state of `Unhealthy` and needs to be reinitialized.

This is a privileged operation that can only be invoked by an authorized user.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

Restores all access to and operations on a data source that has a health state of Suspended

If successful, the health state is set to Running

This is a privileged operation that can only be invoked by an authorized user.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/shrink

The resource supports the following methods:

- [POST](#)

POST

Shrinks the database connection pool in the data source to either the current number of reserved connections or the initial size of the connection pool, whichever is greater.

This is a privileged operation that can only be invoked by an authorized user.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/shutdown

The resource supports the following methods:

- [POST](#)

POST

Shuts down a data source that has a health state of `Running`. If any connections from the data source are currently in use, the operation fails and the health state remains `Running`.

If successful, the health state is set to `Shutdown`.

This is a privileged operation that can only be invoked by an authorized user.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/start

The resource supports the following methods:

- [POST](#)

POST

Starts a data source that has a health state of `Shutdown`

If successful, the health state is set to `Running`

This is a privileged operation that can only be invoked by an authorized user.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

Suspends a data source has the health state of `Running` and disables existing connections. If any connections from the data source are currently in use, the operation fails and the health state remains `Running`

If successful, the health state is set to `Suspended`

This is a privileged operation that can only be invoked by an authorized user.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/testPool

The resource supports the following methods:

- [POST](#)

POST

Tests the connection pool in the data source by reserving and releasing a connection from it.

If the pool configuration attribute `TestConnectionsOnReserve` is enabled, the acquired connection is also tested as part of the reserve operation.

Roles

Admin

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of `weblogic.management.runtime.WorkManagerRuntimeMBean` instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of `weblogic.management.runtime.WorkManagerRuntimeMBean` entities.

This method can return the following links:

- **uri**=`/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes` **rel**=canonical

This resource.

- **uri**=`/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}` **rel**=parent

The parent resource of this resource.

- **uri**=`/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes` **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans

This resource manages a collection of [weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}

This resource manages a [weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}](#) **rel**=self

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes](#) **rel**=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of `weblogic.management.runtime.WorkManagerRuntimeMBean` instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of `weblogic.management.runtime.WorkManagerRuntimeMBean` entities.

This method can return the following links:

- **uri**=`/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes` **rel**=canonical

This resource.

- **uri**=`/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}` **rel**=parent

The parent resource of this resource.

- **uri**=`/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes` **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime rel=capacityRuntime](#)
This resource's capacityRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime rel=maxThreadsConstraintRuntime](#)
This resource's maxThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime rel=minThreadsConstraintRuntime](#)
This resource's minThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime rel=requestClassRuntime](#)
This resource's requestClassRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime

This resource manages a [weblogic.management.runtime.JMSRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers](#) **rel**=JMSServers
This resource's JMSServers collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime](#) **rel**=canonical
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections](#) **rel**=connections
This resource's connections collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) **rel**=parent
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections

This resource manages a collection of [weblogic.management.runtime.JMSConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JMSConnectionRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JMSConnectionRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/connections/{name}

This resource manages a [weblogic.management.runtime.JMSCConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSCConnectionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSCConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/destroy **rel**=action **title**=destroy
This resource's destroy action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions **rel**=sessions
This resource's sessions collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/connections/{name}/destroy

The resource supports the following methods:

- [POST](#)

POST

Destroys server side context for the connection.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/connections/{name}/sessions

This resource manages a collection of [weblogic.management.runtime.JMSSessionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JMSSessionRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JMSSessionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}

This resource manages a [weblogic.management.runtime.JMSSessionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSSessionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSSessionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers](#) **rel=consumers**

This resource's consumers collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/producers](#) **rel=producers**

This resource's producers collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers

This resource manages a collection of [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers/{name}

This resource manages a [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers/{name}](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/producers

This resource manages a collection of [weblogic.management.runtime.JMSProducerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JMSProducerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JMSProducerRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/producers](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/producers](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/connections/{name}/sessions/{name}/producers/{name}

This resource manages a [weblogic.management.runtime.JMSProducerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSProducerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSProducerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/producers/{name}](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/producers](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/producers/{name}](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers

This resource manages a collection of [weblogic.management.runtime.JMSServerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JMSServerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JMSServerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}

This resource manages a [weblogic.management.runtime.JMSServerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSServerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSServerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/closeCursor **rel**=action **title**=closeCursor
This resource's closeCursor action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/forceCommit **rel**=action **title**=forceCommit
This resource's forceCommit action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/forceRollback **rel**=action **title**=forceRollback
This resource's forceRollback action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/getCursorEndPosition **rel**=action
title=getCursorEndPosition
This resource's getCursorEndPosition action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/getCursorSize **rel**=action **title**=getCursorSize
This resource's getCursorSize action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/getCursorStartPosition **rel**=action
title=getCursorStartPosition
This resource's getCursorStartPosition action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/getMessages **rel**=action **title**=getMessages
This resource's getMessages action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/getTransactionStatus **rel**=action
title=getTransactionStatus
This resource's getTransactionStatus action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/pauseConsumption **rel**=action
title=pauseConsumption
This resource's pauseConsumption action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/pauseInsertion **rel**=action **title**=pauseInsertion

This resource's pauseInsertion action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/pauseProduction **rel**=action
title=pauseProduction

This resource's pauseProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/resumeConsumption **rel**=action
title=resumeConsumption

This resource's resumeConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/resumeInsertion **rel**=action
title=resumeInsertion

This resource's resumeInsertion action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/resumeProduction **rel**=action
title=resumeProduction

This resource's resumeProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sort **rel**=action **title**=sort

This resource's sort action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations **rel**=destinations

This resource's destinations collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes **rel**=sessionPoolRuntimes

This resource's sessionPoolRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/closeCursor

The resource supports the following methods:

- [POST](#)

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/destinations

This resource manages a collection of [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/destinations/{name}

This resource manages a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/closeCursor](#) **rel=action**
title=closeCursor
This resource's closeCursor action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/createDurableSubscriber](#)
rel=action **title=createDurableSubscriber**
This resource's createDurableSubscriber action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/deleteMessages](#)
rel=action **title=deleteMessages**
This resource's deleteMessages action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorEndPosition](#)
rel=action **title=getCursorEndPosition**
This resource's getCursorEndPosition action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorSize](#) **rel=action**
title=getCursorSize
This resource's getCursorSize action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorStartPosition](#)
rel=action **title=getCursorStartPosition**
This resource's getCursorStartPosition action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/getMessages](#) **rel=action**
title=getMessages
This resource's getMessages action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseConsumption](#)
rel=action **title=pauseConsumption**
This resource's pauseConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseInsertion **rel**=action **title**=pauseInsertion
This resource's pauseInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseProduction **rel**=action **title**=pauseProduction
This resource's pauseProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeConsumption **rel**=action **title**=resumeConsumption
This resource's resumeConsumption action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeInsertion **rel**=action **title**=resumeInsertion
This resource's resumeInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeProduction **rel**=action **title**=resumeProduction
This resource's resumeProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/sort **rel**=action **title**=sort
This resource's sort action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers **rel**=durableSubscribers
This resource's durableSubscribers collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name} **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/destinations/{name}/closeCursor

The resource supports the following methods:

- [POST](#)

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/destinations/{name}/createDurableSubscriber

The resource supports the following methods:

- [POST](#)

POST

Creates a durable subscriber on the destination with the specified client ID and subscription name. A message selector and no-local flag may also be specified.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

ClientID

An identifier that uniquely identifies a client connection.

Type: string

subscriptionName

The name used to identify this subscription.

Type: string

selector

Only messages with properties matching the message selector expression are delivered. A value of null or an empty string indicates that there is no message selector for the message consumer.

Type: string

noLocal

If set, inhibits the delivery of messages published by its own connection.

Type: boolean

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/destinations/{name}/deleteMessages

The resource supports the following methods:

- [POST](#)

POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A JMS message selector to identify which messages to delete.

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers

This resource manages a collection of [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers
rel=self

This resource.

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM
SRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name
}**

This resource manages a [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/closeCursor rel=action title=closeCursor](#)

This resource's closeCursor action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/deleteMessages rel=action title=deleteMessages](#)

This resource's deleteMessages action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorEndPosition rel=action title=getCursorEndPosition](#)

This resource's getCursorEndPosition action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorSize rel=action title=getCursorSize](#)

This resource's getCursorSize action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorStartPosition rel=action title=getCursorStartPosition](#)

This resource's getCursorStartPosition action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getMessages rel=action title=getMessages](#)

This resource's getMessages action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/sort rel=action title=sort](#)

This resource's sort action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name} rel=canonical](#)

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime **rel**=destinationRuntime

This resource's destinationRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name} **rel**=self

This resource.

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM
SRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name
}/closeCursor**

The resource supports the following methods:

- [POST](#)

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name }/deleteMessages

The resource supports the following methods:

- [POST](#)

POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A JMS message selector to identify which messages to delete.

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name }/destinationRuntime

This resource manages a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor rel=action title=closeCursor](#)

This resource's closeCursor action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/createDurableSubscriber rel=action title=createDurableSubscriber](#)

This resource's createDurableSubscriber action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessages rel=action title=deleteMessages](#)

This resource's deleteMessages action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorEndPosition rel=action title=getCursorEndPosition](#)

This resource's getCursorEndPosition action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSize rel=action title=getCursorSize](#)

This resource's getCursorSize action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorStartPosition rel=action title=getCursorStartPosition](#)

This resource's getCursorStartPosition action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages rel=action title=getMessages](#)

This resource's getMessages action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsumption rel=action title=pauseConsumption](#)

This resource's pauseConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertion **rel**=action **title**=pauseInsertion

This resource's pauseInsertion action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduction **rel**=action **title**=pauseProduction

This resource's pauseProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsumption **rel**=action **title**=resumeConsumption

This resource's resumeConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInsertion **rel**=action **title**=resumeInsertion

This resource's resumeInsertion action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProduction **rel**=action **title**=resumeProduction

This resource's resumeProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/sort **rel**=action **title**=sort

This resource's sort action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/durableSubscribers **rel**=durableSubscribers

This resource's durableSubscribers collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor

The resource supports the following methods:

- [POST](#)

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name }/destinationRuntime/createDurableSubscriber

The resource supports the following methods:

- [POST](#)

POST

Creates a durable subscriber on the destination with the specified client ID and subscription name. A message selector and no-local flag may also be specified.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

ClientID

An identifier that uniquely identifies a client connection.

Type: string

subscriptionName

The name used to identify this subscription.

Type: string

selector

Only messages with properties matching the message selector expression are delivered. A value of null or an empty string indicates that there is no message selector for the message consumer.

Type: string

noLocal

If set, inhibits the delivery of messages published by its own connection.

Type: boolean

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessages

The resource supports the following methods:

- [POST](#)

POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A JMS message selector to identify which messages to delete.

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSize

The resource supports the following methods:

- [POST](#)

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A valid JMS message selector.

Type: string

timeout

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

state

A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

Type: int

Response Body

Contains a JSON object with a string return field.

POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A valid JMS message selector.

Type: string

timeout

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name }/destinationRuntime/pauseConsumption

The resource supports the following methods:

- [POST](#)

POST

Pauses the consumption on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name }/destinationRuntime/pauseInsertion

The resource supports the following methods:

- [POST](#)

POST

Pauses the insertion on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM
SRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name
}/destinationRuntime/pauseProduction**

The resource supports the following methods:

- [POST](#)

POST

Pauses the production on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name }/destinationRuntime/resumeConsumption

The resource supports the following methods:

- [POST](#)

POST

Resumes the consumption operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM
SRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name
}/destinationRuntime/resumeInsertion**

The resource supports the following methods:

- [POST](#)

POST

Resumes the insertion operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name }/destinationRuntime/resumeProduction

The resource supports the following methods:

- [POST](#)

POST

Resumes the production operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM
SRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name
}/destinationRuntime/sort**

The resource supports the following methods:

- [POST](#)

POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The handle of the cursor.

Type: string

start

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

Type: long

fields

The JMS header attributes on which to sort.

Type: array of string

ascending

Determines whether the sort of the corresponding fields element is in ascending or descending order.

Type: array of boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name }/getCursorPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name }/getCursorSize

The resource supports the following methods:

- [POST](#)

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name }/getCursorPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name }/getMessages

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A valid JMS message selector.

Type: string

timeout

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

state

A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

Type: int

Response Body

Contains a JSON object with a string return field.

POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A valid JMS message selector.

Type: string

timeout

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/sort

The resource supports the following methods:

- [POST](#)

POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The handle of the cursor.

Type: string

start

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

Type: long

fields

The JMS header attributes on which to sort.

Type: array of string

ascending

Determines whether the sort of the corresponding fields element is in ascending or descending order.

Type: array of boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/destinations/{name}/getCursorPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/destinations/{name}/getCursorSize

The resource supports the following methods:

- [POST](#)

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/destinations/{name}/getCursorStartPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/destinations/{name}/getMessages

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A valid JMS message selector.

Type: string

timeout

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

state

A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

Type: int

Response Body

Contains a JSON object with a string return field.

POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A valid JMS message selector.

Type: string

timeout

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/destinations/{name}/pauseConsumption

The resource supports the following methods:

- [POST](#)

POST

Pauses the consumption on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/destinations/{name}/pauseInsertion

The resource supports the following methods:

- [POST](#)

POST

Pauses the insertion on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/destinations/{name}/pauseProduction

The resource supports the following methods:

- [POST](#)

POST

Pauses the production on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/destinations/{name}/resumeConsumption

The resource supports the following methods:

- [POST](#)

POST

Resumes the consumption operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/destinations/{name}/resumelInsertion

The resource supports the following methods:

- [POST](#)

POST

Resumes the insertion operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/destinations/{name}/resumeProduction

The resource supports the following methods:

- [POST](#)

POST

Resumes the production operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/destinations/{name}/sort

The resource supports the following methods:

- [POST](#)

POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The handle of the cursor.

Type: string

start

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

Type: long

fields

The JMS header attributes on which to sort.

Type: array of string

ascending

Determines whether the sort of the corresponding fields element is in ascending or descending order.

Type: array of boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/forceCommit

The resource supports the following methods:

- [POST](#)

POST

Causes the work associated with the specified transaction branch to be committed.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

xid

An xid in string representation for a JMS transaction branch.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/forceRollback

The resource supports the following methods:

- [POST](#)

POST

Causes the work associated with the specified transaction branch to be rolled back.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

xid

An xid in string representation for a JMS transaction branch.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/getCursorPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/getCursorSize

The resource supports the following methods:

- [POST](#)

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/getCursorStartPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/getMessages

The resource supports the following methods:

- [POST](#)

POST

Returns a set of messages that are associated with a JMS transaction branch. Note that the result set is returned to the caller in the form of a message cursor that may contain messages from several destinations on this JMS server.

The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

xid

An Xid in string representation for a JMS transaction branch.

Type: string

timeoutSeconds

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/getTransactionStatus

The resource supports the following methods:

- [POST](#)

POST

Given an Xid this method returns the JTA status of the associated JMS transaction branch.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

xid

An Xid in string representation for a JMS transaction branch.

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/logRuntime

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened
This resource's ensureLogOpened action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime/flushLog **rel**=action **title**=flushLog
This resource's flushLog action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation
This resource's forceLogRotation action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/logRuntime/flushLog

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime/flush-

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime/for-

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/pauseConsumption

The resource supports the following methods:

- [POST](#)

POST

Pauses the consumption operation on all the destinations hosted by the JMSServer.

When the JMSServer is paused for consumption, all of its destination's state is marked as "consumption paused" and all the new synchronous receive operations will block until the destination is resumed and there are messages available for consumption. All the synchronous receive with blocking timeout will block until the timeout happens during the consumption paused state.

All the asynchronous consumers attached to that destination will not get any messages delivered to them while the destination in "consumption paused" state.

After a successful consumption "pause" operation, the user has to explicitly "resume" the destination to allow for any further consume operations on that destination

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/pauseInsertion

The resource supports the following methods:

- [POST](#)

POST

Pauses the appearance of any messages on all the destinations of the JMSServer, that are result of the in-flight work completion on all the destinations hosted by this JMSServer.

Definition of In-Flight work

The definitions below are based on the current implementation of WebLogic JMS subsystem.

- In-flight messages associated with Producers
 - UN-BORN MESSAGES

Messages that are produced by the producer, with "birth time" (TimeToDeliver) set in future are called un-born messages and are counted as "pending" messages in the destination statistics and are not available for consumers yet.
 - UN-COMMITTED MESSAGES

These are the messages that are produced by the producer as part of the transaction (using either user transaction or transacted session) and the transaction is still not committed or rolled back. These messages are also counted as "pending" messages in the destination statistics and are not available for consumption.
 - QUOTA BLOCKING SEND

These are the messages that are produced by the producers but are not able reach the destination because of (either message or byte or both) quota limit on the destination and the producers are willing to block for a specific period of time for the quota to be available. These messages are invisible to the system and are not counted against any of the destination statistics.
- In-flight messages associated with Consumers
 - UN-ACKNOWLEDGED (CLIENT ACK PENDING) MESSAGES

These are the messages that are successfully consumed by the clients using a "client acknowledge" session, and are awaiting acknowledgements from the clients. These are "pending messages" which will be removed from the destination/system when the acknowledgement is received.
 - UN-COMMITTED MESSAGES

These are the messages that are consumed (received) by the clients within a transaction (using either user transaction or transacted session) and the transaction is still not committed or rolled back. When the clients successfully commit the transaction the messages get removed from the system.
 - ROLLED BACK MESSAGES

These are the messages that are put back on the destination because of a successful rollback of transactional receive by the consumers. These messages might or might not be ready for consumption (re-delivered) to the clients immediately, depending on the redelivery parameters, RedeliveryDelay and/or RedeliveryDelayOverride and RedeliveryLimit configured on the associated JMSConnectionFactory and JMSDestination respectively.

If there is a redelivery delay configured, then for that "delay" duration, the messages are not available for consumption and are counted as "pending" in

the destination statistics and after the "delay" period, if the redelivery limit is not exceeded, then they are delivered (made available for consumption) on that destination and are counted as "current" messages in the destination statistics. If the redelivery limit exceeds, then those messages will be moved to the ErrorDestination, if one configured.

Another parameter that controls the availability of the rolled back messages is RedeliveryLimit.

- RECOVERED MESSAGES

These messages are similar to ROLLED BACK MESSAGES except that these messages appear on the queue because of an explicit call to session "recover" by the client.

- REDELIVERED MESSAGES

These are again similar to ROLLED BACK MESSAGES except that these messages may re-appear on the destination because of an un-successful delivery attempt to the client (consumer crash, close etc.).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/pauseProduction

The resource supports the following methods:

- [POST](#)

POST

Pauses the new message production on all the destinations hosted by the JMS Server.

When the production is paused, it would prevent any new produce operations from both new and existing producers attached to the destinations. When the destination is "resumed from production pause", all the new message production is allowed from both new and existing producers attached to that destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/resumeConsumption

The resource supports the following methods:

- [POST](#)

POST

Resumes the consumption operation on all the destinations hosted by the JMSServer.

The state of the destinations shall be marked as "consumption enabled" thus allowing all the "consuming" activity to continue normally.

Invoking this API on a JMSServer that is currently not in "consumption paused" state has no effect.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/resumeInsertion

The resource supports the following methods:

- [POST](#)

POST

Resumes the in-flight message production operation on all the destinations hosted by the JMS Server. The state of the JMS Server shall be marked as "insertion enabled" thus allowing all the messages from in-flight work completion are allowed to appear on the destinations.

Invoking this API on a JMS Server that is currently not in "insertion paused" state has no effect.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/resumeProduction

The resource supports the following methods:

- [POST](#)

POST

Resumes the new message production operation on all the destinations hosted by the JMSServer. The state of the JMSServer shall be marked as "production enabled" thus allowing all the new "producing" activity to continue normally. Invoking this API on a JMSServer that is currently not in "production paused" state has no effect.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes

This resource manages a collection of [weblogic.management.runtime.JMSSessionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JMSSessionPoolRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JMSSessionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSessionPoolRuntime/JMSServers/{name}/sessionPoolRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSessionPoolRuntime/JMSServers/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSessionPoolRuntime/JMSServers/{name}/sessionPoolRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}

This resource manages a [weblogic.management.runtime.JMSSessionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSSessionPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSSessionPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSessionPoolRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer **rel**=JMSServer

This resource's JMSServer singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSessionPoolRuntime/JMSServers/{name}/sessionPoolRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSessionPoolRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers **rel**=connectionConsumers

This resource's connectionConsumers collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSessionPoolRuntime/JMSServers/{name}/sessionPoolRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSessionPoolRuntime/JMSServers/{name}/sessionPoolRuntimes/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers

This resource manages a collection of [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers/{name}

This resource manages a [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer

This resource manages a [weblogic.management.runtime.JMSServerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSServerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSServerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/closeCursor rel=action title=closeCursor](#)
This resource's closeCursor action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/forceCommit rel=action title=forceCommit](#)
This resource's forceCommit action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/forceRollback rel=action title=forceRollback](#)
This resource's forceRollback action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorPosition rel=action title=getCursorPosition](#)
This resource's getCursorPosition action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorSize rel=action title=getCursorSize](#)
This resource's getCursorSize action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorPosition rel=action title=getCursorPosition](#)
This resource's getCursorPosition action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getMessages rel=action title=getMessages](#)
This resource's getMessages action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getTransactionStatus rel=action title=getTransactionStatus](#)
This resource's getTransactionStatus action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseConsumption **rel**=action **title**=pauseConsumption
This resource's pauseConsumption action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseInsertion **rel**=action **title**=pauseInsertion
This resource's pauseInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseProduction **rel**=action **title**=pauseProduction
This resource's pauseProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeConsumption **rel**=action **title**=resumeConsumption
This resource's resumeConsumption action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeInsertion **rel**=action **title**=resumeInsertion
This resource's resumeInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeProduction **rel**=action **title**=resumeProduction
This resource's resumeProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/sort **rel**=action **title**=sort
This resource's sort action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations **rel**=destinations
This resource's destinations collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime **rel**=logRuntime
This resource's logRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name} **rel**=parent
The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer
rel=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/sessionPoolRuntimes
rel=sessionPoolRuntimes

This resource's sessionPoolRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/closeCursor

The resource supports the following methods:

- [POST](#)

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations

This resource manages a collection of [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}

This resource manages a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/closeCursor **rel**=action **title**=closeCursor

This resource's closeCursor action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/createDurableSubscriber **rel**=action **title**=createDurableSubscriber

This resource's createDurableSubscriber action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/deleteMessages **rel**=action **title**=deleteMessages

This resource's deleteMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorEndPosition **rel**=action **title**=getCursorEndPosition

This resource's getCursorEndPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorSize **rel**=action **title**=getCursorSize

This resource's getCursorSize action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorStartPosition **rel**=action **title**=getCursorStartPosition

This resource's getCursorStartPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getMessages **rel**=action **title**=getMessages

This resource's getMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseConsumption **rel**=action **title**=pauseConsumption

This resource's pauseConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseInsertion **rel**=action **title**=pauseInsertion
This resource's pauseInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseProduction **rel**=action **title**=pauseProduction
This resource's pauseProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeConsumption **rel**=action **title**=resumeConsumption
This resource's resumeConsumption action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeInsertion **rel**=action **title**=resumeInsertion
This resource's resumeInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeProduction **rel**=action **title**=resumeProduction
This resource's resumeProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/sort **rel**=action **title**=sort
This resource's sort action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers **rel**=durableSubscribers
This resource's durableSubscribers collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name} **rel**=self
This resource.

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM
SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti
nations/{name}/closeCursor**

The resource supports the following methods:

- [POST](#)

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM
SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti
nations/{name}/createDurableSubscriber**

The resource supports the following methods:

- [POST](#)

POST

Creates a durable subscriber on the destination with the specified client ID and subscription name. A message selector and no-local flag may also be specified.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

ClientID

An identifier that uniquely identifies a client connection.

Type: string

subscriptionName

The name used to identify this subscription.

Type: string

selector

Only messages with properties matching the message selector expression are delivered. A value of null or an empty string indicates that there is no message selector for the message consumer.

Type: string

noLocal

If set, inhibits the delivery of messages published by its own connection.

Type: boolean

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti nations/{name}/deleteMessages

The resource supports the following methods:

- [POST](#)

POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A JMS message selector to identify which messages to delete.

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti nations/{name}/durableSubscribers

This resource manages a collection of [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/destinations/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti nations/{name}/durableSubscribers/{name}

This resource manages a [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/closeCursor **rel**=action **title**=closeCursor

This resource's closeCursor action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/deleteMessages **rel**=action **title**=deleteMessages

This resource's deleteMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorPosition **rel**=action **title**=getCursorPosition

This resource's getCursorPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorSize **rel**=action **title**=getCursorSize

This resource's getCursorSize action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorPosition **rel**=action **title**=getCursorPosition

This resource's getCursorPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getMessages **rel**=action **title**=getMessages

This resource's getMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/sort **rel**=action **title**=sort

This resource's sort action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/destinationRuntime **rel**=destinationRuntime

This resource's destinationRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/closeCursor

The resource supports the following methods:

- [POST](#)

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/deleteMessages

The resource supports the following methods:

- [POST](#)

POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A JMS message selector to identify which messages to delete.

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime

This resource manages a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor **rel**=action **title**=closeCursor

This resource's closeCursor action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/createDurableSubscriber **rel**=action **title**=createDurableSubscriber

This resource's createDurableSubscriber action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessages **rel**=action **title**=deleteMessages

This resource's deleteMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorPosition **rel**=action **title**=getCursorPosition

This resource's getCursorPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSize **rel**=action **title**=getCursorSize

This resource's getCursorSize action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorPosition **rel**=action **title**=getCursorPosition

This resource's getCursorPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages **rel**=action **title**=getMessages

This resource's getMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsumption **rel**=action **title**=pauseConsumption
This resource's pauseConsumption action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertion **rel**=action **title**=pauseInsertion
This resource's pauseInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduction **rel**=action **title**=pauseProduction
This resource's pauseProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsumption **rel**=action **title**=resumeConsumption
This resource's resumeConsumption action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInsertion **rel**=action **title**=resumeInsertion
This resource's resumeInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProduction **rel**=action **title**=resumeProduction
This resource's resumeProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/sort **rel**=action **title**=sort
This resource's sort action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/durableSubscribers **rel**=durableSubscribers
This resource's durableSubscribers collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor

The resource supports the following methods:

- [POST](#)

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/createDurableSubscriber

The resource supports the following methods:

- [POST](#)

POST

Creates a durable subscriber on the destination with the specified client ID and subscription name. A message selector and no-local flag may also be specified.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

ClientID

An identifier that uniquely identifies a client connection.

Type: string

subscriptionName

The name used to identify this subscription.

Type: string

selector

Only messages with properties matching the message selector expression are delivered. A value of null or an empty string indicates that there is no message selector for the message consumer.

Type: string

noLocal

If set, inhibits the delivery of messages published by its own connection.

Type: boolean

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessages

The resource supports the following methods:

- [POST](#)

POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A JMS message selector to identify which messages to delete.

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorEndPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSize

The resource supports the following methods:

- [POST](#)

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A valid JMS message selector.

Type: string

timeout

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

state

A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

Type: int

Response Body

Contains a JSON object with a string return field.

POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A valid JMS message selector.

Type: string

timeout

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

Response Body

Contains a JSON object with a string return field.

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM
SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti
nations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsu
mption**

The resource supports the following methods:

- [POST](#)

POST

Pauses the consumption on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM
SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti
nations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertio
n**

The resource supports the following methods:

- [POST](#)

POST

Pauses the insertion on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM
SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti
nations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduct
ion**

The resource supports the following methods:

- [POST](#)

POST

Pauses the production on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM
SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti
nations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsu
mption**

The resource supports the following methods:

- [POST](#)

POST

Resumes the consumption operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM
SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti
nations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInserti
on**

The resource supports the following methods:

- [POST](#)

POST

Resumes the insertion operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM
SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti
nations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProdu
ction**

The resource supports the following methods:

- [POST](#)

POST

Resumes the production operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM
SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti
nations/{name}/durableSubscribers/{name}/destinationRuntime/sort**

The resource supports the following methods:

- [POST](#)

POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The handle of the cursor.

Type: string

start

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

Type: long

fields

The JMS header attributes on which to sort.

Type: array of string

ascending

Determines whether the sort of the corresponding fields element is in ascending or descending order.

Type: array of boolean

Response Body

Contains a JSON object with a long return field.

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM
SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti
nations/{name}/durableSubscribers/{name}/getCursorEndPosition**

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM
SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti
nations/{name}/durableSubscribers/{name}/getCursorSize**

The resource supports the following methods:

- [POST](#)

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM
SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti
nations/{name}/durableSubscribers/{name}/getCursorStartPosition**

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM
SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti
nations/{name}/durableSubscribers/{name}/getMessages**

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A valid JMS message selector.

Type: string

timeout

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

state

A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

Type: int

Response Body

Contains a JSON object with a string return field.

POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A valid JMS message selector.

Type: string

timeout

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/sort

The resource supports the following methods:

- [POST](#)

POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The handle of the cursor.

Type: string

start

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

Type: long

fields

The JMS header attributes on which to sort.

Type: array of string

ascending

Determines whether the sort of the corresponding fields element is in ascending or descending order.

Type: array of boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorSize

The resource supports the following methods:

- [POST](#)

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getMessages

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A valid JMS message selector.

Type: string

timeout

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

state

A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

Type: int

Response Body

Contains a JSON object with a string return field.

POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector

A valid JMS message selector.

Type: string

timeout

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti nations/{name}/pauseConsumption

The resource supports the following methods:

- [POST](#)

POST

Pauses the consumption on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti nations/{name}/pauseInsertion

The resource supports the following methods:

- [POST](#)

POST

Pauses the insertion on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti nations/{name}/pauseProduction

The resource supports the following methods:

- [POST](#)

POST

Pauses the production on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti nations/{name}/resumeConsumption

The resource supports the following methods:

- [POST](#)

POST

Resumes the consumption operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti nations/{name}/resumeInsertion

The resource supports the following methods:

- [POST](#)

POST

Resumes the insertion operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti nations/{name}/resumeProduction

The resource supports the following methods:

- [POST](#)

POST

Resumes the production operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM
SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti
nations/{name}/sort**

The resource supports the following methods:

- [POST](#)

POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The handle of the cursor.

Type: string

start

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

Type: long

fields

The JMS header attributes on which to sort.

Type: array of string

ascending

Determines whether the sort of the corresponding fields element is in ascending or descending order.

Type: array of boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/force Commit

The resource supports the following methods:

- [POST](#)

POST

Causes the work associated with the specified transaction branch to be committed.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

xid

An xid in string representation for a JMS transaction branch.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/force Rollback

The resource supports the following methods:

- [POST](#)

POST

Causes the work associated with the specified transaction branch to be rolled back.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

xid

An xid in string representation for a JMS transaction branch.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getC ursorEndPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorSize

The resource supports the following methods:

- [POST](#)

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getC ursorStartPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getM essages

The resource supports the following methods:

- [POST](#)

POST

Returns a set of messages that are associated with a JMS transaction branch. Note that the result set is returned to the caller in the form of a message cursor that may contain messages from several destinations on this JMS server.

The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

xid

An Xid in string representation for a JMS transaction branch.

Type: string

timeoutSeconds

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getTr ansactionStatus

The resource supports the following methods:

- [POST](#)

POST

Given an Xid this method returns the JTA status of the associated JMS transaction branch.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

xid

An Xid in string representation for a JMS transaction branch.

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logR untime

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/ensureLogOpened rel=action title=ensureLogOpened](#)

This resource's ensureLogOpened action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/flushLog rel=action title=flushLog](#)

This resource's flushLog action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/forceLogRotation rel=action title=forceLogRotation](#)

This resource's forceLogRotation action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime rel=self](#)

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logR untime/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logR untime/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logR untime/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/paus eConsumption

The resource supports the following methods:

- [POST](#)

POST

Pauses the consumption operation on all the destinations hosted by the JMSServer.

When the JMSServer is paused for consumption, all of its destination's state is marked as "consumption paused" and all the new synchronous receive operations will block until the destination is resumed and there are messages available for consumption. All the synchronous receive with blocking timeout will block until the timeout happens during the consumption paused state.

All the asynchronous consumers attached to that destination will not get any messages delivered to them while the destination in "consumption paused" state.

After a successful consumption "pause" operation, the user has to explicitly "resume" the destination to allow for any further consume operations on that destination

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/paus eInsertion

The resource supports the following methods:

- [POST](#)

POST

Pauses the appearance of any messages on all the destinations of the JMS Server, that are result of the in-flight work completion on all the destinations hosted by this JMS Server.

Definition of In-Flight work

The definitions below are based on the current implementation of WebLogic JMS subsystem.

- In-flight messages associated with Producers
 - UN-BORN MESSAGES

Messages that are produced by the producer, with "birth time" (TimeToDeliver) set in future are called un-born messages and are counted as "pending" messages in the destination statistics and are not available for consumers yet.
 - UN-COMMITTED MESSAGES

These are the messages that are produced by the producer as part of the transaction (using either user transaction or transacted session) and the transaction is still not committed or rolled back. These messages are also counted as "pending" messages in the destination statistics and are not available for consumption.
 - QUOTA BLOCKING SEND

These are the messages that are produced by the producers but are not able reach the destination because of (either message or byte or both) quota limit on the destination and the producers are willing to block for a specific period of time for the quota to be available. These messages are invisible to the system and are not counted against any of the destination statistics.
- In-flight messages associated with Consumers
 - UN-ACKNOWLEDGED (CLIENT ACK PENDING) MESSAGES

These are the messages that are successfully consumed by the clients using a "client acknowledge" session, and are awaiting acknowledgements from the clients. These are "pending messages" which will be removed from the destination/system when the acknowledgement is received.
 - UN-COMMITTED MESSAGES

These are the messages that are consumed (received) by the clients within a transaction (using either user transaction or transacted session) and the transaction is still not committed or rolled back. When the clients successfully commit the transaction the messages get removed from the system.
 - ROLLED BACK MESSAGES

These are the messages that are put back on the destination because of a successful rollback of transactional receive by the consumers. These messages might or might not be ready for consumption (re-delivered) to the clients immediately, depending on the redelivery parameters, RedeliveryDelay and/or RedeliveryDelayOverride and RedeliveryLimit configured on the associated JMSConnectionFactory and JMSDestination respectively.

If there is a redelivery delay configured, then for that "delay" duration, the messages are not available for consumption and are counted as "pending" in

the destination statistics and after the "delay" period, if the redelivery limit is not exceeded, then they are delivered (made available for consumption) on that destination and are counted as "current" messages in the destination statistics. If the redelivery limit exceeds, then those messages will be moved to the ErrorDestination, if one configured.

Another parameter that controls the availability of the rolled back messages is RedeliveryLimit.

- RECOVERED MESSAGES

These messages are similar to ROLLED BACK MESSAGES except that these messages appear on the queue because of an explicit call to session "recover" by the client.

- REDELIVERED MESSAGES

These are again similar to ROLLED BACK MESSAGES except that these messages may re-appear on the destination because of an un-successful delivery attempt to the client (consumer crash, close etc.).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseProduction

The resource supports the following methods:

- [POST](#)

POST

Pauses the new message production on all the destinations hosted by the JMS Server.

When the production is paused, it would prevent any new produce operations from both new and existing producers attached to the destinations. When the destination is "resumed from production pause", all the new message production is allowed from both new and existing producers attached to that destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeConsumption

The resource supports the following methods:

- [POST](#)

POST

Resumes the consumption operation on all the destinations hosted by the JMSSEver.

The state of the destinations shall be marked as "consumption enabled" thus allowing all the "consuming" activity to continue normally.

Invoking this API on a JMSSEver that is currently not in "consumption paused" state has no effect.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeInsertion

The resource supports the following methods:

- [POST](#)

POST

Resumes the in-flight message production operation on all the destinations hosted by the JMS Server. The state of the JMS Server shall be marked as "insertion enabled" thus allowing all the messages from in-flight work completion are allowed to appear on the destinations.

Invoking this API on a JMS Server that is currently not in "insertion paused" state has no effect.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeProduction

The resource supports the following methods:

- [POST](#)

POST

Resumes the new message production operation on all the destinations hosted by the JMSServer. The state of the JMSServer shall be marked as "production enabled" thus allowing all the new "producing" activity to continue normally. Invoking this API on a JMSServer that is currently not in "production paused" state has no effect.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/sort

The resource supports the following methods:

- [POST](#)

POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The handle of the cursor.

Type: string

start

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

Type: long

fields

The JMS header attributes on which to sort.

Type: array of string

ascending

Determines whether the sort of the corresponding fields element is in ascending or descending order.

Type: array of boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sort

The resource supports the following methods:

- [POST](#)

POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The handle of the cursor.

Type: string

start

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

Type: long

fields

The JMS header attributes on which to sort.

Type: array of string

ascending

Determines whether the sort of the corresponding fields element is in ascending or descending order.

Type: array of boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime

This resource manages a [weblogic.management.runtime.JTAPartitionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.JTAPartitionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.JTAPartitionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans](#)
rel=nonXAResourceRuntimeMBeans
This resource's nonXAResourceRuntimeMBeans collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#)
rel=parent
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime](#) **rel=self**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans](#)
rel=transactionNameRuntimeMBeans
This resource's transactionNameRuntimeMBeans collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans](#)
rel=transactionResourceRuntimeMBeans
This resource's transactionResourceRuntimeMBeans collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans

This resource manages a collection of [weblogic.management.runtime.NonXAResourceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.NonXAResourceRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.NonXAResourceRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans/{name}

This resource manages a [weblogic.management.runtime.NonXAResourceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.NonXAResourceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.NonXAResourceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans

This resource manages a collection of [weblogic.management.runtime.TransactionNameRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.TransactionNameRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.TransactionNameRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans/{name}

This resource manages a [weblogic.management.runtime.TransactionNameRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.TransactionNameRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.TransactionNameRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans/{name}](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans

This resource manages a collection of [weblogic.management.runtime.TransactionResourceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.TransactionResourceRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.TransactionResourceRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans/{name}

This resource manages a [weblogic.management.runtime.TransactionResourceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.TransactionResourceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.TransactionResourceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans/{name}](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes

This resource manages a collection of [weblogic.management.runtime.LibraryRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.LibraryRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.LibraryRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}

This resource manages a [weblogic.management.runtime.LibraryRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LibraryRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LibraryRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes](#) **rel**=referencingRuntimes

This resource's referencingRuntimes collection resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name}

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes

This resource manages a collection of [weblogic.management.runtime.MailSessionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MailSessionRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MailSessionRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes/{name}

This resource manages a [weblogic.management.runtime.MailSessionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MailSessionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MailSessionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes

This resource manages a collection of [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes/{name}

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes

This resource manages a collection of [weblogic.management.runtime.MessagingBridgeRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MessagingBridgeRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MessagingBridgeRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes/{name}

This resource manages a [weblogic.management.runtime.MessagingBridgeRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MessagingBridgeRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MessagingBridgeRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes/{name}](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes

This resource manages a collection of [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes/{name}

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionResourceMetricsRuntime

This resource manages a [weblogic.management.runtime.PartitionResourceMetricsRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.PartitionResourceMetricsRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.PartitionResourceMetricsRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionResourceMetricsRuntime](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionResourceMetricsRuntime](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime

This resource manages a [weblogic.management.runtime.PartitionWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.PartitionWorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.PartitionWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/fairShareRuntime](#) **rel=fairShareRuntime**
This resource's fairShareRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**
This resource's maxThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/minThreadsConstraintCapRuntime](#) **rel=minThreadsConstraintCapRuntime**
This resource's minThreadsConstraintCapRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/fairShareRuntime

This resource manages a [weblogic.management.runtime.PartitionFairShareRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.PartitionFairShareRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.PartitionFairShareRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/fairShareRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/fairShareRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/maxThreadsConstraintRuntime](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/maxThreadsConstraintRuntime](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/minThreadsConstraintCapRuntime

This resource manages a [weblogic.management.runtime.PartitionMinThreadsConstraintCapRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.PartitionMinThreadsConstraintCapRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.PartitionMinThreadsConstraintCapRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/minThreadsConstraintCapRuntime](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/minThreadsConstraintCapRuntime](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes

This resource manages a collection of [weblogic.management.runtime.PathServiceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.PathServiceRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.PathServiceRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes](#) [rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) [rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes](#) [rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}

This resource manages a [weblogic.management.runtime.PathServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.PathServiceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.PathServiceRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies](#) **rel=assemblies**

This resource's assemblies collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies

This resource manages a collection of [weblogic.management.runtime.PSAssemblyRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.PSAssemblyRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.PSAssemblyRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}

This resource manages a [weblogic.management.runtime.PSAssemblyRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.PSAssemblyRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.PSAssemblyRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/closeCursor](#) **rel**=action
title=closeCursor
This resource's closeCursor action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getCursorEndPosition](#)
rel=action **title**=getCursorEndPosition
This resource's getCursorEndPosition action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getCursorSize](#) **rel**=action
title=getCursorSize
This resource's getCursorSize action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getCursorStartPosition](#)
rel=action **title**=getCursorStartPosition
This resource's getCursorStartPosition action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getMapEntries](#) **rel**=action
title=getMapEntries
This resource's getMapEntries action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/remove](#) **rel**=action
title=remove
This resource's remove action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/closeCursor

The resource supports the following methods:

- [POST](#)

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getCursorPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getCursorSize

The resource supports the following methods:

- [POST](#)

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getCursorPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getMapEntries

The resource supports the following methods:

- [POST](#)

POST

Returns all entries in a persistent map's assembly.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

timeout

how many seconds till operatoin times out. Zero is an infinite timeout.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/remove

The resource supports the following methods:

- [POST](#)

POST

Remove the path service entry referenced by this object.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

the handle to the cursor

Type: string

itemHandle

the handle to a specific item in the cursor

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes

This resource manages a collection of [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}

This resource manages a [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections](#) **rel=connections**

This resource's connections collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections

This resource manages a collection of [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections/{name}

This resource manages a [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections/{name}](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes

This resource manages a collection of [weblogic.management.runtime.RequestClassRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RequestClassRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RequestClassRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes/{name}

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime

This resource manages a [weblogic.management.runtime.ResourceManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ResourceManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ResourceManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes](#) **rel=resourceRuntimes**
This resource's resourceRuntimes collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes

This resource manages a collection of [weblogic.management.runtime.ResourceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ResourceRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ResourceRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}

This resource manages a [weblogic.management.runtime.ResourceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ResourceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ResourceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/fairShareConstraintRuntime **rel**=fairShareConstraintRuntime

This resource's fairShareConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/triggerRuntimes **rel**=triggerRuntimes

This resource's triggerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/fairShareConstraintRuntime

This resource manages a [weblogic.management.runtime.FairShareConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.FairShareConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.FairShareConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/fairShareConstraintRuntimeMBean](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/fairShareConstraintRuntimeMBean](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/triggerRuntimes

This resource manages a collection of [weblogic.management.runtime.TriggerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.TriggerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.TriggerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/triggerRuntimes](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/triggerRuntimes](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/triggerRuntimes/{name}

This resource manages a [weblogic.management.runtime.TriggerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.TriggerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.TriggerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/triggerRuntimes/{name}](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/triggerRuntimes](#)
rel=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/triggerRuntimes/{name}](#)
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resume

The resource supports the following methods:

- [POST](#)

POST

Resume a suspended partition. Allow new requests. This operation transitions the partition into `RUNNING` state.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resumeResourceGroup

The resource supports the following methods:

- [POST](#)

POST

Resume suspended resource group. Allow new requests. This operation transitions the resource group into `RUNNING` state.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName

resourceGroupName

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime

This resource manages a [weblogic.management.runtime.SAFRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.SAFRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.SAFRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents](#) **rel=agents**
This resource's agents collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents

This resource manages a collection of [weblogic.management.runtime.SAFAgentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.SAFAgentRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.SAFAgentRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}

This resource manages a [weblogic.management.runtime.SAFAgentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.SAFAgentRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.SAFAgentRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/pauseForwarding **rel**=action **title**=pauseForwarding
This resource's pauseForwarding action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/pauseIncoming **rel**=action **title**=pauseIncoming
This resource's pauseIncoming action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/pauseReceiving **rel**=action **title**=pauseReceiving
This resource's pauseReceiving action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/resumeForwarding **rel**=action **title**=resumeForwarding
This resource's resumeForwarding action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/resumeIncoming **rel**=action **title**=resumeIncoming
This resource's resumeIncoming action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/resumeReceiving **rel**=action **title**=resumeReceiving
This resource's resumeReceiving action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations **rel**=conversations
This resource's conversations collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime **rel**=logRuntime
This resource's logRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents **rel**=parent
The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints **rel**=remoteEndpoints

This resource's remoteEndpoints collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations

This resource manages a collection of [weblogic.management.runtime.SAFConversationRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.SAFConversationRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.SAFConversationRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations/{name}

This resource manages a [weblogic.management.runtime.SAFConversationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.SAFConversationRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.SAFConversationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations/{name}/destroy **rel**=action
title=destroy
This resource's destroy action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations/{name} **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations/{name}/destroy

The resource supports the following methods:

- [POST](#)

POST

Destroys the conversation and purges all the messages.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened
This resource's ensureLogOpened action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime/flushLog **rel**=action **title**=flushLog
This resource's flushLog action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation
This resource's forceLogRotation action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/pauseForwarding

The resource supports the following methods:

- [POST](#)

POST

Pauses the sending agent on forwarding messages so that the agent will not forward messages but will accept new messages.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/pauseIncoming

The resource supports the following methods:

- [POST](#)

POST

Pauses the sending agent on accepting new messages.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/pauseReceiving

The resource supports the following methods:

- [POST](#)

POST

Pauses the receiving agent on receiving messages.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints

This resource manages a collection of [weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}

This resource manages a [weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/closeCursor **rel**=action **title**=closeCursor
This resource's closeCursor action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/expireAll **rel**=action **title**=expireAll
This resource's expireAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorEndPosition **rel**=action **title**=getCursorEndPosition
This resource's getCursorEndPosition action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorSize **rel**=action **title**=getCursorSize
This resource's getCursorSize action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorStartPosition **rel**=action **title**=getCursorStartPosition
This resource's getCursorStartPosition action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getMessages **rel**=action **title**=getMessages
This resource's getMessages action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/pauseForwarding **rel**=action **title**=pauseForwarding
This resource's pauseForwarding action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/pauseIncoming **rel**=action **title**=pauseIncoming
This resource's pauseIncoming action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/purge **rel**=action **title**=purge
This resource's purge action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/resumeForwarding **rel**=action **title**=resumeForwarding
This resource's resumeForwarding action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/resumeIncoming **rel**=action **title**=resumeIncoming
This resource's resumeIncoming action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/sort **rel**=action **title**=sort
This resource's sort action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name} **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/closeCursor

The resource supports the following methods:

- [POST](#)

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/expireAll

The resource supports the following methods:

- [POST](#)

POST

All pending messages for a remote destination are processed according to the policy specified by the associated Error Handling configuration and then removed.

- When selected, `expireAll` is performed asynchronously by the server.
- Oracle recommends that the remote endpoint is paused for incoming messages prior to expiring messages. When all pending messages are processed and removed, the remote endpoint can be set to resume and accept new messages.
- The state of the `expireAll` operation can be determined by the `getOperationState` method.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorSize

The resource supports the following methods:

- [POST](#)

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorStartPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getMessages

The resource supports the following methods:

- [POST](#)

POST

Queries messages on the queue according to the message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. If the cursor expires, the associated resources are released.

Roles

Admin, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

selector

A valid JMS message selector or SAF message selector.

Type: string

timeout

Specifies the amount of time the message cursor is valid. A value of 0 indicates the cursor does not expire.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/pauseForwarding

The resource supports the following methods:

- [POST](#)

POST

Pauses the forwarding of messages for a remote endpoint. The agent accepts new messages but does not forward them.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/pauseIncoming

The resource supports the following methods:

- [POST](#)

POST

Pauses a remote endpoint so that new messages are not accepted.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/purge

The resource supports the following methods:

- [POST](#)

POST

Destroys all conversations and purges all the pending messages for a remote destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/resumeForwarding

The resource supports the following methods:

- [POST](#)

POST

Resumes the forwarding of messages for the remote endpoint.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/resumeIncoming

The resource supports the following methods:

- [POST](#)

POST

Resumes a remote endpoint so that new messages are accepted.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/sort

The resource supports the following methods:

- [POST](#)

POST

Sorts the entire message result set managed by the cursor according to the SAF header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

Roles

Admin, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The handle of the cursor on which to perform the sort operation

Type: string

start

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

Type: long

fields

The SAF header attributes on which to sort.

Type: array of string

ascending

Determines whether the sort of the corresponding fields element is in ascending or descending order.

Type: array of boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/resumeForwarding

The resource supports the following methods:

- [POST](#)

POST

Resumes the sending agent for forwarding messages.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/resumeIncoming

The resource supports the following methods:

- [POST](#)

POST

Resumes the sending agent for accepting new messages.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/resumeReceiving

The resource supports the following methods:

- [POST](#)

POST

Resumes the receiving agent for receiving messages.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/shutdown

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)
- [POST](#)

POST

Gracefully shuts down the partition after handling inflight work; optionally ignores pending HTTP sessions while handling inflight work.

The following inflight work is allowed to complete before shutdown:

- Pending transaction's and TLOG checkpoint
- Pending HTTP sessions
- Pending JMS work
- Pending work in the execute queues
- RMI requests with transaction context

Further administrative calls are accepted while the partition is completing inflight work. For example, a `forceShutdown` command can be issued to quickly shutdown the partition if graceful shutdown is taking too long to complete.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

timeout

Number of seconds to wait before aborting inflight work and shutting down the partition.

Type: int

ignoreSessions

`true` indicates ignore pending HTTP sessions during inflight work handling.

Type: boolean

waitForAllSessions

`true` indicates waiting for all HTTP sessions during inflight work handling; `false` indicates waiting for non-persisted HTTP sessions only.

Type: boolean

Response Body

Contains an empty JSON object.

POST

Gracefully shuts down the partition after handling inflight work.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

POST

Gracefully shuts down the partition after handling inflight work.

This method is same to call: `shutdown(timeout, ignoreSessions, false);`

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

timeout

timeout

Type: int

ignoreSessions

ignoreSessions

Type: boolean

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/shutdownResourceGroup

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)
- [POST](#)

POST

Gracefully shuts down the resource group after handling inflight work.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName
resourceGroupName

Type: string

Response Body

Contains an empty JSON object.

POST

Gracefully shuts down the partition after handling inflight work. Optionally, ignores pending HTTP sessions while handling inflight work.

The following inflight work is allowed to complete before shutdown:

- Pending transaction's and TLOG checkpoint
- Pending HTTP sessions
- Pending JMS work
- Pending work in the execute queues
- RMI requests with transaction context

Further administrative calls are accepted while the server is completing inflight work. For example a forceShutdown command can be issued to quickly shutdown the partition if graceful shutdown takes a long time.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName
resourceGroupName

Type: string

timeout

Number of seconds to wait before aborting inflight work and shutting down the partition.

Type: int

ignoreSessions

true indicates ignore pending HTTP sessions during inflight work handling.

Type: boolean

waitForAllSessions

true indicates waiting for all HTTP sessions during inflight work handling; false indicates waiting for non-persisted HTTP sessions only.

Type: boolean

Response Body

Contains an empty JSON object.

POST

Gracefully shuts down the partition after handling inflight work.

This method is same to call: `shutdown(timeout, ignoreSessions, false);`

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName

resourceGroupName

Type: string

timeout

timeout

Type: int

ignoreSessions

ignoreSessions

Type: boolean

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/startResourceGroup

The resource supports the following methods:

- [POST](#)

POST

starts the resource group.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName

The resource group name

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/startResourceGroupInAdmin

The resource supports the following methods:

- [POST](#)

POST

Starts the resource group in ADMIN state. Applications and resources are fully available to administrators in ADMIN state. Non-admin users are denied access to applications and resources

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName

resourceGroupName

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/suspend

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends the partition. Denies new requests except by privileged users. Allows pending requests to complete. This operation transitions the partition into `ADMIN` state. Applications and resources are fully available to administrators in `ADMIN` state. Non-admin users are denied access to applications and resources

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

POST

Transitions the partition from `RUNNING` to `ADMIN` state gracefully.

Applications are in admin mode. Inflight work is completed. Applications and resources are fully available to administrators in `ADMIN` state. Non-admin users are denied access to applications and resources

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

timeout

Seconds to wait for partition to transition gracefully. The `forceSuspend()` is called after timeout.

Type: int

ignoreSessions

drop inflight HTTP sessions during graceful suspend

Type: boolean

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/suspendResourceGroup

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspends resource group. Denies new requests except by privileged users. Allows pending requests to complete. This operation transitions the partition into `ADMIN` state. Applications and resources are fully available to administrators in `ADMIN` state. Non-admin users are denied access to applications and resources

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName

resourceGroupName

Type: string

timeout

timeout

Type: int

ignoreSessions

ignoreSessions

Type: boolean

Response Body

Contains an empty JSON object.

POST

Suspends resource group. Denies new requests except by privileged users. Allows pending requests to complete. This operation transitions the partition into `ADMIN` state. Applications and resources are fully available to administrators in `ADMIN` state. Non-admin users are denied access to applications and resources

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName

resourceGroupName

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime

This resource manages a [weblogic.management.runtime.WLDFPartitionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WLDFPartitionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WLDFPartitionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime](#)
rel=WLDFPartitionAccessRuntime
This resource's WLDFPartitionAccessRuntime singleton resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionHarvesterRuntime](#)
rel=WLDFPartitionHarvesterRuntime
This resource's WLDFPartitionHarvesterRuntime singleton resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime](#)
rel=WLDFPartitionImageRuntime
This resource's WLDFPartitionImageRuntime singleton resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime](#)
rel=WLDFWatchNotificationRuntime
This resource's WLDFWatchNotificationRuntime singleton resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#)
rel=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime

This resource manages a [weblogic.management.runtime.WLDFPartitionAccessRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WLDFPartitionAccessRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WLDFPartitionAccessRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes rel=WLDFDataAccessRuntimes](#)
This resource's [WLDFDataAccessRuntimes](#) collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/lookupWLDFDataAccessRuntime rel=action title=lookupWLDFDataAccessRuntime](#)
This resource's [lookupWLDFDataAccessRuntime](#) action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes rel=dataAccessRuntimes](#)
This resource's [dataAccessRuntimes](#) collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes

This resource manages a collection of [weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes
rel=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}

This resource manages a [weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/closeCursor](#) **rel=action** **title=closeCursor**
This resource's closeCursor action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/deleteDataRecords](#) **rel=action** **title=deleteDataRecords**
This resource's deleteDataRecords action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/getDataRecordCount](#) **rel=action** **title=getDataRecordCount**
This resource's getDataRecordCount action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/hasMoreData](#) **rel=action** **title=hasMoreData**
This resource's hasMoreData action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/openCursor](#) **rel=action** **title=openCursor**
This resource's openCursor action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFFPartitionRuntime/WLDFFPartitionAccessRuntime/dataAccessRuntimes/{name}/closeCursor

The resource supports the following methods:

- [POST](#)

POST

Disposes of the cursor once the client has fetched all the records.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

cursorName

cursorName

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/deleteDataRecords

The resource supports the following methods:

- [POST](#)

POST

Delete records within the specified time range that match the specified query. If the query is null or empty, all records within the time range will be deleted.

Start and end times are specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

Not all archives support a deletion feature. If not supported, this method will throw an `UnsupportedOperationException` exception.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

startTime

Start time of the interval (inclusive)

Type: long

endTime

End time of the interval (exclusive)

Type: long

queryString

Query criterion

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFFPartitionRuntime/WLDFFPartitionAccessRuntime/dataAccessRuntimes/{name}/getDataRecordCount

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)
- [POST](#)

POST

The number of records that match the specified query and time range.

Start and end times are specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

startTime

Start time of the interval (inclusive)

Type: long

endTime

End time of the interval (exclusive)

Type: long

query

Query criterion

Type: string

Response Body

Contains a JSON object with a int return field.

POST

The number of records that match the specified query.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

query

Query expression

Type: string

Response Body

Contains a JSON object with a int return field.

POST

The number that match the specified query and record-ID range, and whose timestamp (if it is available) is earlier than the specified end time.

The end time is specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

startRecordId

Record id of the first record

Type: long

endRecordId

Look at records whose record-ids are smaller than specified endrecordId

Type: long

endTime

Look at records which were entered prior to endTime

Type: long

query

Query criterion

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/hasMoreData

The resource supports the following methods:

- [POST](#)

POST

Determines whether the specified cursor has more data to be fetched.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

cursorName

cursorName

Type: string

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/openCursor

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)
- [POST](#)
- [POST](#)
- [POST](#)
- [POST](#)

POST

Opens a cursor with the specified timeout value, in milliseconds.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

query

The query expression to filter the result set from the underlying diagnostic log.

Type: string

cursorTimeout

The timeout interval after which the cursor will become invalid if not invoked.

Type: long

Response Body

Contains a JSON object with a string return field.

POST

Opens a cursor for records that meet the specified time range and query condition. The timeout value for the cursor is also specified.

Timestamps are specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

beginTimestamp

beginTimestamp

Type: long

endTimeStamp

endTimeStamp

Type: long

query

query

Type: string

cursorTimeout

cursorTimeout

Type: long

Response Body

Contains a JSON object with a string return field.

POST

Opens a cursor on the server side for the query.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

query

The query expression to filter the result set from the underlying diagnostic log.

Type: string

Response Body

Contains a JSON object with a string return field.

POST

Opens a cursor with the specified query and time range.

Timestamps are specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

The default cursor timeout period is 5 minutes.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

beginTimestamp

beginTimestamp

Type: long

endTimestamp

endTimestamp

Type: long

query

query

Type: string

Response Body

Contains a JSON object with a string return field.

POST

Opens a cursor using the specified record-ID range, end timestamp, and query. The timeout value for the cursor is also specified.

The timestamp is specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

beginRecordId

Record id of the first record (inclusive) in the result set

Type: long

endRecordId

Record id of the last record (exclusive) in the result set

Type: long

endTimestamp

Include only those records whose timestamp is earlier than this value

Type: long

query

Query criterion

Type: string

cursorTimeout

cursorTimeout

Type: long

Response Body

Contains a JSON object with a string return field.

POST

Opens a cursor with a given query and a record-id range.

The timestamp is specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

The default cursor timeout period is 5 minutes.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

beginRecordId

Record id of the first record (inclusive) in the result set

Type: long

endRecordId

Record id of the last record (exclusive) in the result set

Type: long

endTimestamp

Include only those records whose timestamp is earlier than this value

Type: long

query

Query criterion

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/lookupWLDFDataAccessRuntime

The resource supports the following methods:

- [POST](#)

POST

An instance of a WLDFDataAccessMBean defined by its logical name. The name is constructed from the specific type of log data requested.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

logicalName

logicalName

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.WLDFDataAccessRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes

This resource manages a collection of [weblogic.management.runtime.WLDFDataAccessRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WLDFDataAccessRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WLDFDataAccessRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes rel=self](#)

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes/{name}

This resource manages a [weblogic.management.runtime.WLDFDataAccessRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WLDFDataAccessRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WLDFDataAccessRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes/{name}/closeArchive](#) **rel**=action **title**=closeArchive

This resource's closeArchive action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes/{name}](#) **rel**=canonical

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes](#) **rel**=parent

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes/{name}/closeArchive

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntim

POST

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionHarvesterRuntime

This resource manages a [weblogic.management.runtime.WLDFPartitionHarvesterRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WLDFPartitionHarvesterRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WLDFPartitionHarvesterRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionHarvesterRuntime rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionHarvesterRuntime rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime

This resource manages a [weblogic.management.runtime.WLDFPartitionImageRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WLDFPartitionImageRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WLDFPartitionImageRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/captureImage](#) **rel=action** **title=captureImage**
This resource's captureImage action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/clearCompletedImageCaptureTasks](#) **rel=action** **title=clearCompletedImageCaptureTasks**
This resource's clearCompletedImageCaptureTasks action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/purgeCapturedImages](#) **rel=action** **title=purgeCapturedImages**
This resource's purgeCapturedImages action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/resetImageLockout](#) **rel=action** **title=resetImageLockout**
This resource's resetImageLockout action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks](#) **rel=imageCaptureTasks**
This resource's imageCaptureTasks collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/captureImage

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Creates a diagnostic image in the configured destination directory.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See About Synchronous and Asynchronous Operations.

Roles

Admin

Response Body

Contains a JSON object with a `weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean` reference return field.

POST

Creates a diagnostic image in the configured destination directory.

No additional image capture requests will be accepted until the specified lockout period has expired.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See About Synchronous and Asynchronous Operations.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

lockoutMinutes

number of minutes before the next image capture request will be accepted

Type: int

Response Body

Contains a JSON object with a `weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/clearCompletedImageCaptureTasks

The resource supports the following methods:

- [POST](#)

POST

Removes all completed image capture tasks.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks

This resource manages a collection of [weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks
rel=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFFPartitionRuntime/WLDFFPartitionImageRuntime/imageCaptureTasks/{name}
}

This resource manages a [weblogic.management.runtime.WLDFFImageCreationTaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/cancel rel=action title=cancel](#)
This resource's cancel action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name} rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks rel=parent](#)
The parent resource of this resource.
- [rel=parentTask](#)
This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name} rel=self](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks rel=subTasks](#)
This resource's subTasks collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFFPartitionRuntime/WLDFFPartitionImageRuntime/imageCaptureTasks/{name}/cancel

The resource supports the following methods:

- [POST](#)

POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks

This resource manages a collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.TaskRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name} rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks rel=self](#)

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}

This resource manages a [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.TaskRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/cancel rel=action title=cancel](#)

This resource's cancel action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks rel=parent](#)

The parent resource of this resource.

- [rel=parentTask](#)

This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name} rel=self](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks rel=subTasks](#)

This resource's subTasks collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFFPartitionRuntime/WLDFFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/cancel

The resource supports the following methods:

- [POST](#)

POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks

This resource manages a collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.TaskRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}

This resource manages a [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.TaskRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}/cancel rel=action title=cancel](#)

This resource's cancel action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks rel=parent](#)

The parent resource of this resource.

- [rel=parentTask](#)

This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name} rel=self](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}/subTasks rel=subTasks](#)

This resource's subTasks collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFFPartitionRuntime/WLDFFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}/cancel

The resource supports the following methods:

- [POST](#)

POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/purgeCapturedImages

The resource supports the following methods:

- [POST](#)

POST

Delete captured images specified by the age criteria.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

age

Purge diagnostic images older than specified age specified in the format Days:Hours:Minutes. If empty or null all existing image files on disk are purged. The hours and minutes components are optional.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/resetImageLockout

The resource supports the following methods:

- [POST](#)

POST

Reset the lockout period, thus allowing image capture requests to be accepted.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime

This resource manages a [weblogic.management.runtime.WLDFWatchNotificationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WLDFWatchNotificationRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WLDFWatchNotificationRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime/WLDFWatchJMXNotificationSource](#) **rel**=WLDFWatchJMXNotificationSource

This resource's WLDFWatchJMXNotificationSource singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime/resetWatchAlarm](#) **rel**=action **title**=resetWatchAlarm

This resource's resetWatchAlarm action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime](#) **rel**=canonical

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime](#) **rel**=parent

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime/resetWatchAlarm

The resource supports the following methods:

- [POST](#)

POST

Resets a policy alarm.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

watchName

the name of the policy to reset

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime/WLDFWatchJMXNotificationSource

This resource manages a [weblogic.management.runtime.WLDFWatchNotificationSourceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WLDFWatchNotificationSourceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WLDFWatchNotificationSourceRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime/WLDFWatchJMXNotificationSource](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime/WLDFWatchJMXNotificationSource](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=capacityRuntime**
This resource's capacityRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**
This resource's maxThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**
This resource's minThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=requestClassRuntime**
This resource's requestClassRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime

This resource manages a [weblogic.management.runtime.WseeClusterFrontEndRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WseeClusterFrontEndRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WseeClusterFrontEndRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime/clusterRouting](#) **rel=clusterRouting**
This resource's clusterRouting singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime/clusterRouting

This resource manages a [weblogic.management.runtime.WseeClusterRoutingRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WseeClusterRoutingRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WseeClusterRoutingRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime/clusterRouting](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime/clusterRouting](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes

This resource manages a collection of [weblogic.management.runtime.PathServiceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.PathServiceRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.PathServiceRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/pathServiceRuntimes](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/pathServiceRuntimes](#)
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}

This resource manages a [weblogic.management.runtime.PathServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.PathServiceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.PathServiceRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies](#) **rel=assemblies**
This resource's assemblies collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/pathServiceRuntimes](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies

This resource manages a collection of [weblogic.management.runtime.PSAssemblyRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.PSAssemblyRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.PSAssemblyRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}

This resource manages a [weblogic.management.runtime.PSAssemblyRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.PSAssemblyRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.PSAssemblyRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/closeCursor **rel**=action **title**=closeCursor
This resource's closeCursor action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/getCursorEndPosition **rel**=action **title**=getCursorEndPosition
This resource's getCursorEndPosition action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/getCursorSize **rel**=action **title**=getCursorSize
This resource's getCursorSize action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/getCursorStartPosition **rel**=action **title**=getCursorStartPosition
This resource's getCursorStartPosition action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/getMapEntries **rel**=action **title**=getMapEntries
This resource's getMapEntries action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/remove **rel**=action **title**=remove
This resource's remove action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name} **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/closeCursor

The resource supports the following methods:

- [POST](#)

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/getCursorPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/getCursorSize

The resource supports the following methods:

- [POST](#)

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/getCursorStartPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/getMapEntries

The resource supports the following methods:

- [POST](#)

POST

Returns all entries in a persistent map's assembly.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

timeout

how many seconds till operatoin times out. Zero is an infinite timeout.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/remove

The resource supports the following methods:

- [POST](#)

POST

Remove the path service entry referenced by this object.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

the handle to the cursor

Type: string

itemHandle

the handle to a specific item in the cursor

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes

This resource manages a collection of [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes](#)
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}

This resource manages a [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}/connections](#) **rel=connections**
This resource's connections collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}/connections

This resource manages a collection of [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}/connections](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}/connections](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}/connections/{name}

This resource manages a [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}/connections/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}/connections](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}/connections/{name}](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/requestClassRuntimes

This resource manages a collection of [weblogic.management.runtime.RequestClassRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RequestClassRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RequestClassRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/requestClassRuntimes](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/requestClassRuntimes](#)
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/requestClassRuntimes/{name}

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/requestClassRuntimes/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/requestClassRuntimes](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/requestClassRuntimes/{name}](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/restartSSLChannels

The resource supports the following methods:

- [POST](#)

POST

Restart all SSL channels on which the server is listening. This could be necessary because of some change that the server is not aware of, for instance updates to the keystore.

Roles

Admin

Response Body

Contains an empty JSON object.

Example

Example 1 Invoke the restartSSLChannels Action

This example uses the POST method to invoke the restartSSLChannels action.

Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-H Content-Type:application/json \  
-d "{}" \  
-X POST  
http://localhost:7001/management/weblogic/latest/serverRuntime/restartSSLChannels
```

Example Response

```
HTTP/1.1 200 OK
```

```
Response Body:  
{}
```

/management/weblogic/{version}/serverRuntime/resume

The resource supports the following methods:

- [POST](#)

POST

Resume suspended server. Allow new requests. This operation transitions the server into `RUNNING` state.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/resumeResourceGroup

The resource supports the following methods:

- [POST](#)

POST

Resume suspended resource group. Allow new requests. This operation transitions the resource group into `RUNNING` state.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName

resourceGroupName

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/SAFRuntime

This resource manages a [weblogic.management.runtime.SAFRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.SAFRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.SAFRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/SAFRuntime/agents](#)
rel=agents
This resource's agents collection resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/SAFRuntime](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/SAFRuntime](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents

This resource manages a collection of [weblogic.management.runtime.SAFAgentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.SAFAgentRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.SAFAgentRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/SAFRuntime/agents](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/SAFRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/SAFRuntime/agents](#)
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}

This resource manages a [weblogic.management.runtime.SAFAgentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.SAFAgentRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.SAFAgentRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/pauseForwarding rel=action title=pauseForwarding](#)
This resource's pauseForwarding action resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/pauseIncoming rel=action title=pauseIncoming](#)
This resource's pauseIncoming action resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/pauseReceiving rel=action title=pauseReceiving](#)
This resource's pauseReceiving action resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/resumeForwarding rel=action title=resumeForwarding](#)
This resource's resumeForwarding action resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/resumeIncoming rel=action title=resumeIncoming](#)
This resource's resumeIncoming action resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/resumeReceiving rel=action title=resumeReceiving](#)
This resource's resumeReceiving action resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name} rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/conversations rel=conversations](#)
This resource's conversations collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/logRuntime rel=logRuntime](#)
This resource's logRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints rel=remoteEndpoints](#)

This resource's remoteEndpoints collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/conversations

This resource manages a collection of [weblogic.management.runtime.SAFConversationRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.SAFConversationRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.SAFConversationRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/conversations](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/conversations](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/conversations/{name}

This resource manages a [weblogic.management.runtime.SAFConversationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.SAFConversationRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.SAFConversationRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/conversations/{name}/destroy](#) **rel=action** **title=destroy**

This resource's destroy action resource.

- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/conversations/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/conversations](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/conversations/{name}](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/conversations/{name}/destroy

The resource supports the following methods:

- [POST](#)

POST

Destroys the conversation and purges all the messages.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/logRuntime

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened
This resource's ensureLogOpened action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/logRuntime/flushLog **rel**=action **title**=flushLog
This resource's flushLog action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation
This resource's forceLogRotation action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/logRuntime **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/logRuntime **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/logRuntime/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/ pauseForwarding

The resource supports the following methods:

- [POST](#)

POST

Pauses the sending agent on forwarding messages so that the agent will not forward messages but will accept new messages.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/ pauseIncoming

The resource supports the following methods:

- [POST](#)

POST

Pauses the sending agent on accepting new messages.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/ pauseReceiving

The resource supports the following methods:

- [POST](#)

POST

Pauses the receiving agent on receiving messages.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints

This resource manages a collection of [weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name} rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}

This resource manages a [weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/closeCursor **rel**=action **title**=closeCursor
This resource's closeCursor action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/expireAll **rel**=action **title**=expireAll
This resource's expireAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorEndPosition **rel**=action **title**=getCursorEndPosition
This resource's getCursorEndPosition action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorSize **rel**=action **title**=getCursorSize
This resource's getCursorSize action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorStartPosition **rel**=action **title**=getCursorStartPosition
This resource's getCursorStartPosition action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getMessages **rel**=action **title**=getMessages
This resource's getMessages action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/pauseForwarding **rel**=action **title**=pauseForwarding
This resource's pauseForwarding action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/pauseIncoming **rel**=action **title**=pauseIncoming
This resource's pauseIncoming action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/purge **rel**=action **title**=purge
This resource's purge action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/resumeForwarding **rel**=action **title**=resumeForwarding

This resource's resumeForwarding action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/resumeIncoming **rel**=action **title**=resumeIncoming

This resource's resumeIncoming action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/sort **rel**=action **title**=sort

This resource's sort action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/closeCursor

The resource supports the following methods:

- [POST](#)

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/expireAll

The resource supports the following methods:

- [POST](#)

POST

All pending messages for a remote destination are processed according to the policy specified by the associated Error Handling configuration and then removed.

- When selected, `expireAll` is performed asynchronously by the server.
- Oracle recommends that the remote endpoint is paused for incoming messages prior to expiring messages. When all pending messages are processed and removed, the remote endpoint can be set to resume and accept new messages.
- The state of the `expireAll` operation can be determined by the `getOperationState` method.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorSize

The resource supports the following methods:

- [POST](#)

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorStartPosition

The resource supports the following methods:

- [POST](#)

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getMessages

The resource supports the following methods:

- [POST](#)

POST

Queries messages on the queue according to the message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. If the cursor expires, the associated resources are released.

Roles

Admin, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

selector

A valid JMS message selector or SAF message selector.

Type: string

timeout

Specifies the amount of time the message cursor is valid. A value of 0 indicates the cursor does not expire.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/pauseForwarding

The resource supports the following methods:

- [POST](#)

POST

Pauses the forwarding of messages for a remote endpoint. The agent accepts new messages but does not forward them.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/pauseIncoming

The resource supports the following methods:

- [POST](#)

POST

Pauses a remote endpoint so that new messages are not accepted.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/purge

The resource supports the following methods:

- [POST](#)

POST

Destroys all conversations and purges all the pending messages for a remote destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/resumeForwarding

The resource supports the following methods:

- [POST](#)

POST

Resumes the forwarding of messages for the remote endpoint.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/resumeIncoming

The resource supports the following methods:

- [POST](#)

POST

Resumes a remote endpoint so that new messages are accepted.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/sort

The resource supports the following methods:

- [POST](#)

POST

Sorts the entire message result set managed by the cursor according to the SAF header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

Roles

Admin, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

cursorHandle

The handle of the cursor on which to perform the sort operation

Type: string

start

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

Type: long

fields

The SAF header attributes on which to sort.

Type: array of string

ascending

Determines whether the sort of the corresponding fields element is in ascending or descending order.

Type: array of boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/resumeForwarding

The resource supports the following methods:

- [POST](#)

POST

Resumes the sending agent for forwarding messages.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/resumelIncoming

The resource supports the following methods:

- [POST](#)

POST

Resumes the sending agent for accepting new messages.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/resumeReceiving

The resource supports the following methods:

- [POST](#)

POST

Resumes the receiving agent for receiving messages.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/search

The resource supports the following methods:

- [POST](#)

POST

Search the serverRuntime tree.

Request Body

The search request body includes the search criteria.

Response Body

The search response includes the results of the search.

/management/weblogic/{version}/serverRuntime/serverChannelRuntimes

This resource manages a collection of [weblogic.management.runtime.ServerChannelRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.ServerChannelRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.ServerChannelRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/serverChannelRuntimes](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/serverChannelRuntimes](#)
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/serverChannelRuntimes/{name}

This resource manages a [weblogic.management.runtime.ServerChannelRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ServerChannelRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ServerChannelRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/serverChannelRuntimes/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/serverChannelRuntimes](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/serverChannelRuntimes/{name}](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/serverLogRuntime

This resource manages a [weblogic.management.runtime.ServerLogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ServerLogRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ServerLogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/serverLogRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened
This resource's ensureLogOpened action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/serverLogRuntime/flushLog **rel**=action **title**=flushLog
This resource's flushLog action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/serverLogRuntime/forceLogRotation **rel**=action **title**=forceLogRotation
This resource's forceLogRotation action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/serverLogRuntime **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/serverLogRuntime **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/serverLogRuntime/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/serverLogRuntime/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/serverLogRuntime/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime

This resource manages a [weblogic.management.runtime.ServerSecurityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ServerSecurityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ServerSecurityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime](#) **rel**=defaultRealmRuntime
This resource's defaultRealmRuntime singleton resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes](#) **rel**=realmRuntimes
This resource's realmRuntimes collection resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime](#)
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime

This resource manages a [weblogic.management.runtime.RealmRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RealmRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RealmRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/authenticatorRuntimes **rel**=authenticatorRuntimes
This resource's authenticatorRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/userLockoutManagerRuntime **rel**=userLockoutManagerRuntime
This resource's userLockoutManagerRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/authenticatorRuntimes

This resource manages a collection of [weblogic.management.runtime.AuthenticatorRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.AuthenticatorRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.AuthenticatorRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/authenticatorRuntimes](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/authenticatorRuntimes](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/authenticatorRuntimes/{name}

This resource manages a [weblogic.management.runtime.AuthenticatorRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.AuthenticatorRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.AuthenticatorRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/authenticatorRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/authenticatorRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/authenticatorRuntimes/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/userLockoutManagerRuntime

This resource manages a [weblogic.management.runtime.UserLockoutManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.UserLockoutManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.UserLockoutManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/userLockoutManagerRuntime/clearLockout](#) **rel=action**
title=clearLockout
This resource's clearLockout action resource.
- [uri=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/userLockoutManagerRuntime/getLastLoginFailure](#) **rel=action**
title=getLastLoginFailure
This resource's getLastLoginFailure action resource.
- [uri=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/userLockoutManagerRuntime/getLoginFailureCount](#) **rel=action**
title=getLoginFailureCount
This resource's getLoginFailureCount action resource.
- [uri=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/userLockoutManagerRuntime/isLockedOut](#) **rel=action**
title=isLockedOut
This resource's isLockedOut action resource.
- [uri=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/userLockoutManagerRuntime](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/userLockoutManagerRuntime/clearLockout

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Unlocks a user account.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

userName

- A user name. If the user does not exist, this method returns *false*.

Type: string

Response Body

Contains an empty JSON object.

POST

Unlocks a user account.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

userName

- A user name. If the user does not exist, this method returns *false*.

Type: string

identityDomain

- The identity domain of the user. May be null.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/userLockoutManagerRuntime/getLastLoginFailure

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Returns a string that indicates the time of the last invalid login for this user.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

userName

- A user name. If the user does not exist, this method returns `false`.

Type: string

Response Body

Contains a JSON object with a long return field.

POST

Returns a string that indicates the time of the last invalid login for this user.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

userName

- A user name. If the user does not exist, this method returns `false`.

Type: string

identityDomain

- The identity domain of the user. May be null.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/userLockoutManagerRuntime/getLoginFailureCount

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Returns the current count of login failures for a specific user. This value returns to

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

userName

- A user name. If the user does not exist, this method returns `false`.

Type: string

Response Body

Contains a JSON object with a long return field.

POST

Returns the current count of login failures for a specific user. This value returns to

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

userName

- A user name. If the user does not exist, this method returns `false`.

Type: string

identityDomain

- The identity domain of the user. May be null.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/userLockoutManagerRuntime/isLockedOut

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Indicates whether a user is locked out.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

userName

- A user name. If the user does not exist, this method returns *false*.

Type: string

identityDomain

- The identity domain of the user. May be null.

Type: string

Response Body

Contains a JSON object with a boolean return field.

POST

Indicates whether a user is locked out.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

userName

- A user name. If the user does not exist, this method returns *false*.

Type: string

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes

This resource manages a collection of [weblogic.management.runtime.RealmRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.RealmRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.RealmRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntimes](#) [rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime](#) [rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntimes](#) [rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realms/{name}

This resource manages a [weblogic.management.runtime.RealmRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RealmRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RealmRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/authenticatorRuntimes](#) **rel=authenticatorRuntimes**
This resource's authenticatorRuntimes collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}](#) **rel=self**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime](#) **rel=userLockoutManagerRuntime**
This resource's userLockoutManagerRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realms/{name}/authenticatorRuntimes

This resource manages a collection of [weblogic.management.runtime.AuthenticatorRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.AuthenticatorRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.AuthenticatorRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/authenticatorRuntimes](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/authenticatorRuntimes](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realms/{name}/authenticatorRuntimes/{name}

This resource manages a [weblogic.management.runtime.AuthenticatorRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.AuthenticatorRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.AuthenticatorRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntime/{name}/authenticatorRuntime/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntime/{name}/authenticatorRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntime/{name}/authenticatorRuntime/{name} **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realms/{name}/userLockoutManagerRuntime

This resource manages a [weblogic.management.runtime.UserLockoutManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.UserLockoutManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.UserLockoutManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntime/{name}/userLockoutManagerRuntime/clearLockout **rel**=action **title**=clearLockout
This resource's clearLockout action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntime/{name}/userLockoutManagerRuntime/getLastLoginFailure **rel**=action **title**=getLastLoginFailure
This resource's getLastLoginFailure action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntime/{name}/userLockoutManagerRuntime/getLoginFailureCount **rel**=action **title**=getLoginFailureCount
This resource's getLoginFailureCount action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntime/{name}/userLockoutManagerRuntime/isLockedOut **rel**=action **title**=isLockedOut
This resource's isLockedOut action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntime/{name}/userLockoutManagerRuntime **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntime/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntime/{name}/userLockoutManagerRuntime **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realms/{name}/userLockoutManagerRuntime/clearLockout

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Unlocks a user account.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

userName

- A user name. If the user does not exist, this method returns *false*.

Type: string

Response Body

Contains an empty JSON object.

POST

Unlocks a user account.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

userName

- A user name. If the user does not exist, this method returns *false*.

Type: string

identityDomain

- The identity domain of the user. May be null.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realm Runtimes/{name}/userLockoutManagerRuntime/getLastLoginFailure

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Returns a string that indicates the time of the last invalid login for this user.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

userName

- A user name. If the user does not exist, this method returns *false*.

Type: string

Response Body

Contains a JSON object with a long return field.

POST

Returns a string that indicates the time of the last invalid login for this user.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

userName

- A user name. If the user does not exist, this method returns *false*.

Type: string

identityDomain

- The identity domain of the user. May be null.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime/getLoginFailureCount

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Returns the current count of login failures for a specific user. This value returns to

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

userName

- A user name. If the user does not exist, this method returns *false*.

Type: string

Response Body

Contains a JSON object with a long return field.

POST

Returns the current count of login failures for a specific user. This value returns to

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

userName

- A user name. If the user does not exist, this method returns *false*.

Type: string

identityDomain

- The identity domain of the user. May be null.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime/isLockedOut

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Indicates whether a user is locked out.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

userName

- A user name. If the user does not exist, this method returns *false*.

Type: string

identityDomain

- The identity domain of the user. May be null.

Type: string

Response Body

Contains a JSON object with a boolean return field.

POST

Indicates whether a user is locked out.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

userName

- A user name. If the user does not exist, this method returns *false*.

Type: string

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/shutdown

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)
- [POST](#)

POST

Gracefully shuts down the server after handling inflight work; optionally ignores pending HTTP sessions while handling inflight work.

The following inflight work is allowed to complete before shutdown:

- Pending transaction's and TLOG checkpoint
- Pending HTTP sessions
- Pending JMS work
- Pending work in the execute queues
- RMI requests with transaction context

Further administrative calls are accepted while the server is completing inflight work. For example a `forceShutdown` command can be issued to quickly shutdown the server if graceful shutdown takes a long time.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

timeout

Number of seconds to wait before aborting inflight work and shutting down the server.

Type: int

ignoreSessions

`true` indicates ignore pending HTTP sessions during inflight work handling.

Type: boolean

waitForAllSessions

`true` indicates waiting for all HTTP sessions during inflight work handling; `false` indicates waiting for non-persisted HTTP sessions only.

Type: boolean

Response Body

Contains an empty JSON object.

POST

Gracefully shuts down the server after handling inflight work.

POST

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

POST

Gracefully shuts down the server after handling inflight work.

This method is the same as calling: `shutdown(timeout, ignoreSessions, false);`

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

timeout

timeout

Type: int

ignoreSessions

ignoreSessions

Type: boolean

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/shutdownResourceGroup

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)
- [POST](#)

POST

Gracefully shuts down the resource group after handling inflight work.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName
resourceGroupName

Type: string

Response Body

Contains an empty JSON object.

POST

Gracefully shuts down the resource group after handling inflight work; optionally ignores pending HTTP sessions while handling inflight work.

The following inflight work is allowed to complete before shutdown:

- Pending transaction's and TLOG checkpoint
- Pending HTTP sessions
- Pending JMS work
- Pending work in the execute queues
- RMI requests with transaction context

Further administrative calls are accepted while the server is completing inflight work. For example a forceShutdown command can be issued to quickly shutdown the partition if graceful shutdown takes a long time.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName
resourceGroupName

Type: string

timeout

Number of seconds to wait before aborting inflight work and shutting down the partition.

Type: int

ignoreSessions

true indicates ignore pending HTTP sessions during inflight work handling.

Type: boolean

waitForAllSessions

true indicates waiting for all HTTP sessions during inflight work handling; false indicates waiting for non-persisted HTTP sessions only.

Type: boolean

Response Body

Contains an empty JSON object.

POST

Gracefully shuts down the resource group after handling inflight work.

This method is same to call: `shutdown(timeout, ignoreSessions, false);`

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName

resourceGroupName

Type: string

timeout

timeout

Type: int

ignoreSessions

ignoreSessions

Type: boolean

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/singleSignOnServicesRuntime

This resource manages a [weblogic.management.runtime.SingleSignOnServicesRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.SingleSignOnServicesRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.SingleSignOnServicesRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/singleSignOnServicesRuntime/publish rel=action title=publish](#)
This resource's publish action resource.
- [uri=/management/weblogic/{version}/serverRuntime/singleSignOnServicesRuntime rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/singleSignOnServicesRuntime rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/singleSignOnServicesRuntime/publish

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Publishes SAML 2.0 meta-data for Web Browser SSO Profile

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

fileName

Name of file to create; will silently overwrite existing file, if present

Type: string

Response Body

Contains an empty JSON object.

POST

Publishes SAML 2.0 meta-data for Web Browser SSO Profile

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

fileName

Name of file to create

Type: string

prohibitOverwrite

If true, prohibits overwrite if the file already exists

Type: boolean

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/SNMPAgentRuntime

This resource manages a [weblogic.management.runtime.SNMPAgentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.SNMPAgentRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.SNMPAgentRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/SNMPAgentRuntime/invalidateLocalizedKeyCache](#) **rel**=action **title**=invalidateLocalizedKeyCache
This resource's invalidateLocalizedKeyCache action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/SNMPAgentRuntime/outputCustomMBeansMIBModule](#) **rel**=action **title**=outputCustomMBeansMIBModule
This resource's outputCustomMBeansMIBModule action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/SNMPAgentRuntime](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/SNMPAgentRuntime](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/SNMPAgentRuntime/invalidateLocalizedKeyCache

The resource supports the following methods:

- [POST](#)

POST

Immediately invalidates the cached security keys for the specified WebLogic Server user.

An SNMP security key is an encrypted version of an SNMP agent's engine ID and an authentication password or privacy password. WebLogic Server generates one security key for each entry that you create in the SNMP credential map. When a WebLogic Server SNMP agent receives an SNMPv3 request, it compares the key that is in the request with its WebLogic Server keys. If it finds a match, it processes the request. The SNMP agent also encodes these keys in its responses and notifications. (You configure which keys are encoded when you create a trap destination.)

Instead of regenerating the keys for each SNMPv3 communication, WebLogic Server caches the keys. To make sure that the cache contains the latest set of SNMP credentials, WebLogic Server periodically invalidates the cache. After the cache is invalidated, the next time an SNMP agent requests credentials, WebLogic Server regenerates the cache.

Note that making a change to the credential map does not automatically update the cache. Instead, the cache is updated only after it has been invalidated.

Instead of waiting for WebLogic Server to invalidate the cached entry for a key, you can invalidate it immediately.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

username

Name of the user

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/SNMPAgentRuntime/outputCustomMBeansMIBModule

The resource supports the following methods:

- [POST](#)

POST

Returns WebLogic Server's MIB module for custom MBeans as a `java.lang.String`. You can save the `String` to a file and then load the file into a MIB browser.

When you register custom MBeans in the WebLogic Server Runtime MBean Server, WebLogic Server adds entries to a runtime MIB module that it maintains for custom MBeans. For each custom MBean type, WebLogic Server adds a table to the MIB module. For each instance of the custom MBean, it adds a table row. While WebLogic Server does not persist the MIB module as a file or other data structure, the OIDs in the module remain constant across server sessions.

Roles

Admin

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/startPartition

The resource supports the following methods:

- [POST](#)

POST

starts the partition.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

partitionName

The resource group name

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/startPartitionInAdmin

The resource supports the following methods:

- [POST](#)

POST

starts the Partition in ADMIN state. Applications and resources are fully available to administrators in ADMIN state. But non-admin users are denied access to applications and resources

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

partitionName

partitionName

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/startResourceGroup

The resource supports the following methods:

- [POST](#)

POST

starts the resource group.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

resourceGroupName
The resource group name
Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/startResourceGroupInAdmin

The resource supports the following methods:

- [POST](#)

POST

starts the resource group in ADMIN state. Applications and resources are fully available to administrators in ADMIN state. But non-admin users are denied access to applications and resources

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

resourceGroupName

resourceGroupName

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/suspend

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspend server. Deny new requests (except by privileged users). Allow pending requests to complete. This operation transitions the server into ADMIN state. Applications and resources are fully available to administrators in ADMIN state. But non-admin users are denied access to applications and resources

Roles

Admin

Response Body

Contains an empty JSON object.

POST

Transitions the server from RUNNING to ADMIN state gracefully.

Applications are in admin mode. Inflight work is completed. Applications and resources are fully available to administrators in ADMIN state. But non-admin users are denied access to applications and resources

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

timeout

Seconds to wait for server to transition gracefully. The server calls forceSuspend() after timeout.

Type: int

ignoreSessions

drop inflight HTTP sessions during graceful suspend

Type: boolean

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/suspendResourceGroup

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Suspend resource group. Deny new requests (except by privileged users). Allow pending requests to complete. This operation transitions the partition into `ADMIN` state. Applications and resources are fully available to administrators in `ADMIN` state. But non-admin users are denied access to applications and resources

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

resourceGroupName

resourceGroupName

Type: string

timeout

timeout

Type: int

ignoreSessions

ignoreSessions

Type: boolean

Response Body

Contains an empty JSON object.

POST

Suspend resource group. Deny new requests (except by privileged users). Allow pending requests to complete. This operation transitions the partition into `ADMIN` state. Applications and resources are fully available to administrators in `ADMIN` state. But non-admin users are denied access to applications and resources

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

resourceGroupName

resourceGroupName

POST

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/threadPoolRuntime

This resource manages a [weblogic.management.runtime.ThreadPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.ThreadPoolRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.ThreadPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/threadPoolRuntime](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/threadPoolRuntime](#)
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/timerRuntime

This resource manages a [weblogic.management.runtime.TimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.TimerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.TimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/timerRuntime](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/timerRuntime](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/WANReplicationRuntime

This resource manages a [weblogic.management.runtime.WANReplicationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WANReplicationRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WANReplicationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/WANReplicationRuntime/cleanupExpiredSessionsInTheDatabase](#) **rel**=action
title=cleanupExpiredSessionsInTheDatabase

This resource's [cleanupExpiredSessionsInTheDatabase](#) action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/WANReplicationRuntime](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/WANReplicationRuntime](#)
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/WANReplicationRuntime/cleanupExpiredSessionsInTheDatabase

The resource supports the following methods:

- [POST](#)

POST

Clean up expired sessions in the database

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/webServerRuntimes

This resource manages a collection of [weblogic.management.runtime.WebServerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WebServerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WebServerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/webServerRuntimes](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/webServerRuntimes](#)
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WebServerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WebServerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WebServerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}/logRuntime](#) **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/webServerRuntimes](#)
rel=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}](#)
rel=self

This resource.

/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}/logRuntime

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened
This resource's ensureLogOpened action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}/logRuntime/flushLog **rel**=action **title**=flushLog
This resource's flushLog action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation
This resource's forceLogRotation action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}/logRuntime **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name} **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}/logRuntime **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- [POST](#)

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}/logRuntime/flushLog

The resource supports the following methods:

- [POST](#)

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- [POST](#)

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/WLDFRuntime

This resource manages a [weblogic.management.runtime.WLDFRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WLDFRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WLDFRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime rel=WLDFAccessRuntime](#)
This resource's WLDFAccessRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFArchiveRuntimes rel=WLDFArchiveRuntimes](#)
This resource's WLDFArchiveRuntimes collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime rel=WLDFControlRuntime](#)
This resource's WLDFControlRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime rel=WLDFDebugPatchesRuntime](#)
This resource's WLDFDebugPatchesRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFHarvesterRuntime rel=WLDFHarvesterRuntime](#)
This resource's WLDFHarvesterRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime rel=WLDFImageRuntime](#)
This resource's WLDFImageRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentationRuntimes rel=WLDFInstrumentationRuntimes](#)
This resource's WLDFInstrumentationRuntimes collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFWatchNotificationRuntime rel=WLDFWatchNotificationRuntime](#)
This resource's WLDFWatchNotificationRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime

This resource manages a [weblogic.management.runtime.WLDFAccessRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WLDFAccessRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WLDFAccessRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/WLDFDataAccessRuntimes](#) **rel**=WLDFDataAccessRuntimes
This resource's WLDFDataAccessRuntimes collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/lookupWLDFDataAccessRuntime](#) **rel**=action
title=lookupWLDFDataAccessRuntime
This resource's lookupWLDFDataAccessRuntime action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime](#) **rel**=canonical
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes](#) **rel**=dataAccessRuntimes
This resource's dataAccessRuntimes collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime](#) **rel**=parent
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes

This resource manages a collection of [weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}

This resource manages a [weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/closeCursor](#) **rel**=action
title=closeCursor
This resource's closeCursor action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/deleteDataRecords](#) **rel**=action
title=deleteDataRecords
This resource's deleteDataRecords action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/getDataRecordCount](#) **rel**=action
title=getDataRecordCount
This resource's getDataRecordCount action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/hasMoreData](#) **rel**=action
title=hasMoreData
This resource's hasMoreData action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/openCursor](#) **rel**=action
title=openCursor
This resource's openCursor action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/closeCursor

The resource supports the following methods:

- [POST](#)

POST

Disposes of the cursor once the client has fetched all the records.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

cursorName

cursorName

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/deleteDataRecords

The resource supports the following methods:

- [POST](#)

POST

Delete records within the specified time range that match the specified query. If the query is null or empty, all records within the time range will be deleted.

Start and end times are specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

Not all archives support a deletion feature. If not supported, this method will throw an `UnsupportedOperationException` exception.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

startTime

Start time of the interval (inclusive)

Type: long

endTime

End time of the interval (exclusive)

Type: long

queryString

Query criterion

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/getDataRecordCount

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)
- [POST](#)

POST

The number of records that match the specified query and time range.

Start and end times are specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

startTime

Start time of the interval (inclusive)

Type: long

endTime

End time of the interval (exclusive)

Type: long

query

Query criterion

Type: string

Response Body

Contains a JSON object with a int return field.

POST

The number of records that match the specified query.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

query

Query expression

Type: string

Response Body

Contains a JSON object with a int return field.

POST

The number that match the specified query and record-ID range, and whose timestamp (if it is available) is earlier than the specified end time.

The end time is specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

startRecordId

Record id of the first record

Type: long

endRecordId

Look at records whose record-ids are smaller than specified endrecordId

Type: long

endTime

Look at records which were entered prior to endTime

Type: long

query

Query criterion

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/hasMoreData

The resource supports the following methods:

- [POST](#)

POST

Determines whether the specified cursor has more data to be fetched.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

cursorName

cursorName

Type: string

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/openCursor

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)
- [POST](#)
- [POST](#)
- [POST](#)
- [POST](#)

POST

Opens a cursor with the specified timeout value, in milliseconds.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

query

The query expression to filter the result set from the underlying diagnostic log.

Type: string

cursorTimeout

The timeout interval after which the cursor will become invalid if not invoked.

Type: long

Response Body

Contains a JSON object with a string return field.

POST

Opens a cursor for records that meet the specified time range and query condition. The timeout value for the cursor is also specified.

Timestamps are specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

beginTimestamp

beginTimestamp

Type: long

endTimestamp

endTimestamp

Type: long

query

query

Type: string

cursorTimeout

cursorTimeout

Type: long

Response Body

Contains a JSON object with a string return field.

POST

Opens a cursor on the server side for the query.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

query

The query expression to filter the result set from the underlying diagnostic log.

Type: string

Response Body

Contains a JSON object with a string return field.

POST

Opens a cursor with the specified query and time range.

Timestamps are specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

The default cursor timeout period is 5 minutes.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

beginTimestamp

beginTimestamp

Type: long

endTimestamp

endTimestamp

Type: long

query

query

Type: string

Response Body

Contains a JSON object with a string return field.

POST

Opens a cursor using the specified record-ID range, end timestamp, and query. The timeout value for the cursor is also specified.

The timestamp is specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

beginRecordId

Record id of the first record (inclusive) in the result set

Type: long

endRecordId

Record id of the last record (exclusive) in the result set

Type: long

endTimestamp

Include only those records whose timestamp is earlier than this value

Type: long

query

Query criterion

Type: string

cursorTimeout

cursorTimeout

Type: long

Response Body

Contains a JSON object with a string return field.

POST

Opens a cursor with a given query and a record-id range.

The timestamp is specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

The default cursor timeout period is 5 minutes.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

beginRecordId

Record id of the first record (inclusive) in the result set

Type: long

endRecordId

Record id of the last record (exclusive) in the result set

Type: long

endTimestamp

Include only those records whose timestamp is earlier than this value

Type: long

query

Query criterion

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/lookupWLDFDataAccessRuntime

The resource supports the following methods:

- [POST](#)

POST

An instance of a `WLDFDataAccessMBean` defined by its logical name. The name is constructed from the specific type of log data requested.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

logicalName

logicalName

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.WLDFDataAccessRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/WLDFDataAccessRuntimes

This resource manages a collection of [weblogic.management.runtime.WLDFDataAccessRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WLDFDataAccessRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WLDFDataAccessRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/WLDFDataAccessRuntimes](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/WLDFDataAccessRuntimes](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/WLDFDataAccessRuntimes/{name}

This resource manages a [weblogic.management.runtime.WLDFDataAccessRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WLDFDataAccessRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WLDFDataAccessRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/WLDFDataAccessRuntimes/{name}/closeArchive](#) **rel**=action
title=closeArchive

This resource's closeArchive action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/WLDFDataAccessRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/WLDFDataAccessRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/WLDFDataAccessRuntimes/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/WLDFDataAccessRuntimes/{name}/closeArchive

The resource supports the following methods:

- [POST](#)

POST

POST

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFArchiveRuntimes

This resource manages a collection of [weblogic.management.runtime.WLDFArchiveRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WLDFArchiveRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WLDFArchiveRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFArchiveRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFArchiveRuntimes](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFArchiveRuntimes/{name}

This resource manages a [weblogic.management.runtime.WLDFArchiveRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WLDFArchiveRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WLDFArchiveRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFArchiveRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFArchiveRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFArchiveRuntimes/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime

This resource manages a [weblogic.management.runtime.WLDFControlRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WLDFControlRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WLDFControlRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime rel=self](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls rel=systemResourceControls](#)
This resource's systemResourceControls collection resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls

This resource manages a collection of [weblogic.management.runtime.WLDFSystemResourceControlRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WLDFSystemResourceControlRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WLDFSystemResourceControlRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}

This resource manages a [weblogic.management.runtime.WLDFSystemResourceControlRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WLDFSystemResourceControlRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WLDFSystemResourceControlRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}/harvesterManagerRuntime **rel**=harvesterManagerRuntime

This resource's harvesterManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}/watchManagerRuntime **rel**=watchManagerRuntime

This resource's watchManagerRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}/harvesterManagerRuntime

This resource manages a [weblogic.management.runtime.WLDFHarvesterManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WLDFHarvesterManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WLDFHarvesterManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}/harvesterManagerRuntime](#)
rel=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}/harvesterManagerRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}/watchManagerRuntime

This resource manages a [weblogic.management.runtime.WLDFWatchManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WLDFWatchManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WLDFWatchManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}/watchManagerRuntime/resetWatchAlarm **rel**=action **title**=resetWatchAlarm

This resource's resetWatchAlarm action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}/watchManagerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}/watchManagerRuntime **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}/watchManagerRuntime/resetWatchAlarm

The resource supports the following methods:

- [POST](#)

POST

Resets a policy alarm.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

watchName

the name of the policy to reset

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime

This resource manages a [weblogic.management.runtime.WLDFDebugPatchesRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WLDFDebugPatchesRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WLDFDebugPatchesRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/activateDebugPatch **rel**=action **title**=activateDebugPatch
This resource's activateDebugPatch action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/clearDebugPatchTasks **rel**=action **title**=clearDebugPatchTasks
This resource's clearDebugPatchTasks action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/deactivateAllDebugPatches **rel**=action **title**=deactivateAllDebugPatches
This resource's deactivateAllDebugPatches action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/deactivateDebugPatches **rel**=action **title**=deactivateDebugPatches
This resource's deactivateDebugPatches action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/showDebugPatchInfo **rel**=action **title**=showDebugPatchInfo
This resource's showDebugPatchInfo action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks **rel**=debugPatchTasks
This resource's debugPatchTasks collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/activateDebugPatch

The resource supports the following methods:

- [POST](#)

POST

Activate specified debug patch, optionally within the scope of given application and module

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

patch

Patch to be activated

Type: string

application

If not null, limit the scope of activation to specified application. If null, activate at system level.

Type: string

module

If not null and application is specified, limit the scope of activation within specified module within the application.

Type: string

partitionName

partitionName

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.WLDFDebugPatchTaskRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/clearDebugPatchTasks

The resource supports the following methods:

- [POST](#)

POST

Clear all completed debug patch activation/deactivation tasks

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/deactivateAllDebugPatches

The resource supports the following methods:

- [POST](#)

POST

Deactivate all active debug patches

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin

Response Body

Contains a JSON object with a `weblogic.management.runtime.WLDFDebugPatchTaskRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/deactivateDebugPatches

The resource supports the following methods:

- [POST](#)

POST

Deactivate specified patches within the scope of given application and module.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

patches

Comma separated list of patches to be deactivated

Type: string

application

If not null, deactivate given patches within the scope of specified application. If null, deactivate at system level.

Type: string

module

If not null and application is specified, limit the scope of de-activation to specified module.

Type: string

partitionName

partitionName

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.WLDFDebugPatchTaskRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks

This resource manages a collection of [weblogic.management.runtime.WLDFDebugPatchTaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WLDFDebugPatchTaskRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WLDFDebugPatchTaskRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}

This resource manages a [weblogic.management.runtime.WLDFDebugPatchTaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WLDFDebugPatchTaskRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WLDFDebugPatchTaskRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/cancel](#) **rel=action** **title=cancel**
This resource's cancel action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks](#) **rel=parent**
The parent resource of this resource.
- **rel=parentTask**
This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}](#) **rel=self**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks](#) **rel=subTasks**
This resource's subTasks collection resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/cancel

The resource supports the following methods:

- [POST](#)

POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks

This resource manages a collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.TaskRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}

This resource manages a [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.TaskRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/cancel **rel**=action
title=cancel
This resource's cancel action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks **rel**=parent
The parent resource of this resource.
- **rel**=parentTask
This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/subTasks **rel**=subTasks
This resource's subTasks collection resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/cancel

The resource supports the following methods:

- [POST](#)

POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/subTasks

This resource manages a collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.TaskRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/subTasks](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/subTasks](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/subTasks/{name}

This resource manages a [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.TaskRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/subTasks/{name}/cancel **rel**=action **title**=cancel

This resource's cancel action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/subTasks/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/subTasks **rel**=parent

The parent resource of this resource.

- **rel**=parentTask

This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/subTasks/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/subTasks/{name}/subTasks **rel**=subTasks

This resource's subTasks collection resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/subTasks/{name}/cancel

The resource supports the following methods:

- [POST](#)

POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/showDebugPatchInfo

The resource supports the following methods:

- [POST](#)

POST

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

patch

Debug patch

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFHarvesterRuntime

This resource manages a [weblogic.management.runtime.WLDFHarvesterRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WLDFHarvesterRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WLDFHarvesterRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFHarvesterRuntime](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFHarvesterRuntime](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime

This resource manages a [weblogic.management.runtime.WLDFImageRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WLDFImageRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WLDFImageRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/captureImage **rel**=action **title**=captureImage
This resource's captureImage action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/clearCompletedImageCaptureTasks **rel**=action **title**=clearCompletedImageCaptureTasks
This resource's clearCompletedImageCaptureTasks action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/purgeCapturedImages **rel**=action **title**=purgeCapturedImages
This resource's purgeCapturedImages action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/resetImageLockout **rel**=action **title**=resetImageLockout
This resource's resetImageLockout action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks **rel**=imageCaptureTasks
This resource's imageCaptureTasks collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/captureImage

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)
- [POST](#)
- [POST](#)

POST

Creates a diagnostic image in the specified destination directory, which can be specified either as a relative or absolute pathname. If relative, the path is relative to the server's `logs` directory.

If the directory does not exist, it is created. If the directory exists, it must be writable in order for image creation to proceed.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

destination

absolute or relative directory path

Type: string

Response Body

Contains a JSON object with a `weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean` reference return field.

POST

Creates a diagnostic image in the configured destination directory.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

Roles

Admin

Response Body

Contains a JSON object with a `weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean` reference return field.

POST

Creates a diagnostic image in the specified destination directory, which can be specified either as a relative or absolute pathname. If relative, the path is relative to the server's logs directory.

If the directory does not exist, it is created. If the directory exists, it must be writable in order for image creation to proceed.

No additional image capture requests will be accepted until the specified lockout period has expired.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See About Synchronous and Asynchronous Operations.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

destination

absolute or relative path

Type: string

lockoutMinutes

number of minutes before next image capture request will be accepted

Type: int

Response Body

Contains a JSON object with a `weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean` reference return field.

POST

Creates a diagnostic image in the configured destination directory.

No additional image capture requests will be accepted until the specified lockout period has expired.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See About Synchronous and Asynchronous Operations.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

lockoutMinutes

number of minutes before the next image capture request will be accepted

Type: int

Response Body

Contains a JSON object with a `weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean` reference return field.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/clearCompletedImageCaptureTasks

The resource supports the following methods:

- [POST](#)

POST

POST

Removes all completed image capture tasks.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks

This resource manages a collection of [weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks](#) **rel=canonical**
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime](#) **rel=parent**
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks](#) **rel=self**
This resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}

This resource manages a [weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/cancel](#) **rel**=action **title**=cancel
This resource's cancel action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks](#) **rel**=parent
The parent resource of this resource.
- **rel**=parentTask
This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks](#) **rel**=subTasks
This resource's subTasks collection resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/cancel

The resource supports the following methods:

- [POST](#)

POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks

This resource manages a collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.TaskRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}

This resource manages a [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.TaskRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/cancel](#) **rel**=action
title=cancel
This resource's cancel action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks](#) **rel**=parent
The parent resource of this resource.
- **rel**=parentTask
This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}](#) **rel**=self
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks](#) **rel**=subTasks
This resource's subTasks collection resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/cancel

The resource supports the following methods:

- [POST](#)

POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks

This resource manages a collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.TaskRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}

This resource manages a [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.TaskRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}/cancel **rel**=action **title**=cancel
This resource's cancel action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name} **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks **rel**=parent
The parent resource of this resource.
- **rel**=parentTask
This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name} **rel**=self
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}/subTasks **rel**=subTasks
This resource's subTasks collection resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}/cancel

The resource supports the following methods:

- [POST](#)

POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/purgeCapturedImages

The resource supports the following methods:

- [POST](#)

POST

Delete captured images specified by the age criteria.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

age

Purge diagnostic images older than specified age specified in the format Days:Hours:Minutes. If empty or null all existing image files on disk are purged. The hours and minutes components are optional.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/resetImageLockout

The resource supports the following methods:

- [POST](#)

POST

Reset the lockout period, thus allowing image capture requests to be accepted.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentationRuntimes

This resource manages a collection of [weblogic.management.runtime.WLDFInstrumentationRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WLDFInstrumentationRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WLDFInstrumentationRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentationRuntimes](#) [rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime](#) [rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentationRuntimes](#) [rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentationRuntimes/{name}

This resource manages a [weblogic.management.runtime.WLDFInstrumentationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WLDFInstrumentationRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WLDFInstrumentationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentationRuntimes/{name}/resetMethodInvocationStatisticsData](#) **rel**=action **title**=resetMethodInvocationStatisticsData

This resource's resetMethodInvocationStatisticsData action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentationRuntimes/{name}/resetMethodMemoryAllocationStatisticsData](#) **rel**=action **title**=resetMethodMemoryAllocationStatisticsData

This resource's resetMethodMemoryAllocationStatisticsData action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentationRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentationRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentationRuntimes/{name}](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentationRuntimes/{name}/resetMethodInvocationStatisticsData

The resource supports the following methods:

- [POST](#)

POST

Resets the nested MethodInvocationStatistics structure and reinitializes the underlying metrics.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

expr

Expression conforming to the harvester syntax for the MethodInvocationStatistics property without the attribute name prefix.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentationRuntimes/{name}/resetMethodMemoryAllocationStatisticsData

The resource supports the following methods:

- [POST](#)

POST

Resets the nested MethodMemoryAllocationStatistics structure and reinitializes the underlying metrics.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

expr

Expression conforming to the harvester syntax for the MethodMemoryAllocationStatistics property without the attribute name prefix.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFWatchNotificationRuntime

This resource manages a [weblogic.management.runtime.WLDFWatchNotificationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WLDFWatchNotificationRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WLDFWatchNotificationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFWatchNotificationRuntime/WLDFWatchJMXNotificationSource](#)
rel=WLDFWatchJMXNotificationSource

This resource's WLDFWatchJMXNotificationSource singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFWatchNotificationRuntime/resetWatchAlarm](#) **rel**=action **title**=resetWatchAlarm

This resource's resetWatchAlarm action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFWatchNotificationRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime](#)
rel=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFWatchNotificationRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFWatchNotificationRuntime/resetWatchAlarm

The resource supports the following methods:

- [POST](#)

POST

Resets a policy alarm.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

watchName

the name of the policy to reset

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFWatchNotificationRuntime/WLDFWatchJMXNotificationSource

This resource manages a [weblogic.management.runtime.WLDFWatchNotificationSourceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WLDFWatchNotificationSourceRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WLDFWatchNotificationSourceRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFWatchNotificationRuntime/WLDFWatchJMXNotificationSource](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFWatchNotificationRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFWatchNotificationRuntime/WLDFWatchJMXNotificationSource](#) **rel=self**

This resource.

/management/weblogic/{version}/serverRuntime/workManagerRuntimes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes](#)
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}](#) **rel**=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=capacityRuntime
This resource's capacityRuntime singleton resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=maxThreadsConstraintRuntime
This resource's maxThreadsConstraintRuntime singleton resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=minThreadsConstraintRuntime
This resource's minThreadsConstraintRuntime singleton resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/requestClassRuntime](#) **rel**=requestClassRuntime
This resource's requestClassRuntime singleton resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}](#) **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/requestClassRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/requestClassRuntime](#) **rel**=self

This resource.

/management/weblogic/{version}/serverRuntime/wseeClusterFrontEndRuntime

This resource manages a [weblogic.management.runtime.WseeClusterFrontEndRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WseeClusterFrontEndRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WseeClusterFrontEndRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/wseeClusterFrontEndRuntime rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/wseeClusterFrontEndRuntime/clusterRouting rel=clusterRouting](#)
This resource's clusterRouting singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/wseeClusterFrontEndRuntime rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/wseeClusterFrontEndRuntime/clusterRouting

This resource manages a [weblogic.management.runtime.WseeClusterRoutingRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WseeClusterRoutingRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WseeClusterRoutingRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/wseeClusterFrontEndRuntime/clusterRouting rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/wseeClusterFrontEndRuntime rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/wseeClusterFrontEndRuntime/clusterRouting rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/wseeWsruntime

This resource manages a [weblogic.management.runtime.WseeWsruntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WseeWsruntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WseeWsruntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/wseeWsruntime](#)
rel=canonical
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/wseeWsruntime](#)
rel=self
This resource.

/management/weblogic/{version}/serverRuntime/WTCRuntime

This resource manages a [weblogic.management.runtime.WTCRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WTCRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WTCRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean](#) [rel=WTCStatisticsRuntimeMBean](#)
This resource's [WTCStatisticsRuntimeMBean](#) singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/WTCRuntime/getServiceStatus](#) [rel=action](#) [title=getServiceStatus](#)
This resource's [getServiceStatus](#) action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WTCRuntime/resumeService](#) [rel=action](#) [title=resumeService](#)
This resource's [resumeService](#) action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WTCRuntime/startConnection](#) [rel=action](#) [title=startConnection](#)
This resource's [startConnection](#) action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WTCRuntime/stopConnection](#) [rel=action](#) [title=stopConnection](#)
This resource's [stopConnection](#) action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WTCRuntime/suspendService](#) [rel=action](#) [title=suspendService](#)
This resource's [suspendService](#) action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WTCRuntime](#) [rel=canonical](#)
This resource.
- [uri=/management/weblogic/{version}/serverRuntime](#) [rel=parent](#)
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/WTCRuntime](#) [rel=self](#)
This resource.

/management/weblogic/{version}/serverRuntime/WTCRuntime/getServiceStatus

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)
- [POST](#)
- [POST](#)
- [POST](#)

POST

Returns status of a specific imported service provided by the specified local access point and remote access point list. The service name is the resource name of the WTCImport and WTCEXport. The remote access point list is a comma separated list; for instance, "TDOM1,TDOM2".

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

localAccessPoint

The local access point name.

Type: string

remoteAccessPointList

The comma separated remote access point names.

Type: string

svcName

The resource name of imported or exported service/resource name.

Type: string

Response Body

Contains a JSON object with a int return field.

POST

Returns status of the Import and Export service/resource configured for the targeted WTC server with the specified service name. This service name is the resource name of the WTCImport and WTCEXport. As long as one of the directions is available the returned status will be available.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

svcName

The resource name of imported or exported service/resource name.

Type: string

Response Body

Contains a JSON object with a int return field.

POST

Returns status of the imported or exported service of the specified service name and provided by the specified local access point. The service name is the resource name of the WTCImport and WTCEXport.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

localAccessPoint

The local access point name.

Type: string

svcName

The resource name of imported or exported service/resource name.

Type: string

isImport

The type of service indicate whether it is import or export. If true, then it is imported service, if false it is targeted for exported service.

Type: boolean

Response Body

Contains a JSON object with a int return field.

POST

Returns status of the Import or Export service/resource configured for the targeted WTC server with the specified service name. This service name is the resource name of the WTCImport and WTCEXport.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

svcName

The resource name of imported or exported service/resource name.

Type: string

isImport

The type of service indicate whether it is import or export. If true, then it is imported service, if false it is targeted for exported service.

Type: boolean

Response Body

Contains a JSON object with a int return field.

POST

Returns status of the imported and exported service of the specified service name and provided by the specified local access point. The service name is the resource name of the WTCImport and WTCEXport. As long as one of the directions is available then the returned status will be available.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

localAccessPoint

The local access point name.

Type: string

svcName

The resource name of imported or exported service/resource name.

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/WTCRuntime/resumeService

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)
- [POST](#)
- [POST](#)
- [POST](#)

POST

Resume all the Import or Export services with the specified service name configured for the specified local access point. The service name is the resource name of the WTCImport and WTCEXport.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

localAccessPoint

The local access point name.

Type: string

svcName

The resource name of imported or exported service/resource name.

Type: string

isImport

The type of service indicate whether it is import or export. If true, then it is imported service, if false it is targeted for exported service.

Type: boolean

Response Body

Contains an empty JSON object.

POST

Resume all the Import and Export services with the specified service name. This service name is the resource name of the WTCImport and WTCEXport.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

svcName

The resource name of imported or exported service/resource name.

Type: string

Response Body

Contains an empty JSON object.

POST

Resume a specific Import service with the specified service name configured for the specified local access point and remote access point list. The service name is the resource name of the WTCImport and WTCEXport. The remote access point list is a comma separated list; for instance, "TDOM1,TDOM2".

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

localAccessPoint

The local access point name.

Type: string

remoteAccessPointList

The comma separated remote access point names.

Type: string

svcName

The resource name of imported or exported service/resource name.

Type: string

Response Body

Contains an empty JSON object.

POST

Resume all the Import and Export services with the specified service name configured for the specified local access point. The service name is the resource name of the WTCImport and WTCEXport.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

localAccessPoint

The local access point name.

Type: string

svcName

The resource name of imported or exported service/resource name.

Type: string

Response Body

Contains an empty JSON object.

POST

Resume all the Import or Export services with the specified service name. This service name is the resource name of the WTCImport and WTCEXport.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

svcName

The resource name of imported or exported service/resource name.

Type: string

isImport

The type of service indicate whether it is import or export. If true, then it is imported service, if false it is targeted for exported service.

Type: boolean

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/WTCRuntime/startConnection

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Attempt to start a connection between the specified local and remote domain access points.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

LDomAccessPointId

The local domain access point id.

Type: string

RDomAccessPointId

The remote domain access point id.

Type: string

Response Body

Contains an empty JSON object.

POST

Attempt to start connections between the specified local domain access point and all remote end points defined for the given local domain domain access point.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

LDomAccessPointId

The local domain access point id.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/WTCRuntime/stopConnection

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Attempt to stop the connection between the specified local and remote domain access points.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

LdomAccessPointId

The local domain access point id.

Type: string

RDomAccessPointId

The remote domain access point id.

Type: string

Response Body

Contains an empty JSON object.

POST

Attempt to stop all remote connections configured for the given local access point id.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

LdomAccessPointId

The local domain access point id.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/WTCRuntime/suspendService

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)
- [POST](#)
- [POST](#)
- [POST](#)

POST

Suspend a specific Import service with the specified service name configured for the specified local access point and remote access point list. The service name is the resource name of the WTCImport and WTCEXport. The remote access point list is a comma separated list; for instance, "TDOM1,TDOM2".

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

localAccessPoint

The local access point name.

Type: string

remoteAccessPointList

The comma separated remote access point names.

Type: string

svcName

The resource name of imported or exported service/resource name.

Type: string

Response Body

Contains an empty JSON object.

POST

Suspend all the Import or Export services with the specified service name. This service name is the resource name of the WTCImport and WTCEXport.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

svcName

The resource name of imported or exported service/resource name.

Type: string

isImport

The type of service indicate whether it is import or export. If true, then it is imported service, if false it is targeted for exported service.

Type: boolean

Response Body

Contains an empty JSON object.

POST

Suspend all the Import or Export services with the specified service name configured for the specified local access point. The service name is the resource name of the WTCImport and WTCEExport.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

localAccessPoint

The local access point name.

Type: string

svcName

The resource name of imported or exported service/resource name.

Type: string

isImport

The type of service indicate whether it is import or export. If true, then it is imported service, if false it is targeted for exported service.

Type: boolean

Response Body

Contains an empty JSON object.

POST

Suspend all the Import and Export services with the specified service name. This service name is the resource name of the WTCImport and WTCEExport.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

POST

svcName

The resource name of imported or exported service/resource name.

Type: string

Response Body

Contains an empty JSON object.

POST

Suspend all the Import and Export services with the specified service name configured for the specified local access point. The service name is the resource name of the WTCImport and WTCEXport.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

localAccessPoint

The local access point name.

Type: string

svcName

The resource name of imported or exported service/resource name.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean

This resource manages a [weblogic.management.runtime.WTCStatisticsRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

GET

Get this [weblogic.management.runtime.WTCStatisticsRuntimeMBean](#) instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a [weblogic.management.runtime.WTCStatisticsRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getInTransactionCommittedTotalCount](#) **rel**=action
title=getInTransactionCommittedTotalCount
This resource's getInTransactionCommittedTotalCount action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getInTransactionRolledBackTotalCount](#) **rel**=action
title=getInTransactionRolledBackTotalCount
This resource's getInTransactionRolledBackTotalCount action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getInboundFailReqTotalCount](#) **rel**=action
title=getInboundFailReqTotalCount
This resource's getInboundFailReqTotalCount action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getInboundMessageTotalCount](#) **rel**=action
title=getInboundMessageTotalCount
This resource's getInboundMessageTotalCount action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getInboundNWMessageTotalSize](#) **rel**=action
title=getInboundNWMessageTotalSize
This resource's getInboundNWMessageTotalSize action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getInboundSuccessReqTotalCount](#) **rel**=action
title=getInboundSuccessReqTotalCount
This resource's getInboundSuccessReqTotalCount action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutTransactionCommittedTotalCount](#) **rel**=action
title=getOutTransactionCommittedTotalCount
This resource's getOutTransactionCommittedTotalCount action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutTransactionRolledBackTotalCount](#) **rel**=action
title=getOutTransactionRolledBackTotalCount
This resource's getOutTransactionRolledBackTotalCount action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutboundFailReqTotalCount **rel**=action
title=getOutboundFailReqTotalCount
This resource's getOutboundFailReqTotalCount action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutboundMessageTotalCount **rel**=action
title=getOutboundMessageTotalCount
This resource's getOutboundMessageTotalCount action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutboundNWMessageTotalSize **rel**=action
title=getOutboundNWMessageTotalSize
This resource's getOutboundNWMessageTotalSize action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutboundSuccessReqTotalCount **rel**=action
title=getOutboundSuccessReqTotalCount
This resource's getOutboundSuccessReqTotalCount action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutstandingNWReqCount **rel**=action
title=getOutstandingNWReqCount
This resource's getOutstandingNWReqCount action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean **rel**=canonical
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WTCRuntime **rel**=parent
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean **rel**=self
This resource.

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getInboundFailReqTotalCount

The resource supports the following methods:

- [POST](#)

POST

Returns the total number of inbound non-conversational, non-CORBA request that return failure by specific exported service. If specified service is imported, the return value should be 0.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

svcName

The service resource name.

Type: string

IDomAccessPointId

The local access point ID for this exported service.

Type: string

isImport

Should be false to get value for exported service.

Type: boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getInboundMessageTotalCount

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Returns the total number of inbound non-conversational, non-CORBA request messages received by this exported Service. If specified service is imported, the return value should be 0.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

svcName

The service resource name.

Type: string

IDomAccessPointId

The local access point ID for this exported service.

Type: string

isImport

Should be false to get value for exported service.

Type: boolean

Response Body

Contains a JSON object with a long return field.

POST

Returns the total number of inbound non-conversational, non-CORBA request messages received by this WTC connection. The WTC connection is identified by IDomAccessPointId and rDomAccessPointId pair.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

IDomAccessPointId

The local domain access point id.

Type: string

rDomAccessPointId

The remote domain access point id.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getInboundNWMessageTotalSize

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Returns the total message size of inbound non-conversational, non-CORBA messages received on this WTC connection. The WTC connection is defined by LDomAccessPointId and RDomAccessPointId pair.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

LDomAccessPointId

The local domain access point id.

Type: string

RDomAccessPointId

The remote domain access point id.

Type: string

Response Body

Contains a JSON object with a long return field.

POST

Returns the total size of inbound non-conversational, non-CORBA messages received by this exported Service. If specified service is imported, the return value should be 0.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

svcName

The service resource name.

Type: string

IDomAccessPointId

The local access point ID for this exported service.

Type: string

isImport

Should be false to get value for exported service.

Type: boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getInboundSuccessReqTotalCount

The resource supports the following methods:

- [POST](#)

POST

Returns the total number of inbound non-conversational, non-CORBA request that successfully handled by specific exported service. If specified service is imported, the return value should be 0.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

svcName

The service resource name.

Type: string

IDomAccessPointId

The local access point ID for this exported service.

Type: string

isImport

Should be false to get value for exported service.

Type: boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getInTransactionCommittedTotalCount

The resource supports the following methods:

- [POST](#)

POST

Returns the total number of inbound transactions committed on this WTC connection. The WTC connection is defined by IDomAccessPointId and rDomAccessPointId pair.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

IDomAccessPointId

The local domain access point id.

Type: string

rDomAccessPointId

The remote domain access point id.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getInTransactionRolledBackTotalCount

The resource supports the following methods:

- [POST](#)

POST

Returns the total number of inbound transactions rolled back on this WTC connection. The WTC connection is defined by IDomAccessPointId and rDomAccessPointId pair.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

IDomAccessPointId

The local domain access point id.

Type: string

rDomAccessPointId

The remote domain access point id.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutboundFailReqTotalCount

The resource supports the following methods:

- [POST](#)

POST

Returns the total number of outbound non-conversational, non-CORBA requests return failure by specific imported service. If specified service is exported, the return value should be 0.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

svcName

The service name.

Type: string

IDomAccessPointId

The local access point ID.

Type: string

rDomAccessPointIdList

The remote access point ID list.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutboundMessageTotalCount

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Returns the total number of outbound non-conversational, non-CORBA messages send to this imported Service. If specified service is exported, the return value should be 0.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

svcName

The service name.

Type: string

IDomAccessPointId

The local access point ID.

Type: string

rDomAccessPointIdList

The remote access point ID list.

Type: string

Response Body

Contains a JSON object with a long return field.

POST

Returns the total number of outbound non-conversational, non-CORBA messages received by this WTC connection. The WTC connection is identified by IDomAccessPointId and rDomAccessPointId pair.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

IDomAccessPointId

The local domain access point id.

Type: string

rDomAccessPointId

The remote domain access point id.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutboundNWMessageTotalSize

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Returns the total size of outbound non-conversational, non-CORBA messages send to this imported Service. If specified service is exported, the return value should be 0.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

svcName

The service name.

Type: string

IDomAccessPointId

The local access point ID.

Type: string

rDomAccessPointIdList

The remote access point ID list.

Type: string

Response Body

Contains a JSON object with a long return field.

POST

Returns the total size of outbound non-conversational, non-CORBA messages received on this WTC connection. The WTC connection is defined by LDomAccessPointId and RDomAccessPointId pair.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

LDomAccessPointId

The local domain access point id.

Type: string

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutboundNWMessageTotal-

RDomAccessPointId

The remote domain access point id.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutboundSuccessReqTotalCount

The resource supports the following methods:

- [POST](#)

POST

Returns the total number of outbound non-conversational, non-CORBA requests successfully handled by specific imported service. If specified service is exported, the return value should be 0.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

svcName

The service name.

Type: string

IDomAccessPointId

The local access point ID.

Type: string

rDomAccessPointIdList

The remote access point ID list.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutstandingNWReqCount

The resource supports the following methods:

- [POST](#)

POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

POST

Returns the current number of outstanding inbound non-conversational, non-CORBA requests received on this WTC connection. The WTC connection is defined by LDomAccessPointId and RDomAccessPointId pair.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

IDomAccessPointId

The local domain access point id.

Type: string

rDomAccessPointId

The remote domain access point id.

Type: string

Response Body

Contains a JSON object with a long return field.

POST

Returns the current number of outstanding non-conversational, non-CORBA requests for specific imported/exported service.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

svcName

The service name.

Type: string

IDomAccessPointId

Local access point.

Type: string

rDomAccessPointIdList

Remote Access Point ID List. If null, then the service is an exported service.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutTransactionCommittedTotalCount

The resource supports the following methods:

- [POST](#)

POST

Returns the total number of outbound transaction committed on this WTC connection. The WTC connection is defined by IDomAccessPointId and rDomAccessPointId pair.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

IDomAccessPointId

The local domain access point id.

Type: string

rDomAccessPointId

The remote domain access point id.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutTransactionRolledBackTotalCount

The resource supports the following methods:

- [POST](#)

POST

Returns the total number of outbound transactions rolled back on this WTC connection. The WTC connection is defined by `IDomAccessPointId` and `rDomAccessPointId` pair.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

IDomAccessPointId

The local domain access point id.

Type: string

rDomAccessPointId

The remote domain access point id.

Type: string

Response Body

Contains a JSON object with a long return field.

The following sections describe the data models on which the REST resources operate. These data models describe the information exchanged in REST resources.

com.bea.wls.redef.runtime.ClassRedefinitionRuntimeMBean

This interface provides functionality to monitor the class redefinition process. It also provides methods to explicitly initiate class redefinition.

The properties of the `com.bea.wls.redef.runtime.ClassRedefinitionRuntimeMBean` entity are as follows:

classRedefinitionCount

Number of class redefinitions executed so far.

Type: int

Constraints: Read Only, Restart Required

failedClassRedefinitionCount

Number of failed redefinition operations since the application was deployed.

Type: int

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

processedClassesCount

Number of classes processed since the application was deployed.

Type: int

Constraints: Read Only, Restart Required

totalClassRedefinitionTime

Total time spent processing classes, in nano seconds since the application was deployed.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean

This interface provides functionality to monitor and control a class redefinition request.

The properties of the com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean entity are as follows:

candidateClassesCount

Estimated number of candidate classes to be redefined in the current change-list. Returns -1 if the number is not yet estimated.

Type: int

Constraints: Read Only, Restart Required

completed

This property indicates whether an asynchronous job has completed.

Type: boolean

description

A description of this task.

Type: string

Constraints: Read Only, Restart Required

endTime

This property indicates the time when the asynchronous job ended.

Type: java.util.Date

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

parentTask

The task of which this task is a part.

A value of `null` indicates that this task is not a subtask.

Type: weblogic.management.runtime.TaskRuntimeMBean reference

Constraints: Read Only, Restart Required

processedClassesCount

Number of classes processed so far.

Type: int

Constraints: Read Only, Restart Required

progress

The progress of this task.

Type: string

Constraints: Read Only, Restart Required

running

Indicates whether the task is still running.

Type: boolean

Constraints: Read Only, Restart Required

startTime

This property indicates the time when an asynchronous job was started.

Type: java.util.Date

startTimeAsLong

The time at which this task was started.

Type: long

Constraints: Read Only, Restart Required

systemTask

Indicates whether this task was initiated by the server versus a user.

Type: boolean

Constraints: Read Only, Restart Required

taskError

Returns an exception describing the error, if any, that occurred while performing this task.

Type: java.lang.Throwable

Constraints: Read Only, Restart Required

taskStatus

The status of this task.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

java.lang.Throwable

This entity represents errors and exceptions.

The properties of the java.lang.Throwable entity are as follows:

cause

This property contains the stack trace of errors and exceptions.

Type: java.lang.Throwable

message

This property contains the reason why the error or exception was thrown.

Type: string

java.util.Date

This entity represents a date as a string in ISO 8601 format, yyyy-MM-ddTHH:mm:ss.SSSX

java.util.Properties

This entity represents a JSONObject with a property for each property in the properties object, where the key is the property's name the the value is a string containing the property's value.

weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean

Use this interface to access the specific type of diagnostic data from an underlying log for which this instance is created.

The properties of the weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean entity are as follows:

earliestAvailableTimestamp

The timestamp, in milliseconds, since Jan 1, 1970 AD, 00:00:00 GMT for the earliest record in the diagnostic data log.

Type: long

Constraints: Read Only, Restart Required

latestAvailableTimestamp

The timestamp, in milliseconds, since Jan 1, 1970 AD, 00:00:00 GMT for the newest record in the diagnostic data log.

Type: long

Constraints: Read Only, Restart Required

latestRecordId

The latest known record ID for the underlying archive.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

timestampAvailable

Returns true, if timestamp information is available with the underlying archive.

Type: boolean

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.health.HealthState

This entity represents the health of the services that are in a WebLogic server domain. Selected subsystems within each WebLogic Server instance monitor their health status based on criteria specific to the subsystem.

The properties of the weblogic.health.HealthState entity are as follows:

partitionName

This property indicates the partition name for which the health state is reported.

Type: string

state

This property indicates the reported state as:

- OK - Service is healthy.
- WARN - Service could have problems in the future
- CRITICAL - Something must be done now to prevent service failure
- FAILED - Service has failed and must be restarted
- OVERLOADED - Service is functioning normally but there is too much work in it
- UNKNOWN - Service state cannot be determined

Type: string

subsystemName

This property indicates the service for which the health state is reported.

Type: string

symptoms

This property indicates the cause of the reported state.

Type: array of weblogic.health.Symptom

weblogic.health.Symptom

This entity represents an observation reported by a service with its health state. A symptom can be used to determine the reason for the current health state of a WebLogic server.

The properties of the weblogic.health.Symptom entity are as follows:

info

This property provides additional information about the symptom if available.

Type: string

instanceId

This property represents an identifier for the symptom.

Type: string

severity

This property indicates a low, medium, or high severity level.

Type: string

type

This property represents the cause of the symptom (low memory, network error, stuck threads, and so on).

Type: string

weblogic.management.rest.bean.model.CurrentUser

The authenticated user that is making the request.

The properties of the weblogic.management.rest.bean.model.CurrentUser entity are as follows:

partitionId

The ID of the partition where the component that is being invoked resides.

Type: string

partitionName

The human readable name of the partition ID.

Type: string

user

The login of the user making this request, if the user has been authenticated, or null if the user has not been authenticated.

Type: string

weblogic.management.rest.bean.model.Version

A Version entity describes a version of the WebLogic Server resources.

The properties of the weblogic.management.rest.bean.model.Version entity are as follows:

isLatest

True if this is the default version.

Type: boolean

lifecycle

The lifecycle of this version: active or deprecated

Type: string

version

The name of this version.

Type: string

weblogic.management.runtime.ApplicationRuntimeMBean

An application represents a Java EE enterprise application packaged in an EAR file or EAR exploded directory. The EAR file or directory contains a set of components such as WAR, EJB, and RAR connector components, each of which can be deployed on one or more targets. A target is a server or a cluster. Modules in the application can have one of the following states:

- UNPREPARED - Indicates that none of the modules in this application are currently prepared or active.
- PREPARED - Indicates that none of the modules in this application are currently prepared or active.
- ACTIVATED - Indicates that at least one module in this application is currently active.

ApplicationRuntimeMBean encapsulates runtime information about a deployed enterprise application.

The properties of the weblogic.management.runtime.ApplicationRuntimeMBean entity are as follows:

activeVersionState

Specifies whether this application version is the currently active version.

An application can be the only version currently deployed, or it can have more than one version currently deployed, using the side-by-side deployment feature. If more than one version is deployed, only one version can be active. This attribute specifies the state the current application version is in.

An application can be in an INACTIVE state, which means that it has not been activated yet, or that there is more than one version of the application deployed (using side-by-side deployment) and this version is retiring.

An application can be in ACTIVE_ADMIN state, which means that it is the currently active version for administrative channel requests.

An application can be in ACTIVE state, which means that it is the currently active version for normal (non-administrative) channel requests.

Type: int

Constraints: Read Only, Restart Required

applicationName

The name of the application.

Type: string

Constraints: Read Only, Restart Required

applicationVersion

The application's version identifier.

This is particularly useful, when using the side-by-side deployment feature, to differentiate between two different versions of the same application that are deployed at the same time.

Type: string

Constraints: Read Only, Restart Required

healthState

The HealthState MBean for the application.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

internal

Indicates whether this application is an internal application. Such applications are not displayed in the console or persisted in the config.xml.

Type: boolean

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

overallHealthState

The overall health of the application including that of some of the components that report health. Currently, only connector modules report health status and are the only ones considered in the overall health state of the application.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

partitionName

The application's partition.

Returns the partition to which this application is deployed.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.AsyncReplicationRuntimeMBean

This MBean provides runtime statistics for async replication in a WebLogic Cluster

The properties of the weblogic.management.runtime.AsyncReplicationRuntimeMBean entity are as follows:

detailedSecondariesDistribution

Provides the names of the remote servers (such as myserver) for which the local server is hosting secondary objects. The name is appended with a number to indicate the number of secondaries hosted on behalf of that server.

Type: array of string

Constraints: Read Only, Restart Required

lastSessionsFlushTime

The last time the sessions were flushed, in milliseconds since midnight, January 1, 1970 UTC

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

primaryCount

Provides the number of object that the local server hosts as primaries.

Answer the number of object that the local server hosts as primaries.

Type: long

Constraints: Read Only, Restart Required

secondaryCount

Answer the number of object that the local server hosts as secondaries.

Type: long

Constraints: Read Only, Restart Required

secondaryServerDetails

Type: string

Constraints: Read Only, Restart Required

sessionsWaitingForFlushCount

Number of sessions which are waiting to be flushed.

Type: int

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.AuthenticatorRuntimeMBean

This class is used to monitor and manage authentication provider runtime information.

The properties of the weblogic.management.runtime.AuthenticatorRuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

providerName

Returns name of this security provider.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.BatchJobRepositoryRuntimeMBean

The properties of the weblogic.management.runtime.BatchJobRepositoryRuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.CapacityRuntimeMBean

Monitoring information for Capacity which defines the maximum number of requests that can be enqueued by all the work managers that share it.

The properties of the weblogic.management.runtime.CapacityRuntimeMBean entity are as follows:

count

Total number of requests that can be enqueued.

Type: int

Constraints: Read Only, Has Default Value: -1

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ClassLoaderRuntimeMBean

Provides methods for retrieving runtime information about class loading

The properties of the weblogic.management.runtime.ClassLoaderRuntimeMBean entity are as follows:

afterIndexingFindClassCount

Type: long

Constraints: Read Only, Restart Required

afterIndexingFindClassTime

Type: long

Constraints: Read Only, Restart Required

afterIndexingLoadClassCount

Type: long

Constraints: Read Only, Restart Required

afterIndexingLoadClassTime

Type: long

Constraints: Read Only, Restart Required

afterIndexingResourceCount

Type: long

Constraints: Read Only, Restart Required

afterIndexingResourceTime

Type: long

Constraints: Read Only, Restart Required

beforeIndexingFindClassCount

Type: long

Constraints: Read Only, Restart Required

beforeIndexingFindClassTime

Type: long

Constraints: Read Only, Restart Required

beforeIndexingLoadClassCount

Type: long

Constraints: Read Only, Restart Required

beforeIndexingLoadClassTime

Type: long

Constraints: Read Only, Restart Required

beforeIndexingResourceCount

Type: long

Constraints: Read Only, Restart Required

beforeIndexingResourceTime

Type: long

Constraints: Read Only, Restart Required

defineClassCount

Type: long

Constraints: Read Only, Restart Required

defineClassTime

Type: long

Constraints: Read Only, Restart Required

duringIndexingFindClassCount

Type: long

Constraints: Read Only, Restart Required

duringIndexingFindClassTime

Type: long

Constraints: Read Only, Restart Required

duringIndexingLoadClassCount

Type: long

Constraints: Read Only, Restart Required

duringIndexingLoadClassTime

Type: long

Constraints: Read Only, Restart Required

duringIndexingResourceCount

Type: long

Constraints: Read Only, Restart Required

duringIndexingResourceTime

Type: long

Constraints: Read Only, Restart Required

findClassCount

Type: long

Constraints: Read Only, Restart Required

findClassTime

Type: long

Constraints: Read Only, Restart Required

indexingTime

Type: long

Constraints: Read Only, Restart Required

loadClassCount

Type: long

Constraints: Read Only, Restart Required

loadClassTime

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

parentDelegationCount

Type: long

Constraints: Read Only, Restart Required

parentDelegationTime

Type: long

Constraints: Read Only, Restart Required

resourceCount

Type: long

Constraints: Read Only, Restart Required

resourceTime

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ClusterRuntimeMBean

This class is used for monitoring a server's view of the members of a WebLogic cluster within a WebLogic domain.

The properties of the weblogic.management.runtime.ClusterRuntimeMBean entity are as follows:

activeSingletonServices

Returns an array of the names of the singleton services that are active on this server.

Type: array of string

Constraints: Read Only, Restart Required

aliveServerCount

Provides the current total number of alive servers in this cluster.

Returns the current total number of alive servers in this cluster.

Type: int

Constraints: Read Only, Restart Required

detailedSecondariesDistribution

Provides the names of the remote servers (such as myserver) for which the local server is hosting secondary objects. The name is appended with a number to indicate the number of secondaries hosted on behalf of that server.

Type: array of string

Constraints: Read Only, Restart Required

foreignFragmentsDroppedCount

Provides the number of fragments that originated in foreign domains or clusters which use the same multicast address.

Answer the number of fragments that originated in foreign domains/cluster that use the same multicast address.

Type: long

Constraints: Read Only, Restart Required

fragmentsReceivedCount

Provides the total number of messages received on this server from the cluster. This is applicable to both multicast and unicast message types.

Type: long

Constraints: Read Only, Restart Required

fragmentsSentCount

Returns the total number of message fragments sent from this server into the cluster. This is applicable to both multicast and unicast message types.

Type: long

Constraints: Read Only, Restart Required

healthState

Provides health information returned by the server self-health monitor service.

- HEALTH_OK = 0, Server service is healthy.
- HEALTH_WARN = 1, Service could have problems in the future. Check the server logs and the corresponding RuntimeMBean for more details.
- HEALTH_CRITICAL = 2, Something must be done now to prevent service failure. Check the server logs and the corresponding RuntimeMBean for more details.
- HEALTH_FAILED = 3, Service has failed - must be restarted. Check the server logs and the corresponding RuntimeMBean for more details.
- HEALTH_OVERLOADED = 4, Service is functioning normally but there is too much work in it. CRITICAL and OVERLOADED are different. A subsystem is in the critical state when a part of it is malfunctioning, for example, stuck threads. An overloaded state means that there is more work assigned to the service than the configured threshold. A service might refuse more work in this state.
- LOW_MEMORY_REASON = "server is low on memory", Reason code that indicates that the server is low on memory. Administrators can configure low and

high thresholds for memory usage. The server health changes to OVERLOADED with this reason code if the low threshold is reached.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

multicastMessagesLostCount

Provides the total number of in-coming multicast messages that were lost according to this server.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

primaryCount

Provides the number of object that the local server hosts as primaries.

Answer the number of object that the local server hosts as primaries.

Type: long

Constraints: Read Only, Restart Required

resendRequestsCount

Provides the number of state-delta messages that had to be resent because a receiving server in the cluster missed a message.

Returns the number of state-delta messages that had to be resent because a receiving server in the cluster missed a message.

Type: long

Constraints: Read Only, Restart Required

secondaryCount

Answer the number of object that the local server hosts as secondaries.

Type: long

Constraints: Read Only, Restart Required

secondaryServerDetails

Type: string

Constraints: Read Only, Restart Required

serverNames

Provides the names of the servers in the cluster.

Type: array of string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.CoherenceClusterRuntimeMBean

Coherence cluster run-time information.

The properties of the weblogic.management.runtime.CoherenceClusterRuntimeMBean entity are as follows:

clusterName

The name of the Coherence cluster.

Type: string

Constraints: Read Only, Restart Required

clusterSize

The size of the Coherence cluster.

Type: int

Constraints: Read Only, Restart Required

licenseMode

The license mode for the Coherence cluster. Possible values are Evaluation, Development, or Production.

Type: string

Constraints: Read Only, Restart Required

members

Identifiers for the available Coherence cluster members.

Type: array of string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

version

The Coherence cluster version.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ComponentRuntimeMBean

Base class for all runtime mbeans that provide status of running modules.

The properties of the `weblogic.management.runtime.ComponentRuntimeMBean` entity are as follows:

deploymentState

The current deployment state of the module.

A module can be in one and only one of the following states. State can be changed via deployment or administrator console.

- UNPREPARED. State indicating at this module is neither prepared or active.
- PREPARED. State indicating at this module of this application is prepared, but not active. The classes have been loaded and the module has been validated.
- ACTIVATED. State indicating at this module is currently active.
- NEW. State indicating this module has just been created and is being initialized.

Type: int

Constraints: Read Only, Restart Required

moduleId

Returns the identifier for this Component. The identifier is unique within the application.

Typical modules will use the URI for their id. Web Modules will return their context-root since the web-uri may not be unique within an EAR.

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ConcurrentManagedObjectsRuntimeMBean

Concurrent Managed Objects Runtime information for the global/domain partition or a common partition.

The properties of the `weblogic.management.runtime.ConcurrentManagedObjectsRuntimeMBean` entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

rejectedLongRunningRequests

The number of long-running requests that have been rejected by managed executor services and managed scheduled executor services in this partition on the current server.

Type: long

Constraints: Read Only, Restart Required

rejectedNewThreadRequests

The number of newThread method invocations that have been rejected by managed thread factories in this partition on the current server.

Type: long

Constraints: Read Only, Restart Required

runningLongRunningRequests

The number of running long-running requests submitted to managed executor services and managed scheduled executor services in this partition on the current server.

Type: int

Constraints: Read Only, Restart Required

runningThreadsCount

The number of running threads created by managed thread factories in this partition on the current server.

Type: int

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ConnectorComponentRuntimeMBean

Generates notifications about the deployment state of resource adapters. (Each resource adapter is represented by an instance of `weblogic.management.configuration.ConnectorComponentMBean`.)

In 2-phase deployment, if a resource adapter's state is `PREPARED` then it has achieved the first phase of deployment (everything is set up and all that remains is to enable a reference to the adapter). When the resource adapter is in an `ACTIVATED` state, it has achieved the second phase of deployment, in which applications can obtain a reference to the adapter.

A server instance creates an instance of this interface when it creates an instance of `weblogic.management.configuration.ConnectorComponentMBean`

The properties of the `weblogic.management.runtime.ConnectorComponentRuntimeMBean` entity are as follows:

EISResourceId

Returns the EISResourceId for the component.

Type: string

Constraints: Read Only, Restart Required

EISType

Get the EIS type.

Type: string

Constraints: Read Only, Restart Required

activeVersion

Return true if this version is the active version. Returns true if this resource adapter is not versioned.

Type: boolean

Constraints: Read Only, Restart Required

activeVersionId

Get the active version Id.

Type: string

Constraints: Read Only, Restart Required

componentName

Get the name of the connector component.

Type: string

Constraints: Read Only, Restart Required

configuration

Return the xml string representing the RA configuration. The xml corresponding to the latest schema is returned. The current supported version is "1.0"

Type: string

Constraints: Read Only, Restart Required

configurationVersion

Return the latest configuration version.

Type: string

Constraints: Read Only, Restart Required

configuredProperties

Gets a subset of the resource adapter descriptor information.

Type: java.util.Properties

Constraints: Read Only, Restart Required

connectionPoolCount

The number of connection pools.

Type: int

Constraints: Read Only, Restart Required

deploymentState

The current deployment state of the module.

A module can be in one and only one of the following states. State can be changed via deployment or administrator console.

- UNPREPARED. State indicating at this module is neither prepared or active.
- PREPARED. State indicating at this module of this application is prepared, but not active. The classes have been loaded and the module has been validated.
- ACTIVATED. State indicating at this module is currently active.
- NEW. State indicating this module has just been created and is being initialized.

Type: int

Constraints: Read Only, Restart Required

description

Get the Description for the resource adapter.

Type: string

Constraints: Read Only, Restart Required

descriptions

Get the Descriptions for the resource adapter.

Type: array of string

Constraints: Read Only, Restart Required

healthState

The HealthState mbean for the application.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

inboundConnectionsCount

The number of inbound connections for the resource adapter.

Type: int

Constraints: Read Only, Restart Required

jndiName

Get the Jndi name of the resource adapter.

Type: string

Constraints: Read Only, Restart Required

linkref

Get the linkref.

Type: string

Constraints: Read Only, Restart Required

moduleId

Returns the identifier for this Component. The identifier is unique within the application.

Typical modules will use the URI for their id. Web Modules will return their context-root since the web-uri may not be unique within an EAR.

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

schema

Get the latest schema for RA configuration.

Type: string

Constraints: Read Only, Restart Required

specVersion

Get the spec version.

Type: string

Constraints: Read Only, Restart Required

state

Get the state of the resource adapter.

Type: string

Constraints: Read Only, Restart Required

suspendedState

Gets the suspended state information of the resource adapter.

If getState() returns SUSPENDED then getSuspendedState() returns an integer describing which functions of the resource adapter are suspended: one or more of INBOUND, OUTBOUND or WORK (or ALL) or 0 for nothing suspended

Type: int

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

vendorName

Get the vendor name.

Type: string

Constraints: Read Only, Restart Required

version

Get the version.

Type: string

Constraints: Read Only, Restart Required

versionId

Get the version Id.

Type: string

Constraints: Read Only, Restart Required

versioned

Check if the resource adapter is versioned. Returns true if it is.

Type: boolean

Constraints: Read Only, Restart Required

weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean

This class is used for monitoring a WebLogic Connector Connection Pool

The properties of the weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean entity are as follows:

EISResourceId

The EISResourceId of this Connector connection pool.

Type: string

Constraints: Read Only, Restart Required

MCFClassName

Get the MCF class name.

Type: string

Constraints: Read Only, Restart Required

activeConnectionsCurrentCount

The current total active connections.

Type: int

Constraints: Read Only, Restart Required

activeConnectionsHighCount

The high water mark of active connections in this Connector Pool since the pool was instantiated.

Type: int

Constraints: Read Only, Restart Required

averageActiveUsage

The running average usage of created connections that are active in the Connector Pool since the pool was last shrunk.

Type: int

Constraints: Read Only, Restart Required

capacityIncrement

The initial capacity configured for this Connector connection pool.

Type: int

Constraints: Read Only, Restart Required

closeCount

The number of connections that were closed for the connection pool.

Type: long

Constraints: Read Only, Restart Required

connectionFactoryClassName

The ConnectionFactoryName of this Connector connection pool.

Type: string

Constraints: Read Only, Restart Required

connectionFactoryName

For 1.0 link-ref resource adapters only, the base resource adapter's connection factory name.

Type: string

Constraints: Read Only, Restart Required

connectionsCreatedTotalCount

The total number of Connector connections created in this Connector Pool since the pool is instantiated.

Type: int

Constraints: Read Only, Restart Required

connectionsDestroyedByErrorTotalCount

Return the number of connections that were destroyed because an error event was received.

Type: int

Constraints: Read Only, Restart Required

connectionsDestroyedByShrinkingTotalCount

Return the number of connections that were destroyed as a result of shrinking.

Type: int

Constraints: Read Only, Restart Required

connectionsDestroyedTotalCount

The total number of Connector connections destroyed in this Connector Pool since the pool is instantiated.

Type: int

Constraints: Read Only, Restart Required

connectionsMatchedTotalCount

The total number of times a request for a Connector connections was satisfied via the use of an existing created connection since the pool is instantiated.

Type: int

Constraints: Read Only, Restart Required

connectionsRejectedTotalCount

The total number of rejected requests for a Connector connections in this Connector Pool since the pool is instantiated.

Type: int

Constraints: Read Only, Restart Required

connectorEisType

The EIS type of this Connector connection pool.

Type: string

Constraints: Read Only, Restart Required

currentCapacity

The PoolSize of this Connector connection pool.

Type: long

Constraints: Read Only, Restart Required

freeConnectionsCurrentCount

The current total free connections.

Type: int

Constraints: Read Only, Restart Required

freeConnectionsHighCount

The high water mark of free connections in this Connector Pool since the pool was instantiated.

Type: int

Constraints: Read Only, Restart Required

freePoolSizeHighWaterMark

The FreePoolSizeHighWaterMark of this Connector connection pool.

Type: long

Constraints: Read Only, Restart Required

freePoolSizeLowWaterMark

The FreePoolSizeLowWaterMark of this Connector connection pool.

Type: long

Constraints: Read Only, Restart Required

healthState

The HealthState mbean for the application.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

highestNumWaiters

Gets the highest number of waiters.

Type: long

Constraints: Read Only, Restart Required

initialCapacity

The initial capacity configured for this Connector connection pool.

Type: int

Constraints: Read Only, Restart Required

key

The configured Key for the Connection Factory using this Connector connection pool.

Type: string

Constraints: Read Only, Restart Required

lastShrinkTime

Return the last time that the pool was shrunk.

Type: long

Constraints: Read Only, Restart Required

logFileName

The Log File used by the Resource Adapter for this Connector connection pool.

Type: string

Constraints: Read Only, Restart Required

logFileStreamOpened

Gets the opened state of the log file stream represented by this instance.

Type: boolean

Constraints: Read Only, Restart Required

loggingEnabled

Indicates whether logging is enabled for this Connector connection pool.

Type: boolean

Constraints: Read Only, Restart Required

managedConnectionFactoryClassName

The ManagedConnectionFactoryName of this Connector connection pool.

Type: string

Constraints: Read Only, Restart Required

maxCapacity

The maximum capacity configured for this Connector connection pool.

Type: int

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

numUnavailableCurrentCount

Return the number of unavailable connections.

Type: int

Constraints: Read Only, Restart Required

numUnavailableHighCount

Return the highest unavailable number of connections at any given time.

Type: int

Constraints: Read Only, Restart Required

numWaiters

Gets the current number of waiters.

Type: long

Constraints: Read Only, Restart Required

numWaitersCurrentCount

Return the number of waiters.

Type: int

Constraints: Read Only, Restart Required

poolName

The configured Logical Name for the Connection Factory using this Connector connection pool.

Type: string

Constraints: Read Only, Restart Required

poolSizeHighWaterMark

The PoolSizeHighWaterMark of this Connector connection pool.

Type: long

Constraints: Read Only, Restart Required

poolSizeLowWaterMark

The PoolSizeLowWaterMark of this Connector connection pool.

Type: long

Constraints: Read Only, Restart Required

proxyOn

Return a flag indicating if the proxy is on. Returns true if it is.

Type: boolean

Constraints: Read Only, Restart Required

recycledTotal

The total number of Connector connections that have been recycled in this Connector Pool since the pool is instantiated.

Type: int

Constraints: Read Only, Restart Required

runtimeTransactionSupport

The real transaction support level in use at runtime.

Type: string

Constraints: Read Only, Restart Required

shrinkCountDownTime

The amount of time left (in minutes) until an attempt to shrink the pool will be made.

Type: int

Constraints: Read Only, Restart Required

shrinkPeriodMinutes

The Shrink Period (in minutes) of this Connector connection pool.

Type: int

Constraints: Read Only, Restart Required

shrinkingEnabled

Specifies whether shrinking of this Connector connection pool is enabled.

Type: boolean

Constraints: Read Only, Restart Required

state

Get the state of the pool.

Type: string

Constraints: Read Only, Restart Required

testable

This indicates whether the connection pool is testable or not.

Type: boolean

Constraints: Read Only, Restart Required

transactionSupport

The static transaction support level, either configured in ra.xml or in @Conector annotation, for the Resource Adapter for this Connector connection pool.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ConnectorConnectionRuntimeMBean

This class is used for monitoring individual WebLogic Connector connections

The properties of the weblogic.management.runtime.ConnectorConnectionRuntimeMBean entity are as follows:

EISProductName

Returns the EISProductName associated with the ManagedConnection's MetaData

Type: string

Constraints: Read Only, Restart Required

EISProductVersion

Returns the EISProductVersion associated with the ManagedConnection's MetaData.

Type: string

Constraints: Read Only, Restart Required

activeHandlesCurrentCount

The current total active connection handles for this connection.

Type: int

Constraints: Read Only, Restart Required

activeHandlesHighCount

The high water mark of active connection handles for this connection since the connection was created.

Type: int

Constraints: Read Only, Restart Required

connectionFactoryClassName

Returns the connection factory class name.

Type: string

Constraints: Read Only, Restart Required

creationDurationTime

Return the time taken to create the connection.

Type: long

Constraints: Read Only, Restart Required

currentlyInUse

Indicates whether the connection is currently in use.

Type: boolean

Constraints: Read Only, Restart Required

deletable

Indicates whether the connection can be closed manually through the console.

Type: boolean

Constraints: Read Only, Restart Required

handlesCreatedTotalCount

The total number of connection handles created for this connection since the connection was created.

Type: int

Constraints: Read Only, Restart Required

inTransaction

Indicates whether the connection is currently in use in a transaction.

Type: boolean

Constraints: Read Only, Restart Required

managedConnectionFactoryClassName

Returns the managed connection factory class name.

Type: string

Constraints: Read Only, Restart Required

maxConnections

Returns the MaxConnections associated with the ManagedConnection's MetaData

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

reserveDurationTime

Get the time taken to reserve this connection.

Type: long

Constraints: Read Only, Restart Required

reserveTime

Return the last time the connection was reserved.

Type: long

Constraints: Read Only, Restart Required

shared

Indicates whether the connection is currently being shared by more than one invoker.

Type: boolean

Constraints: Read Only, Restart Required

transactionId

Get the Transaction ID of the transaction that this connection is being used with.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

userName

Returns the UserName associated with the ManagedConnection's MetaData

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ConnectorInboundRuntimeMBean

This class is used for monitoring inbound connections of resource adapters.

The properties of the weblogic.management.runtime.ConnectorInboundRuntimeMBean entity are as follows:

activationSpecClass

The activation spec class.

Type: string

Constraints: Read Only, Restart Required

msgListenerType

The message listener type.

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

state

Return the state of the Inbound connection. The values that are returned are : "Running" and "Suspended".

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ConnectorServiceRuntimeMBean

This interface defines the runtime information that can be accessed at a connector service level. Runtime information can be accessed at a per resource adapter level or at an overall level.

The properties of the weblogic.management.runtime.ConnectorServiceRuntimeMBean entity are as follows:

RACount

Returns the number of resource adapters that have been deployed in the server. This count includes active RAs and Non-active RAs (in the case of versioned RAs that are being replaced by a new version)

Type: int

Constraints: Read Only, Restart Required

activeRACount

Returns the number of resource adapters that are active.

Type: int

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean

This class is used for monitoring Connector Work Manager of resource adapters.

The properties of the weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean entity are as follows:

activeLongRunningRequests

Return The number of current active long-running work requests.

Type: int

Constraints: Read Only, Restart Required

completedLongRunningRequests

The number of completed long-running work requests.

Type: int

Constraints: Read Only, Restart Required

maxConcurrentLongRunningRequests

The maximum number of allowed concurrent long-running work requests. New work submission will be rejected if current running long-running work requests exceed the limit.

Type: int

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.EJBPoolRuntimeMBean

This interface contains accessor methods for all free pool runtime information collected for an EJB.

The properties of the weblogic.management.runtime.EJBPoolRuntimeMBean entity are as follows:

accessTotalCount

Provides a count of the total number of times an attempt was made to get an instance from the free pool.

Type: long

Constraints: Read Only, Restart Required

beansInUseCurrentCount

Provides a count of the number of bean instances currently being used from the free pool.

Type: int

Constraints: Read Only, Restart Required

destroyedTotalCount

Provides a count of the total number of times a bean instance from this pool was destroyed due to a non-application Exception being thrown from it.

Type: long

Constraints: Read Only, Restart Required

missTotalCount

Provides a count of the total number of times a failed attempt was made to get an instance from the free pool. An Attempt to get a bean from the pool will fail if there are no available instances in the pool.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

pooledBeansCurrentCount

Provides a count of the current number of available bean instances in the free pool.

Type: int

Constraints: Read Only, Restart Required

timeoutTotalCount

Provides a count of the total number of Threads that have timed out waiting for an available bean instance from the free pool.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

waiterCurrentCount

Provides a count of the number of Threads currently waiting for an available bean instance from the free pool.

Type: int

Constraints: Read Only, Restart Required

weblogic.management.runtime.EJBTimerRuntimeMBean

This interface contains accessor methods for all EJB Timer runtime information collected for an EJB.

The properties of the weblogic.management.runtime.EJBTimerRuntimeMBean entity are as follows:

activeTimerCount

Provides the current number of active timers for this EJB

Type: int

Constraints: Read Only, Restart Required

cancelledTimerCount

Provides the total number of timers that have been explicitly cancelled for this EJB.

Type: long

Constraints: Read Only, Restart Required

disabledTimerCount

Provides the current number of timers temporarily disabled for this EJB

Type: int

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

timeoutCount

Provides the total number of successful timeout notifications that have been made for this EJB.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.EJBTransactionRuntimeMBean

This interface contains accessor methods for all transaction runtime information collected for an EJB.

The properties of the `weblogic.management.runtime.EJBTransactionRuntimeMBean` entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

transactionsCommittedTotalCount

Provides a count of the total number of transactions that have been committed for this EJB.

Type: long

Constraints: Read Only, Restart Required

transactionsRolledBackTotalCount

Provides a count of the total number of transactions that have been rolled back for this EJB.

Type: long

Constraints: Read Only, Restart Required

transactionsTimedOutTotalCount

Provides a count of the total number of transactions that have timed out for this EJB.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.EntityCacheCumulativeRuntimeMBean

This class is used for monitoring an XML Cache.

The properties of the `weblogic.management.runtime.EntityCacheCumulativeRuntimeMBean` entity are as follows:

avgEntrySizeDiskPurged

Provides the cumulative average size of entries that have been purged from the disk cache.

Type: double

Constraints: Read Only, Restart Required

avgEntrySizeMemoryPurged

Provides the average size of the all the entries that have been purged from the memory.

Type: double

Constraints: Read Only, Restart Required

avgPerEntryDiskSize

Provides the current average size of the entries in the entity disk cache.

Returns the current average size of the entries in the entity disk cache.

Type: double

Constraints: Read Only, Restart Required

avgPerEntryMemorySize

Provides the current average size of the entries in the entity memory cache.

Returns the current average size of the entries in the entity memory cache.

Type: double

Constraints: Read Only, Restart Required

avgPercentPersistent

Provides the current average percentage of entries in the entity cache that have been persisted to the disk cache.

Returns current average percentage of entries in the entity cache that have been persisted to the disk cache.

Type: double

Constraints: Read Only, Restart Required

avgPercentTransient

Provides the current average percentage of entries in the entity cache that are transient, or have not been persisted.

Returns current average percentage of entries in the entity cache that are transient, or have not been persisted.

Type: double

Constraints: Read Only, Restart Required

avgTimeout

Provides the average amount of time that the entity cache has timed out when trying to retrieve an entity.

Returns the average amount of time that the entity cache has timed out when trying to retrieve an entity.

Type: double

Constraints: Read Only, Restart Required

diskPurgesPerHour

Provides cumulative average number of purges from the disk cache per hour.

Type: double

Constraints: Read Only, Restart Required

maxEntryMemorySize

Provides the current maximum size of the entries in the entity memory cache.

Returns the current maximum size of the entries in the entity memory cache.

Type: long

Constraints: Read Only, Restart Required

maxEntryTimeout

Provides the largest timeout value for any current entry in the entity cache.

Returns the largest timeout value for any current entry in the entity cache.

Type: double

Constraints: Read Only, Restart Required

memoryPurgesPerHour

Provides the cumulative average number of entries that have been purged from the entity cache.

Type: double

Constraints: Read Only, Restart Required

minEntryMemorySize

Provides the current minimum size of the entries in the entity memory cache.

Returns the current minimum size of the entries in the entity memory cache.

Type: long

Constraints: Read Only, Restart Required

minEntryTimeout

Provides the smallest timeout value for any current entry in the entity cache.

Returns the smallest timeout value for any current entry in the entity cache.

Type: double

Constraints: Read Only, Restart Required

mostRecentDiskPurge

Provides the date of the most recent purge from the disk cache.

Type: java.util.Date

Constraints: Read Only, Restart Required

mostRecentMemoryPurge

Provides the date of the most recent purge of the entity cache.

Type: java.util.Date

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

percentRejected

Provides the cumulative percent of the potential entries to the entity cache that have been rejected.

Type: double

Constraints: Read Only, Restart Required

totalCurrentEntries

Provides a count of the total current number of entries in the entity cache.

Returns the total current number of entries in the entity cache.

Type: long

Constraints: Read Only, Restart Required

totalItemsDiskPurged

Provides the total number of items that have been purged from the disk cache.

Type: long

Constraints: Read Only, Restart Required

totalItemsMemoryPurged

Provides the cumulative number of items that have been purged from the entity cache.

Type: long

Constraints: Read Only, Restart Required

totalNumberDiskPurges

Provides a count of the total number of entries that have been purged from the disk cache.

Type: long

Constraints: Read Only, Restart Required

totalNumberMemoryPurges

Provides the cumulative number of entries that have been purged from the entity cache.

Type: long

Constraints: Read Only, Restart Required

totalNumberOfRejections

Provides the cumulative total number of rejections of entries from the entity cache for the current session.

Type: long

Constraints: Read Only, Restart Required

totalNumberOfRenewals

Provides a count of the cumulative number of entries that have been refreshed in the entity cache.

Type: long

Constraints: Read Only, Restart Required

totalPersistentCurrentEntries

Provides a count of the total current number of entries in the cache that have been persisted to disk.

Returns the total current number of entries in the cache that have been persisted to disk.

Type: long

Constraints: Read Only, Restart Required

totalSizeOfRejections

Provides the cumulative total size of the rejections from the entity cache.

Type: long

Constraints: Read Only, Restart Required

totalTransientCurrentEntries

Provides a count of the total current number of transient (not yet persisted to disk) entries in the entity cache.

Returns the total current number of transient entries in the entity cache.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.EntityCacheCurrentStateRuntimeMBean

This class is used for monitoring the size and usage of an XML Cache.

The properties of the `weblogic.management.runtime.EntityCacheCurrentStateRuntimeMBean` entity are as follows:

avgPerEntryDiskSize

Provides the current average size of the entries in the entity disk cache.

Returns the current average size of the entries in the entity disk cache.

Type: double

Constraints: Read Only, Restart Required

avgPerEntryMemorySize

Provides the current average size of the entries in the entity memory cache.

Returns the current average size of the entries in the entity memory cache.

Type: double

Constraints: Read Only, Restart Required

avgPercentPersistent

Provides the current average percentage of entries in the entity cache that have been persisted to the disk cache.

Returns current average percentage of entries in the entity cache that have been persisted to the disk cache.

Type: double

Constraints: Read Only, Restart Required

avgPercentTransient

Provides the current average percentage of entries in the entity cache that are transient, or have not been persisted.

Returns current average percentage of entries in the entity cache that are transient, or have not been persisted.

Type: double

Constraints: Read Only, Restart Required

avgTimeout

Provides the average amount of time that the entity cache has timed out when trying to retrieve an entity.

Returns the average amount of time that the entity cache has timed out when trying to retrieve an entity.

Type: double

Constraints: Read Only, Restart Required

diskUsage

Provides the current size of the entity disk cache.

Returns the current size of the entity disk cache.

Type: long

Constraints: Read Only, Restart Required

maxEntryMemorySize

Provides the current maximum size of the entries in the entity memory cache.

Returns the current maximum size of the entries in the entity memory cache.

Type: long

Constraints: Read Only, Restart Required

maxEntryTimeout

Provides the largest timeout value for any current entry in the entity cache.

Returns the largest timeout value for any current entry in the entity cache.

Type: double

Constraints: Read Only, Restart Required

memoryUsage

Provides the current size of the entity memory cache.

Returns current size of the entity memory cache.

Type: long

Constraints: Read Only, Restart Required

minEntryMemorySize

Provides the current minimum size of the entries in the entity memory cache.

Returns the current minimum size of the entries in the entity memory cache.

Type: long

Constraints: Read Only, Restart Required

minEntryTimeout

Provides the smallest timeout value for any current entry in the entity cache.

Returns the smallest timeout value for any current entry in the entity cache.

Type: double

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

totalCurrentEntries

Provides a count of the total current number of entries in the entity cache.

Returns the total current number of entries in the entity cache.

Type: long

Constraints: Read Only, Restart Required

totalPersistentCurrentEntries

Provides a count of the total current number of entries in the cache that have been persisted to disk.

Returns the total current number of entries in the cache that have been persisted to disk.

Type: long

Constraints: Read Only, Restart Required

totalTransientCurrentEntries

Provides a count of the total current number of transient (not yet persisted to disk) entries in the entity cache.

Returns the total current number of transient entries in the entity cache.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ExecuteQueueRuntimeMBean

This bean is used to monitor an execute queue and its associated thread pool.

The properties of the weblogic.management.runtime.ExecuteQueueRuntimeMBean entity are as follows:

executeThreadCurrentIdleCount

The number of idle threads assigned to the queue.

Type: int

Constraints: Read Only, Restart Required

executeThreadTotalCount

The total number of execute threads assigned to the queue.

Type: int

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

pendingRequestCurrentCount

The number of waiting requests in the queue.

Type: int

Constraints: Read Only, Restart Required

pendingRequestOldestTime

The time since the longest waiting request was placed in the queue.

Type: long

Constraints: Read Only, Restart Required

servicedRequestTotalCount

The number of requests that have been processed by the queue.

Type: int

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.FairShareConstraintRuntimeMBean

The properties of the weblogic.management.runtime.FairShareConstraintRuntimeMBean entity are as follows:

activated

Returns true if trigger was successfully executed.

Type: boolean

Constraints: Read Only, Restart Required

initiated

Returns true if trigger execution has begun.

Type: boolean

Constraints: Read Only, Restart Required

lastTimeExecuted

Return last trigger execution date and time.

Type: java.util.Date

Constraints: Read Only, Restart Required

name

Return name of the Resource.

Type: string

Constraints: Read Only, Restart Required

recourseActionEventsHistory

Return details of trigger execution in the past.

Type: array of weblogic.management.runtime.RecourseActionEventVBean

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JDBCDataSourceRuntimeMBean

This class is used for monitoring a WebLogic JDBC Data Source and its associated connection pool.

The properties of the weblogic.management.runtime.JDBCDataSourceRuntimeMBean entity are as follows:

activeConnectionsAverageCount

Average number of active connections in this instance of the data source.

Active connections are connections in use by an application. This value is only valid if the resource is configured to allow shrinking.

Type: int

Constraints: Read Only, Restart Required

activeConnectionsCurrentCount

The number of connections currently in use by applications.

Type: int

Constraints: Read Only, Restart Required

activeConnectionsHighCount

Highest number of active database connections in this instance of the data source since the data source was instantiated.

Active connections are connections in use by an application.

Type: int

Constraints: Read Only, Restart Required

connectionDelayTime

The average amount of time, in milliseconds, that it takes to create a physical connection to the database.

The value is calculated as summary of all times to connect divided by the total number of connections.

Type: int

Constraints: Read Only, Restart Required

connectionsTotalCount

The cumulative total number of database connections created in this data source since the data source was deployed.

Type: int

Constraints: Read Only, Restart Required

currCapacity

The current count of JDBC connections in the connection pool in the data source.

Type: int

Constraints: Read Only, Restart Required

currCapacityHighCount

Highest number of database connections available or in use (current capacity) in this instance of the data source since the data source was deployed.

Type: int

Constraints: Read Only, Restart Required

databaseProductName

The product name of the database that this data source is connected to.

Type: string

Constraints: Read Only, Restart Required

databaseProductVersion

The product version of the database that this data source is connected to.

Type: string

Constraints: Read Only, Restart Required

deploymentState

The current deployment state of the module.

A module can be in one and only one of the following states. State can be changed via deployment or administrator console.

- UNPREPARED. State indicating at this module is neither prepared or active.
- PREPARED. State indicating at this module of this application is prepared, but not active. The classes have been loaded and the module has been validated.
- ACTIVATED. State indicating at this module is currently active.
- NEW. State indicating this module has just been created and is being initialized.

Type: int

Constraints: Read Only, Restart Required

driverName

The product name of the JDBC driver that this data source is configured to use.

Type: string

Constraints: Read Only, Restart Required

driverVersion

The version of the JDBC driver that this data source is configured to use.

Type: string

Constraints: Read Only, Restart Required

enabled

Indicates whether the data source is enabled or disabled:

- `true` if the data source is enabled.
- `false` if the data source is disabled.

Type: boolean

Constraints: Read Only, Restart Required

failedReserveRequestCount

The cumulative, running count of requests for a connection from this data source that could not be fulfilled.

Type: long

Constraints: Read Only, Restart Required

failuresToReconnectCount

The number of times that the data source attempted to refresh a database connection and failed.

Failures may occur when the database is unavailable or when the network connection to the database is interrupted.

Type: int

Constraints: Read Only, Restart Required

highestNumAvailable

Highest number of database connections that were idle and available to be used by an application at any time in this instance of the data source since the data source was deployed.

Type: int

Constraints: Read Only, Restart Required

highestNumUnavailable

Highest number of database connections that were in use by applications or being tested by the system in this instance of the data source since the data source was deployed.

Type: int

Constraints: Read Only, Restart Required

lastTask

Type: weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean reference

Constraints: Read Only, Restart Required

leakedConnectionCount

The number of leaked connections. A leaked connection is a connection that was reserved from the data source but was not returned to the data source by calling `close()`

Type: int

Constraints: Read Only, Restart Required

moduleId

Returns the identifier for this Component. The identifier is unique within the application.

Typical modules will use the URI for their id. Web Modules will return their context-root since the web-uri may not be unique within an EAR.

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

numAvailable

The number of database connections that are currently idle and available to be used by applications in this instance of the data source.

Type: int

Constraints: Read Only, Restart Required

numUnavailable

The number of connections currently in use by applications or being tested in this instance of the data source.

Type: int

Constraints: Read Only, Restart Required

prepStmtCacheAccessCount

The cumulative, running count of the number of times that the statement cache was accessed.

Type: long

Constraints: Read Only, Restart Required

prepStmtCacheAddCount

The cumulative, running count of the number of statements added to the statement cache.

Each connection in the connection pool has its own cache of statements. This number is the sum of the number of statements added to the caches for all connections in the connection pool.

Type: long

Constraints: Read Only, Restart Required

prepStmtCacheCurrentSize

The number of prepared and callable statements currently cached in the statement cache.

Each connection in the connection pool has its own cache of statements. This number is the sum of the number of statements in the caches for all connections in the connection pool.

Type: int

Constraints: Read Only, Restart Required

prepStmtCacheDeleteCount

The cumulative, running count of statements discarded from the cache.

Each connection in the connection pool has its own cache of statements. This number is the sum of the number of statements that were discarded from the caches for all connections in the connection pool.

Type: long

Constraints: Read Only, Restart Required

prepStmtCacheHitCount

The cumulative, running count of the number of times that statements from the cache were used.

Type: int

Constraints: Read Only, Restart Required

prepStmtCacheMissCount

The number of times that a statement request could not be satisfied with a statement from the cache.

Type: int

Constraints: Read Only, Restart Required

properties

The list of properties for a data source that are passed to the JDBC driver when creating database connections.

This is a privileged operation that can only be invoked by an authorized user.

Type: java.util.Properties

Constraints: Read Only, Restart Required

reserveRequestCount

The cumulative, running count of requests for a connection from this data source.

Type: long

Constraints: Read Only, Restart Required

state

The current state of the data source.

Possible states are:

- **Running** - the data source is enabled (deployed and not Suspended). This is the normal state of the data source. This state includes conditions when the database server is not available and the data source is created (creation retry must be enabled) or when all connections have failed connection tests (on creation, on reserve, or periodic testing).
- **Suspended** - the data source has been disabled.
- **Shutdown** - the data source is shutdown and all database connections have been closed.
- **Overloaded** - all resources in pool are in use.
- **Unknown** - the data source state is unknown.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

versionJDBCdriver

The driver class name of the JDBC driver used to create database connections.

Type: string

Constraints: Read Only, Restart Required

waitSecondsHighCount

The highest number of seconds that an application waited for a connection (the longest connection reserve wait time) from this instance of the connection pool since the connection pool was instantiated.

This value is updated when a completed `getConnection` request takes longer to return a connection than any previous request.

Type: int

Constraints: Read Only, Restart Required

waitingForConnectionCurrentCount

The number of connection requests waiting for a database connection.

Type: int

Constraints: Read Only, Restart Required

waitingForConnectionFailureTotal

The cumulative, running count of requests for a connection from this data source that had to wait before getting a connection and eventually failed to get a connection.

Waiting connection requests can fail for a variety of reasons, including waiting for longer than the ConnectionReserveTimeoutSeconds.

Type: long

Constraints: Read Only, Restart Required

waitingForConnectionHighCount

Highest number of application requests concurrently waiting for a connection from this instance of the data source.

Type: int

Constraints: Read Only, Restart Required

waitingForConnectionSuccessTotal

The cumulative, running count of requests for a connection from this data source that had to wait before getting a connection and eventually succeeded in getting a connection.

Type: long

Constraints: Read Only, Restart Required

waitingForConnectionTotal

The cumulative, running count of requests for a connection from this data source that had to wait before getting a connection, including those that eventually got a connection and those that did not get a connection.

Type: long

Constraints: Read Only, Restart Required

weblogic.management.runtime.JDBCDataSourceRuntimeMBean

This class maps to a JDBCDataSource JMO

The properties of the weblogic.management.runtime.JDBCDataSourceRuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean

This class is used for monitoring a WebLogic JDBC Multi Data Source and its associated data sources.

The properties of the `weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean` entity are as follows:

deploymentState

The current deployment state of the module.

A module can be in one and only one of the following states. State can be changed via deployment or administrator console.

- UNPREPARED. State indicating at this module is neither prepared or active.
- PREPARED. State indicating at this module of this application is prepared, but not active. The classes have been loaded and the module has been validated.
- ACTIVATED. State indicating at this module is currently active.
- NEW. State indicating this module has just been created and is being initialized.

Type: int

Constraints: Read Only, Restart Required

maxCapacity

The maximum capacity of this multi data source. The maximum capacity is: - Maximum capacity of first available (not suspended) data source in the list, if the multi data source is using the FAILOVER algorithm (the `FailoverRequestIfBusy` flag is not set). - Sum of maximum capacities of all available (not suspended) data sources, if the multi data source is using other algorithms.

Type: int

Constraints: Read Only, Restart Required

moduleId

Returns the identifier for this Component. The identifier is unique within the application.

Typical modules will use the URI for their id. Web Modules will return their context-root since the web-uri may not be unique within an EAR.

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JDBCPartitionRuntimeMBean

Partition monitoring of WebLogic JDBC resources

The properties of the weblogic.management.runtime.JDBCPartitionRuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JDBCReplayStatisticsRuntimeMBean

This class is used to get replay statics for an Oracle replay datasource aggregated across all connections in the pool.

The properties of the weblogic.management.runtime.JDBCReplayStatisticsRuntimeMBean entity are as follows:

deploymentState

The current deployment state of the module.

A module can be in one and only one of the following states. State can be changed via deployment or administrator console.

- UNPREPARED. State indicating at this module is neither prepared or active.
- PREPARED. State indicating at this module of this application is prepared, but not active. The classes have been loaded and the module has been validated.
- ACTIVATED. State indicating at this module is currently active.
- NEW. State indicating this module has just been created and is being initialized.

Type: int

Constraints: Read Only, Restart Required

failedReplayCount

Obtains the number of replays that failed.

When replay fails, it rethrows the original SQLRecoverableException to the application, with the reason for the failure chained to that original exception. Application can call `getNextException` to retrieve the reason.

Type: long

Constraints: Read Only, Restart Required

moduleId

Returns the identifier for this Component. The identifier is unique within the application.

Typical modules will use the URI for their id. Web Modules will return their context-root since the web-uri may not be unique within an EAR.

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

replayDisablingCount

Obtains the number of times that replay is disabled. When replay is disabled in the middle of a request, the remaining calls in that request are no longer protected by AC. In case an outage strikes one of those remaining calls, no replay will be attempted, and application simply gets an SQLRecoverableException.

Type: long

Constraints: Read Only, Restart Required

successfulReplayCount

Obtains the number of replays that succeeded. Successful replays mask the outages from applications.

Type: long

Constraints: Read Only, Restart Required

totalCalls

Obtains the total number of JDBC calls executed so far.

Type: long

Constraints: Read Only, Restart Required

totalCallsAffectedByOutages

Obtains the number of JDBC calls affected by outages. This includes both local calls and calls that involve roundtrip(s) to the database server.

Type: long

Constraints: Read Only, Restart Required

totalCallsAffectedByOutagesDuringReplay

Obtains the number of JDBC calls affected by outages in the middle of replay. Outages may be cascaded and strike a call multiple times when replay is ongoing. AC automatically reattempts replay when this happens, unless it reaches the maximum retry limit.

Type: long

Constraints: Read Only, Restart Required

totalCallsTriggeringReplay

Obtains the number of JDBC calls that triggered replay. Not all the calls affected by an outage trigger replay, because replay can be disabled for some requests.

Type: long

Constraints: Read Only, Restart Required

totalCompletedRequests

Obtains the total number of completed requests so far.

Type: long

Constraints: Read Only, Restart Required

totalProtectedCalls

Obtains the total number of JDBC calls executed so far that are protected by AC.

Type: long

Constraints: Read Only, Restart Required

totalReplayAttempts

Obtains the number of replay attempts. AC automatically reattempts when replay fails, so this number may exceed the number of JDBC calls that triggered replay.

Type: long

Constraints: Read Only, Restart Required

totalRequests

Obtains the total number of successfully submitted requests so far.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JDBCServiceRuntimeMBean

This class is used for monitoring a WebLogic JDBC service. It maps to a JDBCResource JMO.

The properties of the weblogic.management.runtime.JDBCServiceRuntimeMBean entity are as follows:

healthState

The health state of the JDBC subsystem.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JMSConnectionRuntimeMBean

This class is used for monitoring a WebLogic JMS connection.

The properties of the weblogic.management.runtime.JMSConnectionRuntimeMBean entity are as follows:

clientID

The client ID for this connection.

Type: string

Constraints: Read Only, Restart Required

clientIDPolicy

The ClientIDPolicy on this connection or durable subscriber.

Values are:

- `weblogic.management.configuration.JMSConstants.CLIENT_ID_POLICY_RESTRICTED`: Only one connection that uses this policy exists in a cluster at any given time for a particular `ClientID`
- `weblogic.management.configuration.JMSConstants.CLIENT_ID_POLICY_UNRESTRICTED`: Connections created using this policy can specify any `ClientID`, even when other restricted or unrestricted connections already use the same `ClientID`

Type: string

Constraints: Read Only, Restart Required

hostAddress

The host address of the client JVM as a string.

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

sessionsCurrentCount

The current number of sessions for this connection.

Type: long

Constraints: Read Only, Restart Required

sessionsHighCount

The peak number of sessions for this connection since the last reset.

Type: long

Constraints: Read Only, Restart Required

sessionsTotalCount

The number of sessions on this connection since the last reset.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JMSConsumerRuntimeMBean

This class is used for monitoring a WebLogic JMS consumer.

The properties of the weblogic.management.runtime.JMSConsumerRuntimeMBean entity are as follows:

active

Indicates whether the consumer active. A consumer is active if it has a message listener set up or a synchronous receive in progress.

Type: boolean

Constraints: Read Only, Restart Required

bytesPendingCount

The number of bytes pending (uncommitted and unacknowledged) by this consumer.

Type: long

Constraints: Read Only, Restart Required

bytesReceivedCount

The number of bytes received by this consumer since the last reset.

Type: long

Constraints: Read Only, Restart Required

clientID

The client ID for this connection.

Type: string

Constraints: Read Only, Restart Required

clientIDPolicy

The ClientIDPolicy on this connection or durable subscriber.

Valid values are:

- `weblogic.management.configuration.JMSConstants.CLIENT_ID_POLICY_RESTRICTED`: Only one connection that uses this policy exists in a cluster at any given time for a particular ClientID
- `weblogic.management.configuration.JMSConstants.CLIENT_ID_POLICY_UNRESTRICTED`: Connections created using this policy can specify any ClientID, even when other restricted or unrestricted connections already use the same ClientID

Type: string

Constraints: Read Only, Restart Required

destinationName

The name of the destination for this consumer. In case of a distributed destination, it is the name of the distributed destination, instead of the member destination.

Type: string

Constraints: Read Only, Restart Required

durable

Indicates whether the consumer is durable.

Type: boolean

Constraints: Read Only, Restart Required

memberDestinationName

The name of the destination for this consumer. In case of a distributed destination, it is the name of the member destination.

Type: string

Constraints: Read Only, Restart Required

messagesPendingCount

The number of messages pending (uncommitted and unacknowledged) by this consumer.

Type: long

Constraints: Read Only, Restart Required

messagesReceivedCount

The number of messages received by this consumer since the last reset.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

selector

The selector associated with this consumer, if any.

Type: string

Constraints: Read Only, Restart Required

subscriptionSharingPolicy

The Subscription Sharing Policy on this subscriber.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JMSDestinationRuntimeMBean

This class is used for monitoring a WebLogic JMS destination (topic or queue).

The properties of the `weblogic.management.runtime.JMSDestinationRuntimeMBean` entity are as follows:

bytesCurrentCount

The current number of bytes stored in the destination. This does not include the pending bytes.

Type: long

Constraints: Read Only, Restart Required

bytesHighCount

The peak number of bytes stored in the destination since the last reset.

Type: long

Constraints: Read Only, Restart Required

bytesPendingCount

The number of pending bytes stored in the destination.

Pending bytes are over and above the current number of bytes.

Type: long

Constraints: Read Only, Restart Required

bytesReceivedCount

The number of bytes received in this destination since the last reset.

Type: long

Constraints: Read Only, Restart Required

bytesThresholdTime

The amount of time in the threshold condition since the last reset.

Type: long

Constraints: Read Only, Restart Required

consumersCurrentCount

The current number of consumers accessing this destination.

Type: long

Constraints: Read Only, Restart Required

consumersHighCount

The peak number of consumers accessing this destination since the last reset.

Type: long

Constraints: Read Only, Restart Required

consumersTotalCount

The total number of consumers accessing this destination since the last reset.

Type: long

Constraints: Read Only, Restart Required

consumptionPaused

Indicates the consumption Pause state of the destination.

Type: boolean

Constraints: Read Only, Restart Required

consumptionPausedState

The current consumption pause state of the destination.

Type: string

Constraints: Read Only, Restart Required

destinationType

The destination type, either

`weblogic.management.configuration.JMSConstants.DESTINATION_TYPE_QUEUE` or `weblogic.management.configuration.JMSConstants.DESTINATION_TYPE_TOPIC` depending upon whether the destination is a queue or topic.

Type: string

Constraints: Read Only, Restart Required

insertionPaused

Indicates the InsertionPause state of the destination.

Type: boolean

Constraints: Read Only, Restart Required

insertionPausedState

The current insertion pause state of the destination.

Type: string

Constraints: Read Only, Restart Required

messagesCurrentCount

The current number of messages in the destination. This does not include the pending messages.

Type: long

Constraints: Read Only, Restart Required

messagesDeletedCurrentCount

Returns the number of messages that have been deleted from the destination.

Type: long

Constraints: Read Only, Restart Required

messagesHighCount

The peak number of messages in the destination since the last reset.

Type: long

Constraints: Read Only, Restart Required

messagesMovedCurrentCount

Returns the number of messages that have been moved from the destination.

Type: long

Constraints: Read Only, Restart Required

messagesPendingCount

The number of pending messages in the destination.

Pending messages are over and above the current number of messages. A pending message is one that has either been sent in a transaction and not committed, or that has been received and not committed or acknowledged.

Type: long

Constraints: Read Only, Restart Required

messagesReceivedCount

The number of messages received in this destination since the last reset.

Type: long

Constraints: Read Only, Restart Required

messagesThresholdTime

The amount of time in the threshold condition since the last reset.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

productionPaused

Indicates the ProductionPause state of the destination.

Type: boolean

Constraints: Read Only, Restart Required

productionPausedState

The current production pause state of the destination.

Type: string

Constraints: Read Only, Restart Required

state

The operational state of the destination as a String.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean

This class is used for monitoring a WebLogic JMS durable subscriber.

The properties of the `weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean` entity are as follows:

active

Indicates whether this subscription is being used by a durable subscriber.

Type: boolean

Constraints: Read Only, Restart Required

bytesCurrentCount

The number of bytes received by this durable subscriber.

Type: long

Constraints: Read Only, Restart Required

bytesPendingCount

The number of bytes pending by this durable subscriber.

Type: long

Constraints: Read Only, Restart Required

clientID

A unique client identifier for this durable subscriber.

Note: The client ID is not necessarily equivalent to the WebLogic Server username; that is, a name used to authenticate a user in the WebLogic security realm. You can set the client ID to the WebLogic Server username if it is appropriate for your JMS application.

Type: string

Constraints: Read Only, Restart Required

clientIDPolicy

The policy for the client identifier for this durable subscriber.

Note: The client ID policy is either `Restricted` or `Unrestricted`.

Type: string

Constraints: Read Only, Restart Required

lastMessagesReceivedTime

The time when the last time a subscriber received a message from the subscription. The returned value is a standard java absolute time, which is measured in milliseconds since midnight, January 1, 1970 UTC

This returns the JMS durable subscription boot time if there were no messages that were successfully delivered to any subscriber on this subscription since the subscription was booted. We define the boot time of a durable subscription to be the time the subscription is originally created or recovered during a server reboot or jms migration, which ever is latest.

Type: long

Constraints: Read Only, Restart Required

messagesCurrentCount

The number of messages still available by this durable subscriber.

Type: long

Constraints: Read Only, Restart Required

messagesDeletedCurrentCount

Returns the number of messages that have been deleted from the destination.

Type: long

Constraints: Read Only, Restart Required

messagesHighCount

The peak number of messages for the durable subscriber since the last reset.

Type: long

Constraints: Read Only, Restart Required

messagesMovedCurrentCount

Returns the number of messages that have been moved from the destination.

Type: long

Constraints: Read Only, Restart Required

messagesPendingCount

The number of messages pending (uncommitted and unacknowledged) by this durable subscriber.

Type: long

Constraints: Read Only, Restart Required

messagesReceivedCount

The number of messages received by the durable subscriber since that reset.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

noLocal

Specifies whether this durable subscriber receives local messages that it has published.

To prevent this, set the `noLocal` parameter to `true`

Type: boolean

Constraints: Read Only, Restart Required

selector

The message selector defined for this durable subscriber.

Type: string

Constraints: Read Only, Restart Required

subscribersCurrentCount

The number of subscribers that currently share this subscription.

Type: int

Constraints: Read Only, Restart Required, Has Default Value: 0

subscribersHighCount

The highest number of subscribers that have shared this subscription at the same time since the creation or the last reboot of the subscription, whichever is later.

Type: int

Constraints: Read Only, Restart Required, Has Default Value: 0

subscribersTotalCount

The total number of subscribers that have accessed this subscription since the creation or the last reboot of the subscription, whichever is later.

Type: int

Constraints: Read Only, Restart Required, Has Default Value: 0

subscriptionName

The subscription name for this durable subscriber. This name must be unique for each client ID.

Valid durable subscription names cannot include the following characters: comma ",", equals "=", colon ":", asterisk "*", percent "%", or question mark "?".

Type: string

Constraints: Read Only, Restart Required

subscriptionSharingPolicy

The SubscriptionSharingPolicy on this subscriber.

Type: string

Constraints: Read Only, Restart Required, Has Default Value: Exclusive

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JMSProducerRuntimeMBean

This class is used for monitoring a WebLogic JMS producer.

The properties of the weblogic.management.runtime.JMSProducerRuntimeMBean entity are as follows:

bytesPendingCount

The number of bytes pending (uncommitted and unacknowledged) by this producer.

Type: long

Constraints: Read Only, Restart Required

bytesSentCount

The number of bytes sent by this producer since the last reset.

Type: long

Constraints: Read Only, Restart Required

messagesPendingCount

The number of messages pending (uncommitted and unacknowledged) by this producer.

Type: long

Constraints: Read Only, Restart Required

messagesSentCount

The number of messages sent by this producer since the last reset.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JMSRuntimeMBean

This class is used for monitoring a WebLogic JMS service.

The properties of the weblogic.management.runtime.JMSRuntimeMBean entity are as follows:

JMSServersCurrentCount

The current number of JMS servers that are deployed on this WebLogic Server instance.

Type: long

Constraints: Read Only, Restart Required

JMSServersHighCount

The highest number of JMS servers that were deployed on this WebLogic Server instance since this server was started.

Type: long

Constraints: Read Only, Restart Required

JMSServersTotalCount

The total number of JMS servers that were deployed on this WebLogic Server instance since this server was started.

Type: long

Constraints: Read Only, Restart Required

connectionsCurrentCount

The current number of connections to WebLogic Server server.

Type: long

Constraints: Read Only, Restart Required

connectionsHighCount

The highest number of connections to this WebLogic Server since the last reset.

Type: long

Constraints: Read Only, Restart Required

connectionsTotalCount

The total number of connections made to this WebLogic Server since the last reset.

Type: long

Constraints: Read Only, Restart Required

healthState

The health state of this JMS service.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JMSServerRuntimeMBean

This class is used for monitoring a WebLogic JMS server.

The properties of the weblogic.management.runtime.JMSServerRuntimeMBean entity are as follows:

bytesCurrentCount

The current number of bytes stored on this JMS server.

This number does not include the pending bytes.

Type: long

Constraints: Read Only, Restart Required

bytesHighCount

The peak number of bytes stored in the JMS server since the last reset.

Type: long

Constraints: Read Only, Restart Required

bytesPageableCurrentCount

Return the total number of bytes in all the messages that are currently available to be paged out, but which have not yet been paged out. The JMS server attempts to keep this number smaller than the "MessageBufferSize" parameter.

Type: long

Constraints: Read Only, Restart Required

bytesPagedInTotalCount

Return the total number of bytes that were read from the paging directory since the JMS server was started.

Type: long

Constraints: Read Only, Restart Required

bytesPagedOutTotalCount

Return the total number of bytes that were written to the paging directory since the JMS server was started.

Type: long

Constraints: Read Only, Restart Required

bytesPendingCount

The current number of bytes pending (unacknowledged or uncommitted) stored on this JMS server.

Pending bytes are over and above the current number of bytes.

Type: long

Constraints: Read Only, Restart Required

bytesReceivedCount

The number of bytes received on this JMS server since the last reset.

Type: long

Constraints: Read Only, Restart Required

bytesThresholdTime

The amount of time in the threshold condition since the last reset.

Type: long

Constraints: Read Only, Restart Required

consumptionPaused

Returns the current consumption paused state of the JMSServer as boolean value.

Type: boolean

Constraints: Read Only, Restart Required

consumptionPausedState

Returns the current consumption paused state of the JMSServer as string value.

Type: string

Constraints: Read Only, Restart Required

destinationsCurrentCount

The current number of destinations for this JMS server.

Type: long

Constraints: Read Only, Restart Required

destinationsHighCount

The peak number of destinations on this JMS server since the last reset.

Type: long

Constraints: Read Only, Restart Required

destinationsTotalCount

The number of destinations instantiated on this JMS server since the last reset.

Type: long

Constraints: Read Only, Restart Required

healthState

The health state of this JMS server.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

insertionPaused

Returns the current insertion paused state of the JMSServer as boolean value.

Type: boolean

Constraints: Read Only, Restart Required

insertionPausedState

Returns the current insertion paused state of the JMSServer as string value.

Type: string

Constraints: Read Only, Restart Required

messagesCurrentCount

The current number of messages stored on this JMS server. This number does not include the pending messages.

Type: long

Constraints: Read Only, Restart Required

messagesHighCount

The peak number of messages stored in the JMS server since the last reset.

Type: long

Constraints: Read Only, Restart Required

messagesPageableCurrentCount

Return the number of messages that are currently available for paging in this JMS server but have not yet been paged out. Note that due to internal implementation details, this count may be zero even if "PageableByteCurrentCount" is zero.

Type: int

Constraints: Read Only, Restart Required

messagesPagedInTotalCount

Return the total number of messages that were read from the paging directory since the JMS server was started.

Type: int

Constraints: Read Only, Restart Required

messagesPagedOutTotalCount

Return the total number of messages that were written to the paging directory since the JMS server was started.

Type: int

Constraints: Read Only, Restart Required

messagesPendingCount

The current number of messages pending (unacknowledged or uncommitted) stored on this JMS server.

Pending messages are over and above the current number of messages.

Type: long

Constraints: Read Only, Restart Required

messagesReceivedCount

The number of messages received on this destination since the last reset.

Type: long

Constraints: Read Only, Restart Required

messagesThresholdTime

The amount of time in the threshold condition since the last reset.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

pagingAllocatedIoBufferBytes

See PersistentStoreRuntimeMBean.AllocatedIoBufferBytes

Type: long

Constraints: Read Only, Restart Required

pagingAllocatedWindowBufferBytes

See PersistentStoreRuntimeMBean.AllocatedWindowBufferBytes

Type: long

Constraints: Read Only, Restart Required

pagingPhysicalWriteCount

See PersistentStoreRuntimeMBean.PhysicalWriteCount

Type: long

Constraints: Read Only, Restart Required

pendingTransactions

Returns an array of Xids representing transaction branches that exist on this JMS server in the pending state, i.e. branches that have been prepared by the transaction manager but not yet committed or rolled back.

Type: array of string

Constraints: Read Only, Restart Required

productionPaused

Returns the current production paused state of the JMS Server as boolean value.

Type: boolean

Constraints: Read Only, Restart Required

productionPausedState

Returns the current production paused state of the JMS Server as string value.

Type: string

Constraints: Read Only, Restart Required

sessionPoolsCurrentCount

The current number of session pools instantiated on this JMS server.

Type: long

Constraints: Read Only, Restart Required

sessionPoolsHighCount

The peak number of session pools instantiated on this JMS server since the last reset.

Type: long

Constraints: Read Only, Restart Required

sessionPoolsTotalCount

The number of session pools instantiated on this JMS server since the last reset.

Type: long

Constraints: Read Only, Restart Required

transactions

Returns an array of Xids representing transaction branches that exist on this JMS server in any state.

Type: array of string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JMSSessionPoolRuntimeMBean

This class is used for monitoring a WebLogic JMS session pool.

The properties of the weblogic.management.runtime.JMSSessionPoolRuntimeMBean entity are as follows:

connectionConsumersCurrentCount

The current number of connection consumers for this session pool.

Type: long

Constraints: Read Only, Restart Required

connectionConsumersHighCount

The peak number of simultaneous connection consumers for this session pool.

Type: long

Constraints: Read Only, Restart Required

connectionConsumersTotalCount

The total number of connection consumers made by this session pool since the last reset.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JMSSessionRuntimeMBean

This class is used for monitoring a WebLogic JMS session.

The properties of the weblogic.management.runtime.JMSSessionRuntimeMBean entity are as follows:

acknowledgeMode

The acknowledge mode as one of the following:

- AUTO_ACKNOWLEDGE
- CLIENT_ACKNOWLEDGE
- DUPS_OK_ACKNOWLEDGE
- NO_ACKNOWLEDGE

Type: string

Constraints: Read Only, Restart Required

bytesPendingCount

The number of bytes pending (uncommitted and unacknowledged) for this session.

Type: long

Constraints: Read Only, Restart Required

bytesReceivedCount

The number of bytes received by this session since the last reset.

Type: long

Constraints: Read Only, Restart Required

bytesSentCount

The number of bytes sent by this session since the last reset.

Type: long

Constraints: Read Only, Restart Required

consumersCurrentCount

The current number of consumers for this session.

Type: long

Constraints: Read Only, Restart Required

consumersHighCount

The peak number of consumers for this session since the last reset.

Type: long

Constraints: Read Only, Restart Required

consumersTotalCount

The number of consumers instantiated by this session since the last reset.

Type: long

Constraints: Read Only, Restart Required

messagesPendingCount

The number of messages pending (uncommitted and unacknowledged) for this session.

Type: long

Constraints: Read Only, Restart Required

messagesReceivedCount

The number of messages received by this session since the last reset.

Type: long

Constraints: Read Only, Restart Required

messagesSentCount

The number of bytes sent by this session since the last reset.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

producersCurrentCount

The current number of producers for this session.

Type: long

Constraints: Read Only, Restart Required

producersHighCount

The peak number of producers for this session since the last reset.

Type: long

Constraints: Read Only, Restart Required

producersTotalCount

The number of producers for this session since the last reset.

Type: long

Constraints: Read Only, Restart Required

transacted

Indicates whether the session is transacted.

Type: boolean

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JTAPartitionRuntimeMBean

This interface is used for accessing transaction runtime characteristics within a WebLogic server.

The properties of the weblogic.management.runtime.JTAPartitionRuntimeMBean entity are as follows:

activeTransactionsTotalCount

The number of active transactions on the server.

Type: int

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

registeredNonXAResourceNames

An array of NonXA resource names that are registered with the transaction manager.

Type: array of string

Constraints: Read Only, Restart Required

registeredResourceNames

An array of XA resource names that are registered with the transaction manager.

Type: array of string

Constraints: Read Only, Restart Required

secondsActiveTotalCount

The total number of seconds that transactions were active for all committed transactions.

Type: long

Constraints: Read Only, Restart Required

transactionAbandonedTotalCount

The total number of transactions that were abandoned since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionCommittedTotalCount

The total number of transactions committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionHeuristicsTotalCount

The number of transactions that completed with a heuristic status since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionLLRCommittedTotalCount

The total number of LLR transactions that were committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionNoResourcesCommittedTotalCount

The total number of transactions with no enlisted resources that were committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionOneResourceOnePhaseCommittedTotalCount

The total number of transactions with only one enlisted resource that were one-phase committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionReadOnlyOnePhaseCommittedTotalCount

The total number of transactions with more than one enlisted resource that were one-phase committed due to read-only optimization since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackAppTotalCount

The number of transactions that were rolled back due to an application error.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackResourceTotalCount

The number of transactions that were rolled back due to a resource error.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackSystemTotalCount

The number of transactions that were rolled back due to an internal system error.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackTimeoutTotalCount

The number of transactions that were rolled back due to a timeout expiration.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackTotalCount

The number of transactions that were rolled back since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionTotalCount

The total number of transactions processed. This total includes all committed, rolled back, and heuristic transaction completions since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionTwoPhaseCommittedLoggedTotalCount

The total number of two phase commit transactions that were committed with TLog since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionTwoPhaseCommittedNotLoggedTotalCount

The total number of two phase committed transactions that were committed without TLog since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionTwoPhaseCommittedTotalCount

The total number of transactions with more than one enlisted resource that were two-phase committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JTARecoveryRuntimeMBean

This interface is used for accessing transaction runtime characteristics for recovered transactions that are associated with a particular Transaction Recovery Service.

The properties of the weblogic.management.runtime.JTARecoveryRuntimeMBean entity are as follows:

active

Indicates whether the Transaction Recovery Service is currently activated on this server.

Type: boolean

Constraints: Read Only, Restart Required

initialRecoveredTransactionTotalCount

The total number of transactions that are recovered from the transaction log initially.

Type: int

Constraints: Read Only, Restart Required

initialRecoveredUnloggedTransactionTotalCount

The total number of transactions that are recovered from the no transaction log initially.

Type: int

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

recoveredTransactionCompletionPercent

The percentage of transactions that are recovered from the transaction log initially.

Type: int

Constraints: Read Only, Restart Required

recoveredUnloggedTransactionCompletionPercent

The percentage of transactions that are recovered from the no transaction log initially.

Type: int

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JTARuntimeMBean

This interface is used for accessing transaction runtime characteristics within a WebLogic server.

The properties of the weblogic.management.runtime.JTARuntimeMBean entity are as follows:

activeTransactionsTotalCount

The number of active transactions on the server.

Type: int

Constraints: Read Only, Restart Required

healthState

The health state of the JTA subsystem. for state values.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

registeredNonXAResourceNames

An array of NonXA resource names that are registered with the transaction manager.

Type: array of string

Constraints: Read Only, Restart Required

registeredResourceNames

An array of XA resource names that are registered with the transaction manager.

Type: array of string

Constraints: Read Only, Restart Required

secondsActiveTotalCount

The total number of seconds that transactions were active for all committed transactions.

Type: long

Constraints: Read Only, Restart Required

transactionAbandonedTotalCount

The total number of transactions that were abandoned since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionCommittedTotalCount

The total number of transactions committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionHeuristicsTotalCount

The number of transactions that completed with a heuristic status since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionLLRCommittedTotalCount

The total number of LLR transactions that were committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionNoResourcesCommittedTotalCount

The total number of transactions with no enlisted resources that were committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionOneResourceOnePhaseCommittedTotalCount

The total number of transactions with only one enlisted resource that were one-phase committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionReadOnlyOnePhaseCommittedTotalCount

The total number of transactions with more than one enlisted resource that were one-phase committed due to read-only optimization since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackAppTotalCount

The number of transactions that were rolled back due to an application error.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackResourceTotalCount

The number of transactions that were rolled back due to a resource error.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackSystemTotalCount

The number of transactions that were rolled back due to an internal system error.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackTimeoutTotalCount

The number of transactions that were rolled back due to a timeout expiration.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackTotalCount

The number of transactions that were rolled back since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionTotalCount

The total number of transactions processed. This total includes all committed, rolled back, and heuristic transaction completions since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionTwoPhaseCommittedLoggedTotalCount

The total number of two phase commit transactions that were committed with TLog since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionTwoPhaseCommittedNotLoggedTotalCount

The total number of two phase committed transactions that were committed without TLog since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionTwoPhaseCommittedTotalCount

The total number of transactions with more than one enlisted resource that were two-phase committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JVMRuntimeMBean

Provides methods for retrieving information about the Java Virtual Machine (JVM) within with the current server instance is running. You cannot change the JVM's operating parameters while the JVM is active. Instead, use the startup options that are described in the JVM's documentation.

The WebLogic JVM contains only one of these Runtime MBeans:

- If the JVM is an instance of a JRockit JDK, then the JVM contains `JRockitRuntimeMBean`
- Otherwise, it contains the `JVMRuntimeMBean`

The properties of the `weblogic.management.runtime.JVMRuntimeMBean` entity are as follows:

OSName

Returns the operating system on which the JVM is running.

The operating system on which the JVM is running.

Type: string

Constraints: Read Only, Restart Required

OSVersion

The version of the operating system on which the JVM is running.

Type: string

Constraints: Read Only, Restart Required

heapFreeCurrent

The current amount of memory (in bytes) that is available in the JVM heap.

Type: long

Constraints: Read Only, Restart Required

heapFreePercent

Percentage of the maximum memory that is free.

Type: int

Constraints: Read Only, Restart Required

heapSizeCurrent

The current size (in bytes) of the JVM heap.

Type: long

Constraints: Read Only, Restart Required

heapSizeMax

The maximum free memory configured for this JVM.

Type: long

Constraints: Read Only, Restart Required

javaVMVendor

Returns the vendor of the JVM.

The vendor of the JVM that this server runs.

system property java.vm.vendor is returned

Type: string

Constraints: Read Only, Restart Required

javaVendor

Returns the vendor of Java.

The vendor of Java that this server runs.

Type: string

Constraints: Read Only, Restart Required

javaVersion

The Java version of the JVM.

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

threadStackDump

JVM thread dump. Thread dump is available only on 1.5 VM

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

uptime

The number of milliseconds that the Virtual Machine has been running.

Type: long

Constraints: Read Only, Restart Required

weblogic.management.runtime.JobRuntimeMBean

RuntimeMBean that provides information about a particular job.

The properties of the weblogic.management.runtime.JobRuntimeMBean entity are as follows:

ID

The unique ID corresponding to this job

Type: string

Constraints: Read Only, Restart Required

description

Get the description of the submitted `commonj.timers.TimerListener`. Returns `commonj.timers.TimerListener#toString`

Type: string

Constraints: Read Only, Restart Required

lastLocalExecutionTime

Returns the most recent execution time of this job in the local server. Note that multiple executions of the same job are load-balanced across the cluster and this time indicates when the job was last executed locally.

Type: long

Constraints: Read Only, Restart Required

localExecutionCount

Returns the number of times this job was executed locally. Job executions are load-balanced across the cluster. This count specifies the number of executions of the job in the local server.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

period

Returns the specified periodicity of this job

Type: long

Constraints: Read Only, Restart Required

state

Returns the state of the task. A Job is either in running state or in cancelled state

Type: string

Constraints: Read Only, Restart Required

timeout

Returns when the job will be executed next

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JobSchedulerRuntimeMBean

RuntimeMBean that provides information about jobs scheduled with the Job Scheduler.

The properties of the weblogic.management.runtime.JobSchedulerRuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JoltConnectionPoolRuntimeMBean

This class is used for monitoring a WebLogic Jolt Connection Pool

The properties of the weblogic.management.runtime.JoltConnectionPoolRuntimeMBean entity are as follows:

maxCapacity

The maximum connections configured for this Jolt pool.

Type: int

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

poolName

The configured name of this Jolt pool.

Type: string

Constraints: Read Only, Restart Required

poolState

The pool state as one of 'Active' 'Suspended'.

Type: string

Constraints: Read Only, Restart Required

securityContextPropagation

Indicates whether the security context is propagated.

Type: boolean

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JoltConnectionRuntimeMBean

This class is used for monitoring individual WebLogic Jolt connections

The properties of the weblogic.management.runtime.JoltConnectionRuntimeMBean entity are as follows:

address

The connection Address.

Type: string

Constraints: Read Only, Restart Required

alive

The Connection Alive indicator.

Type: boolean

Constraints: Read Only, Restart Required

errorCount

The Request Error Count.

Type: int

Constraints: Read Only, Restart Required

inTransaction

The Connection in Transaction indicator.

Type: boolean

Constraints: Read Only, Restart Required

lastAccessTime

The Last Access Date and Time.

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

pendingRequestCount

The Pending Request Count.

Type: int

Constraints: Read Only, Restart Required

requestCount

The Request Count.

Type: int

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JoltConnectionServiceRuntimeMBean

This class is used for monitoring a WebLogic Jolt component

The properties of the weblogic.management.runtime.JoltConnectionServiceRuntimeMBean entity are as follows:

connectionPoolCount

The number of configured Jolt connection pools.

Type: int

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.LibraryRuntimeMBean

RuntimeMBean for library deployments.

The properties of the weblogic.management.runtime.LibraryRuntimeMBean entity are as follows:

implementationVersion

Returns the library implementation version. If not set, this value is null.

Type: string

Constraints: Read Only, Restart Required

libraryIdentifier

Returns the library identifier.

The library identifier uniquely identifies this library version across all versions of all deployed applications and deployed libraries. If the library is not versioned, the library identifier is the same as the library name.

Type: string

Constraints: Read Only, Restart Required

libraryName

Returns the library name.

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

partitionName

The library's partition.

Returns the partition to which this library is deployed.

Type: string

Constraints: Read Only, Restart Required

referenced

Returns true if this library is referenced by one or more referencers. Typically, a library referencer is a deployed application.

Type: boolean

Constraints: Read Only, Restart Required

specificationVersion

Returns the library specification version. If not set, this value is null.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.LogBroadcasterRuntimeMBean

This MBean broadcasts JMX notifications for each log message generated in the local WLS server. There is exactly one implementation of this MBean in each WLS server. JMX listeners can register to this MBean and receive log notifications. The type of the notification generated is `WebLogicLogNotification`

The properties of the `weblogic.management.runtime.LogBroadcasterRuntimeMBean` entity are as follows:

messagesLogged

The total number of log messages that this WebLogic Server instance has generated.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.LogRuntimeMBean

This interface defines the control operations for a log in the WebLogic Server.

The properties of the weblogic.management.runtime.LogRuntimeMBean entity are as follows:

logFileStreamOpened

Gets the opened state of the log file stream represented by this instance.

Type: boolean

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.MANAsyncReplicationRuntimeMBean

RuntimeMBean for MAN Asynchronous Replication

The properties of the weblogic.management.runtime.MANAsyncReplicationRuntimeMBean entity are as follows:

activeServersInRemoteCluster

Type: array of string

Constraints: Read Only, Restart Required

detailedSecondariesDistribution

Provides the names of the remote servers (such as myserver) for which the local server is hosting secondary objects. The name is appended with a number to indicate the number of secondaries hosted on behalf of that server.

Type: array of string

Constraints: Read Only, Restart Required

lastSessionsFlushTime

The last time the sessions were flushed, in milliseconds since midnight, January 1, 1970 UTC

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

primaryCount

Provides the number of object that the local server hosts as primaries.

Answer the number of object that the local server hosts as primaries.

Type: long

Constraints: Read Only, Restart Required

remoteClusterReachable

Answer if the remote cluster is reachable or not.

Type: boolean

Constraints: Read Only, Restart Required

secondaryCount

Answer the number of object that the local server hosts as secondaries.

Type: long

Constraints: Read Only, Restart Required

secondaryServerDetails

Type: string

Constraints: Read Only, Restart Required

secondaryServerName

Answer the name of the secondary server

Type: string

Constraints: Read Only, Restart Required

sessionsWaitingForFlushCount

Number of sessions which are waiting to be flushed.

Type: int

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.MANReplicationRuntimeMBean

RuntimeMBean for MAN Replication

The properties of the weblogic.management.runtime.MANReplicationRuntimeMBean entity are as follows:

activeServersInRemoteCluster

Type: array of string

Constraints: Read Only, Restart Required

detailedSecondariesDistribution

Provides the names of the remote servers (such as myserver) for which the local server is hosting secondary objects. The name is appended with a number to indicate the number of secondaries hosted on behalf of that server.

Type: array of string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

primaryCount

Provides the number of object that the local server hosts as primaries.

Answer the number of object that the local server hosts as primaries.

Type: long

Constraints: Read Only, Restart Required

remoteClusterReachable

Answer if the remote cluster is reachable or not.

Type: boolean

Constraints: Read Only, Restart Required

secondaryCount

Answer the number of object that the local server hosts as secondaries.

Type: long

Constraints: Read Only, Restart Required

secondaryServerDetails

Type: string

Constraints: Read Only, Restart Required

secondaryServerName

Answer the name of the secondary server

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.MailSessionRuntimeMBean

RuntimeMBean for JavaMail Sessions

The properties of the weblogic.management.runtime.MailSessionRuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean

ManagedExecutorService Runtime information. It can be the information of a partition level MES, an application level MES or a regular JSR236 MES.

The properties of the weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean entity are as follows:

applicationName

Get the name of the application this ManagedExecutor is associated with

Type: string

Constraints: Read Only, Restart Required

completedLongRunningRequests

Total number of long running tasks which is successfully completed.

Type: long

Constraints: Read Only, Restart Required

completedShortRunningRequests

Total number of short running tasks which is successfully completed.

Type: long

Constraints: Read Only, Restart Required

failedRequests

Total number of tasks which terminated abnormally by throwing exception, including both long and short term tasks.

Type: long

Constraints: Read Only, Restart Required

moduleName

Get the name of the module this ManagedExecutor is associated with

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

partitionName

Get the name of the partition this ManagedExecutor is associated with

Type: string

Constraints: Read Only, Restart Required

rejectedLongRunningRequests

Total number of long running tasks rejected by max-concurrent-long-running-requests

Type: long

Constraints: Read Only, Restart Required

rejectedShortRunningRequests

Total number of short running tasks rejected by workmanager overload policy

Type: long

Constraints: Read Only, Restart Required

runningLongRunningRequests

Total number of long running tasks which is currently running.

Type: long

Constraints: Read Only, Restart Required

submittedShortRunningRequests

Total number of submitted short running tasks

Type: long

Constraints: Read Only, Restart Required

submittedLongRunningRequests

Total number of submitted long running tasks

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean

ManagedScheduledExecutorService Runtime information. It can be the information of a partition level MSES, an application level MSES or a regular JSR236 MSES.

The properties of the weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean entity are as follows:

applicationName

Get the name of the application this ManagedExecutor is associated with

Type: string

Constraints: Read Only, Restart Required

completedLongRunningRequests

Total number of long running tasks which is successfully completed.

Type: long

Constraints: Read Only, Restart Required

completedShortRunningRequests

Total number of short running tasks which is successfully completed.

Type: long

Constraints: Read Only, Restart Required

failedRequests

Total number of tasks which terminated abnormally by throwing exception, including both long and short term tasks.

Type: long

Constraints: Read Only, Restart Required

moduleName

Get the name of the module this ManagedExecutor is associated with

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

partitionName

Get the name of the partition this ManagedExecutor is associated with

Type: string

Constraints: Read Only, Restart Required

rejectedLongRunningRequests

Total number of long running tasks rejected by max-concurrent-long-running-requests

Type: long

Constraints: Read Only, Restart Required

rejectedShortRunningRequests

Total number of short running tasks rejected by workmanager overload policy

Type: long

Constraints: Read Only, Restart Required

runningLongRunningRequests

Total number of long running tasks which is currently running.

Type: long

Constraints: Read Only, Restart Required

submittedShortRunningRequests

Total number of submitted short running tasks

Type: long

Constraints: Read Only, Restart Required

submittedLongRunningRequests

Total number of submitted long running tasks

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean

ManagedThreadFactory Runtime information. It can be the information of a partition level MTF, an application level MTF or a regular JSR236 MTF.

The properties of the weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean entity are as follows:

applicationName

Get the name of the application this ManagedThreadFactory is associated with

Type: string

Constraints: Read Only, Restart Required

completedThreadsCount

The number of completed threads.

Type: long

Constraints: Read Only, Restart Required

moduleName

Get the name of the module this ManagedThreadFactory is associated with

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

partitionName

Get the name of the partition this ManagedThreadFactory is associated with

Type: string

Constraints: Read Only, Restart Required

rejectedNewThreadRequests

The number of newThread method invocations that have been rejected because the limit of running threads was exceeded.

Type: long

Constraints: Read Only, Restart Required

runningThreadsCount

The number of running threads.

Type: int

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean

Runtime information for MaxThreadsConstraint

The properties of the weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity are as follows:

configuredCount

The configured count, or maximum concurrency value.

Type: int

Constraints: Read Only, Restart Required

count

The current maximum concurrency value. This could be different from the configured value as Resource Consumption Management could dynamically reduce the allowed maximum concurrency value based on configured RCM policies and actual thread usage by the partition

Type: int

Constraints: Read Only, Restart Required

deferredRequests

Number of requests that are denied a thread for execution because the constraint is exceeded.

Type: int

Constraints: Read Only, Restart Required

executingRequests

Number of requests that are currently executing.

Type: int

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.MessageDrivenEJBRuntimeMBean

This interface contains accessor methods for all EJB runtime information collected for a Message Driven Bean.

The properties of the `weblogic.management.runtime.MessageDrivenEJBRuntimeMBean` entity are as follows:

EJBName

Provides the name for this EJB as defined in the `javax.ejb.EJB` annotation, or the `ejb-name` when * using the `ejb-jar.xml` deployment descriptor.

Type: string

Constraints: Read Only, Restart Required

JMSConnectionAlive

Provides information about whether the Message Driven Bean is currently connected to the JMS destination it is mapped to.

Returns whether the Message Driven Bean is currently connected to the JMS destination it is mapped to.

Type: boolean

Constraints: Read Only, Restart Required

MDBStatus

Provides the Message Driven Bean status. MDBStatus is used after the MDB is connected to the destination. MDBStatus can be Running or Suspended.

Type: string

Constraints: Read Only, Restart Required

connectionStatus

Provides the connection status for the Message Driven Bean. ConnectionStatus can be Connected or Reconnecting.

Type: string

Constraints: Read Only, Restart Required

destination

Provides a count of the Message Driven Bean destination

Type: string

Constraints: Read Only, Restart Required

healthState

The health state of this MDB.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

jmsClientID

Provides a count of the Message Driven Bean jmsClientID

Type: string

Constraints: Read Only, Restart Required

lastException

Provides the last exception this MDB encountered

Type: java.lang.Throwable

Constraints: Read Only, Restart Required

lastExceptionAsString

Provides the last exception as String this MDB encountered

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

processedMessageCount

Provides a count of the total number of messages processed by this Message Driven Bean.

Type: long

Constraints: Read Only, Restart Required

suspendCount

Provides a count of the total number of times this MDB is suspended by the user or the EJB container.

Type: int

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.MessagingBridgeRuntimeMBean

This class is used for monitoring a WebLogic messaging bridge.

The properties of the weblogic.management.runtime.MessagingBridgeRuntimeMBean entity are as follows:

description

The reason, if the messaging bridge is not running.

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

state

The state of the messaging bridge.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.MigrationDataRuntimeMBean

Runtime information about one past or ongoing migration.

The properties of the weblogic.management.runtime.MigrationDataRuntimeMBean entity are as follows:

clusterMasterName

Name of the server that acted as the cluster master for this migration.

Type: string

Constraints: Read Only, Restart Required

clusterName

Name of the server that acted as the cluster master for this migration.

Type: string

Constraints: Read Only, Restart Required

machineMigratedFrom

Machine from which the server was migrated from

Type: string

Constraints: Read Only, Restart Required

machineMigratedTo

Machine to which the server was migrated to or is in the process of being migrated to.

Type: string

Constraints: Read Only, Restart Required

machinesAttempted

Get all the machines attempted for migration.

Type: array of string

Constraints: Read Only, Restart Required

migrationEndTime

End time of migration

Type: long

Constraints: Read Only, Restart Required

migrationStartTime

Start time of migration

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

serverName

Name of the server migrated

Type: string

Constraints: Read Only, Restart Required

status

Name of the server migrated

Type: int

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.MinThreadsConstraintRuntimeMBean

Monitoring information for MinThreadsConstraint

The properties of the weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity are as follows:

completedRequests

Completed request count.

Type: long

Constraints: Read Only, Restart Required

configuredCount

The configured count, or minimum concurrency value.

Type: int

Constraints: Read Only, Restart Required

count

The current minimum concurrency value. This could be different from the configured value as Resource Consumption Management could dynamically reduce the allowed minimum concurrency value based on configured RCM policies and actual thread usage by the partition

Type: int

Constraints: Read Only, Restart Required

currentWaitTime

The last measured time a request had to wait for a thread. Only requests whose execution is needed to satisfy the constraint are considered.

Type: long

Constraints: Read Only, Restart Required

executingRequests

Number of requests that are currently executing.

Type: int

Constraints: Read Only, Restart Required

maxWaitTime

The max time a request had to wait for a thread. Only requests whose execution is needed to satisfy the constraint are considered.

Type: long

Constraints: Read Only, Restart Required

mustRunCount

Number of requests that must be executed to satisfy the constraint.

Type: int

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

outOfOrderExecutionCount

Number of requests executed out of turn to satisfy this constraint.

Type: long

Constraints: Read Only, Restart Required

partitionLimitReached

Whether the partition-level minimum threads constraint limit has reached, which could cause the number of executing requests to be less than the configured value in this minimum threads constraint.

Type: boolean

Constraints: Read Only, Restart Required

pendingRequests

Pending requests that are waiting for an available thread.

Type: int

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.NonXAResourceRuntimeMBean

This represents runtime statistical information about a NonXAResource

The properties of the weblogic.management.runtime.NonXAResourceRuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

nonXAResourceName

Returns the resource name.

Type: string

Constraints: Read Only, Restart Required

transactionCommittedTotalCount

The total number of transactions committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionHeuristicsTotalCount

The number of transactions that completed with a heuristic status since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackTotalCount

The number of transactions that were rolled back since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionTotalCount

The total number of transactions processed. This total includes all committed, rolled back, and heuristic transaction completions since the server was started.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.PSAssemblyRuntimeMBean

This interface is used for accessing a WebLogic path service entity

The properties of the weblogic.management.runtime.PSAssemblyRuntimeMBean entity are as follows:

mapEntries

Returns all entries in a persistent map's assembly.

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.PartitionFairShareRuntimeMBean

Monitoring information for PartitionFairShare

The properties of the weblogic.management.runtime.PartitionFairShareRuntimeMBean entity are as follows:

configuredFairShare

The configured fair share value.

Type: int

Constraints: Read Only, Restart Required

fairShare

The current fair share value. This could be different from the configured value as Resource Consumption Management could dynamically adjust the actual fair share value based on configured RCM policies and actual thread usage by the partition

Type: int

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

partitionAdjuster

The multiplier to be used to adjust the priority of requests from the partition in the request queue.

Type: double

Constraints: Read Only, Restart Required

threadUse

Total amount of thread use time in milliseconds used by the partition during the past period.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.PartitionMinThreadsConstraintCapRuntimeMBean

Monitoring information for PartitionMinThreadsConstraint

The properties of the weblogic.management.runtime.PartitionMinThreadsConstraintCapRuntimeMBean entity are as follows:

executingRequests

Number of requests that are currently executing.

Type: int

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

sumMinThreadsConstraints

Sum of all configured minimum threads constraints in the partition. This is the number of threads that is needed in order to satisfy all configured minimum threads constraints in the partition if all of them have more than that amount of concurrent work requests.

Type: int

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.PartitionResourceMetricsRuntimeMBean

The runtime MBean interface for partition specific resource consumption metrics. The resource meters are added lazily for a partition. Therefore, the first time these metrics are queried, it might return zero values. Subsequent gets would return non-zero values based on the resource consumption. These metrics are applicable in the context of a partition since either server start or partition creation/restart, whichever was later.

The properties of the weblogic.management.runtime.PartitionResourceMetricsRuntimeMBean entity are as follows:

RCMMetricsDataAvailable

Checks whether RCM metrics data is available for this partition.

Type: boolean

Constraints: Read Only, Restart Required

allocatedMemory

Total allocated memory in bytes for the partition. This metric value increases monotonically over time, it never decreases. Retained memory should be used to get current net values.

Type: long

Constraints: Read Only, Restart Required

cpuTimeNanos

Total CPU time spent measured in nanoseconds in the context of a partition.

Type: long

Constraints: Read Only, Restart Required

cpuUtilizationHistoricalData

Returns a snapshot of the historical data for CPU usage for the partition. CPU Utilization percentage indicates the percentage of CPU utilized by a partition with respect to available CPU to Weblogic Server. Data is returned as a two-dimensional array for the CPU usage scoped to the partition over time. Each item in the array contains a tuple of [timestamp (long), cpuUsage(long)] values.

Type: array of array of long

Constraints: Read Only, Restart Required

currentOpenFileCount

Number of files currently open in the context of a partition.

Type: long

Constraints: Read Only, Restart Required

currentOpenFileDescriptorCount

Number of file descriptors currently open in the context of a partition.

Type: long

Constraints: Read Only, Restart Required

currentOpenSocketCount

Number of sockets currently open in the context of a partition.

Type: long

Constraints: Read Only, Restart Required

fileBytesRead

Total number of file bytes read in the context of a partition.

Type: long

Constraints: Read Only, Restart Required

fileBytesWritten

Total number of file bytes written in the context of a partition.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

networkBytesRead

Total number of bytes read from sockets for a partition.

Type: long

Constraints: Read Only, Restart Required

networkBytesWritten

Total number of bytes written to sockets for a partition.

Type: long

Constraints: Read Only, Restart Required

retainedHeapHistoricalData

Returns a snapshot of the historical data for retained heap memory usage for the partition. Data is returned as a two-dimensional array for the usage of retained heap scoped to the partition over time. Each item in the array contains a tuple of [timestamp(long), retainedHeap(long)] values.

Type: array of array of long

Constraints: Read Only, Restart Required

threadCount

Number of threads currently assigned to the partition.

Type: long

Constraints: Read Only, Restart Required

totalOpenedFileCount

Total number of files opened in the context of a partition.

Type: long

Constraints: Read Only, Restart Required

totalOpenedFileDescriptorCount

Total number of file descriptors opened in the context of a partition.

Type: long

Constraints: Read Only, Restart Required

totalOpenedSocketCount

Total number of sockets opened in the context of a partition.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.PartitionRuntimeMBean

Partition Runtime information.

The properties of the weblogic.management.runtime.PartitionRuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

overallHealthState

The aggregate health state of the partition as reported by components within the partition

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

partitionID

Partition ID for this partition.

Type: string

Constraints: Read Only, Restart Required

restartRequired

Indicates whether the partition must be restarted in order to activate configuration changes.

Type: boolean

Constraints: Read Only, Restart Required

serverName

The server associated with this configuration.

Type: string

Constraints: Read Only, Restart Required

state

The current state of the partition runtime MBean

Type: string

Constraints: Read Only, Restart Required

subsystemHealthStates

An array of health states for major subsystems in the partition.

Type: array of weblogic.health.HealthState

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.PartitionWorkManagerRuntimeMBean

Monitoring information for PartitionWorkManager

The properties of the weblogic.management.runtime.PartitionWorkManagerRuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

overloadRejectedRequestsCount

Number of requests rejected due to configured Shared Capacity for work managers have been reached.

Type: int

Constraints: Read Only, Restart Required

pendingUserRequestCount

The number of pending user requests in the priority queue. The priority queue contains requests from internal subsystems and users. This is just the count of all user requests.

Type: int

Constraints: Read Only, Restart Required

sharedCapacityForWorkManagers

Maximum amount of requests that can be accepted in the priority queue. Note that a request with higher priority will be accepted in place of a lower priority request already in the queue even after the threshold is reached. The lower priority request is kept waiting in the queue till all high priority requests are executed. Also note that further enqueues of the low priority requests are rejected right away.

Type: int

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.PathServiceRuntimeMBean

This interface is used for accessing a WebLogic path service entity

The properties of the weblogic.management.runtime.PathServiceRuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.PersistenceUnitRuntimeMBean

This class is used for monitoring JPA specific runtime stats. Base class for all runtime mbeans that provide status of running modules.

The properties of the weblogic.management.runtime.PersistenceUnitRuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

persistenceUnitName

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean

This class is used for monitoring a Persistent Store Connection.

The properties of the weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean entity are as follows:

createCount

Number of create requests issued by this connection.

Type: long

Constraints: Read Only, Restart Required

deleteCount

Number of delete requests issued by this connection.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

objectCount

Number of objects contained in the connection.

Type: long

Constraints: Read Only, Restart Required

readCount

Number of read requests issued by this connection, including requests that occur during store initialization.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

updateCount

Number of update requests issued by this connection.

Type: long

Constraints: Read Only, Restart Required

weblogic.management.runtime.PersistentStoreRuntimeMBean

This class is used for monitoring a Persistent Store.

The properties of the weblogic.management.runtime.PersistentStoreRuntimeMBean entity are as follows:

allocatedIoBufferBytes

The amount of off-heap (native) memory, in bytes, reserved for file store use.

When applicable, this is a multiple of the file store configurable attribute `IOBufferSize`. Applies to synchronous write policies `Direct-Write` and `Cache-Flush` policies

Type: long

Constraints: Read Only, Restart Required

allocatedWindowBufferBytes

The amount of off-heap (native) memory, in bytes, reserved for file store window buffer use.

Applies to synchronous write policies `Direct-Write-With-Cache` and `Disabled` but only when the native `wfileio` library is loaded. See file store configurable attribute `MaxWindowBufferSize` for more information

Type: long

Constraints: Read Only, Restart Required

createCount

Number of create requests issued by this store.

Type: long

Constraints: Read Only, Restart Required

deleteCount

Number of delete requests issued by this store.

Type: long

Constraints: Read Only, Restart Required

healthState

Implement the HealthFeedback interface by returning the health state of this store.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

objectCount

Number of objects contained in the store.

Type: long

Constraints: Read Only, Restart Required

physicalWriteCount

Number of times the store flushed its data to durable storage.

Type: long

Constraints: Read Only, Restart Required

readCount

Number of read requests issued by this store, including requests that occur during store initialization.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

updateCount

Number of update requests issued by this store.

Type: long

Constraints: Read Only, Restart Required

weblogic.management.runtime.QueryCacheRuntimeMBean

This interface contains accessor methods for all query cache runtime information collected for an EJB. The cache miss counts need some explaining. A query-cache miss can occur due to one of the following reasons:

- The query result was not found in the query-cache
- The query result has timed out
- A bean which satisfies the query was not found in the entity cache
- A query with relationship-caching turned on did not find the related-beans query result
- A query which loads multiple EJBs could not load one or more of them

To better aid tuning, there are separate counters provided for each of the last four of the above causes. The fifth counter is a total cache miss counter. This counter takes into account all five causes of a cache miss.

The properties of the `weblogic.management.runtime.QueryCacheRuntimeMBean` entity are as follows:

cacheAccessCount

Provides a count of the number of accesses of the query cache for this EJB.

Returns the number of accesses of the query cache for this EJB.

Type: long

Constraints: Read Only, Restart Required

cacheHitCount

Provides a count of the number of cache hits of the query cache for this EJB.

Returns the number of cache hits of the query cache for this EJB.

Type: long

Constraints: Read Only, Restart Required

cacheMissByBeanEvictionCount

Provides a count of the number of cache misses of the query cache for this EJB because corresponding beans were not found in the entity cache.

Returns the number of times a cache miss occurred for this EJB because corresponding beans were not found in the entity cache.

Type: long

Constraints: Read Only, Restart Required

cacheMissByDependentQueryMissCount

Provides a count of the number of cache misses of the query cache for this EJB because a dependent query was not found in another EJB's query cache.

Returns the number of times a cache miss occurred for this EJB because a dependent query was not found in another EJB's query cache.

Type: long

Constraints: Read Only, Restart Required

cacheMissByRelatedQueryMissCount

Provides a count of the number of cache misses of the query cache for this EJB because a related query was not found in another EJB's query cache.

Returns the number of times a cache miss occurred for this EJB because a related query was not found in another EJB's query cache.

Type: long

Constraints: Read Only, Restart Required

cacheMissByTimeoutCount

Provides a count of the number of cache misses of the query cache for this EJB due to query results timing out.

Returns the number of cache misses due to query result timeout for this EJB.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

totalCacheMissCount

Provides a count of the total number of cache misses of the query cache for this EJB.

Returns the total number of cache misses of the query cache for this EJB.

Type: long

Constraints: Read Only, Restart Required

totalCachedQueriesCount

Provides a count of the total number of query results for this EJB currently in the query cache.

Returns the total number of query results for this EJB currently in the EJB cache.

Type: int

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.RealmRuntimeMBean

This class is used to monitor and manage per security realm runtime information.

The properties of the weblogic.management.runtime.RealmRuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.RequestClassRuntimeMBean

RequestClassRuntimeMBean presents runtime information about RequestClasses. A request class represents a class of work. Work using the same request class shares the same priority.

The properties of the weblogic.management.runtime.RequestClassRuntimeMBean entity are as follows:

completedCount

Total number of completions since server start

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

pendingRequestCount

Number of requests waiting for a thread to become available.

Type: int

Constraints: Read Only, Restart Required

requestClassType

Returns the type of RequestClass. Either FAIR_SHARE or RESPONSE_TIME or CONTEXT

Type: string

Constraints: Read Only, Restart Required

totalThreadUse

Total amount of thread use time in millisecond's used by the request class since server start.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

virtualTimeIncrement

Current priority of the request class. The priority is relative to other request class priorities. The priority is calculated dynamically frequently and can change.

Type: long

Constraints: Read Only, Restart Required

weblogic.management.runtime.ResourceManagerRuntimeMBean

The `ResourceManagerRuntimeMBean` holds runtime information about a Resource Manager that has been assigned to the current Domain Partition. The `ResourceManagerRuntimeMBean` is used for retrieving the runtime state (information about policy evaluation, current resource usage, recourse actions executed) of configured resource management policies established for the current Partition by a system administrator in the current server instance.

The properties of the `weblogic.management.runtime.ResourceManagerRuntimeMBean` entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ResourceRuntimeMBean

The `ResourceRuntimeMBean` holds runtime state about the policy evaluations that have been performed for a Resource type in the current Domain Partition in the current server instance.

The properties of the `weblogic.management.runtime.ResourceRuntimeMBean` entity are as follows:

name

The name of the policy defined for this resource as configured in the `ResourceManagerMBean` for this MBean's resource type `getResourceType()`.

Type: string

Constraints: Read Only, Restart Required

resourceType

The resource type associated with this MBean.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

usage

The current resource utilization of a Resource by the current Domain Partition, in the current Server instance.

To track or monitor resource consumption for a Domain Partition without creating resource consumption management policies, see `weblogic.management.runtime.PartitionResourceMetricsRuntimeMBean`.

Type: long

Constraints: Read Only, Restart Required

weblogic.management.runtime.RuntimeMBean

The tagging interface for all runtime MBeans.

The properties of the `weblogic.management.runtime.RuntimeMBean` entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.SAFAgentRuntimeMBean

This class is used for monitoring a WebLogic SAF agent.

The properties of the `weblogic.management.runtime.SAFAgentRuntimeMBean` entity are as follows:

bytesCurrentCount

Returns the current number of bytes. This number does not include the pending bytes.

Type: long

Constraints: Read Only, Restart Required

bytesHighCount

Returns the peak number of bytes since the last reset.

Type: long

Constraints: Read Only, Restart Required

bytesPendingCount

Returns the number of pending bytes. Pending bytes are over and above the current number of bytes.

Type: long

Constraints: Read Only, Restart Required

bytesReceivedCount

The number of bytes received since the last reset.

Type: long

Constraints: Read Only, Restart Required

bytesThresholdTime

Returns the amount of time in the threshold condition since the last reset.

Type: long

Constraints: Read Only, Restart Required

conversationsCurrentCount

Returns the current number of conversations

Type: long

Constraints: Read Only, Restart Required

conversationsHighCount

The peak number of conversations since the last reset.

Type: long

Constraints: Read Only, Restart Required

conversationsTotalCount

The total number of conversations since the last reset.

Type: long

Constraints: Read Only, Restart Required

failedMessagesTotal

Returns the total number of messages that have failed to be forwarded since the last reset.

Type: long

Constraints: Read Only, Restart Required

healthState

The health state of this JMS server.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

messagesCurrentCount

Returns the current number of messages. This number includes the pending messages.

Type: long

Constraints: Read Only, Restart Required

messagesHighCount

Returns the peak number of messages since the last reset.

Type: long

Constraints: Read Only, Restart Required

messagesPendingCount

Returns the number of pending messages. Pending messages are over and above the current number of messages. A pending message is one that has either been sent in a transaction and not committed, or been forwarded but has not been acknowledged.

Type: long

Constraints: Read Only, Restart Required

messagesReceivedCount

The number of messages received since the last reset.

Type: long

Constraints: Read Only, Restart Required

messagesThresholdTime

Returns the amount of time in the threshold condition since the last reset.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

pausedForForwarding

Indicates whether or not the sending agent is paused for forwarding at the current time.

Type: boolean

Constraints: Read Only, Restart Required

pausedForIncoming

Indicates whether or not the sending agent is paused for incoming messages at the current time.

Type: boolean

Constraints: Read Only, Restart Required

pausedForReceiving

Indicates whether or not the receiving agent is paused for receiving at the current time.

Type: boolean

Constraints: Read Only, Restart Required

remoteEndpointsCurrentCount

The current number of remote endpoints to which this SAF agent has been storing and forwarding messages.

Type: long

Constraints: Read Only, Restart Required

remoteEndpointsHighCount

The peak number of remote endpoints to which this SAF agent has been storing and forwarding messages since last reset.

Type: long

Constraints: Read Only, Restart Required

remoteEndpointsTotalCount

The number of remote endpoints to which this SAF agent has been storing and forwarding messages since last reset.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.SAFConversationRuntimeMBean

This class is used for monitoring a WebLogic SAF conversation.

The properties of the weblogic.management.runtime.SAFConversationRuntimeMBean entity are as follows:

QOS

The quality of service (QOS) for the SAF conversation.

The quality-of-service values are:

- weblogic.management.runtime.SAFConstants.QOS_EXACTLY_ONCE
- weblogic.management.runtime.SAFConstants.QOS_ATLEAST_ONCE
- weblogic.management.runtime.SAFConstants.QOS_ATMOST_ONCE

Type: string

Constraints: Read Only, Restart Required

conversationName

The name of the conversation.

Type: string

Constraints: Read Only, Restart Required

destinationURL

The URL of the destination.

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean

This class is used for monitoring a WebLogic SAF remote endpoint

The properties of the weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean entity are as follows:

URL

The URL of the remote endpoint.

Type: string

Constraints: Read Only, Restart Required

bytesCurrentCount

Returns the current number of bytes. This number does not include the pending bytes.

Type: long

Constraints: Read Only, Restart Required

bytesHighCount

Returns the peak number of bytes since the last reset.

Type: long

Constraints: Read Only, Restart Required

bytesPendingCount

Returns the number of pending bytes. Pending bytes are over and above the current number of bytes.

Type: long

Constraints: Read Only, Restart Required

bytesReceivedCount

The number of bytes received since the last reset.

Type: long

Constraints: Read Only, Restart Required

bytesThresholdTime

Returns the amount of time in the threshold condition since the last reset.

Type: long

Constraints: Read Only, Restart Required

downtimeHigh

Specifies the longest time, in seconds, that the remote endpoint has not been available since the last reset.

Type: long

Constraints: Read Only, Restart Required

downtimeTotal

Specifies the total time, in seconds, that the remote endpoint has not been available since the last reset.

Type: long

Constraints: Read Only, Restart Required

endpointType

Specifies if the remote endpoint is a JMS or Web Services (WSRM) destination. The possible values are: `weblogic.management.runtime.SAFConstants.JMS_ENDPOINT` or `weblogic.management.runtime.SAFConstants.WS_ENDPOINT`.

Type: string

Constraints: Read Only, Restart Required

failedMessagesTotal

Returns the total number of messages that have failed to be forwarded since the last reset.

Type: long

Constraints: Read Only, Restart Required

lastException

Specifies the exception thrown when message forwarding failed.

Type: `java.lang.Throwable`

Constraints: Read Only, Restart Required

lastTimeConnected

Specifies the last time that the remote endpoint was connected.

Type: `java.util.Date`

Constraints: Read Only, Restart Required

lastTimeFailedToConnect

Specifies the last time that the remote endpoint failed to be connected.

Type: `java.util.Date`

Constraints: Read Only, Restart Required

messagesCurrentCount

Returns the current number of messages. This number includes the pending messages.

Type: long

Constraints: Read Only, Restart Required

messagesHighCount

Returns the peak number of messages since the last reset.

Type: long

Constraints: Read Only, Restart Required

messagesPendingCount

Returns the number of pending messages. Pending messages are over and above the current number of messages. A pending message is one that has either been sent in a transaction and not committed, or been forwarded but has not been acknowledged.

Type: long

Constraints: Read Only, Restart Required

messagesReceivedCount

The number of messages received since the last reset.

Type: long

Constraints: Read Only, Restart Required

messagesThresholdTime

Returns the amount of time in the threshold condition since the last reset.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

operationState

Specifies the state of the most recent `ExireAll` operation.

Type: string

Constraints: Read Only, Restart Required

pausedForForwarding

Indicates if the remote endpoint is currently not forwarding messages.

Type: boolean

Constraints: Read Only, Restart Required

pausedForIncoming

Indicates if a remote endpoint is currently not accepting new messages.

Type: boolean

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

uptimeHigh

Specifies the longest time, in seconds, that the remote endpoint has been available since the last reset.

Type: long

Constraints: Read Only, Restart Required

uptimeTotal

Specifies the total time, in seconds, that the remote endpoint has been available since the last reset.

Type: long

Constraints: Read Only, Restart Required

weblogic.management.runtime.SAFRuntimeMBean

This class is used for monitoring a WebLogic SAF service.

The properties of the weblogic.management.runtime.SAFRuntimeMBean entity are as follows:

healthState

The health state of SAF service.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.SNMPAgentRuntimeMBean

Runtime information for an SNMP agent that is running in the current WebLogic Server domain.

The properties of the weblogic.management.runtime.SNMPAgentRuntimeMBean entity are as follows:

SNMPAgentName

Gets the name of the SNMPAgent MBean configuration that is currently active. Returns null if no SNMPAgent configuration is currently active on this Server.

Type: string

Constraints: Read Only, Restart Required

UDPListenPort

The UDP port on which this SNMP agent is listening for incoming requests from SNMP managers.

SNMP agents can also communicate through the host server's TCP listen port (7001 by default) or through a TCP port that is configured by a custom network channel.

Type: int

Constraints: Read Only, Restart Required

attributeChangeTrapCount

The number of attribute change notifications that this SNMP agent has sent to all trap destinations since the agent's host server was started.

Type: long

Constraints: Read Only, Restart Required

counterMonitorTrapCount

The number of counter monitor notifications that this SNMP agent has sent to all trap destinations since the agent's host server was started.

Type: long

Constraints: Read Only, Restart Required

failedAuthenticationCount

The number of requests that this agent has rejected because of incorrect user credentials.

Type: int

Constraints: Read Only, Restart Required

failedAuthorizationCount

The number of requests that this agent has rejected because an authenticated user does not have sufficient privileges to view the requested information. You use the WebLogic Server security realm to assign privileges to users.

Type: int

Constraints: Read Only, Restart Required

failedEncryptionCount

The number of requests that this agent has rejected because of incorrect privacy (encryption) credentials

Type: int

Constraints: Read Only, Restart Required

gaugeMonitorTrapCount

The number of gauge monitor notifications that this SNMP agent has sent to all trap destinations since the agent's host server was started.

Type: long

Constraints: Read Only, Restart Required

logMessageTrapCount

The number of log message notifications that this SNMP agent has sent to all trap destinations since the agent's host server was started.

Type: long

Constraints: Read Only, Restart Required

masterAgentXPort

The port that this SNMP agent uses to communicate with subagents.

The agent uses subagents to provide access to custom MBeans (MBeans that you create and register) and to other Oracle software components. WebLogic Server SNMP agents do not enable users to register their own subagents.

Type: int

Constraints: Read Only, Restart Required

monitorTrapCount

The total number of all notifications that this SNMP agent has sent to all trap destinations since the agent's host server was started.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

running

Indicates whether this SNMP agent is running.

Type: boolean

Constraints: Read Only, Restart Required

serverStartTrapCount

The number of serverStart notifications that this SNMP agent has sent to all trap destinations since the agent's host server was started.

Type: long

Constraints: Read Only, Restart Required

serverStopTrapCount

The number of serverShutdown notifications that this SNMP agent has sent to all trap destinations since the agent's host server was started.

Type: long

Constraints: Read Only, Restart Required

stringMonitorTrapCount

The number of string monitor notifications that this SNMP agent has sent to all trap destinations since the agent's host server was started.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ServerChannelRuntimeMBean

Runtime information for NetworkAccessPoints or "Channels".

The properties of the weblogic.management.runtime.ServerChannelRuntimeMBean entity are as follows:

acceptCount

The number of sockets that have been accepted on this channel. This includes sockets both past and present so gives a good idea of the connection rate to the server.

Type: long

Constraints: Read Only, Restart Required

associatedVirtualTargetName

Associated virtual-target name with this channel. This may be null.

Type: string

Constraints: Read Only, Restart Required

bytesReceivedCount

The total number of bytes received on this channel.

Type: long

Constraints: Read Only, Restart Required

bytesSentCount

The total number of bytes sent on this channel.

Type: long

Constraints: Read Only, Restart Required

channelName

The channel name of this channel.

Type: string

Constraints: Read Only, Restart Required

connectionsCount

The number of active connections and sockets associated with this channel.

Type: long

Constraints: Read Only, Restart Required

messagesReceivedCount

The number of messages received on this channel.

Type: long

Constraints: Read Only, Restart Required

messagesSentCount

The number of messages sent on this channel.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

publicURL

The physical URL that this channel is listening on.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ServerLogRuntimeMBean

This interface defines the control operations for a log in the WebLogic Server.

The properties of the weblogic.management.runtime.ServerLogRuntimeMBean entity are as follows:

logFileStreamOpened

Gets the opened state of the log file stream represented by this instance.

Type: boolean

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ServerMigrationRuntimeMBean

ServerMigrationRuntimeMBean provides runtime monitoring information about the past migrations performed by this server as the cluster master. If this server was never the cluster master then no information would be available. This RuntimeMBean would be hosted on all cluster members and can be queried for the location of the cluster master which is just another peer in the cluster. JMX clients can make another call to the server hosting the cluster master functionality to get the migration history.

Please note that the migration history is not persisted and is lost when a server is shutdown.

The properties of the `weblogic.management.runtime.ServerMigrationRuntimeMBean` entity are as follows:

clusterMaster

Is the current server the cluster master?

Type: boolean

Constraints: Read Only, Restart Required

clusterMasterName

Returns the server name who is the cluster master. Migration history is only available from the cluster master.

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ServerRuntimeMBean

Provides methods for retrieving runtime information about a server instance and for transitioning a server from one state to another.

The properties of the `weblogic.management.runtime.ServerRuntimeMBean` entity are as follows:

SSLListenPortEnabled

Indicates whether the default SSL listen port is enabled on the server

Type: boolean

Constraints: Read Only, Restart Required

activationTime

The time when the server was started.

Type: long

Constraints: Read Only, Restart Required

adminServer

Indicates whether the server is an Administration Server.

Type: boolean

Constraints: Read Only, Restart Required

adminServerHost

The address on which the Administration Server is listening for connections. For example, this might return the string: santiago

Type: string

Constraints: Read Only, Restart Required

adminServerListenPort

The port on which the Administration Server is listening for connections.

Type: int

Constraints: Read Only, Restart Required

adminServerListenPortSecure

Indicates whether the port that the server uses for administrative traffic is configured to use a secure protocol.

Type: boolean

Constraints: Read Only, Restart Required

administrationPortEnabled

Indicates whether the administration port is enabled on the server

Type: boolean

Constraints: Read Only, Restart Required

administrationURL

The URL that the server and its clients use for administrative connections.

If no administration channel is enabled, then this method returns the URL for connections through the default channel. If the default channel is de-activated, this method returns the URL for a secure channel. If no secure channel is enabled, the method returns null.

The returned URL will be consistent with dynamic channel updates.

Type: string

Constraints: Read Only, Restart Required

currentDirectory

The absolute path of the directory from which the server was started.

This may be used in conjunction with other relative paths in ServerMBean to compute full paths.

Type: string

Constraints: Read Only, Restart Required

currentMachine

Return the machine on which the server is running. This will be different from the configuration if the server gets migrated automatically.

Type: string

Constraints: Restart Required

defaultURL

The URL that clients use to connect to this server's default network channel.

The returned value indicates the default protocol, listen address and listen port:

protocol://listen-addresslisten-port

Note: The default protocol, listen address and listen port are persisted in the domain's `config.xml` file, however when a server instance is started, command-line options can override these persisted values. This `getDefaultURL` method returns the URL values that are currently being used, not necessarily the values that are specified in `config.xml`

The returned URL will be consistent with dynamic channel updates.

Type: string

Constraints: Read Only, Restart Required

healthState

The health state of the server as reported by the server's self-health monitoring.

For example, the server can report if it is overloaded by too many requests, if it needs more memory resources, or if it will soon fail for other reasons.

Type: `weblogic.health.HealthState`

Constraints: Read Only, Restart Required

listenPortEnabled

Indicates whether the default listen port is enabled on the server.

Type: boolean

Constraints: Read Only, Restart Required

middlewareHome

The Oracle Middleware installation directory.

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

openSocketsCurrentCount

The current number of sockets registered for socket muxing on this server.

Type: int

Constraints: Read Only, Restart Required

overallHealthState

Determine the overall health state of this server, taking into account the health of each of its subsystems.

Type: `weblogic.health.HealthState`

Constraints: Read Only, Restart Required

restartRequired

Indicates whether the server must be restarted in order to activate configuration changes.

Type: boolean

Constraints: Read Only, Restart Required

serverClasspath

Get the classpath for this server including domain/lib contents that are automatically picked up and appended to the classpath.

Type: string

Constraints: Read Only, Restart Required

state

The current life cycle state of this server.

For example, a server can be in a RUNNING state in which it can receive and process requests or in an ADMIN state in which it can receive only administrative requests.

Type: string

Constraints: Read Only, Restart Required

stateVal

Returns current state of the server as in integer.

weblogic.management.runtime.ServerStates has more information about the available server states

Type: int

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogicHome

The directory where the WebLogic Server instance (server) is installed, without the trailing "/server".

Type: string

Constraints: Read Only, Restart Required

weblogicVersion

The version of this WebLogic Server instance (server).

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ServerSecurityRuntimeMBean

This class is used for monitoring WebLogic Security Info.

The properties of the weblogic.management.runtime.ServerSecurityRuntimeMBean entity are as follows:

JACCEnabled

Indicates whether JACC (Java Authorization Contract for Containers) was enabled on the commandline for the jvm hosting this server

Type: boolean

Constraints: Read Only, Restart Required, Has Default Value: false

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.SingleSignOnServicesRuntimeMBean

This interface is used to publish SAML 2.0 local site meta-data for single sign-on services.

The properties of the `weblogic.management.runtime.SingleSignOnServicesRuntimeMBean` entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.TaskRuntimeMBean

Exposes monitoring information about an ongoing and potentially long-running administrative process. This should be taken to mean, at minimum, any OA&M operation involving I/O. Examples include starting and stopping servers, deploying and undeploying applications, or migrating services.

An MBean operation of this sort should fork a separate thread to perform the actual work and immediately return an instance of `TaskRuntimeMBean` to the caller. The caller can then use this to track the task's progress as desired. Users can also query for all instances of `TaskRuntimeMBean` to get a summary of both currently-running and recently-completed tasks.

Instance of `TaskRuntimeMBean` continue to exist in the `MBeanServer` after the completion of the work they describe. They will eventually either be explicitly

deregistered by the user, or removed by a scavenger process which periodically purges instances of `TaskRuntimeMBean` that have been completed for some time.

The properties of the `weblogic.management.runtime.TaskRuntimeMBean` entity are as follows:

completed

This property indicates whether an asynchronous job has completed.

Type: boolean

description

A description of this task.

Type: string

Constraints: Read Only, Restart Required

endTime

This property indicates the time when the asynchronous job ended.

Type: `java.util.Date`

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

parentTask

The task of which this task is a part.

A value of `null` indicates that this task is not a subtask.

Type: `weblogic.management.runtime.TaskRuntimeMBean` reference

Constraints: Read Only, Restart Required

progress

The progress of this task.

Type: string

Constraints: Read Only, Restart Required

running

Indicates whether the task is still running.

Type: boolean

Constraints: Read Only, Restart Required

startTime

This property indicates the time when an asynchronous job was started.

Type: `java.util.Date`

startTimeAsLong

The time at which this task was started.

Type: long

Constraints: Read Only, Restart Required

systemTask

Indicates whether this task was initiated by the server versus a user.

Type: boolean

Constraints: Read Only, Restart Required

taskError

Returns an exception describing the error, if any, that occurred while performing this task.

Type: java.lang.Throwable

Constraints: Read Only, Restart Required

taskStatus

The status of this task.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ThreadPoolRuntimeMBean

This bean is used to monitor the self-tuning queue

The properties of the weblogic.management.runtime.ThreadPoolRuntimeMBean entity are as follows:

completedRequestCount

The number of completed requests in the priority queue.

Type: long

Constraints: Read Only, Restart Required

executeThreadIdleCount

The number of idle threads in the pool. This count does not include standby threads and stuck threads. The count indicates threads that are ready to pick up new work when it arrives

Type: int

Constraints: Read Only, Restart Required

executeThreadTotalCount

The total number of threads in the pool.

Type: int

Constraints: Read Only, Restart Required

healthState

The health state of this pool.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

hoggingThreadCount

The threads that are being held by a request right now. These threads will either be declared as stuck after the configured timeout or will return to the pool before that. The self-tuning mechanism will backfill if necessary.

Type: int

Constraints: Read Only, Restart Required

minThreadsConstraintsCompleted

Number of requests with min threads constraint picked up out of order for execution immediately since their min threads requirement was not met. This does not include the case where threads are idle during schedule.

Type: long

Constraints: Read Only, Restart Required

minThreadsConstraintsPending

Number of requests that should be executed now to satisfy the min threads requirement.

Type: int

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

overloadRejectedRequestsCount

Number of requests rejected due to configured Shared Capacity for work managers have been reached.

Type: int

Constraints: Read Only, Restart Required

pendingUserRequestCount

The number of pending user requests in the priority queue. The priority queue contains requests from internal subsystems and users. This is just the count of all user requests.

Type: int

Constraints: Read Only, Restart Required

queueLength

The number of pending requests in the priority queue. This is the total of internal system requests and user requests.

Type: int

Constraints: Read Only, Restart Required

sharedCapacityForWorkManagers

Maximum amount of requests that can be accepted in the priority queue. Note that a request with higher priority will be accepted in place of a lower priority request already in the queue even after the threshold is reached. The lower priority request is

kept waiting in the queue till all high priority requests are executed. Also note that further enqueues of the low priority requests are rejected right away.

Type: int

Constraints: Read Only, Restart Required

standbyThreadCount

The number of threads in the standby pool. Threads that are not needed to handle the present work load are designated as standby and added to the standby pool. These threads are activated when more threads are needed.

Type: int

Constraints: Read Only, Restart Required

stuckThreadCount

Number of stuck threads in the thread pool.

Type: int

Constraints: Read Only, Restart Required

suspended

Indicates if the RequestManager is suspended. A suspended manager will not dequeue work and dispatch threads till it is resumed.

Type: boolean

Constraints: Read Only, Restart Required

throughput

The mean number of requests completed per second.

Type: double

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.TimerRuntimeMBean

This RuntimeMBean exposes information about all active timers present in the WebLogic timer implementation.

The properties of the weblogic.management.runtime.TimerRuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.TransactionNameRuntimeMBean

This interface represents runtime statistics for a transaction name category.

The properties of the weblogic.management.runtime.TransactionNameRuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

secondsActiveTotalCount

The total number of seconds that transactions were active for all committed transactions.

Type: long

Constraints: Read Only, Restart Required

transactionAbandonedTotalCount

The total number of transactions that were abandoned since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionCommittedTotalCount

The total number of transactions committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionHeuristicsTotalCount

The number of transactions that completed with a heuristic status since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionLLRCommittedTotalCount

The total number of LLR transactions that were committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionName

The transaction name.

Type: string

Constraints: Read Only, Restart Required

transactionNoResourcesCommittedTotalCount

The total number of transactions with no enlisted resources that were committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionOneResourceOnePhaseCommittedTotalCount

The total number of transactions with only one enlisted resource that were one-phase committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionReadOnlyOnePhaseCommittedTotalCount

The total number of transactions with more than one enlisted resource that were one-phase committed due to read-only optimization since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackAppTotalCount

The number of transactions that were rolled back due to an application error.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackResourceTotalCount

The number of transactions that were rolled back due to a resource error.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackSystemTotalCount

The number of transactions that were rolled back due to an internal system error.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackTimeoutTotalCount

The number of transactions that were rolled back due to a timeout expiration.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackTotalCount

The number of transactions that were rolled back since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionTotalCount

The total number of transactions processed. This total includes all committed, rolled back, and heuristic transaction completions since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionTwoPhaseCommittedLoggedTotalCount

The total number of two phase commit transactions that were committed with TLog since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionTwoPhaseCommittedNotLoggedTotalCount

The total number of two phase committed transactions that were committed without TLog since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionTwoPhaseCommittedTotalCount

The total number of transactions with more than one enlisted resource that were two-phase committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.TransactionResourceRuntimeMBean

This interface represents runtime statistics for a transactional resource.

The properties of the weblogic.management.runtime.TransactionResourceRuntimeMBean entity are as follows:

healthState

The health state of the Resource.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

resourceName

The resource name.

Type: string

Constraints: Read Only, Restart Required

transactionCommittedTotalCount

The total number of transactions committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionHeuristicCommitTotalCount

The number of transactions for which this resource has returned a heuristic commit decision.

Type: long

Constraints: Read Only, Restart Required

transactionHeuristicHazardTotalCount

The number of transactions for which this resource has reported a heuristic hazard decision.

Type: long

Constraints: Read Only, Restart Required

transactionHeuristicMixedTotalCount

The number of transactions for which this resource has reported a heuristic mixed decision.

Type: long

Constraints: Read Only, Restart Required

transactionHeuristicRollbackTotalCount

The number of transactions for which this resource has returned a heuristic rollback decision.

Type: long

Constraints: Read Only, Restart Required

transactionHeuristicsTotalCount

The number of transactions that completed with a heuristic status since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackTotalCount

The number of transactions that were rolled back since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionTotalCount

The total number of transactions processed. This total includes all committed, rolled back, and heuristic transaction completions since the server was started.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.TriggerRuntimeMBean

The `TriggerRuntimeMBean` holds runtime state (for the current Server instance) for a Trigger that has been configured in the Resource Consumption Management policy of the current Domain Partition.

The WebLogic Resource Consumption Management feature automatically initiates the configured recourse action of a Trigger when the Trigger's configured usage limits are exceeded by a Domain Partition. When a usage limit is exceeded, and the configured recourse action has been successfully executed, the Trigger is *Activated*.

When the current resource usage by the Domain Partition falls below the Trigger's configured usage limit, the feature automatically withdraws the recourse action where possible. When the current usage is below the configured usage limit, and the configured recourse action has been successfully withdrawn, the Trigger is said to be *not Activated*.

The MBean captures the following states for a Trigger when the current resource consumption usage by the Domain Partition exceeds or goes below the configured usage limit for the Domain Partition:

- Whether the Trigger is *Activated* (usage has exceeded the limit and the recourse action was successfully executed) or not
- The time when the last recourse action was executed successfully for the Trigger
- Whether a recourse action has been initiated in response to the resource usage by the Domain Partition exceeding the configured usage limits

The properties of the `weblogic.management.runtime.TriggerRuntimeMBean` entity are as follows:

activated

Indicates if the Trigger is *Activated*

Type: boolean

Constraints: Read Only, Restart Required

initiated

Indicates if a recourse action has been initiated for this Trigger as a result of the current resource usage by a Domain Partition exceeding its usage limit. A new `RecourseActionEventVBean` is added to the array returned by `getRecourseActionEventsHistory()`.

The kind of recourse action initiated (for example, a new recourse action or a withdrawal of an existing recourse action) can be determined through `RecourseActionEventVBean#isActive()`.

Type: boolean

Constraints: Read Only, Restart Required

lastTimeExecuted

The `Date` when the last recourse action was successfully executed for the current Trigger.

Type: `java.util.Date`

Constraints: Read Only, Restart Required

name

The name of the Trigger, as configured in the Resource Consumption Management policy of the Domain Partition.

Type: string

Constraints: Read Only, Restart Required

recourseActionEventsHistory

A list of recourse action events that have been initiated and executed.

Type: array of weblogic.management.runtime.RecourseActionEventVBean

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.UnicastMessagingRuntimeMBean

Monitoring information when unicast messaging is turned on

The properties of the weblogic.management.runtime.UnicastMessagingRuntimeMBean entity are as follows:

discoveredGroupLeaders

Running group leader names

Type: array of string

Constraints: Read Only, Restart Required

groups

Formatted group list

Type: string

Constraints: Read Only, Restart Required

localGroupLeaderName

Name of the local group leader

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

remoteGroupsDiscoveredCount

Returns the total groups discovered by this server

Type: int

Constraints: Read Only, Restart Required

totalGroupsCount

Total configured groups - running and not running

Type: int

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.UserLockoutManagerRuntimeMBean

This class is used to monitor and manage per security realm user lockout information.

The properties of the weblogic.management.runtime.UserLockoutManagerRuntimeMBean entity are as follows:

invalidLoginAttemptsTotalCount

Returns the number of invalid logins attempted since this server has been started and lockouts have been enabled. In a cluster, this method returns the number of invalid logins attempted that have occurred since the cluster has been started because all servers share login failure information.

Type: long

Constraints: Read Only, Restart Required

invalidLoginUsersHighCount

Returns the highest number of users with concurrent unexpired or unexpired invalid login attempts. Invalid login attempts expire as specified by `LockoutResetDuration`. This count is useful in determining whether the `LockoutCacheSize` needs to be modified.

Type: long

Constraints: Read Only, Restart Required

lockedUsersCurrentCount

Returns the number of users that are currently locked out of this server.

Type: long

Constraints: Read Only, Restart Required

loginAttemptsWhileLockedTotalCount

Returns the number of invalid logins attempted since this server has been started and lockouts have been enabled.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

unlockedUsersTotalCount

Returns the number times users have been unlocked since this server has been started.

Type: long

Constraints: Read Only, Restart Required

userLockoutTotalCount

Returns the number of user lockouts that have occurred since this server has been started. In a cluster, this method returns the number of user lockouts that have occurred since the cluster has been started because all servers share login failure information.

Type: long

Constraints: Read Only, Restart Required

weblogic.management.runtime.WANReplicationRuntimeMBean

RuntimeMBean for WAN Replication

The properties of the weblogic.management.runtime.WANReplicationRuntimeMBean entity are as follows:

detailedSecondariesDistribution

Provides the names of the remote servers (such as myserver) for which the local server is hosting secondary objects. The name is appended with a number to indicate the number of secondaries hosted on behalf of that server.

Type: array of string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

numberOfSessionsFlushedToTheDatabase

Type: long

Constraints: Read Only, Restart Required

numberOfSessionsRetrievedFromTheDatabase

Type: long

Constraints: Read Only, Restart Required

primaryCount

Provides the number of object that the local server hosts as primaries.

Answer the number of object that the local server hosts as primaries.

Type: long

Constraints: Read Only, Restart Required

remoteClusterReachable

Answer if the remote cluster is reachable or not.

Type: boolean

Constraints: Restart Required

secondaryCount

Answer the number of object that the local server hosts as secondaries.

Type: long

Constraints: Read Only, Restart Required

secondaryServerDetails

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFAccessRuntimeMBean

Use this interface to access the different types of diagnostic data generated by a server.

The properties of the weblogic.management.runtime.WLDFAccessRuntimeMBean entity are as follows:

availableDiagnosticDataAccessorNames

Type: array of string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFArchiveRuntimeMBean

Use this interface to collect statistical information about the data archives maintained by WLDF. Information provided by this interface is common to all WLDF data archives.

The properties of the weblogic.management.runtime.WLDFArchiveRuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

recordRetrievalTime

Type: long

Constraints: Read Only, Restart Required

recordSeekCount

Type: long

Constraints: Read Only, Restart Required

recordSeekTime

Type: long

Constraints: Read Only, Restart Required

retrievedRecordCount

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFControlRuntimeMBean

This MBean acts as a factory for WLDFSystemResourceControlRuntimeMBeans

The properties of the weblogic.management.runtime.WLDFControlRuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFDataAccessRuntimeMBean

Use this interface to access the specific type of diagnostic data from an underlying log for which this instance is created.

The properties of the `weblogic.management.runtime.WLDFDataAccessRuntimeMBean` entity are as follows:

earliestAvailableTimestamp

Type: long

Constraints: Read Only, Restart Required

latestAvailableTimestamp

Type: long

Constraints: Read Only, Restart Required

latestRecordId

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

timestampAvailable

Type: boolean

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFDebugPatchTaskRuntimeMBean

This interface provides monitoring over activation and deactivation tasks for dynamic debug patches

The properties of the `weblogic.management.runtime.WLDFDebugPatchTaskRuntimeMBean` entity are as follows:

activationTask

Type: boolean

Constraints: Read Only, Restart Required

applicationName

Type: string

Constraints: Read Only, Restart Required

completed

This property indicates whether an asynchronous job has completed.

Type: boolean

description

A description of this task.

Type: string

Constraints: Read Only, Restart Required

endTime

This property indicates the time when the asynchronous job ended.

Type: java.util.Date

moduleName

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

parentTask

The task of which this task is a part.

A value of `null` indicates that this task is not a subtask.

Type: weblogic.management.runtime.TaskRuntimeMBean reference

Constraints: Read Only, Restart Required

patches

Type: string

Constraints: Read Only, Restart Required

progress

The progress of this task.

Type: string

Constraints: Read Only, Restart Required

running

Indicates whether the task is still running.

Type: boolean

Constraints: Read Only, Restart Required

startTime

This property indicates the time when an asynchronous job was started.

Type: java.util.Date

startTimeAsLong

The time at which this task was started.

Type: long

Constraints: Read Only, Restart Required

systemTask

Indicates whether this task was initiated by the server versus a user.

Type: boolean

Constraints: Read Only, Restart Required

taskError

Returns an exception describing the error, if any, that occurred while performing this task.

Type: java.lang.Throwable

Constraints: Read Only, Restart Required

taskStatus

The status of this task.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFDebugPatchesRuntimeMBean

This interface provides functionality to activate/deactivate dynamic debug patches without requiring server restart. It is assumed that the WLDF instrumentation agent is enabled. This is an internal interface.

The properties of the weblogic.management.runtime.WLDFDebugPatchesRuntimeMBean entity are as follows:

activeDebugPatches

Type: array of string

Constraints: Read Only, Restart Required

availableDebugPatches

Type: array of string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFHarvesterManagerRuntimeMBean

Provides statistical information relative to a particular configured Harvester instance, and a means to retrieve an on-demand snapshot of configured attribute values.

The properties of the `weblogic.management.runtime.WLDFHarvesterManagerRuntimeMBean` entity are as follows:

averageSamplingTime

The average amount of time, in nanoseconds, spent in sampling cycles.

Type: long

Constraints: Read Only, Restart Required

currentDataSampleCount

The number of collected data samples in the current snapshot.

Type: long

Constraints: Read Only, Restart Required

currentSnapshotElapsedTime

The elapsed time, in nanoseconds, of a snapshot.

Type: long

Constraints: Read Only, Restart Required

currentSnapshotStartTime

The start time, in milliseconds, of the latest archived snapshot.

Type: long

Constraints: Read Only, Restart Required

maximumSamplingTime

The maximum observed sampling time, in nanoseconds.

Type: long

Constraints: Read Only, Restart Required

minimumSamplingTime

The minimum observed sampling time, in nanoseconds.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

totalDataSampleCount

The number of configured data samples that have been collected and archived so far in this server session.

Type: long

Constraints: Read Only, Restart Required

totalSamplingCycles

The total number of periodic sampling cycles taken thus far.

Type: long

Constraints: Read Only, Restart Required

totalSamplingTime

The total amount of observed time, in nanoseconds, spent in sampling cycles.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFHarvesterRuntimeMBean

Provides aggregated information about all active Harvester configurations, as well as metadata about harvestable and harvested attributes, types, and instances. Harvestable means potentially available for harvesting; harvested means explicitly designated for harvesting. These terms apply to types, instances, and the attributes within those types. In addition, the interface provides access to sampling and snapshot statistics. All statistics are base on data collected during the current server session.

The properties of the weblogic.management.runtime.WLDFHarvesterRuntimeMBean entity are as follows:

averageSamplingTime

The average amount of time, in nanoseconds, spent in sampling cycles.

Type: long

Constraints: Read Only, Restart Required

knownHarvestableTypes

The set of all known types, regardless of whether the types are currently configured for harvesting. The set includes the WebLogic Server MBeans, which are always present, plus any other types that can be discovered. MBeans that are not WebLogic Server MBeans will require instances to exist in order to discover the type.

Type: array of string

Constraints: Read Only, Restart Required

maximumSamplingTime

The maximum sampling time, in nanoseconds.

Type: long

Constraints: Read Only, Restart Required

minimumSamplingTime

The minimum sampling time, in nanoseconds.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

totalSamplingCycles

The total number of sampling cycles taken thus far.

Type: long

Constraints: Read Only, Restart Required

totalSamplingTime

The total amount of time, in nanoseconds, spent in sampling cycles.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean

Exposes monitoring information about a potentially long-running request for the generation of a diagnostic image. Remote clients, as well as clients running within a server, can access this information.

weblogic.management.runtime.WLDFImageRuntimeMBean

WLDFImageRuntimeMBean supports operations to request the generation of a diagnostic image for capturing a running server's internal state information. These operations will fork a separate thread to perform the actual work and immediately return an instance of this MBean to the caller. The caller can then use that instance to track the task's progress.

The properties of the weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean entity are as follows:

completed

This property indicates whether an asynchronous job has completed.

Type: boolean

description

A description of this task.

Type: string

Constraints: Read Only, Restart Required

endTime

This property indicates the time when the asynchronous job ended.

Type: java.util.Date

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

parentTask

The task of which this task is a part.

A value of null indicates that this task is not a subtask.

Type: weblogic.management.runtime.TaskRuntimeMBean reference

Constraints: Read Only, Restart Required

progress

The progress of this task.

Type: string

Constraints: Read Only, Restart Required

running

Indicates whether the task is still running.

Type: boolean

Constraints: Read Only, Restart Required

startTime

This property indicates the time when an asynchronous job was started.

Type: java.util.Date

startTimeAsLong

The time at which this task was started.

Type: long

Constraints: Read Only, Restart Required

systemTask

Indicates whether this task was initiated by the server versus a user.

Type: boolean

Constraints: Read Only, Restart Required

taskError

Returns an exception describing the error, if any, that occurred while performing this task.

Type: java.lang.Throwable

Constraints: Read Only, Restart Required

taskStatus

The status of this task.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFImageRuntimeMBean

This interface controls diagnostic image creation, and provides access to run-time information about past and current diagnostic image capture requests.

The properties of the weblogic.management.runtime.WLDFImageRuntimeMBean entity are as follows:

availableCapturedImages

Returns a list of captured images that are available on the Server.

Type: array of string

Constraints: Read Only, Restart Required

imageDir

The default directory where the server stores captured diagnostic images.

Type: string

Constraints: Read Only, Restart Required

imageTimeout

The default timeout period, in minutes, that the server uses to delay future diagnostic image-capture requests.

Type: int

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFInstrumentationRuntimeMBean

This interface defines various methods for accessing runtime information about the diagnostic instrumentation system.

The properties of the `weblogic.management.runtime.WLDFInstrumentationRuntimeMBean` entity are as follows:

callJoinpointCount

The number of affected CALL joinpoints for all classes that were inspected. (CALL joinpoints are on the caller side.)

Type: int

Constraints: Read Only, Restart Required

classweaveAbortCount

Number of classes for which the class weaving aborted with some exceptional situation.

Type: int

Constraints: Read Only, Restart Required

executionJoinpointCount

The number of affected EXECUTION joinpoints for all classes that were inspected. (EXECUTION joinpoints are on the callee side.)

Type: int

Constraints: Read Only, Restart Required

inspectedClassesCount

The number of classes inspected for weaving (weaving is the insertion of diagnostic code).

Type: int

Constraints: Read Only, Restart Required

maxWeavingTime

For all classes, the weaving time in nanoseconds for the class that required the most time to process (includes the time spent both for inspection and for modification).

Type: long

Constraints: Read Only, Restart Required

minWeavingTime

For all classes, the weaving time in nanoseconds for the class that required the least time to process (includes the time spent both for inspection and for modification).

Type: long

Constraints: Read Only, Restart Required

modifiedClassesCount

The number of modified classes (classes where diagnostic code has been inserted).

Type: int

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

totalWeavingTime

For all classes, the total weaving time in nanoseconds for processing (includes the time spent both for inspection and for modification).

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFPartitionAccessRuntimeMBean

Use this interface to access the different types of diagnostic data generated by a partition.

The properties of the weblogic.management.runtime.WLDFPartitionAccessRuntimeMBean entity are as follows:

availableDiagnosticDataAccessorNames

Type: array of string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFPartitionHarvesterRuntimeMBean

Provides aggregated information about all active Harvester configurations for a partition.

The properties of the weblogic.management.runtime.WLDFPartitionHarvesterRuntimeMBean entity are as follows:

averageSamplingTime

The average amount of time, in nanoseconds, spent in sampling cycles.

Type: long

Constraints: Read Only, Restart Required

maximumSamplingTime

The maximum sampling time, in nanoseconds.

Type: long

Constraints: Read Only, Restart Required

minimumSamplingTime

The minimum sampling time, in nanoseconds.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

totalSamplingCycles

The total number of sampling cycles taken thus far.

Type: long

Constraints: Read Only, Restart Required

totalSamplingTime

The total amount of time, in nanoseconds, spent in sampling cycles.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFPartitionImageRuntimeMBean

This interface controls diagnostic image creation, and provides access to run-time information about past and current diagnostic image capture requests.

The properties of the weblogic.management.runtime.WLDFPartitionImageRuntimeMBean entity are as follows:

availableCapturedImages

Returns a list of captured images that are available on the Server.

Type: array of string

Constraints: Read Only, Restart Required

imageDir

The default directory where the server stores captured diagnostic images.

Type: string

Constraints: Read Only, Restart Required

imageTimeout

The default timeout period, in minutes, that the server uses to delay future diagnostic image-capture requests.

Type: int

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFPartitionRuntimeMBean

This interface provides access to all the runtime MBeans for the WebLogic Diagnostic Framework (WLDF).

The properties of the weblogic.management.runtime.WLDFPartitionRuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFRuntimeMBean

This interface provides access to all the runtime MBeans for the WebLogic Diagnostic Framework (WLDF).

The properties of the weblogic.management.runtime.WLDFRuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFSystemResourceControlRuntimeMBean

This MBean acts as a Runtime Control for a WLDF profile. An WLDF profile could either be a configured system resource or an external descriptor provided by a user at runtime.

The properties of the `weblogic.management.runtime.WLDFSystemResourceControlRuntimeMBean` entity are as follows:

enabled

is the descriptor enabled

Type: boolean

Constraints: Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFWatchManagerRuntimeMBean

Provides access to Policy and Action statistical data for the current instance of this server.

The properties of the `weblogic.management.runtime.WLDFWatchManagerRuntimeMBean` entity are as follows:

activeAlarmWatches

The names of active alarm policies.

Type: array of string

Constraints: Read Only, Restart Required

averageEventDataWatchEvaluationTime

The average Instrumentation event data evaluation cycle time, in milliseconds.

Type: long

Constraints: Read Only, Restart Required

averageHarvesterWatchEvaluationTime

The average Harvester evaluation cycle time, in milliseconds.

Type: long

Constraints: Read Only, Restart Required

averageLogWatchEvaluationTime

The average Log evaluation cycle time, in milliseconds.

Type: long

Constraints: Read Only, Restart Required

currentActiveAlarmsCount

The number of active alarms of any type.

Type: int

Constraints: Read Only, Restart Required

maximumActiveAlarmsCount

The maximum number of active alarms at any one time.

Type: int

Constraints: Read Only, Restart Required

maximumEventDataWatchEvaluationTime

The maximum time spent evaluating EventData policies.

Type: long

Constraints: Read Only, Restart Required

maximumHarvesterWatchEvaluationTime

The maximum time spent evaluating Harvester policies.

Type: long

Constraints: Read Only, Restart Required

maximumLogWatchEvaluationTime

The maximum time spent evaluating Log policies.

Type: long

Constraints: Read Only, Restart Required

minimumEventDataWatchEvaluationTime

The minimum time spent evaluating Log policies.

Type: long

Constraints: Read Only, Restart Required

minimumHarvesterWatchEvaluationTime

The minimum time spent evaluating Harvester policies.

Type: long

Constraints: Read Only, Restart Required

minimumLogWatchEvaluationTime

The minimum time spent evaluating Log policies.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

totalActiveAutomaticResetAlarms

The total number of active automatically reset alarms.

Type: long

Constraints: Read Only, Restart Required

totalActiveManualResetAlarms

The total number of active manually reset alarms.

Type: long

Constraints: Read Only, Restart Required

totalDIMGNotificationsPerformed

The total number of Diagnostic Image actions fired. Diagnostic Image files are not true actions, but this records the number of image captures requested by the policy component.

Type: long

Constraints: Read Only, Restart Required

totalEventDataEvaluationCycles

The total number of times Instrumentation event data policies have been evaluated.

Type: long

Constraints: Read Only, Restart Required

totalEventDataWatchEvaluations

The total number of Instrumentation event data policies that have been evaluated. For each cycle, the Policy and Action component evaluates all of the enabled Instrumentation event data policies.

Type: long

Constraints: Read Only, Restart Required

totalEventDataWatchesTriggered

The total number of Instrumentation event data policies that have evaluated to true and triggered actions.

Type: long

Constraints: Read Only, Restart Required

totalFailedDIMGNotifications

The total number of failed Diagnostic Image action requests.

Type: long

Constraints: Read Only, Restart Required

totalFailedJMSNotifications

The total number of failed JMS action attempts.

Type: long

Constraints: Read Only, Restart Required

totalFailedJMXNotifications

The total number of failed JMX action attempts.

Type: long

Constraints: Read Only, Restart Required

totalFailedNotifications

The total number of failed action requests.

Type: long

Constraints: Read Only, Restart Required

totalFailedSMTPNotifications

The total number of failed SMTP action attempts.

Type: long

Constraints: Read Only, Restart Required

totalFailedSNMPNotifications

The total number of failed SNMP action attempts.

Type: long

Constraints: Read Only, Restart Required

totalHarvesterEvaluationCycles

The total number of times the Harvester has invoked the Policy and Action component to evaluate Harvester policies. (This number corresponds to the number of sampling cycles.)

Type: long

Constraints: Read Only, Restart Required

totalHarvesterWatchEvaluations

The total number of Harvester policies that have been evaluated. For each cycle, the Policy and Action component evaluates all of the enabled Harvester policies.

Type: long

Constraints: Read Only, Restart Required

totalHarvesterWatchesTriggered

The total number of Harvester policies that have evaluated to true and triggered actions.

Type: long

Constraints: Read Only, Restart Required

totalJMSNotificationsPerformed

The total number of JMS actions successfully fired.

Type: long

Constraints: Read Only, Restart Required

totalJMXNotificationsPerformed

The total number of JMX actions successfully fired.

Type: long

Constraints: Read Only, Restart Required

totalLogEvaluationCycles

The total number of times Log policies have been evaluated.

Type: long

Constraints: Read Only, Restart Required

totalLogWatchEvaluations

The total number of Log policies that have been evaluated. For each cycle, the Policy and Action component evaluates all of the enabled Log policies.

Type: long

Constraints: Read Only, Restart Required

totalLogWatchesTriggered

The total number of Log policies that have evaluated to true and triggered actions.

Type: long

Constraints: Read Only, Restart Required

totalNotificationsPerformed

The total number of actions performed.

Type: long

Constraints: Read Only, Restart Required

totalSMTPNotificationsPerformed

The total number of SMTP actions successfully fired.

Type: long

Constraints: Read Only, Restart Required

totalSNMPNotificationsPerformed

The total number of SNMP actions successfully fired.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFWatchNotificationRuntimeMBean

Provides access to policy and action statistical data for the current instance of this server.

Note: As of WebLogic Server 12.2.1, the terms *watch* and *notification* are replaced by *policy* and *action*, respectively. However, the definition of these terms has not changed.

The properties of the weblogic.management.runtime.WLDFWatchNotificationRuntimeMBean entity are as follows:

activeAlarmWatches

The names of active alarm policies.

Type: array of string

Constraints: Read Only, Restart Required

averageEventDataWatchEvaluationTime

The average Instrumentation event data evaluation cycle time, in milliseconds.

Type: long

Constraints: Read Only, Restart Required

averageHarvesterWatchEvaluationTime

The average Harvester evaluation cycle time, in milliseconds.

Type: long

Constraints: Read Only, Restart Required

averageLogWatchEvaluationTime

The average Log evaluation cycle time, in milliseconds.

Type: long

Constraints: Read Only, Restart Required

currentActiveAlarmsCount

The number of active alarms of any type.

Type: int

Constraints: Read Only, Restart Required

maximumActiveAlarmsCount

The maximum number of active alarms at any one time.

Type: int

Constraints: Read Only, Restart Required

maximumEventDataWatchEvaluationTime

The maximum time spent evaluating EventData policies.

Type: long

Constraints: Read Only, Restart Required

maximumHarvesterWatchEvaluationTime

The maximum time spent evaluating Harvester policies.

Type: long

Constraints: Read Only, Restart Required

maximumLogWatchEvaluationTime

The maximum time spent evaluating Log policies.

Type: long

Constraints: Read Only, Restart Required

minimumEventDataWatchEvaluationTime

The minimum time spent evaluating Log policies.

Type: long

Constraints: Read Only, Restart Required

minimumHarvesterWatchEvaluationTime

The minimum time spent evaluating Harvester policies.

Type: long

Constraints: Read Only, Restart Required

minimumLogWatchEvaluationTime

The minimum time spent evaluating Log policies.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

totalActiveAutomaticResetAlarms

The total number of active automatically reset alarms.

Type: long

Constraints: Read Only, Restart Required

totalActiveManualResetAlarms

The total number of active manually reset alarms.

Type: long

Constraints: Read Only, Restart Required

totalDIMGNotificationsPerformed

The total number of Diagnostic Image actions fired. Diagnostic Image files are not true actions, but this records the number of image captures requested by the policy component.

Type: long

Constraints: Read Only, Restart Required

totalEventDataEvaluationCycles

The total number of times Instrumentation event data policies have been evaluated.

Type: long

Constraints: Read Only, Restart Required

totalEventDataWatchEvaluations

The total number of Instrumentation event data policies that have been evaluated. For each cycle, the Policy and Action component evaluates all of the enabled Instrumentation event data policies.

Type: long

Constraints: Read Only, Restart Required

totalEventDataWatchesTriggered

The total number of Instrumentation event data policies that have evaluated to true and triggered actions.

Type: long

Constraints: Read Only, Restart Required

totalFailedDIMGNotifications

The total number of failed Diagnostic Image action requests.

Type: long

Constraints: Read Only, Restart Required

totalFailedJMSNotifications

The total number of failed JMS action attempts.

Type: long

Constraints: Read Only, Restart Required

totalFailedJMXNotifications

The total number of failed JMX action attempts.

Type: long

Constraints: Read Only, Restart Required

totalFailedNotifications

The total number of failed action requests.

Type: long

Constraints: Read Only, Restart Required

totalFailedSMTPNotifications

The total number of failed SMTP action attempts.

Type: long

Constraints: Read Only, Restart Required

totalFailedSNMPNotifications

The total number of failed SNMP action attempts.

Type: long

Constraints: Read Only, Restart Required

totalHarvesterEvaluationCycles

The total number of times the Harvester has invoked the Policy and Action component to evaluate Harvester policies. (This number corresponds to the number of sampling cycles.)

Type: long

Constraints: Read Only, Restart Required

totalHarvesterWatchEvaluations

The total number of Harvester policies that have been evaluated. For each cycle, the Policy and Action component evaluates all of the enabled Harvester policies.

Type: long

Constraints: Read Only, Restart Required

totalHarvesterWatchesTriggered

The total number of Harvester policies that have evaluated to true and triggered actions.

Type: long

Constraints: Read Only, Restart Required

totalJMSNotificationsPerformed

The total number of JMS actions successfully fired.

Type: long

Constraints: Read Only, Restart Required

totalJMXNotificationsPerformed

The total number of JMX actions successfully fired.

Type: long

Constraints: Read Only, Restart Required

totalLogEvaluationCycles

The total number of times Log policies have been evaluated.

Type: long

Constraints: Read Only, Restart Required

totalLogWatchEvaluations

The total number of Log policies that have been evaluated. For each cycle, the Policy and Action component evaluates all of the enabled Log policies.

Type: long

Constraints: Read Only, Restart Required

totalLogWatchesTriggered

The total number of Log policies that have evaluated to true and triggered actions.

Type: long

Constraints: Read Only, Restart Required

totalNotificationsPerformed

The total number of actions performed.

Type: long

Constraints: Read Only, Restart Required

totalSMTPNotificationsPerformed

The total number of SMTP actions successfully fired.

Type: long

Constraints: Read Only, Restart Required

totalSNMPNotificationsPerformed

The total number of SNMP actions successfully fired.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFWatchNotificationSourceRuntimeMBean

Attaches an action listener in order to receive action events when a policy evaluates to true. Note that the listener will receive all actions; the caller must filter the output.

Unlike the deprecated WLDFWatchJMXNotificationRuntimeMBean, the action generated by this source is a Java Map object comprised of simple JDK types, and does not require a client dependency on any WLDF code.

Note: As of WebLogic Server 12.2.1, the terms *watch* and *notification* are replaced by *policy* and *action*, respectively. However, the definition of these terms has not changed.

The properties of the weblogic.management.runtime.WLDFWatchNotificationSourceRuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WTCRuntimeMBean

This class is used to 1. query, stop, and start WTC connections. 2. query, suspend, and resume WTC imported and exported services. 3. retrieve statistics MBean relates to this WTC server. 4. query status of WTC server.

The properties of the weblogic.management.runtime.WTCRuntimeMBean entity are as follows:

WTCServerStartTime

Returns the timestamp when WTC server starts.

Type: long

Constraints: Read Only, Restart Required

WTCServerStatus

Returns the status of WTC server itself.

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WTCStatisticsRuntimeMBean

This class is used to:

- query statistics of WTC connections.
- query statistics of WTC imported and exported services.

The properties of the weblogic.management.runtime.WTCStatisticsRuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WebServerRuntimeMBean

Describes a Web Server (HTTP Server)

The properties of the weblogic.management.runtime.WebServerRuntimeMBean entity are as follows:

defaultWebServer

Indicates whether it is the default WebServer or a VirtualHost

Type: boolean

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

webServerName

Provides the name of the WebServer.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WorkManagerRuntimeMBean

WorkManager Runtime information.

The properties of the weblogic.management.runtime.WorkManagerRuntimeMBean entity are as follows:

applicationName

Get the name of the application this WorkManager is associated with

Type: string

Constraints: Read Only, Restart Required

completedDaemonRequests

The number of daemon requests that have been processed

Type: long

Constraints: Read Only, Restart Required

completedRequests

The number of requests that have been processed, including daemon requests.

Type: long

Constraints: Read Only, Restart Required

healthState

Returns the HealthState mbean for the work manager.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

moduleName

Get the name of the module this WorkManager is associated with

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

partitionName

Returns the name of the partition that the work manager is associated with.

Type: string

Constraints: Read Only, Restart Required

pendingDaemonRequests

The number of daemon requests in progress.

Type: int

Constraints: Read Only, Restart Required

pendingRequests

The number of waiting requests in the queue, including daemon requests.

Type: int

Constraints: Read Only, Restart Required

stuckThreadCount

The number of threads that are considered to be stuck on the basis of any stuck thread constraints.

Type: int

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WseeAggregatableBaseOperationRuntimeMBean

Describes Web Service operation state, such as deployment state and runtime statistics. The derived MBean determines whether this state is for a single operation or whether it is aggregated across operations.

This MBean can describe the operation(s) on a web service client or service. Request statistics relate to outgoing requests on a client or incoming requests on a service. Response statistics relate to an incoming response on a client or an outgoing response on a service.

Time values are reported in milliseconds.

The properties of the `weblogic.management.runtime.WseeAggregatableBaseOperationRuntimeMBean` entity are as follows:

dispatchTimeAverage

Average operation dispatch time for the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

Type: long

Constraints: Read Only, Restart Required

dispatchTimeHigh

Longest operation dispatch time for the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

Type: long

Constraints: Read Only, Restart Required

dispatchTimeLow

Shortest operation dispatch time for the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

Type: long

Constraints: Read Only, Restart Required

dispatchTimeTotal

Total time for all operation dispatches in the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

Type: long

Constraints: Read Only, Restart Required

errorCount

Number of errors sending or receiving a request.

Type: int

Constraints: Read Only, Restart Required

executionTimeAverage

Average operation execution time.

Type: long

Constraints: Read Only, Restart Required

executionTimeHigh

Longest operation execution time.

Type: long

Constraints: Read Only, Restart Required

executionTimeLow

Shortest operation execution time.

Type: long

Constraints: Read Only, Restart Required

executionTimeTotal

Total time for all operation executions.

Type: long

Constraints: Read Only, Restart Required

invocationCount

Total number of operation invocations in the current measurement period.

The measurement period typically starts when WebLogic Server is first started.

Type: int

Constraints: Read Only, Restart Required

lastError

Last error that occurred processing a request.

Type: string

Constraints: Read Only, Restart Required

lastErrorTime

Time on WebLogic Server of the last error for a request (sending or receiving) was detected expressed as the number of milliseconds since midnight, January 1, 1970 UTC.

Type: long

Constraints: Read Only, Restart Required

lastInvocationTime

Time of the last operation request to be sent or received (or 0 if no requests have been sent or received).

Type: long

Constraints: Read Only, Restart Required

lastResponseError

Last response error to arrive for this client/service (or null if no errors have occurred).

Type: string

Constraints: Read Only, Restart Required

lastResponseErrorTime

Time on WebLogic Server of the last error sending or receiving a response (or 0 if no failures have occurred) expressed as the number of milliseconds since midnight, January 1, 1970 UTC.

Type: long

Constraints: Read Only, Restart Required

lastResponseTime

Time on WebLogic Server of the last response to arrive for this client/service (or 0 if no responses have been received) expressed as the number of milliseconds since midnight, January 1, 1970 UTC.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

responseCount

Total number of responses generated from operation invocations.

Type: int

Constraints: Read Only, Restart Required

responseErrorCount

Total number of errors from responses generated from operation invocations.

Type: int

Constraints: Read Only, Restart Required

responseTimeAverage

Average response time from the responses generated from operation invocations.

Type: long

Constraints: Read Only, Restart Required

responseTimeHigh

Longest response time from the responses generated from operation invocations.

Type: long

Constraints: Read Only, Restart Required

responseTimeLow

Lowest response time from the responses generated from operation invocations.

Type: long

Constraints: Read Only, Restart Required

responseTimeTotal

Total time for all responses generated from operation invocations.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WseeBaseOperationRuntimeMBean

Describes the state of a particular Web Service operation, such as deployment state and runtime statistics about the execution of the operation.

This MBean can describe the operation on a web service client or service. Request statistics relate to outgoing requests on a client or incoming requests on a service. Response statistics relate to an incoming response on a client or an outgoing response on a service.

Time values are reported in milliseconds.

The properties of the `weblogic.management.runtime.WseeBaseOperationRuntimeMBean` entity are as follows:

dispatchTimeAverage

Average operation dispatch time for the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

Type: long

Constraints: Read Only, Restart Required

dispatchTimeHigh

Longest operation dispatch time for the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

Type: long

Constraints: Read Only, Restart Required

dispatchTimeLow

Shortest operation dispatch time for the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

Type: long

Constraints: Read Only, Restart Required

dispatchTimeTotal

Total time for all operation dispatches in the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

Type: long

Constraints: Read Only, Restart Required

errorCount

Number of errors sending or receiving a request.

Type: int

Constraints: Read Only, Restart Required

executionTimeAverage

Average operation execution time.

Type: long

Constraints: Read Only, Restart Required

executionTimeHigh

Longest operation execution time.

Type: long

Constraints: Read Only, Restart Required

executionTimeLow

Shortest operation execution time.

Type: long

Constraints: Read Only, Restart Required

executionTimeTotal

Total time for all operation executions.

Type: long

Constraints: Read Only, Restart Required

invocationCount

Total number of operation invocations in the current measurement period.

The measurement period typically starts when WebLogic Server is first started.

Type: int

Constraints: Read Only, Restart Required

lastError

Last error that occurred processing a request.

Type: string

Constraints: Read Only, Restart Required

lastErrorTime

Time on WebLogic Server of the last error for a request (sending or receiving) was detected expressed as the number of milliseconds since midnight, January 1, 1970 UTC.

Type: long

Constraints: Read Only, Restart Required

lastInvocationTime

Time of the last operation request to be sent or received (or 0 if no requests have been sent or received).

Type: long

Constraints: Read Only, Restart Required

lastResponseError

Last response error to arrive for this client/service (or null if no errors have occurred).

Type: string

Constraints: Read Only, Restart Required

lastResponseErrorTime

Time on WebLogic Server of the last error sending or receiving a response (or 0 if no failures have occurred) expressed as the number of milliseconds since midnight, January 1, 1970 UTC.

Type: long

Constraints: Read Only, Restart Required

lastResponseTime

Time on WebLogic Server of the last response to arrive for this client/service (or 0 if no responses have been received) expressed as the number of milliseconds since midnight, January 1, 1970 UTC.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

operationName

Name of the operation for which runtime information is being provided.

Type: string

Constraints: Read Only, Restart Required

responseCount

Total number of responses generated from operation invocations.

Type: int

Constraints: Read Only, Restart Required

responseErrorCount

Total number of errors from responses generated from operation invocations.

Type: int

Constraints: Read Only, Restart Required

responseTimeAverage

Average response time from the responses generated from operation invocations.

Type: long

Constraints: Read Only, Restart Required

responseTimeHigh

Longest response time from the responses generated from operation invocations.

Type: long

Constraints: Read Only, Restart Required

responseTimeLow

Lowest response time from the responses generated from operation invocations.

Type: long

Constraints: Read Only, Restart Required

responseTimeTotal

Total time for all responses generated from operation invocations.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WseeClusterFrontEndRuntimeMBean

Encapsulates runtime information about a particular Web Service cluster front-end instance. This MBean represents a cluster front-end instance (e.g. HttpClusterServlet) that contains a cluster routing function.

The properties of the weblogic.management.runtime.WseeClusterFrontEndRuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WseeClusterRoutingRuntimeMBean

Encapsulates runtime information about a particular Web Service cluster routing instance (whether it be a front-end router or an in-place router).

The properties of the weblogic.management.runtime.WseeClusterRoutingRuntimeMBean entity are as follows:

lastRoutingFailure

The exception that caused the last routing failure, or null if no failures have occurred.

Type: string

Constraints: Read Only, Restart Required

lastRoutingFailureTime

The time (in milliseconds since epoch) of the last routing failure (or 0 if no failures have occurred).

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

requestCount

The number of requests (messages with no RelatesTo header) that have come through this front-end since the server started.

Type: int

Constraints: Read Only, Restart Required

responseCount

The number of responses (messages with a RelatesTo header) that have come through this front-end since the server started.

Type: int

Constraints: Read Only, Restart Required

routedRequestCount

The number of requests that were routed to a specific server instance via routing information in the request (not just load balanced) since the server started.

Type: int

Constraints: Read Only, Restart Required

routedResponseCount

The number of responses that were routed to a specific server instance via routing information in the response (not just load balanced) since the server started.

Type: int

Constraints: Read Only, Restart Required

routingFailureCount

The number of times a message failed to be routed, since the server started.

Type: int

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WseeHandlerRuntimeMBean

Provides runtime information about a SOAP message handler that has been associated with a Web service.

SOAP message handlers are used to intercept both the inbound (request) and outbound (response) SOAP messages so that extra processing can be done on the messages. Programmers specify SOAP message handlers for a Web Service using the @SOAPMessageHandlers and @HandlerChain JWS annotations.

The properties of the weblogic.management.runtime.WseeHandlerRuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WseeMcRuntimeMBean

Describes the state of MakeConnection pending message lists

The properties of the weblogic.management.runtime.WseeMcRuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WseeOperationRuntimeMBean

Describes the state of a particular Web Service operation, such as deployment state and runtime statistics about the execution of the operation.

This MBean can describe the operation on a web service client or service. Request statistics relate to outgoing requests on a client or incoming requests on a service. Response statistics relate to an incoming response on a client or an outgoing response on a service.

Time values are reported in milliseconds

The properties of the weblogic.management.runtime.WseeOperationRuntimeMBean entity are as follows:

dispatchTimeAverage

Average operation dispatch time for the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

Type: long

Constraints: Read Only, Restart Required

dispatchTimeHigh

Longest operation dispatch time for the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

Type: long

Constraints: Read Only, Restart Required

dispatchTimeLow

Shortest operation dispatch time for the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

Type: long

Constraints: Read Only, Restart Required

dispatchTimeTotal

Total time for all operation dispatches in the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

Type: long

Constraints: Read Only, Restart Required

errorCount

Number of errors sending or receiving a request.

Type: int

Constraints: Read Only, Restart Required

executionTimeAverage

Average operation execution time.

Type: long

Constraints: Read Only, Restart Required

executionTimeHigh

Longest operation execution time.

Type: long

Constraints: Read Only, Restart Required

executionTimeLow

Shortest operation execution time.

Type: long

Constraints: Read Only, Restart Required

executionTimeTotal

Total time for all operation executions.

Type: long

Constraints: Read Only, Restart Required

invocationCount

Total number of operation invocations in the current measurement period.

The measurement period typically starts when WebLogic Server is first started.

Type: int

Constraints: Read Only, Restart Required

lastError

Last error that occurred processing a request.

Type: string

Constraints: Read Only, Restart Required

lastErrorTime

Time on WebLogic Server of the last error for a request (sending or receiving) was detected expressed as the number of milliseconds since midnight, January 1, 1970 UTC.

Type: long

Constraints: Read Only, Restart Required

lastInvocationTime

Time of the last operation request to be sent or received (or 0 if no requests have been sent or received).

Type: long

Constraints: Read Only, Restart Required

lastResponseError

Last response error to arrive for this client/service (or null if no errors have occurred).

Type: string

Constraints: Read Only, Restart Required

lastResponseErrorTime

Time on WebLogic Server of the last error sending or receiving a response (or 0 if no failures have occurred) expressed as the number of milliseconds since midnight, January 1, 1970 UTC.

Type: long

Constraints: Read Only, Restart Required

lastResponseTime

Time on WebLogic Server of the last response to arrive for this client/service (or 0 if no responses have been received) expressed as the number of milliseconds since midnight, January 1, 1970 UTC.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

operationName

Name of the operation for which runtime information is being provided.

Type: string

Constraints: Read Only, Restart Required

policyAttachmentSupport

Get attachment support for this port MBean.

Type: string

Constraints: Read Only, Restart Required

policySubjectName

Get subject name for this port MBean.

Type: string

Constraints: Read Only, Restart Required

policySubjectResourcePattern

The policySubject parameter must uniquely identify what application, module, service, and port (port or operation for WLS Policy) is targeted. The syntax currently used by JRF (see [JRF ATTACHMENT POINT]) for J2EE Webservice Endpoints will be used: /{domain}/{instance}/{app}/WEBs|EJBs/{module}/WEBSERVICES/{service}/PORTs/{port}/OPERATIONS/{operation}

Type: string

Constraints: Read Only, Restart Required

policySubjectType

Get subject type for this port MBean.

Type: string

Constraints: Read Only, Restart Required

responseCount

Total number of oresponses generated from operation invocations.

Type: int

Constraints: Read Only, Restart Required

responseErrorCount

Total number of errors from responses generated from operation invocations.

Type: int

Constraints: Read Only, Restart Required

responseTimeAverage

Average response time from the responses generated from operation invocations.

Type: long

Constraints: Read Only, Restart Required

responseTimeHigh

Longest response time from the responses generated from operation invocations.

Type: long

Constraints: Read Only, Restart Required

responseTimeLow

Lowest response time from the responses generated from operation invocations.

Type: long

Constraints: Read Only, Restart Required

responseTimeTotal

Total time for all responses generated from operation invocations.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WseePolicyRuntimeMBean

Specifies runtime information about the WS-Policy files that are available for the Web Service.

Web Services can have one or more WS-Policy files associated with the endpoint itself or its operations; the WS-Policy files specify configuration options for Web Service message-level security (encryption and digital signatures) and reliable SOAP messaging.

Programmers can use the @Policy JWS annotation to associate a WS-Policy file to a Web Service at development time. Administrators can also associate additional WS-Policy files at runtime.

The properties of the weblogic.management.runtime.WseePolicyRuntimeMBean entity are as follows:

availablePolicies

Type: array of string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WseePortPolicyRuntimeMBean

Describes the Web service security policy state of a particular Web service port.

The properties of the weblogic.management.runtime.WseePortPolicyRuntimeMBean entity are as follows:

authenticationSuccesses

Total number of authentication successes detected for this port. Only incoming message processing can add to the success count.

Type: int

Constraints: Read Only, Restart Required

authenticationViolations

Total number of authentication violations generated for this port. Only incoming message processing can add to the violation count.

Type: int

Constraints: Read Only, Restart Required

authorizationSuccesses

Total number of authorization successes detected for this port.

Type: int

Constraints: Read Only, Restart Required

authorizationViolations

Total number of authorization violations generated for this port.

Type: int

Constraints: Read Only, Restart Required

confidentialitySuccesses

Total number of confidentiality successes generated for this port. Both outgoing and incoming message processing can add to the success count.

Type: int

Constraints: Read Only, Restart Required

confidentialityViolations

Total number of confidentiality violations generated for this port. Both outgoing and incoming message processing can add to the violation count.

Type: int

Constraints: Read Only, Restart Required

integritySuccesses

Total number of integrity successes generated for this port. Both outgoing and incoming message processing can add to the success count.

Type: int

Constraints: Read Only, Restart Required

integrityViolations

Total number of integrity violations generated for this port. Both outgoing and incoming message processing can add to the violation count.

Type: int

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

policyFaults

Total number of policy faults generated for this port.

Type: int

Constraints: Read Only, Restart Required

totalFaults

Total number of security faults and violations generated by this port.

Type: int

Constraints: Read Only, Restart Required

totalSecurityFaults

Total number of security faults and violations generated for this port.

Type: int

Constraints: Read Only, Restart Required

totalViolations

Total number of authentication, integrity, and confidentiality violations. Both outgoing and incoming message processing can add to the violation count.

Type: int

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WseePortRuntimeMBean

Describes the state of a particular Web Service port.

The properties of the weblogic.management.runtime.WseePortRuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

policyAttachmentSupport

Get attachment support for this port MBean.

Type: string

Constraints: Read Only, Restart Required

policyFaults

Total number of policy faults.

Type: int

Constraints: Read Only, Restart Required

policySubjectAbsolutePortableExpression

The policySubject AbsolutePortableExpression This is the WSM ResourcePattern AbsolutePortableExpression string

Type: string

Constraints: Read Only, Restart Required

policySubjectName

Get subject name for this port MBean.

Type: string

Constraints: Read Only, Restart Required

policySubjectResourcePattern

The policySubject parameter must uniquely identify what application, module, service or reference-name, and port (port or operation for WLS Policy) is targeted. The syntax currently used by JRF (see [JRF ATTACHMENT POINT]) for J2EE Webservice Endpoints will be used:

`/ {domain} / {instance} / {app} / WEBS | EJBs / {module} / WEBSERVICES / {service} | {reference-name} / PORTs / {port}`

Type: string

Constraints: Read Only, Restart Required

policySubjectType

Get subject type for this port MBean.

Type: string

Constraints: Read Only, Restart Required

portName

Name of this port.

This attribute corresponds to the "name" attribute of the "port" element in the WSDL that describes the Web service. Programmers specify the name of the port using the portName attribute of the @WLXXXTransport annotation, where XXX refers to the type of transport (HTTP, HTTPS, or JMS).

Programmers can also use the WLXXXTransport child element of the jwsc Ant task to specify this attribute.

Type: string

Constraints: Read Only, Restart Required

startTime

Date and time that the Web service endpoint started.

Type: long

Constraints: Read Only, Restart Required

totalFaults

Total number of security faults and violations.

Type: int

Constraints: Read Only, Restart Required

totalSecurityFaults

Total number of security faults and violations.

Type: int

Constraints: Read Only, Restart Required

transportProtocolType

Transport protocol used to invoke this Web service, such as HTTP, HTTPS, or JMS.

This attribute determines the transport that is published in the endpoint address section of the WSDL of the Web Service. Programmers specify the transport by the type of @WLXXXTransport JWS annotation they specify, where XXX refers to the type of transport (HTTP, HTTPS, or JMS).

Programmers can also use the WLXXXTransport child element of the jwsc Ant task to specify this attribute.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WseeV2RuntimeMBean

Encapsulates runtime information about a particular Web Service. The name attribute of this MBean will be the value of the webservice-description-name element in webservices.xml

The properties of the weblogic.management.runtime.WseeV2RuntimeMBean entity are as follows:

URI

Specifies the URI of this Web service.

This attribute corresponds to the final part of the endpoint address in the WSDL that describes the Web Services. It is specified at development time for JAX-RPC services using the serviceURI attribute of the @WLXXXTransport JWS annotation, where XXX refers to the transport, such as HTTP, HTTPS, or JMS. For JAX-WS services, this can be set during compilation.

Type: string

Constraints: Read Only, Restart Required

contextPath

Specifies the context path of this web service.

This attribute corresponds to the initial part of the endpoint address in the WSDL that describes the Web Service. It is specified at development time in JAX-RPC services using the contextPath attribute of the @WLXXXTransport JWS annotation, where XXX refers to the transport, such as HTTP, HTTPS, or JMS. For JAX-WS services the context path is set either during compilation of the service, or by the module (web or EJB) hosting the service.

Type: string

Constraints: Read Only, Restart Required

implementationType

Specifies the implementation type of this service.

Valid values include: JAX-WS 2.0 JAX-RPC 1.1

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

policyFaults

Total number of faults generated by security policy handler.

Type: int

Constraints: Read Only, Restart Required

serviceName

Specifies the qualified name of this Web service.

This attribute is calculated based on actual MBean type and of the form:

WseeRuntimeMBean: <app name>#<app version>!<service name>.

WseeV2RuntimeMBean: <app name>#<app version>!<web WAR name or EJB JAR name>!<service name>.

Type: string

Constraints: Read Only, Restart Required

startTime

Date and time that the Web service starts.

Type: long

Constraints: Read Only, Restart Required

totalFaults

Total number of faults generated by this endpoint.

Type: int

Constraints: Read Only, Restart Required

totalSecurityFaults

Total number of faults generated by this endpoint.

Type: int

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

webserviceDescriptionName

webservice description name for this webservice

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WseeWsruntimeMBean

Encapsulates runtime information about WS-RM functionality. If this MBean is parented by a WseePortRuntimeMBean instance, this MBean represents WS-RM resources contained in a particular Web Service or web service client. If this MBean is parented by ServerRuntimeMBean, this MBean represents WS-RM resources for the entire server/VM (spanning across applications, web services, clients, etc.)

The properties of the weblogic.management.runtime.WseeWsruntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

sequenceids

A list of sequence IDs representing active sequences being managed on the WS-RM destination (receiving side).

Type: array of string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required