

Open Development Tool Installation
Oracle FLEXCUBE Investor Servicing
Release 12.4.0.0.0
E86909_01
[May] [2017]



Table of Contents

1.	OPEN DEVELOPMENT TOOL INSTALLATION	1-1
1.1	INTRODUCTION	1-1
1.2	INSTALLING OPEN DEVELOPMENT TOOL	1-1
2.	SETTING UP DATABASE FOR OPEN DEVELOPMENT TOOL.....	1-1
3.	OPEN DEVELOPMENT TOOL (ODT) APPLICATION FULL DEPLOYMENT.....	1-1
4.	DEVELOPMENT TOOL (ODT) APPLICATION FULL DEPLOYMENT.....	1-1

1. Open Development Tool Installation


1.1 Introduction

This document explains about the creation of .war file using ODT (Open Development Tool) and setting up database for ODT installation.

1.2 Installing Open Development Tool


To install ODT, follow the steps given below:

1. Run 'FCUBSInstaller.bat' batch file to launch Oracle FLEXCUBE Investor Servicing Installer.
2. Click 'Next'. The following screen is displayed.



3. Click 'Open Development Tool'.

4. Click 'Next'. The following screen is displayed.



5. Select 'Build Application' as Oracle FLEXCUBE component for installation.
6. Specify the following details.

Operating System

Specify the operating system in which you are installing Oracle FLEXCUBE.


Application Server

Specify the application server on which you are installing Oracle FLEXCUBE.

DataBase Server


Specify the database server on which you are installing Oracle FLEXCUBE.

7. Click 'Next'. The following screen is displayed.



The screenshot shows the 'Installation Type' screen of the Oracle FLEXCUBE Investor Servicing application. The title bar is red with 'Oracle FLEXCUBE Investor Servicing' and the 'ORACLE' logo. The main area has a label 'Installation Type' and a sub-label 'FC Home' next to a text input field containing 'C:\CONSOLE_EXEC'. To the right of the input field is a yellow folder icon. At the bottom, there is a grey bar with four buttons: 'Log', 'Back', 'Next', and 'Exit'.

8. Specify the source directory. You can use the directory icon to browse to the directory location. The directory must contain FCHome. If the required folders are not present, then the error message is displayed.
9. Click 'Next'. The following screen is displayed:



The screenshot shows the 'Valid Patch List' screen of the Oracle FLEXCUBE Investor Servicing application. The title bar is red with 'Oracle FLEXCUBE Investor Servicing' and the 'ORACLE' logo. The main area has a label 'Valid Patch List' above a table. The table has four columns: 'No', 'Version', 'Type', and 'Select'. It contains one row with the values '1', '12.4.0.0.0', 'CONSOLE', and a checked checkbox. Below the table is a large empty rectangular area. At the bottom, there is a grey bar with four buttons: 'Log', 'Back', 'Next', and 'Exit'.

No	Version	Type	Select
1	12.4.0.0.0	CONSOLE	<input checked="" type="checkbox"/>

10. Select the Console type and click Next. The following screen is displayed:

Oracle FLEXCUBE Investor Servicing **ORACLE**

Build Process
Current screen provides an option to enter application jndi names and logger path

ODT JNDI

Logger Path

PROVIDER_URL

11. Specify the following details.

ODT JNDI

Specify the JNDI for the ODT.

Logger Path

Specify the path where the logs have to be written.

Provider_URL

Specify the provider URL.

12. Click 'Next'. The following screen is displayed.

The screenshot shows the 'Oracle FLEXCUBE Investor Servicing' window with the 'ORACLE' logo. The main section is titled 'Property File Creation' and contains the following elements:

- A header bar with 'Oracle FLEXCUBE Investor Servicing' and the 'ORACLE' logo.
- A title 'Property File Creation'.
- Text: 'Current screen provides an option for Enabling Single Sign on'.
- A checkbox labeled 'SSO Required' which is currently unchecked.
- A text input field labeled 'SSO KEY' containing the text 'DN'.
- Text: 'Authentication details maintained external to FLEXCUBE'.
- A checkbox labeled 'External Password Required' which is currently unchecked.
- A label 'Authentication Type' followed by a dropdown menu showing 'MSAD'.
- A checkbox labeled 'External User Login Required' which is currently unchecked.
- A scrollable text box containing the following text: 'Single sign-on (SSO) is a property of access control of multiple related, but independent software systems. With this property a user logs in once and gains access to all systems without being prompted to log in again at each of them. Conversely, Single sign-off is the property whereby a single action of signing out terminates access to multiple software systems. This screen provides an option for External Authentication. If External Authentication is not required, keep the'.
- A footer bar with four buttons: 'Log', 'Back', 'Next', and 'Exit'.

13. Here we set single sign on properties. Click 'Next'.

This is an external authentication window. If external authentication is not required, then uncheck all the options and click 'Next'. The following screen is displayed:

The screenshot shows a window titled "Oracle FLEXCUBE Investor Servicing" with the Oracle logo in the top right. The main heading is "Property File Creation". Below it, the instruction reads: "Choose Enable SSL option for Securing confidential user information". There are two checked checkboxes: "SSL Enabled?" and "OPSS Available". A red warning box contains the text: "If the SSL Enabled option is unchecked then this setting will put your application at risk. OFSS will not hold any responsibility for the Data Loss." Below this, a red informational box states: "OPSS □ CSF : A credential store is used for secure storage of credentials. CSF is used to access and perform operations on the credential store. The Credential Store Framework enables to manage credentials securely". At the bottom, there are four buttons: "Log", "Back", "Next" (with a mouse cursor over it), and "Exit".

Here we enable SSL information and click 'Next'. The following screen is displayed:

The screenshot shows a window titled "Oracle FLEXCUBE Investor Servicing" with the Oracle logo in the top right. The main heading is "Build Process". Below it, the instruction reads: "Specify the destination directory, application name". There are two input fields: "Destination Directory" with the value "D:\DESTTEMPDIR" and a folder icon to its right, and "Application Name" with the value "RAD". At the bottom, there are four buttons: "Log", "Back", "Next" (with a mouse cursor over it), and "Exit".


Destination Directory

Specify the destination directory. You can use the directory icon to browse to the source directory location.

Application Name


Specify the desired name for the application. For example,,: RAD.

Click 'Next. The following screen is displayed.




You can select all the source directories in this screen. The Installer will copy the sources from the multiple locations into the destination directory. You can have consolidated sources in the destination directory.

Click 'Copy' button to copy sources to the destination location. The following screen is displayed:




Once the copying process is done, the following screen is displayed:




Click 'Build' button to build the war file in the destination location.

The system displays the following screen when the copying is complete.




Click OK. The following screen is displayed:



2. Setting up Database for Open Development Tool

To set up database for Open Development Tool (ODT), follow the steps given below:

1. Run 'FCUBSInstaller.bat' batch file to launch Oracle FLEXCUBE Investor Servicing Installer.
2. Click 'Next', the following screen will be displayed.



3. Click 'Open Development Tool'.

- Click 'Next'. The following screen is displayed.

Oracle FLEXCUBE Investor Servicing ORACLE

Welcome To Oracle FLEXCUBE
Choose Oracle FLEXCUBE Component for installation.

Build Application
Database
Deploy Application

Operating System Linux
Application Server Weblogic
DataBase Server Oracle

Log Back Next Exit

- Select 'Database' as Oracle FLEXCUBE component for installation.
- Specify the following details.


Operating System

Specify the operating system in which you are installing Oracle FLEXCUBE.

Database Server


Specify the database server on which you are installing Oracle FLEXCUBE.

7. Click 'Next'. The following screen is displayed.



The screenshot shows the 'Installation Type' screen of the Oracle FLEXCUBE Investor Servicing application. The title bar is red with 'Oracle FLEXCUBE Investor Servicing' and the 'ORACLE' logo. The main area is titled 'Installation Type' and contains a label 'FC Home' followed by a text input field containing 'C:/CONSOLE_EXEC' and a folder icon. At the bottom, there are four buttons: 'Log', 'Back', 'Next' (with a mouse cursor over it), and 'Exit'.

Browse for Console_EXEC folder and click 'Next'. The following screen is displayed:



The screenshot shows the 'Valid Patch List' screen of the Oracle FLEXCUBE Investor Servicing application. The title bar is red with 'Oracle FLEXCUBE Investor Servicing' and the 'ORACLE' logo. The main area is titled 'Valid Patch List' and contains a table with the following data:

No	Version	Type	Select
1	12.4.0.0.0	CONSOLE	<input checked="" type="checkbox"/>

Below the table is a large empty rectangular area. At the bottom, there are four buttons: 'Log', 'Back', 'Next', and 'Exit'.


Select the console type and select 'Next'. The following screen is displayed:

The screenshot shows a software installation window titled "Oracle FLEXCUBE Investor Servicing" with the Oracle logo in the top right corner. The main content area is titled "Database Installation" and contains the instruction "Specify destination path." Below this, there is a label "Destination Directory" followed by a text input field containing the path "C:\BrnDbgs". To the right of the input field is a yellow folder icon. At the bottom of the window, there is a grey bar containing four buttons: "Log", "Back", "Next", and "Exit".


Destination Directory

Specify the destination directory. You can use the directory icon to browse to the source directory location.

The following screen is displayed:



Click 'Copy'. The following screen is displayed:



Click 'Copy' to copy the source from source directory to the destination directory. Once the source is copied, the following screen is displayed.

Name	Value
Username	installer
Password	••••••••
Service Name	testdb
IP Address	10.10.10.10
Port	1521
TNS Connect Descriptor	testdb.world

8. Specify the following schema details:

User Name

Specify the user name to access the schema.

Password

Specify the schema password for the above user name.

Service Name

Specify service name of database.

IP Address

Specify the IP address of the system where the database schema is installed.


Port

Specify the port number.

TNS Connect Descriptor


Specify a valid connect string that contains the details for database connectivity.

9. Once you have specified the details, click 'Test Connection' button to test the database schema connection.




The above message is displayed if the connection is established successfully.

10. Click 'Next'. The following screen is displayed.




11. Click 'Load ODT DDL' button to start compiling. The objects 'Type', 'Table', and 'Sequence' will be compiled and the count will be updated. You can verify the DDL objects compilation by comparing the current count and the release count. The release count is the number of files in the temporary folder to which the files are copied.



12. Click on ODT DDL log to see the log.

13. Click 'Next'. The following screen is displayed.



14. Click 'Load ODT Objects' button to compile APP objects.

The installer loads the functions, procedures, views, triggers and packages as per your selection and compiles them.



You can verify the application objects compilation by comparing the count shown in this screen with the release count.

15. Click 'ODT Objects Log' to view the log.

The log file 'LoadODTObj.log' will be available in the destination directory under the folder 'DBLogs'.

16. Click 'Next'. The following screen is displayed.

Oracle FLEXCUBE Investor Servicing **ORACLE**

Database Installation
Current screen Displays the number of invalids in the DB.

0%

Object Type	Invalid Count	Total Count
FUNCTION	0	0
PROCEDURE	0	4
VIEW	0	0
TRIGGER	0	0
PACKAGE	3	56
PACKAGE BODY	40	56

17. Click 'Invalids List' button to view the count of invalid objects in the database.

You can view the file 'InvalidList.txt' created by the installer in the destination directory under the folder 'DBLogs'.

18. Click 'Recompile' to re-compile any invalid objects If present. This reduces the invalid object count.



The Installer allows 'Recompile' multiple times in order to reduce the invalid objects count.

The following screen is displayed on successful re-compilation of ODT Objects.

Oracle FLEXCUBE Investor Servicing **ORACLE**

Database Installation
Current screen Displays the number of invalids in the DB.

0%

Object Type	Invalid Count	Total Count
FUNCTION	0	0
PROCEDURE	0	4
VIEW	0	0
TRIGGER	0	0
PACKAGE	0	56
PACKAGE BODY	0	56


Invalids List Recompile

Log Back Next Exit

The database is set up for the ODT installation.


3. Open Development Tool (ODT) Application Full Deployment

1. Launch Oracle FLEXCUBE Investor Servicing Installer.
2. Click on 'Next' to display the screen below.



3. Select 'Open Development Tool'.

4. Click 'Next' to display the screen below.



The image shows a software installation window titled "Oracle FLEXCUBE Investor Servicing" with the Oracle logo in the top right corner. The main content area has a heading "Welcome To Oracle FLEXCUBE" and a sub-heading "Choose Oracle FLEXCUBE Component for installation." Below this is a list box containing three items: "Build Application", "Database", and "Deploy Application". The "Deploy Application" item is currently selected and highlighted in blue. Underneath the list box are three configuration sections, each with a label and a dropdown menu: "Operating System" with "Linux" selected, "Application Server" with "Weblogic" selected, and "DataBase Server" with "Oracle" selected. At the bottom of the window is a grey bar containing four buttons: "Log" on the left, and "Back", "Next", and "Exit" on the right.

5. Select 'Deploy Application'.

Operating System

Select the server's operating system in which you are installing the FCIS application. Select the appropriate one from the adjoining drop-down list.


Application Server

Select 'Weblogic' from the adjoining drop down list.

Database Server

Select the database server in which you are installing the FCIS application. Select the appropriate one from the adjoining drop-down list.

6. WeblogicClick 'Next' to display the screen below.



The screenshot shows the 'Oracle FLEXCUBE Investor Servicing' application deployment window. It features a red header with the Oracle logo. The main section is titled 'Application Deployment' and instructs the user to 'Provide server details for connecting to the server.' Below this is a table with two columns: 'Name' and 'Value'. The table contains four rows: 'Admin IP' with value 'localhost', 'Admin Port' with value '7001', 'Admin Username' with value 'weblogic', and 'Server Admin Password' with a masked password '*****'. Below the table is a 'Test Connection' button. Underneath, the 'Type of Deployment' is set to 'Full Deployment' with a dropdown arrow. At the bottom, there are four buttons: 'Log', 'Back', 'Next', and 'Exit'.

Name	Value
Admin IP	localhost
Admin Port	7001
Admin Username	weblogic
Server Admin Password	*****

Test Connection

Type of Deployment: Full Deployment ▼

Log Back Next Exit

7. Specify the following details:

Admin IP

By default it will display local host and user can not edit it.

Admin Port

Specify port number of weblogic server.

Admin UserName

Specify the appropriate admin username of the weblogic application server.


Server Admin Password

Specify the appropriate server admin password of the weblogic application server.


Type of Deployment

Select 'Full Deployment'.

- Click 'Test Connection' to test the connection with the application server. On successful connection, the following message will be displayed.




- Click 'OK' and click 'Next' to display the screen below.



- Specify the following details

EAR Path

Select the application EAR to be deployed using the browse button.

 The Application EAR path cannot be copied and pasted on to the text box, thereby demanding the use of the browse button to select the EAR.

Property File Path

If the property file is internal to the application EAR, it gets displayed here on selection of EAR path. If the property file is external, specify the location. You can use the directory button to browser and select the directory.

Application Name

Application name gets displayed on selection of EAR path.


Application Context

Application context gets displayed on selection of EAR path..

Manage Resources

Check this box if resources are to be created along with deployment.

11. Click on 'Next' to display the screen below.



The screenshot shows a web application window titled "Oracle FLEXCUBE Investor Servicing" with the Oracle logo. The main content area is titled "Application Deployment" and contains the following text:

Provide server details for connecting to the server.

This screen lists the Resources that are required for Deployment

Resource Name	Resource Type
ODT_DATASOURCE	DataSource

At the bottom of the window, there are four buttons: "Log", "Back", "Next", and "Exit".

The current screen shows a list and type of resources that are created.

12. Click 'Next'. The following screen will be displayed.

S.No.	Property Name	Property Value
1	DataSource Driver	oracle.jdbc.OracleDriver
2	DataSource Type	NXA
3	Schema UserName	abc
4	Schema PAssword	***
5	IP Address	10.184.86.27
6	Port Number	1522
7	Service Name	avast1
8	Initial Capacity	15

13. Specify the following details

Resource ID

Select the data source needs to get created from the adjoining drop down list.

DataSource Driver

Specify the JDBC driver URL with which the connection is established.

Ex: oracle.jdbc.OracleDriver for Non-XA datasources

DataSource Type

Specify the type of datasource that is to be created, XA or Non-XA.

Schema Username

Specify the username of the schema to which the connection is established.

Schema Password

Specify the password of the schema.

IP Address

Specify to provide the host address of the schema.

Port Number

Specify the port number of schema.

Service Name

Specify the schema name.

Initial Capacity

The number of physical connections to create when creating the connection pool in the data source

Maximum Capacity

The maximum number of physical connections that this connection pool can contain.

Capacity Increment

The increment by which this JDBC connection pool's capacity is expanded.

Shrink Frequency

The number of seconds to wait before shrinking a connection pool that has incrementally increased to meet demand.

Connection Reserve Timeout

The number of seconds after which a call to reserve a connection from the connection pool will timeout.

14. Click 'Save Changes' to save the values provided In the table against corresponding value of Resource ID.

15. Click 'Test Connection' to try to establish connection with required details provided in the table.

16. Click on 'Next' to get the following screen.

Modify JDBC URL

17. Select 'Modify JDBC URL' for editing the generated URL.

18. If 'Modify JDBC URL' is selected, on click of 'Next' , the following screen will be displayed.

The screenshot shows a web application window titled 'Oracle FLEXCUBE Investor Servicing' with the Oracle logo. The main heading is 'JDBC Url' with a subtitle 'JDBC url to get connected to the Application server'. There is a 'Resource ID' dropdown menu set to 'ODT_DATASOURCE'. A large text area contains the JDBC URL 'jdbc:oracle:thin:@10.184.86.152:1522:avast1'. Below the text area are two buttons: 'Test Connection' and 'Save Changes'. At the bottom of the window are three buttons: 'Log', 'Back', 'Next', and 'Exit'.

19. Click 'Next', the following screen will be displayed.

The screenshot shows a web application window titled 'Application Full Deployment' with the subtitle 'Specify Server environment details for deployment'. There is a 'Domain Name' text field containing 'Default_domain' and a 'Get Details' button. Below this is a table with the following data:


S.No.	Server Name	Deploy
1	AdminServer	<input type="checkbox"/>
2	ManagedServer	<input type="checkbox"/>
3	ClusterTest	<input type="checkbox"/>
4	AVAST	<input type="checkbox"/>

Below the table is a large empty text area. At the bottom of the window are three buttons: 'Log', 'Back', 'Next', and 'Exit'.

20. The Domain Name shows the weblogic domains name.


21. Click 'Get Details', the list of available servers are displayed in the table. Atleast one server should be selected to proceed to next screen.

22. Click 'Next' to display the screen below.




23. Click 'Start Deployment' to begin the process of application deployment.


On successful deployment, you will get the following message and the screen is expected to look like below.



24. Click 'OK' and the following screen is displayed:




25. If the deployment is not successful, the 'Undeploy' button will be enabled.



26. Click 'Undeploy' for undeploying the partially deployed EAR from the server.


4. Development Tool (ODT) Application Full Deployment

1. Launch Oracle FLEXCUBE Investor Servicing Installer.
2. Click on 'Next' to display the screen below.



3. Select 'Open Development Tool'.

- Click 'Next' to display the screen below.



The image shows a software installation window titled "Oracle FLEXCUBE Investor Servicing" with the Oracle logo in the top right corner. The main content area is titled "Welcome To Oracle FLEXCUBE" and instructs the user to "Choose Oracle FLEXCUBE Component for installation." Below this is a list box containing three options: "Build Application", "Database", and "Deploy Application". The "Deploy Application" option is currently selected and highlighted. Underneath the list box are three dropdown menus for configuration: "Operating System" is set to "Linux", "Application Server" is set to "Weblogic", and "DataBase Server" is set to "Oracle". At the bottom of the window, there is a "Log" button on the left and "Back", "Next", and "Exit" buttons on the right.

- Select 'Deploy Application'.
- Specify the following details:

Operating System

Select the server's operating system in which you are installing the FCIS application. Select the appropriate one from the adjoining drop-down list.

Application Server


Select 'Websphere' from the adjoining drop down list.

Database Server

Select the database server in which you are installing the FCIS application. Select the appropriate one from the adjoining drop-down list.

SelectSelectWebsphere

7. Click on 'Next' to display the screen below.



The screenshot shows the 'Oracle FLEXCUBE Investor Servicing' application deployment screen. It features a red header bar with the Oracle logo. Below the header, the title 'Application Deployment' is displayed, followed by the instruction 'Provide server details for connecting to the server.' A table with two columns, 'Name' and 'Value', contains the following entries: 'Admin IP' with value 'localhost', 'Admin Port' with value '7001', 'Admin Username' with value 'weblogic', and 'Server Admin Password' with a masked password '*****'. Below the table is a 'Test Connection' button. Underneath, the 'Type of Deployment' is set to 'Full Deployment' via a dropdown menu. At the bottom of the window, there are four buttons: 'Log', 'Back', 'Next', and 'Exit'.

Name	Value
Admin IP	localhost
Admin Port	7001
Admin Username	weblogic
Server Admin Password	*****

Test Connection

Type of Deployment: Full Deployment ▼

Log Back Next Exit

8. Specify the following details:

Admin IP

Not applicable.

Admin Port

Not applicable.

Admin UserName

Specify the appropriate admin username of the websphere application server.


Admin Password

Specify the appropriate admin password of the websphere application server.


Type of Deployment

Select 'Full Deployment'.

9. Click on 'Test Connection' to test the connection with the application server. On successful connection, the following message will be displayed.



10. Click on 'OK' and click on 'Next' to display the screen below.



11. Specify the following details:

WAR Path

Select the application WAR to be deployed using the browse button.



The Application WAR path cannot be copied and pasted on to the text box, thereby demanding the use of the browse button to the select the WAR.

Property File Path

If the property file is internal to the application EAR, it gets displayed here on selection of EAR path. If the property file is external, specify the location. You can use the directory button to browser and select the directory..

Application Name

Application name gets displayed on selection of EAR path.


Application Context.

Application context gets displayed on selection of EAR path.

Manage Resources

Not Applicable for websphere application server.

12. Click 'Next' to display the screen below.



The screenshot shows a web application window titled "Oracle FLEXCUBE Investor Servicing" with the Oracle logo in the top right corner. The main content area is titled "Application Deployment" and contains the instruction "Provide server details for connecting to the server." Below this, there are several input fields: "Application Name" (a dropdown menu), "Status" (a text field), "Cell Name" (a text field), "Node Name" (a text field), "Target Type" (a dropdown menu with "Server" selected), "Server Name" (a text field), and "Cluster Name" (a text field). A "Get Details" button is located to the right of the "Application Name" dropdown. At the bottom of the window, there are four buttons: "Log", "Back", "Next", and "Exit".

13. Specify the following details:

Application Name

Not applicable for application full deployment.

Status

Not applicable for application full deployment.

Cell Name

Specify the appropriate cell name.

Node Name

Specify the appropriate node name.

Target Type


Select the appropriate target type.

Server Name


Specify the appropriate server name if the selected target type is 'Server'.

Cluster Name

Specify the appropriate cluster name if the selected target type is 'Cluster'.


 The values fed in the above screen are not validated at the screen level as a result of a limitation and hence, specify accurate information.

14. Click 'Next' to display the screen below.




15. Click 'Start Deployment' to begin the process of application deployment.

16. On successful deployment, you will get the following message is displayed:.



17. Click 'OK' and following screen is displayed:





Open Development Tool Installation
[May] [2017]
Version 12.4.0.0.0

Oracle Financial Services Software Limited
Oracle Park
Off Western Express Highway
Goregaon (East)
Mumbai, Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax: +91 22 6718 3001
www.oracle.com/financialservices/

Copyright © 2007, 2017, Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing. This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing. This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.