

Common Core - Electronic Messaging Service User Guide

Oracle Banking Payments

Release 14.3.0.1.4

Part No. F10815_01

Jan 2020

Common Core - Electronic Messaging Service User Guide
Oracle Financial Services Software Limited

Oracle Park

Off Western Express Highway
Goregaon (East)
Mumbai, Maharashtra 400 063
India

Worldwide Inquiries:

Phone: +91 22 6718 3000

Fax: +91 22 6718 3001

www.oracle.com/financialservices/

Copyright © 2017 - 2018, Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are “commercial computer software” pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Contents

| | |
|--|------------|
| 1. Preface | 1-1 |
| 1.1 Introduction..... | 1-1 |
| 1.2 Audience..... | 1-1 |
| 1.3 Documentation Accessibility..... | 1-1 |
| 1.4 Organization | 1-1 |
| 1.5 Glossary of Icons..... | 1-2 |
| 1.6 Related Documents..... | 1-2 |
| 2. EMS Maintenances | 2-1 |
| 2.1 Introduction..... | 2-1 |
| 2.2 Message Media Control Maintenance..... | 2-1 |
| 2.2.1 Maintaining Message Media Control | 2-2 |
| 2.2.2 Specifying File Prefix | 2-4 |
| 2.2.3 Saving Message Media Control Details..... | 2-4 |
| 2.2.4 Message Media Control Summary | 2-5 |
| 2.3 Media Maintenance | 2-5 |
| 2.3.1 Maintaining Message Media Details | 2-5 |
| 2.4 Message Queues Mapping Maintenance..... | 2-9 |
| 2.4.1 Invoking Message Queue Mapping Maintenance Screen | 2-9 |
| 2.5 Message Queue Maintenance..... | 2-10 |
| 2.5.1 Maintaining Message Queues | 2-10 |
| 2.6 SWIFT Message Notification Browser..... | 2-10 |
| 2.6.1 Viewing SWIFT Notification Messages..... | 2-11 |
| 2.7 SWIFT Net Service Definition..... | 2-13 |
| 2.7.1 Invoking SWIFTNet Service Definition Screen | 2-14 |
| 2.7.2 Viewing SWIFTNet Service Summary..... | 2-15 |
| 2.8 Mapping Rule Group | 2-15 |
| 2.8.1 Invoking Rule Group Mapping Screen..... | 2-16 |
| 2.8.2 Viewing Rule Group Mapping Summary..... | 2-16 |
| 2.9 Defining Rule Group | 2-17 |
| 2.9.1 Invoking Rule Group Definition Screen..... | 2-17 |
| 2.9.2 Viewing Rule Group Summary | 2-18 |
| 2.10 Routing Rule Definition..... | 2-18 |
| 2.10.1 Invoking Routing Rule Definition Screen | 2-19 |
| 2.10.2 Viewing Rule Definition Summary | 2-21 |
| 2.11 Defining Protocol Parameter | 2-22 |
| 2.11.1 Invoking Protocol Parameter Definition Screen..... | 2-22 |
| 2.11.2 Viewing Protocol Parameter Definition Summary..... | 2-23 |
| 2.12 File Transfer Adapter Connector Configuration..... | 2-23 |
| 2.12.1 Invoking File Transfer Adapter Connector Configuration Screen | 2-24 |
| 2.12.2 Viewing File Transfer Adapter Connector Configuration Summary..... | 2-25 |
| 2.13 Distinguished Name Definition | 2-26 |
| 2.13.1 Invoking Distinguished Name Definition Screen..... | 2-26 |
| 2.13.2 Viewing Distinguished Name Summary..... | 2-27 |

| | | |
|-----------|---|------------|
| 2.14 | Defining Debulk Rule | 2-27 |
| | 2.14.1 Invoking Debulk Rule Definition Screen | 2-28 |
| | 2.14.2 Viewing Debulk Rule Summary | 2-29 |
| 2.15 | Connectivity Operation Manager | 2-29 |
| | 2.15.1 Invoking Connectivity Operation Manager Screen | 2-30 |
| 2.16 | Outbound File Browser | 2-31 |
| 2.17 | Inbound File Browser | 2-32 |
| 2.18 | Defining Bulk Preference | 2-33 |
| | 2.18.1 Invoking Bulk Preference Definition Screen | 2-33 |
| | 2.18.2 Viewing Bulking Preference Definition Summary | 2-35 |
| 2.19 | Bulk Monitor | 2-36 |
| | 2.19.1 MQHA Connector Configuration | 2-38 |
| | 2.19.2 MQHA Connector Configuration Summary | 2-40 |
| | 2.19.3 ACK NACK Message Details | 2-41 |
| 3. | Function ID Glossary | 3-1 |

1. Preface

1.1 Introduction

This manual is designed to help acquaint you with the Common Core Electronic Messaging Service module of Oracle Banking Payments.

The module supports various types of media. Besides standard media modes like Mail, Telex and SWIFT you can also use other media types supported by the Media Control System (MCS) installed at the node at which the database of your branch is installed. Oracle Banking Payments gives native support for media like Mail, Telex, and SWIFT using EMS as the MCS.

You can further obtain information specific to a particular field by placing the cursor on the relevant field and striking <F1> on the keyboard.

1.2 Audience

This manual is intended for the following User/User Roles:

| Role | Function |
|---------------------------------------|---|
| Back office data entry clerk | Input functions for contracts |
| Back office managers/officers | Authorization functions |
| Product Managers | Product definition and authorization |
| End of Day operators | Processing during End of Day/Beginning of Day |
| Financial Controller/Product Managers | Generation of reports |

1.3 Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

1.4 Organization

This manual is organized as follows:

| Chapter | Description |
|-----------|--|
| Chapter 1 | <i>Preface</i> gives information on the intended audience. It also lists the various chapters covered in this User Manual. |
| Chapter 2 | EMS Maintenances explains the maintenance of various Messaging functions. |
| Chapter 3 | <i>Function ID Glossary</i> has alphabetical listing of Function/Screen ID's used in the module with page references for quick navigation. |

1.5 Glossary of Icons

This User Manual may refer to all or some of the following icons.

| Icons | Function |
|---|-------------|
|  | Exit |
|  | Add row |
|  | Delete row |
|  | Option List |

1.6 Related Documents

For further information on procedures discussed in the manual, refer to the Oracle Banking Payments manuals on:

- Common Procedures
- Accessibility

2. EMS Maintenances

2.1 Introduction

This chapter contains the following sections:

- [Section 2.2, "Message Media Control Maintenance"](#)
- [Section 2.3, "Media Maintenance"](#)
- [Section 2.4, "Message Queues Mapping Maintenance"](#)
- [Section 2.5, "Message Queue Maintenance"](#)
- [Section 2.6, "SWIFT Message Notification Browser"](#)
- [Section 2.7, "SWIFT Net Service Definition"](#)
- [Section 2.8, "Mapping Rule Group"](#)
- [Section 2.9, "Defining Rule Group"](#)
- [Section 2.10, "Routing Rule Definition"](#)
- [Section 2.11, "Defining Protocol Parameter"](#)
- [Section 2.12, "File Transfer Adapter Connector Configuration"](#)
- [Section 2.13, "Distinguished Name Definition"](#)
- [Section 2.14, "Defining Debulk Rule"](#)
- [Section 2.15, "Connectivity Operation Manager"](#)
- [Section 2.18, "Defining Bulk Preference"](#)

2.2 Message Media Control Maintenance

The messages that are sent from and delivered to your bank are transmitted and received over sources that are external to Oracle Banking Payments. We shall call these external sources Media Control Systems (MCS).

In a distributed environment, the database of a branch is located in a node or server. The MCS of the messages are also installed in a node. Thus, while defining an MCS, you also need to indicate the node in which it is installed.

An MCS can handle only one media, hence you need to set up several media control systems for the various media types maintained for your bank. Apart from indicating the media type for an MCS, you can indicate separate directories from which Oracle Banking Payments should read and write incoming and outgoing messages for a given media.

You can maintain MCS details in the 'Message Media Control Maintenance' screen. The details that you specify in this screen control the medium of delivery and reception of messages.

This section contains the following topic:

- [Section 2.2.1, "Maintaining Message Media Control"](#)
- [Section 2.2.2, "Specifying File Prefix"](#)
- [Section 2.2.3, "Saving Message Media Control Details"](#)

2.2.1 Maintaining Message Media Control

You can invoke 'Message Media Control Maintenance' screen by typing 'MSDMGMCS' in the field at the top right corner of the Application tool bar and clicking on the adjoining arrow button.

If you are maintaining details of a new media control system click the 'New' button on the Application toolbar. The 'Message Media Control Maintenance' screen is displayed without any details.

If you are calling an MCS record that has already been defined, double-click a record of your choice from the summary screen. In the 'Summary' screen, all the media control system records that you have entered will be displayed in a tabular form.

The screen is as shown below:

Message Media Control Maintenance

New Enter Query

Node *

Media Control System *

Media *

Status Active

Delivery Type Folder Queue

In Directory

Out Directory

File Prefix

Unix In-Directory

Unix Out-Directory

In Queue

Out Queue

Unix Swift Server

Microsoft Message Queue

WebSphere Messaging Queue

Fields

| Maker | Date Time: | Mod No | Record Status |
|---------|------------|--------|----------------------|
| Checker | Date Time: | | Authorization Status |

Exit

You can capture the following details on this screen.

Node

A node is the Database instance on which Oracle Banking Payments is installed. On assigning a code to an MCS, you can indicate the node or server at which the MCS is located. A branch's database is located in a node and an MCS is also installed in a node. Thus, while defining an MCS, you need to indicate the node at which it has been installed.

Media Control System

In Oracle Banking Payments, each media control system that you maintain is identified by a 15-character code called an MCS code. You can follow your own convention for devising this code.

The code that you assign an MCS should be unique as it is used to identify the external source.

Media

You need to also specify the media for which your bank is using the MCS. For example, if you set up an MCS say 'MCSSWIFT' and indicate the media type as SWIFT, it indicates that Oracle Banking Payments can receive and transmit SWIFT messages through the MCS 'MCSSWIFT'.

Status

You need to indicate the status of an MCS. The status options available are:

- Active and
- Passive


It is only when an MCS is active that messages will be directed to it. If, for instance, an MCS located at the node in which your branch operates malfunctions, you can indicate that the MCS is passive. In this case, Oracle Banking Payments will not write into or read from the directories on the node. No message will be routed through a passive MCS.

Delivery Type

You can specify the delivery type here. Oracle Banking Payments gives you two options viz. Folder and Queue. Depending on the selection you make, you must specify the details in the corresponding fields as follows.

- Folder – If you choose 'Folder' as the delivery type, you must specify the In Directory and the Out Directory. Further, after selecting 'Folder', if you check the option 'Unix Swift Server' for a UNIX SWIFT server, then you must specify the Unix In-Directory and the Unix Out-Directory. For a Windows Server the In-Directory and Out-Directory must be maintained.
- Queue – If you select 'Queue' as the delivery type, you must specify In Queue, Out Queue and the type of queue – i.e. 'Microsoft Message Queue' or WebSphere Messaging Queue'.

The following diagram illustrates a typical MCS setup:



In Directory and Out Directory

If the Delivery Type is 'Folder' and the SWIFT server is a Windows server then apart from indicating the node on which an MCS is located, you should specify the full path of the directories from which Oracle Banking Payments should read and write incoming and outgoing messages respectively.

File Prefix

For the MCS you are maintaining, you should identify the outgoing message files generated in a different media with unique prefixes. Enter the unique identifier in this field.

In Queue

If the Delivery type is Queue then you should enter the full path of the queue in the node or server into which the MCS should store the incoming message hand-off file. Oracle Banking Payments, by default, will pickup and read all incoming messages transmitted through the specified media from this queue.

Out Queue

Enter the full path of the queue in the node or server into which the message hand-off file from Oracle Banking Payments for the specified media should be stored. The MCS, which is also, located on the same node, will by default store the outgoing messages in this queue.

Unix Swift Server

At your bank, if the SWIFT server is on UNIX, check this option. Subsequently, in this screen, you should specify the default In and Out Directories for the SWIFT message hand-off files.

To continue with your normal banking operations you can connect to another node and indicate the directory on that node from which Oracle Banking Payments should read from and write into.

SWIFT Server on UNIX

If the SWIFT server at your bank is on UNIX, you should indicate it in this screen. Subsequently, you should specify the default In and Out Directories for the SWIFT message hand-off files.

Specifying the UNIX In-Directory

You can specify the full path of the directory on the SWIFT server where you would like to store incoming SWIFT message files. Oracle Banking Payments will pickup and process all incoming SWIFT message files from this directory.

Specifying the UNIX Out-Directory

In this screen, you can also specify the directory on the SWIFT server where you would like to store outgoing SWIFT message hand-off files.

2.2.2 Specifying File Prefix

For the MCS you are maintaining, you should identify outgoing message files generated in the media with unique prefixes. Oracle Banking Payments will automatically prefix outgoing message hand-off files for the MCS with the prefix that you specify.

2.2.3 Saving Message Media Control Details

After you have made the mandatory entries, save the record. An MCS record that you have created should be authorized by a user, bearing a different Login ID, before the End of Day process (EOD) is run.

2.2.4 Message Media Control Summary

You can invoke 'Message Media Control Summary' screen by typing 'MSSMGMCS' in the field at the top right corner of the Application tool bar and clicking on the adjoining arrow button.

Message Media Control Summary

Search Advanced Search Reset Clear All

Case Sensitive

Authorization Status [] Record Status []

Node [] Media Control System []

Media []

Records per page 15 1 Of 1 Go Lock Columns 0

| Authorization Status | Record Status | Node | Media Control System | Media | Status |
|----------------------|---------------|------|----------------------|-------|--------|
| | | | | | |

Exit

You can search using one or more of the following parameters:

- Authorization Status
- Record Status
- Node
- Media Control System
- Media

Once you have specified the search parameters, click 'Search' button. The system displays the records that match the search criteria for the following:

- Authorization Status
- Record Status
- Node
- Media Control System
- Media

Double click on the record to view the record details in the Message Media Control Maintenance screen. You can also export the details into file by clicking on 'Export' button

2.3 Media Maintenance

This section contains the following topic:

- [Section 2.3.1, "Maintaining Message Media Details"](#)

2.3.1 Maintaining Message Media Details

You can invoke the 'Message Media Maintenance' screen by typing 'MSDMEDMT' in the field at the top right corner of the Application tool bar and clicking on the adjoining arrow button.

If you are maintaining details of a new media type, select 'New' from the Actions Menu, or click new icon on the toolbar. The 'Message Media Maintenance' screen is displayed without any details.

If you are calling a Message Media Maintenance record that has already been defined, double-click a record from the summary screen. In the 'Summary' screen, all the media maintenance records that you have entered will be displayed in a tabular form.

The screen is as shown below:

The screenshot shows the 'Media Maintenance' application window. At the top, there are buttons for 'New' and 'Enter Query'. Below this, there are several input fields: 'Media Code *', 'Description *', 'Media Number', 'Message Suffix', 'Message Terminator', and 'Number of Characters'. To the right of these fields is the 'Media Priority *' field. Below the input fields are three checkboxes: 'Test Word Required', 'Stop Processing', and 'Padding Required'. A section titled 'Compatible Media' contains a table with one row: 'Compatible Media *'. At the bottom of the screen, there is a 'Fields' section with a table containing the following columns: 'Maker', 'Date Time:', 'Mod No', and 'Record Status'. Below this table, there are additional labels: 'Checker', 'Date Time:', and 'Authorization Status'. An 'Exit' button is located in the bottom right corner.

In this screen, you can maintain the following:

- The media types that can be used to transmit messages from and to your bank, and
- The compatible media for the media type you are maintaining.

For each media type that you maintain, you should indicate the following parameters:

Indicating a Code to Identify a Media Type

In Oracle Banking Payments, each media type that you maintain is identified with a fifteen-character code called 'Media Code'. You can follow your own convention for devising this code. A Media Type could be SWIFT, Mail, Telex, etc.

The code that you assign a media type should be unique as it is used to identify the media. When you need to indicate that a message should be transmitted through a particular media type, you just need to specify the code assigned to the media type. The message will be routed automatically through the media.

You can enter a short description of the media type that you are maintaining. The description will help you identify the code that it represents.

Opting for Message Markers

You can opt to append end-message markers to outgoing messages generated in a media. These markers are referred to as "Padding Characters" in Oracle Banking Payments. Padding characters would, typically, be a standard set of characters, probably repeated. The padding characters that you specify will be inserted, automatically, at the end of every outgoing message in the media. You can indicate the padding characters that mark the end of an outgoing message (in a specific media) in the Message Suffix field.

When defining a media, you can also capture the padding characters that mark the end of incoming messages in the media. The system identifies the end of an incoming message, in a file containing several messages, when it encounters the padding characters you have

captured for a media type. Enter the padded characters that mark the end of incoming messages in a media in the Message Terminator field.

Note

For Message suffix to be used for Outgoing messages, the 'Padding Required' option should be selected.

Repeating a Set of Padding Characters

If you opted to suffix an outgoing message with a set of padding characters, indicate in the 'Number of Characters' field the number of times the set should be repeated.

The padding characters will be suffixed to every outgoing message in the media as many times as you specify.

Halting the Processing of Messages

At any time, you can opt to halt the processing of messages in a specific media. To halt the processing of incoming and outgoing messages in a media, invoke this screen and navigate to the maintenance record for the media, and choose the 'Stop Processing' option. When you save your changes to the record, Oracle Banking Payments will stop processing messages in the media.

Indicating the Compatible Media for a Media Type

For each media type that you maintain, you can also indicate other media that are compatible. The format of compatible media should be similar.

For example, you are maintaining details for the media type 'mail'. You have indicated media type 'Fax' as compatible media.

In this case, whenever a message is faxed, it will be in the mail format defined for the message in the 'Advice Format File Maintenance' screen.

You can indicate compatible media by selecting the relevant media codes from the picklist available. To add compatible media for a media type, select the code that identifies the compatible media, and click add icon. To delete compatible media, select the codes that identify the media, and click delete icon.

Note

The compatible media that you indicate for a media type should have already been maintained as a media type.

Setting the Priority

While maintaining media types, you can set the usage priority for each media type that you maintain. Consequently, when dispatching messages to customers, the media type used for sending the message will be the one that is higher on the priority rating. For instance, let us assume that the following are the types of media that you bank uses to send advices to customers:

- SWIFT
- Mail
- Telex
- Fax

You have assigned the following priority to each of these media types:

| Media Type | Media Priority |
|-------------------|-----------------------|
|-------------------|-----------------------|

| | |
|-------|---|
| SWIFT | 2 |
| Mail | 1 |
| Telex | 4 |
| Fax | 3 |

When dispatching messages to customers, the system will, by default, select the media type in the ascending order of the priority that you have specified.

Note


The rating that you specify can be anything between 1 and 99. A rating of one would indicate that the usage of the particular media type is highest on the priority list; whereas, a rating of 99 indicates that the usage of the particular media type is of lowest priority.

Saving the Record

After you have made mandatory entries, save the record. A media maintenance record that you have created should be authorized by a user, bearing a different Login ID, before the End of Day processes are triggered. Click 'Exit' or 'Cancel' button to return to the application.

2.3.1.1 Media Maintenance Summary

You can invoke 'Message Media Control Summary' screen by typing 'MSSMEDMT' in the field at the top right corner of the Application tool bar and clicking on the adjoining arrow button.



You can search using one or more of the following parameters:

- Authorization Status
- Record Status
- Media Code
- Description
- Media Number

Once you have specified the search parameters, click 'Search' button. The system displays the records that match the search criteria:

Double click on the record to view the record details in the Media Maintenance screen. You can also export the details into file by clicking on 'Export' button

2.4 Message Queues Mapping Maintenance

This section contains the following topic:

- [Section 2.4.1, "Invoking Message Queue Mapping Maintenance Screen"](#)

2.4.1 Invoking Message Queue Mapping Maintenance Screen

For a combination of the following, you can specify the branch (queue) to which the message is to be routed:

- **Media** – represents the delivery media. Typically, your entry would be SWIFT.
- **BIC Code** - represents the receiver's BIC for which a message is to be routed to a specific queue in a particular branch. You can choose to specify the wildcard ALL entry in this field.
- **Message Type** - indicates the message type for which routing procedure is required. You can choose to specify the wildcard ALL option as well.
- **Currency** – indicates the currency of the incoming message. For example in an MT103 it would be from tag 32A. This is an additional parameter to determine the booking branch and queue. You can also choose to maintain the wildcard ALL entry.
- **Booking Branch** - indicates the branch in which incoming messages are routed. A set of all the branches having the same SWIFT BIC as that mentioned in the BIC code field is displayed in the option list.

This maintenance can be performed through the 'Message Queue Mapping Maintenance' screen. To invoke this screen, type 'MSDQMAP' in the field at the top right corner of the Application tool bar and click the adjoining arrow button.

| Maker | Date Time: | Mod No | Record Status |
|---------|------------|--------|----------------------|
| Checker | Date Time: | | Authorization Status |

While processing MT700 and MT701 messages the System ensures the following:

- MT700 and MT701 are routed to the branch using the Incoming Routing specifications maintained in this screen
- For MT700, in case the branch of the corresponding MT701 is different from that of the MT700 it is re-aligned to the branch of the MT700
- MT701 messages are processed only after the receipt of MT 700

Note

You can maintain the same BIC for the main branch as well as the sub-branch.

2.5 Message Queue Maintenance

This section contains the following topic:

- [Section 2.5.1, "Maintaining Message Queues"](#)

2.5.1 Maintaining Message Queues

All Incoming SWIFT and Non Swift Messages are routed through a messaging queue. You need to maintain different user queues to which incoming messages are directed. Users with appropriate rights are allowed to access a particular queue.

You can invoke the 'Message Queue Maintenance' screen by typing 'MSDQMNT' in the field at the top right corner of the Application tool bar and clicking the adjoining arrow button.

The screenshot shows the 'Message Queue Maintenance' application window. At the top, there is a title bar and a menu bar with 'New' and 'Enter Query'. Below the menu bar, there is a form with a 'Queue *' label and a 'Description' field. There are two radio buttons: 'Auto STP' and 'Collection Queue'. A 'Swift Messages Queue' section is visible, containing a table with a 'Message Code *' column. The table has one row with a checkbox and a text input field. At the bottom, there is a table with columns: 'Maker', 'Date Time:', 'Mod No', 'Record Status', and 'Authorization'. An 'Exit' button is located in the bottom right corner.

In this screen you can capture the following details for a queue:

- A name to identify the queue uniquely throughout the system.
- A short description of the queue
- The codes of various SWIFT and Non SWIFT messages that would be routed to this queue.
- Select collection queue flag if the unique queue you are maintaining here is a collection Queue.

Note

The codes of various SWIFT and Non SWIFT messages list in the grid is not applicable for the collection queue.

You can assign a message to more than one messaging queue. At the time of maintaining rules for a message (discussed in the subsequent sections of this document), you can select the appropriate queue for each rule from the list of queues to which the message is linked.

Select 'Add' from the Actions menu in the Application tool bar or click add icon to add a message to the queue being defined. To remove a message from the queue, Select 'Delete' from the Actions menu in the Application tool bar or click delete icon.

2.6 SWIFT Message Notification Browser

This section contains the following topic:

- [Section 2.6.1, "Viewing SWIFT Notification Messages"](#)

2.6.1 Viewing SWIFT Notification Messages

SWIFT provides the following two types of notification messages to Oracle Banking Payments:

- ACK/NACK acknowledgement messages indicating whether the message has been successfully delivered to SWIFTNet FIN service, from where it gets forwarded to the receiving system
- Delivery notification messages indicating whether the message was successfully delivered to the receiving system

You can access these notifications messages using 'SWIFT Message Notification Browser' screen. You can invoke this screen by screen by typing 'MSSNOTIB' in the field at the top right corner of the Application tool bar and clicking on the adjoining arrow button. The screen is as shown below:

In the above screen, you can base your queries on any or all of the following parameters and fetch records:

- Document Number
- Reference Number
- User Reference
- Swift Message Type
- Acknowledgement Status
- Delivery Notification
- Non-Delivery Warning
- Authorization Status
- Process Status

Select any or all of the above parameters for a query and click 'Search' button. The records meeting the selected criteria are displayed.

System displays the following details pertaining to the fetched records:

- Branch
- Document Number
- Reference Number
- Message Reference
- User Reference
- Swift Message Type
- Acknowledgement Status
- Delivery Notification
- No-Delivery Warning
- Acknowledgement Time
- Delivery Notification Time
- Non-Delivery Warning Time
- Receiver
- Branch Date
- Authorization Status
- Release Time
- Running Number
- Process Status

A back-ground job running on this browser updates the outgoing browser with the ACK/NAK and the delivery status of the message. The sender MUR from SWIFT is used to match the corresponding outgoing browser record.

2.6.1.1 ACK / NAK Message Details

Click the 'View ACK/NAK Message' Section in the Transaction View screen to invoke this sub screen.

The screenshot shows a window titled "Message Details" with a close button in the top right corner. The main content area displays "ACK/NAK Message" and "Document Number * 1922117466470000". Below this, there are several input fields for details:

| | | | |
|--------------------------|-------|----------------------|-------|
| Maker Id | _____ | Authorization Status | _____ |
| Release Time | _____ | Checker Date Stamp | _____ |
| Mod Number | _____ | Checker ID | _____ |
| Error Code | _____ | Error Description | _____ |
| Error Line No. | _____ | | |
| Hours(Receiver Timezone) | _____ | | |
| Mins(Receiver Timezone) | _____ | | |

An "Exit" button is located in the bottom right corner of the window.

2.6.1.2 Delivery Notification Message

Click the 'View Delivery Notification Message' Section in the Transaction View screen to invoke this sub screen.

The screenshot shows a window titled "Message Details" with a document number of 1922117466470000. The message type is "Delivery Notification Message". The form contains the following fields:

| | |
|--------------------------|----------------------|
| Maker Id | Authorization Status |
| Release Time | Checker Date Stamp |
| Mod Number | Checker ID |
| Error Code | Error Description |
| Error Line No. | |
| Hours(Receiver Timezone) | |
| Mins(Receiver Timezone) | |

An "Exit" button is located at the bottom right of the window.

2.6.1.3 Non-Delivery Warning Message

Click the 'View Non-Delivery Warning Message' Section in the Transaction View screen to invoke this sub screen.

The screenshot shows a window titled "Message Details" with a document number of 1922117466470000. The message type is "Non-Delivery Message". The form contains the following fields:

| | |
|--------------------------|----------------------|
| Maker Id | Authorization Status |
| Release Time | Checker Date Stamp |
| Mod Number | Checker ID |
| Error Code | Error Description |
| Error Line No. | |
| Hours(Receiver Timezone) | |
| Mins(Receiver Timezone) | |

An "Exit" button is located at the bottom right of the window.

2.7 SWIFT Net Service Definition

This section contains the following topic:

- [Section 2.7.1, "Invoking SWIFTNet Service Definition Screen"](#)
- [Section 2.7.2, "Viewing SWIFTNet Service Summary"](#)

2.7.1 Invoking SWIFTNet Service Definition Screen

You can invoke 'SWIFTNet Service Definition' screen by typing 'MSDSWTSR' in the field at the top right corner of the Application tool bar and clicking on the adjoining arrow button...

The screenshot shows the 'SWIFTNet Service Definition' application window. At the top, there are 'New' and 'Enter Query' buttons. The main area is titled 'Swift Net service Definition' and contains a 'Service Name' field with a red asterisk, and two radio buttons for 'Service Mode': 'Real Time(RT)' (which is selected) and 'Store And Forward (SnF)'. Below this, there are two panes: 'Requestor DN Details' and 'Responder DN Details'. Each pane has a 'Go' button and a '1 Of 1' indicator. At the bottom of the window, there are several fields: 'Maker', 'Checker', 'Date Time', 'Mod No', 'Record Status', and 'Authorization Status'. An 'Exit' button is located in the bottom right corner.

You can specify the following fields:

Service Name

Specify the SWIFTnet Service name.

Service Mode

Select any one of the service modes.

- Real Time- Choose this button to send and receive messages real-time. Real Time option is selected by default.
- Store and Forward - Choose this button to send and receive messages by storing them in a location and then forwarding them accordingly.

Requestor DN Details

Specify the DN that send request to the service. You must provide at least one DN.

Responder DN

Specify the DN that responds request to the service. You must provide at least one DN.

2.7.2 Viewing SWIFTNet Service Summary

You can invoke 'SWIFTNet Service Summary' screen by typing 'MSSSWTSR' in the field at the top right corner of the Application tool bar and clicking on the adjoining arrow button.

The screenshot shows a web application window titled "SwiftNet Service Definition Summary". At the top, there are buttons for "Search", "Advanced Search", and "Reset". Below these are two dropdown menus: "Authorization Status" and "Record Status". A text input field for "Service Name" is also present. Below the search fields, there is a pagination control showing "Records per page 15" and "1 Of 1" records. A table with columns "Authorization Status", "Record Status", and "Service Name" is displayed, but it is currently empty. An "Exit" button is located in the bottom right corner of the window.

You can search using one or more of the following parameters:

- Service Name
- Authorization Status
- Record Status

Once you have specified the search parameters, click 'Search' button. The system displays the records that match the search criteria for the following

- Service Name
- Authorization Status
- Record Status


2.8 Mapping Rule Group

This section contains the following topic:

- [Section 2.8.1, "Invoking Rule Group Mapping Screen"](#)
- [Section 2.8.2, "Viewing Rule Group Mapping Summary"](#)

2.8.1 Invoking Rule Group Mapping Screen

You can invoke 'Rule Group Mapping' screen by typing 'MSDRLMAP' in the field at the top right corner of the Application tool bar and clicking on the adjoining arrow button..



You can specify the following fields:

Rule Group Name


Specify the unique rule group name.

Module ID

Specify the module that needs to be mapped to the created rule group.

2.8.2 Viewing Rule Group Mapping Summary

You can invoke "Rule Group Mapping Summary" screen by typing 'MSSRLMAP' in the field at the top right corner of the Application tool bar and clicking on the adjoining arrow button.



You can search using one or more of the following parameters:

- Authorization Status
- Record Status

- Module ID

Once you have specified the search parameters, click 'Search' button. The system displays the records that match the search criteria for the following

- Authorization Status
- Record Status
- Rule Group Name
- Description

2.9 Defining Rule Group

This section contains the following topic:

- [Section 2.9.1, "Invoking Rule Group Definition Screen"](#)
- [Section 2.9.2, "Viewing Rule Group Summary"](#)

2.9.1 Invoking Rule Group Definition Screen

You can invoke 'Rule Group Definition' screen by typing 'MSDRLGRP' in the field at the top right corner of the Application tool bar and clicking on the adjoining arrow button..

You can specify the following fields:

Rule Group Name

Specify the unique rule group name.

Description

Enter a brief description of the rule group.

Rule Name

Specify the rule name from the rule definition screen.

Rule Priority

Specify the priority of the rule name.

Move To/ Swap

Specify whether the priority must be swapped or moved.

Move

Click the **Move** button to move the priority record.

2.10.1 Invoking Routing Rule Definition Screen

You can invoke 'Rule Definition' screen by typing 'MSDRLDFN' in the field at the top right corner of the Application tool bar and clicking on the adjoining arrow button..

The screenshot shows the 'Routing Rule Definition' application window. It is divided into several sections:

- Rule Details:** Includes a text field for 'Rule Name' and a larger text area for 'Rule Description'.
- Destination Details:** Includes a dropdown for 'Destination Type' (set to 'Folder'), a text field for 'Folder Path', a text field for 'Queue Jndi Name', a dropdown for 'Protocol Type', a text field for 'Protocol Name', a text field for 'Swift Net Connectivity', and a text field for 'Bulk Rule Name'.
- Expression Details:** A table with columns: Expression Section, Scope, LOP Type, LOP Data Type, Left Operand, Operator, and ROF. It shows '1 Of 1' entries.
- Parameter Definition:** A table with columns: Param Name, Parameter Value, and Param Types. It also shows '1 Of 1' entries.
- Footer:** Contains fields for 'Maker/Checker', 'Date Time', 'Mod No', 'Record Status/Authorization', and an 'Exit' button.

You can specify the following fields:

Rule Name

Specify the unique rule name.

Description

Enter a brief description of the rule name.

Destination Type

Specify the type of destination to which the messages matching the rule criteria is being sent. Select any of the options given below:

- SWIFT connector
- Bulker
- Folder
- Queue

Folder Path

Specify the folder path if the destination is folder.

Queue JNDI Name

Specify JNDI name of the Queue. This is mandatory if the destination type is Queue.

Protocol Type

Specify the type of Protocol. Select from the following option:

- FTA

Note

This is mandatory if the destination is SWIFTNet.

Protocol Name

Specify the required protocol for the selected protocol.

SWIFTNet Connectivity

Specify the name of the connector if the destination type is SWIFTNet.

Bulk Rule Name

Specify the bulk rule name. Alternatively, you can select the bulk rule name from the option list. The list displays all valid values.

Expression Section

Specify the expression section

Scope

Specify the scope.

Left Operand Type

Select the left operand type.

Left Operand Data Type

Select the left operand data type.

Left Operand

Specify the left operand. Alternatively, select the left operand from the option list. The list displays all valid values.

Operator

Select the operator.

Right Operand Type

Select the right operand type.

Right Operand Data Type

Select the right operand data type.

Right Operand

Specify the right operand. Alternatively, select the right operand from the option list. The list displays all valid values.

Scope

Specify the scope.

Logical Operators

Select the logical operators from the drop-down list.

Pre Defined Functions

Select the pre defined functions from the drop-down list.

Parameter Name

Specify the parameter name.

Parameter Value

Specify the value of the parameter.

Parameter Type

Specify the parameter type.

Expression For

Select the expression from the drop-down list.

Final Expression

Specify the final expression.

Build Expression

Click Build Expression to build the expression.

2.10.2 Viewing Rule Definition Summary

You can invoke “Rule Definition Summary” screen by typing ‘MSSRLDFN’ in the field at the top right corner of the Application tool bar and clicking on the adjoining arrow button.

The screenshot shows a web application window titled "Routing Rule Definition Summary". At the top, there are search options: "Search", "Advanced Search", and "Reset". Below this, there are several search criteria fields: "Authorization Status" (a dropdown menu), "Record Status" (a dropdown menu), "Rule Name" (a text input field with a magnifying glass icon), "Rule Description" (a text input field with a magnifying glass icon), "Rule Group Name" (a text input field with a magnifying glass icon), and "Destination Type" (a dropdown menu). Below the search fields, there is a pagination control showing "Records per page: 15", "1 Of 1", and a "Go" button with a dropdown menu showing "0". Below the pagination, there is a table with the following columns: "Authorization Status", "Record Status", "Rule Name", "Rule Description", "Rule Group Name", and "Destination Type". The table is currently empty. At the bottom right of the window, there is an "Exit" button.

You can search using one or more of the following parameters:

- Authorization Status
- Record Status
- Rule Name
- Rule Description
- Rule Group Name
- Destination Name

Once you have specified the search parameters, click 'Search' button. The system displays the records that match the search criteria for the following

- Authorization Status
- Record Status
- Rule Name
- Rule Description

- Rule Group Name
- Destination Type

2.11 Defining Protocol Parameter

This section contains the following topic:

- [Section 2.11.1, "Invoking Protocol Parameter Definition Screen"](#)
- [Section 2.11.2, "Viewing Protocol Parameter Definition Summary"](#)

2.11.1 Invoking Protocol Parameter Definition Screen

You can invoke 'Protocol Parameter Definition' screen by typing 'MSDPTPRM' in the field at the top right corner of the Application tool bar and clicking on the adjoining arrow button...

The screenshot shows the 'Protocol Parameter Definition' application window. At the top, there is a title bar and a menu bar with 'New' and 'Enter Query'. Below the menu bar, there are several input fields: 'Protocol Parameter Name *' (with a red asterisk indicating a required field), 'Description', and 'Protocol Type' (which is a dropdown menu currently showing 'MQHA'). Below these fields is a section titled 'Overlapping Parameter Set' which contains a table with two columns: 'Parameter *' and 'Value'. The table is currently empty. At the bottom of the window, there are several fields for user information: 'Maker', 'Date Time', 'Mod No', and 'Record Status'. There is also an 'Exit' button in the bottom right corner.

You can specify the following fields:

Protocol Parameter Name

Specify the name of the Protocol Parameter.

Description

Specify the description of the Protocol Parameter set.

Protocol Type Mode

The name of the protocol for which parameter list is defined. Select any of the option given below:

- FTA

Parameters

Specify the parameters for the protocol.

Value

Specify the value of the parameter.

2.11.2 Viewing Protocol Parameter Definition Summary

You can invoke “Protocol Parameter Definition Summary” screen by typing ‘MSSPTPRM’ in the field at the top right corner of the Application tool bar and clicking on the adjoining arrow button.

The screenshot shows a web application window titled "Protocol Parameter Definition Summary". At the top, there are search options: "Search", "Advanced Search", and "Reset". Below this, there are two dropdown menus for "Authorization Status" and "Record Status", and a text input field for "Protocol Parameter Name" with a search icon. A pagination bar shows "Records per page 15", "1 Of 1", and a "Go" button with a value of "0". The main area contains a table with columns: "Authorization Status", "Record Status", "Protocol Parameter Name", "Description", and "Protocol Type". The table is currently empty. An "Exit" button is located in the bottom right corner.

You can search using one or more of the following parameters:

- Protocol Parameter Name
- Authorization Status
- Record Status

Once you have specified the search parameters, click 'Search' button. The system displays the records that match the search criteria for the following

- Protocol Parameter Name
- Description
- Authorization Status
- Record Status

2.12 File Transfer Adapter Connector Configuration

You have to create below folder structure for the Swiftnet connectivity:

1. Create a application base directory as per the path mentioned in the mstm_ems_system_parameters (APP_BASE_DIR)
2. Create below folder structure in the application base directory:
 - payload\EMS_OUT
 - xsl
3. In the Xsl folder copy all the xsl required for message transformation

This section contains the following topic:

- [Section 2.12.1, "Invoking File Transfer Adapter Connector Configuration Screen"](#)
- [Section 2.12.2, "Viewing File Transfer Adapter Connector Configuration Summary"](#)

2.12.1 Invoking File Transfer Adapter Connector Configuration Screen

You can invoke 'File Transfer Adapter Connector Configuration' screen by typing 'MSDFTACN' in the field at the top right corner of the Application tool bar and clicking on the adjoining arrow button...

You can specify the following fields:

Operation Type

Select the type of connectivity. Choose between Inbound and Outbound.

Host Code

Specify the host code.

Parameter File Required

Check this box if FCM creates or receives a Parameter File corresponding to each and every data file in configured file directory along with data file.

Data file LAU

Check this box if FCM calculates the LAU of Data File and puts the calculated value in parameter file.

Parameter File LAU

Check this box if parameters defined at emission profile of SAG side are overridden by information in companion file.

Allow Overriding on SAG Profile

Check this box if parameters defined at the emission profile of SAG side will be overridden by information in Companion file.

File Directory

Specifies store details of emission directory for outbound connectivity and reception directory for inbound flow.

Log Directory

Specifies the responses from SAG.

Success Directory

For Outbound connectivity, Delivery notification response related to file transfer status from the SAG are placed in this directory. For inbound connectivity file transfer, success status files are placed in this folder.

Debulk Required

Check this box, if debulk is required for inbound messages.

Debulk Rule Name

Specifies the debulk rule name.

Node

Specifies the node details. This is mandatory for inbound.

Media

Specifies the media details. This is mandatory for inbound.

Media Control System

Specifies the media control system. This is mandatory for inbound.

2.12.2 Viewing File Transfer Adapter Connector Configuration Summary

You can invoke “File Transfer Connector Configuration Summary” screen by typing ‘MSSFTACN’ in the field at the top right corner of the Application tool bar and clicking on the adjoining arrow button.

| Authorization Status | Record Status | FTA Connector Name | Operation Type |
|----------------------|---------------|--------------------|----------------|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

You can search using one or more of the following parameters:

- FTA Connector Name
- Operation Mode
- Auth Status
- Record Status

Once you have specified the search parameters, click 'Search' button. The system displays the records that match the search criteria for the following:

- FTA Connector Name
- Operation Mode
- Auth Status
- Record Status

2.13 Distinguished Name Definition

This section contains the following topic:

- [Section 2.13.1, "Invoking Distinguished Name Definition Screen"](#)
- [Section 2.13.2, "Viewing Distinguished Name Summary"](#)

2.13.1 Invoking Distinguished Name Definition Screen

You can invoke 'Distinguished Name Definition' screen by typing 'MSDDSTNM' in the field at the top right corner of the Application tool bar and clicking on the adjoining arrow button...

The screenshot shows a software window titled "Distinguished Name Definition". The window has a menu bar with "New" and "Enter Query". Below the menu bar, there are three input fields: "Distinguished Name ID *", "Distinguished Name *", and "Description". At the bottom of the window, there is a status bar with the following fields: "Maker", "Date Time:", "Mod No", "Record Status", "Checker", "Date Time:", and "Authorization". An "Exit" button is located in the bottom right corner of the status bar.

You can specify the following fields:

Distinguished Name ID

Specify the unique identification of the distinguished name.

Distinguished Name

Specify the distinguished name to identify the entity that sends or gets messages.

Description

Specify the description of the distinguished name.

2.13.2 Viewing Distinguished Name Summary

You can invoke “Distinguished Name Summary” screen by typing ‘MSSDSTNM’ in the field at the top right corner of the Application tool bar and clicking on the adjoining arrow button.

Distinguished Name Definition Summary

Search Advanced Search Reset Clear All

Case Sensitive

Authorization Status Record Status

Distinguished Name ID Distinguished Name

Records per page 15 1 Of 1 Go Lock Columns 0

| Authorization Status | Record Status | Distinguished Name ID | Distinguished Name | Description |
|----------------------|---------------|-----------------------|--------------------|-------------|
|----------------------|---------------|-----------------------|--------------------|-------------|

Exit

You can search using one or more of the following parameters:

- Distinguished Name Id
- Distinguished Name
- Authorization Status
- Record Status

Once you have specified the search parameters, click ‘Search’ button. The system displays the records that match the search criteria for the following:

- Distinguished Name Id
- Distinguished Name
- Description
- Authorization Status
- Record Status

2.14 Defining Debulk Rule

This section contains the following topic:

- [Section 2.14.1, "Invoking Debulk Rule Definition Screen"](#)
- [Section 2.14.2, "Viewing Debulk Rule Summary"](#)

2.14.1 Invoking Debulk Rule Definition Screen

You can invoke 'Debulk Rule Definition' screen by typing MSDDEBRL' in the field at the top right corner of the Application tool bar and clicking on the adjoining arrow button...

The screenshot shows a web application window titled "Debulk Rule Definition". The window has a "New" button in the top left corner. The main area contains a form with the following fields:

- Debulk Rule Name ***: A text input field.
- Payload Delimiter**: A text input field.
- Protocol**: A dropdown menu with "MQHA" selected.
- Decompression Required**: A checkbox.
- Description**: A text input field.
- Decompression Type**: A dropdown menu.

At the bottom of the window, there is a table with the following columns: "Maker", "Checker", "Date Time:", "Mod No", "Record Status", and "Authorization Status". An "Exit" button is located in the bottom right corner.

You can specify the following fields:

De bulk Rule Name

Specify the name of the debulk file.

Payload Delimiter

Specify the delimiter between payloads.

Protocol

Select the type of protocol.

Decompression Required

Check this box if debulk processing requires decompression.

Decompression Type

Select the type of decompression. Choose among the following:

- ZIP
- GZIP

2.14.2 Viewing Debulk Rule Summary

You can invoke “Debulk Rule Summary” screen by typing ‘MSSDEBRL’ in the field at the top right corner of the Application tool bar and clicking on the adjoining arrow button.

Debulk Rule Definition Summary

Search Advanced Search Reset Clear All

Case Sensitive

Authorization Status [dropdown] Record Status [dropdown]

Debulk Rule Name [input] Protocol [dropdown]

Records per page 15 1 Of 1 Go Lock Columns 0

| Authorization Status | Record Status | Debulk Rule Name | Payload Delimiter | Protocol |
|----------------------|---------------|------------------|-------------------|----------|
| | | | | |

Filter

You can search using one or more of the following parameters:

- Authorization Status
- Record Status
- Debulk Rule Name

Once you have specified the search parameters, click ‘Search’ button. The system displays the records that match the search criteria for the following:

- Authorization Status
- Record Status
- Debulk Rule Name
- Payload Delimiter
- Debulk File Type


2.15 Connectivity Operation Manager

This section contains the following topic:

- [Section 2.15.1, "Invoking Connectivity Operation Manager Screen"](#)

2.15.1 Invoking Connectivity Operation Manager Screen

You can invoke 'Connectivity Operation Manager' screen by typing 'MSDCNMGR' in the field at the top right corner of the Application tool bar and clicking on the adjoining arrow button...



You can specify the following fields:

Connectivity

Specify the required connectivity line.

Operation Type

Select the type of operation.

Status

Specify the display line status.

Start


Click the Start button to start the connectivity line.

Stop

Click the Stop button to start the connectivity line.

2.16 Outbound File Browser

You can use the outbound file browser for searching and viewing the outbound files. To invoke the screen, type 'MSSFLBRW' in the field at the top right corner of the application toolbar and click the adjoining arrow button.




The screenshot shows the 'Outbound File Browser' application window. At the top, there is a search bar with options for 'Search', 'Advanced Search', 'Reset', and 'Clear All'. Below this is a 'Case Sensitive' section with two columns of search criteria, each with a text input field and a magnifying glass icon: File Reference Number, File Type, Generated Date, Handoff Status, File Status, Media, Network Code, and Module. Below the search criteria is a control bar with 'Records per page' set to 15, navigation arrows, '1 Of 1', a 'Go' button, and 'Lock Columns' set to 0. The main area is a table with columns: File Reference Number, File Type, Generated Date, Handoff Status, Receiver BIC, Sender BIC, File Format Type, File Status, and Media. The table is currently empty. At the bottom right, there is an 'Exit' button.

You can search for the records based on one or more of the following parameters:

- File name of the bulked file
- Bulk reference number
- Generated date
- Status
- Bulk preference

Once you have specified the above details, click 'Execute Query' button. The system displays the records that match the search criteria. You can double-click a record to view the details in the 'Outbound File Browser Details' (MSDFLBRW) screen.



The screenshot shows the 'Outbound File Browser Details' application window. The window title is 'New'. The main area is a large, empty white space. At the bottom right, there is an 'Exit' button.

You can view the following details in this screen.

- File name

- Bulk reference number
- File ID
- Generated date
- Generated time
- Status
- Bulk preference
- Number of transactions
- File size

You can resend the selected file from this screen using the 'Resend' button.

2.17 Inbound File Browser

You can use the inbound file browser for searching and viewing the inbound files. To invoke the screen, type 'MSSIFBRW' in the field at the top right corner of the application toolbar and click the adjoining arrow button.

You can search for the records based on one or more of the following parameters:

- File name
- Received date
- Status
- Logical file name
- Transaction ID
- File Act connector name

Once you have specified the above details, click 'Execute Query' button. The system displays the following details of records that match the search criteria.

- File name
- Received Date
- Received Time

- Status
- File Size
- Logical File Name
- Transaction Id
- FileAct Connector Name
- Error Code
- Error Parameter
- Error Description

2.18 Defining Bulk Preference

This section contains the following topic:

- [Section 2.18.1, "Invoking Bulk Preference Definition Screen"](#)
- [Section 2.18.2, "Viewing Bulking Preference Definition Summary"](#)

2.18.1 Invoking Bulk Preference Definition Screen

You can invoke 'Bulk Preference Definition' screen by typing 'MSDBLKRL' in the field at the top right corner of the Application tool bar and clicking on the adjoining arrow button...

You can specify the following fields:

Bulk Preference Name

Specify the name used for storing the Bulk Preference.

Volume Restriction Required?

Check this box to configure volume based bulking.

Maximum number of messages

Specify the maximum number of messages that can be stored in a bulk file.

Minimum number of messages

Specify the maximum number of messages that can be stored in a bulk file.

Maximum size in KB

Specify the distinguished name to identify the entity that sends or gets messages.

Minimum size in KB

Specify the distinguished name to identify the entity that sends or gets messages.

Size Restriction Required

Check this field to configure size based bulking.

Scheduler Type

Select the type of scheduler. Choose any one of the following:

- Time Based
- Frequency

Start Time

Specify the Start Time of the trigger. Enter the format in HH:MM format.

End Time

Specify the Start Time of the trigger. Enter the format in HH:MM format.

Time Interval in Min

Specify the interval of the repeat in MM format.

Scheduling No

Specify the scheduling sequence.

Start Hour

Specify the start hour of the scheduling sequence.

Start Min

Specify the start minute for frequency based scheduler.

Bulk File Name Prefix

Specify the prefix to indicate the name of the bulk file.

Maximum size of a file of KB

Specify the maximum size of a bulk file in KB.

Payload Delimiter

Specify the delimiter while bulking messages.

Maximum settlement amount for a file

Specify the maximum settlement for a file that must be considered while bulking messages.

File Format

Select the file that must be used while bulking messages.

File Type

Select the file type that must be used while bulking messages.

Compression Required

Check this box to indicate that file compression is required.

Compression Type

Specify the required type of compression.

Destination Type

Specify the type of destination.

- Folder
- Queue
- SwiftNet Connectivity

If destination is Swiftnet connectivity then a field swiftnet connectivity needs to be selected from LOV which gives the list of connectivity lines.

Folder Path

Specify the user defined destination folder path.

Queue JNDI Name

Specify JNDI name of the Queue if the destination type is Queue.

SwiftNet Connectivity

Select the swiftnet connectivity from the option list.

Protocol Type

Select the type of Protocol.

- FTA

Protocol Name

Specify the protocol name required for FTA protocol.

2.18.2 Viewing Bulking Preference Definition Summary

You can invoke “Bulking Preference Definition Summary” screen by typing ‘MSSBLKRL’ in the field at the top right corner of the Application tool bar and clicking on the adjoining arrow button.

The screenshot displays the 'Bulking Preference Definition Summary' application window. The window title is 'Bulking Preference Definition Summary'. The interface includes a search bar with the text 'MSSBLKRL' and buttons for 'Search', 'Advanced Search', 'Reset', and 'Clear All'. Below the search bar, there are fields for 'Authorization Status', 'Record Status', 'Bulk Preference Name', and 'Bulk Initiated'. A table below shows columns for 'Authorization Status', 'Record Status', 'Bulk Preference Name', 'Max Number of Messages', 'Size (in KB)', 'Bulk File Name Prefix', and 'Maximum size of'. The table is currently empty. At the bottom right, there is an 'Exit' button.

You can search using one or more of the following parameters:

- Authorization Status
- Record Status
- Bulk Preference Name

- Bulk Initiated

Once you have specified the search parameters, click 'Search' button. The system displays the records that match the search criteria for the following:

- Bulking Preference Name
- Frequency
- Max Number of Messages
- Size (in KB)
- File Format
- Bulk Filename Prefix
- Maximum size of bulk file (in KB)
- Bulk Initiated
- Destination Type
- Auth Status
- Record Status

2.19 Bulk Monitor


You can monitor the messages and executions in bulk using 'Bulk Monitor' screen. To invoke this screen, type 'MSSBLKMN' in the field at the top right corner of the application toolbar and click the adjoining arrow button.

You can search for the records based on one or more of the following parameters.

- Execution start time
- Execution end time
- Bulk preference
- Status
- Number of files generated

Once you have specified the search parameters, click 'Execute Query' button. The system displays the following details of the records that match the filter criteria.

You can view the details of each record in the results. Double-click a record from the results to view the details in 'Bulk Monitor Detail' (MSDBLKMN) screen.



This screen displays the following details of the record.

- Process reference number
- Execution start date
- Execution start time
- Execution end date
- Execution end time
- Status
- Bulk preference name
- Number of files generated
- Error code
- Error parameter
- Error description

You can regenerate the files by clicking 'Regenerate' button. You can also bulk a selected bulk preference ad-hoc using 'Initiate Adhoc Bulking' button.

2.19.1 MQHA Connector Configuration

To invoke this screen, type 'MSDMQHAC' in the field at the top right corner of the application toolbar and click the adjoining arrow button.

The screenshot shows the 'MQHA Connector Configuration' application window. The window title is 'MQHA Connector Configuration' and it has a menu bar with 'New' and 'Enter Query'. The form is divided into several sections: 1. General Configuration: 'MQHA Connector Name *' (text field), 'Operation Mode' (dropdown menu with 'Inbound' selected), 'Service Mode' (radio buttons for 'Real Time(RT)' and 'Store And Forward (SnF)'), 'Product Name *', 'Product Version *', 'Vendor Name *', 'Node', 'Media', 'Media Control System', and 'Host Code'. 2. MQHA Details: 'SAG Login Mode' (dropdown menu with 'Strict SNL' selected), 'SAG Message Partner', and 'Authorization DN *'. 3. Details of Clients: 'SNF Queue'. 4. Request Queue Manager Details: 'Client Request Queue', 'Get File Queue', and 'Server Request Queue'. 5. Response Queue Manager Details: 'Client Response Queue', 'LFT Reply Queue', 'Server Response Queue', and 'Put File Queue'. 6. Debulk Preferences: 'Debulk Required' (checkbox) and 'Debulk Rule Name'. At the bottom, there is a status bar with fields for 'Maker', 'Checker', 'Date Time:', 'Mod No', 'Record Status', 'Authorization Status', and an 'Exit' button.

MQHA Connector Name

Specify the MQHA Connector Name.

Operation Mode

Select the Operation Mode from the drop down.

Service Mode

Select any of the following modes:

- Real Time(RT)
- Store And Forward (SnF).

Product Name

Specify the Product Name.

Product Version

Specify the Product Versionx'

Vendor Name

Specify the Vendor Name.

Node

Specify the node from the LOV.

Media

Specify the media from the LOV.

Media Control System

Specify the media control system.

Host Code

Select the Host code from the LOV.

MQHA Details

SAG Login Mode

Select the SAG Login Mode from the drop down.

Transfer End Point

Specify the Transfer End Point.

SAG Message Partner

Specify the SAG Message Partner.

Authorization DN

Select the Authorization DN from the LOV.

Details of Clients

SNF Queue

Specify SNF Queue details.

Request Queue Manager Details

Client Request Queue

Specify the Client Request Queue details.

Server Request Queue

Specify the Server Request Queue details.

Get File Queue

Specify the Get File Queue details.

Response Queue Manager Details

Client Response Queue

Specify the Client Response Queue details.

Server Response Queue

Specify the Server Response Queue details.

LFT Reply Queue

Specify the LFT Reply Queue details.

Put File Queue

Specify the Put File Queue details.

Debulk Preferences

Debulk Required

Check this box to specify the debulk details.

Debulk Rule Name

Specify the Debulk Rule Name from the LOV.

2.19.2 MQHA Connector Configuration Summary

To invoke this screen, type 'MSSMQHAC' in the field at the top right corner of the application toolbar and click the adjoining arrow button.

MQHA Connector Configuration Summary

Search Advanced Search Reset Clear All

Case Sensitive

Authorization Status [] Record Status []

MQHA Connector Name [] Operation Mode []

Records per page 15 1 Of 1 Go Lock Columns 0

| Authorization Status | Record Status | MQHA Connector Name | Operation Mode | Product Name | Product Version | Vendor Name |
|----------------------|---------------|---------------------|----------------|--------------|-----------------|-------------|
| | | | | | | |

Exit

You can search for the records based on one or more of the following parameters.

- Authorization Status
- Record Status
- MQHA Connector Name
- Operation Mode

Once you have specified the search parameters, click 'Search' button. The system displays the records that match the search criteria for the following:

- Authorization Status
- Record Status
- MQHA Connector Name
- Operation Mode
- Product Name
- Product Version
- Vendor Name

2.19.3 ACK NACK Message Details

To invoke this screen, type 'MSDVWNOT' in the field at the top right corner of the application toolbar and click the adjoining arrow button.

The screenshot shows a web application window titled "ACK NACK Message Details". At the top, there is a search bar with the text "Enter Query". Below this is a large, empty text area labeled "Message". To the left of the message area, there are several input fields: "Document Number*" (with a red asterisk), "Maker ID", "Release Time", "Mod Number", "Error Code", "LBL_ERROR_LINE", "LBL_HRS", and "LBL_MINS". To the right of the message area, there are more input fields: "Authorization Status" (a dropdown menu), "Checker Date Stamp", "LBL_CHECKER_ID", and "Error Description". At the bottom right corner of the window, there is a blue "Exit" button.

Document Number

Specify the Document Number.

Message

Specify the Message details.

Maker ID

Specify the Maker ID:

Release Time

Specify the Release Time.

Mod Number

Specify the Mod Number.'

Error Code

Specify the Error Code.

LBL_ERROR_LINE

Specify the Error Line.

LBL_HRS

Specify the hours.

LBL_MINS

Specify the minutes.

Authorization Status

Specify the Authorization Status.

Checker Date Stamp

Specify the Checker Date Stamp details.

LBL_CHECKER_ID

Specify the Checker ID.

Error Description

Specify the Error Description details.

3. Function ID Glossary

M

MSDBLKMN
MSDBLKRL
MSDCNMGR
MSDDEBRL
MSDDSTNM
MSDFLBRW
MSDFTACN
MSDMEDMT
MSDMGMCS
MSDMQHAC
MSDPTPRM
MSDQMAP
MSDQMNT
MSDRLDFN
MSDRLGRP
MSDRLMAP

MSDSWTSR
MSDVWNOT
MSSBLKMN
MSSBLKRL
MSSDEBRL
MSSDSTNM
MSSFLBRW
MSSFTACN
MSSIFBRW
MSSMEDMT
MSSMGMCS
MSSMQHAC
MSSNOTIB
MSSPTPRM
MSSRLDFN
MSSRLGRP
MSSRLMAP'
MSSSWTSR