

Oracle® Data Provider for .NET

Developer's Guide

12c Release 1 (12.1)

E17732-11

October 2014

Oracle Data Provider for .NET Developer's Guide 12c Release 1 (12.1)

E17732-11

Copyright © 2002, 2014, Oracle and/or its affiliates. All rights reserved.

Primary Authors: Maitreyee Chaliha, Sumit Jeloka, Janis Greenberg

Contributing Authors: Alex Keh, Kiminari Akiyama, Sinclair Hsu, Shailendra Jain, Riaz Ahmed, Ashish Shah, Lakshminarayanan Suriamoorthy, Steven Caminez, Naveen Doraiswamy, Neeraj Gupta, Chithra Ramamurthy, Martha Woo, Arun Singh, Sujith Somanathan, Nishant Singh

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Contents

| | |
|-------------------------------------------------------------------------------|-------|
| Preface | li |
| Audience | li |
| Documentation Accessibility | li |
| Related Documents | lii |
| Passwords in Code Examples | liii |
| Conventions | liii |
| | |
| Changes in This Release for Oracle Data Provider for .NET | lv |
| Changes in Oracle Data Provider for .NET Release 12.1.0.2 | lv |
| Changes in Oracle Data Provider for .NET in ODAC 12c Release 2 | lvi |
| Changes in Oracle Data Provider for .NET in ODAC 12c Release 1 | lvi |
| Changes in Oracle Data Provider for .NET Release 12.1 | lvi |
| Changes in Oracle Data Provider for .NET Release 11.2.0.3.20 | lxi |
| Changes in Oracle Data Provider for .NET Release 11.2.0.3 | lxi |
| Changes in Oracle Data Provider for .NET Release 11.2.0.2 | lxii |
| Changes in Oracle Data Provider for .NET Release 11.2.0.1.2 | lxiii |
| Changes in Oracle Data Provider for .NET Release 11.2 | lxiii |
| Changes in Oracle Data Provider for .NET Release 11.1.0.7.20 | lxiii |
| Changes in Oracle Data Provider for .NET Release 11.1.0.6.20 | lxv |
| Changes in Oracle Data Provider for .NET Release 11.1 | lxvii |
| | |
| 1 Introducing Oracle Data Provider for .NET | |
| .NET Data Access in Oracle: Products and Documentation | 1-1 |
| Oracle Data Provider for .NET (ODP.NET) | 1-1 |
| Oracle Developer Tools for Visual Studio | 1-2 |
| Oracle Database Extensions for .NET | 1-2 |
| Oracle Providers for ASP.NET | 1-2 |
| Oracle Services for Microsoft Transaction Server | 1-3 |
| Oracle TimesTen In-Memory Database | 1-3 |
| Overview of Oracle Data Provider for .NET (ODP.NET) | 1-4 |
| Oracle Data Provider for .NET Assemblies | 1-4 |
| Oracle Data Provider for .NET, Unmanaged Driver Assemblies | 1-5 |
| Oracle Data Provider for .NET, Managed Driver Assemblies | 1-5 |
| Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces | 1-5 |
| Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client | 1-5 |

| | |
|----------------------------------------------------------------------------------|-------------|
| Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Enumerations..... | 1-9 |
| Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces..... | 1-12 |
| Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Structures..... | 1-12 |
| Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Exceptions | 1-12 |
| Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Classes..... | 1-12 |
| Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Interfaces..... | 1-13 |
| Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Enumerations..... | 1-14 |
| Differences between the ODP.NET Managed Driver and Unmanaged Driver | 1-14 |
| Using ODP.NET Client Provider in a Simple Application | 1-17 |

2 Installing and Configuring Oracle Data Provider for .NET

| | |
|-----------------------------------------------------------------------------------------------|-------------|
| System Requirements..... | 2-1 |
| Entity Framework Requirements | 2-2 |
| Entity Framework Database First and Model First Requirements | 2-2 |
| Oracle Data Provider for .NET Versioning Scheme | 2-3 |
| Installing Oracle Data Provider for .NET, Unmanaged Driver..... | 2-5 |
| File Locations After Installation..... | 2-5 |
| Search Order for Unmanaged DLLs..... | 2-6 |
| ODP.NET and Dependent Unmanaged DLL Mismatch..... | 2-6 |
| Installing Oracle Data Provider for .NET, Managed Driver..... | 2-7 |
| File Locations After Installation..... | 2-8 |
| Configuring Oracle Data Provider for .NET | 2-9 |
| Oracle Data Provider for .NET, Unmanaged Driver Configuration | 2-9 |
| Supported Configuration Settings..... | 2-9 |
| Windows Registry..... | 2-17 |
| Configuration File Support..... | 2-17 |
| Oracle Data Provider for .NET, Managed Driver Configuration..... | 2-18 |
| version Section..... | 2-19 |
| dataSources Section | 2-20 |
| settings section | 2-22 |
| LDAPsettings section | 2-24 |
| Lightweight Directory Access Protocol..... | 2-24 |
| implicitRefCursor section | 2-25 |
| distributedTransaction section..... | 2-25 |
| edmMappings section | 2-26 |
| onsConfig section..... | 2-26 |
| Client Side ONS Daemon Configuration | 2-27 |
| Using Oracle Services for MTS with Oracle Data Provider for .NET, Managed Driver | 2-29 |
| Configuration differences between ODP.NET, Managed Driver and ODP.NET, Unmanaged Driver | 2-29 |
| Migrating from ODP.NET, Unmanaged Driver to ODP.NET, Managed Driver..... | 2-30 |
| Configuring a Port to Listen for Database Notifications..... | 2-31 |
| General .NET Programming Recommendations and Tips for ODP.NET..... | 2-32 |

3 Features of Oracle Data Provider for .NET

| | |
|--------------------------------------------------------|------------|
| Base Classes and Provider Factory Classes | 3-1 |
|--------------------------------------------------------|------------|

| | |
|----------------------------------------------------------------------------------------------|------|
| Code Access Security | 3-2 |
| Configuring OraclePermission..... | 3-2 |
| Configuring OraclePermission for Web Applications with High or Medium Trust Levels... | 3-3 |
| Configuring OraclePermission for Windows Applications Running in a Partial Trust Environment | 3-4 |
| Connecting to Oracle Database | 3-4 |
| Connection String Attributes | 3-5 |
| Connection String Builder | 3-7 |
| Specifying the Data Source Attribute..... | 3-7 |
| Using the TNS Alias | 3-7 |
| Using the Connect Descriptor | 3-8 |
| Using Easy Connect Naming Method | 3-8 |
| Using LDAP | 3-8 |
| Data Source Enumerator | 3-8 |
| Using Transport Layer Security and Secure Sockets Layer | 3-9 |
| Using Kerberos | 3-9 |
| Schema Discovery | 3-9 |
| User Customization of Metadata..... | 3-10 |
| Connection Pooling | 3-10 |
| Using Connection Pooling..... | 3-11 |
| Connection Pool Management..... | 3-12 |
| Connection Pool Performance Counters..... | 3-13 |
| Publishing Performance Counters..... | 3-14 |
| Setting Performance Counters Using .NET Configuration Entry..... | 3-14 |
| Instance Names of Performance Counters | 3-14 |
| Pluggable Databases | 3-15 |
| Edition-Based Redefinition..... | 3-16 |
| Operating System Authentication | 3-17 |
| Privileged Connections | 3-18 |
| Password Expiration..... | 3-18 |
| Proxy Authentication..... | 3-19 |
| Dynamic Distributed Transaction Enlistment | 3-21 |
| Client Identifier and End-to-End Tracing..... | 3-21 |
| Transparent Application Failover (TAF) Callback Support | 3-22 |
| TAF Notification | 3-22 |
| When Failover Occurs..... | 3-23 |
| Registering an Event Handler for Failover | 3-23 |
| Real Application Clusters and Global Data Services | 3-24 |
| Fast Application Notification | 3-25 |
| Runtime Connection Load Balancing | 3-26 |
| Fast Connection Failover (FCF)..... | 3-27 |
| Using FCF Planned Outage to Minimize Service Disruption..... | 3-28 |
| Pool Size Attributes in an Oracle RAC Database | 3-28 |
| Using Transaction Guard to Prevent Logical Corruption | 3-29 |
| OracleCommand Object | 3-32 |
| Transactions | 3-32 |
| System.Transactions and Promotable Transactions..... | 3-32 |

| | |
|-------------------------------------------------------------------------------|-------------|
| Implicit Transaction Enlistment Using TransactionScope | 3-33 |
| Explicit Transaction Enlistment Using CommittableTransaction | 3-35 |
| Local Transaction Support for Older Databases | 3-36 |
| Parameter Binding | 3-37 |
| OracleDbType Enumeration Type | 3-37 |
| Inference of DbType, OracleDbType, and .NET Types | 3-39 |
| Inference of DbType from OracleDbType | 3-39 |
| Inference of OracleDbType from DbType | 3-40 |
| Inference of DbType and OracleDbType from Value | 3-40 |
| PL/SQL Associative Array Binding..... | 3-42 |
| Array Binding..... | 3-45 |
| OracleParameter Array Bind Properties | 3-46 |
| Error Handling for Array Binding | 3-46 |
| OracleParameterStatus Enumeration Types..... | 3-48 |
| Batch Processing..... | 3-48 |
| Statement Caching | 3-48 |
| Statement Caching Connection String Attributes | 3-49 |
| Enabling Statement Caching through the Registry..... | 3-49 |
| Statement Caching Methods and Properties..... | 3-49 |
| Connections and Statement Caching | 3-50 |
| Pooling and Statement Caching..... | 3-50 |
| Self-Tuning | 3-50 |
| Self-Tuning Statement Caching | 3-50 |
| Enabling or Disabling Self-Tuning for Applications | 3-51 |
| Tracing Optimization Changes..... | 3-52 |
| ODP.NET Types Overview | 3-52 |
| Obtaining Data from an OracleDataReader Object | 3-53 |
| Typed OracleDataReader Accessors | 3-54 |
| .NET Type Accessors..... | 3-54 |
| ODP.NET Type Accessors | 3-56 |
| Obtaining LONG and LONG RAW Data..... | 3-57 |
| Setting InitialLONGFetchSize to Zero or a Value Greater than Zero | 3-57 |
| Setting InitialLONGFetchSize to -1 | 3-58 |
| Obtaining LOB Data | 3-58 |
| Setting InitialLOBFetchSize to Zero | 3-59 |
| Setting InitialLOBFetchSize to a Value Greater than Zero | 3-59 |
| Setting InitialLOBFetchSize to -1 | 3-60 |
| Methods Supported for InitialLOBFetchSize of -1 and LegacyEntireLobFetch of 1 | 3-61 |
| Performance Considerations Related to the InitialLOBFetchSize Property..... | 3-61 |
| Controlling the Number of Rows Fetched in One Database Round-Trip | 3-62 |
| Use of FetchSize..... | 3-62 |
| Fine-Tuning FetchSize..... | 3-62 |
| Using the RowSize Property | 3-62 |
| Setting FetchSize Value in the Registry | 3-63 |
| Setting FetchSize Value at Design Time..... | 3-63 |
| Setting FetchSize Value at Run Time | 3-63 |
| PL/SQL REF CURSOR and OracleRefCursor..... | 3-63 |

| | |
|------------------------------------------------------------------------------------|------|
| Obtaining an OracleRefCursor Object | 3-64 |
| Obtaining a REF CURSOR Data Type..... | 3-64 |
| Populating an OracleDataReader from a REF CURSOR..... | 3-64 |
| Populating the DataSet from a REF CURSOR | 3-64 |
| Populating an OracleRefCursor from a REF CURSOR | 3-65 |
| Updating a DataSet Obtained from a REF CURSOR..... | 3-65 |
| Behavior of ExecuteScalar Method for REF CURSOR..... | 3-65 |
| Passing a REF CURSOR to a Stored Procedure | 3-65 |
| Implicit REF CURSOR Binding | 3-67 |
| Specifying REF CURSOR Bind and Metadata Information in the .NET Configuration File | 3-67 |
| Sample Configuration File and Application | 3-71 |
| Usage Considerations | 3-73 |
| CommandText Property Considerations | 3-74 |
| Bind Considerations | 3-74 |
| Overloaded Stored Procedures | 3-74 |
| Type Initialization Exceptions..... | 3-74 |
| Using Stored Functions with Function Import..... | 3-75 |
| LOB Support | 3-75 |
| Large Character and Large Binary Data Types | 3-75 |
| Oracle Data Provider for .NET LOB Objects..... | 3-75 |
| Updating LOBs Using a DataSet..... | 3-76 |
| Updating LOBs Using OracleCommand and OracleParameter | 3-77 |
| Updating LOBs Using ODP.NET LOB Objects..... | 3-77 |
| Temporary LOBs | 3-77 |
| ODP.NET XML Support | 3-78 |
| Supported XML Features | 3-78 |
| XQuery Support | 3-79 |
| OracleXmlType and Connection Dependency | 3-80 |
| Updating XMLType Data in the Database | 3-80 |
| Updating with DataSet, OracleDataAdapter, and OracleCommandBuilder..... | 3-80 |
| Updating with OracleCommand and OracleParameter | 3-81 |
| Input Binding | 3-81 |
| Setting XMLType Column to NULL Value | 3-81 |
| Setting XMLType Column to Empty XML Data | 3-81 |
| Updating XML Data in OracleXmlType | 3-81 |
| Characters with Special Meaning in XML..... | 3-82 |
| Retrieving Query Result Set as XML..... | 3-82 |
| Handling Date and Time Format | 3-82 |
| Characters with Special Meaning in Column Data..... | 3-83 |
| Characters in Table or View Name | 3-84 |
| Case-Sensitivity in Column Name to XML Element Name Mapping | 3-84 |
| Column Name to XML Element Name Mapping | 3-84 |
| Improving Default Mapping..... | 3-85 |
| Object-Relational Data..... | 3-85 |
| NULL Values | 3-86 |
| Data Manipulation Using XML..... | 3-86 |
| Handling Date and Time Format..... | 3-86 |

| | |
|------------------------------------------------------------------------|--------------|
| Saving Changes Using XML..... | 3-86 |
| Characters with Special Meaning in Column Data..... | 3-87 |
| Characters with Special Meaning in Table or View Name | 3-87 |
| Case-Sensitivity in XML Element Name to Column Name Mapping | 3-88 |
| XML Element Name to Column Name Mapping | 3-88 |
| Saving Changes to a Table Using an XML Document | 3-88 |
| Improving Default Mapping..... | 3-89 |
| Object-Relational Data..... | 3-90 |
| Multiple Tables..... | 3-90 |
| Commit Transactions | 3-90 |
| Oracle User-Defined Types (UDTs) and .NET Custom Types..... | 3-90 |
| Oracle User-Defined Types (UDTs)..... | 3-91 |
| Custom Types | 3-91 |
| Required Custom Type Implementations | 3-92 |
| Optional Custom Type Implementations..... | 3-93 |
| Specifying Custom Type Mappings | 3-94 |
| Using a Custom Type Factory to Specify Custom Type Mappings | 3-94 |
| Using XML in Configuration Files to Specify Custom Type Mappings | 3-95 |
| Required Attributes..... | 3-95 |
| Optional Attributes..... | 3-95 |
| Using Custom Type Mappings | 3-96 |
| Converting Between Custom Types and Oracle UDTs | 3-96 |
| Oracle UDT Attribute Mappings | 3-97 |
| Oracle UDT Retrieval from OracleDataReader | 3-99 |
| Oracle UDT Metadata Retrieval from OracleDataReader..... | 3-100 |
| Oracle UDT Parameter Binding with OracleParameter | 3-100 |
| Guidelines for Binding UDT Input and Output Parameters | 3-100 |
| UDT Input Parameter Binding with OracleParameters | 3-101 |
| UDT Output Parameter Binding with OracleParameters..... | 3-102 |
| Populating the DataSet with Oracle UDTs..... | 3-103 |
| UDT Method Invocation | 3-104 |
| Configuration Settings for Oracle UDTs..... | 3-104 |
| StatementCacheWithUdts..... | 3-104 |
| UdtCacheSize..... | 3-104 |
| Bulk Copy | 3-105 |
| Data Types Supported by Bulk Copy..... | 3-105 |
| Restrictions on Oracle Bulk Copy of a Single Partition | 3-106 |
| Integrity Constraints Affecting Oracle Bulk Copy | 3-106 |
| Database Insert Triggers | 3-106 |
| Field Defaults..... | 3-106 |
| Oracle Database Advanced Queuing Support | 3-107 |
| Using ODP.NET for Advanced Queuing | 3-109 |
| Enqueuing and Dequeuing Example | 3-110 |
| Continuous Query Notification Support | 3-112 |
| Continuous Query Notification Classes | 3-114 |
| Supported Operations | 3-114 |
| Requirements of Notification Registration..... | 3-116 |

| | |
|------------------------------------------------------------------------|-------|
| Using Continuous Query Notification..... | 3-116 |
| Application Steps | 3-116 |
| Flow of Notification Process..... | 3-116 |
| Best Practice Guidelines and Performance Considerations | 3-118 |
| OracleDataAdapter Safe Type Mapping | 3-119 |
| Comparison Between Oracle Data Types and .NET Types | 3-119 |
| SafeMapping Property | 3-120 |
| Using Safe Type Mapping | 3-121 |
| OracleDataAdapter Requery Property | 3-122 |
| Guaranteeing Uniqueness in Updating DataSet to Database | 3-123 |
| What Constitutes Uniqueness in DataRow Objects? | 3-123 |
| Configuring PrimaryKey and Constraints Properties | 3-124 |
| Updating Without PrimaryKey and Constraints Configuration | 3-125 |
| Globalization Support | 3-125 |
| Globalization Settings..... | 3-125 |
| Client Globalization Settings..... | 3-125 |
| Session Globalization Settings | 3-126 |
| Thread-Based Globalization Settings..... | 3-127 |
| Globalization-Sensitive Operations..... | 3-128 |
| Operations Dependent on Client Computer's Globalization Settings | 3-128 |
| Operations Dependent on Thread Globalization Settings..... | 3-128 |
| Operations Sensitive to Session Globalization Parameters | 3-128 |
| Debug Tracing | 3-129 |

4 ADO.NET Entity Framework and LINQ to Entities

| | |
|--------------------------------------------------------------------------------------------------|------|
| Overview of Entity Framework | 4-1 |
| Mapping Oracle Data Types to EDM Types | 4-2 |
| EDM Type Facets | 4-6 |
| Oracle Number Default Data Type Mapping and Customization | 4-12 |
| Data Type Mapping and Customization Process..... | 4-13 |
| StoreGeneratedPattern Enumeration | 4-14 |
| Identity Attribute | 4-14 |
| Virtual Column | 4-14 |
| Resolving Compilation Errors When Using Custom Mapping | 4-15 |
| Mapping Boolean and Guid Parameters in Custom INSERT, UPDATE, and DELETE Stored Procedures | 4-15 |

5 Oracle Data Provider for .NET Stored Procedures

| | |
|-----------------------------------------------------------------------------------|-----|
| Introducing .NET Stored Procedure Execution Using ODP.NET | 5-1 |
| Limitations and Restrictions on ODP.NET Within .NET Stored Procedure | 5-2 |
| Implicit Database Connection | 5-2 |
| Transaction Support | 5-3 |
| Unsupported SQL Commands..... | 5-6 |
| Oracle User-Defined Type (UDT) Support | 5-6 |
| Porting Client Application to .NET Stored Procedure | 5-6 |

6 Oracle Data Provider for .NET Classes

| | |
|-----------------------------------------------|------|
| OracleClientFactory Class | 6-3 |
| OracleClientFactory Members | 6-5 |
| OracleClientFactory Constructor | 6-6 |
| OracleClientFactory Public Properties | 6-7 |
| CanCreateDataSourceEnumerator | 6-7 |
| OracleClientFactory Public Methods | 6-8 |
| CreateCommand | 6-8 |
| CreateCommandBuilder | 6-9 |
| CreateConnection..... | 6-9 |
| CreateConnectionStringBuilder | 6-9 |
| CreateDataAdapter | 6-10 |
| CreateDataSourceEnumerator | 6-10 |
| CreateParameter..... | 6-10 |
| CreatePermission | 6-11 |
| OracleCommand Class | 6-12 |
| OracleCommand Members..... | 6-14 |
| OracleCommand Constructors | 6-17 |
| OracleCommand() | 6-17 |
| OracleCommand(string) | 6-17 |
| OracleCommand(string, OracleConnection) | 6-18 |
| OracleCommand Static Methods | 6-19 |
| OracleCommand Properties | 6-20 |
| AddRowid | 6-21 |
| AddToStatementCache | 6-22 |
| ArrayBindCount | 6-23 |
| ArrayBindRowsAffected..... | 6-24 |
| BindByName | 6-24 |
| CommandText..... | 6-25 |
| CommandTimeout..... | 6-26 |
| CommandType | 6-27 |
| Connection | 6-27 |
| DesignTimeVisible..... | 6-28 |
| FetchSize..... | 6-28 |
| ImplicitRefCursors..... | 6-29 |
| InitialLOBFetchSize | 6-29 |
| InitialLONGFetchSize | 6-30 |
| Notification | 6-31 |
| NotificationAutoEnlist | 6-32 |
| Parameters | 6-33 |
| RowSize | 6-33 |
| Transaction | 6-34 |
| UpdatedRowSource | 6-35 |
| UseEdmMapping | 6-35 |
| XmlCommandType | 6-36 |
| XmlQueryProperties..... | 6-36 |
| XmlSaveProperties..... | 6-37 |

| | |
|----------------------------------------------|------|
| OracleCommand Public Methods | 6-39 |
| Cancel | 6-39 |
| Clone | 6-43 |
| CreateParameter | 6-44 |
| Dispose | 6-44 |
| ExecuteNonQuery..... | 6-44 |
| ExecuteReader | 6-46 |
| ExecuteReader() | 6-47 |
| ExecuteReader(CommandBehavior)..... | 6-48 |
| ExecuteScalar | 6-49 |
| ExecuteStream | 6-50 |
| ExecuteToStream..... | 6-51 |
| ExecuteXmlReader..... | 6-52 |
| OracleCommandBuilder Class | 6-53 |
| OracleCommandBuilder Members | 6-56 |
| OracleCommandBuilder Constructors | 6-58 |
| OracleCommandBuilder() | 6-58 |
| OracleCommandBuilder(OracleDataAdapter)..... | 6-58 |
| OracleCommandBuilder Static Methods..... | 6-60 |
| DeriveParameters..... | 6-60 |
| OracleCommandBuilder Properties | 6-64 |
| CaseSensitive | 6-64 |
| CatalogLocation | 6-65 |
| CatalogSeparator..... | 6-65 |
| ConflictOption..... | 6-65 |
| DataAdapter | 6-66 |
| QuotePrefix | 6-66 |
| QuoteSuffix | 6-67 |
| SchemaSeparator..... | 6-67 |
| OracleCommandBuilder Public Methods | 6-69 |
| GetDeleteCommand | 6-69 |
| GetDeleteCommand() | 6-70 |
| GetDeleteCommand(bool)..... | 6-70 |
| GetInsertCommand | 6-71 |
| GetInsertCommand()..... | 6-71 |
| GetInsertCommand(bool)..... | 6-72 |
| GetUpdateCommand | 6-73 |
| GetUpdateCommand() | 6-73 |
| GetUpdateCommand(bool)..... | 6-73 |
| QuoteIdentifier | 6-74 |
| RefreshSchema | 6-75 |
| UnquoteIdentifier | 6-75 |
| OracleCommandBuilder Events | 6-78 |
| OracleConnection Class | 6-79 |
| OracleConnection Members | 6-81 |
| OracleConnection Constructors | 6-85 |
| OracleConnection()..... | 6-85 |

| | |
|----------------------------------------------------------------|-------|
| OracleConnection(String) | 6-85 |
| OracleConnection Static Properties | 6-87 |
| IsAvailable | 6-87 |
| OracleConnection Static Methods | 6-89 |
| ClearPool | 6-89 |
| ClearAllPools | 6-90 |
| OracleConnection Properties..... | 6-92 |
| ActionName | 6-93 |
| ClientId | 6-93 |
| ClientInfo..... | 6-94 |
| ConnectionString | 6-94 |
| ConnectionTimeout | 6-100 |
| ConnectionType | 6-100 |
| Database | 6-101 |
| DatabaseDomainName | 6-101 |
| DatabaseName | 6-101 |
| DataSource | 6-102 |
| HostName | 6-102 |
| InstanceName | 6-103 |
| LogicalTransactionId | 6-103 |
| ModuleName..... | 6-103 |
| OracleLogicalTransaction | 6-104 |
| ServerVersion | 6-104 |
| ServiceName | 6-105 |
| State..... | 6-105 |
| StatementCacheSize..... | 6-106 |
| OracleConnection Public Methods..... | 6-107 |
| BeginTransaction..... | 6-108 |
| BeginTransaction()..... | 6-108 |
| BeginTransaction(IsolationLevel)..... | 6-109 |
| ChangeDatabase..... | 6-110 |
| Clone | 6-111 |
| Close | 6-112 |
| CreateCommand | 6-112 |
| EnlistDistributedTransaction | 6-113 |
| EnlistTransaction..... | 6-115 |
| FlushCache..... | 6-116 |
| GetLogicalTransactionStatus..... | 6-117 |
| GetSchema..... | 6-118 |
| GetSchema()..... | 6-119 |
| GetSchema (string collectionName)..... | 6-120 |
| GetSchema (string collectionName, string[] restrictions) | 6-122 |
| GetSessionInfo | 6-124 |
| GetSessionInfo() | 6-125 |
| GetSessionInfo(OracleGlobalization)..... | 6-125 |
| Open | 6-126 |
| OpenWithNewPassword | 6-126 |

| | |
|-------------------------------------------------------|-------|
| PurgeStatementCache | 6-127 |
| SetSessionInfo | 6-128 |
| OracleConnection Events | 6-130 |
| Failover | 6-130 |
| HAEvent | 6-131 |
| InfoMessage | 6-132 |
| StateChange | 6-132 |
| OracleConnectionStringBuilder Class | 6-134 |
| OracleConnectionStringBuilder Members | 6-137 |
| OracleConnectionStringBuilder Constructors | 6-140 |
| OracleConnectionStringBuilder() | 6-140 |
| OracleConnectionStringBuilder(string) | 6-140 |
| OracleConnectionStringBuilder Public Properties | 6-142 |
| ConnectionLifeTime | 6-143 |
| ConnectionTimeout | 6-144 |
| ContextConnection | 6-144 |
| DataSource | 6-145 |
| DBAPrivilege | 6-145 |
| DecrPoolSize | 6-146 |
| Enlist | 6-146 |
| HAEvents | 6-147 |
| IncrPoolSize | 6-147 |
| IsFixedSize | 6-148 |
| Item | 6-148 |
| Keys | 6-149 |
| LoadBalancing | 6-149 |
| MaxPoolSize | 6-150 |
| MetadataPooling | 6-150 |
| MinPoolSize | 6-151 |
| Password | 6-151 |
| PersistSecurityInfo | 6-151 |
| Pooling | 6-152 |
| PromotableTransaction | 6-152 |
| ProxyPassword | 6-153 |
| ProxyUserId | 6-153 |
| SelfTuning | 6-154 |
| StatementCachePurge | 6-154 |
| StatementCacheSize | 6-154 |
| UserID | 6-155 |
| ValidateConnection | 6-155 |
| Values | 6-156 |
| OracleConnectionStringBuilder Public Methods | 6-157 |
| Clear | 6-157 |
| ContainsKey | 6-158 |
| Remove | 6-158 |
| TryGetValue | 6-159 |
| OracleDataAdapter Class | 6-160 |

| | |
|-------------------------------------------------------|-------|
| OracleDataAdapter Members | 6-162 |
| OracleDataAdapter Constructors | 6-165 |
| OracleDataAdapter() | 6-165 |
| OracleDataAdapter(OracleCommand)..... | 6-165 |
| OracleDataAdapter(string, OracleConnection)..... | 6-166 |
| OracleDataAdapter(string, string) | 6-167 |
| OracleDataAdapter Static Methods..... | 6-168 |
| OracleDataAdapter Properties..... | 6-169 |
| DeleteCommand | 6-170 |
| IdentityInsert | 6-170 |
| IdentityUpdate | 6-171 |
| InsertCommand | 6-171 |
| Requery..... | 6-172 |
| ReturnProviderSpecificTypes | 6-172 |
| SafeMapping..... | 6-173 |
| SelectCommand | 6-173 |
| UpdateBatchSize | 6-174 |
| UpdateCommand | 6-175 |
| OracleDataAdapter Public Methods | 6-176 |
| Fill..... | 6-176 |
| Fill(DataTable, OracleRefCursor) | 6-177 |
| Fill(DataSet, OracleRefCursor)..... | 6-177 |
| Fill(DataSet, string, OracleRefCursor) | 6-178 |
| Fill(DataSet, int, int, string, OracleRefCursor)..... | 6-179 |
| OracleDataAdapter Events..... | 6-181 |
| RowUpdated..... | 6-181 |
| RowUpdating | 6-183 |
| OracleDatabase Class | 6-185 |
| OracleDatabase Members | 6-187 |
| OracleDatabase Constructor..... | 6-188 |
| OracleDatabase Properties..... | 6-189 |
| ServerVersion | 6-189 |
| OracleDatabase Public Methods | 6-190 |
| Dispose | 6-190 |
| ExecuteNonQuery..... | 6-190 |
| Shutdown | 6-191 |
| Shutdown() | 6-191 |
| Shutdown(OracleDBShutdownMode, bool)..... | 6-192 |
| Startup | 6-194 |
| Startup()..... | 6-194 |
| Startup(OracleDBStartupMode, string, bool) | 6-195 |
| OracleDataReader Class | 6-197 |
| OracleDataReader Members..... | 6-200 |
| OracleDataReader Static Methods..... | 6-204 |
| OracleDataReader Properties | 6-205 |
| Depth | 6-205 |
| FetchSize | 6-206 |

| | |
|----------------------------------------|-------|
| FieldCount | 6-207 |
| HasRows..... | 6-207 |
| HiddenFieldCount | 6-208 |
| IsClosed | 6-209 |
| Item | 6-210 |
| Item [index]..... | 6-210 |
| Item [string] | 6-210 |
| InitialLOBFetchSize | 6-211 |
| InitialLONGFetchSize | 6-212 |
| RecordsAffected | 6-212 |
| RowSize | 6-213 |
| UseEdmMapping | 6-214 |
| VisibleFieldCount | 6-214 |
| OracleDataReader Public Methods | 6-217 |
| Close | 6-219 |
| Dispose | 6-219 |
| GetBoolean | 6-220 |
| GetByte | 6-220 |
| GetBytes | 6-221 |
| GetChar | 6-222 |
| GetChars | 6-222 |
| GetDataTypeName | 6-223 |
| GetDateTime | 6-224 |
| GetDecimal | 6-225 |
| GetDouble | 6-225 |
| GetEnumerator | 6-226 |
| GetFieldType | 6-227 |
| GetFloat | 6-227 |
| GetGuid | 6-228 |
| GetInt16 | 6-229 |
| GetInt32 | 6-229 |
| GetInt64 | 6-230 |
| GetName | 6-231 |
| GetOracleBFile | 6-232 |
| GetOracleBinary | 6-232 |
| GetOracleBlob | 6-233 |
| GetOracleBlobForUpdate | 6-234 |
| GetOracleBlobForUpdate(int) | 6-234 |
| GetOracleBlobForUpdate(int, int) | 6-236 |
| GetOracleClob | 6-237 |
| GetOracleClobForUpdate | 6-238 |
| GetOracleClobForUpdate(int) | 6-238 |
| GetOracleClobForUpdate(int, int) | 6-241 |
| GetOracleDate | 6-242 |
| GetOracleDecimal | 6-243 |
| GetOracleIntervalDS | 6-243 |
| GetOracleIntervalYM | 6-244 |

| | |
|------------------------------------------------|--------------|
| GetOracleRef..... | 6-245 |
| GetOracleString | 6-245 |
| GetOracleTimeStamp | 6-246 |
| GetOracleTimeStampLTZ | 6-247 |
| GetOracleTimeStampTZ | 6-247 |
| GetOracleXmlType | 6-248 |
| GetOracleValue | 6-248 |
| GetOracleValues | 6-249 |
| GetOrdinal | 6-250 |
| GetProviderSpecificFieldType | 6-250 |
| GetProviderSpecificValue..... | 6-251 |
| GetProviderSpecificValues | 6-252 |
| GetSchemaTable | 6-252 |
| GetString | 6-256 |
| GetTimeSpan | 6-257 |
| GetValue | 6-258 |
| GetValues | 6-258 |
| GetXmlReader | 6-259 |
| IsDBNull | 6-260 |
| NextResult | 6-260 |
| Read | 6-261 |
| OracleDataSourceEnumerator Class | 6-263 |
| OracleDataSourceEnumerator Members..... | 6-265 |
| OracleDataSourceEnumerator Constructor | 6-266 |
| OracleDataSourceEnumerator Public Methods..... | 6-267 |
| GetDataSources | 6-267 |
| OracleError Class..... | 6-269 |
| OracleError Members | 6-271 |
| OracleError Static Methods | 6-272 |
| OracleError Properties..... | 6-273 |
| ArrayBindIndex | 6-273 |
| DataSource | 6-274 |
| Message | 6-274 |
| Number | 6-274 |
| Procedure | 6-275 |
| Source..... | 6-275 |
| OracleError Methods | 6-276 |
| ToString..... | 6-276 |
| OracleErrorCollection Class..... | 6-277 |
| OracleErrorCollection Members | 6-279 |
| OracleErrorCollection Static Methods | 6-280 |
| OracleErrorCollection Properties..... | 6-281 |
| OracleErrorCollection Public Methods | 6-282 |
| OracleException Class | 6-283 |
| OracleException Members..... | 6-285 |
| OracleException Static Methods | 6-287 |
| OracleException Properties | 6-288 |

| | |
|------------------------------------------------------------------------------------------------------------------------|-------|
| DataSource | 6-288 |
| Errors | 6-289 |
| IsRecoverable | 6-289 |
| Message | 6-290 |
| Number | 6-290 |
| Procedure | 6-290 |
| Source | 6-291 |
| OracleException Methods | 6-292 |
| GetObjectData | 6-292 |
| ToString | 6-293 |
| OracleInfoMessageEventArgs Class | 6-294 |
| OracleInfoMessageEventArgs Members | 6-296 |
| OracleInfoMessageEventArgs Static Methods | 6-297 |
| OracleInfoMessageEventArgs Properties | 6-298 |
| Errors | 6-298 |
| Message | 6-298 |
| Source | 6-299 |
| OracleInfoMessageEventArgs Public Methods | 6-300 |
| ToString | 6-300 |
| OracleInfoMessageEventHandler Delegate | 6-301 |
| OracleLogicalTransaction Class | 6-302 |
| OracleLogicalTransaction Members | 6-303 |
| OracleLogicalTransaction Public Read-Only Properties | 6-304 |
| Committed | 6-304 |
| UserCallCompleted | 6-305 |
| UserId | 6-305 |
| DataSource | 6-306 |
| OracleLogicalTransaction Private Properties | 6-307 |
| OracleLogicalTransaction Methods | 6-308 |
| Dispose | 6-308 |
| GetOutcome | 6-308 |
| OracleLogicalTransactionStatus Class | 6-310 |
| OracleLogicalTransactionStatus Properties | 6-311 |
| Committed | 6-311 |
| UserCallCompleted | 6-312 |
| OracleParameter Class | 6-313 |
| OracleParameter Members | 6-315 |
| OracleParameter Constructors | 6-317 |
| OracleParameter() | 6-317 |
| OracleParameter(string, OracleDbType) | 6-318 |
| OracleParameter(string, object) | 6-319 |
| OracleParameter(string, OracleDbType, ParameterDirection) | 6-320 |
| OracleParameter(string, OracleDbType, object, ParameterDirection) | 6-321 |
| OracleParameter(string, OracleDbType, int) | 6-322 |
| OracleParameter(string, OracleDbType, int, string) | 6-323 |
| OracleParameter(string, OracleDbType, int, ParameterDirection, bool, byte, byte, string, DataRowVersion, object) | 6-324 |

| | |
|-----------------------------------------------------------------------------|--------------|
| OracleParameter(string, OracleDbType, int, object, ParameterDirection)..... | 6-326 |
| OracleParameter Static Methods..... | 6-328 |
| OracleParameter Properties..... | 6-329 |
| ArrayBindSize | 6-330 |
| ArrayBindStatus | 6-331 |
| CollectionType | 6-332 |
| DbType | 6-333 |
| Direction | 6-333 |
| IsNullable | 6-334 |
| Offset..... | 6-334 |
| OracleDbType | 6-335 |
| OracleDbTypeEx | 6-336 |
| ParameterName | 6-336 |
| Precision | 6-337 |
| Scale | 6-337 |
| Size | 6-338 |
| SourceColumn | 6-339 |
| SourceColumnNullMapping..... | 6-340 |
| SourceVersion | 6-340 |
| Status | 6-341 |
| UdtTypeName..... | 6-342 |
| Value | 6-342 |
| OracleParameter Public Methods..... | 6-345 |
| Clone | 6-345 |
| Dispose | 6-346 |
| ResetDbType..... | 6-347 |
| ResetOracleDbType..... | 6-347 |
| ToString..... | 6-347 |
| OracleParameterCollection Class..... | 6-349 |
| OracleParameterCollection Members | 6-351 |
| OracleParameterCollection Static Methods..... | 6-353 |
| OracleParameterCollection Properties..... | 6-354 |
| Count | 6-354 |
| Item | 6-354 |
| Item[int]..... | 6-355 |
| Item[string] | 6-355 |
| OracleParameterCollection Public Methods..... | 6-357 |
| Add | 6-357 |
| Add(object) | 6-358 |
| Add(OracleParameter)..... | 6-359 |
| Add(string, object)..... | 6-359 |
| Add(string, OracleDbType)..... | 6-360 |
| Add(string, OracleDbType, ParameterDirection)..... | 6-360 |
| Add(string, OracleDbType, object, ParameterDirection)..... | 6-361 |
| Add(string, OracleDbType, int, object, ParameterDirection)..... | 6-362 |
| Add(string, OracleDbType, int)..... | 6-363 |
| Add (string, OracleDbType, int, string)..... | 6-364 |

| | |
|------------------------------------------------------------------------------------------------------------|-------|
| Add(string, OracleDbType, int, ParameterDirection, bool, byte, byte, string, DataRowVersion, object) 6-364 | |
| AddRange | 6-365 |
| Clear | 6-366 |
| Contains..... | 6-367 |
| Contains(object)..... | 6-367 |
| Contains(string)..... | 6-368 |
| CopyTo | 6-369 |
| IndexOf | 6-370 |
| IndexOf(object)..... | 6-370 |
| IndexOf(String)..... | 6-371 |
| Insert | 6-371 |
| Remove | 6-372 |
| RemoveAt | 6-373 |
| RemoveAt(int)..... | 6-373 |
| RemoveAt(String)..... | 6-374 |
| OraclePermission Class | 6-375 |
| OraclePermission Members..... | 6-376 |
| OraclePermission Constructor | 6-378 |
| OraclePermission Static Methods | 6-379 |
| OraclePermission Public Properties | 6-380 |
| OraclePermission Public Methods..... | 6-381 |
| Add | 6-381 |
| Copy..... | 6-382 |
| IsSubsetOf | 6-383 |
| OraclePermissionAttribute Class | 6-384 |
| OraclePermissionAttribute Members | 6-385 |
| OraclePermissionAttribute Constructor | 6-387 |
| OraclePermissionAttribute Static Methods | 6-388 |
| OraclePermissionAttribute Public Properties | 6-389 |
| OraclePermissionAttribute Public Methods | 6-390 |
| CreatePermission | 6-390 |
| OracleRowUpdatedEventArgs Class | 6-391 |
| OracleRowUpdatedEventArgs Members..... | 6-392 |
| OracleRowUpdatedEventArgs Constructor | 6-394 |
| OracleRowUpdatedEventArgs Static Methods | 6-395 |
| OracleRowUpdatedEventArgs Properties | 6-396 |
| Command..... | 6-396 |
| OracleRowUpdatedEventArgs Public Methods..... | 6-397 |
| OracleRowUpdatedEventHandler Delegate | 6-398 |
| OracleRowUpdatingEventArgs Class | 6-399 |
| OracleRowUpdatingEventArgs Members | 6-400 |
| OracleRowUpdatingEventArgs Constructor | 6-402 |
| OracleRowUpdatingEventArgs Static Methods..... | 6-403 |
| OracleRowUpdatingEventArgs Properties | 6-404 |
| Command..... | 6-404 |
| OracleRowUpdatingEventArgs Public Methods | 6-405 |

| | |
|-----------------------------------------------------|-------|
| OracleRowUpdatingEventHandler Delegate | 6-406 |
| OracleTransaction Class | 6-407 |
| OracleTransaction Members..... | 6-410 |
| OracleTransaction Static Methods | 6-411 |
| OracleTransaction Properties | 6-412 |
| IsolationLevel | 6-412 |
| Connection | 6-412 |
| OracleTransaction Public Methods | 6-414 |
| Commit..... | 6-414 |
| Dispose | 6-416 |
| Rollback | 6-416 |
| Rollback() | 6-417 |
| Rollback(string)..... | 6-418 |
| Save | 6-419 |
| OracleConnectionType Enumeration | 6-422 |
| OracleCollectionType Enumeration | 6-423 |
| OracleDBShutdownMode Enumeration | 6-424 |
| OracleDBStartupMode Enumeration | 6-425 |
| OracleDbType Enumeration | 6-426 |
| OracleIdentityType Enumeration | 6-428 |
| OracleParameterStatus Enumeration | 6-429 |

7 Oracle Data Provider for .NET XML-Related Classes

| | |
|-----------------------------------------------|------|
| OracleXmlCommandType Enumeration | 7-2 |
| OracleXmlQueryProperties Class | 7-3 |
| OracleXmlQueryProperties Members..... | 7-7 |
| OracleXmlQueryProperties Constructor | 7-8 |
| OracleXmlQueryProperties Properties | 7-9 |
| MaxRows..... | 7-9 |
| RootTag | 7-10 |
| RowTag..... | 7-10 |
| Xslt..... | 7-11 |
| XsltParams | 7-11 |
| OracleXmlQueryProperties Public Methods | 7-12 |
| Clone | 7-12 |
| OracleXmlSaveProperties Class | 7-13 |
| OracleXmlSaveProperties Members..... | 7-16 |
| OracleXmlSaveProperties Constructor | 7-17 |
| OracleXmlSaveProperties Properties | 7-18 |
| KeyColumnsList..... | 7-18 |
| RowTag..... | 7-19 |
| Table..... | 7-19 |
| UpdateColumnsList..... | 7-20 |
| Xslt..... | 7-20 |
| XsltParams | 7-21 |
| OracleXmlSaveProperties Public Methods | 7-22 |

| | |
|----------------------------------------------------|------|
| Clone | 7-22 |
| OracleXmlStream Class | 7-23 |
| OracleXmlStream Members | 7-24 |
| OracleXmlStream Constructor | 7-26 |
| OracleXmlStream Static Methods | 7-27 |
| OracleXmlStream Instance Properties | 7-28 |
| CanRead | 7-28 |
| CanSeek | 7-28 |
| Connection | 7-29 |
| Length | 7-29 |
| Position | 7-30 |
| Value | 7-30 |
| OracleXmlStream Instance Methods | 7-32 |
| Clone | 7-32 |
| Close | 7-33 |
| Dispose | 7-33 |
| Read | 7-34 |
| Read(byte[], int, int) | 7-34 |
| Read(char[], int, int) | 7-35 |
| Seek | 7-36 |
| OracleXmlType Class | 7-38 |
| OracleXmlType Members | 7-39 |
| OracleXmlType Constructors | 7-41 |
| OracleXmlType(OracleClob) | 7-41 |
| OracleXmlType(OracleConnection, string) | 7-42 |
| OracleXmlType(OracleConnection, XmlReader) | 7-42 |
| OracleXmlType(OracleConnection, XmlDocument) | 7-43 |
| OracleXmlType Static Methods | 7-45 |
| OracleXmlType Static Fields | 7-46 |
| Null | 7-46 |
| OracleXmlType Instance Properties | 7-47 |
| Connection | 7-47 |
| IsEmpty | 7-48 |
| IsFragment | 7-48 |
| IsNull | 7-49 |
| IsSchemaBased | 7-49 |
| RootElement | 7-50 |
| Schema | 7-50 |
| SchemaUrl | 7-51 |
| Value | 7-51 |
| OracleXmlType Instance Methods | 7-53 |
| Clone | 7-53 |
| Dispose | 7-54 |
| Extract | 7-54 |
| Extract(string, string) | 7-55 |
| Extract(string, XmlNamespaceManager) | 7-55 |
| GetStream | 7-56 |

| | |
|----------------------------------------------------------|------|
| GetXmlDocument | 7-57 |
| GetXmlReader | 7-57 |
| IsExists | 7-58 |
| IsExists(string, string)..... | 7-58 |
| IsExists(string, XmlNameSpaceManager) | 7-59 |
| Transform..... | 7-60 |
| Transform(OracleXmlType, string)..... | 7-60 |
| Transform(string, string)..... | 7-61 |
| Update | 7-61 |
| Update(string, string, string)..... | 7-62 |
| Update(string, XmlNameSpaceManager, string)..... | 7-63 |
| Update(string, string, OracleXmlType)..... | 7-64 |
| Update(string, XmlNameSpaceManager, OracleXmlType) | 7-64 |
| Validate..... | 7-65 |

8 Oracle Data Provider for .NET HA Event Classes

| | |
|----------------------------------------------|------|
| OracleHAEventArgs Class | 8-2 |
| OracleHAEventArgs Members | 8-3 |
| OracleHAEventArgs Properties..... | 8-4 |
| DatabaseDomainName | 8-4 |
| DatabaseName | 8-4 |
| HostName | 8-5 |
| InstanceName | 8-5 |
| Reason..... | 8-6 |
| ServiceName | 8-6 |
| Source..... | 8-7 |
| Status..... | 8-7 |
| Time | 8-7 |
| OracleHAEventHandler Delegate | 8-9 |
| OracleHAEventSource Enumeration | 8-10 |
| OracleHAEventStatus Enumeration | 8-11 |

9 Continuous Query Notification Classes

| | |
|--------------------------------------------------------|------|
| OracleDependency Class | 9-2 |
| OracleDependency Members | 9-3 |
| OracleDependency Constructors | 9-5 |
| OracleDependency ()..... | 9-5 |
| OracleDependency(OracleCommand) | 9-6 |
| OracleDependency(OracleCommand, bool, int, bool) | 9-7 |
| OracleDependency Static Fields | 9-9 |
| Port | 9-9 |
| OracleDependency Static Methods | 9-11 |
| GetOracleDependency | 9-11 |
| OracleDependency Properties..... | 9-12 |
| DataSource | 9-12 |
| HasChanges | 9-13 |
| Id..... | 9-13 |

| | |
|---------------------------------------------------|------|
| IsEnabled | 9-14 |
| QueryBasedNotification | 9-14 |
| RegisteredQueryIDs | 9-15 |
| RegisteredResources..... | 9-15 |
| RowidInfo | 9-16 |
| UserName | 9-17 |
| OracleDependency Methods | 9-18 |
| AddCommandDependency | 9-18 |
| RemoveRegistration | 9-19 |
| OracleDependency Events..... | 9-21 |
| OnChange | 9-21 |
| OracleNotificationRequest Class | 9-22 |
| OracleNotificationRequest Members | 9-23 |
| OracleNotificationRequest Static Methods | 9-24 |
| OracleNotificationRequest Properties..... | 9-25 |
| IsNotifiedOnce | 9-25 |
| IsPersistent | 9-26 |
| Timeout..... | 9-26 |
| GroupingNotificationEnabled | 9-27 |
| GroupingType | 9-27 |
| GroupingInterval | 9-28 |
| OracleNotificationRequest Methods | 9-29 |
| OracleNotificationEventArgs Class | 9-30 |
| OracleNotificationEventArgs Members | 9-31 |
| OracleNotificationEventArgs Static Fields..... | 9-32 |
| OracleNotificationEventArgs Static Methods..... | 9-33 |
| OracleNotificationEventArgs Properties..... | 9-34 |
| Details | 9-34 |
| Info | 9-35 |
| ResourceNames..... | 9-36 |
| Source | 9-36 |
| Type | 9-37 |
| OracleNotificationEventArgs Methods | 9-39 |
| OnChangeEventHandler Delegate | 9-40 |
| OracleRowidInfo Enumeration | 9-41 |
| OracleNotificationType Enumeration | 9-42 |
| OracleNotificationSource Enumeration | 9-43 |
| OracleNotificationInfo Enumeration | 9-44 |

10 Oracle Data Provider for .NET Globalization Classes

| | |
|------------------------------------------|------|
| OracleGlobalization Class | 10-2 |
| OracleGlobalization Members..... | 10-4 |
| OracleGlobalization Static Methods | 10-6 |
| GetClientInfo | 10-6 |
| GetClientInfo()..... | 10-6 |
| GetClientInfo(OracleGlobalization) | 10-7 |

| | |
|------------------------------------------|-------|
| GetThreadInfo | 10-8 |
| GetThreadInfo()..... | 10-8 |
| GetThreadInfo(OracleGlobalization) | 10-9 |
| SetThreadInfo | 10-10 |
| OracleGlobalization Properties | 10-12 |
| Calendar | 10-12 |
| ClientCharacterSet | 10-13 |
| Comparison..... | 10-13 |
| Currency..... | 10-14 |
| DateFormat | 10-14 |
| DateLanguage..... | 10-15 |
| DualCurrency | 10-15 |
| ISOCurrency | 10-16 |
| Language..... | 10-16 |
| LengthSemantics | 10-17 |
| NCharConversionException | 10-17 |
| NumericCharacters..... | 10-18 |
| Sort | 10-18 |
| Territory | 10-19 |
| TimeStampFormat | 10-19 |
| TimeStampTZFormat | 10-20 |
| TimeZone | 10-20 |
| OracleGlobalization Public Methods | 10-22 |
| Clone | 10-22 |
| Dispose | 10-22 |

11 Oracle Data Provider for .NET Failover Classes

| | |
|--------------------------------------------------|-------|
| OracleFailoverEventArgs Class | 11-2 |
| OracleFailoverEventArgs Members | 11-5 |
| OracleFailoverEventArgs Static Methods | 11-6 |
| OracleFailoverEventArgs Properties..... | 11-7 |
| FailoverType..... | 11-7 |
| FailoverEvent..... | 11-7 |
| OracleFailoverEventArgs Public Methods..... | 11-9 |
| OracleFailoverEventHandler Delegate | 11-10 |
| FailoverEvent Enumeration | 11-11 |
| FailoverReturnCode Enumeration | 11-12 |
| FailoverType Enumeration | 11-13 |

12 Oracle Database Advanced Queuing Classes

| | |
|--------------------------------------|------|
| OracleAQAgent Class | 12-2 |
| OracleAQAgent Members | 12-3 |
| OracleAQAgent Constructors | 12-4 |
| OracleAQAgent (string)..... | 12-4 |
| OracleAQAgent (string, string) | 12-4 |
| OracleAQAgent Properties..... | 12-6 |

| | |
|------------------------------------------------------|-------|
| Address..... | 12-6 |
| Name..... | 12-6 |
| OracleAQDequeueOptions Class | 12-8 |
| OracleAQDequeueOptions Members | 12-9 |
| OracleAQDequeueOptions Constructor..... | 12-11 |
| OracleAQDequeueOptions Properties..... | 12-12 |
| ConsumerName | 12-12 |
| Correlation | 12-13 |
| DeliveryMode..... | 12-13 |
| DequeueMode | 12-14 |
| MessageId | 12-14 |
| NavigationMode | 12-15 |
| ProviderSpecificType | 12-15 |
| Visibility | 12-16 |
| Wait..... | 12-16 |
| OracleAQDequeueOptions Public Methods | 12-18 |
| Clone | 12-18 |
| OracleAQEnqueueOptions Class | 12-19 |
| OracleAQEnqueueOptions Members | 12-20 |
| OracleAQEnqueueOptions Constructor..... | 12-21 |
| OracleAQEnqueueOptions Properties..... | 12-22 |
| DeliveryMode..... | 12-22 |
| Visibility | 12-22 |
| OracleAQEnqueueOptions Public Methods | 12-24 |
| Clone | 12-24 |
| OracleAQMessage Class | 12-25 |
| OracleAQMessage Members | 12-26 |
| OracleAQMessage Constructors..... | 12-27 |
| OracleAQMessage()..... | 12-27 |
| OracleAQMessage(Object) | 12-27 |
| OracleAQMessage Properties | 12-29 |
| Correlation | 12-29 |
| Delay | 12-30 |
| DeliveryMode..... | 12-30 |
| DequeueAttempts..... | 12-31 |
| EnqueueTime..... | 12-31 |
| ExceptionQueue | 12-32 |
| Expiration..... | 12-32 |
| MessageId | 12-33 |
| OriginalMessageId..... | 12-33 |
| Payload | 12-34 |
| Priority | 12-34 |
| Recipients | 12-35 |
| SenderId | 12-35 |
| State..... | 12-36 |
| TransactionGroup | 12-36 |
| OracleAQMessageAvailableEventArgs Class | 12-37 |

| | |
|---------------------------------------------------------------------------|--------------|
| OracleAQMessageAvailableEventArgs Members | 12-38 |
| OracleAQMessageAvailableEventArgs Constructor..... | 12-39 |
| OracleAQMessageAvailableEventArgs Properties..... | 12-40 |
| AvailableMessages..... | 12-40 |
| ConsumerName | 12-41 |
| Correlation | 12-41 |
| Delay | 12-42 |
| DeliveryMode..... | 12-42 |
| EnqueueTime..... | 12-42 |
| ExceptionQueue | 12-43 |
| Expiration..... | 12-43 |
| MessageId | 12-43 |
| NotificationType | 12-44 |
| OriginalMessageId..... | 12-44 |
| Priority..... | 12-45 |
| QueueName..... | 12-45 |
| SenderId | 12-45 |
| State..... | 12-46 |
| OracleAQMessageAvailableEventHandler Delegate | 12-47 |
| OracleAQQueue Class | 12-48 |
| OracleAQQueue Members | 12-49 |
| OracleAQQueue Constructors | 12-51 |
| OracleAQQueue(string)..... | 12-51 |
| OracleAQQueue(string, OracleConnection)..... | 12-52 |
| OracleAQQueue(string, OracleConnection, OracleAQMessageType)..... | 12-52 |
| OracleAQQueue(string, OracleConnection, OracleAQMessageType, string)..... | 12-53 |
| OracleAQQueue Static Methods..... | 12-55 |
| Listen..... | 12-55 |
| Listen(OracleConnection, OracleAQAgent[])..... | 12-55 |
| Listen(OracleConnection, OracleAQAgent[], int)..... | 12-56 |
| OracleAQQueue Properties..... | 12-58 |
| Connection | 12-58 |
| DequeueOptions | 12-59 |
| EnqueueOptions..... | 12-59 |
| MessageType | 12-60 |
| Name..... | 12-61 |
| Notification | 12-61 |
| NotificationConsumers | 12-62 |
| UdtTypeName | 12-62 |
| OracleAQQueue Public Methods | 12-64 |
| Dequeue..... | 12-64 |
| Dequeue()..... | 12-64 |
| Dequeue(OracleAQDequeueOptions)..... | 12-65 |
| DequeueArray | 12-66 |
| DequeueArray(int)..... | 12-66 |
| DequeueArray(int, OracleAQDequeueOptions)..... | 12-67 |
| Dispose | 12-68 |

| | |
|---------------------------------------------------------------|-------|
| Enqueue..... | 12-68 |
| Enqueue(OracleAQMessage)..... | 12-69 |
| Enqueue(OracleAQMessage, OracleAQEnqueueOptions)..... | 12-70 |
| EnqueueArray..... | 12-70 |
| EnqueueArray(OracleAQMessage[])..... | 12-71 |
| EnqueueArray(OracleAQMessage[], OracleAQEnqueueOptions)..... | 12-72 |
| Listen..... | 12-72 |
| Listen(string[])..... | 12-73 |
| Listen (string[], int)..... | 12-77 |
| OracleAQQueue Events..... | 12-79 |
| MessageAvailable Event..... | 12-79 |
| OracleAQDequeueMode Enumeration | 12-84 |
| OracleAQMessageDeliveryMode Enumeration | 12-85 |
| OracleAQMessageState Enumeration | 12-86 |
| OracleAQMessageType Enumeration | 12-87 |
| OracleAQNavigationMode Enumeration | 12-88 |
| OracleAQNotificationGroupingType Enumeration | 12-89 |
| OracleAQNotificationType Enumeration | 12-90 |
| OracleAQVisibilityMode Enumeration | 12-91 |

13 Oracle Data Provider for .NET Types Classes

| | |
|----------------------------------------------------|-------|
| OracleBFile Class | 13-2 |
| OracleBFile Members..... | 13-5 |
| OracleBFile Constructors..... | 13-8 |
| OracleBFile(OracleConnection)..... | 13-8 |
| OracleBFile(OracleConnection, string, string)..... | 13-8 |
| OracleBFile Static Fields..... | 13-10 |
| MaxSize..... | 13-10 |
| Null..... | 13-10 |
| OracleBFile Static Methods..... | 13-12 |
| OracleBFile Instance Properties..... | 13-13 |
| CanRead..... | 13-13 |
| CanSeek..... | 13-14 |
| CanWrite..... | 13-14 |
| Connection..... | 13-14 |
| DirectoryName..... | 13-15 |
| FileExists..... | 13-15 |
| FileName..... | 13-16 |
| IsEmpty..... | 13-16 |
| IsNull..... | 13-17 |
| IsOpen..... | 13-17 |
| Length..... | 13-17 |
| Position..... | 13-18 |
| Value..... | 13-18 |
| OracleBFile Instance Methods..... | 13-20 |
| Clone..... | 13-21 |
| Close..... | 13-22 |

| | |
|-----------------------------------------------|-------|
| CloseFile | 13-23 |
| Compare | 13-23 |
| CopyTo | 13-25 |
| CopyTo(OracleBlob) | 13-26 |
| CopyTo(OracleBlob, Int64) | 13-26 |
| CopyTo(Int64, OracleBlob, Int64, Int64) | 13-27 |
| CopyTo(OracleClob) | 13-28 |
| CopyTo(OracleClob, Int64) | 13-29 |
| CopyTo(Int64, OracleClob, Int64, Int64) | 13-30 |
| Dispose | 13-31 |
| IsEqual | 13-31 |
| OpenFile | 13-32 |
| Read | 13-32 |
| Search | 13-34 |
| Seek | 13-36 |
| OracleBlob Class | 13-39 |
| OracleBlob Members | 13-42 |
| OracleBlob Constructors | 13-45 |
| OracleBlob(OracleConnection) | 13-45 |
| OracleBlob(OracleConnection, bool) | 13-46 |
| OracleBlob Static Fields | 13-47 |
| MaxSize | 13-47 |
| Null | 13-47 |
| OracleBlob Static Methods | 13-49 |
| OracleBlob Instance Properties | 13-50 |
| CanRead | 13-50 |
| CanSeek | 13-51 |
| CanWrite | 13-51 |
| Connection | 13-51 |
| IsEmpty | 13-52 |
| IsInChunkWriteMode | 13-52 |
| IsNull | 13-53 |
| IsTemporary | 13-53 |
| Length | 13-53 |
| OptimumChunkSize | 13-54 |
| Position | 13-54 |
| Value | 13-55 |
| OracleBlob Instance Methods | 13-56 |
| Append | 13-57 |
| Append(OracleBlob) | 13-57 |
| Append(byte[], int, int) | 13-58 |
| BeginChunkWrite | 13-59 |
| Clone | 13-59 |
| Close | 13-61 |
| Compare | 13-61 |
| CopyTo | 13-62 |
| CopyTo(OracleBlob) | 13-62 |

| | |
|------------------------------------------------|--------|
| CopyTo(OracleBlob, Int64) | 13-63 |
| CopyTo(Int64, OracleBlob, Int64, Int64) | 13-64 |
| Dispose | 13-66 |
| EndChunkWrite | 13-66 |
| Erase | 13-67 |
| Erase() | 13-67 |
| Erase(Int64, Int64) | 13-67 |
| IsEqual | 13-68 |
| Read | 13-69 |
| Search..... | 13-70 |
| Seek | 13-72 |
| SetLength..... | 13-73 |
| Write..... | 13-73 |
| OracleClob Class | 13-76 |
| OracleClob Members | 13-79 |
| OracleClob Constructors..... | 13-82 |
| OracleClob(OracleConnection)..... | 13-82 |
| OracleClob(OracleConnection, bool, bool) | 13-83 |
| OracleClob Static Fields | 13-84 |
| MaxSize | 13-84 |
| Null | 13-84 |
| OracleClob Static Methods | 13-86 |
| OracleClob Instance Properties..... | 13-87 |
| CanRead | 13-87 |
| CanSeek | 13-88 |
| CanWrite | 13-88 |
| Connection | 13-88 |
| IsEmpty..... | 13-89 |
| IsInChunkWriteMode | 13-89 |
| IsNClob..... | 13-90 |
| IsNull | 13-90 |
| IsTemporary..... | 13-90 |
| Length..... | 13-91 |
| OptimumChunkSize..... | 13-91 |
| Position..... | 13-92 |
| Value | 13-92 |
| OracleClob Instance Methods | 13-94 |
| Append..... | 13-95 |
| Append(OracleClob) | 13-95 |
| Append(byte [], int, int) | 13-96 |
| Append(char [], int, int) | 13-96 |
| BeginChunkWrite | 13-98 |
| Clone | 13-98 |
| Close..... | 13-99 |
| Compare..... | 13-100 |
| CopyTo | 13-101 |
| CopyTo(OracleClob)..... | 13-101 |

| | |
|----------------------------------------------|--------|
| CopyTo(OracleClob, Int64)..... | 13-102 |
| CopyTo(Int64, OracleClob, Int64, Int64)..... | 13-103 |
| Dispose | 13-104 |
| EndChunkWrite | 13-105 |
| Erase..... | 13-105 |
| Erase() | 13-106 |
| Erase(Int64, Int64) | 13-106 |
| GetHashCode | 13-107 |
| IsEqual | 13-107 |
| Read | 13-108 |
| Read(byte [], int, int)..... | 13-108 |
| Read(char [], int, int)..... | 13-109 |
| Search..... | 13-111 |
| Search(byte[], Int64, Int64)..... | 13-111 |
| Search(char[], Int64, Int64)..... | 13-112 |
| Seek | 13-114 |
| SetLength..... | 13-114 |
| Write..... | 13-115 |
| Write(byte[], int, int)..... | 13-115 |
| Write(char[], int, int)..... | 13-116 |
| OracleRefCursor Class | 13-119 |
| OracleRefCursor Members | 13-122 |
| OracleRefCursor Static Methods..... | 13-124 |
| OracleRefCursor Static Fields..... | 13-125 |
| Null | 13-125 |
| OracleRefCursor Properties..... | 13-126 |
| Connection | 13-126 |
| FetchSize..... | 13-127 |
| IsNull | 13-128 |
| RowSize | 13-128 |
| OracleRefCursor Instance Methods..... | 13-130 |
| Dispose | 13-130 |
| GetDataReader | 13-130 |

14 Oracle Data Provider for .NET Types Structures

| | |
|-------------------------------------|-------|
| OracleBinary Structure | 14-2 |
| OracleBinary Members..... | 14-4 |
| OracleBinary Constructor | 14-7 |
| OracleBinary Static Fields | 14-8 |
| Null | 14-8 |
| OracleBinary Static Methods | 14-9 |
| Concat | 14-9 |
| Equals | 14-10 |
| GreaterThan | 14-10 |
| GreaterThanOrEqual | 14-11 |
| LessThan | 14-12 |

| | |
|-----------------------------------------------------|-------|
| LessThanOrEqual | 14-13 |
| NotEquals | 14-13 |
| OracleBinary Static Operators | 14-15 |
| operator + | 14-15 |
| operator == | 14-16 |
| operator > | 14-16 |
| operator >= | 14-17 |
| operator != | 14-18 |
| operator < | 14-18 |
| operator <= | 14-19 |
| OracleBinary Static Type Conversion Operators | 14-21 |
| explicit operator byte[] | 14-21 |
| implicit operator OracleBinary | 14-21 |
| OracleBinary Properties | 14-23 |
| IsNull | 14-23 |
| Item | 14-23 |
| Length | 14-24 |
| Value | 14-25 |
| OracleBinary Instance Methods | 14-26 |
| CompareTo | 14-26 |
| Equals | 14-27 |
| GetHashCode | 14-28 |
| ToString | 14-28 |
| OracleBoolean Structure | 14-30 |
| OracleBoolean Members | 14-32 |
| OracleBoolean Constructors | 14-35 |
| OracleBoolean(bool) | 14-35 |
| OracleBoolean(int) | 14-35 |
| OracleBoolean Static Fields | 14-37 |
| False | 14-37 |
| Null | 14-37 |
| One | 14-38 |
| True | 14-38 |
| Zero | 14-38 |
| OracleBoolean Static Methods | 14-40 |
| And | 14-40 |
| Equals | 14-41 |
| GreaterThan | 14-41 |
| GreaterThanOrEquals | 14-42 |
| LessThan | 14-43 |
| LessThanOrEquals | 14-43 |
| NotEquals | 14-44 |
| OnesComplement | 14-44 |
| Or | 14-45 |
| Parse | 14-46 |
| Xor | 14-46 |
| OracleBoolean Static Operators | 14-48 |

| | |
|------------------------------------------------|-------|
| operator > | 14-48 |
| operator >= | 14-49 |
| operator < | 14-50 |
| operator <= | 14-50 |
| operator == | 14-51 |
| operator != | 14-51 |
| operator ! | 14-52 |
| operator ~ | 14-53 |
| operator false | 14-53 |
| operator true | 14-54 |
| operator & | 14-54 |
| operator | 14-55 |
| operator ^ | 14-55 |
| OracleBoolean Static Type Conversions | 14-57 |
| implicit operator OracleBoolean | 14-57 |
| explicit operator bool | 14-57 |
| explicit operator OracleBoolean | 14-58 |
| explicit operator OracleBoolean(byte) | 14-59 |
| explicit operator OracleBoolean(Decimal) | 14-59 |
| explicit operator OracleBoolean(Double) | 14-59 |
| explicit operator OracleBoolean(Int16) | 14-60 |
| explicit operator OracleBoolean(int) | 14-60 |
| explicit operator OracleBoolean(Int64) | 14-61 |
| explicit operator OracleBoolean(Single) | 14-61 |
| explicit operator OracleBoolean(String) | 14-62 |
| OracleBoolean Properties | 14-63 |
| ByteValue | 14-63 |
| IsFalse | 14-63 |
| IsNull | 14-64 |
| IsTrue | 14-64 |
| Value | 14-65 |
| OracleBoolean Instance Methods | 14-66 |
| CompareTo | 14-66 |
| Equals | 14-67 |
| GetHashCode | 14-67 |
| ToString | 14-68 |
| OracleDate Structure | 14-69 |
| OracleDate Members | 14-71 |
| OracleDate Constructors | 14-74 |
| OracleDate(DateTime) | 14-74 |
| OracleDate(string) | 14-75 |
| OracleDate(int, int, int) | 14-76 |
| OracleDate(int, int, int, int, int, int) | 14-76 |
| OracleDate(byte []) | 14-77 |
| OracleDate Static Fields | 14-79 |
| MaxValue | 14-79 |
| MinValue | 14-79 |

| | |
|-----------------------------------------------------|---------------|
| Null | 14-80 |
| OracleDate Static Methods | 14-81 |
| Equals | 14-81 |
| GreaterThan | 14-82 |
| GreaterThanOrEqual | 14-82 |
| LessThan | 14-83 |
| LessThanOrEqual | 14-84 |
| NotEquals | 14-84 |
| GetSysDate | 14-85 |
| Parse | 14-85 |
| OracleDate Static Operators | 14-87 |
| operator == | 14-87 |
| operator > | 14-88 |
| operator >= | 14-88 |
| operator != | 14-89 |
| operator < | 14-90 |
| operator <= | 14-90 |
| OracleDate Static Type Conversions | 14-92 |
| explicit operator DateTime | 14-92 |
| explicit operator OracleDate | 14-92 |
| explicit operator OracleDate(DateTime) | 14-93 |
| explicit operator OracleDate(OracleTimeStamp) | 14-93 |
| explicit operator OracleDate(string) | 14-94 |
| OracleDate Properties | 14-96 |
| BinData | 14-96 |
| Day | 14-96 |
| IsNull | 14-97 |
| Hour | 14-97 |
| Minute | 14-98 |
| Month | 14-98 |
| Second | 14-98 |
| Value | 14-99 |
| Year | 14-99 |
| OracleDate Methods | 14-101 |
| CompareTo | 14-101 |
| Equals | 14-102 |
| GetHashCode | 14-103 |
| GetDaysBetween | 14-103 |
| ToOracleTimeStamp | 14-103 |
| ToString | 14-104 |
| OracleDecimal Structure | 14-106 |
| OracleDecimal Members | 14-108 |
| OracleDecimal Constructors | 14-113 |
| OracleDecimal(byte []) | 14-113 |
| OracleDecimal(decimal) | 14-114 |
| OracleDecimal(double) | 14-114 |
| OracleDecimal(int) | 14-115 |

| | |
|---------------------------------------------------|--------|
| OracleDecimal(float)..... | 14-115 |
| OracleDecimal(long)..... | 14-116 |
| OracleDecimal(string) | 14-116 |
| OracleDecimal(string, string)..... | 14-117 |
| OracleDecimal Static Fields | 14-119 |
| MaxPrecision | 14-119 |
| MaxScale..... | 14-119 |
| MaxValue | 14-120 |
| MinScale | 14-120 |
| MinValue | 14-120 |
| NegativeOne..... | 14-121 |
| Null | 14-121 |
| One | 14-121 |
| Pi..... | 14-121 |
| Zero | 14-122 |
| OracleDecimal Static (Comparison) Methods..... | 14-123 |
| Equals..... | 14-123 |
| GreaterThan | 14-124 |
| GreaterThanOrEqual | 14-124 |
| LessThan | 14-125 |
| LessThanOrEqual | 14-126 |
| NotEquals | 14-126 |
| OracleDecimal Static (Manipulation) Methods | 14-128 |
| Abs | 14-129 |
| Add | 14-129 |
| AdjustScale..... | 14-130 |
| Ceiling..... | 14-131 |
| ConvertToPrecScale..... | 14-131 |
| Divide | 14-132 |
| Floor | 14-133 |
| Max..... | 14-133 |
| Min | 14-134 |
| Mod..... | 14-134 |
| Multiply..... | 14-135 |
| Negate..... | 14-136 |
| Parse..... | 14-136 |
| Round | 14-137 |
| SetPrecision..... | 14-137 |
| Shift | 14-138 |
| Sign..... | 14-139 |
| Sqrt | 14-140 |
| Subtract..... | 14-140 |
| Truncate..... | 14-141 |
| OracleDecimal Static (Logarithmic) Methods..... | 14-142 |
| Exp..... | 14-142 |
| Log..... | 14-142 |
| Log(OracleDecimal)..... | 14-143 |

| | |
|-----------------------------------------------------------------------------------|--------|
| Log(OracleDecimal, int) | 14-144 |
| Log(OracleDecimal, OracleDecimal) | 14-144 |
| Pow | 14-145 |
| Pow(OracleDecimal, int) | 14-145 |
| Pow(OracleDecimal, OracleDecimal) | 14-146 |
| OracleDecimal Static (Trigonometric) Methods | 14-147 |
| Acos | 14-147 |
| Asin | 14-148 |
| Atan | 14-148 |
| Atan2 | 14-149 |
| Cos | 14-149 |
| Sin | 14-150 |
| Tan | 14-150 |
| Cosh | 14-151 |
| Sinh | 14-151 |
| Tanh | 14-152 |
| OracleDecimal Static (Comparison) Operators | 14-153 |
| operator + | 14-153 |
| operator / | 14-154 |
| operator == | 14-154 |
| operator > | 14-155 |
| operator >= | 14-156 |
| operator != | 14-156 |
| operator < | 14-157 |
| operator <= | 14-157 |
| operator * | 14-158 |
| operator - | 14-159 |
| operator - | 14-159 |
| operator% | 14-160 |
| OracleDecimal Static Operators (Conversion from .NET Type to OracleDecimal) | 14-161 |
| implicit operator OracleDecimal | 14-161 |
| implicit operator OracleDecimal(decimal) | 14-161 |
| implicit operator OracleDecimal(int) | 14-162 |
| implicit operator OracleDecimal(long) | 14-162 |
| explicit operator OracleDecimal | 14-163 |
| explicit operator OracleDecimal(double) | 14-163 |
| explicit operator OracleDecimal(string) | 14-164 |
| OracleDecimal Static Operators (Conversion from OracleDecimal to .NET) | 14-165 |
| explicit operator byte | 14-165 |
| explicit operator decimal | 14-166 |
| explicit operator double | 14-166 |
| explicit operator short | 14-167 |
| explicit operator int | 14-167 |
| explicit operator long | 14-168 |
| explicit operator float | 14-168 |
| OracleDecimal Properties | 14-170 |
| BinData | 14-170 |

| | |
|---------------------------------------------------|---------------|
| Format..... | 14-170 |
| IsInt | 14-171 |
| IsNull | 14-172 |
| IsPositive | 14-172 |
| IsZero | 14-172 |
| Value | 14-173 |
| OracleDecimal Instance Methods | 14-174 |
| CompareTo | 14-174 |
| Equals..... | 14-175 |
| GetHashCode | 14-176 |
| ToByte | 14-176 |
| ToDouble..... | 14-176 |
| ToInt16..... | 14-177 |
| ToInt32..... | 14-177 |
| ToInt64..... | 14-178 |
| ToSingle..... | 14-178 |
| ToString..... | 14-179 |
| OracleIntervalDS Structure..... | 14-180 |
| OracleIntervalDS Members | 14-182 |
| OracleIntervalDS Constructors | 14-185 |
| OracleIntervalDS(TimeSpan) | 14-185 |
| OracleIntervalDS(string)..... | 14-186 |
| OracleIntervalDS(double)..... | 14-186 |
| OracleIntervalDS(int, int, int, int, double)..... | 14-187 |
| OracleIntervalDS(int, int, int, int, int) | 14-188 |
| OracleIntervalDS(byte[])..... | 14-189 |
| OracleIntervalDS Static Fields..... | 14-190 |
| MaxValue | 14-190 |
| MinValue..... | 14-190 |
| Null | 14-191 |
| Zero | 14-191 |
| OracleIntervalDS Static Methods..... | 14-192 |
| Equals..... | 14-192 |
| GreaterThan | 14-193 |
| GreaterThanOrEqual | 14-193 |
| LessThan | 14-194 |
| LessThanOrEqual | 14-195 |
| NotEquals | 14-195 |
| Parse..... | 14-196 |
| SetPrecision..... | 14-197 |
| OracleIntervalDS Static Operators..... | 14-199 |
| operator + | 14-199 |
| operator == | 14-200 |
| operator > | 14-200 |
| operator >= | 14-201 |
| operator != | 14-202 |
| operator < | 14-202 |

| | |
|------------------------------------|--------|
| operator <= | 14-203 |
| operator - | 14-204 |
| operator - | 14-204 |
| operator * | 14-205 |
| operator / | 14-205 |
| OracleIntervalDS Type Conversions | 14-207 |
| explicit operator TimeSpan | 14-207 |
| explicit operator OracleIntervalDS | 14-207 |
| implicit operator OracleIntervalDS | 14-208 |
| OracleIntervalDS Properties | 14-210 |
| BinData | 14-210 |
| Days | 14-211 |
| Hours | 14-211 |
| IsNull | 14-211 |
| Milliseconds | 14-212 |
| Minutes | 14-212 |
| Nanoseconds | 14-213 |
| Seconds | 14-213 |
| TotalDays | 14-213 |
| Value | 14-214 |
| OracleIntervalDS Methods | 14-215 |
| CompareTo | 14-215 |
| Equals | 14-216 |
| GetHashCode | 14-216 |
| ToString | 14-217 |
| OracleIntervalYM Structure | 14-218 |
| OracleIntervalYM Members | 14-220 |
| OracleIntervalYM Constructors | 14-223 |
| OracleIntervalYM(long) | 14-223 |
| OracleIntervalYM(string) | 14-224 |
| OracleIntervalYM(double) | 14-224 |
| OracleIntervalYM(int, int) | 14-225 |
| OracleIntervalYM(byte[]) | 14-225 |
| OracleIntervalYM Static Fields | 14-227 |
| MaxValue | 14-227 |
| MinValue | 14-227 |
| Null | 14-228 |
| Zero | 14-228 |
| OracleIntervalYM Static Methods | 14-229 |
| Equals | 14-229 |
| GreaterThan | 14-230 |
| GreaterThanOrEqual | 14-230 |
| LessThan | 14-231 |
| LessThanOrEqual | 14-232 |
| NotEquals | 14-232 |
| Parse | 14-233 |
| SetPrecision | 14-234 |

| | |
|----------------------------------------------------|---------------|
| OracleIntervalYM Static Operators | 14-235 |
| operator + | 14-235 |
| operator == | 14-236 |
| operator > | 14-236 |
| operator >= | 14-237 |
| operator != | 14-238 |
| operator < | 14-238 |
| operator <= | 14-239 |
| operator - | 14-240 |
| operator - | 14-240 |
| operator * | 14-241 |
| operator / | 14-241 |
| OracleIntervalYM Type Conversions..... | 14-243 |
| explicit operator long | 14-243 |
| explicit operator OracleIntervalYM | 14-243 |
| implicit operator OracleIntervalYM | 14-244 |
| OracleIntervalYM Properties..... | 14-246 |
| BinData | 14-246 |
| IsNull | 14-246 |
| Months..... | 14-247 |
| TotalYears..... | 14-247 |
| Value | 14-248 |
| Years..... | 14-248 |
| OracleIntervalYM Methods | 14-249 |
| CompareTo | 14-249 |
| Equals..... | 14-250 |
| GetHashCode | 14-250 |
| ToString..... | 14-251 |
| OracleString Structure..... | 14-252 |
| OracleString Members..... | 14-254 |
| OracleString Constructors..... | 14-257 |
| OracleString(string) | 14-257 |
| OracleString(string, bool) | 14-258 |
| OracleString(byte [], bool) | 14-258 |
| OracleString(byte [], bool, bool)..... | 14-259 |
| OracleString(byte [], int, int, bool)..... | 14-259 |
| OracleString(byte [], int, int, bool, bool) | 14-260 |
| OracleString Static Fields | 14-262 |
| Null | 14-262 |
| OracleString Static Methods | 14-263 |
| Concat | 14-263 |
| Equals | 14-264 |
| GreaterThan | 14-264 |
| GreaterThanOrEqual | 14-265 |
| LessThan | 14-266 |
| LessThanOrEqual | 14-266 |
| NotEquals | 14-267 |

| | |
|------------------------------------------------------------|---------------|
| OracleString Static Operators..... | 14-268 |
| operator + | 14-268 |
| operator == | 14-269 |
| operator > | 14-269 |
| operator >= | 14-270 |
| operator != | 14-271 |
| operator < | 14-271 |
| operator <= | 14-272 |
| OracleString Type Conversions | 14-274 |
| explicit operator string | 14-274 |
| implicit operator OracleString | 14-274 |
| OracleString Properties | 14-276 |
| IsCaseIgnored | 14-276 |
| IsNull | 14-277 |
| Item | 14-277 |
| Length..... | 14-278 |
| Value | 14-278 |
| OracleString Methods..... | 14-279 |
| Clone | 14-279 |
| CompareTo | 14-280 |
| Equals..... | 14-281 |
| GetHashCode | 14-281 |
| GetNonUnicodeBytes..... | 14-282 |
| GetUnicodeBytes | 14-282 |
| ToString..... | 14-283 |
| OracleTimeStamp Structure..... | 14-284 |
| OracleTimeStamp Members | 14-286 |
| OracleTimeStamp Constructors..... | 14-290 |
| OracleTimeStamp(DateTime) | 14-290 |
| OracleTimeStamp(string)..... | 14-291 |
| OracleTimeStamp(int, int, int) | 14-292 |
| OracleTimeStamp(int, int, int, int, int, int) | 14-293 |
| OracleTimeStamp(int, int, int, int, int, int, double)..... | 14-294 |
| OracleTimeStamp(int, int, int, int, int, int, int) | 14-294 |
| OracleTimeStamp(byte []) | 14-295 |
| OracleTimeStamp Static Fields | 14-297 |
| MaxValue | 14-297 |
| MinValue..... | 14-297 |
| Null | 14-298 |
| OracleTimeStamp Static Methods | 14-299 |
| Equals | 14-299 |
| GreaterThan | 14-300 |
| GreaterThanOrEqual | 14-300 |
| LessThan..... | 14-301 |
| LessThanOrEqual | 14-302 |
| NotEquals | 14-302 |
| GetSysDate | 14-303 |

| | |
|-------------------------------------------------------------|--------|
| Parse | 14-303 |
| SetPrecision..... | 14-305 |
| OracleTimeStamp Static Operators | 14-306 |
| operator + | 14-306 |
| operator + (OracleTimeStamp, OracleIntervalDS)..... | 14-307 |
| operator + (OracleTimeStamp, OracleIntervalYM) | 14-307 |
| operator + (OracleTimeStamp, TimeSpan) | 14-308 |
| operator == | 14-308 |
| operator > | 14-309 |
| operator >= | 14-310 |
| operator != | 14-310 |
| operator < | 14-311 |
| operator <= | 14-312 |
| operator - | 14-312 |
| operator - (OracleTimeStamp, OracleIntervalDS)..... | 14-313 |
| operator - (OracleTimeStamp, OracleIntervalYM) | 14-313 |
| operator - (OracleTimeStamp, TimeSpan) | 14-314 |
| OracleTimeStamp Static Type Conversions..... | 14-315 |
| explicit operator OracleTimeStamp | 14-315 |
| explicit operator OracleTimeStamp(OracleTimeStampLTZ) | 14-315 |
| explicit operator OracleTimeStamp(OracleTimeStampTZ)..... | 14-316 |
| explicit operator OracleTimeStamp(string) | 14-317 |
| implicit operator OracleTimeStamp..... | 14-318 |
| implicit operator OracleTimeStamp(OracleDate) | 14-318 |
| implicit operator OracleTimeStamp(DateTime)..... | 14-319 |
| explicit operator DateTime | 14-319 |
| OracleTimeStamp Properties..... | 14-321 |
| BinData | 14-321 |
| Day | 14-322 |
| IsNull | 14-322 |
| Hour | 14-322 |
| Millisecond..... | 14-323 |
| Minute..... | 14-323 |
| Month..... | 14-324 |
| Nanosecond | 14-324 |
| Second..... | 14-324 |
| Value | 14-325 |
| Year | 14-325 |
| OracleTimeStamp Methods | 14-327 |
| AddDays | 14-327 |
| AddHours | 14-328 |
| AddMilliseconds | 14-328 |
| AddMinutes | 14-329 |
| AddMonths | 14-330 |
| AddNanoseconds | 14-330 |
| AddSeconds | 14-331 |
| AddYears | 14-331 |

| | |
|----------------------------------------------------------------|---------------|
| CompareTo | 14-332 |
| Equals | 14-332 |
| GetHashCode | 14-333 |
| GetDaysBetween | 14-333 |
| GetYearsBetween | 14-334 |
| ToOracleDate | 14-335 |
| ToOracleTimeStampLTZ | 14-335 |
| ToOracleTimeStampTZ | 14-335 |
| ToString | 14-336 |
| OracleTimeStampLTZ Structure | 14-338 |
| OracleTimeStampLTZ Members | 14-340 |
| OracleTimeStampLTZ Constructors | 14-344 |
| OracleTimeStampLTZ(DateTime) | 14-344 |
| OracleTimeStampLTZ(string) | 14-345 |
| OracleTimeStampLTZ(int, int, int) | 14-346 |
| OracleTimeStampLTZ(int, int, int, int, int, int) | 14-347 |
| OracleTimeStampLTZ(int, int, int, int, int, int, double) | 14-348 |
| OracleTimeStampLTZ(int, int, int, int, int, int, int) | 14-348 |
| OracleTimeStampLTZ(byte []) | 14-349 |
| OracleTimeStampLTZ Static Fields | 14-351 |
| MaxValue | 14-351 |
| MinValue | 14-351 |
| Null | 14-352 |
| OracleTimeStampLTZ Static Methods | 14-353 |
| Equals | 14-353 |
| GetLocalTimeZoneName | 14-354 |
| GetLocalTimeZoneOffset | 14-354 |
| GetSysDate | 14-355 |
| GreaterThan | 14-355 |
| GreaterThanOrEqual | 14-356 |
| LessThan | 14-356 |
| LessThanOrEqual | 14-357 |
| NotEquals | 14-358 |
| Parse | 14-358 |
| SetPrecision | 14-359 |
| OracleTimeStampLTZ Static Operators | 14-361 |
| operator + | 14-361 |
| operator + (OracleTimeStampLTZ, OracleIntervalDS) | 14-362 |
| operator + (OracleTimeStampLTZ, OracleIntervalYM) | 14-362 |
| operator + (OracleTimeStampLTZ, TimeSpan) | 14-363 |
| operator == | 14-363 |
| operator > | 14-364 |
| operator >= | 14-365 |
| operator != | 14-365 |
| operator < | 14-366 |
| operator <= | 14-367 |
| operator - | 14-367 |

| | |
|---------------------------------------------------------------|--------|
| operator - (OracleTimeStampLTZ, OracleIntervalDS) | 14-368 |
| operator - (OracleTimeStampLTZ, OracleIntervalYM) | 14-368 |
| operator - (OracleTimeStampLTZ, TimeSpan) | 14-369 |
| OracleTimeStampLTZ Static Type Conversions | 14-371 |
| explicit operator OracleTimeStampLTZ | 14-371 |
| explicit operator OracleTimeStampLTZ(OracleTimeStamp) | 14-371 |
| explicit operator OracleTimeStampLTZ(OracleTimeStampTZ) | 14-372 |
| explicit operator OracleTimeStampLTZ(string) | 14-373 |
| implicit operator OracleTimeStampLTZ | 14-374 |
| implicit operator OracleTimeStampLTZ(OracleDate) | 14-374 |
| implicit operator OracleTimeStampLTZ(DateTime) | 14-375 |
| explicit operator DateTime | 14-375 |
| OracleTimeStampLTZ Properties | 14-377 |
| BinData | 14-377 |
| Day | 14-378 |
| IsNull | 14-378 |
| Hour | 14-378 |
| Millisecond | 14-379 |
| Minute | 14-379 |
| Month | 14-380 |
| Nanosecond | 14-380 |
| Second | 14-380 |
| Value | 14-381 |
| Year | 14-381 |
| OracleTimeStampLTZ Methods | 14-383 |
| AddDays | 14-384 |
| AddHours | 14-384 |
| AddMilliseconds | 14-385 |
| AddMinutes | 14-385 |
| AddMonths | 14-386 |
| AddNanoseconds | 14-386 |
| AddSeconds | 14-387 |
| AddYears | 14-387 |
| CompareTo | 14-388 |
| Equals | 14-389 |
| GetHashCode | 14-389 |
| GetDaysBetween | 14-390 |
| GetYearsBetween | 14-390 |
| ToOracleDate | 14-391 |
| ToOracleTimeStamp | 14-391 |
| ToOracleTimeStampTZ | 14-392 |
| ToString | 14-392 |
| ToUniversalTime | 14-393 |
| OracleTimeStampTZ Structure | 14-395 |
| OracleTimeStampTZ Members | 14-397 |
| OracleTimeStampTZ Constructors | 14-401 |
| OracleTimeStampTZ(DateTime) | 14-402 |

| | |
|-----------------------------------------------------------------------|--------|
| OracleTimeStampTZ(DateTime, string) | 14-402 |
| OracleTimeStampTZ(string) | 14-403 |
| OracleTimeStampTZ(int, int, int) | 14-404 |
| OracleTimeStampTZ(int, int, int, string) | 14-405 |
| OracleTimeStampTZ(int, int, int, int, int, int) | 14-406 |
| OracleTimeStampTZ(int, int, int, int, int, int, string) | 14-407 |
| OracleTimeStampTZ(int, int, int, int, int, int, double) | 14-408 |
| OracleTimeStampTZ(int, int, int, int, int, int, double, string) | 14-409 |
| OracleTimeStampTZ(int, int, int, int, int, int, int) | 14-410 |
| OracleTimeStampTZ(int, int, int, int, int, int, int, string) | 14-411 |
| OracleTimeStampTZ(byte []) | 14-412 |
| OracleTimeStampTZ Static Fields | 14-413 |
| MaxValue | 14-413 |
| MinValue | 14-413 |
| Null | 14-414 |
| OracleTimeStampTZ Static Methods | 14-415 |
| Equals | 14-415 |
| GetSysDate | 14-416 |
| GreaterThan | 14-416 |
| GreaterThanOrEqual | 14-417 |
| LessThan | 14-417 |
| LessThanOrEqual | 14-418 |
| NotEquals | 14-419 |
| Parse | 14-419 |
| SetPrecision | 14-421 |
| OracleTimeStampTZ Static Operators | 14-422 |
| operator + | 14-422 |
| operator +(OracleTimeStampTZ, OracleIntervalDS) | 14-423 |
| operator +(OracleTimeStampTZ, OracleIntervalYM) | 14-423 |
| operator +(OracleTimeStampTZ, TimeSpan) | 14-424 |
| operator == | 14-424 |
| operator > | 14-425 |
| operator >= | 14-426 |
| operator != | 14-426 |
| operator < | 14-427 |
| operator <= | 14-428 |
| operator - | 14-428 |
| operator -(OracleTimeStampTZ, OracleIntervalDS) | 14-429 |
| operator -(OracleTimeStampTZ, OracleIntervalYM) | 14-429 |
| operator -(OracleTimeStampTZ value1, TimeSpan value2) | 14-430 |
| OracleTimeStampTZ Static Type Conversions | 14-431 |
| explicit operator OracleTimeStampTZ | 14-431 |
| explicit operator OracleTimeStampTZ(OracleTimeStamp) | 14-431 |
| explicit operator OracleTimeStampTZ(OracleTimeStampLTZ) | 14-432 |
| explicit operator OracleTimeStampTZ(string) | 14-433 |
| implicit operator OracleTimeStampTZ | 14-434 |
| implicit operator OracleTimeStampTZ(OracleDate) | 14-434 |

| | |
|----------------------------------------------------|--------|
| implicit operator OracleTimeStampTZ(DateTime)..... | 14-435 |
| explicit operator DateTime | 14-436 |
| OracleTimeStampTZ Properties | 14-437 |
| BinData | 14-437 |
| Day | 14-438 |
| IsNull | 14-438 |
| Hour | 14-438 |
| Millisecond..... | 14-439 |
| Minute..... | 14-439 |
| Month..... | 14-440 |
| Nanosecond | 14-440 |
| Second..... | 14-441 |
| TimeZone | 14-441 |
| Value | 14-441 |
| Year | 14-442 |
| OracleTimeStampTZ Methods..... | 14-443 |
| AddDays | 14-444 |
| AddHours | 14-444 |
| AddMilliseconds | 14-445 |
| AddMinutes | 14-445 |
| AddMonths | 14-446 |
| AddNanoseconds | 14-446 |
| AddSeconds | 14-447 |
| AddYears | 14-447 |
| CompareTo | 14-448 |
| Equals..... | 14-449 |
| GetDaysBetween..... | 14-449 |
| GetHashCode | 14-450 |
| GetTimeZoneOffset | 14-450 |
| GetYearsBetween | 14-450 |
| ToLocalTime | 14-451 |
| ToOracleDate | 14-451 |
| ToOracleTimeStampLTZ..... | 14-452 |
| ToOracleTimeStamp..... | 14-452 |
| ToString..... | 14-453 |
| ToUniversalTime..... | 14-454 |
| INullable Interface | 14-455 |
| INullable Interface Members..... | 14-456 |
| INullable Interface Properties | 14-457 |
| IsNull | 14-457 |

15 Oracle Data Provider for .NET Types Exceptions

| | |
|----------------------------------------------------------------|------|
| OracleTypeException Class..... | 15-2 |
| OracleTypeException Members..... | 15-3 |
| OracleTypeException Constructors..... | 15-5 |
| OracleTypeException(string) | 15-5 |
| OracleTypeException(SerializationInfo, StreamingContext) | 15-5 |

| | |
|----------------------------------------------|-------|
| OracleTypeException Static Methods | 15-7 |
| OracleTypeException Properties | 15-8 |
| Message | 15-8 |
| Number | 15-8 |
| Source | 15-9 |
| OracleTypeException Methods..... | 15-10 |
| ToString..... | 15-10 |
| OracleNullValueException Class | 15-11 |
| OracleNullValueException Members | 15-12 |
| OracleNullValueException Constructors | 15-14 |
| OracleNullValueException() | 15-14 |
| OracleNullValueException(string)..... | 15-14 |
| OracleNullValueException Static Methods..... | 15-16 |
| OracleNullValueException Properties..... | 15-17 |
| OracleNullValueException Methods | 15-18 |
| OracleTruncateException Class | 15-19 |
| OracleTruncateException Members | 15-20 |
| OracleTruncateException Constructors..... | 15-22 |
| OracleTruncateException()..... | 15-22 |
| OracleTruncateException(string)..... | 15-22 |
| OracleTruncateException Static Methods | 15-24 |
| OracleTruncateException Properties..... | 15-25 |
| OracleTruncateException Methods | 15-26 |

16 Oracle Data Provider for .NET UDT-Related Classes

| | |
|-------------------------------------------------------|-------|
| OracleCustomTypeMappingAttribute Class | 16-2 |
| OracleCustomTypeMappingAttribute Members..... | 16-4 |
| OracleCustomTypeMappingAttribute Constructors..... | 16-6 |
| OracleCustomTypeMappingAttribute(string) | 16-6 |
| OracleCustomTypeMappingAttribute Static Methods | 16-7 |
| OracleCustomTypeMappingAttribute Properties | 16-8 |
| UdtTypeName..... | 16-8 |
| OracleCustomTypeMappingAttribute Methods..... | 16-9 |
| OracleObjectMappingAttribute Class | 16-10 |
| OracleObjectMappingAttribute Members..... | 16-11 |
| OracleObjectMappingAttribute Constructors | 16-13 |
| OracleObjectMappingAttribute(string) | 16-13 |
| OracleObjectMappingAttribute(int)..... | 16-13 |
| OracleObjectMappingAttribute Static Methods..... | 16-15 |
| OracleObjectMappingAttribute Properties | 16-16 |
| AttributeIndex | 16-16 |
| AttributeName | 16-16 |
| OracleObjectMappingAttribute Methods..... | 16-18 |
| OracleArrayMappingAttribute Class | 16-19 |
| OracleArrayMappingAttribute Members | 16-20 |
| OracleArrayMappingAttribute Constructors | 16-22 |
| OracleArrayMappingAttribute() | 16-22 |

| | |
|-----------------------------------------------------------------|--------------|
| OracleArrayMappingAttribute Static Methods..... | 16-23 |
| OracleArrayMappingAttribute Properties..... | 16-24 |
| OracleArrayMappingAttribute Methods..... | 16-25 |
| IOracleCustomType Interface..... | 16-26 |
| IOracleCustomType Members..... | 16-27 |
| IOracleCustomType Interface Methods..... | 16-28 |
| FromCustomObject..... | 16-28 |
| ToCustomObject..... | 16-29 |
| IOracleCustomTypeFactory Interface..... | 16-30 |
| IOracleCustomTypeFactory Members..... | 16-31 |
| IOracleCustomTypeFactory Interface Methods..... | 16-32 |
| CreateObject..... | 16-32 |
| IOracleArrayTypeFactory Interface..... | 16-33 |
| IOracleArrayTypeFactory Members..... | 16-34 |
| IOracleArrayTypeFactory Interface Methods..... | 16-35 |
| CreateArray..... | 16-35 |
| CreateStatusArray..... | 16-36 |
| OracleUdt Class..... | 16-37 |
| OracleUdt Members..... | 16-38 |
| OracleUDT Static Methods..... | 16-39 |
| GetValue..... | 16-39 |
| GetValue(OracleConnection, IntPtr, string)..... | 16-40 |
| GetValue(OracleConnection, IntPtr, int)..... | 16-41 |
| GetValue(OracleConnection, IntPtr, string, out object)..... | 16-42 |
| GetValue(OracleConnection, IntPtr, int, out object)..... | 16-43 |
| IsDBNull..... | 16-44 |
| IsDBNull(OracleConnection, IntPtr, string)..... | 16-45 |
| IsDBNull(OracleConnection, IntPtr, int)..... | 16-45 |
| SetValue..... | 16-46 |
| SetValue(OracleConnection, IntPtr, string, object)..... | 16-47 |
| SetValue(OracleConnection, IntPtr, int, object)..... | 16-48 |
| SetValue(OracleConnection, IntPtr, string, object, object)..... | 16-49 |
| SetValue(OracleConnection, IntPtr, int, object, object)..... | 16-50 |
| OracleRef Class..... | 16-52 |
| OracleRef Members..... | 16-53 |
| OracleRef Constructors..... | 16-55 |
| OracleRef(OracleConnection, string)..... | 16-55 |
| OracleRef(OracleConnection, string, string)..... | 16-56 |
| OracleRef Static Fields..... | 16-58 |
| Null..... | 16-58 |
| OracleRef Static Methods..... | 16-59 |
| OracleRef Instance Properties..... | 16-60 |
| Connection..... | 16-60 |
| HasChanges..... | 16-60 |
| IsLocked..... | 16-61 |
| IsNull..... | 16-61 |
| ObjectTableName..... | 16-62 |

| | |
|-------------------------------------------------|--------------|
| Value | 16-62 |
| Oracle Ref Instance Methods | 16-64 |
| Clone | 16-64 |
| Delete | 16-65 |
| Dispose | 16-65 |
| Flush..... | 16-66 |
| GetCustomObject | 16-66 |
| GetCustomObject(OracleUdtFetchOption)..... | 16-67 |
| GetCustomObject(OracleUdtFetchOption, int)..... | 16-68 |
| GetCustomObjectForUpdate | 16-69 |
| GetCustomObjectForUpdate(bool) | 16-70 |
| GetCustomObjectForUpdate(bool, int)..... | 16-71 |
| IsEqual | 16-72 |
| Lock..... | 16-72 |
| Update | 16-73 |
| OracleUdtFetchOption Enumeration | 16-75 |
| OracleUdtStatus Enumeration | 16-76 |

17 Oracle Data Provider for .NET

Bulk Copy Classes

| | |
|--------------------------------------------------------------|-------------|
| OracleBulkCopy Class | 17-2 |
| OracleBulkCopy Members..... | 17-3 |
| OracleBulkCopy Constructors | 17-5 |
| OracleBulkCopy(OracleConnection) | 17-5 |
| OracleBulkCopy(string)..... | 17-6 |
| OracleBulkCopy(OracleConnection, OracleBulkCopyOptions)..... | 17-6 |
| OracleBulkCopy(string, OracleBulkCopyOptions) | 17-7 |
| OracleBulkCopy Properties | 17-9 |
| BatchSize | 17-9 |
| BulkCopyOptions | 17-10 |
| BulkCopyTimeout..... | 17-11 |
| ColumnMappings..... | 17-11 |
| Connection | 17-12 |
| DestinationPartitionName..... | 17-12 |
| DestinationTableName | 17-13 |
| NotifyAfter..... | 17-13 |
| OracleBulkCopy Public Methods | 17-15 |
| Close..... | 17-15 |
| Dispose | 17-15 |
| WriteToServer..... | 17-16 |
| WriteToServer(DataRow[])..... | 17-17 |
| WriteToServer(DataTable)..... | 17-17 |
| WriteToServer(IDataReader)..... | 17-18 |
| WriteToServer(DataTable, DataRowState) | 17-18 |
| WriteToServer(OracleRefCursor) | 17-19 |
| OracleBulkCopy Events | 17-21 |
| OracleRowsCopied | 17-21 |

| | |
|-----------------------------------------------------------|-------|
| OracleBulkCopyColumnMapping Class | 17-22 |
| OracleBulkCopyColumnMapping Members..... | 17-24 |
| OracleBulkCopyColumnMapping Constructors..... | 17-25 |
| OracleBulkCopyColumnMapping()..... | 17-25 |
| OracleBulkCopyColumnMapping(int, int)..... | 17-26 |
| OracleBulkCopyColumnMapping(int, string) | 17-26 |
| OracleBulkCopyColumnMapping(string, int) | 17-27 |
| OracleBulkCopyColumnMapping(string, string)..... | 17-27 |
| OracleBulkCopyColumnMapping Methods..... | 17-29 |
| CompareTo | 17-29 |
| OracleBulkCopyColumnMapping Properties | 17-30 |
| DestinationColumn..... | 17-30 |
| DestinationOrdinal | 17-30 |
| SourceColumn | 17-31 |
| SourceOrdinal..... | 17-31 |
| OracleBulkCopyColumnMappingCollection Class | 17-33 |
| OracleBulkCopyColumnMappingCollection Members..... | 17-35 |
| OracleBulkCopyColumnMappingCollection Properties | 17-36 |
| Item[index]..... | 17-36 |
| OracleBulkCopyColumnMappingCollection Public Methods..... | 17-37 |
| Add | 17-37 |
| Add(OracleBulkCopyColumnMapping)..... | 17-38 |
| Add(int, int) | 17-38 |
| Add(int, string)..... | 17-39 |
| Add(string, int)..... | 17-40 |
| Add(string, string) | 17-41 |
| Clear | 17-42 |
| Contains..... | 17-42 |
| CopyTo | 17-43 |
| IndexOf..... | 17-43 |
| Insert | 17-44 |
| Remove | 17-44 |
| RemoveAt..... | 17-45 |
| OracleBulkCopyOptions Enumeration | 17-46 |
| OracleRowsCopiedEventHandler Delegate | 17-47 |
| OracleRowsCopiedEventArgs Class | 17-48 |
| OracleRowsCopiedEventArgs Members..... | 17-49 |
| OracleRowsCopiedEventArgs Constructors..... | 17-50 |
| OracleRowsCopiedEventArgs(long)..... | 17-50 |
| OracleRowsCopiedEventArgs Properties | 17-51 |
| Abort | 17-51 |
| RowsCopied..... | 17-52 |

A Oracle Schema Collections

| | |
|----------------------------------------|-----|
| Common Schema Collections | A-1 |
| MetaDataCollections..... | A-1 |
| DataSourceInformation | A-2 |

| | |
|-------------------------------------------------|------------|
| DataTypes | A-3 |
| Restrictions | A-4 |
| ReservedWords | A-5 |
| ODP.NET-Specific Schema Collection | A-5 |
| Tables | A-5 |
| Columns | A-6 |
| Views | A-6 |
| XMLSchema | A-7 |
| Users | A-7 |
| Synonyms | A-7 |
| Sequences | A-8 |
| Functions | A-8 |
| Procedures | A-9 |
| ProcedureParameters | A-10 |
| Arguments | A-11 |
| Packages | A-11 |
| PackageBodies | A-12 |
| JavaClasses | A-13 |
| Indexes | A-13 |
| IndexColumns | A-16 |
| PrimaryKeys | A-16 |
| ForeignKeys | A-17 |
| ForeignKeyColumns | A-18 |
| UniqueKeys | A-18 |

B Mapping LINQ Canonical Functions and Oracle Functions

Index

Preface

This document is your primary source of introductory, installation, postinstallation configuration, and usage information for Oracle Data Provider for .NET.

Oracle Data Provider for .NET is an implementation of the Microsoft ADO.NET interface.

This Preface contains these topics:

- [Audience](#)
- [Documentation Accessibility](#)
- [Related Documents](#)
- [Passwords in Code Examples](#)
- [Conventions](#)

Audience

Oracle Data Provider for .NET Developer's Guide is intended for programmers who are developing applications to access an Oracle database using Oracle Data Provider for .NET. This documentation is also valuable to systems analysts, project managers, and others interested in the development of database applications.

To use this document, you must be familiar with Microsoft .NET Framework classes and ADO.NET and have a working knowledge of application programming using Microsoft C#, Visual Basic .NET, or another .NET language.

Although the examples in the documentation and the samples in the sample directory are written in C#, developers can use these examples as models for writing code in other .NET languages.

Users should also be familiar with the use of Structured Query Language (SQL) to access information in relational database systems.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or

visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Related Documents

For more information, see these Oracle resources:

- *Oracle Database Installation Guide for Microsoft Windows*
- *Oracle Database Release Notes for Microsoft Windows*
- *Oracle Database Platform Guide for Microsoft Windows*
- *Oracle Database Administrator's Guide*
- *Oracle Database Development Guide*
- *Oracle Database SecureFiles and Large Objects Developer's Guide*
- *Oracle Real Application Clusters Administration and Deployment Guide*
- *Oracle Database New Features Guide*
- *Oracle Database Concepts*
- *Oracle Database Reference*
- *Oracle Database Extensions for .NET Developer's Guide for Microsoft Windows*
- *Oracle Database Object-Relational Developer's Guide*
- *Oracle Database SQL Language Reference*
- *Oracle Database Net Services Administrator's Guide*
- *Oracle Database Net Services Reference*
- *Oracle Call Interface Programmer's Guide*
- *Oracle Services for Microsoft Transaction Server Developer's Guide for Microsoft Windows*
- *Oracle Database Globalization Support Guide*
- *Oracle XML DB Developer's Guide*
- *Oracle XML Developer's Kit Programmer's Guide*
- *Oracle Database Security Guide*
- *Oracle Spatial Developer's Guide*
- *Oracle Data Guard Concepts and Administration*

Many of the examples in this book use the sample schemas, which are installed by default when you select the Basic Installation option with an Oracle Database installation. Refer to *Oracle Database Sample Schemas* for information on how these schemas were created and how you can use them yourself.

To download free release notes, installation documentation, white papers, or other collateral, please visit the Oracle Technology Network (OTN). You must register online before using OTN; registration is free and can be done at

<http://www.oracle.com/technetwork/index.html>

If you already have a username and password for OTN, then you can go directly to the documentation section of the OTN Web site at

<http://www.oracle.com/technetwork/indexes/documentation/index.html>

For additional information, see:

<http://msdn.microsoft.com/netframework>

and

<http://msdn.microsoft.com/library>

Passwords in Code Examples

For simplicity in demonstrating this product, code examples do not perform the password management techniques that a deployed system normally uses. In a production environment, follow the Oracle Database password management guidelines, and disable any sample accounts. See *Oracle Database Security Guide* for password management guidelines and other security recommendations.

Conventions

The following text conventions are used in this document:

| Convention | Meaning |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------|
| boldface | Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary. |
| <i>italic</i> | Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values. |
| monospace | Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter. |

Changes in This Release for Oracle Data Provider for .NET

This preface contains:

- [Changes in Oracle Data Provider for .NET Release 12.1.0.2](#)
- [Changes in Oracle Data Provider for .NET in ODAC 12c Release 2](#)
- [Changes in Oracle Data Provider for .NET in ODAC 12c Release 1](#)
- [Changes in Oracle Data Provider for .NET Release 12.1](#)
- [Changes in Oracle Data Provider for .NET Release 11.2.0.3.20](#)
- [Changes in Oracle Data Provider for .NET Release 11.2.0.3](#)
- [Changes in Oracle Data Provider for .NET Release 11.2.0.2](#)
- [Changes in Oracle Data Provider for .NET Release 11.2.0.1.2](#)
- [Changes in Oracle Data Provider for .NET Release 11.2](#)
- [Changes in Oracle Data Provider for .NET Release 11.1.0.7.20](#)
- [Changes in Oracle Data Provider for .NET Release 11.1.0.6.20](#)
- [Changes in Oracle Data Provider for .NET Release 11.1](#)

Changes in Oracle Data Provider for .NET Release 12.1.0.2

The following are the changes in Oracle Data Provider for .NET for Release 12.1.0.2.

New Features

The following features are new in this release:

- .NET Framework 4.5.2 Certification
ODP.NET managed and unmanaged drivers are certified for .NET Framework 4.5.2.
See also "[System Requirements](#)" on page 2-1 for more information.
- Character Data Types Extended to 32 KB
ODP.NET, Managed Driver supports the `VARCHAR2`, `NVARCHAR2`, and `RAW` data types up to 32 KB in size. No code changes are required to use the larger data types.
By being able to store more data, developers can use these data types more frequently, providing programming flexibility. In addition, SQL Server to Oracle Database application migration is easier with these new data type sizes.

- Return Number of Rows Affected from Each Input in Array Binding Operations
When using array binding to execute multiple DML statements, ODP.NET, Managed Driver provides an array that lists the number of rows affected for each input value from the bound array, rather than just the total number of rows affected. This information provides more detailed feedback for the application developer. To retrieve the row count, ODP.NET can call the `OracleCommand.ArrayBindRowsAffected` property.
With more detailed feedback on the array bound DML execution, the developer can better evaluate the query's efficiency and whether the data changes were correctly applied.
See Also "[ArrayBindRowsAffected](#)" on page 6-24 for more information.

Changes in Oracle Data Provider for .NET in ODAC 12c Release 2

The following are the changes in Oracle Data Provider for .NET for ODAC 12c Release 2.

New Features

The following features are new in this release:

- .NET Framework 4.5.1 Certification
Oracle Data Provider for .NET is now certified for .NET Framework 4.5.1.
See also "[System Requirements](#)" on page 2-1 for more information.
- Improvements to ODP.NET, Managed Driver Versioning
This feature allows unique identification of ODP.NET, Managed Driver assemblies which have the same assembly version number.
See also "[Oracle Data Provider for .NET Versioning Scheme](#)" on page 2-3 for more information.

Changes in Oracle Data Provider for .NET in ODAC 12c Release 1

The following are the changes in Oracle Data Provider for .NET for ODAC 12c Release 1.

New Features

The following feature is new in this release:

- LDAP Connections to Active Directory and Oracle Internet Directory
ODP.NET, Managed Driver supports TNS alias resolution through a LDAP server/service, specifically Microsoft Active Directory and Oracle Internet Directory.
This feature allows ODP.NET, Managed Driver to connect to a database using a directory server/service.
See also "[Lightweight Directory Access Protocol](#)" on page 2-24.

Changes in Oracle Data Provider for .NET Release 12.1

The following are the changes in Oracle Data Provider for .NET for Release 12.1.

New Features

The following features are new in this release:

- ODP.NET, Managed Driver

ODP.NET now includes a fully managed provider version, which is 100% native .NET code. ODP.NET, Managed Driver includes nearly all the features of ODP.NET, Unmanaged Driver and uses the same application programming interface. This makes migrating existing ODP.NET applications to ODP.NET, Managed Driver easier.

With ODP.NET, Managed Driver, it is easier and faster to deploy ODP.NET. There are fewer assemblies, as few as one to deploy, which also makes patching straightforward, and the install size is smaller at less than 10 MB. Only one ODP.NET, Managed Driver assembly is necessary whether you are using 32-bit or 64-bit .NET Framework. Side-by-side deployment with other ODP.NET versions is simple since there are no unmanaged assemblies to account for. As a fully managed provider, ODP.NET can better integrate with Code Access Security and ClickOnce deployment.

See also ["Installing Oracle Data Provider for .NET, Managed Driver"](#) on page 2-7 .

- Support for Pluggable Database

Pluggable Databases (PDBs) enable an Oracle database to contain a portable collection of schemas, schema objects, and nonschema objects that appears to ODP.NET as a separate database. ODP.NET can seamlessly use PDBs.

PDBs allow fast database provisioning, fast database redeployment by unplugging and plugging in existing databases, and quick patching or upgrading many databases at the cost of doing it once or by unplugging a PDB and plugging it into a different container database. A machine can run more database instances in the form of PDBs than as individual, monolithic databases. It is also easier to separate application administrator duties from the Oracle system administrator duties.

See Also:

- ["Pluggable Databases"](#) on page 3-15

- Support for Auto Increment Identity Column

Oracle Database 12c Release 1 (12.1) introduces an auto increment identity column. ODP.NET, Unmanaged Driver 12.1 and higher releases support interacting with this column data. Identity columns are generally used to uniquely identify rows in a table when there is no other natural primary key constraint.

An identity column simplifies .NET development for applications with no natural primary key and eases application migration from databases that have an identity column.

See Also:

- ["IdentityInsert"](#) on page 6-170
- ["IdentityUpdate"](#) on page 6-171
- ["OracleIdentityType Enumeration"](#) on page 6-428

- Support for Character Data Types Extended to 32 KB

Starting with Oracle Database 12c Release 1 (12.1), ODP.NET, Unmanaged Driver now supports the `VARCHAR2`, `NVARCHAR2`, and `RAW` data types up to 32 KB in size. No code changes are required to use the larger data types.

By being able to store more data, developers can use these data types more frequently, providing programming flexibility. In addition, SQL Server to Oracle Database application migration is easier with these new data type sizes.

- Boolean Data Type

Oracle Database 12c Release 1 (12.1) introduces a new PL/SQL Boolean data type, which ODP.NET, Unmanaged Driver can store as an `OracleBoolean` data type. Booleans store `TRUE` or `FALSE` values.

The ODP.NET `OracleBoolean` data type eases parameter binding and data type mapping setup with Boolean values.

See Also:

- ["OracleBoolean Structure"](#) on page 14-30

- Enhanced Implicit REF Cursor Binding

In Oracle Database 12c Release 1 (12.1), ODP.NET 12c can retrieve the results of a `SELECT` statement run in PL/SQL without an explicit target nor `REF CURSOR` data type. ODP.NET retrieves result sets from stored procedures implicitly without declaring a return type. It is no longer necessary to declare `REF CURSOR` metadata in a `.NET` configuration file, except when using Entity Framework, `REF CURSOR`s that can be updated, or constraint metadata is required to be passed to the client side.

This capability simplifies using implicit Oracle result sets. In addition, it eases migration to the Oracle database from other vendor databases that use a similar feature.

See Also:

- ["ImplicitRefCursors"](#) on page 6-29
- ["Implicit REF CURSOR Binding"](#) on page 3-67

- Return Number of Rows Affected from Each Input in Array Binding Operations

When using array binding to execute multiple DML statements, Oracle Data Provider for `.NET`, Unmanaged Driver, now provides an array that lists the number of rows affected for each input value from the bound array, rather than just the total number of rows affected. This information provides more detailed feedback for the application developer. To retrieve the row count, ODP.NET can call the `OracleCommand.ArrayBindRowsAffected` property.

With more detailed feedback on the array bound DML execution, the developer can better evaluate the query's efficiency and whether the data changes were correctly applied.

See Also:

- ["ArrayBindRowsAffected"](#) on page 6-24

- Support for `APPLY` Keyword

Language Integrated Query (LINQ) is a `.NET` querying language. At runtime, LINQ is translated into native database SQL before it can query the database. In

some circumstances, LINQ uses the non-standard APPLY keyword in its SQL translation for retrieving lateral views. Oracle Database and ODP.NET support the APPLY keyword in Oracle Database 12c Release 1 (12.1) to more fully support LINQ.

This feature allows the occasional LINQ query that uses SQL APPLY to work seamlessly with ODP.NET and Oracle Database for lateral views.

See Also:

- [Chapter 4, "ADO.NET Entity Framework and LINQ to Entities"](#)

- Transaction Guard Support

Transaction Guard in Oracle Database 12c Release 1 (12.1) preserves transaction commit outcomes for ODP.NET, Unmanaged Driver, 12c applications during planned and unplanned outages, preventing applications from repeatedly submitting the same transaction. Applications use a new logical transaction identifier to determine the last open transaction's outcome in a database session following an outage. With the known outcome, the application can confidently determine whether to resubmit the transaction or not. Without Transaction Guard, applications that retry operations following outages by committing duplicate transactions can cause logical corruptions.

Transaction Guard preserves the commit outcome for every transaction and makes it available to ODP.NET applications. It allows ODP.NET developers to maintain at-most-once transaction execution.

See Also:

- ["Using Transaction Guard to Prevent Logical Corruption"](#) on page 3-29
- ["OracleLogicalTransactionStatus Class"](#) on page 6-310
- ["GetLogicalTransactionStatus"](#) on page 6-117
- ["LogicalTransactionId"](#) on page 6-103

- Recoverable Error Detection and Recovery

After an Oracle Database 12c Release 1 (12.1) failure, ODP.NET, Unmanaged Driver, 12c can determine if a failed transaction is recoverable or not. ODP.NET returns the `OracleException.IsRecoverable` property indicating whether the transaction is recoverable. If true, the application can retry the transaction.

This feature makes determining whether failed transactions are recoverable easier, allowing applications to proceed quickly to the next step in the recovery process.

See Also:

- ["Using Transaction Guard to Prevent Logical Corruption"](#) on page 3-29

- Support for Faster and Planned Database Outage

In Oracle Database 12c Release 1 (12.1), a database being brought offline automatically alerts ODP.NET applications of the impending downtime. ODP.NET will then stop allocating new connections and close connections returned to the pool from that particular instance.

This feature enables databases to be brought offline more quickly and minimizes potential end user disruptions by disallowing new ODP.NET connections to databases being brought offline.

See Also:

- ["Using FCF Planned Outage to Minimize Service Disruption"](#) on page 3-28

- Support for Oracle Notification Service

Oracle Notification Service (ONS) is a publish and subscribe service for communicating Fast Application Notification (FAN) events. ODP.NET receives fast connection failover and load balancing messages from the database server through ONS. Previously, ODP.NET used Oracle Advanced Queuing (AQ) as its FAN publish and subscribe service.

Because ONS is a memory-based service, it delivers messages faster than AQ. Using ONS, Oracle consolidates the publish and subscribe service that all Oracle data access drivers use.

See Also:

- ["Fast Application Notification"](#) on page 3-25

- Support for Global Data Services

Global Data Services (GDS) is a capability of Oracle Database 12c that extends the concept of services, which previously only was available in Oracle RAC, to a globally distributed configuration that can include a combination of Oracle RAC, Oracle Data Guard, and Oracle GoldenGate. This allows services to be deployed anywhere within this globally distributed configuration, supporting load balancing, high availability, database affinity, and so on with ODP.NET.

ODP.NET applications can now more efficiently use database resources on a global basis to improve performance and availability. Applications that utilize the Oracle RAC concept of services can now extend the same benefits of automatic workload management to their Oracle Data Guard and Oracle GoldenGate configurations. Similarly, Oracle Data Guard and Oracle GoldenGate customers can now fully utilize the benefits of services and automatic workload management for their replicated configurations.

See Also:

- ["Runtime Connection Load Balancing"](#) on page 3-26
- ["Fast Connection Failover \(FCF\)"](#) on page 3-27

- Transaction and Connection Association

Connections associate with `System.Transactions` transactions when they enlist either implicitly through `enlist=true` connection string attribute, or explicitly through `OracleConnection.EnlistTransaction()` method. A connection in ODP.NET now, by default, detaches from a transaction only when the connection object is closed or when the transaction object is disposed.

In earlier ODP.NET releases, the connection would get detached from a transaction under the conditions mentioned earlier and when the transaction was complete (committed, aborted, or timed out). When the transaction timeout elapses before the transaction completes, the connection unbinds itself from the transaction and

all subsequent operations on this connection execute in `AutoCommit` mode. Any operations prior to the timeout roll back, but operations performed after the timeout commit. The new transaction unbinding default behavior also alerts users with an exception if transactions time out and subsequent operations execute on this connection before the transaction is disposed. This new behavior provides a consistent transactional experience for the end user, even when a timeout occurs.

See also "[LegacyTransactionBindingBehavior](#)" on page 2-12 for more information.

- **Greater Granular Connection Pool Monitoring**

Performance counters can now monitor at the application domain, pool, or database instance level.

It is now easier to distinguish which application domains, pools, and instances are healthy and which ones are having problems.

See Also: "[Connection Pool Performance Counters](#)" on page 3-13

Changes in Oracle Data Provider for .NET Release 11.2.0.3.20

The following are changes in Oracle Data Provider for .NET for Release 11.2.0.3.20.

New Features

The following feature is new in this release:

- **.NET Framework 4.5 and Entity Framework 5 Support**

Oracle Data Provider for .NET supports .NET Framework 4.5 and Entity Framework 5.

See also "[System Requirements](#)" on page 2-1 for more information.

Changes in Oracle Data Provider for .NET Release 11.2.0.3

The following are changes in Oracle Data Provider for .NET for Release 11.2.0.3.

New Features

The following features are new in this release:

- **ADO.NET Entity Framework and LINQ to Entities Support**

ODP.NET now includes support for the ADO.NET Entity Framework and LINQ to Entities. Entity Framework is a framework for providing object-relational mapping service on data models. Entity Framework addresses the impedance mismatch between the relational database format and the client's preferred object format. Language Integrated Query (LINQ) defines a set of operators that can be used to query, project, and filter data in arrays, enumerable classes, XML, relational databases, and other data sources. One form of LINQ, LINQ to Entities, allows querying of Entity Framework data sources. ODP.NET supports Entity Framework such that the Oracle database can participate in object-relational modeling and LINQ to Entities queries.

Entity Framework and LINQ provides productivity benefits for the .NET developer. It abstracts the database's data model from the application's data model. Working with object-relational data becomes easier with Entity Framework's tools. Oracle's integration with Entity Framework and LINQ enables Oracle .NET developers to take advantage of all these productivity benefits.

See [Chapter 4, "ADO.NET Entity Framework and LINQ to Entities"](#) for more information on ODP.NET support for the ADO.NET Entity Framework and LINQ to Entities.

- WCF Data Services and OData

Windows Communication Foundation (WCF) Data Services enable developers to create services that use the Open Data Protocol (OData) to expose and consume data over the internet by using the semantics of representational state transfer (REST). OData exposes data as resources that are addressable by URIs. OData uses Entity Data Model conventions to expose resources as sets of entities that are related by associations. ODP.NET supports Entity Framework, and can expose its data through OData and WCF Data Services.

WCF Data Services and OData facilitate creating flexible data services from any data source and naturally integrating them with the Web. All data sources, including Oracle databases, can be used by the same data sharing standard making data exchange more interoperable.

- Implicit REF CURSOR Parameter Binding

ODP.NET can bind REF CURSOR parameters for stored procedures without binding them explicitly. To do so, the application must provide the REF CURSOR metadata as part of the .NET configuration file. This feature allows Entity Framework Function Import to call Oracle stored procedures and return REF CURSOR result sets. ODP.NET can also update the database's data with a DataSet or DataTable obtained through a REF CURSOR.

In Entity Framework, result set parameters are generally not declared. By supporting the implicit REF CURSOR parameter, ODP.NET more closely integrates with typical Entity Framework usage scenarios.

See ["Implicit REF CURSOR Binding"](#) on page 3-67 for detailed information on implicit REF CURSOR parameter binding.

Changes in Oracle Data Provider for .NET Release 11.2.0.2

The following are changes in Oracle Data Provider for .NET for Release 11.2.0.2.

New Features

The following features are new in this release:

- 64-bit ODP.NET XCopy for Windows x64

Now available for Windows x64 systems, ODP.NET XCopy provides system administrators with a smaller client install size than the standard ODP.NET client, and is easier to configure. ODP.NET XCopy simplifies embedding ODP.NET in customized deployment packages.

See Also: XCopy under ["Installing Oracle Data Provider for .NET, Unmanaged Driver"](#) on page 2-5

- TimesTen In-Memory Database Support

Oracle Data Provider for .NET enables fast data access for any .NET application, such as C# .NET, Visual Basic .NET, and ASP.NET, to TimesTen In-memory databases. ODP.NET support for TimesTen includes the classes, enumerations, interfaces, delegates and structures of the `Oracle.DataAccess.Client` and `Oracle.DataAccess.Types` namespaces. ODP.NET supports TimesTen Release 11.2.1.6.1 or later on Microsoft Windows 32-bit and 64-bit platforms. TimesTen can

be used with .NET Framework 2.0, 3.0, 3.5, and 4 with Microsoft Visual Studio 2005 or later.

See Also: The latest TimesTen In-Memory Database documentation and resources can be accessed from:

<http://www.oracle.com/technetwork/database/timesten/index.html>

Changes in Oracle Data Provider for .NET Release 11.2.0.1.2

The following are changes in Oracle Data Provider for .NET for Release 11.2.0.1.2.

New Features

The following features are new in this release:

- Support for Microsoft .NET Framework 4
ODP.NET for .NET Framework 4 supports .NET Framework 4 and the .NET Framework 4 Client Profile.

Changes in Oracle Data Provider for .NET Release 11.2

The following are changes in Oracle Data Provider for .NET for Release 11.2.

New Features

The following features are new in this release:

- End-to-End Tracing: `ClientInfo` Property
ODP.NET now supports the `ClientInfo` write-only property, in addition to the `ActionName`, `ClientId`, and `ModuleName` properties, on the `OracleConnection` object. This property specifies the client information for the connection.
The `ClientInfo` property is an end-to-end tracing attribute that can be set on the client or middle tier. This attribute is propagated to the database server whenever the next server round-trip happens. This reduces the added overhead associated with an independent database round trip. Using the `ClientInfo` property is helpful in tracking database user activities and debugging applications.

See Also:

- "[Client Identifier and End-to-End Tracing](#)" on page 3-21
- "[ClientInfo](#)" on page 6-94
- Edition-Based Redefinition
Edition-based redefinition enables you to upgrade the database component of an application even while the .NET application is being used. This minimizes or eliminates downtime for the application.

See Also: "[Edition-Based Redefinition](#)" on page 3-16

Changes in Oracle Data Provider for .NET Release 11.1.0.7.20

The following are changes in Oracle Data Provider for .NET for Release 11.1.0.7.20.

New Features

The following features are new in this release:

- Self-Tuning for Applications

Based on run-time sampling, ODP.NET dynamically adjusts statement cache size to provide better application performance. Self-tuning also takes into account memory usage on the client machine in order to prevent excessive memory usage. Self-tuning improves ODP.NET performance, reduces network usage, and decreases server CPU and client CPU activity.

See Also: ["Self-Tuning"](#) on page 3-50

- Faster Data Retrieval and Less Memory Usage

Retrieving data using `OracleDataReader` or populating a `DataSet` from an `OracleDataAdapter` is now faster.

ODP.NET reuses the same fetch array buffer for statements executed non-concurrently, saving on memory usage. The fetch array buffer stores data retrieved from the database.

No code changes are necessary to use these features. These features provide better performance and scalability for ODP.NET applications.

- Oracle Streams Advanced Queuing Support

ODP.NET supports access to Oracle Streams Advanced Queuing (AQ). AQ provides database-integrated message queuing functionality to store messages persistently, propagate messages between queues on different machines and databases, and transmit messages using Oracle NET services, HTTP, HTTPS and SMTP.

ODP.NET can access all the operational features of AQ, such as enqueue, dequeue, listen and notification. Oracle Developer Tools for Visual Studio can administer and manage AQ resources.

See Also: ["Oracle Database Advanced Queuing Support"](#) on page 3-107

- Promotable Local Transaction Support

Distributed transactions require the orchestration of application, transaction coordinator, and multiple databases. Local transactions only require an application and a single resource manager, or database. Local transactions have less of an overhead when compared to distributed transactions.

It may be difficult to determine whether a transaction will be local or distributed at design time. Developers are forced to design applications for distributed transactions, even if local transactions are used most of the time. This situation leads to more resource usage than necessary at run time.

Promotable local transactions allow all transactions to remain local until more than one database is brought into the transaction. At this point, the transaction is promoted to a distributed transaction so that it can be managed by the transaction coordinator. This provides a better utilization of system resources. This feature is supported with Oracle Database 11g release 1 (11.1.0.7) and higher.

See Also: ["System.Transactions and Promotable Transactions"](#) on page 3-32

- ODP.NET Security Enhancements

ODP.NET makes use of the `OraclePermission` class to enforce imperative security. This helps ensure that a user or application has a security level adequate for accessing data.

See Also:

- ["Code Access Security"](#) on page 3-2
- ["OraclePermission Class"](#) on page 6-375
- ["OraclePermissionAttribute Class"](#) on page 6-384

- Callbacks for HA Event Notifications

ODP.NET can register for Oracle High Availability (HA) events when `"ha events=true"` is specified in the connection string. ODP.NET is then able to receive notifications on which database, service, host, or instance has gone down or come up. .NET developers can register a callback with ODP.NET to notify the application when one of these events occurs and subsequently execute an event handler, as needed.

See Also:

- [Chapter 8, "Oracle Data Provider for .NET HA Event Classes"](#) on page 8-1
- ["HAEvent"](#) on page 6-131
- ["OracleConnection Properties"](#) on page 6-92

- Database Startup and Shutdown Operations

Users with database administrator privileges can use the `OracleDatabase` class to startup or shutdown a database instance.

See Also:

- ["OracleDatabase Class"](#) on page 6-185
- ["Shutdown"](#) on page 6-191
- ["Startup"](#) on page 6-194

Changes in Oracle Data Provider for .NET Release 11.1.0.6.20

The following are changes in Oracle Data Provider for .NET for Release 11.1.0.6.20.

New Features

The following features are new in this release:

- 32-bit ODP.NET XCopy

Oracle XCopy provides system administrators with an ODP.NET client that is smaller in disk size than the standard ODP.NET client and is easily configurable. Oracle XCopy makes embedding ODP.NET in customized deployment packages much simpler.

See Also: ["XCopy"](#) on page 2-5

- Support for Oracle User-Defined Types

ODP.NET has the ability to represent Oracle UDTs defined in the database as custom types in .NET applications.

See Also:

- ["Oracle User-Defined Types \(UDTs\) and .NET Custom Types"](#) on page 3-90
- [Chapter 16, "Oracle Data Provider for .NET UDT-Related Classes"](#) on page 16-1

- Bulk Copy Operations

ODP.NET supports the Bulk Copy operations to load a large amount of data efficiently.

See Also:

- ["Bulk Copy"](#) on page 3-105
- [Chapter 17, "Oracle Data Provider for .NET Bulk Copy Classes"](#) on page 17-1

- Additional Connection Pool Optimizations for Oracle Real Application Clusters (Oracle RAC) and Oracle Data Guard

ODP.NET now cleans up the connection pool when the database down event is received from Oracle RAC or Oracle Data Guard. This is in addition to the events that ODP.NET already cleaned up the connection pool for: node down, service member down, and service down events.

See Also: ["Real Application Clusters and Global Data Services"](#) on page 3-24

- Windows-Authenticated User Connection Pooling

Operating system-authenticated connections can now be managed as part of ODP.NET connection pools

See Also: ["Operating System Authentication"](#) on page 3-17

- Connection Pool Performance Counters

ODP.NET publishes performance counters for connection pooling, which can be viewed using the Windows Performance Monitor.

See Also: ["Connection Pool Performance Counters"](#) on page 3-13

- End-to-End Tracing Attribute Support

ODP.NET supports the `ActionName`, `ClientId`, `ClientInfo`, and `ModuleName` write-only properties on the `OracleConnection` object. These properties correspond to end-to-end tracing attributes that can be set on the client or middle-tier, and propagated to the database server whenever the next server round-trip happens. This reduces the added overhead associated with an independent database round trip. Using these attributes is helpful in tracking database user activities and debugging applications.

See Also: ["Client Identifier and End-to-End Tracing"](#) on page 3-21

Changes in Oracle Data Provider for .NET Release 11.1

The following are changes in Oracle Data Provider for .NET for Release 11.1.

New Features

The following features are new in this release:

- Performance Enhancements

The following performance enhancements have been made:

- Improved Parameter Context Caching

This release enhances the existing caching infrastructure to cache ODP.NET parameter contexts. This enhancement is independent of database version and it is available for all the supported database versions. This feature provides significant performance improvement for the applications that execute the same statement repeatedly.

This enhancement is transparent to the developer. No code changes are needed to use this feature.

- Efficient LOB Retrieval with LOBS or SecureFiles

When using LOBS or SecureFiles, this release improves the performance of small-sized LOB retrieval by reducing the number of round-trips to the database. SecureFiles is available with Oracle 11g release 1 or later database versions.

This enhancement is transparent to the developer. No code changes are needed to use this feature.

Introducing Oracle Data Provider for .NET

This chapter introduces Oracle Data Provider for .NET (ODP.NET), an implementation of a .NET data provider for Oracle Database.

This chapter contains these topics:

- [.NET Data Access in Oracle: Products and Documentation](#)
- [Overview of Oracle Data Provider for .NET \(ODP.NET\)](#)
- [Oracle Data Provider for .NET Assemblies](#)
- [Differences between the ODP.NET Managed Driver and Unmanaged Driver](#)
- [Using ODP.NET Client Provider in a Simple Application](#)

.NET Data Access in Oracle: Products and Documentation

This section discusses Oracle Data Provider for .NET and Oracle Database components that use Oracle Data Provider for .NET for data access. It briefly describes what each component does and where to find additional documentation.

These Oracle products provide .NET integration on the Windows operating system:

Oracle Data Provider for .NET (ODP.NET)

Oracle Data Provider for .NET provides fast data access from .NET clients to Oracle databases. ODP.NET enables .NET applications to take advantage of Oracle advanced features, such as Oracle Real Application Clusters (Oracle RAC) and XML DB. It is accessible through any .NET language, including C#, Visual Basic .NET, and C++ .NET.

ODP.NET consists of two drivers: ODP.NET, Managed Driver and ODP.NET, Unmanaged Driver. ODP.NET, Managed Driver is a fully managed ADO.NET provider, consisting of fewer DLLs and smaller install size than ODP.NET, Unmanaged Driver. The managed driver has the same exact application programming interfaces (APIs) as ODP.NET, Unmanaged Driver. However, the managed driver's APIs are a subset of the Unmanaged Driver's APIs.

Oracle Data Provider for .NET Developer's Guide for Microsoft Windows describes Oracle Data Provider for .NET features, their use, installation, requirements, and classes. The guide distinguishes which classes and APIs are supported for the managed driver, unmanaged driver, .NET stored procedures, and .NET clients.

Additionally, Oracle Data Provider for .NET Dynamic Help, which is context-sensitive online help, contains the same reference sections available in *Oracle Data Provider for .NET Developer's Guide for Microsoft Windows*, this guide.

Oracle Data Provider for .NET Dynamic Help is integrated with Visual Studio Dynamic Help. With Dynamic Help, you can access Oracle Data Provider for .NET documentation within Visual Studio by placing the cursor on an Oracle Data Provider for .NET keyword and pressing the F1 function key.

Oracle Developer Tools for Visual Studio

Oracle Developer Tools is an add-in to Visual Studio that provides graphical user interface (GUI) access to Oracle functionality. It provides improved developer productivity and ease of use. Oracle Developer Tools provide the ability to build .NET stored procedures using Visual Basic .NET, C#, and other .NET languages.

Oracle Developer Tools for Visual Studio Help describes Oracle Developer Tools. This help is in the form of dynamic help, which installs as part of the product.

Additionally, the Oracle Developer Tools for Visual Studio Help includes the following documentation:

- *Oracle Database PL/SQL Language Reference*
- *Oracle Database SQL Language Reference*
- *Oracle Database Extensions for .NET Developer's Guide for Microsoft Windows*
- *Oracle Database Error Messages*
- Access to Oracle Data Provider for .NET Dynamic Help
- Access to Oracle Providers for ASP.NET Dynamic Help

Oracle Database Extensions for .NET

Oracle Database Extensions for .NET provides the following:

- Hosting of Microsoft Common Language Runtime (CLR) in an external process on the server side, to execute .NET stored procedures.
- ODP.NET data access on the server side, from within the .NET stored procedure.

Oracle Database Extensions for .NET features, their use, installation, and requirements are described in *Oracle Database Extensions for .NET Developer's Guide for Microsoft Windows*.

Oracle Data Provider for .NET Developer's Guide for Microsoft Windows describes all ODP.NET classes. Classes that are not supported by Oracle Database Extensions for .NET are described as *Not Supported in a .NET Stored Procedure*.

See Also:

- Oracle Developer Tools for Visual Studio Help
- *Oracle Database Extensions for .NET Developer's Guide for Microsoft Windows* for more information about .NET stored procedures and functions
- ["Oracle Data Provider for .NET Assemblies"](#) on page 1-4 for class listings
- [Chapter 5, "Oracle Data Provider for .NET Stored Procedures"](#)

Oracle Providers for ASP.NET

Oracle Providers for ASP.NET offer ASP.NET developers an easy to use method to store state common to web applications within an Oracle database. These providers

are modeled on existing Microsoft ASP.NET providers, sharing similar schema and programming interfaces to provide .NET developers a familiar interface. Oracle supports the following providers:

- Cache Dependency Provider
- Membership Provider
- Profile Provider
- Role Provider
- Session State Provider
- Site Map Provider
- Web Events Provider
- Web Parts Personalization Provider

Oracle Providers for ASP.NET classes, their use, installation, and requirements are described in *Oracle Providers for ASP.NET Developer's Guide for Microsoft Windows*, which is also provided as dynamic help.

Oracle Services for Microsoft Transaction Server

Oracle Services for Microsoft Transaction Server (OraMTS) permit Oracle databases to be used as resource managers in Microsoft application coordinated transactions. OraMTS acts as a proxy for the Oracle database to the Microsoft Distributed Transaction Coordinator (MSDTC). As a result, OraMTS provides client-side connection pooling and allows client components that leverage Oracle to participate in promotable and distributed transactions. In addition, OraMTS can operate with Oracle databases running on any operating system, given that the services themselves are run on Windows.

Oracle Services for Microsoft Transaction Server Developer's Guide for Microsoft Windows describes OraMTS, which allows Oracle databases to be used as resource managers in distributed transactions.

Oracle TimesTen In-Memory Database

ODP.NET support for Oracle TimesTen In-Memory Database (TimesTen) provides fast and efficient ADO.NET data access for applications that require the highest performance.

You can use ODP.NET with any of the following TimesTen installations:

- TimesTen Data Manager only (for direct connections)
- TimesTen Client only (for client/server connections, assuming a TimesTen Data Manager instance and TimesTen Server instance are accessible elsewhere)
- TimesTen Data Manager with TimesTen Server

For more information on ODP.NET features specific to a TimesTen environment, refer to the *Oracle Data Provider for .NET Oracle TimesTen In-Memory Database Support User's Guide*.

Note: TimesTen does not support ODP.NET, Managed Driver.

Overview of Oracle Data Provider for .NET (ODP.NET)

Oracle Data Provider for .NET (ODP.NET) is an implementation of a .NET data provider for Oracle Database, using and inheriting from classes and interfaces available in the [Microsoft .NET Framework Class Library](#).

Following the .NET Framework, ODP.NET uses the ADO.NET model, which allows native providers to expose provider-specific features and data types. This is similar to Oracle Provider for OLE DB, where ADO (ActiveX Data Objects) provides an automation layer that exposes an easy programming model. ADO.NET provides a similar programming model, but without the automation layer, for better performance.

Oracle Data Provider for .NET uses Oracle native APIs to offer fast and reliable access to Oracle data and features from any .NET application. ODP.NET consists of two drivers: ODP.NET, Managed Driver and ODP.NET, Unmanaged Driver. ODP.NET, Managed Driver is a fully managed ADO.NET provider, consisting of fewer DLLs and smaller install size than ODP.NET, Unmanaged Driver. The managed driver has the same exact application programming interfaces (APIs) as ODP.NET, Unmanaged Driver. However, the managed driver's APIs are a subset of the Unmanaged Driver's APIs.

The ODP.NET classes described in this guide are contained in the `Oracle.DataAccess.dll` and `Oracle.ManagedDataAccess.dll` assembly.

- **Client Applications:** All ODP.NET classes are available for use in client applications.

As ODP.NET, Managed Driver does not support all classes and members in the ODP.NET, Unmanaged Driver, the unsupported managed driver classes and members will be labeled *Not Supported in ODP.NET, Managed Driver*.

- **.NET Stored Procedures:** Most ODP.NET classes can be used from within .NET stored procedures and functions. Those classes which cannot, are labeled *Not Supported in a .NET Stored Procedure*. Additionally, some classes contain members which may not be supported, and this is so indicated in the member tables that follow the class descriptions, and listed in Chapter 4 of this guide.

See Also:

- [Table 5–1, "API Support Comparison Between Client Application and .NET Stored Procedure"](#)
- ["Oracle Data Provider for .NET Assemblies"](#) on page 1-4 for class lists
- [Chapter 5, "Oracle Data Provider for .NET Stored Procedures"](#)
- *Oracle Database Extensions for .NET Developer's Guide for Microsoft Windows* for more information about .NET stored procedures and functions

Oracle Data Provider for .NET Assemblies

This section contains the following topics:

- [Oracle Data Provider for .NET, Unmanaged Driver Assemblies](#)
- [Oracle Data Provider for .NET, Managed Driver Assemblies](#)
- [Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces](#)
- [Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces](#)

Oracle Data Provider for .NET, Unmanaged Driver Assemblies

The `Oracle.DataAccess.dll` [assembly](#) provides two namespaces:

- The `Oracle.DataAccess.Client` namespace contains ODP.NET classes and enumerations for the client-side provider.
- The `Oracle.DataAccess.Types` namespace contains the Oracle Data Provider for .NET data types (ODP.NET Types).

To use Code First or Entity Framework 6 or higher with ODP.NET, Unmanaged Driver, add `Oracle.DataAccess.EntityFramework.dll` as a project assembly reference. It contains the namespace `Oracle.DataAccess.EntityFramework`.

Oracle Data Provider for .NET, Managed Driver Assemblies

The `Oracle.ManagedDataAccess.dll` [assembly](#) provides two namespaces:

- The `Oracle.ManagedDataAccess.Client` namespace contains ODP.NET classes and enumerations for the client-side provider.
- The `Oracle.ManagedDataAccess.Types` namespace contains the Oracle Data Provider for .NET data types (ODP.NET Types).

ODP.NET, Managed Driver contains additional assemblies. These assemblies are optional to install if not using the specific functionality.

Applications do not need to explicitly add these assemblies to their project. ODP.NET, Managed Driver will access these assemblies by default if installed.

The one exception is `Oracle.ManagedDataAccess.EntityFramework.dll`. That DLL must be explicitly added to a project for its functionality to be used.

- `Oracle.ManagedDataAccessDTC.dll` - Only required when using distributed transactions. The assembly is fully managed, but has 32-bit and x64 versions depending on the .NET Framework's bitness in which it runs. The assembly makes calls to unmanaged assemblies.
- `Oracle.ManagedDataAccess.EntityFramework.dll` - Only required when using Code First or Entity Framework 6 or higher. It contains the `Oracle.ManagedDataAccess.EntityFramework` namespace.

Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces

The `Oracle.DataAccess.Client` and `Oracle.ManagedDataAccess.Client` namespaces contains implementations of core ADO.NET classes and enumerations for ODP.NET, as well as ODP.NET specific classes.

The following tables list ODP.NET classes, enumerations, and types that are supported by the `Oracle.DataAccess.Client` and `Oracle.ManagedDataAccess.Client` namespaces. The tables indicate which of them are not supported by ODP.NET, Managed Driver and/or by .NET stored procedures. All are supported by ODP.NET, Unmanaged Driver.

Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client

[Table 1–1](#) lists the `Oracle.DataAccess.Client` and `Oracle.ManagedDataAccess.Client` classes and delegates.

Table 1–1 Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client

| Class or Delegate | Supported in the ODP.NET, Managed Driver | Supported in .NET Stored Procedures | Description |
|---------------------------------------------------------------|-------------------------------------------------|--------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OnChangeEventHandler Delegate | - | No | The OnChangedEventHandler event delegate represents the signature of the method that handles the notification. |
| OracleAQAgent Class | No | - | The OracleAQAgent class represents agents that may be senders or recipients of a message. |
| OracleAQDequeueOptions Class | No | - | An OracleAQDequeueOptions object represents the options available when dequeuing a message from an OracleAQQueue object. |
| OracleAQEnqueueOptions Class | No | - | The OracleAQEnqueueOptions class represents the options available when enqueueing a message to an OracleAQQueue. |
| OracleAQMessage Class | No | - | An OracleAQMessage object represents a message to be enqueued and dequeued. |
| OracleAQMessageAvailableEventArgs Class | No | - | The OracleAQMessageAvailableEventArgs class provides event data for the OracleAQQueue.MessageAvailable event. |
| OracleAQMessageAvailableEventHandler Delegate | No | - | The OracleAQMessageAvailableEventHandler delegate represents the signature of the method that handles the OracleAQQueue.MessageAvailable event. |
| OracleAQQueue Class | No | - | An OracleAQQueue object represents a queue. |
| OracleBulkCopy Class | No | - | An OracleBulkCopy object efficiently bulk loads or copies data into an Oracle table from another data source. |
| OracleBulkCopyColumnMapping Class | No | - | The OracleBulkCopyColumnMapping class defines the mapping between a column in the data source and a column in the destination database table. |
| OracleBulkCopyColumnMappingCollection Class | No | - | The OracleBulkCopyColumnMappingCollection class represents a collection of OracleBulkCopyColumnMapping objects that are used to map columns in the data source to columns in a destination table. |
| OracleClientFactory Class | - | - | An OracleClientFactory object allows applications to instantiate ODP.NET classes in a generic way. |
| OracleCommand Class | - | - | An OracleCommand object represents a SQL command, a stored procedure or function, or a table name. |

Table 1–1 (Cont.) Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client

| Class or Delegate | Supported in the ODP.NET, Managed Driver | Supported in .NET Stored Procedures | Description |
|-----------------------------------------------------|-------------------------------------------------|--------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OracleCommandBuilder Class | - | - | An <code>OracleCommandBuilder</code> object provides automatic SQL generation for the <code>OracleDataAdapter</code> when the database is updated. |
| OracleConnection Class | - | - | An <code>OracleConnection</code> object represents a connection to Oracle Database. |
| OracleConnectionStringBuilder Class | - | - | An <code>OracleConnectionStringBuilder</code> object allows applications to create or modify connection strings. |
| OracleDataAdapter Class | - | - | An <code>OracleDataAdapter</code> object represents a data provider object that communicates with the <code>DataSet</code> . |
| OracleDatabase Class | No | - | An <code>OracleDatabase</code> object represents a Oracle Database instance. |
| OracleDataReader Class | - | - | An <code>OracleDataReader</code> object represents a forward-only, read-only, in-memory result set. |
| OracleDataSourceEnumerator Class | - | - | An <code>OracleDataSourceEnumerator</code> object allows applications to generically obtain a collection of data sources to connect to. |
| OracleDependency Class | - | No | An <code>OracleDependency</code> class represents dependency between an application and an Oracle database. |
| OracleError Class | - | - | The <code>OracleError</code> object represents an error reported by an Oracle database. |
| OracleErrorCollection Class | - | - | An <code>OracleErrorCollection</code> object represents a collection of <code>OracleErrors</code> . |
| OracleException Class | - | - | The <code>OracleException</code> object represents an exception that is thrown when Oracle Data Provider for .NET encounters an error. |
| OracleFailoverEventArgs Class | No | No | The <code>OracleFailoverEventArgs</code> class provides event data for the <code>OracleConnection.Failover</code> event. |
| OracleFailoverEventHandler Delegate | No | No | The <code>OracleFailoverEventHandler</code> represents the signature of the method that handles the <code>OracleConnection.Failover</code> event. |
| OracleGlobalization Class | - | - | The <code>OracleGlobalization</code> class is used to obtain and set the Oracle globalization settings of the session, thread, and local computer (read-only). |
| OracleHAEventArgs Class | - | - | The <code>OracleHAEventArgs</code> class provides event data for the <code>OracleConnection.HAEvent</code> event. |

Table 1–1 (Cont.) Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client

| Class or Delegate | Supported in the ODP.NET, Managed Driver | Supported in .NET Stored Procedures | Description |
|--------------------------------------------------------|-------------------------------------------------|--------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OracleHAEventHandler Delegate | - | - | The OracleHAEventHandler delegate represents the signature of the method that handles the OracleConnection.HAEvent event. |
| OracleInfoMessageEventArgs Class | - | - | The OracleInfoMessageEventArgs object provides event data for the OracleConnection.InfoMessage event. |
| OracleInfoMessageEventHandler Delegate | - | - | The OracleInfoMessageEventHandler delegate represents the signature of the method that handles the OracleConnection.InfoMessage event. |
| OracleLogicalTransactionStatus Class | - | - | The OracleLogicalTransactionStatus class provides information on the status of a logical transaction. <i>This class has been deprecated in ODP.NET 12.1.0.2. It will be desupported in a future release.</i> |
| OracleNotificationEventArgs Class | - | - | The OracleNotificationEventArgs class provides event data for a notification. |
| OracleNotificationRequest Class | - | No | An OracleNotificationRequest class represents a notification request to be subscribed in the database. |
| OracleParameter Class | - | - | An OracleParameter object represents a parameter for an OracleCommand. |
| OracleParameterCollection Class | - | - | An OracleParameterCollection object represents a collection of OracleParameters. |
| OraclePermission Class | - | - | An OraclePermission object enables ODP.NET to enforce imperative security and helps ensure that a user has a security level adequate for accessing data. |
| OraclePermissionAttribute Class | - | - | An OraclePermissionAttribute object enables ODP.NET to enforce declarative security and helps ensure that a user has a security level adequate for accessing data. |
| OracleRowsCopiedEventHandler Delegate | No | - | The OracleRowsCopiedEventHandler delegate represents the method that handles the OracleRowsCopied event of an OracleBulkCopy object. |
| OracleRowsCopiedEventArgs Class | No | - | The OracleRowsCopiedEventArgs class represents the set of arguments passed as part of event data for the OracleRowsCopied event. |
| OracleRowUpdatedEventArgs Class | - | - | The OracleRowUpdatedEventArgs object provides event data for the OracleDataAdapter.RowUpdated event. |

Table 1–1 (Cont.) Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client

| Class or Delegate | Supported in the ODP.NET, Managed Driver | Supported in .NET Stored Procedures | Description |
|--------------------------------------------------------|------------------------------------------|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OracleRowUpdatedEventHandler Delegate | - | - | The OracleRowUpdatedEventHandler delegate represents the signature of the method that handles the OracleDataAdapter.RowUpdated event. |
| OracleRowUpdatingEventArgs Class | - | - | The OracleRowUpdatingEventArgs object provides event data for the OracleDataAdapter.RowUpdating event. |
| OracleRowUpdatingEventHandler Delegate | - | - | The OracleRowUpdatingEventHandler delegate represents the signature of the method that handles the OracleDataAdapter.RowUpdating event. |
| OracleTransaction Class | - | No | An OracleTransaction object represents a local transaction. |
| OracleXmlQueryProperties Class | No | - | An OracleXmlQueryProperties object represents the XML properties used by the OracleCommand class when the XmlCommandType property is Query . |
| OracleXmlSaveProperties Class | No | - | An OracleXmlSaveProperties object represents the XML properties used by the OracleCommand class when the XmlCommandType property is Insert , Update , or Delete . |

Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Enumerations

Table 1–2 lists the client enumerations.

Table 1–2 Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Enumerations

| Enumeration | Supported in the ODP.NET, Managed Driver | Supported in .NET Stored Procedures | Description |
|-------------------------------------------------|------------------------------------------|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| FailoverEvent Enumeration | No | No | FailoverEvent enumerated values are used to specify the state of the failover. |
| FailoverReturnCode Enumeration | No | No | FailoverReturnCode enumerated values are passed back by the application to the ODP.NET provider to request a retry in case of a failover error or to continue in case of a successful failover. |
| FailoverType Enumeration | No | No | FailoverType enumerated values are used to indicate the type of failover event that was raised. |
| OracleAQDequeueMode Enumeration | No | - | The OracleAQDequeueMode enumeration type specifies the dequeue mode. |

Table 1–2 (Cont.) Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Enumerations

| Enumeration | Supported in the ODP.NET, Managed Driver | Supported in .NET Stored Procedures | Description |
|--------------------------------------------------------------|-------------------------------------------------|--------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OracleAQMessageDeliveryMode Enumeration | No | - | The <code>OracleAQMessageDeliveryMode</code> enumeration type specifies the delivery mode of the message. |
| OracleAQMessageState Enumeration | No | - | The <code>OracleAQMessageState</code> enumeration type identifies the state of the message at the time of dequeue. |
| OracleAQMessageType Enumeration | No | - | The <code>OracleAQMessageType</code> enumeration type specifies the message payload type. |
| OracleAQNavigationMode Enumeration | No | - | The <code>OracleAQNavigationMode</code> enumeration type specifies the navigation mode. |
| OracleAQNotificationGroupingType Enumeration | No | - | The <code>OracleAQNotificationGroupingType</code> enumeration type specifies the notification grouping type. |
| OracleAQNotificationType Enumeration | No | - | The <code>OracleAQNotificationType</code> enumeration type specifies the notification type of the received notification. |
| OracleAQVisibilityMode Enumeration | No | - | The <code>OracleAQVisibilityMode</code> enumeration type specifies whether the enqueue or dequeue operation is part of the current transaction. |
| OracleBulkCopyOptions Enumeration | No | - | The <code>OracleBulkCopyOptions</code> enumeration specifies the values that can be combined with an instance of the <code>OracleBulkCopy</code> class and used as options to determine its behavior and the behavior of the <code>WriteToServer</code> methods for that instance. |
| OracleCollectionType Enumeration | - | No | <code>OracleCollectionType</code> enumerated values specify whether or not the <code>OracleParameter</code> object represents a collection, and if so, specifies the collection type. |
| OracleConnectionType Enumeration | No | - | <code>OracleConnectionType</code> enumerated values specify whether a particular connection object is associated with an Oracle database connection, a TimesTen database connection, or no physical connection at all. |

Table 1–2 (Cont.) Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Enumerations

| Enumeration | Supported in the ODP.NET, Managed Driver | Supported in .NET Stored Procedures | Description |
|------------------------------------------------------|------------------------------------------|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OracleDBShutdownMode Enumeration | No | - | <code>OracleDBShutdownMode</code> enumerated values specify the database shutdown options. |
| OracleDBStartupMode Enumeration | No | - | <code>OracleDBStartupMode</code> enumerated values specify the database startup options. |
| OracleDbType Enumeration | - | - | <code>OracleDbType</code> enumerated values are used to explicitly specify the <code>OracleDbType</code> of a <code>OracleParameter</code> . |
| OracleHAEventSource Enumeration | - | - | The <code>OracleHAEventSource</code> enumeration indicates the source of the HA event. |
| OracleHAEventStatus Enumeration | - | - | The <code>OracleHAEventStatus</code> enumeration indicates the status of the HA event source. |
| OracleIdentityType Enumeration | - | - | The <code>OracleIdentityType</code> enumeration specifies how Oracle identity column values are generated. |
| OracleNotificationInfo Enumeration | - | No | <code>OracleNotificationInfo</code> enumerated values specify the database event that causes the notification. |
| OracleNotificationSource Enumeration | - | No | <code>OracleNotificationSource</code> enumerated values specify the different sources that cause notification. |
| OracleNotificationType Enumeration | - | No | <code>OracleNotificationType</code> enumerated values specify the different types that cause the notification. |
| OracleParameterStatus Enumeration | - | - | The <code>OracleParameterStatus</code> enumeration type indicates whether a NULL value is fetched from a column, or truncation has occurred during the fetch, or a NULL value is to be inserted into a database column. |
| OracleRowidInfo Enumeration | - | - | The <code>OracleRowidInfo</code> enumeration values specify whether ROWID information is included as part of the <code>ChangeNotificationEventArgs</code> or not. |
| OracleXmlCommandType Enumeration | No | - | The <code>OracleXmlCommandType</code> enumeration specifies the values that are allowed for the <code>OracleXmlCommandType</code> property of the <code>OracleCommand</code> class. |

Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces

The `Oracle.DataAccess.Types` and `Oracle.ManagedDataAccess.Types` namespaces provides classes, structures, and exceptions for Oracle native types that can be used with Oracle Data Provider for .NET.

Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Structures

Table 1–3 lists the type structures.

Table 1–3 Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Structures

| Structure | Description |
|----------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| OracleBinary Structure | The <code>OracleBinary</code> structure represents a variable-length stream of binary data. |
| OracleBoolean Structure | The <code>OracleBoolean</code> structure represents a logical value that is either <code>TRUE</code> or <code>FALSE</code> . |
| OracleDate Structure | The <code>OracleDate</code> structure represents the Oracle <code>DATE</code> data type. |
| OracleDecimal Structure | The <code>OracleDecimal</code> structure represents an Oracle <code>NUMBER</code> in the database or any Oracle numeric value. |
| OracleIntervalDS Structure | The <code>OracleIntervalDS</code> structure represents the Oracle <code>INTERVAL DAY TO SECOND</code> data type. |
| OracleIntervalYM Structure | The <code>OracleIntervalYM</code> structure represents the Oracle <code>INTERVAL YEAR TO MONTH</code> data type. |
| OracleString Structure | The <code>OracleString</code> structure represents a variable-length stream of characters. |
| OracleTimeStamp Structure | The <code>OracleTimeStamp</code> structure represents the Oracle <code>TimeStamp</code> data type. |
| OracleTimeStampLTZ Structure | The <code>OracleTimeStampLTZ</code> structure represents the Oracle <code>TIMESTAMP WITH LOCAL TIME ZONE</code> data type. |
| OracleTimeStampTZ Structure | The <code>OracleTimeStampTZ</code> structure represents the Oracle <code>TIMESTAMP WITH TIME ZONE</code> data type. |

Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Exceptions

Type Exceptions are thrown only by ODP.NET type structures. Table 1–4 lists the type exceptions.

Table 1–4 Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Exceptions

| Exception | Description |
|------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| OracleTypeException Class | The <code>OracleTypeException</code> object is the base exception class for handling exceptions that occur in the ODP.NET Types classes. |
| OracleNullValueException Class | The <code>OracleNullValueException</code> represents an exception that is thrown when trying to access an ODP.NET Types structure that is null. |
| OracleTruncateException Class | The <code>OracleTruncateException</code> class represents an exception that is thrown when truncation in an ODP.NET Types class occurs. |

Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Classes

Table 1–5 lists the type classes.

Table 1–5 Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Classes

| Class | Supported in the ODP.NET, Managed Driver | Description |
|--------------------------------------------------------|------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OracleArrayMappingAttribute Class | No | The OracleArrayMappingAttribute class is required to mark a custom class field or property with information that ODP.NET uses when a custom type represents an Oracle Collection type. |
| OracleBFile Class | - | An OracleBFile is an object that has a reference to BFILE data. It provides methods for performing operations on BFILE objects. |
| OracleBlob Class | - | An OracleBlob object is an object that has a reference to BLOB data. It provides methods for performing operations on BLOB objects. |
| OracleClob Class | - | An OracleClob is an object that has a reference to CLOB data. It provides methods for performing operations on CLOB objects. |
| OracleCustomTypeMappingAttribute Class | No | The OracleCustomTypeMappingAttribute class is used to mark a custom type factory class or struct with information that is used by ODP.NET when a custom type is used to represent an Oracle UDT. |
| OracleObjectMappingAttribute Class | No | The OracleObjectMappingAttribute class marks custom class fields or properties with information that ODP.NET uses when a custom type represents an Oracle Object type. |
| OracleRef Class | No | An OracleRef instance represents an Oracle REF, which references a persistent, standalone, referenceable object that resides in the database. The OracleRef object provides methods to insert, update, and delete the Oracle REF. |
| OracleRefCursor Class | - | An OracleRefCursor object represents an Oracle REF CURSOR. |
| OracleUdt Class | No | The OracleUdt class defines static methods that are used when converting between Custom Types and Oracle UDTs and vice-versa. |
| OracleXmlStream Class | No | An OracleXmlStream object represents a sequential read-only stream of XML data stored in an OracleXmlType object. |
| OracleXmlType Class | No | An OracleXmlType object represents an Oracle XmlType instance. |

Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Interfaces

Table 1–6 lists the type interfaces.

Table 1–6 Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Interfaces

| Interface | Supported in the ODP.NET, Managed Driver | Description |
|---------------------------------------------------|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| IOracleArrayTypeFactory Interface | No | The IOracleArrayTypeFactory interface is used by ODP.NET to create arrays that represent Oracle Collections. |

Table 1–6 (Cont.) Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Interfaces

| Interface | Supported in the ODP.NET, Managed Driver | Description |
|----------------------------------------------------|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| IOracleCustomType Interface | No | IOracleCustomType is an interface for converting between a Custom Type and an Oracle Object or Collection Type. |
| IOracleCustomTypeFactory Interface | No | The IOracleCustomTypeFactory interface is used by ODP.NET to create custom objects that represent Oracle Objects or Collections. |
| INullable Interface | - | The INullable interface is used to determine whether or not an ODP.NET type has a NULL value. |

Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Enumerations

Table 1–7 lists the type enumerations.

Table 1–7 Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Enumerations

| Enumeration | Supported in the ODP.NET, Managed Driver | Description |
|--------------------------------------------------|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OracleUdtFetchOption Enumeration | No | OracleUdtFetchOption enumeration values specify how to retrieve a copy of the referenceable object. |
| OracleUdtStatus Enumeration | No | OracleUdtStatus enumeration values specify the status of an object attribute or collection element. An object attribute or a collection element can be a valid value or a null value. |

Differences between the ODP.NET Managed Driver and Unmanaged Driver

ODP.NET, Managed Driver and ODP.NET, Unmanaged Driver have a number of configuration setting differences. To learn more about ODP.NET, Managed Driver .NET configuration settings, refer to "[Oracle Data Provider for .NET, Managed Driver Configuration](#)" on page 2-18 and "[Configuration differences between ODP.NET, Managed Driver and ODP.NET, Unmanaged Driver](#)" on page 2-29.

For distributed transaction setup difference, see "[Using Oracle Services for MTS with Oracle Data Provider for .NET, Managed Driver](#)" on page 2-29.

Table 1–8 list the application programming interfaces not supported in ODP.NET, Managed Driver.

Table 1–8 Application Programming Interfaces not supported in ODP.NET, Managed Driver

| Namespace | Class/Enumeration/Interface | Unsupported Method/Property/Event |
|---------------------------------|---------------------------------|-----------------------------------|
| Oracle.ManagedDataAccess.Client | FailoverEvent enumeration | All |
| Oracle.ManagedDataAccess.Client | FailoverReturnCode enumeration | All |
| Oracle.ManagedDataAccess.Client | FailoverType enumeration | All |
| Oracle.ManagedDataAccess.Client | OracleAQAgent class | All |
| Oracle.ManagedDataAccess.Client | OracleAQDequeueMode enumeration | All |
| Oracle.ManagedDataAccess.Client | OracleAQDequeueOptions class | All |
| Oracle.ManagedDataAccess.Client | OracleAQEnqueueOptions class | All |
| Oracle.ManagedDataAccess.Client | OracleAQMessage class | All |

Table 1–8 (Cont.) Application Programming Interfaces not supported in ODP.NET, Managed Driver

| Namespace | Class/Enumeration/Interface | Unsupported Method/Property/Event |
|---------------------------------|----------------------------------------------|------------------------------------------|
| Oracle.ManagedDataAccess.Client | OracleAQMessageAvailableEventArgs class | All |
| Oracle.ManagedDataAccess.Client | OracleAQMessageAvailableEventHandler class | All |
| Oracle.ManagedDataAccess.Client | OracleAQMessageDeliveryMode enumeration | All |
| Oracle.ManagedDataAccess.Client | OracleAQMessageState enumeration | All |
| Oracle.ManagedDataAccess.Client | OracleAQMessageType enumeration | All |
| Oracle.ManagedDataAccess.Client | OracleAQNavigationMode enumeration | All |
| Oracle.ManagedDataAccess.Client | OracleAQNotificationGroupingType enumeration | All |
| Oracle.ManagedDataAccess.Client | OracleAQNotificationType enumeration | All |
| Oracle.ManagedDataAccess.Client | OracleAQQueue class | All |
| Oracle.ManagedDataAccess.Client | OracleAQVisibilityMode enumeration | All |
| Oracle.ManagedDataAccess.Client | OracleBulkCopy class | All |
| Oracle.ManagedDataAccess.Client | OracleBulkCopyColumnMapping class | All |
| Oracle.ManagedDataAccess.Client | OracleBulkCopyColumnMappingCollection class | All |
| Oracle.ManagedDataAccess.Client | OracleBulkCopyOptions class | All |
| Oracle.ManagedDataAccess.Client | OracleCommand class | ArrayBindRowsAffected property |
| Oracle.ManagedDataAccess.Client | OracleCommand class | ImplicitRefCursors property |
| Oracle.ManagedDataAccess.Client | OracleCommand class | XmlCommandType property |
| Oracle.ManagedDataAccess.Client | OracleCommand class | XmlQueryProperties property |
| Oracle.ManagedDataAccess.Client | OracleCommand class | XmlSaveProperties property |
| Oracle.ManagedDataAccess.Client | OracleConnection class | FlushCache() method |
| Oracle.ManagedDataAccess.Client | OracleConnection class | Failover event |
| Oracle.ManagedDataAccess.Client | OracleConnection class | ConnectionType property |
| Oracle.ManagedDataAccess.Client | OracleConnection class | GetLogicalTransactionStatus() method |
| Oracle.ManagedDataAccess.Client | OracleConnection class | LogicalTransactionId property |
| Oracle.ManagedDataAccess.Client | OracleConnectionType enumeration | All |
| Oracle.ManagedDataAccess.Client | OracleDBShutdownMode enumeration | All |
| Oracle.ManagedDataAccess.Client | OracleDBStartupMode enumeration | All |
| Oracle.ManagedDataAccess.Client | OracleDBType enumeration | XmlType |
| Oracle.ManagedDataAccess.Client | OracleDataReader class | GetOracleRef() method |

Table 1–8 (Cont.) Application Programming Interfaces not supported in ODP.NET, Managed Driver

| Namespace | Class/Enumeration/Interface | Unsupported Method/Property/Event |
|---------------------------------|--------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Oracle.ManagedDataAccess.Client | OracleDataReader class | GetOracleBlobForUpdate() method If the method is called, then a <code>NotSupportedException</code> is thrown. |
| Oracle.ManagedDataAccess.Client | OracleDataReader class | GetOracleClobForUpdate() method If the method is called, then a <code>NotSupportedException</code> is thrown. |
| Oracle.ManagedDataAccess.Client | OracleDataReader class | GetXmlReader() method If the method is called, then a <code>NotSupportedException</code> is thrown. |
| Oracle.ManagedDataAccess.Client | OracleDataReader class | GetOracleXmlType() method |
| Oracle.ManagedDataAccess.Client | OracleDataReader class | IsAutoIncrement and IdentityType properties of the GetSchemaTable |
| Oracle.ManagedDataAccess.Client | OracleDataAdapter class | IdentityInsert property |
| Oracle.ManagedDataAccess.Client | OracleDataAdapter class | IdentityUpdate property |
| Oracle.ManagedDataAccess.Client | OracleDataAdapter class | SafeMapping property |
| Oracle.ManagedDataAccess.Client | OracleDatabase class | All |
| Oracle.ManagedDataAccess.Client | OracleDbType enumeration | Array |
| Oracle.ManagedDataAccess.Client | OracleDbType enumeration | Boolean |
| Oracle.ManagedDataAccess.Client | OracleDbType enumeration | Object |
| Oracle.ManagedDataAccess.Client | OracleDbType enumeration | Ref |
| Oracle.ManagedDataAccess.Client | OracleException class | IsRecoverable property |
| Oracle.ManagedDataAccess.Client | OracleFailoverEventArgs class | All |
| Oracle.ManagedDataAccess.Client | OracleFailoverEventHandler class | All |
| Oracle.ManagedDataAccess.Client | OracleGlobalization class | ClientCharacterSet property |
| Oracle.ManagedDataAccess.Client | OracleGlobalization class | GetClientInfo() method |
| Oracle.ManagedDataAccess.Client | OracleGlobalization class | GetThreadInfo() method |
| Oracle.ManagedDataAccess.Client | OracleGlobalization class | SetThreadInfo() method |
| Oracle.ManagedDataAccess.Client | OracleIdentityType enumeration | All |
| Oracle.ManagedDataAccess.Client | OracleLogicalTransactionStatus class | All |
| Oracle.ManagedDataAccess.Client | OracleNotificationRequest class | GroupingInterval property |
| Oracle.ManagedDataAccess.Client | OracleNotificationRequest class | GroupingNotificationEnabled property |
| Oracle.ManagedDataAccess.Client | OracleNotificationRequest class | GroupingType property |
| Oracle.ManagedDataAccess.Client | OracleRowsCopiedEventArgs class | All |

Table 1–8 (Cont.) Application Programming Interfaces not supported in ODP.NET, Managed Driver

| Namespace | Class/Enumeration/Interface | Unsupported Method/Property/Event |
|---------------------------------|----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| Oracle.ManagedDataAccess.Client | OracleRowsCopiedEventHandler class | All |
| Oracle.ManagedDataAccess.Client | OracleXmlCommandType enumeration | All |
| Oracle.ManagedDataAccess.Client | OracleXmlQueryProperties class | All |
| Oracle.ManagedDataAccess.Client | OracleXmlSaveProperties class | All |
| Oracle.ManagedDataAccess.Types | IOracleArrayTypeFactory interface | All |
| Oracle.ManagedDataAccess.Types | IOracleCustomType interface | All |
| Oracle.ManagedDataAccess.Types | IOracleCustomTypeFactory interface | All |
| Oracle.ManagedDataAccess.Types | OracleArrayMappingAttribute class | All |
| Oracle.ManagedDataAccess.Types | OracleBoolean structure | All |
| Oracle.ManagedDataAccess.Types | OracleCustomTypeMappingAttribute class | All |
| Oracle.ManagedDataAccess.Types | OracleObjectMappingAttribute class | All |
| Oracle.ManagedDataAccess.Types | OracleRef class | All |
| Oracle.ManagedDataAccess.Types | OracleTimestampTZ structure | OracleTimeStampTZ (DateTime dt, string timeZone) constructor. This constructor is supported but the timeZone must be an hour offset. |
| Oracle.ManagedDataAccess.Types | OracleUdt class | All |
| Oracle.ManagedDataAccess.Types | OracleUdtFetchOption enumeration | All |
| Oracle.ManagedDataAccess.Types | OracleUdtStatus enumeration | All |
| Oracle.ManagedDataAccess.Types | OracleXmlStream class | All |
| Oracle.ManagedDataAccess.Types | OracleXmlType class | All |

Using ODP.NET Client Provider in a Simple Application

The following is a simple C# application that connects to Oracle Database and displays its version number before disconnecting using ODP.NET, Unmanaged Driver:

```
// C#

using System;
using Oracle.DataAccess.Client;

class Sample
{
    static void Main()
    {
        // Connect to Oracle
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Display Version Number
        Console.WriteLine("Connected to Oracle " + con.ServerVersion);

        // Close and Dispose OracleConnection
    }
}
```

```
        con.Close();
        con.Dispose();
    }
}
```

If you are using ODP.NET, Managed Driver, then replace the contents of Program.cs with the following C# code. The namespace of ODP.NET, Managed Driver (Oracle.ManagedDataAccess.*) is different from the namespace of ODP.NET, Unmanaged Driver (Oracle.DataAccess.*)

```
// C#
using System;
using Oracle.ManagedDataAccess.Client;
using Oracle.ManagedDataAccess.Types;

namespace Connect
{
    class Program
    {
        static void Main(string[] args)
        {
            try
            {
                // Please replace the connection string attribute settings
                string constr = "user id=scott;password=tiger;data source=oracle";

                OracleConnection con = new OracleConnection(constr);
                con.Open();
                Console.WriteLine("Connected to Oracle Database {0}", con.ServerVersion);
                con.Dispose();

                Console.WriteLine("Press RETURN to exit.");
                Console.ReadLine();
            }
            catch (Exception ex)
            {
                Console.WriteLine("Error : {0}", ex);
            }
        }
    }
}
```

Note: Additional samples are provided in the *ORACLE_HOME\ORACLE_HOME\ODACsamples* directory.

Installing and Configuring Oracle Data Provider for .NET

This section describes installation and configuration requirements for Oracle Data Provider for .NET.

This section contains these topics:

- [System Requirements](#)
- [Entity Framework Requirements](#)
- [Oracle Data Provider for .NET Versioning Scheme](#)
- [Installing Oracle Data Provider for .NET, Unmanaged Driver](#)
- [Installing Oracle Data Provider for .NET, Managed Driver](#)
- [Configuring Oracle Data Provider for .NET](#)
- [Migrating from ODP.NET, Unmanaged Driver to ODP.NET, Managed Driver](#)
- [Configuring a Port to Listen for Database Notifications](#)
- [General .NET Programming Recommendations and Tips for ODP.NET](#)

System Requirements

Oracle Data Provider for .NET, Unmanaged Driver requires the following:

- Windows operating system
 - 32-bit: Windows 7 (Professional, Enterprise, and Ultimate Editions), Windows Server 2008 (Standard, Enterprise, Datacenter, Web, and Foundation Editions), or Windows 8 (Pro and Enterprise Editions).

Oracle supports 32-bit ODP.NET on x86, AMD64, and Intel EM64T processors on these operating systems.

- 64-bit: Windows 7 x64 (Professional, Enterprise, and Ultimate Editions), Windows Server 2008 R2 x64 (Standard, Enterprise, Datacenter, Web, and Foundation Editions), Windows Server 2008 x64 (Standard, Enterprise, Datacenter, Web, and Foundation Editions), Windows 8 (Pro and Enterprise Editions), or Windows Server 2012 x64 (Standard, Datacenter, Essentials, and Foundation Editions).

Oracle supports 32-bit ODP.NET and 64-bit ODP.NET for Windows x64 on these operating systems.

Note: ODP.NET does not support Itanium systems.

- Microsoft .NET Framework
 - ODP.NET for .NET Framework 2.0 is only supported with Microsoft .NET Framework 3.5 SP 1 and later.
 - ODP.NET for .NET Framework 4 is only supported with Microsoft .NET Framework 4, 4.5, 4.5.1, 4.5.2. .NET Framework Client Profile is supported
- Access to Oracle Database 10g Release 2 or later
- Oracle Client release 12.1

This is automatically installed as part of the ODP.NET installation.

Oracle Data Provider for .NET, Managed Driver requires the following:

- Same Windows operating system support as ODP.NET, Unmanaged Driver.
ODP.NET, Managed Driver is built with AnyCPU. It runs on either 32-bit or 64-bit (x64) Windows and on either 32-bit or 64-bit (x64) .NET Framework.
- Microsoft .NET Framework 4, 4.5, 4.5.1, or 4.5.2
- Access to Oracle Database 10g Release 2 or later

Possible additional requirements for both ODP.NET, Managed and Unmanaged Drivers:

- Applications using promotable and distributed transactions require Oracle Services for Microsoft Transaction Server 12.1. ODP.NET only supports the read committed isolation level for distributed transactions.
 - ODP.NET, Unmanaged Driver requires Oracle Services for Microsoft Transaction Server to provide enlistment, commit, and recovery services
 - ODP.NET, Managed Driver requires Oracle Services for Microsoft Transaction Server to provide just recovery services. Enlistment and commit services are included as part of the managed driver.

See Also:

- Document 726240.1 on My Oracle Support (formerly Oracle*MetaLink*) for details on supported configuration for different ODP.NET versions. You can access My Oracle Support from:
 - <https://support.oracle.com>
 - <http://msdn.microsoft.com/netframework>

Entity Framework Requirements

This section contains the following topics:

- [Entity Framework Database First and Model First Requirements](#)

Entity Framework Database First and Model First Requirements

Oracle's support for Entity Framework Database First and Model First has the following version requirements:

- ODP.NET 11.2.0.3 or higher
- Microsoft Entity Framework 4 or higher, up to and including the 6.x versions.

If using Visual Studio tools, then use Visual Studio 2010 or higher and install Oracle Developer Tools for Visual Studio.

Note: Entity Framework 6 is not supported natively at this time. Some Visual Studio versions may default to Entity Framework 6. If so, set your .NET project to use an earlier version of Entity Framework when running on version 6.

Oracle Data Provider for .NET Versioning Scheme

Starting with 11.2.0.1.2, Oracle Data Provider for .NET, Unmanaged Driver ships with two sets of binaries: one set for .NET Framework 2.0 and another for .NET Framework 4. ODP.NET, Managed Driver ships with one set of binaries for .NET Framework 4.

For example, ODP.NET 11.2.0.1.2 binaries would be the following:

- ODP.NET for .NET Framework 4
 - Oracle.DataAccess.dll
 - * Built with .NET Framework 4
 - * Assembly version number: 4.x.x.x
 - OraOps11w.dll
 - * Used by ODP.NET for .NET Framework 2.0 and 4
- ODP.NET for .NET Framework 2.0
 - Oracle.DataAccess.dll
 - * Built with .NET Framework 2.0
 - * Assembly version number: 2.x.x.x
 - OraOps11w.dll
 - * Used by ODP.NET for .NET Framework 2.0 and 4

The convention for ODP.NET assembly/DLL versioning is

n1.o1o2.o3o4.o5

where:

- *n1* is the most significant .NET Framework version number.
- *o1o2* are the first two digits of the ODP.NET product version number.
- *o3o4* are the third and fourth digits of the ODP.NET product version number.
- *o5* is the fifth and last digit of the ODP.NET product version number.

For example, if the ODP.NET product version number is 11.2.0.2, the corresponding ODP.NET assembly versions are:

- .NET Framework 4 version: 4.112.2.0
- .NET Framework 2.0 version: 2.112.2.0

Note that the Oracle installer and documentation still refer to the ODP.NET product version number and not the assembly/DLL version number.

As with the .NET Framework system libraries, the first digit of the assembly version number indicates the version of the .NET Framework to use with an ODP.NET assembly.

Publisher Policy DLL is provided as before so that applications built with older versions of ODP.NET are redirected to the newer ODP.NET assembly, even though the versioning scheme has changed.

ODP.NET, Managed Driver follows a similar version model for its binaries.

ODP.NET for .NET Framework 4:

- Oracle.ManagedDataAccess.dll
 - Built with .NET Framework 4
 - Assembly version number: 4.x.x.x
- Oracle.ManagedDataAccessDTC.dll
 - Used by ODP.NET for .NET Framework 4 for distributed transactions only.

ODP.NET, Managed Driver Versioning

Starting with ODAC 12c Release 2, the ODP.NET, Managed Driver uses assembly manifest attribute `AssemblyInformationalVersionAttribute` to uniquely identify assemblies with the same `AssemblyVersionAttribute` attribute value. This value can be accessed via .NET code, PowerShell, and other Windows applications to identify ODP.NET, Managed Driver versions uniquely.

`AssemblyInformationalVersionAttribute` is set to the same version as the actual .NET assembly version, except the fourth digit, which will no longer be 0. Instead, the version will be unique for each ODP.NET, Managed Driver release by incrementing the fourth digit for every subsequent release.

This value is accessible using .NET Framework `System.Diagnostics.FileVersionInfo.ProductVersion` property. The returned value can be used as a `Version` object or as a comparison `String` using comparison operators or methods. Essentially, among a collection of ODP.NET, Managed Driver assemblies that have the same assembly version, the newest ODP.NET, Managed Driver assembly will have the largest fourth digit `ProductVersion` value than an older assembly.

PowerShell Example: In this example, administrators uniquely distinguish the assemblies between ODP.NET, Managed Driver versions from an old version of ODP.NET, Managed Driver in `c:\old` and a more recent one in `c:\new`.

Script:

```
$VC1 = New-Object System.Version((Get-Command
C:\old\Oracle.ManagedDataAccess.dll).FileVersionInfo.ProductVersion)
$VC2 = New-Object System.Version((Get-Command
C:\new\Oracle.ManagedDataAccess.dll).FileVersionInfo.ProductVersion)
"Compare V1 to V2: " + $VC1.CompareTo($VC2)
"Compare V1 to V1: " + $VC1.CompareTo($VC1)
"Compare V2 to V1: " + $VC2.CompareTo($VC1)
```

Output:

```
Compare V1 to V2: -1
Compare V1 to V1: 0
Compare V2 to V1: 1
```

Note: `ProductVersion` property comparisons will provide correct information on which version is more recent than the other *only* for ODP.NET, Managed Driver released from ODAC 12c Release 2 and later.

Installing Oracle Data Provider for .NET, Unmanaged Driver

Oracle Data Provider for .NET is part of Oracle Data Access Components (ODAC), which can be downloaded from OTN. Beginning with ODAC 11.1.0.6.20, Oracle Data Provider for .NET can be installed through XCopy or Oracle Universal Installer.

- XCopy

Administrators use XCopy to deploy Oracle Data Provider for .NET to large numbers of computers for production deployments. The XCopy has a smaller installation size and fine-grain control during installation and configuration than Oracle Universal Installer.

- Oracle Universal Installer (OUI)

Developers and administrators use Oracle Universal Installer for automated ODP.NET installations. It includes documentation and code samples that are not part of the XCopy.

Note: This section describes installation using the Oracle Universal Installer. For installation and configuration using the XCopy install, refer to the README.TXT file that is part of the XCopy installation.

Additionally, Oracle Data Provider for .NET Dynamic Help is registered with Visual Studio, providing context-sensitive online help that is seamlessly integrated with Visual Studio Dynamic Help. With Dynamic Help, the user can access ODP.NET documentation within the Visual Studio IDE by placing the cursor on an ODP.NET keyword and pressing the F1 function key.

Oracle Data Provider for .NET creates an entry in the `machine.config` file of the computer on which it is installed, for applications using the `OracleClientFactory` class. This enables the `DbProviderFactories` class to recognize ODP.NET.

ODP.NET, Unmanaged Driver Entity Framework 6 and Code First functionality are available through a NuGet package. OUI and Xcopy installations include this package as well, but require post-install configuration steps. The NuGet package for ODP.NET, Unmanaged Driver Entity Framework automates these post-install steps, except for the application-specific connection string settings.

File Locations After Installation

The `Oracle.DataAccess.dll` assembly is installed to the following locations:

.NET Framework 2.0:

`ORACLE_BASE\ORACLE_HOME\odp.net\bin\2.x` directory

.NET Framework 4:

`ORACLE_BASE\ORACLE_HOME\odp.net\bin\4` directory

Note: If the machine has the corresponding .NET Framework installed, then the `Oracle.DataAccess.dll` assembly is added to the Global Assembly Cache (GAC) as well. This is to ensure that existing applications can start using the newly installed ODP.NET version immediately. However, if this is not desired, be sure to remove the policy DLLs from the GAC.

Documentation and the `readme.txt` file can be accessed through `ORACLE_BASE\ORACLE_HOME\ODACDoc\DocumentationLibrary\doc\index.htm`.

Samples are provided in the `ORACLE_BASE\ORACLE_HOME\ODACsamples` directory.

Search Order for Unmanaged DLLs

ODP.NET consists of managed and unmanaged binaries. Through the use of the `DllPath` configuration parameter, each application can specify the `ORACLE_BASE\ORACLE_HOME\bin` location that the dependent unmanaged Oracle Client binaries are loaded from. However, the `ORACLE_BASE\ORACLE_HOME` must have the same ODP.NET version installed as the version that the application uses. Otherwise, a version mismatch exception is thrown.

The `Oracle.DataAccess.dll` searches for dependent unmanaged DLLs (such as Oracle Client) based on the following order:

1. Directory of the application or executable.
2. `DllPath` setting specified by application config or `web.config`.
3. `DllPath` setting specified by `machine.config`.
4. `DllPath` setting specified by the Windows Registry.

`HKEY_LOCAL_MACHINE\Software\Oracle\ODP.NET\version\DllPath`

5. Directories specified by the Windows `PATH` environment variable.

Upon installation of ODP.NET, Oracle Universal Installer sets the `DllPath` Windows Registry value to the `ORACLE_BASE\ORACLE_HOME\bin` directory where the corresponding dependent DLLs are installed. Developers must provide this configuration information on an application-by-application basis.

When a new ODP.NET version is installed, default values are set in the Windows Registry for the new version. Because the policy DLLs redirect all ODP.NET references to this new ODP.NET version, applications use the default values. Developers can provide a `config` or `web.config` file specific to the application to prevent this redirection. The configuration file settings always apply to the application, regardless of whether or not patches or new versions are installed later.

ODP.NET Configuration File Support is only available for version 10.2.0.4 and later.

Note: Both `Oracle.DataAccess.dll` for .NET Framework 2.0 and `Oracle.DataAccess.dll` for .NET Framework 4 use the same unmanaged DLL, `OraOps11w.dll`.

ODP.NET and Dependent Unmanaged DLL Mismatch

To enforce the usage of `Oracle.DataAccess.dll` assembly with the correct version of its unmanaged DLLs, an exception is raised if `Oracle.DataAccess.dll` notices it has loaded a mismatched version of a dependent unmanaged DLL.

Installing Oracle Data Provider for .NET, Managed Driver

Getting started with ODP.NET, Managed Driver

You can get started with ODP.NET Managed Driver by either using the Oracle Universal Installer (OUI), XCopy, or NuGet.

If you are using OUI: Follow the Oracle Universal Installer (OUI) steps to install ODP.NET, Managed Driver

If you are using XCopy: Download ODP.NET, Managed Driver .zip file to a directory for staging the install. The .zip file contains a README file with XCopy installation instructions.

Run the `configure.bat` script in one of the following directories:

- For 32-bit .NET Framework: `OH\odp.net\managed\x86`
- For 64-bit .NET Framework: `OH\odp.net\managed\x64`

Each directory contains an `unconfigure.bat` if ODP.NET, Managed Driver needs to be unconfigured and removed from the machine.

If you are using NuGet: Download the ODP.NET NuGet package(s) and use NuGet Package Manager to install.

The following NuGet packages are available:

- ODP.NET, Managed Driver
- Entity Framework assembly for Code First and Entity Framework 6 or higher use with ODP.NET, Managed Driver

ODP.NET, Managed Driver Files

ODP.NET, Managed Driver consists of the following files:

| File | Description |
|---------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| <code>Oracle.ManagedDataAccess.dll</code> | Platform-independent (AnyCPU), fully-managed ADO.NET provider |
| <code>\x64\Oracle.ManagedDataAccessDTC.dll</code> | Platform-dependent (64-bit .NET Framework only), Managed Assembly for Distributed Transaction support. |
| <code>\x86\Oracle.ManagedDataAccessDTC.dll</code> | Platform-dependent (32-bit .NET Framework only), Managed Assembly for Distributed Transaction support. |
| <code>\Resources\<<lang>\Oracle.ManagedDataAccess.resources.dll</code> | Platform-independent (AnyCPU), fully-managed ADO.NET provider resource DLLs. |
| <code>OraProvCfg.exe</code> | Platform-independent (AnyCPU) utility to configure/unconfigure ODP.NET, Managed and Unmanaged Drivers. |
| <code>configure.bat</code> | Batch file to place ODP.NET, Managed Driver into the GAC and add configuration entries into the <code>machine.config</code> . |
| <code>unconfigure.bat</code> | Batch file to remove ODP.NET, Managed Driver from the GAC and remove configuration entries from <code>machine.config</code> . |
| <code>tnsnames.ora</code> | A sample configuration file that defines data source aliases. |

| File | Description |
|----------------------------------------------|----------------------------------------------------------------------------------------------------|
| sqlnet.ora | A sample configuration file that configures network related settings. |
| ConfigSchema.xsd | An XML schema file that defines the configuration section for ODP.NET, Managed Driver. |
| Oracle.ManagedDataAccess.EntityFramework.dll | Platform-independent (AnyCPU), fully-managed assembly for Code First and Entity Framework 6 higher |
| \x64\Oracle.ManagedDataAccessIOP.dll | Platform-dependent (64-bit .NET Framework), Managed Assembly for Kerberos support |
| \x86\Oracle.ManagedDataAccessIOP.dll | Platform-dependent (32-bit .NET Framework), Managed Assembly for Kerberos support |

- Oracle.ManagedDataAccessDTC.dll is only needed if the application uses distributed transactions.
- If Distributed Transactions are used by the ODP.NET, Managed Driver application, the appropriate Oracle.ManagedDataAccessDTC.dll (32-bit or 64-bit .NET Framework) will be loaded. However, the required Oracle.ManagedDataAccessDTC.dll needs to be either in the GAC or in the same directory as the .exe for it to be loaded by Oracle.ManagedDataAccess.dll.
- Oracle.ManagedDataAccessDTC.dll must not be referenced by the application. ODP.NET, Managed Driver will reference it implicitly.
- On a 64-bit OS, only the x64 version of Oracle.ManagedDataAccessDTC.dll is placed into the GAC upon the completion of an OUI install or an invocation of the XCopy configure.bat.

See Also: *Oracle Database Installation Guide for Microsoft Windows* for installation instructions

File Locations After Installation

The Oracle.ManagedDataAccess.dll assembly is installed to the following locations:

.NET Framework 4:

ORACLE_BASE\ORACLE_HOME\odp.net\bin\4 directory

Note: If the machine has the corresponding .NET Framework installed, then the Oracle.ManagedDataAccess.dll assembly is added to the Global Assembly Cache (GAC) as well. This is to ensure that existing applications can start using the newly installed ODP.NET version immediately. However, if this is not desired, be sure to remove the policy DLLs from the GAC.

Documentation and the readme.txt file can be accessed through ORACLE_BASE\ORACLE_HOME\ODACDoc\DocumentationLibrary\doc\index.htm.

Samples are provided in the ORACLE_BASE\ORACLE_HOME\ODACsamples directory.

Configuring Oracle Data Provider for .NET

The settings for specific versions of ODP.NET, can be configured in several ways for specific effects on precedence:

- The Windows registry entries are machine-wide settings for a particular version of ODP.NET.

Windows registry based configuration is not supported for ODP.NET, Managed Driver, except for connection pool performance counters and event logging.

- The `machine.config` settings are .NET framework-wide settings that override the Windows registry values.
- The application or web config file settings are application-specific settings that override the `machine.config` settings and the Windows registry settings.
- Any attribute settings that are equivalent to the connection string override everything.

The application or web config file can be useful and sometimes essential in scenarios where more than one application on a computer use the same version of ODP.NET, but each application needs a different ODP.NET configuration. The Windows registry value settings for a given version of ODP.NET affect all the applications that use that version of ODP.NET. However, having ODP.NET configuration values in the application or web config file assure that these settings are applied only for that application, thus providing more granularities.

For example, if the application or `web.config` file has a `StatementCacheSize` configuration setting of 100, this application-specific setting forces the version of ODP.NET that is loaded by that application to use 100 for the `StatementCacheSize` and overrides any setting in the `machine.config` and in the registry. Note that for any setting that does not exist in a config file (`machine.config` or application/web config), the value in the registry for a loaded version of ODP.NET is used, as in previous releases.

Note that ODP.NET reads the `machine.config` files from the version of the .NET Framework on which ODP.NET runs, not from the version of ODP.NET.

ODP.NET only reads the Windows Registry and the XML configuration file when it is loaded into memory, thus any configuration changes made after that are not read or used until the application is re-started.

Note: ODP.NET managed and unmanaged driver .NET configuration file settings for native Entity Framework 6 applications have a different format than the traditional .NET configuration file settings. For more information on this format, consult the ODP.NET README.

Oracle Data Provider for .NET, Unmanaged Driver Configuration

The following sections explain how to configure ODP.NET, Unmanaged Driver.

Refer to "[Oracle Data Provider for .NET, Managed Driver Configuration](#)" on page 2-18 for information about how to configure ODP.NET, Managed Driver.

Supported Configuration Settings

ODP.NET, Unmanaged Driver supports the configuration of an attribute as follows:

- In the Windows registry.

- In an XML file.
- Through a different mechanism such as a connection string or programmatically through an ODP.NET class, if applicable.

Table 2–1 describes each configurable attribute that is supported by ODP.NET. In the table, the term Configuration Support is followed by the types of configuration support (Windows registry, XML file, and so on) that are available for that attribute.

The table describes valid values as well as the default for each attribute.

Note: The default values shown are the values used for an attribute if the registry key does not exist or if it is not configured anywhere.

Table 2–1 Configuration Attributes

| Attribute/Setting Name | Description |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CheckConStatus | <p>Specifies whether the status of the connection is checked or not before putting the connection back into the connection pool. This registry entry is not created by the installation of ODP.NET. However, the default value 1 is used.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values: 1: Check the status of the connection. 0: Do not check the status of the connection.</p> <p>Default: 1</p> |
| DbNotificationPort | <p>Specifies the port number which ODP.NET listens to, for all notifications sent by the database for change notification, HA, or RLB features. ODP.NET does not throw any errors if an invalid or used port number is specified. The port can also be set to override the Windows registry and XML configuration file by setting the <code>OracleDependency.Port</code> static field.</p> <p>Configuration Support: XML file, and ODP.NET class</p> <p>Valid Values: -1: Open a random unused port to listen to. $n > 0$: Listen on port n.</p> <p>Default: -1</p> |
| DemandOraclePermission | <p>Specifies whether ODP.NET demands <code>OraclePermission</code> from the .NET application that is trying to access the database using ODP.NET.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values: 0: Disables demands for <code>OraclePermission</code>. 1: Enables demands for <code>OraclePermission</code></p> <p>Default: 0</p> |

Table 2–1 (Cont.) Configuration Attributes

| Attribute/Setting Name | Description |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DllPath | <p>Specifies the location where dependent unmanaged Oracle Client binaries load from.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values:</p> <p>The path where dependent unmanaged Oracle Client binaries reside.</p> <p>Default: <code>ORACLE_BASE\ORACLE_HOME\bin</code></p> |
| DynamicEnlistment | <p>Specifies whether the application enlists in distributed transactions explicitly <i>after</i> an <code>OracleConnection.Open</code> method invocation through <code>EnlistTransaction()</code> or <code>EnlistDistributedTransaction()</code>. To configure ODP.NET to enable dynamic enlistment programmatically, the connection string must contain "enlist=dynamic".</p> <p>Configuration Support:</p> <p>Windows Registry, XML file, and "enlist" connection string attribute</p> <p>Valid Values:</p> <p>0: Disables ability to explicitly enlist in distributed transactions.</p> <p>1: Enables ability to explicitly enlist in distributed transactions.</p> <p>Default: 0</p> |
| FetchSize | <p>Specifies the total memory size, in bytes, that ODP.NET allocates to cache the data fetched from a database round-trip. This value can be set on the <code>OracleCommand</code> and the <code>OracleDataReader</code> <code>FetchSize</code> property as well.</p> <p>Configuration Support:</p> <p>Windows Registry, XML file, and ODP.NET class</p> <p>Valid Values:</p> <p>$0 \leq n \leq \text{int.MaxValue}$: <i>n</i> is the size of the cache in bytes.</p> <p>Default: 131072</p> |
| LegacyEntireLobFetch | <p>Returns either <code>OracleBlob</code> and <code>OracleClob</code> types or <code>OracleBinary</code> and <code>OracleString</code> types from Oracle Database BLOB and CLOB columns. This setting only applies when <code>InitialLobFetchSize</code> is set to -1.</p> <p>Valid Values:</p> <p>0: Returns <code>OracleBlob</code> and <code>OracleClob</code></p> <p>1: Returns <code>OracleBinary</code> and <code>OracleString</code></p> <p>Default: 0</p> |

Table 2–1 (Cont.) Configuration Attributes

| Attribute/Setting Name | Description |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LegacyTransactionBindingBehavior | <p>Specifies when a database connection detaches from a <code>System.Transactions</code> transaction. By default, connections detach from a transaction only when explicitly unbound as is the case when the connection closes or implicitly unbound when the transaction is disposed. Alternatively, this attribute can be set so that the connection detaches whenever the transaction ends (commits, aborts, or times out), the connection closes, or the transaction is disposed.</p> <p>In ODP.NET 11.2.0.3.20 and earlier releases, the latter was the default behavior. Oracle recommends using the current default behavior.</p> <p>In the earlier default behavior, when the timeout elapses before the transaction completes, the connection unbinds itself from the transaction and all subsequent executions on this connection execute in <code>AutoCommit</code> mode. Any operations prior to the timeout roll back, but operations performed after the timeout commit.</p> <p>In the current default setting, users receive an exception when the transaction times out and additional operations execute on the connection.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values:</p> <p>0: Connections detach from transaction when the connection closes or the transaction is disposed.</p> <p>1: Connections detach from transaction when the connection closes, the transaction is disposed, or the transaction completes (commits, rolls back, times out).</p> <p>Default: 0</p> |
| MaxStatementCacheSize | <p>Specifies the maximum number of statements that can be cached when self-tuning is enabled.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values: 0 to <code>System.Int32.MaxValue</code>.</p> <p>Default: 100</p> |
| MetaDataXml | <p>Specifies the name of the XML file that customizes the queries to obtain the metadata the ADO.NET 2.0 <code>GetSchema</code> method returns. <code>MetaDataXml</code> can only be set in a configuration file.</p> <p>Configuration Support: XML file only</p> <p>Valid Values: A complete file name for the XML file.</p> <p>Default: <i>none</i></p> |

Table 2–1 (Cont.) Configuration Attributes

| Attribute/Setting Name | Description |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PerformanceCounters | <p>Enables or disables publishing performance counters for connection pooling. Multiple performance counters can be obtained by adding the valid values.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values:</p> <p>0: Not Enabled</p> <p>1: Number of sessions being established with Oracle Database every second.</p> <p>2: Number of sessions being severed from Oracle Database every second.</p> <p>4: Number of active connections originating from connection pools every second.</p> <p>8: Number of active connections going back to the connection pool every second.</p> <p>16: Total number of active connections.</p> <p>32: Number of inactive connection pools.</p> <p>64: Total number of connections in use.</p> <p>128: Total number of connections available for use in all the connection pools.</p> <p>256: Number of pooled active connections.</p> <p>1024: Number of non-pooled active connections.</p> <p>2048: Number of connections that will be soon available in the pool. User has closed these connections, but they are currently awaiting actions, such transaction completion, before they can be placed back into the pool as free connections.</p> <p>4095: All the above</p> <p>Default: 0</p> |
| PromotableTransaction | <p>Specifies the type of transaction to use when the first connection participates in the <code>TransactionScope</code> object.</p> <p>Configuration Support: Windows Registry, XML file, and <i>promotable transaction</i> connection string attribute</p> <p>Valid Values:</p> <p>local: The first connection opened in the <code>TransactionScope</code> object uses a local transaction.</p> <p>promotable: The first connection and all subsequent connections opened in the same <code>TransactionScope</code> object enlist in the same distributed transaction.</p> <p>Default: promotable</p> |

Table 2–1 (Cont.) Configuration Attributes

| Attribute/Setting Name | Description |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SelfTuning | <p>Specifies whether self-tuning is enabled for an ODP.NET application.</p> <p>Configuration Support: Windows Registry, XML file, and Self Tuning connection string attribute</p> <p>Valid Values:</p> <p>0: Self Tuning is disabled. Used in the registry or XML file.</p> <p>false: Self Tuning is disabled. Used for the Self Tuning connection string attribute.</p> <p>1: Self Tuning is enabled. Used in the registry or XML file.</p> <p>true: Self Tuning is enabled. Used for the Self Tuning connection string attribute.</p> <p>Default: 1</p> |
| StatementCacheSize | <p>Specifies the number of cursors or statements to be cached on the database for each connection. This setting corresponds to <i>Statement Cache Size</i> attribute in the connection string. A value greater than zero also enables statement caching.</p> <p>Configuration Support: Windows Registry, XML file, and <i>Statement Cache Size</i> connection string attribute</p> <p>Valid Values:</p> <p>0 <= n <= the value of OPEN_CURSORS parameter set in <i>init.ora</i> database config file.</p> <p>n is the number to set.</p> <p>Default: 0</p> |
| StatementCacheWithUdts | <p>Specifies whether or not Oracle UDTs retrieved by executing a <i>SELECT</i> statement are cached along with the statement in the statement cache. This setting affects the memory usage and performance of the application.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values:</p> <p>0: Oracle UDTs are not cached with statements.</p> <p>1: Oracle UDTs are cached along with statements.</p> <p>Default: 1</p> |

Table 2–1 (Cont.) Configuration Attributes

| Attribute/Setting Name | Description |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ThreadPoolMaxSize | <p>Specifies the default maximum size of worker threads for each available processor in a process. This value may affect the performance of ODP.NET connection creation, command execution timeout, and external procedures (<code>extproc</code>) that use the thread pool. However, unnecessarily increasing thread pool maximum size can also cause performance problems.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values:</p> <p><code>0 <= n <= int.MaxValue</code>: Allows ODP.NET to reset thread pool maximum size with the value <i>n</i>. The ODP.NET reset operation may be ignored if the value is invalid. For example, if <i>n</i> is less than the number of available processors of the system. In this case, the result is the same as the value <code>-1</code>.</p> <p><code>-1</code>: Leave the thread pool max size as is.</p> <p>Default: <code>-1</code> (this registry entry is not created by default)</p> <p>Note that prior to ODAC 2007 or version 11.1.0.6.20, ODP.NET resets the thread pool maximum size to <code>int.MaxValue</code> when the <code>OracleCommand.CommandTimeout</code> property is set to a value greater than 0. This erroneous behavior has been corrected. <code>OracleCommand.CommandTimeout</code> does not change thread pool maximum size.</p> |
| TraceFileName | <p>Specifies the file name to be used for logging trace information.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values:</p> <p>Any valid directory location and file name.</p> <p>Default: <code>c:\odpnet2.trc</code> (for .NET Framework 2.0)</p> |

Table 2–1 (Cont.) Configuration Attributes

| Attribute/Setting Name | Description |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TraceLevel | <p>Specifies the level of tracing in ODP.NET. Because tracing all the entry and exit calls for all the objects can be excessive, <code>TraceLevel</code> is provided to limit tracing to certain areas of the provider. Each valid value indicates a possible tracing level. Compounded tracing levels can be obtained by adding the valid values.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values:</p> <ul style="list-style-type: none"> 0: None 1: Entry, exit, and SQL statement information 2: Connection pooling statistics 4: Distributed transactions (enlistment and delistment) 8: User-mode dump creation upon unmanaged exception 16: HA Event Information 32: Load Balancing Information 64: Self Tuning Information 127: All the above <p>Default: 0</p> <p>Note: ODP.NET does bit-wise checking on the value. When tracing is enabled, logging to the trace file can affect ODP.NET performance.</p> <p>Note: The user-mode dump creation requires <code>dbghelp.dll</code> version 5.1.2600.0 or later.</p> |
| TraceOption | <p>Specifies whether to log trace information in single or multiple files for different threads. If a single trace file is specified, the file name specified in <code>TraceFileName</code> is used. If the multiple trace files option is requested, a Thread ID is appended to the file name provided to create a trace file for each thread.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values:</p> <ul style="list-style-type: none"> 0: Single trace file 1: Multiple trace files <p>Default: 0</p> |
| UdtCacheSize | <p>Specifies the size of the object cache for each connection in kilobytes (KB) that ODP.NET uses to retrieve and manipulate Oracle UDTs.</p> <p>Configuration Support: Windows Registry and XML file</p> <p>Valid Values:</p> <p>0 <= n <= 4194303, n is the number to set.</p> <p>Default: 4096</p> |

Table 2–1 (Cont.) Configuration Attributes

| Attribute/Setting Name | Description |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>UDT Mapping</i> | <p>Specifies a mapping between a custom type and an Oracle UDT in the database. The mappings can be specified in configuration files and custom type factories. However, if the mapping is specified in both places, mappings specified in the configuration files takes precedence over mappings specified using custom type factories.</p> <p>Configuration Support: XML file and Custom Type Factory Classes</p> <p>Valid Values: Any valid mapping.</p> <p>Default: <i>none</i></p> |

Windows Registry

Upon installation, ODP.NET creates entries for configuration and tracing within the Windows Registry. Configuration and tracing registry values apply across all ODP.NET applications running in that Oracle client installation. Individual ODP.NET applications can override some of these values by configuring them within the ODP.NET application itself (for example, `FetchSize`). Applications can also use the .NET configuration files to override some of the ODP.NET Windows Registry values.

The ODP.NET registry values are located under `HKEY_LOCAL_MACHINE\Software\Oracle\ODP.NET\version\`. There is one key for .NET Framework 3.5, and one key for .NET Framework 4 and later.

Note: 32-bit applications running on an x64-based version of Windows use the registry subkey, `HKEY_LOCAL_MACHINE\Software\Wow6432node` in place of `HKEY_LOCAL_MACHINE\Software`. If such applications use Oracle Data Provider for .NET (32-bit), then the ODP.NET registry values are located under `HKEY_LOCAL_MACHINE\SOFTWARE\Wow6432Node\Oracle\ODP.NET\version\`.

Configuration File Support

For customers who have numerous applications on a computer that depends on a single version of ODP.NET, the Windows Registry settings for a given version of ODP.NET may not necessarily be applicable for all applications that use that version of ODP.NET. To provide more granular control, ODP.NET Configuration File Support allows developers to specify ODP.NET configuration settings in an application config, `web.config`, or a `machine.config` file.

If a computer does not require granular control beyond configuration settings at the ODP.NET version level, there is no need to specify ODP.NET configuration settings through configuration files.

The following is an example of a `web.config` file for .NET Framework 2.0 and later:

```
<?xml version="1.0" encoding="utf-8" ?>
<configuration>
  <oracle.dataaccess.client>
    <settings>
      <add name="DllPath" value="C:\oracle\bin"/>
      <add name="FetchSize" value="131072"/>
    </settings>
  </oracle.dataaccess.client>
</configuration>
```

```

    <add name="PromotableTransaction" value="promotable"/>
    <add name="StatementCacheSize" value="10"/>
    <add name="TraceFileName" value="C:\odpnet2.trc"/>
    <add name="TraceLevel" value="63"/>
    <add name="TraceOption" value="1"/>
  </settings>
</oracle.dataaccess.client>
</configuration>

```

The following is an example of `app.config` for ODP.NET, Unmanaged Driver using .NET Framework 2.0, which sets some additional attributes as well as two UDT type mappings:

```

<?xml version="1.0" encoding="utf-8" ?>
<configuration>
  <oracle.dataaccess.client>
    <settings>
      <add name="DbNotificationPort" value="-1"/>
      <add name="DllPath" value="C:\app\user\product\11.1.0\client_1\bin"/>
      <add name="DynamicEnlistment" value="0"/>
      <add name="FetchSize" value="131072"/>
      <add name="MetaDataXml" value="CustomMetaData.xml"/>
      <add name="PerformanceCounters" value="4095"/>
      <add name="PromotableTransaction" value="promotable"/>
      <add name="StatementCacheSize" value="50"/>
      <add name="ThreadPoolMaxSize" value="30"/>
      <add name="TraceFileName" value="c:\odpnet2.trc"/>
      <add name="TraceLevel" value="0"/>
      <add name="TraceOption" value="0"/>
      <add name="Person" value="udtMapping factoryName='PersonFactory, Sample,
        Version=0.0.0.0, Culture=neutral, PublicKeyToken=null' typeName='PERSON'
        schemaName='SCOTT' dataSource='oracle'"/>
      <add name="Student" value="udtMapping factoryName='StudentFactory, Sample,
        Version=0.0.0.0, Culture=neutral, PublicKeyToken=null' typeName='STUDENT'
        schemaName='SCOTT'"/>
    </settings>
  </oracle.dataaccess.client>
</configuration>

```

Oracle Data Provider for .NET, Managed Driver Configuration

ODP.NET, Managed Driver supports .NET configuration file-based settings in `machine.config`, `application.config`, and `web.config`. It does not support Windows registry based configuration. ODP.NET, Managed Driver settings in .NET configuration files are similar to ODP.NET, Unmanaged Driver settings to make porting easier.

The ODP.NET, Managed Driver configuration file section name is `<oracle.manageddataaccess.client>` as compared to `<oracle.dataaccess.client>` in ODP.NET, Unmanaged Driver. A typical .NET config that uses ODP.NET, Managed Driver has some or all of the following subsections nested within a `<version>` subsection under `<oracle.manageddataaccess.client>` section. Note the tag names are case sensitive, while the attribute names are case insensitive.

```

<?xml version="1.0" encoding="utf-8" ?>
<configuration>
  <oracle.manageddataaccess.client>
    <version number="*">
      <dataSources>
        ...

```



```

    ...
  </dataSources>
  <settings>
    ...
    ...
  </settings>
  <LDAPsettings>
    ...
    ...
  </LDAPsettings>
  <implicitRefCursor>
    ...
    ...
  </implicitRefCursor>
  <edmMappings>
    ...
    ...
  </edmMappings>
</version>
<version number="4.112.3.60">
  <dataSources>
    ...
    ...
  </dataSources>
  <settings>
    ...
    ...
  </settings>
  <LDAPsettings>
    ...
    ...
  </LDAPsettings>
  <implicitRefCursor>
    ...
    ...
  </implicitRefCursor>
  <edmMappings>
    ...
    ...
  </edmMappings>
</version>
</oracle.manageddataaccess.client>
</configuration>

```

The ODP.NET, Managed Driver configuration and settings are described in the following sections. Many of the attributes are the same as ODP.NET, Unmanaged Driver. See [Table 2-1](#) for detailed attribute descriptions.

version Section

All the information required by an application should be grouped under the `version` subsections. Each `<version number="X">` section contains parameters applicable for version X of the ODP.NET, Managed Driver. For example, `<version number="4.112.3.60">` section parameters will be applicable only for those applications using ODP.NET, Managed Driver assembly 4.112.3.60.

Apart from version specific sections, there can also be a generic section `<version number="*">`. This section's parameters are applicable for all ODP.NET, Managed Driver versions. Parameters in the version specific section take precedence over the parameters of the generic section. The following is an example of a version section:

```

<oracle.manageddataaccess.client>
  <version number="*">
    <settings>
      <setting name="TraceOption" value="1"/>
      <setting name="PerformanceCounters" value="0" />
    </settings>
  </version>
  <version number="4.112.3.60">
    <settings>
      <setting name="PerformanceCounters" value="4095" />
    </settings>
  </version>
</oracle.manageddataaccess.client>

```

An application referencing ODP.NET, Managed Driver 4.112.3.60 has the following values set:

- TraceOption = 1
- PerformanceCounters= 4095

dataSources Section

This section can appear only under a <version> section. The mapping between the different data source aliases and corresponding data descriptors should appear in this section. The following is an example.

```

<dataSources>
  <dataSource alias="inst1"
descriptor="(DESCRIPTION=(ADDRESS=(PROTOCOL=tcp)(HOST=sales-server).....))"/>
  <dataSource alias="inst2" descriptor="(DESCRIPTION=.....)"/>
</dataSources>

```

The following precedence order is followed to resolve the data source alias specified in the Data Source attribute in the connection string.

1. data source alias in the dataSources section under <oracle.manageddataaccess.client> section in the .NET config file.
2. data source alias in the tnsnames.ora file at the location specified by TNS_ADMIN in the .NET config file.
3. data source alias in the tnsnames.ora file present in the same directory as the .exe.

Note: The "data source" connection string attribute can alternatively be set to a full descriptor or Easy Connect syntax rather than a data source alias. The above precedence rules apply to resolving a data source alias only.

The ODP.NET managed driver reads and caches all the alias entries from the app.config, web.config, machine.config, and from a tnsnames.ora file that is found at application start-up time. However, aliases that are defined in LDAP servers are resolved and cached on demand. This means for each unique alias that is used by the application, an alias resolution query is executed against an LDAP server and the full descriptor associated with the alias will be cached once it is fetched.

For developers that need to change or add alias settings while developing applications, one may consider using `OracleDataSourceEnumerator.GetDataSources()` rather than restarting the

application. Invoking this method will first wipe out existing cache entries that were read from the `tnsnames.ora` file and all aliases obtained from the LDAP Server. Then, the `tnsnames.ora` is re-parsed and all its entries will be cached again. Please note that the `app.config`, `web.config`, and `machine.config` entries are read only once at application start-up time and thus their contents are maintained and not re-parsed even if `OracleDataSourceEnumerator.GetDataSources()` is invoked.

The `OracleDataSourceEnumerator.GetDataSources()` method invocation has an impact on the connection pool. This is because a connection pool, which is created for each unique connection string, will cache the resolved full descriptor information after the first connection is created for a given connection pool. After that, the connection pool uses the cached full descriptor information for all subsequent connection creations. Thus, for applications that have their `tnsnames.ora` or LDAP entries modified during the execution of an application where an alias points to a different database than before, one should call the `OracleDataSourceEnumerator.GetDataSources()` method to remove old cached entries. This should be followed by the invocation of the `ClearPool(OracleConnection)` instance method or the `ClearAllPools()` static method to remove existing connections and also have it obtain a new full descriptor value that was read by the invocation of `OracleDataSourceEnumerator.GetDataSources()`. Following this scheme will assure that *all* the connections in the connection pool uses the new full descriptor that is now associated with the alias and all connections in a connection pool is established to the same database.

The following keywords are supported within the descriptor setting:

- ADDRESS
- ADDRESS_LIST (Note: only failover supported)
 - Oracle recommends using SCAN listener and Runtime Load Balancing to balance the load when connecting to an Oracle RAC database.
- DESCRIPTION
- DESCRIPTION_LIST (Note: Failover supported; Address_list load balancing not supported)
- HOST (Note: <hostname>, <IPv6 literal>, and <IPv4 literal> are supported)
- IP (Note: "loopback" is supported)
- PROTOCOL (Note: tcp and tcps are supported)
- SDU (Note: 256 to 65536 are supported)
- SECURITY: SSL_VERSION (Note: overrides sqlnet.ora:ssl_version)
- TRANSPORT_CONNECT_TIMEOUT (Note: overrides tcp.connect_timeout)

Note:

- SSL is now supported via method MCS and FILE.
- **Only NTS authentication is supported. No RADIUS nor Kerberos5 authentication.**
- Only SQL*Net, Easy Connect naming, and LDAP (namely, Active Directory and Oracle Internet Directory) are supported.
- No bequeath (beq) support. Default address is instead TCP loopback with port 1521 and Oracle service name from environment (ORACLE_SID)

See Also: *Oracle Database Net Services Reference* for a detailed description of the attributes.

Requirements for connecting to a local database *without* specifying "data source" connection string attribute:

- The listener must be up and running.
- ORACLE_SID environment variable must be set appropriately.

Note: When "data source" connection string attribute is not specified, protocol defaults to 'tcp' and port defaults to '1521'.

settings section

This section can appear only under a <version> section. Any ODP.NET, Managed Driver specific settings should appear in this section. The following is an example of a settings section:

```
<settings>
  <setting name="TraceLevel" value="7" />
  <setting name="TraceOption" value="1"/>
  <setting name="TNS_ADMIN" value="C:\oracle\work"/>
</settings>
```

A new default behavior has been introduced for ODP.NET Release 12.1.0.2 and higher when `InitialLobFetchSize` is set to -1. The new default value is `LegacyEntireLOBFetch = 0`. To use the old behavior, set `LegacyEntireLobFetch = 1` in the ODP.NET configuration. Refer to "[Setting InitialLONGFetchSize to -1](#)" on page 3-58 for more information.

ODP.NET, Managed Driver configuration settings that are supported:

- `DbNotificationPort`
- `DemandOraclePermission`
- `FetchSize`
- `LDAP_ADMIN`: Specifies the `ldap.ora` location. The `LDAP_ADMIN` setting works in conjunction with the `TNS_ADMIN` setting to set `ldap.ora` search order.

`ldap.ora` is searched in the following order:

1. `TNS_ADMIN` in `app/web.config`
2. `LDAP_ADMIN` in `app/web.config`

3. current working directory
 4. %ORACLE_HOME%\network\admin
 5. %ORACLE_HOME%\ldap\admin
- LegacyEntireLOBFetch
 - MaxStatementCacheSize
 - MetaDataXml
 - NAMES.DIRECTORY_PATH: The default search order is TNSNAMES and EZCONNECT. TNSNAMES, LDAP, and EZCONNECT are the only name resolution methods supported, but their precedence order can be modified.
 - NAMES.LDAP_AUTHENTICATE_BIND
 - NAMES.LDAP_CONN_TIMEOUT
 - NODELAY
 - ORACLE_SID
 - PerformanceCounters
 - RECEIVE_BUF_SIZE - Sets TCP SO_RECVBUF, the total buffer space associated with the local side of a TCP socket
 - SelfTuning
 - SEND_BUF_SIZE - Sets TCP SO_SENDBUF, the total buffer space associated with the local side of a TCP socket
 - SQLNET.AUTHENTICATION_SERVICES : Supported values are NTS, null, empty, or not-specified.
 - StatementCacheSize
 - SSL_VERSION
 - TNS_ADMIN : Location where either one or more of tnsnames.ora, ldap.ora, and sqlnet.ora are located.

Note: When installing ODP.NET, Managed Driver and an Oracle Home together, the installer automatically creates a TNS_ADMIN setting in the machine.config file of the .NET Framework. The TNS_ADMIN setting will be set to the directory: <ORACLE_HOME>\Network\Admin\, providing a default machine location to host the tnsnames.ora, sqlnet.ora, and ldap.ora files.

- TraceFileLocation: Trace file destination directory, for example, D:\traces\. This is different from ODP.NET, Unmanaged Driver, which supports TraceFileName.
- TraceLevel : 1 = public APIs; 2 = private APIs; 4 = network APIs/data. These values can be ORed. To enable everything, set TraceLevel to 7. Errors will always be traced.
- TraceOption
- TCP.CONNECT_TIMEOUT
- WALLET_LOCATION : Microsoft Certificate Store (MCS) and file system wallets are supported

There is no support for Oracle Advanced Security Option (ASO) encryption. Setting `SQLNET.ENCRYPTION_SERVER` to `required` is not supported, resulting in client connection establishment failure. Not setting `SQLNET.ENCRYPTION_SERVER` or setting it to any other valid value is supported.

ODP.NET, Managed Provider only supports the ASO NTS authentication adapter. The database server must be on Windows, support NTS external authentication, and have `SQLNET.AUTHENTICATION_REQUIRED` set to `true`, `1`, or `on`. The ODP.NET, Managed Driver client must utilize NTS external authentication as well. All other ASO NTS connection scenarios will fail since the client and server will not be able to agree on an ASO authentication mechanism.

Kerberos NTS external authentication is not supported. NTS external authentication is supported only through Microsoft NT LAN Manager (NTLM).

See Also: *Oracle Database Net Services Reference*

LDAPsettings section

This section can appear only under a `<version>` section. Any ODP.NET, Managed Driver specific LDAP settings should appear in this section. The following is an example of a `<LDAPsetting>` subsection under the `<LDAPsettings>` section:

```
<LDAPsettings>
  <LDAPsetting name="DIRECTORY_TYPE" value="AD" />
  <LDAPsetting name="DEFAULT_ADMIN_CONTEXT" value="dc=Oracle,dc=com"/>
</LDAPsettings>
```

Lightweight Directory Access Protocol

ODP.NET, Managed Driver supports TNS alias resolution through a LDAP server/service, specifically Microsoft Active Directory and Oracle Internet Directory (OID). TNS alias resolution occurs when using the LDAPsettings section or `ldap.ora` file settings. The LDAPsettings section settings take precedence over `ldap.ora` settings.

For Active Directory, only the `DIRECTORY_TYPE` and `DEFAULT_ADMIN_CONTEXT` parameters are required in `ldap.ora`. When the `DIRECTORY_SERVERS` parameter is missing or has no value, the default LDAP server for the current domain will be used.

For OID, all `ldap.ora` parameters must be set with valid values to complete configuration.

ODP.NET, Managed Driver and ODP.NET, Unmanaged Driver support the same level of security when using LDAP for name resolution.

| | Microsoft Active Directory | |
|----------------|----------------------------|---------------|
| Encryption | None | SSL |
| Authentication | Anonymous Domain User | Not Supported |

| Oracle Internet Directory | | |
|---------------------------|-----------|---------------------------------------------------------------------------------------------------------------------------------|
| Encryption | None | SSL |
| Authentication | Anonymous | Anonymous Wallet <i>Note: Wallet based authentication for Oracle Internet Directory is not supported for this release</i> |

See Also:

- *Oracle Database Net Services Reference* for more information on Directory Usage Parameters.
- *Oracle Database Net Services Administrator's Guide* for more information on Managing Network Address.

implicitRefCursor section

This section can appear only under a <version> section. Any information about REF CURSOR parameters that need to be bound implicitly should appear in this section. The following is an example of an <implicitRefCursor> section:

```
<implicitRefCursor>
  <storedProcedure schema="USERREFCUR" name="TestProc1">
    <refCursor name="Param3">
      <bindInfo mode="Output"/>
      <metadata columnOrdinal="0" columnName="DEPTNO" baseColumnName="DEPTNO"
baseSchemaName="USERREFCUR" baseTableName="DEPT" nativeDataType="number"
providerType="Int32" dataType="System.Int16" columnSize="2" allowDBNull="true" />
      <metadata columnOrdinal="1" columnName="DNAME" baseColumnName="DNAME"
baseSchemaName="USERREFCUR" baseTableName="DEPT" nativeDataType="varchar2"
providerDbType="String" columnSize="30" />
    </refCursor>
    <refCursor name="param2">
      <bindInfo mode="Output"/>
      <metadata columnOrdinal="0" columnName="EMPNO" baseColumnName="EMPNO"
baseSchemaName="USERREFCUR" baseTableName="EMP" nativeDataType="number"
providerType="Int32" dataType="System.Int16" columnSize="4" allowDBNull="false" />
    </refCursor>
  </storedProcedure>

  <!--Next stored procedure information-->
  <storedProcedure name="TestProc2">
    ...
    ...
  </storedProcedure>
</implicitRefCursor>
```

distributedTransaction section

This section can appear only under a <version> section. Any information about distributed transactions should appear in this section. The following is an example of a distributedTransaction section:

```
<distributedTransaction>
  <setting name="OMTSRECO_IP_ADDRESS" value="my-pc" />
  <setting name="OMTSRECO_PORT" value="2040" />
  <setting name="ORAMTS_SESS_TXNTIMETOLIVE" value="240" />
</distributedTransaction>
```

OMTSRECO_IP_ADDRESS: Specifies the machine name (or IP address) that the OraMTS Recovery service will be running on to resolve database in-doubt transactions. The default is the local machine name.

OMTSRECO_PORT: Specifies the port that the OraMTS Recovery service will be listening on to resolve database in-doubt transactions. The default is 2030.

ORAMTS_SESS_TXNTIMETOLIVE : Specifies the time in seconds that the transaction can remain inactive after it has been detached or delisted from the database. Once this time expires, the transaction is automatically terminated by the provider. The default is 120 seconds.

edmMappings section

This section can appear only under a <version> section. Any information related to EDM mappings should appear in this section. The following is an example of an edmMappings section:

```
<edmMappings>
  <edmMapping dataType="number">
    <add name="bool" precision="1"/>
    <add name="byte" precision="2" />
    <add name="int16" precision="5" />
  </edmMapping>
</edmMappings>
```

onsConfig section

Oracle Notification Service (ONS) can be configured using either local or remote configuration. Remote configuration is the preferred configuration for standalone client applications. Prior to 12c Release 1 (12.1), this section was mandatory for receiving ONS notifications. With 12.1, this section is optional and the information about the ONS daemons is received from the server itself. However, ODP.NET will also listen for events from any <host:port> pairs that is provided by the user in this section in addition to the <host:port> pairs received from the server.

For local configuration, please ensure that ONS is configured and available on the node where ODP.NET is running, so that ODP.NET can receive events directly from the local ONS daemon. For client side ONS daemon configuration, refer to "[Client Side ONS Daemon Configuration](#)" on page 2-27.. The following is a sample format for the local configuration:

```
<onsConfig configFile="C:\temp\test.config" mode="local">
</onsConfig>
```

Note: The configFile specified in .NET config should contain the same localport and remoteport values as specified in the ons.config used by the local ONS daemon. This will enable the application to receive events from the local ONS daemon.

Remote configuration is used in scenarios where the application directly receives ONS events from the ONS daemons running on remote machines. One of the advantages of this configuration is that no ONS daemon is needed on the client end and, therefore, there is no need to manage this process.

The following is a sample format for remote configuration:


```

<onsConfig mode="remote">
  <ons database="db1">
    <add name="nodeList" value="racnode1:4100, racnode2:4200" />
  </ons>
  <ons database="db2">
    <add name="nodeList" value=" racnode3:4100, racnode4:4200" />
  </ons>
</onsConfig>

```

In case of remote configuration, the application has to specify the <host>:<port> values for every potential database that it can connect to. The <host>:<port> value pairs represent the ports on the the different Oracle RAC nodes where the ONS daemons are talking to their remote clients.

Client Side ONS Daemon Configuration

ONS configuration is controlled by the ONS configuration file, *ORACLE_HOME/opmn/conf/ons.config*. This file tells the ONS daemon how it should behave. The *SRVCTL* utility can be used to start and stop the ONS daemon. It is installed on each node by default during server install. Refer to *Oracle Real Application Clusters Administration and Deployment Guide* for more information on the *SRVCTL* utility.

Configuration information within *ons.config* is defined in simple name and value pairs. An example of *ONS.config* is given below

```

# This is an example ons.config file
#
# The first three values are required
localport=4100
remoteport=4200
nodes=racnode1.example.com:4200,racnode2.example.com:4200

```

Some parameters in the *ons.config* file are required and some are optional. Table [Table 2–2](#) lists the required ONS configuration parameters and [Table 2–3](#) lists the optional ONS configuration parameters.

Table 2–2 Required ONS Configuration Parameters

| Parameter | Explanation |
|------------|-----------------------------------------------------------------------------------------------------------------|
| localport | The port that ONS binds to on the local host interface to talk to local clients. For example, localport=4100 |
| remoteport | The port that ONS binds to on all interfaces for talking to other ONS daemons. For example, remoteport=4200 |

Table 2–2 (Cont.) Required ONS Configuration Parameters

| Parameter | Explanation |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| nodes | <p>A list of other ONS daemons to talk to. Node values are given as a comma-delimited list of either host names or IP addresses plus ports. The port value that is given is the remote port that each ONS instance is listening on. In order to maintain an identical file on all nodes, the <code>host:port</code> of the current ONS node can also be listed in the nodes list. It will be ignored when reading the list.</p> <p>For example, <code>nodes=myhost.example.com:4200,123.123.123.123:4200</code></p> <p>The nodes listed in the nodes line correspond to the individual nodes in the Oracle RAC instance. Listing the nodes ensures that the middle-tier node can communicate with the Oracle RAC nodes. At least one middle-tier node and one node in the Oracle RAC instance must be configured to see one another. As long as one node on each side is aware of the other, all nodes are visible. You need not list every single cluster and middle-tier node in the ONS configuration file of each Oracle RAC node. In particular, if one ONS configuration file cluster node is aware of the middle tier, then all nodes in the cluster are aware of it.</p> |

Table 2–3 Optional ONS Configuration Parameters

| Parameter | Description |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| loglevel | <p>The level of messages that should be logged by ONS. This value is an integer that ranges from 1, which indicates least messages logged, to 9, which indicates most messages logged. The default value is 3.</p> <p>For example, <code>loglevel=3</code></p> |
| logfile | <p>A log file that ONS should use for logging messages. The default value for log file is <code>\$ORACLE_HOME/opmn/logs/ons.log</code>.</p> <p>For example, <code>logfile=C:\app\user\product\12.1.0\opmn\logs\myons.log</code></p> |
| walletfile | <p>The wallet file used by the Oracle Secure Sockets Layer (SSL) to store SSL certificates. If a wallet file is specified to ONS, then it uses SSL when communicating with other ONS instances and require SSL certificate authentication from all ONS instances that try to connect to it. This means that if you want to turn on SSL for one ONS instance, then you must turn it on for all instances that are connected. This value should point to the directory where your <code>ewallet.p12</code> file is located.</p> <p>For example, <code>walletfile=C:\app\user\product\12.1.0\opmn\conf\ssl.wlt\default</code></p> |
| useocr | <p>The value, reserved for use on the server-side, to indicate ONS whether it should store all Oracle RAC nodes and port numbers in Oracle Cluster Registry (OCR) instead of the ONS configuration file or not. A value of <code>useocr=on</code> is used to store all Oracle RAC nodes and port numbers in Oracle Cluster Registry (OCR).</p> <p>Do not use this option on the client-side.</p> |

The `ons.config` file allows blank lines and comments on lines that begin with the number sign (#).

Using Oracle Services for MTS with Oracle Data Provider for .NET, Managed Driver

ODP.NET, Managed Driver incorporates Oracle Services for MTS entire enlistment and commit functionality, allowing those functions to execute using managed code. The Oracle Services for MTS recovery service remains unmanaged.

The `Oracle.ManagedDataAccessDTC.dll` is packaged with the ODP.NET, Managed Driver. This DLL includes the Oracle Services for MTS enlistment and commit functionality and must be deployed with `Oracle.ManagedDataAccess.dll` for any ODP.NET, Managed Driver applications using distributed transactions. It can run alongside the unmanaged Oracle Services for MTS version if unmanaged data access drivers, such as ODBC, are also using distributed transactions on the same machine.

There are two versions of `Oracle.ManagedDataAccessDTC.dll`, one for 32-bit .NET Framework and one for 64-bit .NET Framework, installed with ODP.NET, Managed Driver. Both `Oracle.ManagedDataAccessDTC.dll` are fully managed, but they are platform-specific because the Microsoft Distributed Transaction Coordinator (MS DTC) application programming interfaces are unmanaged code. Thus, ODP.NET, Managed Driver enlistment and commit calls must distinguish whether they are calling 32-bit or 64-bit MS DTC.

The DLLs are located in the following directories:

- For 32-bit .NET Framework: `ORACLE_HOME\odp.net\managed\x86`
- For 64-bit .NET Framework: `ORACLE_HOME\odp.net\managed\x64`

Deploy the `Oracle.ManagedDataAccessDTC.dll` from the directory appropriate for your .NET application's target platform, 32-bit or 64-bit.

`Oracle.ManagedDataAccessDTC.dll` should not be directly referenced by a .NET application. It will be implicitly loaded by ODP.NET, Managed Driver when using distributed transactions.

The Oracle Services for MTS recovery service does not need to run in the same machine as ODP.NET, Managed Driver. Administrators can specify the host machine name that has a running recovery service in the application's .NET config file.

See Also: *Oracle Services for MTS* for Oracle Services for MTS setup of recovery service for ODP.NET, Managed Driver

Configuration differences between ODP.NET, Managed Driver and ODP.NET, Unmanaged Driver

[Table 2–4](#) lists other configuration differences between ODP.NET, Managed Driver and ODP.NET, Unmanaged Driver.

Table 2–4 Configuration Differences between ODP.NET, Unmanaged Driver and ODP.NET, Managed Driver

| Feature Category | Difference compared to ODP.NET, Unmanaged Driver |
|------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Configuration | Configuration file format is different. See " Oracle Data Provider for .NET, Managed Driver Configuration " on page 2-18. |
| Configuration | <code>ConfigSchema.xsd</code> file, shipped with ODP.NET, Managed Driver (when included as part of the schema (XML->Schemas) in Visual Studio) enables <code>app.config</code> intelli-sense. |
| Configuration | Windows Registry based configuration is not supported |

Table 2–4 (Cont.) Configuration Differences between ODP.NET, Unmanaged Driver and ODP.NET, Managed

| Feature Category | Difference compared to ODP.NET, Unmanaged Driver |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Configuration | Oracle High Availability (HA) & Oracle RAC Load Balancing (RLB) notifications use Oracle Notification Service (ONS). Thus, to use HA or RLB, configure database and client to use ONS, rather than Oracle Database Advanced Queuing (AQ). Note that Continuous Query Notification will continue to use AQ. |
| Configuration Parameter | Edition is not supported. |
| Configuration Parameter | CheckConStatus is not supported. |
| Configuration Parameter | DllPath is not supported. |
| Configuration Parameter | StatementCacheWithUdts is not supported. |
| Configuration Parameter | ThreadPoolMaxSize is not supported. |
| Configuration Parameter | TraceFileName has been replaced by TraceFileLocation. |
| Configuration Parameter | UdtCacheSize is not supported. |
| Configuration Parameter | UDT Mapping is not supported. |
| Connection String | Context Connection is not supported. |
| Connection String | Enlist=dynamic will behave the same as Enlist=false. |
| Connection String | LegacyTransactionBindingBehavior setting will be ignored. It will always be set to the default value of 1. |
| Connection String | Promotable Transaction setting will be ignored. It will always be set to promotable and always support promotions. |
| Connection String | Statement Cache Purge is not supported. |
| Connectivity | Connection to Oracle Times Ten Database is not supported. |
| Performance Monitor | NumberOfStatisConnections performance counter is not supported. |
| Performance Monitor | Performance monitor category name is "ODP.NET, Managed Driver" |
| Provider Types | Provider Types accept (via constructors) and generate (via ToString() methods) only culture-invariant strings |
| Tracing | Trace file name format is: <process_name>_PID_<process_id>_DATE_<date>_TIME_<time>.trc. |
| Tracing | Dynamic tracing is enabled by changing the TraceLevel setting in the app/web/machine.config. NOTE: For ASP.NET applications, doing so will recycle the application domain. |
| Tracing | An eventlog entry is generated indicating where the trace file is created or if ODP.NET, Managed Driver had issues creating one. |

Migrating from ODP.NET, Unmanaged Driver to ODP.NET, Managed Driver

To ease migration, the APIs of ODP.NET, Managed Driver are a complete subset of the APIs of ODP.NET, Unmanaged Driver. As long as the existing unmanaged ODP.NET applications use currently available managed ODP.NET APIs, migration is straightforward and simple.

In future versions, the managed driver will support more APIs of ODP.NET, Unmanaged Driver. Both drivers will continue to be enhanced to support the latest Oracle Database and .NET Framework features.

To migrate from unmanaged to managed ODP.NET, perform the following steps:

1. Add a Reference to `Oracle.ManagedDataAccess.dll` in the .NET project.

2. Change the existing ODP.NET, Unmanaged Driver namespace references to ODP.NET, Managed Driver references.

```
// C#
using Oracle.ManagedDataAccess.Client;
using Oracle.ManagedDataAccess.Types;

// VB
Imports Oracle.ManagedDataAccess.Client
Imports Oracle.ManagedDataAccess.Types
```

3. Some provider configuration settings may need to be migrated because ODP.NET, Managed Driver supports very few Windows Registry settings and a different .NET configuration setting format.

Refer to ["Configuring Oracle Data Provider for .NET"](#) on page 2-9 for more information.

Configuring a Port to Listen for Database Notifications

Oracle Data Provider for .NET opens a port to listen for database notifications when the following features are used:

- HA Events
- Load Balancing
- Continuous Query Notification
- AQ Notifications

All these features share the same port, which can be configured centrally by setting the db notifications port in an application or web configuration file.

If the configuration file does not exist or the db notification port is not specified, ODP.NET uses a valid, random port number. The configuration file may also request for a random port by specifying a db notification port value of -1. To specify a particular port in ODP.NET, Unmanaged Driver, for example, 1200, an application or web configuration file can be used as follows:

```
<configuration>
  <oracle.dataaccess.client>
    <settings>
      <add name="DbNotificationPort" value="1200"/>
    </settings>
  </oracle.dataaccess.client>
</configuration>
```

To specify a particular port in ODP.NET, Managed Driver, an application or web configuration file can be used as follows:

```
<configuration>
  <oracle.manageddataaccess.client>
    <version number="*">
      <settings>
        <setting name="DbNotificationPort" value="1200"/>
      </settings>
    </version>
  </oracle.manageddataaccess.client>
</configuration>
```

The port number should be unique for each process running on a computer. Thus, the port number should be set uniquely for each application either programmatically or through an application config file. Note that if the specified port number is already in use or invalid, ODP.NET does not provide any errors.

When the process using ODP.NET starts, the application reads the `db notification` port number and listens on that port. Once the port is opened, the port number cannot be changed during the lifetime of the process.

See Also:

- ["Fast Application Notification"](#) on page 3-25
- ["Runtime Connection Load Balancing"](#) on page 3-26
- ["Continuous Query Notification Support"](#) on page 3-112
- ["Oracle Database Advanced Queuing Support"](#) on page 3-107

General .NET Programming Recommendations and Tips for ODP.NET

- `Thread.Abort()` should not be used, as unmanaged resources may remain unreleased, which can potentially cause memory leaks and hangs.
- To optimize resource usage, ODP.NET objects, such as `OracleConnection` and `OracleCommand`, should be explicitly closed or disposed, or both, when they are no longer needed. This should be done rather than relying on the .NET Framework garbage collector to reclaim resources. Many users have found that under stress conditions, explicit `Close` or `Dispose` calls result in much lower resource usage.
- It is recommended not to proceed with application execution if the application encounters exceptions that are associated with possible memory corruption, such as `System.AccessViolationException` and `System.Runtime.InteropServices.SEHException`.
- If the `HKEY_LOCAL_MACHINE\Software\Oracle\NLS_LANG` registry entry is set to `NA`, ODP.NET encounters `ORA-12705` errors. To eliminate this problem, remove the `HKEY_LOCAL_MACHINE\Software\Oracle\NLS_LANG` registry entry.

Features of Oracle Data Provider for .NET

This section describes Oracle Data Provider for .NET provider-specific features and how to use them to develop .NET applications.

This section contains the following topics:

- [Base Classes and Provider Factory Classes](#)
- [Code Access Security](#)
- [Connecting to Oracle Database](#)
- [Real Application Clusters and Global Data Services](#)
- [Using Transaction Guard to Prevent Logical Corruption](#)
- [OracleCommand Object](#)
- [ODP.NET Types Overview](#)
- [Obtaining Data from an OracleDataReader Object](#)
- [PL/SQL REF CURSOR and OracleRefCursor](#)
- [Implicit REF CURSOR Binding](#)
- [LOB Support](#)
- [ODP.NET XML Support](#)
- [Oracle User-Defined Types \(UDTs\) and .NET Custom Types](#)
- [Bulk Copy](#)
- [Oracle Database Advanced Queuing Support](#)
- [Continuous Query Notification Support](#)
- [OracleDataAdapter Safe Type Mapping](#)
- [OracleDataAdapter Requery Property](#)
- [Guaranteeing Uniqueness in Updating DataSet to Database](#)
- [Globalization Support](#)
- [Debug Tracing](#)

Base Classes and Provider Factory Classes

With ADO.NET, data classes derive from the base classes defined in the `System.Data.Common` namespace. Developers can create provider-specific instances of these base classes using provider factory classes.

Provider factory classes allow generic data access code to access multiple data sources with a minimum of data source-specific code. This reduces much of the conditional logic currently used by applications accessing multiple data sources.

Using Oracle Data Provider for .NET, the `OracleClientFactory` class can be returned and instantiated, enabling an application to create instances of the following ODP.NET classes that inherit from the base classes:

Table 3–1 ODP.NET Classes that Inherit from ADO.NET 2.0 Base Classes

| ODP.NET Classes | Inherited from ADO.NET 2.0 Base Class |
|--------------------------------------------|----------------------------------------|
| <code>OracleClientFactory</code> | <code>DbProviderFactory</code> |
| <code>OracleCommand</code> | <code>DbCommand</code> |
| <code>OracleCommandBuilder</code> | <code>DbCommandBuilder</code> |
| <code>OracleConnection</code> | <code>DbConnection</code> |
| <code>OracleConnectionStringBuilder</code> | <code>DbConnectionStringBuilder</code> |
| <code>OracleDataAdapter</code> | <code>DbDataAdapter</code> |
| <code>OracleDataReader</code> | <code>DbDataReader</code> |
| <code>OracleDataSourceEnumerator</code> | <code>DbDataSourceEnumerator</code> |
| <code>OracleException</code> | <code>DbException</code> |
| <code>OracleParameter</code> | <code>DbParameter</code> |
| <code>OracleParameterCollection</code> | <code>DbParameterCollection</code> |
| <code>OracleTransaction</code> | <code>DbTransaction</code> |

In general, applications still require Oracle-specific connection strings, SQL or stored procedure calls, and declare that a factory from ODP.NET is used.

See Also: [OracleClientFactory Class](#) on page 6-3

Code Access Security

ODP.NET implements code access security through the `OraclePermission` class. This ensures that application code trying to access the database has the requisite permission to do so.

When a .NET assembly tries to access Oracle Database through ODP.NET, ODP.NET demands `OraclePermission`. The .NET runtime security system checks to see whether the calling assembly, and all other assemblies in the call stack, have `OraclePermission` granted to them. If all assemblies in the call stack have `OraclePermission` granted to them, then the calling assembly can access the database. If any one of the assemblies in the call stack does not have `OraclePermission` granted to it, then a security exception is thrown.

Configuring OraclePermission

The `DemandOraclePermission` configuration attribute is used to enable or disable `OraclePermission` demand for an ODP.NET API. The `DemandOraclePermission` value can be specified in the Windows registry for unmanaged ODP.NET only, or an individual application configuration file for both unmanaged and managed ODP.NET.

The following Windows registry key is used to configure the `DemandOraclePermission` configuration attribute:


```
HKEY_LOCAL_MACHINE\SOFTWARE\ORACLE\ODP.NET\Assembly_Version\DemandOraclePermission
```

Here *Assembly_Version* is the full assembly version number of *Oracle.DataAccess.dll*. The *DemandOraclePermission* key is of type *REG_SZ*. It can be set to either 1 (enabled) or 0 (disabled).

You can also enable *OraclePermission* demand for an individual application using its application configuration file. The following example enables the *DemandOraclePermission* property in an application configuration file for ODP.NET, Unmanaged Driver:

```
<configuration>
  <oracle.dataaccess.client>
    <settings>
      <add name="DemandOraclePermission" value="1"/>
    </settings>
  </oracle.dataaccess.client>
</configuration>
```

Similarly, you can use *DemandOraclePermission* to configure ODP.NET, Managed Driver under the settings section for managed provider configuration. See also "[settings section](#)" on page 2-22 for more information.

An application or assembly can successfully access the database if *OraclePermission* has been added to the permission set associated with the assembly's code group. A system administrator can modify the appropriate permission set manually or by using the Microsoft .NET configuration tool (*Mscorcfg.msc*).

Administrators may also use an appropriate .NET Framework Tool, such as the Code Access Security Policy Tool (*Caspol.exe*), to modify security policy at the machine, user, and enterprise levels for including *OraclePermission*.

OracleConnection makes security demands using the *OraclePermission* object when *OraclePermission* demand has been enabled using *DemandOraclePermission* configuration attribute. Application developers should make sure that their code has sufficient permission before using *OracleConnection*.

See Also:

- "[OraclePermission Class](#)" on page 6-375
- "[OraclePermissionAttribute Class](#)" on page 6-384

Configuring OraclePermission for Web Applications with High or Medium Trust Levels

For Web applications operating under high or medium trust, *OraclePermission* needs to be configured in the appropriate *web_TrustLevel.config* file, so that the application does not encounter any security errors.

OraclePermission can be configured using the *OraProvCfg* tool. *OraProvCfg.exe* adds appropriate entries to the *web_hightrust.config* and *web_mediumtrust.config* files associated with the specified .NET framework version.

The following example illustrates using the *OraProvCfg* tool for configuring *OraclePermission* in a .NET 2.0 Web application:

```
OraProvCfg.exe /action:config /product:odp /component:oraclepermission
              /frameworkversion:v2.0.50727
              /providerpath:full_path_of_Oracle.DataAccess.dll
```

On running the preceding command, the following entry is added to the `web_hightrust.config` and `web_mediumtrust.config` files under the ASP.NET permission set:

```
<IPermission class="Oracle.DataAccess.Client.OraclePermission, Oracle.DataAccess,
Version=2.112.2.0, Culture=neutral, PublicKeyToken=89b483f429c47342" version="1"
Unrestricted="true" />
```

`OraProvCfg` can also be used to remove these entries from the `.config` files when required. The following example illustrates this:

```
OraProvCfg.exe /action:unconfig /product:odp /component:oraclepermission
                /frameworkversion:v2.0.50727
                /providerpath:full_path_of_Oracle.DataAccess.dll
```

Configuring OraclePermission for Windows Applications Running in a Partial Trust Environment

For Windows applications operating in a partial trust environment, the `OraclePermission` entry should be specified under the appropriate permission set in the `security.config` file. The `security.config` file is available in the `%windir%\Microsoft.NET\Framework\{version}\CONFIG` folder.

The following example specifies the `OraclePermission` entry for a .NET 2.0 Windows application:

```
<IPermission class="Oracle.DataAccess.Client.OraclePermission, Oracle.DataAccess,
Version=2.112.2.0, Culture=neutral, PublicKeyToken=89b483f429c47342" version="1"
Unrestricted="true" />
```

Connecting to Oracle Database

Oracle Data Provider for .NET can connect to Oracle Database in a number of ways, such as using a user name and password, Windows Native Authentication, Kerberos, and Transport Layer Security/Secure Sockets Layer. This section describes OracleConnection provider-specific features, including:

- [Connection String Attributes](#)
- [Connection String Builder](#)
- [Specifying the Data Source Attribute](#)
- [Schema Discovery](#)
- [Connection Pooling](#)
- [Connection Pool Management](#)
- [Connection Pool Performance Counters](#)
- [Pluggable Databases](#)
- [Edition-Based Redefinition](#)
- [Operating System Authentication](#)
- [Privileged Connections](#)
- [Password Expiration](#)
- [Proxy Authentication](#)
- [Dynamic Distributed Transaction Enlistment](#)

- [Client Identifier and End-to-End Tracing](#)
- [Transparent Application Failover \(TAF\) Callback Support](#)

Connection String Attributes

Table 3–2 lists the supported connection string attributes.

Table 3–2 Supported Connection String Attributes

| Connection String Attribute | Description | Default Value |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| Connection Lifetime | Minimum life time (in seconds) of the connection. | 0 |
| Connection Timeout | Minimum time (in seconds) to wait for a free connection from the pool. | 15 |
| Context Connection | Returns an implicit database connection if set to true. <i>Supported in a .NET stored procedure only</i> | false |
| Data Source | Oracle Net Services Name, Connect Descriptor, or an easy connect naming that identifies the database to which to connect. | empty string |
| DBA Privilege | Administrative privileges: SYSDBA or SYSOPER. | empty string |
| Decr Pool Size | Number of connections that are closed when an excessive amount of established connections are unused. | 1 |
| Enlist | Controls the enlistment behavior and capabilities of a connection in context of COM+ transactions or System.Transactions. | true |
| HA Events | Enables ODP.NET connection pool to proactively remove connections from the pool when an Oracle database service, service member, instance, or node goes down. Works with Oracle Global Data Services, including Oracle RAC, Data Guard, GoldenGate, and some single instance deployments. | false |
| Load Balancing | Enables ODP.NET connection pool to balance work requests across Oracle database instances based on the load balancing advisory and service goal. Works with Oracle Global Data Services, including Oracle RAC, Active Data Guard, and GoldenGate. | false |
| Incr Pool Size | Number of new connections to be created when all connections in the pool are in use. | 5 |
| Max Pool Size | Maximum number of connections in a pool. | 100 |
| Metadata Pooling | Caches metadata information. | True |
| Min Pool Size | Minimum number of connections in a pool. | 1 |

Table 3–2 (Cont.) Supported Connection String Attributes

| Connection String Attribute | Description | Default Value |
|-----------------------------|-------------------------------------------------------------------------------------------------------|---------------|
| Password | Password for the user specified by User Id. | empty string |
| Persist Security Info | Retrieval of the password in the connection string. | false |
| Pooling | Connection pooling. | true |
| Promotable Transaction | Indicates whether or not a transaction is local or distributed throughout its lifetime. | promotable |
| Proxy User Id | User name of the proxy user. | empty string |
| Proxy Password | Password of the proxy user. | empty string |
| Self Tuning | Enables or disables self-tuning for a connection. | true |
| Statement Cache Purge | Statement cache purged when the connection goes back to the pool. | false |
| Statement Cache Size | Statement cache enabled and cache size, that is, the maximum number of statements that can be cached. | 0 |
| User Id | Oracle user name. | empty string |
| Validate Connection | Validation of connections coming from the pool. | false |

The following example uses connection string attributes to connect to Oracle Database:

```
// C#

using System;
using Oracle.DataAccess.Client;

class ConnectionSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();

        //using connection string attributes to connect to Oracle Database
        con.ConnectionString = "User Id=scott;Password=tiger;Data Source=oracle";
        con.Open();
        Console.WriteLine("Connected to Oracle" + con.ServerVersion);

        // Close and Dispose OracleConnection object
        con.Close();
        con.Dispose();
        Console.WriteLine("Disconnected");
    }
}
```

See Also:

- ["OracleConnection Properties"](#) on page 6-92 for detailed information on connection attributes
- ["OracleCommand Object"](#) on page 3-32 for detailed information on statement caching

Connection String Builder

The `OracleConnectionStringBuilder` class makes creating connection strings less error-prone and easier to manage.

Using this class, developers can employ a configuration file to provide the connection string and/or dynamically set the values through the key/value pairs. One example of a configuration file entry follows:

```
<configuration>
  <connectionStrings>
<add name="Publications" providerName="Oracle.DataAccess.Client"
      connectionString="User Id=scott;Password=tiger;Data Source=inst1" />
  </connectionStrings>
</configuration>
```

Connection string information can be retrieved by specifying the connection string name, in this example, `Publications`. Then, based on the `providerName`, the appropriate factory for that provider can be obtained. This makes managing and modifying the connection string easier. In addition, this provides better security against string injection into a connection string.

See Also: [OracleConnectionStringBuilder Class](#) on page 6-134

Specifying the Data Source Attribute

This section describes different ways of specifying the data source attribute.

The following example shows a connect descriptor mapped to a TNS alias called `sales` in the `tnsnames.ora` file:

```
sales=
  (DESCRIPTION=
    (ADDRESS= (PROTOCOL=tcp) (HOST=sales-server) (PORT=1521))
    (CONNECT_DATA=
      (SERVICE_NAME=sales.us.acme.com)))
```

The connection pool will maintain the full descriptor of an alias so that subsequent connection requests with the same connection string will not need to resolve the alias again. This applies to `tnsnames.ora`, `.NET` config data sources, and LDAP aliases. To flush out the cached full descriptor maintained by the connection pool, invoke `OracleDataSourceEnumerator.GetDataSources()` followed by `OracleConnection.ClearPool()` or `OracleConnection.ClearAllPools()`.

If connection pooling is not used, the alias will need to be resolved to the full descriptor for each request. In the case of LDAP, the LDAP server is contacted for each connection request.

Using the TNS Alias

To connect as `scott/tiger` using the TNS Alias, a valid connection appears as follows:

```
"user id=scott;password=tiger;data source=sales";
```

Using the Connect Descriptor

ODP.NET also allows applications to connect without the use of the `tnsnames.ora` file. To do so, the entire connect descriptor can be used as the "data source".

The connection string appears as follows:

```
"user id=scott;password=tiger;data source=" +  
  "(DESCRIPTION=(ADDRESS=(PROTOCOL=tcp) " +  
  "(HOST=sales-server) (PORT=1521)) (CONNECT_DATA="+  
  "(SERVICE_NAME=sales.us.acme.com)))"
```

Using Easy Connect Naming Method

The easy connect naming method enables clients to connect to a database without any configuration.

Prior to using the easy connect naming method, make sure that `EZCONNECT` is specified by the `NAMES.DIRECTORY_PATH` parameter in the `sqlnet.ora` file as follows:

```
NAMES.DIRECTORY_PATH= (TNSNAMES, EZCONNECT)
```

With this enabled, ODP.NET allows applications to specify the "Data Source" attribute in the form of:

```
//host:[port]/[service_name]
```

Using the same example, some valid connection strings follow:

```
"user id=scott;password=tiger;data source=//sales-server:1521/sales.us.acme.com"  
"user id=scott;password=tiger;data source=//sales-server/sales.us.acme.com"  
"user id=scott;password=tiger;data source=sales-server/sales.us.acme.com"
```

If the port number is not specified, 1521 is used by default.

See Also: *Oracle Database Net Services Administrator's Guide* for details and requirements in the section [Using Easy Connect Naming Method](#)

Using LDAP

ODP.NET can connect with connect identifiers mapped to connect descriptors in an LDAP-compliant directory server, such as Oracle Internet Directory and Microsoft Active Directory.

To configure LDAP for ODP.NET, Unmanaged Driver, follow these Oracle documentation instructions in [Configuring the Directory Naming Method](#) in *Oracle Database Net Services Administrator's Guide*.

To configure LDAP for ODP.NET, Managed Driver, follow the instructions in ["settings section"](#) on page 2-22 and ["LDAPsettings section"](#) on page 2-24.

See Also: *Oracle Database Net Services Administrator's Guide* and *Oracle Database Security Guide* for details and requirements in the section [Using LDAP](#)

Data Source Enumerator

The data source enumerator enables the application to generically obtain a collection of the Oracle data sources that the application can connect to.

See Also: ["OracleDataSourceEnumerator Class"](#) on page 6-263

Using Transport Layer Security and Secure Sockets Layer

Transport Layer Security (TLS) and its predecessor, Secure Sockets Layer (SSL), are industry standard protocols for securing network connections. Both managed and unmanaged ODP.NET support SSL for database and transport authentication.

See Also: Enabling Secure Sockets Layer in *Oracle Database Security Guide* for more information about TLS/SSL and configuration with Oracle database.

Using Kerberos

Kerberos is a network authentication service for security in distributed environments. ODP.NET applications can use Kerberos for single sign-on and centralized user authentication. ODP.NET, Unmanaged Driver supports Kerberos for single sign-on and authentication. ODP.NET, Managed Driver does not support Kerberos.

See Also: Configuring Kerberos Authentication in *Oracle Database Security Guide* for more information about Kerberos and configuration with Oracle database.

Schema Discovery

ADO.NET exposes five different types of metadata collections through the `OracleConnection.GetSchema` API. This permits application developers to customize metadata retrieval on an individual-application basis, for any Oracle data source. Thus, developers can build a generic set of code to manage metadata from multiple data sources.

The following types of metadata are exposed:

- `MetaDataCollections`
A list of metadata collections that is available from the data source, such as tables, columns, indexes, and stored procedures.
- `Restrictions`
The restrictions that apply to each metadata collection, restricting the scope of the requested schema information.
- `DataSourceInformation`
Information about the instance of the database that is currently being used, such as product name and version.
- `DataTypes`
A set of information about each data type that the database supports.
- `ReservedWords`
Reserved words for the Oracle query language.

See Also: [Appendix A, "Oracle Schema Collections"](#)

User Customization of Metadata

ODP.NET provides a comprehensive set of database schema information. Developers can extend or customize the metadata that is returned by the `GetSchema` method on an individual application basis.

To do this, developers must create a customized metadata file and provide the file name to the application as follows:

1. Create a customized metadata file and put it in the `CONFIG` subdirectory where the .NET framework is installed. This is the directory that contains `machine.config` and the security configuration settings.

This file must contain the entire set of schema configuration information, not just the changes. Developers provide changes that modify the behavior of the schema retrieval to user-specific requirements. For instance, a developer can filter out internal database tables and just retrieve user-specific tables

2. Add an entry in the `app.config` file of the application, similar to the following, to provide the name of the metadata file, in name-value pair format.

```
<oracle.dataaccess.client>
  <settings>
    <add name="MetaDataXml" value="CustomMetaData.xml" />
  </settings>
</oracle.dataaccess.client>
```

When the `GetSchema` method is called, ODP.NET checks the `app.config` file for the name of the customized metadata XML file. First, the `GetSchema` method searches for an entry in the file with a element named after the provider, in this example, `oracle.dataaccess.client`. In this XML element, the value that corresponds to the name `MetaDataXml` is the name of the customized XML file, in this example, `CustomMetaData.xml`.

If the metadata file is not in the correct directory, then the application loads the default metadata XML file, which is part of ODP.NET.

See Also: ["GetSchema"](#) on page 6-118

Connection Pooling

ODP.NET connection pooling is enabled and disabled using the `Pooling` connection string attribute. By default, connection pooling is enabled. The following are `ConnectionString` attributes that control the behavior of the connection pooling service:

- `Connection Lifetime`
- `Connection Timeout`
- `Decr Pool Size`
- `HA Events`
- `Incr Pool Size`
- `Load Balancing`
- `Max Pool Size`
- `Min Pool Size`
- `Pooling`
- `Validate Connection`

Connection Pooling Example

The following example opens a connection using `ConnectionString` attributes related to connection pooling.

```
// C#

using System;
using Oracle.DataAccess.Client;

class ConnectionPoolingSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();

        //Open a connection using ConnectionString attributes
        //related to connection pooling.
        con.ConnectionString =
            "User Id=scott;Password=tiger;Data Source=oracle;" +
            "Min Pool Size=10;Connection Lifetime=100000;Connection Timeout=60;" +
            "Incr Pool Size=5; Decr Pool Size=2";
        con.Open();
        Console.WriteLine("Connection pool successfully created");

        // Close and Dispose OracleConnection object
        con.Close();
        con.Dispose();
        Console.WriteLine("Connection is placed back into the pool.");
    }
}
```

Using Connection Pooling

When connection pooling is enabled (the default), the `Open` and `Close` methods of the `OracleConnection` object implicitly use the connection pooling service, which is responsible for pooling and returning connections to the application.

The connection pooling service creates connection pools by using the `ConnectionString` property as a signature, to uniquely identify a pool.

When a new connection is opened, if the connection string is not an exact match to an existing pool, then a new pool is created. Prior to ODP.NET 12.1.0.2, only connection string attribute values had to match. Now, connection strings themselves must be an exact match. Keywords supplied in a different order for the same connection will be pooled separately. If a pool already exists with the requested signature, a connection is returned to the application from that pool.

When a connection pool is created, the connection pooling service initially creates the number of connections defined by the `Min Pool Size` attribute of the `ConnectionString` property. This number of connections is always maintained by the connection pooling service for the connection pool.

At any given time, these connections are in use by the application or are available in the pool.

The `Incr Pool Size` attribute of the `ConnectionString` property defines the number of new connections to be created by the connection pooling service when more connections are needed in the connection pool.

When the application closes a connection, the connection pooling service determines whether or not the connection lifetime has exceeded the value of the `Connection Lifetime` attribute. If so, the connection pooling service closes the connection; otherwise, the connection goes back to the connection pool. The connection pooling service enforces the `Connection Lifetime` only when a connection is going back to the connection pool.

The `Max Pool Size` attribute of the `ConnectionString` property sets the maximum number of connections for a connection pool. If a new connection is requested, but no connections are available and the limit for `Max Pool Size` has been reached, then the connection pooling service waits for the time defined by the `Connection Timeout` attribute. If the `Connection Timeout` time has been reached, and there are still no connections available in the pool, the connection pooling service raises an exception indicating that the connection pool request has timed-out. Upon a connection timeout, ODP.NET distinguishes whether the timeout occurred due to the database server failing to deliver a connection in the allotted time or no connection being available in the pool due to the maximum pool size having been reached. The exception text returned will either be "Connection request timed out" in the case of the former or "Pooled connection request timed out" in the case of the latter.

The `Validate Connection` attribute validates connections coming out of the pool. This attribute should be used only when absolutely necessary, because it causes a round-trip to the database to validate each connection immediately before it is provided to the application. If invalid connections are uncommon, developers can create their own event handler to retrieve and validate a new connection, rather than using the `Validate Connection` attribute. This generally provides better performance.

The connection pooling service closes connections when they are not used; connections are closed every 3 minutes. The `Decr Pool Size` attribute of the `ConnectionString` property provides connection pooling service for the maximum number of connections that can be closed every 3 minutes.

Beginning with Oracle Data Provider for .NET release 11.1.0.6.20, enabling connection pooling by setting "pooling=true" in the connection string (which is the case by default) will also pool operating system authenticated connections.

Connection Pool Management

ODP.NET connection pool management provides explicit connection pool control to ODP.NET applications. Applications can explicitly clear connections in a connection pool.

Using connection pool management, applications can do the following:

Note: These APIs are not supported in a .NET stored procedure.

- Clear connections from connection pools using the `ClearPool` method.
- Clear connections in all the connection pools in an application domain, using the `ClearAllPools` method.

See Also:

- ["ClearPool"](#) on page 6-89
- ["ClearAllPools"](#) on page 6-90

Connection Pool Performance Counters

Installing Oracle Data Provider for .NET creates a set of performance counters on the target system. These performance counters are published by ODP.NET for each ODP.NET client application. These performance counters can be viewed using Windows Performance Monitor (Perfmon).

In Perfmon, administrators can add ODP.NET counters to the performance monitor graph. ODP.NET performance counters are published under the following Category Name: Oracle Data Provider for .NET. Administrators can choose the ODP.NET counters to monitor after selecting the Oracle Data Provider for .NET category.

As ODP.NET performance counters are not enabled by default, administrators must enable the specific counters of interest before attempting to monitor them. In addition, at least one ODP.NET instance must be actively running when attempting to monitor using Perfmon.

Oracle Data Provider for .NET enables or disables publishing performance counters for connection pooling, using registry entries.

[Table 3–3](#) lists the performance counters used for connection pooling with their valid registry values.

Table 3–3 Performance Counters for Connection Pooling

| Performance Counter | Valid Values | Description |
|---------------------------------|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| None | 0 | Not enabled (Default) |
| HardConnectsPerSecond | 1 | Number of sessions being established with the Oracle Database every second. |
| HardDisconnectsPerSecond | 2 | Number of sessions being severed from the Oracle Database every second. |
| SoftConnectsPerSecond | 4 | Number of active connections originating from connection pools every second. |
| SoftDisconnectsPerSecond | 8 | Number of active connections going back to the connection pool every second. |
| NumberOfActiveConnectionPools | 16 | Total number of active connection pools. |
| NumberOfInactiveConnectionPools | 32 | Number of inactive connection pools. |
| NumberOfActiveConnections | 64 | Total number of connections in use. |
| NumberOfFreeConnections | 128 | Total number of connections available for use in all the connection pools. |
| NumberOfPooledConnections | 256 | Number of pooled active connections. |
| NumberOfNonPooledConnections | 512 | Number of non-pooled active connections. |
| NumberOfReclaimedConnections | 1024 | Number of connections which were garbage-collected implicitly. |
| NumberOfStasisConnections | 2048 | Number of connections that will be soon available in the pool. User has closed these connections, but they are currently awaiting actions such transaction completion before they can be placed back into the pool as free connections. |

Publishing Performance Counters

Publication of individual performance counters is enabled or disabled using the registry value `PerformanceCounters` of type `REG_SZ` or a .NET configuration file. This registry value is under:

```
HKEY_LOCAL_MACHINE\SOFTWARE\ORACLE\ODP.NET\Assembly_Version
```

where `Assembly_Version` is the full assembly version number of `Oracle.DataAccess.dll`.

Multiple performance counters can be obtained by adding the valid values. For example, if `PerformanceCounters` is set to 3, both `HardConnectsPerSecond` and `HardDisconnectsPerSecond` are enabled.

Setting Performance Counters Using .NET Configuration Entry

Performance counters can be set using an .NET configuration entry. Since .NET configuration entries take precedence over the registry value setting, they can be used for a specific application.

An .NET configuration entry uses name/value pairs as in the following example:

```
<configuration>
  <oracle.dataaccess.client>
    <settings>
      <add name="PerformanceCounters"
          value="3"/>
    </settings>
  </oracle.dataaccess.client>
</configuration>
```

Instance Names of Performance Counters

Performance counters can now monitor at the application domain, pool, or database instance level. Database instance level monitoring only applies if load balancing or Fast Connection Failover features are enabled.

The instance name format is as follows:

```
<Application Domain Name> [<Process Id>, <Application Domain
Id>][<Connection String/Pool Name>][<Instance Name>]. The entry is limited to
127 characters. There is a restriction length on every field in the instance name. The
following table shows the maximum number of characters allocated for each field:
```

| Field Name | Maximum Number of Characters |
|-----------------------------|------------------------------|
| Application Domain | 40 |
| Pool Name/Connection String | 70 |
| Database Instance Name | 16 |

When the length of a field value exceeds the length limit, the string is truncated and appended with "... " to fit within the length limit and indicate the continuation. For example, for a given application called `Program.exe` with a connection string `user id=scott;Password=tiger;data source=inst1;max pool size=125`, one may see the following similar to the following for a process that has two application domains:

- `Program.exe [123, 1]`
- `Program.exe [123, 1][user id=scott;data source=inst1;max pool siz...`

- Program.exe [123, 1][user id=scott;data source=inst1;max pool siz...]
[instA]
- Domain 2[123, 2]
- Domain 2[123, 2][user id=scott;data source=inst1;max pool siz...]
- Domain 2[123, 2][user id=scott;data source=inst1;max pool siz...]
[instB]
- Domain 2[123, 2][user id=scott;data source=inst1;max pool siz...]
[instC]

Since connection pool attributes can be similar in their first 70 characters, applications can set a Pool Name to uniquely identify each one in the monitoring tool. The .NET config file can set the Pool Name attribute:

ODP.NET, Unmanaged Driver

```
<configuration>
  <oracle.dataaccess.client>
    <settings>
      .
      .
      <add name="[connection string without password]" value="connectionPool
name=' [Pool Name] '"/>
      .
    </settings>
  </oracle.dataaccess.client>
</configuration>
```

ODP.NET, Managed Driver

```
<oracle.manageddataaccess.client>
  <version number="*">
    <connectionPools>
      .
      .
      <connectionPool connectionString="[connection string without password]" "
poolName="[Pool Name]"> </connectionPool>
      .
    </connectionPools>
  </version>
</oracle.manageddataaccess.client>
```

The behavior of two of the performance counters has now changed in the 12c release:

- NumberOfPooledConnections -- Sum of the active connections and free connections. Previously, this value was equal to just the number of active connections.
- NumberOfStasisConnections -- No longer supported.

Pluggable Databases

Oracle Database 12c introduced a new feature, Pluggable Databases, which enable an Oracle database to contain a portable collection of schemas, schema objects, and nonschema objects that appears to ODP.NET as a separate database. This self-contained collection is called a pluggable database (PDB).

ODP.NET 12c and higher can connect to PDBs, which clients access through database services. Database services have an optional PDB property. When a PDB is created, a new default database service is created automatically. The service has the same name as the PDB and can be used to access the PDB using the easy connect syntax or the net service name. This service is intended primarily for performing administrative tasks. It is recommended that you create additional services for use in your applications.

All ODP.NET features can be used with PDBs with the following exceptions:

- Continuous Query Notification
- Client Result Cache
- Fast Application Notification events using Oracle Notification Service
- Switching from one PDB to another PDB using the `ALTER SESSION SET CONTAINER` statement

See Also: *Managing Pluggable Databases in Oracle Database Administrator's Guide*

Edition-Based Redefinition

Edition-based redefinition enables you to upgrade the database component of an application even while the application is being used. This minimizes or eliminates downtime for the application.

See Also: For more information on Editions refer to the *Oracle Database Administrator's Guide* and *Oracle Database Development Guide*

ODP.NET 11g Release 2 (11.2.0.1), and higher, supports specifying an Edition at deployment time when used with Oracle Database 11.2 or later. Applications can specify an Edition at deployment time using the registry or configuration file.

An application can create the following registry entry of type `REG_SZ`:

```
HKLM\Software\Oracle\ODP.NET\version\Edition
```

Here *version* is the version of ODP.NET, and *Edition* is a valid Edition string value.

An application can alternatively use the `web.config` or `application.config` configuration file to specify the Edition at deployment time. The `machine.config` configuration file can be used to specify the Edition for all applications that use a particular version of the .NET framework.

The following example sets the Edition to E1 in a .NET configuration file for ODP.NET, Unmanaged Driver:

```
<?xml version="1.0" encoding="utf-8" ?>
<configuration>
  <oracle.dataaccess.client>
    <settings>
      <add name="Edition" value="E1"/>
    </settings>
  </oracle.dataaccess.client>
</configuration>
```

Note:

- ODP.NET only supports deployment-time configuration of Edition.
- ODP.NET does not support usage of the "ALTER SESSION" statement to modify the Edition during the lifetime of a process.
- ODP.NET, Managed Driver does not support Edition-Based Redefinition.

Operating System Authentication

Oracle Database can use Windows user login credentials to authenticate database users. To open a connection using Windows user login credentials, the `User Id` connection string attribute must be set to a slash (/). If the `Password` attribute is provided, it is ignored.

Note: Operating System Authentication is not supported in a .NET stored procedure.

Beginning with Oracle Data Provider for .NET release 11.1.0.6.20, all connections, including those using operating system authentication, can be pooled. Connections are pooled by default, and no configuration is required, as long as pooling is enabled.

The following example shows the use of operating system authentication:

```

/* Create an OS-authenticated user in the database
   Assume init.ora has OS_AUTHENT_PREFIX set to "" and <OS_USER>
   is any valid OS or DOMAIN user.

   create user <OS_USER> identified externally;
   grant connect, resource to <OS_USER>;

   Login through OS Authentication and execute the sample. See Oracle
   documentation for details on how to configure an OS-Authenticated user
*/

// C#

using System;
using Oracle.DataAccess.Client;

class OSAuthenticationSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();

        //Establish connection using OS Authentication
        con.ConnectionString = "User Id=/;Data Source=oracle;";
        con.Open();
        Console.WriteLine("Connected to Oracle" + con.ServerVersion);

        // Close and Dispose OracleConnection object
        con.Close();
        con.Dispose();
        Console.WriteLine("Disconnected");
    }
}

```

```
}  
}
```

See Also: *Oracle Database Platform Guide for Microsoft Windows* for information on how to set up Oracle Database to authenticate database users using Windows user login credentials

Privileged Connections

Oracle allows database administrators to connect to Oracle Database with either SYSDBA or SYSOPER privileges. This is done through the DBA Privilege attribute of the `ConnectionString` property.

The following example connects `scott/tiger` as SYSDBA:

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
  
class PrivilegedConnectionSample  
{  
    static void Main()  
    {  
        OracleConnection con = new OracleConnection();  
  
        //Connect scott/tiger as SYSDBA  
        con.ConnectionString = "User Id=scott;Password=tiger;" +  
            "DBA Privilege=SYSDBA;Data Source=oracle;";  
        con.Open();  
        Console.WriteLine("Connected to Oracle" + con.ServerVersion);  
  
        // Close and Dispose OracleConnection object  
        con.Close();  
        con.Dispose();  
        Console.WriteLine("Disconnected");  
    }  
}
```

See Also: DBA Privilege "[Supported Connection String Attributes](#)" on page 6-96 for further information on privileged connections in the database

Password Expiration

Oracle allows users passwords to expire. ODP.NET lets applications handle the password expiration by providing a new method, `OpenWithNewPassword`, that opens the connection with a new password.

The following example uses the `OracleConnection.OpenWithNewPassword` method to connect with a new password of `panther`:

```
/* Database Setup  
connect / as sysdba;  
drop user testexpire cascade;  
-- create user "testexpire" with password "testexpire"  
grant connect , resource to testexpire identified by testexpire;  
alter user testexpire password expire;  
*/
```



```

// C#

using System;
using Oracle.DataAccess.Client;

class PasswordExpirationSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();

        try
        {
            con.ConnectionString =
                "User Id=testexpire;Password=testexpire;Data Source=oracle";
            con.Open();
            Console.WriteLine("Connected to Oracle" + con.ServerVersion);
        }
        catch (OracleException ex)
        {
            Console.WriteLine(ex.Message);

            //check the error number
            //ORA-28001 : the password has expired
            if (ex.Number == 28001)
            {
                Console.WriteLine("\nChanging password to panther");
                con.OpenWithNewPassword("panther");
                Console.WriteLine("Connected with new password.");
            }
        }
        finally
        {
            // Close and Dispose OracleConnection object
            con.Close();
            con.Dispose();
            Console.WriteLine("Disconnected");
        }
    }
}

```

Note:

- The `OpenWithNewPassword` method should be used only when the user password has expired, not for changing the password.
- If connection pooling is enabled, then invoking the `OpenWithNewPassword` method also clears the connection pool. This closes all idle connections created with the old password.

See Also: ["OpenWithNewPassword"](#) on page 6-126

Proxy Authentication

With proper setup in the database, proxy authentication enables middle-tier applications to control the security by preserving database user identities and

privileges, and auditing actions taken on behalf of these users. This is accomplished by creating and using a proxy database user that connects and authenticates against the database on behalf of a database user (that is, the *real* user) or database users.

Proxy authentication can then be used to provide better scalability with connection pooling. When connection pooling is used in conjunction with proxy authentication, the proxy authenticated connections can be shared among different real users. This is because only the connection and session established for the proxy is cached. An additional session is created for the real user when a proxy authenticated connection is requested, but it will be destroyed appropriately when the proxy authenticated connection is placed back into the pool. This design enables the application to scale well without sacrificing security.

ODP.NET applications can use proxy authentication by setting the "Proxy User Id" and "Proxy Password" attributes in the connection string. The real user is specified by the "User Id" attribute. Optionally, to enforce greater security, the real user's password can be provided through the "Password" connection string attribute. When using distributed transactions in conjunction with proxy authentication, the real user's password is no longer optional, and it must be supplied.

The following example illustrates the use of ODP.NET proxy authentication:

```
/* Log on as DBA (SYS or SYSTEM) that has CREATE USER privilege.
   Create a proxy user and modified scott to allow proxy connection.

   create user appserver identified by eagle;
   grant connect, resource to appserver;
   alter user scott grant connect through appserver;
*/

// C#

using System;
using Oracle.DataAccess.Client;

class ProxyAuthenticationSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();

        // Connecting using proxy authentication
        con.ConnectionString = "User Id=scott;Password=tiger;" +
            "Data Source=oracle;Proxy User Id=appserver;Proxy Password=eagle; ";
        con.Open();
        Console.WriteLine("Connected to Oracle" + con.ServerVersion);

        // Close and Dispose OracleConnection object
        con.Close();
        con.Dispose();
        Console.WriteLine("Disconnected");
    }
}
```

See Also:

- *Oracle Database Development Guide* for details on designing a middle-tier server using proxy users
- *Oracle Database SQL Language Reference* for the description and syntax of the proxy clause for the ALTER USER statement
- *Oracle Database Security Guide* section "Standard Auditing in a Multitier Environment"

Dynamic Distributed Transaction Enlistment

For those applications that dynamically enlist in distributed transactions through the `EnlistDistributedTransaction` of the `OracleConnection` object, the "enlist" connection string attribute must be set to a value of either "dynamic" or "true". If "enlist=true", the connection enlists in a transaction when the `Open` method is called on the `OracleConnection` object, if it is within the context of a COM+ transaction or a `System.Transactions`. If not, the `OracleConnection` object does not enlist in a distributed transaction, but it can later enlist explicitly using the `EnlistDistributedTransaction` or the `EnlistTransaction` method. If "enlist=false", the connection cannot enlist in the transaction.

For applications that cannot be rebuilt using "Enlist=dynamic", a registry string value, named `DynamicEnlistment`, of type `REG_SZ`, should be created and set to 1 under `HKEY_LOCAL_MACHINE\SOFTWARE\ORACLE\ODP.NET\Assembly_Version` where `Assembly_Version` is the full assembly version number of `Oracle.DataAccess.dll`.

If ODP.NET is properly installed, there should already be registry string values such as `StatementCacheSize`, `TraceFileName`, and so forth, under the same ODP.NET key. Dynamic Enlistment can also be configured through an XML configuration file. For details, see "[Configuring Oracle Data Provider for .NET](#)" on page 2-9.

If the `DynamicEnlistment` registry key is set to 0 (or if the registry entry does not exist), it does not affect the application in any way. However, if `DynamicEnlistment` is set to 1, "Enlist=false" is treated the same as "Enlist=dynamic", enabling applications to enlist successfully through the `EnlistDistributedTransaction` method without any code change. Having `DynamicEnlistment` set to 1 does not affect `OracleConnection` objects that have "Enlist=true" or "Enlist=dynamic" in the connection string.

See Also:

- "[Connection String Attributes](#)" on page 3-5
- "[EnlistDistributedTransaction](#)" on page 6-113

Client Identifier and End-to-End Tracing

The client identifier is a predefined attribute from the Oracle application context namespace `USERENV`. It is similar to proxy authentication because it can enable tracking of user identities. However, client identifier does not require the creation of two sessions (one for the proxy user and another for the end user) as proxy authentication does. In addition, the client identifier does not have to be a database user. It can be set to any string. But most importantly, by using client identifier, ODP.NET developers can use application context and Oracle Label Security, and configure Oracle Virtual Private Database (VPD) more easily. To set the client identifier, ODP.NET applications can set the `ClientId` property on the `OracleConnection` object after opening a connection. If connection pooling is enabled, the `ClientId` is reset to null whenever a connection is placed back into the pool.

The client identifier can also be used for end-to-end application tracing. End-to-end tracing simplifies the process of diagnosing performance problems in multitier environments. In multitier environments, a request from an end client is routed to different database sessions by the middle tier making it difficult to track a client across different database sessions. End-to-end tracing uses the client identifier to uniquely trace a specific end-client through all tiers to the database server.

ODP.NET exposes the `ActionName`, `ClientId`, `ClientInfo`, and `ModuleName` write-only properties on the `OracleConnection` object. These properties correspond to the following end-to-end tracing attributes:

- `Action` - Specifies an action, such as an `INSERT` or `UPDATE` operation, in a module
- `ClientId` - Specifies an end user based on the logon ID, such as `HR.HR`
- `Client info` - Specifies user session information
- `Module` - Specifies a functional block, such as Accounts Receivable or General Ledger, of an application

See Also:

- ["OracleConnection Properties"](#) on page 6-92
- ["End-to-End Application Tracing" in the *Oracle Database Performance Tuning Guide*](#)
- [Oracle Database Security Guide](#)

Transparent Application Failover (TAF) Callback Support

Transparent Application Failover (TAF) is a feature in Oracle Database that provides high availability.

Note: ODP.NET, Managed Driver does not support TAF nor TAF callbacks.

TAF enables an application connection to automatically reconnect to another database instance if the connection gets severed. Active transactions roll back, but the new database connection, made by way of a different node, is identical to the original. This is true regardless of how the connection fails.

With TAF, a client notices no loss of connection as long as there is one instance left serving the application. The database administrator controls which applications run on which instances, and also creates a failover order for each application.

When a session fails over to another database, the NLS settings that were initially set on the original session are not carried over to the new session. Therefore, it is the responsibility of the application to set these NLS settings on the new session.

TAF Notification

Given the delays that failovers can cause, applications may wish to be notified by a TAF callback. ODP.NET supports the TAF callback function through the `Failover` event of the `OracleConnection` object, which allows applications to be notified whenever a failover occurs. To receive TAF callbacks, an event handler function must be registered with the `Failover` event.

When Failover Occurs

When a failover occurs, the `Failover` event is raised and the registered event handler is invoked several times during the course of reestablishing the connection to another Oracle instance.

The first call to the event handler occurs when Oracle Database First detects an instance connection loss. This allows the application to act accordingly for the upcoming delay for the failover.

If the failover is successful, the `Failover` event is raised again when the connection is reestablished and usable. At this time, the application can resynchronize the `OracleGlobalization` session setting and inform the application user that a failover has occurred.

If failover is unsuccessful, the `Failover` event is raised to inform the application that a failover did not take place.

The application can determine whether or not the failover is successful by checking the `OracleFailoverEventArgs` object that is passed to the event handler.

Registering an Event Handler for Failover

The following example registers an event handler method called `OnFailover`:

```
// C#

using System;
using Oracle.DataAccess.Client;

class TAFCallbackSample
{
    public static FailoverReturnCode OnFailover(object sender,
                                                OracleFailoverEventArgs eventArgs)
    {
        switch (eventArgs.FailoverEvent)
        {
            case FailoverEvent.Begin :
                Console.WriteLine(
                    "\nFailover Begin - Failing Over ... Please standby\n");
                Console.WriteLine(
                    " Failover type was found to be " + eventArgs.FailoverType);
                break;

            case FailoverEvent.Abort :
                Console.WriteLine(" Failover aborted. Failover will not take place.\n");
                break;

            case FailoverEvent.End :
                Console.WriteLine(" Failover ended ...resuming services\n");
                break;

            case FailoverEvent.Reauth :
                Console.WriteLine(" Failed over user. Resuming services\n");
                break;

            case FailoverEvent.Error :
                Console.WriteLine(" Failover error gotten. Sleeping...\n");
                return FailoverReturnCode.Retry;

            default :
                Console.WriteLine("Bad Failover Event: %d.\n", eventArgs.FailoverEvent);
        }
    }
}
```

```
        break;
    }
    return FailoverReturnCode.Success;
} /* OnFailover */

static void Main()
{
    OracleConnection con = new OracleConnection();

    con.ConnectionString = "User Id=scott;Password=tiger;Data Source=oracle;";
    con.Open();
    con.Failover += new OracleFailoverEventHandler(OnFailover);
    Console.WriteLine("Event Handler is successfully registered");

    // Close and Dispose OracleConnection object
    con.Close();
    con.Dispose();
}
}
```

The `Failover` event invokes only one event handler. If multiple `Failover` event handlers are registered with the `Failover` event, only the event handler registered last is invoked.

Note: Distributed transactions are not supported in an environment where failover is enabled.

See Also:

- *Oracle Database Net Services Administrator's Guide*
- ["OracleFailoverEventHandler Delegate"](#) on page 11-10
- ["OracleFailoverEventArgs Class"](#) on page 11-2

Real Application Clusters and Global Data Services

This section discusses optimizations for the following products:

- Oracle Real Application Clusters (Oracle RAC) is a cluster database with a shared cache architecture that overcomes the limitations of traditional shared-nothing and shared-disk approaches to provide highly scalable and available database solutions for business applications. See *Oracle Real Application Clusters Administration and Deployment Guide*.
- Oracle Data Guard provides one or more standby databases to protect Oracle data from failures, disasters, human error, and data corruptions for high availability in mission critical applications. See *Oracle Data Guard Concepts and Administration*.
- Oracle GoldenGate replicates data among heterogeneous data environments. It enables high availability solutions, real-time data integration, transactional change data capture, data replication, transformations, and verification between operational and analytical enterprise systems. See *Oracle Database High Availability Overview*.
- Global Data Services (GDS), new in Oracle Database 12c, provides database workload management features across replicated databases, such as Data Guard and GoldenGate.

ODP.NET supports Oracle Real Application Clusters (Oracle RAC), Data Guard, and GoldenGate transparently, meaning you do not need to change ODP.NET code to use these Oracle components. To further take advantage of these technologies, ODP.NET offers connection pooling optimization features for achieving better application high availability and performance. You can do this through configuring ODP.NET to receive, respond, and send database status messages to .NET applications.

These optimization configurations include the use of features such as Fast Application Notification (FAN), Runtime Connection Load Balancing, and Fast Connection Failover (FCF).

These connection pooling optimizations can improve high availability and performance for Oracle Real Application Clusters and Global Data Services products:

- [Fast Application Notification](#)
- [Runtime Connection Load Balancing](#)
- [Fast Connection Failover \(FCF\)](#)

Fast Application Notification

Fast Application Notification (FAN) is a high availability and load balancing notification mechanism that Oracle RAC, Data Guard, and GoldenGate use to notify ODP.NET applications about cluster configuration and service-level information, including status changes such as UP or DOWN events and server load. FAN UP and DOWN events can apply to instances, services, and nodes. Based on information received, ODP.NET can adjust its connection pool accordingly to improve application availability and performance. See *Oracle Real Application Clusters Administration and Deployment Guide* for more information about FAN.

With FAN, Oracle RAC, Data Guard, and GoldenGate use one of two Oracle messaging infrastructures to send notifications to ODP.NET applications:

- Oracle Notification Service (ONS)
- Oracle Streams Advanced Queueing (AQ).

[Table 3–4](#) describes when each messaging system is used and the ODP.NET-related client configuration.

Table 3–4 Configurations for ODP.NET Driver Types

| ODP.NET Driver Type | Database Server Version | FAN Infrastructure | Configuration | Manual ONS Configuration Locations |
|---------------------|-------------------------|--------------------|---------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| managed | 12.1 and later | ONS | Automatic or Manual | Either of these two files: <ul style="list-style-type: none"> ■ .NET configuration file ■ ONS configuration file |
| managed | 11.2 and earlier | ONS | Manual | Either of these two files: <ul style="list-style-type: none"> ■ .NET configuration file ■ ONS configuration file |
| unmanaged | 12.1 and later | ONS | Automatic or Manual | oraaccess.xml file |
| unmanaged | 11.2 and earlier | AQ | Automatic | N/A |

To configure the .NET configuration file, see "[onsConfig section](#)" on page 2-26. To configure the ONS configuration file, see "[Client Side ONS Daemon Configuration](#)" on page 2-27. To configure `oraaccess.xml`, see *Oracle Call Interface Programmer's Guide*.

See "[Configuring a Port to Listen for Database Notifications](#)" on page 2-31 for more information on AQ configuration for FAN.

For automatic ONS configuration, developers can add more nodes and ports for ODP.NET to listen to, in addition to the nodes and ports that ODP.NET obtains from the database automatically.

ODP.NET applications do not require code changes to migrate from the AQ to ONS FAN infrastructure. However, some ODP.NET client configuration changes may be necessary when migrating to ONS, a newer database server version, or from ODP.NET, Unmanaged Driver to the managed driver, as documented above.

On the database server side, FAN must be set up and configured.

Using FAN Messages from the database, ODP.NET can do the following:

- With Runtime Connection Load Balancing, ODP.NET load balances connections among Oracle RAC nodes, services, and service members and GDS resources. This feature improves ODP.NET response time and ensures better resource allocation of server resources. See "[Runtime Connection Load Balancing](#)" on page 3-26.
- With the Fast Connection Failover (FCF) feature, Oracle RAC, Data Guard, and GoldenGate can inform the ODP.NET connection pool if database nodes, services, service members, or the databases have gone down. These DOWN messages indicate which connections in the pool are invalid and must be removed. See *Oracle Database Development Guide*.

Runtime Connection Load Balancing

With Runtime Connection Load Balancing, Oracle Data Provider for .NET balances work requests across Oracle RAC instances based on the load balancing advisory and service goal. Because workloads can constantly change, load balancing occurs when the application requests a new connection. Thus, ODP.NET optimizes service levels by connecting users to the least loaded nodes in real-time.

In Oracle Database 12c, Runtime Connection Load Balancing has been extended to Oracle Data Guard and Oracle GoldenGate so that ODP.NET 12c connections can be load balanced with these two database services as part of Global Data Services. No ODP.NET applications require code changes to use Global Data Services if they are already using Runtime Connection Load Balancing.

When Runtime Connection Load Balancing is enabled:

- The ODP.NET connection pool dispenses connections based on the load balancing advisory and service goal.
- The ODP.NET connection pool also balances the number of connections to each service member providing the service, based on the load balancing advisory and service goal.

By default, this feature is disabled. To enable runtime connection load balancing, include "Load Balancing=true" in the connection string. This feature can only be used if "pooling=true". If "Load Balancing=true" is set and the connection attempts to connect to a single-instance database, an `OracleException` is thrown with an error of "ORA-1031: insufficient privileges." In order to use Runtime Connection Load Balancing, specific Oracle server configurations must be set.

The following connection string example enables Runtime Connection Load Balancing:

```
"user id=scott;password=tiger;data source=erp;load balancing=true;"
```

See Also:

- [Table 3–2, "Supported Connection String Attributes"](#)
- ["Configuring a Port to Listen for Database Notifications"](#) on page 2-31
- *Oracle Database Net Services Administrator's Guide* to set up the Oracle Net configuration that Runtime Connection Load Balancing requires
- *Oracle Real Application Clusters Administration and Deployment Guide* for the required Oracle RAC configuration
- *Oracle Database Global Data Services Concepts and Administration Guide*

Fast Connection Failover (FCF)

When an Oracle RAC service, service member, node, or a Data Guard database fails, the severed ODP.NET connection objects may continue to exist in the application. If users attempt to use these invalid connections, they will encounter errors. FCF enables ODP.NET to free these severed connections proactively and quickly. Users then will be able to use the application after a server side failure without manual intervention from an administrator.

In Oracle Database 12c, FCF has been extended to Oracle Data Guard and Oracle GoldenGate for ODP.NET 12c connections through Global Data Services. No ODP.NET applications require code changes to use Global Data Services if they already use FCF.

ODP.NET applications can enable FCF through the High Availability Events, "HA Events", connection string attribute. When HA Events are enabled:

- ODP.NET connection pool proactively removes connections from the pool when a Global Data Service or Oracle RAC service, service member, node, or database goes down.
- ODP.NET proactively forces threads waiting for responses from the downed database to exit out from the existing call to avoid any hangs. When such a connection is then returned to the pool, any resource associated with that connection is freed.
- ODP.NET establishes connections to existing Oracle instances if the removal of severed connections brings the total number of connections below the "min pool size", upon the next connection request.

By default this feature is disabled. To enable HA events, include "HA Events=true" and "pooling=true" in the connection string.

The following connection string example enables HA Events:

```
"user id=scott;password=tiger;data source=erp;HA events=true;"
```

See Also:

- [Table 3–2, "Supported Connection String Attributes"](#)
- ["Configuring a Port to Listen for Database Notifications"](#) on page 2-31
- *Oracle Database Net Services Administrator's Guide* to set up the Oracle Net configuration that FCF requires
- *Oracle Real Application Clusters Administration and Deployment Guide* for the required Oracle RAC configuration
- *Oracle Database Global Data Services Concepts and Administration Guide*

Using FCF Planned Outage to Minimize Service Disruption

FCF not only provides high availability services for unplanned outages, such as node failures, but also for planned outages, such as server repairs, upgrades, and changes, to minimize service disruption to ODP.NET application users.

When a database service is set to be stopped or relocated, a FAN message is published with a planned reason code. A FCF-aware ODP.NET connection pool ("HA Events=true") receives the notification and commences to close idle connections, no longer allowing new connections to that specific database service. Active connections to that specific database service remain until users complete their tasks and the connection is returned to the pool. Thus, no users must stop work mid-stream due to a planned outage.

Eventually, all users complete their tasks and no connections remain to that database service. The database administrator can then stop the service for the planned outage task. This feature allows the database service to be stopped as quickly as possible without end user disruption.

A typical planned outage scenario is as follows:

1. There is a need to upgrade, patch, or repair a software or hardware issue on a database server. Relocate the service from the instance, then shut down the service on the instance.
2. The FAN planned DOWN event clears idle sessions from the ODP.NET connection pool immediately and marks active sessions to be released at the next check-in. These FAN actions drain the sessions from this instance without disrupting the users.

Existing connections on other instances remain usable, and new connections can be opened to these other instances.

3. Not all sessions, in all cases, will check their connections into the pool. It is best practice to have a timeout period after which the instance is forcibly shut down, evicting any remaining client connections.
4. Once the upgrade, patch, or repair is complete, restart the instance and the service on the original node. ODP.NET can now use the instance again.

Pool Size Attributes in an Oracle RAC Database

When connection pools are created for a single-instance database, pool size attributes are applied to the single service. Similarly, when connection pools are created for an Oracle RAC database, the pool size attributes are applied to a service and not to service members. For example, if "Min Pool Size" is set to *N*, ODP.NET does not create

N connections for each service member. Instead, it creates, at minimum, N connections for the entire service, where N connections are distributed among the service members.

The following pool size connection string attributes are applied to a service.

- Min Pool Size
- Max Pool Size
- Incr Pool Size
- Decr Pool Size

Using Transaction Guard to Prevent Logical Corruption

Transaction Guard allows ODP.NET applications to use at-most-once execution in case of planned and unplanned outages and repeated submissions.

ODP.NET returns a logical transaction object, `OracleLogicalTransaction`, which is used to determine the outcome of the last open transaction in a database session following an outage. Without Transaction Guard, applications that attempt to retry operations following outages can cause logical corruption by committing duplicate transactions.

After an outage, one of the traditional problems for recovering applications had been the non-durable commit message sent back to the client. If there is a break between the client and the server, the client sees an error message indicating that the communication failed (also known as a recoverable error). This error does not inform the application if the submission executed any commit operations, or if a procedural call ran to completion while executing all expected commits. The error also does not indicate session state changes or intermittent failures. The client is left wondering if the transaction committed and if it fully completed.

These recoverable errors can cause end users or applications to attempt replay by issuing duplicate transaction submissions or other forms of *logical corruption*. The transaction cannot be validly resubmitted if the non-transactional state is incorrect or if it is committed. Continuing to process a committed but not completed call can result in the application using a database session that is in the wrong state.

Transaction Guard allows ODP.NET to eliminate duplicate transactions automatically and transparently, and in a manner that scales. ODP.NET uses the logical transaction object to identify the last open transaction. At runtime, Oracle retains the transaction status automatically. At commit, the logical transaction object persists. The database maintains the logical transaction status post-commit for as long as the administrator has set the retention period. ODP.NET can then use the logical transaction object to track the next transaction.

When a failure occurs, such as a node, network, or database failure, ODP.NET applications can deterministically conclude whether the transaction committed by querying its status using the logical transaction object. If not committed, the ODP.NET application can learn what state the transaction is in and whether it is recoverable and can be retried through the returned `OracleException`. ODP.NET applications can then take the appropriate action, such as resubmitting the transaction if it is not committed.

Note:

- ODP.NET, Unmanaged Driver supports Transaction Guard and recoverable error detection. ODP.NET, Managed Driver currently does not support either.
- Transaction Guard supports only local transactions. It does not support distributed transactions.

The Transaction Guard feature is enabled or disabled through the Oracle service-level configuration through the `COMMIT_OUTCOME` setting. By default, it is not enabled. This setting can be changed without bringing down the database. Only new connections created against the service will use the new setting.

The following is an example ODP.NET Transaction Guard application scenario:

An ODP.NET application receives a FAN down event or error. FAN automatically aborts the dead session and the application receives an `OracleException`. A Transaction Guard application built to handle errors transparently would do the following:

1. Check the value of the `OracleException.IsRecoverable` property. If the value is true, that application can choose to re-submit the existing transaction based on the current transaction status as described in the following steps. If the value is false, the application should roll-back, re-execute, and re-submit the current transaction.

2. The application retrieves the last logical transaction from the failed session.

```
OracleConnection.OracleLogicalTransaction
```

3. The application retrieves the transaction status, `OracleLogicalTransaction.GetOutcome()`.

Note: Grant the `EXECUTE` privilege on the `DBMS_APP_CONT` package to the database users that retrieve the transaction status.

4. The transaction status indicates two aspects of the outcome:
 - Did it commit successfully? `OracleLogicalTransaction.Committed`
 - Did it complete successfully? `OracleLogicalTransaction.UserCallCompleted`

| Committed Value | UserCallCompleted Value | Outcome |
|-----------------|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| True | True | The transaction was successful. The result can be returned to the application. |
| False | False | The transaction was not successful. The application can resubmit the transaction again. |
| True | False | The transaction committed, but there may be additional state, such as row counts or nested PL/SQL logic, that prevents the application from continuing as expected. |

Sample Code

```
using System;
```

```
using Oracle.DataAccess.Client;

class Test
{
    static void Main()
    {
        bool bReadyToCommit = false;
        string constr = "user id=scott;password=tiger;data source=inst1";
        OracleConnection con = new OracleConnection(constr);
        OracleTransaction txn = null;
        OracleCommand cmd = null;

        try
        {
            con.Open();
            txn = con.BeginTransaction();
            cmd = new OracleCommand(con, "update emp set dept=10 where empno=7654");
            cmd.ExecuteNonQuery();
            bReadyToCommit = true;
        }
        catch(Exception ex)
        {
            Console.WriteLine(ex.ToString());
        }

        try
        {
            if (bReadyToCommit)
                txn.Commit();
        }
        catch(Exception ex)
        {
            if (ex.IsRecoverable)
            {
                OracleLogicalTransaction olt = con.OracleLogicalTransaction;
                olt.GetOutcome(); // or olt.GetOutcome("scott", "tiger", "inst1");

                if (!olt.Committed && !olt.UserCallCompleted)
                {
                    // any chosen processing here if a retry is desired.
                }
                else
                {
                    // transaction committed, but was not full completed
                }
            }
            else
            {
                // Not recoverable transaction. Rollback (and re-execute).
            }
        }
        finally
        {
            txn.Dispose();
            cmd.Dispose();
            con.Dispose();
        }
    }
}
```

See Also:

- ["OracleLogicalTransactionStatus Class"](#) on page 6-310
- ["GetLogicalTransactionStatus"](#) on page 6-117
- ["LogicalTransactionId"](#) on page 6-103
- ["IsRecoverable"](#) on page 6-289
- *Oracle Database Development Guide* for more information on Transaction Guard

OracleCommand Object

The `OracleCommand` object represents SQL statements or stored procedures executed on Oracle Database.

Note: Optimizer hint syntax in the form `--+ ...` is not supported. ODP.NET supports this syntax: `/*+ ... */`.

This section includes the following topics:

- [Transactions](#)
- [System.Transactions and Promotable Transactions](#)
- [Parameter Binding](#)
- [Batch Processing](#)
- [Statement Caching](#)
- [Self-Tuning](#)

Transactions

Oracle Database starts a transaction only in the context of a connection. Once a transaction starts, all the successive command execution on that connection run in the context of that transaction. Transactions can be started only on an `OracleConnection` object, and the read-only `Transaction` property on the `OracleCommand` object is implicitly set by the `OracleConnection` object. Therefore, the application cannot set the `Transaction` property, nor does it need to.

Note: Transactions are not supported in a .NET stored procedure.

Explicit transactions are required with SQL statements containing "FOR UPDATE" and "RETURNING" clauses. This is not necessary if global transactions are used.

System.Transactions and Promotable Transactions

ODP.NET supports `System.Transactions`. A local transaction is created for the first connection opened in the `System.Transactions` scope to Oracle Database 11g release 1 (11.1), or higher. When a second connection is opened, this transaction is automatically promoted to a distributed transaction. This functionality provides enhanced performance and scalability.

Connections created within a transaction context, such as `TransactionScope` or `ServicedComponent`, can be established to different versions of Oracle Database. However, in order to enable the local transaction to be promotable, the following must be true:

- The first connection in the transaction context must be established to an Oracle Database 11g release 1(11.1) instance or higher.
- All connections opened within the transaction context must have the "Promotable Transaction" setting set to "promotable". If you try to open a subsequent connection in the same transaction context with the "Promotable Transaction" setting set to "local", an exception is thrown.
- Promoting local transactions requires Oracle Services for Microsoft Transaction Server 11.1.0.7.20, or higher. If this requirement is not met, then a second connection request in the same transaction context throws an exception.

Transaction promotion will throw an ORA-24797 error when the database transaction is already distributed due to the use of database links.

Setting "local" as the value of "PromotableTransaction" in the registry, configuration file (machine/Web/application), or the "Promotable Transaction" connection string attribute allows only one connection to be opened in the transaction context, which is associated with a local transaction. Such local transactions cannot be promoted. Starting with ODP.NET 12.1.0.2, connections with the `Promotable Transaction` setting set to `local` will begin as and remain a local transaction. If a second connection attempts to join the transaction, an exception will be thrown.

For applications connecting to a pre-Oracle Database 11g release 1 (11.1) instance, refer to "[Local Transaction Support for Older Databases](#)" on page 3-36. This section describes how ODP.NET behavior can be controlled using the "Promotable Transaction" setting.

If applications use `System.Transactions`, it is required that the `enlist` connection string attribute is set to either `true` (default) or `dynamic`. However, `enlist=dynamic` cannot be used with `TransactionScope` because auto-enlistment requires `enlist=true`.

ODP.NET supports the following `System.Transactions` programming models for applications using distributed transactions.

- [Implicit Transaction Enlistment Using TransactionScope](#)
- [Explicit Transaction Enlistment Using CommittableTransaction](#).
- [Local Transaction Support for Older Databases](#)

Implicit Transaction Enlistment Using TransactionScope

The `TransactionScope` class provides a mechanism to write transactional applications where the applications do not need to explicitly enlist in transactions.

To accomplish this, the application uses the `TransactionScope` object to define the transactional code. Connections created within this transactional scope will enlist in a local transaction that can be promoted to a distributed transaction.

Note:

If the first connection is opened to a pre-Oracle Database 11g release 1 (11.1) instance, then the connection enlists as a distributed transaction, by default.

You can optionally create the transaction as a local transaction by using the procedure described in "[Local Transaction Support for Older Databases](#)" on page 36. However, these transactions cannot be promoted to distributed transactions.

Note that the application must call the `Complete` method on the `TransactionScope` object to commit the changes. Otherwise, the transaction is aborted by default.

```
// C#

using System;
using Oracle.DataAccess.Client;
using System.Data;
using System.Data.Common;
using System.Transactions;

class psfTxnScope
{
    static void Main()
    {
        int retVal = 0;
        string providerName = "Oracle.DataAccess.Client";
        string constr =
            @"User Id=scott;Password=tiger;Data Source=oracle;enlist=true";

        // Get the provider factory.
        DbProviderFactory factory = DbProviderFactories.GetFactory(providerName);

        try
        {
            // Create a TransactionScope object, (It will start an ambient
            // transaction automatically).
            using (TransactionScope scope = new TransactionScope())
            {
                // Create first connection object.
                using (DbConnection conn1 = factory.CreateConnection())
                {
                    // Set connection string and open the connection. this connection
                    // will be automatically enlisted in a promotable local transaction.
                    conn1.ConnectionString = constr;
                    conn1.Open();

                    // Create a command to execute the sql statement.
                    DbCommand cmd1 = factory.CreateCommand();
                    cmd1.Connection = conn1;
                    cmd1.CommandText = @"insert into emp (empno, ename, job) values
                                        (1234, 'emp1', 'dev1)";

                    // Execute the SQL statement to insert one row in DB.
                    retVal = cmd1.ExecuteNonQuery();
                    Console.WriteLine("Rows to be affected by cmd1: {0}", retVal);

                    // Close the connection and dispose the command object.
```



```

        conn1.Close();
        conn1.Dispose();
        cmd1.Dispose();
    }

    // The Complete method commits the transaction. If an exception has
    // been thrown or Complete is not called then the transaction is
    // rolled back.
    scope.Complete();
}
}
}
catch (Exception ex)
{
    Console.WriteLine(ex.Message);
    Console.WriteLine(ex.StackTrace);
}
}
}
}

```

Explicit Transaction Enlistment Using CommittableTransaction

The instantiation of the `CommittableTransaction` object and the `EnlistTransaction` method provides an explicit way to create and enlist in a transaction.

Note that the application must call `Commit` or `Rollback` on the `CommittableTransaction` object.

```

// C#

using System;
using Oracle.DataAccess.Client;
using System.Data;
using System.Data.Common;
using System.Transactions;

class psfEnlistTransaction
{
    static void Main()
    {
        int retVal = 0;
        string providerName = "Oracle.DataAccess.Client";
        string constr =
            @"User Id=scott;Password=tiger;Data Source=oracle;enlist=dynamic";

        // Get the provider factory.
        DbProviderFactory factory = DbProviderFactories.GetFactory(providerName);

        try
        {
            // Create a committable transaction object.
            CommittableTransaction cmtTx = new CommittableTransaction();

            // Open a connection to the DB.
            DbConnection conn1 = factory.CreateConnection();
            conn1.ConnectionString = constr;
            conn1.Open();

            // enlist the connection with the committable transaction.
            conn1.EnlistTransaction(cmtTx);

            // Create a command to execute the sql statement.

```

```
DbCommand cmd1 = factory.CreateCommand();
cmd1.Connection = conn1;
cmd1.CommandText = @"insert into emp (empno, ename, job) values
                    (1234, 'emp1', 'dev1')";

// Execute the SQL statement to insert one row in DB.
retVal = cmd1.ExecuteNonQuery();
Console.WriteLine("Rows to be affected by cmd1: {0}", retVal);

// commit/rollback the transaction.
cmtTx.Commit(); // commits the txn.
//cmtTx.Rollback(); // rolls back the txn.

// close and dispose the connection
conn1.Close();
conn1.Dispose();
cmd1.Dispose();
}
catch (Exception ex)
{
    Console.WriteLine(ex.Message);
    Console.WriteLine(ex.StackTrace);
}
}
```

See Also: ["EnlistTransaction"](#) on page 6-115

Local Transaction Support for Older Databases

If the first connection in a `TransactionScope` is opened to a pre-Oracle Database 11g release 1 (11.1) instance, then the connection creates a distributed transaction, by default. You can optionally have the first connection create a local transaction by using the procedure described in this section.

To create local transactions in a `System.Transactions` scope, either the `PromotableTransaction` setting in the registry, machine/`Web/application` configuration file, or the "Promotable Transaction" connection string attribute must be set to "local".

If "local" is specified, the first connection opened in the `TransactionScope` uses a local transaction. If any subsequent connections are opened within the same `TransactionScope`, an exception is thrown. If there are connections already opened in the `TransactionScope`, and an `OracleConnection` with "Promotable Transaction=local" attempts to open within the same `TransactionScope`, an exception is thrown.

If "promotable" is specified, the first and all subsequent connections opened in the same `TransactionScope` enlist in the same distributed transaction.

If both the registry and the connection string attribute are used and set to different values, the connection string attribute overrides the registry entry value. If neither are set, "promotable" is used. This is the default value and is equivalent to previous versions of ODP.NET which only supported distributed transactions.

The registry entry for a particular version of ODP.NET applies for all applications using that version of ODP.NET.

Parameter Binding

When the `DbType` property of an `OracleParameter` object is set, the `OracleDbType` property of the `OracleParameter` object changes accordingly, or vice versa. The parameter set last prevails.

An application can bind the data and have ODP.NET infer both the `DbType` and `OracleDbType` properties from the .NET type of the parameter value.

ODP.NET allows applications to obtain an output parameter as either a .NET Framework type or an ODP.NET type. The application can specify which type to return for an output parameter by setting the `DbType` property of the output parameter (.NET type) or the `OracleDbType` property (ODP.NET type) of the `OracleParameter` object. For example, if the output parameter is set as a `DbType.String` type by setting the `DbType` property, the output data is returned as a .NET `String` type. On the other hand, if the parameter is set as an `OracleDbType.Char` type by setting the `OracleDbType` property, the output data is returned as an `OracleString` type. If both `DbType` and `OracleDbType` properties are set before the command execution, the last setting takes affect.

ODP.NET populates `InputOutput`, `Output`, and `ReturnValue` parameters with the Oracle data, through the execution of the following `OracleCommand` methods:

- `ExecuteReader`
- `ExecuteNonQuery`
- `ExecuteScalar`

An application should not bind a value for output parameters; it is the responsibility of ODP.NET to create the value object and populate the `OracleParameter.Value` property with the object.

When binding by position (default) to a function, ODP.NET expects the return value to be bound first, before any other parameters.

This section describes the following:

- [OracleDbType Enumeration Type](#)
- [Inference of DbType, OracleDbType, and .NET Types](#)
- [PL/SQL Associative Array Binding](#)
- [Array Binding](#)

See Also: ["OracleDbType Enumeration"](#) on page 6-426

OracleDbType Enumeration Type

`OracleDbType` enumerated values are used to explicitly specify the `OracleDbType` value of an `OracleParameter` object.

[Table 3–5](#) lists all the `OracleDbType` enumeration values with a description of each enumerated value.

Table 3–5 OracleDbType Enumeration Values

| Member Name | Description |
|--------------------|-------------------------------------------------------------------------------------------------------------|
| <code>Array</code> | Oracle Collection (<code>VArray</code> or Nested Table) <i>Not Available in ODP.NET, Managed Driver</i> |
| <code>BFile</code> | Oracle BFILE type |

Table 3–5 (Cont.) OracleDbType Enumeration Values

| Member Name | Description |
|--------------|------------------------------------------------------------------------|
| BinaryFloat | Oracle BINARY_FLOAT type |
| BinaryDouble | Oracle BINARY_DOUBLE type |
| Blob | Oracle BLOB type |
| Boolean | Oracle BOOLEAN type <i>Not Available in ODP.NET, Managed Driver</i> |
| Byte | byte type |
| Char | Oracle CHAR type |
| Clob | Oracle CLOB type |
| Date | Oracle DATE type |
| Decimal | Oracle NUMBER type |
| Double | 8-byte FLOAT type |
| Int16 | 2-byte INTEGER type |
| Int32 | 4-byte INTEGER type |
| Int64 | 8-byte INTEGER type |
| IntervalDS | Oracle INTERVAL DAY TO SECOND type |
| IntervalYM | Oracle INTERVAL YEAR TO MONTH type |
| Long | Oracle LONG type |
| LongRaw | Oracle LONG RAW type |
| NChar | Oracle NCHAR type |
| Object | Oracle Object type <i>Not Available in ODP.NET, Managed Driver</i> |
| NClob | Oracle NCLOB type |
| NVarchar2 | Oracle NVARCHAR2 type |
| Raw | Oracle RAW type |
| Ref | Oracle REF type <i>Not Available in ODP.NET, Managed Driver</i> |
| RefCursor | Oracle REF CURSOR type |
| Single | 4-byte FLOAT type |
| TimeStamp | Oracle TIMESTAMP type |
| TimeStampLTZ | Oracle TIMESTAMP WITH LOCAL TIME ZONE type |
| TimeStampTZ | Oracle TIMESTAMP WITH TIME ZONE type |
| Varchar2 | Oracle VARCHAR2 type |
| XmlType | Oracle XMLType type <i>Not Available in ODP.NET, Managed Driver</i> |

Note: PL/SQL LONG, LONG RAW, RAW, and VARCHAR data types can be bound with a size up to 32512 bytes.

Inference of DbType, OracleDbType, and .NET Types

This section explains the inference from the `System.Data.DbType`, `OracleDbType`, and `Value` properties in the `OracleParameter` class.

In the `OracleParameter` class, `DbType`, `OracleDbType`, and `Value` properties are linked. Specifying the value of any of these properties infers the value of one or more of the other properties.

Inference of DbType from OracleDbType In the `OracleParameter` class, specifying the value of `OracleDbType` infers the value of `DbType` as shown in [Table 3–6](#).

Table 3–6 Inference of System.Data.DbType from OracleDbType

| OracleDbType | System.Data.DbType |
|--------------|--------------------|
| Array | Object |
| BFile | Object |
| Blob | Object |
| BinaryFloat | Single |
| BinaryDouble | Double |
| Boolean | Boolean |
| Byte | Byte |
| Char | StringFixedLength |
| Clob | Object |
| Date | Date |
| Decimal | Decimal |
| Double | Double |
| Int16 | Int16 |
| Int32 | Int32 |
| Int64 | Int64 |
| IntervalDS | Object |
| IntervalYM | Int64 |
| Long | String |
| LongRaw | Binary |
| NChar | StringFixedLength |
| NClob | Object |
| NVarchar2 | String |
| Object | Object |
| Raw | Binary |
| Ref | Object |
| RefCursor | Object |
| Single | Single |
| TimeStamp | DateTime |
| TimeStampLTZ | DateTime |

Table 3–6 (Cont.) Inference of System.Data.DbType from OracleDbType

| OracleDbType | System.Data.DbType |
|--------------|--------------------|
| TimeStampTZ | DateTime |
| Varchar2 | String |
| XmlType | String |

Inference of OracleDbType from DbType In the OracleParameter class, specifying the value of DbType infers the value of OracleDbType as shown in [Table 3–7](#).

Table 3–7 Inference of OracleDbType from DbType

| System.Data.DbType | OracleDbType |
|--------------------|----------------------|
| Binary | Raw |
| Boolean | Boolean |
| Byte | Byte |
| Currency | <i>Not Supported</i> |
| Date | Date |
| DateTime | TimeStamp |
| Decimal | Decimal |
| Double | Double |
| Guid | <i>Not Supported</i> |
| Int16 | Int16 |
| Int32 | Int32 |
| Int64 | Int64 |
| Object | Object |
| Sbyte | <i>Not Supported</i> |
| Single | Single |
| String | Varchar2 |
| StringFixedLength | Char |
| Time | TimeStamp |
| UInt16 | <i>Not Supported</i> |
| UInt32 | <i>Not Supported</i> |
| UInt64 | <i>Not Supported</i> |
| VarNumeric | <i>Not Supported</i> |

Inference of DbType and OracleDbType from Value In the OracleParameter class, Value is an object type that can be of any .NET Framework data type or ODP.NET type. If the OracleDbType and DbType properties of the OracleParameter class are not specified, the OracleDbType property is inferred from the type of the Value property.

[Table 3–8](#) shows the inference of DbType and OracleDbType properties from the Value property when the type of Value is one of the .NET Framework data types.

Table 3–8 Inference of DbType and OracleDbType from Value (.NET Datatypes)

| Value (.NET Datatypes) | System.Data.DbType | OracleDbType |
|------------------------|--------------------|--------------|
| Boolean | Boolean | Boolean |
| Byte | Byte | Byte |
| Byte[] | Binary | Raw |
| Char / Char [] | String | Varchar2 |
| DateTime | DateTime | TimeStamp |
| Decimal | Decimal | Decimal |
| Double | Double | Double |
| Float | Single | Single |
| Int16 | Int16 | Int16 |
| Int32 | Int32 | Int32 |
| Int64 | Int64 | Int64 |
| IOracleCustomType | Object | Object |
| Single | Single | Single |
| String | String | Varchar2 |
| TimeSpan | Object | IntervalDS |

Note: Using other .NET Framework data types as values for the OracleParameter class without specifying either the DbType or the OracleDbType properties raises an exception because inferring DbType and OracleDbType properties from other .NET Framework data types is not supported.

Table 3–9 shows the inference of DbType and OracleDbType properties from the Value property when type of Value is one of Oracle.DataAccess.Types.

Table 3–9 Inference of DbType and OracleDbType from Value (ODP.NET Types)

| Value (Oracle.DataAccess.Types) | System.Data.DbType | OracleDbType |
|---------------------------------|--------------------|--------------|
| OracleBFile | Object | BFile |
| OracleBinary | Binary | Raw |
| OracleBlob | Object | Blob |
| OracleBoolean | Boolean | Boolean |
| OracleClob | Object | Clob |
| OracleDate | Date | Date |
| OracleDecimal | Decimal | Decimal |
| OracleIntervalDS | Object | IntervalDS |
| OracleIntervalYM | Int64 | IntervalYM |
| OracleRef | Object | Ref |
| OracleRefCursor | Object | RefCursor |

Table 3–9 (Cont.) Inference of DbType and OracleDbType from Value (ODP.NET Types)

| Value (Oracle.DataAccess.Types) | System.Data.DbType | OracleDbType |
|--------------------------------------------|---------------------------|---------------------|
| OracleString | String | Varchar2 |
| OracleTimeStamp | DateTime | TimeStamp |
| OracleTimeStampLTZ | DateTime | TimeStampLTZ |
| OracleTimeStampTZ | DateTime | TimeStampTZ |
| OracleXmlType | String | XmlType |

PL/SQL Associative Array Binding

ODP.NET supports PL/SQL Associative Arrays (formerly known as PL/SQL Index-By Tables) binding.

An application can bind an `OracleParameter` object, as a PL/SQL Associative Array, to a PL/SQL stored procedure. The following `OracleParameter` properties are used for this feature:

- `CollectionType`
This property must be set to `OracleCollectionType.PLSQLAssociativeArray` to bind a PL/SQL Associative Array.
- `ArrayBindSize`
This property is ignored for the fixed-length element types (such as `Int32`).
For variable-length element types (such as `Varchar2`), each element in the `ArrayBindSize` property specifies the size of the corresponding element in the `Value` property.
For Output parameters, InputOutput parameters, and return values, this property must be set for variable-length variables.
Each ODP.NET array element can store up to 2 GB of characters per element or 4 GB of binary data per element
- `ArrayBindStatus`
This property specifies the execution status of each element in the `OracleParameter.Value` property.
- `Size`
This property specifies the maximum number of elements to be bound in the PL/SQL Associative Array.
- `Value`
This property must be set to an array of values, `null`, or the `DBNull.Value` property.

ODP.NET supports binding parameters of PL/SQL Associative Arrays which contain the following data types.

- `BINARY_FLOAT`
- `CHAR`
- `DATE`
- `NCHAR`

- NUMBER
- NVARCHAR2
- RAW
- ROWID
- UROWID
- VARCHAR2

Using unsupported data types with associative arrays can cause an ORA-600 error.

Example of PL/SQL Associative Arrays

This example binds three OracleParameter objects as PL/SQL Associative Arrays: Param1 as an In parameter, Param2 as an InputOutput parameter, and Param3 as an Output parameter.

PL/SQL Package: MYPACK

/* Setup the tables and required PL/SQL:

```

connect scott/tiger@oracle
CREATE TABLE T1(COL1 number, COL2 varchar2(20));

CREATE or replace PACKAGE MYPACK AS
  TYPE AssocArrayVarchar2_t is table of VARCHAR(20) index by BINARY_INTEGER;
  PROCEDURE TestVarchar2(
    Param1 IN      AssocArrayVarchar2_t,
    Param2 IN OUT AssocArrayVarchar2_t,
    Param3  OUT AssocArrayVarchar2_t);
END MYPACK;
/

CREATE or REPLACE package body MYPACK as
PROCEDURE TestVarchar2(
  Param1 IN      AssocArrayVarchar2_t,
  Param2 IN OUT AssocArrayVarchar2_t,
  Param3  OUT AssocArrayVarchar2_t)
IS
  i integer;
BEGIN
  -- copy a few elements from Param2 to Param1\n
  Param3(1) := Param2(1);
  Param3(2) := NULL;
  Param3(3) := Param2(3);
  -- copy all elements from Param1 to Param2\n
  Param2(1) := Param1(1);
  Param2(2) := Param1(2);
  Param2(3) := Param1(3);
  -- insert some values to db\n
  FOR i IN 1..3 LOOP
    insert into T1 values(i,Param2(i));
  END LOOP;
END TestVarchar2;
END MYPACK;
/
*/

// C#

```

```
using System;
using System.Data;
using Oracle.DataAccess.Client;

class AssociativeArraySample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();

        con.ConnectionString = "User Id=scott;Password=tiger;Data Source=oracle";
        con.Open();
        Console.WriteLine("Connected to Oracle" + con.ServerVersion);

        OracleCommand cmd = new OracleCommand(
            "begin MyPack.TestVarchar2(:1, :2, :3); end;", con);

        OracleParameter Param1 = cmd.Parameters.Add("1", OracleDbType.Varchar2);
        OracleParameter Param2 = cmd.Parameters.Add("2", OracleDbType.Varchar2);
        OracleParameter Param3 = cmd.Parameters.Add("3", OracleDbType.Varchar2);

        Param1.Direction = ParameterDirection.Input;
        Param2.Direction = ParameterDirection.InputOutput;
        Param3.Direction = ParameterDirection.Output;

        // Specify that we are binding PL/SQL Associative Array
        Param1.CollectionType = OracleCollectionType.PLSQLAssociativeArray;
        Param2.CollectionType = OracleCollectionType.PLSQLAssociativeArray;
        Param3.CollectionType = OracleCollectionType.PLSQLAssociativeArray;

        // Setup the values for PL/SQL Associative Array
        Param1.Value = new string[3] {
            "First Element", "Second Element ", "Third Element "
        };
        Param2.Value = new string[3] {
            "First Element", "Second Element ", "Third Element "
        };
        Param3.Value = null;

        // Specify the maximum number of elements in the PL/SQL Associative Array
        Param1.Size = 3;
        Param2.Size = 3;
        Param3.Size = 3;

        // Setup the ArrayBindSize for Param1
        Param1.ArrayBindSize = new int[3] { 13, 14, 13 };

        // Setup the ArrayBindStatus for Param1
        Param1.ArrayBindStatus = new OracleParameterStatus[3] {
            OracleParameterStatus.Success, OracleParameterStatus.Success,
            OracleParameterStatus.Success};

        // Setup the ArrayBindSize for Param2
        Param2.ArrayBindSize = new int[3] { 20, 20, 20 };

        // Setup the ArrayBindSize for Param3
        Param3.ArrayBindSize = new int[3] { 20, 20, 20 };

        // execute the cmd
        cmd.ExecuteNonQuery();
    }
}
```

```

//print out the parameter's values
Console.WriteLine("parameter values after executing the PL/SQL block");
for (int i = 0; i < 3; i++)
    Console.WriteLine("Param2[{0}] = {1} ", i,
        (cmd.Parameters[1].Value as Array).GetValue(i));

for (int i = 0; i < 3; i++)
    Console.WriteLine("Param3[{0}] = {1} ", i,
        (cmd.Parameters[2].Value as Array).GetValue(i));

// Close and Dispose OracleConnection object
con.Close();
con.Dispose();
Console.WriteLine("Disconnected");
}
}

```

Array Binding

The array bind feature enables applications to bind arrays of a type using the `OracleParameter` class. Using the array bind feature, an application can insert multiple rows into a table in a single database round-trip.

The following example inserts three rows into the `Dept` table with a single database round-trip. The `OracleCommand` `ArrayBindCount` property defines the number of elements of the array to use when executing the statement.

```

// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class ArrayBindSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();
        con.ConnectionString = "User Id=scott;Password=tiger;Data Source=oracle;";
        con.Open();
        Console.WriteLine("Connected successfully");

        int[] myArrayDeptNo = new int[3] { 10, 20, 30 };
        OracleCommand cmd = new OracleCommand();

        // Set the command text on an OracleCommand object
        cmd.CommandText = "insert into dept(deptno) values (:deptno)";
        cmd.Connection = con;

        // Set the ArrayBindCount to indicate the number of values
        cmd.ArrayBindCount = 3;

        // Create a parameter for the array operations
        OracleParameter prm = new OracleParameter("deptno", OracleDbType.Int32);

        prm.Direction = ParameterDirection.Input;
        prm.Value = myArrayDeptNo;

        // Add the parameter to the parameter collection
    }
}

```

```
cmd.Parameters.Add(prm);

// Execute the command
cmd.ExecuteNonQuery();
Console.WriteLine("Insert Completed Successfully");

// Close and Dispose OracleConnection object
con.Close();
con.Dispose();
}
}
```

See Also: ["Value"](#) on page 6-342 for more information

OracleParameter Array Bind Properties The `OracleParameter` class provides two properties for granular control when using the array bind feature:

- `ArrayBindSize`

The `ArrayBindSize` property is an array of integers specifying the maximum size for each corresponding value in an array. The `ArrayBindSize` property is similar to the `Size` property of an `OracleParameter` object, except the `ArrayBindSize` property specifies the size for each value in an array.

Before the execution, the application must populate the `ArrayBindSize` property; after the execution, ODP.NET populates it.

The `ArrayBindSize` property is used only for parameter types that have variable length such as `Clob`, `Blob`, and `Varchar2`. The size is represented in bytes for binary data types, and characters for the Unicode string types. The count for string types does not include the terminating character. The size is inferred from the actual size of the value, if it is not explicitly set. For an output parameter, the size of each value is set by ODP.NET. The `ArrayBindSize` property is ignored for fixed-length data types.

- `ArrayBindStatus`

The `ArrayBindStatus` property is an array of `OracleParameterStatus` values that specify the status of each corresponding value in an array for a parameter. This property is similar to the `Status` property of the `OracleParameter` object, except that the `ArrayBindStatus` property specifies the status for each array value.

Before the execution, the application must populate the `ArrayBindStatus` property. After the execution, ODP.NET populates the property. Before the execution, an application using the `ArrayBindStatus` property can specify a `NULL` value for the corresponding element in the array for a parameter. After the execution, ODP.NET populates the `ArrayBindStatus` property, indicating whether the corresponding element in the array has a null value, or if data truncation occurred when the value was fetched.

Error Handling for Array Binding If an error occurs during an array bind execution, it can be difficult to determine which element in the `Value` property caused the error. ODP.NET provides a way to determine the row where the error occurred, making it easier to find the element in the row that caused the error.

When an `OracleException` object is thrown during an array bind execution, the `OracleErrorCollection` object contains one or more `OracleError` objects. Each of these `OracleError` objects represents an individual error that occurred during the

execution, and contains a provider-specific property, `ArrayBindIndex`, which indicates the row number at which the error occurred.

The following example demonstrates error handling for array binding:

```

/* Database Setup
connect scott/tiger@oracle
drop table depttest;
create table depttest(deptno number(2));
*/

// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class ArrayBindExceptionSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();
        con.ConnectionString = "User Id=scott;Password=tiger;Data Source=oracle;";
        con.Open();

        OracleCommand cmd = new OracleCommand();

        // Start a transaction
        OracleTransaction txn = con.BeginTransaction(IsolationLevel.ReadCommitted);

        try
        {
            int[] myArrayDeptNo = new int[3] { 10, 20000, 30 };
            // int[] myArrayDeptNo = new int[3]{ 10,20,30};

            // Set the command text on an OracleCommand object
            cmd.CommandText = "insert into depttest(deptno) values (:deptno)";
            cmd.Connection = con;

            // Set the ArrayBindCount to indicate the number of values
            cmd.ArrayBindCount = 3;

            // Create a parameter for the array operations
            OracleParameter prm = new OracleParameter("deptno", OracleDbType.Int32);

            prm.Direction = ParameterDirection.Input;
            prm.Value = myArrayDeptNo;

            // Add the parameter to the parameter collection
            cmd.Parameters.Add(prm);

            // Execute the command
            cmd.ExecuteNonQuery();
        }
        catch (OracleException e)
        {
            Console.WriteLine("OracleException {0} occured", e.Message);
            if (e.Number == 24381)
                for (int i = 0; i < e.Errors.Count; i++)
                    Console.WriteLine("Array Bind Error {0} occured at Row Number {1}",
                        e.Errors[i].Message, e.Errors[i].ArrayBindIndex);
        }
    }
}

```

```

        txn.Commit();
    }
    cmd.Parameters.Clear();
    cmd.CommandText = "select count(*) from depttest";

    decimal rows = (decimal)cmd.ExecuteScalar();

    Console.WriteLine("{0} row have been inserted", rows);
    con.Close();
    con.Dispose();
}
}

```

See Also: ["ArrayBindIndex"](#) on page 6-273 for more information

OracleParameterStatus Enumeration Types [Table 3–10](#) lists `OracleParameterStatus` enumeration values.

Table 3–10 OracleParameterStatus Members

| Member Names | Description |
|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Success | For input parameters, indicates that the input value has been assigned to the column. For output parameters, indicates that the provider assigned an intact value to the parameter. |
| NullFetched | Indicates that a NULL value has been fetched from a column or an OUT parameter. |
| NullInsert | Indicates that a NULL value is to be inserted into a column. |
| Truncation | Indicates that truncation has occurred when fetching the data from the column. |

Batch Processing

The `OracleDataAdapter.UpdateBatchSize` property enables batch processing when the `OracleDataAdapter.Update` method is called. `UpdateBatchSize` is a numeric property that indicates how many `DataSet` rows to update the Oracle database for each round-trip.

This enables the developer to reduce the number of round-trips to the database.

See Also: ["UpdateBatchSize"](#) on page 6-174

Statement Caching

Statement caching eliminates the need to parse each SQL or PL/SQL statement before execution by caching server cursors created during the initial statement execution. Subsequent executions of the same statement can reuse the parsed information from the cursor, and then execute the statement without reparsing, for better performance.

In order to see performance gains from statement caching, Oracle recommends caching only those statements that will be repeatedly executed. Furthermore, SQL or PL/SQL statements should use parameters rather than literal values. Doing so takes full advantage of statement caching, because parsed information from parameterized

statements can be reused even if the parameter values change in subsequent executions. However, if the literal values in the statements are different, the parsed information cannot be reused unless the subsequent statements also have the same literal values.

Statement Caching Connection String Attributes

The following connection string attributes control the behavior of the ODP.NET statement caching feature:

- `Statement Cache Size`

This attribute enables or disables ODP.NET statement caching. By default, this attribute is set to 0 (disabled). If it is set to a value greater than 0, ODP.NET statement caching is enabled and the value specifies the maximum number of statements that can be cached for a connection. Once a connection has cached up to the specified maximum cache size, the least recently used cursor is freed to make room to cache the newly created cursor.

If self tuning is enabled, then statement caching is enabled as well. The `Statement Cache Size` is configured automatically in such cases.

- `Statement Cache Purge`

This attribute provides a way for connections to purge all statements that are cached when a connection is closed or placed back into the connection pool. By default, this attribute is set to `false`, which means that cursors are not freed when connections are placed back into the pool.

Enabling Statement Caching through the Registry

To enable statement caching by default for all ODP.NET applications running in a system, without changing the application, set the registry key of `HKEY_LOCAL_MACHINE\SOFTWARE\ORACLE\ODP.NET\Assembly_Version\StatementCacheSize` to a value greater than 0. This value specifies the number of cursors that are to be cached on the server.

The default value for the system can be overridden at the connection pool level. The `Statement Cache Size` attribute can be set to a different size than the registry value or it can be turned off. The `Statement Cache Size` can also be configured through an XML configuration file. For details, see "[Configuring Oracle Data Provider for .NET](#)" on page 2-9.

Statement Caching Methods and Properties

The following property and method are relevant only when statement caching is enabled:

- `OracleCommand.AddToStatementCache` property

If statement caching is enabled, having this property set to `true` (default) adds statements to the cache when they are executed. If statement caching is disabled or if this property is set to `false`, the executed statement is not cached.

- `OracleConnection.PurgeStatementCache` method

This method purges all the cached statements by closing all open cursors on the database that are associated with the particular connection. Note that statement caching remains enabled after this call.

Connections and Statement Caching

Statement caching is managed separately for each connection. Therefore, executing the same statement on different connections requires parsing once for each connection and caching a separate cursor for each connection.

Pooling and Statement Caching

Pooling and statement caching can be used in conjunction. If connection pooling is enabled and the `Statement Cache Purge` attribute is set to `false`, statements executed on each separate connection are cached throughout the lifetime of the pooled connection.

If the `Statement Cache Purge` attribute is set to `true`, all the cached cursors are freed when the connection is placed back into the pool. When connection pooling is disabled, cursors are cached during the lifetime of the connection, but the cursors are closed when the `OracleConnection` object is closed or disposed of.

Self-Tuning

ODP.NET applications can be self-tuned for performance optimization. ODP.NET dynamically monitors application queries during runtime.

Note: Self-tuning for applications does not take place if the `Pooling` connection string attribute is set to `false`. Self-tuning is also not supported inside `.NET` stored procedures.

The statement cache size (`StatementCacheSize`) is tuned automatically by monitoring the statements that are executed by the application. The following sections discuss self-tuning in applications:

- [Self-Tuning Statement Caching](#)
- [Enabling or Disabling Self-Tuning for Applications](#)
- [Tracing Optimization Changes](#)

Self-Tuning Statement Caching

Statement caching helps improve performance by eliminating the need to re-parse each SQL or PL/SQL statement before execution.

If self-tuning is enabled for an application, then ODP.NET continuously monitors application behavior in order to determine the optimum value for the statement cache size. Any statement cache size value specified in the connection string, configuration file, or registry is ignored.

When the application first initializes, it uses the default value of statement cache size. As the application executes statements, ODP.NET collects statistics that are used to self-tune the value of statement cache size. Self-tuning of statement cache size results in increased performance.

Note: To take full advantage of statement caching, you should not dynamically generate statements, with different inline values, for every statement execution. Instead, use parameterized commands to minimize the number of unique statements that need to be executed and cached. This is because only one statement needs to be cached for every unique command text, regardless of the parameter values and the number of times that the statement is executed.

The maximum number of statements that can be cached per connection is determined by the `MaxStatementCacheSize` configuration attribute. The `MaxStatementCacheSize` value can be specified in the Windows registry or XML configuration file.

The `MaxStatementCacheSize` setting is useful in limiting the number of cached statements, as well as the number of open cursors. This is because a cached statement equates to a cursor being opened on the server. For this reason, you should not set `MaxStatementCacheSize` to a value that is greater than the database `MAX_OPEN_CURSORS` setting.

The following Windows registry key is used to configure the `MaxStatementCacheSize` configuration attribute:

```
HKLM\Software\Oracle\ODP.NET\version\MaxStatementCacheSize
```

The `MaxStatementCacheSize` key is of type `REG_SZ`. It can be set to an integer value between 0 and `System.Int32.MaxValue`.

The following example sets the `MaxStatementCacheSize` property in an ADO.NET 2.0, or above, configuration file:

```
<?xml version="1.0" encoding="utf-8" ?>
<configuration>
  <oracle.dataaccess.client>
    <settings>
      <add name="MaxStatementCacheSize" value="300"/>
    </settings>
  </oracle.dataaccess.client>
</configuration>
```

If self-tuning is disabled for an application, then the value of statement cache size is determined by the settings in the connection string, configuration file, or the registry. If statement cache size is not specified in any of these sources, then the default value of statement cache size is set to 0. To have ODP.NET configured with the same default settings as previous releases of ODP.NET, disable self-tuning and set the `StatementCacheSize` value to 10.

See Also: ["Statement Caching"](#) on page 3-48

Enabling or Disabling Self-Tuning for Applications

Self-tuning for ODP.NET applications is enabled by default. An application can enable or disable self-tuning using one of the following methods:

- **Self-Tuning Connection String Attribute**

An application can modify the `Self Tuning` connection string attribute to enable or disable self-tuning for a particular connection pool. The default value for `Self Tuning` is `true`.
- **Windows Registry**

An application can enable or disable self-tuning for a particular version of ODP.NET by modifying the following registry entry:

```
HKLM\Software\Oracle\ODP.NET\version\SelfTuning
```

The `SelfTuning` key is of type `REG_SZ`. It can be set to either 1 (enabled) or 0 (disabled).

- **Configuration File**

An ODP.NET application can modify the application configuration file (`app.config`) or Web configuration file (`web.config`) to enable or disable self-tuning.

The following example shows how to enable self-tuning in an ADO.NET 2.0 application configuration file:

```
<?xml version="1.0" encoding="utf-8" ?>
<configuration>
  <oracle.dataaccess.client>
    <settings>
      <add name="SelfTuning" value="1" />
    </settings>
  </oracle.dataaccess.client>
</configuration>
```

Note: If the optimal statement cache size is known for an application, then you can disable self-tuning and set `StatementCacheSize` to its optimum value in the registry, configuration file, or the application. If self-tuning is disabled and `StatementCacheSize` is not set at all, then the default value of 0 is used for `StatementCacheSize`.

Tracing Optimization Changes

Applications can trace optimization changes made by self-tuning. All changes to `StatementCacheSize` are traced. Errors, if any, are also traced.

The `TraceLevel` used for tracing self-tuning is 64.

See Also: [Table 2–1, "Configuration Attributes"](#) for details on `TraceLevel` values

ODP.NET Types Overview

ODP.NET types represent Oracle native data types and PL/SQL data types as a structure or as a class. ODP.NET type structures follow **value semantics**, while ODP.NET type classes follow **reference semantics**. ODP.NET types provide safer and more efficient ways of obtaining Oracle native data and PL/SQL data types in a .NET application than .NET types. For example, an `OracleDecimal` structure holds up to 38 digits of precision, while a .NET `Decimal` only holds up to 28.

[Table 3–11](#) lists data types supported by ODP.NET and their corresponding ODP.NET types: data types in the first column refer to both Oracle native data types and PL/SQL data types of that name. Those data types that exist only in PL/SQL are indicated by (PL/SQL only) after the data type name. The entries for the PL/SQL data types also represent the subtypes of the data types, if any. The third column lists the .NET Framework data type that corresponds to the `Value` property of each ODP.NET type.

Table 3–11 Value Property Type of ODP.NET Type

| Oracle Native Data Type or PL/SQL Data Type | ODP.NET Type | .NET Framework Data Types |
|----------------------------------------------------|------------------------------|----------------------------------|
| BFILE | OracleBFile class | System.Byte[] |
| BINARY_DOUBLE | OracleDecimal structure | System.Decimal |
| BINARY_FLOAT | OracleDecimal structure | System.Decimal |
| BINARY_INTEGER (PL/SQL only) | OracleDecimal structure | System.Decimal |
| BLOB | OracleBlob class | System.Byte[] |
| BOOLEAN (PL/SQL only) | OracleBoolean structure | System.Boolean |
| CHAR | OracleString structure | System.String |
| CLOB | OracleClob class | System.String |
| DATE | OracleDate structure | System.DateTime |
| INTERVAL DAY TO SECOND | OracleIntervalDS structure | System.TimeSpan |
| INTERVAL YEAR TO MONTH | OracleIntervalYM structure | System.Int64 |
| LONG | OracleString structure | System.String |
| LONG RAW | OracleBinary structure | System.Byte[] |
| NCHAR | OracleString structure | System.String |
| NCLOB | OracleClob class | System.String |
| NUMBER | OracleDecimal structure | System.Decimal |
| NVARCHAR2 | OracleString structure | System.String |
| PLS_INTEGER (PL/SQL only) | OracleDecimal Structure | System.Decimal |
| RAW | OracleBinary structure | System.Byte[] |
| REF | OracleRef class | System.String |
| REF CURSOR (PL/SQL only) | OracleRefCursor class | Not Applicable |
| ROWID | OracleString structure | System.String |
| TIMESTAMP | OracleTimeStamp structure | System.DateTime |
| TIMESTAMP WITH LOCAL TIME ZONE | OracleTimeStampLTZ structure | System.DateTime |
| TIMESTAMP WITH TIME ZONE | OracleTimeStampTZ structure | System.DateTime |
| UROWID | OracleString structure | System.String |
| VARCHAR2 | OracleString structure | System.String |
| XMLType | OracleXmlType class | System.String |

Obtaining Data from an OracleDataReader Object

The `ExecuteReader` method of the `OracleCommand` object returns an `OracleDataReader` object, which is a read-only, forward-only result set.

This section provides the following information about the `OracleDataReader` object:

- [Typed OracleDataReader Accessors](#)

- [Obtaining LONG and LONG RAW Data](#)
- [Obtaining LOB Data](#)
- [Controlling the Number of Rows Fetched in One Database Round-Trip](#)

Typed OracleDataReader Accessors

The `OracleDataReader` class provides two types of typed accessors:

- [.NET Type Accessors](#)
- [ODP.NET Type Accessors](#)

.NET Type Accessors

[Table 3–12](#) lists all the Oracle native database types that ODP.NET supports, and the corresponding .NET types that can represent the Oracle native type. If more than one .NET type can be used to represent an Oracle native type, the first entry is the .NET type that best represents the Oracle native type. The third column indicates the valid typed accessor that can be invoked for an Oracle native type to be obtained as a .NET type. If an invalid typed accessor is used for a column, an `InvalidCastException` is thrown. Oracle native data types depend on the version of the database; therefore, some data types are not available in earlier versions of Oracle Database.

See Also:

- ["OracleDataAdapter Class"](#) on page 6-160
- ["OracleDataReader Class"](#) on page 6-197

Table 3–12 .NET Type Accessors

| Oracle Native Data Type | .NET Type | Typed Accessor |
|-------------------------|--------------------------------|-----------------------|
| BFILE | System.Byte[] | GetBytes |
| BINARY_DOUBLE | System.Double | GetDouble |
| BINARY_FLOAT | System.Single | GetFloat |
| BLOB | System.Byte[] | GetBytes |
| CHAR | System.String System.Char[] | GetString GetChars |
| CLOB | System.String System.Char[] | GetString GetChars |
| DATE | System.DateTime | GetDateTime |
| INTERVAL DAY TO SECOND | System.Timespan | GetTimeSpan |
| INTERVAL YEAR TO MONTH | System.Int64 | GetInt64 |
| LONG | System.String System.Char[] | GetString GetChars |
| LONG RAW | System.Byte[] | GetBytes |
| NCHAR | System.String System.Char[] | GetString GetChars |
| NCLOB | System.String System.Char[] | GetString GetChars |

Table 3–12 (Cont.) .NET Type Accessors

| Oracle Native Data Type | .NET Type | Typed Accessor |
|--------------------------------|----------------------|----------------|
| NUMBER | System.Decimal | GetDecimal |
| | System.Byte | GetByte |
| | System.Int16 | GetInt16 |
| | System.Int32 | GetInt32 |
| | System.Int64 | GetInt64 |
| | System.Single | GetFloat |
| NVARCHAR2 | System.Double | GetDouble |
| | System.String | GetString |
| RAW | System.Char[] | GetChars |
| | System.Byte[] | GetBytes |
| REF | System.String | GetString |
| ROWID | System.String | GetString |
| | System.Char[] | GetChars |
| TIMESTAMP | System.DateTime | GetDateTime |
| TIMESTAMP WITH LOCAL TIME ZONE | System.DateTime | GetDateTime |
| TIMESTAMP WITH TIME ZONE | System.DateTime | GetDateTime |
| UROWID | System.String | GetString |
| | System.Char[] | GetChars |
| VARCHAR2 | System.String | GetString |
| | System.Char[] | GetChars |
| XMLType | System.String | GetString |
| | System.Xml.XmlReader | GetXmlReader |

Certain methods and properties of the `OracleDataReader` object require ODP.NET to map a `NUMBER` column to a .NET type based on the precision and scale of the column. These members are:

- `Item` property
- `GetFieldType` method
- `GetValue` method
- `GetValues` method

ODP.NET determines the appropriate .NET type by considering the following .NET types in order, and selecting the first .NET type from the list that can represent the entire range of values of the column:

- `System.Byte`
- `System.Int16`
- `System.Int32`
- `System.Int64`
- `System.Single`
- `System.Double`

- `System.Decimal`

If no .NET type exists that can represent the entire range of values of the column, then an attempt is made to represent the column values as a `System.Decimal` type. If the value in the column cannot be represented as `System.Decimal`, then an exception is raised.

For example, consider two columns defined as `NUMBER(4,0)` and `NUMBER(10,2)`. The first .NET types from the previous list that can represent the entire range of values of the columns are `System.Int16` and `System.Double`, respectively. However, consider a column defined as `NUMBER(20,10)`. In this case, there is no .NET type that can represent the entire range of values on the column, so an attempt is made to return values in the column as a `System.Decimal` type. If a value in the column cannot be represented as a `System.Decimal` type, then an exception is raised.

The `Fill` method of the `OracleDataAdapter` class uses the `OracleDataReader` object to populate or refresh a `DataTable` or `DataSet` with .NET types. As a result, the .NET type used to represent a `NUMBER` column in the `DataTable` or `DataSet` also depends on the precision and scale of the column.

See Also:

- ["OracleDataReader Class"](#) on page 6-197
- ["OracleDataAdapter Class"](#) on page 6-160
- ["Item"](#) on page 6-210
- ["GetFieldType"](#) on page 6-227
- ["GetValues"](#) on page 6-258
- ["GetValue"](#) on page 6-258

ODP.NET Type Accessors

ODP.NET exposes provider-specific types that natively represent the data types in the database. In some cases, these ODP.NET types provide better performance and functioning than the corresponding .NET types. The ODP.NET types can be obtained from the `OracleDataReader` object by calling their respective typed accessor.

See Also: ["ODP.NET Types Overview"](#) on page 3-52 for a list of all ODP.NET types

[Table 3–13](#) lists the valid type accessors that ODP.NET uses to obtain ODP.NET types for an Oracle native type.

Table 3–13 ODP.NET Type Accessors

| Oracle Native Data Type | ODP.NET Type | Typed Accessor |
|-------------------------|----------------------------|-------------------------------------|
| BFILE | <code>OracleBFile</code> | <code>GetOracleBFile</code> |
| BINARY_DOUBLE | <code>OracleDecimal</code> | <code>GetOracleDecimal</code> |
| BINARY_FLOAT | <code>OracleDecimal</code> | <code>GetOracleDecimal</code> |
| BLOB | <code>OracleBlob</code> | <code>GetOracleBlob</code> |
| | <code>OracleBlob</code> | <code>GetOracleBlobForUpdate</code> |
| | <code>OracleBinary</code> | <code>GetOracleBinary</code> |
| CHAR | <code>OracleString</code> | <code>GetOracleString</code> |

Table 3–13 (Cont.) ODP.NET Type Accessors

| Oracle Native Data Type | ODP.NET Type | Typed Accessor |
|--------------------------------|--------------------|------------------------|
| CLOB | OracleClob | GetOracleClob |
| | OracleClob | GetOracleClobForUpdate |
| | OracleString | GetOracleString |
| DATE | OracleDate | GetOracleDate |
| INTERVAL DAY TO SECOND | OracleIntervalDS | GetOracleIntervalDS |
| INTERVAL YEAR TO MONTH | OracleIntervalYM | GetOracleIntervalYM |
| LONG | OracleString | GetOracleString |
| LONG RAW | OracleBinary | GetOracleBinary |
| NCHAR | OracleString | GetOracleString |
| NCLOB | OracleString | GetOracleString |
| NUMBER | OracleDecimal | GetOracleDecimal |
| NVARCHAR2 | OracleString | GetOracleString |
| RAW | OracleBinary | GetOracleBinary |
| REF | OracleRef | GetOracleRef |
| ROWID | OracleString | GetOracleString |
| TIMESTAMP | OracleTimeStamp | GetOracleTimeStamp |
| TIMESTAMP WITH LOCAL TIME ZONE | OracleTimeStampLTZ | GetOracleTimeStampLTZ |
| TIMESTAMP WITH TIME ZONE | OracleTimeStampTZ | GetOracleTimeStampTZ |
| UROWID | OracleString | GetOracleString |
| VARCHAR2 | OracleString | GetOracleString |
| XMLType | OracleString | GetOracleString |
| | OracleXmlType | GetOracleXmlType |

Obtaining LONG and LONG RAW Data

ODP.NET fetches and caches rows from the database during the Read method invocations on the OracleDataReader object. The amount of LONG and LONG RAW column data that is retrieved from this operation is determined by InitialLONGFetchSize. The different behaviors observed when InitialLONGFetchSize is set to 0, greater than 0, and -1 are explained in the following sections.

Note: ODP.NET does not support the CommandBehavior.SequentialAccess enumeration value. Therefore, LONG and LONG RAW data can be fetched randomly.

Setting InitialLONGFetchSize to Zero or a Value Greater than Zero

The specified amount of InitialLONGFetchSize characters or bytes for LONG or LONG RAW column data is retrieved into the cache during the Read method invocations on the OracleDataReader object.

By default, InitialLONGFetchSize is set to 0. In this case, ODP.NET does not fetch any LONG or LONG RAW column data during the Read method invocations on the

OracleDataReader object. The LONG or LONG RAW data is fetched when the typed accessor method is explicitly invoked for the LONG or LONG RAW column, which incurs a database round-trip because no data is cached.

If InitialLONGFetchSize is set to a value greater than 0, that amount of specified data is cached by ODP.NET during the Read method invocations on the OracleDataReader object. If the application requests an amount of data less than or equal to the InitialLONGFetchSize through the typed accessor methods, no database round-trip is incurred. However, an additional database round-trip is required to fetch data beyond InitialLONGFetchSize.

To obtain data beyond the InitialLONGFetchSize characters or bytes, one of the following must be in the select list:

- Primary key
- ROWID
- Unique columns - (defined as a set of columns on which a unique constraint has been defined or a unique index has been created, where at least one of the columns in the set has a NOT NULL constraint defined on it)

To be able to fetch the entire LONG or LONG RAW data without having a primary key column, a ROWID, or unique columns in the select list, set the size of the InitialLONGFetchSize property on the OracleCommand object to equal or greater than the number of characters or bytes needed to be retrieved.

The LONG or LONG RAW data is returned when the appropriate typed accessor method (GetChars, GetOracleString, or GetString for LONG or GetOracleBinary or GetBytes for LONG RAW) is called on the OracleDataReader object.

Setting InitialLONGFetchSize to -1

By setting InitialLONGFetchSize to -1, it is possible to fetch the entire LONG or LONG RAW data from the database for a select query, without requiring a primary key, ROWID, or unique column in the select list.

When InitialLONGFetchSize is set to -1, the entire LONG or LONG RAW data is retrieved and cached during Read method invocations on the OracleDataReader object. Calls to GetString, GetOracleString, GetChars, GetBytes, or GetOracleBinary in the OracleDataReader return the entire column data.

Obtaining LOB Data

ODP.NET fetches and caches rows from the database during the Read method invocations on the OracleDataReader object. The amount of LOB column data that is retrieved from this operation is determined by InitialLOBFetchSize.

The following is a complete list of typed accessor methods that an application can call for the CLOB and BLOB columns, if InitialLOBFetchSize is set to 0, greater than 0, or -1:

- Methods callable for BLOB column
 - GetBytes
 - GetValue
 - GetValues
 - GetOracleBinary
 - GetOracleBlob

- GetOracleBlobForUpdate
- GetOracleValue
- GetOracleValues
- Methods callable for CLOB column
 - GetChars
 - GetString
 - GetValue
 - GetValues
 - GetOracleString
 - GetOracleClob
 - GetOracleClobForUpdate
 - GetOracleValue
 - GetOracleValues

The following sections explain the different behaviors observed when `InitialLOBFetchSize` is set to 0, greater than 0, and -1.

Setting InitialLOBFetchSize to Zero

By default, the `InitialLOBFetchSize` property is 0. This value dictates to ODP.NET that any LOBs selected will have their client LOB data fetches deferred until after the `OracleDataReader Read`, such as when using the an accessor. Each LOB value is retrieved only at the point it is individually accessed.

The advantage of using this retrieval strategy is that it conserves client memory and bandwidth. If the LOBs selected are either very large or not necessary to be immediately consumed by the end user, or both, then the application can perform better if LOBs are retrieved as needed, rather than all at once.

Setting InitialLOBFetchSize to a Value Greater than Zero

If `InitialLOBFetchSize` is set to a value greater than 0, ODP.NET caches LOB data up to `InitialLOBFetchSize` characters or bytes for each LOB selected during the `Read` method invocations on the `OracleDataReader` object. The maximum value is 2,147,483,647 (2GB). If the total size of a selected LOB is less than this number, the entire LOB data will be read.

By pre-fetching all LOB entries in one or more database round trips, applications can perform faster by reducing round trips. This approach is most advantageous when most LOBs are either small in size, or consumed by the end user almost immediately, or both. The down side of a large fetch size is higher memory consumption.

This section discusses the ways to fetch beyond the `InitialLOBFetchSize` characters or bytes that are cached.

The remaining LOB data is returned when a typed accessor is invoked, regardless of the value set to the `InitialLOBFetchSize` property. Primary key, ROWID, or unique columns are not required to be in the query select list to obtain data beyond the specified `InitialLOBFetchSize`.

The `GetOracleBlob`, `GetOracleClob`, `GetOracleBlobForUpdate`, and `GetOracleClobForUpdate` methods can now be invoked even if `InitialLOBFetchSize` is greater than 0.

Setting InitialLOBFetchSize to -1

To fetch all LOB data selected during the read operation and not be bound by a set limit per LOB, set `InitialLOBFetchSize` to -1. A new default behavior has been introduced for ODP.NET Release 12.1.0.2 and higher when `InitialLobFetchSize` is set to -1.

When `LegacyEntireLOBFetch = 0`, which is the default value, the following operations are invoked for a LOB column:

- `OracleDataReader.GetOracleClob()`: returns `OracleClob` object
- `OracleDataReader.GetOracleBlob()` : returns `OracleBlob` object
- `OracleDataReader.GetOracleClobForUpdate()`: returns `OracleClob` object
- `OracleDataReader.GetOracleBlobForUpdate()`: returns `OracleBlob` object
- `OracleDataReader.GetOracleValue()`: returns `OracleClob` object for a CLOB column
- `OracleDataReader.GetOracleValue()`: returns `OracleBlob` object for a BLOB column
- `OracleDataAdapter.Fill()` with `ProviderSpecificTypes=true`: populates `DataTable` with `OracleClob` for a CLOB column
- `OracleDataAdapter.Fill()` with `ProviderSpecificTypes=true`: populates `DataTable` with `OracleBlob` for a BLOB column

To use the old behavior, set `LegacyEntireLobFetch = 1` in the ODP.NET configuration.

When `LegacyEntireLobFetch = 1` and `InitialLOBFetchSize = -1`, `GetOracleClob`, `GetOracleClobForUpdate`, `GetOracleBlob`, and `GetOracleBlobForUpdate` methods are not supported. The following operations are invoked for a LOB column in this scenario:

- `OracleDataReader.GetOracleClob()`: throws `InvalidCastException()`
- `OracleDataReader.GetOracleBlob()`: throws `InvalidCastException()`
- `OracleDataReader.GetOracleClobForUpdate()`: throws `InvalidCastException()`
- `OracleDataReader.GetOracleBlobForUpdate()`: throws `InvalidCastException()`
- `OracleDataReader.GetOracleValue()`: returns `OracleString` object for a CLOB column
- `OracleDataReader.GetOracleValue()`: returns `OracleBinary` object for a BLOB column
- `OracleDataAdapter.Fill()` with `ProviderSpecificTypes=true`: populates `DataTable` with `OracleString` for a CLOB column
- `OracleDataAdapter.Fill()` with `ProviderSpecificTypes=true`: populates `DataTable` with `OracleBinary` for a BLOB column

For releases prior to ODP.NET 12.1.0.2, by setting `InitialLOBFetchSize` to -1, it is possible to fetch the entire LOB data from the database for a select query, without requiring a primary key, ROWID, or unique column in the select list. When `InitialLOBFetchSize` is set to -1, the entire LOB column data is fetched and cached during the `Read` method invocations on the `OracleDataReader` object. Calls to `GetString`, `GetOracleString`, `GetChars`, `GetBytes`, or `GetOracleBinary` in the `OracleDataReader` allow retrieving all data.

Methods Supported for InitialLOBFetchSize of -1 and LegacyEntireLobFetch of 1 This section lists supported and not supported methods for the CLOB and BLOB data types when the InitialLOBFetchSize property is set to -1 and LegacyEntireLobFetch property is set to 1.

Table 3–14 lists supported and not supported methods for the CLOB data types.

Table 3–14 OracleDataReader CLOB Methods

| Supported | Not Supported |
|-----------------|------------------------|
| GetChars | GetOracleClob |
| GetString | GetOracleClobForUpdate |
| GetValue | |
| GetValues | |
| GetOracleString | |
| GetOracleValue | |
| GetOracleValues | |

Table 3–15 lists supported and not supported methods for the BLOB data types.

Table 3–15 OracleDataReader BLOB Methods

| Supported | Not Supported |
|-----------------|------------------------|
| GetBytes | GetOracleBlob |
| GetValue | GetOracleBlobForUpdate |
| GetValues | |
| GetOracleBinary | |
| GetOracleValue | |
| GetOracleValues | |

Performance Considerations Related to the InitialLOBFetchSize Property

This section discusses the advantages and disadvantages of the various InitialLOBFetchSize property settings in different situations.

An application does not have to choose between performance and OracleBlob and OracleClob functionality. Setting the InitialLOBFetchSize property results in a performance boost and still gives the flexibility to use the OracleBlob and OracleClob objects.

If the size of the LOB data is unknown or if the LOB data size varies irregularly, then it is better to leave the InitialLOBFetchSize property to its default value of 0. This still gives better performance in most cases.

Setting the InitialLOBFetchSize property to a size equal to or greater than the LOB data size for most rows improves performance. It is generally recommended that the InitialLOBFetchSize property be set to a value larger than the size of the LOB data for more than 80% of the rows returned by the query. For example, if the size of the LOB data is less than 1 KB in 80% of the rows, and more than 1 MB for 20% of the rows, set the InitialLOBFetchSize property to 1 KB.

See Also:

- ["LOB Support"](#) on page 3-75
- ["InitialLOBFetchSize"](#) on page 6-29
- ["InitialLONGFetchSize"](#) on page 6-30

Controlling the Number of Rows Fetched in One Database Round-Trip

Application performance depends on the number of rows the application needs to fetch, and the number of database round-trips that are needed to retrieve them.

Use of FetchSize

The `FetchSize` property represents the total memory size in bytes that ODP.NET allocates to cache the data fetched from a database round-trip.

The `FetchSize` property can be set on the `OracleCommand`, `OracleDataReader`, or `OracleRefCursor` object, depending on the situation. It controls the fetch size for filling a `DataSet` or `DataTable` using an `OracleDataAdapter`.

If the `FetchSize` property is set on the `OracleCommand` object, then the newly created `OracleDataReader` object inherits the `FetchSize` property of the `OracleCommand` object. This inherited `FetchSize` value can be left as is, or modified to override the inherited value. The `FetchSize` property of the `OracleDataReader` object can be changed before the first `Read` method invocation, which allocates memory specified by the `FetchSize` property. All subsequent fetches from the database use the same cache allocated for that `OracleDataReader` object. Therefore, changing the `FetchSize` value after the first `Read` method invocation has no effect.

Fine-Tuning FetchSize

By fine-tuning the `FetchSize` property, applications can control memory usage and the number of rows fetched in one database round-trip for better performance.

For example, if a query returns 100 rows and each row takes 1024 bytes, then setting the `FetchSize` property to 102400 takes just one database round-trip to fetch 100 rows. For the same query, if the `FetchSize` property is set to 10240, it takes 10 database round-trips to retrieve 100 rows. If the application requires all the rows to be fetched from the result set, the first scenario is faster than the second. However, if the application requires just the first 10 rows from the result set, the second scenario can perform better because it fetches only 10 rows, not 100 rows. When the next 10 rows are fetched, then the memory allocated for rows 1-10 is reused for rows 11-20.

The larger the `FetchSize`, the more system memory is used. Developers should not set large fetch sizes if their client systems have limited memory resources.

Using the RowSize Property

The `RowSize` property of the `OracleCommand` or `OracleRefCursor` object is populated with the row size (in bytes) after an execution of a `SELECT` statement. The `FetchSize` property can then be set to a value relative to the `RowSize` property by setting it to the result of multiplying the `RowSize` value times the number of rows to fetch for each database round-trip.

For example, setting the `FetchSize` to `RowSize * 10` forces the `OracleDataReader` object to fetch exactly 10 rows for each database round-trip. Note that the `RowSize` value does not change due to the data length in each individual column. Instead, the `RowSize` value is determined strictly from the metadata information of the database table(s) that the `SELECT` statement is executed against.

The `RowSize` property can be used to set the `FetchSize` property at design time or at run time, as described in the following sections.

Setting FetchSize Value in the Registry The `HKLM\Software\Oracle\ODP.NET\version\FetchSize` registry entry can be set to specify the default result set fetch size (in bytes) for all applications that use that particular version of ODP.NET or the `FetchSize` attribute in the application configuration or `web.config` file can specify the default value for a given application. By default, the fetch size is 131072 bytes. This value can be overridden programmatically by having the applications set the `FetchSize` property on either the `OracleCommand` or the `OracleDataReader` at run time.

Setting FetchSize Value at Design Time If the row size for a particular `SELECT` statement is already known from a previous execution, the `FetchSize` value of the `OracleCommand` object can be set at design time to the result of multiplying that row size times the number of rows the application wishes to fetch for each database round-trip. The `FetchSize` value set on the `OracleCommand` object is inherited by the `OracleDataReader` object that is created by the `ExecuteReader` method invocation on the `OracleCommand` object. Rather than setting the `FetchSize` value on the `OracleCommand` object, the `FetchSize` value can also be set on the `OracleDataReader` object directly. In either case, the `FetchSize` value is set at design time, without accessing the `RowSize` property value at run time.

Setting FetchSize Value at Run Time Applications that do not know the row size at design time can use the `RowSize` property of the `OracleCommand` object to set the `FetchSize` property of the `OracleDataReader` object. The `RowSize` property provides a dynamic way of setting the `FetchSize` property based on the size of a row.

After an `OracleDataReader` object is obtained by invoking the `ExecuteReader` method on the `OracleCommand` object, the `RowSize` property is populated with the size of the row (in bytes). By using the `RowSize` property, the application can dynamically set the `FetchSize` property of the `OracleDataReader` object to the product of the `RowSize` property value multiplied by the number of rows the application wishes to fetch for each database round-trip. In this scenario, the `FetchSize` property is set by accessing the `RowSize` property at run time.

PL/SQL REF CURSOR and OracleRefCursor

The `REF CURSOR` is a data type in the Oracle PL/SQL language. It represents a cursor or a result set in Oracle Database. The `OracleRefCursor` object is a corresponding ODP.NET type for the `REF CURSOR` type.

This section discusses the following aspects of using the `REF CURSOR` data type and `OracleRefCursor` objects:

- [Obtaining an OracleRefCursor Object](#)
- [Obtaining a REF CURSOR Data Type](#)
- [Populating an OracleDataReader from a REF CURSOR](#)
- [Populating the DataSet from a REF CURSOR](#)
- [Populating an OracleRefCursor from a REF CURSOR](#)
- [Updating a DataSet Obtained from a REF CURSOR](#)
- [Behavior of ExecuteScalar Method for REF CURSOR](#)
- [Passing a REF CURSOR to a Stored Procedure](#)

Obtaining an OracleRefCursor Object

There are no constructors for `OracleRefCursor` objects. They can be acquired only as parameter values from PL/SQL stored procedures, stored functions, or anonymous blocks.

An `OracleRefCursor` object is a connected object. The connection used to execute the command returning an `OracleRefCursor` object is required for its lifetime. Once the connection associated with an `OracleRefCursor` object is closed, the `OracleRefCursor` object cannot be used.

Obtaining a REF CURSOR Data Type

A `REF CURSOR` data type can be obtained as an `OracleDataReader`, `DataSet`, or `OracleRefCursor` object. If the `REF CURSOR` data type is obtained as an `OracleRefCursor` object, it can be used to create an `OracleDataReader` object or populate a `DataSet` from it. When accessing a `REF CURSOR` data type, always bind it as an `OracleDbType.RefCursor` parameter.

Populating an OracleDataReader from a REF CURSOR

A `REF CURSOR` data type can be obtained as an `OracleDataReader` object by calling the `ExecuteReader` method of the `OracleCommand` object. The output parameter with the `OracleDbType` property set is bound to `OracleDbType.RefCursor`. None of the output parameters of type `OracleDbType.RefCursor` is populated after the `ExecuteReader` method is invoked.

If there are multiple output `REF CURSOR` parameters, use the `NextResult` method of the `OracleDataReader` object to access the next `REF CURSOR` data type. The `OracleDataReader.NextResult` method provides sequential access to the `REF CURSOR` data types; only one `REF CURSOR` data type can be accessed at a given time.

The order in which `OracleDataReader` objects are created for the corresponding `REF CURSOR` data types depends on the order in which the parameters are bound. If a PL/SQL stored function returns a `REF CURSOR` data type, then it becomes the first `OracleDataReader` object and all the output `REF CURSOR` data types follow the order in which the parameters are bound.

Populating the DataSet from a REF CURSOR

For the `Fill` method to populate the `DataSet` properly, the `SelectCommand` property of the `OracleDataAdapter` class must be bound with an output parameter of type `OracleDbType.RefCursor`. If the `Fill` method is successful, the `DataSet` is populated with a `DataTable` that represents a `REF CURSOR` data type.

If the command execution returns multiple `REF CURSOR` data types, the `DataSet` is populated with multiple `DataTable` objects.

With Oracle Data Provider for .NET release 11.1.0.6.20, the extended property, `RefCursorName`, has been introduced on the `DataTable`, to identify the `REF CURSOR` that populates the `DataTable`.

This property is particularly useful when a `DataSet` is being populated with more than one `REF CURSOR`, one or more of which is `NULL`. For example, if a `DataSet` is populated by executing a stored procedure that returns three `REF CURSORS` and the second `REF CURSOR` is `NULL`, the `RefCursorName` property value for the first `DataTable` is `RefCursor` and for the second `DataTable`, `RefCursor2`. No `DataTable` is populated for the `NULL` `REF CURSOR`.

Populating an OracleRefCursor from a REF CURSOR

When the `ExecuteNonQuery` method is invoked on a command that returns one or more `REF CURSOR` data types, each of the `OracleCommand` parameters that are bound as an `OracleDbType.RefCursor` gets a reference to an `OracleRefCursor` object.

To create an `OracleDataReader` object from an `OracleRefCursor` object, invoke the `GetDataReader` method from the `OracleRefCursor` object. Subsequent calls to the `GetDataReader` method return a reference to the same `OracleDataReader` object.

To populate a `DataSet` with an `OracleRefCursor` object, the application can invoke a `Fill` method of the `OracleDataAdapter` class that takes an `OracleRefCursor` object. Similar to the `OracleDataReader` object, an `OracleRefCursor` object is forward-only. Therefore, once a row is read from an `OracleRefCursor` object, that same row cannot be obtained again from it unless it is populated again from a query.

When multiple `REF CURSOR` data types are returned from a command execution as `OracleRefCursor` objects, the application can choose to create an `OracleDataReader` object or populate a `DataSet` with a particular `OracleRefCursor` object. All the `OracleDataReader` objects or `DataSet` objects created from the `OracleRefCursor` objects are active at the same time, and can be accessed in any order.

Updating a DataSet Obtained from a REF CURSOR

`REF CURSOR` types cannot be updated. However, data that is retrieved into a `DataSet` can be updated. Therefore, the `OracleDataAdapter` class requires a custom SQL statement to flush any `REF CURSOR` data updates to the database.

The `OracleCommandBuilder` object cannot be used to generate SQL statements for `REF CURSOR` updates.

Behavior of ExecuteScalar Method for REF CURSOR

The `ExecuteScalar` method returns the value of the first column of the first row of the `REF CURSOR` if it is one of the following:

- A return value of a stored function execution
- The first bind parameter of a stored procedure execution

See Also: *Oracle Database SecureFiles and Large Objects Developer's Guide* for more information

Passing a REF CURSOR to a Stored Procedure

An application can retrieve a `REF CURSOR` type from a PL/SQL stored procedure or function and pass it to another stored procedure or function. This feature is useful in scenarios where a stored procedure or a function returns a `REF CURSOR` type to the .NET application, and based on the application logic, the application passes this `REF CURSOR` to another stored procedure for processing. Note that if you retrieve the data from a `REF CURSOR` type in the .NET application, you cannot pass it back to another stored procedure.

The following example demonstrate passing a `REF CURSOR`:

```
/*
connect scott/tiger@oracle
create table test (col1 number);
insert into test(col1) values (1);
commit;
```

```
create or replace package testPkg as type empCur is REF Cursor;
end testPkg;
/

create or replace procedure testSP(param1 IN testPkg.empCur, param2 OUT NUMBER)
as
begin
FETCH param1 into param2;
end;
/
*/

// C#

using System;
using Oracle.DataAccess.Client;
using System.Data;

class InRefCursorParameterSample
{
    static void Main()
    {
        OracleConnection conn = new OracleConnection
            ("User Id=scott; Password=tiger; Data Source=oracle");

        conn.Open(); // Open the connection to the database

        // Command text for getting the REF Cursor as OUT parameter
        String cmdTxt1 = "begin open :1 for select col1 from test; end;";

        // Command text to pass the REF Cursor as IN parameter
        String cmdTxt2 = "begin testSP (:1, :2); end;";

        // Create the command object for executing cmdTxt1 and cmdTxt2
        OracleCommand cmd = new OracleCommand(cmdTxt1, conn);

        // Bind the Ref cursor to the PL/SQL stored procedure
        OracleParameter outRefPrm = cmd.Parameters.Add("outRefPrm",
            OracleDbType.RefCursor, DBNull.Value, ParameterDirection.Output);

        cmd.ExecuteNonQuery(); // Execute the anonymous PL/SQL block

        // Reset the command object to execute another anonymous PL/SQL block
        cmd.Parameters.Clear();
        cmd.CommandText = cmdTxt2;

        // REF Cursor obtained from previous execution is passed to this
        // procedure as IN parameter
        OracleParameter inRefPrm = cmd.Parameters.Add("inRefPrm",
            OracleDbType.RefCursor, outRefPrm.Value, ParameterDirection.Input);

        // Bind another Number parameter to get the REF Cursor column value
        OracleParameter outNumPrm = cmd.Parameters.Add("outNumPrm",
            OracleDbType.Int32, DBNull.Value, ParameterDirection.Output);

        cmd.ExecuteNonQuery(); //Execute the stored procedure

        // Display the out parameter value
        Console.WriteLine("out parameter is: " + outNumPrm.Value.ToString());
    }
}
```



```

    }
}

```

Implicit REF CURSOR Binding

ODP.NET 11g Release 2 (11.2.0.3.0), and higher, enables applications to run stored procedures with REF CURSOR parameters without using explicit binding for these parameters in the .NET code. ODP.NET unmanaged and managed drivers support REF CURSOR implicit binding through configuration done in .NET configuration files.

For a read-only result set, such as a REF CURSOR using `OracleDataReader`, REF CURSOR schema information is retrieved automatically.

For some scenarios, such as when updateable REF CURSORS or Entity Framework is used, developers need to define the REF CURSOR schema information so that the application can bind the implicit REF CURSOR. Entity Framework applications use implicit REF CURSOR binding to instantiate complex types from REF CURSOR data. Applications must specify REF CURSOR bind and metadata information in the `app.config`, `web.config`, or `machine.config` .NET configuration file.

The attributes supplied in the .NET configuration file are also used when the application requests for schema information from the `OracleDataReader` object that represents a REF CURSOR. This means that for REF CURSORS that are created using a SELECT from a single table, the application can update that table through the use of `OracleDataAdapter` and `OracleCommandBuilder`.

When using the Entity Framework, function imports can return an implicitly-bound REF CURSOR. The REF CURSOR can be returned as a collection of complex types or entity types. To return a complex type collection, the .NET configuration file needs to define the REF CURSOR bind and metadata information. To return an entity type collection, only the bind information needs to be defined in the .NET configuration file.

Note: ODP.NET, Managed Driver currently does not support implicit ref cursors, it currently supports only implicit binding.

This section contains the following topics:

- [Specifying REF CURSOR Bind and Metadata Information in the .NET Configuration File](#)
- [Sample Configuration File and Application](#)
- [Usage Considerations](#)

Specifying REF CURSOR Bind and Metadata Information in the .NET Configuration File

Specify the REF CURSOR information in the `oracle.dataaccess.client` configuration section of the .NET configuration file. Use an `<add>` element for each piece of information. The add element uses name-value attributes to specify REF CURSOR information. Use the following format to specify bind information:

```

<add
name="SchemaName.PackageName.StoredProcedureName.RefCursor.RefCursorParameterPositionOrName"
value="implicitRefCursor bindinfo='mode=InputOutput|Output|ReturnValue'" />

```

Use the following format to specify metadata information:

```

<add

```

```
name="SchemaName.PackageName.StoredProcedureName.RefCursorMetaData.RefCursorParameterPositionOrName.Column.ColumnOrdinal"
value="implicitRefCursor metadata=AttributesList" />
```

Each REF CURSOR column needs to have an add element defined for it. For example, if you have a REF CURSOR returning five columns, then you need to define five add elements in the config file.

Each add element contains the name and value attributes. The value attribute must begin with the word `implicitRefCursor` followed by the `bindinfo` or `metadata` attribute for specifying bind or metadata information.

The `bindinfo` information is used by ODP.NET for binding REF CURSOR parameters. The `metadata` information is used by ODP.NET to associate the schema information with the appropriate REF CURSOR. The metadata comprises of an attributes list that includes parameters together with their values.

The *SchemaName*, *PackageName*, and *StoredProcedureName* are case-sensitive. In order to run a stored procedure with implicit REF CURSOR binding, the *SchemaName.PackageName.StoredProcedureName* portion of the name attribute must exactly match the name specified in the data dictionary for that stored procedure.

Note: If the application uses implicit REF CURSOR binding feature outside of Entity Framework, then the .NET configuration file and `OracleCommand.CommandText` do not require the schema name concatenated before the stored procedure name.

If any schema, package, or stored procedure name in the database contains lowercase characters, then it must be enclosed within double quotation marks (") in the config file to preserve the case. Double quotation marks are used within the name attribute by using `"`; when needed. For example, if the schema name is `HrSchema`, the package name is `HrPackage`, and the stored procedure name is `HrStoredProcedure` in the database, the config file should use the following:

```
<add
name="&quot;HrSchema&quot; . &quot;HrPackage&quot; . &quot;HrStoredProcedure&quot; . Ref
CursorMetaData . . . />
```

By default, Oracle Database stores these names as uppercase characters. ODP.NET assumes default behavior, and converts all names to uppercase characters unless you explicitly preserve the case by using double quotation marks.

Note: The *SchemaName*, *PackageName*, *StoredProcedureName*, or *ParameterName* cannot contain a period (".") in the name. For example, `P.0` is an unacceptable parameter name.

Depending on whether the application uses bind-by-name or bind-by-position, the *RefCursorParameterPositionOrName* portion of the name attribute must be set with the correct parameter position (for bind by position) or parameter name (for bind by name). For functions, the position is 0-based, where the position 0 represents the return value. For procedures, the position is 1-based, as there are no return values for procedures. For example, if a stored procedure accepts five parameters, returning only two REF CURSORS in the third and fifth parameter positions, then the .NET config REF CURSOR bind information should contain one entry for position 3 and one entry for position 5.

If bind-by-name is used, the attribute name is used to identify the REF CURSOR parameter. The name should use the same name and case as the one specified in the data dictionary for that stored procedure.

For bindinfo, the mode specifies the parameter direction of the parameter. The mode must be either InputOutput, Output, or ReturnValue.

Note: Implicit REF CURSOR binding for an input REF CURSOR parameter is not supported.

An exception is thrown at runtime if the .NET configuration file contains an entry for a REF CURSOR whose mode is set to Input.

For metadata, The *AttributesList* contains the list of parameters. [Table 3-16](#) describes the parameters that can be included in the *AttributesList*.

[Example 3-1](#) shows a sample add element that uses bindinfo. Here, the schema name is SCOTT and the stored procedure name is TESTPROC. The parameter name is parameter1. The mode is output.

Example 3-1 Using the add Element with bindinfo

```
<add name="SCOTT.TESTPROC.RefCursor.parameter1" value="implicitRefCursor
  bindinfo='mode=Output' " />
```

[Example 3-2](#) shows a sample add element that uses metadata.

Example 3-2 Using the add Element with metadata

```
<add name="scott.TestProc.RefCursorMetaData.parameter1.Column.0"
  value="implicitRefCursor metadata='ColumnName=EMPNO;BaseColumnName=EMPNO;
  BaseSchemaName=SCOTT;BaseTableName=EMP;NativeDataType=number;
  ProviderType=Int32;DataType=System.Int32;ColumnSize=4;AllowDBNull=false;
  IsKey=true' " />
```

Table 3-16 Allowed Parameters in Attributes List

| Name | Type | Required/Optional for Entity Framework | Description |
|----------------|---------------------------------------|----------------------------------------|----------------------------------------------------------------------------|
| ColumnName | System.String | Required | The name of the column. |
| ProviderType | Oracle.DataAccess.Client.OracleDbType | Required | The database column type (OracleDbType) of the column |
| NativeDataType | System.String | Required | The Oracle type. For example, NCLOB. |
| BaseColumnName | System.String | Optional | The name of the column in the database if an alias is used for the column. |
| BaseSchemaName | System.String | Optional | The name of the schema in the database that contains the column. |
| BaseTableName | System.String | Optional | The name of the table or view in the database that contains the column. |

Table 3–16 (Cont.) Allowed Parameters in Attributes List

| Name | Type | Required/Optional for Entity Framework | Description |
|------------------|--------------------|-----------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ColumnSize | System.Int64 | Optional | The maximum possible length of a value in the column |
| NumericPrecision | System.Int16 | Optional | The maximum precision of the column, if the column is a numeric data type. |
| NumericScale | System.Int16 | Optional | The maximum scale of the column, if the column is a numeric data type. |
| IsUnique | System.Boolean | Optional | Indicates whether or not the column is unique. |
| IsKey | System.Boolean | Optional | Indicates whether or not the column is a key column. For a table to be updated with the REF CURSOR information, at least one of the columns in the REF CURSOR metadata should have this value set to true |
| IsRowID | System.Boolean | Optional | true if the column is a ROWID, otherwise false. |
| DataType | System.RuntimeType | Optional | Maps to the common language runtime type. |
| AllowDBNull | System.Boolean | Optional | true if null values are allowed, otherwise false |
| IsAliased | System.Boolean | Optional | true if the column is an alias; otherwise false. |
| IsByteSemantic | System.Boolean | Optional | IsByteSemantic is: <ul style="list-style-type: none"> ■ true if the ColumnSize value uses bytes semantics ■ false if ColumnSize uses character semantics |
| IsExpression | System.Boolean | Optional | true if the column is an expression, else false. |
| IsHidden | System.Boolean | Optional | true if the column is hidden, else false. |
| IsReadOnly | System.Boolean | Optional | true if the column is read-only, else false |
| IsLong | System.Boolean | Optional | true if the column is of LONG, LONG RAW, BLOB, CLOB, or BFILE type, else false. |
| UdtTypeName | System.String | Optional | The type name of the UDT. |
| ProviderDbType | System.Data.DbType | Optional | System.Data.DbType |
| ObjectName | System.String | Optional | Represents the name of the object. |

Some of the attributes, listed in [Table 3–16](#), automatically have their values set using the result set's metadata. Developers can override these default values by setting a value explicitly.

You may have to explicitly define some attributes listed as optional for certain operations. For example, updateable REF CURSOR requires the developer to define key information.

Sample Configuration File and Application

This section builds a sample application to illustrate implicit REF CURSOR binding. It contains the following topics:

- [Sample Stored Procedure and Function](#)
- [Sample Application Configuration File](#)
- [Sample Application That Uses the Configuration File](#)

Sample Stored Procedure and Function

```
CREATE OR REPLACE FUNCTION GETEMP (
  EMPID IN NUMBER) return sys_refcursor is
  emp sys_refcursor;
BEGIN
  OPEN emp FOR SELECT empno, ename FROM emp where empno = EMPID;
  return emp;
END;
/

CREATE OR REPLACE PROCEDURE "GetEmpAndDept" (
  EMPS OUT sys_refcursor,
  DEPTS OUT sys_refcursor) AS
BEGIN
  OPEN EMPS for SELECT empno, ename from emp;
  OPEN DEPTS for SELECT deptno, dname from dept;
END;
/
```

Sample Application Configuration File

```
<?xml version="1.0" encoding="utf-8"?>
<configuration>
  <oracle.dataaccess.client>
    <settings>

      <!-- The following is for SCOTT.GETEMP -->
      <add name="SCOTT.GETEMP.RefCursor.0"
        value="implicitRefCursor bindinfo='mode=ReturnValue' " />

      <!-- The following is for SCOTT.GETEMP's REF CURSOR metadata -->
      <add name="SCOTT.GETEMP.RefCursorMetaData.0.Column.0"
        value="implicitRefCursor metadata='ColumnName=EMPNO;
        BaseColumnName=EMPNO;BaseSchemaName=SCOTT;BaseTableName=EMP;
        NativeDataType=number;ProviderType=Int32;ProviderDbType=Int32;
        DataType=System.Int32;ColumnSize=4;NumericPrecision=10;
        NumericScale=3;AllowDBNull=false;IsKey=true' " />

      <add name="SCOTT.GETEMP.RefCursorMetaData.0.Column.1"
        value="implicitRefCursor metadata='ColumnName=ENAME;
        BaseColumnName=ENAME;BaseSchemaName=SCOTT;BaseTableName=EMP;
        NativeDataType=varchar2;ProviderType=Varchar2;
```

```

        ProviderDbType=String;DataType=System.String;
        ColumnSize=10;AllowDBNull=true' " />

<!-- The following is for "SCOTT"."GetEmpAndDept" -->
<add name="SCOTT.&quot;GetEmpAndDept&quot;".RefCursor.EMPS"
    value="implicitRefCursor bindinfo='mode=Output' " />

<!-- The following is for SCOTT.GETEMP's EMPS REF CURSOR metadata -->
<add name="SCOTT.&quot;GetEmpAndDept&quot;".RefCursorMetaData.EMPS.Column.0"
    value="implicitRefCursor metadata='ColumnName=EMPNO;
    BaseColumnName=EMPNO;BaseSchemaName=SCOTT;BaseTableName=EMP;
    NativeDataType=number;ProviderType=Int32;ProviderDbType=Int32;
    DataType=System.Int32;ColumnSize=4;NumericPrecision=10;
    NumericScale=3;AllowDBNull=false;IsKey=true' " />

<add name="SCOTT.&quot;GetEmpAndDept&quot;".RefCursorMetaData.EMPS.Column.1"
    value="implicitRefCursor metadata='ColumnName=ENAME;
    BaseColumnName=ENAME;BaseSchemaName=SCOTT;BaseTableName=EMP;
    NativeDataType=varchar2;ProviderType=Varchar2;
    ProviderDbType=String;DataType=System.String;
    ColumnSize=10;AllowDBNull=true' " />

<!-- The following is for SCOTT.GETEMP's DEPTS REF CURSOR metadata -->
<add name="SCOTT.&quot;GetEmpAndDept&quot;".RefCursor.DEPTS"
    value="implicitRefCursor bindinfo='mode=Output' " />

<add name="SCOTT.&quot;GetEmpAndDept&quot;".RefCursorMetaData.DEPTS.Column.0"
    value="implicitRefCursor metadata='ColumnName=DEPTNO;
    BaseColumnName=DEPTNO;BaseSchemaName=SCOTT;BaseTableName=DEPT;
    NativeDataType=number;ProviderType=Int32;ProviderDbType=Int32;
    DataType=System.Int32;ColumnSize=4;NumericPrecision=10;
    NumericScale=3;AllowDBNull=false;IsKey=true' " />

<add name="SCOTT.&quot;GetEmpAndDept&quot;".RefCursorMetaData.DEPTS.Column.1"
    value="implicitRefCursor metadata='ColumnName=DNAME;
    BaseColumnName=DNAME;BaseSchemaName=SCOTT;BaseTableName=DEPT;
    NativeDataType=varchar2;ProviderType=Varchar2;
    ProviderDbType=String;DataType=System.String;
    ColumnSize=10;AllowDBNull=true' " />
</settings>
</oracle.dataaccess.client>
</configuration>

```

Sample Application That Uses the Configuration File

```

using System;
using System.Data;
using Oracle.DataAccess.Client;

class Program
{
    static void Main(string[] args)
    {
        try
        {
            // Open a connection
            string constr =

```

```

        "User Id=scott;Password=tiger;Data Source=inst1";
OracleConnection con = new OracleConnection(constr);
con.Open();

// Use implicit REF CURSOR binding
// to execute SCOTT.GETEMP function
// Use bind by position as configured
// in app.config for SCOT.GETEMP
OracleCommand cmd = con.CreateCommand();
cmd.CommandText = "SCOTT.GETEMP";
cmd.CommandType = CommandType.StoredProcedure;
cmd.BindByName = false;
OracleParameter empid = cmd.Parameters.Add("empid",
    OracleDbType.Int32, ParameterDirection.Input);
empid.Value = 7654;

// Populate the DataSet
OracleDataAdapter adapter = new OracleDataAdapter(cmd);
DataSet ds = new DataSet();
adapter.Fill(ds);
Console.WriteLine("Retrieved {0} row from EMP",
    ds.Tables[0].Rows.Count);

// Use implicit REF CURSOR binding
// to execute "SCOTT"."GetEmpAndDept" procedure
// Use bind by name as configured
// in app.config for "SCOTT"."GetEmpAndDept"
cmd = con.CreateCommand();
cmd.CommandText = "\"SCOTT\".\"GetEmpAndDept\"";
cmd.CommandType = CommandType.StoredProcedure;
cmd.BindByName = true;
adapter = new OracleDataAdapter(cmd);
adapter.Fill(ds);
Console.WriteLine("Retrieved {0} rows from DEPT",
    ds.Tables[1].Rows.Count);
}
catch (Exception ex)
{
    // Output the message
    Console.WriteLine(ex.Message);
    if (ex.InnerException != null)
    {
        // If any details are available regarding
        // errors in the app.config, print them out
        Console.WriteLine(ex.InnerException.Message);
        if (ex.InnerException.InnerException != null)
        {
            Console.WriteLine(
                ex.InnerException.InnerException.Message);
        }
    }
}
}
}
}

```

Usage Considerations

This section discusses the following usage considerations when using implicit REF CURSOR:

- [CommandText Property Considerations](#)
- [Bind Considerations](#)
- [Overloaded Stored Procedures](#)
- [Type Initialization Exceptions](#)
- [Using Stored Functions with Function Import](#)

CommandText Property Considerations

ODP.NET applications should ensure that the stored procedure name and the `OracleCommand.CommandText` match exactly. Let's take a scenario where the stored procedure name in the database is `SCOTT.TESTPROC`. Now, if the `CommandText` uses `TESTPROC`, ODP.NET will look for entries matching `TESTPROC` only. The current schema name will not be automatically appended to `TESTPROC`. So, the correct `CommandText` to use in this scenario would be `SCOTT.TESTPROC`.

Also, the `CommandText` is case-sensitive and must use the same case as the stored procedure name in the database. So if the stored procedure name in the database is `SCOTT.Testproc`, then the `CommandText` must use `SCOTT.Testproc`.

Bind Considerations

If information about a `REF CURSOR` parameter has been added to the configuration file, then applications should not try to explicitly bind the `REF CURSOR` parameter to `OracleCommand`. ODP.NET automatically binds the `REF CURSOR` parameter at the appropriate locations based on the information provided in the configuration file. If the application stored procedure also has non-`REF CURSOR` parameters, then these parameters must still be explicitly bound to `OracleCommand`.

If the information specified in the configuration file for a stored procedure identifies the `REF CURSOR` parameter by name, then all the other non-`REF CURSOR` parameters should also be bound by name. Also the `BindByName` property for the `OracleCommand` object should be set to `true` in this case. Entity Framework always uses `BindByName` to run stored procedures. Your `.NET` configuration file parameter names must use the same case that was used when creating the stored procedure in the database.

If the `OracleCommand.BindByName` property is set to `false` (default), then ODP.NET assumes that the parameters have been bound based on their position, and all parameters have been specified in the correct order. For such cases, the parameters specified in the configuration file are bound in the same order in which they appear in the configuration file.

Overloaded Stored Procedures

ODP.NET does not support multiple stored procedures with the same name inside the configuration file. If an ODP.NET application uses an overloaded stored procedure, the application can store only one overloaded stored procedure information in the configuration file.

Type Initialization Exceptions

Type initialization exceptions can be caused by invalid `.NET` configuration file entries. Evaluate the exception that is caught as well as its inner exceptions to determine the `.NET` configuration file entry or the attribute setting that is causing the exception.

ODP.NET tracing logs the valid and invalid `.NET` configuration file entries that ODP.NET has parsed. To look for `.NET` configuration file related entries, set the `TraceLevel` to the *Entry, exit, and SQL statement information* level setting. Trace entries

related to implicit `REF CURSOR` binding have a `(REFCURSOR)` entry along with `(ERROR)`, if any errors are encountered.

Using Stored Functions with Function Import

Function Import only supports stored procedures, and does not support functions. When using the **Add Function Import** dialog for the Entity Data Model that you have created, the **Get Column Information** button does not return the metadata information for the `REF CURSOR` that is being returned by a stored function, even if it is configured properly in the .NET configuration file.

LOB Support

ODP.NET provides an easy and optimal way to access and manipulate large object (LOB) data types.

Note: SecureFiles can be used with existing ODP.NET LOB classes.

This section includes the following topics:

- [Large Character and Large Binary Data Types](#)
- [Oracle Data Provider for .NET LOB Objects](#)
- [Updating LOBs Using a DataSet](#)
- [Updating LOBs Using OracleCommand and OracleParameter](#)
- [Updating LOBs Using ODP.NET LOB Objects](#)
- [Temporary LOBs](#)

Large Character and Large Binary Data Types

Oracle Database supports large character and large binary data types.

Large Character Data Types

- `CLOB` - Character data can store up to 4 gigabytes.
- `NCLOB` - Unicode National character set data can store up to 4 gigabytes.

Large Binary Data Types

- `BLOB` - Unstructured binary data can store up to 4 gigabytes.
- `BFILE` - Binary data stored in external file can store up to 4 gigabytes.

Note: `LONG` and `LONG RAW` data types are made available for backward compatibility in Oracle9i, but should not be used in new applications.

Oracle Data Provider for .NET LOB Objects

ODP.NET provides three objects for manipulating LOB data: `OracleBFile`, `OracleBlob`, and `OracleClob`.

[Table 3–17](#) shows the proper ODP.NET object to use for a particular Oracle LOB type.

Table 3–17 ODP.NET LOB Objects

| Oracle LOB Type | ODP.NET LOB Object |
|-----------------|--------------------|
| BFILE | OracleBFile |
| BLOB | OracleBlob |
| CLOB | OracleClob |
| NCLOB | OracleClob |

The ODP.NET LOB objects can be obtained by calling the proper typed accessor on the `OracleDataReader` object, or by calling the proper typed accessor as an output parameter on a command execution with the proper bind type.

All ODP.NET LOB objects inherit from the `.NET Stream` class to provide generic `Stream` operations. The LOB data (except for `BFILE` types) can be updated using the ODP.NET LOB objects by using methods such as `Write`. Data is not cached in the LOB objects when read and write operations are carried out. Therefore, each read or write request incurs a database round-trip. The `OracleClob` object overloads the `Read` method, providing two ways to read data from a `CLOB`. The `Read` method that takes a `byte[]` as the buffer populates it with `CLOB` data as Unicode byte array. The `Read` method that takes a `char[]` as the buffer populates it with Unicode characters.

Additional methods can also be found on the `OracleBFile` object. An `OracleBFile` object must be explicitly opened using the `OpenFile` method before any data can be read from it. To close a previously opened `BFILE`, use the `CloseFile` method.

Every ODP.NET LOB object is a connected object and requires a connection during its lifetime. If the connection associated with a LOB object is closed, then the LOB object is not usable and should be disposed of.

If an ODP.NET LOB object is obtained from an `OracleDataReader` object through a typed accessor, then its `Connection` property is set with a reference to the same `OracleConnection` object used by the `OracleDataReader` object. If a LOB object is obtained as an output parameter, then its `Connection` property is set with a reference to the same `OracleConnection` property used by the `OracleCommand` object. If a LOB object is obtained by invoking an ODP.NET LOB object constructor to create a temporary LOB, the `Connection` property is set with a reference to the `OracleConnection` object provided in the constructor.

The ODP.NET LOB object `Connection` property is read-only and cannot be changed during its lifetime. In addition, the ODP.NET LOB types object can be used only within the context of the same `OracleConnection` referenced by the ODP.NET LOB object. For example, the ODP.NET LOB `Connection` property must reference the same connection as the `OracleCommand` object if the ODP.NET LOB object is a parameter of the `OracleCommand`. If that is not the case, ODP.NET raises an exception when the command is executed.

See Also: *Oracle Database SecureFiles and Large Objects Developer's Guide* for complete information about Oracle Database 10g LOBs and how to use them

Updating LOBs Using a DataSet

`BFILE` and `BLOB` data are stored in the `DataSet` as byte arrays while `CLOB` and `NCLOB` data are stored as strings. In a similar manner to other types, an `OracleDataAdapter` object can be used to fill and update LOB data changes along with the use of the `OracleCommandBuilder` object for automatically generating SQL.

Note that an Oracle LOB column can store up to 4 GB of data. When the LOB data is fetched into the `DataSet`, the actual amount of LOB data the `DataSet` can hold for a LOB column is limited to the maximum size of a .NET string type, which is 2 GB. Therefore, when fetching LOB data that is greater than 2 GB, ODP.NET LOB objects must be used to avoid any data loss.

Updating LOBs Using `OracleCommand` and `OracleParameter`

To update LOB columns, LOB data can be bound as a parameter for SQL statements, anonymous PL/SQL blocks, or stored procedures. The parameter value can be set as a .NET Framework type, ODP.NET type, or as an ODP.NET LOB object type. For example, when inserting .NET string data into a LOB column in an Oracle9i database or later, that parameter can be bound as `OracleDbType.Varchar2`. For a parameter whose value is set to an `OracleClob` object, the parameter should be bound as `OracleDbType.Clob`.

Updating LOBs Using ODP.NET LOB Objects

Oracle BFILEs cannot be updated; therefore, `OracleBFile` objects do not allow updates to BFILE columns.

Two requirements must be met to update LOB data using ODP.NET LOB objects:

1. A transaction must be started before a LOB column is selected.

The transaction must be started using the `BeginTransaction` method on the `OracleConnection` object before the command execution, so that the lock can be released when the `OracleTransaction.Commit` or `Rollback` method is invoked.

2. The row in which the LOB column resides must be locked; as part of an entire result set, or on a row-by-row basis.

- a. Locking the entire result set

Add the `FOR UPDATE` clause to the end of the `SELECT` statement. After execution of the command, the entire result set is locked.

- b. Locking the row - there are two options:

- Invoke one of the `OracleDataReader` typed accessors (`GetOracleClobForUpdate` or `GetOracleBlobForUpdate`) on the `OracleDataReader` object to obtain an ODP.NET LOB object, while also locking the current row.

This approach requires a primary key, unique column(s), or a ROWID in the result set because the `OracleDataReader` object must uniquely identify the row to re-select it for locking.

- Execute an `INSERT` or an `UPDATE` statement that returns a LOB in the `RETURNING` clause.

Temporary LOBs

Temporary LOBs can be instantiated for BLOB, CLOB, and NLOB objects. To instantiate an ODP.NET LOB object that represents a temporary LOB, the `OracleClob` or the `OracleBlob` constructor can be used.

Temporary ODP.NET LOB objects can be used for the following purposes:

- To initialize and populate a LOB column with empty or non-empty LOB data.

- To pass a LOB type as an input parameter to a SQL statement, an anonymous PL/SQL block, or a stored procedure.
- To act as the source or the destination of data transfer between two LOB objects as in the `CopyTo` operation.

Note: Temporary LOBs are not transaction aware. Commit and rollback operations do not affect the data referenced by a temporary LOB.

ODP.NET XML Support

ODP.NET allows the extraction of data from relational and object-relational tables and views as XML documents. The use of XML documents for insert, update, and delete operations to the database is also allowed. Oracle Database supports XML natively in the database, through Oracle XML DB, a distinct group of technologies related to high-performance XML storage and retrieval. Oracle XML DB is an evolution of the database that encompasses both SQL and XML data models in a highly interoperable manner, providing native XML support.

Note: ODP.NET, Managed Driver does not support ODP.NET XML Classes. However, it does interoperate with .NET Framework's XML classes, support XQuery, and support SQL to XML implicit conversion between Oracle Database to .NET as string or LOB client-side data types.

ODP.NET, Managed Driver follows XPath 1.0 specification and hence it does not support default XML namespaces. XML namespaces must be explicitly added to search or update nodes. This behavior differs from ODP.NET, Unmanaged Driver.

For samples related to ODP.NET XML support in ODAC installs, see the following directory:

`ORACLE_BASE\ORACLE_HOME\ODACsamples`

This section includes these topics:

- [Supported XML Features](#)
- [OracleXmlType and Connection Dependency](#)
- [Updating XMLType Data in the Database](#)
- [Updating XML Data in OracleXmlType](#)
- [Characters with Special Meaning in XML](#)
- [Retrieving Query Result Set as XML](#)
- [Data Manipulation Using XML](#)

Supported XML Features

XML support in ODP.NET provides the ability to do the following:

- Store XML data natively in the database as the Oracle database native type, `XMLType`.

- Access relational and object-relational data as XML data from an Oracle Database instance into the Microsoft .NET environment, and process the XML using the Microsoft .NET Framework.
- Save changes to the database using XML data.
- Execute XQuery statements.

See Also: ["XQuery Support"](#) on page 3-79

For the .NET application developer, these features include the following:

- Enhancements to the `OracleCommand`, `OracleConnection`, and `OracleDataReader` classes.
- The following XML-specific classes:
 - `OracleXmlType`
`OracleXmlType` objects are used to retrieve Oracle native `XMLType` data.
 - `OracleXmlStream`
`OracleXmlStream` objects are used to retrieve XML data from `OracleXmlType` objects as a read-only .NET Stream object.
 - `OracleXmlQueryProperties`
`OracleXmlQueryProperties` objects represent the XML properties used by the `OracleCommand` class when the `XmlCommandType` property is `Query`.
 - `OracleXmlSaveProperties`
`OracleXmlSaveProperties` objects represent the XML properties used by the `OracleCommand` class when the `XmlCommandType` property is `Insert`, `Update`, or `Delete`.

See Also:

- ["OracleCommand Class"](#) on page 6-12
- ["OracleXmlType Class"](#) on page 7-38
- ["OracleXmlStream Class"](#) on page 7-23
- ["OracleXmlQueryProperties Class"](#) on page 7-3
- ["OracleXmlSaveProperties Class"](#) on page 7-13
- *Oracle XML DB Developer's Guide*

XQuery Support

ODP.NET supports the XQuery language through a native implementation of SQL/XML functions, `XMLQuery` and `XMLTable`. When executing XQuery statements, Oracle XML DB generally evaluates XQuery expressions by compiling them into the same underlying structures as relational queries. Queries are optimized, leveraging both relational-database and XQuery-specific optimization technologies, so that Oracle XML DB serves as a native XQuery engine.

The treatment of all XQuery expressions, whether natively compiled or evaluated functionally, is transparent: programmers do not need to change their code to take advantage of XQuery optimizations.

See Also: *Oracle XML DB Developer's Guide* to learn more about Oracle's XQuery support

OracleXmlType and Connection Dependency

The read-only `Connection` property of the `OracleXmlType` class holds a reference to the `OracleConnection` object used to instantiate the `OracleXmlType` class.

How the `OracleXmlType` object obtains a reference to an `OracleConnection` object depends on how the `OracleXmlType` class is instantiated:

- Instantiated from an `OracleDataReader` class using the `GetOracleXmlType`, `GetOracleValue`, or `GetOracleValues` method:
The `Connection` property is set with a reference to the same `OracleConnection` object used by the `OracleDataReader` object.
- Instantiated by invoking an `OracleXmlType` constructor with one of the parameters of type `OracleConnection`:
The `Connection` property is set with a reference to the same `OracleConnection` object provided in the constructor.
- Instantiated by invoking an `OracleXmlType(OracleClob)` constructor:
The `Connection` property is set with a reference to the `OracleConnection` object used by the `OracleClob` object.

An `OracleXmlType` object that is associated with one connection cannot be used with a different connection. For example, if an `OracleXmlType` object is obtained using `OracleConnection A`, that `OracleXmlType` object cannot be used as an input parameter of a command that uses `OracleConnection B`. By checking the `Connection` property of the `OracleXmlType` objects, the application can ensure that `OracleXmlType` objects are used only within the context of the `OracleConnection` referenced by its `connection` property. Otherwise, ODP.NET raises an exception.

Updating XMLType Data in the Database

Updating `XMLType` columns does not require a transaction. However, encapsulating the entire database update process within a transaction is highly recommended. This allows the updates to be rolled back if there are any errors.

`XMLType` columns in the database can be updated using Oracle Data Provider for .NET in a few ways:

- [Updating with DataSet, OracleDataAdapter, and OracleCommandBuilder](#)
- [Updating with OracleCommand and OracleParameter](#)

Updating with DataSet, OracleDataAdapter, and OracleCommandBuilder

If the `XMLType` column is fetched into the `DataSet`, the `XMLType` data is represented as a .NET `String`.

Modifying `XMLType` data in the `DataSet` does not require special treatment. `XMLType` data can be modified in the same way as any data that is stored in the `DataSet`. When a change is made and the `OracleDataAdapter.Update` method is invoked, the `OracleDataAdapter` object ensures that the `XMLType` data is handled properly. The `OracleDataAdapter` object uses any custom SQL `INSERT`, `UPDATE`, or `DELETE` statements that are provided. Otherwise, valid SQL statements are generated by the `OracleCommandBuilder` object as needed to **flush** the changes to the database.

Updating with OracleCommand and OracleParameter

The `OracleCommand` class provides a powerful way of updating `XMLType` data, especially with the use of an `OracleParameter` object. To update columns in a database table, the new value for the column can be passed as an input parameter of a command.

Input Binding To update an `XMLType` column in the database, a SQL statement can be executed using static values. In addition, input parameters can be bound to SQL statements, anonymous PL/SQL blocks, or stored procedures to update `XMLType` columns. The parameter value can be set as .NET Framework Types, ODP.NET Types, or `OracleXmlType` objects.

While `XMLType` columns can be updated using an `OracleXmlType` object, having an instance of an `OracleXmlType` class does not guarantee that the `XMLType` column in the database can be updated.

Setting XMLType Column to NULL Value Applications can set an `XMLType` column in the database to a `NULL` value, with or without input binding, as follows:

- Setting `NULL` values in an `XMLType` column with input binding

To set the `XMLType` column to `NULL`, the application can bind an input parameter whose value is `DBNull.Value`. This indicates to the `OracleCommand` object that a `NULL` value is to be inserted.

Passing in a null `OracleXmlType` object as an input parameter does not insert a `NULL` value into the `XMLType` column. In this case, the `OracleCommand` object raises an exception.

- Setting `NULL` Values in an `XMLType` Column without input binding

The following example demonstrates setting `NULL` values in an `XMLType` column without input binding:

```
// Create a table with an XMLType column in the database
CREATE TABLE XML_TABLE(NUM_COL number, XMLTYPE_COL xmltype);
```

An application can set a `NULL` value in the `XMLType` column by explicitly inserting a `NULL` value or by not inserting anything into that column as in the following examples:

```
insert into xml_table(xmltype_col) values(NULL);

update xml_table t set t.xmltype_col=NULL;
```

Setting XMLType Column to Empty XML Data The `XMLType` column can be initialized with empty XML data, using a SQL statement:

```
// Create a table with an XMLType column in the database
CREATE TABLE XML_TABLE(NUM_COL number, XMLTYPE_COL xmltype);

INSERT INTO XML_TABLE (NUM_COL, XMLTYPE_COL) VALUES (4,
XMLType.createxml('<DOC/>'));
```

Updating XML Data in OracleXmlType

The following are ways that XML data can be updated in an `OracleXmlType` object.

- The XML data can be updated by passing an XPATH expression and the new value to the `Update` method on the `OracleXmlType` object.
- The XML data can be retrieved on the client side as the .NET Framework `XmlDocument` object using the `GetXmlDocument` method on the `OracleXmlType` object. This XML data can then be manipulated using suitable .NET Framework classes. A new `OracleXmlType` can be created with the updated XML data from the .NET Framework classes. This new `OracleXmlType` is bound as an input parameter to an update or insert statement.

Characters with Special Meaning in XML

The following characters in [Table 3–18](#) have special meaning in XML. For more information, refer to the XML 1.0 specifications

Table 3–18 Characters with Special Meaning in XML

| Character | Meaning in XML | Entity Encoding |
|-----------|-------------------------------------|-----------------|
| < | Begins an XML tag | < |
| > | Ends an XML tag | > |
| " | Quotation mark | " |
| ' | Apostrophe or single quotation mark | ' |
| & | Ampersand | & |

When these characters appear as data in an XML element, they are replaced with their equivalent entity encoding.

Also certain characters are not valid in XML element names. When SQL identifiers (such as column names) are mapped to XML element names, these characters are converted to a sequence of hexadecimal digits, derived from the Unicode encoding of the character, bracketed by an introductory underscore, a lowercase `x` and a trailing underscore. A blank space is not a valid character in an XML element name. If a SQL identifier contains a space character, then in the corresponding XML element name, the space character is replaced by `_x0020_`, which is based on Unicode encoding of the space character.

Retrieving Query Result Set as XML

This section discusses retrieving the result set from a SQL query as XML data.

Handling Date and Time Format

The generated XML `DATE` and `TIMESTAMP` formats are based on the standard XML Schema formats.

See Also:

<http://www.w3.org/TR/2004/REC-xmlschema-2-20041028/datatypes.html#isoformats> for more information on the XML Schema specification.

Characters with Special Meaning in Column Data

If the data in any of the select list columns in the query contains any characters with special meaning in XML (see [Table 3-18](#)), these characters are replaced with their corresponding entity encoding in the result XML document.

The following examples demonstrate how ODP.NET handles the angle bracket characters in the column data:

```

/* Database Setup
connect scott/tiger@oracle
drop table specialchars;
create table specialchars ("id" number, name varchar2(255));
insert into specialchars values (1, '<Jones>');
commit;
*/

// C#

using System;
using System.Data;
using System.Xml;
using Oracle.DataAccess.Client;

class QueryResultAsXMLSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();

        con.ConnectionString = "User Id=scott;Password=tiger;Data Source=oracle;";
        con.Open();

        // Create the command
        OracleCommand cmd = new OracleCommand("", con);

        // Set the XML command type to query.
        cmd.XmlCommandType = OracleXmlCommandType.Query;

        // Set the SQL query
        cmd.CommandText = "select * from specialchars";

        // Set command properties that affect XML query behavior.
        cmd.BindByName = true;

        // Set the XML query properties
        cmd.XmlQueryProperties.MaxRows = -1;

        // Get the XML document as an XmlReader.
        XmlReader xmlReader = cmd.ExecuteXmlReader();
        XmlDocument xmlDocument = new XmlDocument();

        xmlDocument.PreserveWhitespace = true;
        xmlDocument.Load(xmlReader);
        Console.WriteLine(xmlDocument.OuterXml);

        // Close and Dispose OracleConnection object
        con.Close();
        con.Dispose();
    }
}

```

The following XML document is generated for that table: The XML entity encoding that represents the angle brackets appears in bold.

```
<?xml version = '1.0'?>
<ROWSET>
  <ROW>
    <id>1</id >
    <NAME>&lt;Jones&gt;</NAME>
  </ROW>
</ROWSET>
```

Characters in Table or View Name

If a table or view name has any non-alphanumeric characters other than an underscore (_), the table or view name must be enclosed in quotation marks.

For example, to select all entries from a table with the name test'ing, the CommandText property of the OracleCommand object must be set to the following string:

```
"select * from \"test'ing\"";
```

Case-Sensitivity in Column Name to XML Element Name Mapping

The mapping of SQL identifiers (column names) to XML element names is case-sensitive, and the element names are in exactly the same case as the column names of the table or view.

However, the root tag and row tag names are case-insensitive. The following example demonstrates case-sensitivity in this situation:

```
//Create the following table
create table casesensitive_table ("Id" number, NAME varchar2(255));

//insert name and id
insert into casesensitive_table values(1, 'Smith');
```

The following XML document is generated:

```
<?xml version = '1.0'?>
  <ROWSET>
    <ROW>
      <Id>1</Id>
      <NAME>Smith</NAME>
    </ROW>
  </ROWSET>
```

Note that the element name for the Id column matches the case of the column name.

Column Name to XML Element Name Mapping

For each row generated by the SQL query, the SQL identifier (column name) maps to an XML element in the generated XML document, as shown in the following example:

```
// Create the following table
create table emp_table (EMPLOYEE_ID NUMBER(4), LAST_NAME varchar2(25));
// Insert some data
insert into emp_table values(205, 'Higgins');
```

The SQL query, `SELECT * FROM EMP_TABLE`, generates the following XML document:

```
<?XML version="1.0"?>
```

```

<ROWSET>
  <ROW>
    <EMPLOYEE_ID>205</EMPLOYEE_ID>
    <LAST_NAME>Higgins</LAST_NAME>
  </ROW>
</ROWSET>

```

The `EMPLOYEE_ID` and `LAST_NAME` database columns of the `employees` table map to the `EMPLOYEE_ID` and `LAST_NAME` elements of the generated XML document.

This section demonstrates how Oracle database handles the mapping of SQL identifiers to XML element names, when retrieving query results as XML from the database. The demonstration uses the `specialchars` table involving the `some id` column.

```

// Create the specialchars table
create table specialchars ("some id" number, name varchar2(255));

```

Note that the `specialchars` table has a column named `some id` that contains a blank space character. The space character is not allowed in an XML element name.

When retrieving the query results as XML, the SQL identifiers in the query select list can contain characters that are not valid in XML element names. When these SQL identifiers (such as column names) are mapped to XML element names, each of these characters is converted to a sequence of hexadecimal digits, derived from the Unicode encoding of the characters, bracketed by an introductory underscore, a lowercase `x`, and a trailing underscore.

Thus, the SQL query in the following example can be used to get a result as an XML document from the `specialchars` table:

```
select "some id", name from specialchars;
```

See Also: ["Characters with Special Meaning in XML"](#) on page 3-82

Improving Default Mapping You can improve the default mapping of SQL identifiers to XML element names by using the following techniques:

- Modify the source. Create an object-relational view over the source schema, and make that view the new source.
- Use cursor subqueries and `cast-multiset` constructs in the SQL query.
- Create an alias for the column or attribute names in the SQL query. Prefix the aliases with an at sign (`@`) to map them to XML attributes instead of XML elements.
- Modify the XML document. Use [Extensible Stylesheet Language Transformation \(XSLT\)](#) to transform the XML document. Specify the XSL document and parameters. The transformation is done automatically after the XML document is generated from the relational data. Note that this may have an impact on performance.
- Specify the name of the root tag and row tag used in the XML document.

Object-Relational Data

ODP.NET can generate an XML document for data stored in object-relational columns, tables, and views, as shown in the following example:

```
// Create the following tables and types
CREATE TYPE "EmployeeType" AS OBJECT (EMPNO NUMBER, ENAME VARCHAR2(20));
/
CREATE TYPE EmployeeListType AS TABLE OF "EmployeeType";
/
CREATE TABLE mydept (DEPTNO NUMBER, DEPTNAME VARCHAR2(20),
    EMPLIST EmployeeListType)
    NESTED TABLE EMPLIST STORE AS EMPLIST_TABLE;
INSERT INTO mydept VALUES (1, 'depta',
    EmployeeListType("EmployeeType"(1, 'empa')));
```

The following XML document is generated for the table:

```
<?xml version = "1.0"?>
<ROWSET>
  <ROW>
    <DEPTNO>1</DEPTNO>
    <DEPTNAME>depta</DEPTNAME>
    <EMPLIST>
      <EmployeeType>
        <EMPNO>1</EMPNO>
        <ENAME>empa</ENAME>
      </EmployeeType>
    </EMPLIST>
  </ROW>
</ROWSET>
```

ODP.NET encloses each item in a collection element, with the database type name of the element in the collection. The `mydept` table has a collection in the `EMPLIST` database column and each item in the collection is of type `EmployeeType`. Therefore, in the XML document, each item in the collection is enclosed in the type name `EmployeeType`, which appears in bold in the example.

NULL Values

If any database row has a column with a NULL value, then that column does not appear for that row in the generated XML document.

Data Manipulation Using XML

This section discusses making changes to the database data using XML.

Handling Date and Time Format

The generated XML `DATE` and `TIMESTAMP` formats are based on the standard XML Schema formats.

See Also:

<http://www.w3.org/TR/2004/REC-xmlschema-2-20041028/datatypes.html#isoformats> for more information on the XML Schema specification.

Saving Changes Using XML

Changes can be saved to database tables and views using XML data. However, insert, update, and delete operations cannot be combined in a single XML document. ODP.NET cannot accept a single XML document and determine which are insert, update, or delete changes.

The insert change must be in an XML document containing only rows to be inserted, the update changes only with rows to be updated, and the delete changes only with rows to be deleted.

For example, using the `employees` table that comes with the HR sample schema, you can specify the following query:

```
select employee_id, last_name from employees where employee_id = 205;
```

The following XML document is generated:

```
<?xml version = '1.0'?>
<ROWSET>
  <ROW>
    <EMPLOYEE_ID>205</EMPLOYEE_ID>
    <LAST_NAME>Higgins</LAST_NAME>
  </ROW>
</ROWSET>
```

To change the name of employee 205 from **Higgins** to **Smith**, specify the `employees` table and the XML data containing the changes as follows:

```
<?xml version = '1.0'?>
<ROWSET>
  <ROW>
    <EMPLOYEE_ID>205</EMPLOYEE_ID>
    <LAST_NAME>Smith</LAST_NAME>
  </ROW>
</ROWSET>
```

Characters with Special Meaning in Column Data

If the data in any of the elements in the XML document contains characters that have a special meaning in XML (see [Table 3-18](#)), these characters must be replaced with appropriate entity encoding, or be preceded by an escape character in the XML document, so that the data is stored correctly in the database table column. Otherwise, ODP.NET throws an exception.

The following example demonstrates how ODP.NET handles the angle bracket special characters in the column data, using entity encoding:

```
// Create the following table
create table specialchars ("id" number, name varchar2(255));
```

The following XML document can be used to insert values (1, '<Jones>') into the `specialchars` table. The XML entity encoding that represents the angle brackets appears in bold.

```
<?xml version = '1.0'?>
<ROWSET>
  <ROW>
    <id>1</id >
    <NAME>&lt;Jones&gt;</NAME>
  </ROW>
</ROWSET>
```

Characters with Special Meaning in Table or View Name

If a table or view name has any non-alphanumeric characters other than an underscore (`_`), the table or view name must be enclosed in quotation marks.

For example, to save changes to a table with the name `test'ing`, the `OracleCommand.XmlSaveProperties.TableName` property must be set to `"\"test'ing\""`.

Case-Sensitivity in XML Element Name to Column Name Mapping

For each XML element that represents a row of data in the XML document, the child XML elements map to database column names. The mapping of the child element name to the column name is always case-sensitive, but the root tag and row tag names are case-insensitive. The following example demonstrates this case-sensitivity:

```
//Create the following table
create table casesensitive_table ("Id" number, NAME varchar2(255));
```

The following XML document can be used to insert values (1, Smith) into the `casesensitive_table`:

```
<?xml version = '1.0'?>
  <ROWSET>
    <ROW>
      <Id>1</Id>
      <NAME>Smith</NAME>
    </ROW>
  </ROWSET>
```

Note that the element name for the `Id` column matches the case of the column name.

XML Element Name to Column Name Mapping

This section describes how Oracle database handles the mapping of XML element names to column names when using XML for data manipulation in the database. The following `specialchars` table involving the `some id` column demonstrates this handling.

```
// Create the specialchars table
create table specialchars ("some id" number, name varchar2(255));
```

Note that the `specialchars` table has a column named `some id` that contains a blank space character. The space character is not allowed in an XML element name.

Saving Changes to a Table Using an XML Document

When an XML document is used to save changes to a table or view, the `OracleCommand.XmlSaveProperties.UpdateColumnsList` property is used to specify the list of columns to update or insert.

When an XML document is used to save changes to a column in a table or view, and the corresponding column name contains any of the characters that are not valid in an XML element name, the escaped column name must be specified in the `UpdateColumnsList` property as in the following example.

The following XML document can be used to insert values (2, `<Jones>`) into the `specialchars` table:

```
<?xml version = '1.0'?>
  <ROWSET>
    <ROW>
      <some_x0020_id>2</some_x0020_id>
      <NAME>&lt;Jones&gt;</NAME>
    </ROW>
  </ROWSET>
```

The following example specifies the list of columns to update or insert:

```

/* Database Setup
connect scott/tiger@oracle
drop table specialchars;
create table specialchars ("some id" number, name varchar2(255));
insert into specialchars values (1, '<Jones>');
commit;
*/

// C#

using System;
using System.Data;
using System.Xml;
using Oracle.DataAccess.Client;

class InsertUsingXmlDocSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();

        con.ConnectionString = "User Id=scott;Password=tiger;Data Source=oracle;";
        con.Open();
        Console.WriteLine("Connected Successfully");

        // Create the command
        OracleCommand cmd = new OracleCommand("", con);

        // Set the XML command type to query.
        cmd.XmlCommandType = OracleXmlCommandType.Insert;

        // Set the XML document
        cmd.CommandText = "<?xml version = '1.0'?>\n" + "<ROWSET>\n" + "<ROW>\n" +
            "<some_x0020_id>2</some_x0020_id>\n" + "<NAME>&lt;Jones&gt;</NAME>\n" +
            "</ROW>\n" + "</ROWSET>\n";
        cmd.XmlSaveProperties.Table = "specialchars";

        string[] ucols = new string[2];

        ucols[0] = "some_x0020_id";
        ucols[1] = "NAME";
        cmd.XmlSaveProperties.UpdateColumnsList = ucols;

        // Insert rows
        int rows = cmd.ExecuteNonQuery();

        Console.WriteLine("Number of rows inserted successfully : {0} ", rows);

        // Close and Dispose OracleConnection object
        con.Close();
        con.Dispose();
    }
}

```

Improving Default Mapping You can improve the default mapping by using the following techniques:

- Modify the target. Create an object-relational view over the target schema, and make the view the new target.
- Modify the XML document. Use XSLT to transform the XML document. Specify the XSL document and parameters. The transformation is done before the changes are saved. Note that this may have an impact on performance.
- Specify the name of the row tag used in the XML document.

Object-Relational Data

Changes in an XML document can also be saved to object-relational data. Each item in a collection can be specified in one of the following ways in the XML document:

- By enclosing the database type name of the item as the XML element name.
- By enclosing the name of the database column holding the collection with `ITEM` appended as the XML element name.

Multiple Tables

Oracle Database does not save changes to multiple relational tables that have been joined together. Oracle recommends that you create a view on those relational tables, and then update that view. If the view cannot be updated, triggers can be used instead.

See Also: *Oracle Database SQL Language Reference* for the description and syntax of the `CREATE VIEW` statement

Commit Transactions

When the changes in an XML document are made, either all the changes are committed, or if an error occurs, all changes are rolled back.

Oracle User-Defined Types (UDTs) and .NET Custom Types

ODP.NET has the ability to represent Oracle UDTs found in the database as custom types in .NET applications. UDTs are useful in representing complex entities as a single object that can be shared among applications. Oracle products, such as Oracle Spatial and Oracle XML DB, use their own complex types frequently.

To represent Oracle UDTs as .NET custom types, applications must apply .NET attributes to custom classes and structs, and to their public fields and properties.

Note: ODP.NET, Managed Driver does not support UDTs and .NET Custom Types

To convert between UDTs and custom types, ODP.NET uses custom interfaces.

This section discusses the following topics:

- [Oracle User-Defined Types \(UDTs\)](#)
- [Custom Types](#)
- [Specifying Custom Type Mappings](#)
- [Converting Between Custom Types and Oracle UDTs](#)
- [Oracle UDT Attribute Mappings](#)
- [Oracle UDT Retrieval from OracleDataReader](#)

- [Oracle UDT Metadata Retrieval from OracleDataReader](#)
- [Oracle UDT Parameter Binding with OracleParameter](#)
- [Populating the DataSet with Oracle UDTs](#)
- [UDT Method Invocation](#)
- [Configuration Settings for Oracle UDTs](#)

Oracle User-Defined Types (UDTs)

Oracle Data Provider for .NET supports Oracle object types or user-defined types (UDTs), which are defined in the Oracle database.

There are two kinds of UDTs:

- Object types (Oracle Object)
- Collection types (which can be `VARRAY` types or nested table types)

Additionally, ODP.NET supports references (`REF`) to object types.

See Also: ["OracleRef Class"](#) on page 16-52

The term UDT is used interchangeably with Oracle object types and abstract data types (ADTs).

See Also: *Oracle Database Object-Relational Developer's Guide* for complete descriptions of object types

The name of the Oracle UDT is case-sensitive and must be in the form `schema_name.type_name`.

UDT samples are provided in the `ORACLE_BASE\ORACLE_HOME\ODP.NET\Samples\UDT` directory.

Custom Types

Oracle Data Provider for .NET supports UDTs by representing Oracle UDTs defined in the database as .NET types, that is, custom types. For every Oracle UDT that the application wishes to fetch and manipulate, one custom type factory and one custom type are needed. The custom factory class is solely responsible for instantiating the custom type. ODP.NET uses the interfaces implemented on the custom factory classes to instantiate custom types at run time. Custom types define the mapping between the Oracle UDT attributes or elements to the .NET members. ODP.NET uses the interfaces implemented on the custom type instances to transfer values between the Oracle UDT and the custom type at run time.

Custom types can be .NET classes or structures. They can represent either Oracle Objects or Oracle Collections. Custom types can be implemented manually by the application developer or generated through an ODP.NET code generation tool.

Once the factory class and the custom type are defined and meet the implementation requirements, the application may set ODP.NET to automatically discover the mapping between the Oracle UDT and the custom type. This discovery process is based on the attribute that is applied on the custom factory class. Alternatively, the application can provide an explicit mapping through a configuration file.

Oracle Collections can be represented as an array of .NET Types. For example, an Oracle Collection type of NUMBER can be mapped to an `int []`. Moreover, an Oracle Collection type of an Oracle UDT can be mapped to an array of the custom type.

Custom types must adhere to certain requirements in order for ODP.NET to represent Oracle UDTs as custom types. These requirements are as follows:

Required Custom Type Implementations

This section lists the required implementations for a custom .NET class or structure.

- `Oracle.DataAccess.Types.IOracleCustomType` interface implementation
This interface is used for conversions between custom types and Oracle UDTs.
The interface methods are implemented using the static methods of the `OracleUdt` class.
- Custom Type Factories
A custom type factory is used to create an instance of a custom type. A custom type factory is an implementation of either the `IOracleCustomTypeFactory` interface, the `IOracleArrayTypeFactory` interface, or both interfaces, as follows:
 - To create a custom type that represents an Oracle Object, the custom type or a separate custom type factory class must implement the `Oracle.DataAccess.Types.IOracleCustomTypeFactory` interface.
 - To create a custom type that represents an Oracle Collection, the custom type or a separate custom type factory class must implement the `Oracle.DataAccess.Types.IOracleCustomTypeFactory` interface and the `Oracle.DataAccess.Types.IOracleArrayTypeFactory` interface.
 - To create an array type that represents an Oracle Collection, a custom type factory class must implement the `Oracle.DataAccess.Types.IOracleArrayTypeFactory` interface.
- Custom Type Member Mapping Attributes
The custom type member mapping attributes specify the mapping between custom type members and either Oracle object attributes or Oracle collection elements.
There are two types of custom type member mapping attributes:
 - `OracleObjectMappingAttribute`
This attribute specifies the mapping between custom type members and Oracle object attributes for custom types that represent Oracle objects.
This attribute must be applied to each custom type member (either field or property) that represents an Oracle Object attribute.

Note: Not all Oracle object attributes need to be mapped to custom type members. If there is no `OracleObjectMappingAttribute` for a particular object attribute, ODP.NET ignores that object attribute when converting between Oracle objects and custom types.

 - `OracleArrayMappingAttribute`
This attribute specifies the custom type member that stores the elements of an Oracle collection for custom types representing Oracle collections.

The attribute must be specified on only one of the custom type members.

- `Oracle.DataAccess.Types.INullable` interface implementation

This interface is used to determine if an instance of a custom type represents a null UDT.

The `IsNull` property of the interface enables applications and ODP.NET to determine whether or not the UDT is null.

- Static `Null` field

The public static `Null` property is used to return a null UDT.

This property returns a custom type with an `IsNull` property that returns true.

Optional Custom Type Implementations

The following are optional:

- `IXMLSerializable`

The `IXMLSerializable` interface is used in the .NET 2.0 framework to enable conversion between the custom type and its XML representation.

This interface is only used if the serialization and deserialization of a custom type is needed in the `DataSet`.

- Static `Parse` and Public `ToString` methods

These methods enable conversion between the custom type and its string representation.

These methods are invoked when a `DataGrid` control is used to accept changes and display instance values.

- Type Inheritance

Type Inheritance refers to the process of deriving an Oracle UDT in the database from a super type.

If the custom type represents an Oracle UDT that is derived from a super type, the custom class should follow the same type hierarchy, that is, the custom class should be derived from another custom class that represents the super type defined in the database.

- `OracleCustomTypeMappingAttribute`

The `OracleCustomTypeMappingAttribute` object specifies the mapping between a custom type (or an array type) and an Oracle UDT.

There must be a unique custom type factory for each Oracle UDT used by the application as follows:

- Oracle Object Types:

The custom type factory must return a custom type that only represents the specified Oracle Object Type.

- Oracle Collection Types:

The custom type factory may return a custom type that can be used by other Oracle Collection Types. This is common when an array type is used to represent an Oracle Collection, for example, when an `int[]` is used to represent a collection of `NUMBERS`.

If the `OracleCustomTypeMappingAttribute` is not specified, then custom type mappings must be specified through XML configuration files, that is, `machine.config`, and either `app.config` for Windows applications or `web.config` for web applications.

See Also:

- ["IOracleCustomType Interface"](#) on page 16-26
- ["OracleRef Class"](#) on page 16-52
- ["IOracleCustomTypeFactory Interface"](#) on page 16-30

Specifying Custom Type Mappings

After creating a custom type, the application must specify a custom type mapping that maps the custom type to an Oracle UDT in the database. This can be done using a custom type factory or XML in configuration files.

Using XML to specify custom type mappings has priority, if both techniques have been implemented. At run time, if ODP.NET finds custom type mappings specified in configuration files, it ignores any custom type mappings specified through the `OracleCustomTypeMappingAttribute` object.

Custom type mappings cannot be specified using synonyms, regardless of whether or not the mapping is provided through the `OracleCustomTypeMappingAttribute` object or the XML configuration file.

See Also: *Oracle Developer Tools for Visual Studio help* sections on User-Defined Types Node, under Server Explorer for Visual Studio 2005 and Oracle Explorer for Visual Studio 2003, for further information on UDT mapping

This section contains these topics:

- ["Using a Custom Type Factory to Specify Custom Type Mappings"](#)
- ["Using XML in Configuration Files to Specify Custom Type Mappings"](#)

Using a Custom Type Factory to Specify Custom Type Mappings

The application can specify a custom type mapping using a custom type factory. The application supplies the name of the Oracle UDT, in the format `schema_name.type_name`, to an `OracleCustomTypeMappingAttribute` object and applies the name to the corresponding custom type factory. A custom type factory is a class or struct that implements either or both the `IOracleCustomTypeFactory` and `IOracleArrayTypeFactory` interfaces.

Note that for each Oracle UDT used by the application, there must be a unique custom type factory. Additionally, for Oracle Object Types, the custom type factory must return a custom type that uniquely represents the specified Oracle Object Type. For Oracle Collection Types, the custom type factory returns a custom type that can be used by other Oracle Collection Types. This is common when a custom type that is an array type represents an Oracle Collection, that is, when an `int []` is used to represent a collection of `NUMBERS`.

At run time, using reflection programming, ODP.NET discovers all the custom type mappings specified by the application through the `OracleCustomTypeMappingAttribute` object.

Note: The UDT name that is specified in the `OracleCustomTypeMappingAttribute` may not contain a period.

Using XML in Configuration Files to Specify Custom Type Mappings

The application can specify a custom type mapping with XML in configuration files, for example: using `machine.config`, and either `app.config` for Windows applications or `web.config` for web applications.

The custom type mappings must be specified in the `oracle.dataaccess.client` configuration section group. Each custom type mapping must be added to the collection of custom type mappings using the XML element `<add>`.

Each custom type mapping consists of a name attribute and a value attribute. The name attribute may be any user-specified name that represents the custom type mapping. The value attribute must begin with `udtMapping` and be followed by the required and optional attributes listed below.

Required Attributes

- `factoryName`

The case-sensitive assembly qualified name of the custom type factory class or struct.

If the assembly that defines the custom type factory does not have a strong name, then a partial assembly name consisting of just the assembly name is sufficient. In the case of strongly named assemblies, a complete assembly name is required. It must include the assembly name, the `Version`, `Culture`, `PublicKeyToken`.

- `typeName`

The case-sensitive name of the UDT defined in the database. By default all UDTs are created in the database with upper case names

- `schemaName`

The case-sensitive schema in which the UDT is defined in the database. By default all schemas are created in the database with upper case names

Optional Attributes

- `dataSource`

If specified, indicates that the custom type mapping applies only to Oracle UDTs defined in the database that the application connects to, as specified by the TNS name alias.

The Data Source is case-insensitive.

The following is an example of the format of the XML that can be specified in the configuration file for .NET 2.0:

```
<oracle.dataaccess.client>
  <settings>
    <add name="Person" value="udtMapping factoryName='Sample.PersonFactory,
      Sample, Version=1.0.0.0, Culture=neutral, PublicKeyToken=null'
      typeName='PERSON' schemaName='SCOTT' dataSource='oracle'"/>
    <add name="Student" value="udtMapping factoryName='Sample.StudentFactory,
      Sample, Version=1.0.0.0, Culture=neutral, PublicKeyToken=null'
      typeName='STUDENT' schemaName='SCOTT'"/>
  </settings>
```

```
</oracle.dataaccess.client>
```

Using Custom Type Mappings

During data retrieval, the application uses the custom type mappings to convert an Oracle UDT to a custom type. When data is provided back to the database through an input or input/output parameter, or by an update through an Oracle REF, the application uses the mappings to convert the custom type to an Oracle UDT.

In the case of input and input/output parameters, the application must also set the `OracleParameter.UdtTypeName` property to the user-defined type name of the parameter.

In certain cases, where Oracle UDTs are part of a type hierarchy, the custom type must be instantiated as a specific type in the type hierarchy. The Oracle UDT provided by the custom type mapping must be a subtype of the Oracle UDT specified by the `OracleParameter.UdtTypeName` property.

For example, the parameter for a stored procedure is of type, `SCOTT.PERSON` and has a subtype, `SCOTT.STUDENT`. The application has a custom class instance that represents `SCOTT.STUDENT`. The `UdtTypeName` is set to `SCOTT.PERSON`, but the custom type mapping indicates that the custom class is mapped to `SCOTT.STUDENT` and overrides the `UdtTypeName` when it instantiates the Oracle UDT. Thus, ODP.NET instantiates and binds Oracle UDTs appropriately when the custom object represents an Oracle UDT that is a subtype of the parameter type.

Converting Between Custom Types and Oracle UDTs

ODP.NET can convert between Oracle UDTs and custom types, if the proper attribute mappings are specified and the custom types are defined properly.

ODP.NET performs a conversion whenever an Oracle UDT is fetched as:

- In, out, in/out parameters bound for SQL or PL/SQL execution

The `DbType` property of `OracleParameter` must be set to `DbType.Object` or the `OracleDbType` property must be set to `OracleDbType.Object` or `OracleDbType.Array`.

For parameters that are user-defined types, the `UdtTypeName` property of the `OracleParameter` object must be always set to the parameter type.

Note: The `UdtTypeName` may differ from the Oracle UDT specified in the custom type mapping. This is the case when the parameter type is a super type of the Oracle UDT that the custom type represents.

- Column value retrieved from an `OracleDataReader` object

If the application requests for the value either through the `GetValue`, `GetValues`, `GetOracleValue`, `GetOracleValues`, `GetProviderSpecificValue`, or `GetProviderSpecificValues` methods or the `Item[]` property for a UDT column, ODP.NET finds the corresponding custom type that represents the Oracle UDT and carries out the proper conversion.

- Part of a Resultset that populates the `DataSet`

If the application populates the `DataSet` with a result that contains UDTs using the `Fill` method on the `OracleDataAdapter`, the `DataSet` is populated with custom types that represent Oracle UDTs. With ADO.NET 2.0, the `DataSet` is populated with custom types for UDT columns regardless of whether the `ReturnProviderSpecificTypes` on the `OracleDataAdapter` is set to `true` or `false`.

- A Object referenced through a REF

When an Object referenced by a REF is retrieved, the custom type that represents the Oracle UDT is returned.

The application can use the `OracleUdtFetchOption` method to control the copy of the Object that is returned as follows:

- If the `OracleUdtFetchOption.Cache` option is specified and a cached copy of the object exists, the cached copy is immediately returned. If no cached copy exists, the latest object copy from the database is cached and returned.
- If the `OracleUdtFetchOption.Server` option is specified, the latest object copy from the database is cached and returned. If the object is already cached, the latest object copy overwrites the existing one.
- If the `OracleUdtFetchOption.TransactionCache` option is specified, there are two possibilities within the same transaction:
 - If the object copy was previously retrieved using the `Server` or `TransactionCache` option, the `TransactionCache` option behavior becomes equivalent to the `Cache` option behavior.
 - If the object copy was not previously retrieved using the `Server` or `TransactionCache` option, the `TransactionCache` option behavior becomes equivalent to the `Server` option behavior.

Oracle UDT Attribute Mappings

Table 3–19 lists valid mappings of attributes (for objects) and elements (for collections), between Oracle UDT types and custom object types which can be either .NET types or Oracle provider-specific types (ODP.NET types).

Oracle collections do not have to map to a custom class. They can map to arrays of a specific type. Table 3–19 indicates those collections with elements of a specified Oracle type that can map to arrays of a .NET Type or a provider-specific type. For example, if an Oracle Collection is a `VARRAY` of `NUMBER(8)`, it can map to a `typeof(int[])`. This eliminates the need to construct a class that only holds an `int[]`.

For .NET 2.0, Oracle Collections can be mapped to Nullable types. This allows .NET 2.0 applications to obtain a nullable `int[]` which can hold null values in the `int[]`.

Note that Oracle UDT attributes and elements cannot be mapped to `object` or `object[]`.

Table 3–19 Attribute Mappings Between UDTs and Custom Object Types

| Type of UDT Attribute or Element | .NET Type | ODP.NET Type |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|
| BFILE #1 | <code>System.Byte[]</code> | <code>OracleBFile</code> |
| BINARY FLOAT | <code>System.Byte</code> , <code>System.Int16</code> , <code>System.Int32</code> , <code>System.Int64</code> , <code>System.Single</code> , <code>System.Double</code> , <code>System.Decimal</code> | <code>OracleDecimal</code> |

Table 3–19 (Cont.) Attribute Mappings Between UDTs and Custom Object Types

| Type of UDT Attribute or Element | .NET Type | ODP.NET Type |
|----------------------------------|-----------------------------------------------------------------------------------------------------------------------|--------------------|
| BINARY DOUBLE | System.Byte, System.Int16, System.Int32, System.Int64, System.Single, System.Double, System.Decimal | OracleDecimal |
| BLOB | System.Byte[] | OracleBlob |
| CHAR | System.Char[], System.String | OracleString |
| CLOB | System.Char[], System.String | OracleClob |
| DATE | System.DateTime | OracleDate |
| INTERVAL DAY TO SECOND | System.TimeSpan, | OracleIntervalDS |
| INTERVAL YEAR TO MONTH | System.Int64 | OracleIntervalYM |
| LONG RAW | System.Byte[] | OracleBinary |
| NCHAR | System.Char[], System.String | OracleString |
| NCLOB | System.Char[], System.String | OracleClob |
| Nested Table | <i>custom type, .NET type[], or custom type[]</i> | <i>ODP Type[]</i> |
| NUMBER | System.Byte, System.Int16, System.Int32, System.Int64, System.Single, System.Double, System.Decimal | OracleDecimal |
| NVARCHAR2 | System.Char[], System.String | OracleString |
| Object Type | <i>custom type</i> | N/A |
| RAW | System.Byte[] | OracleBinary |
| REF | System.String | OracleRef |
| TIMESTAMP | System.DateTime | OracleTimeStamp |
| TIMESTAMP WITH LOCAL TIME ZONE | System.DateTime | OracleTimeStampLTZ |
| TIMESTAMP WITH TIME ZONE | System.DateTime | OracleTimeStampTZ |
| VARCHAR2 | System.Char[], System.String | OracleString |
| VARRAY | <i>custom type, .NET type[], or custom type[]</i> | <i>ODP Type[]</i> |

Notes:

1. Conversion from a System.Byte[] to a BFILE is not supported, and therefore, System.Byte[] only represents a BFILE in read-only scenarios.

Oracle UDT Retrieval from OracleDataReader

In order to retrieve Oracle UDTs from the `OracleDataReader`, an application must specify a custom type mapping that determines the type that will represent the Oracle UDT. Once a custom type mapping has been specified and any necessary custom types have been created, the application can retrieve Oracle UDTs.

Table 3–20 shows the type and value returned from an `OracleDataReader` object based on the method invoked, the column type, and whether or not there is a valid Custom type mapping.

Note: *PS Object* refers to a provider-specific object.

Table 3–20 Type and Value Returned from `OracleDataReader` Object

| OracleDataReader method/property invocation | Column Data Type | Custom Type Mapping | Value Returned for Oracle UDT | NULL Value Returned for Oracle UDT |
|--------------------------------------------------------------------------------------------------------------------------|-----------------------|------------------------------|--------------------------------------------------------------------------------------------------|------------------------------------|
| Item[index], Item[name], GetValue(), GetValues() | Object, Collection | none | Exception thrown | Exception thrown |
| Item[index], Item[name], GetValue(), GetValues() | Object | <i>schema.type</i> | <i>custom object</i> | <code>DBNull.Value</code> |
| Item[index], Item[name], GetValue(), GetValues() | Collection | <i>schema.type</i> | <i>custom object</i> <i>custom object[]</i> <i>.NET Type[]</i> <i>PS object[]</i> | <code>DBNull.Value</code> |
| Item[index], Item[name], GetValue(), GetValues() | REF | none <i>schema.type</i> | <i>string</i> (HEX) | <code>DBNull.Value</code> |
| GetString() | REF | none <i>schema.type</i> | <i>string</i> (HEX) | Exception thrown |
| GetProviderSpecificValue(), GetProviderSpecificValues(), GetOracleValue(), GetOracleValues() | Object, Collection | <i>schema.type</i> | <i>custom object</i> | <i>custom type.Null</i> |
| GetProviderSpecificValue(), GetProviderSpecificValues(), GetOracleValue(), GetOracleValues() | Collection | <i>schema.type</i> | <i>custom object[]</i> <i>.NET Type[]</i> <i>PS object[]</i> | null |
| GetProviderSpecificValue(), GetProviderSpecificValues(), GetOracleValue(), GetOracleValues(), GetOracleRef() | REF | none <i>schema.type</i> | <code>OracleRef</code> | <code>OracleRef.Null</code> |
| GetOracleString() | REF | none <i>schema.type</i> | <code>OracleString</code> (HEX) | <code>OracleString.Null</code> |

See Also: ["Obtaining Data from an OracleDataReader Object"](#) on page 3-53

Oracle UDT Metadata Retrieval from OracleDataReader

An `OracleDataReader` object can return metadata used to determine the custom type that represents an Oracle UDT when a .NET Type or Provider-Specific Type accessor is invoked. The same custom type is used when populating the `DataSet` using the `OracleDataAdapter.Fill` method.

[Table 3–21](#) shows the values returned from the `OracleDataReader` `GetFieldType` and `GetProviderSpecificFieldType` methods that specify the .NET type of the column.

Table 3–21 Values Returned from OracleDataReader Methods

| OracleDataReader Method/Property invocation | Column Data Type | Custom Type Mapping | Return Value |
|--------------------------------------------------|--------------------|---------------------------------|----------------------------------------------------------------------------------------------------|
| <code>GetFieldType(index)</code> | Object, Collection | none | Exception thrown |
| <code>GetFieldType(index)</code> | Object | <code>schema.type</code> | <code>typeof(custom type)</code> |
| <code>GetFieldType(index)</code> | Collection | <code>schema.type</code> | <code>typeof(custom type) typeof(custom type[]) typeof(.NET type[]) typeof(PS type[])</code> |
| <code>GetFieldType(index)</code> | REF | none <code>schema.type</code> | <code>typeof(string)</code> |
| <code>GetProviderSpecificFieldType(index)</code> | Object, Collection | none | Exception thrown |
| <code>GetProviderSpecificFieldType(index)</code> | Object, | <code>schema.type</code> | <code>typeof(custom type)</code> |
| <code>GetProviderSpecificFieldType(index)</code> | Collection | <code>schema.type</code> | <code>typeof(custom type) typeof(custom type[]) typeof(.NET type[]) typeof(PS type[])</code> |
| <code>GetProviderSpecificFieldType(index)</code> | REF | none <code>schema.type</code> | <code>typeof(OracleRef)</code> |

Oracle UDT Parameter Binding with OracleParameter

This section discusses using UDT output and input parameter bindings with an `OracleParameter` object.

See Also: ["Parameter Binding"](#) on page 3-37

This section contains these topics:

- [Guidelines for Binding UDT Input and Output Parameters](#)
- [UDT Input Parameter Binding with OracleParameters](#)
- [UDT Output Parameter Binding with OracleParameters](#)

Guidelines for Binding UDT Input and Output Parameters

Developers must consider the following when using UDT parameter bindings with an `OracleParameter` object.

- The `UdtTypeName` property must be set. Binding is based on the `UdtTypeName` property regardless of the parameter direction.

Note: The `UdtTypeName` may differ from the Oracle UDT specified in the custom type mapping. This occurs when the parameter type is a super type of the Oracle UDT that the custom type represents.

- In case of Input/Output binding, the behavior is the same as Input and Output parameters.
- For Input parameter values, the bind value is converted to the UDT specified by the custom type mapping.
- For Output parameters:
 - If the value being returned is an Oracle Object or Collection, it is converted to a custom type or array type as specified by the custom type mapping. The value returned is always a custom type or an array type, regardless of whether the property most recently set was `DbType` or `OracleDbType`.
 - If the value being returned is a REF, then no custom type mapping is required.

UDT Input Parameter Binding with OracleParameters

Only certain combinations of these `OracleParameter` property values, `DbType`, `OracleDbType`, and `UdtTypeName`, can exist on the `OracleParameter` object. `OracleParameter` objects cannot be set to combinations that are not listed.

Table 3–22 describes the valid ways of binding input parameters for Oracle UDTs.

The last column indicates the Oracle type that ODP.NET converts the `OracleParameter` value to before binding.

Table 3–22 Valid Ways to Bind Input Parameters for Oracle UDTs

| OracleParameter. Value | OracleParameter. DbType or OracleParameter. OracleDbType | OracleParameter . UdtTypeName | Custom Type Mappings | Oracle Type converted to before Binding |
|------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|----------------------------------|------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| <i>custom object</i> <i>custom object[]</i> <i>.NET object[]</i> <i>PS object[]</i> String(HEX) OracleString(HEX) OracleRef | DbType.Object OracleDbType.Object OracleDbType.Array OracleDbType.Ref | not set | none <i>schema.type</i> | Exception thrown |
| <i>custom object[]</i> <i>.NET object[]</i> <i>PS object[]</i> | DbType.Object OracleDbType.Object OracleDbType.Array | <i>schema.type</i> | none | Exception thrown |
| <i>custom object</i> | DbType.Object | <i>schema.type</i> | <i>schema.type</i> | Specified UDT is instantiated. Value is bound as Object or Collection, based on the <code>UdtTypeName</code> property |
| <i>custom object</i> | OracleDbType.Object | <i>schema.type</i> | <i>schema.type</i> | Specified UDT is instantiated. <i>schema.type</i> must represent an object. |

Table 3–22 (Cont.) Valid Ways to Bind Input Parameters for Oracle UDTs

| OracleParameter.Value | OracleParameter.DbType or OracleDbType | OracleParameter.UdtTypeName | Custom Type Mappings | Oracle Type converted to before Binding |
|----------------------------------------------------------------------------------------------------|----------------------------------------------------------------|-----------------------------|------------------------------|--------------------------------------------------------------------------------|
| <i>custom object</i> | OracleDbType.Array | <i>schema.type</i> | <i>schema.type</i> | Specified UDT is instantiated. <i>schema.type</i> must represent a collection. |
| <i>.NET object[]</i> <i>PS object[]</i> <i>custom object[]</i> | DbType.Object OracleDbType.Array | <i>schema.type</i> | <i>schema.type</i> | UDT specified by OracleParameter.UdtTypeName is instantiated. |
| <i>.NET object[]</i> <i>PS object[]</i> <i>custom object[]</i> | OracleDbType.Object | <i>schema.type</i> | none <i>schema.type</i> | Exception thrown |
| <i>custom object</i> <i>.NET object[]</i> <i>PS object[]</i> <i>custom object[]</i> | OracleDbType.Ref | <i>schema.type</i> | none <i>schema.type</i> | Exception thrown |
| String(HEX) OracleString(HEX) OracleRef | DbType.Object OracleDbType.Object OracleDbType.Array | <i>schema.type</i> | none <i>schema.type</i> | Exception thrown |
| Char[](HEX) String(HEX) OracleString(HEX) OracleRef | OracleDbType.Ref | <i>schema.type</i> | none <i>schema.type</i> | A REF |

UDT Output Parameter Binding with OracleParameters

Only certain combinations of these OracleParameter property values, DbType, OracleDbType, and UdtTypeName, can exist on the OracleParameter object. OracleParameter objects cannot be set to combinations that are not listed.

Table 3–23 shows the supported ODP.NET output parameter bindings of Oracle database objects.

The last column indicates the type that ODP.NET converts the OracleParameter value to before binding.

Table 3–23 Valid Ways to Bind Output Parameters for Oracle UDTs

| Type returned from Oracle | OracleParameter.DbType | OracleParameter.UdtTypeName | Custom Type Mappings | Type converted to |
|---------------------------|--------------------------------------------------------------------------------------|-----------------------------|---------------------------|----------------------|
| Object/Collection/REF | DbType.Object OracleDbType.Object OracleDbType.Array OracleDbType.Ref | not set | none <i>schema.type</i> | Exception thrown |
| Object/Collection | DbType.Object OracleDbType.Object OracleDbType.Array | <i>schema.type</i> | none | Exception thrown |
| Object | DbType.Object OracleDbType.Object | <i>schema.type</i> | <i>schema.type</i> | <i>custom object</i> |
| Object | OracleDbType.Array OracleDbType.Ref | <i>schema.type</i> | none <i>schema.type</i> | Exception thrown |

Table 3–23 (Cont.) Valid Ways to Bind Output Parameters for Oracle UDTs

| Type returned from Oracle | OracleParameter.DbType | OracleParameter.UdtTypeName | Custom Type Mappings | Type converted to |
|---------------------------|----------------------------------------------------------|-----------------------------|---------------------------|-------------------------------------------------------------------------------------------|
| Collection | OracleDbType.Array DbType.Object | <i>schema.type</i> | <i>schema.type</i> | <i>custom object</i> <i>custom object[]</i> <i>.NET object[]</i> <i>PS object[]</i> |
| Collection | OracleDbType.Ref OracleDbType.Object | <i>schema.type</i> | none <i>schema.type</i> | Exception thrown |
| REF | DbType.Object OracleDbType.Object OracleDbType.Array | <i>schema.type</i> | none <i>schema.type</i> | Exception thrown |
| REF | OracleDbType.Ref | <i>schema.type</i> | none <i>schema.type</i> | OracleRef |

See Also:

- ["Parameter Binding"](#) on page 3-37
- ["Typed OracleDataReader Accessors"](#) on page 3-54

Populating the DataSet with Oracle UDTs

The DataSet is a disconnected result set. With ADO.NET 2.0, both .NET types and provider-specific types can be used to populate the DataSet. This section describes the types used to populate the DataSet when the column is an Oracle UDT.

[Table 3–24](#) lists the types that populate the DataSet column, based on the Oracle column type, the `ReturnProviderSpecificTypes` property of the `DataAdapter`, the existence of a custom type mapping, the DataSet column type, the DataSet column value, and the DataSet column null value.

Table 3–24 Types that Populate the DataSet with ADO.NET 2.0

| Oracle Column Type | ReturnProviderSpecificTypes Property | Custom Type Mappings | DataSet Column Type | DataSet Column Value | DataSet Column Null Value |
|---------------------|--------------------------------------|---------------------------|--------------------------------------------------------------------------------------------------------|------------------------------------------------------------------|-----------------------------|
| Object / Collection | False/True | none | Exception thrown | Exception thrown | Exception thrown |
| Object / Collection | False | <i>schema.type</i> | <code>typeof(custom type)</code> | <i>custom object</i> | <code>DBNull.Value</code> |
| Object / Collection | True | <i>schema.type</i> | <code>typeof(custom type)</code> | <i>custom object</i> | <i>custom object.Null</i> |
| Collection | False | <i>schema.type</i> | <code>typeof(custom type[])</code> <code>typeof(.NET type[])</code> <code>typeof(PS type[])</code> | <i>.NET type[]</i> <i>PS object[]</i> <i>custom object[]</i> | <code>DBNull.Value</code> |
| Collection | True | <i>schema.type</i> | <code>typeof(custom type[])</code> <code>typeof(.NET type[])</code> <code>typeof(PS type[])</code> | <i>.NET type[]</i> <i>PS object[]</i> <i>custom object[]</i> | null |
| REF | False | none <i>schema.type</i> | <code>typeof(string)</code> | string/HEX | <code>DBNull.Value</code> |
| REF | True | none <i>schema.type</i> | <code>typeof(OracleRef)</code> | OracleRef | <code>OracleRef.Null</code> |

UDT Method Invocation

ODP.NET supports invocation of methods defined for a UDT on the database. This can be accomplished by doing the following:

1. Set the `CommandType` as `CommandType.StoredProcedure`.
2. Set the `CommandText` as "*type_name.procedure_name*"
3. Execute the command using any of the `Execute` methods on the `OracleCommand` object.

For instance functions, the parameters are as follows:

- The first parameter must be the return value.
- The second parameter must be the UDT instance on which the instance method is invoked, which is the instance of the .NET custom object.
- Subsequent parameters are for the function.

For instance procedures, the first parameter must be the UDT instance.

For static methods, the UDT instance is not needed.

Configuration Settings for Oracle UDTs

ODP.NET exposes two configuration settings to determine how ODP.NET handles Oracle UDTs.

- [StatementCacheWithUdts](#)
- [UdtCacheSize](#)

These configuration settings can be specified as machine-wide settings for a particular version of ODP.NET, using the registry key with the name that exists under `HKEY_LOCAL_MACHINE\SOFTWARE\ORACLE\ODP.NET\Assembly_Version`. The configuration settings specified in the registry can be overridden if an entry is created in the `machine.config` for .NET framework-wide settings, or in the `app.config` or `web.config` for application-specific settings. For details on configuring ODP.NET, see "[Configuring Oracle Data Provider for .NET](#)" on page 2-9.

StatementCacheWithUdts

`StatementCacheWithUdts` specifies whether or not ODP.NET caches Oracle UDTs retrieved by a `SELECT` statement along with the statement when it is returned to the statement cache. Possible values are 1 - Yes (the default) or 0 - No.

For the value of 1, the Oracle UDTs are cached along with the statements. Therefore, the memory that contained the UDTs can be re-used; subsequent executions of the same statement do not require additional memory. This may result in an overall higher performance.

For the value of 0, ODP.NET frees the memory for the retrieved Oracle UDTs before the statement is returned to the statement cache. This may result in poorer performance because subsequent executions will require new memory allocations.

UdtCacheSize

`UdtCacheSize` specifies the size of the object cache for each connection that ODP.NET uses when retrieving and manipulating Oracle UDTs. The value for this setting must be specified in kilobytes (KB) with the default 4096KB, equivalent to 4 MB.

This configuration setting is used to determine how frequently the objects in the object cache will be purged (using an LRU approach) as the limit of the object cache size approaches.

Bulk Copy

ODP.NET provides a Bulk Copy feature which enables applications to efficiently load large amounts of data from a table in one database to another table in the same or a different database.

The ODP.NET Bulk Copy feature uses a direct path load approach, which is similar to, but not the same as Oracle SQL*Loader. Using direct path load is faster than conventional loading (using conventional SQL `INSERT` statements). Conventional loading formats Oracle data blocks and writes the data blocks directly to the data files. Bulk Copy eliminates considerable processing overhead.

The ODP.NET Bulk Copy feature can load data into older Oracle databases.

Note: ODP.NET, Managed Driver does not support Bulk Copy.

See Also: ["System Requirements"](#) on page 2-1 to learn which versions of the Oracle Database ODP.NET interoperates with

The ODP.NET Bulk Copy feature is subject to the same basic restrictions and integrity constraints for direct path loads, as discussed in the next few sections.

Data Types Supported by Bulk Copy

Bulk Copy supports the following Oracle database data types:

- NUMBER
- BINARY_DOUBLE
- BINARY_FLOAT
- CHAR
- NCHAR
- VARCHAR2
- NVARCHAR2
- LONG
- CLOB
- BLOB
- DATE
- TIMESTAMP
- TIMESTAMP WITH TIME ZONE
- TIMESTAMP WITH LOCAL TIME ZONE
- INTERVAL YEAR TO MONTH
- INTERVAL DAY TO SECOND

Bulk copy does not support overwrites.

Restrictions on Oracle Bulk Copy of a Single Partition

- The table that contains the partition cannot have any global indexes defined on it.
- The tables that the partition is a member of cannot have referential and check constraints enabled.
- Enabled triggers are not allowed.

Integrity Constraints Affecting Oracle Bulk Copy

During a Oracle bulk copy, some integrity constraints are automatically enabled or disabled, as follows:

Enabled Constraints

During an Oracle bulk copy, the following constraints are automatically enabled by default:

- NOT NULL
- UNIQUE
- PRIMARY KEY (unique-constraints on not-null columns)

NOT NULL constraints are checked at column array build time. Any row that violates the NOT NULL constraint is rejected.

UNIQUE constraints are verified when indexes are rebuilt at the end of the load. The index is left in an Index Unusable state if it violates a UNIQUE constraint.

Disabled Constraints

During an Oracle bulk copy, the following constraints are automatically disabled by default:

- CHECK constraints
- Referential constraints (FOREIGN KEY)

If the `EVALUATE CHECK_CONSTRAINTS` clause is specified, then CHECK constraints are not automatically disabled. The CHECK constraints are evaluated during a direct path load and any row that violates the CHECK constraint is rejected.

Database Insert Triggers

Table insert triggers are disabled when a direct path load begins. After the rows are loaded and indexes rebuilt, any triggers that were disabled are automatically reenabled. The log file lists all triggers that were disabled for the load. There should be no errors reenabling triggers.

Unlike integrity constraints, insert triggers are not reapplied to the whole table when they are enabled. As a result, insert triggers do not fire for any rows loaded on the direct path. When using the direct path, the application must ensure that any behavior associated with insert triggers is carried out for the new rows.

Field Defaults

Default column specifications defined in the database are not available with direct path loading. Fields for which default values are desired must be specified with the `DEFAULTIF` clause. If a `DEFAULTIF` clause is not specified and the field is NULL, then a null value is inserted into the database.

See Also: [Chapter 17, "Oracle Data Provider for .NET Bulk Copy Classes"](#)

Oracle Database Advanced Queuing Support

Oracle Database Advanced Queuing (AQ) provides database-integrated message queuing functionality. Oracle Database AQ is built on top of Oracle Streams and leverages the functions of Oracle Database so that messages can be stored persistently, propagated between queues on different computers and databases, and transmitted using Oracle Net Services and HTTP(S).

Note: ODP.NET, Managed Driver does not support the AQ .NET classes.

See Also: *Oracle Database Advanced Queuing User's Guide*

As Oracle Database AQ is implemented in database tables, all operational benefits of high availability, scalability, and reliability are also applicable to queue data. Oracle Database AQ supports standard database features such as recovery, restart, and security.

The following items discuss Oracle Database AQ concepts:

- **Queues and Queue Tables**

Messages enqueued in a queue are stored in a queue table. A queue table must be created before creating a queue based on it. Use the `DBMS_AQADM` PL/SQL package or Oracle Developer Tools for Visual Studio to create and administer queue tables and queues.

Queues are represented by `OracleAQQueue` objects.

See Also: ["OracleAQQueue Class"](#) on page 12-48

- **Single-Consumer and Multiple-Consumer Queues**

A single-consumer queue is created based on a single consumer queue table. Messages enqueued in a single-consumer queue can be dequeued by only a single consumer.

A multiple-consumer queue is based on a multiple-consumer queue table. This queue supports queue subscribers and message recipients.

- **Message Recipients**

A message producer can submit a list of recipients when enqueueing a message. This allows for a unique set of recipients for each message in the queue. The recipient list associated with the message overrides the subscriber list, if any, associated with the queue. The recipients need not be in the subscriber list. However, recipients can be selected from among the subscribers.

The `Recipients` property of an `OracleAQMessage` can be used to specify the recipients to a specific message in terms of `OracleAQAgent` objects.

See Also:

- ["Recipients"](#) on page 12-35
- ["OracleAQAgent Class"](#) on page 12-2

- Enqueue

Messages are enqueued when producer applications push the messages into a queue. This is accomplished by calling the `Enqueue` method on an `OracleAQQueue` object. Multiple messages can be enqueued using the `EnqueueArray` method.

See Also:

- ["Enqueue"](#) on page 12-68
- ["EnqueueArray"](#) on page 12-70

- Dequeue

Messages are dequeued when consumer applications pull the messages from a queue. This is accomplished by calling the `Dequeue` method on an `OracleAQQueue` object. Multiple messages can be dequeued using the `DequeueArray` method.

See Also:

- ["Dequeue"](#) on page 12-64
- ["DequeueArray"](#) on page 12-66

- Listen

Subscriber applications can use a `Listen` call to monitor multiple queues for subscriptions on different queues. This is a more scalable solution for cases where a subscriber application has subscribed to many queues and wishes to receive messages that arrive in any of the queues.

This is accomplished by calling the `Listen` method of the `OracleAQQueue` class, passing the list of subscriptions in form of an array.

See Also: ["Listen"](#) on page 12-72

- Notification

Subscriber applications can utilize the notification mechanism to get notifications about message availability in a queue. The applications can decide to skip or dequeue the message from the queue based on the information received.

A subscriber application must register for event notification on the queues from which it wants to receive notifications. This is represented by the `MessageAvailable` event on `OracleAQQueue`. The event is triggered when messages matching the subscriptions arrive.

Notifications can be registered as regular or grouping notifications. A time out value for these notifications can also be specified. Various notification options can be set using the `OracleAQQueue.Notification` property. Notifications set on an `OracleAQQueue` object gets cancelled automatically when the object gets disposed.

See Also:

- ["MessageAvailable Event"](#) on page 12-79
 - ["Notification"](#) on page 12-61
- Buffered Messaging

In buffered messaging, messages reside in a shared memory area. This makes it faster than persistent messaging. The messages are written to disk only when the total memory consumption of buffered messages approaches the available shared memory limit. Buffered messaging is ideal for applications that do not require the reliability and transaction support of Oracle Database AQ persistent messaging.

Buffered and persistent messages use the same single-consumer or multi-consumer queues, and the same administrative and operational interfaces. They are distinguished from each other by a delivery mode parameter. When an application enqueues a message to an Oracle Database AQ queue, it sets the delivery mode parameter as well.

The delivery mode parameter can be set on `OracleAQMessage` by modifying the `DeliveryMode` property. Buffered messaging is supported in all queue tables created with compatibility 8.1 or higher.

See Also: ["DeliveryMode"](#) on page 12-30

Using ODP.NET for Advanced Queuing

.NET applications can use ODP.NET to access all the operational features of AQ such as Enqueuing, Dequeuing, Listen, and Notification.

[Table 3–25](#) maps the AQ features to their corresponding ODP.NET implementation.

Table 3–25 Mapping AQ Features with their ODP.NET Implementation

| Functionality | ODP.NET Implementation |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Create a Message | Create an <code>OracleAQMessage</code> object |
| Enqueue a single message | Specify the message as <code>OracleAQMessage</code> , queue as <code>OracleAQQueue</code> and enqueue options on <code>OracleAQQueue</code> , call <code>OracleAQQueue.Enqueue</code> |
| Enqueue multiple messages | Specify the messages as an <code>OracleAQMessage</code> array in <code>OracleAQQueue.EnqueueArray</code> |
| Dequeue a single message | Specify dequeue options on <code>OracleAQQueue</code> and call <code>OracleAQQueue.Dequeue</code> |
| Dequeue multiple messages | Call <code>OracleAQQueue.DequeueArray</code> |
| Listen for messages on Queue(s) | Call <code>OracleAQQueue.Listen</code> . To listen on multiple queues use static <code>Listen</code> method of <code>OracleAQQueue</code> |
| Message Notifications | Use <code>OracleAQQueue.MessageAvailable Event</code> along with the <code>NotificationConsumers</code> property |

Note: AQ samples are provided in the `ORACLE_BASE\ORACLE_HOME\ODP.NET\Samples` directory.

Enqueuing and Dequeuing Example

The following example demonstrates enqueueing and dequeuing messages using a single consumer queue. The first part of the example performs the requisite database setup for the database user, SCOTT. The second part of the example demonstrates enqueueing and dequeuing messages.

```
-- Part I: Database setup required for this demo

-----
-- SQL to grant appropriate privilege to database user, SCOTT
-----
SQL> ALTER USER SCOTT ACCOUNT UNLOCK IDENTIFIED BY Pwd4Sct;
User altered.
SQL> GRANT ALL ON DBMS_AQADM TO scott;

-----
-- PL/SQL to create queue-table and queue and start queue for SCOTT
-----
BEGIN
  DBMS_AQADM.CREATE_QUEUE_TABLE(
    queue_table=>'scott.test_q_tab',
    queue_payload_type=>'RAW',
    multiple_consumers=>FALSE);

  DBMS_AQADM.CREATE_QUEUE(
    queue_name=>'scott.test_q',
    queue_table=>'scott.test_q_tab');

  DBMS_AQADM.START_QUEUE(queue_name=>'scott.test_q');
END;
/

-----
-- PL/SQL to stop queue and drop queue & queue-table from SCOTT
-----
BEGIN
  DBMS_AQADM.STOP_QUEUE('scott.test_q');

  DBMS_AQADM.DROP_QUEUE(
    queue_name => 'scott.test_q',
    auto_commit => TRUE);

  DBMS_AQADM.DROP_QUEUE_TABLE(
    queue_table => 'scott.test_q_tab',
    force => FALSE,
    auto_commit => TRUE);
END;
/
-- End of Part I, database setup.

//Part II: Enqueuing and dequeuing messages
//C#
using System;
using System.Text;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

namespace ODPSample
{
  /// <summary>
```

```
/// Demonstrates Enqueuing and Dequeuing raw message
/// using a single consumer queue
/// </summary>
class EnqueueDequeue
{
    static void Main(string[] args)
    {
        // Create connection
        string constr = "user id=scott;password=Pwd4Sct;data source=oracle";
        OracleConnection con = new OracleConnection(constr);

        // Create queue
        OracleAQQueue queue = new OracleAQQueue("scott.test_q", con);

        try
        {
            // Open connection
            con.Open();

            // Begin txn for enqueue
            OracleTransaction txn = con.BeginTransaction();

            // Set message type for the queue
            queue.MessageType = OracleAQMessageType.Raw;

            // Prepare message and RAW payload
            OracleAQMessage enqMsg = new OracleAQMessage();
            byte[] bytePayload = { 0, 1, 2, 3, 4, 5, 6, 7, 8, 9 };
            enqMsg.Payload = bytePayload;

            // Prepare to Enqueue
            queue.EnqueueOptions.Visibility = OracleAQVisibilityMode.OnCommit;

            // Enqueue message
            queue.Enqueue(enqMsg);

            Console.WriteLine("Enqueued Message Payload      : "
                + ByteArrayToString(enqMsg.Payload as byte[]));
            Console.WriteLine("MessageId of Enqueued Message : "
                + ByteArrayToString(enqMsg.MessageId));

            // Enqueue txn commit
            txn.Commit();

            // Begin txn for Dequeue
            txn = con.BeginTransaction();

            // Prepare to Dequeue
            queue.DequeueOptions.Visibility = OracleAQVisibilityMode.OnCommit;
            queue.DequeueOptions.Wait = 10;

            // Dequeue message
            OracleAQMessage deqMsg = queue.Dequeue();

            Console.WriteLine("Dequeued Message Payload      : "
                + ByteArrayToString(deqMsg.Payload as byte[]));
            Console.WriteLine("MessageId of Dequeued Message : "
                + ByteArrayToString(deqMsg.MessageId));

            // Dequeue txn commit
```

```
        txn.Commit();
    }
    catch (Exception e)
    {
        Console.WriteLine("Error: {0}", e.Message);
    }
    finally
    {
        // Close/Dispose objects
        queue.Dispose();
        con.Close();
        con.Dispose();
    }
}

// Function to convert byte[] to string
static private string ByteArrayToString(byte[] byteArray)
{
    StringBuilder sb = new StringBuilder();
    for (int n = 0; n < byteArray.Length; n++)
    {
        sb.Append((int.Parse(byteArray[n].ToString()).ToString("X"));
    }
    return sb.ToString();
}
}
```

Continuous Query Notification Support

Oracle Data Provider for .NET provides a notification framework that supports Continuous Query Notification, enabling applications to receive client-side notifications when there is a change in a query result set, schema objects, or the state of the database, even if no Oracle Data Provider for .NET database connection exists. Using Continuous Query Notification, an application can maintain the validity of the client-side cache (for example, the ADO.NET DataSet) easily. Continuous Query Notification was previously known as Database Change Notification.

Note: Continuous Query Notification is not supported in a .NET stored procedure.

Using the notification framework, applications can specify a query result set as a registered query for notification request on the database, and create this notification registration to maintain the validity of the query result set. When there is a change on the database that could affect the client-side cache's query results, the notification framework notifies the application.

Note: The content of a change notification is referred to as an *invalidation message*. It indicates that the query result set is now invalid and provides information about the changes.

Based on the information provided by the invalidation message, the application can then act accordingly. For example, the application might need to refresh its own copy of the data for the registered query that is stored locally in the application.

Note: If a registered object is dropped from the database and a new one is created with the same name in the same schema, re-registration is required to receive notifications for the newly created object.

See Also: *Oracle Database Development Guide* for further information on Continuous Query Notification

Firewalls, such as Windows Firewall, may be set up to block TCP network ports, which blocks incoming database notifications. Ensure the firewall is configured so that database applications can use the designated port for Continuous Query Notification.

See Also: *Oracle Database Platform Guide for Microsoft Windows* for details on configuring the Windows Firewall

Beginning with Oracle Database 11g and ODP.NET 11g (11.1), Continuous Query Notification queries can be query-based (default) or object-based. The query-based registrations allow ODP.NET to notify applications when the selected rows have changed in the database. The object-based registrations allow ODP.NET to notify applications for any changes that occur in the table(s) containing the selected rows.

Query-based registrations have two modes: guaranteed mode and best-effort mode. In guaranteed mode, any continuous query notification ensures that a change occurred to something contained in the queried result set. However, if a query is complex, then it cannot be registered in guaranteed mode. Best-effort mode is used in such cases.

Best-effort mode simplifies the query for query-based registration. No notifications are lost from the simplification. However, the simplification may cause false positives, as the simpler version's query result could change when the original query result would not.

There still remain some restrictions on which queries can have best-effort mode query-based registrations. In such cases, developers can use object-based registrations, which can register most query types. Object-based registrations generate notifications when the query object changes, even if the actual query result does not. This also means that object-based registrations are more prone to false positives than query-based registrations. Developers should be aware of the relative strengths and weaknesses of each continuous query notification option and choose the one that best suits their requirements.

If a large number of rows are modified at once, consuming significant shared pool resources, the application will not receive any change notifications with specific row information that had undergone changes. Rather, it will receive a notification with `OracleNotificationEventArgs.Info` property set to `OracleNotificationInfo.Error`.

See Also:

- ["Configuring a Port to Listen for Database Notifications"](#) on page 2-31
- *Oracle Database Development Guide* for further details on the requirements for Continuous Query Notification

This section contains the following topics:

- [Continuous Query Notification Classes](#)
- [Supported Operations](#)

- [Requirements of Notification Registration](#)
- [Using Continuous Query Notification](#)
- [Best Practice Guidelines and Performance Considerations](#)

Continuous Query Notification Classes

The following classes are associated with Continuous Query Notification Support:

- `OracleDependency`

Represents a dependency between an application and an Oracle database based on the database events which the application is interested in. It contains information about the dependency and provides the mechanism to notify the application when specified database events occurs. The `OracleDependency` class is also responsible for creating the notification listener to listen for database notifications. There is only one database notification listener for each application domain. This notification listener terminates when the application process terminates.

The dependency between the application and the database is not established when the `OracleDependency` object is created. The dependency is established when the command that is associated with this `OracleDependency` object is executed. That command execution creates a continuous query notification registration in the database.

When a change has occurred in the database, the `HasChanges` property of the `OracleDependency` object is set to true. Furthermore, if an event handler was registered with the `OnChange` event of the `OracleDependency` object, the registered event handler function will be invoked.
- `OracleNotificationRequest`

Represents a notification request to be registered in the database. It contains information about the request and the properties of the notification.
- `OracleNotificationEventArgs`

Represents the **invalidation message** generated for a notification when a specified database event occurs and contains details about that database event.

See Also:

- ["OracleDependency Class" on page 9-2](#)
- ["OracleNotificationRequest Class" on page 9-22](#)
- ["OracleNotificationEventArgs Class" on page 9-30](#)

Supported Operations

The ODP.NET notification framework in conjunction with Continuous Query Notification supports the following activities:

- Creating a notification registration by:
 - Creating an `OracleDependency` instance and binding it to an `OracleCommand` instance.
- Grouping multiple notification requests into one registration by:
 - Using the `OracleDependency.AddCommandDependency` method.
 - Setting the `OracleCommand.Notification` request using the same `OracleNotificationRequest` instance.

- Registering for Continuous Query Notification by:
 - Executing the `OracleCommand`. If either the notification property is null or `NotificationAutoEnlist` is false, the notification will not be made.
- Removing notification registration by:
 - Using the `OracleDependency.RemoveRegistration` method.
 - Setting the `Timeout` property in the `OracleNotificationRequest` instance before the registration is created.
 - Setting the `IsNotifiedOnce` property to true in the `OracleNotificationRequest` instance before the registration is created. The registration is removed once a database notification is sent.
- Ensuring Change Notification Persistence by:
 - Specifying whether or not the invalidation message is queued persistently in the database before delivery. If an invalidation message is to be stored persistently in the database, then the change notification is guaranteed to be sent. If an invalidation message is stored in an in-memory queue, the change notification can be received faster, however, it could be lost upon database shutdown or crashes.
- Retrieving notification information including:
 - The changed object name.
 - The schema name of the changed object.
 - Database events that cause the notification, such as insert, delete, and so on.
 - The `RowID` of the modified object row.

In Oracle SQL, the `ROWIDTOCHAR (ROWID)` and `ROWIDTONCHAR (ROWID)` functions convert a `ROWID` value to `VARCHAR2` and `NVARCHAR` data types, respectively.

If these functions are used within a SQL statement, `ROWIDS` are not returned in the `OracleNotificationEventArgs` object that is passed to the continuous query notification callback.

- Defining the listener port number.

By default, the static `OracleDependency.Port` property is set to -1. This indicates that the ODP.NET listens on a port that is randomly picked when ODP.NET registers a continuous query notification request for the first time during the execution of an application.

ODP.NET creates only one listener that listens on one port within an application domain. Once ODP.NET starts the listener, the port number cannot be changed; Changes to the static `OracleDependency.Port` property will generate an error if a listener has already been created.

See Also:

- ["OracleCommand Class"](#) on page 6-12
- ["Notification"](#) on page 6-31
- ["NotificationAutoEnlist"](#) on page 6-32
- ["OracleDependency Class"](#) on page 9-2
- ["OracleNotificationEventArgs Class"](#) on page 9-30

Requirements of Notification Registration

The connected user must have the `CHANGE NOTIFICATION` privilege to create a notification registration.

This SQL statement grants the `CHANGE NOTIFICATION` privilege:

```
grant change notification to user name
```

This SQL statement revokes the `CHANGE NOTIFICATION` privilege:

```
revoke change notification from user name
```

Using Continuous Query Notification

This section describes what the application should do, and the flow of the process, when an application uses Continuous Query Notification to receive notifications for any changes in the registered query result set.

Application Steps

The application should do the following:

1. Create an `OracleDependency` instance.
2. Assign an event handler to the `OracleDependency.OnChange` event property if the application wishes to have an event handler invoked when database changes are detected. Otherwise, the application can choose to poll on the `HasChanges` property of the `OracleDependency` object. This event handler is invoked when the change notification is received.
3. Set the port number for the listener to listen on. The application can specify the port number for one notification listener to listen on. If the application does not specify a port number, a random one is used by the listener.
4. Bind the `OracleDependency` instance to an `OracleCommand` instance that contains the actual query to be executed. Internally, the Continuous Query Notification request (an `OracleNotificationRequest` instance) is created and assigned to the `OracleCommand.Notification` property.

Flow of Notification Process

1. When the command associated with the notification request is executed, the notification registration is created in the database. The command execution must return a result set, or contain one or more `REF` cursors for a PL/SQL stored procedure.
2. ODP.NET starts the application listener on the first successful notification registration.
3. When a change related to the registration occurs in the database, the application is notified through the event delegate assigned to the `OracleDependency.OnChange` event property, or the application can poll the `OracleDependency.HasChanges` property.

The following example demonstrates the continuous query notification feature.

```
// Database Setup
// NOTE: unless the following SQL command is executed,
// ORA-29972 will be obtained from running this sample
/*
grant change notification to scott;
```

```
*/
using System;
using System.Threading;
using System.Data;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

//This sample shows the continuous query notification feature in ODP.NET.
//Application specifies to get a notification when emp table is updated.
//When emp table is updated, the application will get a notification
//through an event handler.
namespace NotificationSample
{
    public class MyNotificationSample
    {
        public static bool IsNotified = false;

        public static void Main(string[] args)
        {
            //To Run this sample, make sure that the change notification privilege
            //is granted to scott.
            string constr = "User Id=scott;Password=tiger;Data Source=oracle";
            OracleConnection con = null;
            OracleDependency dep = null;

            try
            {
                con = new OracleConnection(constr);
                OracleCommand cmd = new OracleCommand("select * from emp", con);
                con.Open();

                // Set the port number for the listener to listen for the notification
                // request
                OracleDependency.Port = 1005;

                // Create an OracleDependency instance and bind it to an OracleCommand
                // instance.
                // When an OracleDependency instance is bound to an OracleCommand
                // instance, an OracleNotificationRequest is created and is set in the
                // OracleCommand's Notification property. This indicates subsequent
                // execution of command will register the notification.
                // By default, the notification request is using the Database Change
                // Notification.
                dep = new OracleDependency(cmd);

                // Add the event handler to handle the notification. The
                // OnMyNotification method will be invoked when a notification message
                // is received from the database
                dep.OnChange +=
                    new OnChangeEventHandler(MyNotificationSample.OnMyNotificaton);

                // The notification registration is created and the query result sets
                // associated with the command can be invalidated when there is a
                // change. When the first notification registration occurs, the
                // notification listener is started and the listener port number
                // will be 1005.
                cmd.ExecuteNonQuery();

                // Updating emp table so that a notification can be received when
                // the emp table is updated.
            }
            catch { }
        }
    }
}
```

```
        // Start a transaction to update emp table
        OracleTransaction txn = con.BeginTransaction();
        // Create a new command which will update emp table
        string updateCmdText =
            "update emp set sal = sal + 10 where empno = 7782";
        OracleCommand updateCmd = new OracleCommand(updateCmdText, con);
        // Update the emp table
        updateCmd.ExecuteNonQuery();
        //When the transaction is committed, a notification will be sent from
        //the database
        txn.Commit();
    }
    catch (Exception e)
    {
        Console.WriteLine(e.Message);
    }

    con.Close();
    // Loop while waiting for notification
    while(MyNotificationSample.IsNotified == false)
    {
        Thread.Sleep(100);
    }
}

public static void OnMyNotificaton(object src,
    OracleNotificationEventArgs arg)
{
    Console.WriteLine("Notification Received");
    DataTable changeDetails = arg.Details;
    Console.WriteLine("Data has changed in {0}",
        changeDetails.Rows[0]["ResourceName"]);
    MyNotificationSample.IsNotified = true;
}
}
```

Best Practice Guidelines and Performance Considerations

This section provides guidelines for working with Continuous Query Notification and the ODP.NET notification framework, and discusses the performance impacts.

Every change notification registration consumes database memory, storage or network resources, or some combination thereof. The resource consumption further depends on the volume and size of the **invalidation message**. In order to scale well with a large number of mid-tier clients, Oracle recommends that the client implement these best practices:

- Few and mostly read-only tables

There should be few registered objects, and these should be mostly read-only, with very infrequent invalidations. If an object is extremely volatile, then a large number of invalidation notifications are sent, potentially requiring a lot of space (in memory or on disk) in the invalidation queue. This is also true if a large number of objects are registered.
- Few rows updated for each table

Transactions should update (or insert or delete) only a small number of rows within the registered tables. Depending on database resources, a whole table could

Oracle Date Type to .NET DateTime Type

The Oracle data type `DATE` can represent dates in BC whereas the .NET `DateTime` type cannot. If a `DATE` that goes to BC get retrieved into a .NET `DateTime` type, it loses data.

Table 3–27 lists the maximum and minimum values for Oracle `Date` and .NET `DateTime` types.

Table 3–27 Oracle Date to .NET DateTime Comparisons

| Value Limits | Oracle Date | .NET DateTime |
|--------------|-----------------|----------------------------------|
| Maximum | Dec 31, 9999 AD | Dec 31, 9999 AD 23:59:59.9999999 |
| Minimum | Jan 1, 4712 BC | Jan 1, 0001 AD 00:00:00.0000000 |

Oracle TimeStamp Type to .NET DateTime Type

Similar to the `DATE` data type, the Oracle `TimeStamp` data type can represent a date in BC, and a .NET `DateTime` type cannot. If a `TimeStamp` that goes to BC is retrieved into a .NET `DateTime` type, it loses data. The Oracle `TimeStamp` type can represent values in units of $e-9$; the .NET `DateTime` type can represent only values in units of $e-7$. The Oracle `TimeStamp` with time zone data type can store time zone information, and the .NET `DateTime` type cannot.

Table 3–28 lists the maximum and minimum values for Oracle `TimeStamp` and .NET `DateTime` types.

Table 3–28 Oracle TimeStamp to .NET DateTime Comparisons

| Value Limits | Oracle TimeStamp | .NET DateTime |
|--------------|------------------------------------|----------------------------------|
| Maximum | Dec 31, 9999 AD 23:59:59.999999999 | Dec 31, 9999 AD 23:59:59.9999999 |
| Minimum | Jan 1, 4712 BC 00:00:00.000000000 | Jan 1, 0001 AD 00:00:00.0000000 |

Oracle INTERVAL DAY TO SECOND to .NET TimeSpan

The Oracle data type `INTERVAL DAY TO SECOND` can hold up to 9 precision, and the .NET `TimeSpan` type can hold up to 7 precision. If an `INTERVAL DAY TO SECOND` data type that has more than 7 precision is retrieved into a .NET `TimeSpan` type, it loses precision. The Oracle `INTERVAL DAY TO SECOND` type can represent values in units of $e-9$, and the .NET `TimeSpan` type can represent only values in units of $e-7$.

Table 3–29 lists the maximum and minimum values for Oracle `INTERVAL DAY TO SECOND` and .NET `DateTime` types.

Table 3–29 Oracle INTERVAL DAY TO SECOND to .NET TimeSpan Comparisons

| Value Limits | Oracle INTERVAL DAY TO SECOND | .NET TmeSpan |
|--------------|-------------------------------|----------------------------|
| Maximum | +999999999 23:59:59.999999999 | +10675199 02:48:05.4775807 |
| Minimum | -999999999 23:59:59.999999999 | -10675199 02:48:05.4775808 |

SafeMapping Property

The `OracleDataAdapter Safe Type Mapping` feature prevents data loss when populating Oracle data for any of these types into a .NET `DataSet`. By setting the `SafeMapping` property appropriately, these types can be safely represented in the `DataSet`, as either of the following:

- .NET `byte[]` in Oracle format
- .NET `String`

By default, Safe Type Mapping is disabled.

Using Safe Type Mapping

To use the Safe Type Mapping feature, the `OracleDataAdapter.SafeMapping` property must be set with a hash table of key-value pairs. The key-value pairs must map database table column names (of type `string`) to a .NET type (of type `Type`). ODP.NET supports Safe Type Mapping to `byte[]` and `String` types. Any other type mapping causes an exception.

In situations where the column names are not known at design time, an asterisk ("`*`") can be used to map all occurrences of database types to a safe .NET type. If both the valid column name and the asterisk are present, the column name is used.

Note:

- Database table column names are case-sensitive.
 - Column names in the hash table that correspond to invalid column names are ignored.
-
-

Safe Type Mapping as a string is more readable without further conversion. Converting certain Oracle data types to a string requires extra conversion, which can be slower than converting it to a `byte[]`. Conversion of .NET strings back to ODP.NET types relies on the formatting information of the session.

SafeTyping Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class SafeMappingSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";

        // In this SELECT statement, EMPNO, HIREDATE and SALARY must be
        // preserved using safe type mapping.
        string cmdstr = "SELECT EMPNO, ENAME, HIREDATE, SAL FROM EMP";

        // Create the adapter with the selectCommand txt and the connection string
        OracleDataAdapter adapter = new OracleDataAdapter(cmdstr, constr);

        // Get the connection from the adapter
        OracleConnection connection = adapter.SelectCommand.Connection;

        // Create the safe type mapping for the adapter
        // which can safely map column data to byte arrays, where
        // applicable. By executing the following statement, EMPNO, HIREDATE AND
        // SALARY columns will be mapped to byte[]
        adapter.SafeMapping.Add("*", typeof(byte[]));
    }
}
```

```
// Map HIREDATE to a string
// If the column name in the EMP table is case-sensitive,
// the safe type mapping column name must be case-sensitive.
adapter.SafeMapping.Add("HIREDATE", typeof(string));

// Map EMPNO to a string
// If the column name in the EMP table is case-sensitive,
// the safe type mapping column name must also be case-sensitive.
adapter.SafeMapping.Add("EMPNO", typeof(string));
adapter.SafeMapping.Add("SAL", typeof(string));

// Create and fill the DataSet using the EMP
DataSet dataset = new DataSet();
adapter.Fill(dataset, "EMP");

// Get the EMP table from the dataset
DataTable table = dataset.Tables["EMP"];

// Get the first row from the EMP table
DataRow row = table.Rows[0];

// Print out the row info
Console.WriteLine("EMPNO Column: type = " + row["EMPNO"].GetType() +
    "; value = " + row["EMPNO"]);
Console.WriteLine("ENAME Column: type = " + row["ENAME"].GetType() +
    "; value = " + row["ENAME"]);
Console.WriteLine("HIREDATE Column: type = " + row["HIREDATE"].GetType()+
    "; value = " + row["HIREDATE"]);
Console.WriteLine("SAL Column: type = " + row["SAL"].GetType() +
    "; value = " + row["SAL"]);
    }
}
```

See Also: ["SafeMapping"](#) on page 6-173

OracleDataAdapter Requery Property

The `OracleDataAdapter Requery` property controls whether or not queries are reexecuted for `OracleDataAdapter Fill` calls after the initial `Fill` call.

The `OracleDataAdapter Fill` method allows appending or refreshing data in the `DataSet`. When appending the `DataSet` using the same query with subsequent `Fill` calls, reexecuting the query may not be desirable.

When the `Requery` property is set to `true`, each subsequent `Fill` call reexecutes the query and fills the `DataSet`. This is an expensive operation, and if the reexecution is not required, set `Requery` to `false`. If any of the `SelectCommand` properties or associated parameters must be changed, `Requery` must be set to `true`.

When the `Requery` property is set to `false`, the `DataSet` has all the data as a snapshot at a particular time. The query is executed only for the first `Fill` call; subsequent `Fill` calls fetch the data from a cursor opened with the first execution of the query. This feature is supported only for forward-only fetches. `Fill` calls that try to fetch rows before the last fetched row raise an exception. The connection used for the first `Fill` call must be available for subsequent `Fill` calls.

When filling a `DataSet` with an `OracleRefCursor` object, the `Requery` property can be used in a similar manner. When the `Requery` property is set to `false`, both the

connection used for the first `Fill` call and the `OracleRefCursor` object must be available for the subsequent `Fill` calls.

See Also:

- ["Requery"](#) on page 6-172
- ["SelectCommand"](#) on page 6-173

Guaranteeing Uniqueness in Updating DataSet to Database

This section describes how the `OracleDataAdapter` object configures the `PrimaryKey` and `Constraints` properties of the `DataTable` object which guarantee uniqueness when the `OracleCommandBuilder` object is updating `DataSet` changes to the database.

Using the `OracleCommandBuilder` object to dynamically generate DML statements to be executed against the database is one of the ways to reconcile changes made in a single `DataTable` object with the database.

In this process, the `OracleCommandBuilder` object must not be allowed to generate DML statements that may affect (update or delete) more than a single row in the database when reconciling a single `DataRow` change. Otherwise the `OracleCommandBuilder` could corrupt data in the database.

To guarantee that each `DataRow` object change affects only a single row, there must be a set of `DataColumn` objects in the `DataTable` for which all rows in the `DataTable` have a unique set of values. The set of `DataColumn` objects indicated by the properties `DataTable.PrimaryKey` and `DataTable.Constraints` meets this requirement. The `OracleCommandBuilder` object determines uniqueness in the `DataTable` by checking if the `DataTable.PrimaryKey` is not a null value or if there exists a `UniqueConstraint` object in the `DataTable.Constraints` collection.

This discussion first explains what constitutes uniqueness in `DataRow` objects and then explains how to maintain that uniqueness while updating, through the `DataTable` property configuration.

This section includes the following topics:

- [What Constitutes Uniqueness in DataRow Objects?](#)
- [Configuring PrimaryKey and Constraints Properties](#)
- [Updating Without PrimaryKey and Constraints Configuration](#)

What Constitutes Uniqueness in DataRow Objects?

This section describes the minimal conditions that must be met to guarantee uniqueness of `DataRow` objects. The condition of uniqueness must be guaranteed before the `DataTable.PrimaryKey` and `DataTable.Constraints` properties can be configured, as described in the next section.

Uniqueness is guaranteed in a `DataTable` object if any one of the following is true:

- All the columns of the primary key are in the select list of the `OracleDataAdapter.SelectCommand` property.
- All the columns of a unique constraint are in the select list of the `OracleDataAdapter.SelectCommand` property, with at least one involved column having a `NOT NULL` constraint defined on it.

- All the columns of a unique index are in the select list of the `OracleDataAdapter.SelectCommand` property, with at least one of the involved columns having a `NOT NULL` constraint defined on it.
- A `ROWID` is present in the select list of the `OracleDataAdapter.SelectCommand` property.

Note: A set of columns, on which a unique constraint has been defined or a unique index has been created, requires at least one column that cannot be null for the following reason: if all the columns of the column set can be null, then multiple rows could exist that have a `NULL` value for each column in the column set. This would violate the uniqueness condition that each row has a unique set of values for the column set.

Configuring PrimaryKey and Constraints Properties

If the minimal conditions described in "[What Constitutes Uniqueness in DataRow Objects?](#)" on page 3-123 are met, then the `DataTable.PrimaryKey` or `DataTable.Constraints` properties can be set.

After these properties are set, the `OracleCommandBuilder` object can determine uniqueness in the `DataTable` by checking the `DataTable.PrimaryKey` property or the presence of a `UniqueConstraint` object in the `DataTable.Constraints` collection. Once uniqueness is determined, the `OracleCommandBuilder` object can safely generate DML statements to update the database.

The `OracleDataAdapter.FillSchema` method attempts to set these properties according to this order of priority:

1. If the primary key is returned in the select list, it is set as the `DataTable.PrimaryKey` property.
2. If a set of columns that meets the following criteria is returned in the select list, it is set as the `DataTable.PrimaryKey` property.

Criteria: The set of columns has a unique constraint defined on it or a unique index created on it, with each column having a `NOT NULL` constraint defined on it.

3. If a set of columns that meets the following criteria is returned in the select list, a `UniqueConstraint` object is added to the `DataTable.Constraints` collection, but the `DataTable.PrimaryKey` property is not set.

Criteria: The set of columns has a unique constraint defined on it or a unique index created on it, with at least one column having a `NOT NULL` constraint defined on it.

4. If a `ROWID` is part of the select list, it is set as the `DataTable.PrimaryKey` property.

Additionally, the `OracleDataAdapter.FillSchema` method performs as follows:

- Setting the `DataTable.PrimaryKey` property implicitly creates a `UniqueConstraint` object.
- If a column is part of the `DataTable.PrimaryKey` property or the `UniqueConstraint` object, or both, it will be repeated for each occurrence of the column in the select list.

Updating Without PrimaryKey and Constraints Configuration

If the `DataTable.PrimaryKey` or `Constraints` properties have not been configured, for example, if the application has not called the `OracleDataAdapter.FillSchema` method, the `OracleCommandBuilder` object directly checks the select list of the `OracleDataAdapter.SelectCommand` property to determine if it guarantees uniqueness in the `DataTable`. However this check results in a database round-trip to retrieve the metadata for the `SELECT` statement of the `OracleDataAdapter.SelectCommand`.

Note that `OracleCommandBuilder` object cannot update a `DataTable` created from PL/SQL statements because they do not return any key information in their metadata.

Globalization Support

ODP.NET globalization support enables applications to manipulate culture-sensitive data appropriately. This feature ensures proper string format, date, time, monetary, numeric, sort order, and calendar conventions depending on the Oracle globalization settings.

Note:

- ODP.NET, Managed Driver is not `NLS_LANG` sensitive. It is only .NET locale sensitive.
 - ODP.NET, Managed Driver does not support thread-based globalization.
-
-

See Also: ["OracleGlobalization Class"](#) on page 10-2

This section includes the following:

- [Globalization Settings](#)
- [Globalization-Sensitive Operations](#)

Globalization Settings

An `OracleGlobalization` object can be used to represent the following:

- [Client Globalization Settings](#)
- [Session Globalization Settings](#)
- [Thread-Based Globalization Settings](#)

Client Globalization Settings

Client globalization settings are derived from the Oracle globalization setting (`NLS_LANG`) in the Windows registry of the local computer. The client globalization parameter settings are read-only and remain constant throughout the lifetime of the application. These settings can be obtained by calling the `OracleGlobalization.GetClientInfo` static method.

The following example retrieves the client globalization settings:

```
// C#
using System;
using Oracle.DataAccess.Client;
```

```
class ClientGlobalizationSample
{
    static void Main()
    {
        OracleGlobalization ClientGlob = OracleGlobalization.GetClientInfo();

        Console.WriteLine("Client machine language: " + ClientGlob.Language);
        Console.WriteLine("Client characterset: " + ClientGlob.ClientCharacterSet);
    }
}
```

The properties of the `OracleGlobalization` object provide the Oracle globalization value settings.

Session Globalization Settings

Session globalization parameters are initially identical to client globalization settings. Unlike client settings, session globalization settings can be updated. However, they can be obtained only after establishing a connection against the database. The session globalization settings can be obtained by calling the `GetSessionInfo` method on the `OracleConnection` object. Invoking this method returns an instance of an `OracleGlobalization` class whose properties represent the globalization settings of the session.

When the `OracleConnection` object establishes a connection, it implicitly opens a session whose globalization parameters are initialized with those values specified by the client computer's Oracle globalization (or (NLS)) registry settings. The session settings can be updated and can change during its lifetime.

The following example changes the date format setting on the session:

```
// C#

using System;
using Oracle.DataAccess.Client;

class SessionGlobalizationSample
{
    static void Main()
    {
        OracleConnection con = new OracleConnection();

        con.ConnectionString = "User Id=scott;Password=tiger;Data Source=oracle;";
        con.Open();

        OracleGlobalization SessionGlob = con.GetSessionInfo();

        // SetSessionInfo updates the Session with the new value
        SessionGlob.DateFormat = "YYYY/MM/DD";
        con.SetSessionInfo(SessionGlob);
        Console.WriteLine("Date Format successfully changed for the session");

        // Close and Dispose OracleConnection object
        con.Close();
        con.Dispose();
    }
}
```

Thread-Based Globalization Settings

Thread-based globalization parameter settings are specific to each thread. Initially, these settings are identical to the client globalization parameters, but they can be changed as specified by the application. When ODP.NET Types are converted to and from strings, the thread-based globalization parameters are used, if applicable.

Thread-based globalization parameter settings are obtained by invoking the `GetThreadInfo` static method of the `OracleGlobalization` class. The `SetThreadInfo` static method of the `OracleGlobalization` class can be called to set the thread's globalization settings.

ODP.NET classes and structures rely solely on the `OracleGlobalization` settings when manipulating culture-sensitive data. They do not use .NET thread culture information. If the application uses only .NET types, `OracleGlobalization` settings have no effect. However, when conversions are made between ODP.NET types and .NET types, `OracleGlobalization` settings are used where applicable.

Note: Changes to the `System.Threading.Thread.CurrentThread.CurrentCulture` property do not impact the `OracleGlobalization` settings of the thread or the session, or the reverse.

The following example shows how the thread's globalization settings are used by the ODP.NET Types:

```
// C#

using System;
using Oracle.DataAccess.Types;
using Oracle.DataAccess.Client;

class ThreadBasedGlobalizationSample
{
    static void Main(string[] args)
    {
        // Set the thread's DateFormat for the OracleDate constructor
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.DateFormat = "YYYY-MON-DD";
        OracleGlobalization.SetThreadInfo(info);

        // construct OracleDate from a string using the DateFormat specified.
        OracleDate date = new OracleDate("1999-DEC-01");

        // Set a different DateFormat for the thread
        info.DateFormat = "MM/DD/YYYY";
        OracleGlobalization.SetThreadInfo(info);

        // Print "12/01/1999"
        Console.WriteLine(date.ToString());
    }
}
```

The `OracleGlobalization` object validates property changes made to it. If an invalid value is used to set a property, an exception is thrown. Note that changes made to the `Territory` and `Language` properties change other properties of the `OracleGlobalization` object implicitly.

See Also: *Oracle Database Globalization Support Guide* for more information on the properties affected by Territory and Language globalization settings

Globalization-Sensitive Operations

This section lists ODP.NET types and operations that are dependent on or sensitive to globalization settings.

Operations Dependent on Client Computer's Globalization Settings

The `OracleString` structure depends on the `OracleGlobalization` settings of the client computer. The client character set of the local computer is used when it converts a Unicode string to a `byte[]` in the `GetNonUnicode` method and when it converts a `byte[]` of ANSI characters to Unicode in the `OracleString` constructor that accepts a `byte[]`.

Operations Dependent on Thread Globalization Settings

The thread globalization settings are used by ODP.NET types whenever they are converted to and from .NET string types, where applicable. Specific thread globalization settings are used in most cases, depending on the ODP.NET type, by the following:

- The `ToString` method
- The `Parse` static method
- Constructors that accept .NET string data
- Conversion operators to and from .NET strings

For example, the `OracleDate` type uses the `DateFormat` property of the thread globalization settings when the `ToString` method is invoked on it. This returns a `DATE` as a string in the format specified by the thread's settings.

For more details on the ODP.NET type methods that convert between ODP.NET types and .NET string types, and to identify which thread globalization settings are used for that particular method, read the remarks in [Chapter 10](#).

The thread globalization settings also affect data that is retrieved into the `DataSet` as a string using Safe Type Mapping. If the type is format-sensitive, the strings are always in the format specified by the thread globalization settings.

For example, `INTERVAL DAY TO SECOND` data is not affected by thread settings because no format is applicable for this type. However, the `DateFormat` and `NumericCharacters` properties can impact the string representation of `DATE` and `NUMBER` types, respectively, when they are retrieved as strings into the `DataSet` through Safe Type Mapping.

See Also:

- ["OracleDataAdapter Safe Type Mapping"](#) on page 3-119
- [Chapter 10, "Oracle Data Provider for .NET Globalization Classes"](#)
- [Chapter 14, "Oracle Data Provider for .NET Types Structures"](#)

Operations Sensitive to Session Globalization Parameters

Session globalization settings affect any data that is retrieved from or sent to the database as a string.

For example, if a `DATE` column is selected with the `TO_CHAR` function applied on it, the `DATE` column data will be a string in the date format specified by the `DateFormat` property of the session globalization settings. Transmitting data in the other direction, the string data that is to be inserted into the `DATE` column, must be in the format specified by the `DateFormat` property of the session globalization settings.

Debug Tracing

ODP.NET provides debug tracing support, which allows logging of all the ODP.NET activities into a trace file. Different levels of tracing are available.

The provider can record the following information:

- Entry and exit information for the ODP.NET public methods
- User-provided SQL statements as well as SQL statements modified by the provider
- Connection pooling statistics such as enlistment and delistment
- Thread ID (entry and exit)
- HA Events and Load Balancing information
- Distributed Transactions
- Self-tuning information
- User-mode dumps upon unmanaged exceptions

To enable ODP.NET for tracing, `TraceFileName`, `TraceLevel`, and `TraceOption` must be set appropriately either in the Windows Registry or in an XML configuration file.

See Also: ["Configuring Oracle Data Provider for .NET"](#) on page 2-9 for further details

ADO.NET Entity Framework and LINQ to Entities

This section describes ADO.NET Entity Framework and LINQ to Entities. Entity Framework is a framework for providing object-relational mapping service on data models.

This section contains these topics:

- [Overview of Entity Framework](#)
- [Mapping Oracle Data Types to EDM Types](#)
- [Oracle Number Default Data Type Mapping and Customization](#)

Overview of Entity Framework

ODP.NET 11.2.0.3.0 and higher includes support for the ADO.NET Entity Framework and LINQ to Entities. ODP.NET also supports Entity SQL.

Entity Framework is a framework for providing object-relational mapping service on data models. Entity Framework addresses the impedance mismatch between the relational database format and the client's preferred object format. Language Integrated Query (LINQ) defines a set of operators that can be used to query, project, and filter data in arrays, enumerable classes, XML, relational databases, and other data sources. One form of LINQ, LINQ to Entities, allows querying of Entity Framework data sources. ODP.NET supports Entity Framework such that the Oracle database can participate in object-relational modeling and LINQ to Entities queries.

Entity Framework and LINQ provides productivity benefits for the .NET developer. It abstracts the database's data model from the application's data model. Working with object-relational data becomes easier with Entity Framework's tools. Oracle's integration with Entity Framework and LINQ enables Oracle .NET developers to take advantage of all these productivity benefits.

Note:

- Entity Framework and LINQ to Entities support is included in ODP.NET for .NET Framework 4. ODP.NET for .NET Framework 2.0 does not support the ADO.NET Entity Framework and LINQ to Entities.
 - Code First is supported starting with Entity Framework 6 and higher.
 - Binding scalar parameters is supported with ODP.NET and Entity Framework. In Entity Framework, parameter binding by name is supported. Binding by position is not supported.
-
-

Entity data models can be generated from Oracle database schemas. Schemas can be generated from entity data models. These Oracle entity data models can be queried and manipulated using Visual Studio and ODP.NET. Oracle supports Code First, Database First, and Model First modeling approaches. Specifying filters on the Visual Studio Server Explorer data connection enables the Entity Data Model Wizard to also filter Oracle database objects that are fetched and displayed.

LINQ to Entities can perform queries on the Oracle Database using ODP.NET, including using LINQ to Entities built-in functions. `INSERTS`, `UPDATES`, and `DELETES` can be executed using Oracle stored procedures, or by using the `ObjectContext.SaveChanges` method.

ODP.NET supports function import of Oracle stored procedures that Entity Framework can then execute. These Oracle function imports can return a collection of scalar, complex, and entity types, including returning an Oracle implicit result set as an entity type. Implicit result set binding is supported using Oracle `REF CURSOR`. See "[Implicit REF CURSOR Binding](#)" on page 3-67 for more details.

See Also: For a tutorial on how to use Entity Framework, Language Integrated Query (LINQ), and generate Data Definition Language (DDL) scripts using Model First, refer to:

<http://www.oracle.com/webfolder/technetwork/tutorials/obe/db/dotnet/EntityFrameworkOBE/EntityFrameworkOBE.htm>

Mapping Oracle Data Types to EDM Types

The ODP.NET manifest file describes the primitive types, such as `VARCHAR2` and `Number`, and the Entity Data Model (EDM) types, such as `string` and `Int32`, that they map to. It also includes the facets for each EDM type.

ODP.NET does not support Time literals and canonical functions related to the Time type.

Oracle considers both `NULL` and empty strings to be `NULL` strings and are considered to be equal. Operations, such as `Equals()`, `Length()`, and `Trim()` on such strings will result in a `NULL` string.

[Table 4–1](#) maps the Oracle data types to their corresponding EDM types. The table also includes details about provider type attributes and the EDM type facets associated with each Oracle data type.

Table 4–1 Mapping of Oracle Data Types and EDM Types

| Oracle Data Types | EDM Types (Primitive-TypeKind) | Provider Type Attributes: Name and Value | EDM Type Facets |
|--------------------------|-------------------------------------------|----------------------------------------------------------------------------------------------------------------|------------------------------------------------------------|
| Bfile | Binary | <ul style="list-style-type: none"> ▪ Equal Comparable: False ▪ Order Comparable: False | EDM Type Facets for Bfile |
| Binary_Double | Double | <ul style="list-style-type: none"> ▪ Equal Comparable: True ▪ Order Comparable: True | Not Applicable |
| Binary_Float | Single | <ul style="list-style-type: none"> ▪ Equal Comparable: True ▪ Order Comparable: True | Not Applicable |
| Binary_Integer | Int32 | <ul style="list-style-type: none"> ▪ Equal Comparable: True ▪ Order Comparable: True | Not Applicable |
| Blob | Binary | <ul style="list-style-type: none"> ▪ Equal Comparable: False ▪ Order Comparable: False | EDM Type Facets for Blob |
| Char | String | <ul style="list-style-type: none"> ▪ Equal Comparable: True ▪ Order Comparable: True | EDM Type Facets for Char |
| Clob | String | <ul style="list-style-type: none"> ▪ Equal Comparable: False ▪ Order Comparable: False | EDM Type Facets for Clob |
| Date | DateTime | <ul style="list-style-type: none"> ▪ Equal Comparable: True ▪ Order Comparable: True | EDM Type Facets for Date |
| Float | Decimal | <ul style="list-style-type: none"> ▪ Equal Comparable: True ▪ Order Comparable: True | EDM Type Facets for Float |
| Int | Int32 | <ul style="list-style-type: none"> ▪ Equal Comparable: True ▪ Order Comparable: True | Not Applicable |
| Interval Day To Second | Decimal | <ul style="list-style-type: none"> ▪ Equal Comparable: True ▪ Order Comparable: True | EDM Type Facets for Interval Day To Second |

Table 4–1 (Cont.) Mapping of Oracle Data Types and EDM Types

| Oracle Data Types | EDM Types (Primitive-TypeKind) | Provider Type Attributes: Name and Value | EDM Type Facets |
|--------------------------|-------------------------------------------|----------------------------------------------------------------------------------------------------------------|------------------------------------------------------------|
| Interval Year To Month | Decimal | <ul style="list-style-type: none"> ■ Equal Comparable: True ■ Order Comparable: True | EDM Type Facets for Interval Year To Month |
| Long | String | <ul style="list-style-type: none"> ■ Equal Comparable: False ■ Order Comparable: False | EDM Type Facets for Long |
| Long Raw | Binary | <ul style="list-style-type: none"> ■ Equal Comparable: False ■ Order Comparable: False | EDM Type Facets for Long Raw |
| NChar | String | <ul style="list-style-type: none"> ■ Equal Comparable: True ■ Order Comparable: True | EDM Type Facets for NChar |
| NClob | String | <ul style="list-style-type: none"> ■ Equal Comparable: False ■ Order Comparable: False | EDM Type Facets for NClob |
| Nested Table | | Not Applicable | Not Applicable and Not Supported |
| Number (1,0) | Int16 | <ul style="list-style-type: none"> ■ Equal Comparable: True | Not Applicable |
| Number (2,0) | | <ul style="list-style-type: none"> ■ Order Comparable: True | |
| Number (3,0) | | | |
| Number (4,0) | | | |
| Number (5,0) | | | |
| Number (6,0) | Int32 | <ul style="list-style-type: none"> ■ Equal Comparable: True | Not Applicable |
| Number (7,0) | | <ul style="list-style-type: none"> ■ Order Comparable: True | |
| Number (8,0) | | | |
| Number (9,0) | | | |
| Number (10,0) | | | |
| Number (11,0) | Int64 | <ul style="list-style-type: none"> ■ Equal Comparable: True | Not Applicable |
| Number (12,0) | | <ul style="list-style-type: none"> ■ Order Comparable: True | |
| Number (13,0) | | | |
| Number (14,0) | | | |
| Number (15,0) | | | |
| Number (16,0) | | | |
| Number (17,0) | | | |
| Number (18,0) | | | |
| Number (19,0) | | | |

Table 4–1 (Cont.) Mapping of Oracle Data Types and EDM Types

| Oracle Data Types | EDM Types (Primitive-TypeKind) | Provider Type Attributes: Name and Value | EDM Type Facets |
|-----------------------------------|-------------------------------------------|--------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------|
| Number (all other cases) | Decimal | <ul style="list-style-type: none"> ■ Equal Comparable: True ■ Order Comparable: True | EDM Type Facets for Number |
| NVarchar2 | String | <ul style="list-style-type: none"> ■ Equal Comparable: True ■ Order Comparable: True | EDM Type Facets for NVarchar2 |
| Object | | Not Applicable | Not Applicable and Not Supported |
| Raw | Binary | <ul style="list-style-type: none"> ■ Equal Comparable: True ■ Order Comparable: True | EDM Type Facets for Raw |
| Raw(16) | Guid | <ul style="list-style-type: none"> ■ Equal Comparable: True ■ Order Comparable: True | Not Applicable |
| Ref | | Not Applicable | Not Applicable and Not Supported |
| ROWID | String | <ul style="list-style-type: none"> ■ Equal Comparable: True ■ Order Comparable: True | EDM Type Facets for ROWID |
| Smallint | Int16 | <ul style="list-style-type: none"> ■ Equal Comparable: True ■ Order Comparable: True | Not Applicable |
| Timestamp | DateTime | <ul style="list-style-type: none"> ■ Equal Comparable: True ■ Order Comparable: True | EDM Type Facets for Timestamp |
| Timestamp with Local Time Zone | DateTime | <ul style="list-style-type: none"> ■ Equal Comparable: True ■ Order Comparable: True | EDM Type Facets for Timestamp with Local Time Zone |
| Timestamp with Time Zone | DateTimeOffset | <ul style="list-style-type: none"> ■ Equal Comparable: True ■ Order Comparable: True | EDM Type Facets for Timestamp with Time Zone |
| UROWID (size) | Binary | <ul style="list-style-type: none"> ■ Equal Comparable: True ■ Order Comparable: True | EDM Type Facets for UROWID |

Table 4–1 (Cont.) Mapping of Oracle Data Types and EDM Types

| Oracle Data Types | EDM Types (Primitive-TypeKind) | Provider Type Attributes: Name and Value | EDM Type Facets |
|-------------------|--------------------------------|----------------------------------------------------------------------------------------------------------------|----------------------------------------------|
| Varchar2 | String | <ul style="list-style-type: none"> ■ Equal Comparable: True ■ Order Comparable: True | EDM Type Facets for Varchar2 |
| VArray | | Not Applicable | Not Applicable and Not Supported |
| XMLType | String | <ul style="list-style-type: none"> ■ Equal Comparable: False ■ Order Comparable: False | EDM Type Facets for XMLType |

EDM Type Facets

The following sections enumerate the EDM type facets for the preceding Oracle data types:

EDM Type Facets for Bfile

| Facet name | Attribute name | Value |
|-------------|----------------|------------|
| MaxLength | DefaultValue | 2147483648 |
| | Constant | True |
| FixedLength | DefaultValue | False |
| | Constant | True |

EDM Type Facets for Blob

| Facet name | Attribute name | Value |
|-------------|----------------|------------|
| MaxLength | DefaultValue | 2147483648 |
| | Constant | True |
| FixedLength | DefaultValue | False |
| | Constant | True |

EDM Type Facets for Char

| Facet name | Attribute name | Value |
|-------------|----------------|-------|
| MaxLength | Minimum | 1 |
| | Maximum | 2000 |
| | DefaultValue | 2000 |
| | Constant | False |
| Unicode | DefaultValue | False |
| | Constant | True |
| FixedLength | DefaultValue | True |
| | Constant | True |

EDM Type Facets for Clob

| Facet name | Attribute name | Value |
|-------------|----------------|------------|
| MaxLength | DefaultValue | 2147483647 |
| | Constant | True |
| Unicode | DefaultValue | False |
| | Constant | True |
| FixedLength | DefaultValue | False |
| | Constant | True |

EDM Type Facets for Date

| Facet name | Attribute name | Value |
|------------|----------------|-------|
| Precision | Constant | True |
| | DefaultValue | 0 |

EDM Type Facets for Float

| Facet name | Attribute name | Value |
|------------|----------------|-------|
| Precision | Minimum | 0 |
| | Maximum | 126 |
| | DefaultValue | 0 |
| | Constant | False |
| Scale | Minimum | 0 |
| | Maximum | 38 |
| | DefaultValue | 0 |
| | Constant | False |

EDM Type Facets for Interval Day To Second

| Facet name | Attribute name | Value |
|------------|----------------|-------|
| Precision | Minimum | 1 |
| | Maximum | 251 |
| | DefaultValue | 251 |
| | Constant | False |
| Scale | Minimum | 0 |
| | Maximum | 9 |
| | DefaultValue | 0 |
| | Constant | False |

Note: EDM types do not support `TimeSpan`.

Use `Decimal` to represent the total number of seconds. An application can obtain a `TimeSpan` by using the `TimeSpan.FromSeconds` static method.

EDM Type Facets for Interval Year To Month

| Facet name | Attribute name | Value |
|------------|----------------|-------|
| Precision | Minimum | 1 |
| | Maximum | 250 |
| | DefaultValue | 250 |
| | Constant | False |
| Scale | Minimum | 0 |
| | Maximum | 9 |
| | DefaultValue | 0 |
| | Constant | False |

EDM Type Facets for Long

| Facet name | Attribute name | Value |
|-------------|----------------|------------|
| MaxLength | DefaultValue | 2147483647 |
| | Constant | True |
| Unicode | DefaultValue | False |
| | Constant | True |
| FixedLength | DefaultValue | False |
| | Constant | True |

EDM Type Facets for Long Raw

| Facet name | Attribute name | Value |
|-------------|----------------|------------|
| MaxLength | DefaultValue | 2147483647 |
| | Constant | True |
| FixedLength | DefaultValue | False |
| | Constant | True |

EDM Type Facets for NChar

| Facet name | Attribute name | Value |
|------------|----------------|-------|
| MaxLength | Minimum | 1 |
| | Maximum | 1000 |
| | DefaultValue | 1000 |
| | Constant | False |

| Facet name | Attribute name | Value |
|-------------|----------------|-------|
| Unicode | DefaultValue | True |
| | Constant | True |
| FixedLength | DefaultValue | True |
| | Constant | True |

Note: For `NChar`, the actual data is subject to the maximum byte limit of 2000.

The value of 1000 for `Maximum` and `DefaultValue` allows the EDM wizard to display columns of `NCHAR(1000)`, where 1000 is the maximum number of characters allowed in DDL.

EDM Type Facets for NClob

| Facet name | Attribute name | Value |
|-------------|----------------|------------|
| MaxLength | DefaultValue | 2147483647 |
| | Constant | True |
| Unicode | DefaultValue | True |
| | Constant | True |
| FixedLength | DefaultValue | False |
| | Constant | True |

EDM Type Facets for Number

| Facet name | Attribute name | Value |
|------------|----------------|-------|
| Precision | Minimum | 1 |
| | Maximum | 38 |
| | DefaultValue | 38 |
| | Constant | False |
| Scale | Minimum | 0 |
| | Maximum | 38 |
| | DefaultValue | 0 |
| | Constant | False |

EDM Type Facets for NVarchar2

| Facet name | Attribute name | Value |
|------------|----------------|-------|
| MaxLength | Minimum | 1 |
| | Maximum | 2000 |
| | DefaultValue | 2000 |
| | Constant | False |
| Unicode | DefaultValue | True |
| | Constant | True |

| Facet name | Attribute name | Value |
|-------------|----------------|-------|
| FixedLength | DefaultValue | False |
| | Constant | True |

Note: For NVARCHAR2, the actual data is subject to the maximum byte limit of 4000.

The value of 2000 for Maximum and DefaultValue allows the EDM wizard to display columns of NVARCHAR2(2000), where 2000 is the maximum number of characters allowed in DDL.

EDM Type Facets for Raw

| Facet name | Attribute name | Value |
|-------------|----------------|-------|
| MaxLength | Minimum | 1 |
| | Maximum | 2000 |
| | Constant | False |
| FixedLength | DefaultValue | False |
| | Constant | True |

EDM Type Facets for ROWID

| Facet name | Attribute name | Value |
|-------------|----------------|-------|
| MaxLength | DefaultValue | 18 |
| | Constant | True |
| Unicode | DefaultValue | False |
| | Constant | True |
| FixedLength | DefaultValue | True |
| | Constant | True |

EDM Type Facets for Timestamp

| Facet name | Attribute name | Value |
|------------|----------------|-------|
| Precision | Minimum | 0 |
| | Maximum | 9 |
| | DefaultValue | 6 |
| | Constant | False |

EDM Type Facets for Timestamp with Local Time Zone

| Facet name | Attribute name | Value |
|------------|----------------|-------|
| Precision | Minimum | 0 |
| | Maximum | 9 |
| | DefaultValue | 6 |
| | Constant | False |

EDM Type Facets for Timestamp with Time Zone

| Facet name | Attribute name | Value |
|------------|----------------|-------|
| Precision | Minimum | 0 |
| | Maximum | 9 |
| | DefaultValue | 6 |
| | Constant | False |

EDM Type Facets for UROWID

| Facet name | Attribute name | Value |
|-------------|----------------|-------|
| MaxLength | DefaultValue | 4000 |
| | Constant | True |
| FixedLength | DefaultValue | True |
| | Constant | True |

EDM Type Facets for Varchar2

| Facet name | Attribute name | Value |
|-------------|----------------|-------|
| MaxLength | Minimum | 1 |
| | Maximum | 4000 |
| | DefaultValue | 4000 |
| | Constant | False |
| Unicode | DefaultValue | False |
| | Constant | True |
| FixedLength | DefaultValue | False |
| | Constant | True |

EDM Type Facets for XMLType

| Facet name | Attribute name | Value |
|-------------|----------------|------------|
| MaxLength | DefaultValue | 2147483647 |
| | Constant | True |
| Unicode | DefaultValue | True |
| | Constant | True |
| FixedLength | DefaultValue | False |
| | Constant | True |

Oracle Number Default Data Type Mapping and Customization

You can configure a custom mapping in the .NET configuration file to override the default mapping for the `Number(p, 0)` Oracle data type. So, for example, `Number(1, 0)`, which is mapped to `Int16` by default, can be custom mapped to the .NET `Bool` or .NET `Byte` type.

[Example 4-1](#) shows a sample `app.config` file that uses custom mapping to map the `Number(1, 0)` Oracle data type to the `bool` EDM type. The example also maps `Number(3, 0)` to `byte`, and sets the maximum precisions for the `Int16`, `Int32`, and `Int64` data types to 4, 9, and 18 respectively.

Example 4-1 Sample Application Configuration File to Custom Map the Number (p,0) Data Type

```
<?xml version="1.0" encoding="utf-8"?>
<configuration>
  <connectionStrings>
  </connectionStrings>
  <oracle.dataaccess.client>
    <settings>
      <add name="bool" value="edmmapping number(1,0)" />
      <add name="byte" value="edmmapping number(3,0)" />
      <add name="int16" value="edmmapping number(4,0)" />
      <add name="int32" value="edmmapping number(9,0)" />
      <add name="int64" value="edmmapping number(18,0)" />
    </settings>
  </oracle.dataaccess.client>
</configuration>
```

[Example 4-2](#) shows a ODP.NET, Managed Driver sample `app.config` file.

Example 4-2 Sample ODP.NET, Managed Driver Application Configuration File to Custom Map the Number Data Type

```
<?xml version="1.0" encoding="utf-8" ?>
<configuration>
  <oracle.manageddataaccess.client>
    <version number="*">
      <edmMappings>
        <edmMapping dataType="number">
          <add name="bool" precision="1" />
          <add name="byte" precision="3" />
          <add name="int16" precision="4" />
          <add name="int32" precision="9" />
          <add name="int64" precision="18" />
        </edmMapping>
      </edmMappings>
    </version>
  </oracle.manageddataaccess.client>
</configuration>
```

[Example 4-1](#) and [Example 4-2](#) customizes the mappings as follows:

| Oracle Type | Default EDM Type | Custom EDM Type |
|-----------------------------------------------------------|--------------------|-------------------|
| <code>Number(1, 0)</code> | <code>Int16</code> | <code>bool</code> |
| <code>Number(2, 0)</code> to <code>Number(3, 0)</code> | <code>Int16</code> | <code>byte</code> |

| Oracle Type | Default EDM Type | Custom EDM Type |
|-------------------------------------|------------------|-----------------|
| Number (4, 0) | Int16 | Int16 |
| Number (5, 0) | Int16 | Int32 |
| Number (6, 0) to Number (9, 0) | Int32 | Int32 |
| Number (10, 0) | Int32 | Int64 |
| Number (11, 0) to Number (18, 0) | Int64 | Int64 |
| Number (19, 0) | Int64 | Decimal |

Custom mapping configures the maximum precision of the Oracle `Number` type that would map to the .NET/EDM type. So, for example, the preceding custom application configuration file configures ODP.NET to map `Number (10, 0)` through `Number (18, 0)` to `Int64`, as opposed to the default range of `Number (11, 0)` through `Number (19, 0)` for `Int64`.

Note:

- Custom mapping does not require you to map all the .NET/EDM types. For example, if custom mapping is required just for `Int16`, then having a single entry for `Int16` is sufficient. Default mapping gets used for the other types.
 - When using Model First, a `Byte` attribute is mapped to `Number (3, 0)` by default. However, when a model is generated for a `Number (3, 0)` column, it gets mapped to `Int16` by default unless custom mapping for `Byte` is specified.
 - ODP.NET managed and unmanaged driver .NET configuration file settings for native Entity Framework 6 applications have a different format than the traditional .NET configuration file settings. For more information on this format, refer to the ODP.NET README. The README also describes ODP.NET-specific steps to migrate from an Entity Framework 5 application to Entity Framework 6.
-
-

You must make sure that your mappings allow the data to fit within the range of the .NET/EDM type and the `Number (p, s)` type. If you select a .NET/EDM type with a range too small for the Oracle `Number` data, then errors will occur during data retrieval. Also, if you select a .NET/EDM type, and the corresponding data is too big for the Oracle `Number` column, then INSERTs and UPDATEs to the Oracle database will error out.

Data Type Mapping and Customization Process

To enable custom mapping, add the mapping information to the .NET config file *prior* to EDM creation.

If the EDM was created already before providing the mapping information, then you can *modify* the mappings either through the Visual Studio tools or manually. Using Visual Studio, go to the EDM Model Browser page. Right-click on the table(s) requiring new data type mapping and select **Table Mapping** from the pop-up menu.

The **Mapping Details** window will appear usually at the bottom of your screen. Update **Column Mappings** as desired.

If you need to *add* or *delete* mappings, find the **Type** values in the CSDL mapping section of your project's existing EDMX file. Add or delete those **Type** values to the .NET data types you want the application to use. In the example below, the property name types for `BOOLCOL` and `BYTECOL` are added to the CSDL and mapped to `Boolean` and `Byte`, respectively.

Example Mapping Before CSDL Customization:

```
<Property Name="INT16COL" Type="Int16" Nullable="false" />
```

Example Mapping After CSDL Customization:

```
<Property Name="BOOLCOL" Type="Boolean" Nullable="false" />
<Property Name="BYTECOL" Type="Byte" Nullable="false" />
<Property Name="INT16COL" Type="Int16" Nullable="false" />
```

You can employ combinations of these customization possibilities depending on your planned mapping changes. If *many* tables and *many* columns require mapping changes, it is most efficient to delete the EDMX file and regenerate the data model. If a *few* tables and *many* columns require changes, then delete the affected tables, save the EDMX file, and select **Update Model from Database...** to include those tables again. If only a *single* table and *one or two* columns require changes, then modify the EDMX either manually or by using the **Mapping Details** window.

StoreGeneratedPattern Enumeration

The following sections describe the Identity attribute and the Virtual column.

Identity Attribute

Oracle Database 12c (12.1) and later versions support table or view Identity attribute columns. Oracle has three Identity attribute types. When the EDM wizard generates a data model from an Oracle Identity attribute-containing table or view, ODP.NET will set the value of `StoreGeneratedPattern` to `Identity` in the .edmx file for any of three Oracle Identity types. The Identity attribute-associated column will use the server-generated value during `INSERT`; hence, application developers no longer need to create a sequence nor trigger. If the .NET application attempts to set the Identity attribute itself, this value will be ignored.

For Oracle Database 11g Release 2 (11.2) and earlier versions that do not support Identity columns, application developers can manually set `StoreGeneratedPattern` to `Identity` in columns through the entity model designer Properties after model generation, then create an `INSERT` trigger. Depending on the data type, a sequence may not be necessary if a server function, such as `sys_guid()`, can generate the value for the column.

Virtual Column

Oracle Database 11g (11.1) and later versions can store expressions directly in base tables as Virtual columns, also known as Generated columns. Virtual columns cannot be inserted into or updated. ODP.NET will not automatically set `StoreGeneratedPattern` to `Computed` in the EF model for Virtual columns. To avoid errors, application developers need to add or change the value of `StoreGeneratedPattern` to `Computed` for Virtual columns after the model generation. Once done, Virtual columns are excluded from `INSERTS` and `UPDATES` upon calling `SaveChanges()`.

Resolving Compilation Errors When Using Custom Mapping

If the custom mapping in a .NET configuration file has changed, then regenerate the data model to solve compilation errors introduced by the changes.

Under certain scenarios, custom mapping may cause compilation errors when a project that uses custom mapping is loaded by Visual Studio. You may use the following workaround for such scenarios:

1. Open Visual Studio Help, About Microsoft Visual Studio. Click **OK** to exit the dialog box.

Alternatively, open the to-be-used connection in Server Explorer.

2. Compile the project again to eliminate the compilation errors.

Mapping Boolean and Guid Parameters in Custom INSERT, UPDATE, and DELETE Stored Procedures

When using your custom INSERT, UPDATE, or DELETE stored procedure in Stored Procedure Mapping, the following error might occur:

```
Error 2042: Parameter Mapping specified is not valid.
```

This can happen if a Number parameter has been mapped to a Boolean attribute, or if a RAW parameter has been mapped to a Guid attribute.

The solution is to manually add `Precision="1"` for the Number parameter, and `MaxLength="16"` for the RAW parameter of your stored procedure in the SSDL.

Oracle Data Provider for .NET Stored Procedures

This section discusses server-side features provided by Oracle Data Provider for .NET.

With the support for .NET stored procedures in Oracle Databases for Windows that Oracle Database Extensions for .NET provides, ODP.NET can be used to access Oracle data through the [implicit database connection](#) that is available from the context of the .NET stored procedure execution. Explicit user connections can also be created to establish connections to the database that hosts the .NET stored procedure or to other Oracle Databases.

See Also: *Oracle Database Extensions for .NET Developer's Guide for Microsoft Windows*

This section contains these topics:

- [Introducing .NET Stored Procedure Execution Using ODP.NET](#)
- [Limitations and Restrictions on ODP.NET Within .NET Stored Procedure](#)
- [Porting Client Application to .NET Stored Procedure](#)

Introducing .NET Stored Procedure Execution Using ODP.NET

Oracle Data Provider for .NET classes and APIs provide data access to the Oracle Database from a .NET client application and from .NET stored procedures and functions.

However, some limitations and restrictions exist when Oracle Data Provider for .NET is used within a .NET stored procedure. These are discussed in the next section.

The following is a simple .NET stored procedure example.

```
using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

public class CLRLibrary1
{
    // .NET Stored Function returning the DEPTNO of the employee whose
    // EMPNO is 'empno'
    public static uint GetDeptNo(uint empno)
    {
        uint deptno = 0;
```

```

// Create and open a context connection
OracleConnection conn = new OracleConnection();
if( OracleConnection.IsAvailable == true )
{
    conn.ConnectionString = "context connection=true";
}
else
{
    //set connection string for a normal client connection
    conn.ConnectionString = "user id=scott;password=tiger;" +
        "data source=oracle";
}
conn.Open();

// Create and execute a command
OracleCommand cmd = conn.CreateCommand();
cmd.CommandText = "SELECT DEPTNO FROM EMP WHERE EMPNO = :1";
cmd.Parameters.Add(":1", OracleDbType.Int32, empno,
    System.Data.ParameterDirection.Input);
OracleDataReader rdr = cmd.ExecuteReader();
if (rdr.Read())
    deptno = (uint)rdr.GetInt32(0);
rdr.Close();
cmd.Dispose();
conn.Close();
return deptno;
} // GetDeptNo
} // CLRLibrary1

```

See Also:

- *Oracle Database Extensions for .NET Developer's Guide for Microsoft Windows* for more information about how to create .NET Stored procedures
- [Table 5-1, "API Support Comparison Between Client Application and .NET Stored Procedure"](#) on page 5-6

Limitations and Restrictions on ODP.NET Within .NET Stored Procedure

This section covers important concepts that apply when Oracle Data Provider for .NET is used within a .NET stored procedure.

Note: ODP.NET, Managed Driver does not support .NET stored procedures.

Implicit Database Connection

Within a .NET stored procedure, an implicit database connection is available for use to access Oracle data. This implicit database connection should be used rather than establishing a user connection because the **implicit database connection** is already established by the caller of the .NET stored procedure, thereby minimizing resource usage.

To obtain an `OracleConnection` object in a .NET stored procedure that represents the implicit database connection, set the `ConnectionString` property of the `OracleConnection` object to "context connection=true" and invoke the `Open` method.

No connection string attributes can be used with "context connection=true", except the Statement Cache Size attribute.

The availability of the implicit database connection can be checked at run time through the static `OracleConnection.IsAvailable` property. This property always returns `true` when Oracle Data Provider for .NET is used within a .NET stored procedure. Otherwise, `false` is returned.

Note: DBLinks are not supported in .NET stored procedures.

Only one implicit database connection is available within a .NET stored procedure invocation. To establish more connections in addition to the implicit database connection, an explicit connection must be created. When the `Close` method is invoked on the `OracleConnection` that represents the implicit database connection, the connection is not actually closed. Therefore, the `Open` method of the same or another `OracleConnection` object can be invoked to obtain the connection that represents the implicit database connection.

The implicit database connection can only be acquired by the `Open` method invocation by a native Oracle thread that initially invokes the .NET stored procedure. However, threads spawned from the native Oracle thread can use implicit database connections that are obtained by the native Oracle thread.

See Also: ["IsAvailable"](#) on page 6-87

Transaction Support

The .NET stored procedure execution automatically inherits the current transaction on the implicit database connection. No explicit transaction can be started, committed, or rolled back inside a .NET stored procedure on a Context connection. However, explicit transaction can be started, committed, or rolled back inside a .NET stored procedure on a Client connection.

For example, `OracleConnection.BeginTransaction` is not allowed inside a .NET stored procedure for a context connection, but is allowed for a client connection. .NET stored procedures do not support distributed transactions. If you have enlisted a client connection in a distributed transaction and call a .NET stored procedure or function, an error occurs.

If a .NET stored procedure or function performs operations on the database that are required to be part of a transaction, the transaction must be started prior to calling the .NET stored procedure. Any desired commit or rollback must be performed after returning from the .NET stored procedure or function.

The following example consists of a client application and a .NET stored procedure, `InsertRecordSP`, that inserts an employee record into an `EMP` table.

Example (.NET Stored Procedure)

```
using System;
using System.Data;
using Oracle.DataAccess.Client;
// This class represents an Oracle .NET stored procedure that inserts
// an employee record into an EMP table of SCOTT schema.
public class InsertRecordSP
{
    // This procedure will insert a row into the emp database
    // For simplicity we are using only two parameters, the rest are hard coded
```

```

public static void InsertRecord( int EmpNo, string EmpName )
{
    if(OracleConnection.IsAvailable == true )
    {
        OracleConnection conn = new OracleConnection(
            "context connection=true");
        conn.Open();
        // Create new command object from connection context
        OracleCommand Cmd = conn.CreateCommand();
        Cmd.CommandText = "INSERT INTO EMP( EMPNO, ENAME, JOB," +
            "MGR, HIREDATE, SAL, COMM, DEPTNO ) " +
            "VALUES ( :1, :2, 'ANALYST', 7566, " +
            "'06-DEC-04', 5000, 0, 20 )";
        Cmd.Parameters.Add( ":1", OracleDbType.Int32,
            EmpNo, ParameterDirection.Input );
        Cmd.Parameters.Add( ":2", OracleDbType.Varchar2,
            EmpName, ParameterDirection.Input );
        Cmd.ExecuteNonQuery();
    }
}

```

Example (Client Application)

The example enters new employee, Bernstein, employee number 7950, into the EMP table.

```

// C#
// This sample demonstrates how to start the transaction with ODP.NET client
// application and execute an Oracle .NET stored procedure that performs
// a DML operation. Since .NET stored procedure inherits the current
// transaction from the implicit database connection, DML operation
// in .NET stored procedure will not be in auto-committed mode.
// Therefore, it is up to the client application to do a COMMIT or ROLLBACK
// after returning from .NET stored procedure
using System;
using System.Data;
using Oracle.DataAccess.Client;
// In this class we are starting a transaction on the client side and
// executing a .NET stored procedure, which inserts a record into EMP
// table and then verifies record count before and after COMMIT statement
class TransactionSample
{
    static void Main(string[] args)
    {
        OracleConnection Conn = null;
        OracleTransaction Txn = null;
        OracleCommand Cmd = null;
        try
        {
            Console.WriteLine( "Sample: Open DB connection in non auto-committed "
                + "mode," +
                "DML operation performed by .NET stored " +
                "procedure doesn't have an effect before COMMIT " +
                "is called." );
            // Create and Open oracle connection
            Conn = new OracleConnection();
            Conn.ConnectionString = "User Id=scott;Password=tiger;" +
                "Data Source=oracle;";
            Conn.Open();
            // Start transaction

```

```

Txn = Conn.BeginTransaction( IsolationLevel.ReadCommitted );
// Create command object
Cmd = new OracleCommand();
Cmd.Connection = Conn;
Cmd.CommandType = CommandType.StoredProcedure;
Cmd.CommandText = "InsertRecord"; // .NET Stored procedure
// Parameter settings
OracleParameter EmpNoPrm = Cmd.Parameters.Add(
    "empno", OracleDbType.Int32 );
EmpNoPrm.Direction = ParameterDirection.Input;
EmpNoPrm.Value = 7950;
OracleParameter EmpNamePrm = Cmd.Parameters.Add(
    "ename", OracleDbType.Varchar2, 10 );
EmpNamePrm.Direction = ParameterDirection.Input;
EmpNamePrm.Value = "Bernstein";
// Execute .NET stored procedure
Cmd.ExecuteNonQuery();
Console.WriteLine( "Number of record(s) before COMMIT {0}",
    RecordCount() );
Txn.Commit();
Console.WriteLine( "Number of record(s) after COMMIT {0}",
    RecordCount() );
}
catch( OracleException OE )
{
    Console.WriteLine( OE.Message );
}
finally
{
    // Cleanup objects
    if( null != Txn )
        Txn.Dispose();
    if( null != Cmd )
        Cmd.Dispose();
    if( null != Conn && Conn.State == ConnectionState.Open )
        Conn.Close();
}
}
static int RecordCount()
{
    int EmpCount = 0;
    OracleConnection Conn = null;
    OracleCommand Cmd = null;
    try
    {
        Conn = new OracleConnection( "User Id=scott;Password=tiger;" +
            "Data Source=oracle;" );
        Conn.Open();
        Cmd = new OracleCommand( "SELECT COUNT(*) FROM EMP", Conn );
        Object o = Cmd.ExecuteScalar();
        EmpCount = Convert.ToInt32(o.ToString());
    }
    catch( OracleException OE )
    {
        Console.WriteLine( OE.Message );
    }
    finally
    {
        if( null != Cmd )
            Cmd.Dispose();
    }
}

```

```

    }
    return EmpCount;
  }
}

```

Unsupported SQL Commands

Transaction controls commands such as `COMMIT`, `ROLLBACK`, and `SAVEPOINT` are not supported in a .NET stored procedure.

Data definition commands such as `CREATE` and `ALTER` are not supported with an implicit database connection, but they are supported with an explicit user connection in a .NET stored procedure.

Oracle User-Defined Type (UDT) Support

UDTs are not supported within a context connection but they are supported with a client connection. UDTs are not supported as parameters to .NET stored procedures.

Porting Client Application to .NET Stored Procedure

All classes and class members provide the same functionality for both client applications and .NET stored procedures, unless it is otherwise stated.

Table 5–1 lists those classes or class members that have different behavior depending on whether or not they are used in a client application or in a .NET stored procedure.

Column Headings

The column headings for this table are:

Client application: The client application.

Implicit connection: The implicit database connections in a .NET stored procedure.

Explicit connection: The explicit user connections in a .NET stored procedure.

Table 5–1 API Support Comparison Between Client Application and .NET Stored Procedure

| Class or Class Members | Client Application | Implicit Connection/ Explicit Connection |
|---------------------------------------------------------------------|--------------------|---------------------------------------------|
| OnChangeEventHandler Delegate -all members | Yes | No/No |
| OracleDependency Class -all members | Yes | No/No |
| OracleNotificationEventArgs Class -all members | Yes | No/No |
| OracleNotificationRequest Class -all members | Yes | No/No |
| OracleFailoverEventArgs Class -all members | Yes | No/No |
| OracleFailoverEventHandler Delegate -all members | Yes | No/No |
| OracleTransaction Class -all members | Yes | No/No |

Table 5–1 (Cont.) API Support Comparison Between Client Application and .NET Stored Procedure

| Class or Class Members | Client Application | Implicit Connection/ Explicit Connection |
|---------------------------------------|---------------------------|-----------------------------------------------------|
| OracleCommand Class | | |
| -Transaction Property | Yes | No #1/No #1 |
| OracleConnection Class | | |
| -ConnectionTimeout Property | Yes | Yes #3/Yes |
| -DataSource Property | Yes | Yes #2/Yes |
| -BeginTransaction Method | Yes | No/Yes |
| -ChangeDatabase Method | No | No/No |
| -Clone Method | Yes | No/Yes |
| -EnlistDistributedTransaction Method | Yes | No/No |
| -OpenWithNewPassword Method | Yes | No/Yes |
| -Failover Event | Yes | No/No |
| -OracleFailoverEventHandler Delegate | Yes | No/No |
| ODP.NET Enumerations | | |
| -FailoverEvent Enumeration | Yes | No/No |
| -FailoverReturnCode Enumeration | Yes | No/No |
| -FailoverType Enumeration | Yes | No/No |
| -OracleNotificationInfo Enumeration | Yes | No/No |
| -OracleNotificationSource Enumeration | Yes | No/No |
| -OracleNotificationType Enumeration | Yes | No/No |

Comments on Items in Table 5–1

1. Always returns null.
2. Implicit database connection always returns an empty string.
3. Implicit database connection always returns 0.

Oracle Data Provider for .NET Classes

This chapter describes the following Oracle Data Provider for .NET classes.

- [OracleClientFactory Class](#)
- [OracleCommand Class](#)
- [OracleCommandBuilder Class](#)
- [OracleConnection Class](#)
- [OracleConnectionStringBuilder Class](#)
- [OracleDataAdapter Class](#)
- [OracleDatabase Class](#)
- [OracleDataReader Class](#)
- [OracleDataSourceEnumerator Class](#)
- [OracleError Class](#)
- [OracleErrorCollection Class](#)
- [OracleException Class](#)
- [OracleInfoMessageEventArgs Class](#)
- [OracleInfoMessageEventHandler Delegate](#)
- [OracleLogicalTransaction Class](#)
- [OracleLogicalTransactionStatus Class](#)
- [OracleParameter Class](#)
- [OracleParameterCollection Class](#)
- [OraclePermission Class](#)
- [OraclePermissionAttribute Class](#)
- [OracleRowUpdatedEventArgs Class](#)
- [OracleRowUpdatedEventHandler Delegate](#)
- [OracleRowUpdatingEventArgs Class](#)
- [OracleRowUpdatingEventHandler Delegate](#)
- [OracleTransaction Class](#)
- [OracleConnectionType Enumeration](#)
- [OracleCollectionType Enumeration](#)

-
- [OracleDBShutdownMode Enumeration](#)
 - [OracleDBStartupMode Enumeration](#)
 - [OracleDbType Enumeration](#)
 - [OracleIdentityType Enumeration](#)
 - [OracleParameterStatus Enumeration](#)

OracleClientFactory Class

An OracleClientFactory object allows applications to instantiate ODP.NET classes in a generic way.

Class Inheritance

System.Object

System.Data.Common.DbProviderFactory

Oracle.DataAccess.Client.OracleClientFactory

Declaration

```
// C#
public sealed class OracleClientFactory : DbProviderFactory
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#

using System;
using System.Data;
using System.Data.Common;
using Oracle.DataAccess.Client;

class FactorySample
{
    static void Main()
    {
        string constr = "user id=scott;password=tiger;data source=oracle";

        DbProviderFactory factory =
            DbProviderFactories.GetFactory("Oracle.DataAccess.Client");

        DbConnection conn = factory.CreateConnection();

        try
        {
            conn.ConnectionString = constr;
            conn.Open();

            DbCommand cmd = factory.CreateCommand();
            cmd.Connection = conn;
        }
    }
}
```

```
cmd.CommandText = "select * from emp";

DbDataReader reader = cmd.ExecuteReader();
while (reader.Read())
    Console.WriteLine(reader["EMPNO"] + " : " + reader["ENAME"]);
}
catch (Exception ex)
{
    Console.WriteLine(ex.Message);
    Console.WriteLine(ex.StackTrace);
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleClientFactory Members](#)
- [OracleClientFactory Constructor](#)
- [OracleClientFactory Public Properties](#)
- [OracleClientFactory Public Methods](#)

OracleClientFactory Members

OracleClientFactory members are listed in the following tables.

OracleClientFactory Constructor

The OracleClientFactory constructor is listed in [Table 6-1](#)

Table 6-1 OracleClientFactory Constructor

| Property | Description |
|-------------------------------------------------|----------------------------------------------------------|
| OracleClientFactory Constructor | Instantiates a new instance of OracleClientFactory class |

OracleClientFactory Public Properties

The OracleClientFactory public properties are listed in [Table 6-2](#).

Table 6-2 OracleClientFactory Public Properties

| Property | Description |
|-----------------------------------------------|-----------------------------------------------------------------------------|
| CanCreateDataSourceEnumerator | Indicates whether or not the CreateDataSourceEnumerator method is supported |

OracleClientFactory Public Methods

OracleClientFactory Public Methods are listed in [Table 6-3](#).

Table 6-3 OracleClientFactory Public Method

| Method | Description |
|-----------------------------------------------|----------------------------------------------------------------------------------------------------|
| CreateCommand | Returns a DbCommand object that represents an OracleCommand object |
| CreateCommandBuilder | Returns a DbCommandBuilder object that represents an OracleCommandBuilder object |
| CreateConnection | Returns a DbConnection object that represents an OracleConnection object |
| CreateConnectionStringBuilder | Returns a DbConnectionStringBuilder object that represents an OracleConnectionStringBuilder object |
| CreateDataAdapter | Returns a DbDataAdapter object that represents an OracleDataAdapter object |
| CreateDataSourceEnumerator | Returns a DbDataSourceEnumerator object that represents an OracleDataSourceEnumerator object |
| CreateParameter | Returns a DbParameter object that represents an OracleParameter object |
| CreatePermission | Returns a CodeAccessPermission object that represents an OraclePermission object |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleClientFactory Class](#)

OracleClientFactory Constructor

The `OracleClientFactory` constructor creates a new instances of the `OracleClientFactory` class.

Declaration

```
// C#  
public OracleClientFactory();
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

OracleClientFactory Public Properties

The OracleClientFactory public properties are listed in [Table 6–4](#).

Table 6–4 OracleClientFactory Public Properties

| Property | Description |
|-----------------------------------------------|---------------------------------------------------------------------------------------------|
| CanCreateDataSourceEnumerator | Indicates whether or not the CreateDataSourceEnumerator method is supported |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

CanCreateDataSourceEnumerator

This property indicates whether or not the [CreateDataSourceEnumerator](#) method is supported.

Declaration

```
// C#
public override bool CanCreateDataSourceEnumerator { get; }
```

Property Value

Returns true.

Remarks

ODP.NET supports the [OracleDataSourceEnumerator](#) object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

OracleClientFactory Public Methods

The `OracleClientFactory` public method is listed in [Table 6–5](#).

Table 6–5 OracleClientFactory Public Method

| Method | Description |
|-----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| CreateCommand | Returns a <code>DbCommand</code> object that represents an <code>OracleCommand</code> object |
| CreateCommandBuilder | Returns a <code>DbCommandBuilder</code> object that represents an <code>OracleCommandBuilder</code> object |
| CreateConnection | Returns a <code>DbConnection</code> object that represents an <code>OracleConnection</code> object |
| CreateConnectionStringBuilder | Returns a <code>DbConnectionStringBuilder</code> object that represents an <code>OracleConnectionStringBuilder</code> object |
| CreateDataAdapter | Returns a <code>DbDataAdapter</code> object that represents an <code>OracleDataAdapter</code> object |
| CreateDataSourceEnumerator | Returns a <code>DbDataSourceEnumerator</code> object that represents an <code>OracleDataSourceEnumerator</code> object |
| CreateParameter | Returns a <code>DbParameter</code> object that represents an <code>OracleParameter</code> object |
| CreatePermission | Returns a <code>CodeAccessPermission</code> object that represents an <code>OraclePermission</code> object |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

CreateCommand

This method returns a `DbCommand` object that represents an `OracleCommand` object.

Declaration

```
// C#
public override DbCommand CreateCommand();
```

Return Value

A `DbCommand` object that represents an `OracleCommand` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

CreateCommandBuilder

This method returns a `DbCommandBuilder` object that represents an `OracleCommandBuilder` object.

Declaration

```
// C#  
public override DbCommandBuilder CreateCommandBuilder();
```

Return Value

A `DbCommandBuilder` object that represents an `OracleCommandBuilder` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

CreateConnection

This method returns a `DbConnection` object that represents an `OracleConnection` object.

Declaration

```
// C#  
public override DbConnection CreateConnection();
```

Return Value

A `DbConnection` object that represents an `OracleConnection` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

CreateConnectionStringBuilder

This method returns a `DbConnectionStringBuilder` object that represents an `OracleConnectionStringBuilder` object.

Declaration

```
// C#  
public override DbConnectionStringBuilder CreateConnectionStringBuilder();
```

Return Value

A `DbConnectionStringBuilder` object that represents an `OracleConnectionStringBuilder` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

CreateDataAdapter

This method returns a `DbDataAdapter` object that represents an `OracleDataAdapter` object.

Declaration

```
// C#  
public override DbDataAdapter CreateDataAdapter();
```

Return Value

A `DbDataAdapter` object that represents an `OracleDataAdapter` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

CreateDataSourceEnumerator

This method returns a `DbDataSourceEnumerator` object that represents an `OracleDataSourceEnumerator` object.

Declaration

```
// C#  
public override DbDataSourceEnumerator CreateDataSourceEnumerator();
```

Return Value

A `DbDataSourceEnumerator` object that represents an `OracleDataSourceEnumerator` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)
- ["OracleDataSourceEnumerator Class"](#) on page 6-263

CreateParameter

This method returns a `DbParameter` object that represents an `OracleParameter` object.

Declaration

```
// C#  
public override DbParameter CreateParameter();
```

Return Value

A `DbParameter` object that represents an `OracleParameter` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

CreatePermission

This method returns a `CodeAccessPermission` object that represents an `OraclePermission` object.

Declaration

```
// C#  
public override System.Security.CodeAccessPermission CreatePermission(  
    System.Security.Permissions.PermissionState state);
```

Parameter

- *state*

A `PermissionState` object.

Return Value

A `CodeAccessPermission` object that represents an `OraclePermission` object.

Remarks

This method enables users, writing provider-independent code, to get a `CodeAccessPermission` instance that represents an `OraclePermission` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleClientFactory Class](#)
- [OracleClientFactory Members](#)

OracleCommand Class

An `OracleCommand` object represents a SQL command, a stored procedure, or a table name. The `OracleCommand` object is responsible for formulating the request and passing it to the database. If results are returned, `OracleCommand` is responsible for returning results as an `OracleDataReader`, a `.NET XmlReader`, a `.NET Stream`, a scalar value, or as output parameters.

Class Inheritance

`System.Object`

`System.MarshalByRefObject`

`System.ComponentModel.Component`

`System.Data.Common.DbCommand`

`Oracle.DataAccess.Client.OracleCommand`

Declaration

```
// C#
public sealed class OracleCommand : DbCommand, ICloneable
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------------------|----------------------------------------------|
| Assembly | <code>Oracle.DataAccess.dll</code> | <code>Oracle.ManagedDataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Client</code> | <code>Oracle.ManagedDataAccess.Client</code> |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

The execution of any transaction-related statements from an `OracleCommand` is not recommended because it is not reflected in the state of the `OracleTransaction` object represents the current local transaction, if one exists.

`ExecuteXmlReader`, `ExecuteStream`, and `ExecuteToStream` methods are only supported for XML operations.

`ExecuteReader` and `ExecuteScalar` methods are not supported for XML operations.

To minimize the number of open server cursors, `OracleCommand` objects should be explicitly disposed.

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;
```

```
class OracleCommandSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        string cmdQuery = "select ename, empno from emp";

        // Create the OracleCommand
        OracleCommand cmd = new OracleCommand(cmdQuery);

        cmd.Connection = con;
        cmd.CommandType = CommandType.Text;

        // Execute command, create OracleDataReader object
        OracleDataReader reader = cmd.ExecuteReader();

        while (reader.Read())
        {
            // output Employee Name and Number
            Console.WriteLine("Employee Name : " + reader.GetString(0) + " , " +
                "Employee Number : " + reader.GetDecimal(1));
        }

        // Clean up
        reader.Dispose();
        cmd.Dispose();
        con.Dispose();
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleCommand Members](#)
- [OracleCommand Constructors](#)
- [OracleCommand Static Methods](#)
- [OracleCommand Properties](#)
- [OracleCommand Public Methods](#)

OracleCommand Members

OracleCommand members are listed in the following tables.

OracleCommand Constructors

OracleCommand constructors are listed in [Table 6-6](#).

Table 6-6 OracleCommand Constructors

| Constructor | Description |
|--------------------------------------------|-----------------------------------------------------------------|
| OracleCommand Constructors | Instantiates a new instance of OracleCommand class (Overloaded) |

OracleCommand Static Methods

The OracleCommand static method is listed in [Table 6-7](#).

Table 6-7 OracleCommand Static Method

| Method | Description |
|------------------------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

OracleCommand Properties

OracleCommand properties are listed in [Table 6-8](#).

Table 6-8 OracleCommand Properties

| Property | Description |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| AddRowid | Adds the ROWID as part of the select list |
| AddToStatementCache | Causes executed statements to be cached, when the property is set to true and statement caching is enabled |
| ArrayBindCount | Specifies if the array binding feature is to be used and also specifies the maximum number of array elements to be bound in the Value property |
| ArrayBindRowsAffected | Returns the number of affected rows for each iteration while executing a DML using array binding |
| BindByName | Specifies the binding method in the collection |
| CommandText | Specifies the SQL statement or stored procedure to run against the Oracle database or the XML data used to store changes to the Oracle database |
| CommandTimeout | Specifies the number of seconds the command is allowed to execute before terminating the execution with an exception |
| CommandType | Specifies the command type that indicates how the CommandText property is to be interpreted |
| Connection | Specifies the OracleConnection object that is used to identify the connection to execute a command |
| Container | Inherited from System.ComponentModel.Component |
| DesignTimeVisible | Specifies whether or not the OracleCommand object is visible on designer controls. |
| FetchSize | Specifies the size of OracleDataReader's internal cache to store result set data |

Table 6–8 (Cont.) OracleCommand Properties

| Property | Description |
|----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ImplicitRefCursors | Specifies an array of <code>OracleRefCursors</code> mapped to an implicit resultset returned by the stored procedure. <i>Not available in the ODP.NET, Managed Driver</i> |
| InitialLOBFetchSize | Specifies the amount of data that the <code>OracleDataReader</code> initially fetches for LOB columns |
| InitialLONGFetchSize | Specifies the amount of data that the <code>OracleDataReader</code> initially fetches for LONG and LONG RAW columns |
| Notification | Indicates that there is a notification request for the command |
| NotificationAutoEnlist | Indicates whether or not to register for a continuous query notification with the database automatically when the command is executed |
| Parameters | Specifies the parameters for the SQL statement or stored procedure |
| RowSize | Specifies the amount of memory needed by the <code>OracleDataReader</code> internal cache to store one row of data |
| Site | Inherited from <code>System.ComponentModel.Component</code> |
| Transaction | Specifies the <code>OracleTransaction</code> object in which the <code>OracleCommand</code> executes <i>Not supported in a .NET stored procedure</i> |
| UpdatedRowSource | Specifies how query command results are applied to the row being updated <i>Not supported in a .NET stored procedure</i> |
| UseEdmMapping | Indicates whether or not the command object utilizes the Entity Data Model mapping configuration values |
| XmlCommandType | Specifies the type of XML operation on the <code>OracleCommand</code> <i>Not available in the ODP.NET, Managed Driver</i> |
| XmlQueryProperties | Specifies the properties that are used when an XML document is created from the result set of a SQL query statement <i>Not available in the ODP.NET, Managed Driver</i> |
| XmlSaveProperties | Specifies the properties that are used when an XML document is used to save changes to the database <i>Not available in the ODP.NET, Managed Driver</i> |

OracleCommand Public Methods

`OracleCommand` public methods are listed in [Table 6–9](#).

Table 6–9 OracleCommand Public Methods

| Public Method | Description |
|------------------------------|-------------------------------------------------------------------------------------|
| Cancel | Attempts to cancel a command that is currently executing on a particular connection |
| Clone | Creates a copy of <code>OracleCommand</code> object |
| CreateObjRef | Inherited from <code>System.MarshalByRefObject</code> |

Table 6–9 (Cont.) OracleCommand Public Methods

| Public Method | Description |
|----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CreateParameter | Creates a new instance of <code>OracleParameter</code> class |
| Dispose | Releases any resources or memory allocated by the object |
| <code>Equals</code> | Inherited from <code>System.Object</code> (Overloaded) |
| ExecuteNonQuery | Executes a SQL statement or a command using the <code>XmlCommandType</code> and <code>CommandText</code> properties and returns the number of rows affected |
| ExecuteReader | Executes a command (Overloaded) |
| ExecuteScalar | Returns the first column of the first row in the result set returned by the query |
| ExecuteStream | Executes a command using the <code>XmlCommandType</code> and <code>CommandText</code> properties and returns the results in a new <code>Stream</code> object |
| ExecuteToStream | Executes a command using the <code>XmlCommandType</code> and <code>CommandText</code> properties and appends the results as an XML document to the existing <code>Stream</code> |
| ExecuteXmlReader | Executes a command using the <code>XmlCommandType</code> and <code>CommandText</code> properties and returns the result as an XML document in a .NET <code>XmlTextReader</code> object |
| <code>GetHashCode</code> | Inherited from <code>System.Object</code> |
| <code>GetLifetimeService</code> | Inherited from <code>System.MarshalByRefObject</code> |
| <code>GetType</code> | Inherited from <code>System.Object</code> |
| <code>InitializeLifetimeService</code> | Inherited from <code>System.MarshalByRefObject</code> |
| <code>Prepare</code> | <i>This method is a no-op</i> |
| <code>ToString</code> | Inherited from <code>System.Object</code> |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)

OracleCommand Constructors

OracleCommand constructors instantiate new instances of OracleCommand class.

Overload List:

- [OracleCommand\(\)](#)
This constructor instantiates a new instance of OracleCommand class.
- [OracleCommand\(string\)](#)
This constructor instantiates a new instance of OracleCommand class using the supplied SQL command or stored procedure, and connection to the Oracle database.
- [OracleCommand\(string, OracleConnection\)](#)
This constructor instantiates a new instance of OracleCommand class using the supplied SQL command or stored procedure, and connection to the Oracle database.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)

OracleCommand()

This constructor instantiates a new instance of OracleCommand class.

Declaration

```
// C#  
public OracleCommand();
```

Remarks

Default constructor.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)

OracleCommand(string)

This constructor instantiates a new instance of OracleCommand class using the supplied SQL command or stored procedure, and connection to the Oracle database.

Declaration

```
// C#  
public OracleCommand(string cmdText);
```

Parameters

- *cmdText*

The SQL command or stored procedure to be executed.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)

OracleCommand(string, OracleConnection)

This constructor instantiates a new instance of `OracleCommand` class using the supplied SQL command or stored procedure, and connection to the Oracle database.

Declaration

```
// C#  
public OracleCommand(string cmdText, OracleConnection OracleConnection);
```

Parameters

- *cmdText*

The SQL command or stored procedure to be executed.

- *OracleConnection*

The connection to the Oracle database.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)

OracleCommand Static Methods

The OracleCommand static method is listed in [Table 6–10](#).

Table 6–10 OracleCommand Static Method

| Method | Description |
|--------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)

OracleCommand Properties

OracleCommand properties are listed in [Table 6–11](#).

Table 6–11 OracleCommand Properties

| Property | Description |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AddRowid | Adds the ROWID as part of the select list |
| AddToStatementCache | Causes executed statements to be cached, when the property is set to true and statement caching is enabled |
| ArrayBindCount | Specifies if the array binding feature is to be used and also specifies the maximum number of array elements to be bound in the Value property |
| ArrayBindRowsAffected | Returns the number of affected rows for each iteration while executing a DML using array binding |
| BindByName | Specifies the binding method in the collection |
| CommandText | Specifies the SQL statement or stored procedure to run against the Oracle database or the XML data used to store changes to the Oracle database |
| CommandTimeout | Specifies the number of seconds the command is allowed to execute before terminating the execution with an exception |
| CommandType | Specifies the command type that indicates how the CommandText property is to be interpreted |
| Connection | Specifies the OracleConnection object that is used to identify the connection to execute a command |
| Container | Inherited from System.ComponentModel.Component |
| DesignTimeVisible | Specifies whether or not the OracleCommand object is visible on designer controls. |
| FetchSize | Specifies the size of OracleDataReader's internal cache to store result set data |
| ImplicitRefCursors | Specifies an array of OracleRefCursors mapped to an implicit resultset returned by the stored procedure. <i>Not available in the ODP.NET, Managed Driver</i> |
| InitialLOBFetchSize | Specifies the amount of data that the OracleDataReader initially fetches for LOB columns |
| InitialLONGFetchSize | Specifies the amount that of data the OracleDataReader initially fetches for LONG and LONG RAW columns |
| Notification | Indicates that there is a notification request for the command |
| NotificationAutoEnlist | Indicates whether or not to register for a continuous query notification with the database automatically when the command is executed |
| Parameters | Specifies the parameters for the SQL statement or stored procedure |
| RowSize | Specifies the amount of memory needed by the OracleDataReader internal cache to store one row of data |
| Site | Inherited from System.ComponentModel.Component |

Table 6–11 (Cont.) OracleCommand Properties

| Property | Description |
|------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| Transaction | Specifies the <code>OracleTransaction</code> object in which the <code>OracleCommand</code> executes <i>Not supported in a .NET stored procedure</i> |
| UpdatedRowSource | Specifies how query command results are applied to the row being updated <i>Not supported in a .NET stored procedure</i> |
| UseEdmMapping | Indicates whether or not the command object utilizes the Entity Data Model mapping configuration values |
| XmlCommandType | Specifies the type of XML operation on the <code>OracleCommand</code> |
| XmlQueryProperties | Specifies the properties that are used when an XML document is created from the result set of a SQL query statement |
| XmlSaveProperties | Specifies the properties that are used when an XML document is used to save changes to the database |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)

AddRowid

This property adds the ROWID as part of the select list.

Declaration

```
// C#
public bool AddRowid {get; set;}
```

Property Value

bool

Remarks

Default is false.

This ROWID column is hidden and is not accessible by the application. To gain access to the ROWIDs of a table, the ROWID must explicitly be added to the select list without the use of this property.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["LOB Support"](#) on page 3-75 for further information on how this property used with LOBs

AddToStatementCache

This property causes executed statements to be cached when the property is set to true and statement caching is enabled. If statement caching is disabled or if this property is set to false, the executed statement is not cached.

Declaration

```
// C#  
public bool AddToStatementCache{get; set;}
```

Return Value

Returns bool value. A value of true indicates that statements are being added to the cache, false indicates otherwise.

Property Value

A bool value that indicates that the statements will be cached when they are executed, if statement caching is enabled.

Remarks

Default is true.

AddToStatementCache is ignored if statement caching is disabled. Statement caching is enabled by setting the Statement Cache Size connection string attribute to a value greater than 0.

When statement caching is enabled, however, this property provides a way to selectively add statements to the cache.

Example

```
// C#  
  
using System;  
using System.Data;  
using Oracle.DataAccess.Client;  
  
class AddToStatementCacheSample  
{  
    static void Main()  
    {  
        string constr = "User Id=scott;Password=tiger;Data Source=oracle;" +  
            "statement cache size=10";  
        OracleConnection con = new OracleConnection(constr);  
        con.Open();  
  
        OracleCommand cmd = new OracleCommand("select * from emp", con);  
  
        if (cmd.AddToStatementCache)  
            Console.WriteLine("Added to the statement cache:" + cmd.CommandText);  
        else  
            Console.WriteLine("Not added to the statement cache:" + cmd.CommandText);  
  
        // The execution of "select * from emp" will be added to the statement cache  
        // because statement cache size is greater than 0 and OracleCommand's  
        // AddToStatementCache is true by default.  
        OracleDataReader readerEmp = cmd.ExecuteReader();  
  
        // Do not add "select * from dept" to the statement cache
```

```

cmd.CommandText = "select * from dept";
cmd.AddToStatementCache = false;

if (cmd.AddToStatementCache)
    Console.WriteLine("Added to the statement cache:" + cmd.CommandText);
else
    Console.WriteLine("Not added to the statement cache:" + cmd.CommandText);

// The execution of "select * from dept" will not be added to the
// statement cache because AddToStatementCache is set to false.
OracleDataReader readerDept = cmd.ExecuteReader();

// Clean up
con.Dispose();
}
}

```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["Statement Caching"](#) on page 3-48
- [ConnectionString](#) on page 6-94

ArrayBindCount

This property specifies if the array binding feature is to be used and also specifies the number of array elements to be bound in the `OracleParameter.Value` property.

Declaration

```

// C#
public int ArrayBindCount {get; set;}

```

Property Value

An int value that specifies number of array elements to be bound in the `OracleParameter.Value` property.

Exceptions

`ArgumentException` - The `ArrayBindCount` value specified is invalid.

Remarks

Default = 0.

If `ArrayBindCount` is equal to 0, array binding is not used; otherwise, array binding is used and `OracleParameter.Value` property is interpreted as an array of values. The value of `ArrayBindCount` must be specified to use the array binding feature.

If neither `DbType` nor `OracleDbType` is set, it is strongly recommended that you set `ArrayBindCount` before setting the `OracleParameter.Value` property so that inference of `DbType` and `OracleDbType` from `Value` can be correctly done.

Array binding is not used by default.

If the `XmlCommandType` property is set to any value other than `None`, this property is ignored.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["Array Binding"](#) on page 3-45
- ["Value"](#) on page 6-342

ArrayBindRowsAffected

This property returns the number of affected rows for each iteration while executing a DML using array binding.

Declaration

```
// C#  
public long[] ArrayBindRowsAffected ;
```

Property Value

A long type

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["Array Binding"](#) on page 3-45
- ["Value"](#) on page 6-342

BindByName

This property specifies the binding method in the collection.

Declaration

```
// C#  
public bool BindByName {get; set;}
```

Property Value

Returns `true` if the parameters are bound by name; returns `false` if the parameters are bound by position.

Remarks

Default = `false`.

`BindByName` is ignored under the following conditions:

- The value of the `XmlCommandType` property is `Insert`, `Update`, or `Delete`.
- The value of the `XmlCommandType` property is `Query`, but there are no parameters set on the `OracleCommand`.

If the `XmlCommandType` property is `OracleXmlCommandType.Query` and any parameters are set on the `OracleCommand`, the `BindByName` property must be set to `true`. Otherwise, the following `OracleCommand` methods throw an `InvalidOperationException`.

- `ExecuteNonQuery`
- `ExecuteXmlReader`
- `ExecuteStream`
- `ExecuteToStream`

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["Array Binding"](#) on page 3-45
- ["Value"](#) on page 6-342

CommandText

This property specifies the SQL statement or stored procedure to run against the Oracle database or the XML data used to store changes to the Oracle database.

Declaration

```
// C#
public override string CommandText {get; set;}
```

Property Value

A string.

Implements

`IDbCommand`

Remarks

The default is an empty string.

When the `CommandType` property is set to `StoredProcedure`, the `CommandText` property is set to the name of the stored procedure. The command calls this stored procedure when an `Execute` method is called.

The effects of `XmlCommandType` values on `CommandText` are:

- `XmlCommandType = None`.
`CommandType` property determines the contents of `CommandText`.
- `XmlCommandType = Query`.
`CommandText` must be a SQL query. The SQL query should be a select statement. `CommandType` property is ignored.
- `XmlCommandType` property is `Insert`, `Update`, or `Delete`.
`CommandText` must be an XML document. `CommandType` property is ignored.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)

CommandTimeout

This property specifies the minimum number of seconds that the command is allowed to execute before terminating with an exception.

Declaration

```
// C#  
public override int CommandTimeout {get; set;}
```

Property Value

int

Implements

IDbCommand.CommandTimeout

Exceptions

InvalidArgument - The specified value is less than 0.

Remarks

Default is 0 seconds, which enforces no time limit.

When the specified timeout value expires before a command execution finishes, the command attempts to cancel. If cancellation is successful, an exception is thrown with the message of ORA-01013: user requested cancel of current operation. Other possible exceptions thrown after a command timeout expiration occurs include ORA-00936 and ORA-00604. If the command executed in time without any errors, no exceptions are thrown.

In a situation where multiple OracleCommand objects use the same connection, the timeout expiration on one of the OracleCommand objects may terminate any of the executions on the single connection. To make the timeout expiration of a OracleCommand cancel only its own command execution, simply use one OracleCommand for each connection if that OracleCommand sets the CommandTimeout property to a value greater than 0.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- <http://msdn.microsoft.com/library> for detailed information about this Microsoft .NET Framework 1.1 feature

CommandType

This property specifies the command type that indicates how the `CommandText` property is to be interpreted.

Declaration

```
// C#  
public override CommandType CommandType {get; set;}
```

Property Value

A `CommandType`.

Exceptions

`ArgumentException` - The value is not a valid `CommandType` such as: `CommandType.Text`, `CommandType.StoredProcedure`, `CommandType.TableDirect`.

Remarks

Default = `CommandType.Text`

If the value of the `XmlCommandType` property is not `None`, then the `CommandType` property is ignored.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)

Connection

This property specifies the `OracleConnection` object that is used to identify the connection to execute a command.

Declaration

```
// C#  
public OracleConnection Connection {get; set;}
```

Property Value

An `OracleConnection` object.

Implements

`IDbCommand`

Remarks

Default = `null`

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)

DesignTimeVisible

This property specifies whether or not the `OracleCommand` object is visible on designer controls.

Declaration

```
// C#  
public override bool DesignTimeVisible { get; set; }
```

Property Value

A value that indicate whether or not `OracleCommand` object is visible in a control. The default is `true`.

Remarks

This property is used by developers to indicate whether or not `OracleCommand` object is visible in a control.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)

FetchSize

This property specifies the size of `OracleDataReader`'s internal cache to store result set data.

Declaration

```
// C#  
public long FetchSize {get; set;}
```

Property Value

A `long` that specifies the size (in bytes) of the `OracleDataReader`'s internal cache.

Exceptions

`ArgumentException` - The `FetchSize` value specified is invalid.

Remarks

Default = 131072.

The `FetchSize` property is inherited by the `OracleDataReader` that is created by a command execution returning a result set. The `FetchSize` property on the `OracleDataReader` object determines the amount of data the `OracleDataReader` fetches into its internal cache for each database round-trip.

If the `XmlCommandType` property is set to any value other than `None`, this property is ignored.

The `RowSize` and `FetchSize` properties handle UDT and `XMLType` data differently than other scalar data types. Because only a reference to the UDT and `XMLType` data is stored in the ODP.NET's internal cache, the `RowSize` property accounts for only the memory needed for the reference (which is very small) and not the actual size of the UDT and

`XMLType` data. Thus, applications can inadvertently fetch a large number of UDT or `XMLType` instances from the database in a single database round-trip. This is because the actual size of UDT and `XMLType` data do not count against the `FetchSize`, and it would require numerous UDT and `XMLType` references to fill up the default cache size of 131072 bytes. Therefore, when fetching UDT or `XMLType` data, the `FetchSize` property must be appropriately configured to control the number of UDT and `XMLType` instances that are to be fetched, rather than the amount of the actual UDT and `XMLType` data to be fetched.

NOTE: For LOB and `LONG` data types, only the sizes specified in the `InitialLOBFetchSize` and `InitialLONGFetchSize` properties are accounted for by the `RowSize` property in addition to the metadata and reference information that is maintained by the cache for each LOB in the select list.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- `OracleDataReader` ["FetchSize"](#) on page 6-206

ImplicitRefCursors

This property returns an array of `OracleRefCursors`, where each `OracleRefCursor` maps to an implicit resultset returned by the stored procedure.

Declaration

```
// C#
public OracleRefCursor[] ImplicitRefCursors {get; set;}
```

Property Value

An array of `OracleRefCursors`.

Remarks

This property is populated only when the stored procedure is executed through `ExecuteNonQuery` and it does not get populated in any other scenarios.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)

InitialLOBFetchSize

This property specifies the amount of data that the `OracleDataReader` initially fetches for LOB columns.

Declaration

```
// C#
public int InitialLOBFetchSize {get; set;}
```

Property Value

An int specifying the number of characters or bytes to fetch initially.

Exceptions

ArgumentException - The InitialLOBFetchSize value specified is invalid.

Remarks

The value of InitialLOBFetchSize specifies the initial amount of LOB data that is immediately fetched by the OracleDataReader. The property value specifies the number of characters for CLOB and NCLOB data, and the number of bytes for BLOB data.

The InitialLOBFetchSize value is used to determine the length of the LOB column data to fetch, if the LOB column is in the select list. If the select list does not contain a LOB column, the InitialLOBFetchSize value is ignored.

When InitialLOBFetchSize is set to -1, the entire LOB data is prefetched and stored in the fetch array.

Default = 0.

The maximum value supported for InitialLOBFetchSize is 2 GB.

GetOracleBlob and GetOracleClob methods can be used to retrieve any LOBs no matter the InitialLOBFetchSize value.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["Obtaining LOB Data"](#) on page 3-58 for more information on setting InitialLOBFetchSize values

InitialLONGFetchSize

This property specifies the amount of data that the OracleDataReader initially fetches for LONG and LONG RAW columns.

Declaration

```
// C#  
public int InitialLONGFetchSize {get; set;}
```

Property Value

An int specifying the amount.

Exceptions

ArgumentException - The InitialLONGFetchSize value specified is invalid.

Remarks

The maximum value supported for InitialLONGFetchSize is 32767. If this property is set to a higher value, the provider resets it to 32767.

The value of InitialLONGFetchSize specifies the initial amount of LONG or LONG RAW data that is immediately fetched by the OracleDataReader. The property value specifies the number of characters for LONG data and the number of bytes for LONG RAW.

To fetch more than the specified `InitialLONGFetchSize` amount, one of the following must be in the select list:

- Primary key
- ROWID
- Unique columns - (defined as a set of columns on which a unique constraint has been defined or a unique index has been created, where at least one of the columns in the set has a NOT NULL constraint defined on it)

The `InitialLONGFetchSize` value is used to determine the length of the LONG and LONG RAW column data to fetch if one of the two is in the select list. If the select list does not contain a LONG or a LONG RAW column, the `InitialLONGFetchSize` value is ignored.

When `InitialLONGFetchSize` is set to -1, the entire LONG or LONG RAW data is prefetched and stored in the fetch array. Calls to `GetString`, `GetChars`, or `GetBytes` in `OracleDataReader` allow retrieving the entire data.

Default = 0.

Setting this property to 0 defers the LONG and LONG RAW data retrieval entirely until the application specifically requests it.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["Obtaining LONG and LONG RAW Data"](#) on page 3-57 for further information

Notification

This instance property indicates that there is a notification request for the command.

Declaration

```
// C#
public OracleNotificationRequest Notification {set; get;}
```

Property Value

A notification request for the command.

Remarks

When a changed notification is first registered, the client listener is started in order to receive any database notification. The listener uses the port number defined in the `OracleDependency.Port` static field. Subsequent change notification registrations use the same listener in the same client process and do not start another listener.

When `Notification` is set to an `OracleNotificationRequest` instance, a notification registration is created (if it has not already been created) when the command is executed. Once the registration is created, the properties of the `OracleNotificationRequest` instance cannot be modified. If the notification registration has already been created, the result set that is associated with the command is added to the existing registration.

When `Notification` is set to `null`, subsequent command executions do not require a notification request. If a notification request is not required, set the `Notification` property to `null`, or set the `NotificationAutoEnlist` property to `false`.

For Continuous Query Notification, a notification request can be used for multiple command executions. In that case, any query result set associated with different commands can be invalidated within the same registration.

When the `OracleDependency.OnChange` event is fired, if the `ROWID` column is explicitly included in the query (or `AddRowid` property is set to `true`), then the `Rowid` column contains `ROWID` values in the `DataTable` referenced by the `OracleNotificationEventArgs.Details` property. This behavior can be overridden by explicitly requesting for an inclusion and exclusion of `ROWID` values in the `OracleNotificationEventArgs` by setting the `OracleDependency.RowidInfo` to `OracleRowidInfo.Include` or `OracleRowidInfo.Exclude`, respectively.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["Continuous Query Notification Support"](#) on page 3-112
- [Chapter 9, "Continuous Query Notification Classes"](#) on page 9-1

NotificationAutoEnlist

This instance property indicates whether or not to register for a continuous query notification with the database automatically when the command is executed.

Declaration

```
// C#  
public bool NotificationAutoEnlist {set; get;}
```

Property Value

A `bool` value indicating whether or not to make a continuous query notification request automatically, when the command is executed. If `NotificationAutoEnlist` is set to `true`, and the `Notification` property is set appropriately, a continuous query notification request is registered automatically; otherwise, no continuous query notification registration is made.

Default value: `true`

Remarks

A notification request can be used for multiple command executions using the same `OracleCommand` instance. In that case, set the `NotificationAutoEnlist` property to `true`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["Continuous Query Notification Support"](#) on page 3-112
- [Chapter 9, "Continuous Query Notification Classes"](#) on page 9-1

Parameters

This property specifies the parameters for the SQL statement or stored procedure.

Declaration

```
// C#
public OracleParameterCollection Parameters {get;}
```

Property Value

OracleParameterCollection

Implements

IDbCommand

Remarks

Default value = an empty collection

The number of the parameters in the collection must be equal to the number of parameter placeholders within the command text, or an error is raised.

If the command text does not contain any parameter tokens (such as ,:1,:2), the values in the Parameters property are ignored.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)

RowSize

This property specifies the amount of memory needed by the OracleDataReader internal cache to store one row of data.

Declaration

```
// C#
public long RowSize {get;}
```

Property Value

A long that indicates the amount of memory (in bytes) that an OracleDataReader needs to store one row of data for the executed query.

Remarks

Default value = 0

The `RowSize` property is set to a nonzero value after the execution of a command that returns a result set. This property can be used at design time or dynamically during runtime, to set the `FetchSize`, based on number of rows. For example, to enable the `OracleDataReader` to fetch `N` rows for each database round-trip, the `OracleDataReader` `FetchSize` property can be set dynamically to `RowSize * N`. Note that for the `FetchSize` to take effect appropriately, it must be set after `OracleCommand.ExecuteReader()` but before `OracleDataReader.Read()`.

ODP.NET now supports values up to 32K for `VARCHAR2`, `NVARCHAR2` or `RAW` type columns in its calculation of `RowSize` value.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- `OracleDataReader` ["FetchSize"](#) on page 6-28

Transaction

This property specifies the `OracleTransaction` object in which the `OracleCommand` executes.

Declaration

```
// C#  
public OracleTransaction Transaction {set; get;}
```

Property Value

`OracleTransaction`

Implements

`IDbCommand`

Remarks

Default value = null

`Transaction` returns a reference to the transaction object associated with the `OracleCommand` connection object. Thus the command is executed in whatever transaction context its connection is currently in.

Note: When this property is accessed through an `IDbCommand` reference, its set accessor method is not operational.

Remarks (.NET Stored Procedure)

Always returns null.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)

UpdatedRowSource

This property specifies how query command results are applied to the row to be updated.

Declaration

```
// C#  
public override UpdateRowSource UpdatedRowSource {get; set;}
```

Property Value

An UpdateRowSource.

Implements

IDbCommand

Exceptions

ArgumentException - The UpdateRowSource value specified is invalid.

Remarks

Always returns UpdateRowSource,

Set accessor throws an ArgumentException if the value is other than UpdateRowSource.None.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)

UseEdmMapping

This property Indicates whether or not the OracleCommand object utilizes the Entity Data Model mapping configuration values.

Declaration

```
// C#  
public bool UseEdmMapping
```

Property Value

A bool.

Remarks

Default is false.

The `UseEdmMapping` property allows user to explicitly specify that the `OracleCommand` object should use the Entity Data Model mapping configuration values. This enables use of Entity Framework Multiple Result Sets feature.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)

XmlCommandType

This property specifies the type of XML operation on the `OracleCommand`.

Declaration

```
// C#  
public OracleXmlCommandType XmlCommandType {get; set;}
```

Property Value

An `OracleXmlCommandType`.

Remarks

Default value is `None`.

`XmlCommandType` values and usage:

- `None` - The `CommandType` property specifies the type of operation.
- `Query` - `CommandText` property must be set to a SQL select statement. The query is executed, and the results are returned as an XML document. The SQL select statement in the `CommandText` and the properties specified by the `XmlQueryProperties` property are used to perform the operation. The `CommandType` property is ignored.
- `Insert, Update, or Delete` - `CommandText` property is an XML document containing the changes to be made. The XML document in the `CommandText` and the properties specified by the `XmlSaveProperties` property are used to perform the operation. The `CommandType` property is ignored.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)

XmlQueryProperties

This property specifies the properties that are used when an XML document is created from the result set of a SQL query statement.

Declaration

```
// C#  
public OracleXmlQueryProperties XmlQueryProperties {get; set;}
```

Property Value

OracleXmlQueryProperties.

Remarks

When a new instance of OracleCommand is created, an instance of OracleXmlQueryProperties is automatically available on the OracleCommand instance through the OracleCommand.XmlQueryProperties property.

A new instance of OracleXmlQueryProperties can be assigned to an OracleCommand instance. Assigning an instance of OracleXmlQueryProperties to the XmlQueryProperties of an OracleCommand instance creates a new instance of the given OracleXmlQueryProperties instance for the OracleCommand. This way each OracleCommand instance has its own OracleXmlQueryProperties instance.

Use the default constructor to get a new instance of OracleXmlQueryProperties.

Use the OracleXmlQueryProperties.Clone() method to get a copy of an OracleXmlQueryProperties instance.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)

XmlSaveProperties

This property specifies the properties that are used when an XML document is used to save changes to the database.

Declaration

```
// C#
public OracleXmlSaveProperties XmlSaveProperties {get; set;}
```

Property Value

OracleXmlSaveProperties.

Remarks

When a new instance of OracleCommand is created, an instance of OracleXmlSaveProperties is automatically available on the OracleCommand instance through the OracleCommand.XmlSaveProperties property.

A new instance of OracleXmlSaveProperties can be assigned to an OracleCommand instance. Assigning an instance of OracleXmlSaveProperties to the XmlSaveProperties of an OracleCommand instance creates a new instance of the given OracleXmlSaveProperties instance for the OracleCommand. This way each OracleCommand instance has its own OracleXmlSaveProperties instance.

Use the default constructor to get a new instance of OracleXmlSaveProperties.

Use the OracleXmlSaveProperties.Clone() method to get a copy of an OracleXmlSaveProperties instance.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)

OracleCommand Public Methods

OracleCommand public methods are listed in [Table 6–12](#).

Table 6–12 OracleCommand Public Methods

| Public Method | Description |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Cancel | Attempts to cancel a command that is currently executing on a particular connection |
| Clone | Creates a copy of OracleCommand object |
| CreateObjRef | Inherited from System.MarshalByRefObject |
| CreateParameter | Creates a new instance of OracleParameter class |
| Dispose | Releases any resources or memory allocated by the object |
| Equals | Inherited from System.Object (Overloaded) |
| ExecuteNonQuery | Executes a SQL statement or a command using the XmlCommandType and CommandText properties and returns the number of rows affected |
| ExecuteReader | Executes a command (Overloaded) |
| ExecuteScalar | Returns the first column of the first row in the result set returned by the query |
| ExecuteStream | Executes a command using the XmlCommandType and CommandText properties and returns the results in a new Stream object |
| ExecuteToStream | Executes a command using the XmlCommandType and CommandText properties and appends the results as an XML document to the existing Stream |
| ExecuteXmlReader | Executes a command using the XmlCommandType and CommandText properties and returns the result as an XML document in a .NET XmlTextReader object |
| GetHashCode | Inherited from System.Object |
| GetLifetimeService | Inherited from System.MarshalByRefObject |
| GetType | Inherited from System.Object |
| InitializeLifetimeService | Inherited from System.MarshalByRefObject |
| Prepare | <i>This method is a no-op</i> |
| ToString | Inherited from System.Object |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)

Cancel

This method attempts to cancel a command that is currently executing on a particular connection.

Declaration

```
// C#  
public override void Cancel();
```

Implements

```
IDbCommand.Cancel
```

Remarks

If cancellation of the command succeeds, an exception is thrown. If cancellation is not successful, no exception is thrown. If there is no command being executed at the time of the `Cancel` invocation, `Cancel` does nothing. Invoking the `Cancel` method does not guarantee that the command executing at the time will always be cancelled. The execution may complete before it can be terminated. In such cases, no exception is thrown.

When multiple `OracleCommand` objects share the same connection, only one command can be executed on that connection at any one time. When it is invoked, the `Cancel` method attempts to cancel the statement currently running on the connection that the `OracleCommand` object is using to execute the command. However, when multiple `OracleCommand` objects execute statements on the same connection simultaneously, issuing a `Cancel` method invocation may cancel any of the issued commands. This is because the command designated for cancellation may complete before the `Cancel` invocation is effective. If this happens, a command executed by a different `OracleCommand` could be cancelled instead.

There are several ways to avoid this non-deterministic situation that the `Cancel` method can cause:

- The application can create just one `OracleCommand` object for each connection. Doing so assures that the `Cancel` invocation only cancels commands executed by the `OracleCommand` object using a particular connection.
- Command executions in the application are synchronized between `OracleCommand` objects that use the same connection.

These suggestions do not apply if `Cancel` is not used in the application.

Because the termination on the currently running execution is non-deterministic, it is recommended that any *non-atomic* SQL or PL/SQL execution be started within a transaction. When the command execution successfully terminates with an exception of `ORA-01013: user requested cancel of current operation`, the transaction can be rolled back for data integrity. Other possible exceptions thrown after a command cancellation occurs include `ORA-00936` and `ORA-00604`. Examples of non-atomic execution are collections of DML command executions that are executed one-by-one and multiple DML commands that are part of a PL/SQL stored procedure or function.

Example

```
// C#  
  
// This example shows how command executions can be cancelled in a  
// deterministic way even if multiple commands are executed on a single  
// connection. This is accomplished by synchronizing threads through events.  
// Since the Cancel method terminates the currently running operation on the  
// connection, threads must be serialized if multiple threads are using the  
// same connection to execute server round-trip incurring operations.  
// Furthermore, the example shows how the execution and cancel threads should  
// be synchronized so that nth iteration of the command execution does not  
// inappropriately cancel the (n+1)th command executed by the same thread.
```



```
using System;
using System.Data;
using Oracle.DataAccess.Client;
using System.Threading;

class CancelSample
{
    private OracleCommand cmd;
    Thread t1, t2;
    // threads signal following events when assigned operations are completed

    private AutoResetEvent ExecuteEvent = new AutoResetEvent(false);
    private AutoResetEvent CancelEvent = new AutoResetEvent(false);
    private AutoResetEvent FinishedEvent = new AutoResetEvent(false);
    AutoResetEvent[] ExecuteAndCancel = new AutoResetEvent[2];

    // Default constructor
    CancelSample()
    {
        cmd = new OracleCommand("select * from all_objects",
            new OracleConnection("user id=scott;password=tiger;data source=oracle"));
        ExecuteAndCancel[0] = ExecuteEvent;
        ExecuteAndCancel[1] = CancelEvent;
    }

    // Constructor that takes a particular command and connection
    CancelSample(string command, OracleConnection con)
    {
        cmd = new OracleCommand(command, con);
        ExecuteAndCancel[0] = ExecuteEvent;
        ExecuteAndCancel[1] = CancelEvent;
    }

    // Execution of the command
    public void Execute()
    {
        OracleDataReader reader = null;
        try
        {
            Console.WriteLine("Execute.");
            reader = cmd.ExecuteReader();
            Console.WriteLine("Execute Done.");
            reader.Close();
        }
        catch(Exception e)
        {
            Console.WriteLine("The command has been cancelled.", e.Message);
        }
        Console.WriteLine("ExecuteEvent.Set()");
        ExecuteEvent.Set();
    }

    // Canceling of the command
    public void Cancel()
    {
        try
        {
            // cancel query if it takes longer than 100 ms to finish execution
            System.Threading.Thread.Sleep(100);
        }
    }
}
```

```
        Console.WriteLine("Cancel.");
        cmd.Cancel();
    }
    catch (Exception e)
    {
        Console.WriteLine(e.ToString());
    }
    Console.WriteLine("Cancel done.");
    Console.WriteLine("CancelEvent.Set()");
    CancelEvent.Set();
}

// Execution of the command with a potential of cancelling
public void ExecuteWithinLimitedTime()
{
    for (int i = 0; i < 5; i++)
    {
        Monitor.Enter(typeof(CancelSample));
        try
        {
            Console.WriteLine("Executing " + this.cmd.CommandText);
            ExecuteEvent.Reset();
            CancelEvent.Reset();
            t1 = new Thread(new ThreadStart(this.Execute));
            t2 = new Thread(new ThreadStart(this.Cancel));
            t1.Start();
            t2.Start();
        }
        finally
        {
            WaitHandle.WaitAll(ExecuteAndCancel);
            Monitor.Exit(typeof(CancelSample));
        }
    }
    FinishedEvent.Set();
}

[MTAThread]
static void Main()
{
    try
    {
        AutoResetEvent[] ExecutionCompleteEvents = new AutoResetEvent[3];

        // Create the connection that is to be used by three commands
        OracleConnection con = new OracleConnection("user id=scott;" +
            "password=tiger;data source=oracle");
        con.Open();

        // Create instances of CancelSample class
        CancelSample test1 = new CancelSample("select * from all_objects", con);
        CancelSample test2 = new CancelSample("select * from all_objects, emp",
            con);
        CancelSample test3 = new CancelSample("select * from all_objects, dept",
            con);

        // Create threads for each CancelSample object instance
        Thread t1 = new Thread(new ThreadStart(test1.ExecuteWithinLimitedTime));
        Thread t2 = new Thread(new ThreadStart(test2.ExecuteWithinLimitedTime));
        Thread t3 = new Thread(new ThreadStart(test3.ExecuteWithinLimitedTime));
    }
}
```

```

// Obtain a handle to an event from each object
ExecutionCompleteEvents[0] = test1.FinishedEvent;
ExecutionCompleteEvents[1] = test2.FinishedEvent;
ExecutionCompleteEvents[2] = test3.FinishedEvent;

// Start all threads to execute three commands using a single connection
t1.Start();
t2.Start();
t3.Start();

// Wait for all three commands to finish executing/canceling before
//closing the connection
WaitHandle.WaitAll(ExecutionCompleteEvents);
con.Close();
}
catch (Exception e)
{
    Console.WriteLine(e.ToString());
}
}
}

```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- <http://msdn.microsoft.com/library> for detailed information about this Microsoft .NET Framework 1.1 feature

Clone

This method creates a copy of an OracleCommand object.

Declaration

```

// C#
public object Clone();

```

Return Value

An OracleCommand object.

Implements

ICloneable

Remarks

The cloned object has the same property values as that of the object being cloned.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)

CreateParameter

This method creates a new instance of `OracleParameter` class.

Declaration

```
// C#  
public OracleParameter CreateParameter();
```

Return Value

A new `OracleParameter` with default values.

Implements

`IDbCommand`

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)

Dispose

This method releases any resources or memory allocated by the object.

Declaration

```
// C#  
public void Dispose();
```

Implements

`IDisposable`

Remarks

The `Dispose` method also closes the `OracleCommand` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)

ExecuteNonQuery

This method executes a SQL statement or a command using the `XmlCommandType` and `CommandText` properties and returns the number of rows affected.

Declaration

```
// C#  
public override int ExecuteNonQuery();
```

Return Value

The number of rows affected.

Implements

IDbCommand

Exceptions

InvalidOperationException - The command cannot be executed.

Remarks

ExecuteNonQuery returns the number of rows affected, for the following:

- If the command is UPDATE, INSERT, or DELETE and the XmlCommandType property is set to OracleXmlCommandType.None.
- If the XmlCommandType property is set to OracleXmlCommandType.Insert, OracleXmlCommandType.Update, OracleXmlCommandType.Delete.

For all other types of statements, the return value is -1.

ExecuteNonQuery is used for either of the following:

- Catalog operations (for example, querying the structure of a database or creating database objects such as tables).
- Changing the data in a database without using a DataSet, by executing UPDATE, INSERT, or DELETE statements.
- Changing the data in a database using an XML document.

Although ExecuteNonQuery does not return any rows, it populates any output parameters or return values mapped to parameters with data.

If the XmlCommandType property is set to OracleXmlCommandType.Query then ExecuteNonQuery executes the select statement in the CommandText property, and if successful, returns -1. The XML document that is generated is discarded. This is useful for determining if the operation completes successfully without getting the XML document back as a result.

If the XmlCommandType property is set to OracleXmlCommandType.Insert, OracleXmlCommandType.Update, or OracleXmlCommandType.Delete, then the value of the CommandText property is an XML document. ExecuteNonQuery saves the changes in that XML document to the table or view that is specified in the XmlSaveProperties property. The return value is the number of rows that are processed in the XML document. Also, each row in the XML document could affect multiple rows in the database, but the return value is still the number of rows in the XML document.

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class ExecuteNonQuerySample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleCommand cmd = new OracleCommand(
```

```
        "select sal from emp where empno=7934", con);

object sal = cmd.ExecuteScalar();
Console.WriteLine("Employee sal before update: " + sal);

cmd.CommandText = "update emp set sal = sal + .01 where empno=7934";

// Auto-commit changes
int rowsUpdated = cmd.ExecuteNonQuery();

if (rowsUpdated > 0)
{
    cmd.CommandText = "select sal from emp where empno=7934";
    sal = cmd.ExecuteScalar();
    Console.WriteLine("Employee sal after update: " + sal);
}

// Clean up
cmd.Dispose();
con.Dispose();
}
}
```

Requirements

For XML support, this method requires Oracle9i XML Developer's Kits (Oracle XDK) or later, to be installed in the database. Oracle XDK can be downloaded from Oracle Technology Network (OTN).

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- <http://otn.oracle.com/>

ExecuteReader

Overload List:

ExecuteReader executes a command specified in the CommandText.

- [ExecuteReader\(\)](#)

This method executes a command specified in the CommandText and returns an OracleDataReader object.

- [ExecuteReader\(CommandBehavior\)](#)

This method executes a command specified in the CommandText and returns an OracleDataReader object, using the specified CommandBehavior value.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)

ExecuteReader()

This method executes a command specified in the `CommandText` and returns an `OracleDataReader` object.

Declaration

```
// C#
public OracleDataReader ExecuteReader();
```

Return Value

An `OracleDataReader`.

Implements

`IDbCommand`

Exceptions

`InvalidOperationException` - The command cannot be executed.

Remarks

When the `CommandType` property is set to `CommandType.StoredProcedure`, the `CommandText` property should be set to the name of the stored procedure.

The specified command executes this stored procedure when `ExecuteReader` is called. If parameters for the stored procedure consist of `REF CURSOR` objects, behavior differs depending on whether `ExecuteReader()` or `ExecuteNonQuery()` is called. If `ExecuteReader()` is invoked, `REF CURSOR` objects can be accessed through the `OracleDataReader` that is returned.

If more than one `REF CURSOR` is returned from a single execution, subsequent `REF CURSOR` objects can be accessed sequentially by the `NextResult` method on the `OracleDataReader`. If the `ExecuteNonQuery` method is invoked, the output parameter value can be cast to a `OracleRefCursor` type and the `OracleRefCursor` object then can be used to either populate a `DataSet` or create an `OracleDataReader` object from it. This approach provides random access to all the `REF CURSOR` objects returned as output parameters.

The value of 100 is used for the `FetchSize`. If 0 is specified, no rows are fetched. For further information, see ["Obtaining LONG and LONG RAW Data"](#) on page 3-57.

If the value of the `XmlCommandType` property is set to `OracleXmlCommandType.Insert`, `OracleXmlCommandType.Update`, `OracleXmlCommandType.Delete`, or `OracleXmlCommandType.Query` then the `ExecuteReader` method throws an `InvalidOperationException`.

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class ExecuteReaderSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
```

```
con.Open();

OracleCommand cmd = new OracleCommand("select ename from emp", con);

OracleDataReader reader = cmd.ExecuteReader();

while (reader.Read())
{
    Console.WriteLine("Employee Name : " + reader.GetString(0));
}

// Clean up
reader.Dispose();
cmd.Dispose();
con.Dispose();
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- ["OracleRefCursor Class"](#) on page 13-119

ExecuteReader(CommandBehavior)

This method executes a command specified in the `CommandText` and returns an `OracleDataReader` object, using the specified behavior.

Declaration

```
// C#
public OracleDataReader ExecuteReader(CommandBehavior behavior);
```

Parameters

- *behavior*
The expected behavior.

Return Value

An `OracleDataReader`.

Implements

`IDbCommand`

Exceptions

`InvalidOperationException` - The command cannot be executed.

Remarks

A description of the results and the effect on the database of the query command is indicated by the supplied *behavior* that specifies command behavior.

For valid `CommandBehavior` values and for the command behavior of each `CommandBehavior` enumerated type, read the .NET Framework documentation.

When the `CommandType` property is set to `CommandType.StoredProcedure`, the `CommandText` property should be set to the name of the stored procedure. The command executes this stored procedure when `ExecuteReader()` is called.

If the stored procedure returns stored REF CURSORS, read the section on `OracleRefCursors` for more details. See "[OracleRefCursor Class](#)" on page 13-119.

The value of 100 is used for the `FetchSize`. If 0 is specified, no rows are fetched. For more information, see "[Obtaining LONG and LONG RAW Data](#)" on page 3-57.

If the value of the `XmlCommandType` property is set to `OracleXmlCommandType.Insert`, `OracleXmlCommandType.Update`, `OracleXmlCommandType.Delete`, or `OracleXmlCommandType.Query` then the `ExecuteReader` method throws an `InvalidOperationException`.

See Also:

- "[Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces](#)" on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- "[OracleRefCursor Class](#)" on page 13-119

ExecuteScalar

This method executes the query using the connection, and returns the first column of the first row in the result set returned by the query.

Declaration

```
// C#
public override object ExecuteScalar();
```

Return Value

An object which represents the value of the first row, first column.

Implements

`IDbCommand`

Exceptions

`InvalidOperationException` - The command cannot be executed.

Remarks

Extra columns or rows are ignored. `ExecuteScalar` retrieves a single value (for example, an aggregate value) from a database. This requires less code than using the `ExecuteReader()` method, and then performing the operations necessary to generate the single value using the data returned by an `OracleDataReader`.

If the query does not return any row, it returns null.

The `ExecuteScalar` method throws an `InvalidOperationException`, if the value of the `XmlCommandType` property is set to one of the following `OracleXmlCommandType` values: `Insert`, `Update`, `Delete`, `Query`.

Example

```
// C#
```

```
using System;
using System.Data;
using Oracle.DataAccess.Client;

class ExecuteScalarSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleCommand cmd = new OracleCommand("select count(*) from emp", con);

        object count = cmd.ExecuteScalar();

        Console.WriteLine("There are {0} rows in table emp", count);

        // Clean up
        cmd.Dispose();
        con.Dispose();
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleCommand Class](#)
- [OracleCommand Members](#)

ExecuteStream

This method executes a command using the `XmlCommandType` and `CommandText` properties and returns the result as an XML document in a new `Stream` object.

Declaration

```
// C#
public Stream ExecuteStream();
```

Return Value

A `Stream`.

Remarks

The behavior of `ExecuteStream` varies depending on the `XmlCommandType` property value:

- `XmlCommandType = OracleXmlCommandType.None`
`ExecuteStream` throws an `InvalidOperationException`.
- `XmlCommandType = OracleXmlCommandType.Query`
`ExecuteStream` executes the select statement in the `CommandText` property, and if successful, returns an `OracleClob` object containing the XML document that was generated. `OracleClob` contains Unicode characters.

If the SQL query does not return any rows, then `ExecuteStream` returns an `OracleClob` object containing an empty XML document.

- `XmlCommandType = OracleXmlCommandType.Insert, OracleXmlCommandType.Update, or OracleXmlCommandType.Delete.`

The value of the `CommandText` property is an XML document. `ExecuteStream` saves the data in that XML document to the table or view that is specified in the `XmlSaveProperties` property and an empty `OracleClob` is returned.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- *Oracle XML DB Developer's Guide*
- <http://otn.oracle.com/>

ExecuteToStream

This method executes a command using the `XmlCommandType` and `CommandText` properties and appends the result as an XML document to the existing `Stream` provided by the application.

Declaration

```
// C#
public void ExecuteToStream(Stream outputStream);
```

Parameters

- `outputStream`
A `Stream`.

Remarks

The behavior of `ExecuteToStream` varies depending on the `XmlCommandType` property value:

- `XmlCommandType = OracleXmlCommandType.None`
`ExecuteToStream` throws an `InvalidOperationException`.
- `XmlCommandType = OracleXmlCommandType.Query`
`ExecuteToStream` executes the select statement in the `CommandText` property, and if successful, appends the XML document that was generated to the given `Stream`.
If the SQL query does not return any rows, then nothing is appended to the given `Stream`. The character set of the appended data is Unicode.
- `XmlCommandType = OracleXmlCommandType.Insert, OracleXmlCommandType.Update, or OracleXmlCommandType.Delete`

The value of the `CommandText` property is an XML document. `ExecuteToStream` saves the changes in that XML document to the table or view that is specified in the `XmlSaveProperties` property. Nothing is appended to the given `Stream`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- *Oracle XML DB Developer's Guide*
- <http://otn.oracle.com/>

ExecuteXmlReader

This method executes the command using the `XmlCommandType` and `CommandText` properties and returns the result as an XML document in a .NET `XmlTextReader` object.

Declaration

```
// C#  
public XmlReader ExecuteXmlReader();
```

Return Value

An `XmlReader`.

Remarks

The behavior of `ExecuteXmlReader` varies depending on the `XmlCommandType` property value:

- `XmlCommandType = OracleXmlCommandType.None`
`ExecuteStream` throws an `InvalidOperationException`.
- `XmlCommandType = OracleXmlCommandType.Query`
`ExecuteXmlReader` executes the select statement in the `CommandText` property, and if successful, returns a .NET `XmlTextReader` object containing the XML document that was generated.

If the XML document is empty, which can happen if the SQL query does not return any rows, then an empty .NET `XmlTextReader` object is returned.
- `XmlCommandType = OracleXmlCommandType.Insert, OracleXmlCommandType.Update, or OracleXmlCommandType.Delete`.

The value of the `CommandText` property is an XML document, and `ExecuteXmlReader` saves the changes in that XML document to the table or view that is specified in the `XmlSaveProperties` property. An empty .NET `XmlTextReader` object is returned.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommand Class](#)
- [OracleCommand Members](#)
- *Oracle XML DB Developer's Guide*
- <http://otn.oracle.com/>

OracleCommandBuilder Class

An OracleCommandBuilder object provides automatic SQL generation for the OracleDataAdapter when updates are made to the database.

Class Inheritance

System.Object

System.MarshalByRefObject

System.ComponentModel.Component

System.Data.Common.DbCommandBuilder

Oracle.DataAccess.Client.OracleCommandBuilder

Declaration

```
// C#
public sealed class OracleCommandBuilder : DbCommandBuilder
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

OracleCommandBuilder automatically generates SQL statements for single-table updates when the SelectCommand property of the OracleDataAdapter is set. An exception is thrown if the DataSet contains multiple tables. The OracleCommandBuilder registers itself as a listener for RowUpdating events whenever its DataAdapter property is set. Only one OracleDataAdapter object and one OracleCommandBuilder object can be associated with each other at one time.

To generate INSERT, UPDATE, or DELETE statements, the OracleCommandBuilder uses ExtendedProperties within the DataSet to retrieve a required set of metadata. If the SelectCommand is changed after the metadata is retrieved (for example, after the first update), the RefreshSchema method should be called to update the metadata.

OracleCommandBuilder first looks for the metadata from the ExtendedProperties of the DataSet; if the metadata is not available, OracleCommandBuilder uses the SelectCommand property of the OracleDataAdapter to retrieve the metadata.

Example

The following example performs an update on the EMP table. It uses the OracleCommandBuilder object to create the UpdateCommand for the OracleDataAdapter object when OracleDataAdapter.Update() is called.

```
// C#
```

```
using System;
using System.Data;
using Oracle.DataAccess.Client;

class OracleCommandBuilderSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        string cmdstr = "SELECT empno, sal from emp";

        // Create the adapter with the selectCommand txt and the
        // connection string
        OracleDataAdapter adapter = new OracleDataAdapter(cmdstr, constr);

        // Create the builder for the adapter to automatically generate
        // the Command when needed
        OracleCommandBuilder builder = new OracleCommandBuilder(adapter);

        // Create and fill the DataSet using the EMP
        DataSet dataset = new DataSet();
        adapter.Fill(dataset, "EMP");

        // Get the EMP table from the dataset
        DataTable table = dataset.Tables["EMP"];

        // Indicate DataColumn EMPNO is unique
        // This is required by the OracleCommandBuilder to update the EMP table
        table.Columns["EMPNO"].Unique = true;

        // Get the first row from the EMP table
        DataRow row = table.Rows[0];

        // Update the salary
        double sal = double.Parse(row["SAL"].ToString());
        row["SAL"] = sal + .01;

        // Now update the EMP using the adapter
        // The OracleCommandBuilder will create the UpdateCommand for the
        // adapter to update the EMP table
        adapter.Update(dataset, "EMP");

        Console.WriteLine("Row updated successfully");
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Members](#)
- [OracleCommandBuilder Constructors](#)
- [OracleCommandBuilder Static Methods](#)
- [OracleCommandBuilder Properties](#)
- [OracleCommandBuilder Public Methods](#)
- [OracleCommandBuilder Events](#)

OracleCommandBuilder Members

OracleCommandBuilder members are listed in the following tables.

OracleCommandBuilder Constructors

OracleCommandBuilder constructors are listed in [Table 6-13](#).

Table 6-13 OracleCommandBuilder Constructors

| Constructor | Description |
|---------------------------------------------------|------------------------------------------------------------------------|
| OracleCommandBuilder Constructors | Instantiates a new instance of OracleCommandBuilder class (Overloaded) |

OracleCommandBuilder Static Methods

OracleCommandBuilder static methods are listed in [Table 6-14](#).

Table 6-14 OracleCommandBuilder Static Methods

| Method | Description |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DeriveParameters | Queries for the parameters of a stored procedure or function, represented by a specified OracleCommand, and populates the OracleParameterCollection of the command with the return values |
| Equals | Inherited from System.Object (Overloaded) |

OracleCommandBuilder Properties

OracleCommandBuilder properties are listed in [Table 6-15](#).

Table 6-15 OracleCommandBuilder Properties

| Property | Description |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Container | Inherited from System.ComponentModel.Component |
| CaseSensitive | Indicates whether or not double quotes are used around Oracle object names when generating SQL statements |
| CatalogLocation | <i>Not Supported</i> |
| CatalogSeparator | <i>Not Supported</i> |
| ConflictOption | <i>Not Supported</i> |
| DataAdapter | Indicates the OracleDataAdapter for which the SQL statements are generated |
| QuotePrefix | Specifies the beginning character or characters used to specify database objects whose names contain special characters such as spaces or reserved words |
| QuoteSuffix | Specifies the ending character or characters used to specify database objects whose names contain special characters such as spaces or reserved words |
| SchemaSeparator | Specifies the character to be used for the separator between the schema identifier and other identifiers |
| Site | Inherited from System.ComponentModel.Component |

OracleCommandBuilder Public Methods

OracleCommandBuilder public methods are listed in [Table 6–16](#).

Table 6–16 OracleCommandBuilder Public Methods

| Public Method | Description |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| CreateObjRef | Inherited from System.MarshalByRefObject |
| Dispose | Inherited from System.ComponentModel.Component |
| Equals | Inherited from System.Object (Overloaded) |
| GetDeleteCommand | Gets the automatically generated OracleCommand object that has the SQL statement (CommandText) perform deletions on the database (Overloaded) |
| GetHashCode | Inherited from System.Object |
| GetInsertCommand | Gets the automatically generated OracleCommand object that has the SQL statement (CommandText) perform insertions on the database (Overloaded) |
| GetLifetimeService | Inherited from System.MarshalByRefObject |
| GetType | Inherited from System.Object |
| GetUpdateCommand | Gets the automatically generated OracleCommand object that has the SQL statement (CommandText) perform updates on the database (Overloaded) |
| InitializeLifetimeService | Inherited from System.MarshalByRefObject |
| QuoteIdentifier | Returns the correct quoted form of the provided unquoted identifier, with any embedded quotes in the identifier properly escaped |
| RefreshSchema | Refreshes the database schema information used to generate INSERT, UPDATE, or DELETE statements |
| UnquoteIdentifier | Returns the correct unquoted form of the provided quoted identifier, removing any escape notation for quotes embedded in the identifier |
| ToString | Inherited from System.Object |

OracleCommandBuilder Events

The OracleCommandBuilder event is listed in [Table 6–17](#).

Table 6–17 OracleCommandBuilder Events

| Event Name | Description |
|------------|------------------------------------------------|
| Disposed | Inherited from System.ComponentModel.Component |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Class](#)

OracleCommandBuilder Constructors

OracleCommandBuilder constructors create new instances of the OracleCommandBuilder class.

Overload List:

- [OracleCommandBuilder\(\)](#)
This constructor creates an instance of the OracleCommandBuilder class.
- [OracleCommandBuilder\(OracleDataAdapter\)](#)
This constructor creates an instance of the OracleCommandBuilder class and sets the DataAdapter property to the provided OracleDataAdapter object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

OracleCommandBuilder()

This constructor creates an instance of the OracleCommandBuilder class.

Declaration

```
// C#  
public OracleCommandBuilder();
```

Remarks

Default constructor.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

OracleCommandBuilder(OracleDataAdapter)

This constructor creates an instance of the OracleCommandBuilder class and sets the DataAdapter property to the provided OracleDataAdapter object.

Declaration

```
// C#  
public OracleCommandBuilder(OracleDataAdapter da);
```

Parameters

- *da*
The OracleDataAdapter object provided.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

OracleCommandBuilder Static Methods

OracleCommandBuilder static methods are listed in [Table 6–18](#).

Table 6–18 OracleCommandBuilder Static Methods

| Method | Description |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DeriveParameters | Queries for the parameters of a stored procedure or function, represented by a specified OracleCommand, and populates the OracleParameterCollection of the command with the return values |
| Equals | Inherited from System.Object (Overloaded) |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

DeriveParameters

This method queries for the parameters of a stored procedure or function, represented by a specified OracleCommand, and populates the OracleParameterCollection of the command with the return values.

Declaration

```
// C#
public static void DeriveParameters(OracleCommand command);
```

Parameters

- *command*

The command that represents the stored procedure or function for which parameters are to be derived.

Exceptions

InvalidOperationException - The CommandText is not a valid stored procedure or function name, the CommandType is not CommandType.StoredProcedure, or the Connection.State is not ConnectionState.Open.

Remarks

When DeriveParameters is used to populate the Parameter collection of an OracleCommand Object that represents a stored function, the return value of the function is bound as the first parameter (at position 0 of the OracleParameterCollection).

DeriveParameters can only be used for stored procedures or functions, not for anonymous PL/SQL blocks.

DeriveParameters incurs a database round-trip to retrieve parameter metadata prior to executing the stored procedure/function. It should only be used during design time. To avoid unnecessary database round-trips in a production environment, the

`DeriveParameters` method itself should be replaced with the explicit parameter settings that were returned by the `DeriveParameters` method at design time.

`DeriveParameters` can only preserve the case of the stored procedure or function name if it is encapsulated by double-quotes. For example, if the stored procedure in the database is named `GetEmployees` with mixed-case, the `CommandText` property on the `OracleCommand` object must be set appropriately as in the following example:

```
cmd.CommandText = "\"GetEmployees\"";
```

Stored procedures and functions in a package must be provided in the following format:

```
<package name>.<procedure or function name>
```

For example, to obtain parameters for a stored procedure named `GetEmployees` (mixed-case) in a package named `EmpProcedures` (mixed-case), the name provided to the `OracleCommand` is:

```
"\"EmpProcedures\".\"GetEmployees\""
```

`DeriveParameters` cannot be used for object type methods.

The derived parameters contain all the metadata information that is needed for the stored procedure to execute properly. The application must provide the value of the parameters before execution, if required. The application may also modify the metadata information of the parameters before execution. For example, the `Size` property of the `OracleParameter` may be modified for PL/SQL character and string types to optimize the execution of the stored procedure.

The output values of derived parameters return as `.NET` Types by default. To obtain output parameters as provider types, the `OracleDbType` property of the parameter must be set explicitly by the application to override this default behavior. One quick way to do this is to set the `OracleDbType` to itself for all output parameters that should be returned as provider types.

The `BindByName` property of the supplied `OracleCommand` is left as is, but the application can change its value.

If the specified stored procedure or function is overloaded, the first overload is used to populate the parameters collection.

```
// Database Setup
/*
connect scott/tiger@oracle
CREATE OR REPLACE PROCEDURE MyOracleStoredProc (arg_in IN VARCHAR2,
  arg_out OUT VARCHAR2) IS
BEGIN
  arg_out := arg_in;
END;
/
*/

// C#
using System;
using System.Data;
using Oracle.DataAccess.Client;

class DeriveParametersSample
{
  static void Main()
  {
```

```
// Create the PL/SQL Stored Procedure MyOracleStoredProc as indicated in
// the preceding Database Setup

string constr = "User Id=scott;Password=tiger;Data Source=oracle";
OracleConnection con = new OracleConnection(constr);
con.Open();

// Create an OracleCommand
OracleCommand cmd = new OracleCommand("MyOracleStoredProc", con);
cmd.CommandType = CommandType.StoredProcedure;

// Derive Parameters
OracleCommandBuilder.DeriveParameters(cmd);
Console.WriteLine("Parameters Derived");

// Prints "Number of Parameters for MyOracleStoredProc = 2"
Console.WriteLine("Number of Parameters for MyOracleStoredProc = {0}",
    cmd.Parameters.Count);

// The PL/SQL stored procedure MyOracleStoredProc has one IN and
// one OUT parameter. Set the Value for the IN parameter.
cmd.Parameters[0].Value = "MyText";

// The application may modify the other OracleParameter properties also
// This sample uses the default Size for the IN parameter and modifies
// the Size for the OUT parameter

// The default size for OUT VARCHAR2 is 4000
// Prints "cmd.Parameters[1].Size = 4000"
Console.WriteLine("cmd.Parameters[1].Size = " + cmd.Parameters[1].Size);

// Set the Size for the OUT parameter
cmd.Parameters[1].Size = 6;

// Execute the command
cmd.ExecuteNonQuery();

// Prints "cmd.Parameters[1].Value = MyText"
Console.WriteLine("cmd.Parameters[1].Value = " + cmd.Parameters[1].Value);

con.Close();
con.Dispose();
}
}
```

Example**See Also:**

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)
- [OracleCommand Class](#)
- [OracleParameter Class](#)
- [OracleParameterCollection Class](#)
- <http://msdn.microsoft.com/library> for detailed information about this Microsoft .NET Framework 1.1 feature

OracleCommandBuilder Properties

OracleCommandBuilder properties are listed in [Table 6–19](#).

Table 6–19 OracleCommandBuilder Properties

| Property | Description |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Container | Inherited from <code>System.ComponentModel.Component</code> |
| CaseSensitive | Indicates whether or not double quotes are used around Oracle object names when generating SQL statements |
| CatalogLocation | <i>Not Supported</i> |
| CatalogSeparator | <i>Not Supported</i> |
| ConflictOption | <i>Not Supported</i> |
| DataAdapter | Indicates the <code>OracleDataAdapter</code> for which the SQL statements are generated |
| QuotePrefix | Specifies the beginning character or characters used to specify database objects whose names contain special characters such as spaces or reserved words |
| QuoteSuffix | Specifies the ending character or characters used to specify database objects whose names contain special characters such as spaces or reserved words |
| SchemaSeparator | Specifies the character to be used for the separator between the schema identifier and other identifiers |
| Site | Inherited from <code>System.ComponentModel.Component</code> |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

CaseSensitive

This property indicates whether or not double quotes are used around Oracle object names (for example, tables or columns) when generating SQL statements.

Declaration

```
// C#
bool CaseSensitive {get; set;}
```

Property Value

A `bool` that indicates whether or not double quotes are used.

Remarks

Default = `false`

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

CatalogLocation

This property is not supported.

Declaration

```
// C#  
public override CatalogLocation CatalogLocation {get; set;}
```

Exceptions

NotSupportedException - This property is not supported.

Remarks

This property is not supported.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

CatalogSeparator

This property is not supported.

Declaration

```
// C#  
public override string CatalogSeparator {get; set;}
```

Exceptions

NotSupportedException - This property is not supported.

Remarks

This property is not supported.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

ConflictOption

This property is not supported.

Declaration

```
// C#  
public override string ConflictOption {get; set;}
```

Exceptions

NotSupportedException - This property is not supported.

Remarks

This property is not supported.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

DataAdapter

This property indicates the OracleDataAdapter object for which the SQL statements are generated.

Declaration

```
// C#  
OracleDataAdapter DataAdapter{get; set;}
```

Property Value

An OracleDataAdapter object.

Remarks

Default = null

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

QuotePrefix

This property specifies the beginning character or characters used to specify database objects whose names contain special characters such as spaces or reserved words.

Declaration

```
// C#  
public override string QuotePrefix {get; set;}
```

Property Value

The beginning character or characters to use. The default value is "\".

Remarks

This property is independent of any `OracleConnection` or `OracleCommand` objects.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

QuoteSuffix

This property specifies the ending character or characters used to specify database objects whose names contain special characters such as spaces or reserved words.

Declaration

```
// C#  
public override string QuoteSuffix {get; set;}
```

Property Value

The ending character or characters to use. The default value is "\".

Remarks

This property is independent of any `OracleConnection` or `OracleCommand` objects.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

SchemaSeparator

This property specifies the character to be used for the separator between the schema identifier and other identifiers.

Declaration

```
// C#  
public override string SchemaSeparator {get; set; }
```

Property Value

The character to be used as the schema separator.

Exceptions

`NotSupportedException` - The input value is not a dot (.).

Remarks

The default schema separator is a dot (.). The only acceptable value for this property is a dot (.).

This property is independent of any `OracleConnection` or `OracleCommand` objects.

Example

```
// C#

using System;
using System.Data;
using System.Data.Common;
using Oracle.DataAccess.Client;

class SchemaSeparatorSample
{
    static void Main(string[] args)
    {
        try
        {
            OracleCommandBuilder cmdBuilder = new OracleCommandBuilder();

            //schemaSeparator is dot(.)
            Console.WriteLine("schemaSeparator is {0}",
                cmdBuilder.SchemaSeparator);

            //set the schemaseparator, only '.' is allowed.
            cmdBuilder.SchemaSeparator = ".";

            // the only acceptable value for this property is a dot (.)
            // Hence the following line will throw NotSupportedException
            cmdBuilder.SchemaSeparator = "!";
        }
        catch (Exception ex)
        {
            Console.WriteLine(ex.Message);
            Console.WriteLine(ex.StackTrace);
        }
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

OracleCommandBuilder Public Methods

OracleCommandBuilder public methods are listed in [Table 6–20](#).

Table 6–20 OracleCommandBuilder Public Methods

| Public Method | Description |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| CreateObjRef | Inherited from System.MarshalByRefObject |
| Dispose | Inherited from System.ComponentModel.Component |
| Equals | Inherited from System.Object (Overloaded) |
| GetDeleteCommand | Gets the automatically generated OracleCommand object that has the SQL statement (CommandText) perform deletions on the database (Overloaded) |
| GetHashCode | Inherited from System.Object |
| GetInsertCommand | Gets the automatically generated OracleCommand object that has the SQL statement (CommandText) perform insertions on the database (Overloaded) |
| GetLifetimeService | Inherited from System.MarshalByRefObject |
| GetType | Inherited from System.Object |
| GetUpdateCommand | Gets the automatically generated OracleCommand object that has the SQL statement (CommandText) perform updates on the database (Overloaded) |
| InitializeLifetimeService | Inherited from System.MarshalByRefObject |
| QuoteIdentifier | Returns the correct quoted form of the provided unquoted identifier, with any embedded quotes in the identifier properly escaped |
| RefreshSchema | Refreshes the database schema information used to generate INSERT, UPDATE, or DELETE statements |
| UnquoteIdentifier | Returns the correct unquoted form of the provided quoted identifier, removing any escape notation for quotes embedded in the identifier |
| ToString | Inherited from System.Object |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

GetDeleteCommand

Gets the automatically generated OracleCommand object that has the SQL statement (CommandText) perform deletions on the database

Overload List

- [GetDeleteCommand\(\)](#)

This method gets the automatically generated OracleCommand object that has the SQL statement (CommandText) perform deletions on the database when an application calls Update() on the OracleDataAdapter.

- [GetDeleteCommand\(bool\)](#)

This method gets the automatically generated `OracleCommand` object that has the SQL statement (`CommandText`) perform deletions on the database when an application calls `Update()` on the `OracleDataAdapter`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

GetDeleteCommand()

This method gets the automatically generated `OracleCommand` object that has the SQL statement (`CommandText`) perform deletions on the database when an application calls `Update()` on the `OracleDataAdapter`.

Declaration

```
// C#  
public OracleCommand GetDeleteCommand();
```

Return Value

An `OracleCommand`.

Exceptions

`ObjectDisposedException` - The `OracleCommandBuilder` object is already disposed.

`InvalidOperationException` - Either the `SelectCommand` or the `DataAdapter` property is null, or the primary key cannot be retrieved from the `SelectCommand` property of the `OracleDataAdapter`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

GetDeleteCommand(bool)

This method gets the automatically generated `OracleCommand` object that has the SQL statement (`CommandText`) perform deletions on the database when an application calls `Update()` on the `OracleDataAdapter`.

Declaration

```
// C#  
public OracleCommand GetDeleteCommand(bool useColumnsForParameterNames);
```

Parameters

- `useColumnsForParameterNames`

If true, the method generates parameter names matching column names if possible. If false, the method binds parameters by position.

Return Value

An OracleCommand.

Exceptions

ObjectDisposedException - The OracleCommandBuilder object is already disposed.

InvalidOperationException - Either the SelectCommand or the DataAdapter property is null, or the primary key cannot be retrieved from the SelectCommand property of the OracleDataAdapter.

Remarks

If the bool is true, the method generates parameter names matching column names if possible. If false, the method binds parameters by position.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

GetInsertCommand

Gets the automatically generated OracleCommand object that has the SQL statement (CommandText) perform insertions on the database

Overload List

- [GetInsertCommand\(\)](#)

This method gets the automatically generated OracleCommand object that has the SQL statement (CommandText) perform insertions on the database when an application calls Update() on the OracleDataAdapter.
- [GetInsertCommand\(bool\)](#)

This method gets the automatically generated OracleCommand object that has the SQL statement (CommandText) perform insertions on the database when an application calls Update() on the OracleDataAdapter.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

GetInsertCommand()

This method gets the automatically generated OracleCommand object that has the SQL statement (CommandText) perform insertions on the database when an application calls Update() on the OracleDataAdapter.

Declaration

```
// C#  
public OracleCommand GetInsertCommand();
```

Return Value

An OracleCommand.

Exceptions

ObjectDisposedException - The OracleCommandBuilder object is already disposed.

InvalidOperationException - Either the SelectCommand or the DataAdapter property is null, or the primary key cannot be retrieved from the SelectCommand property of the OracleDataAdapter.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

GetInsertCommand(bool)

This method gets the automatically generated OracleCommand object that has the SQL statement (CommandText) perform insertions on the database when an application calls Update() on the OracleDataAdapter.

Declaration

```
// C#  
public OracleCommand GetInsertCommand(bool useColumnsForParameterNames);
```

Parameters

- useColumnsForParameterNames

If true, the method generates parameter names matching column names if possible. If false, the method binds parameters by position.

Return Value

An OracleCommand.

Exceptions

ObjectDisposedException - The OracleCommandBuilder object is already disposed.

InvalidOperationException - Either the SelectCommand or the DataAdapter property is null, or the primary key cannot be retrieved from the SelectCommand property of the OracleDataAdapter.

Remarks

If the bool is true, the method generates parameter names matching column names if possible. If false, the method binds parameters by position.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

GetUpdateCommand

Gets the automatically generated `OracleCommand` object that has the SQL statement (`CommandText`) perform updates on the database

Overload List

- [GetUpdateCommand\(\)](#)

This method gets the automatically generated `OracleCommand` object that has the SQL statement (`CommandText`) perform updates on the database when an application calls `Update()` on the `OracleDataAdapter`.

- [GetUpdateCommand\(bool\)](#)

This method gets the automatically generated `OracleCommand` object that has the SQL statement (`CommandText`) perform updates on the database when an application calls `Update()` on the `OracleDataAdapter`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

GetUpdateCommand()

This method gets the automatically generated `OracleCommand` object that has the SQL statement (`CommandText`) perform updates on the database when an application calls `Update()` on the `OracleDataAdapter`.

Declaration

```
// C#  
public OracleCommand GetUpdateCommand();
```

Return Value

An `OracleCommand`.

Exceptions

`ObjectDisposedException` - The `OracleCommandBuilder` object is already disposed.

`InvalidOperationException` - Either the `SelectCommand` or the `DataAdapter` property is null, or the primary key cannot be retrieved from the `SelectCommand` property of the `OracleDataAdapter`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

GetUpdateCommand(bool)

This method gets the automatically generated `OracleCommand` object that has the SQL statement (`CommandText`) perform updates on the database when an application calls `Update()` on the `OracleDataAdapter`.

Declaration

```
// C#  
public OracleCommand GetUpdateCommand(bool useColumnsForParameterNames);
```

Parameters

- `useColumnsForParameterNames`

If true, the method generates parameter names matching column names if possible. If false, the method binds parameters by position.

Return Value

An `OracleCommand`.

Exceptions

`ObjectDisposedException` - The `OracleCommandBuilder` object is already disposed.

`InvalidOperationException` - Either the `SelectCommand` or the `DataAdapter` property is null, or the primary key cannot be retrieved from the `SelectCommand` property of the `OracleDataAdapter`.

Remarks

If the bool is true, the method generates parameter names matching column names if possible. If false, the method binds parameters by position.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

QuoteIdentifier

This method returns the correct quoted form of the provided unquoted identifier, with any embedded quotes in the identifier properly escaped.

Declaration

```
// C#  
public override string QuoteIdentifier(string unquotedIdentifier);
```

Parameters

- `UnquotedIdentifier`

An unquoted identifier string.

Return Value

The quoted version of the identifier. Embedded quotes within the identifier are properly escaped.

Exceptions

`ArgumentNullException` - The input parameter is null.

Remarks

This method is independent of any `OracleConnection` or `OracleCommand` objects.

Example

```
// C#

using System;
using System.Data;
using System.Data.Common;
using Oracle.DataAccess.Client;

class QuoteIdentifierSample
{
    static void Main(string[] args)
    {
        OracleCommandBuilder builder = new OracleCommandBuilder();
        string quoteIdentifier = builder.QuoteIdentifier("US\"ER");

        //quoteIdentifier for "US\"ER" is (\\"US\\"ER\\")
        Console.WriteLine("quoteIdentifier is {0}" , quoteIdentifier);
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

RefreshSchema

This method refreshes the database schema information used to generate INSERT, UPDATE, or DELETE statements.

Declaration

```
// C#
public override void RefreshSchema();
```

Remarks

An application should call `RefreshSchema` whenever the `SelectCommand` value of the `OracleDataAdapter` object changes.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

UnquoteIdentifier

This method returns the correct unquoted form of the provided quoted identifier, removing any escape notation for quotes embedded in the identifier.

Declaration

```
// C#  
public override string UnquoteIdentifier(string quotedIdentifier);
```

Parameters

- *quotedIdentifier*

The quoted string identifier.

Return Value

The unquoted identifier, with escape notation for any embedded quotes removed.

Exceptions

ArgumentNullException - The input parameter is null.

ArgumentException - The input parameter is empty.

Remarks

This method is independent of any OracleConnection or OracleCommand objects.

Example

```
// C#  
  
using System;  
using System.Data;  
using System.Data.Common;  
using Oracle.DataAccess.Client;  
  
class UnQuoteIdentifierSample  
{  
    static void Main(string[] args)  
    {  
        //create an OracleCommandBuilder object.  
        OracleCommandBuilder builder = new OracleCommandBuilder();  
  
        string identifier = "US\"ER\"";  
        Console.WriteLine("Identifier is {0}", identifier);  
  
        // quote the identifier  
        string quoteIdentifier = builder.QuoteIdentifier(identifier);  
  
        //quoteIdentifier of "US\"ER\" is (\\"US\"\"ER\"")  
        Console.WriteLine("QuotedIdentifier is {0}" , quoteIdentifier);  
        string unquoteIdentifier = builder.UnquoteIdentifier(quoteIdentifier);  
  
        //And its unquoteIdentifier is US\"ER  
        Console.WriteLine("UnquotedIdentifier is {0}" , unquoteIdentifier);  
    }  
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

OracleCommandBuilder Events

The OracleCommandBuilder event is listed in [Table 6–21](#).

Table 6–21 OracleCommandBuilder Event

| Event Name | Description |
|------------|------------------------------------------------|
| Disposed | Inherited from System.ComponentModel.Component |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleCommandBuilder Class](#)
- [OracleCommandBuilder Members](#)

OracleConnection Class

An OracleConnection object represents a connection to an Oracle database.

Class Inheritance

```
System.Object
    System.MarshalByRefObject
        System.ComponentModel.Component
            System.Data.Common.DbConnection
                Oracle.DataAccess.Client.OracleConnection
```

Declaration

```
// C#
public sealed class OracleConnection : DbConnection, IDbConnection, ICloneable
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class OracleConnectionSample
{
    static void Main()
    {
        // Connect
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Execute a SQL SELECT
        OracleCommand cmd = con.CreateCommand();
        cmd.CommandText = "select * from emp";
        OracleDataReader reader = cmd.ExecuteReader();

        // Print all employee numbers
        while (reader.Read())
            Console.WriteLine(reader.GetInt32(0));
    }
}
```

```
// Clean up
reader.Dispose();
cmd.Dispose();
con.Dispose();
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleConnection Members](#)
- [OracleConnection Constructors](#)
- [OracleConnection Static Properties](#)
- [OracleConnection Static Methods](#)
- [OracleConnection Properties](#)
- [OracleConnection Public Methods](#)
- [OracleConnection Events](#)

OracleConnection Members

OracleConnection members are listed in the following tables.

OracleConnection Constructors

OracleConnection constructors are listed in [Table 6-22](#).

Table 6-22 OracleConnection Constructors

| Constructor | Description |
|-----------------------------------------------|------------------------------------------------------------------------|
| OracleConnection Constructors | Instantiates a new instance of the OracleConnection class (Overloaded) |

OracleConnection Static Properties

The OracleConnection static property is listed in [Table 6-24](#).

Table 6-23 OracleConnection Static Property

| Property | Description |
|-----------------------------|--------------------------------------------------------------------------------|
| IsAvailable | Indicates whether or not the implicit database connection is available for use |

OracleConnection Static Methods

The OracleConnection static methods are listed in [Table 6-24](#).

Table 6-24 OracleConnection Static Methods

| Method | Description |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |
| ClearPool | Clears the connection pool that is associated with the provided OracleConnection object. <i>Not supported in a .NET stored procedure</i> |
| ClearAllPools | Clears all connections from all the connection pools <i>Not supported in a .NET stored procedure</i> |

OracleConnection Properties

OracleConnection properties are listed in [Table 6-25](#).

Table 6-25 OracleConnection Properties

| Property | Description |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| ActionName | Specifies the action name for the connection |
| ClientId | Specifies the client identifier for the connection |
| ClientInfo | Specifies the client information for the connection |
| ConnectionString | Specifies connection information used to connect to an Oracle database |
| ConnectionTimeout | Indicates the maximum amount of time that the Open method can take to obtain a pooled connection before the request is terminated |

Table 6–25 (Cont.) OracleConnection Properties

| Property | Description |
|------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ConnectionType | Determines whether a particular connection object is associated with a TimesTen database connection, an Oracle database connection, or no physical connection <i>Not available in ODP.NET, Managed Driver</i> |
| Container | Inherited from <code>System.ComponentModel.Component</code> |
| Database | <i>Not Supported</i> |
| DatabaseDomainName | Specifies the name of the database domain to which the connection is set |
| DatabaseName | Specifies the name of the database to which the connection is set |
| DataSource | Specifies the Oracle Net Services Name, Connect Descriptor, or an easy connect naming that identifies the database to which to connect |
| HostName | Specifies the name of the host to which the connection is set |
| InstanceName | Specifies the name of the instance to which the connection is set |
| LogicalTransactionId | Specifies the logical transaction id that is associated with the connection at the time of the invocation <i>Not available in ODP.NET, Managed Driver</i> <i>This property has been deprecated in 12.1.0.2. It will be desupported in a future release.</i> |
| ModuleName | Specifies the module name for the connection |
| OracleLogicalTransaction | Returns an instance of an <code>OracleLogicalTransaction</code> object. |
| ServerVersion | Specifies the version number of the Oracle database to which the <code>OracleConnection</code> has established a connection |
| ServiceName | Specifies the name of the service to which the connection is set |
| Site | Inherited from <code>System.ComponentModel.Component</code> |
| State | Specifies the current state of the connection |
| StatementCacheSize | Specifies the current size of the statement cache associated with this connection |

OracleConnection Public Methods

`OracleConnection` public methods are listed in [Table 6–26](#).

Table 6–26 OracleConnection Public Methods

| Public Method | Description |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------|
| BeginTransaction | Begins a local transaction (Overloaded) <i>Not supported in a .NET stored procedure for context connection</i> |
| ChangeDatabase | <i>Not Supported</i> |
| Clone | Creates a copy of an <code>OracleConnection</code> object <i>Not supported in a .NET stored procedure</i> |
| Close | Closes the database connection |
| CreateCommand | Creates and returns an <code>OracleCommand</code> object associated with the <code>OracleConnection</code> object |

Table 6–26 (Cont.) OracleConnection Public Methods

| Public Method | Description |
|----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CreateObjRef | Inherited from System.MarshalByRefObject |
| Dispose | Inherited from System.ComponentModel.Component |
| EnlistDistributedTransaction | Enables applications to explicitly enlist in a specified distributed transaction <i>Not supported in a .NET stored procedure</i> |
| EnlistTransaction | Enables applications to enlist in a specified distributed transaction <i>Not supported in a .NET stored procedure</i> |
| Equals | Inherited from System.Object (Overloaded) |
| FlushCache | Flushes all updates and deletes made through REF objects retrieved using this connection <i>Not available in ODP.NET, Managed Driver</i> |
| GetHashCode | Inherited from System.Object |
| GetLifetimeService | Inherited from System.MarshalByRefObject |
| GetLogicalTransactionStatus | Returns the status of the current local transaction associated with the connection <i>Not available in the ODP.NET, Managed Driver</i> <i>This method has been deprecated in ODP.NET 12.1.0.2. It will be desupported in a future release.</i> |
| GetSchema | Returns schema information for the data source of the OracleConnection |
| GetSessionInfo | Returns or refreshes the property values of the OracleGlobalization object that represents the globalization settings of the session (Overloaded) |
| GetType | Inherited from System.Object |
| InitializeLifetimeService | Inherited from System.MarshalByRefObject |
| Open | Opens a database connection with the property settings specified by the ConnectionString |
| OpenWithNewPassword | Opens a new connection with the new password <i>Not supported in a .NET stored procedure for context connection</i> |
| PurgeStatementCache | Flushes the Statement Cache by closing all open cursors on the database, when statement caching is enabled |
| SetSessionInfo | Alters the session's globalization settings with the property values provided by the OracleGlobalization object |
| ToString | Inherited from System.Object |

OracleConnection Events

OracleConnection events are listed in [Table 6–27](#).

Table 6–27 OracleConnection Events

| Event Name | Description |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Disposed | Inherited from System.ComponentModel.Component |
| Failover | An event that is triggered when an Oracle failover occurs <i>Not supported in a .NET stored procedure</i> <i>Not Available in ODP.NET, Managed Driver</i> |
| HAEvent | An event that is triggered when an HA event occurs. |
| InfoMessage | An event that is triggered for any message or warning sent by the database |
| StateChange | An event that is triggered when the connection state changes |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)

OracleConnection Constructors

OracleConnection constructors instantiate new instances of the OracleConnection class.

Overload List:

- [OracleConnection\(\)](#)
This constructor instantiates a new instance of the OracleConnection class using default property values.
- [OracleConnection\(String\)](#)
This constructor instantiates a new instance of the OracleConnection class with the provided connection string.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

OracleConnection()

This constructor instantiates a new instance of the OracleConnection class using default property values.

Declaration

```
// C#  
public OracleConnection();
```

Remarks

The properties for OracleConnection are set to the following default values:

- ConnectionString = empty string
- ConnectionTimeout = 15 (default value of 0 is used for the implicit database connection)
- DataSource = empty string
- ServerVersion = empty string

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

OracleConnection(String)

This constructor instantiates a new instance of the OracleConnection class with the provided connection string.

Declaration

```
// C#  
public OracleConnection(String connectionString);
```

Parameters

- *connectionString*

The connection information used to connect to the Oracle database.

Remarks

The `ConnectionString` property is set to the supplied *connectionString*. The `ConnectionString` property is parsed and an exception is thrown if it contains invalid connection string attributes or attribute values.

The properties of the `OracleConnection` object default to the following values unless they are set by the connection string:

- `ConnectionString` = empty string
- `ConnectionTimeout` = 15 (default value of 0 is used for the implicit database connection)
- `DataSource` = empty string
- `ServerVersion` = empty string

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

OracleConnection Static Properties

The OracleConnection static property is listed in [Table 6–28](#).

Table 6–28 OracleConnection Static Property

| Property | Description |
|-----------------------------|--------------------------------------------------------------------------------|
| IsAvailable | Indicates whether or not the implicit database connection is available for use |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

IsAvailable

This property indicates whether or the implicit database connection is available for use.

Declaration

```
// C#
public static bool IsAvailable {get;}
```

Property Value

Returns true if the implicit database connection is available for use.

Remarks

The availability of the implicit database connection can be checked at runtime through this static property. When Oracle Data Provider for .NET is used within a .NET stored procedure, this property always returns true. Otherwise, false is returned.

To obtain an OracleConnection object in a .NET stored procedure that represents the implicit database connection, set the ConnectionString property of the OracleConnection object to "context connection=true" and invoke the Open method.

Note that not all features that are available for an explicit user connection are available for an implicit database connection. See ["Implicit Database Connection"](#) on page 5-2 for details.

Example

```
// C# (Library/DLL)
using System;
using Oracle.DataAccess.Client;

public class IsAvailableSample
{
    static void MyStoredProcedure()
    {
        OracleConnection con = new OracleConnection();
        if (OracleConnection.IsAvailable)
        {
            // This function is invoked as a stored procedure
        }
    }
}
```

```
        // Obtain the implicit database connection by setting
        //   "context connection=true" in the connection string
        con.ConnectionString = "context connection=true";
    }
    else
    {
        // This function is not invoked as a stored procedure
        // Set the connection string for a normal client connection
        con.ConnectionString = "user id=scott;password=tiger;data source=oracle";
    }

    con.Open();
    Console.WriteLine("connected!");
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

OracleConnection Static Methods

The OracleConnection static methods are listed in [Table 6–29](#).

Table 6–29 OracleConnection Static Methods

| Method | Description |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |
| ClearPool | Clears the connection pool that is associated with the provided OracleConnection object. <i>Not supported in a .NET stored procedure</i> |
| ClearAllPools | Clears all connections from all the connection pools <i>Not supported in a .NET stored procedure</i> |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

ClearPool

This method clears the connection pool that is associated with the provided OracleConnection object.

Declaration

```
// C#
public static void ClearPool(OracleConnection connection);
```

Remarks

When this method is invoked, all idle connections are closed and freed from the pool. Currently used connections are not discarded until they are returned to the pool.

Beginning with ODP.NET 12c Release 1 (12.1), ClearPool does not automatically repopulate the pool with new connections. This prevents the pool from being repopulated with invalid connections if client remains unable to connect with the database server. Developers programmatically control when the pool is repopulated by calling OracleConnection.Open(), which will repopulate the pool with at least the Min Pool Size number of connections.

Connections created after this method invocation are not cleared unless another invocation is made.

This method can be invoked with an OracleConnection object before opening the connection as well as after, provided the ConnectionString is properly set.

Exceptions

InvalidOperationException – Either the connection pool cannot be found or the provided connection string is invalid.

Example

```
// C#
```

```
// Sample demonstrating the use of ClearPool API in OracleConnection class

using System;
using Oracle.DataAccess.Client;

class ClearPoolSample
{
    static void Main()
    {
        Console.WriteLine("Running ClearPool sample..." );
        // Set the connection string
        string strConn = "User Id=scott;Password=tiger;Data Source=oracle;" +
            "Min pool size=5;";
        OracleConnection conn = new OracleConnection(strConn);

        // Open the connection
        conn.Open();

        // Clears the connection pool associated with connection 'conn'
        OracleConnection.ClearPool (conn);

        // This connection will be placed back into the pool
        conn.Close ();

        // Open the connection again to create additional connections in the pool
        conn.Open();

        // Create a new connection object
        OracleConnection connNew = new OracleConnection(strConn);

        // Clears the pool associated with Connection 'connNew'
        // Since the same connection string is set for both the connections,
        // connNew and conn, they will be part of the same connection pool.
        // We need not do an Open() on the connection object before calling
        // ClearPool
        OracleConnection.ClearPool (connNew);

        // cleanup
        conn.Close();
        Console.WriteLine("Done!");
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

ClearAllPools

This method clears all connections from all the connection pools.

Declaration

```
// C#
public static void ClearAllPools();
```

Remarks

This call is analogous to calling `ClearPool` for all the connection pools that are created for the application.

Exceptions

`InvalidOperationException` – No connection pool could be found for the application.

Example

```
// C#
// Sample demonstrating the use of ClearAllPools API in OracleConnection class

using System;
using Oracle.DataAccess.Client;

class ClearAllPoolsSample
{
    static void Main()
    {
        Console.WriteLine("Running ClearAllPools sample..." );
        // Set the connection string
        string strConn = "User Id=scott;Password=tiger;Data Source=oracle;" +
            "Min pool size=5;";
        OracleConnection conn = new OracleConnection(strConn);

        // Create another connection object with a different connection string
        string strConnNew = "User Id=scott;Password=tiger;Data Source=oracle;";
        OracleConnection connNew = new OracleConnection(strConnNew);

        // Open the connections. Separate pools are created for conn and connNew
        conn.Open();
        connNew.Open();

        // Clears the pools associated with conn and connNew
        OracleConnection.ClearAllPools ();

        // cleanup
        conn.Close();
        connNew.Close();
        Console.WriteLine("Done!");
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["ClearPool"](#) on page 6-89

OracleConnection Properties

OracleConnection properties are listed in [Table 6–30](#)

Table 6–30 OracleConnection Properties

| Property | Description |
|------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ActionName | Specifies the action name for the connection |
| ClientId | Specifies the client identifier for the connection |
| ClientInfo | Specifies the client information for the connection |
| ConnectionString | Specifies connection information used to connect to an Oracle database |
| ConnectionTimeout | Indicates the maximum amount of time that the <code>Open</code> method can take to obtain a pooled connection before the request is terminated |
| ConnectionType | Determines whether a particular connection object is associated with a TimesTen database connection, an Oracle database connection, or no physical connection <i>Not available in ODP.NET, Managed Driver</i> |
| <code>Container</code> | Inherited from <code>System.ComponentModel.Component</code> |
| Database | <i>Not Supported</i> |
| DatabaseDomainName | Specifies the name of the database domain to which the connection is set |
| DatabaseName | Specifies the name of the database to which the connection is set |
| DataSource | Specifies the Oracle Net Services Name, Connect Descriptor, or an easy connect naming that identifies the database to which to connect |
| HostName | Specifies the name of the host to which the connection is set |
| InstanceName | Specifies the name of the instance to which the connection is set |
| LogicalTransactionId | Specifies the logical transaction id that is associated with the connection at the time of the invocation <i>Not available in ODP.NET, Managed Driver</i> <i>This property has been deprecated in 12.1.0.2. It will be desupported in a future release.</i> |
| ModuleName | Specifies the module name for the connection |
| OracleLogicalTransaction | Returns an instance of an <code>OracleLogicalTransaction</code> object. |
| ServerVersion | Specifies the version number of the Oracle database to which the <code>OracleConnection</code> has established a connection |
| ServiceName | Specifies the name of the service to which the connection is set |
| <code>Site</code> | Inherited from <code>System.ComponentModel.Component</code> |
| State | Specifies the current state of the connection |
| StatementCacheSize | Specifies the current size of the statement cache associated with this connection |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

ActionName

This property specifies the action name for the connection.

Declaration

```
// C#  
public string ActionName {set;}
```

Property Value

The string to be used as the action name.

Remarks

The default value is null.

Using the `ActionName` property allows the application to set the action name in the application context for a given `OracleConnection` object.

The `ActionName` property is reset to null when the `Close` or `Dispose` method is called on the `OracleConnection` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["Client Identifier and End-to-End Tracing"](#) on page 3-21
- *Oracle Database Security Guide*

ClientId

This property specifies the client identifier for the connection.

Declaration

```
// C#  
public string ClientId {set;}
```

Property Value

The string to be used as the client identifier.

Remarks

The default value is null.

Using the `ClientId` property allows the application to set the client identifier in the application context for a given `OracleConnection` object.

Setting `ClientId` to `null` resets the client identifier for the connection. `ClientId` is set to `null` when the `Close` or `Dispose` method is called on the `OracleConnection` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["Client Identifier and End-to-End Tracing"](#) on page 3-21
- *Oracle Database Security Guide*

ClientInfo

This property specifies the client information for the connection.

Declaration

```
// C#  
public string ClientInfo {set;}
```

Property Value

The string to be used as the client information.

Remarks

The default value is `null`.

Using the `ClientInfo` property allows the application to set the client information in the application context for a given `OracleConnection` object.

The `ClientInfo` property is reset to `null` when the `Close` or `Dispose` method is called on the `OracleConnection` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["Client Identifier and End-to-End Tracing"](#) on page 3-21
- *Oracle Database Security Guide*

ConnectionString

This property specifies connection information used to connect to an Oracle database.

Declaration

```
// C#  
public override string ConnectionString{get; set;}
```

Property Value

If the connection string is supplied through the constructor, this property is set to that string.

Implements

IDbConnection

Exceptions

ArgumentException - An invalid syntax is specified for the connection string.

InvalidOperationException - ConnectionString is being set while the connection is open.

Remarks

The default value is an empty string.

ConnectionString must be a string of attribute name and value pairings, separated by a semi-colon, for example:

```
"User Id=scott;password=tiger;data source=oracle"
```

If the ConnectionString is not in a proper format, an exception is thrown. All spaces are ignored unless they are within double quotes.

When the ConnectionString property is set, the OracleConnection object immediately parses the string for errors. An ArgumentException is thrown if the ConnectionString contains invalid attributes or invalid values. Attribute values for User Id, Password, Proxy User Id, Proxy Password, and Data Source (if provided) are not validated until the Open method is called.

The connection must be closed to set the ConnectionString property. When the ConnectionString property is reset, all previously set values are reinitialized to their default values before the new values are applied.

Starting with ODP.NET 11.1, password and proxy password connection string attribute values are accepted as case-sensitive strings. Thus, they are passed to the database for authentication in the case provided in the connection string. Therefore, if the database is configured to support case-sensitive passwords, passwords must be passed in the correct case.

If a connection string attribute is set more than once, the last setting takes effect and no exceptions are thrown.

Boolean connection string attributes can be set to either true, false, yes, or no.

Remarks (.NET Stored Procedure)

To obtain an OracleConnection object in a .NET stored procedure that represents the implicit database connection, set the ConnectionString property of the OracleConnection object to "context connection=true" and invoke the Open method. Other connection string attributes cannot be used in conjunction with "context connection" when it is set to true.

Supported Connection String Attributes

[Table 6–31](#) lists the supported connection string attributes.

Table 6–31 Supported Connection String Attributes

| Connection String Attribute | Description | Default Value |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| Connection Lifetime | <p>Minimum life time (in seconds) of the connection.</p> <p>This attribute specifies the lifetime of the connection in seconds. Before the <code>Connection</code> is placed back into the pool, the lifetime of the connection is checked. If the lifetime of the connection exceeds this property value, the connection is closed and disposed of. If this property value is 0, the connection lifetime is never checked. Connections that have exceeded their lifetimes are not closed and disposed of, if doing so brings the number of connections in the pool below the <code>Min Pool Size</code>.</p> | 0 |
| Connection Timeout | <p>Minimum time (in seconds) to wait for a free connection from the pool.</p> <p>This attribute specifies the minimum amount of time (in seconds) that the <code>Open()</code> method must take to obtain a pooled connection before it terminates the request. This value comes into effect only if no free connection is available from the connection pool and the <code>Max Pool Size</code> is reached. If a free connection is not available within the specified time, an exception is thrown. <code>Connection Timeout</code> does not limit the time required to open new connections.</p> <p>This attribute value takes effect for pooled connection requests and not for new connection requests.</p> <p>(The default value is 0 for the implicit database connection in a .NET stored procedure.)</p> | 15 |
| Context Connection | <p>Returns an implicit database connection if set to true.</p> <p>An implicit database connection can only be obtained from within a .NET stored procedure. Other connection string attributes cannot be used in conjunction with "context connection" when it is set to true.</p> <p><i>Supported in a .NET stored procedure only</i></p> | false |
| Data Source | <p>Oracle Net Services Name, Connect Descriptor, or an easy connect naming that identifies the database to which to connect.</p> | empty string |
| DBA Privilege | <p>Administrative privileges <code>SYSDBA</code> or <code>SYSOPER</code>.</p> <p>This connection string attribute only accepts <code>SYSDBA</code> or <code>SYSOPER</code> as the attribute value. It is case-insensitive.</p> | empty string |
| Decr Pool Size | <p>Number of connections that are closed when an excessive amount of established connections are unused.</p> <p>This connection string attribute controls the maximum number of unused connections that are closed when the pool regulator makes periodic checks. The regulator thread is spawned every 3 minutes and closes up to <code>Decr Pool Size</code> amount of pooled connections if they are not used. The pool regulator never takes the total number of connections below the <code>Min Pool Size</code> by closing pooled connections.</p> | 1 |

Table 6–31 (Cont.) Supported Connection String Attributes

| Connection String Attribute | Description | Default Value |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|
| Enlist | <p>Controls the enlistment behavior and capabilities of a connection in context of COM+ transactions or System.Transactions.</p> <p>If this attribute is set to <code>true</code>, the connection is automatically enlisted in the thread's transaction context. If this attribute is set to <code>false</code>, no enlistments are made. If this attribute is set to <code>dynamic</code>, applications can dynamically enlist in distributed transactions. This attribute can be set to <code>true</code>, <code>false</code>, <code>yes</code>, <code>no</code>, or <code>dynamic</code>.</p> | <code>true</code> |
| HA Events | <p>Enables ODP.NET connection pool to proactively remove connections from the pool when an Oracle database service, service member, or node goes down.</p> <p>This feature can be used with Global Data Services, including Oracle RAC, Data Guard, GoldenGate, and single instance deployments. "pooling=true" must also be set</p> <p>This attribute can be set to <code>true</code>, <code>false</code>, <code>yes</code>, or <code>no</code>.</p> | <code>false</code> |
| Load Balancing | <p>Enables ODP.NET connection pool to balance work requests across Oracle database instances based on the load balancing advisory and service goal.</p> <p>This feature can be used with Global Data Services, including Oracle RAC, Active Data Guard, and GoldenGate. "pooling=true" must also be set.</p> <p>This attribute can be set to <code>true</code>, <code>false</code>, <code>yes</code>, or <code>no</code>.</p> | <code>false</code> |
| Incr Pool Size | <p>Number of new connections to be created when all connections in the pool are in use.</p> <p>This connection string attribute determines the number of new connections that are established when a pooled connection is requested, but no unused connections are available and Max Pool Size is not reached. If new connections have been created for a pool, the regulator thread skips a cycle and does not have an opportunity to close any connections for 6 minutes. Note, however, that some connections can be still be closed during this time if their lifetime has been exceeded.</p> | 5 |
| Max Pool Size | <p>Maximum number of connections in a pool.</p> <p>This attribute specifies the maximum number of connections allowed in the particular pool used by that OracleConnection. Simply changing this attribute in the connection string does not change the Max Pool Size restriction on a currently existing pool. Doing so simply creates a new pool with a different Max Pool Size restriction. This attribute must be set to a value greater than the Min Pool Size. This value is ignored unless Pooling is turned on.</p> | 100 |
| Metadata Pooling | <p>Caches metadata information.</p> <p>This attribute indicates whether or not metadata information for executed queries are cached for improved performance.</p> | <code>True</code> |

Table 6–31 (Cont.) Supported Connection String Attributes

| Connection String Attribute | Description | Default Value |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| Min Pool Size | <p>Minimum number of connections in a pool.</p> <p>This attribute specifies the minimum number of connections to be maintained by the pool during its entire lifetime. Simply changing this attribute in the connection string does not change the <code>Min Pool Size</code> restriction on a currently existing pool. Doing so simply creates a new pool with a different <code>Min Pool Size</code> restriction. This value is ignored unless <code>Pooling</code> is turned on.</p> | 1 |
| Password | <p>Password for the user specified by <code>User Id</code>.</p> <p>This attribute specifies an Oracle user's password. <code>Password</code> is case-sensitive by default for Oracle Database 11g release 1 (11.1) and later.</p> | empty string |
| Persist Security Info | <p>Retrieval of the password in the connection string.</p> <p>If this attribute is set to <code>false</code>, the <code>Password</code> value setting is not returned when the application requests the <code>ConnectionString</code> after the connection is successfully opened by the <code>Open()</code> method. This attribute can be set to either <code>true</code>, <code>false</code>, <code>yes</code>, or <code>no</code>.</p> | false |
| Pooling | <p>Connection pooling.</p> <p>This attribute specifies whether or not connection pooling is to be used. Pools are created using an attribute value matching algorithm. This means that connection strings which only differ in the number of spaces in the connection string use the same pool. If two connection strings are identical except that one sets an attribute to a default value while the other does not set that attribute, both requests obtain connections from the same pool. This attribute can be set to either <code>true</code>, <code>false</code>, <code>yes</code>, or <code>no</code>.</p> | true |
| Promotable Transaction | <p>Promotable to distributed transaction or not.</p> <p>If "promotable" is specified, the first and all subsequent connections opened in the same <code>TransactionScope</code> enlist in the same distributed transaction. If "local" is specified, the first connection opened in the <code>TransactionScope</code> uses a local transaction.</p> | promotable |
| Proxy User Id | <p>User name of the proxy user.</p> <p>This connection string attribute specifies the middle-tier user, or the proxy user, who establishes a connection on behalf of a client user specified by the <code>User Id</code> attribute. ODP.NET attempts to establish a proxy connection if either the <code>Proxy User Id</code> or the <code>Proxy Password</code> attribute is set to a non-empty string.</p> <p>For the proxy user to connect to an Oracle database using operating system authentication, the <code>Proxy User Id</code> must be set to <code>"/</code>". The <code>Proxy Password</code> is ignored in this case. The <code>User Id</code> cannot be set to <code>"/</code>" when establishing proxy connections. The case of this attribute value is preserved.</p> | empty string |

Table 6–31 (Cont.) Supported Connection String Attributes

| Connection String Attribute | Description | Default Value |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| Proxy Password | <p>Password of the proxy user.</p> <p>This connection string attribute specifies the password of the middle-tier user or the proxy user. This user establishes a connection on behalf of a client user specified by the <code>User Id</code> attribute. ODP.NET attempts to establish a proxy connection if either the <code>Proxy User Id</code> or the <code>Proxy Password</code> attribute is set to a non-empty string.</p> <p>The case of this attribute value is preserved if it is surrounded by double quotes.</p> | empty string |
| Statement Cache Purge | <p>Statement cache purged when the connection goes back to the pool.</p> <p>If statement caching is enabled, setting this attribute to <code>true</code> purges the Statement Cache when the connection goes back to the pool.</p> | false |
| Statement Cache Size | <p>Statement cache enabled and cache size set size, that is, the maximum number of statements that can be cached.</p> <p>A value greater than zero enables statement caching and sets the cache size to itself.</p> <p>This value should not be greater than the value of the <code>OPEN_CURSORS</code> parameter set in the <code>init.ora</code> database configuration file.</p> | 0 |
| Self Tuning | <p>Enables or disables self-tuning for the connection.</p> <p>If self-tuning is enabled, then the <code>StatementCacheSize</code> settings in the registry, configuration files, and connection string are ignored.</p> <p>If self-tuning is disabled, then a <code>StatementCacheSize</code> value of 0 is used unless <code>StatementCachSize</code> is specified in the registry, configuration file, or connection string.</p> | true |
| User Id | <p>Oracle user name.</p> <p>This attribute specifies the Oracle user name. The case of this attribute value is preserved if it is surrounded by double quotes. For the user to connect to an Oracle database using operating system authentication, set the <code>User Id</code> to <code>"/</code>". Any <code>Password</code> attribute setting is ignored in this case.</p> | empty string |
| Validate Connection | <p>Validation of connections coming from the pool.</p> <p>Validation causes a round-trip to the database for each connection. Therefore, it should only be used when necessary.</p> | false |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

ConnectionTimeout

This property indicates the minimum amount of time that the `Open` method can take to obtain a pooled connection before the request is terminated.

Declaration

```
// C#  
public override int ConnectionTimeout {get;}
```

Property Value

The minimum time allowed for a pooled connection request, in seconds.

Implements

`IDbConnection`

Remarks

This property indicates the connection timeout that has been set using the `ConnectionString` attribute `Connection Timeout`.

This property is read-only.

Remarks (.NET Stored Procedure)

There is no connection string specified by the application and a connection on the implicit database is always available, therefore, this property is set to 0.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

ConnectionType

This property enables an ODP.NET application to determine whether a particular connection object is associated with an Oracle database connection, a TimesTen database connection, or no physical connection at all.

Declaration

```
// C#  
public OracleConnectionType ConnectionType {get;}
```

Property Value

The `OracleConnectionType` that this connection object is associated with.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- [OracleConnectionType Enumeration](#)

Database

This property is not supported.

Declaration

```
// C#  
public override string Database {get;}
```

Property Value

A string.

Implements

IDbConnection.Database

Remarks

This property is not supported. It always returns an empty string.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

DatabaseDomainName

This property specifies the name of the database domain that this connection is connected to.

Declaration

```
// C#  
public string DatabaseDomainName {get;}
```

Property Value

The database domain that this connection is connected to.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

DatabaseName

This property specifies the name of the database that this connection is connected to.

Declaration

```
// C#  
public string DatabaseName {get;}
```

Property Value

The database that this connection is connected to.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

DataSource

This property specifies the Oracle Net Services Name, Connect Descriptor, or an easy connect naming that identifies the database to which to connect

Declaration

```
// C#  
public override string DataSource {get;}
```

Property Value

Oracle Net Services Name, Connect Descriptor, or an easy connect naming that identifies the database to which to connect.

Remarks (.NET Stored Procedure)

The value of this property is always an empty string for the implicit database connection.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

HostName

This property specifies the name of the host that this connection is connected to.

Declaration

```
// C#  
public string HostName {get;}
```

Property Value

The host that this connection is connected to.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

InstanceName

This property specifies the name of the instance that this connection is connected to.

Declaration

```
// C#  
public string InstanceName {get;}
```

Property Value

The instance that this connection is connected to.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

LogicalTransactionId

This property provides the logical transaction ID that the connection is associated with.

Declaration

```
// C#  
public string LogicalTransactionId {get;}
```

Property Value

`LogicalTransactionId` returns a byte [] that represents the logical transaction id that is associated with the connection at the time of the invocation.

Remarks

`LogicalTransactionId` can then be used to get the status of the logical transaction by invoking `GetLogicalTransactionStatus` and passing the byte[] as an input parameter.

The return value is NULL if the database version is earlier than 12.1.

Only local transactions support using `LogicalTransactionId`. The property is not supported with distributed transactions.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

ModuleName

This property specifies the module name for the connection.

Declaration

```
// C#
```

```
public string ModuleName {set;}
```

Property Value

The string to be used as the module name.

Remarks

The default value is null.

Using the `ModuleName` property allows the application to set the module name in the application context for a given `OracleConnection` object.

The `ModuleName` property is reset to null when the `Close` or `Dispose` method is called on the `OracleConnection` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["Client Identifier and End-to-End Tracing"](#) on page 3-21
- *Oracle Database Security Guide*

OracleLogicalTransaction

This is a read-only property that returns an instance of an `OracleLogicalTransaction` object.

Declaration

```
// C#  
public string OracleLogicalTransaction {get;}
```

Property Value

An instance of an `OracleLogicalTransaction` object.

Remarks

The same `OracleLogicalTransaction` object is returned unless the logical transaction ID changes on that `OracleConnection` object.

This property will return `NULL` if the database server version is 11.2 or earlier

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- [OracleLogicalTransaction Class](#)

ServerVersion

This property specifies the version number of the Oracle database to which the `OracleConnection` has established a connection.

Declaration

```
// C#  
public override string ServerVersion {get;}
```

Property Value

The version of the Oracle database.

Exceptions

InvalidOperationException - The connection is closed.

Remarks

The default is an empty string.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

ServiceName

This property specifies the name of the service that this connection is connected to.

Declaration

```
// C#  
public string ServiceName {get;}
```

Property Value

The service that this connection is connected to.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

State

This property specifies the current state of the connection.

Declaration

```
// C#  
public override ConnectionState State {get;}
```

Property Value

The `ConnectionState` of the connection.

Implements

IDbConnection

Remarks

ODP.NET supports `ConnectionState.Closed` and `ConnectionState.Open` for this property. The default value is `ConnectionState.Closed`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

StatementCacheSize

This property specifies the current size of the statement cache associated with this connection.

Declaration

```
// C#  
public int StatementCacheSize{get;}
```

Property Value

An integer value indicating the size of the statement cache.

Remarks

If self tuning is not enabled, then the default value of this property depends upon the statement cache size specified in the connection string, application configuration file, or the registry. If none of these values are specified, then a default value of 0 is used.

If self tuning is enabled, then the property value is adjusted automatically. Any values specified in the connection string, application configuration file, or the registry are ignored.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

OracleConnection Public Methods

OracleConnection public methods are listed in [Table 6–32](#).

Table 6–32 OracleConnection Public Methods

| Public Method | Description |
|----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| BeginTransaction | Begins a local transaction (Overloaded) <i>Not supported in a .NET stored procedure for context connection</i> |
| ChangeDatabase | <i>Not Supported</i> |
| Clone | Creates a copy of an OracleConnection object <i>Not supported in a .NET stored procedure</i> |
| Close | Closes the database connection |
| CreateCommand | Creates and returns an OracleCommand object associated with the OracleConnection object |
| CreateObjRef | Inherited from System.MarshalByRefObject |
| Dispose | Inherited from System.ComponentModel.Component |
| EnlistDistributedTransaction | Enables applications to explicitly enlist in a specified distributed transaction <i>Not supported in a .NET stored procedure</i> |
| EnlistTransaction | Enables applications to enlist in a specified distributed transaction <i>Not supported in a .NET stored procedure</i> |
| Equals | Inherited from System.Object (Overloaded) |
| FlushCache | Flushes all updates and deletes made through REF objects retrieved using this connection <i>Not available in ODP.NET, Managed Driver</i> |
| GetHashCode | Inherited from System.Object |
| GetLifetimeService | Inherited from System.MarshalByRefObject |
| GetLogicalTransactionStatus | Returns the status of the current local transaction associated with the connection <i>Not available in the ODP.NET, Managed Driver</i> <i>This method has been deprecated in ODP.NET 12.1.0.2. It will be desupported in a future release.</i> |
| GetSchema | Returns schema information for the data source of the OracleConnection |
| GetSessionInfo | Returns or refreshes the property values of the OracleGlobalization object that represents the globalization settings of the session (Overloaded) |
| GetType | Inherited from System.Object |
| InitializeLifetimeService | Inherited from System.MarshalByRefObject |
| Open | Opens a database connection with the property settings specified by the ConnectionString |
| OpenWithNewPassword | Opens a new connection with the new password <i>Not supported in a .NET stored procedure for context connection</i> |

Table 6–32 (Cont.) OracleConnection Public Methods

| Public Method | Description |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| PurgeStatementCache | Flushes the Statement Cache by closing all open cursors on the database, when statement caching is enabled |
| SetSessionInfo | Alters the session's globalization settings with the property values provided by the <code>OracleGlobalization</code> object |
| <code>ToString</code> | Inherited from <code>System.Object</code> |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

BeginTransaction

`BeginTransaction` methods begin local transactions.

Overload List

- [BeginTransaction\(\)](#)
This method begins a local transaction.
- [BeginTransaction\(IsolationLevel\)](#)
This method begins a local transaction with the specified isolation level.

BeginTransaction()

This method begins a local transaction.

Declaration

```
// C#
public OracleTransaction BeginTransaction();
```

Return Value

An `OracleTransaction` object representing the new transaction.

Implements

`IDbConnection`

Exceptions

`InvalidOperationException` - A transaction has already been started.

Remarks

The transaction is created with its isolation level set to its default value of `IsolationLevel.ReadCommitted`. All further operations related to the transaction must be performed on the returned `OracleTransaction` object.

Remarks (.NET Stored Procedure)

Using this method in a .NET stored procedure for context connection causes a Not Supported exception.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

BeginTransaction(IsolationLevel)

This method begins a local transaction with the specified isolation level.

Declaration

```
// C#  
public OracleTransaction BeginTransaction(IsolationLevel isolationLevel);
```

Parameters

- *isolationLevel*

The isolation level for the new transaction.

Return Value

An OracleTransaction object representing the new transaction.

Implements

IDbConnection

Exceptions

InvalidOperationException - A transaction has already been started.

ArgumentException - The isolationLevel specified is invalid.

Remarks

The following isolation levels are supported: IsolationLevel.ReadCommitted and IsolationLevel.Serializable.

Although the BeginTransaction method supports the IsolationLevel.Serializable isolation level, serializable transactions are not supported when using System.Transactions and TransactionScope.

Requesting other isolation levels causes an exception.

Remarks (.NET Stored Procedure)

Using this method in a .NET stored procedure for context connection causes a Not Supported exception.

Example

```
// C#  
  
using System;  
using System.Data;  
using Oracle.DataAccess.Client;
```

```
class BeginTransactionSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Create an OracleCommand object using the connection object
        OracleCommand cmd = con.CreateCommand();

        // Start a transaction
        OracleTransaction txn = con.BeginTransaction(IsolationLevel.ReadCommitted);

        // Update EMP table
        cmd.CommandText = "update emp set sal = sal + 100";
        cmd.ExecuteNonQuery();

        // Rollback transaction
        txn.Rollback();
        Console.WriteLine("Transaction rolledback");

        // Clean up
        txn.Dispose();
        cmd.Dispose();
        con.Dispose();
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

ChangeDatabase

This method is not supported.

Declaration

```
// C#
public override void ChangeDatabase(string databaseName);
```

Parameters

- *databaseName*

The name of the database that replaces the current database name.

Implements

IDbConnection.ChangeDatabase

Exceptions

NotSupportedException - Method not supported.

Remarks

This method is not supported and throws a `NotSupportedException` if invoked.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

Clone

This method creates a copy of an `OracleConnection` object.

Declaration

```
// C#
public object Clone();
```

Return Value

An `OracleConnection` object.

Implements

`ICloneable`

Remarks

The cloned object has the same property values as that of the object being cloned.

Remarks (.NET Stored Procedure)

This method is not supported for an implicit database connection.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;

class CloneSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Need a proper casting for the return value when cloned
        OracleConnection clonedCon = (OracleConnection)con.Clone();

        // Cloned connection is always closed, regardless of its source,
        // But the connection string should be identical
        clonedCon.Open();
        if (clonedCon.ConnectionString.Equals(con.ConnectionString))
            Console.WriteLine("The connection strings are the same.");
        else
            Console.WriteLine("The connection strings are different.");
    }
}
```

```
// Close and Dispose OracleConnection object
clonedCon.Dispose();
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

Close

This method closes the connection to the database.

Declaration

```
// C#
public override void Close();
```

Implements

IDbConnection

Remarks

Performs the following:

- Rolls back any pending transactions.
- Places the connection to the connection pool if connection pooling is enabled. Even if connection pooling is enabled, the connection can be closed if it exceeds the connection lifetime specified in the connection string. If connection pooling is disabled, the connection is closed.
- Closes the connection to the database.

The connection can be reopened using `Open()`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

CreateCommand

This method creates and returns an `OracleCommand` object associated with the `OracleConnection` object.

Declaration

```
// C#
public OracleCommand CreateCommand();
```

Return Value

The `OracleCommand` object.

Implements

IDbConnection

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class CreateCommandSample
{
    static void Main()
    {
        // Connect
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Execute a SQL SELECT
        OracleCommand cmd = con.CreateCommand();
        cmd.CommandText = "select * from emp";
        OracleDataReader reader = cmd.ExecuteReader();

        // Print all employee numbers
        while (reader.Read())
            Console.WriteLine(reader.GetInt32(0));

        // Clean up
        reader.Dispose();
        cmd.Dispose();
        con.Dispose();
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

EnlistDistributedTransaction

This method enables applications to explicitly enlist in a specific distributed transaction after a connection has been opened.

Declaration

```
// C#
public void EnlistDistributedTransaction(ITransaction transaction);
```

Parameters

- *transaction*
An *ITransaction* interface.

Exceptions

`InvalidOperationException` - The connection is part of a local transaction or the connection is closed.

Remarks

`EnlistDistributedTransaction` enables objects to enlist in a specific transaction that is passed to the method. The `ITransaction` interface can be obtained by applying an (`ITransaction`) cast to the `ContextUtil.Transaction` property within the component that started the distributed transaction.

The connection must be open before calling this method or an `InvalidOperationException` is thrown.

If a connection is part of a local transaction that was started implicitly or explicitly while attempting to enlist in a distributed transaction, the local transaction is rolled back and an exception is thrown.

By default, distributed transactions roll back, unless the method-level `AutoComplete` declaration is set.

Invoking the commit on the `ITransaction` raises an exception.

Invoking the rollback on the `ITransaction` method and calling `ContextUtil.SetComplete` on the same distributed transaction raises an exception.

Remarks (.NET Stored Procedure)

Using this method causes a Not Supported exception.

Example**Application:**

```
// C#

/* This is the class that will utilize the Enterprise Services
   component. This module needs to be built as an executable.

   The Enterprise Services Component DLL must be built first
   before building this module.
   In addition, the DLL needs to be referenced appropriately
   when building this application.
*/

using System;
using System.EnterpriseServices;
using DistribTxnSample;

class DistribTxnSample_App
{
    static void Main()
    {
        {
            DistribTxnSample_Comp comp = new DistribTxnSample_Comp();
            comp.DoWork();
        }
    }
}
```

Component:

```
// C#

/* This module needs to be
```

```

1) built as a component DLL/Library
2) built with a strong name

This library must be built first before the application is built.
*/

using System;
using System.Data;
using Oracle.DataAccess.Client;
using System.EnterpriseServices;

namespace DistribTxnSample
{
    [Transaction(TransactionOption.RequiresNew)]
    public class DistribTxnSample_Comp : ServicedComponent
    {
        public void DoWork()
        {
            string constr =
                "User Id=scott;Password=tiger;Data Source=oracle;enlist=false";
            OracleConnection con = new OracleConnection(constr);
            con.Open();

            // Enlist in a distributed transaction
            con.EnlistDistributedTransaction((ITransaction)ContextUtil.Transaction);

            // Update EMP table
            OracleCommand cmd = con.CreateCommand();
            cmd.CommandText = "UPDATE emp set sal = sal + .01";
            cmd.ExecuteNonQuery();

            // Commit
            ContextUtil.SetComplete();

            // Dispose OracleConnection object
            con.Dispose();
        }
    }
}

```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["EnlistTransaction"](#) on page 6-115
- <http://msdn.microsoft.com/library> for detailed information about this Microsoft .NET Framework 1.1 feature

EnlistTransaction

This method enlists the connection to the specified transaction.

Declaration

```
// C#
```

```
public override void EnlistTransaction(Transaction transaction)
```

Parameters

- *transaction*
A `System.Transactions.Transaction` object.

Exceptions

`InvalidOperationException` - The connection is part of a local transaction or the connection is closed.

Remarks

Invocation of this method immediately enlists the connection to a transaction that is specified by the provided transaction parameter.

If `OracleConnection` is still associated with a distributed transaction that has not completed from a previous `EnlistTransaction` method invocation, calling this method will cause an exception to be thrown.

In general, for transaction enlistments to succeed, the "enlist" connection string attribute must be set to either "true" or "dynamic" before invoking the `Open` method. Setting the "enlist" connection string attribute to "true" will implicitly enlist the connection when the `Open` method is called, if the connection is within a transaction context. Setting it to "dynamic" allows the connection to dynamically enlist in transactions when an `EnlistTransaction` or `EnlistDistributedTransaction` method is called. The "enlist" attribute should be set to "false" only if the connection will never enlist in a transaction.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["System.Transactions and Promotable Transactions"](#) on page 3-32
- ["EnlistDistributedTransaction"](#) on page 6-113

FlushCache

This method flushes all updates and deletes made through `REF` objects retrieved using this connection.

Declaration

```
// c#  
public void FlushCache();
```

Exceptions

`InvalidOperationException` - The specified connection is not open.

Remarks

Before flushing objects, it is required that the application has explicitly started a transaction by executing the `BeginTransaction` method on the `OracleConnection` object. This is because if the object being flushed has not already been locked by the application, an exclusive lock is obtained implicitly for the object. The lock is only released when the transaction commits or rollbacks.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

GetLogicalTransactionStatus

This method on the already existing `OracleConnection` object returns the status of the current local transaction associated with the connection.

Declaration

```
// C#
public OracleLogicalTransactionStatus GetLogicalTransactionStatus(byte);
```

Return Value

The status of the current local transaction associated with the connection.

Exceptions

If this method is invoked on the same `OracleConnection` object from which the LTXID is obtained, an "ORA-14906: GetLTXID outcome operation is not permitted on the current session" exception will be thrown.

Remarks

This call returns a NULL if the LTXID is NULL or if the Oracle Database version is not greater than or equal to 12.1.

Example

```
// C#
// NOTE: User HR requires execution access on SYS.DBMS_APP_CONT for this demo.
// NOTE: The database service must be set with commit_outcome = true
// FIXME - show this example is used after a session loss

using System;
using Oracle.DataAccess.Client;

class TransactionGuardDemo
{
    static void Main(string[] args)
    {
        // Establish a connection to an Oracle database for checking the status
        string statusConStr = "user id=hr;password=hr;data source=oracle";
        OracleConnection statusCon = new OracleConnection(statusConStr);
        statusCon.Open();

        // Establish a connection to an Oracle database for the transaction
```

```
string txnConStr = "user id=hr;password=hr;data source=oracle";
OracleConnection txnCon = new OracleConnection(txnConStr);
txnCon.Open();

// Obtain the logical transaction id
byte[] logicalTransactionId = txnCon.LogicalTransactionId;

try
{
    // Begin a local transaction
    OracleTransaction txn = txnCon.BeginTransaction();

    // Do transactional work
    OracleCommand cmd = new OracleCommand("update employees set salary=salary+10
where employee_id=100", txnCon);
    cmd.ExecuteNonQuery();

    // Commit the transaction
    txn.Commit();
}
finally
{
    // Obtain the transaction status for the specified logical transaction id
    OracleLogicalTransactionStatus status =
        statusCon.GetLogicalTransactionStatus(logicalTransactionId);

    // Output the status of the logical transaction
    Console.WriteLine("Has the transaction been committed? " +
status.Committed);
    Console.WriteLine("Has the user call been completed? " +
status.UserCallCompleted);
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

GetSchema

GetSchema methods return schema information for the data source of the OracleConnection.

Overload List

- [GetSchema\(\)](#)

This method returns schema information for the data source of the OracleConnection.
- [GetSchema \(string collectionName\)](#)

This method returns schema information for the data source of the OracleConnection using the specified string for the collection name.
- [GetSchema \(string collectionName, string\[\] restrictions\)](#)

This method returns schema information for the data source of the OracleConnection using the specified string for the collection name and the specified string array for the restriction values.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

GetSchema()

This method returns schema information for the data source of the OracleConnection.

Declaration

```
// C#
public override DataTable GetSchema();
```

Return Value

A DataTable object.

Exceptions

InvalidOperationException – The connection is closed.

Remarks

This method returns a DataTable object that contains a row for each metadata collection available from the database.

The method is equivalent to specifying the String value "MetaDataCollections" when using the GetSchema(String) method.

Example

```
// C#

using System;
using System.Data;
using System.Data.Common;
using Oracle.DataAccess.Client;

class GetSchemaSample
{
    static void Main(string[] args)
    {
        string constr = "User Id=scott; Password=tiger; Data Source=oracle;";
        string ProviderName = "Oracle.DataAccess.Client";

        DbProviderFactory factory = DbProviderFactories.GetFactory(ProviderName);

        using (DbConnection conn = factory.CreateConnection())
        {
            try
            {
                conn.ConnectionString = constr;
                conn.Open();
            }
        }
    }
}
```

```
        //Get all the schema collections and write to an XML file.
        //The XML file name is Oracle.DataAccess.Client_Schema.xml
        DataTable dtSchema = conn.GetSchema();
        dtSchema.WriteXml(ProviderName + "_Schema.xml");
    }
    catch (Exception ex)
    {
        Console.WriteLine(ex.Message);
        Console.WriteLine(ex.StackTrace);
    }
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleConnection Class](#)
- [OracleConnection Members](#)

GetSchema (string collectionName)

This method returns schema information for the data source of the OracleConnection using the specified string for the collection name.

Declaration

```
// C#
public override DataTable GetSchema (string collectionName);
```

Parameters

collectionName

Name of the collection for which metadata is required.

Return Value

A DataTable object.

Exceptions

ArgumentException – The requested collection is not defined.

InvalidOperationException – The connection is closed.

InvalidOperationException – The requested collection is not supported by current version of Oracle database.

InvalidOperationException – No population string is specified for requested collection.

Example

```
// C#

using System;
using System.Data;
using System.Data.Common;
using Oracle.DataAccess.Client;
```



```
class GetSchemaSample
{
    static void Main(string[] args)
    {
        string constr = "User Id=scott; Password=tiger; Data Source=oracle;";
        string ProviderName = "Oracle.DataAccess.Client";

        DbProviderFactory factory = DbProviderFactories.GetFactory(ProviderName);

        using (DbConnection conn = factory.CreateConnection())
        {
            try
            {
                conn.ConnectionString = constr;
                conn.Open();

                //Get MetaDataCollections and write to an XML file.
                //This is equivalent to GetSchema()
                DataTable dtMetadata =
                    conn.GetSchema(DbMetaDataCollectionNames.MetaDataCollections);
                dtMetadata.WriteXml(ProviderName + "_MetaDataCollections.xml");

                //Get Restrictions and write to an XML file.
                DataTable dtRestrictions =
                    conn.GetSchema(DbMetaDataCollectionNames.Restrictions);
                dtRestrictions.WriteXml(ProviderName + "_Restrictions.xml");

                //Get DataSourceInformation and write to an XML file.
                DataTable dtDataSrcInfo =
                    conn.GetSchema(DbMetaDataCollectionNames.DataSourceInformation);
                dtDataSrcInfo.WriteXml(ProviderName + "_DataSourceInformation.xml");

                //data types and write to an XML file.
                DataTable dtDataTypes =
                    conn.GetSchema(DbMetaDataCollectionNames.DataTypes);
                dtDataTypes.WriteXml(ProviderName + "_DataTypes.xml");

                //Get ReservedWords and write to an XML file.
                DataTable dtReservedWords =
                    conn.GetSchema(DbMetaDataCollectionNames.ReservedWords);
                dtReservedWords.WriteXml(ProviderName + "_ReservedWords.xml");

                //Get all the tables and write to an XML file.
                DataTable dtTables = conn.GetSchema("Tables");
                dtTables.WriteXml(ProviderName + "_Tables.xml");

                //Get all the views and write to an XML file.
                DataTable dtViews = conn.GetSchema("Views");
                dtViews.WriteXml(ProviderName + "_Views.xml");

                //Get all the columns and write to an XML file.
                DataTable dtColumns = conn.GetSchema("Columns");
                dtColumns.WriteXml(ProviderName + "_Columns.xml");
            }
            catch (Exception ex)
            {
                Console.WriteLine(ex.Message);
                Console.WriteLine(ex.StackTrace);
            }
        }
    }
}
```

```
    }  
  }  
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

GetSchema (string collectionName, string[] restrictions)

This method returns schema information for the data source of the `OracleConnection` using the specified string for the collection name and the specified string array for the restriction values.

Declaration

```
// C#  
public override DataTable GetSchema (string collectionName,  
    string[] restrictions);
```

Parameters

- *collectionName*
The name of the collection of metadata being retrieved.
- *restrictions*
An array of restrictions that apply to the metadata being retrieved.

Return Value

A `DataTable` object.

Exception

- `ArgumentException` – The requested collection is not defined.
- `InvalidOperationException` – One of the following conditions exist:
 - The connection is closed.
 - The requested collection is not supported by the current version of Oracle database.
 - More restrictions were provided than the requested collection supports.
 - No population string is specified for requested collection.

Remarks

This method takes the name of a metadata collection and an array of `String` values that specify the restrictions for filtering the rows in the returned `DataTable`. This returns a `DataTable` that contains only rows from the specified metadata collection that match the specified restrictions.

For example, if the `Columns` collection has three restrictions (`owner`, `tablename`, and `columnname`), to retrieve all the columns for the `EMP` table regardless of schema, the `GetSchema` method must pass in at least these values: `null`, `EMP`.

If no restriction value is passed in, default values are used for that restriction, which is the same as passing in null. This differs from passing in an empty string for the parameter value. In this case, the empty string (" ") is considered the value for the specified parameter.

collectionName is not case-sensitive, but restrictions (string values) are.

Example

```
// C#

using System;
using System.Data;
using System.Data.Common;
using Oracle.DataAccess.Client;

class GetSchemaSample
{
    static void Main(string[] args)
    {
        string constr = "User Id=scott; Password=tiger; Data Source=oracle;";
        string ProviderName = "Oracle.DataAccess.Client";

        DbProviderFactory factory = DbProviderFactories.GetFactory(ProviderName);

        using (DbConnection conn = factory.CreateConnection())
        {
            try
            {
                conn.ConnectionString = constr;
                conn.Open();

                //Get Restrictions
                DataTable dtRestrictions =
                    conn.GetSchema(DbMetaDataCollectionNames.Restrictions);

                DataView dv = dtRestrictions.DefaultView;

                dv.RowFilter = "CollectionName = 'Columns'";
                dv.Sort = "RestrictionNumber";

                for (int i = 0; i < dv.Count; i++)
                    Console.WriteLine("{0} (default) {1}" ,
                        dtRestrictions.Rows[i]["RestrictionName"],
                        dtRestrictions.Rows[i]["RestrictionDefault"]);

                //Set restriction string array
                string[] restrictions = new string[3];

                //Get all columns from all tables owned by "SCOTT"
                restrictions[0] = "SCOTT";
                DataTable dtAllScottCols = conn.GetSchema("Columns", restrictions);

                // clear collection
                for (int i = 0; i < 3; i++)
                    restrictions[i] = null;

                //Get all columns from all tables named "EMP" owned by any
                //owner/schema
                restrictions[1] = "EMP";
                DataTable dtAllEmpCols = conn.GetSchema("Columns", restrictions);
            }
        }
    }
}
```

```
        // clear collection
        for (int i = 0; i < 3; i++)
            restrictions[i] = null;

        //Get columns named "EMPNO" from tables named "EMP",
        //owned by any owner/schema
        restrictions[1] = "EMP";
        restrictions[2] = "EMPNO";
        DataTable dtAllScottEmpCols = conn.GetSchema("Columns", restrictions);

        // clear collection
        for (int i = 0; i < 3; i++)
            restrictions[i] = null;

        //Get columns named "EMPNO" from all
        //tables, owned by any owner/schema
        restrictions[2] = "EMPNO";
        DataTable dtAllEmpNoCols = conn.GetSchema("Columns", restrictions);
    }
    catch (Exception ex)
    {
        Console.WriteLine(ex.Message);
        Console.WriteLine(ex.Source);
    }
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

GetSessionInfo

`GetSessionInfo` returns or refreshes an `OracleGlobalization` object that represents the globalization settings of the session.

Overload List:

- [GetSessionInfo\(\)](#)

This method returns a new instance of the `OracleGlobalization` object that represents the globalization settings of the session.

- [GetSessionInfo\(OracleGlobalization\)](#)

This method refreshes the provided `OracleGlobalization` object with the globalization settings of the session.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

GetSessionInfo()

This method returns a new instance of the `OracleGlobalization` object that represents the globalization settings of the session.

Declaration

```
// C#
public OracleGlobalization GetSessionInfo();
```

Return Value

The newly created `OracleGlobalization` object.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;

class GetSessionInfoSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Get session info from connection object
        OracleGlobalization info = con.GetSessionInfo();

        // Update session info
        info.DateFormat = "YYYY-MM-DD";
        con.SetSessionInfo(info);

        // Execute SQL SELECT
        OracleCommand cmd = con.CreateCommand();
        cmd.CommandText = "select TO_CHAR(hiredate) from emp";
        Console.WriteLine("Hire Date ({0}): {1}",
            info.DateFormat, cmd.ExecuteScalar());

        // Clean up
        cmd.Dispose();
        con.Dispose();
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

GetSessionInfo(OracleGlobalization)

This method refreshes the provided `OracleGlobalization` object with the globalization settings of the session.

Declaration

```
// C#  
public void GetSessionInfo(OracleGlobalization oraGlob);
```

Parameters

- *oraGlob*

The OracleGlobalization object to be updated.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

Open

This method opens a connection to an Oracle database.

Declaration

```
// C#  
public override void Open();
```

Implements

IDbConnection

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The connection is already opened or the connection string is null or empty.

Remarks

The connection is obtained from the pool if connection pooling is enabled. Otherwise, a new connection is established.

It is possible that the pool does not contain any unused connections when the `Open()` method is invoked. In this case, a new connection is established.

If no connections are available within the specified connection timeout value, when the Max Pool Size is reached, an `OracleException` is thrown.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

OpenWithNewPassword

This method opens a new connection with the new password.

Declaration

```
// C#
```

```
public void OpenWithNewPassword(string newPassword);
```

Parameters

- *newPassword*

A string that contains the new password.

Remarks

This method uses the `ConnectionString` property settings to establish a new connection. The old password must be provided in the connection string as the `Password` attribute value.

This method can only be called on an `OracleConnection` in the *closed* state.

Remarks (.NET Stored Procedure)

This method is not supported in a .NET stored procedure for context connection.

Note: If connection pooling is enabled, then invoking the `OpenWithNewPassword` method also clears the connection pool. This closes all idle connections created with the old password.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["Password Expiration"](#) on page 3-18

PurgeStatementCache

This method flushes the statement cache by closing all open cursors on the database, when statement caching is enabled.

Declaration

```
// C#  
public void PurgeStatementCache();
```

Remarks

Flushing the statement cache repetitively results in decreased performance and may negate the performance benefit gained by enabling the statement cache.

Statement caching remains enabled after the call to `PurgeStatementCache`.

Invocation of this method purges the cached cursors that are associated with the `OracleConnection`. It does not purge all the cached cursors in the database.

Example

```
// C#  
  
using System;  
using System.Data;  
using Oracle.DataAccess.Client;
```

```
class PurgeStatementCacheSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle;" +
            "Statement Cache Size=20";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleCommand cmd = new OracleCommand("select * from emp", con);
        cmd.CommandType = CommandType.Text;
        OracleDataReader reader = cmd.ExecuteReader();

        // Purge Statement Cache
        con.PurgeStatementCache();

        // Close and Dispose OracleConnection object
        Console.WriteLine("Statement Cache Flushed");
        con.Close();
        con.Dispose();
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["Statement Caching"](#) on page 3-48
- [ConnectionString](#) on page 6-94

SetSessionInfo

This method alters the session's globalization settings with all the property values specified in the provided `OracleGlobalization` object.

Declaration

```
// C#
public void SetSessionInfo(OracleGlobalization oraGlob);
```

Parameters

- *oraGlob*

An `OracleGlobalization` object.

Remarks

Calling this method is equivalent to calling an `ALTER SESSION SQL` on the session.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;
```



```
class SetSessionInfoSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Get session info from connection object
        OracleGlobalization info = con.GetSessionInfo();

        // Execute SQL SELECT
        OracleCommand cmd = con.CreateCommand();
        cmd.CommandText = "select TO_CHAR(hiredate) from emp";
        Console.WriteLine("Hire Date ({0}): {1}",
            info.DateFormat, cmd.ExecuteScalar());

        // Update session info
        info.DateFormat = "MM-DD-RR";
        con.SetSessionInfo(info);

        // Execute SQL SELECT again
        Console.WriteLine("Hire Date ({0}): {1}",
            info.DateFormat, cmd.ExecuteScalar());

        // Clean up
        cmd.Dispose();
        con.Dispose();
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

OracleConnection Events

OracleConnection events are listed in [Table 6–33](#).

Table 6–33 OracleConnection Events

| Event Name | Description |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Disposed | Inherited from <code>System.ComponentModel.Component</code> |
| Failover | An event that is triggered when an Oracle failover occurs <i>Not supported in a .NET stored procedure</i> <i>Not available in ODP.NET, Managed Driver</i> |
| HAEvent | An event that is triggered when an HA event occurs. |
| InfoMessage | An event that is triggered for any message or warning sent by the database |
| StateChange | An event that is triggered when the connection state changes |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)

Failover

This event is triggered when an Oracle failover occurs.

Declaration

```
// C#
public event OracleFailoverEventHandler Failover;
```

Event Data

The event handler receives an `OracleFailoverEventArgs` object which exposes the following properties containing information about the event.

- `FailoverType`
Indicates the type of the failover.
- `FailoverEvent`
Indicates the state of the failover.

Remarks

The `Failover` event is raised when a connection to an Oracle instance is unexpectedly severed. The client should create an `OracleFailoverEventHandler` delegate to listen to this event.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["OracleFailoverEventArgs Properties"](#) on page 11-7
- ["OracleFailoverEventHandler Delegate"](#) on page 11-10

HAEvent

This event is triggered when an HA event occurs.

Declaration

```
// C#  
public static event OracleHAEventHandler HAEvent;
```

Event Data

The event handler receives an `OracleHAEventArgs` object which exposes the following properties containing information about the event.

- `Source`
Indicates the source of the event.
- `Status`
Indicates the status of the event.
- `DatabaseName`
Indicates the database name affected by this event.
- `DatabaseDomainName`
Indicates the database domain name affected by this event.
- `HostName`
Indicates the host name affected by this event.
- `InstanceName`
Indicates the instance name affected by this event.
- `ServiceName`
Indicates the service name affected by this event.
- `Time`
Indicates the time of the event.

Remarks

The `HAEvent` is static, which means that any HA Events that happen within the application domain can trigger this event. Note that in order to receive HA event notifications, `OracleConnection` objects that establish connections within the application domain must have `"ha events=true"` in the application. Otherwise, the application never receives any HA Events.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["OracleHAEventArgs Properties"](#) on page 8-4
- ["OracleHAEventHandler Delegate"](#) on page 8-9

InfoMessage

This event is triggered for any message or warning sent by the database.

Declaration

```
// C#  
public event OracleInfoMessageEventHandler InfoMessage;
```

Event Data

The event handler receives an `OracleInfoMessageEventArgs` object which exposes the following properties containing information about the event.

- `Errors`
The collection of errors generated by the data source.
- `Message`
The error text generated by the data source.
- `Source`
The name of the object that generated the error.

Remarks

In order to respond to warnings and messages from the database, the client should create an `OracleInfoMessageEventHandler` delegate to listen to this event.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- ["OracleInfoMessageEventArgs Properties"](#) on page 6-298
- ["OracleInfoMessageEventHandler Delegate"](#) on page 6-301

StateChange

This event is triggered when the connection state changes.

Declaration

```
// C#  
public override event StateChangeEventHandler StateChange;
```

Event Data

The event handler receives a `StateChangeEventArgs` object which exposes the following properties containing information about the event.

- `CurrentState`
The new state of the connection.
- `OriginalState`
The original state of the connection.

Remarks

The `StateChange` event is raised after a connection changes state, whenever an explicit call is made to `Open`, `Close` or `Dispose`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnection Class](#)
- [OracleConnection Members](#)
- Microsoft ADO.NET documentation for a description of `StateChangeEventHandler`

OracleConnectionStringBuilder Class

An `OracleConnectionStringBuilder` object allows applications to create or modify connection strings.

Class Inheritance

`System.Object`

`System.Data.Common.DbConnectionStringBuilder`

`Oracle.DataAccess.Client.OracleConnectionStringBuilder`

Declaration

```
// C#
public sealed class OracleConnectionStringBuilder : DbConnectionStringBuilder
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|-----------------------|---------------------------------------|----------------------------------------------|
| Assembly | <code>Oracle.DataAccess.dll</code> | <code>Oracle.ManagedDataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Client</code> | <code>Oracle.ManagedDataAccess.Client</code> |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

The following rules must be followed for setting values with reserved characters:

- Values containing characters enclosed within single quotes

If the value contains characters that are enclosed within single quotation marks, then the entire value must be enclosed within double quotation marks.

For example, `password = "'scoTT' "` where the value is `'scoTT'`.
- Values containing characters enclosed within double quotes

Values should be enclosed in double quotation marks to preserve the case and to avoid the upper casing of values.

If the value contains characters enclosed in double quotation marks, then it must be enclosed in single quotation marks.

For example, `password = '"scoTT" '` where the value is `"scoTT"`.
- Values containing characters enclosed in both single and double quotes

If the value contains characters enclosed in both single and double quotation marks, the quotation mark used to enclose the value must be doubled each time it occurs within the value.

For example, `password = '"sco' 'TT" '` where the value is `"sco'TT"`.
- Values containing spaces

All leading and trailing spaces are ignored, but the spaces between the value are recognized. If the value needs to have leading or trailing spaces then it must be enclosed in double quotation marks.

For example, `User ID = Sco TT` where the value is `<Sco TT>`.

For example, `User ID = "Sco TT "` where the value is `<Sco TT>`.

5. Keywords occurring multiple times in a connection string

If a specific keyword occurs multiple times in a connection string, the last occurrence listed is used in the value set.

For example, with `"User ID = scott; password = tiger; User ID = david"` connection string, `User ID` value is `david`.

Example

```
// C#

using System;
using System.Data;
using System.Data.Common;
using Oracle.DataAccess.Client;
using System.Collections;

class ConnectionStringBuilderSample
{
    static void Main(string[] args)
    {
        bool bRet = false;

        // Create an instance of OracleConnectionStringBuilder
        OracleConnectionStringBuilder connStrBuilder =
            new OracleConnectionStringBuilder();

        // Add new key/value pairs to the connection string
        connStrBuilder.Add("User Id", "scott");
        connStrBuilder.Add("Password", "tiger");
        connStrBuilder.Add("Data Source", "oracle");
        connStrBuilder.Add("pooling", false);

        // Modify the existing value
        connStrBuilder["Data source"] = "inst1";

        // Remove an entry from the connection string
        bRet = connStrBuilder.Remove("pooling");

        //ContainsKey indicates whether or not the specific key exist
        //returns true even if the user has not specified it explicitly
        Console.WriteLine("Enlist exist: " +
            connStrBuilder.ContainsKey("Enlist"));

        //returns false
        connStrBuilder.ContainsKey("Invalid");

        // ShouldSerialize indicates whether or not a specific key
        // exists in connection string inherited from DbConnectionStringBuilder.
        // returns true if the key is explicitly added the user otherwise false;
        // this will return false as this key doesn't exist.
        connStrBuilder.ShouldSerialize("user");
    }
}
```

```
// returns false because this key is not added by user explicitly.
connStringBuilder.ShouldSerialize("Enlist");

// IsFixedSize [read-only property]
Console.WriteLine("Connection String is fixed size only: "
    + connStringBuilder.IsFixedSize);
Console.WriteLine("Key/Value Pair Count: " + connStringBuilder.Count);

//adding a new key which is not supported by the provider
//is not allowed.
try
{
    //this will throw an exception.
    connStringBuilder.Add("NewKey", "newValue");
}
catch (Exception ex)
{
    Console.WriteLine(ex.Message);
}

Console.WriteLine("Key/Value Pair Count: " + connStringBuilder.Count);

//modifying a existing key is allowed.
connStringBuilder.Add("Enlist", false);
Console.WriteLine("Key/Value Pair Count: " + connStringBuilder.Count);

// Get all the keys and values supported by the provider.
ICollection keyCollection = connStringBuilder.Keys;
ICollection valueCollection = connStringBuilder.Values;

IEnumerator keys = keyCollection.GetEnumerator();
IEnumerator values = valueCollection.GetEnumerator();

while (keys.MoveNext())
{
    values.MoveNext();
    Console.WriteLine("Key: {0}    Value: {1} \n"
        ,keys.Current ,values.Current);
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleConnectionStringBuilder Members](#)
- [OracleConnectionStringBuilder Constructors](#)
- [OracleConnectionStringBuilder Public Properties](#)
- [OracleConnectionStringBuilder Public Methods](#)

OracleConnectionStringBuilder Members

OracleConnectionStringBuilder members are listed in the following tables.

OracleConnectionStringBuilder Constructors

OracleConnectionStringBuilder constructors are listed in [Table 6–34](#).

Table 6–34 OracleConnectionStringBuilder Constructors

| Constructor | Description |
|------------------------------------------------------------|---------------------------------------------------------------------------------|
| OracleConnectionStringBuilder Constructors | Instantiates a new instance of OracleConnectionStringBuilder class (Overloaded) |

OracleConnectionStringBuilder Public Properties

OracleConnectionStringBuilder instance properties are listed in [Table 6–35](#).

Table 6–35 OracleConnectionStringBuilder Public Properties

| Properties | Description |
|------------------------------------|---------------------------------------------------------------------------------------------------------|
| BrowsableConnectionString | Inherited from System.Data.Common.DbConnectionStringBuilder |
| ConnectionLifeTime | Specifies the value corresponding to the Connection Lifetime attribute in the ConnectionString property |
| ConnectionString | Inherited from System.Data.Common.DbConnectionStringBuilder |
| ConnectionTimeout | Specifies the value corresponding to the Connection Timeout attribute in the ConnectionString property |
| ContextConnection | Specifies the value corresponding to the Context Connection attribute in the ConnectionString property |
| Count | Inherited from System.Data.Common.DbConnectionStringBuilder |
| DataSource | Specifies the value corresponding to the Data Source attribute in the ConnectionString property |
| DBAPrivilege | Specifies the value corresponding to the DBA Privilege attribute in the ConnectionString property |
| DecrPoolSize | Specifies the value corresponding to the Decr Pool Size attribute in the ConnectionString property |
| Enlist | Specifies the value corresponding to the Enlist attribute in the ConnectionString property |
| HAEvents | Specifies the value corresponding to the HA Events attribute in the ConnectionString property |
| IncrPoolSize | Specifies the value corresponding to the Incr Pool Size attribute in the ConnectionString property |
| IsFixedSize | Indicates whether or not the Connection String Builder has a fixed size |
| IsReadOnly | Inherited from System.Data.Common.DbConnectionStringBuilder |
| Item | Specifies the value associated with the specified attribute |
| Keys | Specifies a collection of attributes contained in the Connection String Builder |

Table 6–35 (Cont.) OracleConnectionStringBuilder Public Properties

| Properties | Description |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------|
| LoadBalancing | Specifies the value corresponding to the Load Balancing attribute in the ConnectionString property |
| MaxPoolSize | Specifies the value corresponding to the Max Pool Size attribute in the ConnectionString property |
| MetadataPooling | Specifies the value that corresponds to the Metadata Pooling attribute in the ConnectionString property |
| MinPoolSize | Specifies the value corresponding to the Min Pool Size attribute in the ConnectionString property |
| Password | Specifies the value corresponding to the Password attribute in the ConnectionString property |
| PersistSecurityInfo | Specifies the value corresponding to the Persist Security Info attribute in the ConnectionString property |
| Pooling | Specifies the value corresponding to the Pooling attribute in the ConnectionString property |
| PromotableTransaction | Specifies the value corresponding to the PromotableTransaction attribute in the ConnectionString property |
| ProxyPassword | Specifies the value corresponding to the Proxy User Id attribute in the ConnectionString property |
| ProxyUserId | Specifies the value corresponding to the Proxy User Id attribute in the ConnectionString property |
| SelfTuning | Specifies the value corresponding to the Self Tuning attribute in the ConnectionString property |
| StatementCachePurge | Specifies the value corresponding to the Statement Cache Purge attribute in the ConnectionString property |
| StatementCacheSize | Specifies the value corresponding to the Statement Cache Size attribute in the ConnectionString property |
| UserID | Specifies the value corresponding to the User Id attribute in the ConnectionString property |
| ValidateConnection | Specifies the value corresponding to the Validate Connection attribute in the ConnectionString property |
| Values | Specifies a collection of values contained in the Connection String Builder |

OracleConnectionStringBuilder Public Methods

OracleConnectionStringBuilder instance methods are listed in [Table 6–36](#).

Table 6–36 OracleConnectionStringBuilder Public Methods

| Methods | Description |
|------------------------------|------------------------------------------------------------------------------------------------|
| Add | Inherited from System.Data.Common.DbConnectionStringBuilder |
| Clear | Clears the connection string contents |
| ContainsKey | Indicates whether or not a specific attribute in the connection string is supported by ODP.NET |
| EquivalentTo | Inherited from System.Data.Common.DbConnectionStringBuilder |

Table 6–36 (Cont.) OracleConnectionStringBuilder Public Methods

| Methods | Description |
|-----------------------------|---------------------------------------------------------------------------------------|
| Remove | Removes the entry corresponding to the specified attribute from the connection string |
| ShouldSerialize | Inherited from System.Data.Common.DbConnectionStringBuilder |
| ToString | Inherited from System.Data.Common.DbConnectionStringBuilder |
| TryGetValue | Returns the value corresponding to the supplied attribute, as an output parameter |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)

OracleConnectionStringBuilder Constructors

OracleConnectionStringBuilder constructors instantiate new instances of the OracleConnectionStringBuilder class.

Overload List:

- [OracleConnectionStringBuilder\(\)](#)
This constructor instantiates a new instance of OracleConnectionStringBuilder class.
- [OracleConnectionStringBuilder\(string\)](#)
This constructor instantiates a new instance of the OracleConnectionStringBuilder class with the provided connection string.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

OracleConnectionStringBuilder()

This constructor instantiates a new instance of the OracleConnectionStringBuilder class.

Declaration

```
// C#  
public OracleConnectionStringBuilder();
```

Remarks

The `ConnectionString` property is empty after the object is created.

See Also: ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5

OracleConnectionStringBuilder(string)

This constructor instantiates a new instance of the OracleConnectionStringBuilder class with the provided connection string.

Declaration

```
// C#  
public OracleConnectionStringBuilder(string connectionString);
```

Parameters

- *connectionString*
The connection information.

Exceptions

`ArgumentNullException` - The *connectionString* parameter is null.

ArgumentException - The *connectionString* parameter is invalid.

Remarks

The `ConnectionString` property of this instance is set to the supplied connection string.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

OracleConnectionStringBuilder Public Properties

OracleConnectionStringBuilder public properties are listed in [Table 6–37](#).

Table 6–37 OracleConnectionStringBuilder Public Properties

| Properties | Description |
|------------------------------------|---------------------------------------------------------------------------------------------------------|
| BrowsableConnectionString | Inherited from System.Data.Common.DbConnectionStringBuilder |
| ConnectionLifeTime | Specifies the value corresponding to the Connection Lifetime attribute in the ConnectionString property |
| ConnectionString | Inherited from System.Data.Common.DbConnectionStringBuilder |
| ConnectionTimeout | Specifies the value corresponding to the Connection Timeout attribute in the ConnectionString property |
| ContextConnection | Specifies the value corresponding to the Context Connection attribute in the ConnectionString property |
| Count | Inherited from System.Data.Common.DbConnectionStringBuilder |
| DataSource | Specifies the value corresponding to the Data Source attribute in the ConnectionString property |
| DBAPrivilege | Specifies the value corresponding to the DBA Privilege attribute in the ConnectionString property |
| DecrPoolSize | Specifies the value corresponding to the Decr Pool Size attribute in the ConnectionString property |
| Enlist | Specifies the value corresponding to the Enlist attribute in the ConnectionString property |
| HAEvents | Specifies the value corresponding to the HA Events attribute in the ConnectionString property |
| IncrPoolSize | Specifies the value corresponding to the Incr Pool Size attribute in the ConnectionString property |
| IsFixedSize | Indicates whether or not the Connection String Builder has a fixed size |
| IsReadOnly | Inherited from System.Data.Common.DbConnectionStringBuilder |
| Item | Specifies the value associated with the specified attribute |
| Keys | Specifies a collection of attributes contained in the Connection String Builder |
| LoadBalancing | Specifies the value corresponding to the Load Balancing attribute in the ConnectionString property |
| MaxPoolSize | Specifies the value corresponding to the Max Pool Size attribute in the ConnectionString property |
| MetadataPooling | Specifies the value that corresponds to the Metadata Pooling attribute in the ConnectionString property |
| MinPoolSize | Specifies the value corresponding to the Min Pool Size attribute in the ConnectionString property |
| Password | Specifies the value corresponding to the Password attribute in the ConnectionString property |

Table 6–37 (Cont.) OracleConnectionStringBuilder Public Properties

| Properties | Description |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------|
| PersistSecurityInfo | Specifies the value corresponding to the Persist Security Info attribute in the ConnectionString property |
| Pooling | Specifies the value corresponding to the Pooling attribute in the ConnectionString property |
| PromotableTransaction | Specifies the value corresponding to the PromotableTransaction attribute in the ConnectionString property |
| ProxyPassword | Specifies the value corresponding to the Proxy User Id attribute in the ConnectionString property |
| ProxyUserId | Specifies the value corresponding to the Proxy User Id attribute in the ConnectionString property |
| SelfTuning | Specifies the value corresponding to the Self Tuning attribute in the ConnectionString property |
| StatementCachePurge | Specifies the value corresponding to the Statement Cache Purge attribute in the ConnectionString property |
| StatementCacheSize | Specifies the value corresponding to the Statement Cache Size attribute in the ConnectionString property |
| UserID | Specifies the value corresponding to the User Id attribute in the ConnectionString property |
| ValidateConnection | Specifies the value corresponding to the Validate Connection attribute in the ConnectionString property |
| Values | Specifies a collection of values contained in the Connection String Builder |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

ConnectionLifeTime

This property specifies the value corresponding to the Connection LifeTime attribute in the ConnectionString property.

Declaration

```
// C#
public int ConnectionLifeTime{get; set;}
```

Property Value

An int that represents the value of the supplied attribute.

Exceptions

OracleException - The specified value is less than zero.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

ConnectionTimeout

This property specifies the value corresponding to the `Connection Timeout` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public int ConnectionTimeout {get; set;}
```

Property Value

An `int` that represents the value of the supplied attribute.

Exceptions

`OracleException` - The specified value is less than zero.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

ContextConnection

This property specifies the value corresponding to the `Context Connection` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public bool ContextConnection {get; set;}
```

Property Value

A `bool` that represents the value of the supplied attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

DataSource

This property specifies the value corresponding to the Data Source attribute in the ConnectionString property.

Declaration

```
// C#  
public string DataSource{get; set;}
```

Property Value

A string that represents the value of the supplied attribute.

Exceptions

ArgumentNullException - The specified value is null.

Remarks

When an OracleConnectionStringBuilder instance is created, this property is set to the default value of the corresponding connection string attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

DBAPrivilege

This property specifies the value corresponding to the DBA Privilege attribute in the ConnectionString property.

Declaration

```
// C#  
public string DBAPrivilege{get; set;}
```

Property Value

A string that represents the value of the supplied attribute.

Possible values are SYSDBA or SYSOPER.

Exceptions

ArgumentNullException - The specified value is null.

OracleException - The specified value is invalid.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

DecrPoolSize

This property specifies the value corresponding to the `Decr Pool Size` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public int DecrPoolSize{get; set;}
```

Property Value

An `int` that represents the value of the supplied attribute.

Exceptions

`OracleException` - The specified value is less than 1.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

Enlist

This property specifies the value corresponding to the `Enlist` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public string Enlist{get; set;};
```

Property Value

A string that represents the value of the supplied attribute. Values are case-insensitive. Possible values are: `dynamic`, `true`, `false`, `yes`, and `no`.

Exceptions

`ArgumentNullException` - The specified value is null.

`OracleException` - The supplied value is not one of following: `dynamic`, `true`, `false`, `yes`, or `no`.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

HAEvents

This property specifies the value corresponding to the `HA Events` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public bool HAEvents{get; set;}
```

Property Value

A `bool` that represents the value of the supplied attribute.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

IncrPoolSize

This property specifies the value corresponding to the `Incr Pool Size` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public int IncrPoolSize{get; set;}
```

Property Value

An `int` that represents the value of the supplied attribute.

Exceptions

`OracleException` - The specified value is less than 1.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

IsFixedSize

Indicates whether or not the Connection String Builder has a fixed size.

Declaration

```
// C#  
public override bool IsFixedSize{get;}
```

Property Value

Returns `true` if the Connection String Builder has a fixed size; otherwise, returns `false`.

Remarks

Attributes cannot be added or removed. They can only be modified for connection strings with a fixed size.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

Item

This property specifies the value associated with the specified attribute.

Declaration

```
// C#  
public override object this[string keyword]{get; set;}
```

Property Value

An object value corresponding to the attribute.

Exceptions

`ArgumentNullException` - The specified attribute is null.

OracleException - The specified attribute is not supported or the specified value is invalid.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

Keys

This property specifies a collection of attributes contained in the Connection String Builder.

Declaration

```
// C#  
public override ICollection Keys{get;}
```

Property Value

Returns an `ICollection` that represents the attributes in the Connection String Builder.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

LoadBalancing

This property specifies the value corresponding to the Load Balancing attribute in the `ConnectionString` property.

Declaration

```
// C#  
public bool LoadBalancing {get; set;}
```

Property Value

A `bool` that contains the value of the supplied attribute.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

MaxPoolSize

This property specifies the value corresponding to the Max Pool Size attribute in the `ConnectionString` property.

Declaration

```
// C#  
public int MaxPoolSize{get; set;}
```

Property Value

An `int` that represents the value of the supplied attribute.

Exceptions

`OracleException` - The specified value is less than 1.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

MetadataPooling

This property specifies the value that corresponds to the Metadata Pooling attribute in the `ConnectionString` property.

Declaration

```
// C#  
public bool MetadataPooling{get; set;};
```

Property Value

A `bool` containing the value of the supplied attribute.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

MinPoolSize

This property specifies the value corresponding to the `Min Pool Size` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public int MinPoolSize{get; set;}
```

Property Value

An `int` that contains the value of the supplied attribute.

Exceptions

`OracleException` - The specified value is less than 0.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

Password

This property specifies the value corresponding to the `Password` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public string Password{get; set;}
```

Property Value

A `string` that contains the value of the supplied attribute.

Exception

`ArgumentNullException` - The specified value is null.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

PersistSecurityInfo

This property specifies the value corresponding to the `Persist Security Info` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public bool PersistSecurityInfo{get; set;}
```

Property Value

A `bool` that represents the value of the supplied attribute.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property gets set to the default value of the corresponding connection string attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

Pooling

This property specifies the value corresponding to the `Pooling` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public bool Pooling {get; set;}
```

Property Value

A `bool` that represents the value of the supplied attribute.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

PromotableTransaction

This property specifies the value corresponding to the `PromotableTransaction` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public string PromotableTransaction {get; set;}
```

Property Value

A `string` that represents the value of the supplied attribute

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

ProxyPassword

This property specifies the value corresponding to the Proxy Password attribute in the ConnectionString property.

Declaration

```
// C#  
public string ProxyPassword {get; set;}
```

Property Value

A string that represents the value of the supplied attribute.

Exception

ArgumentNullException - The specified value is null.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

ProxyUserId

This property specifies the value corresponding to the Proxy User Id attribute in the ConnectionString property.

Declaration

```
// C#  
public string ProxyUserId {get; set;}
```

Property Value

A string that represents the value of the supplied attribute.

Exception

ArgumentNullException - The specified value is null.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

SelfTuning

This property specifies the value corresponding to the `Self Tuning` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public bool SelfTuning {get; set;}
```

Property Value

A `bool` that represents the value of the supplied attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

StatementCachePurge

This property specifies the value corresponding to the `Statement Cache Purge` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public bool StatementCachePurge {get; set;}
```

Property Value

A `bool` that represents the value of the supplied attribute.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

StatementCacheSize

This property specifies the value corresponding to the `Statement Cache Size` attribute in the `ConnectionString` property.

Declaration

```
// C#  
public int StatementCacheSize{get; set;}
```

Property Value

An int that represents the value of the supplied attribute.

Exceptions

OracleException - The specified value is less than zero.

Remarks

When an OracleConnectionStringBuilder instance is created, this property is set to the default value of the corresponding connection string attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

UserID

This property specifies the value corresponding to the User Id attribute in the ConnectionString property.

Declaration

```
// C#  
public string UserID{get; set;}
```

Property Value

A string that represents the value of the supplied attribute.

Exception

ArgumentNullException - The specified value is null.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

ValidateConnection

This property specifies the value corresponding to the Validate Connection attribute in the ConnectionString property.

Declaration

```
// C#  
public bool ValidateConnection{get; set;}
```

Property Value

A bool that represents the value of the supplied attribute.

Remarks

When an `OracleConnectionStringBuilder` instance is created, this property is set to the default value of the corresponding connection string attribute.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

Values

This property specifies a collection of values contained in the Connection String Builder.

Declaration

```
// C#  
public override ICollection Values{get;}
```

Property Value

Returns an `ICollection` that represents the values in the Connection String Builder.

Remarks

The order of the values in the `ICollection` is unspecified, but is the same as the associated attributes in the `ICollection` returned by the `Keys` property.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

OracleConnectionStringBuilder Public Methods

OracleConnectionStringBuilder public methods are listed in [Table 6–38](#).

Table 6–38 OracleConnectionStringBuilder Public Methods

| Methods | Description |
|-----------------------------|------------------------------------------------------------------------------------------------|
| Add | Inherited from System.Data.Common.DbConnectionStringBuilder |
| Clear | Clears the connection string contents |
| ContainsKey | Indicates whether or not a specific attribute in the connection string is supported by ODP.NET |
| EquivalentTo | Inherited from System.Data.Common.DbConnectionStringBuilder |
| Remove | Removes the entry corresponding to the specified attribute from the connection string |
| ShouldSerialize | Inherited from System.Data.Common.DbConnectionStringBuilder |
| ToString | Inherited from System.Data.Common.DbConnectionStringBuilder |
| TryGetValue | Returns the value corresponding to the supplied attribute, as an output parameter |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

Clear

This method clears the connection string contents.

Declaration

```
// C#
public override void Clear();
```

Remarks

All key/value pairs are removed from the OracleConnectionStringBuilder object and the ConnectionString property is set to Empty.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

ContainsKey

This method indicates whether or not a specific attribute in the connection string is supported by ODP.NET.

Declaration

```
// C#  
public override bool ContainsKey(string keyword);
```

Parameters

- *keyword*
The attribute being verified.

Return Value

Returns `true` if the specified attribute exists; otherwise, returns `false`.

Exceptions

`ArgumentNullException` - The specified attribute is null.

Remarks

This method indicates if the attribute is part of the provider-supported attributes. It does not indicate if the user added the attribute to the connection string.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

Remove

This method removes the entry corresponding to the specified attribute from the connection string.

Declaration

```
// C#  
public override bool Remove(string keyword);
```

Parameters

- *keyword*
The attribute that specifies the entry to be removed.

Return Value

Returns `true` if the attribute existed in the connection string and the corresponding entry was removed; otherwise, returns `false`.

Exceptions

`ArgumentNullException` - The specified attribute is null.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

TryGetValue

This method returns the value corresponding to the supplied attribute, as an output parameter.

Declaration

```
// C#  
public override bool TryGetValue(string keyword, out object value);
```

Parameters

- *keyword*
The attribute for which the value is being retrieved.
- *value*
The value of the supplied attribute.
Sets *value* to the default value if the attribute is not present in the connection string.

Return Value

Returns *true* if the value that corresponds to the attribute has been successfully retrieved; otherwise, returns *false*. If the attribute is not present in the connection string, returns *false* and sets the *value* to null.

Exceptions

ArgumentNullException - The specified attribute is null.

Remarks

If the function returns *false*, sets *value* to null.

If the attribute is not present in the connection string, sets *value* to the default value.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleConnectionStringBuilder Class](#)
- [OracleConnectionStringBuilder Members](#)

OracleDataAdapter Class

An `OracleDataAdapter` object represents a data provider object that populates the `DataSet` and updates changes in the `DataSet` to the Oracle database.

Class Inheritance

`System.Object`

`System.MarshalByRefObject`

`System.ComponentModel.Component`

`System.Data.Common.DataAdapter`

`System.Data.Common.DbDataAdapter`

`Oracle.DataAccess.Client.OracleDataAdapter`

Declaration

```
// C#
public sealed class OracleDataAdapter : DbDataAdapter, IDbDataAdapter
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

The following example uses the `OracleDataAdapter` and the dataset to update the EMP table:

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class OracleDataAdapterSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        string cmdstr = "SELECT empno, sal from emp";

        // Create the adapter with the selectCommand txt and the
        // connection string
        OracleDataAdapter adapter = new OracleDataAdapter(cmdstr, constr);

        // Create the builder for the adapter to automatically generate
```



```
// the Command when needed
OracleCommandBuilder builder = new OracleCommandBuilder(adapter);

// Create and fill the DataSet using the EMP
DataSet dataset = new DataSet();
adapter.Fill(dataset, "EMP");

// Get the EMP table from the dataset
DataTable table = dataset.Tables["EMP"];

// Indicate DataColumn EMPNO is unique
// This is required by the OracleCommandBuilder to update the EMP table
table.Columns["EMPNO"].Unique = true;

// Get the first row from the EMP table
DataRow row = table.Rows[0];

// Update the salary
double sal = double.Parse(row["SAL"].ToString());
row["SAL"] = sal + .01;

// Now update the EMP using the adapter
// The OracleCommandBuilder will create the UpdateCommand for the
// adapter to update the EMP table
adapter.Update(dataset, "EMP");

Console.WriteLine("Row updated successfully");
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataAdapter Members](#)
- [OracleDataAdapter Constructors](#)
- [OracleDataAdapter Static Methods](#)
- [OracleDataAdapter Properties](#)
- [OracleDataAdapter Public Methods](#)
- [OracleDataAdapter Events](#)

OracleDataAdapter Members

OracleDataAdapter members are listed in the following tables.

OracleDataAdapter Constructors

OracleDataAdapter constructors are listed in [Table 6–39](#).

Table 6–39 OracleDataAdapter Constructors

| Constructor | Description |
|------------------------------------------------|---------------------------------------------------------------------|
| OracleDataAdapter Constructors | Instantiates a new instance of OracleDataAdapter class (Overloaded) |

OracleDataAdapter Static Methods

The OracleDataAdapter static method is listed in [Table 6–40](#).

Table 6–40 OracleDataAdapter Static Method

| Method | Description |
|------------------------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

OracleDataAdapter Properties

OracleDataAdapter properties are listed in [Table 6–41](#).

Table 6–41 OracleDataAdapter Properties

| Property | Description |
|---------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AcceptChangesDuringFill | Inherited from System.Data.Common.DataAdapter |
| Container | Inherited from System.ComponentModel.Component |
| ContinueUpdateOnError | Inherited from System.Data.Common.DataAdapter |
| DeleteCommand | A SQL statement or stored procedure to delete rows from an Oracle database |
| IdentityInsert | Determines whether or not to insert identity column values in the DataSet into the database when the Update method is invoked. <i>Not available in the ODP.NET, Managed Driver</i> |
| IdentityUpdate | Determines whether or not to update identity column values in the DataSet into the database when the Update method is invoked. <i>Not available in the ODP.NET, Managed Driver</i> |
| InsertCommand | A SQL statement or stored procedure to insert new rows into an Oracle database |
| MissingMappingAction | Inherited from System.Data.Common.DataAdapter |
| MissingSchemaAction | Inherited from System.Data.Common.DataAdapter |
| Requery | Determines whether or not the SelectCommand is reexecuted on the next call to Fill |
| ReturnProviderSpecificTypes | Determines if the Fill method returns ODP.NET-specific values or .NET common language specification values |

Table 6–41 (Cont.) OracleDataAdapter Properties

| Property | Description |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SafeMapping | Creates a mapping between column names in the result set to .NET types, to preserve the data <i>Not available in the ODP.NET, Managed Driver</i> |
| SelectCommand | A SQL statement or stored procedure that returns a single or multiple result set |
| Site | Inherited from System.ComponentModel.Component |
| TableMappings | Inherited from System.Data.Common.DataAdapter |
| UpdateBatchSize | Specifies a value that enables or disables batch processing support, and specifies the number of SQL statements that can be executed in a single round-trip to the database |
| UpdateCommand | A SQL statement or stored procedure to update rows from the DataSet to an Oracle database |

OracleDataAdapter Public Methods

OracleDataAdapter public methods are listed in [Table 6–42](#).

Table 6–42 OracleDataAdapter Public Methods

| Public Method | Description |
|---------------------------|---------------------------------------------------------------------------------------------|
| CreateObjRef | Inherited from System.MarshalByRefObject |
| Dispose | Inherited from System.ComponentModel.Component |
| Equals | Inherited from System.Object (Overloaded) |
| Fill | Adds or refreshes rows in the DataSet to match the data in the Oracle database (Overloaded) |
| FillSchema | Inherited from System.Data.Common.DbDataAdapter |
| GetFillParameters | Inherited from System.Data.Common.DbDataAdapter |
| GetHashCode | Inherited from System.Object |
| GetLifetimeService | Inherited from System.MarshalByRefObject |
| GetType | Inherited from System.Object |
| InitializeLifetimeService | Inherited from System.MarshalByRefObject |
| ToString | Inherited from System.Object |
| Update | Inherited from System.Data.Common.DbDataAdapter |

OracleDataAdapter Events

OracleDataAdapter events are listed in [Table 6–43](#).

Table 6–43 OracleDataAdapter Events

| Event Name | Description |
|------------|-------------------------------------------------|
| Disposed | Inherited from System.ComponentModel.Component |
| FillError | Inherited from System.Data.Common.DbDataAdapter |

Table 6–43 (Cont.) OracleDataAdapter Events

| Event Name | Description |
|-----------------------------|----------------------------------------------------------------------------------------|
| RowUpdated | This event is raised when row(s) have been updated by the <code>Update()</code> method |
| RowUpdating | This event is raised when row data are about to be updated to the database |

OracleDataAdapter Constructors

OracleDataAdapter constructors create new instances of an OracleDataAdapter class.

Overload List:

- [OracleDataAdapter\(\)](#)

This constructor creates an instance of an OracleDataAdapter class.

- [OracleDataAdapter\(OracleCommand\)](#)

This constructor creates an instance of an OracleDataAdapter class with the provided OracleCommand as the SelectCommand.

- [OracleDataAdapter\(string, OracleConnection\)](#)

This constructor creates an instance of an OracleDataAdapter class with the provided OracleConnection object and the command text for the SelectCommand.

- [OracleDataAdapter\(string, string\)](#)

This constructor creates an instance of an OracleDataAdapter class with the provided connection string and the command text for the SelectCommand.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

OracleDataAdapter()

This constructor creates an instance of an OracleDataAdapter class with no arguments.

Declaration

```
// C#
public OracleDataAdapter();
```

Remarks

Initial values are set for the following OracleDataAdapter properties as indicated:

- `MissingMappingAction = MissingMappingAction.Passthrough`
- `MissingSchemaAction = MissingSchemaAction.Add`

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

OracleDataAdapter(OracleCommand)

This constructor creates an instance of an OracleDataAdapter class with the provided OracleCommand as the SelectCommand.

Declaration

```
// C#  
public OracleDataAdapter(OracleCommand selectCommand);
```

Parameters

- *selectCommand*

The `OracleCommand` that is to be set as the `SelectCommand` property.

Remarks

Initial values are set for the following `OracleDataAdapter` properties as indicated:

- `MissingMappingAction = MissingMappingAction.Passthrough`
- `MissingSchemaAction = MissingSchemaAction.Add`

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

OracleDataAdapter(string, OracleConnection)

This constructor creates an instance of an `OracleDataAdapter` class with the provided `OracleConnection` object and the command text for the `SelectCommand`.

Declaration

```
// C#  
public OracleDataAdapter(string selectCommandText, OracleConnection  
    selectConnection);
```

Parameters

- *selectCommandText*

The string that is set as the `CommandText` of the `SelectCommand` property of the `OracleDataAdapter`.

- *selectConnection*

The `OracleConnection` to connect to the Oracle database.

Remarks

The `OracleDataAdapter` opens and closes the connection, if it is not already open. If the connection is open, it must be explicitly closed.

Initial values are set for the following `OracleDataAdapter` properties as indicated:

- `MissingMappingAction = MissingMappingAction.Passthrough`
- `MissingSchemaAction = MissingSchemaAction.Add`

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

OracleDataAdapter(string, string)

This constructor creates an instance of an `OracleDataAdapter` class with the provided connection string and the command text for the `SelectCommand`.

Declaration

```
// C#  
public OracleDataAdapter(string selectCommandText, string  
    selectConnectionString);
```

Parameters

- *selectCommandText*
The string that is set as the `CommandText` of the `SelectCommand` property of the `OracleDataAdapter`.
- *selectConnectionString*
The connection string.

Remarks

Initial values are set for the following `OracleDataAdapter` properties as indicated:

- `MissingMappingAction = MissingMappingAction.Passthrough`
- `MissingSchemaAction = MissingSchemaAction.Add`

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

OracleDataAdapter Static Methods

The `OracleDataAdapter` static method is listed in [Table 6-44](#).

Table 6-44 *OracleDataAdapter Static Method*

| Method | Description |
|---------------------|--------------------------------------------------------|
| <code>Equals</code> | Inherited from <code>System.Object</code> (Overloaded) |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

OracleDataAdapter Properties

OracleDataAdapter properties are listed in [Table 6–45](#).

Table 6–45 OracleDataAdapter Properties

| Property | Description |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AcceptChangesDuringFill | Inherited from <code>System.Data.Common.DataAdapter</code> |
| Container | Inherited from <code>System.ComponentModel.Component</code> |
| ContinueUpdateOnError | Inherited from <code>System.Data.Common.DataAdapter</code> |
| DeleteCommand | A SQL statement or stored procedure to delete rows from an Oracle database |
| IdentityInsert | Determines whether or not to insert identity column values in the <code>DataSet</code> into the database when the <code>Update</code> method is invoked. <i>Not available in the ODP.NET, Managed Driver</i> |
| IdentityUpdate | Determines whether or not to update identity column values in the <code>DataSet</code> into the database when the <code>Update</code> method is invoked. <i>Not available in the ODP.NET, Managed Driver</i> |
| InsertCommand | A SQL statement or stored procedure to insert new rows into an Oracle database |
| MissingMappingAction | Inherited from <code>System.Data.Common.DataAdapter</code> |
| MissingSchemaAction | Inherited from <code>System.Data.Common.DataAdapter</code> |
| Requery | Determines whether or not the <code>SelectCommand</code> is reexecuted on the next call to <code>Fill</code> |
| ReturnProviderSpecificTypes | Determines if the <code>Fill</code> method returns ODP.NET-specific values or .NET common language specification values |
| SafeMapping | Creates a mapping between column names in the result set to .NET types, to preserve the data <i>Not Available in ODP.NET, Managed Driver</i> |
| SelectCommand | A SQL statement or stored procedure that returns a single or multiple result set |
| Site | Inherited from <code>System.ComponentModel.Component</code> |
| TableMappings | Inherited from <code>System.Data.Common.DataAdapter</code> |
| UpdateBatchSize | Specifies a value that enables or disables batch processing support, and specifies the number of SQL statements that can be executed in a single round-trip to the database |
| UpdateCommand | A SQL statement or stored procedure to update rows from the <code>DataSet</code> to an Oracle database |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

DeleteCommand

This property is a SQL statement or stored procedure to delete rows from an Oracle database.

Declaration

```
// C#  
public OracleCommand DeleteCommand {get; set;}
```

Property Value

An `OracleCommand` used during the `Update` call to delete rows from tables in the Oracle database, corresponding to the deleted rows in the `DataSet`.

Remarks

Default = null

If there is primary key information in the `DataSet`, the `DeleteCommand` can be automatically generated using the `OracleCommandBuilder`, if no command is provided for this.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

IdentityInsert

When inserting `DataSet` data into the database, this property indicates whether the database generates the inserted row's identity column value or `DataSet` supplies this value.

Declaration

```
// C#  
public bool IdentityInsert {get; set;}
```

Property Value

When set to `true`, ODP.NET inserts `DataSet` identity column values into the database. When set to `false`, the database determines the inserted identity column values.

Remarks

This property applies only to identity columns of type `GENERATED BY DEFAULT` and `GENERATED BY DEFAULT ON NULL`. Identity column of type `GENERATED ALWAYS` will ignore this property and will always use database generated values.

When set to `false`, the server will generate an identity value for the row. That generated identity value returns back to the client to update the `DataSet` value.

When this property is set to `true` for the `GENERATED BY DEFAULT` case and the application attempts to insert a `NULL` value into the database's identity column, the `NOT NULL` constraint is violated and an error occurs. ODP.NET will then allow the database to generate the identity column value and return the generated value to the `DataSet`.

The default value for this property is `false`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- [OracleIdentityType Enumeration](#)

IdentityUpdate

When updating DataSet data into the database, this property indicates whether to replace the database's identity column values with values of the DataSet or leave the current values unchanged.

Declaration

```
// C#  
public bool IdentityUpdate {get; set;}
```

Property Value

When set to true, ODP.NET updates the database identity column values with the values of the DataSet. When set to false, the database identity columns are left unchanged.

Remarks

This property applies only to identity columns of type `GENERATED BY DEFAULT` and `GENERATED BY DEFAULT ON NULL`. In the case of type `GENERATED ALWAYS`, this property will be ignored and the database will always retain its current identity values.

When set to false, the existing identity column value in the server is returned to the DataSet.

When this property is set to true for the `GENERATED BY DEFAULT` and `GENERATED BY DEFAULT ON NULL` cases and the application attempts to update the database's identity column with a NULL value, the `NOT NULL` constraint is violated and an error occurs. ODP.NET then does not update the identity column value and instead returns the existing identity column value of the database to the DataSet.

The default value for this property is false.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- [OracleIdentityType Enumeration](#)

InsertCommand

This property is a SQL statement or stored procedure to insert new rows into an Oracle database.

Declaration

```
// C#  
public OracleCommand InsertCommand {get; set;}
```

Property Value

An `OracleCommand` used during the `Update` call to insert rows into a table, corresponding to the inserted rows in the `DataSet`.

Remarks

Default = null

If there is primary key information in the `DataSet`, the `InsertCommand` can be automatically generated using the `OracleCommandBuilder`, if no command is provided for this property.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

Requery

This property determines whether or not the `SelectCommand` is reexecuted on the next call to `Fill`.

Declaration

```
// C#  
public Boolean Requery {get; set;}
```

Property Value

Returns true if the `SelectCommand` is reexecuted on the next call to `Fill`; otherwise, returns false.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleDataAdapter Requery Property"](#) on page 3-122

ReturnProviderSpecificTypes

This property determines if the `Fill` method returns ODP.NET-specific values or .NET common language specification compliant values.

Declaration

```
// C#  
public Boolean ReturnProviderSpecificTypes {get; set;}
```

Property Value

A value that indicates whether or not the `Fill` method returns ODP.NET-specific values.

Starting with ODP.NET 12.1.0.2, when set to true and `LegacyEntireLOBFetch = 0` (default), BLOB and CLOB column values are represented in the `DataTable` as `OracleBlob` and `OracleClob`, respectively.

A value of false indicates that the `Fill` method returns .NET common language specification compliant values.

The default is false.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

SafeMapping

This property creates a mapping between column names in the result set to .NET types that represent column values in the `DataSet`, to preserve the data.

Declaration

```
// C#
public Hashtable SafeMapping {get; set;}
```

Property Value

A hash table.

Remarks

Default = null

The `SafeMapping` property is used, when necessary, to preserve data in the following types:

- DATE
- `TimeStamp` (refers to all `TimeStamp` objects)
- INTERVAL DAY TO SECOND
- NUMBER

Example

See the example in ["OracleDataAdapter Safe Type Mapping"](#) on page 3-119.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleDataAdapter Safe Type Mapping"](#) on page 3-119

SelectCommand

This property is a SQL statement or stored procedure that returns single or multiple result sets.

Declaration

```
// C#  
public OracleCommand SelectCommand {get; set;}
```

Property Value

An `OracleCommand` used during the `Fill` call to populate the selected rows to the `DataSet`.

Remarks

Default = null

If the `SelectCommand` does not return any rows, no tables are added to the dataset and no exception is raised.

If the `SELECT` statement selects from a `VIEW`, no key information is retrieved when a `FillSchema()` or a `Fill()` with `MissingSchemaAction.AddWithKey` is invoked.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleDataAdapter Requery Property"](#) on page 3-122

UpdateBatchSize

This property specifies a value that enables or disables batch processing support, and specifies the number of SQL statements that can be executed in a single round-trip to the database.

Declaration

```
// C#  
public virtual int UpdateBatchSize {get; set;}
```

Property Value

An integer that returns the batch size.

Exceptions

`ArgumentOutOfRangeException` - The value is set to a number < 0.

Remarks

Update batches executed with large amounts of data may encounter an "PLS-00123: Program too large" error. To avoid this error, reduce the size of `UpdateBatchSize` to a smaller value.

For each row in the `DataSet` that has been modified, added, or deleted, one SQL statement will be executed on the database.

Values are as follows:

- Value = 0
The data adapter executes all the SQL statements in a single database round-trip
- Value = 1 - Default value

This value disables batch updating and SQL statements are executed one at a time.

- Value = n where $n > 1$

The data adapter updates n rows of data per database round-trip.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["Batch Processing"](#) on page 3-48

UpdateCommand

This property is a SQL statement or stored procedure to update rows from the DataSet to an Oracle database.

Declaration

```
// C#  
public OracleCommand UpdateCommand {get; set;}
```

Property Value

An OracleCommand used during the Update call to update rows in the Oracle database, corresponding to the updated rows in the DataSet.

Remarks

Default = null

If there is primary key information in the DataSet, the UpdateCommand can be automatically generated using the OracleCommandBuilder, if no command is provided for this property.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleDataAdapter Requery Property"](#) on page 3-122

OracleDataAdapter Public Methods

OracleDataAdapter public methods are listed in [Table 6–46](#).

Table 6–46 OracleDataAdapter Public Methods

| Public Method | Description |
|---------------------------|---------------------------------------------------------------------------------------------|
| CreateObjRef | Inherited from System.MarshalByRefObject |
| Dispose | Inherited from System.ComponentModel.Component |
| Equals | Inherited from System.Object (Overloaded) |
| Fill | Adds or refreshes rows in the DataSet to match the data in the Oracle database (Overloaded) |
| FillSchema | Inherited from System.Data.Common.DbDataAdapter |
| GetFillParameters | Inherited from System.Data.Common.DbDataAdapter |
| GetHashCode | Inherited from System.Object |
| GetLifetimeService | Inherited from System.MarshalByRefObject |
| GetType | Inherited from System.Object |
| InitializeLifetimeService | Inherited from System.MarshalByRefObject |
| ToString | Inherited from System.Object |
| Update | Inherited from System.Data.Common.DbDataAdapter |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

Fill

Fill populates or refreshes the specified DataTable or DataSet.

Overload List:

- [Fill\(DataTable, OracleRefCursor\)](#)
This method adds or refreshes rows in the specified DataTable to match those in the provided OracleRefCursor object.
- [Fill\(DataSet, OracleRefCursor\)](#)
This method adds or refreshes rows in the DataSet to match those in the provided OracleRefCursor object.
- [Fill\(DataSet, string, OracleRefCursor\)](#)
This method adds or refreshes rows in the specified source table of the DataSet to match those in the provided OracleRefCursor object.
- [Fill\(DataSet, int, int, string, OracleRefCursor\)](#)
This method adds or refreshes rows in a specified range in the DataSet to match rows in the provided OracleRefCursor object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

Fill(DataTable, OracleRefCursor)

This method adds or refreshes rows in the specified `DataTable` to match those in the provided `OracleRefCursor` object.

Declaration

```
// C#  
public int Fill(DataTable dataTable, OracleRefCursor refCursor);
```

Parameters

- `dataTable`
The `DataTable` object being populated.
- `refCursor`
The `OracleRefCursor` that rows are being retrieved from.

Return Value

The number of rows added to or refreshed in the `DataTable`.

Exceptions

`ArgumentNullException` - The `dataTable` or `refCursor` parameter is null.

`InvalidOperationException` - The `OracleRefCursor` is already being used to fetch data.

`NotSupportedException` - The `SafeMapping` type is not supported.

Remarks

No schema or key information is provided, even if the `Fill` method is called with `MissingSchemaAction` set to `MissingSchemaAction.AddWithKey`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleDataAdapter Requery Property"](#) on page 3-122

Fill(DataSet, OracleRefCursor)

This method adds or refreshes rows in the `DataSet` to match those in the provided `OracleRefCursor` object.

Declaration

```
// C#
```

```
public int Fill(DataSet dataSet, OracleRefCursor refCursor);
```

Parameters

- *dataSet*
The DataSet object being populated.
- *refCursor*
The OracleRefCursor that rows are being retrieved from.

Return Value

Returns the number of rows added or refreshed in the DataSet.

Exceptions

ArgumentNullException - The *dataSet* or *refCursor* parameter is null.

InvalidOperationException - The OracleRefCursor is already being used to fetch data.

InvalidOperationException - The OracleRefCursor is ready to fetch data.

NotSupportedException - The SafeMapping type is not supported.

Remarks

If there is no DataTable to refresh, a new DataTable named Table is created and populated using the provided OracleRefCursor object.

No schema or key information is provided, even if the Fill method is called with MissingSchemaAction set to MissingSchemaAction.AddWithKey.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleDataAdapter Requery Property"](#) on page 3-122

Fill(DataSet, string, OracleRefCursor)

This method adds or refreshes rows in the specified source table of the DataSet to match those in the provided OracleRefCursor object.

Declaration

```
// C#  
public int Fill(DataSet dataSet, string srcTable, OracleRefCursor  
    refCursor);
```

Parameters

- *dataSet*
The DataSet object being populated.
- *srcTable*
The name of the source table used in the table mapping.
- *refCursor*

The `OracleRefCursor` that rows are being retrieved from.

Return Value

Returns the number of rows added or refreshed into the `DataSet`.

Exceptions

`ArgumentNullException` - The `dataSet` or `refCursor` parameter is null.

`InvalidOperationException` - The `OracleRefCursor` is already being used to fetch data or the source table name is invalid.

`NotSupportedException` - The `SafeMapping` type is not supported.

Remarks

No schema or key information is provided, even if the `Fill` method is called with `MissingSchemaAction` set to `MissingSchemaAction.AddWithKey`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleDataAdapter Requery Property"](#) on page 3-122

Fill(DataSet, int, int, string, OracleRefCursor)

This method adds or refreshes rows in a specified range in the `DataSet` to match rows in the provided `OracleRefCursor` object.

Declaration

```
// C#
public int Fill(DataSet dataSet, int startRecord, int maxRecords,
    string srcTable, OracleRefCursor refCursor);
```

Parameters

- `dataSet`
The `DataSet` object being populated.
- `startRecord`
The record number to start with.
- `maxRecords`
The maximum number of records to obtain.
- `srcTable`
The name of the source table used in the table mapping.
- `refCursor`
The `OracleRefCursor` that rows are being retrieved from.

Return Value

This method returns the number of rows added or refreshed in the `DataSet`. This does not include rows affected by statements that do not return rows.

Exceptions

`ArgumentNullException` - The `dataSet` or `refCursor` parameter is null.

`InvalidOperationException` - The `OracleRefCursor` is already being used to fetch data or the source table name is invalid.

`NotSupportedException` - The `SafeMapping` type is not supported.

Remarks

No schema or key information is provided, even if the `Fill` method is called with `MissingSchemaAction` set to `MissingSchemaAction.AddWithKey`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleDataAdapter Requery Property"](#) on page 3-122

OracleDataAdapter Events

OracleDataAdapter events are listed in [Table 6–47](#).

Table 6–47 OracleDataAdapter Events

| Event Name | Description |
|-----------------------------|----------------------------------------------------------------------------------------|
| Disposed | Inherited from <code>System.ComponentModel.Component</code> |
| FillError | Inherited from <code>System.Data.Common.DbDataAdapter</code> |
| RowUpdated | This event is raised when row(s) have been updated by the <code>Update()</code> method |
| RowUpdating | This event is raised when row data are about to be updated to the database |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)

RowUpdated

This event is raised when row(s) have been updated by the `Update()` method.

Declaration

```
// C#
public event OracleRowUpdatedEventHandler RowUpdated;
```

Event Data

The event handler receives an `OracleRowUpdatedEventArgs` object which exposes the following properties containing information about the event.

- `Command`
The `OracleCommand` executed during the `Update`.
- `Errors` (inherited from `RowUpdatedEventArgs`)
The exception, if any, is generated during the `Update`.
- `RecordsAffected` (inherited from `RowUpdatedEventArgs`)
The number of rows modified, inserted, or deleted by the execution of the `Command`.
- `Row` (inherited from `RowUpdatedEventArgs`)
The `DataRow` sent for `Update`.
- `StatementType` (inherited from `RowUpdatedEventArgs`)
The type of SQL statement executed.
- `Status` (inherited from `RowUpdatedEventArgs`)
The `UpdateStatus` of the `Command`.
- `TableMapping` (inherited from `RowUpdatedEventArgs`)

The DataTableMapping used during the Update.

Example

The following example shows how to use the RowUpdating and RowUpdated events.

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class RowUpdatedSample
{
    // Event handler for RowUpdating event
    protected static void OnRowUpdating(object sender,
                                        OracleRowUpdatingEventArgs e)
    {
        Console.WriteLine("Row updating....");
        Console.WriteLine("Event arguments:");
        Console.WriteLine("Command Text: " + e.Command.CommandText);
        Console.WriteLine("Command Type: " + e.StatementType);
        Console.WriteLine("Status: " + e.Status);
    }

    // Event handler for RowUpdated event
    protected static void OnRowUpdated(object sender,
                                       OracleRowUpdatedEventArgs e)
    {
        Console.WriteLine("Row updated....");
        Console.WriteLine("Event arguments:");
        Console.WriteLine("Command Text: " + e.Command.CommandText);
        Console.WriteLine("Command Type: " + e.StatementType);
        Console.WriteLine("Status: " + e.Status);
    }

    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        string cmdstr = "SELECT EMPNO, ENAME, SAL FROM EMP";

        // Create the adapter with the selectCommand txt and the
        // connection string
        OracleDataAdapter adapter = new OracleDataAdapter(cmdstr, constr);

        // Create the builder for the adapter to automatically generate
        // the Command when needed
        OracleCommandBuilder builder = new OracleCommandBuilder(adapter);

        // Create and fill the DataSet using the EMP
        DataSet dataset = new DataSet();
        adapter.Fill(dataset, "EMP");

        // Get the EMP table from the dataset
        DataTable table = dataset.Tables["EMP"];

        // Indicate DataColumn EMPNO is unique
        // This is required by the OracleCommandBuilder to update the EMP table
        table.Columns["EMPNO"].Unique = true;

        // Get the first row from the EMP table
```

```

        DataRow row = table.Rows[0];

        // Update the salary
        double sal = double.Parse(row["SAL"].ToString());
        row["SAL"] = sal + .01;

        // Set the event handlers for the RowUpdated and the RowUpdating event
        // the OnRowUpdating() method will be triggered before the update, and
        // the OnRowUpdated() method will be triggered after the update
        adapter.RowUpdating += new OracleRowUpdatingEventHandler(OnRowUpdating);
        adapter.RowUpdated += new OracleRowUpdatedEventHandler(OnRowUpdated);

        // Now update the EMP using the adapter
        // The OracleCommandBuilder will create the UpdateCommand for the
        // adapter to update the EMP table
        // The OnRowUpdating() and the OnRowUpdated() methods will be triggered
        adapter.Update(dataset, "EMP");
    }
}

```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleRowUpdatedEventHandler Delegate"](#) on page 6-398

RowUpdating

This event is raised when row data are about to be updated to the database.

Declaration

```

// C#
public event OracleRowUpdatingEventHandler RowUpdating;

```

Event Data

The event handler receives an `OracleRowUpdatingEventArgs` object which exposes the following properties containing information about the event.

- **Command**
The `OracleCommand` executed during the Update.
- **Errors (inherited from `RowUpdatingEventArgs`)**
The exception, if any, is generated during the Update.
- **Row (inherited from `RowUpdatingEventArgs`)**
The `DataRow` sent for Update.
- **StatementType (inherited from `RowUpdatingEventArgs`)**
The type of SQL statement executed.
- **Status (inherited from `RowUpdatingEventArgs`)**
The `UpdateStatus` of the Command.
- **TableMapping (inherited from `RowUpdatingEventArgs`)**

The `DataTableMapping` used during the Update.

Example

The example for the `RowUpdated` event also shows how to use the `RowUpdating` event. See `RowUpdated` event ["Example"](#) on page 6-182.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataAdapter Class](#)
- [OracleDataAdapter Members](#)
- ["OracleRowUpdatingEventHandler Delegate"](#) on page 6-406

OracleDatabase Class

An OracleDatabase object represents an Oracle Database instance.

Class Inheritance

System.Object

Oracle.DataAccess.Client.OracleDatabase

Declaration

```
// C#
public sealed class OracleDatabase : IDisposable
```

Requirements

| | |
|-----------------------|----------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | Oracle.DataAccess.dll |
| Namespace | Oracle.DataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;

namespace Startup
{
    class Test
    {
        static void Main()
        {
            OracleConnection con = null;
            OracleDatabase db = null;
            string constring = "dba privilege=sysdba;user id=scott;password=tiger;data
source=oracle";

            try
            {
                // Open a connection to see if the DB is up
                con = new OracleConnection(constring);
                con.Open();

                Console.WriteLine("The Oracle database is already up.");
            }
            catch (OracleException ex)
            {
                // If the database is down, start up the DB
                if (ex.Number == 1034)
```

```
{
    Console.WriteLine("The Oracle database is down.");

    // Create an instance of an OracleDatabase object
    db = new OracleDatabase(constring);

    // Start up the database
    db.Startup();

    Console.WriteLine("The Oracle database is now up.");

    // Executing Startup() is the same as the following:
    // db.Startup(OracleDBStartupMode.NoRestriction, null, true);
    // which is also the same as:
    // db.Startup(OracleDBStartupMode.NoRestriction, null, false);
    // db.ExecuteNonQuery("ALTER DATABASE MOUNT");
    // db.ExecuteNonQuery("ALTER DATABASE OPEN");

    // Dispose the OracleDatabase object
    db.Dispose();
}
else
{
    Console.WriteLine("Error: " + ex.Message);
}
}
finally
{
    // Dispose the OracleConnetion object
    con.Dispose();
}
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDatabase Members](#)
- [OracleDatabase Constructor](#)
- [OracleDatabase Properties](#)
- [OracleDatabase Public Methods](#)

OracleDatabase Members

OracleDatabase members are listed in the following tables.

OracleDatabase Constructors

The OracleDatabase constructor is listed in [Table 6-48](#).

Table 6-48 OracleDatabase Constructors

| Constructor | Description |
|--------------------------------------------|------------------------------------------------------------------------------------------|
| OracleDatabase Constructor | Instantiates a new instance of OracleDatabase class using the supplied connection string |

OracleDatabase Properties

The OracleDatabase properties are listed in [Table 6-49](#).

Table 6-49 OracleDatabase Properties

| Property | Description |
|-------------------------------|-------------------------------------------------------------------------------------------------------|
| ServerVersion | Specifies the database version number of the Oracle Database instance to which the connection is made |

OracleDatabase Public Methods

The OracleDatabase public methods are listed in [Table 6-50](#).

Table 6-50 OracleDatabase Public Methods

| Public Method | Description |
|---------------------------------|-----------------------------------------------------------------|
| Dispose | Releases any resources or memory allocated by the object. |
| ExecuteNonQuery | Executes the supplied non-SELECT statement against the database |
| Shutdown | Shuts down the database (Overloaded) |
| Startup | Starts up the database (Overloaded) |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDatabase Class](#)

OracleDatabase Constructor

The `OracleDatabase` constructor instantiates a new instance of the `OracleDatabase` class using the supplied connection string.

Declaration

```
// C#  
public OracleDatabase(String connectionString);
```

Parameters

- *connectionString*

The connection information used to connect to the Oracle Database instance.

Remarks

The *connectionString* follows the same format used by the `OracleConnection` object. However, the `OracleDatabase` constructor accepts only the `user id`, `password`, `data source`, and `dba privilege` connection string attributes. All other attribute values are ignored. The supplied *connectionString* must contain the `dba privilege` connection string attribute that is set to either `SYSDBA` or `SYSOPER`.

The `OracleDatabase` object creates a connection upon construction and remains connected throughout its lifetime. The connection is destroyed when the `OracleDatabase` object is disposed. This connection is not pooled to be used by another `OracleDatabase` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)

OracleDatabase Properties

The OracleDatabase properties are listed in [Table 6–51](#).

Table 6–51 OracleDatabase Properties

| Property | Description |
|-------------------------------|-------------------------------------------------------------------------------------------------------|
| ServerVersion | Specifies the database version number of the Oracle Database instance to which the connection is made |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)

ServerVersion

This property returns the database version number of the Oracle Database instance to which the connection is made.

Declaration

```
Public string ServerVersion {get;}
```

Property value

Returns the database version of the Oracle Database instance.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)

OracleDatabase Public Methods

The OracleDatabase public methods are listed in [Table 6–52](#).

Table 6–52 OracleDatabase Public Methods

| Public Method | Description |
|---------------------------------|-----------------------------------------------------------------|
| Dispose | Releases any resources or memory allocated by the object. |
| ExecuteNonQuery | Executes the supplied non-SELECT statement against the database |
| Shutdown | Shuts down the database (Overloaded) |
| Startup | Starts up the database (Overloaded) |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)

Dispose

This method releases any resources or memory allocated by the object.

Declaration

```
// C#
public void Dispose();
```

Implements

IDisposable

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)

ExecuteNonQuery

This method executes the supplied non-SELECT statement against the database.

Declaration

```
// C#
public void ExecuteNonQuery(string sql);
```

Exceptions

OracleException - The command execution has failed.

Remarks

This method is meant for execution of DDL statements such as ALTER DATABASE statements to OPEN and MOUNT the database, for example. This method should not be used to execute SQL SELECT statements. This method does not support any parameter binding.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)

Shutdown

Shutdown methods shut down a database instance.

Overload List

- [Shutdown\(\)](#)

This method shuts down the database.

- [Shutdown\(OracleDBShutdownMode, bool\)](#)

This method shuts down the database using the specified mode.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)
- ["OracleDBShutdownMode Enumeration"](#) on page 6-424

Shutdown()

This method shuts down the database.

Declaration

```
// C#
public void Shutdown();
```

Exceptions

OracleException - The database shutdown request has failed.

Remarks

This method shuts down a database instance in the OracleDBShutdownMode.Default mode. New connections are refused, and the method waits for the existing connections to end.

Note: As the shutdown is effected using the OracleDBShutdownMode.Default mode, the shutdown request may remain pending if there are open connections other than the connection created by the OracleDatabase object.

After the connections have closed, the method closes the database, dismounts the database, and shuts down the instance using the `OracleDBShutdownMode.Final` mode.

This method does not throw exceptions for cases where the database has been already closed, dismounted, or shutdown appropriately. If other errors are encountered, then an exception is thrown.

Invoking this method against an Oracle Real Application Clusters (Oracle RAC) database shuts down only that database instance to which the `OracleDatabase` object is connected.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)
- ["OracleDBShutdownMode Enumeration"](#) on page 6-424

Shutdown(OracleDBShutdownMode, bool)

This method shuts down the database instance using the specified mode.

Declaration

```
//C#  
public void Shutdown(OracleDBShutdownMode shutdownMode, bool  
bCloseDismountAndFinalize);
```

Parameters

- *shutdownMode*
A `OracleDBShutdownMode` enumeration value.
- *bCloseDismountAndFinalize*
A boolean signifying whether the database is to be closed, dismounted, and finalized.

Exceptions

`OracleException` - The database shutdown request has failed.

Remarks

This method shuts down a database instance in the specified mode. If the *bCloseDismountAndFinalize* parameter is `true`, then the method also closes the database, dismounts the database, and shuts down the instance using the `OracleDBShutdownMode.Final` mode.

If the *bCloseDismountAndFinalize* parameter is `true`, then this method does not throw exceptions for cases where the database has been already closed, dismounted, or shutdown appropriately. If other errors are encountered, then an exception is thrown.

If the *bCloseDismountAndFinalize* parameter is `false`, then the application needs to explicitly close and dismount the database. The application can then reinvoke the method using the `OracleDBShutdownMode.Final` mode to properly shut down the database. For example, if `db` is an instance of the `OracleDatabase` class, then the application invokes the following:

1. `db.Shutdown(OracleDBShutdownMode.Default, false);`
2. `db.ExecuteNonQuery("ALTER DATABASE CLOSE NORMAL");`
3. `db.ExecuteNonQuery("ALTER DATABASE DISMOUNT");`
4. `db.Shutdown(OracleDBShutdownMode.Final);`

Note:

- The `OracleDBShutdownMode.Final` enumeration value should not be used as the `shutdownMode` for the initial method invocation. The `OracleDBShutdownMode.Final` mode should be used only if the database is already closed and dismantled. Otherwise, the method might wait indefinitely.
 - If the specified `shutdownMode` is `OracleDBShutdownMode.Final`, then the value of the `bCloseDismountAndFinalize` input parameter is ignored, as the database should have been closed and dismantled already.
-
-

If the specified `shutdownMode` is `OracleDBShutdownMode.Abort`, then the value of the `bCloseDismountAndFinalize` input parameter is ignored, as the `Abort` mode requires the database to be closed, dismantled, and finalized.

Invoking this method against an Oracle Real Application Clusters (Oracle RAC) database shuts down only that database instance to which the `OracleDatabase` object is connected.

Example

```
using System;
using Oracle.DataAccess.Client;

namespace Shutdown
{
    class Test
    {
        static void Main()
        {
            OracleConnection con = null;
            OracleDatabase db = null;
            string constring = "user id=scott;password=tiger;data source=oracle;" +
                "pooling=false;dba privilege=sysdba";

            try
            {
                // Open a connection to see if the DB is up;
                con = new OracleConnection(constring);
                con.Open();

                Console.WriteLine("The Oracle database is currently up.");

                // If open succeeds, we know that the database is up.
                // We have to dispose the connection so that we can
                // shutdown the database.
                con.Dispose();

                // Shutdown the database
                db = new OracleDatabase(constring);
            }
        }
    }
}
```

```
db.Shutdown();

Console.WriteLine("The Oracle database is shut down.");

// Executing Shutdown() above is the same as the following:
// db.Shutdown(OracleDBShutdownMode.Default, false);
// db.ExecuteNonQuery("ALTER DATABASE CLOSE NORMAL");
// db.ExecuteNonQuery("ALTER DATABASE DISMOUNT");
// db.Shutdown(OracleDBShutdownMode.Final);

// Dispose the OracleDatabase object
db.Dispose();
}
catch (OracleException ex)
{
    Console.WriteLine("An error has occurred: {0}", ex.Message);
}
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)
- ["OracleDBShutdownMode Enumeration"](#) on page 6-424

Startup

Startup methods enable a user with database administrator privileges to start a database instance.

Overload List

- [Startup\(\)](#)
This method starts a database instance using the server-side parameter file.
- [Startup\(OracleDBStartupMode, string, bool\)](#)
This method starts a database instance using the client-side parameter file.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)
- ["OracleDBStartupMode Enumeration"](#) on page 6-425

Startup()

This method starts up the database.

Declaration

```
// C#
```

```
public void Startup();
```

Exceptions

OracleException - The database startup request has failed.

Remarks

This method starts a database instance in the `OracleDbStartupMode.Normal` mode using the server-side parameter file (`spfile`). After the database is successfully started, this method also executes the `ALTER DATABASE MOUNT` and `ALTER DATABASE OPEN` statements.

This method does not throw exceptions for cases where the database is already mounted, opened, or started appropriately. If other errors are encountered, then an exception is thrown.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)
- ["OracleDBStartupMode Enumeration"](#) on page 6-425

Startup(OracleDBStartupMode, string, bool)

This method starts up the database using the specified startup mode.

Declaration

```
// C#
public void Startup(OracleDbStartupMode startupMode, string pfile, bool
bMountAndOpen);
```

Parameters

- *startupMode*
An `OracleDBStartupMode` enumeration value.
- *pfile*
The location and name of the client-side parameter file. For example, "c:\admin\init.ora".

The name of the parameter file varies depending on the operating system. For example, it can be in mixed case or lowercase, or it can have a logical name or a variation of the name `init.ora`. The default location is usually `ORACLE_HOME/dbs` or `ORACLE_HOME/database`.
- *bMountAndOpen*
A true/false value signifying whether the database is to be mounted and opened.

Exceptions

OracleException - The database startup request has failed.

Remarks

This method starts a database instance in the specified mode using the specified client-side parameter file. After the database is successfully started, and if *bMountAndOpen* input parameter is true, this method also executes the ALTER DATABASE MOUNT and ALTER DATABASE OPEN statements.

If *bMountAndOpen* is true, then this method does not throw an exception for cases where the database is already mounted, opened, or started appropriately. If other errors are encountered, then an exception is thrown.

If *bMountAndOpen* is false, then the database must be mounted and opened explicitly by the application. For example, if *db* is an instance of the *OracleDatabase* class, then the application invokes the following:

1. `db.Startup(OracleDBStartupMode.NoRestriction, null, false);`
2. `db.ExecuteNonQuery("ALTER DATABASE MOUNT");`
3. `db.ExecuteNonQuery("ALTER DATABASE OPEN");`

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDatabase Class](#)
- [OracleDatabase Members](#)
- ["OracleDBStartupMode Enumeration"](#) on page 6-425

OracleDataReader Class

An OracleDataReader object represents a forward-only, read-only, in-memory result set.

Unlike the DataSet, the OracleDataReader object stays connected and fetches one row at a time.

The following section contain related information:

- ["Obtaining LONG and LONG RAW Data"](#) on page 3-57.
- ["Obtaining Data from an OracleDataReader Object"](#) on page 3-53.

Class Inheritance

System.Object

System.MarshalByRefObject

System.Data.Common.DataReader

System.Data.Common.DbDataReader

Oracle.DataAccess.Client.OracleDataReader

Declaration

```
// C#
public sealed class OracleDataReader : DbDataReader, IEnumerable,
    IDataReader, IDisposable, IDataRecord
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

An OracleDataReader instance is constructed by a call to the ExecuteReader method of the OracleCommand object. The only properties that can be accessed after the DataReader is closed or has been disposed, are IsClosed and RecordsAffected.

To minimize the number of open database cursors, OracleDataReader objects should be explicitly disposed.

Example

The following OracleDataReader example retrieves the data from the EMP table:

```
/* Database Setup, if you have not done so yet.
connect scott/tiger@oracle
CREATE TABLE empInfo (
empno NUMBER(4) PRIMARY KEY,
```

```
empName VARCHAR2(20) NOT NULL,
hiredate DATE,
salary NUMBER(7,2),
jobDescription Clob,
byteCodes BLOB
);

Insert into empInfo(EMPNO,EMPNAME,JOBDESCRIPTION,byteCodes) values
(1,'KING','SOFTWARE ENGR', '5657');
Insert into empInfo(EMPNO,EMPNAME,JOBDESCRIPTION,byteCodes) values
(2,'SCOTT','MANAGER', '5960');
commit;

*/

// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class OracleDataReaderSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        string cmdstr = "SELECT * FROM EMPINFO";
        OracleConnection connection = new OracleConnection(constr);
        OracleCommand cmd = new OracleCommand(cmdstr, con);

        OracleDataReader reader = cmd.ExecuteReader();

        // Declare the variables to retrieve the data in EmpInfo
        short empNo;
        string empName;
        DateTime hireDate;
        double salary;
        string jobDesc;
        byte[] byteCodes = new byte[10];

        // Read the next row until end of row
        while (reader.Read())
        {
            empNo = reader.GetInt16(0);
            Console.WriteLine("Employee number: " + empNo);
            empName = reader.GetString(1);
            Console.WriteLine("Employee name: " + empName);

            // The following columns can have NULL value, so it
            // is important to call IsDBNull before getting the column data
            if (!reader.IsDBNull(2))
            {
                hireDate = reader.GetDateTime(2);
                Console.WriteLine("Hire date: " + hireDate);
            }

            if (!reader.IsDBNull(3))
```

```
{
    salary = reader.GetDouble(3);
    Console.WriteLine("Salary: " + salary);
}

if (!reader.IsDBNull(4))
{
    jobDesc = reader.GetString(4);
    Console.WriteLine("Job Description: " + jobDesc);
}

if (!reader.IsDBNull(5))
{
    long len = reader.GetBytes(5, 0, byteCodes, 0, 10);

    Console.Write("Byte codes: ");
    for (int i = 0; i < len; i++)
        Console.Write(byteCodes[i].ToString("x"));

    Console.WriteLine();
}

Console.WriteLine();
}

// Clean up
reader.Dispose();
con.Dispose();
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleDataReader Members](#)
- [OracleDataReader Static Methods](#)
- [OracleDataReader Properties](#)
- [OracleDataReader Public Methods](#)
- [OracleDataReader SchemaTable](#)

OracleDataReader Members

OracleDataReader members are listed in the following tables.

OracleDataReader Static Methods

The OracleDataReader static method is listed in [Table 6–53](#).

Table 6–53 OracleDataReader Static Method

| Method | Description |
|------------------------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

OracleDataReader Properties

OracleDataReader properties are listed in [Table 6–54](#).

Table 6–54 OracleDataReader Properties

| Property | Description |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| Depth | Gets a value indicating the depth of nesting for the current row |
| FetchSize | Specifies the size of OracleDataReader's internal cache |
| FieldCount | Gets the number of columns in the result set |
| HasRows | Indicates whether the OracleDataReader has one or more rows |
| HiddenFieldCount | Gets the number of fields in the OracleDataReader that are hidden |
| IsClosed | Indicates whether or not the data reader is closed |
| Item | Gets the value of the column (Overloaded) |
| InitialLOBFetchSize | Specifies the amount that the OracleDataReader initially fetches for LOB columns |
| InitialLONGFetchSize | Specifies the amount that the OracleDataReader initially fetches for LONG and LONG RAW columns |
| RecordsAffected | Gets the number of rows changed, inserted, or deleted by execution of the SQL statement |
| RowSize | Gets the amount of memory the internal cache of the OracleDataReader needs to store one row of data. |
| UseEdmMapping | Indicates whether or not the OracleDataReader utilizes the Entity Data Model mapping configuration when returning values |
| VisibleFieldCount | Gets the number of fields in the OracleDataReader that are not hidden |

OracleDataReader Public Methods

OracleDataReader public methods are listed in [Table 6–55](#).

Table 6–55 OracleDataReader Public Methods

| Public Method | Description |
|-----------------------|-----------------------------|
| Close | Closes the OracleDataReader |

Table 6–55 (Cont.) OracleDataReader Public Methods

| Public Method | Description |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| CreateObjRef | Inherited from System.MarshalByRefObject |
| Dispose | Releases any resources or memory allocated by the object |
| Equals | Inherited from System.Object (Overloaded) |
| GetBoolean | <i>Not Supported</i> |
| GetByte | Returns the byte value of the specified column |
| GetBytes | Populates the provided byte array with up to the maximum number of bytes, from the specified offset (in bytes) of the column |
| GetChar | <i>Not Supported</i> |
| GetChars | Populates the provided character array with up to the maximum number of characters, from the specified offset (in characters) of the column |
| GetData | <i>Not Supported</i> |
| GetDataTypeName | Returns the ODP.NET type name of the specified column |
| GetDateTime | Returns the DateTime value of the specified column |
| GetDecimal | Returns the decimal value of the specified NUMBER column |
| GetDouble | Returns the double value of the specified NUMBER column or BINARY_DOUBLE column |
| GetEnumerator | Returns an IEnumerator that can be used to iterate through the collection |
| GetFieldType | Returns the Type of the specified column |
| GetFloat | Returns the float value of the specified NUMBER column or BINARY_FLOAT column |
| GetGuid | <i>Not Supported</i> |
| GetHashCode | Inherited from System.Object |
| GetInt16 | Returns the Int16 value of the specified NUMBER column |
| GetInt32 | Returns the Int32 value of the specified NUMBER column |
| GetInt64 | Returns the Int64 value of the specified NUMBER column |
| GetLifetimeService | Inherited by System.MarshalByRefObject |
| GetName | Returns the name of the specified column |
| GetOracleBFile | Returns an OracleBFile object of the specified BFILE column |
| GetOracleBinary | Returns an OracleBinary structure of the specified column |
| GetOracleBlob | Returns an OracleBlob object of the specified BLOB column |
| GetOracleBlobForUpdate | Returns an updatable OracleBlob object of the specified BLOB column |
| GetOracleClob | Returns an OracleClob object of the specified CLOB column |
| GetOracleClobForUpdate | Returns an updatable OracleClob object of the specified CLOB column |
| GetOracleDate | Returns an OracleDate structure of the specified DATE column |

Table 6–55 (Cont.) OracleDataReader Public Methods

| Public Method | Description |
|----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| GetOracleDecimal | Returns an <code>OracleDecimal</code> structure of the specified <code>NUMBER</code> column |
| GetOracleIntervalDS | Returns an <code>OracleIntervalDS</code> structure of the specified <code>INTERVAL DAY TO SECOND</code> column |
| GetOracleIntervalYM | Returns an <code>OracleIntervalYM</code> structure of the specified <code>INTERVAL YEAR TO MONTH</code> column |
| GetOracleRef | Returns an <code>OracleRef</code> object of the specified <code>REF</code> column |
| GetOracleString | Returns an <code>OracleString</code> structure of the specified column |
| GetOracleTimeStamp | Returns an <code>OracleTimeStamp</code> structure of the Oracle <code>TimeStamp</code> column |
| GetOracleTimeStampLTZ | Returns an <code>OracleTimeStampLTZ</code> structure of the specified Oracle <code>TimeStamp WITH LOCAL TIME ZONE</code> column |
| GetOracleTimeStampTZ | Returns an <code>OracleTimeStampTZ</code> structure of the specified Oracle <code>TimeStamp WITH TIME ZONE</code> column |
| GetOracleXmlType | Returns an <code>OracleXmlType</code> object of the specified <code>XMLType</code> column |
| GetOracleValue | Returns the specified column value as a <code>ODP.NET</code> type |
| GetOracleValues | Gets all the column values as <code>ODP.NET</code> types |
| GetOrdinal | Returns the 0-based ordinal (or index) of the specified column name |
| GetProviderSpecificFieldType | Returns the provider-specific type of the specified column |
| GetProviderSpecificValue | Returns an object that represents the underlying provider-specific value of the specified ordinal |
| GetProviderSpecificValues | Returns an array of objects that represent the underlying provider-specific values |
| GetSchemaTable | Returns a <code>DataTable</code> that describes the column metadata of the <code>OracleDataReader</code> |
| GetString | Returns the string value of the specified column |
| GetTimeSpan | Returns the <code>TimeSpan</code> value of the specified <code>INTERVAL DAY TO SECOND</code> column |
| GetType | Inherited from <code>System.Object</code> class |
| GetValue | Returns the column value as a <code>.NET</code> type |
| GetValues | Gets all the column values as <code>.NET</code> types |
| GetXmlReader | Returns the value of an <code>XMLType</code> column as an instance of an <code>.NET XmlTextReader</code> |
| IsDBNull | Indicates whether or not the column value is null |
| NextResult | Advances the data reader to the next result set when reading the results |
| Read | Reads the next row in the result set |
| ToString | Inherited from <code>System.Object</code> |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)

OracleDataReader Static Methods

The `OracleDataReader` static method is listed in [Table 6-56](#).

Table 6-56 *OracleDataReader Static Method*

| Method | Description |
|---------------------|--------------------------------------------------------|
| <code>Equals</code> | Inherited from <code>System.Object</code> (Overloaded) |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

OracleDataReader Properties

OracleDataReader properties are listed in [Table 6–57](#).

Table 6–57 OracleDataReader Properties

| Property | Description |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| Depth | Gets a value indicating the depth of nesting for the current row |
| FetchSize | Specifies the size of OracleDataReader's internal cache |
| FieldCount | Gets the number of columns in the result set |
| HasRows | Indicates whether the OracleDataReader has one or more rows |
| HiddenFieldCount | Gets the number of fields in the OracleDataReader that are hidden |
| IsClosed | Indicates whether or not the data reader is closed |
| Item | Gets the value of the column (Overloaded) |
| InitialLOBFetchSize | Specifies the amount that the OracleDataReader initially fetches for LOB columns |
| InitialLONGFetchSize | Specifies the amount that the OracleDataReader initially fetches for LONG and LONG RAW columns |
| RecordsAffected | Gets the number of rows changed, inserted, or deleted by execution of the SQL statement |
| RowSize | Gets the amount of memory the internal cache of the OracleDataReader needs to store one row of data |
| UseEdmMapping | Indicates whether or not the OracleDataReader utilizes the Entity Data Model mapping configuration when returning values |
| VisibleFieldCount | Gets the number of fields in the OracleDataReader that are not hidden |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

Depth

This property gets a value indicating the depth of nesting for the current row.

Declaration

```
// C#
public override int Depth {get;}
```

Property Value

The depth of nesting for the current row.

Implements

IDataReader

Exceptions

InvalidOperationException - The reader is closed.

Remarks

Default = 0

This property always returns zero because Oracle does not support nesting.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

FetchSize

This property specifies the size of OracleDataReader's internal cache.

Declaration

```
// C#  
public long FetchSize {get; set;}
```

Property Value

A long that specifies the amount of memory (in bytes) that the OracleDataReader uses for its internal cache.

Exceptions

ArgumentException - The FetchSize value specified is invalid.

Remarks

Default = The OracleCommand's FetchSize property value.

The FetchSize property is inherited by the OracleDataReader that is created by a command execution returning a result set. The FetchSize property on the OracleDataReader object determines the amount of data fetched into its internal cache for each database round-trip.

The RowSize and FetchSize properties handle UDT and XMLType data differently than other scalar data types. Because only a reference to the UDT and XMLType data is stored in the ODP.NET's internal cache, the RowSize property accounts for only the memory needed for the reference (which is very small) and not the actual size of the UDT and XMLType data. Thus, applications can inadvertently fetch a large number of UDT or XMLType instances from the database in a single database round-trip. This is because the actual size of UDT and XMLType data does not count against the FetchSize, and it would require numerous UDT and XMLType references to fill up the default cache size of 131072 bytes. Therefore, when fetching UDT or XMLType data, the FetchSize property must be appropriately configured to control the number of UDT and XMLType instances that are to be fetched, rather than the amount of the actual UDT and XMLType data to be fetched.

NOTE: For LOB and LONG data types, only the sizes specified in the `InitialLOBFetchSize` and `InitialLONGFetchSize` properties are accounted for by the `RowSize` property in addition to the metadata and reference information that is maintained by the cache for each LOB in the select list.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- [OracleDataReader "RowSize"](#) on page 213
- [OracleCommand "ExecuteReader\(\)"](#) on page 6-47
- [OracleCommand "RowSize"](#) on page 6-33

FieldCount

This property returns the number of columns in the result set.

Declaration

```
// C#  
public override int FieldCount {get;}
```

Property Value

The number of columns in the result set if one exists, otherwise 0.

Implements

`IDataRecord`

Exceptions

`InvalidOperationException` - The reader is closed.

Remarks

Default = 0

This property has a value of 0 for queries that do not return result sets.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

HasRows

This property indicates whether the `OracleDataReader` has one or more rows.

Declaration

```
// C#  
public override bool HasRows {get;}
```

Return Value

bool

Remarks

HasRows indicates whether or not the OracleDataReader has any rows.

The value of HasRows does not change based on the row position. For example, even if the application has read all the rows from the result set and the next Read method invocation will return false, the HasRows property still returns true since the result set was not empty to begin with.

Rows are fetched to determine the emptiness of the OracleDataReader when HasRows property is accessed for the first time after the creation of the OracleDataReader object.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
  
class HasRowsSample  
{  
    static void Main()  
    {  
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";  
        OracleConnection con = new OracleConnection(constr);  
        con.Open();  
  
        OracleCommand cmd = new OracleCommand(  
            "select * from emp where empno = 9999", con);  
  
        OracleDataReader reader = cmd.ExecuteReader();  
  
        if (!reader.HasRows)  
            Console.WriteLine("The result set is empty.");  
        else  
            Console.WriteLine("The result set is not empty.");  
  
        con.Dispose();  
    }  
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- <http://msdn.microsoft.com/library> for detailed information about this Microsoft .NET Framework 1.1 feature

HiddenFieldCount

This property gets the number of fields in the OracleDataReader that are hidden.

Declaration

```
// C#  
public int HiddenFieldcount { get; }
```

Property Value

The number of fields in the `OracleDataReader` that are hidden.

Exceptions

`InvalidOperationException` - The reader is closed.

Remarks

`OracleDataReader.FieldCount` and `OracleDataReader.VisibleFieldCount` return the visible field count.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["VisibleFieldCount"](#) on page 6-214
- ["FieldCount"](#) on page 6-207

IsClosed

This property indicates whether or not the data reader is closed.

Declaration

```
// C#  
public override bool IsClosed {get;}
```

Property Value

If the `OracleDataReader` is in a closed state, returns `true`; otherwise, returns `false`.

Implements

`IDataReader`

Remarks

Default = `true`

`IsClosed` and `RecordsAffected` are the only two properties that are accessible after the `OracleDataReader` is closed.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

Item

This property gets the value of the column in .NET data type.

Overload List:

- [Item \[index\]](#)

This property gets the .NET value of the column specified by the column index.

- [Item \[string\]](#)

This property gets the .NET value of the column specified by the column name.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

Item [index]

This property gets the .NET value of the column specified by the column index.

Declaration

```
// C#  
public override object this[int index] {get;}
```

Parameters

- *index*

The zero-based index of the column.

Property Value

The .NET value of the specified column.

Implements

`IDataRecord`

Remarks

Default = Not Applicable

In C#, this property is the indexer for this class.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

Item [string]

This property gets the .NET value of the column specified by the column name.

Declaration

```
// C#  
public override object this[string columnName] {get;}
```

Parameters

- *columnName*

The name of the column.

Property Value

The .NET Value of the specified column.

Implements

IDataRecord

Remarks

Default = Not Applicable

A case-sensitive search is made to locate the specified column by its name. If this fails, then a case-insensitive search is made.

In C#, this property is the indexer for this class.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

InitialLOBFetchSize

This property specifies the amount that the OracleDataReader initially fetches for LOB columns.

Declaration

```
// C#  
public int InitialLOBFetchSize {get;}
```

Property Value

The size of the chunk to retrieve.

Exceptions

InvalidOperationException - The reader is closed.

Remarks

The maximum value supported for InitialLOBFetchSize is 2 GB.

Default is the OracleCommand.InitialLOBFetchSize, from which this value is inherited.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["InitialLOBFetchSize"](#) on page 6-29 for further information on `OracleCommand.InitialLOBFetchSize`
- ["Obtaining LOB Data"](#) on page 3-58

InitialLONGFetchSize

This property specifies the amount that the `OracleDataReader` initially fetches for LONG and LONG RAW columns.

Declaration

```
// C#  
public long InitialLONGFetchSize {get;}
```

Property Value

The size of the chunk to retrieve. The default is 0.

Exceptions

`InvalidOperationException` - The reader is closed.

Remarks

The maximum value supported for `InitialLONGFetchSize` is 32767. If this property is set to a higher value, the provider resets it to 32767.

Default is `OracleCommand.InitialLONGFetchSize`, from which this value is inherited.

This property is read-only for the `OracleDataReader`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["InitialLONGFetchSize"](#) on page 6-30 for further information on `OracleCommand.InitialLONGFetchSize`
- ["Obtaining LONG and LONG RAW Data"](#) on page 3-57

RecordsAffected

This property gets the number of rows changed, inserted, or deleted by execution of the SQL statement.

Declaration

```
// C#  
public int RecordsAffected {get;}
```

Property Value

The number of rows affected by execution of the SQL statement.

Implements

IDataReader

Remarks

Default = 0

The value of -1 is returned for SELECT statements.

IsClosed and RecordsAffected are the only two properties that are accessible after the OracleDataReader is closed.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

RowSize

This property gets the amount of memory the internal cache of the OracleDataReader needs to store one row of data.

Declaration

```
// C#  
public long RowSize {get;}
```

Property Value

A long that indicates the amount of memory (in bytes) that an OracleDataReader needs to store one row of data for the executed query.

Remarks

The RowSize property is set to a nonzero value when the OracleDataReader object is created. This property can be used at design time or dynamically during runtime, to set the FetchSize property, based on the number of rows. For example, to enable the OracleDataReader object to fetch *N* rows for each database round-trip, the OracleDataReader FetchSize property can be set dynamically to RowSize * *N*. Note that for the FetchSize property to take effect appropriately, it must be set before the first invocation of OracleDataReader.Read() for the particular result set.

ODP.NET now supports values up to 32K for VARCHAR2, NVARCHAR2 or RAW type columns in its calculation of RowSize value

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["FetchSize"](#) on page 206

UseEdmMapping

This read-only property indicates whether or not the `OracleDataReader` utilizes the Entity Data Model mapping configuration when returning values.

Declaration

```
// C#  
public bool UseEdmMapping {get;}
```

Property Value

A boolean that indicates whether the `OracleDataReader` uses the Entity Data Model mapping configuration for returning values.

Remarks

Default is false.

The value is inherited from the `OracleCommand` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- [OracleCommand Class](#)

VisibleFieldCount

This property gets the number of fields in the `OracleDataReader` that are not hidden.

Declaration

```
// C#  
public override int VisibleFieldcount { get; }
```

Property Value

The number of fields that are not hidden.

Exceptions

`InvalidOperationException` - The reader is closed.

Remarks

If an application sets the `AddRowid` property on an `OracleCommand` object to true, then the application can access the `RowId` but it is not a visible field. If `RowId` is added in the select statement list, then it is a visible field. `OracleDataReader.VisibleFieldCount` and `OracleDataReader.FieldCount` always have the same value.

Example

```
// C#

using System;
using System.Data;
using System.Data.Common;
using Oracle.DataAccess.Client;

class VisibleFieldCountSample
{
    static void Main(string[] args)
    {
        string constr = "User Id=scott; Password=tiger; Data Source=oracle;";
        DbProviderFactory factory =
            DbProviderFactories.GetFactory("Oracle.DataAccess.Client");

        using (DbConnection conn = factory.CreateConnection())
        {
            conn.ConnectionString = constr;
            try
            {
                conn.Open();
                OracleCommand cmd = (OracleCommand)factory.CreateCommand();
                cmd.Connection = (OracleConnection)conn;

                //to gain access to ROWIDs of the table
                cmd.AddRowid = true;
                cmd.CommandText = "select empno, ename from emp;";

                OracleDataReader reader = cmd.ExecuteReader();

                int visFC = reader.VisibleFieldCount; //Results in 2
                int hidFC = reader.HiddenFieldCount; // Results in 1

                Console.WriteLine("Visible field count: " + visFC);
                Console.WriteLine("Hidden field count: " + hidFC);

                reader.Dispose();
                cmd.Dispose();
            }
            catch (Exception ex)
            {
                Console.WriteLine(ex.Message);
                Console.WriteLine(ex.StackTrace);
            }
        }
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["VisibleFieldCount"](#) on page 6-214
- ["FieldCount"](#) on page 6-207

OracleDataReader Public Methods

OracleDataReader public methods are listed in [Table 6–58](#).

Table 6–58 OracleDataReader Public Methods

| Public Method | Description |
|------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| Close | Closes the OracleDataReader |
| CreateObjRef | Inherited from System.MarshalByRefObject |
| Dispose | Releases any resources or memory allocated by the object |
| Equals | Inherited from System.Object (Overloaded) |
| GetBoolean | <i>Not Supported</i> |
| GetByte | Returns the byte value of the specified column |
| GetBytes | Populates the provided byte array with up to the maximum number of bytes, from the specified offset (in bytes) of the column |
| GetChar | <i>Not Supported</i> |
| GetChars | Populates the provided character array with up to the maximum number of characters, from the specified offset (in characters) of the column |
| GetData | <i>Not Supported</i> |
| GetDataTypeName | Returns the ODP.NET type name of the specified column |
| GetDateTime | Returns the DateTime value of the specified column |
| GetDecimal | Returns the decimal value of the specified NUMBER column |
| GetDouble | Returns the double value of the specified NUMBER column or BINARY_DOUBLE column |
| GetEnumerator | Returns an IEnumerator that can be used to iterate through the collection |
| GetFieldType | Returns the Type of the specified column |
| GetFloat | Returns the float value of the specified NUMBER column or BINARY_FLOAT column |
| GetGuid | <i>Not Supported</i> |
| GetHashCode | Inherited from System.Object |
| GetInt16 | Returns the Int16 value of the specified NUMBER column |
| GetInt32 | Returns the Int32 value of the specified NUMBER column |
| GetInt64 | Returns the Int64 value of the specified NUMBER column |
| GetLifetimeService | Inherited by System.MarshalByRefObject |
| GetName | Returns the name of the specified column |
| GetOracleBFile | Returns an OracleBFile object of the specified BFILE column |
| GetOracleBinary | Returns an OracleBinary structure of the specified column |
| GetOracleBlob | Returns an OracleBlob object of the specified BLOB column |

Table 6–58 (Cont.) OracleDataReader Public Methods

| Public Method | Description |
|----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| GetOracleBlobForUpdate | Returns an updatable <code>OracleBlob</code> object of the specified BLOB column <i>Not Available in ODP.NET, Managed Driver</i> |
| GetOracleClob | Returns an <code>OracleClob</code> object of the specified CLOB column |
| GetOracleClobForUpdate | Returns an updatable <code>OracleClob</code> object of the specified CLOB column <i>Not Available in ODP.NET, Managed Driver</i> |
| GetOracleDate | Returns an <code>OracleDate</code> structure of the specified DATE column |
| GetOracleDecimal | Returns an <code>OracleDecimal</code> structure of the specified NUMBER column |
| GetOracleIntervalDS | Returns an <code>OracleIntervalDS</code> structure of the specified INTERVAL DAY TO SECOND column |
| GetOracleIntervalYM | Returns an <code>OracleIntervalYM</code> structure of the specified INTERVAL YEAR TO MONTH column |
| GetOracleRef | Returns an <code>OracleRef</code> object of the specified REF column <i>Not Available in ODP.NET, Managed Driver</i> |
| GetOracleString | Returns an <code>OracleString</code> structure of the specified column |
| GetOracleTimeStamp | Returns an <code>OracleTimeStamp</code> structure of the Oracle TimeStamp column |
| GetOracleTimeStampLTZ | Returns an <code>OracleTimeStampLTZ</code> structure of the specified Oracle TimeStamp WITH LOCAL TIME ZONE column |
| GetOracleTimeStampTZ | Returns an <code>OracleTimeStampTZ</code> structure of the specified Oracle TimeStamp WITH TIME ZONE column |
| GetOracleXmlType | Returns an <code>OracleXmlType</code> object of the specified XMLType column <i>Not Available in ODP.NET, Managed Driver</i> |
| GetOracleValue | Returns the specified column value as a ODP.NET type |
| GetOracleValues | Gets all the column values as ODP.NET types |
| GetOrdinal | Returns the 0-based ordinal (or index) of the specified column name |
| GetProviderSpecificFieldType | Returns the provider-specific type of the specified column |
| GetProviderSpecificValue | Returns an object that represents the underlying provider-specific value of the specified ordinal |
| GetProviderSpecificValues | Returns an array of objects that represent the underlying provider-specific values |
| GetSchemaTable | Returns a <code>DataTable</code> that describes the column metadata of the <code>OracleDataReader</code> |
| GetString | Returns the string value of the specified column |
| GetTimeSpan | Returns the <code>TimeSpan</code> value of the specified INTERVAL DAY TO SECOND column |
| GetType | Inherited from <code>System.Object</code> class |
| GetValue | Returns the column value as a .NET type |
| GetValues | Gets all the column values as .NET types |

Table 6–58 (Cont.) OracleDataReader Public Methods

| Public Method | Description |
|------------------------------|----------------------------------------------------------------------------------------------------------|
| GetXmlReader | Returns the value of an <code>XMLType</code> column as an instance of an .NET <code>XmlTextReader</code> |
| IsDBNull | Indicates whether or not the column value is null |
| NextResult | Advances the data reader to the next result set when reading the results |
| Read | Reads the next row in the result set |
| ToString | Inherited from <code>System.Object</code> |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

Close

This method closes the `OracleDataReader`.

Declaration

```
// C#
public override void Close();
```

Implements

`IDataReader`

Remarks

The `Close` method frees all resources associated with the `OracleDataReader`.

Example

The code example for the `OracleDataReader` class includes the `Close` method. See [OracleDataReader Overview "Example"](#) on page 6-197.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

Dispose

This method releases any resources or memory allocated by the object.

Declaration

```
// C#
public void Dispose();
```

Implements

IDisposable

Remarks

The `Dispose` method also closes the `OracleDataReader`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetBoolean

This method is not supported.

Declaration

```
// C#  
public override bool GetBoolean(int index);
```

Parameters

- *index*
The zero-based column index.

Implements

IDataRecord

Exceptions

`NotSupportedException` - This property is not supported.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetByte

This method returns the byte value of the specified column.

Declaration

```
// C#  
public override byte GetByte(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The value of the column as a byte.

Implements

IDataRecord

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is NULL.

Remarks

`IsDBNull` should be called to check for NULL values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetBytes

This method populates the provided byte array with up to the maximum number of bytes, from the specified offset (in bytes) of the column.

Declaration

```
// C#  
public override long GetBytes(int index, long fieldOffset, byte[] buffer,  
    int bufferOffset, int length);
```

Parameters

- *index*
The zero-based column index.
- *fieldOffset*
The offset within the column from which reading begins (in bytes).
- *buffer*
The byte array that the data is read into.
- *bufferOffset*
The offset within the buffer to begin reading data into (in bytes).
- *length*
The maximum number of bytes to read (in bytes).

Return Value

The number of bytes read.

Implements

IDataRecord

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

This method returns the number of bytes read into the buffer. This may be less than the actual length of the field if the method has been called previously for the same column.

If a null reference is passed for buffer, the length of the field in bytes is returned.

`IsDBNull` should be called to check for `NULL` values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetChar

This method is not supported.

Declaration

```
// C#  
public override long GetChar(int index);
```

Parameters

- *index*
The zero based column index.

Implements

`IDataRecord`

Exceptions

`NotSupportedException` - This property is not supported.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetChars

This method populates the provided character array with up to the maximum number of characters, from the specified offset (in characters) of the column.

Declaration

```
// C#  
public override long GetChars(int index, long fieldOffset, char[] buffer,  
    int bufferOffset, int length);
```

Parameters

- *index*
The zero based column index.
- *fieldOffset*
The index within the column from which to begin reading (in characters).
- *buffer*
The character array that the data is read into.
- *bufferOffset*
The index within the buffer to begin reading data into (in characters).
- *length*
The maximum number of characters to read (in characters).

Return Value

The number of characters read.

Implements

IDataRecord

Exceptions

InvalidOperationException - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

IndexOutOfRangeException - The column index is invalid.

InvalidCastException - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

This method returns the number of characters read into the buffer. This may be less than the actual length of the field, if the method has been called previously for the same column.

If a null reference is passed for `buffer`, the length of the field in characters is returned.

`IsDBNull` should be called to check for `NULL` values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetDataTypeName

This method returns the ODP.NET type name of the specified column.

Declaration

```
// C#  
public override string GetDataTypeName(int index);
```

Parameters

- *index*

The zero-based column index.

Return Value

The name of the ODP.NET type of the column.

Implements

IDataRecord

Exceptions

InvalidOperationException - The reader is closed.

IndexOutOfRangeException - The column index is invalid.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetDateTime

This method returns the `DateTime` value of the specified column.

Declaration

```
// C#  
public override DateTime GetDateTime(int index);
```

Parameters

- *index*

The zero-based column index.

Return Value

The `DateTime` value of the column.

Implements

IDataRecord

Exceptions

InvalidOperationException - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

IndexOutOfRangeException - The column index is invalid.

InvalidCastException - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetDecimal

This method returns the decimal value of the specified `NUMBER` column.

Declaration

```
// C#  
public override decimal GetDecimal(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The decimal value of the column.

Implements

`IDataRecord`

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetDouble

This method returns the double value of the specified `NUMBER` column or `BINARY_DOUBLE` column.

Declaration

```
// C#
```

```
public override double GetDouble(int index);
```

Parameters

- *index*

The zero-based column index.

Return Value

The double value of the column.

Implements

IDataRecord

Exceptions

InvalidOperationException - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

IndexOutOfRangeException - The column index is invalid.

InvalidCastException - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

`GetDouble` now supports retrieval of data from `BINARY_DOUBLE` columns.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetEnumerator

This method returns an `IEnumerator` that can be used to iterate through the collection (record set).

Declaration

```
// C#  
public override IEnumerator GetEnumerator();
```

Return Value

An `IEnumerator` that can be used to iterate through the collection (record set).

Exceptions

InvalidOperationException - The reader is closed.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetFieldType

This method returns the type of the specified column.

Declaration

```
// C#  
public override Type GetFieldType(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The type of the default .NET type of the column.

Implements

IDataRecord

Exceptions

InvalidOperationException - The reader is closed, or the specified column is a UDT but no registered custom type mapping exists for the UDT.

IndexOutOfRangeException - The column index is invalid.

Remarks

`GetFieldType` returns a type that corresponds to the value that the application obtains after invoking the `GetValue` accessor or `Item` property on the `OracleDataReader`. For example, if the column is a string, this method returns a .NET Type object for a .NET string.

If the attribute is a UDT, this method may return either of the following:

- A .NET Type of the custom type if a custom type mapping exists for the Oracle object or collection.
- A .NET Type of string if the column is an Oracle REF.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetFloat

This method returns the float value of the specified NUMBER column or BINARY_FLOAT column.

Declaration

```
// C#  
public override float GetFloat(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The float value of the column.

Implements

IDataRecord

Exceptions

InvalidOperationException - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

IndexOutOfRangeException - The column index is invalid.

InvalidCastException - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

`GetFloat` now supports retrieval of data from `BINARY_FLOAT` columns.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetGuid

This method is not supported.

Declaration

```
// C#  
public override Guid GetGuid(int index);
```

Parameters

- *index*
The zero-based column index.

Implements

IDataRecord

Exceptions

NotSupportedException - This property is not supported.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetInt16

This method returns the Int16 value of the specified NUMBER column.

Note: short is equivalent to Int16.

Declaration

```
// C#
public override short GetInt16(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The Int16 value of the column.

Implements

IDataRecord

Exceptions

InvalidOperationException - The connection is closed, the reader is closed, *Read()* has not been called, or all rows have been read.

IndexOutOfRangeException - The column index is invalid.

InvalidCastException - The accessor method is invalid for this column type or the column value is NULL.

Remarks

IsDBNull should be called to check for NULL values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetInt32

This method returns the Int32 value of the specified NUMBER column.

Note: int is equivalent to Int32.

Declaration

```
// C#  
public override int GetInt32(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `Int32` value of the column.

Implements

`IDataRecord`

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetInt64

This method returns the `Int64` value of the specified `NUMBER` column.

Note: `long` is equivalent to `Int64`.

Declaration

```
// C#  
public override long GetInt64(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `Int64` value of the column.

Implements

IDataRecord

Exceptions

InvalidOperationException - The connection is closed, the reader is closed, Read() has not been called, or all rows have been read.

IndexOutOfRangeException - The column index is invalid.

InvalidCastException - The accessor method is invalid for this column type or the column value is NULL.

Remarks

IsDBNull should be called to check for NULL values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetName

This method returns the name of the specified column.

Declaration

```
// C#  
public override string GetName(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The name of the column.

Implements

IDataRecord

Exceptions

InvalidOperationException - The reader is closed.

IndexOutOfRangeException - The column index is invalid.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetOracleBFile

This method returns an `OracleBFile` object of the specified `BFILE` column.

Declaration

```
// C#  
public OracleBFile GetOracleBFile(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `OracleBFile` value of the column.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetOracleBinary

This method returns an `OracleBinary` structure of the specified column.

Declaration

```
// C#  
public OracleBinary GetOracleBinary(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `OracleBinary` value of the column.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is NULL.

Remarks

`IsDBNull` should be called to check for NULL values before calling this method.

`GetOracleBinary` is used on the following Oracle types:

- BFILE
- BLOB
- LONG RAW
- RAW

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetOracleBlob

This method returns an `OracleBlob` object of the specified BLOB column.

Declaration

```
// C#  
public OracleBlob GetOracleBlob(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `OracleBlob` value of the column.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is NULL.

Remarks

`IsDBNull` should be called to check for NULL values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetOracleBlobForUpdate

GetOracleBlobForUpdate returns an updatable OracleBlob object of the specified BLOB column.

Overload List:

- [GetOracleBlobForUpdate\(int\)](#)
This method returns an updatable OracleBlob object of the specified BLOB column.
- [GetOracleBlobForUpdate\(int, int\)](#)
This method returns an updatable OracleBlob object of the specified BLOB column using a WAIT clause.

GetOracleBlobForUpdate(int)

This method returns an updatable OracleBlob object of the specified BLOB column.

Declaration

```
// C#  
public OracleBlob GetOracleBlobForUpdate(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

An updatable OracleBlob object.

Exceptions

InvalidOperationException - The connection is closed, the reader is closed, Read() has not been called, or all rows have been read.

IndexOutOfRangeException - The column index is invalid.

InvalidCastException - The accessor method is invalid for this column type or the column value is NULL.

Remarks

When the OracleCommand's ExecuteReader() method is invoked, all the data fetched by the OracleDataReader is from a particular snapshot. Therefore, calling an accessor method on the same column always returns the same value. However, the GetOracleBlobForUpdate() method incurs a database round-trip to obtain a reference to the current BLOB data while also locking the row using the FOR UPDATE clause. This means that the OracleBlob obtained from GetOracleBlob() can have a different value than the OracleBlob obtained from GetOracleBlobForUpdate() since it is not obtained from the original snapshot.

The returned OracleBlob object can be used to safely update the BLOB because the BLOB column has been locked after a call to this method.

Invoking this method internally executes a SELECT...FOR UPDATE statement without a WAIT clause. Therefore, the statement can wait indefinitely until a lock is acquired for that row.

IsDBNull should be called to check for NULL values before calling this method.

Example

The following example gets the OracleBlob object for update from the reader, updates the OracleBlob object, and then commits the transaction.

```

/* Database Setup, if you have not done so yet.
connect scott/tiger@oracle
CREATE TABLE empInfo (
empno NUMBER(4) PRIMARY KEY,
empName VARCHAR2(20) NOT NULL,
hiredate DATE,
salary NUMBER(7,2),
jobDescription Clob,
byteCodes BLOB
);

Insert into empInfo(EMPNO,EMPNAME,JOBDESCRIPTION,byteCodes) values
(1,'KING','SOFTWARE ENGR', '5657');
Insert into empInfo(EMPNO,EMPNAME,JOBDESCRIPTION,byteCodes) values
(2,'SCOTT','MANAGER', '5960');
commit;

*/
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class GetOracleBlobForUpdateSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Get the ByteCodes for empno = 1
        string cmdstr = "SELECT BYTECODES, EMPNO FROM EMPINFO where EMPNO = 1";
        OracleCommand cmd = new OracleCommand(cmdstr, con);

        // Since we are going to update the OracleBlob object, we will
        //have to create a transaction
        OracleTransaction txn = con.BeginTransaction();

        // Get the reader
        OracleDataReader reader = cmd.ExecuteReader();

        // Declare the variables to retrieve the data in EmpInfo
        OracleBlob byteCodesBlob;

        // Read the first row
        reader.Read();
        if (!reader.IsDBNull(0))
        {
            byteCodesBlob = reader.GetOracleBlobForUpdate(0);

            // Close the reader
            reader.Close();
        }
    }
}

```

```
// Update the ByteCodes object
byte[] addedBytes = new byte[2] {0, 0};
byteCodesBlob.Append(addedBytes, 0, addedBytes.Length);

// Now commit the transaction
txn.Commit();
Console.WriteLine("Blob Column successfully updated");
}
else
    reader.Dispose();

// Close the connection
con.Dispose();
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["LOB Support"](#) on page 3-75

GetOracleBlobForUpdate(int, int)

This method returns an updatable `OracleBlob` object of the specified BLOB column using a `WAIT` clause.

Declaration

```
// C#
public OracleBlob GetOracleBlobForUpdate(int index, int wait);
```

Parameters

- *index*
The zero-based column index.
- *wait*
The number of seconds the method waits to acquire a lock.

Return Value

An updatable `OracleBlob` object.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

When the `OracleCommand`'s `ExecuteReader()` method is invoked, all the data fetched by the `OracleDataReader` is from a particular snapshot. Therefore, calling an accessor method on the same column always returns the same value. However, the `GetOracleBlobForUpdate()` method incurs a database round-trip to obtain a reference to the current BLOB data while also locking the row using the `FOR UPDATE` clause. This means that the `OracleBlob` obtained from `GetOracleBlob()` can have a different value than the `OracleBlob` obtained from `GetOracleBlobForUpdate()` since it is not obtained from the original snapshot.

`IsDBNull` should be called to check for `NULL` values before calling this method.

The returned `OracleBlob` object can be used to safely update the BLOB because the BLOB column has been locked after a call to this method.

Invoking this method internally executes a `SELECT...FOR UPDATE` statement which locks the row.

Different `WAIT` clauses are appended to the statement, depending on the `wait` value. If the `wait` value is:

- 0
"NOWAIT" is appended at the end of a `SELECT...FOR UPDATE` statement. The statement executes immediately whether the lock is acquired or not. If the lock is not acquired, an exception is thrown.
- *n*
"WAIT *n*" is appended at the end of a `SELECT...FOR UPDATE` statement. The statement executes as soon as the lock is acquired. However, if the lock cannot be acquired by *n* seconds, this method call throws an exception.

The `WAIT n` feature is only available for Oracle9i or later. For any version lower than Oracle9i, *n* is implicitly treated as -1 and nothing is appended at the end of a `SELECT...FOR UPDATE` statement.
- -1
Nothing is appended at the end of the `SELECT...FOR UPDATE`. The statement execution waits indefinitely until a lock can be acquired.

Example

The `GetOracleBlobForUpdate` methods are comparable. See ["Example"](#) on page 6-235 for a code example demonstrating usage.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["LOB Support"](#) on page 3-75

GetOracleClob

This method returns an `OracleClob` object of the specified CLOB column.

Declaration

```
// C#
```

```
public OracleClob GetOracleClob(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `OracleClob` value of the column.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["LOB Support"](#) on page 3-75

GetOracleClobForUpdate

`GetOracleClobForUpdate` returns an updatable `OracleClob` object of the specified CLOB column.

Overload List:

- [GetOracleClobForUpdate\(int\)](#)
This method returns an updatable `OracleClob` object of the specified CLOB column.
- [GetOracleClobForUpdate\(int, int\)](#)
This method returns an updatable `OracleClob` object of the specified CLOB column using a `WAIT` clause.

GetOracleClobForUpdate(int)

This method returns an updatable `OracleClob` object of the specified CLOB column.

Declaration

```
// C#  
public OracleClob GetOracleClobForUpdate(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

An updatable OracleClob.

Exceptions

InvalidOperationException - The connection is closed, the reader is closed, Read() has not been called, or all rows have been read.

IndexOutOfRangeException - The column index is invalid.

InvalidCastException - The accessor method is invalid for this column type or the column value is NULL.

Remarks

When the OracleCommand's ExecuteReader() method is invoked, all the data fetched by the OracleDataReader is from a particular snapshot. Therefore, calling an accessor method on the same column always returns the same value. However, the GetOracleClobForUpdate() method incurs a database round-trip to obtain a reference to the current CLOB data while also locking the row using the FOR UPDATE clause. This means that the OracleClob obtained from GetOracleClob() can have a different value than the OracleClob obtained from GetOracleClobForUpdate() since it is not obtained from the original snapshot.

The returned OracleClob object can be used to safely update the CLOB because the CLOB column is locked after a call to this method.

Invoking this method internally executes a SELECT..FOR UPDATE statement without a WAIT clause. Therefore, the statement can wait indefinitely until a lock is acquired for that row.

IsDBNull should be called to check for NULL values before calling this method.

Example

The following example gets the OracleClob object for update from the reader, updates the OracleClob object, and then commits the transaction.

```

/* Database Setup, if you have not done so yet.
connect scott/tiger@oracle
CREATE TABLE empInfo (
empno NUMBER(4) PRIMARY KEY,
empName VARCHAR2(20) NOT NULL,
hiredate DATE,
salary NUMBER(7,2),
jobDescription Clob,
byteCodes BLOB
);

Insert into empInfo(EMPNO,EMPNAME,JOBDESCRIPTION,byteCodes) values
(1,'KING','SOFTWARE ENGR', '5657');
Insert into empInfo(EMPNO,EMPNAME,JOBDESCRIPTION,byteCodes) values
(2,'SCOTT','MANAGER', '5960');
commit;

*/
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

```

```
class GetOracleClobForUpdateSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Get the job description for empno = 1
        string cmdStr = "SELECT JOBDESCRIPTION, EMPNO FROM EMPINFO where EMPNO = 1";
        OracleCommand cmd = new OracleCommand(cmdStr, con);

        // Since we are going to update the OracleClob object, we will
        // have to create a transaction
        OracleTransaction txn = con.BeginTransaction();

        // Get the reader
        OracleDataReader reader = cmd.ExecuteReader();

        // Declare the variables to retrieve the data in EmpInfo
        OracleClob jobDescClob;

        // Read the first row
        reader.Read();

        if (!reader.IsDBNull(0))
        {
            jobDescClob = reader.GetOracleClobForUpdate(0);

            // Close the reader
            reader.Close();

            // Update the job description Clob object
            char[] jobDesc = "-SALES".ToCharArray();
            jobDescClob.Append(jobDesc, 0, jobDesc.Length);

            // Now commit the transaction
            txn.Commit();
            Console.WriteLine("Clob Column successfully updated");
        }
        else
            reader.Close();

        // Close the connection
        con.Close();
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["LOB Support"](#) on page 3-75

GetOracleClobForUpdate(int, int)

This method returns an updatable `OracleClob` object of the specified CLOB column using a `WAIT` clause.

Declaration

```
// C#  
public OracleClob GetOracleClobForUpdate(int index, int wait);
```

Parameters

- *index*
The zero-based column index.
- *wait*
The number of seconds the method waits to acquire a lock.

Return Value

An updatable `OracleClob`.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

When the `OracleCommand`'s `ExecuteReader()` method is invoked, all the data fetched by the `OracleDataReader` is from a particular snapshot. Therefore, calling an accessor method on the same column always returns the same value. However, the `GetOracleClobForUpdate()` method incurs a database round-trip to obtain a reference to the current CLOB data while also locking the row using the `FOR UPDATE` clause. This means that the `OracleClob` obtained from `GetOracleClob()` can have a different value than the `OracleClob` obtained from `GetOracleClobForUpdate()` since it is not obtained from the original snapshot.

Invoking this method internally executes a `SELECT . .FOR UPDATE` statement which locks the row.

The returned `OracleClob` object can be used to safely update the CLOB because the CLOB column is locked after a call to this method.

Different `WAIT` clauses are appended to the statement, depending on the `wait` value. If the `wait` value is:

- 0
"NOWAIT" is appended at the end of a `SELECT . .FOR UPDATE` statement. The statement executes immediately whether the lock is acquired or not. If the lock is not acquired, an exception is thrown.
- *n*
"WAIT *n*" is appended at the end of a `SELECT . .FOR UPDATE` statement. The statement executes as soon as the lock is acquired. However, if the lock cannot be acquired by *n* seconds, this method call throws an exception.

The `WAIT n` feature is only available for Oracle9i or later. For any version lower than Oracle9i, `n` is implicitly treated as -1 and nothing is appended at the end of a `SELECT...FOR UPDATE` statement.

- -1

Nothing is appended at the end of the `SELECT...FOR UPDATE`. The statement execution waits indefinitely until a lock can be acquired.

`IsDBNull` should be called to check for `NULL` values before calling this method.

Example

The `GetOracleClobForUpdate` methods are comparable. See ["Example"](#) on page 6-239 for a code example demonstrating usage.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["LOB Support"](#) on page 3-75

GetOracleDate

This method returns an `OracleDate` structure of the specified `DATE` column.

Declaration

```
// C#  
public OracleDate GetOracleDate(int index);
```

Parameters

- `index`
The zero-based column index.

Return Value

The `OracleDate` value of the column.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["LOB Support"](#) on page 3-75

GetOracleDecimal

This method returns an `OracleDecimal` structure of the specified `NUMBER` column.

Declaration

```
// C#  
public OracleDecimal GetOracleDecimal(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `OracleDecimal` value of the column.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetOracleIntervalDS

This method returns an `OracleIntervalDS` structure of the specified `INTERVAL DAY TO SECOND` column.

Declaration

```
// C#  
public OracleIntervalDS GetOracleIntervalDS(int index);
```

Parameters

- *index*

The zero-based column index.

Return Value

The `OracleIntervalDS` value of the column.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetOracleIntervalYM

This method returns an `OracleIntervalYM` structure of the specified `INTERVAL YEAR TO MONTH` column.

Declaration

```
// C#  
public OracleIntervalYM GetOracleIntervalYM(int index);
```

Parameters

- *index*

The zero-based column index.

Return Value

The `OracleIntervalYM` value of the column.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetOracleRef

This method returns an `OracleRef` object of the specified REF column.

Declaration

```
// C#  
public OracleRef GetOracleRef(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `OracleRef` object of the specified column.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, the `Read` method has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetOracleString

This method returns an `OracleString` structure of the specified column.

Declaration

```
// C#  
public OracleString GetOracleString(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `OracleString` value of the column.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

If the column is an Oracle `REF` column, the string returned is a hexadecimal value that represents the `REF` in the database.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetOracleTimeStamp

This method returns an `OracleTimeStamp` structure of the Oracle `TimeStamp` column.

Declaration

```
// C#  
public OracleTimeStamp GetOracleTimeStamp(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `OracleTimeStamp` value of the column.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`GetOracleTimeStamp` is used with the Oracle Type `TimeStamp`.

`IsDBNull` should be called to check for `NULL` values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetOracleTimeStampLTZ

This method returns an `OracleTimeStampLTZ` structure of the specified Oracle `TimeStamp WITH LOCAL TIME ZONE` column.

Declaration

```
// C#  
public OracleTimeStampLTZ GetOracleTimeStampLTZ(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `OracleTimeStampLTZ` value of the column.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`GetOracleTimeStampLTZ` is used with the Oracle Type `TimeStamp with Local Time Zone` columns.

`IsDBNull` should be called to check for `NULL` values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetOracleTimeStampTZ

This method returns an `OracleTimeStampTZ` structure of the specified Oracle `TimeStamp WITH TIME ZONE` column.

Declaration

```
// C#  
public OracleTimeStampTZ GetOracleTimeStampTZ(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `OracleTimeStampTZ` value of the column.

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

`IndexOutOfRangeException` - The column index is invalid.

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

Used with the Oracle Type `TimeStamp with Local Time Zone` columns

`IsDBNull` should be called to check for `NULL` values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetOracleXmlType

This method returns an `OracleXmlType` object of the specified `XMLType` column.

Declaration

```
// C#
public OracleXmlType GetOracleXmlType(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `OracleXmlType` value of the column.

Exceptions

`InvalidCastException` - The accessor method is invalid for this column type or the column value is `NULL`.

Remarks

`IsDBNull` should be called to check for `NULL` values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetOracleValue

This method returns the specified column value as an `ODP.NET` type.

Declaration

```
// C#  
public object GetOracleValue(int index);
```

Parameters

- *index*

The zero-based column index.

Return Value

The value of the column as an ODP.NET type.

Exceptions

InvalidOperationException - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

IndexOutOfRangeException - The column index is invalid.

Remarks

If the column is an Oracle object or Oracle collection column and a custom type mapping exists, then a custom type is returned.

If the column is an Oracle REF column, then an `OracleRef` is returned.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetOracleValues

This method gets all the column values as ODP.NET types.

Declaration

```
// C#  
public int GetOracleValues(object[] values);
```

Parameters

- *values*

An array of objects to hold the ODP.NET types as the column values.

Return Value

The number of ODP.NET types in the *values* array.

Exceptions

InvalidOperationException - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

Remarks

This method provides a way to retrieve all column values rather than retrieving each column value individually.

The number of column values retrieved is the minimum of the length of the *values* array and the number of columns in the result set.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)
- ["LOB Support"](#) on page 3-75

GetOrdinal

This method returns the 0-based ordinal (or index) of the specified column name.

Declaration

```
// C#  
public override int GetOrdinal(string name);
```

Parameters

- *name*
The specified column name.

Return Value

The index of the column.

Implements

IDataRecord

Exceptions

InvalidOperationException - The reader is closed.

IndexOutOfRangeException - The column index is invalid.

Remarks

A case-sensitive search is made to locate the specified column by its name. If this fails, then a case-insensitive search is made.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetProviderSpecificFieldType

This method returns the provider-specific type of the specified column.

Declaration

```
// C#public override Type GetProviderSpecificFieldType(int index);
```

Parameters

- *index*
A zero-based column index.

Return Value

The provider-specific type of the specified column. This is a member of the `Oracle.DataAccess.Types` namespace.

Exceptions

`IndexOutOfRangeException` - The column index is invalid.

`InvalidOperationException` - The reader is closed, or the specified column is a UDT but no registered custom type mapping exists for the UDT.

Remarks

`GetProviderSpecificFieldType` returns a type that corresponds to the value the application obtains after invoking the `GetProviderSpecificValue` accessor on the `OracleDataReader`. For example, if the column is a string, this method returns a .NET Type object for an `OracleString`.

If the attribute is a UDT, this method may return any of the following:

- A .NET Type of the custom type, if the column is an Oracle object or Oracle collection column and a custom type mapping exists.
- A .NET Type of `OracleRef` if the column is an Oracle REF.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetProviderSpecificValue

This method returns an object that represents the underlying provider-specific value of the specified ordinal.

Declaration

```
// C#
public override object GetProviderSpecificValue (int index);
```

Parameters

index
A zero-based column index.

Return Value

An Object that is a representation of the underlying provider-specific field type.

Exceptions

`IndexOutOfRangeException` - The column index is invalid.

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called or all rows have been read.

Remarks

If the column is an Oracle object or collection column, and a custom type mapping exists, a custom type is returned.

If the column is an Oracle REF column, an `OracleRef` is returned.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetProviderSpecificValues

This method returns an array of objects that represent the underlying provider-specific values.

Declaration

```
// C#  
public override int GetProviderSpecificValues(object [ ] values);
```

Parameters

- *values*
An array of objects.

Return Value

The number of `Object` instances in the array.

Exceptions

`InvalidOperationException` - The reader is closed.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetSchemaTable

This method returns a `DataTable` that describes the column metadata of the `OracleDataReader`.

Declaration

```
// C#  
public override DataTable GetSchemaTable();
```

Return Value

A `DataTable` that contains the metadata of the result set.

Implements

`IDataReader`

Exceptions

`InvalidOperationException` - The connection is closed or the reader is closed.

Remarks

The `OracleDataReader.GetSchemaTable` method returns the `SchemaTable`.

OracleDataReader SchemaTable

The `OracleDataReader SchemaTable` is a `DataTable` that describes the column metadata of the `OracleDataReader`.

The value of `ColumnSize` can show value up to 32K depending on the definition of `VARCHAR2`, `NVARCHAR2`, or `RAW` type columns in the table definition.

The columns of the `SchemaTable` are in the order shown.

Table 6–59 OracleDataReader SchemaTable

| Name | Name Type | Description |
|-------------------------------|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>ColumnName</code> | <code>System.String</code> | The name of the column. |
| <code>ColumnOrdinal</code> | <code>System.Int32</code> | The 0-based ordinal of the column. |
| <code>ColumnSize</code> | <code>System.Int64</code> | <p>The maximum possible length of a value in the column. <code>ColumnSize</code> value is determined as follows:</p> <ul style="list-style-type: none"> ■ <code>CHAR</code> and <code>VARCHAR2</code> types: <ul style="list-style-type: none"> in bytes - if <code>IsByteSemantic</code> boolean value is true in characters - if <code>IsByteSemantic</code> boolean value is false ■ All other types: <ul style="list-style-type: none"> in bytes <p>See "IsByteSemantic" on page 6-255 for more information.</p> |
| <code>NumericPrecision</code> | <code>System.Int16</code> | <p>The maximum precision of the column, if the column is a numeric data type.</p> <p>This column has valid values for Oracle <code>NUMBER</code>, Oracle <code>INTERVAL YEAR TO MONTH</code>, and Oracle <code>INTERVAL DAY TO SECOND</code> columns. For all other columns, the value is null.</p> |
| <code>NumericScale</code> | <code>System.Int16</code> | <p>The scale of the column.</p> <p>This column has valid values for Oracle <code>NUMBER</code>, Oracle <code>INTERVAL DAY TO SECOND</code>, and the Oracle <code>TIMESTAMP</code> columns. For all other columns, the value is null.</p> |

Table 6–59 (Cont.) OracleDataReader SchemaTable

| Name | Name Type | Description |
|----------------|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IsUnique | System.Boolean | <p data-bbox="748 262 1243 287">Indicates whether or not the column is unique.</p> <p data-bbox="748 302 1333 380">true if no two rows in the base table can have the same value in this column, where the base table is the table returned in <code>BaseTableName</code>.</p> <p data-bbox="748 394 1349 447">IsUnique is guaranteed to be true if one of the following applies in descending order of priority:</p> <ul data-bbox="748 462 1360 674" style="list-style-type: none"> <li data-bbox="748 462 1360 539">■ the column constitutes a base table primary key by itself and a NOT NULL constraint has been defined on the column <li data-bbox="748 554 1360 632">■ there is a unique constraint or a unique index that applies only to this column and a NOT NULL constraint has been defined on the column <li data-bbox="748 646 1235 674">■ the column is an explicitly selected ROWID <p data-bbox="748 688 1305 741">IsUnique is false if the column can contain duplicate values in the base table.</p> <p data-bbox="748 756 967 781">The default is false.</p> <p data-bbox="748 795 1360 842">The value of this property is the same for each occurrence of the base table column in the select list.</p> |
| IsKey | System.Boolean | <p data-bbox="748 867 1308 892">Indicates whether or not the column is a key column.</p> <p data-bbox="748 907 1360 1035">true if the column is one of a set of columns in the rowset that, taken together, uniquely identify the row. The set of columns with IsKey set to true must uniquely identify a row in the rowset. There is no requirement that this set of columns is a minimal set of columns.</p> <p data-bbox="748 1050 1305 1102">This set of columns can be generated from one of the following in descending order of priority:</p> <ul data-bbox="748 1117 1360 1581" style="list-style-type: none"> <li data-bbox="748 1117 1360 1224">■ A base table primary key with the following condition: A NOT NULL constraint must be defined on the column or on all of the columns, in the case of a composite primary key. <li data-bbox="748 1239 1360 1367">■ Any of the unique constraints or unique indexes with the following condition: A NOT NULL constraint must be defined on the column or on all of the columns, in the case of a composite unique constraint or composite unique index. <li data-bbox="748 1381 1330 1459">■ A base table composite primary key with the following condition: A NULL constraint must be defined on at least one, but not all, of the columns. <li data-bbox="748 1474 1333 1581">■ Any of the composite unique constraints or composite unique indexes with the following condition: A NULL constraint must be defined on at least one, but not all, of the columns. <p data-bbox="748 1596 1360 1696">An explicitly selected ROWID. false if the column is not required to uniquely identify the row. The value of this property is the same for each occurrence of the base table column in the select list.</p> |
| IsRowID | System.Boolean | true if the column is a ROWID, otherwise false. |
| BaseColumnName | System.String | The name of the column in the database if an alias is used for the column. |
| BaseSchemaName | System.String | The name of the schema in the database that contains the column. |

Table 6–59 (Cont.) OracleDataReader SchemaTable

| Name | Name Type | Description |
|-----------------|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| BaseTableName | System.String | The name of the table or view in the database that contains the column. |
| DataType | System.RuntimeType | Maps to the common language runtime type. |
| ProviderType | Oracle.DataAccess.Client.OracleDbType | The database column type (OracleDbType) of the column. |
| AllowDBNull | System.Boolean | true if null values are allowed, otherwise false. |
| IsAliased | System.Boolean | true if the column is an alias; otherwise false. |
| IsByteSemantic | System.Boolean | IsByteSemantic is: <ul style="list-style-type: none"> ■ true if the ColumnSize value uses bytes semantics ■ false if ColumnSize uses character semantics This value is always true when connected to a database version earlier than Oracle9i. |
| IsExpression | System.Boolean | true if the column is an expression; otherwise false. |
| IsHidden | System.Boolean | true if the column is hidden; otherwise false. |
| IsReadOnly | System.Boolean | true if the column is read-only; otherwise false. |
| IsLong | System.Boolean | true if the column is a LONG, LONG RAW, BLOB, CLOB, or BFILE; otherwise false. |
| UdtTypeName | System.String | The type name of the UDT. |
| IsIdentity | System.Boolean | true if the column is an identity column; otherwise false. |
| IsAutoIncrement | System.Boolean | true if the column assigns values to new rows in fixed increments; otherwise false. <i>Not Available in ODP.NET, Managed Driver</i> |
| IdentityType | OracleIdentityType | An OracleIdentityType enumeration value that specifies how the identity column values are generated; otherwise DBNull.Value, if the column is not an identity column. <i>Not Available in ODP.NET, Managed Driver</i> |

Example

This example creates and uses the SchemaTable from the reader.

```

/* Database Setup, if you have not done so yet.
connect scott/tiger@oracle
CREATE TABLE empInfo (
empno NUMBER(4) PRIMARY KEY,
empName VARCHAR2(20) NOT NULL,
hiredate DATE,
salary NUMBER(7,2),
jobDescription Clob,
byteCodes BLOB
);

Insert into empInfo(EMPNO,EMPNAME,JOBDESCRIPTION,byteCodes) values
(1,'KING','SOFTWARE ENGR', '5657');
Insert into empInfo(EMPNO,EMPNAME,JOBDESCRIPTION,byteCodes) values
(2,'SCOTT','MANAGER', '5960');
commit;

*/

```

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class GetSchemaTableSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        string cmdstr = "SELECT EMPNO,EMPNAME FROM EMPINFO where EMPNO = 1";
        OracleCommand cmd = new OracleCommand(cmdstr, con);

        //get the reader
        OracleDataReader reader = cmd.ExecuteReader();

        //get the schema table
        DataTable schemaTable = reader.GetSchemaTable();

        //retrieve the first column info.
        DataRow row = schemaTable.Rows[0];

        //print out the column info
        Console.WriteLine("Column name: " + row["COLUMNNAME"]);
        Console.WriteLine("Precision: " + row["NUMERICPRECISION"]);
        Console.WriteLine("Scale: " + row["NUMERICSCALE"]);
        reader.Close();

        // Close the connection
        con.Close();
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetString

This method returns the string value of the specified column.

Declaration

```
// C#
public override string GetString(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The string value of the column.

Implements

IDataRecord

Exceptions

InvalidOperationException - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

IndexOutOfRangeException - The column index is invalid.

InvalidCastException - The accessor method is invalid for this column type or the column value is NULL.

Remarks

Call the `IsDBNull` method to check for null values before calling this method.

If the column is an Oracle REF column, the string returned is a hexadecimal string that represents the REF in the database.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetTimeSpan

This method returns the `TimeSpan` value of the specified `INTERVAL DAY TO SECOND` column.

Declaration

```
// C#
public TimeSpan GetTimeSpan(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The `TimeSpan` value of the column.

Implements

IDataRecord

Exceptions

InvalidOperationException - The connection is closed, the reader is closed, `Read()` has not been called, or all rows have been read.

IndexOutOfRangeException - The column index is invalid.

InvalidCastException - The accessor method is invalid for this column type or the column value is NULL.

Remarks

`IsDBNull` should be called to check for NULL values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetValue

This method returns the column value as a .NET type.

Declaration

```
// C#  
public override object GetValue(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

The value of the column as a .NET type.

Implements

`IDataRecord`

Exceptions

`InvalidOperationException` - The connection is closed, the reader is closed, `Read()` has not been called, all rows have been read, or no valid custom type mapping has been specified for the Oracle Object or Oracle Collection column.

`IndexOutOfRangeException` - The column index is invalid.

Remarks

If the column is an Oracle Object or an Oracle Collection column, the .NET custom type corresponding to the custom type mapping is returned.

If the column is an Oracle REF column, a hexadecimal value is returned as a .NET string that represents the REF in the database.

If the UDT is NULL, `DBNull.Value` is returned

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetValues

This method gets all the column values as .NET types.

Declaration

```
// C#
public override int GetValues(object[ ] values);
```

Parameters

- *values*

An array of objects to hold the .NET types as the column values.

Return Value

The number of objects in the *values* array.

Implements

IDataRecord

Exceptions

InvalidOperationException - The connection is closed, the reader is closed, *Read()* has not been called, or all rows have been read.

Remarks

This method provides a way to retrieve all column values rather than retrieving each column value individually.

The number of column values retrieved is the minimum of the length of the values array and the number of columns in the result set.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

GetXmlReader

This method returns the contents of an *XMLType* column as an instance of an .NET *XmlTextReader* object.

Declaration

```
// C#
public XmlReader GetXmlReader(int index);
```

Parameters

- *index*

The zero-based column index.

Return Value

A .NET *XmlTextReader*.

Exceptions

InvalidCastException - The accessor method is invalid for this column type or the column value is *NULL*.

Remarks

IsDBNull should be called to check for NULL values before calling this method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

IsDBNull

This method indicates whether or not the column value is NULL.

Declaration

```
// C#  
public override bool IsDBNull(int index);
```

Parameters

- *index*
The zero-based column index.

Return Value

Returns true if the column is a NULL value; otherwise, returns false.

Implements

IDataRecord

Exceptions

InvalidOperationException - The reader is closed, Read() has not been called, or all rows have been read.

IndexOutOfRangeException - The column index is invalid.

Remarks

This method should be called to check for NULL values before calling the other accessor methods.

Example

The code example for the OracleDataReader class includes the IsDBNull method. See ["Example"](#) on page 6-197.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

NextResult

This method advances the data reader to the next result set.

Declaration

```
// C#
public override bool NextResult();
```

Return Value

Returns true if another result set exists; otherwise, returns false.

Implements

IDataReader

Exceptions

InvalidOperationException - The connection is closed or the reader is closed.

Remarks

NextResult is used when reading results from stored procedure execution that return more than one result set.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

Read

This method reads the next row in the result set.

Declaration

```
// C#
public override bool Read();
```

Return Value

Returns true if another row exists; otherwise, returns false.

Implements

IDataReader

Exceptions

InvalidOperationException - The connection is closed or the reader is closed.

Remarks

The initial position of the data reader is before the first row. Therefore, the Read method must be called to fetch the first row. The row that was just read is considered the *current row*. If the OracleDataReader has no more rows to read, it returns false.

Example

The code example for the OracleDataReader class includes the Read method. See ["Example" on page 6-197](#).

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataReader Class](#)
- [OracleDataReader Members](#)

OracleDataSourceEnumerator Class

An OracleDataSourceEnumerator object allows applications to generically obtain a collection of data sources to connect to.

Class Inheritance

System.Object

System.DbDataSourceEnumerator

Oracle.DataAccess.Client.OracleDataSourceEnumerator

Declaration

```
// C#
public sealed class OracleDataSourceEnumerator : DbDataSourceEnumerator
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#

using System;
using System.Data;
using System.Data.Common;
using Oracle.DataAccess.Client;

class DataSourceEnumSample
{
    static void Main()
    {
        string ProviderName = "Oracle.DataAccess.Client";

        DbProviderFactory factory = DbProviderFactories.GetFactory(ProviderName);

        if (factory.CanCreateDataSourceEnumerator)
        {
            DbDataSourceEnumerator dsenum = factory.CreateDataSourceEnumerator();
            DataTable dt = dsenum.GetDataSources();

            // Print the first column/row entry in the DataTable
            Console.WriteLine(dt.Columns[0] + " : " + dt.Rows[0][0]);
            Console.WriteLine(dt.Columns[1] + " : " + dt.Rows[0][1]);
            Console.WriteLine(dt.Columns[2] + " : " + dt.Rows[0][2]);
            Console.WriteLine(dt.Columns[3] + " : " + dt.Rows[0][3]);
        }
    }
}
```

```
        Console.WriteLine(dt.Columns[4] + " : " + dt.Rows[0][4]);
    }
    else
        Console.WriteLine("Data source enumeration is not supported by provider");
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleDataSourceEnumerator Members](#)
- [OracleDataSourceEnumerator Constructor](#)
- [OracleDataSourceEnumerator Public Methods](#)

OracleDataSourceEnumerator Members

OracleDataSourceEnumerator members are listed in the following tables.

OracleDataSourceEnumerator Constructor

OracleDataSourceEnumerator Public Methods are listed in [Table 6–60](#).

Table 6–60 OracleDataSourceEnumerator Method

| Method | Description |
|--------------------------------------------------------|---------------------------------------------------------------------|
| OracleDataSourceEnumerator Constructor | Instantiates a new instance of the OracleDataSourceEnumerator class |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataSourceEnumerator Class](#)

OracleDataSourceEnumerator Public Methods

OracleDataSourceEnumerator Public Methods are listed in [Table 6–61](#).

Table 6–61 OracleDataSourceEnumerator Method

| Method | Description |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| GetDataSources | Returns a DataTable object with information on all the TNS alias entries in the tnsnames.ora file and entries retrieved from the LDAP servers configured in ldap.ora if LDAP Naming is enabled |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataSourceEnumerator Class](#)

OracleDataSourceEnumerator Constructor

OracleDataSourceEnumerator constructor creates new instances of an OracleDataSourceEnumerator class.

Declaration

```
// C#  
public OracleDataSourceEnumerator();
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataSourceEnumerator Class](#)
- [OracleDataSourceEnumerator Members](#)

OracleDataSourceEnumerator Public Methods

The OracleDataSourceEnumerator static method is listed in [Table 6–62](#).

Table 6–62 OracleDataSourceEnumerator Method

| Method | Description |
|--------------------------------|---------------------------------------------------------------------------------------------------|
| GetDataSources | Returns a DataTable object with information on all the TNS alias entries in the tnsnames.ora file |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDataSourceEnumerator Class](#)
- [OracleDataSourceEnumerator Members](#)

GetDataSources

This method returns a DataTable object with information on all the TNS alias entries in the tnsnames.ora file and entries retrieved from the LDAP servers configured in ldap.ora if LDAP naming is enabled.

Declaration

```
// C#
public override DataTable GetDataSources();
```

Return Value

A DataTable object.

Remarks

This method returns a DataTable object for each TNS alias entry that exists in the tnsnames.ora file and each entry retrieved from the LDAP servers. If a tnsnames.ora file is not found and LDAP Naming is not configured, then the returned DataTable object will be empty.

When Oracle Internet Directory (OID) is used for the TNS naming repository, there is a limit of 1000 TNS entries retrieved.

The following columns are returned for each row, but only the InstanceName column is populated.

- InstanceName (type: System.String)
- ServerName (type: System.String)
- ServiceName (type: System.String)
- Protocol (type: System.String)
- Port (type: System.String)

If the TNS and/or LDAP information changes for existing pooled connections, then calling GetDataSources will not return these changes unless the pools have been cleared.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleDataSourceEnumerator Class](#)
- [OracleDataSourceEnumerator Members](#)

OracleError Class

The OracleError class represents an error reported by Oracle.

Class Inheritance

System.Object

Oracle.DataAccess.Client.OracleError

Declaration

```
// C#
public sealed class OracleError
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

The OracleError class represents a warning or an error reported by Oracle.

If there are multiple errors, ODP.NET only returns the first error message on the stack.

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class OracleErrorsSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Create an OracleCommand object using the connection object
        OracleCommand cmd = con.CreateCommand();

        try
        {
            cmd.CommandText = "insert into notable values (99, 'MyText')";
            cmd.ExecuteNonQuery();
        }
    }
}
```

```
    }
    catch (OracleException ex)
    {
        Console.WriteLine("Record is not inserted into the database table.");

        foreach (OracleError error in ex.Errors)
        {
            Console.WriteLine("Error Message: " + error.Message);
            Console.WriteLine("Error Source: " + error.Source);
        }
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleError Members](#)
- [OracleError Static Methods](#)
- [OracleError Properties](#)
- [OracleError Methods](#)

OracleError Members

OracleError members are listed in the following tables.

OracleError Static Methods

The OracleError static method is listed in [Table 6–63](#).

Table 6–63 OracleError Static Method

| Method | Description |
|------------------------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

OracleError Properties

OracleError properties are listed in [Table 6–64](#).

Table 6–64 OracleError Properties

| Property | Description |
|--------------------------------|----------------------------------------------------------------------------------|
| ArrayBindIndex | Specifies the row number of errors that occurred during the Array Bind execution |
| DataSource | Specifies the Oracle service name (TNS name) that identifies the Oracle database |
| Message | Specifies the message describing the error |
| Number | Specifies the Oracle error number |
| Procedure | Specifies the stored procedure that causes the error |
| Source | Specifies the name of the data provider that generates the error |

OracleError Methods

OracleError methods are listed in [Table 6–65](#).

Table 6–65 OracleError Methods

| Method | Description |
|-----------------------------|----------------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |
| GetHashCode | Inherited from System.Object |
| GetType | Inherited from System.Object |
| ToString | Returns a string representation of the OracleError |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleError Class](#)

OracleError Static Methods

The `OracleError` static method is listed in [Table 6–66](#).

Table 6–66 *OracleError Static Method*

| Method | Description |
|---------------------|--------------------------------------------------------|
| <code>Equals</code> | Inherited from <code>System.Object</code> (Overloaded) |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleError Class](#)
- [OracleError Members](#)

OracleError Properties

OracleError properties are listed in [Table 6–67](#).

Table 6–67 OracleError Properties

| Property | Description |
|--------------------------------|----------------------------------------------------------------------------------|
| ArrayBindIndex | Specifies the row number of errors that occurred during the Array Bind execution |
| DataSource | Specifies the Oracle service name (TNS name) that identifies the Oracle database |
| Message | Specifies the message describing the error |
| Number | Specifies the Oracle error number |
| Procedure | Specifies the stored procedure that causes the error |
| Source | Specifies the name of the data provider that generates the error |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleError Class](#)
- [OracleError Members](#)

ArrayBindIndex

This property specifies the row number of errors that occurred during the Array Bind execution.

Declaration

```
// C#
public int ArrayBindIndex {get;}
```

Property Value

An int value that specifies the row number for errors that occurred during the Array Bind execution.

Remarks

Default = 0.

This property is used for Array Bind operations only.

ArrayBindIndex represents the zero-based row number at which the error occurred during an Array Bind operation. For example, if an array bind execution causes two errors on the 2nd and 4th operations, two OracleError objects appear in the OracleErrorCollection with the ArrayBindIndex property values 2 and 4 respectively.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleError Class](#)
- [OracleError Members](#)
- ["Array Binding"](#) on page 3-45

DataSource

This property specifies the Oracle service name (TNS name) that identifies the Oracle database.

Declaration

```
// C#  
public string DataSource {get;}
```

Property Value

A string.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleError Class](#)
- [OracleError Members](#)

Message

This property specifies the message describing the error.

Declaration

```
// C#  
public string Message {get;}
```

Property Value

A string.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleError Class](#)
- [OracleError Members](#)

Number

This property specifies the Oracle error number.

Declaration

```
// C#  
public int Number {get;}
```

Property Value

An int.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleError Class](#)
- [OracleError Members](#)

Procedure

This property specifies the stored procedure that causes the error.

Declaration

```
// C#  
public string Procedure {get;}
```

Property Value

The stored procedure name.

Remarks

Represents the stored procedure which creates this `OracleError` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleError Class](#)
- [OracleError Members](#)

Source

This property specifies the name of the data provider that generates the error.

Declaration

```
// C#  
public string Source {get;}
```

Property Value

A string.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleError Class](#)
- [OracleError Members](#)

OracleError Methods

OracleError methods are listed in [Table 6–68](#).

Table 6–68 OracleError Methods

| Method | Description |
|-----------------------------|----------------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |
| GetHashCode | Inherited from System.Object |
| GetType | Inherited from System.Object |
| ToString | Returns a string representation of the OracleError |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleError Class](#)
- [OracleError Members](#)

ToString

Overrides Object

This method returns a string representation of the OracleError.

Declaration

```
// C#  
public override string ToString();
```

Return Value

Returns a string with the format Ora- error number: Class.Method name error message stack trace information.

Example

ORA-24333: zero iteration count

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleError Class](#)
- [OracleError Members](#)

OracleErrorCollection Class

An OracleErrorCollection class represents a collection of all errors that are thrown by the Oracle Data Provider for .NET.

Class Inheritance

System.Object

System.ArrayList

Oracle.DataAccess.Client.OracleErrorCollection

Declaration

```
// C#
public sealed class OracleErrorCollection : ArrayList
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

A simple ArrayList that holds a list of OracleErrors.

If there are multiple errors, ODP.NET only returns the first error message on the stack.

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class OracleErrorCollectionSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Create an OracleCommand object using the connection object
        OracleCommand cmd = con.CreateCommand();

        try
        {
            cmd.CommandText = "insert into notable values (99, 'MyText')";
```

```
        cmd.ExecuteNonQuery();
    }
    catch (OracleException ex)
    {
        Console.WriteLine("Record is not inserted into the database table.");

        foreach (OracleError error in ex.Errors)
        {
            Console.WriteLine("Error Message: " + error.Message);
            Console.WriteLine("Error Source: " + error.Source);
        }
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleErrorCollection Members](#)
- [OracleErrorCollection Static Methods](#)
- [OracleErrorCollection Properties](#)
- [OracleErrorCollection Public Methods](#)

OracleErrorCollection Members

OracleErrorCollection members are listed in the following tables.

OracleErrorCollection Static Methods

OracleErrorCollection static methods are listed in [Table 6-69](#).

Table 6-69 OracleErrorCollection Static Methods

| Method | Description |
|--------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

OracleErrorCollection Properties

OracleErrorCollection properties are listed in [Table 6-70](#).

Table 6-70 OracleErrorCollection Properties

| Property | Description |
|----------------|---------------------------------------------|
| Capacity | Inherited from System.Collections.ArrayList |
| Count | Inherited from System.Collections.ArrayList |
| IsReadOnly | Inherited from System.Collections.ArrayList |
| IsSynchronized | Inherited from System.Collections.ArrayList |
| Item | Inherited from System.Collections.ArrayList |

OracleErrorCollection Public Methods

OracleErrorCollection public methods are listed in [Table 6-71](#).

Table 6-71 OracleErrorCollection Public Methods

| Public Method | Description |
|---------------|---------------------------------------------|
| CopyTo | Inherited from System.Collections.ArrayList |
| Equals | Inherited from System.Object (Overloaded) |
| GetHashCode | Inherited from System.Object |
| GetType | Inherited from System.Object |
| ToString | Inherited from System.Object |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleErrorCollection Class](#)

OracleErrorCollection Static Methods

The `OracleErrorCollection` static method is listed in [Table 6-72](#).

Table 6-72 OracleErrorCollection Static Method

| Method | Description |
|---------------------|--------------------------------------------------------|
| <code>Equals</code> | Inherited from <code>System.Object</code> (Overloaded) |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleErrorCollection Class](#)
- [OracleErrorCollection Members](#)

OracleErrorCollection Properties

OracleErrorCollection properties are listed in [Table 6-73](#).

Table 6-73 OracleErrorCollection Properties

| Property | Description |
|----------------|---------------------------------------------|
| Capacity | Inherited from System.Collections.ArrayList |
| Count | Inherited from System.Collections.ArrayList |
| IsReadOnly | Inherited from System.Collections.ArrayList |
| IsSynchronized | Inherited from System.Collections.ArrayList |
| Item | Inherited from System.Collections.ArrayList |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleErrorCollection Class](#)
- [OracleErrorCollection Members](#)

OracleErrorCollection Public Methods

OracleErrorCollection public methods are listed in [Table 6-74](#).

Table 6-74 OracleErrorCollection Public Methods

| Public Method | Description |
|---------------|---------------------------------------------|
| CopyTo | Inherited from System.Collections.ArrayList |
| Equals | Inherited from System.Object (Overloaded) |
| GetHashCode | Inherited from System.Object |
| GetType | Inherited from System.Object |
| ToString | Inherited from System.Object |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleErrorCollection Class](#)
- [OracleErrorCollection Members](#)

OracleException Class

The `OracleException` class represents an exception that is thrown when the Oracle Data Provider for .NET encounters an error. Each `OracleException` object contains at least one `OracleError` object in the `Error` property that describes the error or warning.

Class Inheritance

```
System.Object
    System.Exception
        System.SystemException
            System.Runtime.InteropServices.ExternalException
                System.Data.Common.DbException
                    Oracle.DataAccess.Client.OracleException
```

Declaration

```
// C#
public sealed class OracleException : SystemException
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

If there are multiple errors, ODP.NET only returns the first error message on the stack.

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class OracleExceptionSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Create an OracleCommand object using the connection object
        OracleCommand cmd = con.CreateCommand();
```

```
try
{
    cmd.CommandText = "insert into notable values (99, 'MyText')";
    cmd.ExecuteNonQuery();
}
catch (OracleException ex)
{
    Console.WriteLine("Record is not inserted into the database table.");
    Console.WriteLine("Exception Message: " + ex.Message);
    Console.WriteLine("Exception Source: " + ex.Source);
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleException Members](#)
- [OracleException Methods](#)
- [OracleException Static Methods](#)
- [OracleException Static Methods](#)
- [OracleException Properties](#)
- [OracleException Methods](#)

OracleException Members

OracleException members are listed in the following tables.

OracleException Static Methods

The OracleException static method is listed in [Table 6-75](#).

Table 6-75 OracleException Static Method

| Method | Description |
|--------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

OracleException Properties

OracleException properties are listed in [Table 6-76](#).

Table 6-76 OracleException Properties

| Property | Description |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| DataSource | Specifies the TNS name that contains the information for connecting to an Oracle instance |
| Errors | Specifies a collection of one or more OracleError objects that contain information about exceptions generated by the Oracle database |
| HelpLink | Inherited from System.Exception |
| InnerException | Inherited from System.Exception |
| IsRecoverable | Specifies whether the current operation producing this exception can succeed if retried <i>Not available in the ODP.NET, Managed Driver</i> |
| Message | Specifies the error messages that occur in the exception |
| Number | Specifies the Oracle error number |
| Procedure | Specifies the stored procedure that cause the exception |
| Source | Specifies the name of the data provider that generates the error |
| StackTrace | Inherited from System.Exception |
| TargetSite | Inherited from System.Exception |

OracleException Methods

OracleException methods are listed in [Table 6-77](#).

Table 6-77 OracleException Methods

| Method | Description |
|-------------------------------|------------------------------------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |
| GetBaseException | Inherited from System.Exception |
| GetHashCode | Inherited from System.Object |
| GetObjectData | Sets the serializable info object with information about the exception |
| GetType | Inherited from System.Object |

Table 6–77 (Cont.) OracleException Methods

| Method | Description |
|--------------------------|----------------------------------------------------|
| ToString | Returns the fully qualified name of this exception |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleException Class](#)

OracleException Static Methods

The `OracleException` static method is listed in [Table 6-78](#).

Table 6-78 *OracleException Static Method*

| Method | Description |
|---------------------|--------------------------------------------------------|
| <code>Equals</code> | Inherited from <code>System.Object</code> (Overloaded) |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleException Class](#)
- [OracleException Members](#)

OracleException Properties

OracleException properties are listed in [Table 6–79](#).

Table 6–79 OracleException Properties

| Property | Description |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| DataSource | Specifies the TNS name that contains the information for connecting to an Oracle instance |
| Errors | Specifies a collection of one or more <code>OracleError</code> objects that contain information about exceptions generated by the Oracle database |
| <code>HelpLink</code> | Inherited from <code>System.Exception</code> |
| <code>InnerException</code> | Inherited from <code>System.Exception</code> |
| IsRecoverable | Specifies whether the current operation producing this exception can succeed if retried <i>Not available in the ODP.NET, Managed Driver</i> |
| Message | Specifies the error messages that occur in the exception |
| Number | Specifies the Oracle error number |
| Procedure | Specifies the stored procedure that cause the exception |
| Source | Specifies the name of the data provider that generates the error |
| <code>StackTrace</code> | Inherited from <code>System.Exception</code> |
| <code>TargetSite</code> | Inherited from <code>System.Exception</code> |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleException Class](#)
- [OracleException Members](#)

DataSource

This property specifies the TNS name that contains the information for connecting to an Oracle instance.

Declaration

```
// C#
public string DataSource {get;}
```

Property Value

The TNS name containing the connect information.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleException Class](#)
- [OracleException Members](#)

Errors

This property specifies a collection of one or more `OracleError` objects that contain information about exceptions generated by the Oracle database.

Declaration

```
// C#  
public OracleErrorCollection Errors {get;}
```

Property Value

An `OracleErrorCollection`.

Remarks

The `Errors` property contains at least one instance of `OracleError` objects.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleException Class](#)
- [OracleException Members](#)

IsRecoverable

This property specifies whether the current operation producing this exception can succeed if retried.

Declaration

```
// C#  
public bool IsRecoverable {get;}
```

Property Value

A `bool`.

Remarks

When a database outage occurs, such as during a network failure, the session becomes unavailable and the client receives an error code. The client can have difficulty determining whether the in-flight operation committed or needs to be resubmitted. Oracle automatically determines whether an in-flight database operation can be recovered or not using the `IsRecoverable` property. If `IsRecoverable` returns true after an outage, then the application can retrieve the current operation status and complete the transaction. If `IsRecoverable` returns false, then the application can rollback the current operation and resubmit the transaction.

This property is often used in conjunction with Transaction Guard.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleException Class](#)
- [OracleException Members](#)
- [Using Transaction Guard to Prevent Logical Corruption](#)

Message

Overrides Exception

This property specifies the error messages that occur in the exception.

Declaration

```
// C#  
public override string Message {get;}
```

Property Value

A string.

Remarks

Message is a concatenation of all errors in the Errors collection. Each error message is concatenated and is followed by a carriage return, except the last one.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleException Class](#)
- [OracleException Members](#)

Number

This property specifies the Oracle error number.

Declaration

```
// C#  
public int Number {get;}
```

Property Value

The error number.

Remarks

This error number can be the topmost level of error generated by Oracle and can be a provider-specific error number.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleException Class](#)
- [OracleException Members](#)

Procedure

This property specifies the stored procedure that caused the exception.

Declaration

```
// C#  
public string Procedure {get;}
```

Property Value

The stored procedure name.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleException Class](#)
- [OracleException Members](#)

Source

Overrides Exception

This property specifies the name of the data provider that generates the error.

Declaration

```
// C#  
public override string Source {get;}
```

Property Value

The name of the data provider.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleException Class](#)
- [OracleException Members](#)

OracleException Methods

OracleException methods are listed in [Table 6–80](#).

Table 6–80 OracleException Methods

| Method | Description |
|-------------------------------|------------------------------------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |
| GetBaseException | Inherited from System.Exception |
| GetHashCode | Inherited from System.Object |
| GetObjectData | Sets the serializable info object with information about the exception |
| GetType | Inherited from System.Object |
| ToString | Returns the fully qualified name of this exception |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleException Class](#)
- [OracleException Members](#)

GetObjectData

Overrides Exception

This method sets the serializable info object with information about the exception.

Declaration

```
// C#
public override void GetObjectData(SerializationInfo info, StreamingContext
    context);
```

Parameters

- *info*
A SerializationInfo object.
- *context*
A StreamingContext object.

Remarks

The information includes DataSource, Message, Number, Procedure, Source, and StackTrace.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleException Class](#)
- [OracleException Members](#)

Tostring

Overrides Exception

This method returns the fully qualified name of this exception, the error message in the `Message` property, the `InnerException.ToString()` message, and the stack trace.

Declaration

```
// C#  
public override string ToString();
```

Return Value

The string representation of the exception.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
  
class ToStringSample  
{  
    static void Main()  
    {  
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";  
        OracleConnection con = new OracleConnection(constr);  
        con.Open();  
  
        // Create an OracleCommand object using the connection object  
        OracleCommand cmd = con.CreateCommand();  
  
        try  
        {  
            cmd.CommandText = "insert into notable values (99, 'MyText')";  
            cmd.ExecuteNonQuery(); // This will throw an exception  
        }  
        catch (OracleException ex)  
        {  
            Console.WriteLine("Record is not inserted into the database table.");  
            Console.WriteLine("ex.ToString() : " + ex.ToString());  
        }  
    }  
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleException Class](#)
- [OracleException Members](#)

OracleInfoMessageEventArgs Class

The `OracleInfoMessageEventArgs` class provides event data for the `OracleConnection.InfoMessage` event. When any warning occurs in the database, the `OracleConnection.InfoMessage` event is triggered along with the `OracleInfoMessageEventArgs` object that stores the event data.

Class Inheritance

`System.Object`

`System.EventArgs`

`Oracle.DataAccess.Client.OracleInfoMessageEventArgs`

Declaration

```
// C#
public sealed class OracleInfoMessageEventArgs
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|-----------------------|---------------------------------------|----------------------------------------------|
| Assembly | <code>Oracle.DataAccess.dll</code> | <code>Oracle.ManagedDataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Client</code> | <code>Oracle.ManagedDataAccess.Client</code> |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class InfoMessageSample
{
    public static void WarningHandler(object src,
        OracleInfoMessageEventArgs args)
    {
        Console.WriteLine("Source object is: " + src.GetType().Name);
        Console.WriteLine("InfoMessageArgs.Message is " + args.Message);
        Console.WriteLine("InfoMessageArgs.Source is " + args.Source);
    }
    static void Main()
    {
        OracleConnection con = new OracleConnection("User Id=scott;" +
            "Password=tiger;Data Source=oracle;");

        con.Open();
    }
}
```

```
OracleCommand cmd = con.CreateCommand();

//Register to the InfoMessageHandler
cmd.Connection.InfoMessage +=
    new OracleInfoMessageEventHandler(WarningHandler);

cmd.CommandText =
    "create or replace procedure SelectWithNoInto( " +
    " empname in VARCHAR2) AS " +
    "BEGIN " +
    " select * from emp where ename = empname; " +
    "END SelectWithNoInto;";

// Execute the statement that produces a warning
cmd.ExecuteNonQuery();

// Clean up
cmd.Dispose();
con.Dispose();
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleInfoMessageEventArgs Members](#)
- [OracleInfoMessageEventArgs Static Methods](#)
- [OracleInfoMessageEventArgs Properties](#)
- [OracleInfoMessageEventArgs Public Methods](#)
- ["OracleConnection Class"](#) on page 6-79

OracleInfoMessageEventArgs Members

OracleInfoMessageEventArgs members are listed in the following tables.

OracleInfoMessageEventArgs Static Methods

The OracleInfoMessageEventArgs static methods is listed in [Table 6–81](#).

Table 6–81 OracleInfoMessageEventArgs Static Method

| Method | Description |
|------------------------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

OracleInfoMessageEventArgs Properties

The OracleInfoMessageEventArgs properties are listed in [Table 6–82](#).

Table 6–82 OracleInfoMessageEventArgs Properties

| Property | Description |
|-------------------------|-----------------------------------------------------------------|
| Errors | Specifies the collection of errors generated by the data source |
| Message | Specifies the error text generated by the data source |
| Source | Specifies the name of the object that generated the error |

OracleInfoMessageEventArgs Public Methods

The OracleInfoMessageEventArgs methods are listed in [Table 6–83](#).

Table 6–83 OracleInfoMessageEventArgs Public Methods

| Method | Description |
|-----------------------------|-----------------------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |
| GetHashCode | Inherited from System.Object |
| GetType | Inherited from System.Object |
| ToString | Returns the string representation of the current instance |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleInfoMessageEventArgs Class](#)

OracleInfoMessageEventArgs Static Methods

The `OracleInfoMessageEventArgs` static method is listed in [Table 6–84](#).

Table 6–84 *OracleInfoMessageEventArgs Static Method*

| Method | Description |
|---------------------|--------------------------------------------------------|
| <code>Equals</code> | Inherited from <code>System.Object</code> (Overloaded) |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleInfoMessageEventArgs Class](#)
- [OracleInfoMessageEventArgs Members](#)

OracleInfoMessageEventArgs Properties

The OracleInfoMessageEventArgs properties are listed in [Table 6–85](#).

Table 6–85 OracleInfoMessageEventArgs Properties

| Property | Description |
|-------------------------|-----------------------------------------------------------------|
| Errors | Specifies the collection of errors generated by the data source |
| Message | Specifies the error text generated by the data source |
| Source | Specifies the name of the object that generated the error |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleInfoMessageEventArgs Class](#)
- [OracleInfoMessageEventArgs Members](#)

Errors

This property specifies the collection of errors generated by the data source.

Declaration

```
// C#  
public OracleErrorCollection Errors {get;}
```

Property Value

The collection of errors.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleInfoMessageEventArgs Class](#)
- [OracleInfoMessageEventArgs Members](#)

Message

This property specifies the error text generated by the data source.

Declaration

```
// C#  
public string Message {get;}
```

Property Value

The error text.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleInfoMessageEventArgs Class](#)
- [OracleInfoMessageEventArgs Members](#)

Source

This property specifies the name of the object that generated the error.

Declaration

```
// C#  
public string Source {get;}
```

Property Value

The object that generated the error.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleInfoMessageEventArgs Class](#)
- [OracleInfoMessageEventArgs Members](#)

OracleInfoMessageEventArgs Public Methods

The `OracleInfoMessageEventArgs` methods are listed in [Table 6–86](#).

Table 6–86 OracleInfoMessageEventArgs Public Methods

| Method | Description |
|--------------------------|-----------------------------------------------------------|
| <code>Equals</code> | Inherited from <code>System.Object</code> (Overloaded) |
| <code>GetHashCode</code> | Inherited from <code>System.Object</code> |
| <code>GetType</code> | Inherited from <code>System.Object</code> |
| ToString | Returns the string representation of the current instance |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleInfoMessageEventArgs Class](#)
- [OracleInfoMessageEventArgs Members](#)

ToString

Overrides `Object`

This method returns the string representation of the current instance.

Declaration

```
// C#
public override string ToString();
```

Return Value

Returns the `OracleInfoMessageEventArgs` value in a string representation.

Remarks

If the current instance has a null value, the returned string is null.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleInfoMessageEventArgs Class](#)
- [OracleInfoMessageEventArgs Members](#)

OracleInfoMessageEventHandler Delegate

The `OracleInfoMessageEventHandler` represents the signature of the method that handles the `OracleConnection.InfoMessage` event.

Declaration

```
// C#
public delegate void OracleInfoMessageEventHandler(object sender,
    OracleInfoMessageEventArgs eventArgs);
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Parameters

- *sender*
The source of the event.
- *eventArgs*
The `OracleInfoMessageEventArgs` object that contains the event data.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- ["InfoMessage"](#) on page 6-132

OracleLogicalTransaction Class

The `OracleLogicalTransaction` class provides detailed information about the logical transaction status. Applications can conclusively determine the outcome of the running transaction during the last database outage, then act accordingly to commit, complete, or rollback the transaction.

Class Inheritance

`System.Object`

`System.MarshalByRefObject`

`Oracle.DataAccess.Client.OracleLogicalTransaction`

Declaration

```
// C#  
public sealed class OracleLogicalTransaction
```

Requirements

| | |
|-----------------------|---------------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | <code>Oracle.DataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Client</code> |
| .NET Framework | 3.5, 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleLogicalTransaction Members](#)
- [OracleLogicalTransaction Public Read-Only Properties](#)
- [OracleLogicalTransaction Private Properties](#)
- [OracleLogicalTransaction Methods](#)

OracleLogicalTransaction Members

OracleLogicalTransaction members are listed in the following tables.

OracleLogicalTransaction Public Read-Only Properties

OracleLoigcalTransaction public read-only properties are listed in [Table 6-87](#)

Table 6-87 OracleLogicalTransaction Public Read-Only Properties

| Property | Description |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Committed | Specifies if the transaction was committed or not |
| UserCallCompleted | Specifies if the transaction completed and that the information returned may be incomplete and/or not all expected work was completed |
| UserId | Specifies the user ID that is associated with the connection from which this object was obtained from |
| DataSource | Specifies the data source, for example TNS alias, that is associated with the connection from which this object was obtained from |

OracleLogicalTransaction Private Properties

OracleLoigcalTransaction private properties are listed in [Table 6-88](#)

Table 6-88 OracleLogicalTransaction Private Properties

| Property | Description |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| OracleConnection | Holds a reference to a "cloned" OracleConnection which is identical to the one that the OracleLogicalTransaction was obtained from. |

OracleLogicalTransaction Methods

OracleLoigcalTransaction private properties are listed in [Table 6-89](#)

Table 6-89 OracleLogicalTransaction Methods

| Property | Description |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Dispose | This method releases any resources or memory allocated by the object |
| GetOutcome | This method retrieves the transaction outcome from the database server. The method will determine whether the transaction committed and completed or not. |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleLogicalTransaction Class](#)

OracleLogicalTransaction Public Read-Only Properties

OracleLoigcalTransaction public read-only properties are listed in [Table 6–90](#)

Table 6–90 OracleLogicalTransaction Public Read-Only Properties

| Property | Description |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Committed | Specifies if the transaction was committed or not |
| UserCallCompleted | Specifies if the transaction completed and that the information returned may be incomplete and/or not all expected work was completed |
| UserId | Specifies the user ID that is associated with the connection from which this object was obtained from |
| DataSource | Specifies the datasource, for example TNS alias, that is associated with the connection from which this object was obtained from |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleLogicalTransaction Class](#)
- [OracleLogicalTransaction Members](#)

Committed

This property specifies if the transaction was committed or not.

Declaration

```
// C#
public bool? Committed {get;}
```

Property Value

bool.

Remarks

If `GetOutcome()` is not called, the this property holds a null value.

Once `GetOutcome()` is called, then this property will hold either true or false.

[Table 6–91](#) describes the possible outcomes of the `Committed` and `UserCallCompleted` properties.

Table 6–91 Outcome of OracleLogicalTransaction Committed and UserCallCompleted Properties

| Committed Value | UserCallCompleted Value | Outcome |
|-----------------|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| false | false | The call did not execute the commit. |
| true | true | The call did execute the commit and there was no additional information to return and no more work to do if that call was a PL/SQL procedure. |

Table 6–91 (Cont.) Outcome of OracleLogicalTransaction Committed and UserCallCompleted Properties

| Committed Value | UserCallCompleted Value | Outcome |
|-----------------|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| true | false | The transaction is committed, but the information returned may be incomplete and/or not all expected work was completed. Examples of incomplete information or incomplete work done include: the number of rows modified when using autocommit or commit on success, parameter and function results when calling PL/SQL procedures, or PL/SQL procedures with more work to do after the commit. In order to function correctly, .NET applications that use data returned from the commit must check the UserCallCompleted value. |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleLogicalTransaction Class](#)
- [OracleLogicalTransaction Members](#)

UserCallCompleted

This property specifies if the transaction completed and that the information returned may be incomplete and/or not all expected work was completed.

Declaration

```
// C#
public bool? UserCallCompleted {get;}
```

Property Value

bool

Remarks

If `GetOutcome()` is not called, the this property holds a null value.

Once `GetOutcome()` is called, then this property will hold either `true` or `false`.

[Table 6–91](#) describes the possible outcomes of the `Committed` and `UserCallCompleted` properties.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleLogicalTransaction Class](#)
- [OracleLogicalTransaction Members](#)

Userld

This property specifies user ID that is associated with the connection from which this object was obtained form.

Declaration

```
// C#  
public string UserId {get;}
```

Property Value

The user ID as a string.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleLogicalTransaction Class](#)
- [OracleLogicalTransaction Members](#)

DataSource

This property specifies the data source, for example TNS alias, that is associated with the connection from which this object was obtained from.

Declaration

```
// C#  
public string DataSource {get;}
```

Property Value

The data source as a string.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleLogicalTransaction Class](#)
- [OracleLogicalTransaction Members](#)

OracleLogicalTransaction Private Properties

OracleLoigcalTransaction private properties are listed in [Table 6-92](#)

Table 6-92 OracleLogicalTransaction Private Properties

| Property | Description |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| OracleConnection | Holds a reference to a "cloned" OracleConnection which is identical to the one that the OracleLogicalTransaction was obtained from. |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleLogicalTransaction Class](#)
- [OracleLogicalTransaction Members](#)

OracleLogicalTransaction Methods

OracleLoigcalTransaction private properties are listed in [Table 6-93](#)

Table 6-93 OracleLogicalTransaction Methods

| Property | Description |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Dispose | This method releases any resources or memory allocated by the object |
| GetOutcome | This method retrieves the transaction outcome from the database server. The method will determine whether the transaction committed and completed or not. |

Dispose

This method releases any resources or memory allocated by the object

Declaration

```
// C#
public void Dispose();
```

Implements

IDisposable

Remarks

The `Dispose` method also closes the `OracleLogicalTransaction` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleLogicalTransaction Class](#)
- [OracleLogicalTransaction Members](#)

GetOutcome

The `GetOutcome` method retrieves the transaction outcome from the database server. The method will determine whether the transaction committed and completed or not.

Overload List:

- `GetOutcome()`

This method uses cloned `OracleConnection` that the `OracleLogicalTransaction` was obtained from.

The connection is opened with `pooling=false` and thus the connection gets severed/closed/freed as soon as the outcome is forced.

Repeated calls will not incur server round-trip.
- `GetOutcome(string userid, string password, string dataSource)`

This method uses cloned `OracleConnection` that the `OracleLogicalTransaction` was obtained from.

The connection gets severed/closed/freed as soon as the outcome is forced.

Repeated calls will not incur server round-trip.

Note: Once one server round-trip is incurred for the `GetOutcome()` invocation, the PL/SQL `ForceOutcome` is never invoked again against the server for a given `OracleLogicalTransaction` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleLogicalTransaction Class](#)
- [OracleLogicalTransaction Members](#)

OracleLogicalTransactionStatus Class

The `OracleLogicalTransactionStatus` class provides information on the status of a logical transaction.

This class has been deprecated in ODP.NET 12.1.0.2. It will be desupported in a future release.

Class Inheritance

`System.Object`

`System.MarshalByRefObject`

`Oracle.DataAccess.Client.OracleLogicalTransactionStatus`

Declaration

```
// C#  
public sealed class OracleLogicalTransactionStatus
```

Requirements

| | |
|-----------------------|---------------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | <code>Oracle.DataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Client</code> |
| .NET Framework | 3.5, 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleLogicalTransactionStatus Properties](#)

OracleLogicalTransactionStatus Properties

OracleLoigcalTransactionStatus properties are listed in [Table 6–94](#)

Table 6–94 OracleLogicalTransactionStatus Properties

| Property | Description |
|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Committed | Specifies if a transaction was committed |
| UserCallCompleted | Specifies if the application expects additional data such as PL/SQL out binds or DML to be returned with the COMMIT or if the COMMIT is part way through a PL/SQL |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleLogicalTransactionStatus Class](#)

Committed

This property returns true if the transaction was committed.

Declaration

```
// C#
public bool Committed {get; set;}
```

Property Value

bool

Remarks

[Table 6–95](#) describes the possible outcomes of the [Committed](#) and [UserCallCompleted](#) properties.

Table 6–95 Outcome of OracleLogicalTransactionStatus Properties

| Committed Value | UserCallCompleted Value | Outcome |
|-----------------|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| false | false | The call did not execute the commit. |
| true | true | The call did execute the commit and there was no additional information to return and no more work to do if that call was a PL/SQL procedure. |
| true | false | The transaction is committed, but the information returned may be incomplete and/or not all expected work was completed. Examples of incomplete information or incomplete work done include: the number of rows modified when using autocommit or commit on success, parameter and function results when calling PL/SQL procedures, or PL/SQL procedures with more work to do after the commit. In order to function correctly, .NET applications that use data returned from the commit must check the UserCallCompleted value. |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleLogicalTransactionStatus Class](#)

UserCallCompleted

This property returns `true` if the application expects additional data such as PL/SQL out binds or DML to be returned with the commit or if the commit is part way through a PL/SQL procedure.

Declaration

```
// C#  
public bool UserCallCompleted {get; set;}
```

Property Value

`bool`

Remarks

[Table 6–95](#) describes the possible outcomes of the `Committed` and `UserCallCompleted` properties.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleLogicalTransactionStatus Class](#)

OracleParameter Class

An OracleParameter object represents a parameter for an OracleCommand or a DataSet column.

Class Inheritance

```
System.Object
    System.MarshalByRefObject
        System.Data.Common.DbParameter
            Oracle.DataAccess.Client.OracleParameter
```

Declaration

```
// C#
public sealed class OracleParameter : DbParameter, IDisposable, ICloneable
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Exceptions

ArgumentException - The type binding is invalid.

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class OracleParameterSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleParameter[] prm = new OracleParameter[3];

        // Create OracleParameter objects through OracleParameterCollection
        OracleCommand cmd = con.CreateCommand();
```

```
cmd.CommandText = "select max(empno) from emp";
int maxno = int.Parse(cmd.ExecuteScalar().ToString());

prm[0] = cmd.Parameters.Add("paramEmpno", OracleDbType.Decimal,
    maxno + 10, ParameterDirection.Input);
prm[1] = cmd.Parameters.Add("paramEname", OracleDbType.Varchar2,
    "Client", ParameterDirection.Input);
prm[2] = cmd.Parameters.Add("paramDeptNo", OracleDbType.Decimal,
    10, ParameterDirection.Input);
cmd.CommandText =
    "insert into emp(empno, ename, deptno) values(:1, :2, :3)";
cmd.ExecuteNonQuery();

Console.WriteLine("Record for employee id {0} has been inserted.",
    maxno + 10);
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleParameter Members](#)
- [OracleParameter Constructors](#)
- [OracleParameter Static Methods](#)
- [OracleParameter Properties](#)
- [OracleParameter Public Methods](#)

OracleParameter Members

OracleParameter members are listed in the following tables.

OracleParameter Constructors

OracleParameter constructors are listed in [Table 6–96](#).

Table 6–96 OracleParameter Constructors

| Constructor | Description |
|----------------------------------------------|-------------------------------------------------------------------|
| OracleParameter Constructors | Instantiates a new instance of OracleParameter class (Overloaded) |

OracleParameter Static Methods

OracleParameter static methods are listed in [Table 6–97](#).

Table 6–97 OracleParameter Static Methods

| Method | Description |
|------------------------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

OracleParameter Properties

OracleParameter properties are listed in [Table 6–98](#).

Table 6–98 OracleParameter Properties

| Property | Description |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ArrayBindSize | Specifies the input or output size of elements in Value property of a parameter before or after an Array Bind or PL/SQL Associative Array Bind execution |
| ArrayBindStatus | Specifies the input or output status of elements in Value property of a parameter before or after an Array Bind or PL/SQL Associative Array Bind execution |
| CollectionType | Specifies whether or not the OracleParameter represents a collection, and if so, specifies the collection type |
| DbType | Specifies the data type of the parameter using the Data.DbType enumeration type |
| Direction | Specifies whether the parameter is input-only, output-only, bi-directional, or a stored function return value parameter |
| IsNullable | Not supported |
| Offset | Specifies the offset to the Value property or offset to the elements in the Value property |
| OracleDbType | Specifies the Oracle data type |
| OracleDbTypeEx | Specifies the Oracle data type to bind the parameter as, but returns a .NET type as output |
| ParameterName | Specifies the name of the parameter |
| Precision | Specifies the maximum number of digits used to represent the Value property |
| Scale | Specifies the number of decimal places to which Value property is resolved |

Table 6–98 (Cont.) OracleParameter Properties

| Property | Description |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Size | Specifies the maximum size, in bytes or characters, of the data transmitted to or from the database. For PL/SQL Associative Array Bind, <code>Size</code> specifies the maximum number of elements in PL/SQL Associative Array |
| SourceColumn | Specifies the name of the <code>DataTable</code> Column of the <code>DataSet</code> |
| SourceColumnNull Mapping | Specifies a value which indicates whether the source column is nullable |
| SourceVersion | Specifies the <code>DataRowVersion</code> value to use when loading the <code>Value</code> property of the parameter |
| Status | Indicates the status of the execution related to the data in the <code>Value</code> property |
| UdtTypeName | Specifies the Oracle user-defined type name if the parameter is a user-defined data type |
| Value | Specifies the value of the <code>Parameter</code> |

OracleParameter Public Methods

OracleParameter public methods are listed in [Table 6–99](#).

Table 6–99 OracleParameter Public Methods

| Public Method | Description |
|----------------------------------------|--------------------------------------------------------------------------------------------------------------------|
| Clone | Creates a shallow copy of an <code>OracleParameter</code> object |
| <code>CreateObjRef</code> | Inherited from <code>System.MarshalByRefObject</code> |
| Dispose | Releases allocated resources |
| <code>Equals</code> | Inherited from <code>System.Object</code> (Overloaded) |
| <code>GetHashCode</code> | Inherited from <code>System.Object</code> |
| <code>GetLifetimeService</code> | Inherited from <code>System.MarshalByRefObject</code> |
| <code>GetType</code> | Inherited from <code>System.Object</code> |
| <code>InitializeLifetimeService</code> | Inherited from <code>System.MarshalByRefObject</code> |
| ResetDbType | Resets the type associated with the parameter so that it can infer its type from the value passed in the parameter |
| ResetOracleDbType | Resets the type associated with the parameter so that it can infer its type from the value passed in the parameter |
| ToString | Returns the string representation of the current instance |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)

OracleParameter Constructors

OracleParameter constructors instantiate new instances of the OracleParameter class.

Overload List:

- [OracleParameter\(\)](#)
This constructor instantiates a new instance of OracleParameter class.
- [OracleParameter\(string, OracleDbType\)](#)
This constructor instantiates a new instance of OracleParameter class using the supplied parameter name and Oracle data type.
- [OracleParameter\(string, object\)](#)
This constructor instantiates a new instance of the OracleParameter class using the supplied parameter name and parameter value.
- [OracleParameter\(string, OracleDbType, ParameterDirection\)](#)
This constructor instantiates a new instance of the OracleParameter class using the supplied parameter name, data type, and parameter direction.
- [OracleParameter\(string, OracleDbType, object, ParameterDirection\)](#)
This constructor instantiates a new instance of the OracleParameter class using the supplied parameter name, data type, value, and direction.
- [OracleParameter\(string, OracleDbType, int\)](#)
This constructor instantiates a new instance of the OracleParameter class using the supplied parameter name, data type, and size.
- [OracleParameter\(string, OracleDbType, int, string\)](#)
This constructor instantiates a new instance of the OracleParameter class using the supplied parameter name, data type, size, and source column.
- [OracleParameter\(string, OracleDbType, int, ParameterDirection, bool, byte, byte, string, DataRowVersion, object\)](#)
This constructor instantiates a new instance of the OracleParameter class using the supplied parameter name, data type, size, direction, null indicator, precision, scale, source column, source version and parameter value.
- [OracleParameter\(string, OracleDbType, int, object, ParameterDirection\)](#)
This constructor instantiates a new instance of the OracleParameter class using the supplied parameter name, data type, size, value, and direction.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)

OracleParameter()

This constructor instantiates a new instance of OracleParameter class.

Declaration

```
// C#  
public OracleParameter();
```

Remarks**Default Values:**

- DbType - String
- ParameterDirection - Input
- isNullable - true
- offset - 0
- OracleDbType - Varchar2
- ParameterAlias - Empty string
- ParameterName - Empty string
- Precision - 0
- Size - 0
- SourceColumn - Empty string
- SourceVersion - Current
- ArrayBindStatus - Success
- Value - null

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#) on page 6-429
- ["OracleParameterCollection Class"](#) on page 6-349

OracleParameter(string, OracleDbType)

This constructor instantiates a new instance of `OracleParameter` class using the supplied parameter name and Oracle data type.

Declaration

```
// C#  
public OracleParameter(string parameterName, OracleDbType oraType);
```

Parameters

- *parameterName*
The parameter name.
- *oraType*
The data type of the `OracleParameter`.

Remarks

Changing the `DbType` implicitly changes the `OracleDbType`.

Unless explicitly set in the constructor, all the properties have the default values.

Default Values:

- `DbType` - String
- `ParameterDirection` - Input
- `isNullable` - true
- `offset` - 0
- `OracleDbType` - Varchar2
- `ParameterAlias` - Empty string
- `ParameterName` - Empty string
- `Precision` - 0
- `Size` - 0
- `SourceColumn` - Empty string
- `SourceVersion` - Current
- `ArrayBindStatus` - Success
- `Value` - null

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#) on page 6-429
- ["OracleParameterCollection Class"](#) on page 6-349

OracleParameter(string, object)

This constructor instantiates a new instance of the `OracleParameter` class using the supplied parameter name and parameter value.

Declaration

```
// C#
public OracleParameter(string parameterName, object obj);
```

Parameters

- *parameterName*
The parameter name.
- *obj*
The value of the `OracleParameter`.

Remarks

Unless explicitly set in the constructor, all the properties have the default values.

Default Values:

- DbType - String
- ParameterDirection - Input
- isNullable - true
- offset - 0
- OracleDbType - Varchar2
- ParameterAlias - Empty string
- ParameterName - Empty string
- Precision - 0
- Size - 0
- SourceColumn - Empty string
- SourceVersion - Current
- ArrayBindStatus - Success
- Value - null

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#) on page 6-429
- ["OracleParameterCollection Class"](#) on page 6-349

OracleParameter(string, OracleDbType, ParameterDirection)

This constructor instantiates a new instance of the `OracleParameter` class using the supplied parameter name, data type, and parameter direction.

Declaration

```
// C#  
public OracleParameter(string parameterName, OracleDbType type,  
    ParameterDirection direction);
```

Parameters

- *parameterName*
The parameter name.
- *type*
The data type of the `OracleParameter`.
- *direction*
The direction of the `OracleParameter`.

Remarks

Unless explicitly set in the constructor, all the properties have the default values.

Default Values:

- DbType - String
- ParameterDirection - Input
- isNullable - true
- offset - 0
- OracleDbType - Varchar2
- ParameterAlias - Empty string
- ParameterName - Empty string
- Precision - 0
- Size - 0
- SourceColumn - Empty string
- SourceVersion - Current
- ArrayBindStatus - Success
- Value - null

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#) on page 6-429
- ["OracleParameterCollection Class"](#) on page 6-349

OracleParameter(string, OracleDbType, object, ParameterDirection)

This constructor instantiates a new instance of the `OracleParameter` class using the supplied parameter name, data type, value, and direction.

Declaration

```
// C#
public OracleParameter(string parameterName, OracleDbType type, object obj,
    ParameterDirection direction);
```

Parameters

- *parameterName*
The parameter name.
- *type*
The data type of the `OracleParameter`.
- *obj*
The value of the `OracleParameter`.
- *direction*
The `ParameterDirection` value.

Remarks

Changing the `DbType` implicitly changes the `OracleDbType`.

Unless explicitly set in the constructor, all the properties have the default values.

Default Values:

- `DbType` - String
- `ParameterDirection` - Input
- `isNullable` - true
- `offset` - 0
- `OracleDbType` - Varchar2
- `ParameterAlias` - Empty string
- `ParameterName` - Empty string
- `Precision` - 0
- `Size` - 0
- `SourceColumn` - Empty string
- `SourceVersion` - Current
- `ArrayBindStatus` - Success
- `Value` - null

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#) on page 6-429
- ["OracleParameterCollection Class"](#) on page 6-349

OracleParameter(string, OracleDbType, int)

This constructor instantiates a new instance of the `OracleParameter` class using the supplied parameter name, data type, and size.

Declaration

```
// C#
public OracleParameter(string parameterName, OracleDbType type,
    int size);
```

Parameters

- *parameterName*
The parameter name.
- *type*
The data type of the `OracleParameter`.
- *size*
The size of the `OracleParameter` value.

Remarks

Unless explicitly set in the constructor, all the properties have the default values.

Default Values:

- DbType - String
- ParameterDirection - Input
- isNullable - true
- offset - 0
- OracleDbType - Varchar2
- ParameterAlias - Empty string
- ParameterName - Empty string
- Precision - 0
- Size - 0
- SourceColumn - Empty string
- SourceVersion - Current
- ArrayBindStatus - Success
- Value - null

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#) on page 6-429
- ["OracleParameterCollection Class"](#) on page 6-349

OracleParameter(string, OracleDbType, int, string)

This constructor instantiates a new instance of the OracleParameter class using the supplied parameter name, data type, size, and source column.

Declaration

```
// C#  
public OracleParameter(string parameterName, OracleDbType type, int size,  
    string srcColumn);
```

Parameters

- *parameterName*
The parameter name.
- *type*
The data type of the OracleParameter.
- *size*
The size of the OracleParameter value.
- *srcColumn*

The name of the source column.

Remarks

Unless explicitly set in the constructor, all the properties have the default values.

Default Values:

- DbType - String
- ParameterDirection - Input
- isNullable - true
- offset - 0
- OracleDbType - Varchar2
- ParameterAlias - Empty string
- ParameterName - Empty string
- Precision - 0
- Size - 0
- SourceColumn - Empty string
- SourceVersion - Current
- ArrayBindStatus - Success
- Value - null

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#) on page 6-429

OracleParameter(string, OracleDbType, int, ParameterDirection, bool, byte, byte, string, DataRowVersion, object)

This constructor instantiates a new instance of the `OracleParameter` class using the supplied parameter name, data type, size, direction, null indicator, precision, scale, source column, source version and parameter value.

Declaration

```
// C#
public OracleParameter(string parameterName, OracleDbType oraType,
    int size, ParameterDirection direction, bool isNullable, byte
    precision, byte scale, string srcColumn, DataRowVersion srcVersion,
    object obj);
```

Parameters

- *parameterName*
The parameter name.
- *oraType*

The data type of the OracleParameter.

- *size*
The size of the OracleParameter value.
- *direction*
The ParameterDirection value.
- *isNullable*
An indicator that specifies if the parameter value can be null.
- *precision*
The precision of the parameter value.
- *scale*
The scale of the parameter value.
- *srcColumn*
The name of the source column.
- *srcVersion*
The DataRowVersion value.
- *obj*
The parameter value.

Exceptions

ArgumentException - The supplied value does not belong to the type of Value property in any of the OracleTypes.

Remarks

Unless explicitly set in the constructor, all the properties have the default values.

Default Values:

- DbType - String
- ParameterDirection - Input
- isNullable - true
- offset - 0
- OracleDbType - Varchar2
- ParameterAlias - Empty string
- ParameterName - Empty string
- Precision - 0
- Size - 0
- SourceColumn - Empty string
- SourceVersion - Current
- ArrayBindStatus - Success
- Value - null

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#) on page 6-429

OracleParameter(string, OracleDbType, int, object, ParameterDirection)

This constructor instantiates a new instance of the `OracleParameter` class using the supplied parameter name, data type, size, value, and direction.

Declaration

```
// C#
public OracleParameter(string parameterName, OracleDbType type, int size,
    object obj, ParameterDirection direction);
```

Parameters

- *parameterName*
The parameter name.
- *type*
The data type of the `OracleParameter`.
- *size*
The size of the `OracleParameter` value.
- *obj*
The value of the `OracleParameter`.
- *direction*
The `ParameterDirection` value.

Remarks

Changing the `DbType` implicitly changes the `OracleDbType`.

Unless explicitly set in the constructor, all the properties have the default values.

Default Values:

- `DbType` - `String`
- `ParameterDirection` - `Input`
- `isNullable` - `true`
- `offset` - `0`
- `OracleDbType` - `Varchar2`
- `ParameterAlias` - `Empty string`
- `ParameterName` - `Empty string`
- `Precision` - `0`
- `Size` - `0`

- SourceColumn - Empty string
- SourceVersion - Current
- ArrayBindStatus - Success
- Value - null

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#) on page 6-429
- ["OracleParameterCollection Class"](#) on page 6-349

OracleParameter Static Methods

The `OracleParameter` static method is listed in [Table 6–100](#).

Table 6–100 *OracleParameter Static Method*

| Method | Description |
|---------------------|--------------------------------------------------------|
| <code>Equals</code> | Inherited from <code>System.Object</code> (Overloaded) |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)

OracleParameter Properties

OracleParameter properties are listed in [Table 6–101](#).

Table 6–101 OracleParameter Properties

| Property | Description |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ArrayBindSize | Specifies the input or output size of elements in <code>Value</code> property of a parameter before or after an Array Bind or PL/SQL Associative Array Bind execution |
| ArrayBindStatus | Specifies the input or output status of elements in <code>Value</code> property of a parameter before or after an Array Bind or PL/SQL Associative Array Bind execution |
| CollectionType | Specifies whether or not the <code>OracleParameter</code> represents a collection, and if so, specifies the collection type |
| DbType | Specifies the data type of the parameter using the <code>Data.DbType</code> enumeration type |
| Direction | Specifies whether the parameter is input-only, output-only, bi-directional, or a stored function return value parameter |
| IsNullable | Not supported |
| Offset | Specifies the offset to the <code>Value</code> property or offset to the elements in the <code>Value</code> property |
| OracleDbType | Specifies the Oracle data type |
| OracleDbTypeEx | Specifies the Oracle data type to bind the parameter as, but returns a .NET type as output |
| ParameterName | Specifies the name of the parameter |
| Precision | Specifies the maximum number of digits used to represent the <code>Value</code> property |
| Scale | Specifies the number of decimal places to which <code>Value</code> property is resolved |
| Size | Specifies the maximum size, in bytes or characters, of the data transmitted to or from the database. For PL/SQL Associative Array Bind, <code>Size</code> specifies the maximum number of elements in PL/SQL Associative Array |
| SourceColumn | Specifies the name of the <code>DataTable Column</code> of the <code>DataSet</code> |
| SourceColumnNull Mapping | Specifies a value which indicates whether the source column is nullable |
| SourceVersion | Specifies the <code>DataRowVersion</code> value to use when loading the <code>Value</code> property of the parameter |
| Status | Indicates the status of the execution related to the data in the <code>Value</code> property |
| UdtTypeName | Specifies the Oracle user-defined type name if the parameter is a user-defined data type |
| Value | Specifies the value of the <code>Parameter</code> |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)

ArrayBindSize

This property specifies the maximum size, in bytes or characters, of the data for each array element transmitted to or from the database. This property is used for Array Bind or PL/SQL Associative Array execution.

Declaration

```
// C#
public int[] ArrayBindSize {get; set; }
```

Property Value

An array of int values specifying the size.

Remarks

Default = null.

This property is only used for variable size element types for an Array Bind or PL/SQL Associative Array. For fixed size element types, this property is ignored.

Each element in the ArrayBindSize corresponds to the bind size of an element in the Value property. Before execution, ArrayBindSize specifies the maximum size of each element to be bound in the Value property. After execution, it contains the size of each element returned in the Value property.

For binding a PL/SQL Associative Array, whose elements are of a variable-length element type, as an InputOutput, Out, or ReturnValue parameter, this property must be set properly. The number of elements in ArrayBindSize must be equal to the value specified in the OracleParameter.Size property.

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class ArrayBindSizeSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleParameter[] prm = new OracleParameter[3];

        // Create OracleParameter objects through OracleParameterCollection
        OracleCommand cmd = con.CreateCommand();

        cmd.CommandText = "select max(empno) from emp";
```

```

int maxno = int.Parse(cmd.ExecuteScalar().ToString());

// Set the ArrayBindCount for Array Binding
cmd.ArrayBindCount = 2;

prm[0] = cmd.Parameters.Add("paramEmpno", OracleDbType.Decimal,
    new int[2] {maxno + 10, maxno + 11}, ParameterDirection.Input);
prm[1] = cmd.Parameters.Add("paramEname", OracleDbType.Varchar2,
    new string[2] {"Client1xxx", "Client2xxx"}, ParameterDirection.Input);
prm[2] = cmd.Parameters.Add("paramDeptNo", OracleDbType.Decimal,
    new int[2] {10, 10}, ParameterDirection.Input);

// Set the ArrayBindSize for prm[1]
// These sizes indicate the maximum size of the elements in Value property
prm[1].ArrayBindSize = new int[2];
prm[1].ArrayBindSize[0] = 7; // Set ename = "Client1"
prm[1].ArrayBindSize[1] = 7; // Set ename = "Client2"

cmd.CommandText =
    "insert into emp(empno, ename, deptno) values(:1, :2, :3)";

cmd.ExecuteNonQuery();

Console.WriteLine("Record for employee id {0} has been inserted.",
    maxno + 10);
Console.WriteLine("Record for employee id {0} has been inserted.",
    maxno + 11);

prm[0].Dispose();
prm[1].Dispose();
prm[2].Dispose();
cmd.Dispose();

con.Close();
con.Dispose();
}
}

```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["ArrayBindCount"](#) on page 6-23
- ["Size"](#) on page 6-338 and ["Value"](#) on page 6-342 for more information on binding Associative Arrays
- ["ArrayBindStatus"](#) on page 6-331

ArrayBindStatus

This property specifies the input or output status of each element in the `Value` property before or after an Array Bind or PL/SQL Associative Array execution.

Declaration

```

// C#
public OracleParameterStatus[] ArrayBindStatus { get; set; }

```

Property Value

An array of `OracleParameterStatus` enumerated values.

Exceptions

`ArgumentOutOfRangeException` - The `Status` value specified is invalid.

Remarks

Default = `null`.

`ArrayBindStatus` is used for Array Bind and PL/SQL Associative Array execution only.

Before execution, `ArrayBindStatus` indicates the bind status of each element in the `Value` property. After execution, it contains the execution status of each element in the `Value` property.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["ArrayBindCount"](#) on page 6-23
- ["OracleParameterStatus Enumeration"](#) on page 6-429
- ["Value"](#) on page 6-342 for more information on binding Associative Arrays
- ["ArrayBindSize"](#) on page 6-330

CollectionType

This property specifies whether or not the `OracleParameter` represents a collection, and if so, specifies the collection type.

Declaration

```
// C#  
public OracleCollectionType CollectionType { get; set; }
```

Property Value

An `OracleCollectionType` enumerated value.

Exceptions

`ArgumentException` - The `OracleCollectionType` value specified is invalid.

Remarks

Default = `OracleCollectionType.None`. If `OracleParameter` is used to bind a PL/SQL Associative Array, then `CollectionType` must be set to `OracleCollectionType.PLSQLAssociativeArray`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)

DbType

This property specifies the data type of the parameter using the `Data.DbType` enumeration type.

Declaration

```
// C#
public override DbType DbType {get; set; }
```

Property Value

A `DbType` enumerated value.

Implements

`IDataParameter`

Exceptions

`ArgumentException` - The `DbType` value specified is invalid.

Remarks

Default = `DbType.String`

`DbType` is the data type of each element in the array if the `OracleParameter` object is used for Array Bind or PL/SQL Associative Array Bind execution.

Due to the link between `DbType` and `OracleDbType` properties, if the `DbType` property is set, the `OracleDbType` property is inferred from `DbType`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["Inference of OracleDbType from DbType"](#) on page 3-40
- ["CollectionType"](#) on page 6-332

Direction

This property specifies whether the parameter is input-only, output-only, bi-directional, or a stored function return value parameter.

Declaration

```
// C#
public override ParameterDirection Direction { get; set; }
```

Property Value

A `ParameterDirection` enumerated value.

Implements

`IDataParameter`

Exceptions

`ArgumentOutOfRangeException` - The `ParameterDirection` value specified is invalid.

Remarks

Default = `ParameterDirection.Input`

Possible values: `Input`, `InputOutput`, `Output`, and `ReturnValue`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)

IsNullable

This property is not supported.

Declaration

```
// C#  
public override bool IsNullable { get; set; }
```

Implements

`IDataParameter`

Property Value

This property is not supported.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)

Offset

This property specifies the offset to the `Value` property.

Declaration

```
// C#  
public int Offset { get; set; }
```

Property Value

An `int` that specifies the offset.

Exceptions

`ArgumentOutOfRangeException` - The `Offset` value specified is invalid.

Remarks

Default = 0

For Array Bind and PL/SQL Associative Array Bind, `Offset` applies to every element in the `Value` property.

The `Offset` property is used for binary and string data types. The `Offset` property represents the number of bytes for binary types and the number of characters for strings. The count for strings does not include the terminating character if a null is referenced. The `Offset` property is used by parameters of the following types:

- `OracleDbType.BFile`
- `OracleDbType.Blob`
- `OracleDbType.LongRaw`
- `OracleDbType.Raw`
- `OracleDbType.Char`
- `OracleDbType.Clob`
- `OracleDbType.NClob`
- `OracleDbType.NChar`
- `OracleDbType.NVarchar2`
- `OracleDbType.Varchar2`

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)

OracleDbType

This property specifies the Oracle data type.

Declaration

```
// C#
public OracleDbType OracleDbType { get; set; }
```

Property Value

An `OracleDbType` enumerated value.

Remarks

Default = `OracleDbType.Varchar2`

If the `OracleParameter` object is used for Array Bind or PL/SQL Associative Array Bind execution, `OracleDbType` is the data type of each element in the array.

The `OracleDbType` property and `DbType` property are linked. Therefore, setting the `OracleDbType` property changes the `DbType` property to a supporting `DbType`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleDbType Enumeration"](#) on page 6-426
- ["Inference of DbType from OracleDbType"](#) on page 3-39
- ["CollectionType"](#) on page 6-332

OracleDbTypeEx

This property specifies the Oracle data type to bind the parameter as, but returns a .NET type as output.

Declaration

```
// C#  
public OracleDbType OracleDbTypeEx { get; set; }
```

Property Value

An `OracleDbType` enumerated value.

Remarks

This property is used by applications that need to bind a parameter value as an Oracle type, but need a .NET type back for output. This property should be used with an output or input/output parameter. For an input parameter, using `OracleDbTypeEx` has the same affect as using `OracleDbType`. The .NET type that is returned for the output is the .NET type that the Oracle type closely maps to.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleDbType Enumeration"](#) on page 6-426
- ["OracleDbType"](#) on page 6-335
- ["Inference of DbType from OracleDbType"](#) on page 3-39
- ["CollectionType"](#) on page 6-332

ParameterName

This property specifies the name of the parameter.

Declaration

```
// C#  
public override string ParameterName { get; set; }
```

Property Value

String

Implements

IDataParameter

Remarks

Default = null

Oracle supports ParameterName up to 30 characters.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)

Precision

This property specifies the maximum number of digits used to represent the Value property.

Declaration

```
// C#  
public byte Precision { get; set; }
```

Property Value

byte

Remarks

Default = 0

The Precision property is used by parameters of type OracleDbType.Decimal.

Oracle supports Precision range from 0 to 38.

For Array Bind and PL/SQL Associative Array Bind, Precision applies to each element in the Value property.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["Value"](#) on page 6-342

Scale

This property specifies the number of decimal places to which Value property is resolved.

Declaration

```
// C#  
public byte Scale { get; set; }
```

Property Value

byte

Remarks

Default = 0.

Scale is used by parameters of type `OracleDbType.Decimal`.

Oracle supports Scale between -84 and 127.

For Array Bind and PL/SQL Associative Array Bind, Scale applies to each element in the Value property.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["Value"](#) on page 6-342

Size

This property specifies the maximum size, in bytes or characters, of the data transmitted to or from the database.

Declaration

```
// C#  
public override int Size { get; set;}
```

Property Value

int

Exceptions

`ArgumentOutOfRangeException` - The Size value specified is invalid.

`InvalidOperationException` - The Size = 0 when the `OracleParameter` object is used to bind a PL/SQL Associative Array.

Remarks

For PL/SQL Associative Array Bind, Size specifies the maximum number of elements in PL/SQL Associative Array.

If Size is not explicitly set, it is inferred from the actual size of the specified parameter value when binding only for input parameters. Output parameters must have their size defined explicitly.

The default value is 0.

Before execution, this property specifies the maximum size to be bound in the Value property. After execution, it contains the size of the type in the Value property.

Size is used for parameters of the following types:

- `OracleDbType.Blob`
- `OracleDbType.Char`
- `OracleDbType.Clob`

- `OracleDbType.LongRaw`
- `OracleDbType.NChar`
- `OracleDbType.NClob`
- `OracleDbType.NVarchar2`
- `OracleDbType.Raw`
- `OracleDbType.Varchar2`

The value of `Size` is handled as follows:

- Fixed length data types: ignored
- Variable length data types: describes the maximum amount of data transmitted to or from the database. For character data, `Size` is in number of characters and for binary data, it is in number of bytes.

If the `Size` is not explicitly set, it is inferred from the actual size of the specified parameter value when binding.

Note: `Size` does not include the null terminating character for the string data.

If the `OracleParameter` object is used to bind a PL/SQL Associative Array, `Size` specifies the maximum number of elements in the PL/SQL Associative Array. Before the execution, this property specifies the maximum number of elements in the PL/SQL Associative Array. After the execution, it specifies the current number of elements returned in the PL/SQL Associative Array. For `Output` and `InputOutput` parameters and return values, `Size` specifies the maximum number of elements in the PL/SQL Associative Array.

ODP.NET does not support binding an empty PL/SQL Associative Array. Therefore, `Size` cannot be set to 0 when the `OracleParameter` object is used to bind a PL/SQL Associative Array.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleDbType Enumeration"](#) on page 6-426
- ["CollectionType"](#) on page 6-332
- ["ArrayBindSize"](#) on page 6-330
- ["ArrayBindStatus"](#) on page 6-331
- ["Value"](#) on page 6-342

SourceColumn

This property specifies the name of the `DataTable` Column of the `DataSet`.

Declaration

```
// C#
```

```
public override string SourceColumn { get; set; }
```

Property Value

A string.

Implements

IDataParameter

Remarks

Default = empty string

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)

SourceColumnNullMapping

This property specifies a value which indicates whether the source column is nullable.

Declaration

```
// C#  
public bool SourceColumnNullMapping { get; set; }
```

Property Value

Returns true if the source column can be nullified; otherwise, returns false.

Remarks

The default value is false.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)

SourceVersion

This property specifies the DataRowVersion value to use when loading the Value property of the parameter.

Declaration

```
// C#  
public override DataRowVersion SourceVersion { get; set; }
```

Property Value

DataRowVersion

Implements

IDataParameter

Exceptions

ArgumentOutOfRangeException - The DataRowVersion value specified is invalid.

Remarks

Default = DataRowVersion.Current

SourceVersion is used by the OracleDataAdapter.UpdateCommand() during the OracleDataAdapter.Update to determine whether the original or current value is used for a parameter value. This allows primary keys to be updated. This property is ignored by the OracleDataAdapter.InsertCommand() and the OracleDataAdapter.DeleteCommand().

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)

Status

This property indicates the status of the execution related to the data in the Value property.

Declaration

```
// C#
public OracleParameterStatus Status { get; set; }
```

Property Value

An OracleParameterStatus enumerated value.

Exceptions

ArgumentOutOfRangeException - The Status value specified is invalid.

Remarks

Default = OracleParameterStatus.Success

Before execution, this property indicates the bind status related to the Value property. After execution, it returns the status of the execution.

Status indicates if:

- A NULL is fetched from a column.
- Truncation has occurred during the fetch; then Value was not big enough to hold the data.
- A NULL is to be inserted into a database column; then Value is ignored, and a NULL is inserted into a database column.

This property is ignored for Array Bind and PL/SQL Associative Array Bind. Instead, ArrayBindStatus property is used.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["OracleParameterStatus Enumeration"](#) on page 6-429
- ["ArrayBindStatus"](#) on page 6-331

UdtTypeName

This property specifies the Oracle user-defined type name if the parameter is a user-defined data type.

Declaration

```
// C#  
public string UdtTypeName {get; set;}
```

Property Value

Name of the Oracle UDT.

Remarks

The `UdtTypeName` property corresponds to the user-defined type name of the parameter. This property must always be specified if the parameter is a user-defined type.

Note that when a custom object is provided as an input parameter value, it is converted to the Oracle UDT that is specified by the custom type mapping on the connection used to execute the command.

The Oracle UDT specified by the custom type mapping and by the `OracleParameter.UdtTypeName` property differs if the application binds a custom object that represents a subtype of the parameter type.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)

Value

This property specifies the value of the Parameter.

Declaration

```
// C#  
public override object Value { get; set; }
```

Property Value

An object.

Implements

IDataParameter

Exceptions

ArgumentException - The Value property specified is invalid.

InvalidArgumentException- The Value property specified is invalid.

Remarks

Default = null

If the OracleParameter object is used for Array Bind or PL/SQL Associative Array, Value is an array of parameter values.

The Value property can be overwritten by OracleDataAdapter.Update().

The provider attempts to convert any type of value if it supports the IConvertible interface. Conversion errors occur if the specified type is not compatible with the value.

When sending a null parameter value to the database, the user must specify DBNull, not null. The null value in the system is an empty object that has no value. DBNull is used to represent null values. The user can also specify a null value by setting Status to OracleParameterStatus.NullValue. In this case, the provider sends a null value to the database.

If neither OracleDbType nor DbType are set, their values can be inferred by Value. Please see the following for related information:

- Tables in section ["Inference of DbType and OracleDbType from Value"](#) on page 3-40
- ["ArrayBindCount"](#) on page 6-23
- ["ArrayBindSize"](#) on page 6-330
- ["ArrayBindStatus"](#) on page 6-331
- ["OracleDbType Enumeration"](#) on page 6-426

For input parameters the value is:

- Bound to the OracleCommand that is sent to the database.
- Converted to the data type specified in OracleDbType or DbType when the provider sends the data to the database.

For output parameters the value is:

- Set on completion of the OracleCommand (true for return value parameters also).
- Set to the data from the database, to the data type specified in OracleDbType or DbType.

When array binding is used with:

- Input parameter - Value should be set to an array of values. OracleCommand.ArrayBindCount should be set to a value that is greater than zero to indicate the number of elements to be bound.

The number of elements in the array should be equal to the OracleCommand.ArrayBindCount property; otherwise, their minimum value is used to bind the elements in the array.

- Output parameter - `OracleCommand.ArrayBindCount` should be set to a value that is greater than zero to indicate the number of elements to be retrieved (for `SELECT` statements).

When PL/SQL Associative Array binding is used with:

- Input parameter – `Value` should be set to an array of values. `CollectionType` should be set to `OracleCollection.PLSQLAssociativeArray`. `Size` should be set to specify the possible maximum number of array elements in the PL/SQL Associative Array. If `Size` is smaller than the number of elements in `Value`, then `Size` specifies the number of elements in the `Value` property to be bound.
- Output parameter - `CollectionType` should be set to `OracleCollection.PLSQLAssociativeArray`. `Size` should be set to specify the maximum number of array elements in PL/SQL Associative Array.

Each parameter should have a value. To bind a parameter with a null value, set `Value` to `DBNull.Value`, or set `Status` to `OracleParameterStatus.NullInsert`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)
- ["ArrayBindCount"](#) on page 6-23
- ["OracleParameterStatus Enumeration"](#) on page 6-429

OracleParameter Public Methods

OracleParameter public methods are listed in [Table 6–102](#).

Table 6–102 OracleParameter Public Methods

| Public Method | Description |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------|
| Clone | Creates a shallow copy of an OracleParameter object |
| CreateObjRef | Inherited from System.MarshalByRefObject |
| Dispose | Releases allocated resources |
| Equals | Inherited from System.Object (Overloaded) |
| GetHashCode | Inherited from System.Object |
| GetLifetimeService | Inherited from System.MarshalByRefObject |
| GetType | Inherited from System.Object |
| InitializeLifetimeService | Inherited from System.MarshalByRefObject |
| ResetDbType | Resets the type associated with the parameter so that it can infer its type from the value passed in the parameter |
| ResetOracleDbType | Resets the type associated with the parameter so that it can infer its type from the value passed in the parameter |
| ToString | Returns the string representation of the current instance |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)

Clone

This method creates a shallow copy of an OracleParameter object.

Declaration

```
// C#
public object Clone();
```

Return Value

An OracleParameter object.

Implements

ICloneable

Remarks

The cloned object has the same property values as that of the object being cloned.

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class CloneSample
{
    static void Main()
    {
        OracleParameter prm1 = new OracleParameter();

        // Prints "prm1.ParameterName = "
        Console.WriteLine("prm1.ParameterName = " + prm1.ParameterName);

        // Set the ParameterName before cloning
        prm1.ParameterName = "MyParam";

        // Clone the OracleParameter
        OracleParameter prm2 = (OracleParameter) prm1.Clone();

        // Prints "prm2.ParameterName = MyParam"
        Console.WriteLine("prm2.ParameterName = " + prm2.ParameterName);

        prm1.Dispose();
        prm2.Dispose();
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

Dispose

This method releases resources allocated for an `OracleParameter` object.

Declaration

```
// C#
public void Dispose();
```

Implements

`IDisposable`

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleParameter Class](#)
- [OracleParameter Members](#)

ResetDbType

This method resets the type associated with the parameter so that it can infer its type from the value passed in the parameter.

Declaration

```
// C#  
public override void ResetDbType();
```

Remarks

If an application does not set the `DbType` or `OracleDbType` properties of an `OracleParameter` object, then these values are inferred from the value set by the application to that `OracleParameter` object. Calling `ResetDbType` method resets these properties so that `OracleParameter` can again infer its type from the value passed into the `OracleParameter`. Calling this method affects both the `DbType` and `OracleDbType` properties of the `OracleParameter` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)

ResetOracleDbType

This method resets the type associated with the parameter so that it can infer its type from the value passed in the parameter.

Declaration

```
// C#  
public override void ResetOracleDbType();
```

Remarks

If an application does not set the `DbType` or `OracleDbType` properties of an `OracleParameter` object, then these values are inferred from the value set by the application to that `OracleParameter` object. Calling the `ResetOracleDbType` method resets these properties so that `OracleParameter` can again infer its type from the value passed into the `OracleParameter`. Calling this method affects both the `DbType` and `OracleDbType` properties of the `OracleParameter` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)

ToString

Overrides `Object`

This method returns the string representation of the current instance.

Declaration

```
// C#  
public override string ToString();
```

Return Value

Returns the `OracleParameter` value in a string representation.

Remarks

If the current instance has a null value, the returned string is null.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameter Class](#)
- [OracleParameter Members](#)

OracleParameterCollection Class

An OracleParameterCollection class represents a collection of all parameters relevant to an OracleCommand object and their mappings to DataSet columns.

Class Inheritance

System.Object

System.MarshalByRefObject

System.Data.Common.DbParameterCollection

Oracle.DataAccess.Client.OracleParameterCollection

Declaration

```
// C#
public sealed class OracleParameterCollection : DbParameterCollection,
    IDataParameterCollection, IList, ICollection, IEnumerable
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

The position of an OracleParameter added into the OracleParameterCollection is the binding position in the SQL statement. Position is 0-based and is used only for positional binding. If named binding is used, the position of an OracleParameter in the OracleParameterCollection is ignored.

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class OracleParameterCollectionSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleParameter[] prm = new OracleParameter[3];
```

```
// Create OracleParameter objects through OracleParameterCollection
OracleCommand cmd = con.CreateCommand();

cmd.CommandText = "select max(empno) from emp";
int maxno = int.Parse(cmd.ExecuteScalar().ToString());

prm[0] = cmd.Parameters.Add("paramEmpno", OracleDbType.Decimal,
    maxno + 10, ParameterDirection.Input);
prm[1] = cmd.Parameters.Add("paramEname", OracleDbType.Varchar2,
    "Client", ParameterDirection.Input);
prm[2] = cmd.Parameters.Add("paramDeptNo", OracleDbType.Decimal,
    10, ParameterDirection.Input);
cmd.CommandText =
    "insert into emp(empno, ename, deptno) values(:1, :2, :3)";
cmd.ExecuteNonQuery();

Console.WriteLine("Record for employee id {0} has been inserted.",
    maxno + 10);

// Remove all parameters from OracleParameterCollection
cmd.Parameters.Clear();

prm[0].Dispose();
prm[1].Dispose();
prm[2].Dispose();
cmd.Dispose();

con.Close();
con.Dispose();
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Members](#)
- [OracleParameterCollection Static Methods](#)
- [OracleParameterCollection Properties](#)
- [OracleParameterCollection Public Methods](#)

OracleParameterCollection Members

OracleParameterCollection members are listed in the following tables.

OracleParameterCollection Static Methods

OracleParameterCollection static methods are listed in [Table 6–103](#).

Table 6–103 OracleParameterCollection Static Methods

| Method | Description |
|------------------------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

OracleParameterCollection Properties

OracleParameterCollection properties are listed in [Table 6–104](#).

Table 6–104 OracleParameterCollection Properties

| Property | Description |
|-----------------------|------------------------------------------------------------|
| Count | Specifies the number of OracleParameters in the collection |
| Item | Gets and sets the OracleParameter object (Overloaded) |

OracleParameterCollection Public Methods

OracleParameterCollection public methods are listed in [Table 6–105](#).

Table 6–105 OracleParameterCollection Public Methods

| Public Method | Description |
|---------------------------|------------------------------------------------------------------------------------------------------------|
| Add | Adds objects to the collection (Overloaded) |
| AddRange | Adds elements to the end of the OracleParameterCollection |
| Clear | Removes all the OracleParameter objects from the collection |
| Contains | Indicates whether or not objects exist in the collection (Overloaded) |
| CopyTo | Copies OracleParameter objects from the collection, starting with the supplied index to the supplied array |
| CreateObjRef | Inherited from System.MarshalByRefObject |
| Equals | Inherited from System.Object (Overloaded) |
| GetHashCode | Inherited from System.Object |
| GetLifetimeService | Inherited from System.MarshalByRefObject |
| GetType | Inherited from System.Object |
| InitializeLifetimeService | Inherited from System.MarshalByRefObject |
| IndexOf | Returns the index of the objects in the collection (Overloaded) |
| Insert | Inserts the supplied OracleParameter to the collection at the specified index |
| Remove | Removes objects from the collection |

Table 6–105 (Cont.) OracleParameterCollection Public Methods

| Public Method | Description |
|--------------------------|--------------------------------------------------------------|
| RemoveAt | Removes objects from the collection by location (Overloaded) |
| <code>ToString</code> | Inherited from <code>System.Object</code> |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)

OracleParameterCollection Static Methods

The OracleParameterCollection static method is listed in [Table 6–106](#).

Table 6–106 OracleParameterCollection Static Method

| Method | Description |
|--------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

OracleParameterCollection Properties

OracleParameterCollection properties are listed in [Table 6–107](#).

Table 6–107 OracleParameterCollection Properties

| Property | Description |
|-----------------------|------------------------------------------------------------|
| Count | Specifies the number of OracleParameters in the collection |
| Item | Gets and sets the OracleParameter object (Overloaded) |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Count

This property specifies the number of OracleParameter objects in the collection.

Declaration

```
// C#
public override int Count {get;}
```

Property Value

The number of OracleParameter objects.

Implements

ICollection

Remarks

Default = 0

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Item

Item gets and sets the OracleParameter object.

Overload List:

- [Item\[int\]](#)
This property gets and sets the OracleParameter object at the index specified by the supplied parameterIndex.
- [Item\[string\]](#)

This property gets and sets the `OracleParameter` object using the parameter name specified by the supplied `parameterName`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Item[int]

This property gets and sets the `OracleParameter` object at the index specified by the supplied `parameterIndex`.

Declaration

```
// C#  
public object Item[int parameterIndex] {get; set;}
```

Property Value

An object.

Implements

`IList`

Exceptions

`IndexOutOfRangeException` - The supplied index does not exist.

Remarks

The `OracleParameterCollection` class is a zero-based index.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Item[string]

This property gets and sets the `OracleParameter` object using the parameter name specified by the supplied `parameterName`.

Declaration

```
// C#  
public OracleParameter Item[string parameterName] {get; set;};
```

Property Value

An `OracleParameter`.

Implements

`IDataParameterCollection`

Exceptions

`IndexOutOfRangeException` - The supplied parameter name does not exist.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

OracleParameterCollection Public Methods

OracleParameterCollection public methods are listed in [Table 6–108](#).

Table 6–108 OracleParameterCollection Public Methods

| Public Method | Description |
|---------------------------|------------------------------------------------------------------------------------------------------------|
| Add | Adds objects to the collection (Overloaded) |
| AddRange | Adds elements to the end of the OracleParameterCollection |
| Clear | Removes all the OracleParameter objects from the collection |
| Contains | Indicates whether or not objects exist in the collection (Overloaded) |
| CopyTo | Copies OracleParameter objects from the collection, starting with the supplied index to the supplied array |
| CreateObjRef | Inherited from System.MarshalByRefObject |
| Equals | Inherited from System.Object (Overloaded) |
| GetHashCode | Inherited from System.Object |
| GetLifetimeService | Inherited from System.MarshalByRefObject |
| GetType | Inherited from System.Object |
| InitializeLifetimeService | Inherited from System.MarshalByRefObject |
| IndexOf | Returns the index of the objects in the collection (Overloaded) |
| Insert | Inserts the supplied OracleParameter to the collection at the specified index |
| Remove | Removes objects from the collection |
| RemoveAt | Removes objects from the collection by location (Overloaded) |
| ToString | Inherited from System.Object |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Add

Add adds objects to the collection.

Overload List:

- [Add\(object\)](#)
This method adds the supplied object to the collection.
- [Add\(OracleParameter\)](#)
This method adds the supplied OracleParameter object to the collection.

- [Add\(string, object\)](#)

This method adds an `OracleParameter` object to the collection using the supplied name and object value.
- [Add\(string, OracleDbType\)](#)

This method adds an `OracleParameter` object to the collection using the supplied name and database type.
- [Add\(string, OracleDbType, ParameterDirection\)](#)

This method adds an `OracleParameter` object to the collection using the supplied name, database type, and direction.
- [Add\(string, OracleDbType, object, ParameterDirection\)](#)

This method adds an `OracleParameter` object to the collection using the supplied name, database type, parameter value, and direction.
- [Add\(string, OracleDbType, int, object, ParameterDirection\)](#)

This method adds an `OracleParameter` object to the collection using the supplied name, database type, size, parameter value, and direction.
- [Add\(string, OracleDbType, int\)](#)

This method adds an `OracleParameter` object to the collection using the supplied name, database type, and size.
- [Add \(string, OracleDbType, int, string\)](#)

This method adds an `OracleParameter` object to the collection using the supplied name, database type, size, and source column.
- [Add\(string, OracleDbType, int, ParameterDirection, bool, byte, byte, string, DataRowVersion, object\)](#)

This method adds an `OracleParameter` object to the collection using the supplied name, database type, size, direction, null indicator, precision, scale, source column, source version, and parameter value.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Add(object)

This method adds the supplied object to the collection.

Declaration

```
// C#  
public override int Add(object obj);
```

Parameters

- *obj*

The supplied object.

Return Value

The index at which the new `OracleParameter` is added.

Implements

`IList`

Remarks

`InvalidCastException` - The supplied *obj* cannot be cast to an `OracleParameter` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Add(OracleParameter)

This method adds the supplied `OracleParameter` object to the collection.

Declaration

```
// C#  
public OracleParameter Add(OracleParameter paramObj);
```

Parameters

- *paramObj*
The supplied `OracleParameter` object.

Return Value

The newly created `OracleParameter` object which was added to the collection.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Add(string, object)

This method adds an `OracleParameter` object to the collection using the supplied name and object value

Declaration

```
// C#  
public OracleParameter Add(string name, object val);
```

Parameters

- *name*
The parameter name.
- *val*

The `OracleParameter` value.

Return Value

The newly created `OracleParameter` object which was added to the collection.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Add(string, OracleDbType)

This method adds an `OracleParameter` object to the collection using the supplied name and database type.

Declaration

```
// C#  
public OracleParameter Add(string name, OracleDbType dbType);
```

Parameters

- *name*
The parameter name.
- *dbType*
The data type of the `OracleParameter`.

Return Value

The newly created `OracleParameter` object which was added to the collection.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Add(string, OracleDbType, ParameterDirection)

This method adds an `OracleParameter` object to the collection using the supplied name, database type, and direction.

Declaration

```
// C#  
public OracleParameter Add(string name, OracleDbType dbType,  
    ParameterDirection direction);
```

Parameters

- *name*
The parameter name.
- *dbType*

The data type of the OracleParameter.

- *direction*

The OracleParameter direction.

Return Value

The newly created OracleParameter object which was added to the collection.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)
- ["OracleDbType Enumeration"](#) on page 6-426

Add(string, OracleDbType, object, ParameterDirection)

This method adds an OracleParameter object to the collection using the supplied name, database type, parameter value, and direction.

Declaration

```
// C#
public OracleParameter Add(string name, OracleDbType dbType, object val,
    ParameterDirection dir);
```

Parameters

- *name*
The parameter name.
- *dbType*
The data type of the OracleParameter.
- *val*
The OracleParameter value.
- *dir*
The ParameterDirection value.

Return Value

The newly created OracleParameter object which was added to the collection.

Example

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class AddSample
{
    static void Main()
    {
        OracleCommand cmd = new OracleCommand();
```

```
// Add parameter to the OracleParameterCollection
OracleParameter prm = cmd.Parameters.Add(
    "MyParam", OracleDbType.Decimal, 1, ParameterDirection.Input);

// Prints "cmd.Parameters.Count = 1"
Console.WriteLine("cmd.Parameters.Count = " + cmd.Parameters.Count);

prm.Dispose();
cmd.Dispose();
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)
- ["OracleDbType Enumeration"](#) on page 6-426

Add(string, OracleDbType, int, object, ParameterDirection)

This method adds an `OracleParameter` object to the collection using the supplied name, database type, size, parameter value, and direction.

Declaration

```
// C#
public OracleParameter Add(string name, OracleDbType dbType, int size,
    object val, ParameterDirection dir;
```

Parameters

- *name*
The parameter name.
- *dbType*
The data type of the `OracleParameter`.
- *size*
The size of `OracleParameter`.
- *val*
The `OracleParameter` value.
- *dir*
The `ParameterDirection` value.

Return Value

The newly created `OracleParameter` object which was added to the collection.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)
- ["OracleDbType Enumeration"](#) on page 6-426

Add(string, OracleDbType, int)

This method adds an `OracleParameter` object to the collection using the supplied name, database type, and size.

Declaration

```
// C#
public OracleParameter Add(string name, OracleDbType dbType, int size);
```

Parameters

- *name*
The parameter name.
- *dbType*
The data type of the `OracleParameter`.
- *size*
The size of `OracleParameter`.

Return Value

The newly created `OracleParameter` object which was added to the collection.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;

class AddSample
{
    static void Main()
    {
        OracleCommand cmd = new OracleCommand();

        // Add parameter to the OracleParameterCollection
        OracleParameter prm = cmd.Parameters.Add(
            "MyParam", OracleDbType.Varchar2, 10);

        // Prints "cmd.Parameters.Count = 1"
        Console.WriteLine("cmd.Parameters.Count = " + cmd.Parameters.Count);

        prm.Dispose();
        cmd.Dispose();
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Add (string, OracleDbType, int, string)

This method adds an `OracleParameter` object to the collection using the supplied name, database type, size, and source column.

Declaration

```
// C#
public OracleParameter Add(string name, OracleDbType dbType, int size,
    string srcColumn);
```

Parameters

- *name*
The parameter name.
- *dbType*
The data type of the `OracleParameter`.
- *size*
The size of `OracleParameter`.
- *srcColumn*
The name of the source column.

Return Value

An `OracleParameter`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Add(string, OracleDbType, int, ParameterDirection, bool, byte, byte, string, DataRowVersion, object)

This method adds an `OracleParameter` object to the collection using the supplied name, database type, size, direction, null indicator, precision, scale, source column, source version, and parameter value.

Declaration

```
// C#
public OracleParameter Add(string name, OracleDbType dbType, int size,
    ParameterDirection dir, bool isNullable, byte precision,
    byte scale, string srcColumn, DataRowVersion version, object val);
```

Parameters

- *name*
The parameter name.
- *dbType*
The data type of the OracleParameter.
- *size*
The size of OracleParameter.
- *dir*
The ParameterDirection value.
- *isNullable*
An indicator that specifies if the parameter value can be null.
- *precision*
The precision of the parameter value.
- *scale*
The scale of the parameter value.
- *srcColumn*
The name of the source column.
- *version*
The DataRowVersion value.
- *val*
The parameter value.

Return Value

The newly created OracleParameter object which was added to the collection.

Exceptions

ArgumentException - The type of supplied *val* does not belong to the type of Value property in any of the ODP.NET Types.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

AddRange

This method adds elements to the end of the OracleParameterCollection.

Declaration

```
// C#  
public override void AddRange(Array paramArray );
```

Parameters*paramArray*

An array of `OracleParameter` objects.

Exceptions

`ArgumentNullException` - The input parameter is null.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Clear

This method removes all the `OracleParameter` objects from the collection.

Declaration

```
// C#  
public override void Clear();
```

Implements

`IList`

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
  
class ClearSample  
{  
    static void Main()  
    {  
        OracleCommand cmd = new OracleCommand();  
  
        // Add parameter to the OracleParameterCollection  
        OracleParameter prm = cmd.Parameters.Add("MyParam", OracleDbType.Decimal);  
  
        // Prints "cmd.Parameters.Count = 1"  
        Console.WriteLine("cmd.Parameters.Count = " + cmd.Parameters.Count);  
  
        // Clear all parameters in the OracleParameterCollection  
        cmd.Parameters.Clear();  
  
        // Prints "cmd.Parameters.Count = 0"  
        Console.WriteLine("cmd.Parameters.Count = " + cmd.Parameters.Count);  
  
        prm.Dispose();  
        cmd.Dispose();  
    }  
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Contains

Contains indicates whether or not the supplied object exists in the collection.

Overload List:

- [Contains\(object\)](#)

This method indicates whether or not the supplied object exists in the collection.

- [Contains\(string\)](#)

This method indicates whether or not an `OracleParameter` object exists in the collection using the supplied string.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Contains(object)

This method indicates whether or not the supplied object exists in the collection.

Declaration

```
// C#  
public override bool Contains(object obj)
```

Parameters

- *obj*
The object.

Return Value

A `bool` that indicates whether or not the `OracleParameter` specified is inside the collection.

Implements

`IList`

Exceptions

`InvalidCastException` - The supplied *obj* is not an `OracleParameter` object.

Remarks

Returns `true` if the collection contains the `OracleParameter` object; otherwise, returns `false`.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;

class ContainsSample
{
    static void Main()
    {
        OracleCommand cmd = new OracleCommand();

        // Add parameter to the OracleParameterCollection
        OracleParameter prm1 = cmd.Parameters.Add("MyParam", OracleDbType.Decimal);

        // Check if the OracleParameterCollection contains prm1
        bool bContains = cmd.Parameters.Contains(prm1);

        // Prints "bContains = True"
        Console.WriteLine("bContains = " + bContains);

        OracleParameter prm2 = new OracleParameter();

        // Check if the OracleParameterCollection contains prm2
        bContains = cmd.Parameters.Contains(prm2);

        // Prints "bContains = False"
        Console.WriteLine("bContains = " + bContains);

        prm1.Dispose();
        prm2.Dispose();
        cmd.Dispose();
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Contains(string)

This method indicates whether or not an `OracleParameter` object exists in the collection using the supplied string.

Declaration

```
// C#
public override bool Contains(string name);
```

Parameters

- *name*
The name of `OracleParameter` object.

Return Value

Returns true if the collection contains the `OracleParameter` object with the specified parameter name; otherwise, returns false.

Implements

`IDataParameterCollection`

Example

```
// C#

using System;
using Oracle.DataAccess.Client;

class ContainsSample
{
    static void Main()
    {
        OracleCommand cmd = new OracleCommand();

        // Add parameter to the OracleParameterCollection
        OracleParameter prm = cmd.Parameters.Add("MyParam", OracleDbType.Decimal);

        // Check if the OracleParameterCollection contains "MyParam"
        bool bContains = cmd.Parameters.Contains("MyParam");

        // Prints "bContains = True"
        Console.WriteLine("bContains = " + bContains);

        // Check if the OracleParameterCollection contains "NoParam"
        bContains = cmd.Parameters.Contains("NoParam");

        // Prints "bContains = False"
        Console.WriteLine("bContains = " + bContains);

        prm.Dispose();
        cmd.Dispose();
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

CopyTo

This method copies `OracleParameter` objects from the collection, starting with the supplied index to the supplied array.

Declaration

```
// C#
public override void CopyTo(Array array, int index);
```

Parameters

- *array*
The specified array.
- *index*
The array index.

Implements

ICollection

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

IndexOf

IndexOf returns the index of the `OracleParameter` object in the collection.

Overload List:

- [IndexOf\(object\)](#)
This method returns the index of the `OracleParameter` object in the collection.
- [IndexOf\(String\)](#)
This method returns the index of the `OracleParameter` object with the specified name in the collection.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

IndexOf(object)

This method returns the index of the `OracleParameter` object in the collection.

Declaration

```
// C#  
public override int IndexOf(object obj);
```

Parameters

- *obj*
The specified object.

Return Value

Returns the index of the `OracleParameter` object in the collection.

Implements

IList

Exceptions

InvalidCastException - The supplied *obj* cannot be cast to an OracleParameter object.

Remarks

Returns the index of the supplied OracleParameter *obj* in the collection.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

IndexOf(String)

This method returns the index of the OracleParameter object with the specified name in the collection.

Declaration

```
// C#  
public override int IndexOf(String name);
```

Parameters

- *name*

The name of parameter.

Return Value

Returns the index of the supplied OracleParameter in the collection.

Implements

IDataParameterCollection

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Insert

This method inserts the supplied OracleParameter object to the collection at the specified index.

Declaration

```
// C#  
public override void Insert(int index, object obj);
```

Parameters

- *index*
The specified index.
- *obj*
The OracleParameter object.

Implements

IList

Remarks

An `InvalidCastException` is thrown if the supplied *obj* cannot be cast to an OracleParameter object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

Remove

This method removes the supplied OracleParameter from the collection.

Declaration

```
// C#  
public override void Remove(object obj);
```

Parameters

- *obj*
The specified object to remove.

Implements

IList

Exceptions

`InvalidCastException` - The supplied *obj* cannot be cast to an OracleParameter object.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
  
class RemoveSample  
{  
    static void Main()  
    {  
        OracleCommand cmd = new OracleCommand();  
  
        // Add 2 parameters to the OracleParameterCollection
```

```

OracleParameter prm1 = cmd.Parameters.Add("MyParam1", OracleDbType.Decimal);
OracleParameter prm2 = cmd.Parameters.Add("MyParam2", OracleDbType.Decimal);

// Prints "cmd.Parameters.Count = 2"
Console.WriteLine("cmd.Parameters.Count = " + cmd.Parameters.Count);

// Remove the 1st parameter from the OracleParameterCollection
cmd.Parameters.Remove(prm1);

// Prints "cmd.Parameters.Count = 1"
Console.WriteLine("cmd.Parameters.Count = " + cmd.Parameters.Count);

// Prints "cmd.Parameters[0].ParameterName = MyParam2"
Console.WriteLine("cmd.Parameters[0].ParameterName = " +
    cmd.Parameters[0].ParameterName);

prm1.Dispose();
prm2.Dispose();
cmd.Dispose();
}
}

```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

RemoveAt

RemoveAt removes the `OracleParameter` object from the collection by location.

Overload List:

- [RemoveAt\(int\)](#)

This method removes from the collection the `OracleParameter` object located at the index specified by the supplied index.

- [RemoveAt\(String\)](#)

This method removes from the collection the `OracleParameter` object specified by the supplied name.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

RemoveAt(int)

This method removes from the collection the `OracleParameter` object located at the index specified by the supplied index.

Declaration

```
// C#  
public override void RemoveAt(int index);
```

Parameters

- *index*

The specified index from which the `OracleParameter` is to be removed.

Implements

`IList`

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

RemoveAt(String)

This method removes from the collection the `OracleParameter` object specified by the supplied name.

Declaration

```
// C#  
public override void RemoveAt(String name);
```

Parameters

- *name*

The name of the `OracleParameter` object to be removed from the collection.

Implements

`IDataParameterCollection`

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleParameterCollection Class](#)
- [OracleParameterCollection Members](#)

OraclePermission Class

An OraclePermission object enables ODP.NET to enforce imperative security and helps ensure that a user has a security level adequate for accessing data.

Class Inheritance

```
System.Object
  System.Security.CodeAccessPermission
    System.Data.Common.DBDataPermission
      Oracle.DataAccess.Client.OraclePermission
```

Declaration

```
// C#
public class OraclePermission: DBDataPermission
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OraclePermission Members](#)
- [OraclePermission Constructor](#)
- [OraclePermission Static Methods](#)
- [OraclePermission Public Properties](#)
- [OraclePermission Public Methods](#)

OraclePermission Members

OraclePermission members are listed in the following tables.

OraclePermission Constructors

The OraclePermission constructor is listed in [Table 6–109](#).

Table 6–109 OraclePermission Constructor

| Constructor | Description |
|----------------------------------------------|------------------------------------------------------------|
| OraclePermission Constructor | Instantiates a new instance of the OraclePermission class. |

OraclePermission Static Methods

The OraclePermission static methods are listed in [Table 6–110](#).

Table 6–110 OraclePermission Static Methods

| Static Method | Description |
|------------------|-------------------------------------|
| Equals | Inherited from System.Object |
| ReferenceEquals | Inherited from System.Object |
| RevertAll | Inherited from CodeAccessPermission |
| RevertAssert | Inherited from CodeAccessPermission |
| RevertDeny | Inherited from CodeAccessPermission |
| RevertPermitOnly | Inherited from CodeAccessPermission |

OraclePermission Public Properties

The OraclePermission public methods are listed in [Table 6–114](#).

Table 6–111 OraclePermission Public Properties

| Public Properties | Description |
|--------------------|-------------------------------------------------------------------------------------|
| AllowBlankPassword | Inherited from DBDataPermission OraclePermission does not support this property. |

OraclePermission Public Methods

The OraclePermission public methods are listed in [Table 6–112](#).

Table 6–112 OraclePermission Public Methods

| Public Method | Description |
|----------------------|--------------------------------------------------------------------------------------------------------|
| Add | Adds a new connection string fragment and a list of restricted keywords to the OraclePermission object |
| Assert | Inherited from CodeAccessPermission |
| Copy | Returns a copy of the current permission object |
| Demand | Inherited from CodeAccessPermission |
| Deny | Inherited from CodeAccessPermission |
| Equals | Inherited from CodeAccessPermission |

Table 6–112 (Cont.) OraclePermission Public Methods

| Public Method | Description |
|----------------------------|-------------------------------------------------------------------------------------------------------------------|
| FromXml | Inherited from DBDataPermission |
| GetHashCode | Inherited from CodeAccessPermission |
| GetType | Inherited from System.Object |
| Intersect | Inherited from DBDataPermission |
| IsSubsetOf | Returns a boolean value that indicates whether or not the current permission is a subset of the target permission |
| IsUnrestricted | Inherited from DBDataPermission |
| PermitOnly | Inherited from CodeAccessPermission |
| ToString | Inherited from CodeAccessPermission |
| ToXml | Inherited from DBDataPermission |
| Union | Inherited from DBDataPermission |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OraclePermission Class](#)

OraclePermission Constructor

The `OraclePermission` constructor instantiates a new instance of the `OraclePermission` class.

Declaration

```
// C#  
public OraclePermission (PermissionState state);
```

Parameters

- *state*

The *state* parameter takes one of the following two values:
`PermissionState.None` or `PermissionState.Unrestricted`.

Exceptions

`ArgumentException` - The `PermissionState` value is invalid.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OraclePermission Class](#)
- [OraclePermission Members](#)

OraclePermission Static Methods

The OraclePermission static methods are listed in [Table 6–113](#).

Table 6–113 OraclePermission Static Methods

| Static Method | Description |
|------------------|-------------------------------------|
| Equals | Inherited from System.Object |
| ReferenceEquals | Inherited from System.Object |
| RevertAll | Inherited from CodeAccessPermission |
| RevertAssert | Inherited from CodeAccessPermission |
| RevertDeny | Inherited from CodeAccessPermission |
| RevertPermitOnly | Inherited from CodeAccessPermission |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OraclePermission Class](#)
- [OraclePermission Members](#)

OraclePermission Public Properties

The `OraclePermission` public methods are listed in [Table 6-114](#).

Table 6-114 *OraclePermission Public Properties*

| Public Properties | Description |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>AllowBlankPassword</code> | Inherited from <code>DBDataPermission</code> <code>OraclePermission</code> ignores the value of this property. Any value set for this property, for an <code>OraclePermission</code> object, is ignored. |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OraclePermission Class](#)
- [OraclePermission Members](#)

OraclePermission Public Methods

The OraclePermission public methods are listed in [Table 6–115](#).

Table 6–115 OraclePermission Public Methods

| Public Method | Description |
|----------------------------|-------------------------------------------------------------------------------------------------------------------|
| Add | Adds a new connection string fragment and a list of restricted keywords to the OraclePermission object |
| Assert | Inherited from CodeAccessPermission |
| Copy | Returns a copy of the current permission object |
| Demand | Inherited from CodeAccessPermission |
| Deny | Inherited from CodeAccessPermission |
| Equals | Inherited from CodeAccessPermission |
| FromXml | Inherited from DBDataPermission |
| GetHashCode | Inherited from CodeAccessPermission |
| GetType | Inherited from System.Object |
| Intersect | Inherited from DBDataPermission |
| IsSubsetOf | Returns a boolean value that indicates whether or not the current permission is a subset of the target permission |
| IsUnrestricted | Inherited from DBDataPermission |
| PermitOnly | Inherited from CodeAccessPermission |
| ToString | Inherited from CodeAccessPermission |
| ToXml | Inherited from DBDataPermission |
| Union | Inherited from DBDataPermission |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OraclePermission Class](#)
- [OraclePermission Members](#)

Add

This method adds a new connection string fragment and a list of restricted keywords to the OraclePermission object.

Declaration

```
// C#
public void Add(string connStr, string keyRestrict,
    KeyRestrictionBehavior behavior);
```

Parameters

- *connStr*

The connection string fragment.

- *keyRestrict*

The key restrictions.

- *behavior*

One of the following `KeyRestrictionBehavior` enumerations:

- `AllowOnly`
- `PreventUsage`

Exceptions

`ArgumentException` - The `KeyRestrictionBehavior` value or the format of the `connStr` or `keyRestrict` string is invalid.

Remarks

The `Add` method configures the connection strings allowed or disallowed by the permission object.

Opening an `OracleConnection` is allowed or denied based upon the connection string fragment, key restrictions combination, and the key restriction behavior.

In the following example, `KeyRestrictionBehavior.AllowOnly` allows connection strings that use `orcl` as the `Data Source` with any `User Id` and `Password` combination but no other connection string keywords. Connection string keywords other than `User Id` and `Password` cause security exceptions.

```
orclPermission.Add("Data Source=orcl;", "User Id=;Password=;",  
    KeyRestrictionBehavior.AllowOnly);
```

In the next example, `KeyRestrictionBehavior.PreventUsage` restricts connection strings that use the keyword `Pooling`. Use of the `Pooling` keyword causes an exception.

```
orclPermission.Add("Data Source=orcl;", "Pooling=;",  
    KeyRestrictionBehavior.PreventUsage)
```

As a general rule, in an unrestricted environment, any connection string that is not allowed is restricted and throws a security exception.

If a connection string fragment contains key-value pairs for the `password` and `proxy password` attributes, then values for these attributes are ignored. However, the presence of the attributes themselves is still checked. This means that the connection is allowed only if the `password` and `proxy` attributes keywords are allowed in the connection string.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OraclePermission Class](#)
- [OraclePermission Members](#)

Copy

This method returns a copy of the current permission object.

Declaration

```
// C#  
public override IPermission Copy();
```

Return Value

A copy of the `OraclePermission` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OraclePermission Class](#)
- [OraclePermission Members](#)

IsSubsetOf

This method returns a boolean value that indicates whether or not the current permission is a subset of the target permission.

Declaration

```
// C#  
public override bool IsSubsetOf(IPermission target);
```

Parameters

- *target*
A permission that must be of type `OraclePermission`.

Return Value

A `bool` value that indicates whether or not the current permission is a subset of the target permission.

Exceptions

`ArgumentException` - The permission is not of the `OraclePermission` type.

Remarks

The `AllowBlankPassword` property is ignored when evaluating whether or not the current permission is a subset of the target permission.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OraclePermission Class](#)
- [OraclePermission Members](#)

OraclePermissionAttribute Class

An `OraclePermissionAttribute` object enables ODP.NET to enforce declarative security and helps ensure that a user has a security level adequate for accessing data.

Class Inheritance

```
System.Object
  System.Attribute
    System.Security.Permissions.SecurityAttribute
      System.Security.Permissions.CodeAccessSecurityAttribute
        System.Data.Common.DBDataPermissionAttribute
          Oracle.DataAccess.Client.OraclePermissionAttribute
```

Declaration

```
// C#
[Serializable, AttributeUsage(AttributeTargets.Method |
AttributeTargets.Constructor | AttributeTargets.Class | AttributeTargets.Struct |
AttributeTargets.Assembly, AllowMultiple = true, Inherited = false)]
public sealed class OraclePermissionAttribute: DBDataPermissionAttribute
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OraclePermissionAttribute Members](#)
- [OraclePermissionAttribute Constructor](#)
- [OraclePermissionAttribute Static Methods](#)
- [OraclePermissionAttribute Public Properties](#)
- [OraclePermissionAttribute Public Methods](#)

OraclePermissionAttribute Members

OraclePermissionAttribute members are listed in the following tables.

OraclePermissionAttribute Constructor

The OraclePermissionAttribute constructor is listed in [Table 6–116](#).

Table 6–116 OraclePermission Constructor

| Constructor | Description |
|-------------------------------------------------------|---------------------------------------------------------------------|
| OraclePermissionAttribute Constructor | Instantiates a new instance of the OraclePermissionAttribute class. |

OraclePermissionAttribute Static Methods

The OraclePermissionAttribute static methods are listed in [Table 6–117](#).

Table 6–117 OraclePermissionAttribute Static Methods

| Static Methods | Description |
|---------------------|----------------------------------------------|
| GetCustomAttribute | Inherited from System.Attribute (Overloaded) |
| GetCustomAttributes | Inherited from System.Attribute(Overloaded) |
| IsDefined | Inherited from System.Attribute(Overloaded) |
| ReferenceEquals | Inherited from System.Object |

OraclePermissionAttribute Public Properties

The OraclePermissionAttribute public properties are listed in [Table 6–118](#).

Table 6–118 OraclePermissionAttribute Public Properties

| Public Properties | Description |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Action | Inherited from SecurityAttribute |
| AllowBlankPassword | Inherited from DBDataPermissionAttribute. OraclePermissionAttribute ignores this property. Any value set for this property, for an OraclePermissionAttribute object, is ignored. |
| ConnectionString | Inherited from DBDataPermissionAttribute |
| KeyRestrictionBehavior | Inherited from DBDataPermissionAttribute |
| KeyRestrictions | Inherited from DBDataPermissionAttribute |
| TypeId | Inherited from System.Attribute |
| Unrestricted | Inherited from SecurityAttribute |

OraclePermissionAttribute Public Methods

The OraclePermissionAttribute public methods are listed in [Table 6–119](#).

Table 6–119 OraclePermissionAttribute Public Methods

| Public Methods | Description |
|----------------------------------|-----------------------------------------------------------------------------------------------|
| CreatePermission | Returns a new OraclePermissionAttribute object that is configured based on the attributes set |
| Equals | Inherited from System.Attribute |
| GetHashCode | Inherited from System.Attribute |
| GetType | Inherited from System.Attribute |
| IsDefaultAttribute | Inherited from System.Attribute |
| Match | Inherited from System.Attribute |
| ShouldSerializeConnectionString | Inherited from DBDataPermissionAttribute |
| ShouldSerializeKeyRestrictions | Inherited from DBDataPermissionAttribute |
| ToString | Inherited from System.Object |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OraclePermissionAttribute Class](#)

OraclePermissionAttribute Constructor

The `OraclePermissionAttribute` constructor instantiates new instances of the `OraclePermissionAttribute` class.

Declaration

```
// C#  
public OraclePermissionAttribute (SecurityAction action);
```

Parameters

- *action*

A `System.Security.Permissions.SecurityAction` value representing an action that can be performed using declarative security.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OraclePermissionAttribute Class](#)
- [OraclePermissionAttribute Members](#)

OraclePermissionAttribute Static Methods

The OraclePermissionAttribute static methods are listed in [Table 6–120](#).

Table 6–120 OraclePermissionAttribute Static Methods

| Static Methods | Description |
|---------------------|----------------------------------------------|
| GetCustomAttribute | Inherited from System.Attribute (Overloaded) |
| GetCustomAttributes | Inherited from System.Attribute(Overloaded) |
| IsDefined | Inherited from System.Attribute(Overloaded) |
| ReferenceEquals | Inherited from System.Object |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OraclePermissionAttribute Class](#)
- [OraclePermissionAttribute Members](#)

OraclePermissionAttribute Public Properties

The OraclePermissionAttribute public properties are listed in [Table 6–121](#).

Table 6–121 OraclePermissionAttribute Public Properties

| Public Properties | Description |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Action | Inherited from SecurityAttribute |
| AllowBlankPassword | Inherited from DBDataPermissionAttribute. OraclePermissionAttribute ignores this property. Any value set for this property, for an OraclePermissionAttribute object, is ignored. |
| ConnectionString | Inherited from DBDataPermissionAttribute |
| KeyRestrictionBehavior | Inherited from DBDataPermissionAttribute |
| KeyRestrictions | Inherited from DBDataPermissionAttribute |
| TypeId | Inherited from System.Attribute |
| Unrestricted | Inherited from SecurityAttribute |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OraclePermissionAttribute Class](#)
- [OraclePermissionAttribute Members](#)

OraclePermissionAttribute Public Methods

The `OraclePermissionAttribute` public methods are listed in [Table 6–122](#).

Table 6–122 OraclePermissionAttribute Public Methods

| Public Methods | Description |
|----------------------------------------------|------------------------------------------------------------------------------------------------------------|
| CreatePermission | Returns a new <code>OraclePermissionAttribute</code> object that is configured based on the attributes set |
| <code>Equals</code> | Inherited from <code>System.Attribute</code> |
| <code>GetHashCode</code> | Inherited from <code>System.Attribute</code> |
| <code>GetType</code> | Inherited from <code>System.Attribute</code> |
| <code>IsDefaultAttribute</code> | Inherited from <code>System.Attribute</code> |
| <code>Match</code> | Inherited from <code>System.Attribute</code> |
| <code>ShouldSerializeConnectionString</code> | Inherited from <code>DBDataPermissionAttribute</code> |
| <code>ShouldSerializeKeyRestrictions</code> | Inherited from <code>DBDataPermissionAttribute</code> |
| <code>ToString</code> | Inherited from <code>System.Object</code> |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OraclePermissionAttribute Class](#)
- [OraclePermissionAttribute Members](#)

CreatePermission

This method returns a new `OraclePermissionAttribute` object that is configured based on the attributes set.

Declaration

```
// C#
public override IPermission CreatePermission();
```

Return Value

An `OraclePermission` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OraclePermissionAttribute Class](#)
- [OraclePermissionAttribute Members](#)

OracleRowUpdatedEventArgs Class

The `OracleRowUpdatedEventArgs` class provides event data for the `OracleDataAdapter.RowUpdated` event.

Class Inheritance

`System.Object`

`System.EventArgs`

`System.RowUpdatedEventArgs`

`System.OracleRowUpdatedEventArgs`

Declaration

```
// C#
public sealed class OracleRowUpdatedEventArgs : RowUpdatedEventArgs
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------------------|----------------------------------------------|
| Assembly | <code>Oracle.DataAccess.dll</code> | <code>Oracle.ManagedDataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Client</code> | <code>Oracle.ManagedDataAccess.Client</code> |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

The example for the `RowUpdated` event shows how to use `OracleRowUpdatedEventArgs`. See `RowUpdated` event "[Example](#)" on page 6-182.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleRowUpdatedEventArgs Members](#)
- [OracleRowUpdatedEventArgs Constructor](#)
- [OracleRowUpdatedEventArgs Static Methods](#)
- [OracleRowUpdatedEventArgs Properties](#)
- [OracleRowUpdatedEventArgs Public Methods](#)
- [OracleDataAdapter Class](#) on page 6-160

OracleRowUpdatedEventArgs Members

OracleRowUpdatedEventArgs members are listed in the following tables.

OracleRowUpdatedEventArgs Constructors

OracleRowUpdatedEventArgs constructors are listed in [Table 6–123](#).

Table 6–123 OracleRowUpdatedEventArgs Constructors

| Constructor | Description |
|-------------------------------------------------------|----------------------------------------------------------------|
| OracleRowUpdatedEventArgs Constructor | Instantiates a new instance of OracleRowUpdatedEventArgs class |

OracleRowUpdatedEventArgs Static Methods

The OracleRowUpdatedEventArgs static method is listed in [Table 6–124](#).

Table 6–124 OracleRowUpdatedEventArgs Static Method

| Method | Description |
|--------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

OracleRowUpdatedEventArgs Properties

The OracleRowUpdatedEventArgs properties are listed in [Table 6–125](#).

Table 6–125 OracleRowUpdatedEventArgs Properties

| Property | Description |
|-------------------------|------------------------------------------------------------------------------------|
| Command | Specifies the OracleCommand that is used when OracleDataAdapter.Update() is called |
| Errors | Inherited from System.Data.Common.RowUpdatedEventArgs |
| RecordsAffected | Inherited from System.Data.Common.RowUpdatedEventArgs |
| Row | Inherited from System.Data.Common.RowUpdatedEventArgs |
| StatementType | Inherited from System.Data.Common.RowUpdatedEventArgs |
| Status | Inherited from System.Data.Common.RowUpdatedEventArgs |
| TableMapping | Inherited from System.Data.Common.RowUpdatedEventArgs |

OracleRowUpdatedEventArgs Public Methods

The OracleRowUpdatedEventArgs properties are listed in [Table 6–126](#).

Table 6–126 OracleRowUpdatedEventArgs Public Methods

| Public Method | Description |
|---------------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |
| GetHashCode | Inherited from System.Object |
| GetType | Inherited from System.Object |

Table 6–126 (Cont.) OracleRowUpdatedEventArgs Public Methods

| Public Method | Description |
|-----------------------|-------------------------------------------|
| <code>ToString</code> | Inherited from <code>System.Object</code> |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleRowUpdatedEventArgs Class](#)

OracleRowUpdatedEventArgs Constructor

The `OracleRowUpdatedEventArgs` constructor creates a new `OracleRowUpdatedEventArgs` instance.

Declaration

```
// C#  
public OracleRowUpdatedEventArgs(DataRow row, IDbCommand command,  
    StatementType statementType, DataTableMapping tableMapping);
```

Parameters

- *row*
The `DataRow` sent for Update.
- *command*
The `IDbCommand` executed during the Update.
- *statementType*
The `StatementType` Enumeration value indicating the type of SQL statement executed.
- *tableMapping*
The `DataTableMapping` used for the Update.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleRowUpdatedEventArgs Class](#)
- [OracleRowUpdatedEventArgs Members](#)

OracleRowUpdatedEventArgs Static Methods

The OracleRowUpdatedEventArgs static method is listed in [Table 6–127](#).

Table 6–127 OracleRowUpdatedEventArgs Static Method

| Method | Description |
|--------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleRowUpdatedEventArgs Class](#)
- [OracleRowUpdatedEventArgs Members](#)

OracleRowUpdatedEventArgs Properties

The OracleRowUpdatedEventArgs properties are listed in [Table 6–128](#).

Table 6–128 OracleRowUpdatedEventArgs Properties

| Property | Description |
|-------------------------|------------------------------------------------------------------------------------|
| Command | Specifies the OracleCommand that is used when OracleDataAdapter.Update() is called |
| Errors | Inherited from System.Data.Common.RowUpdatedEventArgs |
| RecordsAffected | Inherited from System.Data.Common.RowUpdatedEventArgs |
| Row | Inherited from System.Data.Common.RowUpdatedEventArgs |
| StatementType | Inherited from System.Data.Common.RowUpdatedEventArgs |
| Status | Inherited from System.Data.Common.RowUpdatedEventArgs |
| TableMapping | Inherited from System.Data.Common.RowUpdatedEventArgs |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleRowUpdatedEventArgs Class](#)
- [OracleRowUpdatedEventArgs Members](#)

Command

This property specifies the OracleCommand that is used when OracleDataAdapter.Update() is called.

Declaration

```
// C#
public new OracleCommand Command {get;}
```

Property Value

The OracleCommand executed when Update is called.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleRowUpdatedEventArgs Class](#)
- [OracleRowUpdatedEventArgs Members](#)

OracleRowUpdatedEventArgs Public Methods

The OracleRowUpdatedEventArgs properties are listed in [Table 6–129](#).

Table 6–129 OracleRowUpdatedEventArgs Public Methods

| Public Method | Description |
|---------------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |
| GetHashCode | Inherited from System.Object |
| GetType | Inherited from System.Object |
| ToString | Inherited from System.Object |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleRowUpdatedEventArgs Class](#)
- [OracleRowUpdatedEventArgs Members](#)

OracleRowUpdatedEventHandler Delegate

The `OracleRowUpdatedEventHandler` delegate represents the signature of the method that handles the `OracleDataAdapter.RowUpdated` event.

Declaration

```
// C#  
public delegate void OracleRowUpdatedEventHandler(object sender,  
    OracleRowUpdatedEventArgs eventArgs);
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Parameters

- *sender*
The source of the event.
- *eventArgs*
The `OracleRowUpdatedEventArgs` object that contains the event data.

Remarks

Event callbacks can be registered through this event delegate for applications that wish to be notified after a row is updated.

In the .NET framework, the convention of an event delegate requires two parameters: the object that raises the event and the event data.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- ["RowUpdated"](#) on page 6-181

OracleRowUpdatingEventArgs Class

The `OracleRowUpdatingEventArgs` class provides event data for the `OracleDataAdapter.RowUpdating` event.

Class Inheritance

`System.Object`

`System.EventArgs`

`System.RowUpdatingEventArgs`

`System.OracleRowUpdatingEventArgs`

Declaration

```
// C#
public sealed class OracleRowUpdatingEventArgs : RowUpdatingEventArgs
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------------------|----------------------------------------------|
| Assembly | <code>Oracle.DataAccess.dll</code> | <code>Oracle.ManagedDataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Client</code> | <code>Oracle.ManagedDataAccess.Client</code> |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

The example for the `RowUpdated` event shows how to use `OracleRowUpdatingEventArgs`. See `RowUpdated` event "[Example](#)" on page 6-182.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleRowUpdatingEventArgs Members](#)
- [OracleRowUpdatingEventArgs Constructor](#)
- [OracleRowUpdatingEventArgs Static Methods](#)
- [OracleRowUpdatingEventArgs Properties](#)
- [OracleRowUpdatingEventArgs Public Methods](#)
- ["OracleDataAdapter Class"](#) on page 6-160

OracleRowUpdatingEventArgs Members

OracleRowUpdatingEventArgs members are listed in the following tables.

OracleRowUpdatingEventArgs Constructors

OracleRowUpdatingEventArgs constructors are listed in [Table 6–130](#).

Table 6–130 OracleRowUpdatingEventArgs Constructors

| Constructor | Description |
|--------------------------------------------------------|------------------------------------------------------------------------------|
| OracleRowUpdatingEventArgs Constructor | Instantiates a new instance of OracleRowUpdatingEventArgs class (Overloaded) |

OracleRowUpdatingEventArgs Static Methods

The OracleRowUpdatingEventArgs static methods are listed in [Table 6–131](#).

Table 6–131 OracleRowUpdatingEventArgs Static Methods

| Method | Description |
|--------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

OracleRowUpdatingEventArgs Properties

The OracleRowUpdatingEventArgs properties are listed in [Table 6–132](#).

Table 6–132 OracleRowUpdatingEventArgs Properties

| Property | Description |
|-------------------------|----------------------------------------------------------------------------------------|
| Command | Specifies the OracleCommand that is used when the OracleDataAdapter.Update() is called |
| Errors | Inherited from System.Data.Common.RowUpdatingEventArgs |
| Row | Inherited from System.Data.Common.RowUpdatingEventArgs |
| StatementType | Inherited from System.Data.Common.RowUpdatingEventArgs |
| Status | Inherited from System.Data.Common.RowUpdatingEventArgs |
| TableMapping | Inherited from System.Data.Common.RowUpdatingEventArgs |

OracleRowUpdatingEventArgs Public Methods

The OracleRowUpdatingEventArgs public methods are listed in [Table 6–133](#).

Table 6–133 OracleRowUpdatingEventArgs Public Methods

| Public Method | Description |
|---------------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |
| GetHashCode | Inherited from System.Object |
| GetType | Inherited from System.Object |
| ToString | Inherited from System.Object |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleRowUpdatingEventArgs Class](#)

OracleRowUpdatingEventArgs Constructor

The `OracleRowUpdatingEventArgs` constructor creates a new instance of the `OracleRowUpdatingEventArgs` class using the supplied data row, `IDbCommand`, type of SQL statement, and table mapping.

Declaration

```
// C#  
public OracleRowUpdatingEventArgs(DataRow row, IDbCommand command,  
    StatementType statementType, DataTableMapping tableMapping);
```

Parameters

- *row*
The `DataRow` sent for Update.
- *command*
The `IDbCommand` executed during the Update.
- *statementType*
The `StatementType` enumeration value indicating the type of SQL statement executed.
- *tableMapping*
The `DataTableMapping` used for the Update.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleRowUpdatingEventArgs Class](#)
- [OracleRowUpdatingEventArgs Members](#)

OracleRowUpdatingEventArgs Static Methods

The OracleRowUpdatingEventArgs static method is listed in [Table 6–134](#).

Table 6–134 OracleRowUpdatingEventArgs Static Method

| Method | Description |
|--------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleRowUpdatingEventArgs Class](#)
- [OracleRowUpdatingEventArgs Members](#)

OracleRowUpdatingEventArgs Properties

The OracleRowUpdatingEventArgs properties are listed in [Table 6–135](#).

Table 6–135 OracleRowUpdatingEventArgs Properties

| Property | Description |
|-------------------------|----------------------------------------------------------------------------------------|
| Command | Specifies the OracleCommand that is used when the OracleDataAdapter.Update() is called |
| Errors | Inherited from System.Data.Common.RowUpdatingEventArgs |
| Row | Inherited from System.Data.Common.RowUpdatingEventArgs |
| StatementType | Inherited from System.Data.Common.RowUpdatingEventArgs |
| Status | Inherited from System.Data.Common.RowUpdatingEventArgs |
| TableMapping | Inherited from System.Data.Common.RowUpdatingEventArgs |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleRowUpdatingEventArgs Class](#)
- [OracleRowUpdatingEventArgs Members](#)

Command

This property specifies the OracleCommand that is used when the OracleDataAdapter.Update() is called.

Declaration

```
// C#
public new OracleCommand Command {get; set;}
```

Property Value

The OracleCommand executed when Update is called.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleRowUpdatingEventArgs Class](#)
- [OracleRowUpdatingEventArgs Members](#)

OracleRowUpdatingEventArgs Public Methods

The OracleRowUpdatingEventArgs public methods are listed in [Table 6–136](#).

Table 6–136 OracleRowUpdatingEventArgs Public Methods

| Public Method | Description |
|---------------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |
| GetHashCode | Inherited from System.Object |
| GetType | Inherited from System.Object |
| ToString | Inherited from System.Object |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleRowUpdatingEventArgs Class](#)
- [OracleRowUpdatingEventArgs Members](#)

OracleRowUpdatingEventHandler Delegate

The `OracleRowUpdatingEventHandler` delegate represents the signature of the method that handles the `OracleDataAdapter.RowUpdating` event.

Declaration

```
// C#
public delegate void OracleRowUpdatingEventHandler (object sender,
    OracleRowUpdatingEventArgs eventArgs);
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Parameters

- *sender*
The source of the event.
- *eventArgs*
The `OracleRowUpdatingEventArgs` object that contains the event data.

Remarks

Event callbacks can be registered through this event delegate for applications that wish to be notified after a row is updated.

In the .NET framework, the convention of an event delegate requires two parameters: the object that raises the event and the event data.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- ["RowUpdating"](#) on page 6-183

OracleTransaction Class

An OracleTransaction object represents a local transaction.

Class Inheritance

```
System.Object
    System.MarshalByRefObject
        System.Data.Common.DbTransaction
            Oracle.DataAccess.Client.OracleTransaction
```

Declaration

```
// C#
public sealed class OracleTransaction : DbTransaction

// C#
public sealed class OracleTransaction : MarshalByRefObject,
    IDbTransaction, IDisposable
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

The application calls `BeginTransaction` on the `OracleConnection` object to create an `OracleTransaction` object. The `OracleTransaction` object can be created in `Read Committed` mode only. Any other mode results in an exception.

The execution of a **DDL** statement in the context of a transaction is not recommended since it results in an implicit commit that is not reflected in the state of the `OracleTransaction` object.

All operations related to **savepoints** pertain to the current local transaction. Operations like commit and rollback performed on the transaction have no effect on data in any existing `DataSet`.

Example

```
// Database Setup, if you have not done so yet.
/*
connect scott/tiger@oracle
DROP TABLE MyTable;
CREATE TABLE MyTable (MyColumn NUMBER);
--CREATE TABLE MyTable (MyColumn NUMBER PRIMARY KEY);

*/
```

```
// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class OracleTransactionSample
{
    static void Main()
    {
        // Drop & Create MyTable as indicated Database Setup, at beginning

        // This sample starts a transaction and inserts two records with the same
        // value for MyColumn into MyTable.
        // If MyColumn is not a primary key, the transaction will commit.
        // If MyColumn is a primary key, the second insert will violate the
        // unique constraint and the transaction will rollback.

        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleCommand cmd = con.CreateCommand();

        // Check the number of rows in MyTable before transaction
        cmd.CommandText = "SELECT COUNT(*) FROM MyTable";
        int myTableCount = int.Parse(cmd.ExecuteScalar().ToString());

        // Print the number of rows in MyTable
        Console.WriteLine("myTableCount = " + myTableCount);

        // Start a transaction
        OracleTransaction txn = con.BeginTransaction(
            IsolationLevel.ReadCommitted);

        try
        {
            // Insert the same row twice into MyTable
            cmd.CommandText = "INSERT INTO MyTable VALUES (1)";
            cmd.ExecuteNonQuery();
            cmd.ExecuteNonQuery(); // This may throw an exception
            txn.Commit();
        }
        catch (Exception e)
        {
            // Print the exception message
            Console.WriteLine("e.Message = " + e.Message);

            // Rollback the transaction
            txn.Rollback();
        }

        // Check the number of rows in MyTable after transaction
        cmd.CommandText = "SELECT COUNT(*) FROM MyTable";
        myTableCount = int.Parse(cmd.ExecuteScalar().ToString());

        // Prints the number of rows
        // If MyColumn is not a PRIMARY KEY, the value should increase by two.
    }
}
```



```
// If MyColumn is a PRIMARY KEY, the value should remain same.
Console.WriteLine("myTableCount = " + myTableCount);

txn.Dispose();
cmd.Dispose();

con.Close();
con.Dispose();
}
}
```

Not supported in a .NET stored procedure

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleTransaction Members](#)
- [OracleTransaction Static Methods](#)
- [OracleTransaction Properties](#)

OracleTransaction Members

OracleTransaction members are listed in the following tables.

OracleTransaction Static Methods

The OracleTransaction static method is listed in [Table 6–137](#).

Table 6–137 OracleTransaction Static Method

| Method | Description |
|------------------------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

OracleTransaction Properties

OracleTransaction properties are listed in [Table 6–138](#).

Table 6–138 OracleTransaction Properties

| Property | Description |
|--------------------------------|------------------------------------------------------------------|
| IsolationLevel | Specifies the isolation level for the transaction |
| Connection | Specifies the connection that is associated with the transaction |

OracleTransaction Public Methods

OracleTransaction public methods are listed in [Table 6–139](#).

Table 6–139 OracleTransaction Public Methods

| Public Method | Description |
|-------------------------------------------|----------------------------------------------------------|
| Commit | Commits the database transaction |
| CreateObjRef | Inherited from System.MarshalByRefObject |
| Dispose | Frees the resources used by the OracleTransaction object |
| Equals | Inherited from System.Object (Overloaded) |
| GetHashCode | Inherited from System.Object |
| GetLifetimeService | Inherited from System.MarshalByRefObject |
| GetType | Inherited from System.Object |
| InitializeLifetimeService | Inherited from System.MarshalByRefObject |
| Rollback | Rolls back a database transaction (Overloaded) |
| Save | Creates a savepoint within the current transaction |
| ToString | Inherited from System.Object |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleTransaction Class](#)

OracleTransaction Static Methods

The OracleTransaction static method is listed in [Table 6–140](#).

Table 6–140 OracleTransaction Static Method

| Method | Description |
|--------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

OracleTransaction Properties

OracleTransaction properties are listed in [Table 6–141](#).

Table 6–141 OracleTransaction Properties

| Property | Description |
|--------------------------------|------------------------------------------------------------------|
| IsolationLevel | Specifies the isolation level for the transaction |
| Connection | Specifies the connection that is associated with the transaction |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

IsolationLevel

This property specifies the isolation level for the transaction.

Declaration

```
// C#  
public override IsolationLevel IsolationLevel {get;}
```

Property Value

IsolationLevel

Implements

IDbTransaction

Exceptions

InvalidOperationException - The transaction has already completed.

Remarks

Default = IsolationLevel.ReadCommitted

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

Connection

This property specifies the connection that is associated with the transaction.

Declaration

```
// C#  
public OracleConnection Connection {get;}
```

Property Value

Connection

Implements

IDbTransaction

Remarks

This property indicates the `OracleConnection` object that is associated with the transaction.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

OracleTransaction Public Methods

OracleTransaction public methods are listed in [Table 6–142](#).

Table 6–142 OracleTransaction Public Methods

| Public Method | Description |
|---------------------------|----------------------------------------------------------|
| Commit | Commits the database transaction |
| CreateObjRef | Inherited from System.MarshalByRefObject |
| Dispose | Frees the resources used by the OracleTransaction object |
| Equals | Inherited from System.Object (Overloaded) |
| GetHashCode | Inherited from System.Object |
| GetLifetimeService | Inherited from System.MarshalByRefObject |
| GetType | Inherited from System.Object |
| InitializeLifetimeService | Inherited from System.MarshalByRefObject |
| Rollback | Rolls back a database transaction (Overloaded) |
| Save | Creates a savepoint within the current transaction |
| ToString | Inherited from System.Object |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

Commit

This method commits the database transaction.

Declaration

```
// C#
public override void Commit();
```

Implements

IDbTransaction

Exceptions

InvalidOperationException - The transaction has already been completed successfully, has been rolled back, or the associated connection is closed.

Remarks

Upon a successful commit, the transaction enters a completed state.

Example

```
// Database Setup, if you have not done so yet
/*
connect scott/tiger@oracle
```

```
DROP TABLE MyTable;
CREATE TABLE MyTable (MyColumn NUMBER);
--CREATE TABLE MyTable (MyColumn NUMBER PRIMARY KEY);

*/

// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class CommitSample
{
    static void Main()
    {
        // Drop & Create MyTable as indicated in Database Setup, at beginning

        // This sample starts a transaction and inserts two records with the same
        // value for MyColumn into MyTable.
        // If MyColumn is not a primary key, the transaction will commit.
        // If MyColumn is a primary key, the second insert will violate the
        // unique constraint and the transaction will rollback.

        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleCommand cmd = con.CreateCommand();

        // Check the number of rows in MyTable before transaction
        cmd.CommandText = "SELECT COUNT(*) FROM MyTable";
        int myTableCount = int.Parse(cmd.ExecuteScalar().ToString());

        // Print the number of rows in MyTable
        Console.WriteLine("myTableCount = " + myTableCount);

        // Start a transaction
        OracleTransaction txn = con.BeginTransaction(
            IsolationLevel.ReadCommitted);

        try
        {
            // Insert the same row twice into MyTable
            cmd.CommandText = "INSERT INTO MyTable VALUES (1)";
            cmd.ExecuteNonQuery();
            cmd.ExecuteNonQuery(); // This may throw an exception
            txn.Commit();
        }
        catch (Exception e)
        {
            // Print the exception message
            Console.WriteLine("e.Message = " + e.Message);

            // Rollback the transaction
            txn.Rollback();
        }

        // Check the number of rows in MyTable after transaction
    }
}
```

```
cmd.CommandText = "SELECT COUNT(*) FROM MyTable";
myTableCount = int.Parse(cmd.ExecuteScalar().ToString());

// Prints the number of rows
// If MyColumn is not a PRIMARY KEY, the value should increase by two.
// If MyColumn is a PRIMARY KEY, the value should remain same.
Console.WriteLine("myTableCount = " + myTableCount);

txn.Dispose();
cmd.Dispose();

con.Close();
con.Dispose();
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

Dispose

This method frees the resources used by the OracleTransaction object.

Declaration

```
// C#
public void Dispose();
```

Implements

IDisposable

Remarks

This method releases both the managed and unmanaged resources held by the OracleTransaction object. If the transaction is not in a completed state, an attempt to rollback the transaction is made.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

Rollback

Rollback rolls back a database transaction.

Overload List:

- [Rollback\(\)](#)
This method rolls back a database transaction.
- [Rollback\(string\)](#)

This method rolls back a database transaction to a **savepoint** within the current transaction.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

Rollback()

This method rolls back a database transaction.

Declaration

```
// C#
public override void Rollback();
```

Implements

IDbTransaction

Exceptions

InvalidOperationException - The transaction has already been completed successfully, has been rolled back, or the associated connection is closed.

Remarks

After a Rollback(), the OracleTransaction object can no longer be used because the Rollback ends the transaction.

Example

```
// Database Setup, if you have not done so yet.
/*
connect scott/tiger@oracle
DROP TABLE MyTable;
CREATE TABLE MyTable (MyColumn NUMBER);

*/

// C#

using System;
using System.Data;
using Oracle.DataAccess.Client;

class RollbackSample
{
    static void Main()
    {
        // Drop & Create MyTable as indicated previously in Database Setup

        // This sample starts a transaction and inserts one record into MyTable.
        // It then rollsback the transaction, the number of rows remains the same

        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();
```

```
OracleCommand cmd = con.CreateCommand();

// Check the number of rows in MyTable before transaction
cmd.CommandText = "SELECT COUNT(*) FROM MyTable";
int myTableCount = int.Parse(cmd.ExecuteScalar().ToString());

// Print the number of rows in MyTable
Console.WriteLine("myTableCount = " + myTableCount);

// Start a transaction
OracleTransaction txn = con.BeginTransaction(
    IsolationLevel.ReadCommitted);

// Insert a row into MyTable
cmd.CommandText = "INSERT INTO MyTable VALUES (1)";
cmd.ExecuteNonQuery();

// Rollback the transaction
txn.Rollback();

// Check the number of rows in MyTable after transaction
cmd.CommandText = "SELECT COUNT(*) FROM MyTable";
myTableCount = int.Parse(cmd.ExecuteScalar().ToString());

// Prints the number of rows, should remain the same
Console.WriteLine("myTableCount = " + myTableCount);

txn.Dispose();
cmd.Dispose();

con.Close();
con.Dispose();
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

Rollback(string)

This method rolls back a database transaction to a **savepoint** within the current transaction.

Declaration

```
// C#
public override void Rollback(string savepointName);
```

Parameters

- *savepointName*

The name of the savepoint to rollback to, in the current transaction.

Exceptions

`InvalidOperationException` - The transaction has already been completed successfully, has been rolled back, or the associated connection is closed.

Remarks

After a rollback to a savepoint, the current transaction remains active and can be used for further operations.

The *savepointName* specified does not have to match the case of the *savepointName* created using the *Save* method, since savepoints are created in the database in a case-insensitive manner.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

Save

This method creates a **savepoint** within the current transaction.

Declaration

```
// C#
public void Save(string savepointName);
```

Parameters

- *savepointName*

The name of the savepoint being created in the current transaction.

Exceptions

`InvalidOperationException` - The transaction has already been completed.

Remarks

After creating a savepoint, the transaction does not enter a completed state and can be used for further operations.

The *savepointName* specified is created in the database in a case-insensitive manner. Calling the `Rollback` method rolls back to *savepointName*. This allows portions of a transaction to be rolled back, instead of the entire transaction.

Example

```
// Database Setup, if you have not done so yet.
/*
connect scott/tiger@oracle
DROP TABLE MyTable;
CREATE TABLE MyTable (MyColumn NUMBER);

*/

// C#

using System;
```

```
using System.Data;
using Oracle.DataAccess.Client;

class SaveSample
{
    static void Main()
    {
        // Drop & Create MyTable as indicated in Database Setup, at beginning

        // This sample starts a transaction and creates a savepoint after
        // inserting one record into MyTable.
        // After inserting the second record it rollsback to the savepoint
        // and commits the transaction. Only the first record will be inserted

        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleCommand cmd = con.CreateCommand();

        // Check the number of rows in MyTable before transaction
        cmd.CommandText = "SELECT COUNT(*) FROM MyTable";
        int myTableCount = int.Parse(cmd.ExecuteScalar().ToString());

        // Print the number of rows in MyTable
        Console.WriteLine("myTableCount = " + myTableCount);

        // Start a transaction
        OracleTransaction txn = con.BeginTransaction(
            IsolationLevel.ReadCommitted);

        // Insert a row into MyTable
        cmd.CommandText = "INSERT INTO MyTable VALUES (1)";
        cmd.ExecuteNonQuery();

        // Create a savepoint
        txn.Save("MySavePoint");

        // Insert another row into MyTable
        cmd.CommandText = "insert into mytable values (2)";
        cmd.ExecuteNonQuery();

        // Rollback to the savepoint
        txn.Rollback("MySavePoint");

        // Commit the transaction
        txn.Commit();

        // Check the number of rows in MyTable after transaction
        cmd.CommandText = "SELECT COUNT(*) FROM MyTable";
        myTableCount = int.Parse(cmd.ExecuteScalar().ToString());

        // Prints the number of rows, should have increased by 1
        Console.WriteLine("myTableCount = " + myTableCount);

        txn.Dispose();
        cmd.Dispose();

        con.Close();
        con.Dispose();
    }
}
```

```
}  
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleTransaction Class](#)
- [OracleTransaction Members](#)

OracleConnectionType Enumeration

OracleConnectionType enumerated values specify whether a particular connection object is associated with an Oracle database connection, a TimesTen database connection, or no physical connection at all.

Table 6–143 lists all the OracleConnectionType enumeration values with a description of each enumerated value.

Table 6–143 OracleConnectionType Enumeration Values

| Member Name | Description |
|-------------|---------------------------------------------------------------------|
| Undefined | No connection is associated with the OracleConnection object. |
| Oracle | The OracleConnection object is associated with an Oracle database. |
| TimesTen | The OracleConnection object is associated with a TimesTen database. |

Requirements

| | |
|----------------|---------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | Oracle.DataAccess.dll |
| Namespace | Oracle.DataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- ["OracleConnection Class"](#) on page 6-79
- ["ConnectionType"](#) on page 6-100

OracleCollectionType Enumeration

OracleCollectionType enumerated values specify whether or not the OracleParameter object represents a collection, and if so, specifies the collection type.

Table 6-144 lists all the OracleCollectionType enumeration values with a description of each enumerated value.

Table 6-144 OracleCollectionType Enumeration Values

| Member Name | Description |
|-----------------------|---------------------------------------------------------------------------------------------|
| None | Is not a collection type |
| PLSQLAssociativeArray | Indicates that the collection type is a PL/SQL Associative Array (or PL/SQL Index-By Table) |

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- ["OracleParameter Class"](#) on page 6-313
- ["CollectionType"](#) on page 6-332

OracleDBShutdownMode Enumeration

OracleDBShutdownMode enumerated values specify the database shutdown options.

Table 6–146 lists all the OracleDBShutdownMode enumeration values with a description of each enumerated value.

Table 6–145 OracleDBShutdownMode Enumeration Values

| Member Name | Description |
|--------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Default | Refuses new connections and waits for existing connections to end. |
| Transactional | Refuses new connections and does not allow any new transactions. Waits for active transactions to commit. |
| TransactionalLocal | Refuses new connections and does not allow any new transactions. Waits for only local transactions to commit. |
| Immediate | Does not wait for current calls to complete or users to disconnect from the database. All uncommitted transactions are terminated and rolled back. |
| Final | Shuts down the database. Used in the second call for shutdown after the database has been closed and dismounted. |
| Abort | Does not wait for current calls to complete or users to disconnect from the database. All uncommitted transactions are terminated and are not rolled back. |

Requirements

| | |
|-----------------------|----------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | Oracle.DataAccess.dll |
| Namespace | Oracle.DataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- ["OracleConnection Class"](#) on page 6-79
- ["Shutdown"](#) on page 6-191

OracleDBStartupMode Enumeration

OracleDBStartupMode enumerated values specify the database startup options.

[Table 6-146](#) lists all the OracleDBStartupMode enumeration values with a description of each enumerated value.

Table 6-146 OracleDBStartupMode Enumeration Values

| Member Name | Description |
|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| NoRestriction | Starts the database and allows access to all users. |
| Restrict | Starts the database and allows database access only to users having the CREATE SESSION and RESTRICTED SESSION privileges. These privileges are normally assigned to database administrators. |
| Force | Shuts down a running instance in abort mode and starts a new instance. |

Requirements

| | |
|----------------|---------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | Oracle.DataAccess.dll |
| Namespace | Oracle.DataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- ["OracleConnection Class"](#) on page 6-79
- ["Startup"](#) on page 6-194

OracleDbType Enumeration

OracleDbType enumerated values are used to explicitly specify the OracleDbType of an OracleParameter.

Table 6–147 lists all the OracleDbType enumeration values with a description of each enumerated value.

Table 6–147 OracleDbType Enumeration Values

| Member Name | Description |
|--------------|-----------------------------------------------------------------------------------------------|
| Array | Oracle Collection (VArray or Nested Table) <i>Not Available in ODP.NET, Managed Driver</i> |
| BFile | Oracle BFILE type |
| BinaryFloat | Oracle BINARY_FLOAT type |
| BinaryDouble | Oracle BINARY_DOUBLE type |
| Blob | Oracle BLOB type |
| Boolean | Oracle BOOLEAN type <i>Not Available in ODP.NET, Managed Driver</i> |
| Byte | byte type |
| Char | Oracle CHAR type |
| Clob | Oracle CLOB type |
| Date | Oracle DATE type |
| Decimal | Oracle NUMBER type |
| Double | 8-byte FLOAT type |
| Int16 | 2-byte INTEGER type |
| Int32 | 4-byte INTEGER type |
| Int64 | 8-byte INTEGER type |
| IntervalDS | Oracle INTERVAL DAY TO SECOND type |
| IntervalYM | Oracle INTERVAL YEAR TO MONTH type |
| Long | Oracle LONG type |
| LongRaw | Oracle LONG RAW type |
| NChar | Oracle NCHAR type |
| NClob | Oracle NCLOB type |
| NVarchar2 | Oracle NVARCHAR2 type |
| Object | Oracle Object <i>Not Available in ODP.NET, Managed Driver</i> |
| Raw | Oracle RAW type |
| Ref | Oracle REF <i>Not Available in ODP.NET, Managed Driver</i> |
| RefCursor | Oracle REF CURSOR type |

Table 6–147 (Cont.) OracleDbType Enumeration Values

| Member Name | Description |
|--------------|-------------------------------------------------|
| Single | 4-byte FLOAT type, supports 6 precisions |
| TimeStamp | Oracle TIMESTAMP type |
| TimeStampLTZ | Oracle TIMESTAMP WITH LOCAL TIME ZONE type |
| TimeStampTZ | Oracle TIMESTAMP WITH TIME ZONE type |
| Varchar2 | Oracle VARCHAR2 type |
| XmlType | Oracle XMLType type |
| | <i>Not Available in ODP.NET, Managed Driver</i> |

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- ["OracleParameter Class"](#) on page 6-313
- ["OracleParameterCollection Class"](#) on page 6-349
- OracleParameter ["OracleDbType"](#) on page 6-335

OracleIdentityType Enumeration

The `OracleIdentityType` enumeration specifies how Oracle identity column values are generated.

[Table 6-148](#) lists all the `OracleIdentityType` enumeration values with a description of each enumerated value.

Table 6-148 *OracleIdentityType Members*

| Member Name | Description |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>GeneratedAlways</code> | Indicates that unique values are generated for every insertion. No updates or inserts are allowed for this identity column. |
| <code>GeneratedByDefault</code> | Indicates that the values are generated only if no explicit value is provided for the identity column. Null values are not allowed for this identity column. |
| <code>GeneratedByDefaultOnNull</code> | Indicates that the values are generated only if no explicit value is provided or a NULL is inserted for the identity column. |

Requirements

| | |
|-----------------------|---------------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | <code>Oracle.DataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Client</code> |
| .NET Framework | 3.5, 4.0, 4.5 |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- ["OracleDataAdapter Class"](#) on page 6-160
- OracleDataAdapter ["IdentityInsert"](#) on page 6-170
- OracleDataAdapter ["IdentityUpdate"](#) on page 6-171

OracleParameterStatus Enumeration

The `OracleParameterStatus` enumeration type indicates whether a `NULL` value is fetched from a column, or truncation has occurred during the fetch, or a `NULL` value is to be inserted into a database column.

[Table 6–149](#) lists all the `OracleParameterStatus` enumeration values with a description of each enumerated value.

Table 6–149 OracleParameterStatus Members

| Member Name | Description |
|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Success | Indicates that (for input parameters) the input value has been assigned to the column. For output parameter, it indicates that the provider assigned an intact value to the parameter. |
| NullFetched | Indicates that a <code>NULL</code> value has been fetched from a column or an <code>OUT</code> parameter. |
| NullInsert | Indicates that a <code>NULL</code> value is to be inserted into a column. |
| Truncation | Indicates that truncation has occurred when fetching the data from the column. |

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- ["OracleParameter Class"](#) on page 6-313
- OracleParameter ["ArrayBindStatus"](#) on page 6-331
- OracleParameter ["Value"](#) on page 6-342

Oracle Data Provider for .NET XML-Related Classes

This chapter describes ODP.NET XML-related classes and enumerations.

This chapter contains these topics:

- [OracleXmlCommandType Enumeration](#)
- [OracleXmlQueryProperties Class](#)
- [OracleXmlSaveProperties Class](#)
- [OracleXmlStream Class](#)
- [OracleXmlType Class](#)

All offsets are 0-based for `OracleXmlStream` object parameters.

OracleXmlCommandType Enumeration

The `OracleXmlCommandType` enumeration specifies the values that are allowed for the `XmlCommandType` property of the `OracleCommand` class. It is used to specify the type of XML operation.

[Table 7-1](#) lists all the `OracleXmlCommandType` enumeration values with a description of each enumerated value.

Table 7-1 *OracleXmlCommandType Members*

| Member Name | Description |
|-------------|------------------------------------------------------------------------------------------------------------------------------|
| None | No XML operation is desired |
| Query | The command text is a SQL query and the result of the query is an XML document. The SQL query needs to be a select statement |
| Insert | The command text is an XML document containing rows to insert. |
| Update | The command text is an XML document containing rows to update. |
| Delete | The command text is an XML document containing rows to delete. |

See Also: ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5

OracleXmlQueryProperties Class

An `OracleXmlQueryProperties` object represents the XML properties used by the `OracleCommand` class when the `XmlCommandType` property is `Query`.

Class Inheritance

`System.Object`

`System.OracleXmlQueryProperties`

Declaration

```
public sealed class OracleXmlQueryProperties : ICloneable
```

Requirements

| | |
|-----------------------|---------------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | <code>Oracle.DataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Client</code> |
| .NET Framework | 3.5, 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

`OracleXmlQueryProperties` can be accessed, and modified using the `XmlQueryProperties` property of the `OracleCommand` class. Each `OracleCommand` object has its own instance of the `OracleXmlQueryProperties` class in the `XmlQueryProperties` property.

Use the default constructor to get a new instance of the `OracleXmlQueryProperties`. Use the `OracleXmlQueryProperties.Clone()` method to get a copy of an `OracleXmlQueryProperties` instance.

Example

This example retrieves relational data as XML.

```
// C#

using System;
using System.IO;
using System.Data;
using System.Xml;
using System.Text;
using Oracle.DataAccess.Client;

class OracleXmlQueryPropertiesSample
{
    static void Main()
    {
        int rows = 0;
        StreamReader sr = null;
```

```

// Define the XSL document for doing the transform.
string xslstr = "<?xml version='1.0'?>\n" +
  "<xsl:stylesheet version=\"1.0\" \" +
  \" xmlns:xsl=\"http://www.w3.org/1999/XSL/Transform\">\n\" +
  \" <xsl:output encoding=\"utf-8\"/>\n\" +
  \" <xsl:template match=\"/\">\n\" +
  \" <EMPLOYEES>\n\" +
  \" <xsl:apply-templates select=\"ROWSET\"/>\n\" +
  \" </EMPLOYEES>\n\" +
  \" </xsl:template>\n\" +
  \" <xsl:template match=\"ROWSET\">\n\" +
  \" <xsl:apply-templates select=\"ROW\"/>\n\" +
  \" </xsl:template>\n\" +
  \" <xsl:template match=\"ROW\">\n\" +
  \" <EMPLOYEE>\n\" +
  \" <EMPLOYEE_ID>\n\" +
  \" <xsl:apply-templates select=\"EMPNO\"/>\n\" +
  \" </EMPLOYEE_ID>\n\" +
  \" <EMPLOYEE_NAME>\n\" +
  \" <xsl:apply-templates select=\"ENAME\"/>\n\" +
  \" </EMPLOYEE_NAME>\n\" +
  \" <HIRE_DATE>\n\" +
  \" <xsl:apply-templates select=\"HIREDATE\"/>\n\" +
  \" </HIRE_DATE>\n\" +
  \" <JOB_TITLE>\n\" +
  \" <xsl:apply-templates select=\"JOB\"/>\n\" +
  \" </JOB_TITLE>\n\" +
  \" </EMPLOYEE>\n\" +
  \" </xsl:template>\n\" +
  \"</xsl:stylesheet>\n\";

// Create the connection.
string constr = "User Id=scott;Password=tiger;Data Source=oracle";
OracleConnection con = new OracleConnection(constr);
con.Open();

// Set the date, and timestamp formats for Oracle 9i Release 2, or later.
// This is just needed for queries.
if (!con.ServerVersion.StartsWith("9.0") &&
    !con.ServerVersion.StartsWith("8.1"))
{
  OracleGlobalization sessionParams = con.GetSessionInfo();
  sessionParams.DateFormat = "YYYY-MM-DD\"T\"HH24:MI:SS";
  sessionParams.TimeStampFormat = "YYYY-MM-DD\"T\"HH24:MI:SS.FF3";
  sessionParams.TimeStampTZFormat = "YYYY-MM-DD\"T\"HH24:MI:SS.FF3";
  con.SetSessionInfo(sessionParams);
}

// Create the command.
OracleCommand cmd = new OracleCommand("", con);

// Set the XML command type to query.
cmd.XmlCommandType = OracleXmlCommandType.Query;

// Set the SQL query.
cmd.CommandText = "select * from emp e where e.empno = :empno";

// Set command properties that affect XML query behaviour.
cmd.BindByName = true;

```

```
// Bind values to the parameters in the SQL query.
Int32 empNum = 7369;
cmd.Parameters.Add("empno", OracleDbType.Int32, empNum,
    ParameterDirection.Input);

// Set the XML query properties.
cmd.XmlQueryProperties.MaxRows = 1;
cmd.XmlQueryProperties.RootTag = "ROWSET";
cmd.XmlQueryProperties.RowTag = "ROW";
cmd.XmlQueryProperties.Xslt = xsltstr;

// Test query execution without returning a result.
Console.WriteLine("SQL query: select * from emp e where e.empno = 7369");
Console.WriteLine("Maximum rows: all rows (-1)");
Console.WriteLine("Return Value from OracleCommand.ExecuteNonQuery()");
rows = cmd.ExecuteNonQuery();
Console.WriteLine(rows);
Console.WriteLine("\n");

// Get the XML document as an XmlReader.
Console.WriteLine("SQL query: select * from emp e where e.empno = 7369");
Console.WriteLine("Maximum rows: all rows (-1)");
Console.WriteLine("XML Document from OracleCommand.ExecuteXmlReader()");

XmlReader xmlReader = cmd.ExecuteXmlReader();
XmlDocument xmlDocument = new XmlDocument();
xmlDocument.PreserveWhitespace = true;
xmlDocument.Load(xmlReader);
Console.WriteLine(xmlDocument.OuterXml);
Console.WriteLine("\n");

// Change the SQL query, and set the maximum number of rows to 2.
cmd.CommandText = "select * from emp e";
cmd.Parameters.Clear();
cmd.XmlQueryProperties.MaxRows = 2;

// Get the XML document as a Stream.
Console.WriteLine("SQL query: select * from emp e");
Console.WriteLine("Maximum rows: 2");
Console.WriteLine("XML Document from OracleCommand.ExecuteStream()");
Stream stream = cmd.ExecuteStream();
sr = new StreamReader(stream, Encoding.Unicode);
Console.WriteLine(sr.ReadToEnd());
Console.WriteLine("\n");

// Get all the rows.
cmd.XmlQueryProperties.MaxRows = -1;

// Append the XML document to an existing Stream.
Console.WriteLine("SQL query: select * from emp e");
Console.WriteLine("Maximum rows: all rows (-1)");
Console.WriteLine("XML Document from OracleCommand.ExecuteToStream()");
MemoryStream mstream = new MemoryStream(32);
cmd.ExecuteToStream(mstream);
mstream.Seek(0, SeekOrigin.Begin);
sr = new StreamReader(mstream, Encoding.Unicode);
Console.WriteLine(sr.ReadToEnd());
Console.WriteLine("\n");

// Clean up.
```

```
cmd.Dispose();  
con.Close();  
con.Dispose();  
}  
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleXmlQueryProperties Members](#)
- [OracleXmlQueryProperties Constructor](#)
- [OracleXmlQueryProperties Properties](#)
- [OracleXmlQueryProperties Public Methods](#)

OracleXmlQueryProperties Members

OracleXmlQueryProperties members are listed in the following tables.

OracleXmlQueryProperties Constructors

The OracleXmlQueryProperties constructors are listed in [Table 7-2](#).

Table 7-2 OracleXmlQueryProperties Constructors

| Constructor | Description |
|------------------------------------------------------|-------------------------------------------------------------------|
| OracleXmlQueryProperties Constructor | Instantiates a new instance of the OracleXmlQueryProperties class |

OracleXmlQueryProperties Properties

The OracleXmlQueryProperties properties are listed in [Table 7-3](#).

Table 7-3 OracleXmlQueryProperties Properties

| Name | Description |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------|
| MaxRows | Specifies the maximum number of rows from the result set of the query that can be represented in the result XML document |
| RootTag | Specifies the root element of the result XML document |
| RowTag | Specifies the value of the XML element which identifies a row of data from the result set in an XML document |
| Xslt | Specifies the XSL document used for XML transformation using XSLT |
| XsltParams | Specifies parameters for the XSL document |

OracleXmlQueryProperties Public Methods

The OracleXmlQueryProperties public methods are listed in [Table 7-4](#).

Table 7-4 OracleXmlQueryProperties Public Methods

| Name | Description |
|-----------------------|------------------------------------------------------|
| Clone | Creates a copy of an OracleXmlQueryProperties object |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleXmlQueryProperties Class](#)

OracleXmlQueryProperties Constructor

The `OracleXmlQueryProperties` constructor instantiates a new instance of the `OracleXmlQueryProperties` class.

Declaration

```
// C#  
public OracleXmlQueryProperties();
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleXmlQueryProperties Class](#)
- [OracleXmlQueryProperties Members](#)

OracleXmlQueryProperties Properties

The OracleXmlQueryProperties properties are listed in [Table 7-5](#).

Table 7-5 OracleXmlQueryProperties Properties

| Name | Description |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------|
| MaxRows | Specifies the maximum number of rows from the result set of the query that can be represented in the result XML document |
| RootTag | Specifies the root element of the result XML document |
| RowTag | Specifies the value of the XML element which identifies a row of data from the result set in an XML document |
| Xslt | Specifies the XSL document used for XML transformation using XSLT |
| XsltParams | Specifies parameters for the XSL document |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleXmlQueryProperties Class](#)
- [OracleXmlQueryProperties Members](#)

MaxRows

This property specifies the maximum number of rows from the result set of the query that can be represented in the result XML document.

Declaration

```
// C#
public int MaxRows {get; set;}
```

Property Value

The maximum number of rows.

Exceptions

ArgumentException - The new value for MaxRows is not valid.

Remarks

Default value is -1.

Possible values are:

- -1 (all rows).
- A number greater than or equal to 0.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleXmlQueryProperties Class](#)
- [OracleXmlQueryProperties Members](#)

RootTag

This property specifies the root element of the result XML document.

Declaration

```
// C#  
public string RootTag {get; set;}
```

Property Value

The root element of the result XML document.

Remarks

The default root tag is ROWSET.

To indicate that no root tag is be used in the result XML document, set this property to null or "" or `String.Empty`.

If both `RootTag` and `RowTag` are set to null, an XML document is returned only if the result set returns one row and one column.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleXmlQueryProperties Class](#)
- [OracleXmlQueryProperties Members](#)

RowTag

This property specifies the value of the XML element which identifies a row of data from the result set in an XML document.

Declaration

```
// C#  
public string RowTag {get; set;}
```

Property Value

The value of the XML element.

Remarks

The default is ROW.

To indicate that no row tag is be used in the result XML document, set this property to null or "" or `String.Empty`.

If both `RootTag` and `RowTag` are set to null, an XML document is returned only if the result set returns one row and one column.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleXmlQueryProperties Class](#)
- [OracleXmlQueryProperties Members](#)

Xslt

This property specifies the XSL document used for XML transformation using XSLT.

Declaration

```
// C#  
public string Xslt {get; set;}
```

Property Value

The XSL document used for XML transformation.

Remarks

Default value is null.

The XSL document is used for XML transformation of the XML document generated from the result set of the query.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleXmlQueryProperties Class](#)
- [OracleXmlQueryProperties Members](#)

XsltParams

This property specifies parameters for the XSL document.

Declaration

```
// C#  
public string XsltParams {get; set;}
```

Property Value

The parameters for the XSL document.

Remarks

Default value is null.

The parameters are specified as a string of "name=value" pairs of the form "param1=value1; param2=value2;..." delimited by semicolons.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleXmlQueryProperties Class](#)
- [OracleXmlQueryProperties Members](#)

OracleXmlQueryProperties Public Methods

The `OracleXmlQueryProperties` public methods are listed in [Table 7-6](#).

Table 7-6 *OracleXmlQueryProperties Public Methods*

| Name | Description |
|-----------------------|-------------------------------------------------------------------|
| Clone | Creates a copy of an <code>OracleXmlQueryProperties</code> object |

Clone

This method creates a copy of an `OracleXmlQueryProperties` object.

Declaration

```
// C#  
public object Clone();
```

Return Value

An `OracleXmlQueryProperties` object

Implements

`ICloneable`

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleXmlQueryProperties Class](#)
- [OracleXmlQueryProperties Members](#)

OracleXmlSaveProperties Class

An OracleXmlSaveProperties object represents the XML properties used by the OracleCommand class when the XmlCommandType property is Insert, Update, or Delete.

Class Inheritance

System.Object

System.OracleXmlSaveProperties

Declaration

```
public sealed class OracleXmlSaveProperties : ICloneable
```

Requirements

| | |
|-----------------------|----------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | Oracle.DataAccess.dll |
| Namespace | Oracle.DataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

OracleXmlSaveProperties can be accessed and modified using the XmlSaveProperties property of the OracleCommand class. Each OracleCommand object has its own instance of the OracleXmlSaveProperties class in the XmlSaveProperties property.

Use the default constructor to get a new instance of OracleXmlSaveProperties. Use the OracleXmlSaveProperties.Clone() method to get a copy of an OracleXmlSaveProperties instance.

Example

This sample demonstrates how to do inserts, updates, and deletes to a relational table or view using an XML document.

```
// C#
/* -- If HR account is being locked, you need to log on as a DBA
   -- to unlock the account first. Unlock a locked users account:

ALTER USER hr ACCOUNT UNLOCK;
*/

using System;
using Oracle.DataAccess.Client;

class OracleXmlSavePropertiesSample
{
    static void Main()
    {
```

```
string[] KeyColumnsList = null;
string[] UpdateColumnsList = null;
int rows = 0;

// Create the connection.
string constr = "User Id=hr;Password=hr;Data Source=oracle";
OracleConnection con = new OracleConnection(constr);
con.Open();

// Create the command.
OracleCommand cmd = new OracleCommand("", con);

// Set the XML command type to insert.
cmd.XmlCommandType = OracleXmlCommandType.Insert;

// Set the XML document.
cmd.CommandText = "<?xml version=\"1.0\"?>\n" +
    "<ROWSET>\n" +
    "  <MYROW num = \"1\">\n" +
    "    <EMPLOYEE_ID>1234</EMPLOYEE_ID>\n" +
    "    <LAST_NAME>Smith</LAST_NAME>\n" +
    "    <EMAIL>Smith@Oracle.com</EMAIL>\n" +
    "    <HIRE_DATE>1982-01-23T00:00:00.000</HIRE_DATE>\n" +
    "    <JOB_ID>IT_PROG</JOB_ID>\n" +
    "  </MYROW>\n" +
    "  <MYROW num = \"2\">\n" +
    "    <EMPLOYEE_ID>1235</EMPLOYEE_ID>\n" +
    "    <LAST_NAME>Barney</LAST_NAME>\n" +
    "    <EMAIL>Barney@Oracle.com</EMAIL>\n" +
    "    <HIRE_DATE>1982-01-23T00:00:00.000</HIRE_DATE>\n" +
    "    <JOB_ID>IT_PROG</JOB_ID>\n" +
    "  </MYROW>\n" +
    "</ROWSET>\n";

// Set the XML save properties.
KeyColumnsList = new string[1];
KeyColumnsList[0] = "EMPLOYEE_ID";
UpdateColumnsList = new string[5];
UpdateColumnsList[0] = "EMPLOYEE_ID";
UpdateColumnsList[1] = "LAST_NAME";
UpdateColumnsList[2] = "EMAIL";
UpdateColumnsList[3] = "HIRE_DATE";
UpdateColumnsList[4] = "JOB_ID";
cmd.XmlSaveProperties.KeyColumnsList = KeyColumnsList;
cmd.XmlSaveProperties.RowTag = "MYROW";
cmd.XmlSaveProperties.Table = "employees";
cmd.XmlSaveProperties.UpdateColumnsList = UpdateColumnsList;
cmd.XmlSaveProperties.Xslt = null;
cmd.XmlSaveProperties.XsltParams = null;

// Do the inserts.
rows = cmd.ExecuteNonQuery();
Console.WriteLine("rows: " + rows);

// Set the XML command type to update.
cmd.XmlCommandType = OracleXmlCommandType.Update;

// Set the XML document.
cmd.CommandText = "<?xml version=\"1.0\"?>\n" +
    "<ROWSET>\n"
```

```

    " <MYROW num = \"1\">\n" +
    " <EMPLOYEE_ID>1234</EMPLOYEE_ID>\n" +
    " <LAST_NAME>Adams</LAST_NAME>\n" +
    " </MYROW>\n" +
    "</ROWSET>\n";

    // Set the XML save properties.
    KeyColumnsList = new string[1];
    KeyColumnsList[0] = "EMPLOYEE_ID";
    UpdateColumnsList = new string[1];
    UpdateColumnsList[0] = "LAST_NAME";
    cmd.XmlSaveProperties.KeyColumnsList = KeyColumnsList;
    cmd.XmlSaveProperties.UpdateColumnsList = UpdateColumnsList;
    rows = cmd.ExecuteNonQuery();
    Console.WriteLine("rows: " + rows);

    // Set the XML command type to delete.
    cmd.XmlCommandType = OracleXmlCommandType.Delete;

    // Set the XML document.
    cmd.CommandText = "<?xml version=\"1.0\"?>\n" +
        "<ROWSET>\n" +
        " <MYROW num = \"1\">\n" +
        " <EMPLOYEE_ID>1234</EMPLOYEE_ID>\n" +
        " </MYROW>\n" +
        " <MYROW num = \"2\">\n" +
        " <EMPLOYEE_ID>1235</EMPLOYEE_ID>\n" +
        " </MYROW>\n" +
        "</ROWSET>\n";

    // Set the XML save properties.
    KeyColumnsList = new string[1];
    KeyColumnsList[0] = "EMPLOYEE_ID";
    cmd.XmlSaveProperties.KeyColumnsList = KeyColumnsList;
    cmd.XmlSaveProperties.UpdateColumnsList = null;

    // Do the deletes.
    rows = cmd.ExecuteNonQuery();
    Console.WriteLine("rows: " + rows);

    // Clean up.
    cmd.Dispose();
    con.Close();
    con.Dispose();
}
}

```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleXmlSaveProperties Members](#)
- [OracleXmlSaveProperties Constructor](#)
- [OracleXmlSaveProperties Properties](#)
- [OracleXmlSaveProperties Public Methods](#)

OracleXmlSaveProperties Members

OracleXmlSaveProperties members are listed in the following tables.

OracleXmlSaveProperties Constructor

OracleXmlSaveProperties constructors are listed in [Table 7-7](#)

Table 7-7 OracleXmlSaveProperties Constructor

| Constructor | Description |
|-----------------------------------------------------|------------------------------------------------------------------|
| OracleXmlSaveProperties Constructor | Instantiates a new instance of the OracleXmlSaveProperties class |

OracleXmlSaveProperties Properties

The OracleXmlSaveProperties properties are listed in [Table 7-8](#).

Table 7-8 OracleXmlSaveProperties Properties

| Name | Description |
|-----------------------------------|----------------------------------------------------------------------------------------------------------------|
| KeyColumnsList | Specifies the list of columns used as a key to locate existing rows for update or delete using an XML document |
| RowTag | Specifies the value for the XML element that identifies a row of data in an XML document |
| Table | Specifies the name of the table or view to which changes are saved |
| UpdateColumnsList | Specifies the list of columns to update or insert |
| Xslt | Specifies the XSL document used for XML transformation using XSLT |
| XsltParams | Specifies the parameters for the XSLT document specified in the Xslt property |

OracleXmlSaveProperties Public Methods

The OracleXmlSaveProperties public methods are listed in [Table 7-9](#).

Table 7-9 OracleXmlSaveProperties Public Methods

| Name | Description |
|-----------------------|-----------------------------------------------------|
| Clone | Creates a copy of an OracleXmlSaveProperties object |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

OracleXmlSaveProperties Constructor

The `OracleXmlSaveProperties` constructor instantiates a new instance of `OracleXmlSaveProperties` class.

Declaration

```
// C#  
public OracleXmlSaveProperties;
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

OracleXmlSaveProperties Properties

The OracleXmlSaveProperties properties are listed in [Table 7–10](#).

Table 7–10 OracleXmlSaveProperties Properties

| Name | Description |
|-----------------------------------|----------------------------------------------------------------------------------------------------------------|
| KeyColumnsList | Specifies the list of columns used as a key to locate existing rows for update or delete using an XML document |
| RowTag | Specifies the value for the XML element that identifies a row of data in an XML document |
| Table | Specifies the name of the table or view to which changes are saved |
| UpdateColumnsList | Specifies the list of columns to update or insert |
| Xslt | Specifies the XSL document used for XML transformation using XSLT |
| XsltParams | Specifies the parameters for the XSLT document specified in the Xslt property |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

KeyColumnsList

This property specifies the list of columns used as a key to locate existing rows for update or delete using an XML document.

Declaration

```
// C#
public string[] KeyColumnsList {get; set;}
```

Property Value

The list of columns.

Remarks

Default value is null.

The first null value (if any) terminates the list.

KeyColumnsList usage with XMLCommandType property values:

- Insert - KeyColumnsList is ignored and can be null.
- Update - KeyColumnsList must be specified; it identifies the columns to use to find the rows to be updated.
- Delete - If KeyColumnsList is null, all the column values in each row element in the XML document are used to locate the rows to delete. Otherwise, KeyColumnsList specifies the columns used to identify the rows to delete.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

RowTag

This property specifies the value for the XML element that identifies a row of data in an XML document.

Declaration

```
// C#  
public string RowTag {get; set;}
```

Property Value

An XML element name.

Remarks

The default value is `ROW`.

Each element in the XML document identifies one row in a table or view.

If `RowTag` is set to "" or `null`, no row tag is used in the XML document. In this case, the XML document is assumed to contain only one row.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

Table

This property specifies the name of the table or view to which changes are saved.

Declaration

```
// C#  
public string Table {get; set;}
```

Property Value

A table name.

Remarks

Default value is `null`.

The property must be set to a valid table or view name.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

UpdateColumnsList

This property specifies the list of columns to update or insert.

Declaration

```
// C#  
public string[] UpdateColumnsList {get; set;}
```

Property Value

A list of columns.

Remarks

Default value is null.

The first null value (if any) terminates the list.

UpdateColumnList usage with XMLCommandType property values:

- Insert - UpdateColumnList indicates which columns are assigned values when a new row is created. If UpdateColumnList is null, then all columns are assigned values. If a column is on the UpdateColumnList, but no value is specified for the row in the XML file, then NULL is used. If a column is not on the UpdateColumnList, then the default value for that column is used.
- Update - UpdateColumnList specifies columns to modify for each row of data in the XML document. If UpdateColumnList is null, all the values in each XML element in the XML document are used to modify the columns.
- Delete - UpdateColumnsList is ignored and can be null.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

Xslt

This property specifies the XSL document used for XML transformation using XSLT.

Declaration

```
// C#  
public string Xslt {get; set;}
```

Property Value

The XSL document used for XML transformation.

Remarks

Default = null.

The XSL document is used for XSLT transformation of a given XML document. The transformed XML document is used to save changes to the table or view.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

XsltParams

This property specifies the parameters for the XSLT document specified in the `Xslt` property.

Declaration

```
// C#  
public string XsltParams {get; set;}
```

Property Value

The parameters for the XSLT document.

Remarks

Default is null.

This property is a string delimited by semicolons in "name=value" pairs of the form "param1=value1; param2=value2; ...".

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

OracleXmlSaveProperties Public Methods

The OracleXmlSaveProperties public methods are listed in [Table 7–11](#).

Table 7–11 OracleXmlSaveProperties Public Methods

| Name | Description |
|-----------------------|-----------------------------------------------------|
| Clone | Creates a copy of an OracleXmlSaveProperties object |

Clone

This method creates a copy of an OracleXmlSaveProperties object.

Declaration

```
// C#  
public object Clone();
```

Return Value

An OracleXmlSaveProperties object

Implements

ICloneable

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleXmlSaveProperties Class](#)
- [OracleXmlSaveProperties Members](#)

OracleXmlStream Class

An `OracleXmlStream` object represents a read-only stream of XML data stored in an `OracleXmlType` object.

Class Inheritance

```
System.Object
    System.MarshalByRefObject
        System.Stream
            System.OracleXmlStream
```

Declaration

```
// C#
public sealed class OracleXmlStream : IDisposable, ICloneable
```

Requirements

| | |
|-----------------------|----------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | Oracle.DataAccess.dll |
| Namespace | Oracle.DataAccess.Types |
| .NET Framework | 3.5, 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleXmlStream Members](#)
- [OracleXmlStream Constructor](#)
- [OracleXmlStream Static Methods](#)
- [OracleXmlStream Instance Properties](#)
- [OracleXmlStream Instance Methods](#)

OracleXmlStream Members

OracleXmlStream members are listed in the following tables.

OracleXmlStream Constructors

The OracleXmlStream constructors are listed in [Table 7-12](#).

Table 7-12 OracleXmlStream Constructors

| Constructor | Description |
|---------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| OracleXmlStream Constructor | Creates an instance of an OracleXmlStream object which provides a Stream representation of the XML data stored in an OracleXmlType |

OracleXmlStream Static Methods

The OracleXmlStream static methods are listed in [Table 7-13](#).

Table 7-13 OracleXmlStream Static Methods

| Methods | Description |
|---------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

OracleXmlStream Instance Properties

The OracleXmlStream instance properties are listed in [Table 7-14](#).

Table 7-14 OracleXmlStream Instance Properties

| Properties | Description |
|----------------------------|-----------------------------------------------------------------------------------|
| CanRead | Indicates whether or not the XML stream can be read |
| CanSeek | Indicates whether or not forward and backward seek operation can be performed |
| CanWrite | <i>Not Supported</i> |
| Connection | Indicates the OracleConnection that is used to retrieve the XML data |
| Length | Indicates the number of bytes in the XML stream |
| Position | Gets or sets the byte position within the stream |
| Value | Returns the XML data, starting from the first character in the stream as a string |

OracleXmlStream Instance Methods

The OracleXmlStream instance methods are listed in [Table 7-15](#).

Table 7-15 OracleXmlStream Instance Methods

| Methods | Description |
|-----------------------|-------------------------------------------------------------------------|
| BeginRead | Inherited from System.IO.Stream |
| BeginWrite | Inherited from System.IO.Stream |
| Clone | Creates a copy of an OracleXmlStream object |
| Close | Closes the current stream and releases any resources associated with it |

Table 7–15 (Cont.) OracleXmlStream Instance Methods

| Methods | Description |
|---------------------------|-------------------------------------------------------------------------------------------------------|
| Dispose | Releases resources allocated by this object |
| EndRead | Inherited from <code>System.IO.Stream</code> |
| EndWrite | Inherited from <code>System.IO.Stream</code> |
| Equals | Inherited from <code>System.Object</code> |
| Flush | <i>Not Supported</i> |
| GetHashCode | Inherited from <code>System.Object</code> |
| GetLifetimeService | Inherited from <code>System.MarshalByRefObject</code> |
| GetType | Inherited from <code>System.Object</code> |
| InitializeLifetimeService | Inherited from <code>System.MarshalByRefObject</code> |
| Read | Reads a specified amount from the current stream instance and populates the array buffer (Overloaded) |
| ReadByte | Inherited from <code>System.IO.Stream</code> |
| Seek | Sets the position within the current stream and returns the new position within the current stream |
| SetLength | <i>Not Supported</i> |
| ToString | Inherited from <code>System.Object</code> |
| Write | <i>Not Supported</i> |
| WriteByte | <i>Not Supported</i> |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlStream Class](#)

OracleXmlStream Constructor

This constructor creates an instance of an `OracleXmlStream` object which provides a Stream representation of the XML data stored in an `OracleXmlType` object.

Declaration

```
// C#  
public OracleXmlStream(OracleXmlType xmlType);
```

Parameters

- *xmlType*
The `OracleXmlType` object.

Remarks

The `OracleXmlStream` implicitly uses the `OracleConnection` object from the `OracleXmlType` object from which it was constructed.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

OracleXmlStream Static Methods

The OracleXmlStream static methods are listed in [Table 7-16](#).

Table 7-16 OracleXmlStream Static Methods

| Methods | Description |
|---------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

OracleXmlStream Instance Properties

The `OracleXmlStream` instance properties are listed in [Table 7-17](#).

Table 7-17 OracleXmlStream Instance Properties

| Properties | Description |
|----------------------------|-----------------------------------------------------------------------------------|
| CanRead | Indicates whether or not the XML stream can be read |
| CanSeek | Indicates whether or not forward and backward seek operation can be performed |
| <code>CanWrite</code> | <i>Not Supported</i> |
| Connection | Indicates the <code>OracleConnection</code> that is used to retrieve the XML data |
| Length | Indicates the number of bytes in the XML stream |
| Position | Gets or sets the byte position within the stream |
| Value | Returns the XML data, starting from the first character in the stream as a string |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

CanRead

Overrides `Stream`

This property indicates whether or not the XML stream can be read.

Declaration

```
// C#
public override bool CanRead{get;}
```

Property Value

If the XML stream is can be read, returns `true`; otherwise, returns `false`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

CanSeek

Overrides `Stream`

This property indicates whether or not forward and backward seek operation can be performed.

Declaration

```
// C#  
public override bool CanSeek{get;}
```

Property Value

If forward and backward seek operations can be performed, this property returns true. Otherwise, returns false.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

Connection

This instance property indicates the `OracleConnection` that is used to retrieve the XML data.

Declaration

```
// C#  
public OracleConnection Connection {get;}
```

Property Value

An `OracleConnection`.

Exceptions

`ObjectDisposedException` - The object is already disposed.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

Length

Overrides `Stream`

This property indicates the number of bytes in the XML stream.

Declaration

```
// C#  
public override Int64 Length{get;}
```

Property Value

An `Int64` value representing the number of bytes in the XML stream. An empty stream has a length of 0 bytes.

Exceptions

`ObjectDisposedException` - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

Position

Overrides Stream

This property gets or sets the byte position within the stream.

Declaration

```
// C#  
public override Int64 Position{get; set;}
```

Property Value

An Int64 that indicates the current position in the stream.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

ArgumentOutOfRangeException - The Position is less than 0.

Remarks

The beginning of the stream is represented by position 0. Seeking to any location beyond the length of the stream is supported.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

Value

This property returns the XML data, starting from the first character of the stream as a string.

Declaration

```
// C#  
public string Value{get; set;}
```

Property Value

A string.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The value of `Position` is neither used nor changed by using this property.

The maximum length of the string that can be returned by this property is 2 GB.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

OracleXmlStream Instance Methods

The OracleXmlStream instance methods are listed in [Table 7–18](#).

Table 7–18 OracleXmlStream Instance Methods

| Methods | Description |
|---------------------------|-----------------------------------------------------------------------------------------------------------|
| BeginRead | Inherited from System.IO.Stream |
| BeginWrite | Inherited from System.IO.Stream |
| Clone | Creates a copy of an OracleXmlStream object |
| Close | Closes the current stream and releases any resources associated with it |
| Dispose | Releases resources allocated by this object |
| EndRead | Inherited from System.IO.Stream |
| EndWrite | Inherited from System.IO.Stream |
| Equals | Inherited from System.Object |
| Flush | <i>Not Supported</i> |
| GetHashCode | Inherited from System.Object |
| GetLifetimeService | Inherited from System.MarshalByRefObject |
| GetType | Inherited from System.Object |
| InitializeLifetimeService | Inherited from System.MarshalByRefObject |
| Read | Reads a specified amount from the current XML stream instance and populates the array buffer (Overloaded) |
| ReadByte | Inherited from System.IO.Stream |
| Seek | Sets the position within the current stream and returns the new position within the current stream |
| SetLength | <i>Not Supported</i> |
| ToString | Inherited from System.Object |
| Write | <i>Not Supported</i> |
| WriteByte | <i>Not Supported</i> |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

Clone

This method creates a copy of an OracleXmlStream object.

Declaration

```
// C#
public object Clone();
```

Return Value

An OracleXmlStream object.

Implements

ICloneable

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

Remarks

The cloned object has the same property values as that of the object being cloned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

Close

Overrides Stream

This method closes the current stream and releases any resources associated with it.

Declaration

```
// C#  
public override void Close();
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

Dispose

This public method releases resources allocated by this object.

Declaration

```
// C#  
public void Dispose();
```

Implements

IDisposable

Remarks

The object cannot be reused after being disposed. Although some properties can still be accessed, their values cannot be accountable. Since resources are freed, method calls can lead to exceptions.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

Read

This method reads a specified amount from the current XML stream instance and populates the array buffer.

Overload List:

- [Read\(byte\[\] , int, int\)](#)

This method reads a specified amount of unicode bytes from the current instance, advances the position within the stream, and populates the byte array buffer.

- [Read\(char\[\] , int, int\)](#)

This method reads a specified amount of characters from the current instance, advances the position within the stream, and populates the character array buffer.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

Read(byte[] , int, int)

Overrides [Stream](#)

This method reads a specified amount of unicode bytes from the current instance, advances the position within the stream, and populates the byte array buffer.

Declaration

```
// C#  
public override int Read(byte[] buffer, int offset, int count);
```

Parameters

- *buffer*
The byte array buffer that is populated.
- *offset*
The zero-based offset (in bytes) at which the buffer is populated.
- *count*
The maximum amount of bytes to be read.

Return Value

The number of unicode bytes read into the given `byte[]` buffer or 0 if the end of the stream has been reached.

Remarks

This method reads a maximum of *count* bytes from the current stream and stores them in buffer beginning at *offset*. The current position within the stream is advanced by the number of bytes read. However, if an exception occurs, the current position within the stream remains unchanged.

The XML data is read starting from the position specified by the `Position` property.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

Read(char[], int, int)

Overrides `Stream`

This method reads a specified amount of characters from the current instance, advances the position within the stream, and populates the character array buffer.

Declaration

```
// C#  
public override int Read(char[] buffer, int offset, int count);
```

Parameters

- *buffer*
The character array buffer to be populated.
- *offset*
The zero-based offset (in characters) in the buffer at which the buffer is populated.
- *count*
The maximum amount of characters to be read from the stream.

Return Value

The return value indicates the number of characters read from the stream or 0 if the end of the stream has been reached.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

This method requires that the `Position` on the stream instance be zero or an even number.

The XML data is read starting from the position specified by the `Position` property.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

Seek

Overrides `Stream`.

This method sets the position within the current stream and returns the new position within the current stream.

Declaration

```
// C#  
public long Seek(long offset, SeekOrigin origin);
```

Parameters

- *offset*
A byte offset relative to *origin*.
 - If *offset* is negative, the new position precedes the position specified by *origin* by the number of bytes specified by *offset*.
 - If *offset* is zero, the new position is the position specified by *origin*.
 - If *offset* is positive, the new position follows the position specified by *origin* by the number of bytes specified by *offset*.
- *origin*
A value of type `SeekOrigin` indicating the reference point used to obtain the new position.

Return Value

The new `Position` within the current stream.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object

Remarks

Use the `CanSeek` property to determine whether or not the current instance supports seeking. Seeking to any location beyond the length of the stream is supported.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleXmlStream Class](#)
- [OracleXmlStream Members](#)

OracleXmlType Class

An OracleXmlType object represents an Oracle XMLType instance.

Class Inheritance

System.Object

System.OracleXmlType

Declaration

```
// C#  
public sealed class OracleXmlType : IDisposable, INullable
```

Requirements

| | |
|-----------------------|----------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | Oracle.DataAccess.dll |
| Namespace | Oracle.DataAccess.Types |
| .NET Framework | 3.5, 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

OracleXmlType objects can be used for well-formed XML documents with or without XML schemas or XML fragments.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Members](#)
- [OracleXmlType Constructors](#)
- [OracleXmlType Static Methods](#)
- [OracleXmlType Static Fields](#)
- [OracleXmlType Instance Properties](#)
- [OracleXmlType Instance Methods](#)

OracleXmlType Members

OracleXmlType members are listed in the following tables.

OracleXmlType Constructors

The OracleXmlType constructors are listed in [Table 7-19](#).

Table 7-19 OracleXmlType Constructors

| Constructor | Description |
|--------------------------------------------|-------------------------------------------------------------|
| OracleXmlType Constructors | Creates an instance of the OracleXmlType class (Overloaded) |

OracleXmlType Static Methods

The OracleXmlType static methods are listed in [Table 7-20](#).

Table 7-20 OracleXmlType Static Methods

| Methods | Description |
|------------------------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

OracleXmlType Static Fields

The OracleXmlType static field is listed in [Table 7-21](#).

Table 7-21 OracleXmlType Static Field

| Static Field | Description |
|----------------------|---------------------------------------------------------------------------|
| Null | Represents a null value that can be assigned to an OracleXmlType instance |

OracleXmlType Instance Properties

The OracleXmlType instance properties are listed in [Table 7-22](#).

Table 7-22 OracleXmlType Instance Properties

| Properties | Description |
|-------------------------------|----------------------------------------------------------------------------------------------------------|
| Connection | Indicates the OracleConnection that is used to retrieve and store XML data in the OracleXmlType |
| IsEmpty | Indicates whether or not the OracleXmlType is empty |
| IsFragment | Indicates whether the XML data is a collection of XML elements or a well-formed XML document |
| IsNull | Indicates whether or not the OracleXmlType is null |
| IsSchemaBased | Indicates whether or not the XML data represented by the OracleXmlType is based on an XML schema |
| RootElement | Represents the name of the top-level element of the schema-based XML data contained in the OracleXmlType |
| Schema | Represents the XML schema of the XML data contained in the OracleXmlType |
| SchemaUrl | Represents in the database for the XML schema of the XML data contained in the OracleXmlType. |
| Value | Returns the XML data starting from the first character in the current instance as a string |

OracleXmlType Instance Methods

The OracleXmlType instance methods are listed in [Table 7-23](#).

Table 7-23 OracleXmlType Instance Methods

| Methods | Description |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| Clone | Creates a copy of the OracleXmlType instance |
| Dispose | Releases the resources allocated by this OracleXmlType object |
| Equals | Inherited from System.Object |
| Extract | Extracts a subset from the XML data using the given XPath expression (Overloaded) |
| GetHashCode | Inherited from System.Object |
| GetStream | Returns an instance of OracleXmlStream which provides a read-only stream of the XML data stored in this OracleXmlType instance |
| GetType | Inherited from System.Object |
| GetXmlDocument | Returns a XmlDocument object containing the XML data stored in this OracleXmlType instance |
| GetXmlReader | Returns a XmlTextReader object that can be used to manipulate XML data directly using the .NET Framework classes and methods |
| IsExists | Checks for the existence of a particular set of nodes identified by the given XPath expression in the XMLdata (Overloaded) |
| ToString | Inherited from System.Object |
| Transform | Transforms the OracleXmlType into another OracleXmlType instance using the given XSL document (Overloaded) |
| Update | Updates the XML node or fragment identified by the given XPath expression in the current OracleXmlType instance (Overloaded) |
| Validate | Validates whether or not the XML data in the OracleXmlType object conforms to the given XML schema. |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)

OracleXmlType Constructors

OracleXmlType constructors create instances of the OracleXmlType class.

Overload List:

- [OracleXmlType\(OracleClob\)](#)
This constructor creates an instance of the OracleXmlType class using the XML data contained in an OracleClob object.
- [OracleXmlType\(OracleConnection, string\)](#)
This constructor creates an instance of the OracleXmlType class using the XML data contained in the .NET String.
- [OracleXmlType\(OracleConnection, XmlReader\)](#)
This constructor creates an instance of the OracleXmlType class using the contents of the .NET XmlReader object.
- [OracleXmlType\(OracleConnection, XmlDocument\)](#)
This constructor creates an instance of the OracleXmlType object using the contents of the XML **DOM** document in the .NET XmlDocument object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

OracleXmlType(OracleClob)

This constructor creates an instance of the OracleXmlType class using the XML data contained in an OracleClob object.

Declaration

```
// C#
public OracleXmlType(OracleClob oraClob);
```

Parameters

- *oraClob*
An OracleClob object.

Exceptions

ArgumentNullException - The OracleClob object is null.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

Remarks

The CLOB data depends on a valid connection object and the new OracleXMLType uses the OracleConnection in the OracleClob object to store data for the current instance.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

OracleXmlType(OracleConnection, string)

This constructor creates an instance of the `OracleXmlType` class using the XML data contained in the .NET String.

Declaration

```
// C#
public OracleXmlType(OracleConnection con, string xmlData);
```

Parameters

- `con`
An `OracleConnection` object.
- `xmlData`
A string containing the XML data.

Exceptions

`ArgumentNullException` - The `OracleConnection` object is null.

`ArgumentException` - The `xmlData` argument is an empty string.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The new `OracleXmlType` uses the given `OracleConnection` object to store data for the current instance.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

OracleXmlType(OracleConnection, XmlReader)

This constructor creates an instance of the `OracleXmlType` class using the contents of the .NET `XmlReader` object.

Declaration

```
// C#
public OracleXmlType(OracleConnection con, XmlReader reader);
```

Parameters

- `con`

An OracleConnection object.

- *reader*

An XmlReader object.

Exceptions

ArgumentNullException - The OracleConnection object is null.

ArgumentException - The *reader* argument contains no data.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

Remarks

The new OracleXMLType uses the given OracleConnection object to store data for the current instance.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

OracleXmlType(OracleConnection, XmlDocument)

This constructor creates an instance of the OracleXmlType object using the contents of the XML **DOM** document in the .NET XmlDocument object.

Declaration

```
// C#
public OracleXmlType(OracleConnection con, XmlDocument domDoc);
```

Parameters

- *con*
An OracleConnection object.
- *domDoc*
An XML document.

Exceptions

ArgumentNullException - The OracleConnection object is null.

ArgumentException - The *domDoc* argument contains no data.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

Remarks

The new OracleXMLType uses the given OracleConnection object to store data for the current instance.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

OracleXmlType Static Methods

The OracleXmlType static methods are listed in [Table 7-24](#).

Table 7-24 OracleXmlType Static Methods

| Methods | Description |
|---------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

OracleXmlType Static Fields

The OracleXmlType static field is listed in [Table 7-25](#).

Table 7-25 OracleXmlType Static Field

| Static Field | Description |
|----------------------|---------------------------------------------------------------------------|
| Null | Represents a null value that can be assigned to an OracleXmlType instance |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Null

This static field represents a null value that can be assigned to an OracleXmlType instance.

Declaration

```
// C#  
public static readonly OracleXmlType Null;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

OracleXmlType Instance Properties

The OracleXmlType instance properties are listed in [Table 7–26](#).

Table 7–26 OracleXmlType Instance Properties

| Properties | Description |
|-------------------------------|----------------------------------------------------------------------------------------------------------|
| Connection | Indicates the OracleConnection that is used to retrieve and store XML data in the OracleXmlType |
| IsEmpty | Indicates whether or not the OracleXmlType is empty |
| IsFragment | Indicates whether the XML data is a collection of XML elements or a well-formed XML document |
| IsNull | Indicates whether or not the OracleXmlType is null |
| IsSchemaBased | Indicates whether or not the XML data represented by the OracleXmlType is based on an XML schema |
| Null | Represents a null value that can be assigned to an OracleXmlType instance |
| RootElement | Represents the name of the top-level element of the schema-based XML data contained in the OracleXmlType |
| Schema | Represents the XML schema of the XML data contained in the OracleXmlType |
| SchemaUrl | Represents URL in the database for the XML schema of the XML data contained in the OracleXmlType |
| Value | Returns the XML data starting from the first character in the current instance as a string |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Connection

This property indicates the OracleConnection that is used to retrieve and store XML data in the OracleXmlType.

Declaration

```
// C#
public OracleConnection Connection {get;}
```

Property Value

An OracleConnection object.

Exceptions

ObjectDisposedException - The object is already disposed.

Remarks

The connection must explicitly be opened by the user before creating or using `OracleXmlType`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

IsEmpty

This property indicates whether or not the `OracleXmlType` is empty.

Declaration

```
// C#  
public bool IsEmpty {get;}
```

Property Value

Returns `true` if the `OracleXmlType` represents an empty XML document. Returns `false` otherwise.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

IsFragment

This property indicates whether the XML data is a collection of XML elements or a well-formed XML document.

Declaration

```
// C#  
public bool IsFragment {get;}
```

Property Value

Returns `true` if the XML data contained in the `OracleXmlType` object is a collection of XML elements with no root element. Returns `false` otherwise.

Exceptions

`ObjectDisposedException` - The object is already disposed.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

IsNull

This property indicates whether or not the `OracleXmlType` is null.

Declaration

```
// C#  
public bool IsNull {get;}
```

Property Value

Returns true if the `OracleXmlType` represents a null value. Returns false otherwise.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

IsSchemaBased

This property indicates whether or not the XML data represented by the `OracleXmlType` is based on an XML schema.

Declaration

```
// C#  
public bool IsSchemaBased {get;}
```

Property Value

Returns true if the XML data represented by the `OracleXmlType` is based on an XML schema. Returns false otherwise.

Exceptions

`ObjectDisposedException` - The object is already disposed.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

RootElement

This property represents the name of the top-level or root element of the schema-based XML data contained in the `OracleXmlType`.

Declaration

```
// C#  
public string RootElement{get;}
```

Property Value

A string that represents the name of the top-level or root element of the XML data contained in the `OracleXmlType`.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

If the `OracleXmlType` instance contains non-schema based XML data, this property returns an empty string.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Schema

This property represents the XML schema for the XML data contained in the `OracleXmlType`.

Declaration

```
// C#  
public OracleXmlType Schema {get;}
```

Property Value

An `OracleXmlType` instance that represents the XML schema for the XML data contained in the `OracleXmlType`.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

If the `OracleXmlType` instance contains non-schema based XML data, this property returns an `OracleXmlType` instance representing an empty XML document.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

SchemaUrl

This property represents the XML schema in the database for the XML schema of the XML data contained in the `OracleXmlType`.

Declaration

```
// C#  
public string SchemaUrl {get;}
```

Property Value

A string that represents the URL in the database for the XML schema of the XML data.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

If the `OracleXmlType` instance contains non-schema based XML data, this property returns an empty string.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Value

This property returns the XML data starting from the first character in the current instance as a string.

Declaration

```
// C#  
public string Value{get;}
```

Property Value

The entire XML data as a string.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

OracleXmlType Instance Methods

The OracleXmlType instance methods are listed in [Table 7-27](#).

Table 7-27 OracleXmlType Instance Methods

| Methods | Description |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| Clone | Creates a copy of the OracleXmlType instance |
| Dispose | Releases the resources allocated by this OracleXmlType object |
| Equals | Inherited from System.Object |
| Extract | Extracts a subset from the XML data using the given XPath expression (Overloaded) |
| GetHashCode | Inherited from System.Object |
| GetStream | Returns an instance of OracleXmlStream which provides a read-only stream of the XML data stored in this OracleXmlType instance |
| GetType | Inherited from System.Object |
| GetXmlDocument | Returns a XmlDocument object containing the XML data stored in this OracleXmlType instance |
| GetXmlReader | Returns a XmlTextReader object that can be used to manipulate XML data directly using the .NET Framework classes and methods |
| IsExists | Checks for the existence of a particular set of nodes identified by the given XPath expression in the XMLdata (Overloaded) |
| ToString | Inherited from System.Object |
| Transform | Transforms the OracleXmlType into another OracleXmlType instance using the given XSL document (Overloaded) |
| Update | Updates the XML node or fragment identified by the given XPath expression in the current OracleXmlType instance (Overloaded) |
| Validate | Validates whether or not the XML data in the OracleXmlType object conforms to the given XML schema. |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Clone

This method creates a copy of this OracleXmlType instance.

Declaration

```
// C#
public object Clone();
```

Implements

ICloneable

Return Value

An OracleXmlType object.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Dispose

This method releases the resources allocated by this object.

Declaration

```
// C#  
public void Dispose();
```

Implements

IDisposable

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Extract

This method extracts a subset from the XML data using the given XPath expression.

Overload List:

- [Extract\(string, string\)](#)
This method extracts a subset from the XML data represented by the OracleXmlType object using the given XPath expression and a string parameter for namespace resolution.
- [Extract\(string, XmlNamespaceManager\)](#)
This method extracts a subset from the XML data represented by the OracleXmlType object, using the given XPath expression and a .NET XmlNamespaceManager object for namespace resolution.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Extract(string, string)

This method extracts a subset from the XML data represented by the `OracleXmlType` object using the given XPath expression and a string parameter for namespace resolution.

Declaration

```
// C#
public OracleXmlType Extract(string xpathExpr, string nsMap);
```

Parameters

- *xpathExpr*
The XPath expression.
- *nsMap*
The string parameter used for namespace resolution of the XPath expression. *nsMap* has zero or more namespaces separated by spaces. *nsMap* can be null. For example:

```
xmlns:nsi="http://www.company1.com" xmlns:nsz="http://www.company2.com"
```

Return Value

An `OracleXmlType` object.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentNullException` - The *xpathExpr* is null or zero-length.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Extract(string, XmlNamespaceManager)

This public method extracts a subset from the XML data represented by the `OracleXmlType` object, using the given XPath expression and a `.NET XmlNamespaceManager` object for namespace resolution.

Declaration

```
// C#
```

```
public OracleXmlType Extract(string xpathExpr, XmlNamespaceManager nsMgr);
```

Parameters

- *xpathExpr*

The XPath expression.

- *nsMgr*

The .NET `XmlNamespaceManager` object used for namespace resolution of the XPath expression. *nsMgr* can be null.

Return Value

An `OracleXmlType`.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentNullException` - The *xpathExpr* is null or zero-length.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The default namespace is ignored if its value is an empty string.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

GetStream

This public method returns an instance of `OracleXmlStream` which provides a read-only stream of the XML data stored in this `OracleXmlType` instance.

Declaration

```
// C#  
public Stream GetStream();
```

Return Value

A `Stream` object.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

GetXmlDocument

This public method returns a `XmlDocument` object containing the XML data stored in this `OracleXmlType` instance.

Declaration

```
// C#  
public XmlDocument GetXmlDocument();
```

Return Value

An `XmlDocument` object.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The XML data in the `XmlDocument` object is a copy of the XML data in the `OracleXmlType` instance and modifying it does not automatically modify the XML data in the `OracleXmlType` instance. The `XmlDocument` instance returned has the `PreserveWhitespace` property set to true.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

GetXmlReader

This public method returns a `XmlTextReader` object that can be used to manipulate XML data directly using the .NET Framework classes and methods.

Declaration

```
// C#  
public XmlTextReader GetXmlReader();
```

Return Value

An `XmlTextReader` object.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The `XmlTextReader` is a read-only, forward-only representation of the XML data stored in the `OracleXmlType` instance.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

IsExists

`IsExists` checks for the existence of a particular set of nodes identified by the XPath expression in the XML data.

Overload List:

- [IsExists\(string, string\)](#)

This method checks for the existence of a particular set of nodes identified by the XPath expression in the XML data represented by the current `OracleXmlType` instance using a string parameter for namespace resolution.

- [IsExists\(string, XmlNamespaceManager\)](#)

This method checks for the existence of a particular set of nodes identified by the XPath expression in the XML document represented by the current `OracleXmlType` instance using a .NET `XmlNamespaceManager` object for namespace resolution.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

IsExists(string, string)

This method checks for the existence of a particular set of nodes identified by the XPath expression in the XML data represented by the current `OracleXmlType` instance using a string parameter for namespace resolution.

Declaration

```
// C#  
public bool IsExists(string xpathExpr, string nsMap);
```

Parameters

- `xpathExpr`
The XPath expression.
- `nsMap`

The string parameter used for namespace resolution of the XPath expression. *nsMap* has zero or more namespaces separated by spaces. *nsMap* can be null.

Return Value

Returns true if the required set of nodes exists; otherwise, returns false.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentNullException` - The *xpathExpr* is null or zero-length.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The default namespace is ignored if its value is an empty string.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

IsExists(string, XmlNameSpaceManager)

This method checks the existence of a particular set of nodes identified by the XPath expression in the XML document represented by the current `OracleXmlType` instance using a `.NET XmlNameSpaceManager` object for namespace resolution.

Declaration

```
// C#
public bool IsExists(string xpathExpr, XmlNameSpaceManager nsMgr);
```

Parameters

- *xpathExpr*
The XPath expression.
- *nsMgr*
The `.NET XmlNameSpaceManager` object used for namespace resolution of the XPath expression. *nsMgr* can be null.

Return Value

Returns true if the required set of nodes exists; otherwise, returns false.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentNullException` - The *xpathExpr* is null or zero-length.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The default namespace is ignored if its value is an empty string.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Transform

This method transforms the `OracleXmlType` into another `OracleXmlType` instance using the given XSL document.

Overload List:

- [Transform\(OracleXmlType, string\)](#)

This method transforms the current `OracleXmlType` instance into another `OracleXmlType` instance using the given XSL document (as an `OracleXmlType` object) and a string of XSLT parameters.

- [Transform\(string, string\)](#)

This public method transforms the current `OracleXmlType` instance into another `OracleXmlType` instance using the given XSL document and a string of XSLT parameters.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Transform(OracleXmlType, string)

This method transforms the current `OracleXmlType` instance into another `OracleXmlType` instance using the given XSL document and a string of XSLT parameters.

Declaration

```
// C#  
public OracleXmlType Transform(OracleXmlType xslDoc, string paramMap);
```

Parameters

- *xslDoc*
The XSL document as an `OracleXmlType` object.
- *paramMap*
A string which provides the parameters for the XSL document.
For this release, *paramMap* is ignored.

Return Value

An `OracleXmlType` object containing the transformed XML document.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentNullException` - The `xslDoc` parameter is null.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Transform(string, string)

This method transforms the current `OracleXmlType` instance into another `OracleXmlType` instance using the given XSL document and a string of XSLT parameters.

Declaration

```
// C#  
public OracleXmlType Transform(string xslDoc, string paramMap);
```

Parameters

- `xslDoc`
The XSL document to be used for XSLT.
- `paramMap`
A string which provides the parameters for the XSL document.
For this release, `paramMap` is ignored.

Return Value

An `OracleXmlType` object containing the transformed XML document.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentNullException` - The `xslDoc` parameter is null.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Update

This method updates the XML node or fragment identified by the given XPath expression in the current `OracleXmlType` instance.

Overload List:

- [Update\(string, string, string\)](#)

This method updates the XML nodes identified by the given XPath expression with the given string value and a string parameter for namespace resolution.
- [Update\(string, XmlNamespaceManager, string\)](#)

This method updates the XML nodes identified by the given XPath expression with the given string value and a .NET `XmlNamespaceManager` object for namespace resolution.
- [Update\(string, string, OracleXmlType\)](#)

This method updates the XML nodes identified by the given XPath expression with the XML data stored in the given `OracleXmlType` value and a string parameter for namespace resolution.
- [Update\(string, XmlNamespaceManager, OracleXmlType\)](#)

This method updates the XML nodes identified by the given XPath expression with the XML data stored in the given `OracleXmlType` value and a .NET `XmlNamespaceManager` object for namespace resolution.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Update(string, string, string)

This method updates the XML nodes identified by the given XPath expression with the given string value and a string parameter for namespace resolution.

Declaration

```
// C#  
public void Update(string xpathExpr, string nsMap, string value);
```

Parameters

- *xpathExpr*

The XPath expression that identifies the nodes to update.
- *nsMap*

The string parameter used for namespace resolution of the XPath expression. *nsMap* has zero or more namespaces separated by spaces. *nsMap* can be null. For example:

```
xmlns:nsi="http://www.company1.com" xmlns:nsz="http://www.company2.com"
```
- *value*

The new value as a string.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentNullException` - The *xpathExpr* is null or zero-length.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

Remarks

The default namespace is ignored if its value is an empty string.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Update(string, XmlNamespaceManager, string)

This method updates the XML nodes identified by the given XPath expression with the given string value and a .NET `XmlNamespaceManager` object for namespace resolution.

Declaration

```
// C#  
public void Update(string xpathExpr, XmlNamespaceManager nsMgr, string  
    value);
```

Parameters

- *xpathExpr*
The XPath expression that identifies the nodes to update.
- *nsMgr*
The .NET `XmlNamespaceManager` object used for namespace resolution of the XPath expression. *nsMgr* can be null.
- *value*
The new value as a string.

Exceptions

ObjectDisposedException - The object is already disposed.

ArgumentNullException - The *xpathExpr* is null or zero-length.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

Remarks

The default namespace is ignored if its value is an empty string.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Update(string, string, OracleXmlType)

This method updates the XML nodes identified by the given XPath expression with the XML data stored in the given `OracleXmlType` value and a string parameter for namespace resolution.

Declaration

```
// C#  
public void Update(string xpathExpr, string nsMap, OracleXmlType value);
```

Parameters

- *xpathExpr*
The XPath expression that identifies the nodes to update.
- *nsMap*
The string parameter used for namespace resolution of the XPath expression. *nsMap* has zero or more namespaces separated by spaces. *nsMap* can be null.
- *value*
The new value as an `OracleXmlType` object.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentNullException` - The *xpathExpr* is null or zero-length.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The default namespace is ignored if its value is an empty string.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Update(string, XmlNamespaceManager, OracleXmlType)

This method updates the XML nodes identified by the given XPath expression with the XML data stored in the given `OracleXmlType` value and a `.NET XmlNamespaceManager` object for namespace resolution.

Declaration

```
// C#  
public void Update(string xpathExpr, XmlNamespaceManager nsMgr, OracleXmlType value);
```

Parameters

- *xpathExpr*
The XPath expression that identifies the nodes to update.
- *nsMgr*

The .NET `XmlNamespaceManager` object used for namespace resolution of the XPath expression. `nsMgr` can be null.

- *value*

The new value as an `OracleXmlType` object.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentNullException` - The `xpathExpr` is null or zero-length.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The default namespace is ignored if its value is an empty string.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Validate

This methods validates whether or not the XML data in the `OracleXmlType` object conforms to the given XML schema.

Declaration

```
// C#
public bool Validate(String schemaUrl);
```

Parameters

- `schemaUrl`

A string representing the [URL](#) in the database of the XML schema.

Return Value

Returns true if the XML data conforms to the XML schema; otherwise, returns false.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentNullException` - The `schemaUrl` argument is null or an empty string.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleXmlType Class](#)
- [OracleXmlType Members](#)

Oracle Data Provider for .NET HA Event Classes

This chapter describes the following ODP.NET HA event class and enumerations:

- [OracleHAEventArgs Class](#)
- [OracleHAEventHandler Delegate](#)
- [OracleHAEventSource Enumeration](#)
- [OracleHAEventStatus Enumeration](#)

OracleHAEventArgs Class

The OracleHAEventArgs class provides event data for the OracleConnection.HAEvent event.

Class Inheritance

System.Object

System.EventArgs

Oracle.DataAccess.Client.OracleHAEventArgs

Declaration

```
// C#
public sealed class OracleHAEventArgs
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

When any HA event occurs for a service, service member, host, node, or instance that an OracleConnection object is set to with "ha events=true", the OracleConnection.HAEvent is triggered and passes an instance of OracleHAEventArgs to all the delegates that have registered with the event.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleHAEventArgs Members](#)
- [OracleHAEventArgs Properties](#)
- ["OracleConnection Class"](#) on page 6-79
- ["HAEvent"](#) on page 6-131

OracleHAEventArgs Members

OracleHAEventArgs members are listed in the following table.

OracleHAEventArgs Properties

The OracleHAEventArgs properties are listed in [Table 8-2](#).

Table 8-1 OracleHAEventArgs Properties

| Name | Description |
|------------------------------------|--------------------------------------------------------------------|
| DatabaseDomainName | Specifies the domain name of the database affected by the HAevent |
| DatabaseName | Specifies the database affected by the HAevent |
| HostName | Specifies the host that triggered the event |
| InstanceName | Specifies the instance that triggered the event |
| Reason | Specifies the reason for which the HA event was sent by the server |
| ServiceName | Specifies the service that triggered the event |
| Source | Specifies the source that triggered the event |
| Status | Specifies the status of the source that triggered the event |
| Time | Specifies the time when the event was triggered on the server |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleHAEventArgs Class](#)
- ["HAEvent"](#) on page 6-131

OracleHAEventArgs Properties

The OracleHAEventArgs properties are listed in [Table 8–2](#).

Table 8–2 OracleHAEventArgs Properties

| Name | Description |
|------------------------------------|--------------------------------------------------------------------|
| DatabaseDomainName | Specifies the domain name of the database affected by the HAevent |
| DatabaseName | Specifies the database affected by the HAevent |
| HostName | Specifies the host that triggered the event |
| InstanceName | Specifies the instance that triggered the event |
| Reason | Specifies the reason for which the HA event was sent by the server |
| ServiceName | Specifies the service that triggered the event |
| Source | Specifies the source that triggered the event |
| Status | Specifies the status of the source that triggered the event |
| Time | Specifies the time when the event was triggered on the server |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)

DatabaseDomainName

This property specifies the domain name of the database that is affected by the HA event.

Declaration

```
// C#
public string DatabaseDomainName {get;}
```

Property Value

The domain name of the database that is affected by the HA Event.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)
- ["HAEvent"](#) on page 6-131

DatabaseName

This property specifies the database that is affected by the HA event.

Declaration

```
// C#  
public string DatabaseName {get;}
```

Property Value

This property specifies the database name that is affected by the HA event.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)
- ["HAEvent"](#) on page 6-131

HostName

This property specifies the host that triggered the HA event.

Declaration

```
// C#  
public string HostName {get;}
```

Property Value

The host that is affected by the HA Event.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)
- ["HAEvent"](#) on page 6-131

InstanceName

This property specifies the instance that triggered the HA event.

Declaration

```
// C#  
public string InstanceName {get;}
```

Property Value

The instance that is affected by the HA Event.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)
- ["HAEvent"](#) on page 6-131

Reason

This property specifies reason for which the HA event was sent by the server.

Declaration

```
// C#  
public string Reason {get;}
```

Property Value

The reason the HA Event was triggered. Possible values include `Data_Guard_Failover`, `Failure`, `Dependency`, `User`, `Autostart`, and `Restart`.

The value `User` is indicative of a planned outage. All other values are indicative of an unplanned outage.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)
- ["HAEvent"](#) on page 6-131

ServiceName

This property specifies the service that triggered the HA event.

Declaration

```
// C#  
public string ServiceName {get;}
```

Property Value

The service that is affected by the HA Event.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)
- ["HAEvent"](#) on page 6-131

Source

This property specifies the source that triggered the HA event.

Declaration

```
// C#  
public OracleHAEventSource Source {get;}
```

Property Value

The source that triggered the HA Event.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)
- ["HAEvent"](#) on page 6-131

Status

This property specifies the status of the source that triggered the HA event.

Declaration

```
// C#  
public OracleHAEventStatus Status {get;}
```

Property Value

The status of the source that triggered the HA Event.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)
- ["HAEvent"](#) on page 6-131

Time

This property specifies the time when the HA event was triggered on the server.

Declaration

```
// C#  
public DateTime Time {get;}
```

Property Value

The time that the HA Event was triggered.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleHAEventArgs Class](#)
- [OracleHAEventArgs Members](#)
- ["HAEvent"](#) on page 6-131

OracleHAEHandler Delegate

The `OracleHAEHandler` delegate represents the signature of the method that handles the `OracleConnection.HAEEvent` event.

Declaration

```
// C#
public delegate void OracleHAEHandler(OracleHAEEventArgs eventArgs);
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Parameters

- *sender*
The source of the event.
- *EventArgs*
The `OracleHAEEventArgs` object that contains the event data.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleHAEEventArgs Class](#)
- ["HAEEvent"](#) on page 6-131

OracleHAEvntSource Enumeration

The `OracleHAEvntSource` enumeration indicates the source of the HA event.

[Table 8–3](#) lists all the `OracleHAEvntSource` enumeration values with a description of each enumerated value.

Table 8–3 OracleHAEvntSource Enumeration Member Values

| Member Name | Description |
|----------------------------|-------------------------------------------------|
| <code>Service</code> | The source of the HA Event is a service. |
| <code>ServiceMember</code> | The source of the HA Event is a service member. |
| <code>Database</code> | The source of the HA Event is a database. |
| <code>Host</code> | The source of the HA Event is a host. |
| <code>Instance</code> | The source of the HA Event is an instance. |

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|-----------------------|---------------------------------------|----------------------------------------------|
| Assembly | <code>Oracle.DataAccess.dll</code> | <code>Oracle.ManagedDataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Client</code> | <code>Oracle.ManagedDataAccess.Client</code> |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleHAEvntArgs Class](#)
- ["Source"](#) on page 8-7

OracleHAEventStatus Enumeration

The `OracleHAEventStatus` enumeration indicates the status of the HA event source.

[Table 8-4](#) lists all the `OracleHAEventStatus` enumeration values with a description of each enumerated value.

Table 8-4 OracleHAEventStatus Enumeration Values

| Member Name | Description |
|-------------|-------------------------------------|
| Up | The source of the HA Event is up. |
| Down | The source of the HA Event is down. |

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleHAEventArgs Class](#)
- ["Status"](#) on page 8-7

Continuous Query Notification Classes

This chapter describes Oracle Data Provider for .NET Continuous Query Notification Classes, Event Delegates, and Enumerations.

See Also: ["Continuous Query Notification Support"](#) on page 3-112

This chapter contains these topics:

- [OracleDependency Class](#)
- [OracleNotificationRequest Class](#)
- [OracleNotificationEventArgs Class](#)
- [OnChangeEventHandler Delegate](#)
- [OracleRowidInfo Enumeration](#)
- [OracleNotificationType Enumeration](#)
- [OracleNotificationSource Enumeration](#)
- [OracleNotificationInfo Enumeration](#)

OracleDependency Class

An `OracleDependency` class represents a dependency between an application and an Oracle database, enabling the application to get notifications whenever the data of interest or the state of the Oracle database changes.

Class Inheritance

`System.Object`

`Oracle.DataAccess.Client.OracleDependency`

Declaration

```
// C#  
public sealed class OracleDependency
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------------------|----------------------------------------------|
| Assembly | <code>Oracle.DataAccess.dll</code> | <code>Oracle.ManagedDataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Client</code> | <code>Oracle.ManagedDataAccess.Client</code> |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Not supported in a .NET stored procedure

Thread Safety

All public static methods are thread-safe, although methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDependency Members](#)
- [OracleDependency Constructors](#)
- [OracleDependency Static Fields](#)
- [OracleDependency Static Methods](#)
- [OracleDependency Methods](#)
- [OracleDependency Properties](#)
- [OracleDependency Events](#)

OracleDependency Members

OracleDependency members are listed in the following tables.

OracleDependency Constructors

OracleDependency constructors are listed in [Table 9-1](#).

Table 9-1 OracleDependency Constructors

| Constructors | Description |
|-----------------------------------------------|--------------------------------------------------------------------|
| OracleDependency Constructors | Instantiates a new instance of OracleDependency class (Overloaded) |

OracleDependency Static Fields

The OracleDependency static field is listed in [Table 9-2](#).

Table 9-2 OracleDependency Static Field

| Static Field | Description |
|----------------------|-------------------------------------------------------------------------------------------------|
| Port | Indicates the port number that the notification listener listens on, for database notifications |

OracleDependency Static Methods

OracleDependency static methods are listed in [Table 9-3](#).

Table 9-3 OracleDependency Static Methods

| Static Methods | Description |
|-------------------------------------|-------------------------------------------------------------------------------|
| Equals | Inherited from System.Object |
| GetOracleDependency | Returns an OracleDependency instance based on the specified unique identifier |

OracleDependency Properties

OracleDependency properties are listed in [Table 9-4](#).

Table 9-4 OracleDependency Properties

| Properties | Description |
|----------------------------------------|----------------------------------------------------------------------------------------------|
| DataSource | Indicates the data source associated with the OracleDependency instance |
| HasChanges | Indicates whether or not there is any change in the database associated with this dependency |
| Id | Represents the unique identifier for the OracleDependency instance |
| IsEnabled | Specifies whether or not the dependency is enabled between the application and the database |
| QueryBasedNotification | Specifies whether the change notification registration is object-based or query-based |
| RegisteredQueryIDs | Provides a list of CHANGE_NOTIFICATION_QUERY_IDS |
| RegisteredResources | Indicates the database resources that are registered in the notification registration |

Table 9–4 (Cont.) OracleDependency Properties

| Properties | Description |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------|
| RowidInfo | Specifies whether or not ROWID information is part of change notification events fired whenever data changes on the database |
| UserName | Indicates the database user name associated with the OracleDependency instance |

OracleDependency Methods

OracleDependency methods are listed in [Table 9–5](#).

Table 9–5 OracleDependency Methods

| Methods | Description |
|--------------------------------------|-----------------------------------------------------------------------------|
| AddCommandDependency | Binds the OracleDependency instance to the specified OracleCommand instance |
| Equals | Inherited from System.Object |
| GetHashCode | Inherited from System.Object |
| GetType | Inherited from System.Object |
| RemoveRegistration | Removes the specified dependency between the application and the database |
| ToString | Inherited from System.Object |

OracleDependency Events

The OracleDependency event is listed in [Table 9–6](#).

Table 9–6 OracleDependency Events

| Event | Description |
|--------------------------|-----------------------------------------------------------------------------------------------------------------|
| OnChange | An event that is sent when a database notification associated with the dependency is received from the database |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDependency Class](#)

OracleDependency Constructors

OracleDependency constructors create instances of the OracleDependency class.

Overload List:

- [OracleDependency \(\)](#)

This constructor creates an instance of the OracleDependency class.

- [OracleDependency\(OracleCommand\)](#)

This constructor creates an instance of the OracleDependency class and binds it to the specified OracleCommand instance.

- [OracleDependency\(OracleCommand, bool, int, bool\)](#)

This constructor creates an instance of the OracleDependency class and binds it to the specified OracleCommand instance, specifying whether or not a notification is to be removed upon notification, the timeout value of the notification registration, and the persistence of the notification.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDependency Class](#)
- [OracleDependency Members](#)

OracleDependency ()

This constructor creates an instance of the OracleDependency class.

Declaration

```
// C#  
public OracleDependency ()
```

Remarks

Using this constructor does not bind any OracleCommand to the newly constructed OracleDependency. Use the `AddCommandDependency` method to do so.

Note: The dependency between the application and the database is not established when the OracleDependency instance is created. The dependency is established when the command that is associated with this dependency is executed.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDependency Class](#)
- [OracleDependency Members](#)

OracleDependency(OracleCommand)

This constructor creates an instance of the `OracleDependency` class and binds it to an `OracleCommand` instance.

Declaration

```
// C#  
public OracleDependency (OracleCommand cmd)
```

Parameters

- *cmd*

The command that the `OracleDependency` object binds to.

Exceptions

`ArgumentNullException` - The *cmd* parameter is null.

`InvalidOperationException` - The specified `OracleCommand` instance already contains a notification request.

Remarks

When this `OracleDependency` constructor binds the `OracleCommand` instance to an `OracleDependency` instance, it causes the creation of an `OracleNotificationRequest` instance and then sets that `OracleNotificationRequest` instance to the `OracleCommand.Notification` property.

The Continuous Query Notification is registered with the database, when the command is executed. Any of the command execution methods (for example, `ExecuteNonQuery`, `ExecuteReader`, and so on) will register the notification request. An `OracleDependency` may be bound to more than one `OracleCommand`. When one of these `OracleCommand` object statements is executed, the statement is registered with the associated `OracleCommand`. Although the registration happens on each `OracleCommand` separately, one `OracleDependency` can be responsible for detecting and sending notifications that occur for all `OracleCommand` objects that the `OracleDependency` is associated with. The `OnChangeEventArgs` that is passed to the application for the `OnChange` event provides information on what has changed in the database.

The `OracleNotificationRequest` instance that is created by this constructor has the following default property values:

- `IsNotifiedOnce` is set to the value `True`.
- `Timeout` is set to 50,000 seconds.
- `IsPersistent` is set to the value `False`, that is, the invalidation message is not persistent, but is stored in an in-memory queue before delivery.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDependency Class](#)
- [OracleDependency Members](#)

OracleDependency(OracleCommand, bool, int, bool)

This constructor creates an instance of the `OracleDependency` class and binds it to the specified `OracleCommand` instance, while specifying whether or not a registration is to be removed upon notification, the timeout value of the notification registration, and the persistence of the notification.

Declaration

```
// C#
public OracleDependency (OracleCommand cmd, bool isNotifiedOnce, long timeout,
    bool isPersistent)
```

Parameters

- *cmd*
The command associated with the Continuous Query Notification request.
- *isNotifiedOnce*
An indicator that specifies whether or not the registration is removed automatically once the notification occurs.
- *timeout*
The amount of time, in seconds, that the registration stays active. When *timeout* is set to 0, the registration never expires. The valid values for *timeout* are between 0 and 4294967295.
- *isPersistent*
Indicates whether or not the invalidation message should be queued persistently in the database before delivery. If the *isPersistent* parameter is set to `True`, the message is queued persistently in the database and cannot be lost upon database failures or shutdowns. If the *isPersistent* property is set to `False`, the message is stored in an in-memory queue before delivery and might be lost.

Database performance is faster if the message is stored in an in-memory queue rather than in the database queue.

Exceptions

`ArgumentNullException` - The *cmd* parameter is null.

`ArgumentOutOfRangeException` - The specified *timeout* is invalid.

`InvalidOperationException` - The specified `OracleCommand` instance already contains a notification request.

Remarks

When this `OracleDependency` constructor binds the `OracleCommand` instance to an `OracleDependency` instance, it causes the creation of an `OracleNotificationRequest` instance and then sets that `OracleNotificationRequest` instance to the `OracleCommand.Notification` property.

The Continuous Query Notification is registered with the database, when the command is executed. Any of the command execution methods (for example, `ExecuteNonQuery`, `ExecuteReader`, and so on) will register the notification request. An `OracleDependency` may be bound to more than one `OracleCommand`. When one of these `OracleCommand` object statements is executed, the statement is registered with the associated `OracleCommand`. Although the registration happens on each `OracleCommand`

separately, one `OracleDependency` can be responsible for detecting and sending notifications that occur for all `OracleCommand` objects that the `OracleDependency` is associated with. The `OnChangeEventArgs` that is passed to the application for the `OnChange` event provides information on what has changed in the database.

The `OracleNotificationRequest` instance that is created by this constructor has the following default property values:

- `IsNotifiedOnce` is set to the specified value.
- `Timeout` is set to the specified value.
- `IsPersistent` is set to the specified value.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDependency Class](#)
- [OracleDependency Members](#)

OracleDependency Static Fields

The OracleDependency static field is listed in [Table 9-7](#).

Table 9-7 OracleDependency Static Field

| Static Field | Description |
|----------------------|-------------------------------------------------------------------------------------------------|
| Port | Indicates the port number that the notification listener listens on, for database notifications |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDependency Class](#)
- [OracleDependency Members](#)

Port

This static field indicates the port number that the notification listener listens on, for database notifications.

Declaration

```
// C#
public static int Port{get; set}
```

Property Value

An `int` value that represents the number of the port that listens for the database notifications. If the port number is set to `-1`, a random port number is assigned for the listener when the listener is started. Otherwise, the specified port number is used to start the listener.

Exceptions

`ArgumentOutOfRangeException` - The port number is set to a negative value.

`InvalidOperationException` - The port number is being changed after the listener has started.

Remarks

The port number specified by the `OracleDependency.Port` static field is used by the notification listener that runs within the same application domain as ODP.NET. This port number receives Continuous Query Notifications from the database. One notification listener is capable of listening to all Continuous Query Notifications and therefore, only one notification listener is created for each application domain.

The notification listener is created when a command associated with an `OracleDependency` object is executed for the first time during the application domain lifetime. The port number specified for the `OracleDependency.Port` static field is used by the listener for its lifetime. The `OracleDependency.Port` static field can be changed after the creation of the notification listener, but doing so does not affect the actual port number that the notification listener listens on.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDependency Class](#)
- [OracleDependency Members](#)

OracleDependency Static Methods

OracleDependency static methods are listed in [Table 9–8](#).

Table 9–8 OracleDependency Static Methods

| Static Methods | Description |
|-------------------------------------|--------------------------------------------------------------------------------------------|
| Equals | Inherited from <code>System.Object</code> |
| GetOracleDependency | Returns an <code>OracleDependency</code> instance based on the specified unique identifier |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDependency Class](#)
- [OracleDependency Members](#)

GetOracleDependency

This static method returns an `OracleDependency` instance based on the specified unique identifier.

Declaration

```
// C#
public static OracleDependency GetOracleDependency(string guid)
```

Parameters

- *guid*
The string representation of the unique identifier of an `OracleDependency` instance.

Exceptions

`ArgumentException` - The specified unique identifier cannot locate an `OracleDependency` instance.

Return Value

An `OracleDependency` instance that has the specified *guid* parameter.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDependency Class](#)
- [OracleDependency Members](#)

OracleDependency Properties

OracleDependency properties are listed in [Table 9-9](#).

Table 9-9 OracleDependency Properties

| Properties | Description |
|----------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| DataSource | Indicates the data source associated with the OracleDependency instance |
| HasChanges | Indicates whether or not there is any change in the database associated with this dependency |
| Id | Represents the unique identifier for the OracleDependency instance |
| IsEnabled | Specifies whether or not the dependency is enabled between the application and the database |
| QueryBasedNotification | Specifies whether the change notification registration is object-based or query-based |
| RegisteredQueryIDs | Provides a list of CHANGE_NOTIFICATION_QUERY_IDS |
| RegisteredResources | Indicates the database resources that are registered in the notification registration |
| RowidInfo | Specifies whether or not ROWID information is part of change notification events fired whenever data changes on the database |
| UserName | Indicates the database user name associated with the OracleDependency instance |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDependency Class](#)
- [OracleDependency Members](#)

DataSource

This property indicates the data source associated with the OracleDependency instance.

Declaration

```
// C#
public string DataSource{get;}
```

Property Value

A string that indicates the data source associated with the OracleDependency instance.

Remarks

The DataSource property is populated with the data source once the OracleCommand associated with the OracleDependency executes and registers for the notification successfully.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDependency Class](#)
- [OracleDependency Members](#)

HasChanges

This property indicates whether or not there is any change in the database associated with this dependency.

Declaration

```
// C#  
public bool HasChanges{get;}
```

Property Value

A `bool` value that returns `True` if the database has detected changes that are associated with this dependency; otherwise, returns `False`.

Remarks

As an alternative to using the `OnChange` event, applications can check the `HasChanges` property to determine if there are any changes in the database associated with this dependency.

Once the `HasChanges` property is accessed, its value is reset to `False` so that the next notification can then be acknowledged.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDependency Class](#)
- [OracleDependency Members](#)

Id

This property represents the unique identifier for the `OracleDependency` instance.

Declaration

```
// C#  
public string Id{get;}
```

Property Value

A string that represents the unique identifier that was generated for the `OracleDependency` instance when it was created.

Remarks

This property is set when the `OracleDependency` instance is created.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDependency Class](#)
- [OracleDependency Members](#)

IsEnabled

This property specifies whether or not the dependency is enabled between the application and the database.

Declaration

```
// C#  
public bool IsEnabled {get;}
```

Property Value

A `bool` value that specifies whether or not dependency is enabled between the application and the database.

Remarks

The dependency between the application and the database is not established when the `OracleDependency` instance is created. The dependency is established when the command that is associated with this dependency is executed, at which time the notification request is registered with the database. The dependency ends when the notification registration is removed from the database or when it times out.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDependency Class](#)
- [OracleDependency Members](#)

QueryBasedNotification

This instance property specifies whether the change notification registration is object-based or query-based.

Declaration

```
// C#  
public bool QueryBasedNotification{get; set;}
```

Property Value

Specifies whether the change notification registration is object-based or not.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

This property value will be ignored if it is set after the command execution that registers the command for change notification.

By default, this property is true.

ODP.NET developers can register their queries on the row level, not just the object level, beginning with Oracle Data Provider for .NET release 11.1 and Oracle Database 11g release 1 (11.1). The application only receives notification when the selected row or rows change. Query-based notifications provide developers more granularity for using client-side cached data, as they can be more specific about what changes the application needs to be notified of.

`OracleNotificationType` enumeration is set to `Query` for query-based notifications.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDependency Class](#)
- [OracleDependency Members](#)

RegisteredQueryIDs

This instance property provides a list of `CHANGE_NOTIFICATION_QUERY_IDS`.

Declaration

```
// C#
public ArrayList RegisteredQueryIDs {get;}
```

Property Value

This property is an `ArrayList` of `CHANGE_NOTIFICATION_QUERY_IDS`.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

This property provides a list of `CHANGE_NOTIFICATION_QUERY_IDS` that uniquely identify the query that has been registered for change notification. The notification returned from the database will also contain these IDs, allowing applications to determine the query that the notifications are for.

The `QueryId` at index *n* in `RegisteredQueryIDs` is for the statement at index *n* the `RegisteredResources` at index *n*.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDependency Class](#)
- [OracleDependency Members](#)

RegisteredResources

This property indicates the database resources that are registered in the notification registration.

Declaration

```
// C#
```

```
public ArrayList RegisteredResources{get;}
```

Property Value

The registered resources in the notification registration.

Remarks

The `ArrayList` contains all the command statement or statements that are registered for notification through this `OracleDependency` object. It is appropriately updated when the Continuous Query Notification is registered by a command execution.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDependency Class](#)
- [OracleDependency Members](#)

RowidInfo

This property specifies whether or not ROWID information is part of change notification events fired whenever data changes on the database.

Declaration

```
// C#  
public OracleRowidInfo RowidInfo {get; set;};
```

Property Value

An `OracleRowidInfo` enumeration type that determines the inclusion of ROWID in the change notification event.

Remarks

There are three `OracleRowidInfo` enumeration types that are valid for this property:

- **Default** includes ROWID information in the change notification event only if `OracleCommand.AddRowid` property is set to `true` or if ROWID is in the select list of the query that is registered for change notification.
- **Include** includes ROWID information regardless of whether or not ROWID is in the select-list for the query.
- **Exclude** excludes ROWID information regardless of whether or not ROWID is in the select-list.

For change notification registrations that involve stored procedure executions, change notification events related to the REF CURSOR contain ROWID information only if `RowidInfo` property is set to `OracleRowidInfo.Include`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDependency Class](#)
- [OracleDependency Members](#)
- ["OracleRowidInfo Enumeration"](#) on page 9-41

UserName

This property indicates the database user name associated with the `OracleDependency` instance.

Declaration

```
// C#  
public string UserName{get;}
```

Property Value

A string that indicates the database user name associated with the `OracleDependency` instance. This database user registers the Continuous Query Notification request with the database.

Remarks

The `UserName` property is populated with the user name once the `OracleCommand` associated with the `OracleDependency` executes and registers for the notification successfully. Only the database user who creates the notification registration, or the database system administrator, can remove the registration.

The user specified by this property must have the `CHANGE NOTIFICATION` privilege to register successfully for the Continuous Query Notification with the database.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDependency Class](#)
- [OracleDependency Members](#)

OracleDependency Methods

OracleDependency methods are listed in [Table 9–10](#).

Table 9–10 OracleDependency Methods

| Methods | Description |
|--------------------------------------|-----------------------------------------------------------------------------|
| AddCommandDependency | Binds the OracleDependency instance to the specified OracleCommand instance |
| Equals | Inherited from System.Object |
| GetHashCode | Inherited from System.Object |
| GetType | Inherited from System.Object |
| RemoveRegistration | Removes the specified dependency between the application and the database |
| ToString | Inherited from System.Object |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDependency Class](#)
- [OracleDependency Members](#)

AddCommandDependency

This instance method binds the OracleDependency instance to the specified OracleCommand instance.

Declaration

```
// C#
Public void AddCommandDependency (OracleCommand cmd);
```

Parameters

- *cmd*

The command that is to be bound to the OracleDependency object.

Exceptions

ArgumentNullException - The *cmd* parameter is null.

InvalidOperationException - The specified OracleCommand instance already contains a notification request.

Remarks

An OracleDependency instance can bind to multiple OracleCommand instances.

While it binds an existing OracleDependency instance to an OracleCommand instance, the AddCommandDependency method creates an OracleNotificationRequest instance, and sets it to the specified OracleCommand.Notification property.

When this method creates an OracleNotificationRequest instance, the following OracleNotificationRequest properties are set:

- `IsNotifiedOnce` is set to the value `True`.
- `Timeout` is set to 50,000 seconds.
- `IsPersistent` is set to the value `False`, indicating that the invalidation message is stored in an in-memory queue before delivery.

With this method, multiple commands can be associated with a single Continuous Query Notification registration request. Furthermore, the `OracleNotificationRequest` attribute values assigned to the `OracleCommand` can be changed once the association between the `OracleCommand` and the `OracleDependency` is established.

However, when multiple `OracleCommand` objects are associated with a single `OracleDependency` object, the `OracleNotificationRequest` attributes (`Timeout`, `IsPersistent`, and `IsNotifiedOnce`) of the first executed `OracleCommand` object are used for registration, the attributes associated with subsequent `OracleCommand` executions will be ignored.

Furthermore, once a command associated with an `OracleDependency` is executed and registered, all other subsequent command executions and registration associated with the same `OracleDependency` must use a connection with the same "User Id" and "Data Source" connection string attribute value settings.

Otherwise, an exception will be thrown.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDependency Class](#)
- [OracleDependency Members](#)
- ["OracleDependency\(OracleCommand\)"](#) on page 9-6 for `OracleNotificationRequest` property value

RemoveRegistration

This instance method removes the specified dependency between the application and the database. Once the registration of the dependency is removed from the database, the `OracleDependency` is no longer able to detect any changes that the database undergoes.

Declaration

```
// C#
public void RemoveRegistration(OracleConnection con)
```

Parameters

- `con`
The connection associated with the `OracleDependency` instance.

Exceptions

`InvalidOperationException` - The associated connection is not open.

Remarks

The notification registration associated with the `OracleDependency` instance is removed from the database.

The `OracleConnection` parameter must be in an *opened state*. This instance method does not open the connection implicitly for the application.

An exception is thrown if the dependency is not valid.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDependency Class](#)
- [OracleDependency Members](#)

OracleDependency Events

The OracleDependency event is listed in [Table 9–11](#).

Table 9–11 OracleDependency Event

| Event | Description |
|--------------------------|-----------------------------------------------------------------------------------------------------------------|
| OnChange | An event that is sent when a database notification associated with the dependency is received from the database |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDependency Class](#)
- [OracleDependency Members](#)

OnChange

The OnChange event is sent when a database notification associated with the dependency is received from the database. The information related to the notification is stored in the OracleChangeNotificationEventArgs class.

Declaration

```
// C#
public event OnChangeEventHandler OnChange;
```

Remarks

The OnChange event occurs if any result set associated with the dependency changes. For objects that are part of a Transaction, notifications will be received for each modified object. This event also occurs for other actions related to database or registration status, such as database shutdowns and startups, or registration timeouts.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleDependency Class](#)
- [OracleDependency Members](#)

OracleNotificationRequest Class

An `OracleNotificationRequest` class represents a notification request to be subscribed in the database. It contains information about the request and the characteristics of the notification. Using the `OracleNotificationRequest` class, Oracle Data Provider for .NET can create the notification registration in the database.

Class Inheritance

`System.Object`

`Oracle.DataAccess.Client.OracleNotificationRequest`

Declaration

```
// C#  
public sealed class OracleNotificationRequest
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------------------|----------------------------------------------|
| Assembly | <code>Oracle.DataAccess.dll</code> | <code>Oracle.ManagedDataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Client</code> | <code>Oracle.ManagedDataAccess.Client</code> |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Not supported in a .NET stored procedure

Thread Safety

All public static methods are thread-safe, although methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Static Methods](#)
- [OracleNotificationRequest Properties](#)
- [OracleNotificationRequest Methods](#)

OracleNotificationRequest Members

OracleNotificationRequest members are listed in the following tables.

OracleNotificationRequest Static Method

The OracleNotificationRequest static method is listed in [Table 9–12](#).

Table 9–12 OracleNotificationRequest Static Method

| Static Method | Description |
|---------------|------------------------------|
| Equals | Inherited from System.Object |

OracleNotificationRequest Properties

OracleNotificationRequest properties are listed in [Table 9–13](#).

Table 9–13 OracleNotificationRequest Properties

| Properties | Description |
|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------|
| IsNotifiedOnce | Indicates whether or not the registration is to be removed upon notification |
| IsPersistent | Indicates whether or not the notification message should be queued persistently in the database before delivery |
| Timeout | Specifies the time that the registration remains alive |
| GroupingNotificationEnabled | Specifies whether grouping notification is enabled or not |
| GroupingType | Specifies the type of grouping notification |
| GroupingInterval | Specifies the interval between grouping notifications, in seconds |

OracleNotificationRequest Methods

OracleNotificationRequest methods are listed in [Table 9–14](#).

Table 9–14 OracleNotificationRequest Methods

| Methods | Description |
|-------------|------------------------------|
| Equals | Inherited from System.Object |
| GetHashCode | Inherited from System.Object |
| GetType | Inherited from System.Object |
| ToString | Inherited from System.Object |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

OracleNotificationRequest Static Methods

The `OracleNotificationRequest` static method is listed in [Table 9–15](#).

Table 9–15 *OracleNotificationRequest Static Method*

| Static Method | Description |
|---------------------|-------------------------------------------|
| <code>Equals</code> | Inherited from <code>System.Object</code> |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

OracleNotificationRequest Properties

The OracleNotificationRequest properties are listed in [Table 9–16](#).

Table 9–16 OracleNotificationRequest Properties

| Properties | Description |
|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------|
| IsNotifiedOnce | Indicates whether or not the registration is to be removed upon notification |
| IsPersistent | Indicates whether or not the notification message should be queued persistently in the database before delivery |
| Timeout | Specifies the time that the registration remains alive |
| GroupingNotificationEnabled | Specifies whether grouping notification is enabled or not |
| GroupingType | Specifies the type of grouping notification |
| GroupingInterval | Specifies the interval between grouping notifications, in seconds |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

IsNotifiedOnce

This property indicates whether or not the registration is to be removed upon notification.

Declaration

```
// C#
public bool IsNotifiedOnce{get; set;}
```

Property Value

A `bool` value that indicates whether or not the registration is to be removed upon notification.

Remarks

The default value is `false` for AQ. This is different from change notification where the default value is `true`.

Modifying this property after the completion of a successful registration has no effect.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

IsPersistent

This property indicates whether or not the notification message should be queued persistently in the database until delivery.

Declaration

```
// C#  
public bool IsPersistent{get; set;}
```

Property Value

A `bool` value that indicates whether or not the notifications should be stored persistently in the database until delivery.

When the `IsPersistent` property is set to `True`, the message is queued persistently in the database and cannot be lost upon database failures or shutdowns. When the `IsPersistent` property is set to `False`, the message is stored in an in-memory queue before delivery and could be lost.

This property does not apply to `NotificationRegistration` which is always persistent.

This property only applies to the notification message after it has been sent.

Remarks

The default value is `false`.

The database performs faster if the message is stored in an in-memory queue rather than a database queue.

Modifying this property after the completion of a successful registration has no effect.

This property is ignored for grouping notifications.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

Timeout

This property specifies the time, in seconds, that the registration remains alive.

Declaration

```
// C#  
public long Timeout{get; set;}
```

Property Value

A `long` value that specifies the time, in seconds, that the registration remains alive. The valid values for the `Timeout` property are between 0 and 4294967295.

Exceptions

`ArgumentOutOfRangeException` - The specified `Timeout` is invalid.

Remarks

The default value is 0 (infinite) for AQ and 50000 for change notification. If the Timeout property is set to 0, then the registration does not expire.

If the registration is removed because the Timeout value has been reached, then the database sends a notification indicating the expiration.

Modifying this property after the completion of a successful registration has no effect.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

GroupingNotificationEnabled

This property specifies whether grouping notification is enabled or not.

Declaration

```
// C#
public bool GroupingNotificationEnabled {get; set}
```

Property Value

A true value indicates that grouping notification is enabled. A false value indicates that grouping notification is disabled.

Remarks

The default value is false.

Modifying this property after the completion of a successful registration has no effect.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

GroupingType

This property specifies the type of grouping notification.

Declaration

```
// C#
public OracleAQNotificationGroupingType GroupingType {get; set}
```

Property Value

An OracleAQNotificationGroupingType enum value

Remarks

The default value is OracleAQNotificationGroupingType.Summary.

Modifying this property after the completion of a successful registration has no effect.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

GroupingInterval

This property specifies the interval of grouping notification in seconds. The group notifications are delivered at intervals specified by this property.

Declaration

```
// C#  
public int GroupingInterval {get; set}
```

Property Value

An integer specifying the grouping interval in seconds.

Remarks

The default value is 600 seconds.

The range of GroupingInterval is from 0 to `Int32.MaxValue`.

Modifying this property after the completion of a successful registration has no effect.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

OracleNotificationRequest Methods

OracleNotificationRequest methods are listed in [Table 9-17](#).

Table 9-17 OracleNotificationRequest Methods

| Methods | Description |
|-------------|------------------------------|
| Equals | Inherited from System.Object |
| GetHashCode | Inherited from System.Object |
| GetType | Inherited from System.Object |
| ToString | Inherited from System.Object |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleNotificationRequest Members](#)
- [OracleNotificationRequest Class](#)

OracleNotificationEventArgs Class

The OracleNotificationEventArgs class provides event data for a notification.

Class Inheritance

System.Object

System.EventArgs

Oracle.DataAccess.Client.OracleNotificationEventArgs

Declaration

```
// C#  
public sealed class OracleNotificationEventArgs
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Not supported in a .NET stored procedure

Thread Safety

All public static methods are thread-safe, although methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleNotificationEventArgs Members](#)
- [OracleNotificationEventArgs Static Fields](#)
- [OracleNotificationEventArgs Static Methods](#)
- [OracleNotificationEventArgs Properties](#)
- [OracleNotificationEventArgs Methods](#)

OracleNotificationEventArgs Members

OracleNotificationEventArgs members are listed in the following tables.

OracleNotificationEventArgs Static Fields

The OracleNotificationEventArgs static field is listed in [Table 9–18](#).

Table 9–18 OracleNotificationEventArgs Static Field

| Static Field | Description |
|--------------|---------------------------------|
| Empty | Inherited from System.EventArgs |

OracleNotificationEventArgs Static Methods

The OracleNotificationEventArgs static method is listed in [Table 9–19](#).

Table 9–19 OracleNotificationEventArgs Static Method

| Static Method | Description |
|---------------|------------------------------|
| Equals | Inherited from System.Object |

OracleNotificationEventArgs Properties

OracleNotificationEventArgs properties are listed in [Table 9–20](#).

Table 9–20 OracleNotificationEventArgs Properties

| Properties | Description |
|-------------------------------|----------------------------------------------------------------------|
| Details | Contains detailed information about the current notification |
| Info | Indicates the database events for the notification |
| ResourceNames | Indicates the database resources related to the current notification |
| Source | Returns the database event source for the notification |
| Type | Returns the database event type for the notification |

OracleNotificationEventArgs Methods

OracleNotificationEventArgs methods are listed in [Table 9–21](#).

Table 9–21 OracleNotificationEventArgs Methods

| Methods | Description |
|-------------|------------------------------|
| Equals | Inherited from System.Object |
| GetHashCode | Inherited from System.Object |
| GetType | Inherited from System.Object |
| ToString | Inherited from System.Object |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleNotificationEventArgs Class](#)

OracleNotificationEventArgs Static Fields

The OracleNotificationEventArgs static field is listed in [Table 9-22](#).

Table 9-22 OracleNotificationEventArgs Static Field

| Static Field | Description |
|--------------|---------------------------------|
| Empty | Inherited from System.EventArgs |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)

OracleNotificationEventArgs Static Methods

The OracleNotificationEventArgs static method is listed in [Table 9–23](#).

Table 9–23 OracleNotificationEventArgs Static Method

| Static Method | Description |
|---------------|------------------------------|
| Equals | Inherited from System.Object |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)

OracleNotificationEventArgs Properties

OracleNotificationEventArgs properties are listed in [Table 9–24](#).

Table 9–24 OracleNotificationEventArgs Properties

| Properties | Description |
|-------------------------------|----------------------------------------------------------------------|
| Details | Contains detailed information about the current notification |
| Info | Indicates the database events for the notification |
| ResourceNames | Indicates the database resources related to the current notification |
| Source | Returns the database event source for the notification |
| Type | Returns the database event type for the notification |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)

Details

This property contains detailed information about the current notification.

Declaration

```
// C#
Public DataTable Details{get;}
```

Property Value

A `DataTable` instance that contains detailed information about the current notification.

Remarks

The returned `DataTable` object contains column data about the current notification in order as shown in [Table 9–25](#).

Table 9–25 DataTable Object Column Data

| Name | Type | Description |
|--------------|------------------------|---------------------------------------------------------------------------------------|
| ResourceName | System.String | The resource name of the invalidated object in the format <Schema_name>.<object_name> |
| Info | OracleNotificationInfo | The information about the database event that occurs on a resource |
| Rowid | System.String | The rowid for the invalidated table row |
| QueryId | Int32 | The CHANGE_NOTIFICATION_QUERY_ID |

The `QueryId` column contains the `CHANGE_NOTIFICATION_QUERY_ID` that corresponds to the pseudo-column that may have been retrieved by a `SELECT` statement at the time of

the query-based notification. Also, the `OracleDependency` object maintains all the `CHANGE_NOTIFICATION_QUERY_IDS` that are registered with it.

For Continuous Query Notification:

- The `Details` property indicates changes for each invalidated object in the notification in the data table.
- If `ROWID` information is requested, then the `ROWID` information is populated into the `Rowid` column. However, if many rows are modified in a table, then the whole table is invalidated, and `ROWID` information is not provided. Therefore, the `Rowid` column contains all `Null` values.
- If the database event is related to a DDL change of the table or a table drop, then the `Rowid` column is set to `Null`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)

Info

This property indicates the database events for the notification.

Declaration

```
// C#
public OracleNotificationInfo Info{get;}
```

Property Value

An `OracleNotificationInfo` value that indicates the database event for the notification.

Remarks

The `OracleNotificationInfo` value is an enumeration type. If several events are received from the invalidation message, the `Info` property is set to one of the `OracleNotificationInfo` enumeration values associated with the database events. For example, if a table has been altered and a new row has been inserted into another table, the `Info` property is set to either `OracleNotificationInfo.Altered` or `OracleNotificationInfo.Insert`.

To obtain more detailed information from the invalidation message, use the `Details` and the `ResourceNames` properties.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)
- ["Details"](#) on page 9-34
- ["ResourceNames"](#) on page 9-36
- ["OracleNotificationInfo Enumeration"](#) on page 9-44

ResourceNames

This property indicates the database resources related to the current notification.

Declaration

```
// C#  
public string[] ResourceNames{get;}
```

Property Value

A string array that indicates the database resources related to the current notification.

Remarks

For Continuous Query Notification, the `ResourceNames` property contains information about the invalidated object names in the format `<schema_name>.<object_name>`. To obtain more detailed information about the changes for invalidated objects, use the `Details` property.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)
- ["Details"](#) on page 9-34

Source

This property returns the database event source for the notification.

Declaration

```
// C#  
public OracleNotificationSource Source{get;}
```

Property Value

The `OracleNotificationSource` value for the notification.

Remarks

The `OracleNotificationSource` value is an enumeration type. If several event sources are received from the notification message, the `Source` property is set to one of the `OracleNotificationSource` enumeration values related to the database event source.

For example, if a table has been altered (by the `ALTER TABLE` command) and a new row has been inserted into the same table, the `Source` property is set to either `OracleNotificationSource.Object` or `OracleNotificationSource.Data`.

For Continuous Query Notification:

- When the `Source` property is set to `OracleNotificationSource.Data`:
 - The `Info` property is set to one of the following:
 - * `OracleNotificationInfo.Insert`
 - * `OracleNotificationInfo.Delete`
 - * `OracleNotificationInfo.Update`
 - The `ResourceNames` property is set, and the elements are set to the invalidated object names.
 - The `Details` property contains detailed information on the change of each invalidated table.
- When the `Source` property is set to `OracleNotificationSource.Database`:
 - The `Info` property is set to one of the following:
 - * `OracleNotificationInfo.Startup`
 - * `OracleNotificationInfo.Shutdown`
 - * `OracleNotificationInfo.Shutdown_Any`
 - * `OracleNotificationInfo.Dropped`
- When the `Source` property is set to `OracleNotificationSource.Object`:
 - The `Info` property is set to either `OracleNotificationInfo.Altered` or `OracleNotificationInfo.Dropped`.
 - The `ResourceNames` property is set, and the array elements of the `ResourceNames` property are set to the object names that have been altered or dropped.
 - The `Details` property contains detailed information on the changes of the object.
- When the `Source` property is set to `OracleNotificationSource.Subscription`:
 - The `Info` property is set to the following:
 - * `OracleNotificationInfo.End`

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)
- ["OracleNotificationSource Enumeration"](#) on page 9-43

Type

This property returns the database event type for the notification.

Declaration

```
// C#  
public OracleNotificationType Type{get;}
```

Property Value

An `OracleNotificationType` enumeration value that represents the type of the database event notification.

Remarks

The `OracleNotificationType` value is an enumeration type. If several event types are received from the notification message, then the `Type` property is set to one of the `OracleNotificationType` enumeration values related to the database event type.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)
- ["OracleNotificationType Enumeration"](#) on page 9-42

OracleNotificationEventArgs Methods

OracleNotificationEventArgs methods are listed in [Table 9–26](#).

Table 9–26 OracleNotificationEventArgs Methods

| Methods | Description |
|-------------|------------------------------|
| Equals | Inherited from System.Object |
| GetHashCode | Inherited from System.Object |
| GetType | Inherited from System.Object |
| ToString | Inherited from System.Object |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)

OnChangeEventHandler Delegate

The `OnChangeEventHandler` delegate represents the signature of the method that handles the notification.

Declaration

```
// C#  
public delegate void OnChangeEventHandler(object sender,  
    OracleNotificationEventArgs args);
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Not supported in a .NET stored procedure

Parameters

- *sender*
The source of the event.
- *args*
The `OracleNotificationEventArgs` instance that contains the event data.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleNotificationEventArgs Class](#)
- [OracleNotificationEventArgs Members](#)

OracleRowidInfo Enumeration

OracleRowidInfo enumeration values specify whether ROWID information is included as part of the ChangeNotificationEventArgs or not.

Table 9–28 lists all the OracleRowidInfoenumeration values with a description of each enumerated value.

Table 9–27 OracleRowidInfo Members

| Member Name | Description |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Default | ROWID information is included only if <code>OracleCommand.AddRowid</code> property is set to true or if ROWID column is explicitly included in the query. |
| Include | ROWID information is included regardless of whether ROWID is included in the select-list of the query or not. |
| Exclude | ROWID information is not included regardless of whether ROWID is included in the select-list of the query or not. |

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------------------|----------------------------------------------|
| Assembly | <code>Oracle.DataAccess.dll</code> | <code>Oracle.ManagedDataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Client</code> | <code>Oracle.ManagedDataAccess.Client</code> |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- ["RowidInfo"](#) on page 9-16

OracleNotificationType Enumeration

OracleNotificationType enumerated values specify the different types that cause the notification.

Table 9–28 lists all the OracleNotificationType enumeration values with a description of each enumerated value.

Table 9–28 OracleNotificationType Members

| Member Name | Description |
|-------------|---------------------------------------------|
| Change | A change occurs in the database. |
| Subscribe | A change occurs in the subscription. |
| Query | A query-based change occurs in the database |

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

See Also: ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5

OracleNotificationSource Enumeration

OracleNotificationSource enumerated values specify the different sources that cause notification.

[Table 9–29](#) lists all the OracleNotificationSource enumeration values with a description of each enumerated value.

Table 9–29 OracleNotificationSource Members

| Member Name | Description |
|--------------|-----------------------------------------------------------------|
| Data | The data in a table has changed. |
| Database | A database event such as a database startup or shutdown occurs. |
| Object | A database object is altered or dropped. |
| Subscription | The subscription is changed. |

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

See Also: ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5

OracleNotificationInfo Enumeration

OracleNotificationInfo enumerated values specify the database event that causes the notification.

Table 9–30 lists all the OracleNotificationInfo enumeration values with a description of each enumerated value.

Table 9–30 OracleNotificationInfo Members

| Member Name | Description |
|--------------|----------------------------------------------------------------------------------------|
| Insert | A row is inserted. |
| Delete | A row is deleted. |
| Update | A row is updated. |
| Startup | A database starts. |
| Shutdown | A database shuts down. |
| Shutdown_any | A database instance in a Real Application Cluster (Oracle RAC) environment shuts down. |
| Alter | An object is altered. |
| Drop | An object or database is dropped. |
| End | A registration is removed. |
| Error | A notification error occurs. |

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

See Also: ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5

10

Oracle Data Provider for .NET Globalization Classes

This chapter describes the ODP.NET globalization classes.

This chapter contains these topics:

- [OracleGlobalization Class](#)

OracleGlobalization Class

The OracleGlobalization class is used to obtain and set the Oracle globalization settings of the session, thread, and local computer (read-only).

Class Inheritance

System.Object

Oracle.DataAccess.Client.OracleGlobalization

Declaration

```
public sealed class OracleGlobalization : ICloneable, IDisposable
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|---------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Client | Oracle.ManagedDataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

An exception is thrown for invalid property values. All newly set property values are validated, except the `TimeZone` property.

Changing the OracleGlobalization object properties does not change the globalization settings of the session or the thread. Either the `SetSessionInfo` method of the OracleConnection object or the `SetThreadInfo` method of the OracleGlobalization object must be called to alter the session's and thread's globalization settings, respectively.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
  
class OracleGlobalizationSample  
{  
    static void Main()  
    {  
        // Get thread's globalization info  
        OracleGlobalization glob = OracleGlobalization.GetThreadInfo();  
  
        // Prints "glob.Language = AMERICAN"  
        Console.WriteLine("glob.Language = " + glob.Language);  
  
        // Set language on thread's globalization info  
        glob.Language = "FRENCH";  
        OracleGlobalization.SetThreadInfo(glob);  
    }  
}
```

```
OracleGlobalization.GetThreadInfo(glob);

// Prints "glob.Language = FRENCH"
Console.WriteLine("glob.Language = " + glob.Language);

glob.Dispose();
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Members](#)
- [OracleGlobalization Static Methods](#)
- [OracleGlobalization Properties](#)
- [OracleGlobalization Public Methods](#)
- *Oracle Database SQL Language Reference*
- *Oracle Database Globalization Support Guide*

OracleGlobalization Members

OracleGlobalization members are listed in the following tables.

OracleGlobalization Static Methods

The OracleGlobalization static methods are listed in [Table 10-1](#).

Table 10-1 OracleGlobalization Static Methods

| Name | Description |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| GetClientInfo | Returns an OracleGlobalization object that represents the Oracle globalization settings of the local computer (Overloaded) <i>Not Available in ODP.NET, Managed Driver</i> |
| GetThreadInfo | Returns or refreshes an OracleGlobalization instance that represents Oracle globalization settings of the current thread (Overloaded) <i>Not Available in ODP.NET, Managed Driver</i> |
| SetThreadInfo | Sets Oracle globalization parameters to the current thread <i>Not Available in ODP.NET, Managed Driver</i> |

OracleGlobalization Properties

The OracleGlobalization properties are listed in [Table 10-2](#).

Table 10-2 OracleGlobalization Properties

| Name | Description |
|------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Calendar | Specifies the calendar system |
| ClientCharacterSet | Specifies a client character set <i>Not Available in ODP.NET, Managed Driver</i> |
| Comparison | Specifies a method of comparison for WHERE clauses and comparison in PL/SQL blocks |
| Currency | Specifies the string to use as a local currency symbol for the L number format element |
| DateFormat | Specifies the date format for Oracle Date type as a string |
| DateLanguage | Specifies the language used to spell day and month names and date abbreviations |
| DualCurrency | Specifies the dual currency symbol, such as <i>Euro</i> , for the U number format element |
| ISOCurrency | Specifies the string to use as an international currency symbol for the C number format element |
| Language | Specifies the default language of the database |
| LengthSemantics | Enables creation of CHAR and VARCHAR2 columns using either byte or character (default) length semantics |
| NCharConversionException | Determines whether or not data loss during an implicit or explicit character type conversion reports an error |
| NumericCharacters | Specifies the characters used for the decimal character and the group separator character for numeric values in strings |
| Sort | Specifies the collating sequence for ORDER BY clause |

Table 10–2 (Cont.) OracleGlobalization Properties

| Name | Description |
|-----------------------------------|---------------------------------------------------|
| Territory | Specifies the name of the territory |
| TimeStampFormat | Specifies the string format for TimeStamp types |
| TimeStampTZFormat | Specifies the string format for TimeStampTZ types |
| TimeZone | Specifies the time zone region name |

OracleGlobalization Public Methods

OracleGlobalization public methods are listed in [Table 10–3](#).

Table 10–3 OracleGlobalization Public Methods

| Public Method | Description |
|-------------------------|----------------------------------------------------------|
| Clone | Creates a copy of an OracleGlobalization object |
| Dispose | Releases any resources or memory allocated by the object |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

OracleGlobalization Static Methods

The OracleGlobalization static methods are listed in [Table 10–4](#).

Table 10–4 OracleGlobalization Static Methods

| Name | Description |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| GetClientInfo | Returns an OracleGlobalization object that represents the Oracle globalization settings of the local computer (Overloaded) <i>Not Available in ODP.NET, Managed Driver</i> |
| GetThreadInfo | Returns or refreshes an OracleGlobalization instance that represents Oracle globalization settings of the current thread (Overloaded) <i>Not Available in ODP.NET, Managed Driver</i> |
| SetThreadInfo | Sets Oracle globalization parameters to the current thread <i>Not Available in ODP.NET, Managed Driver</i> |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

GetClientInfo

GetClientInfo returns an OracleGlobalization object instance that represents the Oracle globalization settings of the local computer.

Overload List:

- [GetClientInfo\(\)](#)
This method returns an OracleGlobalization instance that represents the globalization settings of the local computer.
- [GetClientInfo\(OracleGlobalization\)](#)
This method refreshes the provided OracleGlobalization object with the globalization settings of the local computer.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

GetClientInfo()

This method returns an OracleGlobalization instance that represents the globalization settings of the local computer.

Declaration

```
// C#
```

```
public static OracleGlobalization GetClientInfo();
```

Return Value

An OracleGlobalization instance.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;

class GetClientInfoSample
{
    static void Main()
    {
        // Get client's globalization info
        OracleGlobalization glob = OracleGlobalization.GetClientInfo();

        // Prints "glob.Language = AMERICAN"
        Console.WriteLine("glob.Language = " + glob.Language);

        glob.Dispose();
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

GetClientInfo(OracleGlobalization)

This method refreshes the provided OracleGlobalization object with the globalization settings of the local computer.

Declaration

```
// C#
public static void GetClientInfo(OracleGlobalization oraGlob);
```

Parameters

- *oraGlob*

The OracleGlobalization object being updated.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;

class GetClientInfoSample
{
    static void Main()
    {
        // Get client's globalization info
```

```
OracleGlobalization glob = OracleGlobalization.GetClientInfo();

// Prints "glob.Language = AMERICAN"
Console.WriteLine("glob.Language = " + glob.Language);

// Get client's globalization info using overload
OracleGlobalization.GetClientInfo(glob);

// Prints "glob.Language = AMERICAN"
Console.WriteLine("glob.Language = " + glob.Language);

glob.Dispose();
}
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

GetThreadInfo

GetThreadInfo returns or refreshes an OracleGlobalization instance.

Overload List:

- [GetThreadInfo\(\)](#)
This method returns an OracleGlobalization object instance of the current thread.
- [GetThreadInfo\(OracleGlobalization\)](#)
This method refreshes the OracleGlobalization object instance with the globalization settings of the current thread.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

GetThreadInfo()

This method returns an OracleGlobalization instance of the current thread.

Declaration

```
// C#
public static OracleGlobalization GetThreadInfo();
```

Return Value

An OracleGlobalization instance.

Remarks

Initially, `GetThreadInfo()` returns an `OracleGlobalization` object that has the same property values as that returned by `GetClientInfo()`, unless the application changes it by invoking `SetThreadInfo()`.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;

class GetThreadInfoSample
{
    static void Main()
    {
        // Get thread's globalization info
        OracleGlobalization glob = OracleGlobalization.GetThreadInfo();

        // Prints "glob.Language = AMERICAN"
        Console.WriteLine("glob.Language = " + glob.Language);

        // Get thread's globalization info using overloaded
        OracleGlobalization.GetThreadInfo(glob);

        // Prints "glob.Language = AMERICAN"
        Console.WriteLine("glob.Language = " + glob.Language);

        glob.Dispose();
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

GetThreadInfo(OracleGlobalization)

This method refreshes the `OracleGlobalization` object with the globalization settings of the current thread.

Declaration

```
// C#
public static void GetThreadInfo(OracleGlobalization oraGlob);
```

Parameters

- *oraGlob*
The `OracleGlobalization` object being updated.

Remarks

Initially `GetThreadInfo()` returns an `OracleGlobalization` object that has the same property values as that returned by `GetClientInfo()`, unless the application changes it by invoking `SetThreadInfo()`.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;

class GetThreadInfoSample
{
    static void Main()
    {
        // Get thread's globalization info
        OracleGlobalization glob = OracleGlobalization.GetThreadInfo();

        // Prints "glob.Language = AMERICAN"
        Console.WriteLine("glob.Language = " + glob.Language);

        // Get thread's globalization info using overloaded
        OracleGlobalization.GetThreadInfo(glob);

        // Prints "glob.Language = AMERICAN"
        Console.WriteLine("glob.Language = " + glob.Language);

        glob.Dispose();
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

SetThreadInfo

This method sets Oracle globalization parameters to the current thread.

Declaration

```
// C#
public static void SetThreadInfo(OracleGlobalization oraGlob);
```

Parameters

- *oraGlob*
An OracleGlobalization object.

Remarks

Any .NET string conversions to and from ODP.NET Types, as well as ODP.NET Type constructors, use the globalization property values where applicable. For example, when constructing an OracleDate structure from a .NET string, that string is expected to be in the format specified by the OracleGlobalization.DateFormat property of the thread.

Example

```
// C#

using System;
```

```
using Oracle.DataAccess.Client;

class SetThreadInfoSample
{
    static void Main()
    {
        // Get thread's globalization info
        OracleGlobalization glob1 = OracleGlobalization.GetThreadInfo();

        // Prints "glob1.Language = AMERICAN"
        Console.WriteLine("glob1.Language = " + glob1.Language);

        // Set language on thread's globalization info
        glob1.Language = "FRENCH";
        OracleGlobalization.SetThreadInfo(glob1);
        OracleGlobalization glob2 = OracleGlobalization.GetThreadInfo();

        // Prints "glob2.Language = FRENCH"
        Console.WriteLine("glob2.Language = " + glob2.Language);

        glob1.Dispose();
        glob2.Dispose();
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

OracleGlobalization Properties

The OracleGlobalization properties are listed in [Table 10-5](#).

Table 10-5 OracleGlobalization Properties

| Name | Description |
|------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Calendar | Specifies the calendar system |
| ClientCharacterSet | Specifies a client character set <i>Not Available in ODP.NET, Managed Driver</i> |
| Comparison | Specifies a method of comparison for WHERE clauses and comparison in PL/SQL blocks |
| Currency | Specifies the string to use as a local currency symbol for the L number format element |
| DateFormat | Specifies the date format for Oracle Date type as a string |
| DateLanguage | Specifies the language used to spell day and month names and date abbreviations |
| DualCurrency | Specifies the dual currency symbol, such as <i>Euro</i> , for the U number format element |
| ISOCurrency | Specifies the string to use as an international currency symbol for the C number format element |
| Language | Specifies the default language of the database |
| LengthSemantics | Enables creation of CHAR and VARCHAR2 columns using either byte or character (default) length semantics |
| NCharConversionException | Determines whether or not data loss during an implicit or explicit character type conversion reports an error |
| NumericCharacters | Specifies the characters used for the decimal character and the group separator character for numeric values in strings |
| Sort | Specifies the collating sequence for ORDER by clause |
| Territory | Specifies the name of the territory |
| TimeStampFormat | Specifies the string format for TimeStamp types |
| TimeStampTZFormat | Specifies the string format for TimeStampTZ types |
| TimeZone | Specifies the time zone region name |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

Calendar

This property specifies the calendar system.

Declaration

```
// C#
```

```
public string Calendar {get; set;}
```

Property Value

A string representing the Calendar.

Exceptions

ObjectDisposedException - The object is already disposed.

Remarks

The default value is the NLS_CALENDAR setting of the local computer. This value is the same regardless of whether or not the OracleGlobalization object represents the settings of the client, thread, or session.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

ClientCharacterSet

This property specifies a client character set.

Declaration

```
// C#
public string ClientCharacterSet {get;}
```

Property Value

A string that the provides the name of the character set of the local computer.

Remarks

The default value is the character set of the local computer.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

Comparison

This property represents a method of comparison for WHERE clauses and comparison in PL/SQL blocks.

Declaration

```
// C#
public string Comparison {get; set;}
```

Property Value

A string that provides the name of the method of comparison.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The default value is the `NLS_COMP` setting of the local computer.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

Currency

This property specifies the string to use as a local currency symbol for the L number format element.

Declaration

```
// C#  
public string Currency {get; set;}
```

Property Value

The string to use as a local currency symbol for the L number format element.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The default value is the `NLS_CURRENCY` setting of the local computer.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)
- *Oracle Database SQL Language Reference* for further information on the L number format element

DateFormat

This property specifies the date format for Oracle Date type as a string.

Declaration

```
// C#  
public string DateFormat {get; set;}
```

Property Value

The date format for Oracle Date type as a string

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The default value is the `NLS_DATE_FORMAT` setting of the local computer.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

DateLanguage

This property specifies the language used to spell names of days and months, and date abbreviations (for example: a.m., p.m., AD, BC).

Declaration

```
// C#  
public string DateLanguage {get; set;}
```

Property Value

A string specifying the language.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The default value is the `NLS_DATE_LANGUAGE` setting of the local computer.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

DualCurrency

This property specifies the dual currency symbol, such as *Euro*, for the U number format element.

Declaration

```
// C#  
public string DualCurrency {get; set;}
```

Property Value

A string that provides the dual currency symbol.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The default value is the `NLS_DUAL_CURRENCY` setting of the local computer.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)
- *Oracle Database SQL Language Reference* for further information on the U number format element

ISOCurrency

This property specifies the string to use as an international currency symbol for the C number format element.

Declaration

```
// C#  
public string ISOCurrency {get; set;}
```

Property Value

The string used as an international currency symbol.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The default value is the `NLS_ISO_CURRENCY` setting of the local computer.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)
- *Oracle Database SQL Language Reference* for further information on the C number format element

Language

This property specifies the default language of the database.

Declaration

```
// C#  
public string Language {get; set;}
```

Property Value

The default language of the database.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The default value is the NLS_LANGUAGE setting of the local computer.

Language is used for messages, day and month names, and sorting algorithms. It also determines NLS_DATE_LANGUAGE and NLS_SORT parameter values.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

LengthSemantics

This property indicates whether or not CHAR and VARCHAR2 columns use byte or character (default) length semantics.

Declaration

```
// C#  
public string LengthSemantics {get; set;}
```

Property Value

A string that indicates either byte or character length semantics.

Exceptions

ObjectDisposedException - The object is already disposed.

Remarks

The default value is the NLS_LENGTH_SEMANTICS setting of the local computer.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

NCharConversionException

This property determines whether or not data loss during an implicit or explicit character type conversion reports an error.

Declaration

```
// C#  
public bool NCharConversionException {get; set;}
```

Property Value

A string that indicates whether or not a character type conversion causes an error message.

Exceptions

ObjectDisposedException - The object is already disposed.

Remarks

The default value of `NLS_NCHAR_CONV_EXCP` is `False`, unless it is overridden by a setting in the `INIT.ORA` file.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

NumericCharacters

This property specifies the characters used for the decimal character and the group separator character for numeric values in strings.

Declaration

```
// C#  
public string NumericCharacters {get; set;}
```

Property Value

A string that represents the characters used.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The default value is the `NLS_NUMERIC_CHARACTERS` setting of the local computer.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

Sort

This property specifies the collating sequence for `ORDER BY` clause.

Declaration

```
// C#  
public string Sort {get; set;}
```

Property Value

A string that indicates the collating sequence.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The default value is the `NLS_SORT` setting of the local computer.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

Territory

This property specifies the name of the territory.

Declaration

```
// C#  
public string Territory {get; set;}
```

Property Value

A string that provides the name of the territory.

Exceptions

ObjectDisposedException - The object is already disposed.

Remarks

The default value is the NLS_TERRITORY setting of the local computer.

Changing this property changes other globalization properties.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)
- *Oracle Database Globalization Support Guide.*

TimeStampFormat

This property specifies the string format for TimeStamp types.

Declaration

```
// C#  
public string TimeStampFormat {get; set;}
```

Property Value

The string format for TimeStamp types.

Exceptions

ObjectDisposedException - The object is already disposed.

Remarks

The default value is the NLS_TIMESTAMP_FORMAT setting of the local computer.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

TimeStampTZFormat

This property specifies the string format for TimeStampTZ types.

Declaration

```
// C#  
public string TimeStampTZFormat {get; set;}
```

Property Value

The string format for TimeStampTZ types.

Exceptions

ObjectDisposedException - The object is already disposed.

Remarks

The default value is the NLS_TIMESTAMP_TZ_FORMAT setting of the local computer.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

TimeZone

This property specifies the time zone region name or hour offset.

Declaration

```
// C#  
public string TimeZone {get; set;}
```

Property Value

The string represents the time zone region name or the time zone offset.

Exceptions

ObjectDisposedException - The object is already disposed.

Remarks

The default value is the time zone region name of the local computer

TimeZone is only used when the thread constructs one of the TimeStamp structures. TimeZone has no effect on the session.

TimeZone can be either an hour offset, for example, 7:00, or a valid time zone region name that is provided in V\$TIMEZONE_NAMES, such as US/Pacific. Time zone abbreviations are not supported.

Note: PST is a time zone region name as well as a time zone abbreviation; therefore it is accepted by OracleGlobalization.

This property returns an empty string if the OracleGlobalization object is obtained using `GetSessionInfo()` or `GetSessionInfo(OracleGlobalization)`. Initially, by default, the time zone of the session is identical to the time zone of the thread. Therefore, given that the session time zone is not changed by invoking `ALTER SESSION` calls, the session time zone can be fetched from the client's globalization settings.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

OracleGlobalization Public Methods

OracleGlobalization public methods are listed in [Table 10–6](#).

Table 10–6 OracleGlobalization Public Methods

| Public Method | Description |
|-------------------------|----------------------------------------------------------|
| Clone | Creates a copy of an OracleGlobalization object |
| Dispose | Releases any resources or memory allocated by the object |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

Clone

This method creates a copy of an OracleGlobalization object.

Declaration

```
// C#  
public object Clone();
```

Return Value

An OracleGlobalization object.

Implements

ICloneable

Remarks

The cloned object has the same property values as that of the object being cloned.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

Dispose

This method releases any resources or memory allocated by the object.

Declaration

```
// C#  
public void Dispose();
```

Implements

IDisposable

Remarks

The `Dispose` method also closes the `OracleGlobalization` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleGlobalization Class](#)
- [OracleGlobalization Members](#)

Oracle Data Provider for .NET Failover Classes

This chapter describes the ODP.NET failover classes and enumerations.

This chapter contains these topics:

- [OracleFailoverEventArgs Class](#)
- [OracleFailoverEventHandler Delegate](#)
- [FailoverEvent Enumeration](#)
- [FailoverReturnCode Enumeration](#)
- [FailoverType Enumeration](#)

OracleFailoverEventArgs Class

The `OracleFailoverEventArgs` class provides event data for the `OracleConnection.Failover` event. When database failover occurs, the `OracleConnection.Failover` event is triggered along with the `OracleFailoverEventArgs` object that stores the event data.

Class Inheritance

`System.Object`

`System.EventArgs`

`Oracle.DataAccess.Client.OracleFailoverEventArgs`

Declaration

```
// C#
public sealed class OracleFailoverEventArgs
```

Requirements

| | |
|-----------------------|---------------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | <code>Oracle.DataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Client</code> |
| .NET Framework | 3.5, 4.0, 4.5 |

Not supported in a .NET stored procedure

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example (Oracle.DataAccess.Client only)

```
// Transparent Application Failover (TAF) Setup
// Refer Oracle® Database Net Services Administrator's Guide

// C#

using System;
using System.Threading;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class FailoverSample
{
    static void Main(string[] args)
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        // Register the event handler OnFailover
        con.Failover += new OracleFailoverEventHandler(OnFailover);
    }
}
```

```
        Console.WriteLine("Wait for a failover for 5 seconds");
        Thread.Sleep(5000);

        con.Close();
        con.Dispose();
    }

    // TAF callback function
    static FailoverReturnCode OnFailover(object sender,
        OracleFailoverEventArgs eventArgs)
    {
        switch (eventArgs.FailoverEvent)
        {
            case FailoverEvent.Begin:
            {
                Console.WriteLine("FailoverEvent.Begin - Failover is starting");
                Console.WriteLine("FailoverType = " + eventArgs.FailoverType);
                break;
            }
            case FailoverEvent.End:
            {
                Console.WriteLine("FailoverEvent.End - Failover was successful");
                break;
            }
            case FailoverEvent.Reauth:
            {
                Console.WriteLine("FailoverEvent.Reauth - User reauthenticated");
                break;
            }
            case FailoverEvent.Error:
            {
                Console.WriteLine("FailoverEvent.Error - Failover was unsuccessful");

                // Sleep for 3 sec and Retry
                Thread.Sleep(3000);
                return FailoverReturnCode.Retry;
            }
            case FailoverEvent.Abort:
            {
                Console.WriteLine("FailoverEvent.Abort - Failover was unsuccessful");
                break;
            }
            default:
            {
                Console.WriteLine("Invalid FailoverEvent : " + eventArgs.FailoverEvent);
                break;
            }
        }
        return FailoverReturnCode.Success;
    }
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleFailoverEventArgs Members](#)
- [OracleFailoverEventArgs Static Methods](#)
- [OracleFailoverEventArgs Properties](#)
- [OracleFailoverEventArgs Public Methods](#)
- ["OracleConnection Class"](#) on page 6-79
- *Oracle Database Net Services Administrator's Guide*

OracleFailoverEventArgs Members

OracleFailoverEventArgs members are listed in the following tables.

OracleFailoverEventArgs Static Methods

The OracleFailoverEventArgs static methods are listed in [Table 11-1](#).

Table 11-1 OracleFailoverEventArgs Static Methods

| Methods | Description |
|---------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

OracleFailoverEventArgs Properties

The OracleFailoverEventArgs properties are listed in [Table 11-2](#).

Table 11-2 OracleFailoverEventArgs Properties

| Name | Description |
|-------------------------------|---------------------------------------------------------|
| FailoverType | Specifies the type of failover the client has requested |
| FailoverEvent | Indicates the state of the failover |

OracleFailoverEventArgs Public Methods

The OracleFailoverEventArgs public methods are listed in [Table 11-3](#).

Table 11-3 OracleFailoverEventArgs Public Methods

| Name | Description |
|-------------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |
| GetHashCode | Inherited from System.Object |
| GetType | Inherited from System.Object |
| ToString | Inherited from System.Object |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleFailoverEventArgs Class](#)
- ["FailoverType Enumeration"](#) on page 11-13

OracleFailoverEventArgs Static Methods

The `OracleFailoverEventArgs` static methods are listed in [Table 11-1](#).

Table 11-4 *OracleFailoverEventArgs Static Methods*

| Methods | Description |
|---------------------|--------------------------------------------------------|
| <code>Equals</code> | Inherited from <code>System.Object</code> (Overloaded) |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleFailoverEventArgs Class](#)
- [OracleFailoverEventArgs Members](#)

OracleFailoverEventArgs Properties

The OracleFailoverEventArgs properties are listed in [Table 11-5](#).

Table 11-5 OracleFailoverEventArgs Properties

| Name | Description |
|-------------------------------|---------------------------------------------------------|
| FailoverType | Specifies the type of failover the client has requested |
| FailoverEvent | Indicates the state of the failover |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleFailoverEventArgs Class](#)
- [OracleFailoverEventArgs Members](#)

FailoverType

This property indicates the state of the failover.

Declaration

```
// C#
public FailoverType FailoverType {get;}
```

Property Value

A FailoverType enumeration value.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleFailoverEventArgs Class](#)
- [OracleFailoverEventArgs Members](#)
- ["FailoverType Enumeration"](#) on page 11-13

FailoverEvent

This property indicates the state of the failover.

Declaration

```
// C#
public FailoverEvent FailoverEvent {get;}
```

Property Value

A FailoverEvent enumerated value.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleFailoverEventArgs Class](#)
- [OracleFailoverEventArgs Members](#)
- ["FailoverEvent Enumeration"](#) on page 11-11

OracleFailoverEventArgs Public Methods

The OracleFailoverEventArgs public methods are listed in [Table 11–6](#).

Table 11–6 OracleFailoverEventArgs Public Methods

| Name | Description |
|-------------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |
| GetHashCode | Inherited from System.Object |
| GetType | Inherited from System.Object |
| ToString | Inherited from System.Object |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleFailoverEventArgs Class](#)
- [OracleFailoverEventArgs Members](#)

OracleFailoverEventHandler Delegate

The `OracleFailoverEventHandler` represents the signature of the method that handles the `OracleConnection.Failover` event.

Declaration

```
// C#  
public delegate FailoverReturnCode OracleFailoverEventHandler(object sender,  
    OracleFailoverEventArgs eventArgs);
```

Requirements

| | |
|-----------------------|----------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | Oracle.DataAccess.dll |
| Namespace | Oracle.DataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 |

Not supported in a .NET stored procedure

Parameter

- `sender`
The source of the event.
- `eventArgs`
The `OracleFailoverEventArgs` object that contains the event data.

Return Type

An `int`.

Remarks

To receive failover notifications, a callback function can be registered as follows:

```
ConObj.Failover += new OracleFailoverEventHandler(OnFailover);
```

The definition of the callback function `OnFailover` can be as follows:

```
public FailoverReturnCode OnFailover(object sender, OracleFailoverEventArgs  
eventArgs)
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleFailoverEventArgs Class](#)
- [OracleFailoverEventArgs Members](#)
- ["Failover"](#) on page 6-130

FailoverEvent Enumeration

FailoverEvent enumerated values are used to specify the state of the failover.

[Table 11-7](#) lists all the FailoverEvent enumeration values with a description of each enumerated value.

Table 11-7 FailoverEvent Enumeration Values

| Member Names | Description |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| FailoverEvent.Begin | Indicates that failover has detected a lost connection and that failover is starting. |
| FailoverEvent.End | Indicates successful completion of failover. |
| FailoverEvent.Abort | Indicates that failover was unsuccessful, and there is no option of retrying. |
| FailoverEvent.Error | Indicates that failover was unsuccessful, and it gives the application the opportunity to handle the error and retry failover. The application can retry failover by returning <code>FailoverReturnCode.Retry</code> for the event notification. |
| FailoverEvent.Reauth | Indicates that a user handle has been reauthenticated. This applies to the situation where a client has multiple user sessions on a single server connection. During the initial failover, only the active user session is failed over. Other sessions are failed over when the application tries to use them. This is the value passed to the callback during these subsequent failovers. |

Requirements

| | |
|----------------|---------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | Oracle.DataAccess.dll |
| Namespace | Oracle.DataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 |

See Also:

- [FailoverEvent Enumeration](#) on page 11-11
- ["OracleFailoverEventArgs Class"](#) on page 11-2
- ["FailoverEvent"](#) on page 11-7
- *Oracle Real Application Clusters Administration and Deployment Guide*
- *Oracle Database Net Services Reference*

FailoverReturnCode Enumeration

FailoverReturnCode enumerated values are passed back by the application to the ODP.NET provider to request a retry in case of a failover error, or to continue in case of a successful failover.

[Table 11-8](#) lists the FailoverReturnCode enumeration values with a description of each enumerated value.

Table 11-8 FailoverReturnCode Enumeration Values

| Member Names | Description |
|----------------------------|---------------------------------------------------------------------------------------------|
| FailoverReturnCode.Retry | Requests ODP.NET to retry failover in case FailoverEvent.Error is passed to the application |
| FailoverReturnCode.Success | Requests ODP.NET to proceed so that the application receive more notifications, if any |

Requirements

| | |
|----------------|---------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | Oracle.DataAccess.dll |
| Namespace | Oracle.DataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 |

See Also:

- [FailoverEvent Enumeration](#) on page 11-11
- ["OracleFailoverEventArgs Class"](#) on page 11-2
- ["FailoverEvent"](#) on page 11-7
- *Oracle Real Application Clusters Administration and Deployment Guide*
- *Oracle Database Net Services Reference*

FailoverType Enumeration

FailoverType enumerated values are used to indicate the type of failover event that was raised.

[Table 11–9](#) lists all the FailoverType enumeration values with a description of each enumerated value.

Table 11–9 FailoverType Enumeration Values

| Member Names | Description |
|----------------------|--------------------------------------------------------------------|
| FailoverType.Session | Indicates that the user has requested only session failover. |
| FailoverType.Select | Indicates that the user has requested select and session failover. |

Requirements

| | |
|----------------|---------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | Oracle.DataAccess.dll |
| Namespace | Oracle.DataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 |

See Also:

- [FailoverEvent Enumeration](#) on page 11-11
- ["OracleFailoverEventArgs Class"](#) on page 11-2
- ["FailoverType"](#) on page 11-7
- *Oracle Real Application Clusters Administration and Deployment Guide*
- *Oracle Database Net Services Reference*

Oracle Database Advanced Queuing Classes

This chapter describes the following Oracle Data Provider for .NET classes:

- [OracleAQAgent Class](#)
- [OracleAQDequeueOptions Class](#)
- [OracleAQEnqueueOptions Class](#)
- [OracleAQMessage Class](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventHandler Delegate](#)
- [OracleAQQueue Class](#)
- [OracleAQDequeueMode Enumeration](#)
- [OracleAQMessageDeliveryMode Enumeration](#)
- [OracleAQMessageState Enumeration](#)
- [OracleAQMessageType Enumeration](#)
- [OracleAQNavigationMode Enumeration](#)
- [OracleAQNotificationGroupingType Enumeration](#)
- [OracleAQNotificationType Enumeration](#)
- [OracleAQVisibilityMode Enumeration](#)

OracleAQAgent Class

The OracleAQAgent class represents agents that may be senders or recipients of a message.

Class Inheritance

System.Object

OracleAQAgent

Declaration

```
// C#  
public sealed class OracleAQAgent
```

Requirements

| | |
|-----------------------|----------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | Oracle.DataAccess.dll |
| Namespace | Oracle.DataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

An agent may be a consumer, another queue, or a consumer of another queue. The queue may be either local or remote. A remote queue is specified through a database link.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleAQAgent Members](#)
- [OracleAQAgent Constructors](#)
- [OracleAQAgent Properties](#)

OracleAQAgent Members

OracleAQAgent members are listed in the following tables.

OracleAQAgent Constructors

OracleAQAgent constructors are listed in [Table 12-1](#).

Table 12-1 OracleAQAgent Constructors

| Constructor | Description |
|--------------------------------------------|----------------------------------------------------------------------|
| OracleAQAgent Constructors | Instantiates a new instance of the OracleAQAgent class (Overloaded). |

OracleAQAgent Properties

OracleAQAgent properties are listed in [Table 12-2](#).

Table 12-2 OracleAQAgent Properties

| Property | Description |
|-------------------------|-------------------------------------|
| Address | Specifies the address of the agent. |
| Name | Specifies the name of the agent. |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQAgent Class](#)

OracleAQAgent Constructors

OracleAQAgent constructors instantiate new instances of the OracleAQAgent class.

Overload List:

- [OracleAQAgent \(string\)](#)
This constructor instantiates the OracleAQAgent class using the specified name.
- [OracleAQAgent \(string, string\)](#)
This constructor instantiates the OracleAQAgent class using the specified name and address.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQAgent Class](#)
- [OracleAQAgent Members](#)

OracleAQAgent (string)

This constructor instantiates the OracleAQAgent class using the specified name.

Declaration

```
// C#  
public OracleAQAgent(string name);
```

Parameters

- *name*
The name of the agent.

Exceptions

ArgumentNullException - The *name* parameter is null.

ArgumentException - The *name* parameter is empty.

Remarks

The agent name signifies the name of a producer or consumer of a message. In the context of functionality exposed by `Listen`, an agent name corresponds to the name of a consumer for which a message is expected on a multiconsumer queue. It may also be set on a message to signify sender identification or intended recipients of the message.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQAgent Class](#)
- [OracleAQAgent Members](#)

OracleAQAgent (string, string)

This constructor instantiates the OracleAQAgent class using the specified name and address.

Declaration

```
// C#  
public OracleAQAgent(string name, string address);
```

Parameters

- *name*
The name of the agent.
- *address*
The address is of the form [*schema.*]queue[@*dblink*].

Exceptions

ArgumentNullException - The *address* parameter is null.

ArgumentException - The *address* parameter is empty.

Remarks

The agent name signifies the name of a producer or consumer of a message. In the context of functionality exposed by `Listen`, an agent name corresponds to the name of a consumer for which a message is expected on a multiconsumer queue.

The *name* parameter can be specified as `null` in this constructor. In such a scenario, the agent only has an *address*.

The *address* parameter signifies the name of the queue against which this agent listens for new messages. The *address* represents a queue at a local or remote database. The validity of the *address* is not checked implicitly. The exceptions due to wrong *address* are thrown only during database operations such as `Listen`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQAgent Class](#)
- [OracleAQAgent Members](#)

OracleAQAgent Properties

OracleAQAgent properties are listed in [Table 12-3](#).

Table 12-3 OracleAQAgent Properties

| Property | Description |
|-------------------------|-------------------------------------|
| Address | Specifies the address of the agent. |
| Name | Specifies the name of the agent. |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQAgent Class](#)
- [OracleAQAgent Members](#)

Address

This instance property specifies the address of the agent.

Declaration

```
// C#  
public string Address {get; }
```

Property Value

A string that specifies the agent address.

Remarks

The address represents a queue at a local or remote database. The default value is null. The address of the agent is of the form [*schema.*]*queue*[*@dblink*]. The string length can be up to 128 characters.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQAgent Class](#)
- [OracleAQAgent Members](#)

Name

This instance property specifies the name of the agent.

Declaration

```
// C#  
public string Name {get; }
```

Property Value

A string.

Remarks

The default is `null`. The string length can be up to 30 characters. A non-`null` value implies that this agent name either corresponds to a consumer name in a multiconsumer queue, or a recipient as specified in message properties.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQAgent Class](#)
- [OracleAQAgent Members](#)

OracleAQDequeueOptions Class

An OracleAQDequeueOptions object represents the options available when dequeuing a message from an OracleAQQueue object.

Class Inheritance

System.Object

OracleAQDequeueOptions

Declaration

```
// C#  
public sealed class OracleAQDequeueOptions : ICloneable
```

Requirements

| | |
|-----------------------|----------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | Oracle.DataAccess.dll |
| Namespace | Oracle.DataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleAQDequeueOptions Members](#)
- [OracleAQDequeueOptions Constructor](#)
- [OracleAQDequeueOptions Properties](#)
- [OracleAQDequeueOptions Public Methods](#)

OracleAQDequeueOptions Members

OracleAQDequeueOptions members are listed in the following tables.

OracleAQDequeueOptions Constructor

The OracleAQDequeueOptions constructor is listed in [Table 12–4](#).

Table 12–4 OracleAQDequeueOptions Constructor

| Constructor | Description |
|----------------------------------------------------|-----------------------------------------------------------------|
| OracleAQDequeueOptions Constructor | Instantiates a new instance of the OracleAQDequeueOptions class |

OracleAQDequeueOptions Properties

OracleAQDequeueOptions properties are listed in [Table 12–5](#).

Table 12–5 OracleAQDequeueOptions Properties

| Property | Description |
|--------------------------------------|------------------------------------------------------------------------------------------------------------|
| ConsumerName | Specifies the consumer name for which to dequeue the message |
| Correlation | Specifies the correlation identifier of the message to be dequeued |
| DeliveryMode | Specifies the expected delivery mode of the message being dequeued |
| DequeueMode | Specifies the locking behavior associated with the dequeue operation |
| MessageId | Specifies the message identifier of the message to be dequeued |
| NavigationMode | Specifies the position of the message that will be retrieved |
| ProviderSpecificType | Specifies whether the payload of a dequeued message is provided as an ODP.NET specific type or a .NET type |
| Visibility | Specifies whether or not the new message is dequeued as part of the current transaction |
| Wait | Specifies the wait time, in seconds, for a message that matches the search criteria |

OracleAQDequeueOptions Public Methods

OracleAQDequeueOptions public methods are listed in [Table 12–6](#).

Table 12–6 OracleAQDequeueOptions Public Methods

| Public Method | Description |
|-----------------------|-----------------------------------------------------|
| Clone | Creates a copy of an OracleAQDequeueOptions object. |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQDequeueOptions Class](#)

OracleAQDequeueOptions Constructor

The `OracleAQDequeueOptions` constructor creates an instance of the `OracleAQDequeueOptions` class and sets all its properties to their default values.

Declaration

```
// C#  
public OracleAQDequeueOptions();
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

OracleAQDequeueOptions Properties

OracleAQDequeueOptions properties are listed in [Table 12-7](#).

Table 12-7 OracleAQDequeueOptions Properties

| Property | Description |
|--------------------------------------|------------------------------------------------------------------------------------------------------------|
| ConsumerName | Specifies the consumer name for which to dequeue the message |
| Correlation | Specifies the correlation identifier of the message to be dequeued |
| DeliveryMode | Specifies the expected delivery mode of the message being dequeued |
| DequeueMode | Specifies the locking behavior associated with the dequeue operation |
| MessageId | Specifies the message identifier of the message to be dequeued |
| NavigationMode | Specifies the position of the message that will be retrieved |
| ProviderSpecificType | Specifies whether the payload of a dequeued message is provided as an ODP.NET specific type or a .NET type |
| Visibility | Specifies whether or not the new message is dequeued as part of the current transaction |
| Wait | Specifies the wait time, in seconds, for a message that matches the search criteria |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

ConsumerName

This instance property specifies the consumer name for which to dequeue the message.

Declaration

```
// C#
public string ConsumerName {get;set;}
```

Property Value

A string.

Remarks

The `ConsumerName` property only accesses those messages that match the consumer name. If a queue is not set up for multiple consumers, then this field should be set to null.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

Correlation

This instance property specifies the correlation identifier of the message to be dequeued.

Declaration

```
// C#
public string Correlation {get;set;}
```

Property Value

A string.

Remarks

This property specifies the identification of the message to be dequeued. Special pattern matching characters, such as the percent sign (%) and the underscore (_) can be used. If more than one message satisfies the pattern, then the order of dequeuing is undetermined.

The maximum length of Correlation is 128.

MessageId and Correlation are two independent identifiers. While MessageId is unique for a message, a group of messages can be assigned the same Correlation. Also, pattern matching is possible only with Correlation.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

DeliveryMode

This instance property specifies the expected delivery mode of the message being dequeued.

Declaration

```
// C#
public OracleAQMessageDeliveryMode DeliveryMode {get;set;}
```

Property Value

An OracleAQMessageDeliveryMode enumerated value.

Remarks

This property specifies the type of messages to be dequeued. It can be set to dequeue either persistent or buffered messages, or both from a queue. The following values are valid:

- `OracleAQMessageDeliveryMode.Persistent`
- `OracleAQMessageDeliveryMode.Buffered`
- `OracleAQMessageDeliveryMode.PersistentOrBuffered`

The default value is `OracleAQMessageDeliveryMode.Persistent`.

Buffered messaging is supported in all queue tables created with a database compatibility level of 8.1 or higher.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

DequeueMode

This instance property specifies the locking behavior associated with the dequeue operation.

Declaration

```
// C#  
public OracleAQDequeueMode DequeueMode {get;set;}
```

Property Value

An `OracleAQDequeueMode` enumerated value.

Exceptions

`ArgumentOutOfRangeException` - The specified `DequeueMode` value is invalid.

Remarks

The default value is `OracleAQDequeueMode.Remove`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

MessageId

This instance property specifies the message identifier of the message to be dequeued.

Declaration

```
// C#  
public byte[] MessageId {get;set;}
```

Property Value

A `byte[]`.

Remarks

The dequeue operation succeeds only if the message ID of the message being dequeued matches with the message ID specified.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

NavigationMode

This instance property specifies the position of the message that will be retrieved.

Declaration

```
// C#
public OracleAQNavigationMode NavigationMode {get;set;}
```

Property Value

An OracleAQNavigationMode enumerated value.

Exceptions

ArgumentOutOfRangeException - The specified NavigationMode value is invalid.

Remarks

The default value is OracleAQNavigationMode.NextMessage.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

ProviderSpecificType

This property specifies whether the payload of a dequeued message is provided as an ODP.NET specific type or a .NET type.

Declaration

```
// C#
public bool ProviderSpecificType {get;set;}
```

Property Value

A bool.

Remarks

The default value of this property is false. For a discussion of how this property affects payload type, refer to ["MessageType"](#) under the OracleAQQueue class.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)
- ["MessageType"](#) on page 12-60

Visibility

This instance property specifies whether or not the new message is dequeued as part of the current transaction.

Declaration

```
// C#  
public OracleAQVisibilityMode Visibility {get;set;}
```

Property Value

An OracleAQVisibilityMode enumerated value.

Exceptions

ArgumentOutOfRangeException - The Visibility value specified is invalid.

Remarks

The default value is OracleAQVisibilityMode.OnCommit. You must use transactions when using the default value for this property. This ensures that applications do not lose messages and the messages are appropriately removed from the queue after the dequeue operation is successful. If transactions are not used when using the default visibility mode of OracleAQVisibilityMode.OnCommit, then messages are not removed from the queue.

Using the alternative visibility mode value, OracleAQVisibilityMode.Immediate can eliminate the need to create, commit, and rollback a transaction. However, if an error occurs during the dequeue operation, then the message may be lost.

The visibility parameter is ignored when DequeueMode is set to OracleAQDequeueMode.Browse.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

Wait

This instance property specifies the wait time, in seconds, for a message that matches the search criteria.

Declaration

```
// C#  
public int Wait {get;set;}
```

Property Value

Any positive integer value or 0 or -1.

Exceptions

`ArgumentOutOfRangeException` - The specified `Wait` value is invalid.

Remarks

The default value is -1, which implies an infinite wait. The following values are valid:

- Positive integer: Wait time in seconds.
- -1: Wait forever.
- 0: Do not wait.

A value of less than -1 raises an `ArgumentOutOfRangeException`.

This parameter is ignored if messages in the same group are being dequeued.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

OracleAQDequeueOptions Public Methods

The OracleAQDequeueOptions public method is listed in [Table 12–8](#).

Table 12–8 OracleAQDequeueOptions Public Methods

| Public Method | Description |
|-----------------------|----------------------------------------------------|
| Clone | Creates a copy of an OracleAQDequeueOptions object |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

Clone

This method creates a copy of an OracleAQDequeueOptions object.

Declaration

```
// C#  
public object Clone();
```

Return Value

An OracleAQDequeueOptions object.

Implements

ICloneable.

Remarks

The cloned object has the same property values as the object being cloned.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQDequeueOptions Class](#)
- [OracleAQDequeueOptions Members](#)

OracleAQEnqueueOptions Class

The OracleAQEnqueueOptions class represents the options available when enqueueing a message to an OracleAQQueue.

Class Inheritance

System.Object

OracleAQEnqueueOptions

Declaration

```
// C#
public sealed class OracleAQEnqueueOptions : ICloneable
```

Requirements

| | |
|-----------------------|----------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | Oracle.DataAccess.dll |
| Namespace | Oracle.DataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleAQEnqueueOptions Members](#)
- [OracleAQEnqueueOptions Constructor](#)
- [OracleAQEnqueueOptions Properties](#)
- [OracleAQEnqueueOptions Public Methods](#)

OracleAQEnqueueOptions Members

The OracleAQEnqueueOptions members are listed in the following tables.

OracleAQEnqueueOptions Constructor

OracleAQEnqueueOptions constructor is listed in [Table 12–9](#).

Table 12–9 OracleAQEnqueueOptions Constructor

| Constructor | Description |
|----------------------------------------------------|------------------------------------------------------------------|
| OracleAQEnqueueOptions Constructor | Instantiates a new instance of the OracleAQEnqueueOptions class. |

OracleAQEnqueueOptions Properties

OracleAQEnqueueOptions properties are listed in [Table 12–10](#).

Table 12–10 OracleAQEnqueueOptions Properties

| Property | Description |
|------------------------------|------------------------------------------------------------------------------------------|
| DeliveryMode | Specifies the delivery mode of the message being enqueued. |
| Visibility | Specifies whether or not the new message is enqueued as part of the current transaction. |

OracleAQEnqueueOptions Public Methods

The OracleAQEnqueueOptions public method is listed in [Table 12–11](#).

Table 12–11 OracleAQEnqueueOptions Public Methods

| Public Method | Description |
|-----------------------|-----------------------------------------------------|
| Clone | Creates a copy of an OracleAQEnqueueOptions object. |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQEnqueueOptions Class](#)

OracleAQEnqueueOptions Constructor

This constructor creates an instance of the `OracleAQEnqueueOptions` class with default property values.

Declaration

```
// C#  
public OracleAQEnqueueOptions();
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleAQEnqueueOptions Class](#)
- [OracleAQEnqueueOptions Members](#)

OracleAQEnqueueOptions Properties

OracleAQEnqueueOptions properties are listed in [Table 12–12](#).

Table 12–12 OracleAQEnqueueOptions Properties

| Property | Description |
|------------------------------|------------------------------------------------------------------------------------------|
| DeliveryMode | Specifies the delivery mode of the message being enqueued. |
| Visibility | Specifies whether or not the new message is enqueued as part of the current transaction. |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQEnqueueOptions Class](#)
- [OracleAQEnqueueOptions Members](#)

DeliveryMode

This instance property specifies the delivery mode of the message being enqueued.

Declaration

```
// C#
public OracleAQMessageDeliveryMode DeliveryMode {get;set;}
```

Exceptions

ArgumentOutOfRangeException - The specified Visibility value is invalid.

Remarks

The valid values can be any of the following enumerated values:

- OracleAQMessageDeliveryMode.Persistent
- OracleAQMessageDeliveryMode.Buffered

The default is OracleAQMessageDeliveryMode.Persistent.

OracleAQMessageDeliveryMode.PersistentOrBuffered cannot be set on this property.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQEnqueueOptions Class](#)
- [OracleAQEnqueueOptions Members](#)

Visibility

This instance property specifies whether or not the new message is enqueued as part of the current transaction.

Declaration

```
// C#
```

```
public OracleAQVisibilityMode Visibility {get;set;}
```

Property Value

An OracleAQVisibilityMode enumerated value.

Exceptions

ArgumentOutOfRangeException - The specified Visibility value is invalid.

Remarks

The default value is OracleAQVisibilityMode.OnCommit. You must use transactions when using the default value. If transactions are not used when using the default visibility mode of OracleAQVisibilityMode.OnCommit, then messages are not enqueued to the queue.

Using the alternative visibility mode value, OracleAQVisibilityMode.Immediate eliminates the need to use a transaction. The queue is not affected in case the enqueue operation fails. The message does not get enqueued to the queue for such cases.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleAQEnqueueOptions Class](#)
- [OracleAQEnqueueOptions Members](#)

OracleAQEnqueueOptions Public Methods

OracleAQEnqueueOptions public method is listed in [Table 12–13](#).

Table 12–13 OracleAQEnqueueOptions Public Methods

| Public Method | Description |
|-----------------------|-----------------------------------------------------|
| Clone | Creates a copy of an OracleAQEnqueueOptions object. |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQEnqueueOptions Class](#)
- [OracleAQEnqueueOptions Members](#)

Clone

This method creates a copy of an OracleAQEnqueueOptions object.

Declaration

```
// C#  
public object Clone();
```

Return Value

An OracleAQEnqueueOptions object.

Implements

ICloneable.

Remarks

The cloned object has the same property values as that of the object being cloned.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQEnqueueOptions Class](#)
- [OracleAQEnqueueOptions Members](#)

OracleAQMessage Class

An OracleAQMessage object represents a message to be enqueued and dequeued.

Class Inheritance

System.Object

OracleAQMessage

Declaration

```
// C#
public sealed class OracleAQMessage
```

Requirements

| | |
|-----------------------|---------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | Oracle.DataAccess.dll |
| Namespace | Oracle.DataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

An OracleAQMessage object consists of control information (metadata) and Payload (data). The control information is exposed by various properties on the OracleAQMessage object and is used by Oracle Streams Advanced Queuing to manage messages. The payload is the information stored in the queue.

Note: An instance of OracleAQMessage cannot be re-used across multiple operations of OracleAQQueue public method [Enqueue\(\)](#) or [EnqueueArray\(\)](#), if the payload is an XmlReader. This is a direct consequence of the forward-only semantics of the XmlReader, as an [Enqueue\(\)](#) or [EnqueueArray\(\)](#) operation internally invokes a read operation on the XmlReader to extract the data to be enqueued.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessage Members](#)
- [OracleAQMessage Constructors](#)
- [OracleAQMessage Properties](#)

OracleAQMessage Members

OracleAQMessage members are listed in the following tables.

OracleAQMessage Constructor

OracleAQMessage constructors are listed in [Table 12-14](#).

Table 12-14 OracleAQMessage Constructors

| Constructor | Description |
|----------------------------------------------|-------------------------------------------------------------------------------------|
| OracleAQMessage Constructors | Instantiates a new instance of the <code>OracleAQMessage</code> class (Overloaded). |

OracleAQMessage Properties

OracleAQMessage properties are listed in [Table 12-15](#).

Table 12-15 OracleAQMessage Properties

| Property | Description |
|-----------------------------------|-------------------------------------------------------------------------------------------------------------|
| Correlation | Specifies an identification for the message. |
| Delay | Specifies the duration, in seconds, after which an enqueued message is available for dequeuing. |
| DeliveryMode | Specifies the delivery mode of the dequeued message. |
| DequeueAttempts | Returns the number of attempts that have been made to dequeue the message. |
| EnqueueTime | Specifies the time when the message was enqueued. |
| ExceptionQueue | Specifies the name of the queue that the message should be moved to if it cannot be processed successfully. |
| Expiration | Specifies the duration, in seconds, for which an enqueued message is available for dequeuing. |
| MessageId | Returns the message identifier. |
| OriginalMessageId | Specifies the identifier of the message in the last queue that generated this message. |
| Payload | Specifies the payload of the message. |
| Priority | Specifies the priority of the message. |
| Recipients | Specifies the list of recipients that overrides the default queue subscribers. |
| SenderId | Identifies the original sender of the message. |
| State | Specifies the state of the message at the time of dequeue. |
| TransactionGroup | Specifies the transaction group for the dequeued message. |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessage Class](#)

OracleAQMessage Constructors

OracleAQMessage constructors create new instances of the OracleAQMessage class.

Overload List:

- [OracleAQMessage\(\)](#)

This constructor instantiates the OracleAQMessage class.

- [OracleAQMessage\(Object\)](#)

This constructor instantiates the OracleAQMessage class using the object provided as the payload.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

OracleAQMessage()

This constructor instantiates the OracleAQMessage class.

Declaration

```
// C#  
public OracleAQMessage();
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

OracleAQMessage(Object)

This constructor instantiates the OracleAQMessage class using the Object provided as the *payload*.

Declaration

```
// C#  
public OracleAQMessage(Object payload);
```

Parameters

- *payload*

An Object specifying *payload*. It can be one of the following types:

- byte[]
- IOracleCustomType
- OracleBinary
- OracleXmlType

- String
- XmlReader

Exceptions

`ArgumentException` - The specified *payload* value is of invalid type.

Remarks

The ODP.NET AQ implementation currently does not support user defined types with LOB attributes. It also does not support other variants of user defined types such as `VARRAY` and nested tables, as Oracle Streams AQ does not support them inherently.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

OracleAQMessage Properties

OracleAQMessage properties are listed in [Table 12–16](#).

Table 12–16 OracleAQMessage Properties

| Property | Description |
|-----------------------------------|-------------------------------------------------------------------------------------------------------------|
| Correlation | Specifies an identification for the message. |
| Delay | Specifies the duration, in seconds, after which an enqueued message is available for dequeuing. |
| DeliveryMode | Specifies the delivery mode of the dequeued message. |
| DequeueAttempts | Returns the number of attempts that have been made to dequeue the message. |
| EnqueueTime | Specifies the time when the message was enqueued. |
| ExceptionQueue | Specifies the name of the queue that the message should be moved to if it cannot be processed successfully. |
| Expiration | Specifies the duration, in seconds, for which an enqueued message is available for dequeuing. |
| MessageId | Returns the message identifier. |
| OriginalMessageId | Specifies the identifier of the message in the last queue that generated this message. |
| Payload | Specifies the payload of the message. |
| Priority | Specifies the priority of the message. |
| Recipients | Specifies the list of recipients that overrides the default queue subscribers. |
| SenderId | Identifies the original sender of the message. |
| State | Specifies the state of the message at the time of dequeue. |
| TransactionGroup | Specifies the transaction group for the dequeued message. |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

Correlation

This instance property specifies an identification for the message.

Declaration

```
// C#
public string Correlation {get;set;}
```

Property Value

A string that specifies the identification for the message.

Remarks

The producer of a message can set this property at the time of enqueueing. The consumer can then use this identification to dequeue specific messages by setting the `Correlation` property of an `OracleAQDequeueOptions` object. For more information regarding dequeuing messages based on `Correlation`, refer to "[Correlation](#)" under the `OracleAQDequeueOptions` class.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)
- ["Correlation"](#) on page 12-13

Delay

This instance property specifies the duration, in seconds, after which an enqueued message is available for dequeuing.

Declaration

```
// C#  
public int Delay {get;set;}
```

Property Value

An integer that indicates the number of seconds after which an enqueued message is available for dequeuing.

Exceptions

`ArgumentException` - The value specified is less than 0.

Remarks

This property delays the immediate consumption of an enqueued message. The following are valid values for this property:

- Positive integer - Indicates the delay in seconds.
- 0 - indicates that the message is immediately available for dequeuing.

The default value is 0. The `Delay` property is not supported with buffered messaging.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

DeliveryMode

This instance property specifies the delivery mode of the dequeued message.

Declaration

```
// C#  
public OracleAQMessageDeliveryMode DeliveryMode {get;}
```

Property Value

An `OracleAQMessageDeliveryMode` enumerated value (`OracleAQMessageDeliveryMode.Persistent` or `OracleAQMessageDeliveryMode.Buffered`).

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

DequeueAttempts

This instance property returns the number of attempts that have been made to dequeue the message.

Declaration

```
// C#  
public int DequeueAttempts {get;}
```

Property Value

An integer that indicates the number of dequeue attempts.

Remarks

This property is available in an `OracleAQMessage` after the message has been dequeued from a queue.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

EnqueueTime

This instance property specifies the time when the message was enqueued.

Declaration

```
// C#  
public DateTime EnqueueTime {get;}
```

Property Value

A `DateTime` object.

Remarks

This property is available after the message is dequeued. It provides the enqueue time of a dequeued message.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

ExceptionQueue

This instance property specifies the name of the queue that the message should be moved to if it cannot be processed successfully.

Declaration

```
// C#  
public string ExceptionQueue {get;set;}
```

Property Value

The name of the queue that a message should be moved to if it cannot be processed successfully. The default value is null.

Remarks

This property specifies the queue that a message should be moved to if the message has expired or if the number of unsuccessful dequeue attempts have exceeded the `max_retries` value for the queue.

If this property is not set or the specified exception queue name does not exist, then the default exception queue associated with the queue table is used.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

Expiration

This instance property specifies the duration, in seconds, for which an enqueued message is available for dequeuing.

Declaration

```
// C#  
public int Expiration {get;set;}
```

Property Value

An integer that specifies the number of seconds an enqueued message is available for dequeuing.

Exceptions

`ArgumentException` - The value specified is less than -1.

Remarks

The value specified is an offset from the value specified in the `Delay` property.

The following are valid values for the property:

- Positive integer - Indicates the expiration in seconds.
- -1 - Indicates that the message never expires.

The default value is -1. When a message expires, the message moves from the `READY` state to the `EXPIRED` state.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

MessageId

This instance property returns the message identifier.

Declaration

```
// C#
public byte[] MessageId {get;}
```

Property Value

A `byte[]` that specifies the message identifier.

Remarks

This property is available after an enqueue or dequeue operation. Dequeued buffered messages have a null value for `MessageId`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

OriginalMessageId

This instance property specifies the identifier of the message in the last queue that generated this message.

Declaration

```
// C#
public byte[] OriginalMessageId {get;}
```

Property Value

A `byte[]` that specifies the original message identifier.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

Payload

This instance property specifies the payload of the message.

Declaration

```
// C#  
public Object Payload {get;set;}
```

Property Value

An `Object` that specifies the payload of the message.

Exceptions

`ArgumentException` - The specified object is not one of the allowed types.

Remarks

For a complete discussion of various payload types, refer to ["MessageType"](#) under the `OracleAQQueue` class.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)
- ["MessageType"](#) on page 12-60

Priority

This instance property specifies the priority of the message.

Declaration

```
// C#  
public int Priority {get;set;}
```

Property Value

An integer that specifies the priority of the message.

Remarks

The default value is 0. In order to take effect, this property must be set prior to enqueueing the message.

Smaller values indicate higher priority for the message. Negative values may also be used.

The priority of an enqueued message is useful for priority-based dequeuing.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

Recipients

This instance property specifies the list of recipients that overrides the default queue subscribers.

Declaration

```
// C#
public OracleAQAgent[] Recipients {get; set}
```

Property Value

An OracleAQAgent[].

Remarks

This recipient list is valid only for messages being enqueued to multiconsumer queues. The list of recipients is not returned with the message at the time of dequeuing.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

SenderId

This instance property identifies the original sender of the message.

Declaration

```
// C#
public OracleAQAgent SenderId {get; set}
```

Property Value

An OracleAQAgent object.

Remarks

Sender identification is supported in all queue tables created with a database compatibility level of 8.1 or higher.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

State

This instance property specifies the state of the message at the time of dequeue.

Declaration

```
// C#  
public OracleAQMessageState State {get;}
```

Property Value

An `OracleAQMessageState` enumerated value.

Remarks

This property is available after the message is dequeued.

The state of buffered messages dequeued by specifying `Correlation` under `dequeue` options is always `OracleAQMessageState.Ready`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

TransactionGroup

This instance property specifies the transaction group for the dequeued message.

Declaration

```
// C#  
public string TransactionGroup {get;}
```

Property Value

A string that specifies the transaction group.

Remarks

This property is set only after the call to `DequeueArray`. This property is supported only when using Oracle Database 10g database or higher.

Messages belonging to one queue can be grouped to form a set that can only be consumed by one user at a time. This requires that the queue be created in a queue table that is enabled for message grouping. All messages belonging to a group must be created in the same transaction. Also, all messages created in one transaction belong to the same group.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessage Class](#)
- [OracleAQMessage Members](#)

OracleAQMessageAvailableEventArgs Class

The OracleAQMessageAvailableEventArgs class provides event data for the OracleAQQueue.MessageAvailable event.

Class Inheritance

System.Object

System.EventArgs

Oracle.DataAccess.Client.OracleAQMessageAvailableEventArgs

Declaration

```
// C#
public sealed class OracleAQMessageAvailableEventArgs
```

Requirements

| | |
|-----------------------|----------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | Oracle.DataAccess.dll |
| Namespace | Oracle.DataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

This class cannot be inherited.

For detailed information on all the inherited properties and methods, please read the documentation provided by Microsoft's .NET Documentation.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleAQMessageAvailableEventArgs Members](#)
- [OracleAQMessageAvailableEventArgs Constructor](#)
- [OracleAQMessageAvailableEventArgs Properties](#)

OracleAQMessageAvailableEventArgs Members

OracleAQMessageAvailableEventArgs members are listed in the following tables.

OracleAQMessageAvailableEventArgs Constructor

OracleAQMessageAvailableEventArgs properties are listed in [Table 12-17](#)

Table 12-17 OracleAQMessageAvailableEventArgs Constructor

| Property | Description |
|---------------------------------------------------------------|-----------------------------------------------------------------------------|
| OracleAQMessageAvailableEventArgs Constructor | Instantiates a new instance of the OracleAQMessageAvailableEventArgs class. |

OracleAQMessageAvailableEventArgs Properties

OracleAQMessageAvailableEventArgs properties are listed in [Table 12-18](#).

Table 12-18 OracleAQMessageAvailableEventArgs Properties

| Property | Description |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------|
| AvailableMessages | Specifies the number of messages that raised this notification. |
| ConsumerName | Provides the name of the consumer for which the message is available for dequeuing. |
| Correlation | Provides the name of the consumer for which the message is available for dequeuing. |
| Delay | Specifies the duration, in seconds, after which an enqueued message is available for dequeuing. |
| DeliveryMode | Specifies the delivery mode of the message. |
| EnqueueTime | Specifies the time when the message was enqueued. |
| ExceptionQueue | Specifies the name of the queue that the message is moved to if it cannot be processed successfully. |
| Expiration | Specifies the duration, in seconds, for which an enqueued message is available for dequeuing before expiring. |
| MessageId | Returns an array of message identifiers. |
| NotificationType | Indicates the type of notification such as regular, grouping, or timeout. |
| OriginalMessageId | Specifies the ID of the message, in the last queue, that generated this message. |
| Priority | Specifies the priority of the message. |
| QueueName | Indicates the name of the queue that contains the message to be dequeued. |
| SenderId | Identifies the original sender of the message. |
| State | Specifies the state of the message. |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessageAvailableEventArgs Class](#)

OracleAQMessageAvailableEventArgs Constructor

This constructor creates an instance of the `OracleAQMessageAvailableEventArgs` class with default property values.

Declaration

```
// C#  
public OracleAQMessageAvailableEventArgs();
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

OracleAQMessageAvailableEventArgs Properties

OracleAQMessageAvailableEventArgs properties are listed in [Table 12–19](#).

Table 12–19 OracleAQMessageAvailableEventArgs Properties

| Property | Description |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------|
| AvailableMessages | Specifies the number of messages that raised this notification. |
| ConsumerName | Provides the name of the consumer for which the message is available for dequeuing. |
| Correlation | Provides the name of the consumer for which the message is available for dequeuing. |
| Delay | Specifies the duration, in seconds, after which an enqueued message is available for dequeuing. |
| DeliveryMode | Specifies the delivery mode of the message. |
| EnqueueTime | Specifies the time when the message was enqueued. |
| ExceptionQueue | Specifies the name of the queue that the message is moved to if it cannot be processed successfully. |
| Expiration | Specifies the duration, in seconds, for which an enqueued message is available for dequeuing before expiring. |
| MessageId | Returns an array of message identifiers. |
| NotificationType | Indicates the type of notification such as regular, grouping, or timeout. |
| OriginalMessageId | Specifies the ID of the message, in the last queue, that generated this message. |
| Priority | Specifies the priority of the message. |
| QueueName | Indicates the name of the queue that contains the message to be dequeued. |
| SenderId | Identifies the original sender of the message. |
| State | Specifies the state of the message. |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

AvailableMessages

This instance property specifies the number of messages that raised this notification.

Declaration

```
// C#
public int AvailableMessages{get;}
```

Property Value

An integer indicating the number of messages that raised this notification.

Remarks

The property value is 1 for a regular notification type. The notification type can be specified using the `OracleAQQueue.Notification` property.

This property is not relevant if the `NotificationType` is `OracleAQNotificationType.Timeout`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

ConsumerName

This property provides the name of the consumer for which the message is available for dequeuing.

Declaration

```
// C#  
public string ConsumerName {get;}
```

Property Value

A string that identifies the name of the consumer.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

Correlation

This instance property specifies the identification for the message.

Declaration

```
// C#  
public string Correlation {get;}
```

Property Value

A string that specifies the identification for the message.

Remarks

This property specifies the correlation of the message for which the notification is raised. The consumer can then use this identification to dequeue specific messages by setting the **"Correlation"** property of the `OracleAQDequeueOptions` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)
- ["Correlation"](#) on page 13

Delay

This instance property specifies the duration, in seconds, after which an enqueued message is available for dequeuing.

Declaration

```
// C#  
public int Delay {get;}
```

Property Value

An integer that indicates the duration, in seconds, after which an enqueued message is available for dequeuing.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

DeliveryMode

This instance property specifies the delivery mode of the message.

Declaration

```
// C#  
public OracleAQMessageDeliveryMode DeliveryMode {get;}
```

Property Value

An `OracleAQMessageDeliveryMode` enumerated value.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

EnqueueTime

This instance property specifies the time when the message was enqueued.

Declaration

```
// C#  
public DateTime EnqueueTime {get;}
```


Property Value

A `DateTime` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

ExceptionQueue

This instance property specifies the name of the queue that the message is moved to if it cannot be processed successfully.

Declaration

```
// C#
public string ExceptionQueue {get;}
```

Property Value

The name of the queue that a message to is moved if it cannot be processed successfully.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

Expiration

This instance property specifies the duration, in seconds, for which an enqueued message is available for dequeuing before expiring.

Declaration

```
// C#
public int Expiration {get;}
```

Property Value

An integer that specifies the duration, in seconds, for which an enqueued message is available for dequeuing.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

MessageId

This instance property returns an array of message identifiers.

Declaration

```
// C#  
public byte[][] MessageId{get;}
```

Property Value

A `byte[][]` that specifies the message identifiers received as part of the notification.

Remarks

This property specifies the message identifiers of the messages that raise the notification.

The size of the `MessageId` array is 1 for regular notifications. The size of the `MessageId` array is 1 for grouping notifications if the notification grouping type is `OracleAQNotificationGroupingType.Last`.

This property is not relevant if the `NotificationType` is `OracleAQNotificationType.Timeout`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

NotificationType

This property indicates the type of notification such as regular, grouping, or timeout.

Declaration

```
// C#  
public OracleAQNotificationType NotificationType {get;}
```

Property Value

An `OracleAQNotificationType` enum value.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

OriginalMessageId

This property specifies the ID of the message, in the last queue, that generated this message.

Declaration

```
// C#  
public byte[] OriginalMessageId {get;}
```

Property Value

A `byte[]` that specifies the original message ID.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

Priority

This instance property specifies the priority of the message.

Declaration

```
// C#
public int Priority {get;}
```

Property Value

An integer that specifies the priority of the message.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

QueueName

This property indicates the name of the queue that contains the message to be dequeued.

Declaration

```
// C#
public string QueueName {get;}
```

Property Value

A string.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

SenderId

This property identifies the original sender of the message.

Declaration

```
// C#
public OracleAQAgent SenderId {get;}
```

Property Value

An OracleAQAgent object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

State

This instance property specifies the state of the message.

Declaration

```
// C#  
public OracleAQMessageState State {get;}
```

Property Value

An OracleAQMessageState enumerated value.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQMessageAvailableEventArgs Class](#)
- [OracleAQMessageAvailableEventArgs Members](#)

OracleAQMessageAvailableEventHandler Delegate

The `OracleAQMessageAvailableEventHandler` delegate represents the signature of the method that handles the `OracleAQQueue.MessageAvailable` event.

Declaration

```
// C#  
public delegate void OracleAQMessageAvailableEventHandler (object  
    sender, OracleAQMessageAvailableEventArgs eventArgs);
```

Parameters

- *sender*

The source of the event.

- *eventArgs*

The `OracleAQMessageAvailableEventArgs` object that contains the event data.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- ["MessageAvailable Event"](#) on page 12-79

OracleAQQueue Class

An OracleAQQueue object represents a queue.

Class Inheritance

System.Object

OracleAQQueue

Declaration

```
// C#  
public class OracleAQQueue : IDisposable
```

Requirements

| | |
|-----------------------|----------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | Oracle.DataAccess.dll |
| Namespace | Oracle.DataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

A queue is a repository of messages and may either be a user queue, or an exception queue. A user queue is for normal message processing. A message is moved from a user queue to an exception queue if it cannot be retrieved and processed for some reason.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleAQQueue Members](#)
- [OracleAQQueue Constructors](#)
- [OracleAQQueue Static Methods](#)
- [OracleAQQueue Properties](#)
- [OracleAQQueue Public Methods](#)
- [OracleAQQueue Events](#)

OracleAQQueue Members

OracleAQQueue members are listed in the following tables.

OracleAQQueue Constructors

OracleAQQueue constructors are listed in [Table 12–20](#).

Table 12–20 OracleAQQueue Constructors

| Constructor | Description |
|--------------------------------------------|---------------------------------------------------------------------|
| OracleAQQueue Constructors | Instantiate a new instance of the OracleAQQueue class (Overloaded). |

OracleAQQueue Static Methods

The OracleAQQueue static method is listed in [Table 12–21](#).

Table 12–21 OracleAQQueue Static Methods

| Static Method | Description |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Listen | Listens for messages on one or more queues for one or more consumers, as specified in the array of OracleAQAgent objects (Overloaded). |

OracleAQQueue Properties

OracleAQQueue properties are listed in [Table 12–22](#).

Table 12–22 OracleAQQueue Properties

| Property | Description |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| Connection | Specifies the OracleConnection object associated with the queue. |
| DequeueOptions | Specifies the dequeuing options to use when dequeuing a message from a queue. |
| EnqueueOptions | Specifies the enqueueing options used to enqueue a message to a queue. |
| MessageType | Specifies the type of queue table associated with this queue. |
| Name | Returns the name of the queue. |
| Notification | Specifies the various notification options for notifications that are registered using the MessageAvailable event. |
| NotificationConsumers | Specifies the array of consumers, for a multiconsumer queue, that are to be notified asynchronously for any incoming messages on the queue. |
| UdtTypeName | Specifies the type name on which the queue and the corresponding queue table is based if the MessageType is OracleAQMessageType.UDT. |

OracleAQQueue Public Methods

The OracleAQQueue public methods are listed in [Table 12–23](#).

Table 12–23 OracleAQQueue Public Methods

| Public Method | Description |
|------------------------------|-------------------------------------------------------------------------------------------|
| Dequeue | Dequeues messages from queues (Overloaded). |
| DequeueArray | Dequeues multiple messages from queues (Overloaded). |
| Dispose | Releases any resources or memory allocated by the object |
| Enqueue | Enqueues messages to queues (Overloaded). |
| EnqueueArray | Enqueues multiple messages to a queue (Overloaded). |
| Listen | Listens for messages on the queue on behalf of <code>listenConsumers</code> (Overloaded). |

OracleAQQueue Events

The OracleAQQueue event is listed in [Table 12–24](#).

Table 12–24 OracleAQQueue Events

| Event Name | Description |
|----------------------------------------|--------------------------------------------------------------------------------------------|
| MessageAvailable Event | Notifies when a message is available in the queue for <code>NotificationConsumers</code> . |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)

OracleAQQueue Constructors

OracleAQQueue constructors create new instances of the OracleAQQueue class.

Overload List:

- [OracleAQQueue\(string\)](#)
This constructor takes a queue name to initialize a queue object.
- [OracleAQQueue\(string, OracleConnection\)](#)
This constructor takes a queue name and connection to initialize a queue object. The connection does not need be open during the queue object construction.
- [OracleAQQueue\(string, OracleConnection, OracleAQMessageType\)](#)
This constructor takes a queue name, connection, and message type enumeration to initialize a queue object.
- [OracleAQQueue\(string, OracleConnection, OracleAQMessageType, string\)](#)
This constructor takes a queue name, connection, message type enumeration, and UDT type name to initialize a queue object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

OracleAQQueue(string)

This constructor takes a queue name to initialize a queue object.

Declaration

```
// C#
public OracleAQQueue(string name);
```

Parameters

- *name*
The name of the queue as specified in the database.

Exceptions

ArgumentNullException - The queue name is null.

ArgumentException - The queue name is empty.

Remarks

The operation of creating an OracleAQQueue object does not involve checking for the existence of the queue in the database.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

OracleAQQueue(string, OracleConnection)

This constructor takes a queue name and connection to initialize a queue object. The connection does not need to be open during the queue object construction.

Declaration

```
// C#  
public OracleAQQueue(string name, OracleConnection con);
```

Parameters

- *name*
Name of the queue as specified in the database.
- *con*
An `OracleConnection` object that connects to the queue.

Exceptions

`ArgumentNullException` - Either the connection is null or queue name is null.

`ArgumentException` - Queue name is empty.

Remarks

The connection can be accessed using the `Connection` property, and it must be opened before calling any operational APIs such as `Enqueue` and `Dequeue`.

Creating an `OracleAQQueue` object does not check for the existence of the queue in the database.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

OracleAQQueue(string, OracleConnection, OracleAQMessageType)

This constructor takes a queue name, connection and message type enumeration to initialize a queue object. The connection does not need to be open during the queue object construction.

Declaration

```
// C#  
public OracleAQQueue(string name, OracleConnection con, OracleAQMessageType  
    messageType);
```

Parameters

- *name*
The name of the queue as specified in the database.
- *con*
An `OracleConnection` object that is used to connect to the queue.
- *messageType*
An `OracleAQMessageType` enumeration specifying the type of the message that is enqueued or dequeued from this queue.

Exceptions

`ArgumentNullException` - Either the connection is null or queue name is null.

`ArgumentException` - Queue name is empty or the specified message type is not valid.

Remarks

Creating an `OracleAQQueue` object does not check for the existence of the queue in the database.

You need to set the `UdtTypeName` property before using the queue object if the `messageType` is a UDT. Another approach is to create a queue using the other constructor overload by supplying the `udtTypeName`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

OracleAQQueue(string, OracleConnection, OracleAQMessageType, string)

This constructor takes a queue name, connection, message type enumeration, and UDT type name to initialize a queue object. The connection does not need to be open during the queue object construction.

Declaration

```
// C#
public OracleAQQueue(string name, OracleConnection con, OracleAQMessageType
    messageType, string udtTypeName);
```

Parameters

- *name*
The name of the queue as specified in the database.
- *con*
An `OracleConnection` object that is used to connect to the queue.
- *messageType*
An `OracleAQMessageType` enumeration specifying the type of the message that is enqueued or dequeued from this queue.
- *udtTypeName*

The name of the database object type used if the `messageType` is UDT. The `udtTypeName` parameter represents the type on which the queue is based.

Exceptions

`ArgumentNullException` - The connection is null or the queue name is null.

`ArgumentException` - The queue name is empty or the specified `messageType` is not valid.

Remarks

Creating an `OracleAQQueue` object does not check for the existence of the queue in the database.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

OracleAQQueue Static Methods

OracleAQQueue static methods are listed in [Table 12–25](#).

Table 12–25 OracleAQQueue Static Methods

| Static Method | Description |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Listen | Listens for messages on one or more queues for one or more consumers, as specified in the array of OracleAQAgent objects (Overloaded). |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Listen

Listen methods listen for messages on one or more queues for one or more consumers as specified in the array of OracleAQAgent objects.

Overload list

- [Listen\(OracleConnection, OracleAQAgent\[\]\)](#)

This static method listens for messages on one or more queues for one or more consumers as specified in the array of OracleAQAgent objects.

- [Listen\(OracleConnection, OracleAQAgent\[\], int\)](#)

This static method listens for messages on one or more queues for one or more consumers as specified in the array of OracleAQAgent objects. It also specifies a wait time.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Listen(OracleConnection, OracleAQAgent[])

This static method listens for messages on one or more queues for one or more consumers as specified in the array of OracleAQAgent objects.

Declaration

```
// C#
public static OracleAQAgent Listen(OracleConnection con, OracleAQAgent[]
    listenConsumers);
```

Parameters

- *con*
An OracleConnection instance.

- *listenConsumers*

The array of consumers being listened for. The name of the `OracleAQAgent` object must be null or empty for single consumer queues.

Return Value

An `OracleAQAgent` object.

Exceptions

`ArgumentNullException` - The *con* or *listenConsumers* parameter is null.

`InvalidOperationException` - The connection is not open.

Remarks

`Listen` is useful in situations where one needs to monitor multiple queues until a message is available for a consumer in one of the queues. The `Name` property of the `OracleAQAgent` object represents the name of the consumer and the `Address` property represents the name of the queue.

This call blocks the calling thread until there is a message ready for consumption for a consumer in the list. It returns an `OracleAQAgent` object which specifies the consumer and queue for which a message is ready to be dequeued.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Listen(OracleConnection, OracleAQAgent[], int)

This static method listens for messages on one or more queues for one or more consumers as specified in the array of `OracleAQAgent` objects. The `Name` property of the `OracleAQAgent` object represents the name of the consumer and the `Address` property of the `OracleAQAgent` object represents the name of the queue.

In case of timeout, this method returns null.

Declaration

```
// C#
public static OracleAQAgent Listen(OracleConnection con, OracleAQAgent[]
    listenConsumers, int waitTime);
```

Parameters

- *con*
An `OracleConnection` instance.
- *listenConsumers*
The array of consumers being listened for. The name of the `OracleAQAgent` object must be null or empty for single consumer queues.
- *waitTime*
Wait time in seconds.

Return Value

An OracleAQAgent object.

Exceptions

ArgumentNullException - The *con* or *listenConsumers* parameter is null.

InvalidOperationException - The connection is not open.

ArgumentException - *waitTime* is less than -1.

Remarks

Listen is useful in situations where one needs to monitor multiple queues until a message is available for a consumer in one of the queues. The *Name* property of the OracleAQAgent object represents the name of the consumer and the *Address* property of the OracleAQAgent object represents the name of the queue.

A *waitTime* of -1 implies an infinite wait time.

This call blocks the calling thread until there is a message ready for consumption for a consumer in the list. It returns an OracleAQAgent object which specifies the consumer and queue for which a message is ready to be dequeued.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

OracleAQQueue Properties

OracleAQQueue properties are listed in [Table 12–26](#).

Table 12–26 OracleAQQueue Properties

| Property | Description |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connection | Specifies the <code>OracleConnection</code> object associated with the queue. |
| DequeueOptions | Specifies the dequeuing options to use when dequeuing a message from a queue. |
| EnqueueOptions | Specifies the enqueueing options used to enqueue a message to a queue. |
| MessageType | Specifies the type of queue table associated with this queue. |
| Name | Returns the name of the queue. |
| Notification | Specifies the various notification options for notifications that are registered using the <code>MessageAvailable</code> event. |
| NotificationConsumers | Specifies the array of consumers, for a multiconsumer queue, that are to be notified asynchronously for any incoming messages on the queue. |
| UdtTypeName | Specifies the type name on which the queue and the corresponding queue table is based if the <code>MessageType</code> is <code>OracleAQMessageType.UDT</code> . |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Connection

This property specifies the `OracleConnection` object associated with the queue.

Declaration

```
// C#
public OracleConnection Connection {get; set;}
```

Property Value

An `OracleConnection` object that indicates the connection associated with the queue.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

This connection must be opened before calling methods like `Enqueue` and `Dequeue`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

DequeueOptions

This instance property specifies the dequeuing options to use when dequeuing a message from a queue.

Declaration

```
// C#  
public OracleAQDequeueOptions DequeueOptions {get; set}
```

Property Value

An OracleAQDequeueOptions object.

Exceptions

ObjectDisposedException - The object is already disposed.

Remarks

The default value is an OracleAQDequeueOptions object with default property values. Setting this property to null resets all dequeue options to their default values.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

EnqueueOptions

This instance property specifies the enqueueing options used to enqueue a message to a queue.

Declaration

```
// C#  
public OracleAQEnqueueOptions EnqueueOptions {get; set}
```

Property Value

An OracleAQEnqueueOptions object.

Exceptions

ObjectDisposedException - The object is already disposed.

Remarks

The default value is an OracleAQEnqueueOptions object with default property values. Setting this property to null resets all enqueue options to their default values.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

MessageType

This instance property specifies the type of queue table associated with this queue.

Declaration

```
// C#
public OracleAQMessageType MessageType {get; set;}
```

Property Value

An OracleAQMessageType enumerated value.

Exceptions

ArgumentOutOfRangeException - The type value specified is invalid.

ObjectDisposedException - The object is already disposed.

Remarks

The MessageType property also dictates the type of message payloads that are enqueued or dequeued from the queue. It is possible to enqueue a variety of payloads depending on the MessageType.

[Table 12-27](#) lists the allowed payload types for various message types.

Table 12-27 Message Types and Payloads

| OracleAQQueue.MessageType | Allowed OracleAQMessage.Payload type to Enqueue |
|---------------------------|------------------------------------------------------------------------------|
| OracleAQMessageType.Raw | OracleBinary, byte[] |
| OracleAQMessageType.Xml | OracleXmlType, XmlReader, String (well-formed XML, else exception is raised) |
| OracleAQMessageType.UDT | UDT Custom Object |

[Table 12-28](#) lists the payload types for dequeued messages.

Table 12-28 Payload Types for Dequeued Messages

| OracleAQQueue.MessageType | DequeueOptions.ProviderSpecificType | OracleAQMessage.Payload of dequeued message |
|---------------------------|-------------------------------------|---------------------------------------------|
| OracleAQMessageType.Xml | true | OracleXmlType |
| OracleAQMessageType.Xml | false | XmlReader |
| OracleAQMessageType.Raw | true | OracleBinary |
| OracleAQMessageType.Raw | false | Byte[] |
| OracleAQMessageType.UDT | N.A. | UDT Custom Object |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Name

This instance property returns the name of the queue.

Declaration

```
// C#  
public string Name {get;}
```

Property Value

A string that indicates the name of the queue.

Exceptions

`ObjectDisposedException` - The object is already disposed.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Notification

This instance property specifies the various notification options for notifications that are registered using the `MessageAvailable` event.

Declaration

```
// C#  
public OracleNotificationRequest Notification {get;}
```

Property Value

Specifies an `OracleNotificationRequest` object whose properties can be changed to alter the notification behavior.

Remarks

This property can be used to change various notification options. The notification options must be changed before registering with the `MessageAvailable` event. This property can be modified again only after unregistering from the `MessageAvailable` event.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

NotificationConsumers

This instance property specifies the array of consumers, for a multiconsumer queue, that are to be notified asynchronously for any incoming messages on the queue.

Declaration

```
// C#  
public string[] NotificationConsumers {get; set;}
```

Property Value

Specifies an array of consumer name strings for which the notifications are delivered.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - `MessageAvailable` registration is active.

Remarks

The consumer names must be in uppercase. This functionality only supports queues with uppercase names.

The list of consumers is used in the `MessageAvailable` event. The list must be set before registering for the event. This property cannot be modified after registering for the `MessageAvailable` event. This property can be modified again only after unregistering from `MessageAvailable` event.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

UdtTypeName

This instance property specifies the type name on which the queue and the corresponding queue table is based if the `MessageType` is `OracleAQMessageType.UDT`.

Declaration

```
// C#  
public string UdtTypeName {get; set;}
```

Property Value

Specifies the Oracle user-defined type name if the `MessageType` is `OracleAQMessageType.UDT`.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The `UdtTypeName` property corresponds to the user-defined type name of the payload. This property must always be specified if the payload is a user-defined type. This property need not be set for other payload types.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

OracleAQQueue Public Methods

OracleAQQueue public methods are listed in [Table 12–29](#).

Table 12–29 OracleAQQueue Public Methods

| Public Method | Description |
|------------------------------|-------------------------------------------------------------------------------------------|
| Dequeue | Dequeues messages from queues (Overloaded). |
| DequeueArray | Dequeues multiple messages from queues (Overloaded). |
| Dispose | Releases any resources or memory allocated by the object |
| Enqueue | Enqueues messages to queues (Overloaded). |
| EnqueueArray | Enqueues multiple messages to a queue (Overloaded). |
| Listen | Listens for messages on the queue on behalf of <code>listenConsumers</code> (Overloaded). |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Dequeue

Dequeue methods dequeue messages from queues.

Overload List

- [Dequeue\(\)](#)
This instance method dequeues messages from a queue using the `DequeueOptions` for the instance.
- [Dequeue\(OracleAQDequeueOptions\)](#)
This instance method dequeues messages from a queue using the supplied dequeue options.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Dequeue()

This instance method is used to dequeue a message from a queue using the `DequeueOptions` for the instance.

Declaration

```
// C#
```

```
public OracleAQMessage Dequeue();
```

Return Value

An `OracleAQMessage` instance representing the dequeued message.

Exceptions

`InvalidOperationException` - The connection is not open.

`ObjectDisposedException` - The object is already disposed.

`OracleException` - In case of timeout, an exception is thrown with the message, ORA-25228: timeout or end-of-fetch during message dequeue from queue_name. Timeout may happen if `DequeueOptions.Wait` is set to a value other than -1.

Remarks

The `MessageType` property must be set appropriately before calling this function. If the `MessageType` is `OracleAQMessageType.UDT`, then the `UdtTypeName` property must also be set.

Dequeued buffered messages always have null `MessageId` values.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Dequeue(OracleAQDequeueOptions)

This instance method dequeues messages from a queue using the supplied dequeue options.

Declaration

```
// C#
public OracleAQMessage Dequeue(OracleAQDequeueOptions dequeueOptions);
```

Parameters

- *dequeueOptions*
An `OracleAQDequeueOptions` object.

Return Value

An `OracleAQMessage` instance representing the dequeued message.

Exceptions

`InvalidOperationException` - The connection is not open.

`ObjectDisposedException` - The object is already disposed.

`OracleException` - In case of timeout, an exception is thrown with the message, ORA-25228: timeout or end-of-fetch during message dequeue from queue_name. Timeout may happen if `DequeueOptions.Wait` is set to a value other than -1.

Remarks

If the supplied `dequeueOptions` object is `null`, then the dequeue options default values are used. The queue object's `DequeueOptions` property is ignored for this operation.

Calling this method does not change the `DequeueOptions` property of the queue.

The `MessageType` property must be set appropriately before calling this function. If the `MessageType` is `OracleAQMessageType.UDT`, then the `UdtTypeName` property must also be set.

Dequeued buffered messages always have `null` `MessageId` values.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

DequeueArray

`DequeueArray` methods dequeue multiple messages from queues.

Overload List

- [DequeueArray\(int\)](#)

This instance method dequeues multiple messages from a queue using the `DequeueOptions` of the instance.

- [DequeueArray\(int, OracleAQDequeueOptions\)](#)

This instance method dequeues multiple messages from a queue using the supplied dequeue options.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

DequeueArray(int)

This instance method dequeues multiple messages from a queue using the `DequeueOptions` of the instance.

Declaration

```
// C#  
public OracleAQMessage[] DequeueArray(int dequeueCount);
```

Parameters

- `dequeueCount`

An integer specifying the numbers of messages to dequeue.

Return Value

An array of `OracleAQMessage` instances representing the dequeued messages.

Exceptions

`ArgumentOutOfRangeException` - `dequeueCount` is less than or equal to 0.

`InvalidOperationException` - The connection is not open.

`ObjectDisposedException` - The object is already disposed.

`OracleException` - In case of timeout, an exception is thrown with the message, ORA-25228: timeout or end-of-fetch during message dequeue from `queue_name`. Timeout may happen if `DequeueOptions.Wait` is set to a value other than -1.

Remarks

This method is supported for Oracle Database 10g and higher releases.

The `MessageType` property must be set appropriately before calling this function. If the `MessageType` is `OracleAQMessageType.UDT`, then the `UdtTypeName` property must be set as well.

The size of the returned array may be less than the `dequeueCount`. It depends on the actual number of messages present in the queue.

For database versions earlier than Oracle Database 12c Release 1 (12.1), the `MessageId` property of persistent `OracleAQMessage` objects retrieved using `DequeueArray` is always null.

Dequeued buffered messages always have null `MessageId` values irrespective of the database version.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

DequeueArray(int, OracleAQDequeueOptions)

This instance method dequeues multiple messages from a queue using the supplied dequeue options.

Declaration

```
// C#
public OracleAQMessage[] DequeueArray(int dequeueCount, OracleAQDequeueOptions dequeueOptions);
```

Parameters

- *dequeueCount*
An integer specifying the numbers of messages to dequeue.
- *dequeueOptions*
An `OracleAQDequeueOptions` object.

Return Value

An array of `OracleAQMessage` instances representing the dequeued messages.

Exceptions

`ArgumentOutOfRangeException` - `dequeueCount` is less than or equal to 0.

`InvalidOperationException` - The connection is not open.

`ObjectDisposedException` - The object is already disposed.

`OracleException` - In case of timeout, an exception is thrown with the message, ORA-25228: timeout or end-of-fetch during message dequeue from `queue_name`. Timeout may happen if `DequeueOptions.Wait` is set to a value other than -1.

Remarks

This method is supported for Oracle Database 10g Release 1 (10.1) and higher releases. Calling this method does not change the `DequeueOptions` property of the queue.

If the supplied `dequeueOptions` object is `null`, then the dequeue options default values are used. The `DequeueOptions` property of the queue object is ignored in this operation.

The `MessageType` property must be set appropriately before calling this function. If the `MessageType` is `OracleAQMessageType.UDT`, then the `UdtTypeName` property must be set as well.

The size of the returned array may be less than the `dequeueCount`. It depends on the actual number of messages present in the queue.

For database versions earlier than Oracle Database 12c Release 1 (12.1), the `MessageId` property of persistent `OracleAQMessage` objects retrieved using `DequeueArray` is always `null`.

Dequeued buffered messages always have `null` `MessageId` values irrespective of the database version.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Dispose

This method releases any resources or memory allocated by the object.

Declaration

```
// C#  
public void Dispose();
```

Implements

`IDisposable`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Enqueue

`Enqueue` instance methods enqueue messages to queues.

Overload List

- [Enqueue\(OracleAQMessage\)](#)

This instance method enqueues messages to a queue using the `EnqueueOptions` of the instance.

- [Enqueue\(OracleAQMessage, OracleAQEnqueueOptions\)](#)

This instance method enqueues messages to a queue using the supplied enqueue options.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Enqueue(OracleAQMessage)

This instance method enqueues messages to a queue using the `EnqueueOptions` of the instance.

Declaration

```
// C#
public void Enqueue(OracleAQMessage message);
```

Parameters

- *message*

An `OracleAQMessage` object.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The connection is not open.

`ArgumentNullException` - The message parameter is null.

`ArgumentException` - The message payload is `OracleXmlType` and the connection used to create `OracleXmlType` is different from the queue's connection.

Remarks

`MessageId` of the enqueued message is populated after the call to `Enqueue` completes. Enqueued buffered messages always have null `MessageId` values.

The `MessageType` property needs to be set appropriately before calling this function. If the `MessageType` is `OracleAQMessageType.UDT`, then the `UdtTypeName` property must be set as well.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Enqueue(OracleAQMessage, OracleAQEnqueueOptions)

This instance method enqueues messages to a queue using the supplied enqueue options.

Declaration

```
// C#  
public void Enqueue(OracleAQMessage message, OracleAQEnqueueOptions  
enqueueOptions);
```

Parameters

- *message*
An OracleAQMessage object.
- *enqueueOptions*
An OracleAQEnqueueOptions object.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The connection is not open.

ArgumentNullException - The message parameter is null.

ArgumentException - The message payload is OracleXmlType and the connection used to create OracleXmlType is different from the queue's connection.

Remarks

If the supplied enqueueOptions object is null, then the enqueue options default values are used. The EnqueueOptions property of the queue object is ignored in this operation.

The MessageId of the enqueued message is populated after the call to Enqueue completes. Enqueued buffered messages always have null MessageId values. Calling this method does not change the EnqueueOptions property of the queue.

The MessageType property must be set appropriately before calling this function. If the MessageType is OracleAQMessageType.UDT, then the UdtTypeName property must also be set.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

EnqueueArray

EnqueueArray instance methods enqueue multiple messages to a queue.

Overload List

- [EnqueueArray\(OracleAQMessage\[\]\)](#)
This instance method enqueues multiple messages to a queue using the EnqueueOptions of the instance.

- [EnqueueArray\(OracleAQMessage\[\], OracleAQEnqueueOptions\)](#)

This instance method enqueues multiple messages to a queue using the supplied enqueue options.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

EnqueueArray(OracleAQMessage[])

This instance method enqueues multiple messages to a queue using the `EnqueueOptions` of the instance.

Declaration

```
// C#
public int EnqueueArray(OracleAQMessage[] messages);
```

Parameters

- *messages*
An array of `OracleAQMessage` objects.

Return Value

An integer representing the number of messages actually enqueued.

Exceptions

`ArgumentNullException` - The message parameter is null.

`ArgumentException` - At least one of the `OracleAQMessage[]` elements is null, or at least one of the `OracleAQMessage[]` elements has a payload of `OracleXmlType`, which is created using a connection that is different from the queue's connection.

`InvalidOperationException` - The `OracleAQMessage` array is empty or the connection is not open.

`ObjectDisposedException` - The object is already disposed.

Remarks

This method is supported by Oracle Database 10g and higher releases. The `MessageId` properties of the enqueued messages are populated after the call to `Enqueue` completes. Enqueued buffered messages always have null `MessageId` values.

The `MessageType` property must be set appropriately before calling this function. If the `MessageType` is `OracleAQMessageType.UDT`, then the `UdtTypeName` property must also be set.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

EnqueueArray(OracleAQMessage[], OracleAQEnqueueOptions)

This instance method enqueues multiple messages to a queue using the supplied enqueue options.

Declaration

```
// C#  
public int EnqueueArray(OracleAQMessage[] messages, OracleAQEnqueueOptions  
    enqueueOptions);
```

Parameters

- *messages*
An array of OracleAQMessage objects.
- *enqueueOptions*
An OracleAQEnqueueOptions object.

Return Value

An integer representing the number of messages actually enqueued.

Exceptions

ArgumentNullException - The message parameter is null.

ArgumentException - At least one of the OracleAQMessage[] elements is null, or at least one of the OracleAQMessage[] elements has a payload of OracleXmlType, which is created using a connection that is different from the queue's connection.

InvalidOperationException - The OracleAQMessage array is empty or the connection is not open.

ObjectDisposedException - The object is already disposed.

Remarks

This method is supported by Oracle Database 10g and higher releases. MessageId properties of the enqueued messages are populated after the call to Enqueue completes. Enqueued buffered messages always have null MessageId values. Calling this method does not change the EnqueueOptions property of the queue.

If the supplied enqueueOptions object is null, then the enqueue options default values are used. The EnqueueOptions property of the queue object is ignored in this operation.

The MessageType property must be set appropriately before calling this function. If the MessageType is OracleAQMessageType.UDT, then the UdtTypeName property must also be set.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Listen

Listen methods listen for messages on the queue on behalf of listenConsumers.

Overload List

- [Listen\(string\[\]\)](#)
This method listens for messages on the queue on behalf of `listenConsumers`.
- [Listen \(string\[\], int\)](#)
This method listens for messages on behalf of `listenConsumers` for a specified time.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Listen(string[])

This method listens for messages on the queue on behalf of `listenConsumers`.

Declaration

```
// C#
public string Listen(string[] listenConsumers);
```

Parameters

- *listenConsumers*
An array of consumers to listen for on this queue. This parameter should be null in case of single consumer queues.

Return Value

A string.

Exceptions

`InvalidOperationException` - The connection is not open.
`ObjectDisposedException` - The object is already disposed.

Remarks

This call blocks the calling thread until there is a message ready for consumption for a consumer in the `listenConsumers` array. It returns a string representing the consumer name for which the message is ready.

`Listen` is useful in situations that require waiting until a message is available in the queue for consumers whose names are specified in `listenConsumers`.

Example

The following example demonstrates using the `Listen` method. The first part of the example performs the requisite database setup for the database user, `SCOTT`. The second part of the example demonstrates how a thread can listen and wait until a message is enqueued.

```
-- Part I: Database setup required for this demo
```

```
-----
-- SQL to grant appropriate privilege to database user, SCOTT
```

```
-----
SQL> ALTER USER SCOTT ACCOUNT UNLOCK IDENTIFIED BY Pwd4Sct;
User altered.
GRANT ALL ON DBMS_AQADM TO scott;

-----
-- PLSQL to create queue-table and queue and start queue for SCOTT
-----
BEGIN
  DBMS_AQADM.CREATE_QUEUE_TABLE(
    queue_table=>'scott.test_q_tab',
    queue_payload_type=>'RAW',
    multiple_consumers=>FALSE);

  DBMS_AQADM.CREATE_QUEUE(
    queue_name=>'scott.test_q',
    queue_table=>'scott.test_q_tab');

  DBMS_AQADM.START_QUEUE(queue_name=>'scott.test_q');
END;
/

-----
-- PLSQL to stop queue and drop queue & queue-table from SCOTT
-----
BEGIN
  DBMS_AQADM.STOP_QUEUE('scott.test_q');

  DBMS_AQADM.DROP_QUEUE(
    queue_name => 'scott.test_q',
    auto_commit => TRUE);

  DBMS_AQADM.DROP_QUEUE_TABLE(
    queue_table => 'scott.test_q_tab',
    force => FALSE,
    auto_commit => TRUE);
END;
/
-- End of Part I, database setup.

//Part II: Demonstrates using the Listen method
//C#
using System;
using System.Text;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;
using System.Threading;

namespace ODPSample
{
  /// <summary>
  /// Demonstrates how a thread can listen and wait until a message is enqueued.
  /// Once a message is enqueued, the listening thread returns from the
  /// blocked Listen() method invocation and dequeues the message.
  /// </summary>
  class EnqueueDequeue
  {
    static bool s_bListenReturned = false;

    static void Main(string[] args)
```



```
{
    // Create connection
    string constr = "user id=scott;password=Pwd4Sct;data source=oracle";
    OracleConnection con = new OracleConnection(constr);

    // Create queue
    OracleAQQueue queue = new OracleAQQueue("scott.test_q", con);

    try
    {
        // Open connection
        con.Open();

        // Set message type for the queue
        queue.MessageType = OracleAQMessageType.Raw;

        // Spawning a thread which will listen for a message
        ThreadStart ts = new ThreadStart(TestListen);
        Thread t = new Thread(ts);
        t.Start();

        System.Threading.Thread.Sleep(2000);

        // Begin transaction for enqueue
        OracleTransaction txn = con.BeginTransaction();

        // Prepare message and RAW payload
        OracleAQMessage enqMsg = new OracleAQMessage();
        byte[] bytePayload = { 0, 1, 2, 3, 4, 5, 6, 7, 8, 9 };
        enqMsg.Payload = bytePayload;

        // Prepare to Enqueue
        queue.EnqueueOptions.Visibility = OracleAQVisibilityMode.OnCommit;

        Console.WriteLine("[Main Thread]   Enqueuing a message...");
        Console.WriteLine("[Main Thread]   Enqueued Message Payload       : "
            + ByteArrayToString(enqMsg.Payload as byte[]));
        Console.WriteLine();

        // Enqueue message
        queue.Enqueue(enqMsg);

        // Enqueue transaction commit
        txn.Commit();

        // Loop till Listen returns
        while (!s_bListenReturned)
            System.Threading.Thread.Sleep(1000);
    }
    catch (Exception e)
    {
        Console.WriteLine("Error: {0}", e.Message);
    }
    finally
    {
        // Close/Dispose objects
        queue.Dispose();
        con.Close();
        con.Dispose();
    }
}
```

```
    }

    static void TestListen()
    {
        // Create connection
        string constr = "user id=scott;password=Pwd4Sct;data source=oracle";
        OracleConnection conListen = new OracleConnection(constr);

        // Create queue
        OracleAQQueue queueListen = new OracleAQQueue("scott.test_q", conListen);

        try
        {
            // Open the connection for Listen thread.
            // Connection blocked on Listen thread can not be used for other DB
            // operations
            conListen.Open();

            // Set message type for the queue
            queueListen.MessageType = OracleAQMessageType.Raw;

            // Listen
            queueListen.Listen(null);

            Console.WriteLine("[Listen Thread] Listen returned... Dequeuing...");

            // Begin txn for Dequeue
            OracleTransaction txn = conListen.BeginTransaction();

            // Prepare to Dequeue
            queueListen.DequeueOptions.Visibility = OracleAQVisibilityMode.OnCommit;
            queueListen.DequeueOptions.Wait = 10;

            // Dequeue message
            OracleAQMessage deqMsg = queueListen.Dequeue();
            Console.WriteLine("[Listen Thread] Dequeued Message Payload      : "
                + ByteArrayToString(deqMsg.Payload as byte[]));

            // Dequeue txn commit
            txn.Commit();

            // Allow the main thread to exit
            s_bListenReturned = true;
        }
        catch (Exception e)
        {
            Console.WriteLine("Error: {0}", e.Message);
        }
        finally
        {
            // Close/Dispose objects
            queueListen.Dispose();
            conListen.Close();
            conListen.Dispose();
        }
    }

    // Function to convert byte[] to string
    static private string ByteArrayToString(byte[] byteArray)
    {
```

```

        StringBuilder sb = new StringBuilder();
        for (int n = 0; n < byteArray.Length; n++)
        {
            sb.Append((int.Parse(byteArray[n].ToString())).ToString("X"));
        }
        return sb.ToString();
    }
}
}

```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

Listen (string[], int)

This method listens for messages on behalf of `listenConsumers` for a specified time.

Declaration

```

// C#
public string Listen(string[] listenConsumers, int waitTime);

```

Parameters

- *listenConsumers*
Array of consumers for which to listen on this queue.
- *waitTime*
Wait time in seconds.

Return Value

A string

Exceptions

`InvalidOperationException` - The connection is not open.

`ArgumentException` - `waitTime` is less than -1.

`ObjectDisposedException` - The object is already disposed.

Remarks

`Listen` is useful in situations that require waiting until a message is available in the queue for consumers whose names are specified in `listenConsumers`.

This call blocks the calling thread until there is a message ready for consumption for a consumer in the `listenConsumers` array. It returns a string representing the consumer name for which the message is ready. The method returns null if a timeout occurs.

The `listenConsumers` parameter should be null for single consumer queues. An empty string is returned in such cases.

A `waitTime` of -1 implies infinite wait time.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

OracleAQQueue Events

The OracleAQQueue event is listed in [Table 12–30](#).

Table 12–30 OracleAQQueue Events

| Event Name | Description |
|---------------------------------------|------------------------------------------------------------------------------|
| MessageAvailableEvent | Notifies when a message is available in the queue for NotificationConsumers. |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

MessageAvailable Event

This event is notified when a message is available in the queue for NotificationConsumers.

Declaration

```
// C#
public event OracleAQMessageAvailableEventHandler MessageAvailable;
```

Event Data

The event handler receives an OracleAQMessageAvailableEventArgs object.

Exceptions

InvalidOperationException - The connection is not open.

Remarks

Asynchronous notification is supported in all queue tables created with a database compatibility level of 8.1 or higher.

In order to receive the notification about message availability, the client must create an OracleAQMessageAvailableEventHandler delegate to listen to this event. The delegate should be added to this event only after setting the [NotificationConsumers](#) and [Notification](#) properties.

The notification registration takes place after the first delegate is added to the event. The notification is unregistered when the last delegate is removed from the event. Notifications set on an OracleAQQueue object get cancelled automatically when the object gets disposed.

Oracle Data Provider for .NET opens a port to listen for notifications. HA events, load balancing, and continuous query notification features also share the same port. This port can be configured centrally by setting the database notification port in an application or Web configuration file. The following example code specifies a port number of 1200:

```
<configuration>
  <oracle.dataaccess.client>
```

```
<settings>
  <add name="DbNotificationPort" value="1200"/>
</settings>
</oracle.dataaccess.client>
</configuration>
```

If the configuration file does not exist or the db notification port is not specified, then ODP.NET uses a valid and random port number. The configuration file may also request for a random port number by specifying a db notification port value of -1.

The notification listener, which runs in the same application domain as ODP.NET, uses the specified port number to listen to notifications from the database. A notification listener gets created when the application registers with `OracleAQQueue.MessageAvailable` event. One notification listener can listen to all notification types. Only one notification listener is created for each application domain.

Example

The following example demonstrates application notification. The first part of the example performs the requisite database setup for the database user, SCOTT. The second part of the example demonstrates how an application is notified when a message is available in the queue.

```
-- Part I: Database setup required for this demo

-----
-- SQL to grant appropriate privilege to database user, SCOTT
-----
SQL> ALTER USER SCOTT ACCOUNT UNLOCK IDENTIFIED BY Pwd4Sct;
User altered.
SQL> GRANT ALL ON DBMS_AQADM TO scott;

-----
-- PLSQL to create queue-table and queue and start queue for SCOTT
-----
BEGIN
  DBMS_AQADM.CREATE_QUEUE_TABLE(
    queue_table=>'scott.test_q_tab',
    queue_payload_type=>'RAW',
    multiple_consumers=>FALSE);

  DBMS_AQADM.CREATE_QUEUE(
    queue_name=>'scott.test_q',
    queue_table=>'scott.test_q_tab');

  DBMS_AQADM.START_QUEUE(queue_name=>'scott.test_q');
END;
/

-----
-- PLSQL to stop queue and drop queue & queue-table from SCOTT
-----
BEGIN
  DBMS_AQADM.STOP_QUEUE('scott.test_q');

  DBMS_AQADM.DROP_QUEUE(
    queue_name => 'scott.test_q',
    auto_commit => TRUE);
```

```
DBMS_AQADM.DROP_QUEUE_TABLE(
    queue_table => 'scott.test_q_tab',
    force => FALSE,
    auto_commit => TRUE);
END;
/
-- End of Part I, database setup.

//Part II: Demonstrates application notification
//C#
using System;
using System.Text;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

namespace ODPSample
{
    /// <summary>
    /// Demonstrates how the application can be notified when a message is
    /// available in a queue.
    /// </summary>
    class Notification
    {
        static bool isNotified = false;

        static void Main(string[] args)
        {
            // Create connection
            string constr = "user id=scott;password=Pwd4Sct;data source=oracle";
            OracleConnection con = new OracleConnection(constr);

            // Create queue
            OracleAQQueue queue = new OracleAQQueue("scott.test_q", con);

            try
            {
                // Open connection
                con.Open();

                // Set message type for the queue
                queue.MessageType = OracleAQMessageType.Raw;

                // Add the event handler to handle the notification. The
                // MsgReceived method will be invoked when a message is enqueued
                queue.MessageAvailable +=
                    new OracleAQMessageAvailableEventHandler(Notification.MsgReceived);

                Console.WriteLine("Notification registered...");

                // Begin txn for enqueue
                OracleTransaction txn = con.BeginTransaction();

                Console.WriteLine("Now enqueueing message...");

                // Prepare message and RAW payload
                OracleAQMessage enqMsg = new OracleAQMessage();
                byte[] bytePayload = { 0, 1, 2, 3, 4, 5, 6, 7, 8, 9 };
                enqMsg.Payload = bytePayload;

                // Prepare to Enqueue
```

```
queue.EnqueueOptions.Visibility = OracleAQVisibilityMode.OnCommit;

// Enqueue message
queue.Enqueue(enqMsg);

Console.WriteLine("Enqueued Message Payload      : "
    + ByteArrayToString(enqMsg.Payload as byte[]));
Console.WriteLine("MessageId of Enqueued Message : "
    + ByteArrayToString(enqMsg.MessageId));
Console.WriteLine();

// Enqueue txn commit
txn.Commit();

// Loop while waiting for notification
while (isNotified == false)
{
    System.Threading.Thread.Sleep(2000);
}
}
catch (Exception e)
{
    Console.WriteLine("Error: {0}", e.Message);
}
finally
{
    // Close/Dispose objects
    queue.Dispose();
    con.Close();
    con.Dispose();
}
}

static void MsgReceived(object src, OracleAQMessageAvailableEventArgs arg)
{
    try
    {
        Console.WriteLine("Notification Received...");
        Console.WriteLine("QueueName : {0}", arg.QueueName);
        Console.WriteLine("Notification Type : {0}", arg.NotificationType);

//following type-cast to "byte[]" is required only for .NET 1.x
        byte[] notifiedMsgId = (byte[]) arg.MessageId[0];
        Console.WriteLine("MessageId of Notified Message : "
            + ByteArrayToString(notifiedMsgId));
        isNotified = true;
    }
    catch (Exception e)
    {
        Console.WriteLine("Error: {0}", e.Message);
    }
}

// Function to convert byte[] to string
static private string ByteArrayToString(byte[] byteArray)
{
    StringBuilder sb = new StringBuilder();
    for (int n = 0; n < byteArray.Length; n++)
    {
        sb.Append((int.Parse(byteArray[n].ToString()).ToString("X"));
    }
}
```



```
    }  
    return sb.ToString();  
  }  
}
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleAQQueue Class](#)
- [OracleAQQueue Members](#)

OracleAQDequeueMode Enumeration

Table 12–31 lists all the OracleAQDequeueMode enumeration values with a description of each enumerated value.

Table 12–31 OracleAQDequeueMode Members

| Member Name | Description |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| Browse | Reads the message without acquiring any lock on the message. This is equivalent to a SELECT statement. |
| Locked | Reads and obtains a write lock on the message. The lock lasts for the duration of the transaction. This is equivalent to a SELECT FOR UPDATE statement. |
| Remove | Reads the message and updates or deletes it. This is the default. The message can be retained in the queue table based on the retention properties |
| RemoveNoData | Confirms receipt of the message but does not deliver the actual message content. |

Requirements

| | |
|-----------------------|---------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | Oracle.DataAccess.dll |
| Namespace | Oracle.DataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- ["OracleAQDequeueOptions Class"](#) on page 12-8
- ["DequeueMode"](#) on page 12-14

OracleAQMessageDeliveryMode Enumeration

The `OracleAQMessageDeliveryMode` enumeration type specifies the delivery mode of the message.

[Table 12–32](#) lists all the `OracleAQMessageDeliveryMode` enumeration values with a description of each enumerated value.

Table 12–32 OracleAQMessageDeliveryMode Members

| Member Name | Description |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Buffered | <p>Indicates a buffered message.</p> <p>Both enqueue and dequeue buffered messaging operations must be in <code>IMMEDIATE</code> visibility mode. This means that these operations cannot be part of another transaction. You cannot specify <code>delay</code> when enqueueing buffered messages.</p> <p>Dequeuing applications can choose to dequeue persistent messages only, buffered messages only, or both types.</p> <p>Buffered messages can be queried using the <code>AQ\$Queue_Table_Name</code> view. These messages appear with states, <code>IN-MEMORY</code> or <code>SPILLED</code>.</p> <p>Transaction grouping queues and array enqueues are not supported for buffered messages in Oracle Database 11g release 1 (11.1). One can still use the array enqueue procedure to enqueue buffered messages, but the array size must be set to 1. Array dequeue is not supported for buffered messaging, but one can still use the array dequeue procedure by setting array size to 1.</p> <p>Buffered messaging is faster than persistent messaging. Use buffered messaging for applications that do not require the reliability and transaction support of Oracle Streams AQ persistent messaging.</p> |
| Persistent | <p>Indicates a persistent message.</p> <p>Persistent messaging ensures reliability and support transactions. It is slower than buffered messaging.</p> |
| PersistentOrBuffered | <p>Indicates a persistent or buffered message.</p> <p>This is used with <code>Dequeue()</code> when a consumer wants to dequeue a message irrespective of whether it is <code>Persistent</code> or <code>Buffered</code>.</p> |

Requirements

| | |
|-----------------------|---------------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | <code>Oracle.DataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Client</code> |
| .NET Framework | 3.5, 4.0, 4.5 |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- ["OracleAQDequeueOptions Class"](#) on page 12-8
- ["DeliveryMode"](#) on page 12-13

OracleAQMessageState Enumeration

The `OracleAQMessageState` enumeration type identifies the state of the message at the time of dequeue.

[Table 12-33](#) lists all the `OracleAQMessageState` enumeration values with a description of each enumerated value.

Table 12-33 OracleAQMessageState Members

| Member Name | Description |
|-------------|-------------------------------------------------------------------|
| Expired | Indicates that the message has been moved to the exception queue. |
| Processed | Indicates that the message has been processed and retained. |
| Ready | Indicates that the message is ready to be processed. |
| Waiting | Indicates that the message delay has not been reached. |

Requirements

| | |
|----------------|---------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | Oracle.DataAccess.dll |
| Namespace | Oracle.DataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- ["OracleAQMessage Class"](#) on page 12-25
- ["State"](#) on page 12-36

OracleAQMessageType Enumeration

The `OracleAQMessageType` enumeration type specifies the message payload type.

[Table 12-34](#) lists all the `OracleAQMessageType` enumeration values with a description of each enumerated value.

Table 12-34 OracleAQMessageType Members

| Member Name | Description |
|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Raw | Indicates the Raw message type. The data type of the payload must be either <code>OracleBinary</code> or <code>byte[]</code> to enqueue the message. |
| Udt | Indicates the Oracle UDT message type. The ODP.NET AQ implementation currently does not support user defined types with LOB attributes. It also does not support other variants of user defined types such as <code>VARRAY</code> and nested tables, as Oracle Streams AQ does not support them inherently. |
| Xml | Indicates the XML message type. The data type of the payload must be <code>OracleXmlType</code> , <code>XmlReader</code> , or <code>String</code> in order to enqueue the message. If the data type is <code>String</code> , it must be well-formed XML, else an exception is raised when enqueueing the message. |

Requirements

| | |
|----------------|---------------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | <code>Oracle.DataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Client</code> |
| .NET Framework | 3.5, 4.0, 4.5 |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- ["OracleAQQueue Class"](#) on page 12-48
- ["OracleAQQueue Constructors"](#) on page 12-51
- ["MessageType"](#) on page 12-60

OracleAQNavigationMode Enumeration

Table 12–35 lists all the OracleAQNavigationMode enumeration values with a description of each enumerated value.

Table 12–35 OracleAQNavigationMode Members

| Member Name | Description |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| FirstMessage | Retrieves the first message that is available and matches the search criteria. This resets the position to the beginning of the queue. |
| FirstMessageMultiGroup | Indicates that a call to DequeueArray resets the position to the beginning of the queue, and dequeues messages that are available and match the search criteria. Messages are dequeued till the dequeueCount limit is reached. The dequeued messages can belong to different transaction groups. You can use the OracleAQMessage.TransactionGroup property to distinguish between messages from different transaction groups. All messages from the same transaction group have the same value for the OracleAQMessage.TransactionGroup property. |
| NextMessage | Retrieves the next message that is available and matches the search criteria. If the previous message belongs to a message group, AQ retrieves the next available message that matches the search criteria and belongs to the message group. |
| NextMessageMultiGroup | Indicates that a call to DequeueArray dequeues the next set of messages that are available and match the search criteria. Messages are dequeued till the dequeueCount limit is reached. The dequeued messages can belong to different transaction groups. You can use the OracleAQMessage.TransactionGroup property to distinguish between messages from different transaction groups. All messages from the same transaction group have the same value for the OracleAQMessage.TransactionGroup property. |
| NextTransaction | Skips the remainder of the current transaction group (if any) and retrieves the first message of the next transaction group. |

Requirements

| | |
|-----------------------|----------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | Oracle.DataAccess.dll |
| Namespace | Oracle.DataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- ["OracleAQDequeueOptions Class"](#) on page 12-8
- ["NavigationMode"](#) on page 12-15

OracleAQNotificationGroupingType Enumeration

The `OracleAQNotificationGroupingType` enumeration type specifies the notification grouping type.

[Table 12–36](#) lists all the `OracleAQNotificationGroupingType` enumeration values with a description of each enumerated value.

Table 12–36 OracleAQNotificationGroupingType Members

| Member Name | Description |
|-------------|-----------------------------------------------------------------------------------------|
| Last | Indicates that only details of the last message in the notification group are provided. |
| Summary | Indicates that the Summary of all messages in the notification group is provided. |

Requirements

| | |
|----------------|---------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | Oracle.DataAccess.dll |
| Namespace | Oracle.DataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- ["OracleNotificationRequest Class"](#) on page 9-22

OracleAQNotificationType Enumeration

The `OracleAQNotificationType` enumeration type specifies the notification type of the received notification.

[Table 12-37](#) lists all the `OracleAQNotificationType` enumeration values with a description of each enumerated value.

Table 12-37 OracleAQNotificationType Members

| Member Name | Description |
|-------------|----------------------------------------------------------------------|
| Group | Indicates that the received notification is a grouping notification. |
| Regular | Indicates that the received notification is a regular notification. |
| Timeout | Indicates that the received notification is raised due to a timeout. |

Requirements

| | |
|----------------|---------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | Oracle.DataAccess.dll |
| Namespace | Oracle.DataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5

OracleAQVisibilityMode Enumeration

[Table 12–38](#) lists all the OracleAQVisibilityMode enumeration values with a description of each enumerated value.

Table 12–38 OracleAQVisibilityMode Members

| Member Name | Description |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| Immediate | Indicates that the enqueue or dequeue operation is not part of the current transaction. The operation constitutes a transaction of its own. |
| OnCommit | Indicates that the enqueue or dequeue operation is part of the current transaction. This is the default case. |

Requirements

| | |
|----------------|---------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | Oracle.DataAccess.dll |
| Namespace | Oracle.DataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5

Oracle Data Provider for .NET Types Classes

This chapter describes the large object and `REF CURSOR` objects provided by Oracle Data Provider for .NET.

This chapter contains these topics:

- ODP.NET Types (ODP.NET LOB objects) consisting of these object classes:
 - [OracleBFile Class](#)
 - [OracleBlob Class](#)
 - [OracleClob Class](#)
- [OracleRefCursor Class](#)

All offsets are 0-based for all ODP.NET LOB object parameters.

OracleBFile Class

An OracleBFile is an object that has a reference to BFILE data. It provides methods for performing operations on BFILES.

Note: OracleBFile is supported for applications running against Oracle8.x and later.

Class Inheritance

System.Object

System.MarshalByRefObject

System.IO.Stream

Oracle.DataAccess.Types.OracleBFile

Declaration

```
// C#
public sealed class OracleBFile : Stream, ICloneable, INullable
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|--------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Types | Oracle.ManagedDataAccess.Types |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

OracleBFile is supported for applications running against Oracle8.x and later.

Example

```
// Database Setup, if you have not done so yet.
/* Log on as DBA (SYS or SYSTEM) that has CREATE ANY DIRECTORY privilege.

CREATE OR REPLACE DIRECTORY MYDIR AS 'C:\TEMP';

*/

// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class OracleBFileSample
{
    static void Main()
```

```
{
    // Create MYDIR directory object as indicated previously and create a file
    // MyFile.txt with the text ABCDABC under C:\TEMP directory.
    // Note that the byte representation of the ABCDABC is 65666768656667

    string constr = "User Id=scott;Password=tiger;Data Source=oracle";
    OracleConnection con = new OracleConnection(constr);
    con.Open();

    OracleBFile bFile = new OracleBFile(con, "MYDIR", "MyFile.txt");

    // Open the OracleBFile
    bFile.OpenFile();

    // Read 7 bytes into readBuffer, starting at buffer offset 0
    byte[] readBuffer = new byte[7];
    int bytesRead = bFile.Read(readBuffer, 0, 7);

    // Prints "bytesRead = 7"
    Console.WriteLine("bytesRead = " + bytesRead);

    // Prints "readBuffer = 65666768656667"
    Console.Write("readBuffer = ");
    for(int index = 0; index < readBuffer.Length; index++)
    {
        Console.Write(readBuffer[index]);
    }
    Console.WriteLine();

    // Search for the 2nd occurrence of a byte pattern {66,67}
    // starting from byte offset 1 in the OracleBFile
    byte[] pattern = new byte[2] {66, 67};
    long posFound = bFile.Search(pattern, 1, 2);

    // Prints "posFound = 6"
    Console.WriteLine("posFound = " + posFound);

    // Close the OracleBFile
    bFile.CloseFile();

    bFile.Close();
    bFile.Dispose();

    con.Close();
    con.Dispose();
}
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleBFile Members](#)
- [OracleBFile Constructors](#)
- [OracleBFile Static Fields](#)
- [OracleBFile Static Methods](#)
- [OracleBFile Instance Properties](#)
- [OracleBFile Instance Methods](#)

OracleBFile Members

OracleBFile members are listed in the following tables.

OracleBFile Constructors

OracleBFile constructors are listed in [Table 13-1](#).

Table 13-1 OracleBFile Constructors

| Constructor | Description |
|------------------------------------------|-----------------------------------------------------------|
| OracleBFile Constructors | Creates an instance of the OracleBFile class (Overloaded) |

OracleBFile Static Fields

OracleBFile static fields are listed in [Table 13-2](#).

Table 13-2 OracleBFile Static Fields

| Field | Description |
|-------------------------|--------------------------------------------------------------------------------------------------------------------|
| MaxSize | The static field holds the maximum number of bytes a BFILE can hold, which is 4,294,967,295 ($2^{32} - 1$) bytes |
| Null | Represents a null value that can be assigned to the value of an OracleBFile instance |

OracleBFile Static Methods

OracleBFile static methods are listed in [Table 13-3](#).

Table 13-3 OracleBFile Static Methods

| Methods | Description |
|------------------------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

OracleBFile Instance Properties

OracleBFile instance properties are listed in [Table 13-4](#).

Table 13-4 OracleBFile Instance Properties

| Properties | Description |
|-------------------------------|--------------------------------------------------------------------------------|
| CanRead | Indicates whether or not the LOB stream can be read |
| CanSeek | Indicates whether or not forward and backward seek operations can be performed |
| CanWrite | Indicates whether or not the LOB object supports writing |
| Connection | Indicates the connection used to read from a BFILE |
| DirectoryName | Indicates the directory alias of the BFILE |
| FileExists | Indicates whether or not the specified BFILE exists |
| FileName | Indicates the name of the BFILE |
| IsEmpty | Indicates whether the BFILE is empty or not |

Table 13–4 (Cont.) OracleBFile Instance Properties

| Properties | Description |
|--------------------------|--------------------------------------------------------------------------|
| IsNull | Indicates whether or not the current instance has a null value |
| IsOpen | Indicates whether the BFILE has been opened by this instance or not |
| Length | Indicates the size of the BFILE data in bytes |
| Position | Indicates the current read position in the LOB stream |
| Value | Returns the data, starting from the first byte in BFILE, as a byte array |

OracleBFile Instance Methods

OracleBFile instance methods are listed in [Table 13–5](#).

Table 13–5 OracleBFile Instance Methods

| Methods | Description |
|-------------------------------------------|------------------------------------------------------------------------------------------|
| BeginRead | Inherited from <code>System.IO.Stream</code> |
| BeginWrite | <i>Not Supported</i> |
| Clone | Creates a copy of an OracleBFile object |
| Close | Closes the current stream and releases any resources associated with the stream |
| CloseFile | Closes the BFILE referenced by the current BFILE instance |
| Compare | Compares data referenced by the two OracleBFiles |
| CreateObjRef | Inherited from <code>System.MarshalByRefObject</code> |
| CopyTo | Copies data as specified (Overloaded) |
| Dispose | Releases resources allocated by this object |
| EndRead | Inherited from <code>System.IO.Stream</code> |
| EndWrite | <i>Not Supported</i> |
| Equals | Inherited from <code>System.Object</code> (Overloaded) |
| Flush | <i>Not Supported</i> |
| GetHashCode | Inherited from <code>System.Object</code> |
| GetLifetimeService | Inherited from <code>System.MarshalByRefObject</code> |
| GetType | Inherited from <code>System.Object</code> |
| InitializeLifetimeService | Inherited from <code>System.MarshalByRefObject</code> |
| IsEqual | Compares the LOB references |
| OpenFile | Opens the BFILE specified by the <code>FileName</code> and <code>DirectoryName</code> |
| Read | Reads a specified amount of bytes from the OracleBFile instance and populates the buffer |
| ReadByte | Inherited from <code>System.IO.Stream</code> |
| Search | Searches for a binary pattern in the current instance of an OracleBFile |

Table 13–5 (Cont.) OracleBFile Instance Methods

| Methods | Description |
|----------------------|---------------------------------------------|
| Seek | Sets the position on the current LOB stream |
| SetLength | <i>Not Supported</i> |
| ToString | Inherited from <code>System.Object</code> |
| Write | <i>Not Supported</i> |
| WriteByte | <i>Not Supported</i> |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Members](#)

OracleBFile Constructors

OracleBFile constructors create new instances of the OracleBFile class.

Overload List:

- [OracleBFile\(OracleConnection\)](#)
This constructor creates an instance of the OracleBFile class with an OracleConnection object.
- [OracleBFile\(OracleConnection, string, string\)](#)
This constructor creates an instance of the OracleBFile class with an OracleConnection object, the location of the BFILE, and the name of the BFILE.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

OracleBFile(OracleConnection)

This constructor creates an instance of the OracleBFile class with an OracleConnection object.

Declaration

```
// C#  
public OracleBFile(OracleConnection con);
```

Parameters

- *con*
The OracleConnection object.

Exceptions

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

Remarks

The connection must be opened explicitly by the application. OracleBFile does not open the connection implicitly.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

OracleBFile(OracleConnection, string, string)

This constructor creates an instance of the OracleBFile class with an OracleConnection object, the location of the BFILE, and the name of the BFILE.

Declaration

```
// C#  
public OracleBFile(OracleConnection con, string directoryName, string  
    fileName);
```

Parameters

- *con*
The OracleConnection object.
- *directoryName*
The directory alias created by the CREATE DIRECTORY SQL statement.
- *fileName*
The name of the external LOB.

Exceptions

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

Remarks

The OracleConnection must be opened explicitly by the application. OracleBFile does not open the connection implicitly.

To initialize a BFILE column using an OracleBFile instance as an input parameter of a SQL INSERT statement, *directoryName* and *fileName* must be properly set.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

OracleBFile Static Fields

OracleBFile static fields are listed in [Table 13–6](#).

Table 13–6 OracleBFile Static Fields

| Field | Description |
|-------------------------|--------------------------------------------------------------------------------------------------------------------|
| MaxSize | The static field holds the maximum number of bytes a BFILE can hold, which is 4,294,967,295 ($2^{32} - 1$) bytes |
| Null | Represents a null value that can be assigned to the value of an OracleBFile instance |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

MaxSize

This static field holds the maximum number of bytes a BFILE can hold, which is 4,294,967,295 ($2^{32} - 1$) bytes.

Declaration

```
// C#  
public static readonly Int64 MaxSize = 4294967295;
```

Remarks

This field is useful in code that checks whether or not the operation exceeds the maximum length allowed.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

Null

This static field represents a null value that can be assigned to the value of an OracleBFile instance.

Declaration

```
// C#  
public static readonly OracleBFile Null;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

OracleBFile Static Methods

OracleBFile static methods are listed in [Table 13-7](#).

Table 13-7 OracleBFile Static Methods

| Methods | Description |
|---------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

OracleBFile Instance Properties

OracleBFile instance properties are listed in [Table 13–8](#).

Table 13–8 OracleBFile Instance Properties

| Properties | Description |
|-------------------------------|--------------------------------------------------------------------------------|
| CanRead | Indicates whether or not the LOB stream can be read |
| CanSeek | Indicates whether or not forward and backward seek operations can be performed |
| CanWrite | Indicates whether or not the LOB object supports writing |
| Connection | Indicates the connection used to read from a BFILE |
| DirectoryName | Indicates the directory alias of the BFILE |
| FileExists | Indicates whether or not the specified BFILE exists |
| FileName | Indicates the name of the BFILE |
| IsEmpty | Indicates whether the BFILE is empty or not |
| IsNull | Indicates whether or not the current instance has a null value |
| IsOpen | Indicates whether the BFILE has been opened by this instance or not |
| Length | Indicates the size of the BFILE data in bytes |
| Position | Indicates the current read position in the LOB stream |
| Value | Returns the data, starting from the first byte in BFILE, as a byte array |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

CanRead

Overrides [Stream](#)

This instance property indicates whether or not the LOB stream can be read.

Declaration

```
// C#
public override bool CanRead{get;}
```

Property Value

If the LOB stream can be read, returns `true`; otherwise, returns `false`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

CanSeek

Overrides `Stream`

This instance property indicates whether or not forward and backward seek operations can be performed.

Declaration

```
// C#  
public override bool CanSeek{get;}
```

Property Value

If forward and backward seek operations can be performed, returns `true`; otherwise, returns `false`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

CanWrite

Overrides `Stream`

This instance property indicates whether or not the LOB object supports writing.

Declaration

```
// C#  
public override bool CanWrite{get;}
```

Property Value

BFILE is read only.

Remarks

BFILE is read-only, therefore, the boolean value is always `false`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

Connection

This instance property indicates the connection used to read from a BFILE.

Declaration

```
// C#  
public OracleConnection Connection {get;}
```

Property Value

An object of `OracleConnection`.

Exceptions

ObjectDisposedException - The object is already disposed.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

DirectoryName

This instance property indicates the directory alias of the BFILE.

Declaration

```
// C#  
public string DirectoryName {get;set;}
```

Property Value

A string.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The value of the DirectoryName changed while the BFILE is open.

Remarks

The maximum length of a DirectoryName is 30 bytes.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

FileExists

This instance property indicates whether or not the BFILE specified by the DirectoryName and FileName exists.

Declaration

```
// C#  
public bool FileExists {get;}
```

Property Value

bool

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

Remarks

Unless a connection, file name, and directory name are provided, this property is set to false by default.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

FileName

This instance property indicates the name of the BFILE.

Declaration

```
// C#  
public string FileName {get;set}
```

Property Value

A string that contains the BFILE name.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The value of the DirectoryName changed while the BFILE is open.

Remarks

The maximum length of a FileName is 255 bytes.

Changing the FileName property while the BFILE object is opened causes an exception.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

IsEmpty

This instance property indicates whether the BFILE is empty or not.

Declaration

```
// C#  
public bool IsEmpty {get;}
```

Property Value

bool

Exceptions

ObjectDisposedException - The object is already disposed.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

IsNull

This property indicates whether or not the current instance has a null value.

Declaration

```
// C#  
public bool IsNull{get;}
```

Property Value

Returns true if the current instance has a null value; otherwise, returns false.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

IsOpen

This instance property indicates whether the BFILE has been opened by this instance or not.

Declaration

```
// C#  
public bool IsOpen {get;}
```

Property Value

A bool.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

Length

Overrides Stream

This instance property indicates the size of the BFILE data in bytes.

Declaration

```
// C#  
public override Int64 Length {get;}
```

Property Value

Int64

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

Position

Overrides Stream

This instance property indicates the current read position in the LOB stream.

Declaration

```
// C#  
public override Int64 Position{get; set;}
```

Property Value

An Int64 value that indicates the read position.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

ArgumentOutOfRangeException - The value is less than 0.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

Value

This instance property returns the data, starting from the first byte in BFILE, as a byte array.

Declaration

```
// C#  
public byte[] Value{get;}
```

Property Value

A byte array.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

Remarks

The length of data is bound by the maximum length of the byte array. The current value of the Position property is not used or changed.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

OracleBFile Instance Methods

OracleBFile instance methods are listed in [Table 13–9](#).

Table 13–9 OracleBFile Instance Methods

| Methods | Description |
|---------------------------|------------------------------------------------------------------------------------------|
| BeginRead | Inherited from <code>System.IO.Stream</code> |
| BeginWrite | <i>Not Supported</i> |
| Clone | Creates a copy of an OracleBFile object |
| Close | Closes the current stream and releases any resources associated with the stream |
| CloseFile | Closes the BFILE referenced by the current BFILE instance |
| Compare | Compares data referenced by the two OracleBFiles |
| CreateObjRef | Inherited from <code>System.MarshalByRefObject</code> |
| CopyTo | Copies data as specified (Overloaded) |
| Dispose | Releases resources allocated by this object |
| EndRead | Inherited from <code>System.IO.Stream</code> |
| EndWrite | <i>Not Supported</i> |
| Equals | Inherited from <code>System.Object</code> (Overloaded) |
| Flush | <i>Not Supported</i> |
| GetHashCode | Inherited from <code>System.Object</code> |
| GetLifetimeService | Inherited from <code>System.MarshalByRefObject</code> |
| GetType | Inherited from <code>System.Object</code> |
| InitializeLifetimeService | Inherited from <code>System.MarshalByRefObject</code> |
| IsEqual | Compares the LOB references |
| OpenFile | Opens the BFILE specified by the <code>FileName</code> and <code>DirectoryName</code> |
| Read | Reads a specified amount of bytes from the OracleBFile instance and populates the buffer |
| ReadByte | Inherited from <code>System.IO.Stream</code> |
| Search | Searches for a binary pattern in the current instance of an OracleBFile |
| Seek | Sets the position on the current LOB stream |
| SetLength | <i>Not Supported</i> |
| ToString | Inherited from <code>System.Object</code> |
| Write | <i>Not Supported</i> |
| WriteByte | <i>Not Supported</i> |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleBFile Class](#)
- [OracleBFile Members](#)

Clone

This instance method creates a copy of an OracleBFile object.

Declaration

```
// C#
public object Clone();
```

Return Value

An OracleBFile object.

Implements

ICloneable

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

Remarks

The cloned object has the same property values as that of the object being cloned.

Example

```
// Database Setup, if you have not done so yet.
/* Log on as DBA (SYS or SYSTEM) that has CREATE ANY DIRECTORY privilege.

CREATE OR REPLACE DIRECTORY MYDIR AS 'C:\TEMP';

*/

// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class CloneSample
{
    static void Main()
    {
        // Create MYDIR directory object as indicated above and create a file
        // MyFile.txt with the text ABCDABC under C:\TEMP directory.
        // Note that the byte representation of the ABCDABC is 65666768656667

        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();
```

```
OracleBFile bFile1 = new OracleBFile(con, "MYDIR", "MyFile.txt");

// Open the OracleBFile
bFile1.OpenFile();

// Prints "bFile1.Position = 0"
Console.WriteLine("bFile1.Position = " + bFile1.Position);

// Set the Position before calling Clone()
bFile1.Position = 1;

// Clone the OracleBFile
OracleBFile bFile2 = (OracleBFile) bFile1.Clone();

// Open the OracleBFile
bFile2.OpenFile();

// Prints "bFile2.Position = 1"
Console.WriteLine("bFile2.Position = " + bFile2.Position);

// Close the OracleBFile
bFile1.CloseFile();

bFile1.Close();
bFile1.Dispose();

// Close the Cloned OracleBFile
bFile2.CloseFile();

bFile2.Close();
bFile2.Dispose();

con.Close();
con.Dispose();
}
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

Close

Overrides Stream

This instance method closes the current stream and releases any resources associated with it.

Declaration

```
// C#
public override void Close();
```

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

CloseFile

This instance method closes the BFILE referenced by the current BFILE instance.

Declaration

```
// C#  
public void CloseFile();
```

Remarks

No error is returned if the BFILE exists, but is not opened.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

Compare

This instance method compares data referenced by the two OracleBFiles.

Declaration

```
// C#  
public int Compare(Int64 src_offset, OracleBFile obj, Int64 dst_offset,  
    Int64 amount);
```

Parameters

- *src_offset*
The offset of the current instance.
- *obj*
The provided OracleBFile object.
- *dst_offset*
The offset of the OracleBFile object.
- *amount*
The number of bytes to compare.

Return Value

Returns a number that is:

- Less than zero: if the BFILE data of the current instance is less than that of the provided BFILE data.
- Zero: if both the BFILES store the same data.
- Greater than zero: if the BFILE data of the current instance is greater than that of the provided BFILE data.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - The `src_offset`, the `dst_offset`, or the `amount` is less than 0.

Remarks

The provided object and the current instance must be using the same connection, that is, the same `OracleConnection` object.

The BFILE needs to be opened using `OpenFile` before the operation.

Example

```
// Database Setup, if you have not done so yet.
/* Log on as DBA (SYS or SYSTEM) that has CREATE ANY DIRECTORY privilege.

CREATE OR REPLACE DIRECTORY MYDIR AS 'C:\TEMP';

*/

// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class CompareSample
{
    static void Main()
    {
        // Create MYDIR directory object as indicated previously and create a file
        // MyFile.txt with the text ABCDABC under C:\TEMP directory.
        // Note that the byte representation of the ABCDABC is 65666768656667

        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBFile bFile1 = new OracleBFile(con, "MYDIR", "MyFile.txt");
        OracleBFile bFile2 = new OracleBFile(con, "MYDIR", "MyFile.txt");

        // Open the OracleBFiles
        bFile1.OpenFile();
        bFile2.OpenFile();

        // Compare 2 bytes from the 1st byte of bFile1 and
        // the 5th byte of bFile2 onwards
        int result = bFile1.Compare(1, bFile2, 5, 2);
    }
}
```

```

// Prints "result = 0" (Indicates the data is identical)
Console.WriteLine("result = " + result);

// Close the OracleBFiles
bFile1.CloseFile();
bFile2.CloseFile();

bFile1.Close();
bFile1.Dispose();

bFile2.Close();
bFile2.Dispose();

con.Close();
con.Dispose();
}
}

```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

CopyTo

CopyTo copies data from the current instance to the provided object.

Overload List:

- [CopyTo\(OracleBlob\)](#)
This instance method copies data from the current instance to the provided OracleBlob object.
- [CopyTo\(OracleBlob, Int64\)](#)
This instance method copies data from the current OracleBFile instance to the provided OracleBlob object with the specified destination offset.
- [CopyTo\(Int64, OracleBlob, Int64, Int64\)](#)
This instance method copies data from the current OracleBFile instance to the provided OracleBlob object with the specified source offset, destination offset, and character amounts.
- [CopyTo\(OracleClob\)](#)
This instance method copies data from the current OracleBFile instance to the provided OracleClob object.
- [CopyTo\(OracleClob, Int64\)](#)
This instance method copies data from the current OracleBFile instance to the provided OracleClob object with the specified destination offset.
- [CopyTo\(Int64, OracleClob, Int64, Int64\)](#)
This instance method copies data from the current OracleBFile instance to the provided OracleClob object with the specified source offset, destination offset, and amount of characters.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

CopyTo(OracleBlob)

This instance method copies data from the current instance to the provided `OracleBlob` object.

Declaration

```
// C#  
public Int64 CopyTo(OracleBlob obj);
```

Parameters

- *obj*
The `OracleBlob` object to which the data is copied.

Return Value

The return value is the amount copied.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - This exception is thrown if any of the following conditions exist:

- The `OracleConnection` is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

Remarks

The provided object and the current instance must be using the same connection; that is, the same `OracleConnection` object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

CopyTo(OracleBlob, Int64)

This instance method copies data from the current `OracleBFile` instance to the provided `OracleBlob` object with the specified destination offset.

Declaration

```
// C#  
public Int64 CopyTo(OracleBlob obj, Int64 dst_offset);
```

Parameters

- *obj*
The OracleBlob object to which the data is copied.
- *dst_offset*
The offset (in bytes) at which the OracleBlob object is copied.

Return Value

The return value is the amount copied.

Exceptions

ObjectDisposedException - The object is already disposed.

ArgumentOutOfRangeException - The *dst_offset* is less than 0.

InvalidOperationException - This exception is thrown if any of the following conditions exist:

- The OracleConnection is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

Remarks

If the *dst_offset* is beyond the end of the OracleBlob data, spaces are written into the OracleBlob until the *dst_offset* is met.

The offsets are 0-based. No character conversion is performed by this operation.

The provided object and the current instance must be using the same connection; that is, the same OracleConnection object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

CopyTo(Int64, OracleBlob, Int64, Int64)

This instance method copies data from the current OracleBFile instance to the provided OracleBlob object with the specified source offset, destination offset, and character amounts.

Declaration

```
// C#
public Int64 CopyTo(Int64 src_offset, OracleBlob obj, Int64 dst_offset,
    Int64 amount);
```

Parameters

- *src_offset*
The offset (in bytes) in the current instance, from which the data is read.
- *obj*
An OracleBlob object to which the data is copied.

- *dst_offset*
The offset (in bytes) to which the `OracleBlob` object is copied.
- *amount*
The amount of data to be copied.

Return Value

The return value is the amount copied.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentOutOfRangeException` - The *src_offset*, the *dst_offset*, or the *amount* is less than 0.

`InvalidOperationException` - This exception is thrown if any of the following conditions exist:

- The `OracleConnection` is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

Remarks

If the *dst_offset* is beyond the end of the `OracleBlob` data, spaces are written into the `OracleBlob` until the *dst_offset* is met.

The offsets are 0-based. No character conversion is performed by this operation.

The provided object and the current instance must be using the same connection; that is, the same `OracleConnection` object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

CopyTo(OracleClob)

This instance method copies data from the current `OracleBFile` instance to the provided `OracleClob` object.

Declaration

```
// C#  
public Int64 CopyTo(OracleClob obj);
```

Parameters

- *obj*
The `OracleClob` object to which the data is copied.

Return Value

The return value is the amount copied.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - This exception is thrown if any of the following conditions exist:

- The `OracleConnection` is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

Remarks

The provided object and the current instance must be using the same connection, that is, the same `OracleConnection` object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

CopyTo(OracleClob, Int64)

This instance method copies data from the current `OracleBFile` instance to the provided `OracleClob` object with the specified destination offset.

Declaration

```
// C#
public Int64 CopyTo(OracleClob obj, Int64 dst_offset);
```

Parameters

- *obj*
The `OracleClob` object that the data is copied to.
- *dst_offset*
The offset (in characters) at which the `OracleClob` object is copied to.

Return Value

The amount copied.

Exceptions**Exceptions**

`ObjectDisposedException` - The object is already disposed.

`ArgumentOutOfRangeException` - The *dst_offset* is less than 0.

`InvalidOperationException` - This exception is thrown if any of the following conditions exist:

- The `OracleConnection` is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

Remarks

If the *dst_offset* is beyond the end of the `OracleClob` data, spaces are written into the `OracleClob` until the *dst_offset* is met.

The offsets are 0-based. No character conversion is performed by this operation.

The provided object and the current instance must be using the same connection, that is, the same `OracleConnection` object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

CopyTo(Int64, OracleClob, Int64, Int64)

This instance method copies data from the current `OracleBFile` instance to the provided `OracleClob` object with the specified source offset, destination offset, and amount of characters.

Declaration

```
// C#
public Int64 CopyTo(Int64 src_offset, OracleClob obj, Int64 dst_offset,
    Int64 amount);
```

Parameters

- *src_offset*
The offset (in characters) in the current instance, from which the data is read.
- *obj*
An `OracleClob` object that the data is copied to.
- *dst_offset*
The offset (in characters) at which the `OracleClob` object is copied to.
- *amount*
The amount of data to be copied.

Return Value

The return value is the amount copied.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentOutOfRangeException` - The *src_offset*, the *dst_offset*, or the *amount* is less than 0.

`InvalidOperationException` - This exception is thrown if any of the following conditions exist:

- The `OracleConnection` is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

Remarks

If the *dst_offset* is beyond the end of the current `OracleClob` data, spaces are written into the `OracleClob` until the *dst_offset* is met.

The offsets are 0-based. No character conversion is performed by this operation.

The provided object and the current instance must be using the same connection, that is, the same `OracleConnection` object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

Dispose

This instance method releases resources allocated by this object.

Declaration

```
// C#  
public void Dispose();
```

Implements

`IDisposable`

Remarks

Although some properties can still be accessed, their values may not be accountable. Since resources are freed, method calls may lead to exceptions. The object cannot be reused after being disposed.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

IsEqual

This instance method compares the LOB references.

Declaration

```
// C#  
public bool IsEqual(OracleBFile obj);
```

Parameters

- *obj*
The provided `OracleBFile` object.

Return Value

Returns `true` if the current `OracleBFile` and the provided `OracleBFile` object refer to the same external LOB. Returns `false` otherwise.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

Note that this method can return `true` even if the two `OracleBFile` objects return `false` for `==` or `Equals()` since two different `OracleBFile` instances can refer to the same external LOB.

The provided object and the current instance must be using the same connection; that is, the same `OracleConnection` object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

OpenFile

This instance method opens the `BFILE` specified by the `FileName` and `DirectoryName`.

Declaration

```
// C#  
public void OpenFile();
```

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

Many operations, such as `Compare()`, `CopyTo()`, `Read()`, and `Search()` require that the `BFILE` be opened using `OpenFile` before the operation.

Calling `OpenFile` on an opened `BFILE` is not operational.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

Read

Overrides `Stream`

This instance method reads a specified amount of bytes from the `OracleBFile` instance and populates the buffer.

Declaration

```
// C#
public override int Read(byte[] buffer, int offset, int count);
```

Parameters

- *buffer*
The byte array buffer to be populated.
- *offset*
The offset of the byte array buffer to be populated.
- *count*
The amount of bytes to read.

Return Value

The return value indicates the number of bytes read from the BFILE, that is, the external LOB.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

ArgumentOutOfRangeException - Either the *offset* or the *count* parameter is less than 0 or the *offset* is greater than or equal to the *buffer.Length* or the *offset* and the *count* together are greater than *buffer.Length*.

Remarks

The LOB data is read starting from the position specified by the *Position* property.

Example

```
// Database Setup, if you have not done so yet.
/* Log on as DBA (SYS or SYSTEM) that has CREATE ANY DIRECTORY privilege.

CREATE OR REPLACE DIRECTORY MYDIR AS 'C:\TEMP';

*/

// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class ReadSample
{
    static void Main()
    {
        // Create MYDIR directory object as indicated previously and create a file
        // MyFile.txt with the text ABCDABC under C:\TEMP directory.
        // Note that the byte representation of the ABCDABC is 65666768656667

        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();
```

```
OracleBFile bFile = new OracleBFile(con, "MYDIR", "MyFile.txt");

// Open the OracleBFile
bFile.OpenFile();

// Read 7 bytes into readBuffer, starting at buffer offset 0
byte[] readBuffer = new byte[7];
int bytesRead = bFile.Read(readBuffer, 0, 7);

// Prints "bytesRead = 7"
Console.WriteLine("bytesRead = " + bytesRead);

// Prints "readBuffer = 65666768656667"
Console.Write("readBuffer = ");
for(int index = 0; index < readBuffer.Length; index++)
{
    Console.Write(readBuffer[index]);
}
Console.WriteLine();

// Close the OracleBFile
bFile.CloseFile();

bFile.Close();
bFile.Dispose();

con.Close();
con.Dispose();
}
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

Search

This instance method searches for a binary pattern in the current instance of an `OracleBFile`.

Declaration

```
// C#
public int Search(byte[] val, Int64 offset, Int64 nth);
```

Parameters

- *val*
The binary pattern being searched for.
- *offset*
The 0-based offset (in bytes) starting from which the `OracleBFile` is searched.
- *nth*

The specific occurrence (1-based) of the match for which the offset is returned.

Return Value

Returns the absolute *offset* of the start of the matched pattern (in bytes) for the *nth* occurrence of the match. Otherwise, 0 is returned.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - Either the *offset* is less than 0 or *nth* is less than or equal to 0 or *val.Length* is greater than 16383 or *nth* is greater than or equal to `OracleBFile.MaxSize` or *offset* is greater than or equal to `OracleBFile.MaxSize`.

Remarks

The limit of the search pattern is 16383 bytes.

Example

```
// Database Setup, if you have not done so yet.
/* Log on as DBA (SYS or SYSTEM) that has CREATE ANY DIRECTORY privilege.

CREATE OR REPLACE DIRECTORY MYDIR AS 'C:\TEMP';

*/

// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class SearchSample
{
    static void Main()
    {
        // Create MYDIR directory object as indicated previously and create a file
        // MyFile.txt with the text ABCDABC under C:\TEMP directory.
        // Note that the byte representation of the ABCDABC is 65666768656667

        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBFile bFile = new OracleBFile(con, "MYDIR", "MyFile.txt");

        // Open the OracleBFile
        bFile.OpenFile();

        // Search for the 2nd occurrence of a byte pattern {66,67}
        // starting from byte offset 1 in the OracleBFile
        byte[] pattern = new byte[2] {66, 67};
        long posFound = bFile.Search(pattern, 1, 2);

        // Prints "posFound = 6"
        Console.WriteLine("posFound = " + posFound);
    }
}
```

```
// Close the OracleBFile
bFile.CloseFile();

bFile.Close();
bFile.Dispose();

con.Close();
con.Dispose();
}
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

Seek

Overrides Stream

This instance method sets the position on the current LOB stream.

Declaration

```
// C#
public override Int64 Seek(Int64 offset, SeekOrigin origin);
```

Parameters

- *offset*
A byte offset relative to origin.
- *origin*
A value of type `System.IO.SeekOrigin` indicating the reference point used to obtain the new position.

Return Value

Returns an `Int64` that indicates the position.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

If *offset* is negative, the new position precedes the position specified by *origin* by the number of bytes specified by *offset*.

If *offset* is zero, the new position is the position specified by *origin*.

If *offset* is positive, the new position follows the position specified by *origin* by the number of bytes specified by *offset*.

`SeekOrigin.Begin` specifies the beginning of a stream.

SeekOrigin.Current specifies the current position within a stream.

SeekOrigin.End specifies the end of a stream.

Example

```
// Database Setup, if you have not done so yet.
/* Log on as DBA (SYS or SYSTEM) that has CREATE ANY DIRECTORY privilege.

CREATE OR REPLACE DIRECTORY MYDIR AS 'C:\TEMP';

*/

// C#

using System;
using System.IO;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class SeekSample
{
    static void Main()
    {
        // Create MYDIR directory object as indicated previously and create a file
        // MyFile.txt with the text ABCDABC under C:\TEMP directory.
        // Note that the byte representation of the ABCDABC is 65666768656667

        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBFile bFile = new OracleBFile(con, "MYDIR", "MyFile.txt");

        // Open the OracleBFile
        bFile.OpenFile();

        // Set the Position to 2 with respect to SeekOrigin.Begin
        long newPosition = bFile.Seek(2, SeekOrigin.Begin);

        // Prints "newPosition      = 2"
        Console.WriteLine("newPosition      = " + newPosition);

        // Prints "bFile.Position = 2"
        Console.WriteLine("bFile.Position = " + bFile.Position);

        // Read 2 bytes into readBuffer, starting at buffer offset 1
        byte[] readBuffer = new byte[4];
        int bytesRead = bFile.Read(readBuffer, 1, 2);

        // Prints "bytesRead      = 2"
        Console.WriteLine("bytesRead      = " + bytesRead);

        // Prints "readBuffer      = 067680"
        Console.Write("readBuffer      = ");
        for(int index = 0; index < readBuffer.Length; index++)
        {
            Console.Write(readBuffer[index]);
        }
        Console.WriteLine();
    }
}
```

```
// Close the OracleBFile
bFile.CloseFile();

bFile.Close();
bFile.Dispose();

con.Close();
con.Dispose();
}
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBFile Class](#)
- [OracleBFile Members](#)

OracleBlob Class

An OracleBlob object is an object that has a reference to BLOB data. It provides methods for performing operations on BLOBs.

Class Inheritance

System.Object

System.MarshalByRefObject

System.IO.Stream

Oracle.DataAccess.Types.OracleBlob

Declaration

```
// C#
public sealed class OracleBlob : Stream, ICloneable, INullable
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|--------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Types | Oracle.ManagedDataAccess.Types |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class OracleBlobSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBlob blob = new OracleBlob(con);

        // Write 4 bytes from writeBuffer, starting at buffer offset 0
        byte[] writeBuffer = new byte[4] {1, 2, 3, 4};
        blob.Write(writeBuffer, 0, 4);

        // Append first 2 bytes from writeBuffer {1, 2} to the oracleBlob
        blob.Append(writeBuffer, 0, 2);

        // Prints "blob.Length = 6"
```

```
Console.WriteLine("blob.Length = " + blob.Length);

// Reset the Position for the Read
blob.Position = 0;

// Read 6 bytes into readBuffer, starting at buffer offset 0
byte[] readBuffer = new byte[6];
int bytesRead = blob.Read(readBuffer, 0, 6);

// Prints "bytesRead = 6"
Console.WriteLine("bytesRead = " + bytesRead);

// Prints "readBuffer = 123412"
Console.Write("readBuffer = ");
for(int index = 0; index < readBuffer.Length; index++)
{
    Console.Write(readBuffer[index]);
}
Console.WriteLine();

// Search for the 2nd occurrence of a byte pattern '12'
// starting from byte offset 0 in the OracleBlob
byte[] pattern = new byte[2] {1, 2};
long posFound = blob.Search(pattern, 0, 2);

// Prints "posFound = 5"
Console.WriteLine("posFound = " + posFound);

// Erase 4 bytes of data starting at byte offset 1
// Sets bytes to zero
blob.Erase(1, 4);

byte[] erasedBuffer = blob.Value;

//Prints "erasedBuffer = 100002"
Console.Write("erasedBuffer = ");
for(int index = 0; index < erasedBuffer.Length; index++)
{
    Console.Write(erasedBuffer[index]);
}
Console.WriteLine();

blob.Close();
blob.Dispose();

con.Close();
con.Dispose();
}
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleBlob Members](#)
- [OracleBlob Constructors](#)
- [OracleBlob Static Fields](#)
- [OracleBlob Static Methods](#)
- [OracleBlob Instance Properties](#)
- [OracleBlob Instance Methods](#)

OracleBlob Members

OracleBlob members are listed in the following tables.

OracleBlob Constructors

OracleBlob constructors are listed in [Table 13–10](#).

Table 13–10 OracleBlob Constructors

| Constructor | Description |
|-----------------------------------------|----------------------------------------------------------|
| OracleBlob Constructors | Creates an instance of the OracleBlob class (Overloaded) |

OracleBlob Static Fields

OracleBlob static fields are listed in [Table 13–11](#).

Table 13–11 OracleBlob Static Fields

| Field | Description |
|-------------------------|--------------------------------------------------------------------------------------------------|
| MaxSize | Holds the maximum number of bytes a BLOB can hold, which is 4,294,967,295 ($2^{32} - 1$) bytes |
| Null | Represents a null value that can be assigned to the value of an OracleBlob instance |

OracleBlob Static Methods

OracleBlob static methods are listed in [Table 13–12](#).

Table 13–12 OracleBlob Static Methods

| Methods | Description |
|------------------------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

OracleBlob Instance Properties

OracleBlob instance properties are listed in [Table 13–13](#).

Table 13–13 OracleBlob Instance Properties

| Properties | Description |
|------------------------------------|-----------------------------------------------------------------------------|
| CanRead | Indicates whether or not the LOB stream can be read |
| CanSeek | Indicates whether or not forward and backward seek operations be performed |
| CanWrite | Indicates whether or not the LOB object supports writing |
| Connection | Indicates the OracleConnection that is used to retrieve and write BLOB data |
| IsEmpty | Indicates whether the BLOB is empty or not |
| IsInChunkWriteMode | Indicates whether or not the BLOB has been opened to defer index updates |
| IsNull | Indicates whether or not the current instance has a null value |

Table 13–13 (Cont.) OracleBlob Instance Properties

| Properties | Description |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| IsTemporary | Indicates whether or not the current instance is bound to a temporary BLOB |
| Length | Indicates the size of the BLOB data |
| OptimumChunkSize | Indicates the optimal data buffer length (or multiples thereof) that read and write operations should use to improve performance |
| Position | Indicates the current read or write position in the LOB stream |
| Value | Returns the data, starting from the first byte in BLOB, as a byte array |

OracleBlob Instance Methods

OracleBlob instance methods are listed in [Table 13–14](#).

Table 13–14 OracleBlob Instance Methods

| Methods | Description |
|--------------------------------------------|----------------------------------------------------------------------------------|
| Append | Appends the supplied data to the current OracleBlob instance (Overloaded) |
| BeginChunkWrite | Opens the BLOB |
| BeginRead | Inherited from <code>System.IO.Stream</code> |
| BeginWrite | Inherited from <code>System.IO.Stream</code> |
| Clone | Creates a copy of an OracleBlob object |
| Close | Closes the current stream and releases any resources associated with it |
| Compare | Compares data referenced by the current instance and that of the supplied object |
| CopyTo | Copies from the current OracleBlob instance to an OracleBlob object (Overloaded) |
| CreateObjRef | Inherited from <code>System.MarshalByRefObject</code> |
| Dispose | Releases resources allocated by this object |
| EndChunkWrite | Closes the BLOB referenced by the current OracleBlob instance |
| EndRead | Inherited from <code>System.IO.Stream</code> |
| EndWrite | Inherited from <code>System.IO.Stream</code> |
| Equals | Inherited from <code>System.Object</code> (Overloaded) |
| Erase | Erases data (Overloaded) |
| Flush | <i>Not supported</i> |
| GetHashCode | Inherited from <code>System.Object</code> |
| GetLifetimeService | Inherited from <code>System.MarshalByRefObject</code> |
| GetType | Inherited from <code>System.Object</code> |
| InitializedLifetimeService | Inherited from <code>System.MarshalByRefObject</code> |

Table 13–14 (Cont.) OracleBlob Instance Methods

| Methods | Description |
|---------------------------|-----------------------------------------------------------------------------------------------|
| IsEqual | Compares the LOB data referenced by the two OracleBlobs |
| Read | Reads a specified amount of bytes from the ODP.NET LOB Type instance and populates the buffer |
| ReadByte | Inherited from <code>System.IO.Stream</code> |
| Search | Searches for a binary pattern in the current instance of an OracleBlob |
| Seek | Sets the position in the current LOB stream |
| SetLength | Trims or truncates the BLOB value to the specified length |
| ToString | Inherited from <code>System.Object</code> |
| Write | Writes the supplied buffer into the OracleBlob |
| WriteByte | Inherited from <code>System.IO.Stream</code> |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Members](#)

OracleBlob Constructors

OracleBlob constructors are listed in [Table 13–10](#).

Overload List:

- [OracleBlob\(OracleConnection\)](#)

This constructor creates an instance of the OracleBlob class bound to a temporary BLOB with an OracleConnection object.

- [OracleBlob\(OracleConnection, bool\)](#)

This constructor creates an instance of the OracleBlob class bound to a temporary BLOB with an OracleConnection object and a boolean value for caching.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

OracleBlob(OracleConnection)

This constructor creates an instance of the OracleBlob class bound to a temporary BLOB with an OracleConnection object.

Declaration

```
// C#  
public OracleBlob(OracleConnection con);
```

Parameters

- *con*
The OracleConnection object.

Exceptions

InvalidOperationException - The OracleConnection is not opened.

Remarks

The connection must be opened explicitly by the application. OracleBlob does not open the connection implicitly.

The temporary BLOB utilizes the provided connection to store BLOB data. Caching is not turned on by this constructor.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

OracleBlob(OracleConnection, bool)

This constructor creates an instance of the OracleBlob class bound to a temporary BLOB with an OracleConnection object and a boolean value for caching.

Declaration

```
// C#  
public OracleBlob(OracleConnection con, bool bCaching);
```

Parameters

- *con*
The OracleConnection object.
- *bCaching*
A flag for enabling or disabling server-side caching.

Exceptions

InvalidOperationException - The OracleConnection is not opened.

Remarks

The connection must be opened explicitly by the application. OracleBlob does not open the connection implicitly.

The temporary BLOB uses the provided connection to store BLOB data. The *bCaching* input parameter determines whether or not server-side caching is used.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

OracleBlob Static Fields

OracleBlob static fields are listed in [Table 13–15](#).

Table 13–15 OracleBlob Static Fields

| Field | Description |
|-------------------------|-------------------------------------------------------------------------------------------------------|
| MaxSize | Holds the maximum number of bytes a BLOB can hold, which is 4,294,967,295 (2 ³² - 1) bytes |
| Null | Represents a null value that can be assigned to the value of an OracleBlob instance |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

MaxSize

The `MaxSize` field holds the maximum number of bytes a BLOB can hold, which is 4,294,967,295 (2³² - 1) bytes.

Declaration

```
// C#
public static readonly Int64 MaxSize = 4294967295;
```

Remarks

This field can be useful in code that checks whether or not the operation exceeds the maximum length allowed.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Null

This static field represents a null value that can be assigned to the value of an OracleBlob instance.

Declaration

```
// C#
public static readonly OracleBlob Null;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

OracleBlob Static Methods

OracleBlob static methods are listed in [Table 13-16](#).

Table 13-16 OracleBlob Static Methods

| Methods | Description |
|---------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

OracleBlob Instance Properties

OracleBlob instance properties are listed in [Table 13–17](#).

Table 13–17 OracleBlob Instance Properties

| Properties | Description |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| CanRead | Indicates whether or not the LOB stream can be read |
| CanSeek | Indicates whether or not forward and backward seek operations be performed |
| CanWrite | Indicates whether or not the LOB object supports writing |
| Connection | Indicates the OracleConnection that is used to retrieve and write BLOB data |
| IsEmpty | Indicates whether the BLOB is empty or not |
| IsInChunkWriteMode | Indicates whether or not the BLOB has been opened to defer index updates |
| IsNull | Indicates whether or not the current instance has a null value |
| IsTemporary | Indicates whether or not the current instance is bound to a temporary BLOB |
| Length | Indicates the size of the BLOB data |
| OptimumChunkSize | Indicates the optimal data buffer length (or multiples thereof) that read and write operations should use to improve performance |
| Position | Indicates the current read or write position in the LOB stream |
| Value | Returns the data, starting from the first byte in BLOB, as a byte array |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

CanRead

Overrides [Stream](#)

This instance property indicates whether or not the LOB stream can be read.

Declaration

```
// C#
public override bool CanRead{get;}
```

Property Value

If the LOB stream can be read, returns `true`; otherwise, returns `false`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

CanSeek

Overrides `Stream`

This instance property indicates whether or not forward and backward seek operations can be performed.

Declaration

```
// C#  
public override bool CanSeek{get;}
```

Property Value

If forward and backward seek operations can be performed, returns `true`; otherwise, returns `false`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

CanWrite

Overrides `Stream`

This instance property indicates whether or not the LOB object supports writing.

Declaration

```
// C#  
public override bool CanWrite{get;}
```

Property Value

If the LOB stream can be written, returns `true`; otherwise, returns `false`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Connection

This instance property indicates the `OracleConnection` that is used to retrieve and write BLOB data.

Declaration

```
// C#  
public OracleConnection Connection {get;}
```

Property Value

An object of `OracleConnection`.

Exceptions

`ObjectDisposedException` - The object is already disposed.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

IsEmpty

This instance property indicates whether the BLOB is empty or not.

Declaration

```
// C#  
public bool IsEmpty {get;}
```

Property Value

A `bool` that indicates whether or not the BLOB is empty.

Exceptions

`ObjectDisposedException` - The object is already disposed.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

IsInChunkWriteMode

This instance property indicates whether or not the BLOB has been opened to defer index updates.

Declaration

```
// C#  
public bool IsInChunkWriteMode{get;}
```

Property Value

If the BLOB has been opened, returns `true`; otherwise, returns `false`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

IsNull

This property indicates whether or not the current instance has a null value.

Declaration

```
// C#  
public bool IsNull{get;}
```

Property Value

Returns `true` if the current instance has a null value; otherwise, returns `false`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

IsTemporary

This instance property indicates whether or not the current instance is bound to a temporary BLOB.

Declaration

```
// C#  
public bool IsTemporary {get;}
```

Property Value

`bool`

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Length

Overrides `Stream`

This instance property indicates the size of the BLOB data in bytes.

Declaration

```
// C#  
public override Int64 Length {get;}
```

Property Value

A number indicating the size of the BLOB data in bytes.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

OptimumChunkSize

This instance property indicates the optimal data buffer length (or multiples thereof) that read and write operations should use to improve performance.

Declaration

```
// C#  
public int OptimumChunkSize{get;}
```

Property Value

A number representing the minimum bytes to retrieve or send.

Exceptions

`ObjectDisposedException` - The object is already disposed.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Position

Overrides `Stream`

This instance property indicates the current read or write position in the LOB stream.

Declaration

```
// C#  
public override Int64 Position{get; set;}
```

Property Value

An `Int64` that indicates the read or write position.

Exceptions

`ObjectDisposedException` - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

ArgumentOutOfRangeException - The Position is less than 0.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Value

This instance property returns the data, starting from the first byte in the BLOB, as a byte array.

Declaration

```
// C#  
public Byte[] Value{get;}
```

Property Value

A byte array.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

ArgumentOutOfRangeException - The Value is less than 0.

Remarks

The value of Position is not used or changed by using this property. 2 GB is the maximum byte array length that can be returned by this property.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

OracleBlob Instance Methods

OracleBlob instance methods are listed in [Table 13–18](#).

Table 13–18 OracleBlob Instance Methods

| Methods | Description |
|---------------------------------|-----------------------------------------------------------------------------------------------|
| Append | Appends the supplied data to the current OracleBlob instance (Overloaded) |
| BeginChunkWrite | Opens the BLOB |
| BeginRead | Inherited from <code>System.IO.Stream</code> |
| BeginWrite | Inherited from <code>System.IO.Stream</code> |
| Clone | Creates a copy of an OracleBlob object |
| Close | Closes the current stream and releases any resources associated with it |
| Compare | Compares data referenced by the current instance and that of the supplied object |
| CopyTo | Copies from the current OracleBlob instance to an OracleBlob object (Overloaded) |
| CreateObjRef | Inherited from <code>System.MarshalByRefObject</code> |
| Dispose | Releases resources allocated by this object |
| EndChunkWrite | Closes the BLOB referenced by the current OracleBlob instance |
| EndRead | Inherited from <code>System.IO.Stream</code> |
| EndWrite | Inherited from <code>System.IO.Stream</code> |
| Equals | Inherited from <code>System.Object</code> (Overloaded) |
| Erase | Erases data (Overloaded) |
| Flush | <i>Not supported</i> |
| GetHashCode | Inherited from <code>System.Object</code> |
| GetLifetimeService | Inherited from <code>System.MarshalByRefObject</code> |
| GetType | Inherited from <code>System.Object</code> |
| InitializedLifetimeService | Inherited from <code>System.MarshalByRefObject</code> |
| IsEqual | Compares the LOB data referenced by the two OracleBlobs |
| Read | Reads a specified amount of bytes from the ODP.NET LOB Type instance and populates the buffer |
| ReadByte | Inherited from <code>System.IO.Stream</code> |
| Search | Searches for a binary pattern in the current instance of an OracleBlob |
| Seek | Sets the position in the current LOB stream |
| SetLength | Trims or truncates the BLOB value to the specified length |
| ToString | Inherited from <code>System.Object</code> |
| Write | Writes the supplied buffer into the OracleBlob |
| WriteByte | Inherited from <code>System.IO.Stream</code> |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Append

Append appends the supplied data to the end of the current OracleBlob instance.

Overload List:

- [Append\(OracleBlob\)](#)

This instance method appends the BLOB data referenced by the provided OracleBlob object to the current OracleBlob instance.

- [Append\(byte\[\], int, int\)](#)

This instance method appends data from the supplied byte array buffer to the end of the current OracleBlob instance.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Append(OracleBlob)

This instance method appends the BLOB data referenced by the provided OracleBlob object to the current OracleBlob instance.

Declaration

```
// C#
public void Append(OracleBlob obj);
```

Parameters

- *obj*
An object of OracleBlob.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The parameter has a different connection than the object, OracleConnection is not opened, or OracleConnection has been reopened.

Remarks

No character set conversions are made.

The provided object and the current instance must be using the same connection; that is, the same OracleConnection object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Append(byte[] , int, int)

This instance method appends data from the supplied byte array buffer to the end of the current OracleBlob instance.

Declaration

```
// C#  
public void Append(byte[] buffer, int offset, int count);
```

Parameters

- *buffer*
An array of bytes.
- *offset*
The zero-based byte offset in the buffer from which data is read.
- *count*
The number of bytes to be appended.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
using Oracle.DataAccess.Types;  
  
class AppendSample  
{  
    static void Main()  
    {  
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";  
        OracleConnection con = new OracleConnection(constr);  
        con.Open();  
  
        OracleBlob blob = new OracleBlob(con);  
  
        // Append 2 bytes {4, 5} to the OracleBlob  
        byte[] buffer = new byte[3] {4, 5, 6};  
        blob.Append(buffer, 0, 2);  
  
        byte[] appendBuffer = blob.Value;  
  
        // Prints "appendBuffer = 45"  
    }  
}
```

```

        Console.WriteLine("appendBuffer = ");
        for(int index = 0; index < appendBuffer.Length; index++)
        {
            Console.WriteLine(appendBuffer[index]);
        }
        Console.WriteLine();

        blob.Close();
        blob.Dispose();

        con.Close();
        con.Dispose();
    }
}

```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

BeginChunkWrite

This instance method opens the BLOB.

Declaration

```

// C#
public void BeginChunkWrite();

```

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The *OracleConnection* is not open or has been closed during the lifetime of the object.

Remarks

BeginChunkWrite does not need to be called before manipulating the BLOB data. This is provided for performance reasons.

After this method is called, write operations do not cause the domain or function-based index on the column to be updated. Index updates occur only once after *EndChunkWrite* is called.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Clone

This instance method creates a copy of an *OracleBlob* object.

Declaration

```
// C#  
public object Clone();
```

Return Value

An OracleBlob object.

Implements

ICloneable

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

Remarks

The cloned object has the same property values as that of the object being cloned.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
using Oracle.DataAccess.Types;  
  
class CloneSample  
{  
    static void Main()  
    {  
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";  
        OracleConnection con = new OracleConnection(constr);  
        con.Open();  
  
        OracleBlob blob1 = new OracleBlob(con);  
  
        // Prints "blob1.Position = 0"  
        Console.WriteLine("blob1.Position = " + blob1.Position);  
  
        // Set the Position before calling Clone()  
        blob1.Position = 1;  
  
        // Clone the OracleBlob  
        OracleBlob blob2 = (OracleBlob)blob1.Clone();  
  
        // Prints "blob2.Position = 1"  
        Console.WriteLine("blob2.Position = " + blob2.Position);  
  
        blob1.Close();  
        blob1.Dispose();  
  
        blob2.Close();  
        blob2.Dispose();  
  
        con.Close();  
        con.Dispose();  
    }  
}
```

}

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

CloseOverrides `Stream`

This instance method closes the current stream and releases any resources associated with it.

Declaration

```
// C#
public override void Close();
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Compare

This instance method compares data referenced by the current instance and that of the supplied object.

Declaration

```
// C#
public int Compare(Int64 src_offset, OracleBlob obj, Int64 dst_offset,
    Int64 amount);
```

Parameters

- *src_offset*
The comparison starting point (in bytes) for the current instance.
- *obj*
The provided `OracleBlob` object.
- *dst_offset*
The comparison starting point (in bytes) for the provided `OracleBlob`.
- *amount*
The number of bytes to compare.

Return Value

Returns a value that is:

- Less than zero: if the data referenced by the current instance is less than that of the supplied instance

- Zero: if both objects reference the same data
- Greater than zero: if the data referenced by the current instance is greater than that of the supplied instance

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The parameter has a different connection than the object, `OracleConnection` is not opened, or `OracleConnection` has been reopened.

`ArgumentOutOfRangeException` - The `src_offset`, the `dst_offset`, or the `amount` parameter is less than 0.

Remarks

The provided object and the current instance must be using the same connection, that is, the same `OracleConnection` object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

CopyTo

`CopyTo` copies data from the current instance to the provided `OracleBlob` object.

Overload List:

- [CopyTo\(OracleBlob\)](#)

This instance method copies data from the current instance to the provided `OracleBlob` object.

- [CopyTo\(OracleBlob, Int64\)](#)

This instance method copies data from the current `OracleBlob` instance to the provided `OracleBlob` object with the specified destination offset.

- [CopyTo\(Int64, OracleBlob, Int64, Int64\)](#)

This instance method copies data from the current `OracleBlob` instance to the provided `OracleBlob` object with the specified source offset, destination offset, and character amounts.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

CopyTo(OracleBlob)

This instance method copies data from the current instance to the provided `OracleBlob` object.

Declaration

```
// C#  
public Int64 CopyTo(OracleBlob obj);
```

Parameters

- *obj*

The OracleBlob object to which the data is copied.

Return Value

The return value is the amount copied.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - This exception is thrown if any of the following conditions exist:

- The OracleConnection is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

Remarks

The provided object and the current instance must be using the same connection; that is, the same OracleConnection object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

CopyTo(OracleBlob, Int64)

This instance method copies data from the current OracleBlob instance to the provided OracleBlob object with the specified destination offset.

Declaration

```
// C#  
public Int64 CopyTo(OracleBlob obj, Int64 dst_offset);
```

Parameters

- *obj*

The OracleBlob object to which the data is copied.

- *dst_offset*

The offset (in bytes) at which the OracleBlob object is copied.

Return Value

The return value is the amount copied.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentOutOfRangeException` - The `dst_offset` is less than 0.

`InvalidOperationException` - This exception is thrown if any of the following conditions exist:

- The `OracleConnection` is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

Remarks

If the `dst_offset` is beyond the end of the `OracleBlob` data, spaces are written into the `OracleBlob` until the `dst_offset` is met.

The offsets are 0-based. No character conversion is performed by this operation.

The provided object and the current instance must be using the same connection; that is, the same `OracleConnection` object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

CopyTo(Int64, OracleBlob, Int64, Int64)

This instance method copies data from the current `OracleBlob` instance to the provided `OracleBlob` object with the specified source offset, destination offset, and character amounts.

Declaration

```
// C#
public Int64 CopyTo(Int64 src_offset, OracleBlob obj, Int64 dst_offset,
    Int64 amount);
```

Parameters

- `src_offset`
The offset (in bytes) in the current instance, from which the data is read.
- `obj`
The `OracleBlob` object to which the data is copied.
- `dst_offset`
The offset (in bytes) at which the `OracleBlob` object is copied.
- `amount`
The amount of data to be copied.

Return Value

The return value is the amount copied.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The parameter has a different connection than the object, `OracleConnection` is not opened, or `OracleConnection` has been reopened.

`ArgumentOutOfRangeException` - The `src_offset`, the `dst_offset`, or the `amount` parameter is less than 0.

Remarks

If the `dst_offset` is beyond the end of the `OracleBlob` data, spaces are written into the `OracleBlob` until the `dst_offset` is met.

The offsets are 0-based. No character conversion is performed by this operation.

The provided object and the current instance must be using the same connection; that is, the same `OracleConnection` object.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class CopyToSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBlob blob1 = new OracleBlob(con);
        OracleBlob blob2 = new OracleBlob(con);

        // Write 4 bytes, starting at buffer offset 0
        byte[] buffer = new byte[4] {1, 2, 3, 4};
        blob1.Write(buffer, 0, 4);

        // Copy 2 bytes from byte 0 of blob1 to byte 1 of blob2
        blob1.CopyTo(0, blob2, 1, 2);

        byte[] copyBuffer = blob2.Value;

        //Prints "Value = 012"
        Console.Write("Value = ");
        for(int index = 0; index < copyBuffer.Length; index++)
        {
            Console.Write(copyBuffer[index]);
        }
        Console.WriteLine();

        blob1.Close();
        blob1.Dispose();

        blob2.Close();
        blob2.Dispose();

        con.Close();
    }
}
```

```
        con.Dispose();  
    }  
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Dispose

This instance method releases resources allocated by this object.

Declaration

```
// C#  
public void Dispose();
```

Implements

IDisposable

Remarks

Once `Dispose()` is called, the object of `OracleBlob` is in an uninitialized state.

Although some properties can still be accessed, their values may not be accountable. Since resources are freed, method calls may lead to exceptions. The object cannot be reused after being disposed.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

EndChunkWrite

This instance method closes the BLOB referenced by the current `OracleBlob` instance.

Declaration

```
// C#  
public void EndChunkWrite();
```

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

Index updates occur immediately if there is write operation(s) deferred by the `BeginChunkWrite` method.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Erase

Erase erases a portion or all data.

Overload List:

- [Erase\(\)](#)
This instance method erases all data.
- [Erase\(Int64, Int64\)](#)
This instance method erases a specified portion of data.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Erase()

This instance method erases all data.

Declaration

```
// C#
public Int64 Erase();
```

Return Value

The number of bytes erased.

Remarks

Erase() replaces all data with zero-byte fillers.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Erase(Int64, Int64)

This instance method erases a specified portion of data.

Declaration

```
// C#
public Int64 Erase(Int64 offset, Int64 amount);
```

Parameters

- *offset*
The offset from which to erase.
- *amount*
The quantity (in bytes) to erase.

Return Value

The number of bytes erased.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - The *offset* or *amount* parameter is less than 0.

Remarks

Replaces the specified *amount* of data with zero-byte fillers.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

IsEqual

This instance method compares the LOB data referenced by the two `OracleBlobs`.

Declaration

```
// C#  
public bool IsEqual(OracleBlob obj);
```

Parameters

- *obj*
An `OracleBlob` object.

Return Value

If the current `OracleBlob` and the provided `OracleBlob` refer to the same LOB, returns `true`. Returns `false` otherwise.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

Note that this method can return `true` even if the two `OracleBlob` objects return `false` for `==` or `Equals()` because two different `OracleBlob` instances can refer to the same LOB.

The provided object and the current instance must be using the same connection, that is, the same `OracleConnection` object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Read

Overrides `Stream`

This instance method reads a specified amount of bytes from the ODP.NET LOB instance and populates the `buffer`.

Declaration

```
// C#  
public override int Read(byte[] buffer, int offset, int count);
```

Parameters

- *buffer*
The byte array buffer to be populated.
- *offset*
The starting offset (in bytes) at which the buffer is populated.
- *count*
The amount of bytes to read.

Return Value

The return value indicates the number of bytes read from the LOB.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - This exception is thrown if any of the following conditions exist:

- The *offset* or the *count* parameter is less than 0.
- The *offset* is greater than or equal to the `buffer.Length`.
- The *offset* and the *count* together are greater than the `buffer.Length`.

Remarks

The LOB data is read starting from the position specified by the `Position` property.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class ReadSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBlob blob = new OracleBlob(con);

        // Write 3 bytes, starting at buffer offset 1
        byte[] writeBuffer = new byte[4] {1, 2, 3, 4};
        blob.Write(writeBuffer, 1, 3);

        // Reset the Position for Read
        blob.Position = 1;

        // Read 2 bytes into buffer starting at buffer offset 1
        byte[] readBuffer = new byte[4];
        int bytesRead = blob.Read(readBuffer, 1, 2);

        // Prints "bytesRead = 2"
        Console.WriteLine("bytesRead = " + bytesRead);

        // Prints "readBuffer = 0340"
        Console.Write("readBuffer = ");
        for(int index = 0; index < readBuffer.Length; index++)
        {
            Console.Write(readBuffer[index]);
        }
        Console.WriteLine();

        blob.Close();
        blob.Dispose();

        con.Close();
        con.Dispose();
    }
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Search

This instance method searches for a binary pattern in the current instance of an OracleBlob.

Declaration

```
// C#
public Int64 Search(byte[] val, int64 offset, int64 nth);
```

Parameters

- *val*
The binary pattern being searched for.
- *offset*
The 0-based offset (in bytes) starting from which the OracleBlob is searched.
- *nth*
The specific occurrence (1-based) of the match for which the absolute offset (in bytes) is returned.

Return Value

Returns the absolute *offset* of the start of the matched pattern (in bytes) for the *nth* occurrence of the match. Otherwise, 0 is returned.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

ArgumentOutOfRangeException - This exception is thrown if any of the following conditions exist:

- The *offset* is less than 0.
- The *nth* is less than or equal to 0.
- The *val.Length* is greater than 16383.
- The *nth* is greater than or equal to OracleBlob.MaxSize.
- The *offset* is greater than or equal to OracleBlob.MaxSize.

Remarks

The limit of the search pattern is 16383 bytes.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class SearchSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleBlob blob = new OracleBlob(con);
```

```
// Write 7 bytes, starting at buffer offset 0
byte[] buffer = new byte[7] {1, 2, 3, 4, 1, 2, 3};
blob.Write(buffer, 0, 7);

// Search for the 2nd occurrence of a byte pattern '23'
// starting at offset 1 in the OracleBlob
byte[] pattern = new byte[2] {2, 3};
long posFound = blob.Search(pattern, 1, 2);

// Prints "posFound = 6"
Console.WriteLine("posFound = " + posFound);

blob.Close();
blob.Dispose();

con.Close();
con.Dispose();
}
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Seek

Overrides `Stream`

This instance method sets the position on the current LOB stream.

Declaration

```
// C#
public override Int64 Seek(Int64 offset, SeekOrigin origin);
```

Parameters

- *offset*
A byte offset relative to origin.
- *origin*
A value of type `System.IO.SeekOrigin` indicating the reference point used to obtain the new position.

Return Value

Returns `Int64` for the position.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

If *offset* is negative, the new position precedes the position specified by *origin* by the number of bytes specified by *offset*.

If *offset* is zero, the new position is the position specified by *origin*.

If *offset* is positive, the new position follows the position specified by *origin* by the number of bytes specified by *offset*.

SeekOrigin.Begin specifies the beginning of a stream.

SeekOrigin.Current specifies the current position within a stream.

SeekOrigin.End specifies the end of a stream.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

SetLength

Overrides Stream

This instance method trims or truncates the BLOB value to the specified length (in bytes).

Declaration

```
// C#  
public override void SetLength(Int64 newLen);
```

Parameters

- *newLen*

The desired length of the current stream in bytes.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

ArgumentOutOfRangeException - The *newLen* parameter is less than 0.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

Write

Overrides Stream

This instance method writes the supplied buffer into the OracleBlob.

Declaration

```
// C#  
public override void Write(byte[] buffer, int offset, int count);
```

Parameters

- *buffer*
The byte array buffer that provides the data.
- *offset*
The 0-based offset (in bytes) from which the buffer is read.
- *count*
The amount of data (in bytes) that is to be written into the OracleBlob.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

ArgumentOutOfRangeException - This exception is thrown if any of the following conditions exist:

- The *offset* or the *count* is less than 0.
- The *offset* is greater than or equal to the *buffer.Length*.
- The *offset* and the *count* together are greater than *buffer.Length*.

Remarks

Destination *offset* in the OracleBlob can be specified by the Position property.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
using Oracle.DataAccess.Types;  
  
class WriteSample  
{  
    static void Main()  
    {  
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";  
        OracleConnection con = new OracleConnection(constr);  
        con.Open();  
  
        OracleBlob blob = new OracleBlob(con);  
  
        // Set the Position for the Write  
        blob.Position = 0;  
  
        // Begin ChunkWrite to improve performance  
        // Index updates occur only once after EndChunkWrite  
        blob.BeginChunkWrite();  
  
        // Write to the OracleBlob in 5 chunks of 2 bytes each  
        byte[] b = new byte[2] {1, 2};
```

```
for(int index = 0; index < 5; index++)
{
    blob.Write(b, 0, b.Length);
}
blob.EndChunkWrite();

byte[] chunkBuffer = blob.Value;

// Prints "chunkBuffer = 1212121212"
Console.Write("chunkBuffer = ");
for(int index = 0; index < chunkBuffer.Length; index++)
{
    Console.Write(chunkBuffer[index]);
}
Console.WriteLine();

blob.Close();
blob.Dispose();

con.Close();
con.Dispose();
}
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBlob Class](#)
- [OracleBlob Members](#)

OracleClob Class

An OracleClob is an object that has a reference to CLOB data. It provides methods for performing operations on CLOBs.

Note: The OracleClob object uses the client side character set when retrieving or writing CLOB data using a .NET Framework byte array.

Class Inheritance

```
System.Object
    System.MarshalByRefObject
        System.IO.Stream
            Oracle.DataAccess.Types.OracleClob
```

Declaration

```
// C#
public sealed class OracleClob : Stream, ICloneable, INullable
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|--------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Types | Oracle.ManagedDataAccess.Types |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class OracleClobSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleClob clob = new OracleClob(con);

        // Write 4 chars from writeBuffer, starting at buffer offset 0
        char[] writeBuffer = new char[4] {'a', 'b', 'c', 'd'};
```

```
clob.Write(writeBuffer, 0, 4);

// Append first 2 chars from writeBuffer {'a', 'b'} to the oracleClob
clob.Append(writeBuffer, 0, 2);

// Prints "clob.Length = 12"
Console.WriteLine("clob.Length = " + clob.Length);

// Reset the Position for the Read
clob.Position = 0;

// Read 6 chars into readBuffer, starting at buffer offset 0
char[] readBuffer = new char[6];
int charsRead = clob.Read(readBuffer, 0, 6);

// Prints "charsRead = 6"
Console.WriteLine("charsRead = " + charsRead);

// Prints "readBuffer = abcdab"
Console.Write("readBuffer = ");
for(int index = 0; index < readBuffer.Length; index++)
{
    Console.Write(readBuffer[index]);
}
Console.WriteLine();

// Search for the 2nd occurrence of a char pattern 'ab'
// starting from char offset 0 in the OracleClob
char[] pattern = new char[2] {'a', 'b'};
long posFound = clob.Search(pattern, 0, 2);

// Prints "posFound = 5"
Console.WriteLine("posFound = " + posFound);

// Erase 4 chars of data starting at char offset 1
// Sets chars to ''
clob.Erase(1, 4);

//Prints "clob.Value = a b"
Console.WriteLine("clob.Value = " + clob.Value);

clob.Close();
clob.Dispose();

con.Close();
con.Dispose();
}
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleClob Members](#)
- [OracleClob Constructors](#)
- [OracleClob Static Fields](#)
- [OracleClob Static Methods](#)
- [OracleClob Instance Properties](#)
- [OracleClob Instance Methods](#)

OracleClob Members

OracleClob members are listed in the following tables.

OracleClob Constructors

OracleClob constructors are listed in [Table 13-19](#).

Table 13-19 OracleClob Constructors

| Constructor | Description |
|-----------------------------------------|------------------------------------------------------------------------------------|
| OracleClob Constructors | Creates an instance of the OracleClob class bound to a temporary CLOB (Overloaded) |

OracleClob Static Fields

OracleClob static fields are listed in [Table 13-20](#).

Table 13-20 OracleClob Static Fields

| Field | Description |
|-------------------------|--------------------------------------------------------------------------------------------------|
| MaxSize | Holds the maximum number of bytes a CLOB can hold, which is 4,294,967,295 ($2^{32} - 1$) bytes |
| Null | Represents a null value that can be assigned to the value of an OracleClob instance |

OracleClob Static Methods

OracleClob static methods are listed in [Table 13-21](#).

Table 13-21 OracleClob Static Methods

| Methods | Description |
|------------------------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

OracleClob Instance Properties

OracleClob instance properties are listed in [Table 13-22](#).

Table 13-22 OracleClob Instance Properties

| Properties | Description |
|------------------------------------|--------------------------------------------------------------------------------|
| CanRead | Indicates whether or not the LOB stream can be read |
| CanSeek | Indicates whether or not forward and backward seek operations can be performed |
| CanWrite | Indicates whether or not the LOB stream can be written |
| Connection | Indicates the OracleConnection that is used to retrieve and write CLOB data |
| IsEmpty | Indicates whether the CLOB is empty or not |
| IsInChunkWriteMode | Indicates whether or not the CLOB has been opened |
| IsNClob | Indicates whether or not the OracleClob object represents an NCLOB. |

Table 13–22 (Cont.) OracleClob Instance Properties

| Properties | Description |
|----------------------------------|--------------------------------------------------------------------------------------------------------------|
| IsNull | Indicates whether or not the current instance has a null value |
| IsTemporary | Indicates whether or not the current instance is bound to a temporary CLOB |
| Length | Indicates the size of the CLOB data in bytes |
| OptimumChunkSize | Indicates the minimum number of bytes to retrieve or send from the database during a read or write operation |
| Position | Indicates the current read or write position in the LOB stream in bytes |
| Value | Returns the data, starting from the first character in the CLOB or NCLOB, as a string |

OracleClob Instance Methods

The OracleClob instance methods are listed in [Table 13–23](#).

Table 13–23 OracleClob Instance Methods

| Methods | Description |
|-------------------------------------------|---------------------------------------------------------------------------------|
| Append | Appends data to the current OracleClob instance (Overloaded) |
| BeginChunkWrite | Opens the CLOB |
| BeginRead | Inherited from <code>System.IO.Stream</code> |
| BeginWrite | Inherited from <code>System.IO.Stream</code> |
| Clone | Creates a copy of an OracleClob object |
| Close | Closes the current stream and releases resources associated with it |
| Compare | Compares data referenced by the current instance to that of the supplied object |
| CopyTo | Copies the data to an OracleClob (Overloaded) |
| CreateObjRef | Inherited from <code>System.MarshalByRefObject</code> |
| Dispose | Releases resources allocated by this object |
| EndChunkWrite | Closes the CLOB referenced by the current OracleClob instance |
| EndRead | Inherited from <code>System.IO.Stream</code> |
| EndWrite | Inherited from <code>System.IO.Stream</code> |
| Equals | Inherited from <code>System.Object</code> (Overloaded) |
| Erase | Erases the specified amount of data (Overloaded) |
| Flush | <i>Not supported</i> |
| GetHashCode | Returns a hash code for the current instance |
| GetLifetimeService | Inherited from <code>System.MarshalByRefObject</code> |
| GetType | Inherited from <code>System.Object</code> |
| InitializeLifetimeService | Inherited from <code>System.MarshalByRefObject</code> |

Table 13–23 (Cont.) OracleClob Instance Methods

| Methods | Description |
|---------------------------|--------------------------------------------------------------------------------------------------|
| IsEqual | Compares the LOB data referenced by two OracleClobs |
| Read | Reads from the current instance (Overloaded) |
| ReadByte | Inherited from <code>System.IO.Stream</code> |
| Search | Searches for a character pattern in the current instance of <code>OracleClob</code> (Overloaded) |
| Seek | Sets the position in the current LOB stream |
| SetLength | Trims or truncates the CLOB value |
| ToString | Inherited from <code>System.Object</code> |
| Write | Writes the provided buffer into the <code>OracleClob</code> (Overloaded) |
| WriteByte | Inherited from <code>System.IO.Stream</code> |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)

OracleClob Constructors

OracleClob constructors create instances of the OracleClob class bound to a temporary CLOB.

Overload List:

- [OracleClob\(OracleConnection\)](#)

This constructor creates an instance of the OracleClob class bound to a temporary CLOB with an OracleConnection object.

- [OracleClob\(OracleConnection, bool, bool\)](#)

This constructor creates an instance of the OracleClob class that is bound to a temporary CLOB, with an OracleConnection object, a boolean value for caching, and a boolean value for NCLOB.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

OracleClob(OracleConnection)

This constructor creates an instance of the OracleClob class bound to a temporary CLOB with an OracleConnection object.

Declaration

```
// C#  
public OracleClob(OracleConnection con);
```

Parameters

- *con*
The OracleConnection object.

Exceptions

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

Remarks

The connection must be opened explicitly by the application. OracleClob does not open the connection implicitly. The temporary CLOB utilizes the provided connection to store CLOB data. Caching is not enabled by default.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

OracleClob(OracleConnection, bool, bool)

This constructor creates an instance of the `OracleClob` class that is bound to a temporary CLOB, with an `OracleConnection` object, a boolean value for caching, and a boolean value for NCLOB.

Declaration

```
// C#  
public OracleClob(OracleConnection con, bool bCaching, bool bNCLOB);
```

Parameters

- *con*
The `OracleConnection` object connection.
- *bCaching*
A flag that indicates whether or not server-side caching is enabled.
- *bNCLOB*
A flag that is set to true if the instance is a NCLOB or false if it is a CLOB.

Exceptions

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

The connection must be opened explicitly by the application. `OracleClob` does not open the connection implicitly. The temporary CLOB or NCLOB uses the provided connection to store CLOB data.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

OracleClob Static Fields

OracleClob static fields are listed in [Table 13–24](#).

Table 13–24 OracleClob Static Fields

| Field | Description |
|-------------------------|-------------------------------------------------------------------------------------------------------|
| MaxSize | Holds the maximum number of bytes a CLOB can hold, which is 4,294,967,295 (2 ³² - 1) bytes |
| Null | Represents a null value that can be assigned to the value of an OracleClob instance |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

MaxSize

The `MaxSize` field holds the maximum number of bytes a CLOB can hold, which is 4,294,967,295 (2³² - 1) bytes.

Declaration

```
// C#  
public static readonly Int64 MaxSize = 4294967295;
```

Remarks

This field is useful in code that checks whether or not your operation exceeds the maximum length (in bytes) allowed.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

Null

This static field represents a null value that can be assigned to the value of an OracleClob instance.

Declaration

```
// C#  
public static readonly OracleClob Null;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

OracleClob Static Methods

OracleClob static methods are listed in [Table 13-25](#).

Table 13-25 OracleClob Static Methods

| Methods | Description |
|---------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

OracleClob Instance Properties

OracleClob instance properties are listed in [Table 13–26](#).

Table 13–26 OracleClob Instance Properties

| Properties | Description |
|------------------------------------|--------------------------------------------------------------------------------------------------------------|
| CanRead | Indicates whether or not the LOB stream can be read |
| CanSeek | Indicates whether or not forward and backward seek operations can be performed |
| CanWrite | Indicates whether or not the LOB stream can be written |
| Connection | Indicates the OracleConnection that is used to retrieve and write CLOB data |
| IsEmpty | Indicates whether the CLOB is empty or not |
| IsInChunkWriteMode | Indicates whether or not the CLOB has been opened |
| IsNClob | Indicates whether or not the OracleClob object represents an NCLOB. |
| IsNull | Indicates whether or not the current instance has a null value |
| IsTemporary | Indicates whether or not the current instance is bound to a temporary CLOB |
| Length | Indicates the size of the CLOB data in bytes |
| OptimumChunkSize | Indicates the minimum number of bytes to retrieve or send from the database during a read or write operation |
| Position | Indicates the current read or write position in the LOB stream in bytes |
| Value | Returns the data, starting from the first character in the CLOB or NCLOB, as a string |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

CanRead

Overrides [Stream](#)

This instance property indicates whether or not the LOB stream can be read.

Declaration

```
// C#
public override bool CanRead{get;}
```

Property Value

If the LOB stream can be read, returns true; otherwise, returns false.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

CanSeek

Overrides `Stream`

This instance property indicates whether or not forward and backward seek operations can be performed.

Declaration

```
// C#  
public override bool CanSeek{get;}
```

Property Value

If forward and backward seek operations can be performed, returns `true`; otherwise, returns `false`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

CanWrite

Overrides `Stream`

This instance property indicates whether or not the LOB object supports writing.

Declaration

```
// C#  
public override bool CanWrite{get;}
```

Property Value

If the LOB stream can be written, returns `true`; otherwise, returns `false`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

Connection

This instance property indicates the `OracleConnection` that is used to retrieve and write CLOB data.

Declaration

```
// C#  
public OracleConnection Connection {get;}
```

Property Value

An OracleConnection.

Exceptions

ObjectDisposedException - The object is already disposed.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

IsEmpty

This instance property indicates whether the CLOB is empty or not.

Declaration

```
// C#  
public bool IsEmpty {get;}
```

Property Value

A bool.

Exceptions

ObjectDisposedException - The object is already disposed.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

IsInChunkWriteMode

This instance property indicates whether or not the CLOB has been opened to defer index updates.

Declaration

```
// C#  
public bool IsInChunkWriteMode{get;}
```

Property Value

If the CLOB has been opened, returns true; otherwise, returns false.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

IsNClob

This instance property indicates whether or not the `OracleClob` object represents an `NClob`.

Declaration

```
// C#  
public bool IsNClob {get;}
```

Property Value

A `bool`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

IsNull

This property indicates whether or not the current instance has a null value.

Declaration

```
// C#  
public bool IsNull{get;}
```

Property Value

Returns `true` if the current instance has a null value; otherwise, returns `false`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

IsTemporary

This instance property indicates whether or not the current instance is bound to a temporary `CLOB`.

Declaration

```
// C#  
public bool IsTemporary {get;}
```

Property Value

A bool.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

Length

Overrides Stream

This instance property indicates the size of the CLOB data in bytes.

Declaration

```
// C#  
public override Int64 Length {get;}
```

Property Value

An Int64 that indicates the size of the CLOB in bytes.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

OptimumChunkSize

This instance property indicates the minimum number of bytes to retrieve or send from the database during a read or write operation.

Declaration

```
// C#  
public int OptimumChunkSize{get;}
```

Property Value

A number representing the minimum bytes to retrieve or send.

Exceptions

ObjectDisposedException - The object is already disposed.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

Position

Overrides Stream

This instance property indicates the current read or write position in the LOB stream in bytes.

Declaration

```
// C#  
public override Int64 Position{get; set;}
```

Property Value

An `Int64` that indicates the read or write position.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - The `Position` is less than 0.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

Value

This instance property returns the data, starting from the first character in the CLOB or NCLOB, as a string.

Declaration

```
// C#  
public string Value{get;}
```

Property Value

A string.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - The `Value` is less than 0.

Remarks

The value of `Position` is neither used nor changed by using this property.

The maximum string length that can be returned by this property is 2 GB.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

OracleClob Instance Methods

The OracleClob instance methods are listed in [Table 13–27](#).

Table 13–27 OracleClob Instance Methods

| Methods | Description |
|---------------------------------|-------------------------------------------------------------------------------------|
| Append | Appends data to the current OracleClob instance (Overloaded) |
| BeginChunkWrite | Opens the CLOB |
| BeginRead | Inherited from <code>System.IO.Stream</code> |
| BeginWrite | Inherited from <code>System.IO.Stream</code> |
| Clone | Creates a copy of an OracleClob object |
| Close | Closes the current stream and releases resources associated with it |
| Compare | Compares data referenced by the current instance to that of the supplied object |
| CopyTo | Copies the data to an OracleClob (Overloaded) |
| CreateObjRef | Inherited from <code>System.MarshalByRefObject</code> |
| Dispose | Releases resources allocated by this object |
| EndChunkWrite | Closes the CLOB referenced by the current OracleClob instance |
| EndRead | Inherited from <code>System.IO.Stream</code> |
| EndWrite | Inherited from <code>System.IO.Stream</code> |
| Equals | Inherited from <code>System.Object</code> (Overloaded) |
| Erase | Erases the specified amount of data (Overloaded) |
| Flush | <i>Not supported</i> |
| GetHashCode | Returns a hash code for the current instance |
| GetLifetimeService | Inherited from <code>System.MarshalByRefObject</code> |
| GetType | Inherited from <code>System.Object</code> |
| InitializeLifetimeService | Inherited from <code>System.MarshalByRefObject</code> |
| IsEqual | Compares the LOB data referenced by two OracleClobs |
| Read | Reads from the current instance (Overloaded) |
| ReadByte | Inherited from <code>System.IO.Stream</code> |
| Search | Searches for a character pattern in the current instance of OracleClob (Overloaded) |
| Seek | Sets the position in the current LOB stream |
| SetLength | Trims or truncates the CLOB value |
| ToString | Inherited from <code>System.Object</code> |
| Write | Writes the provided buffer into the OracleClob (Overloaded) |
| WriteByte | Inherited from <code>System.IO.Stream</code> |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

Append

This instance method appends data to the current `OracleClob` instance.

Overload List:

- [Append\(OracleClob\)](#)

This instance method appends the CLOB data referenced by the provided `OracleClob` object to the current `OracleClob` instance.

- [Append\(byte \[\], int, int\)](#)

This instance method appends data at the end of the CLOB, from the supplied byte array buffer, starting from offset (in bytes) of the supplied byte array buffer.

- [Append\(char \[\], int, int\)](#)

This instance method appends data from the supplied character array buffer to the end of the current `OracleClob` instance, starting at the offset (in characters) of the supplied character buffer.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

Append(OracleClob)

This instance method appends the CLOB data referenced by the provided `OracleClob` object to the current `OracleClob` instance.

Declaration

```
// C#
public void Append(OracleClob obj);
```

Parameters

- *obj*
An `OracleClob` object.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The parameter has a different connection than the object, `OracleConnection` is not opened, or `OracleConnection` has been reopened.

Remarks

No character set conversions are made.

The provided object and the current instance must be using the same connection; that is, the same `OracleConnection` object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

Append(byte [], int, int)

This instance method appends data at the end of the CLOB, from the supplied byte array buffer, starting from offset (in bytes) of the supplied byte array buffer.

Declaration

```
// C#  
public int Append(byte[] buffer, int offset, int count);
```

Parameters

- *buffer*
An array of bytes, representing a Unicode string.
- *offset*
The zero-based byte offset in the buffer from which data is read.
- *count*
The number of bytes to be appended.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - Either the *offset* or the *count* parameter is not even.

Remarks

Both *offset* and *count* must be even numbers for CLOB and NCLOB because every two bytes represent a Unicode character.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

Append(char [], int, int)

This instance method appends data from the supplied character array buffer to the end of the current `OracleClob` instance, starting at the offset (in characters) of the supplied character buffer.

Declaration

```
// C#  
public void Append(char[] buffer, int offset, int count);
```

Parameters

- *buffer*
An array of characters.
- *offset*
The zero-based offset (in characters) in the buffer from which data is read.
- *count*
The number of characters to be appended.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
using Oracle.DataAccess.Types;  
  
class AppendSample  
{  
    static void Main()  
    {  
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";  
        OracleConnection con = new OracleConnection(constr);  
        con.Open();  
  
        OracleClob clob = new OracleClob(con);  
  
        // Append 2 chars {'d', 'e'} to the OracleClob  
        char[] buffer = new char[3] {'d', 'e', 'f'};  
        clob.Append(buffer, 0, 2);  
  
        // Prints "clob.Value = de"  
        Console.WriteLine("clob.Value = " + clob.Value);  
  
        clob.Close();  
        clob.Dispose();  
  
        con.Close();  
        con.Dispose();  
    }  
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

BeginChunkWrite

This instance method opens the CLOB.

Declaration

```
// C#  
public void BeginChunkWrite();
```

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The *OracleConnection* is not open or has been closed during the lifetime of the object.

Remarks

BeginChunkWrite does not need to be called before manipulating the CLOB data. This is provided for performance reasons.

After this method is called, write operations do not cause the domain or function-based index on the column to be updated. Index updates occur only once after *EndChunkWrite* is called.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

Clone

This instance method creates a copy of an *OracleClob* object.

Declaration

```
// C#  
public object Clone();
```

Return Value

An *OracleClob* object.

Implements

ICloneable

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The *OracleConnection* is not open or has been closed during the lifetime of the object.

Remarks

The cloned object has the same property values as that of the object being cloned.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class CloneSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleClob clob1 = new OracleClob(con);

        // Prints "clob1.Position = 0"
        Console.WriteLine("clob1.Position = " + clob1.Position);

        // Set the Position before calling Clone()
        clob1.Position = 1;

        // Clone the OracleClob
        OracleClob clob2 = (OracleClob)clob1.Clone();

        // Prints "clob2.Position = 1"
        Console.WriteLine("clob2.Position = " + clob2.Position);

        clob1.Close();
        clob1.Dispose();

        clob2.Close();
        clob2.Dispose();

        con.Close();
        con.Dispose();
    }
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Close

Overrides Stream

This instance method closes the current stream and releases resources associated with it.

Declaration

```
// C#  
public override void Close();
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Compare

This instance method compares data referenced by the current instance to that of the supplied object.

Declaration

```
// C#  
public int Compare(Int64 src_offset, OracleClob obj, Int64 dst_offset,  
    Int64 amount);
```

Parameters

- *src_offset*
The comparison starting point (in characters) for the current instance.
- *obj*
The provided OracleClob object.
- *dst_offset*
The comparison starting point (in characters) for the provided OracleClob.
- *amount*
The number of characters to compare.

Return Value

The method returns a value that is:

- Less than zero: if the data referenced by the current instance is less than that of the supplied instance.
- Zero: if both objects reference the same data.
- Greater than zero: if the data referenced by the current instance is greater than that of the supplied instance.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The parameter has a different connection than the object, OracleConnection is not opened, or OracleConnection has been reopened.

ArgumentOutOfRangeException - Either the *src_offset*, *dst_offset*, or *amount* parameter is less than 0.

Remarks

The character set of the two `OracleClob` objects being compared should be the same for a meaningful comparison.

The provided object and the current instance must be using the same connection, that is, the same `OracleConnection` object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

CopyTo

`CopyTo` copies data from the current instance to the provided `OracleClob` object.

Overload List:■ [CopyTo\(OracleClob\)](#)

This instance method copies data from the current instance to the provided `OracleClob` object.

■ [CopyTo\(OracleClob, Int64\)](#)

This instance method copies data from the current `OracleClob` instance to the provided `OracleClob` object with the specified destination offset.

■ [CopyTo\(Int64, OracleClob, Int64, Int64\)](#)

This instance method copies data from the current `OracleClob` instance to the provided `OracleClob` object with the specified source offset, destination offset, and character amounts.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

CopyTo(OracleClob)

This instance method copies data from the current instance to the provided `OracleClob` object.

Declaration

```
// C#  
public Int64 CopyTo(OracleClob obj);
```

Parameters

-
- obj*

The `OracleClob` object to which the data is copied.

Return Value

The return value is the amount copied.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - This exception is thrown if any of the following conditions exist:

- The `OracleConnection` is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

Remarks

The provided object and the current instance must be using the same connection, that is, the same `OracleConnection` object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

CopyTo(OracleClob, Int64)

This instance method copies data from the current `OracleClob` instance to the provided `OracleClob` object with the specified destination offset.

Declaration

```
// C#  
public Int64 CopyTo(OracleClob obj, Int64 dst_offset);
```

Parameters

- *obj*
The `OracleClob` object to which the data is copied.
- *dst_offset*
The offset (in characters) at which the `OracleClob` object is copied.

Return Value

The return value is the amount copied.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`ArgumentOutOfRangeException` - The *dst_offset* is less than 0.

`InvalidOperationException` - This exception is thrown if any of the following conditions exist:

- The `OracleConnection` is not open or has been closed during the lifetime of the object.
- The LOB object parameter has a different connection than the object.

Remarks

If the *dst_offset* is beyond the end of the OracleClob data, spaces are written into the OracleClob until the *dst_offset* is met.

The offsets are 0-based. No character conversion is performed by this operation.

The provided object and the current instance must be using the same connection; that is, the same OracleConnection object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

CopyTo(Int64, OracleClob, Int64, Int64)

This instance method copies data from the current OracleClob instance to the provided OracleClob object with the specified source offset, destination offset, and character amounts.

Declaration

```
// C#  
public Int64 CopyTo(Int64 src_offset, OracleClob obj, Int64 dst_offset,  
    Int64 amount);
```

Parameters

- *src_offset*
The offset (in characters) in the current instance, from which the data is read.
- *obj*
The OracleClob object to which the data is copied.
- *dst_offset*
The offset (in characters) at which the OracleClob object is copied.
- *amount*
The amount of data to be copied.

Return Value

The return value is the amount copied.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The parameter has a different connection than the object, OracleConnection is not opened, or OracleConnection has been reopened.

ArgumentOutOfRangeException - The *src_offset*, the *dst_offset*, or the *amount* parameter is less than 0.

Remarks

If the *dst_offset* is beyond the end of the OracleClob data, spaces are written into the OracleClob until the *dst_offset* is met.

The offsets are 0-based. No character conversion is performed by this operation.

The provided object and the current instance must be using the same connection, that is, the same `OracleConnection` object.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class CopyToSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleClob clob1 = new OracleClob(con);
        OracleClob clob2 = new OracleClob(con);

        // Write 4 chars, starting at buffer offset 0
        char[] buffer = new char[4] {'a', 'b', 'c', 'd'};
        clob1.Write(buffer, 0, 4);

        // Copy 2 chars from char 0 of clob1 to char 1 of clob2
        clob1.CopyTo(0, clob2, 1, 2);

        //Prints "clob2.Value = ab"
        Console.WriteLine("clob2.Value = " + clob2.Value);

        clob1.Close();
        clob1.Dispose();

        clob2.Close();
        clob2.Dispose();

        con.Close();
        con.Dispose();
    }
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Dispose

This instance method releases resources allocated by this object.

Declaration

```
public void Dispose();
```

Implements

IDisposable

Remarks

The object cannot be reused after being disposed. Although some properties can still be accessed, their values cannot be accountable. Since resources are freed, method calls can lead to exceptions.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

EndChunkWrite

This instance method closes the CLOB referenced by the current OracleClob instance.

Declaration

```
// C#  
public void EndChunkWrite();
```

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

Remarks

Index updates occur immediately if write operation(s) are deferred by the BeginChunkWrite method.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

Erase

Erase erases part or all data.

Overload List:

- [Erase\(\)](#)
This instance method erases all data.
- [Erase\(Int64, Int64\)](#)
This instance method replaces the specified amount of data (in characters) starting from the specified offset with zero-byte fillers (in characters).

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

Erase()

This instance method erases all data.

Declaration

```
// C#  
public Int64 Erase();
```

Return Value

The number of characters erased.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

Erase(Int64, Int64)

This instance method replaces the specified amount of data (in characters) starting from the specified *offset* with zero-byte fillers (in characters).

Declaration

```
// C#  
public Int64 Erase(Int64 offset, Int64 amount);
```

Parameters

- *offset*
The offset.
- *amount*
The amount of data.

Return Value

The actual number of characters erased.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The *OracleConnection* is not open or has been closed during the lifetime of the object.

ArgumentOutOfRangeException - The *offset* or *amount* parameter is less than 0.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

GetHashCode

Overrides `Object`

This method returns a hash code for the current instance.

Declaration

```
// C#  
public override int GetHashCode();
```

Return Value

An `int` representing a hash code.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

IsEqual

This instance method compares the LOB data referenced by two `OracleClob`s.

Declaration

```
// C#  
public bool IsEqual(OracleClob obj);
```

Parameters

- *obj*
An `OracleClob` object.

Return Value

Returns `true` if the current `OracleClob` and the provided `OracleClob` refer to the same LOB. Otherwise, returns `false`.

Remarks

Note that this method can return `true` even if the two `OracleClob` objects returns `false` for `==` or `Equals()` because two different `OracleClob` instances can refer to the same LOB.

The provided object and the current instance must be using the same connection, that is, the same `OracleConnection` object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

Read

Read reads a specified amount from the current instance and populates the array buffer.

Overload List:

- [Read\(byte \[\], int, int\)](#)

This instance method reads a specified amount of bytes from the current instance and populates the byte array *buffer*.
- [Read\(char \[\], int, int\)](#)

This instance method reads a specified amount of characters from the current instance and populates the character array buffer.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

Read(byte [], int, int)

Overrides *Stream*

This instance method reads a specified amount of bytes from the current instance and populates the byte array *buffer*.

Declaration

```
// C#  
public override int Read(byte [] buffer, int offset, int count);
```

Parameters

- *buffer*

The byte array buffer that is populated.
- *offset*

The offset (in bytes) at which the buffer is populated.
- *count*

The amount of bytes to be read.

Return Value

The number of bytes read from the CLOB.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

Both *offset* and *count* must be even numbers for CLOB and NCLOB because every two bytes represent a Unicode character.

The LOB data is read starting from the position specified by the `Position` property, which must also be an even number.

`OracleClob` is free to return fewer bytes than requested, even if the end of the stream has not been reached.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

Read(char [], int, int)

This instance method reads a specified amount of characters from the current instance and populates the character array buffer.

Declaration

```
// C#  
public int Read(char[ ] buffer, int offset, int count);
```

Parameters

- *buffer*
The character array buffer that is populated.
- *offset*
The offset (in characters) at which the buffer is populated.
- *count*
The amount of characters to be read.

Return Value

The return value indicates the number of characters read from the CLOB.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - This exception is thrown if any of the following conditions exist:

- The *offset* or the *count* is less than 0.
- The *offset* is greater than or equal to the `buffer.Length`.

- The *offset* and the *count* together are greater than *buffer.Length*.

Remarks

Handles all CLOB and NCLOB data as Unicode.

The LOB data is read starting from the position specified by the *Position* property.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class ReadSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleClob clob = new OracleClob(con);

        // Write 3 chars, starting at buffer offset 1
        char[] writeBuffer = new char[4] {'a', 'b', 'c', 'd'};
        clob.Write(writeBuffer, 1, 3);

        // Reset the Position (in bytes) for Read
        clob.Position = 2;

        // Read 2 chars into buffer starting at buffer offset 1
        char[] readBuffer = new char[4];
        int charsRead = clob.Read(readBuffer, 1, 2);

        // Prints "charsRead = 2"
        Console.WriteLine("charsRead = " + charsRead);

        // Prints "readBuffer = cd "
        Console.Write("readBuffer = ");
        for(int index = 0; index < readBuffer.Length; index++)
        {
            Console.Write(readBuffer[index]);
        }
        Console.WriteLine();

        clob.Close();
        clob.Dispose();

        con.Close();
        con.Dispose();
    }
}
```


See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

Search

Search searches for a character pattern in the current instance of OracleClob.

Overload List:

- [Search\(byte\[\] , Int64, Int64\)](#)
This instance method searches for a character pattern, represented by the byte array, in the current instance of OracleClob.
- [Search\(char\[\] , Int64, Int64\)](#)
This instance method searches for a character pattern in the current instance of OracleClob.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

Search(byte[] , Int64, Int64)

This instance method searches for a character pattern, represented by the byte array, in the current instance of OracleClob.

Declaration

```
// C#
public int Search(byte[] val, Int64 offset, Int64 nth);
```

Parameters

- *val*
A Unicode byte array.
- *offset*
The 0-based offset (in characters) starting from which the OracleClob is searched.
- *nth*
The specific occurrence (1-based) of the match for which the absolute offset (in characters) is returned.

Return Value

Returns the absolute *offset* of the start of the matched pattern (in bytes) for the *nth* occurrence of the match. Otherwise, 0 is returned.

Exceptions

ObjectDisposedException - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - This exception is thrown if any of the following conditions exist:

- The *offset* is less than 0.
- The *nth* is less than or equal to 0.
- The *nth* is greater than or equal to `OracleClob.MaxValue`.
- The *offset* is greater than or equal to `OracleClob.MaxValue`.

Remarks

The `byte[]` is converted to Unicode before the search is made.

The limit of the search pattern is 16383 bytes.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

Search(char[], Int64, Int64)

This instance method searches for a character pattern in the current instance of `OracleClob`.

Declaration

```
// C#  
public Int64 Search(char [ ] val, Int64 offset, Int64 nth);
```

Parameters

- *val*
The Unicode string being searched for.
- *offset*
The 0-based offset (in characters) starting from which the `OracleClob` is searched.
- *nth*
The specific occurrence (1-based) of the match for which the absolute offset (in characters) is returned.

Return Value

Returns the absolute *offset* of the start of the matched pattern (in characters) for the *nth* occurrence of the match. Otherwise, 0 is returned.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

ArgumentOutOfRangeException - This exception is thrown if any of the following conditions exist:

- The *offset* is less than 0.
- The *nth* is less than or equal to 0.
- The *val.Length* doubled is greater than 16383.
- The *nth* is greater than or equal to `OracleClob.MaxValue`.
- The *offset* is greater than or equal to `OracleClob.MaxValue`.

Remarks

The limit of the search pattern is 16383 bytes.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class SearchSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleClob clob = new OracleClob(con);

        // Write 7 chars, starting at buffer offset 0
        char[] buffer = new char[7] {'a', 'b', 'c', 'd', 'a', 'b', 'c'};
        clob.Write(buffer, 0, 7);

        // Search for the 2nd occurrence of a char pattern 'bc'
        // starting at offset 1 in the OracleBlob
        char[] pattern = new char[2] {'b', 'c'};
        long posFound = clob.Search(pattern, 1, 2);

        // Prints "posFound = 6"
        Console.WriteLine("posFound = " + posFound);

        clob.Close();
        clob.Dispose();

        con.Close();
        con.Dispose();
    }
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

Seek

Overrides `Stream`

This instance method sets the position on the current LOB stream.

Declaration

```
// C#  
public override Int64 Seek(Int64 offset, SeekOrigin origin);
```

Parameters

- *offset*
A byte offset relative to origin.
- *origin*
A value of type `System.IO.SeekOrigin` indicating the reference point used to obtain the new position.

Return Value

Returns an `Int64` that indicates the position.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

Remarks

If *offset* is negative, the new position precedes the position specified by *origin* by the number of characters specified by *offset*.

If *offset* is zero, the new position is the position specified by *origin*.

If *offset* is positive, the new position follows the position specified by *origin* by the number of characters specified by *offset*.

`SeekOrigin.Begin` specifies the beginning of a stream.

`SeekOrigin.Current` specifies the current position within a stream.

`SeekOrigin.End` specifies the end of a stream.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

SetLength

Overrides `Stream`

This instance method trims or truncates the CLOB value to the specified length (in characters).

Declaration

```
// C#
```

```
public override void SetLength(Int64 newLen);
```

Parameters

- *newLen*

The desired length of the current stream in characters.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

ArgumentOutOfRangeException - The *newLen* parameter is greater than 0.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

Write

This instance method writes data from the provided array buffer into the OracleClob.

Overload List:

- [Write\(byte\[\], int, int\)](#)

This instance method writes data from the provided byte array buffer into the OracleClob.

- [Write\(char\[\], int, int\)](#)

This instance method writes data from the provided character array buffer into the OracleClob.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

Write(byte[], int, int)

Overrides Stream

This instance method writes data from the provided byte array buffer into the OracleClob.

Declaration

```
// C#
public override void Write(byte[ ] buffer, int offset, int count);
```

Parameters

- *buffer*

The byte array buffer that represents a Unicode string.

- *offset*

The offset (in bytes) from which the buffer is read.

- *count*

The amount of data (in bytes) from the buffer to be written into the OracleClob.

Exceptions

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

`ArgumentOutOfRangeException` - This exception is thrown if any of the following conditions exist:

- The *offset* or the *count* is less than 0.
- The *offset* is greater than or equal to the *buffer.Length*.
- The *offset* and the *count* together are greater than the *buffer.Length*.
- The *offset*, the *count*, or the `Position` is not even.

Remarks

Both *offset* and *count* must be even numbers for CLOB and NCLOB because every two bytes represent a Unicode character.

The LOB data is read starting from the position specified by the `Position` property. The `Position` property must be an even number.

If necessary, proper data conversion is carried out from the client character set to the database character set.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleClob Class](#)
- [OracleClob Members](#)

Write(char[], int, int)

This instance method writes data from the provided character array buffer into the OracleClob.

Declaration

```
// C#  
public void Write(char[ ] buffer, int offset, int count);
```

Parameters

- *buffer*

The character array buffer that is written to the OracleClob.

- *offset*

The offset (in characters) from which the *buffer* is read.

- *count*
The amount (in characters) from the buffer that is to be written into the OracleClob.

Exceptions

ObjectDisposedException - The object is already disposed.

InvalidOperationException - The OracleConnection is not open or has been closed during the lifetime of the object.

ArgumentOutOfRangeException - This exception is thrown if any of the following conditions exist:

- The *offset* or the *count* is less than 0.
- The *offset* is greater than or equal to the *buffer.Length*.
- The *offset* and the *count* together are greater than *buffer.Length*.
- The Position is not even.

Remarks

Handles all CLOB and NCLOB data as Unicode.

The LOB data is read starting from the position specified by the Position property.

If necessary, proper data conversion is carried out from the client character set to the database character set.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class WriteSample
{
    static void Main()
    {
        string constr = "User Id=scott;Password=tiger;Data Source=oracle";
        OracleConnection con = new OracleConnection(constr);
        con.Open();

        OracleClob clob = new OracleClob(con);

        // Set the Position for the Write;
        clob.Position = 0;

        // Begin ChunkWrite to improve performance
        // Index updates occur only once after EndChunkWrite
        clob.BeginChunkWrite();

        // Write to the OracleClob in 5 chunks of 2 chars each
        char[] c = new char[2] {'a', 'b'};
        for (int index = 0; index < 5; index++)
        {
            clob.Write(c, 0, c.Length);
        }
        clob.EndChunkWrite();
    }
}
```

```
// Prints "clob.Value = ababababab"
Console.WriteLine("clob.Value = " + clob.Value);

clob.Close();
clob.Dispose();

con.Close();
con.Dispose();
}
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleClob Class](#)
- [OracleClob Members](#)

OracleRefCursor Class

An OracleRefCursor object represents an Oracle REF CURSOR.

Class Inheritance

System.Object

System.MarshalRefByObject

Oracle.DataAccess.Types.OracleRefCursor

Declaration

```
// C#
public sealed class OracleRefCursor : MarshalByRefObject, IDisposable, INullable
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|--------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Types | Oracle.ManagedDataAccess.Types |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

To minimize the number of open server cursors, OracleRefReader objects should be explicitly disposed.

Example

```
// Database Setup
/*
connect scott/tiger@oracle
CREATE OR REPLACE FUNCTION MyFunc(refcur_out OUT SYS_REFCURSOR)
RETURN SYS_REFCURSOR IS refcur_ret SYS_REFCURSOR;
BEGIN
OPEN refcur_ret FOR SELECT * FROM EMP;
OPEN refcur_out FOR SELECT * FROM DEPT;
RETURN refcur_ret;
END MyFunc;
/
*/

// C#
using System;
using System.Data;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class OracleRefCursorSample
{
```

```
static void Main()
{
    // Example demonstrates how to use REF CURSORS returned from
    // PL/SQL Stored Procedures or Functions
    // Create the PL/SQL Function MyFunc as defined previously

    string constr = "User Id=scott;Password=tiger;Data Source=oracle";
    OracleConnection con = new OracleConnection(constr);
    con.Open();

    // Create an OracleCommand
    OracleCommand cmd = new OracleCommand("MyFunc", con);
    cmd.CommandType = CommandType.StoredProcedure;

    // Bind the parameters
    // p1 is the RETURN REF CURSOR bound to SELECT * FROM EMP;
    OracleParameter p1 =
        cmd.Parameters.Add("refcur_ret", OracleDbType.RefCursor);
    p1.Direction = ParameterDirection.ReturnValue;

    // p2 is the OUT REF CURSOR bound to SELECT * FROM DEPT
    OracleParameter p2 =
        cmd.Parameters.Add("refcur_out", OracleDbType.RefCursor);
    p2.Direction = ParameterDirection.Output;

    // Execute the command
    cmd.ExecuteNonQuery();

    // Construct an OracleDataReader from the REF CURSOR
    OracleDataReader reader1 = ((OracleRefCursor)p1.Value).GetDataReader();

    // Prints "reader1.GetName(0) = EMPNO"
    Console.WriteLine("reader1.GetName(0) = " + reader1.GetName(0));

    // Construct an OracleDataReader from the REF CURSOR
    OracleDataReader reader2 = ((OracleRefCursor)p2.Value).GetDataReader();

    // Prints "reader2.GetName(0) = DEPTNO"
    Console.WriteLine("reader2.GetName(0) = " + reader2.GetName(0));

    reader1.Close();
    reader1.Dispose();

    reader2.Close();
    reader2.Dispose();

    p1.Dispose();
    p2.Dispose();

    cmd.Dispose();

    con.Close();
    con.Dispose();
}
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleRefCursor Members](#)
- [OracleRefCursor Static Methods](#)
- [OracleRefCursor Static Fields](#)
- [OracleRefCursor Properties](#)
- [OracleRefCursor Instance Methods](#)

OracleRefCursor Members

OracleRefCursor members are listed in the following tables.

OracleRefCursor Static Methods

OracleRefCursor static methods are listed in [Table 13–28](#).

Table 13–28 OracleRefCursor Static Methods

| Methods | Description |
|------------------------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

OracleRefCursor Static Fields

OracleRefCursor static field is listed in [Table 13–29](#).

Table 13–29 OracleRefCursor Static Field

| Methods | Description |
|----------------------|-----------------------------------------------------------------------------|
| Null | Represents a null value that can be assigned to an OracleRefCursor instance |

OracleRefCursor Properties

OracleRefCursor properties are listed in [Table 13–30](#).

Table 13–30 OracleRefCursor Properties

| Properties | Description |
|----------------------------|--------------------------------------------------------------------------------------------------|
| Connection | A reference to the OracleConnection used to fetch the REF CURSOR data |
| FetchSize | Specifies the size that the OracleDataReader internal cache needs to store result set data |
| IsNull | Indicates whether or not the OracleRefCursor is null |
| RowSize | Specifies the amount of memory the OracleRefcursor internal cache needs to store one row of data |

OracleRefCursor Instance Methods

OracleRefCursor instance methods are listed in [Table 13–31](#).

Table 13–31 OracleRefCursor Instance Methods

| Methods | Description |
|-------------------------------|----------------------------------------------------------------|
| Dispose | Disposes the resources allocated by the OracleRefCursor object |
| Equals | Inherited from System.Object (Overloaded) |
| GetDataReader | Returns an OracleDataReader object for the REF CURSOR |
| GetHashCode | Inherited from System.Object |
| GetType | Inherited from System.Object |
| ToString | Inherited from System.Object |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRefCursor Class](#)

OracleRefCursor Static Methods

OracleRefCursor static methods are listed in [Table 13–32](#).

Table 13–32 OracleRefCursor Static Methods

| Methods | Description |
|---------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

OracleRefCursor Static Fields

OracleRefCursor static field is listed in [Table 13–32](#).

Table 13–33 OracleRefCursor Static Field

| Methods | Description |
|----------------------|-----------------------------------------------------------------------------|
| Null | Represents a null value that can be assigned to an OracleRefCursor instance |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

Null

This static field represents a null value that can be assigned to an OracleRefCursor instance.

Declaration

```
// C#  
public static readonly OracleRefCursor Null;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

OracleRefCursor Properties

OracleRefCursor properties are listed in [Table 13–34](#).

Table 13–34 OracleRefCursor Properties

| Properties | Description |
|----------------------------|---------------------------------------------------------------------------------------------------------------|
| Connection | A reference to the <code>OracleConnection</code> used to fetch the REF CURSOR data |
| FetchSize | Specifies the size that the <code>OracleDataReader</code> internal cache needs to store result set data |
| IsNull | Indicates whether or not the <code>OracleRefCursor</code> is null |
| RowSize | Specifies the amount of memory the <code>OracleRefCursor</code> internal cache needs to store one row of data |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

Connection

This property refers to the `OracleConnection` used to fetch the REF CURSOR data.

Declaration

```
// C#
public OracleConnection Connection {get;}
```

Property Value

An `OracleConnection`.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

This property is bound to a REF CURSOR once it is set. After the `OracleRefCursor` object is created by the constructor, this property is initially null. An `OracleRefCursor` object can be bound to a REF CURSOR after a command execution.

If the connection is closed or returned to the connection pool, the `OracleRefCursor` is placed in an uninitialized state and no operation can be carried out from it. However, the uninitialized `OracleRefCursor` can be reassigned to another REF CURSOR.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

FetchSize

This property specifies the size that the `OracleDataReader` internal cache needs to store result set data.

Declaration

```
// C#  
public long FetchSize {get; set;}
```

Property Value

A `long` that specifies the size (in bytes) of the `OracleRefCursor` internal cache.

Exceptions

`ArgumentException` - The `FetchSize` value specified is invalid.

Remarks

Default = 131072.

The `FetchSize` property value is inherited by the `OracleCommand` that created the `OracleRefCursor` object. The `FetchSize` property on the `OracleDataReader` object determines the amount of data the `OracleRefCursor` fetches into its internal cache for each database round-trip.

This property is useful if the `OracleRefCursor` is explicitly used to fill the `DataSet` or `DataTable` through the `OracleDataAdapter`, because it can provide control on how the data of the `REF CURSOR` is fetched.

If an `OracleDataReader` object is created from the `OracleRefCursor`, the resulting `OracleDataReader` object inherits the `FetchSize` value of the `OracleDataReader` object. However, the inherited value can be overridden, if it is set before the first invocation of the `OracleDataReader` `Read` method for the given result set, by setting the `OracleDataReader` `FetchSize` property.

The `RowSize` and `FetchSize` properties handle UDT and `XMLType` data differently than other scalar data types. Because only a reference to the UDT and `XMLType` data is stored in the ODP.NET's internal cache, the `RowSize` property accounts for only the memory needed for the reference (which is very small) and not the actual size of the UDT and `XMLType` data. Thus, applications can inadvertently fetch a large number of UDT or `XMLType` instances from the database in a single database round-trip. This is because the actual size of UDT and `XMLType` data does not count against the `FetchSize`, and it would require numerous UDT and `XMLType` references to fill up the default cache size of 131072 bytes. Therefore, when fetching UDT or `XMLType` data, the `FetchSize` property must be appropriately configured to control the number of UDT and `XMLType` instances that are to be fetched, rather than the amount of the actual UDT and `XMLType` data to be fetched.

NOTE: For LOB and `LONG` data types, only the sizes specified in the `InitialLOBFetchSize` and `InitialLONGFetchSize` properties are accounted for by the `RowSize` property in addition to the metadata and reference information that is maintained by the cache for each LOB in the select list.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

IsNull

This property indicates whether or not the `OracleRefCursor` is null.

Declaration

```
// C#  
public bool IsNull {get;}
```

Property Value

Returns true if the `OracleRefCursor` represents a null value. Returns false otherwise.

Exception

`ObjectDisposedException` - The object is already disposed.

`InvalidOperationException` - The `OracleConnection` is not open or has been closed during the lifetime of the object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

RowSize

This property specifies the amount of memory the `OracleRefcursor` internal cache needs to store one row of data.

Declaration

```
// C#  
public long RowSize {get;}
```

Property Value

A long that indicates the amount of memory (in bytes) that an `OracleRefcursor` needs to store one row of data for the executed query.

Remarks

The `RowSize` property is set to a nonzero value when the `OracleRefcursor` object is created. This property can be used at design time or dynamically during run time, to set the `FetchSize`, based on number of rows. For example, to enable the `OracleRefcursor` to fetch *N* rows for each database round-trip, the `OracleRefcursor FetchSize` property can be set dynamically to `RowSize * N`. Note that for the `FetchSize` to take effect appropriately, it must be set before the it is used to fill the `DataSet/DataTable` using `OracleDataAdapter`.

If an `OracleDataReader` is obtained from the `OracleRefCursor` through the `GetDataReader` method, the resulting `OracleDataReader` will have its `FetchSize` property set to the `FetchSize` value of the `OracleRefCursor`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

OracleRefCursor Instance Methods

OracleRefCursor instance methods are listed in [Table 13–35](#).

Table 13–35 OracleRefCursor Instance Methods

| Methods | Description |
|-------------------------------|----------------------------------------------------------------|
| Dispose | Disposes the resources allocated by the OracleRefCursor object |
| Equals | Inherited from System.Object (Overloaded) |
| GetDataReader | Returns an OracleDataReader object for the REF CURSOR |
| GetHashCode | Inherited from System.Object |
| GetType | Inherited from System.Object |
| ToString | Inherited from System.Object |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

Dispose

This instance method disposes of the resources allocated by the OracleRefCursor object.

Declaration

```
// C#
public void Dispose();
```

Implements

IDisposable

Remarks

The object cannot be reused after being disposed.

Once `Dispose()` is called, the object of `OracleRefCursor` is in an uninitialized state. Although some properties can still be accessed, their values may not be accountable. Since resources are freed, method calls can lead to exceptions.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

GetDataReader

This instance method returns an OracleDataReader object for the REF CURSOR.

Declaration

```
// C#  
public OracleDataReader GetDataReader();
```

Return Value

OracleDataReader

Remarks

Using the OracleDataReader, rows can be fetched from the REF CURSOR.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRefCursor Class](#)
- [OracleRefCursor Members](#)

Oracle Data Provider for .NET Types Structures

This chapter describes the ODP.NET Types structures.

This chapter contains these topics:

- [OracleBinary Structure](#)
- [OracleBoolean Structure](#)
- [OracleDate Structure](#)
- [OracleDecimal Structure](#)
- [OracleIntervalDS Structure](#)
- [OracleIntervalYM Structure](#)
- [OracleString Structure](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampTZ Structure](#)
- [INullable Interface](#)

OracleBinary Structure

The OracleBinary structure represents a variable-length stream of binary data to be stored in or retrieved from a database.

Class Inheritance

System.Object

System.ValueType

Oracle.DataAccess.Types.OracleBinary

Declaration

```
// C#
public struct OracleBinary : IComparable, INullable, IXmlSerializable
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|--------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Types | Oracle.ManagedDataAccess.Types |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#

using System;
using Oracle.DataAccess.Types;

class OracleBinarySample
{
    static void Main(string[] args)
    {
        // Initialize the OracleBinary structures
        OracleBinary binary1= new OracleBinary(new byte[] {1,2,3,4,5});
        OracleBinary binary2 = new OracleBinary(new byte[] {1,2,3});
        OracleBinary binary3 = new OracleBinary(new byte[] {4,5});
        OracleBinary binary4 = binary2 + binary3;

        // Compare binary1 and binary4; they're equal
        if (binary1 == binary4)
            Console.WriteLine("The two OracleBinary structs are equal");
        else
            Console.WriteLine("The two OracleBinary structs are different");
    }
}
```


See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Members](#)
- [OracleBinary Constructor](#)
- [OracleBinary Static Fields](#)
- [OracleBinary Static Methods](#)
- [OracleBinary Static Operators](#)
- [OracleBinary Static Type Conversion Operators](#)
- [OracleBinary Properties](#)
- [OracleBinary Instance Methods](#)

OracleBinary Members

OracleBinary members are listed in the following tables:

OracleBinary Constructors

OracleBinary constructors are listed in [Table 14-1](#)

Table 14-1 OracleBinary Constructors

| Constructor | Description |
|------------------------------------------|-------------------------------------------------------|
| OracleBinary Constructor | Instantiates a new instance of OracleBinary structure |

OracleBinary Static Fields

The OracleBinary static fields are listed in [Table 14-2](#).

Table 14-2 OracleBinary Static Fields

| Field | Description |
|----------------------|-------------------------------------------------------------------------------------------|
| Null | Represents a null value that can be assigned to an instance of the OracleBinary structure |

OracleBinary Static Methods

The OracleBinary static methods are listed in [Table 14-3](#).

Table 14-3 OracleBinary Static Methods

| Methods | Description |
|------------------------------------|-------------------------------------------------------------------------------------------|
| Concat | Returns the concatenation of two OracleBinary structures |
| Equals | Determines if two OracleBinary values are equal (Overloaded) |
| GreaterThan | Determines if the first of two OracleBinary values is greater than the second |
| GreaterThanOrEqual | Determines if the first of two OracleBinary values is greater than or equal to the second |
| LessThan | Determines if the first of two OracleBinary values is less than the second |
| LessThanOrEqual | Determines if the first of two OracleBinary values is less than or equal to the second |
| NotEquals | Determines if two OracleBinary values are not equal |

OracleBinary Static Operators

The OracleBinary static operators are listed in [Table 14-4](#).

Table 14-4 OracleBinary Static Operators

| Operator | Description |
|-----------------------------|-------------------------------------------------|
| operator + | Concatenates two OracleBinary values |
| operator == | Determines if two OracleBinary values are equal |

Table 14–4 (Cont.) OracleBinary Static Operators

| Operator | Description |
|--------------------------------|-------------------------------------------------------------------------------------------|
| operator > | Determines if the first of two OracleBinary values is greater than the second |
| operator >= | Determines if the first of two OracleBinary values is greater than or equal to the second |
| operator != | Determines if two OracleBinary values are not equal |
| operator < | Determines if the first of two OracleBinary value is less than the second |
| operator <= | Determines if the first of two OracleBinary value is less than or equal to the second |

OracleBinary Static Type Conversion Operators

The OracleBinary static type conversion operators are listed in [Table 14–5](#).

Table 14–5 OracleBinary Static Type Conversion Operators

| Operator | Description |
|------------------------------------------------|---------------------------------------------------------|
| explicit operator byte[] | Converts an instance value to a byte array |
| implicit operator OracleBinary | Converts an instance value to an OracleBinary structure |

OracleBinary Properties

The OracleBinary properties are listed in [Table 14–6](#).

Table 14–6 OracleBinary Properties

| Properties | Description |
|------------------------|-------------------------------------------------------------------------|
| IsNull | Indicates whether or not the current instance has a null value |
| Item | Obtains the particular byte in an OracleBinary structure using an index |
| Length | Returns the length of the binary data |
| Value | Returns the binary data that is stored in an OracleBinary structure |

OracleBinary Instance Methods

The OracleBinary instance methods are listed in [Table 14–7](#).

Table 14–7 OracleBinary Instance Methods

| Methods | Description |
|-----------------------------|---------------------------------------------------------------------------------------------------------|
| CompareTo | Compares the current instance to an object and returns an integer that represents their relative values |
| Equals | Determines if two objects contain the same binary data (Overloaded) |
| GetHashCode | Returns a hash code for the current instance |
| GetType | Inherited from System.Object |
| ToString | Converts the current OracleBinary structure to a string |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)

OracleBinary Constructor

The `OracleBinary` constructor instantiates a new instance of the `OracleBinary` structure and sets its value to the provided array of bytes.

Declaration

```
// C#  
public OracleBinary(byte[] bytes);
```

Parameters

- *bytes*

A byte array.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

OracleBinary Static Fields

The OracleBinary static fields are listed in [Table 14–8](#).

Table 14–8 OracleBinary Static Fields

| Field | Description |
|----------------------|-------------------------------------------------------------------------------------------|
| Null | Represents a null value that can be assigned to an instance of the OracleBinary structure |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

Null

This static field represents a null value that can be assigned to an instance of the OracleBinary structure.

Declaration

```
// C#  
public static readonly OracleBinary Null;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

OracleBinary Static Methods

The OracleBinary static methods are listed in [Table 14–9](#).

Table 14–9 OracleBinary Static Methods

| Methods | Description |
|------------------------------------|-------------------------------------------------------------------------------------------|
| Concat | Returns the concatenation of two OracleBinary structures |
| Equals | Determines if two OracleBinary values are equal (Overloaded) |
| GreaterThan | Determines if the first of two OracleBinary values is greater than the second |
| GreaterThanOrEqual | Determines if the first of two OracleBinary values is greater than or equal to the second |
| LessThan | Determines if the first of two OracleBinary values is less than the second |
| LessThanOrEqual | Determines if the first of two OracleBinary values is less than or equal to the second |
| NotEquals | Determines if two OracleBinary values are not equal |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

Concat

This method returns the concatenation of two OracleBinary structures.

Declaration

```
// C#
public static OracleBinary Concat(OracleBinary value1, OracleBinary value2);
```

Parameters

- *value1*
The first OracleBinary.
- *value2*
The second OracleBinary.

Return Value

An OracleBinary.

Remarks

If either argument has a null value, the returned OracleBinary structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

Equals

This method determines if two `OracleBinary` values are equal.

Declaration

```
// C#  
public static bool Equals(OracleBinary value1, OracleBinary value2);
```

Parameters

- *value1*
The first `OracleBinary`.
- *value2*
The second `OracleBinary`.

Return Value

Returns true if two `OracleBinary` values are equal; otherwise returns false.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleBinary` that has a value is greater than an `OracleBinary` that has a null value.
- Two `OracleBinary`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

GreaterThan

This method determines whether or not the first of two `OracleBinary` values is greater than the second.

Declaration

```
// C#  
public static bool GreaterThan(OracleBinary value1, OracleBinary value2);
```

Parameters

- *value1*
The first `OracleBinary`.
- *value2*

The second OracleBinary.

Return Value

Returns true if the first of two OracleBinary values is greater than the second; otherwise returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleBinary that has a value is greater than an OracleBinary that has a null value.
- Two OracleBinarys that contain a null value are equal.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Types;  
  
class GreaterThanSample  
{  
    static void Main(string[] args)  
    {  
        OracleBinary binary1 = OracleBinary.Null;  
        OracleBinary binary2 = new OracleBinary(new byte[] {1});  
  
        // Compare two OracleBinary structs; binary1 < binary2  
        if (OracleBinary.GreaterThan(binary1, binary2))  
            Console.WriteLine("binary1 > binary2");  
        else  
            Console.WriteLine("binary1 < binary2");  
    }  
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

GreaterThanOrEqual

This method determines whether or not the first of two OracleBinary values is greater than or equal to the second.

Declaration

```
// C#  
public static bool GreaterThanOrEqual(OracleBinary value1, OracleBinary value2);
```

Parameters

- *value1*
The first OracleBinary.
- *value2*

The second `OracleBinary`.

Return Value

Returns `true` if the first of two `OracleBinary` values is greater than or equal to the second; otherwise returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleBinary` that has a value is greater than an `OracleBinary` that has a null value.
- Two `OracleBinary`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

LessThan

This method determines whether or not the first of two `OracleBinary` values is less than the second.

Declaration

```
// C#  
public static bool LessThan(OracleBinary value1, OracleBinary value2);
```

Parameters

- *value1*
The first `OracleBinary`.
- *value2*
The second `OracleBinary`.

Return Value

Returns `true` if the first of two `OracleBinary` values is less than the second; otherwise returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleBinary` that has a value is greater than an `OracleBinary` that has a null value.
- Two `OracleBinary`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

LessThanOrEqual

This method determines whether or not the first of two `OracleBinary` values is less than or equal to the second.

Declaration

```
// C#  
public static bool LessThanOrEqual(OracleBinary value1, OracleBinary value2);
```

Parameters

- *value1*
The first `OracleBinary`.
- *value2*
The second `OracleBinary`.

Return Value

Returns true if the first of two `OracleBinary` values is less than or equal to the second; otherwise returns false.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleBinary` that has a value is greater than an `OracleBinary` that has a null value.
- Two `OracleBinary`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

NotEquals

This method determines whether or not two `OracleBinary` values are not equal.

Declaration

```
// C#  
public static bool NotEquals(OracleBinary value1, OracleBinary value2);
```

Parameters

- *value1*
The first `OracleBinary`.

- *value2*
The second OracleBinary.

Return Value

Returns true if two OracleBinary values are not equal; otherwise returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleBinary that has a value is greater than an OracleBinary that has a null value.
- Two OracleBinarys that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

OracleBinary Static Operators

The OracleBinary static operators are listed in [Table 14–10](#).

Table 14–10 OracleBinary Static Operators

| Operator | Description |
|--------------------------------|-------------------------------------------------------------------------------------------|
| operator + | Concatenates two OracleBinary values |
| operator == | Determines if two OracleBinary values are equal |
| operator > | Determines if the first of two OracleBinary values is greater than the second |
| operator >= | Determines if the first of two OracleBinary values is greater than or equal to the second |
| operator != | Determines if two OracleBinary values are not equal |
| operator < | Determines if the first of two OracleBinary value is less than the second |
| operator <= | Determines if the first of two OracleBinary value is less than or equal to the second |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

operator +

This method concatenates two OracleBinary values.

Declaration

```
// C#
public static OracleBinary operator + (OracleBinary value1, OracleBinary value2);
```

Parameters

- *value1*
The first OracleBinary.
- *value2*
The second OracleBinary.

Return Value

OracleBinary

Remarks

If either argument has a null value, the returned OracleBinary structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

operator ==

This method determines if two OracleBinary values are equal.

Declaration

```
// C#  
public static bool operator == (OracleBinary value1, OracleBinary value2);
```

Parameters

- *value1*
The first OracleBinary.
- *value2*
The second OracleBinary.

Return Value

Returns true if they are the same; otherwise returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleBinary that has a value is greater than an OracleBinary that has a null value.
- Two OracleBinarys that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

operator >

This method determines if the first of two OracleBinary values is greater than the second.

Declaration

```
// C#  
public static bool operator > (OracleBinary value1, OracleBinary value2);
```

Parameters

- *value1*
The first OracleBinary.
- *value2*

The second OracleBinary.

Return Value

Returns true if the first of two OracleBinary values is greater than the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleBinary that has a value is greater than an OracleBinary that has a null value.
- Two OracleBinarys that contain a null value are equal.

Example

```
// C#
using System;
using Oracle.DataAccess.Types;

class OperatorSample
{
    static void Main(string[] args)
    {
        OracleBinary binary1 = OracleBinary.Null;
        OracleBinary binary2 = new OracleBinary(new byte[] {1});

        // Compare two OracleBinary structs; binary1 < binary2
        if (binary1 > binary2)
            Console.WriteLine("binary1 > binary2");
        else
            Console.WriteLine("binary1 < binary2");
    }
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

operator >=

This method determines if the first of two OracleBinary values is greater than or equal to the second.

Declaration

```
// C#
public static bool operator >= (OracleBinary value1, OracleBinary value2);
```

Parameters

- *value1*
The first OracleBinary.
- *value2*

The second OracleBinary.

Return Value

Returns true if the first of two OracleBinary values is greater than or equal to the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleBinary that has a value is greater than an OracleBinary that has a null value.
- Two OracleBinaries that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

operator !=

This method determines if two OracleBinary values are not equal.

Declaration

```
// C#  
public static bool operator != (OracleBinary value1, OracleBinary value2);
```

Parameters

- *value1*
The first OracleBinary.
- *value2*
The second OracleBinary.

Return Value

Returns true if the two OracleBinary values are not equal; otherwise, returns false.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

operator <

This method determines if the first of two OracleBinary values is less than the second.

Declaration

```
// C#  
public static bool operator < ( OracleBinary value1, OracleBinary value2);
```


Parameters

- *value1*
The first OracleBinary.
- *value2*
The second OracleBinary.

Return Value

Returns true if the first of two OracleBinary values is less than the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleBinary that has a value is greater than an OracleBinary that has a null value.
- Two OracleBinarys that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

operator <=

This method determines if the first of two OracleBinary values is less than or equal to the second.

Declaration

```
// C#
public static bool operator <= (OracleBinary value1, OracleBinary value1);
```

Parameters

- *value1*
The first OracleBinary.
- *value2*
The second OracleBinary.

Return Value

Returns true if the first of two OracleBinary values is less than or equal to the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleBinary that has a value is greater than an OracleBinary that has a null value.
- Two OracleBinarys that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

OracleBinary Static Type Conversion Operators

The OracleBinary static type conversion operators are listed in [Table 14–11](#).

Table 14–11 OracleBinary Static Type Conversion Operators

| Operator | Description |
|------------------------------------------------|---------------------------------------------------------|
| explicit operator byte[] | Converts an instance value to a byte array |
| implicit operator OracleBinary | Converts an instance value to an OracleBinary structure |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

explicit operator byte[]

This method converts an OracleBinary value to a byte array.

Declaration

```
// C#
public static explicit operator byte[] (OracleBinary val);
```

Parameters

- *val*
An OracleBinary.

Return Value

A byte array.

Exceptions

OracleNullValueException - The OracleBinary structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

implicit operator OracleBinary

This method converts a byte array to an OracleBinary structure.

Declaration

```
// C#
public static implicit operator OracleBinary(byte[] bytes);
```

Parameters

- *bytes*
A byte array.

Return Value

OracleBinary

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

OracleBinary Properties

The OracleBinary properties are listed in [Table 14–12](#).

Table 14–12 OracleBinary Properties

| Properties | Description |
|------------------------|-------------------------------------------------------------------------|
| IsNull | Indicates whether or not the current instance has a null value |
| Item | Obtains the particular byte in an OracleBinary structure using an index |
| Length | Returns the length of the binary data |
| Value | Returns the binary data that is stored in an OracleBinary structure |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

IsNull

This property indicates whether or not the current instance has a null value.

Declaration

```
// C#
public bool IsNull {get;}
```

Property Value

Returns true if the current instance has a null value; otherwise returns false.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

Item

This property obtains the particular byte in an OracleBinary structure using an index.

Declaration

```
// C#
public byte this[int index] {get;}
```

Property Value

A byte in the specified index.

Exceptions

OracleNullValueException - The current instance has a null value.

Example

```
// C#

using System;
using Oracle.DataAccess.Types;

class ItemSample
{
    static void Main(string[] args)
    {
        OracleBinary binary = new OracleBinary(new byte[] {1,2,3,4});

        // Prints the value 4
        Console.WriteLine(binary.Length - 1);
    }
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

Length

This property returns the length of the binary data.

Declaration

```
// C#
public int length {get;}
```

Property Value

Length of the binary data.

Exceptions

OracleNullValueException - The current instance has a null value.

Example

```
// C#

using System;
using Oracle.DataAccess.Types;

class LengthSample
{
    static void Main(string[] args)
    {
        OracleBinary binary = new OracleBinary(new byte[] {1,2,3,4});

        // Prints the value 4
        Console.WriteLine(binary.Length);
    }
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

Value

This property returns the binary data that is stored in the OracleBinary structure.

Declaration

```
// C#  
public byte[] Value {get;}
```

Property Value

Binary data.

Exceptions

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

OracleBinary Instance Methods

The `OracleBinary` instance methods are listed in [Table 14–13](#).

Table 14–13 OracleBinary Instance Methods

| Methods | Description |
|-----------------------------|---------------------------------------------------------------------------------------------------------|
| CompareTo | Compares the current instance to an object and returns an integer that represents their relative values |
| Equals | Determines if two objects contain the same binary data (Overloaded) |
| GetHashCode | Returns a hash code for the current instance |
| GetType | Inherited from <code>System.Object</code> |
| ToString | Converts the current <code>OracleBinary</code> structure to a string |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

CompareTo

This method compares the current instance to an object and returns an integer that represents their relative values

Declaration

```
// C#
public int CompareTo(object obj);
```

Parameters

- *obj*
The object being compared.

Return Value

The method returns a number that is:

- Less than zero: if the current `OracleBinary` instance value is less than *obj*.
- Zero: if the current `OracleBinary` instance and *obj* values have the same binary data.
- Greater than zero: if the current `OracleBinary` instance value is greater than *obj*.

Implements

`Comparable`

Exceptions

`ArgumentException` - The parameter is not of type `OracleBinary`.

Remarks

The following rules apply to the behavior of this method.

- The comparison must be between `OracleBinary`s. For example, comparing an `OracleBinary` instance with an `OracleTimeStamp` instance is not allowed. When an `OracleBinary` is compared with a different type, an `ArgumentException` is thrown.
- Any `OracleBinary` that has a value is greater than an `OracleBinary` that has a null value.
- Two `OracleBinary`s that contain a null value are equal.

Example

```
// C#
using System;
using Oracle.DataAccess.Types;

class CompareToSample
{
    static void Main(string[] args)
    {
        OracleBinary binary1 = new OracleBinary(new byte[] {1,2,3});
        OracleBinary binary2 = new OracleBinary(new byte[] {1,2,3,4});

        // Compare
        if (binary1.CompareTo(binary2) == 0)
            Console.WriteLine("binary1 is the same as binary2");
        else
            Console.WriteLine("binary1 is different from binary2");
    }
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

Equals

This method determines whether or not an object is an instance of `OracleBinary`, and has the same binary data as the current instance.

Declaration

```
// C#
public override bool Equals(object obj);
```

Parameters

- *obj*
The object being compared.

Return Value

Returns `true` if *obj* is an instance of `OracleBinary`, and has the same binary data as the current instance; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleBinary` that has a value is greater than an `OracleBinary` that has a null value.
- Two `OracleBinary`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

GetHashCode

Overrides `Object`

This method returns a hash code for the `OracleBinary` instance.

Declaration

```
// C#  
public override int GetHashCode();
```

Return Value

An `int` that represents the hash.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

ToString

Overrides `Object`

This method converts an `OracleBinary` instance to a string instance.

Declaration

```
// C#  
public override string ToString();
```

Return Value

string

Remarks

If the current `OracleBinary` instance has a null value, the returned string "null".

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleBinary Structure](#)
- [OracleBinary Members](#)

OracleBoolean Structure

The OracleBoolean structure represents a logical value that is either TRUE or FALSE.

Class Inheritance

System.Object

System.ValueType

Oracle.DataAccess.Types.OracleBoolean

Declaration

```
// C#
public struct OracleBoolean : IComparable, INullable, IXmlSerializable
```

Requirements

| Provider | ODP.NET, Unmanaged Driver |
|----------------|---------------------------|
| Assembly | Oracle.DataAccess.dll |
| Namespace | Oracle.DataAccess.Types |
| .NET Framework | 3.5, 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

A OracleBoolean structure represents three possible values: TRUE, FALSE, and NULL. A non-zero value is interpreted as TRUE.

Example

```
// C#
using System;
using System.Data;
using Oracle.DataAccess.Types;

class OracleBooleanSample
{
    static void Main(string[] args)
    {
        OracleBoolean oracleBoolean1 = new OracleBoolean(true);
        OracleBoolean oracleBoolean2 = new OracleBoolean(0);

        Console.WriteLine("oracleBoolean1 : " + oracleBoolean1);
        Console.WriteLine("oracleBoolean2 : " + oracleBoolean2);
    }
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleBoolean Members](#)
- [OracleBoolean Constructors](#)
- [OracleBoolean Static Fields](#)
- [OracleBoolean Static Methods](#)
- [OracleBoolean Static Operators](#)
- [OracleBoolean Static Type Conversions](#)
- [OracleBoolean Properties](#)
- [OracleBoolean Instance Methods](#)

OracleBoolean Members

OracleBoolean members are listed in the following tables:

OracleBoolean Constructors

OracleBoolean constructors are listed in [Table 14–14](#)

Table 14–14 OracleBoolean Constructors

| Constructor | Description |
|--------------------------------------------|---------------------------------------------------------------------|
| OracleBoolean Constructors | Instantiates a new instance of OracleBoolean structure (Overloaded) |

OracleBoolean Static Fields

The OracleBoolean static fields are listed in [Table 14–15](#).

Table 14–15 OracleBoolean Static Fields

| Field | Description |
|-----------------------|----------------------------------------------------------------------------|
| False | Represents a false value that can be assigned to an OracleBoolean instance |
| Null | Represents a null value that can be assigned to an OracleBoolean instance |
| One | Indicates a constant representing the positive one value |
| True | Represents a true value that can be assigned to an OracleBoolean instance |
| Zero | Indicates a constant representing the zero value |

OracleBoolean Static Methods

OracleBoolean static methods are listed in [Table 14–16](#)

Table 14–16 OracleBoolean Static Methods

| Methods | Description |
|-------------------------------------|--------------------------------------------------------------------------------------------------------|
| And | Returns the result of bitwise AND operation of two OracleBoolean instances |
| Equals | Determines whether or not the two OracleBoolean values are equal |
| GreaterThan | Determines whether or not the first of two OracleBoolean values is greater than the second |
| GreaterThanOrEquals | Determines whether or not the first of two OracleBoolean values is greater than or equal to the second |
| LessThan | Determines whether or not the first of two OracleBoolean values is less than the second |
| LessThanOrEquals | Determines whether or not the first of two OracleBoolean values is less than or equal to the second |
| NotEquals | Determines whether or not two OracleBoolean values are not equal |
| OnesComplement | Returns the result of a one's complement operation on the specified OracleBoolean value |

Table 14–16 (Cont.) OracleBoolean Static Methods

| Methods | Description |
|-----------------------|---------------------------------------------------------------------------------------|
| Or | Returns the result of bitwise OR operation of two OracleBoolean instances |
| Parse | Returns an OracleBoolean structure and sets its value using a string |
| Xor | Returns the result of a bitwise exclusive OR operation of two OracleBoolean instances |

OracleBoolean Static Operators

The OracleBoolean static operators are listed in [Table 14–17](#).

Table 14–17 OracleBoolean Static Operators

| Field | Description |
|--------------------------------|--------------------------------------------------------------------------------------------------------|
| operator > | Determines whether or not the first of two OracleBoolean values is greater than the second |
| operator >= | Determines whether or not the first of two OracleBoolean values is greater than or equal to the second |
| operator < | Determines whether or not the first of two OracleBoolean values is less than the second |
| operator <= | Determines whether or not the first of two OracleBoolean values is less than or equal to the second |
| operator == | Indicates whether or not the two OracleBoolean instances are equal |
| operator != | Determines whether or not two OracleBoolean values are not equal |
| operator ! | Determines the result of a NOT operation on a OracleBoolean |
| operator ~ | Returns the result of a one's complement operation on the specified OracleBoolean value |
| operator false | Determines whether or not the specified OracleBoolean value is false |
| operator true | Determines whether or not the specified OracleBoolean value is true |
| operator & | Returns the result of bitwise AND operation of two OracleBoolean instances |
| operator | Returns the result of bitwise OR operation of two OracleBoolean instances |
| operator ^ | Returns the result of bitwise exclusive OR operation of two OracleBoolean instances |

The OracleBoolean Static Type conversions

The OracleBoolean static type conversions are listed in [Table 14–18](#)

Table 14–18 OracleBoolean Static Type Conversions

| Field | Description |
|-------------------------------------------------|---------------------------------------------------------------|
| implicit operator OracleBoolean | Returns the OracleBoolean representation of a boolean value |
| explicit operator bool | Returns the boolean representation of the OracleBoolean value |

Table 14–18 (Cont.) OracleBoolean Static Type Conversions

| Field | Description |
|-------------------------------------------------|-----------------------------------------------------------------|
| explicit operator OracleBoolean | Converts a structure to an OracleBoolean structure (Overloaded) |

OracleBoolean Properties

The OracleBoolean properties are listed in [Table 14–25](#).

Table 14–19 OracleBoolean Properties

| Properties | Description |
|---------------------------|---------------------------------------------------------------------|
| ByteValue | Returns a byte that represents the OracleBoolean structure |
| IsFalse | Indicates whether or not the value of the current instance is false |
| IsNull | Indicates whether or not the current instance has a null value |
| IsTrue | Indicates whether or not the value of the current instance is true |
| Value | Returns a boolean value that represents the current instance |

OracleBoolean Instance Methods

The OracleBoolean instance methods are listed in [Table 14–20](#).

Table 14–20 OracleBoolean Instance Methods

| Method | Description |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| CompareTo | Compares the current instance to the supplied object and returns an integer that represents their relative values |
| Equals | Determines whether or not an object is an instance of OracleBoolean, and whether or not the value of the object is equal to the current instance |
| GetHashCode | Returns a hash code for the current instance |
| ToString | Returns the string representation of the current instance |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)

OracleBoolean Constructors

The `OracleBoolean` constructors instantiates a new instance of the `OracleBoolean` structure.

Overload List:

- [OracleBoolean\(bool\)](#)

This constructor creates a new instance of the `OracleBoolean` structure and sets its value to the supplied `Boolean` value.

- [OracleBoolean\(int\)](#)

This constructor creates a new instance of the `OracleBoolean` structure and sets its value to the supplied `Int32` value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

OracleBoolean(bool)

This constructor creates a new instance of the `OracleBoolean` structure and sets its value to the supplied `Boolean` value.

Declaration

```
// C#  
public OracleBoolean(bool value) ;
```

Parameters

- *value*

The provided `Boolean` value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

OracleBoolean(int)

This constructor creates a new instance of the `OracleBoolean` structure and sets its value to the supplied `Int32` value.

Declaration

```
// C#  
public OracleBoolean(int value)
```

Parameters

- *value*

The provided Int32 value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

OracleBoolean Static Fields

The OracleBoolean static fields are listed in [Table 14–21](#).

Table 14–21 OracleBoolean Static Fields

| Field | Description |
|-----------------------|----------------------------------------------------------------------------|
| False | Represents a false value that can be assigned to an OracleBoolean instance |
| Null | Represents a null value that can be assigned to an OracleBoolean instance |
| One | Indicates a constant representing the positive one value |
| True | Represents a true value that can be assigned to an OracleBoolean instance |
| Zero | Indicates a constant representing the zero value |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

False

This static field represents a false value that can be assigned to an OracleBoolean instance.

Declaration

```
// C#
public static readonly OracleBoolean False;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

Null

This static field represents a null value that can be assigned to an OracleBoolean instance.

Declaration

```
// C#
public static readonly OracleBoolean Null;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

One

This static field indicates a constant representing the positive one value.

Declaration

```
// C#  
public static readonly OracleBoolean One;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

True

This static field represents a true value that can be assigned to an OracleBoolean instance.

Declaration

```
// C#  
public static readonly OracleBoolean True;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

Zero

This static field indicates a constant representing the zero value.

Declaration

```
// C#  
public static readonly OracleBoolean Zero;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

OracleBoolean Static Methods

OracleBoolean static methods are listed in [Table 14–22](#)

Table 14–22 OracleBoolean Static Methods

| Methods | Description |
|-------------------------------------|--------------------------------------------------------------------------------------------------------|
| And | Returns the result of bitwise AND operation of two OracleBoolean instances |
| Equals | Determines whether or not the two OracleBoolean values are equal |
| GreaterThan | Determines whether or not the first of two OracleBoolean values is greater than the second |
| GreaterThanOrEquals | Determines whether or not the first of two OracleBoolean values is greater than or equal to the second |
| LessThan | Determines whether or not the first of two OracleBoolean values is less than the second |
| LessThanOrEquals | Determines whether or not the first of two OracleBoolean values is less than or equal to the second |
| NotEquals | Determines whether or not two OracleBoolean values are not equal |
| OnesComplement | Returns the result of a one's complement operation on the specified OracleBoolean value |
| Or | Returns the result of bitwise OR operation of two OracleBoolean instances |
| Parse | Returns an OracleBoolean structure and sets its value using a string |
| Xor | Returns the result of a bitwise exclusive OR operation of two OracleBoolean instances |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

And

This method returns the result of bitwise AND operation of two OracleBoolean instances.

Declaration

```
// C#
public static OracleBoolean And(OracleBoolean value1, OracleBoolean value2);
```

Parameters

- *value1*
An OracleBoolean instance
- *value2*

An OracleBoolean instance

Return Value

An OracleBoolean that contains the value of the result of bitwise AND operation of two OracleBoolean instances.

Remarks

If either of the specified OracleBoolean instances is null, an OracleBoolean with a null value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

Equals

This method returns an OracleBoolean that indicates whether or not the two OracleBoolean instances are equal.

Declaration

```
// C#  
public static OracleBoolean Equal(OracleBoolean value1, OracleBoolean value2);
```

Parameters

- *value1*
An OracleBoolean instance
- *value2*
An OracleBoolean instance

Return Value

An OracleBoolean that is true if the specified two OracleBoolean instances are equal; otherwise, returns an OracleBoolean that is false.

Remarks

If either of the specified OracleBoolean instances is null, an OracleBoolean with a null value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

GreaterThan

This method determines if the first of two OracleBoolean values is greater than the second.

Declaration

```
// C#  
public static OracleBoolean GreaterThan(OracleBoolean value1, OracleBoolean  
value2);
```

Parameters

- *value1*
The first OracleBoolean
- *value2*
The second OracleBoolean

Return Value

An OracleBoolean that is true if the first of two OracleBoolean values is greater than the second; otherwise, returns false.

Remarks

If either of the specified OracleBoolean instances is null, an OracleBoolean with a null value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

GreaterThanOrEquals

This method determines if the first of two OracleBoolean values is greater than or equal to the second.

Declaration

```
// C#  
public static OracleBoolean GreaterThanOrEquals(OracleBoolean value1,  
OracleBoolean value2);
```

Parameters

- *value1*
The first OracleBoolean
- *value2*
The second OracleBoolean

Return Value

An OracleBoolean that is true if the first of two OracleBoolean values is greater than or equal to the second; otherwise, returns false.

Remarks

If either of the specified OracleBoolean instances is null, an OracleBoolean with a null value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

LessThan

This method determines if the first of two OracleBoolean values is less than the second.

Declaration

```
// C#  
public static OracleBoolean LessThan(OracleBoolean value1, OracleBoolean value2);
```

Parameters

- *value1*
The first OracleBoolean
- *value2*
The second OracleBoolean

Return Value

An OracleBoolean that is true if the first of two OracleBoolean values is less than the second; otherwise, returns false.

Remarks

If either of the specified OracleBoolean instances is null, an OracleBoolean with a null value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

LessThanOrEquals

This method determines if the first of two OracleBoolean values is less or equal than the second.

Declaration

```
// C#  
public static OracleBoolean LessThanOrEquals(OracleBoolean value1, OracleBoolean value2);
```

Parameters

- *value1*
The first OracleBoolean
- *value2*

The second OracleBoolean

Return Value

An OracleBoolean that is true if the first of two OracleBoolean values is less than or equal to the second; otherwise, returns false.

Remarks

If either of the specified OracleBoolean instances is null, an OracleBoolean with a null value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

NotEquals

This method determines if two OracleBoolean values are not equal.

Declaration

```
// C#  
public static OracleBoolean NotEquals(OracleBoolean value1, OracleBoolean value2);
```

Parameters

- *value1*
The first OracleBoolean
- *value2*
The second OracleBoolean

Return Value

An OracleBoolean that is true if two OracleBoolean values are not equal; otherwise, returns false.

Remarks

If either of the specified OracleBoolean instances is null, an OracleBoolean with a null value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

OnesComplement

This method returns the result of a one's complement operation on the specified OracleBoolean value.

Declaration

```
// C#  
public static OracleBoolean OnesComplement(OracleBoolean value1);
```

Parameters

- *value1*
An OracleBoolean instance

Return Value

An OracleBoolean that contains the value of the result of a one's complement operation on the specified OracleBoolean value.

Remarks

If the specified OracleBoolean instance is null, an OracleBoolean with a null value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

Or

This method returns the result of bitwise OR operation of two OracleBoolean instances.

Declaration

```
// C#  
public static OracleBoolean Or(OracleBoolean value1, OracleBoolean value2);
```

Parameters

- *value1*
An OracleBoolean instance
- *value2*
An OracleBoolean instance

Return Value

An OracleBoolean that contains the value of the result of bitwise OR operation of two OracleBoolean instances.

Remarks

If either of the specified OracleBoolean instances is null, an OracleBoolean with a null value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

Parse

This method converts a string to an OracleBoolean.

Declaration

```
// C#  
public static OracleBoolean Parse(string str);
```

Parameters

- *str*
The string being converted.

Return Value

A new OracleBoolean structure.

Exceptions

ArgumentNullException – The *str* parameter is null.

IndexOutOfRangeException – The *str* parameter is an empty string.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

Xor

This method returns the result of a bitwise exclusive OR operation of two OracleBoolean instances.

Declaration

```
// C#  
public static OracleBoolean Xor(OracleBoolean value1, OracleBoolean value2);
```

Parameters

- *value1*
An OracleBoolean instance
- *value2*
An OracleBoolean instance

Return Value

An OracleBoolean that contains the value of the result of bitwise exclusive OR operation of two OracleBoolean instances.

Remarks

If either of the specified OracleBoolean instances is null, an OracleBoolean with a null value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

OracleBoolean Static Operators

The OracleBoolean static operators are listed in [Table 14–23](#).

Table 14–23 OracleBoolean Static Operators

| Field | Description |
|--------------------------------|--------------------------------------------------------------------------------------------------------|
| operator > | Determines whether or not the first of two OracleBoolean values is greater than the second |
| operator >= | Determines whether or not the first of two OracleBoolean values is greater than or equal to the second |
| operator < | Determines whether or not the first of two OracleBoolean values is less than the second |
| operator <= | Determines whether or not the first of two OracleBoolean values is less than or equal to the second |
| operator == | Indicates whether or not the two OracleBoolean instances are equal |
| operator != | Determines whether or not two OracleBoolean values are not equal |
| operator ! | Determines the result of a NOT operation on a OracleBoolean |
| operator ~ | Returns the result of a one's complement operation on the specified OracleBoolean value |
| operator false | Determines whether or not the specified OracleBoolean value is false |
| operator true | Determines whether or not the specified OracleBoolean value is true |
| operator & | Returns the result of bitwise AND operation of two OracleBoolean instances |
| operator | Returns the result of bitwise OR operation of two OracleBoolean instances |
| operator ^ | Returns the result of bitwise exclusive OR operation of two OracleBoolean instances |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

operator >

This method determines whether or not the first of two OracleBoolean values is greater than the second.

Declaration

```
// C#
public static operator > (OracleBoolean value1, OracleBoolean value2);
```

Parameters

- *value1*
An OracleBoolean instance
- *value2*
An OracleBoolean instance

Return Value

An OracleBoolean that is true if the first of two OracleBoolean values is greater than the second; otherwise, returns false.

Remarks

If either of the specified OracleBoolean instances is null, an OracleBoolean with a null value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

operator >=

This method determines whether or not the first of two OracleBoolean values is greater than or equal to the second.

Declaration

```
// C#  
public static operator >= (OracleBoolean value1, OracleBoolean value2);
```

Parameters

- *value1*
An OracleBoolean instance
- *value2*
An OracleBoolean instance

Return Value

An OracleBoolean that is true if the first of two OracleBoolean values is greater than or equal to the second; otherwise, returns false.

Remarks

If either of the specified OracleBoolean instances is null, an OracleBoolean with a null value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

operator <

This method determines whether or not the first of two OracleBoolean values is less than the second.

Declaration

```
// C#  
public static operator < (OracleBoolean value1, OracleBoolean value2);
```

Parameters

- *value1*
An OracleBoolean instance
- *value2*
An OracleBoolean instance

Return Value

An OracleBoolean that is true if the first of two OracleBoolean values is less than the second; otherwise, returns false.

Remarks

If either of the specified OracleBoolean instances is null, an OracleBoolean with a null value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

operator <=

This method determines whether or not the first of two OracleBoolean values is less than or equal to the second.

Declaration

```
// C#  
public static operator <= (OracleBoolean value1, OracleBoolean value2);
```

Parameters

- *value1*
An OracleBoolean instance

- *value2*
An OracleBoolean instance

Return Value

An OracleBoolean that is true if the first of two OracleBoolean values is less than or equal to the second; otherwise, returns false.

Remarks

If either of the specified OracleBoolean instances is null, an OracleBoolean with a null value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

operator ==

This method returns an OracleBoolean that indicates whether or not the two OracleBoolean instances are equal.

Declaration

```
// C#  
public static operator == (OracleBoolean value1, OracleBoolean value2);
```

Parameters

- *value1*
An OracleBoolean instance
- *value2*
An OracleBoolean instance

Return Value

An OracleBoolean that is true if the specified two OracleBoolean instances are equal; otherwise, returns false.

Remarks

If either of the specified OracleBoolean instances is null, an OracleBoolean with a null value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

operator !=

This method determines whether or not two OracleBoolean values are not equal.

Declaration

```
// C#  
public static operator != (OracleBoolean value1, OracleBoolean value2);
```

Parameters

- *value1*
An OracleBoolean instance
- *value2*
An OracleBoolean instance

Return Value

An OracleBoolean that is true if two OracleBoolean values are not equal; otherwise, returns false.

Remarks

If either of the specified OracleBoolean instances is null, an OracleBoolean with a null value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

operator !

This method determines the result of a NOT operation on a OracleBoolean.

Declaration

```
// C#  
public static operator ! (OracleBoolean value1);
```

Parameters

- *value1*
An OracleBoolean instance

Return Value

An OracleBoolean that is true if the specified OracleBoolean value is true; otherwise, returns false.

Remarks

If the specified OracleBoolean instance is null, an OracleBoolean with a null value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

operator ~

This method returns the result of a one's complement operation on the specified OracleBoolean value.

Declaration

```
// C#  
public static operator ~ (OracleBoolean value1);
```

Parameters

- *value1*
An OracleBoolean instance

Return Value

An OracleBoolean that contains the value of the result of a one's complement operation on the specified OracleBoolean value.

Remarks

If the specified OracleBoolean instance is null, an OracleBoolean with a null value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

operator false

This method determines whether or not the specified OracleBoolean value is false.

Declaration

```
// C#  
public static operator false (OracleBoolean value1);
```

Parameters

- *value1*
An OracleBoolean instance

Return Value

An OracleBoolean that is true if specified OracleBoolean value is false; otherwise, returns false.

Remarks

This property will return `false` if the current instance is `null`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

operator true

This method determines whether or not the specified `OracleBoolean` value is `true`.

Declaration

```
// C#  
public static operator true (OracleBoolean value1);
```

Parameters

- *value1*
An `OracleBoolean` instance

Return Value

An `OracleBoolean` that is `true` if specified `OracleBoolean` value is `true`; otherwise, returns `false`.

Remarks

This property will return `false` if the current instance is `null`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

operator &

This method returns the result of bitwise `AND` operation of two `OracleBoolean` instances.

Declaration

```
// C#  
public static operator & (OracleBoolean value1, OracleBoolean value2);
```

Parameters

- *value1*
An `OracleBoolean` instance
- *value2*
An `OracleBoolean` instance

Return Value

An OracleBoolean that contains the value of the result of bitwise AND operation of two OracleBoolean instances.

Remarks

If either of the specified OracleBoolean instances is null, an OracleBoolean with a null value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

operator |

This method returns the result of bitwise OR operation of two OracleBoolean instances.

Declaration

```
// C#
public static operator | (OracleBoolean value1, OracleBoolean value2);
```

Parameters

- *value1*
An OracleBoolean instance
- *value2*
An OracleBoolean instance

Return Value

An OracleBoolean that contains the value of the result of bitwise OR operation of two OracleBoolean instances.

Remarks

If either of the specified OracleBoolean instances is null, an OracleBoolean with a null value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

operator ^

This method returns the result of bitwise exclusive OR operation of two OracleBoolean instances.

Declaration

```
// C#
```

```
public static operator ^ (OracleBoolean value1, OracleBoolean value2);
```

Parameters

- *value1*
An OracleBoolean instance
- *value2*
An OracleBoolean instance

Return Value

An OracleBoolean that contains the value of the result of bitwise exclusive OR operation of two OracleBoolean instances.

Remarks

If either of the specified OracleBoolean instances is null, an OracleBoolean with a null value will be returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

OracleBoolean Static Type Conversions

The OracleBoolean static type conversions are listed in [Table 14–24](#)

Table 14–24 OracleBoolean Static Type Conversions

| Field | Description |
|-------------------------------------------------|-----------------------------------------------------------------|
| implicit operator OracleBoolean | Returns the OracleBoolean representation of a boolean value |
| explicit operator bool | Returns the boolean representation of the OracleBoolean value |
| explicit operator OracleBoolean | Converts a structure to an OracleBoolean structure (Overloaded) |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

implicit operator OracleBoolean

This method returns the OracleBoolean representation of a boolean value.

Declaration

```
// C#
public static implicit operator OracleBoolean(bool value1);
```

Parameters

- *value1*
An OracleBoolean instance

Return Value

An OracleBoolean.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

explicit operator bool

This method returns the boolean representation of the OracleBoolean value.

Declaration

```
// C#
public static explicit operator bool(OracleBoolean value1);
```

Parameters

- *value1*
An OracleBoolean structure

Return Value

A boolean

Exception

OracleNullValueException – OracleBoolean has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

explicit operator OracleBoolean

explicit operator OracleBoolean converts the provided structure to an OracleBoolean structure.

Overload List

- [explicit operator OracleBoolean\(byte\)](#)
This method converts the supplied byte to an OracleBoolean structure.
- [explicit operator OracleBoolean\(Decimal\)](#)
This method converts the supplied Decimal to an OracleBoolean structure.
- [explicit operator OracleBoolean\(Double\)](#)
This method converts the supplied Double to an OracleBoolean structure.
- [explicit operator OracleBoolean\(Int16\)](#)
This method converts the supplied Int16 to an OracleBoolean structure.
- [explicit operator OracleBoolean\(int\)](#)
This method converts the supplied int to an OracleBoolean structure.
- [explicit operator OracleBoolean\(Int64\)](#)
This method converts the supplied Int64 to an OracleBoolean structure.
- [explicit operator OracleBoolean\(Single\)](#)
This method converts the supplied Single to an OracleBoolean structure.
- [explicit operator OracleBoolean\(String\)](#)
This method converts the supplied String to an OracleBoolean structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

explicit operator OracleBoolean(byte)

This method converts the supplied byte to an OracleBoolean structure.

Declaration

```
// C#  
public static explicit operator OracleBoolean(byte value1);
```

Parameters

- *value1*
A byte

Return Value

An OracleBoolean structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

explicit operator OracleBoolean(Decimal)

This method converts the supplied Decimal to an OracleBoolean structure.

Declaration

```
// C#  
public static explicit operator OracleBoolean(Decimal value1);
```

Parameters

- *value1*
A Decimal

Return Value

An OracleBoolean structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

explicit operator OracleBoolean(Double)

This method converts the supplied Double to an OracleBoolean structure.

Declaration

```
// C#  
public static explicit operator OracleBoolean(Double value1);
```

Parameters

- *value1*
A Double

Return Value

An OracleBoolean structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

explicit operator OracleBoolean(Int16)

This method converts the supplied Int16 to an OracleBoolean structure.

Declaration

```
// C#  
public static explicit operator OracleBoolean(Int16 value1);
```

Parameters

- *value1*
An Int16

Return Value

An OracleBoolean structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

explicit operator OracleBoolean(int)

This method converts the supplied int to an OracleBoolean structure.

Declaration

```
// C#  
public static explicit operator OracleBoolean(int value1);
```

Parameters

- *value1*
An int

Return Value

An OracleBoolean structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

explicit operator OracleBoolean(Int64)

This method converts the supplied Int64 to an OracleBoolean structure.

Declaration

```
// C#  
public static explicit operator OracleBoolean(Int64 value1);
```

Parameters

- *value1*
An Int64

Return Value

An OracleBoolean structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

explicit operator OracleBoolean(Single)

This method converts the supplied Single to an OracleBoolean structure.

Declaration

```
// C#  
public static explicit operator OracleBoolean(Single value1);
```

Parameters

- *value1*
A Single

Return Value

An OracleBoolean structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

explicit operator OracleBoolean(String)

This method converts the supplied String to an OracleBoolean structure.

Declaration

```
// C#  
public static explicit operator OracleBoolean(String value1);
```

Parameters

- *value1*
A String

Return Value

An OracleBoolean structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

OracleBoolean Properties

The OracleBoolean properties are listed in [Table 14–25](#).

Table 14–25 OracleBoolean Properties

| Properties | Description |
|---------------------------|---------------------------------------------------------------------|
| ByteValue | Returns a byte that represents the OracleBoolean structure |
| IsFalse | Indicates whether or not the value of the current instance is false |
| IsNull | Indicates whether or not the current instance has a null value |
| IsTrue | Indicates whether or not the value of the current instance is true |
| Value | Returns a boolean value that represents the current instance |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

ByteValue

This property returns a byte that represents the OracleBoolean structure.

Declaration

```
// C#
public byte ByteValue {get;}
```

Property Value

A byte that represents the value of OracleBoolean structure.

Exceptions

[OracleNullValueException](#) – The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

IsFalse

This property indicates whether or not the value of the current instance is false.

Declaration

```
// C#
public bool IsFalse {get;}
```

Property Value

A bool value that returns `true` if the current instance is `false`; otherwise, returns `false`.

Remarks

This property will return `false` if the current instance is null.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

IsNull

This property indicates whether or not the current instance has a null value.

Declaration

```
// C#  
public bool IsNull {get;}
```

Property Value

A bool value that returns `true` if the current instance has a null value; otherwise, returns `false`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

IsTrue

This property indicates whether or not the value of the current instance is `true`.

Declaration

```
// C#  
public bool IsTrue {get;}
```

Property Value

A bool value that returns `true` if the current instance is `true`; otherwise, returns `false`.

Remarks

This property will return `false` if the current instance is null.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

Value

This property returns a boolean value that represents the current instance.

Declaration

```
// C#  
public bool Value {get;}
```

Property Value

A bool value that returns true if the current instance is true; otherwise, returns false.

Exceptions

[OracleNullValueException](#) – The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

OracleBoolean Instance Methods

The `OracleBoolean` instance methods are listed in [Table 14–26](#).

Table 14–26 OracleBoolean Instance Methods

| Method | Description |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CompareTo | Compares the current instance to the supplied object and returns an integer that represents their relative values |
| Equals | Determines whether or not an object is an instance of <code>OracleBoolean</code> , and whether or not the value of the object is equal to the current instance |
| GetHashCode | Returns a hash code for the current instance |
| ToString | Returns the <code>string</code> representation of the current instance |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

CompareTo

This method compares the current instance to the supplied object and returns an integer that represents their relative values.

Declaration

```
// C#
public int CompareTo(object obj);
```

Parameter

- *obj*
The supplied instance.

Return Value

The method returns a number:

- Less than zero: if the value of the current instance is less than *obj*.
- Zero: if the value of the current instance is equal to *obj*.
- Greater than zero: if the value of the current instance is greater than *obj*.

Implements

`IComparable`

Exceptions

`ArgumentException` - The parameter is not of type `OracleBoolean`.

Remarks

The following rules apply to the behavior of this method.

- The comparison must be between `OracleBoolean`. For example, comparing an `OracleBoolean` instance with an `OracleBinary` instance is not allowed. When an `OracleBoolean` is compared with a different type, an `ArgumentException` is thrown.
- Any `OracleBoolean` that has a value compares greater than an `OracleBoolean` that has a null value.
- Two `OracleBoolean` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

Equals

Overrides `Object`

This method determines whether or not an object is an instance of `OracleBoolean`, and whether or not the value of the object is equal to the current instance.

Declaration

```
// C#  
public override bool Equals(object obj);
```

Parameter

- `obj`
An `OracleBoolean` instance.

Return Value

Returns `true` if `obj` is an instance of `OracleBoolean`, and the value of `obj` is equal to the current instance; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleBoolean` that has a value compares greater than an `OracleBoolean` that has a null value.
- Two `OracleBooleans` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

GetHashCode

Overrides `Object`

This method returns a hash code for the current instance.

Declaration

```
// C#  
public override int GetHashCode();
```

Return Value

Returns a hash code.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

ToString

Overrides Object

This method returns the string representation of the current instance.

Declaration

```
// C#  
public override string ToString();
```

Return Value

Returns the OracleBoolean value in a string representation.

Remarks

If the current instance has a null value, the returned string is null.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleBoolean Structure](#)
- [OracleBoolean Members](#)

OracleDate Structure

The OracleDate structure represents the Oracle DATE data type to be stored in or retrieved from a database. Each OracleDate stores the following information: year, month, day, hour, minute, and second.

Class Inheritance

System.Object

System.ValueType

Oracle.DataAccess.Types.OracleDate

Declaration

```
// C#
public struct OracleDate : IComparable, INullable, IXmlSerializable
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|--------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Types | Oracle.ManagedDataAccess.Types |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#

using System;
using Oracle.DataAccess.Types;
using Oracle.DataAccess.Client;

class OracleDateSample
{
    static void Main(string[] args)
    {
        // Initialize the dates to the lower and upper boundaries
        OracleDate date1 = OracleDate.MinValue;
        OracleDate date2 = OracleDate.MaxValue;
        OracleDate date3 = new OracleDate(DateTime.MinValue);
        OracleDate date4 = new OracleDate(DateTime.MaxValue);

        // Set the thread's DateFormat for output
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.DateFormat = "DD-MON-YYYY BC";
        OracleGlobalization.SetThreadInfo(info);

        // Print the lower and upper boundaries
        Console.WriteLine("OracleDate ranges from\n{0}\nto\n{1}\n",
            date1, date2);
        Console.WriteLine(".NET DateTime ranges from\n{0}\nto\n{1}\n",
```

```
        date3, date4);  
    }  
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Members](#)
- [OracleDate Constructors](#)
- [OracleDate Static Fields](#)
- [OracleDate Static Methods](#)
- [OracleDate Static Operators](#)
- [OracleDate Static Type Conversions](#)
- [OracleDate Properties](#)
- [OracleDate Methods](#)

OracleDate Members

OracleDate members are listed in the following tables:

OracleDate Constructors

OracleDate constructors are listed in [Table 14-27](#)

Table 14-27 OracleDate Constructors

| Constructor | Description |
|-----------------------------------------|------------------------------------------------------------------|
| OracleDate Constructors | Instantiates a new instance of OracleDate structure (Overloaded) |

OracleDate Static Fields

The OracleDate static fields are listed in [Table 14-28](#).

Table 14-28 OracleDate Static Fields

| Field | Description |
|--------------------------|----------------------------------------------------------------------------------------------------|
| MaxValue | Represents the maximum valid date for an OracleDate structure, which is December 31, 9999 23:59:59 |
| MinValue | Represents the minimum valid date for an OracleDate structure, which is January 1, -4712 0:0:0 |
| Null | Represents a null value that can be assigned to the value of an OracleDate structure instance |

OracleDate Static Methods

The OracleDate static methods are listed in [Table 14-29](#).

Table 14-29 OracleDate Static Methods

| Methods | Description |
|------------------------------------|-----------------------------------------------------------------------------------------|
| Equals | Determines if two OracleDate values are equal (Overloaded) |
| GreaterThan | Determines if the first of two OracleDate values is greater than the second |
| GreaterThanOrEqual | Determines if the first of two OracleDate values is greater than or equal to the second |
| LessThan | Determines if the first of two OracleDate values is less than the second |
| LessThanOrEqual | Determines if the first of two OracleDate values is less than or equal to the second |
| NotEquals | Determines if two OracleDate values are not equal |
| GetSysDate | Returns an OracleDate structure that represents the current date and time |
| Parse | Returns an OracleDate structure and sets its value using a string |

OracleDate Static Operators

The OracleDate static operators are listed in [Table 14-30](#).

Table 14–30 OracleDate Static Operators

| Operator | Description |
|-----------------------------|------------------------------------------------------------------------------------------------------|
| <code>operator ==</code> | Determines if two <code>OracleDate</code> values are the same |
| <code>operator ></code> | Determines if the first of two <code>OracleDate</code> values is greater than the second |
| <code>operator >=</code> | Determines if the first of two <code>OracleDate</code> values is greater than or equal to the second |
| <code>operator !=</code> | Determines if the two <code>OracleDate</code> values are not equal |
| <code>operator <</code> | Determines if the first of two <code>OracleDate</code> values is less than the second |
| <code>operator <=</code> | Determines if the first of two <code>OracleDate</code> values is less than or equal to the second |

OracleDate Static Type Conversions

The `OracleDate` static type conversions are listed in [Table 14–31](#).

Table 14–31 OracleDate Static Type Conversions

| Operator | Description |
|-------------------------------------------|---------------------------------------------------------------------------|
| <code>explicit operator DateTime</code> | Converts a structure to a <code>DateTime</code> structure |
| <code>explicit operator OracleDate</code> | Converts a structure to an <code>OracleDate</code> structure (Overloaded) |

OracleDate Properties

The `OracleDate` properties are listed in [Table 14–32](#).

Table 14–32 OracleDate Properties

| Properties | Description |
|----------------------|----------------------------------------------------------------------------------------------|
| <code>BinData</code> | Gets an array of bytes that represents an Oracle <code>DATE</code> in Oracle internal format |
| <code>Day</code> | Gets the day component of an <code>OracleDate</code> method |
| <code>IsNull</code> | Indicates whether or not the current instance has a null value |
| <code>Hour</code> | Gets the hour component of an <code>OracleDate</code> |
| <code>Minute</code> | Gets the minute component of an <code>OracleDate</code> |
| <code>Month</code> | Gets the month component of an <code>OracleDate</code> |
| <code>Second</code> | Gets the second component of an <code>OracleDate</code> |
| <code>Value</code> | Gets the date and time that is stored in the <code>OracleDate</code> structure |
| <code>Year</code> | Gets the year component of an <code>OracleDate</code> |

OracleDate Methods

The `OracleDate` methods are listed in [Table 14–33](#).

Table 14–33 OracleDate Methods

| Methods | Description |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| <code>CompareTo</code> | Compares the current <code>OracleDate</code> instance to an object, and returns an integer that represents their relative values |

Table 14–33 (Cont.) OracleDate Methods

| Methods | Description |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Equals | Determines whether or not an object has the same date and time as the current <code>OracleDate</code> instance (Overloaded) |
| GetHashCode | Returns a hash code for the <code>OracleDate</code> instance |
| GetDaysBetween | Calculates the number of days between the current <code>OracleDate</code> instance and an <code>OracleDate</code> structure |
| GetType | Inherited from <code>System.Object</code> |
| ToOracleTimeStamp | Converts the current <code>OracleDate</code> structure to an <code>OracleTimeStamp</code> structure |
| ToString | Converts the current <code>OracleDate</code> structure to a string |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)

OracleDate Constructors

The `OracleDate` constructors instantiates a new instance of the `OracleDate` structure.

Overload List:

- [OracleDate\(DateTime\)](#)

This constructor creates a new instance of the `OracleDate` structure and sets its value for date and time using the supplied `DateTime` value.
- [OracleDate\(string\)](#)

This constructor creates a new instance of the `OracleDate` structure and sets its value using the supplied string.
- [OracleDate\(int, int, int\)](#)

This constructor creates a new instance of the `OracleDate` structure and set its value for date using the supplied year, month, and day.
- [OracleDate\(int, int, int, int, int, int\)](#)

This constructor creates a new instance of the `OracleDate` structure and set its value for time using the supplied year, month, day, hour, minute, and second.
- [OracleDate\(byte \[\]\)](#)

This constructor creates a new instance of the `OracleDate` structure and sets its value to the provided byte array, which is in the internal Oracle `DATE` format.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

OracleDate(DateTime)

This constructor creates a new instance of the `OracleDate` structure and sets its value for date and time using the supplied `DateTime` value.

Declaration

```
// C#  
public OracleDate (DateTime dt);
```

Parameters

- *dt*

The provided `DateTime` value.

Remarks

The `OracleDate` structure only supports up to a second precision. The time value in the provided `DateTime` structure that has a precision smaller than second is ignored.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

OracleDate(string)

This constructor creates a new instance of the OracleDate structure and sets its value using the supplied string.

Declaration

```
// C#
public OracleDate (string dateStr);
```

Parameters

- *dateStr*
 - A string that represents an Oracle DATE.

Exceptions

ArgumentException - The *dateStr* is an invalid string representation of an Oracle DATE or the *dateStr* is not in the date format specified by the thread's OracleGlobalization.DateFormat property, which represents the Oracle NLS_DATE_FORMAT parameter.

ArgumentNullException - The *dateStr* is null.

Remarks

The names and abbreviations used for months and days are in the language specified by the DateLanguage and Calendar properties of the thread's OracleGlobalization object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#

using System;
using Oracle.DataAccess.Types;
using Oracle.DataAccess.Client;

class OracleDateSample
{
    static void Main(string[] args)
    {
        // Set the thread's DateFormat for the OracleDate constructor
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.DateFormat = "YYYY-MON-DD";
        OracleGlobalization.SetThreadInfo(info);

        // construct OracleDate from a string using the DateFormat specified.
        OracleDate date = new OracleDate("1999-DEC-01");

        // Set a different DateFormat for the thread
        info.DateFormat = "MM/DD/YYYY";
    }
}
```

```
OracleGlobalization.SetThreadInfo(info);

// Print "12/01/1999"
Console.WriteLine(date.ToString());
}
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- *Oracle Database SQL Language Reference* for further information on date format elements

OracleDate(int, int, int)

This constructor creates a new instance of the `OracleDate` structure and set its value for date using the supplied year, month, and day.

Declaration

```
// C#
public OracleDate (int year, int month, int day);
```

Parameters

- *year*
The supplied year. Range of *year* is (-4712 to 9999).
- *month*
The supplied month. Range of *month* is (1 to 12).
- *day*
The supplied day. Range of *day* is (1 to 31).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleDate` (that is, the day is out of range for the month).

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

OracleDate(int, int, int, int, int, int)

This constructor creates a new instance of the `OracleDate` structure and set its value for time using the supplied year, month, day, hour, minute, and second.

Declaration

```
// C#  
public OracleDate (int year, int month, int day, int hour, int minute, int  
second);
```

Parameters

- *year*
The supplied year. Range of *year* is (-4712 to 9999).
- *month*
The supplied month. Range of *month* is (1 to 12).
- *day*
The supplied day. Range of *day* is (1 to 31).
- *hour*
The supplied hour. Range of *hour* is (0 to 23).
- *minute*
The supplied minute. Range of *minute* is (0 to 59).
- *second*
The supplied second. Range of *second* is (0 to 59).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleDate` (that is, the day is out of range for the month).

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

OracleDate(byte [])

This constructor creates a new instance of the `OracleDate` structure and sets its value to the provided byte array, which is in the internal Oracle `DATE` format.

Declaration

```
// C#  
public OracleDate(byte [] bytes);
```

Parameters

- *bytes*
A byte array that represents Oracle `DATE` in the internal Oracle `DATE` format.

Exceptions

ArgumentException - *bytes* is null or *bytes* is not in internal Oracle DATE format or *bytes* is not a valid Oracle DATE.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

OracleDate Static Fields

The OracleDate static fields are listed in [Table 14–34](#).

Table 14–34 OracleDate Static Fields

| Field | Description |
|--------------------------|----------------------------------------------------------------------------------------------------|
| MaxValue | Represents the maximum valid date for an OracleDate structure, which is December 31, 9999 23:59:59 |
| MinValue | Represents the minimum valid date for an OracleDate structure, which is January 1, -4712 0:0:0 |
| Null | Represents a null value that can be assigned to the value of an OracleDate structure instance |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

MaxValue

This static field represents the maximum valid date for an OracleDate structure, which is December 31, 9999 23:59:59.

Declaration

```
// C#
public static readonly OracleDate MaxValue;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

MinValue

This static field represents the minimum valid date for an OracleDate structure, which is January 1, -4712.

Declaration

```
// C#
public static readonly OracleDate MinValue;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

Null

This static field represents a null value that can be assigned to the value of an OracleDate instance.

Declaration

```
// C#  
public static readonly OracleDate Null;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

OracleDate Static Methods

The OracleDate static methods are listed in [Table 14–35](#).

Table 14–35 OracleDate Static Methods

| Methods | Description |
|------------------------------------|-----------------------------------------------------------------------------------------|
| Equals | Determines if two OracleDate values are equal (Overloaded) |
| GreaterThan | Determines if the first of two OracleDate values is greater than the second |
| GreaterThanOrEqual | Determines if the first of two OracleDate values is greater than or equal to the second |
| LessThan | Determines if the first of two OracleDate values is less than the second |
| LessThanOrEqual | Determines if the first of two OracleDate values is less than or equal to the second |
| NotEquals | Determines if two OracleDate values are not equal |
| GetSysDate | Returns an OracleDate structure that represents the current date and time |
| Parse | Returns an OracleDate structure and sets its value using a string |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

Equals

Overloads Object

This method determines if two OracleDate values are equal.

Declaration

```
// C#
public static bool Equals(OracleDate value1, OracleDate value2);
```

Parameters

- *value1*
The first OracleDate.
- *value2*
The second OracleDate.

Return Value

Returns true if two OracleDate values are equal; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleDate that has a value compares greater than an OracleDate that has a null value.
- Two OracleDates that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

GreaterThan

This method determines if the first of two OracleDate values is greater than the second.

Declaration

```
// C#  
public static bool GreaterThan(OracleDate value1, OracleDate value2);
```

Parameters

- *value1*
The first OracleDate.
- *value2*
The second OracleDate.

Return Value

Returns true if the first of two OracleDate values is greater than the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleDate that has a value compares greater than an OracleDate that has a null value.
- Two OracleDates that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

GreaterThanOrEqual

This method determines if the first of two OracleDate values is greater than or equal to the second.

Declaration

```
// C#  
public static bool GreaterThanOrEqual(OracleDate value1, OracleDate value2);
```


Parameters

- *value1*
The first OracleDate.
- *value2*
The second OracleDate.

Return Value

Returns true if the first of two OracleDate values is greater than or equal to the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleDate that has a value compares greater than an OracleDate that has a null value.
- Two OracleDates that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

LessThan

This method determines if the first of two OracleDate values is less than the second.

Declaration

```
// C#  
public static bool LessThan(OracleDate value1, OracleDate value2);
```

Parameters

- *value1*
The first OracleDate.
- *value2*
The second OracleDate.

Return Value

Returns true if the first of two OracleDate values is less than the second. Otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleDate that has a value compares greater than an OracleDate that has a null value.
- Two OracleDates that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

LessThanOrEqual

This method determines if the first of two `OracleDate` values is less than or equal to the second.

Declaration

```
// C#  
public static bool LessThanOrEqual(OracleDate value1, OracleDate value2);
```

Parameters

- *value1*
The first `OracleDate`.
- *value2*
The second `OracleDate`.

Return Value

Returns `true` if the first of two `OracleDate` values is less than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleDate` that has a value compares greater than an `OracleDate` that has a null value.
- Two `OracleDates` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

NotEquals

This method determines if two `OracleDate` values are not equal.

Declaration

```
// C#  
public static bool NotEquals(OracleDate value1, OracleDate value2);
```

Parameters

- *value1*
The first `OracleDate`.

- *value2*
The second OracleDate.

Return Value

Returns true if two OracleDate values are not equal; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleDate that has a value compares greater than an OracleDate that has a null value.
- Two OracleDates that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

GetSysDate

This method gets an OracleDate structure that represents the current date and time.

Declaration

```
// C#  
public static OracleDate GetSysDate ();
```

Return Value

An OracleDate structure that represents the current date and time.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

Parse

This method gets an OracleDate structure and sets its value for date and time using the supplied string.

Declaration

```
// C#  
public static OracleDate Parse (string dateStr);
```

Parameters

- *dateStr*
A string that represents an Oracle DATE.

Return Value

An OracleDate structure.

Exceptions

ArgumentException - The *dateStr* is an invalid string representation of an Oracle DATE or the *dateStr* is not in the date format specified by the thread's OracleGlobalization.DateFormat property, which represents the Oracle NLS_DATE_FORMAT parameter.

ArgumentNullException - The *dateStr* is null.

Remarks

The names and abbreviations used for months and days are in the language specified by the DateLanguage and Calendar properties of the thread's OracleGlobalization object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#

using System;
using Oracle.DataAccess.Types;
using Oracle.DataAccess.Client;

class ParseSample
{
    static void Main(string[] args)
    {
        // Set the thread's DateFormat for the OracleDate constructor
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.DateFormat = "YYYY-MON-DD";
        OracleGlobalization.SetThreadInfo(info);

        // Construct OracleDate from a string using the DateFormat specified
        OracleDate date = OracleDate.Parse("1999-DEC-01");

        // Set a different DateFormat on the thread for ToString()
        info.DateFormat = "MM-DD-YY";
        OracleGlobalization.SetThreadInfo(info);

        // Print "12-01-1999"
        Console.WriteLine(date.ToString());
    }
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125
- *Oracle Database SQL Language Reference* for further information on datetime format elements

OracleDate Static Operators

The OracleDate static operators are listed in [Table 14–36](#).

Table 14–36 OracleDate Static Operators

| Operator | Description |
|-----------------------------|-----------------------------------------------------------------------------------------|
| <code>operator ==</code> | Determines if two OracleDate values are the same |
| <code>operator ></code> | Determines if the first of two OracleDate values is greater than the second |
| <code>operator >=</code> | Determines if the first of two OracleDate values is greater than or equal to the second |
| <code>operator !=</code> | Determines if the two OracleDate values are not equal |
| <code>operator <</code> | Determines if the first of two OracleDate values is less than the second |
| <code>operator <=</code> | Determines if the first of two OracleDate values is less than or equal to the second |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

operator ==

This method determines if two OracleDate values are the same.

Declaration

```
// C#
public static bool operator == (OracleDate value1, OracleDate value2);
```

Parameters

- *value1*
The first OracleDate.
- *value2*
The second OracleDate.

Return Value

Returns true if they are the same; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleDate that has a value compares greater than an OracleDate that has a null value.
- Two OracleDates that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

operator >

This method determines if the first of two `OracleDate` values is greater than the second.

Declaration

```
// C#  
public static bool operator > (OracleDate value1, OracleDate value2);
```

Parameters

- *value1*
The first `OracleDate`.
- *value2*
The second `OracleDate`.

Return Value

Returns `true` if the first of two `OracleDate` values is greater than the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleDate` that has a value compares greater than an `OracleDate` that has a null value.
- Two `OracleDates` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

operator >=

This method determines if the first of two `OracleDate` values is greater than or equal to the second.

Declaration

```
// C#  
public static bool operator >= (OracleDate value1, OracleDate value2);
```

Parameters

- *value1*
The first `OracleDate`.

- *value2*
The second OracleDate.

Return Value

Returns true if the first of two OracleDate values is greater than or equal to the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleDate that has a value compares greater than an OracleDate that has a null value.
- Two OracleDates that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

operator !=

This method determines if the two OracleDate values are not equal.

Declaration

```
// C#  
public static bool operator != (OracleDate value1, OracleDate value2);
```

Parameters

- *value1*
The first OracleDate.
- *value2*
The second OracleDate.

Return Value

Returns true if the two OracleDate values are not equal; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleDate that has a value compares greater than an OracleDate that has a null value.
- Two OracleDates that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

operator <

This method determines if the first of two OracleDate values is less than the second.

Declaration

```
// C#  
public static bool operator < (OracleDate value1, OracleDate value2);
```

Parameters

- *value1*
The first OracleDate.
- *value2*
The second OracleDate.

Return Value

Returns true if the first of two OracleDate values is less than the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleDate that has a value compares greater than an OracleDate that has a null value.
- Two OracleDates that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

operator <=

This method determines if the first of two OracleDate values is less than or equal to the second.

Declaration

```
// C#  
public static bool operator <= (OracleDate value1, OracleDate value2);
```

Parameters

- *value1*
The first OracleDate.
- *value2*
The second OracleDate.

Return Value

Returns true if the first of two OracleDate values is less than or equal to the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleDate` that has a value compares greater than an `OracleDate` that has a null value.
- Two `OracleDates` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

OracleDate Static Type Conversions

The `OracleDate` static type conversions are listed in [Table 14–37](#).

Table 14–37 OracleDate Static Type Conversions

| Operator | Description |
|----------------------------------------------|---------------------------------------------------------------------------|
| explicit operator DateTime | Converts a structure to a <code>DateTime</code> structure |
| explicit operator OracleDate | Converts a structure to an <code>OracleDate</code> structure (Overloaded) |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

explicit operator DateTime

This method converts an `OracleDate` structure to a `DateTime` structure.

Declaration

```
// C#
public static explicit operator DateTime(OracleDate val);
```

Parameters

- `val`
An `OracleDate` structure.

Return Value

A `DateTime` structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

explicit operator OracleDate

`explicit operator OracleDate` converts the provided structure to an `OracleDate` structure.

Overload List:

- [explicit operator OracleDate\(DateTime\)](#)
This method converts a `DateTime` structure to an `OracleDate` structure.
- [explicit operator OracleDate\(OracleTimeStamp\)](#)
This method converts an `OracleTimeStamp` structure to an `OracleDate` structure.

- [explicit operator OracleDate\(string\)](#)

This method converts the supplied string to an OracleDate structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

explicit operator OracleDate(DateTime)

This method converts a DateTime structure to an OracleDate structure.

Declaration

```
// C#  
public static explicit operator OracleDate(DateTime dt);
```

Parameters

- *dt*
A DateTime structure.

Return Value

An OracleDate structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

explicit operator OracleDate(OracleTimeStamp)

This method converts an OracleTimeStamp structure to an OracleDate structure.

Declaration

```
// C#  
public explicit operator OracleDate(OracleTimeStamp ts);
```

Parameters

- *ts*
OracleTimeStamp

Return Value

The returned OracleDate structure contains the date and time in the OracleTimeStamp structure.

Remarks

The precision of the OracleTimeStamp value can be lost during the conversion.

If the `OracleTimeStamp` structure has a null value, the returned `OracleDate` structure also has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

explicit operator OracleDate(string)

This method converts the supplied string to an `OracleDate` structure.

Declaration

```
// C#
public explicit operator OracleDate (string dateStr);
```

Parameters

- *dateStr*
A string representation of an Oracle DATE.

Return Value

The returned `OracleDate` structure contains the date and time in the string *dateStr*.

Exceptions

`ArgumentNullException` - The *dateStr* is null.

`ArgumentException` - This exception is thrown if any of the following conditions exist:

- The *dateStr* is an invalid string representation of an Oracle DATE.
- The *dateStr* is not in the date format specified by the thread's `OracleGlobalization.DateFormat` property, which represents the Oracle NLS_DATE_FORMAT parameter.

Remarks

The names and abbreviations used for months and days are in the language specified by the `DateLanguage` and `Calendar` properties of the thread's `OracleGlobalization` object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class OracleDateSample
{
    static void Main(string[] args)
    {
        // Set the thread's DateFormat to a specific format
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.DateFormat = "YYYY-MON-DD";
    }
}
```

```
OracleGlobalization.SetThreadInfo(info);

// Construct OracleDate from a string using the DateFormat specified
OracleDate date = (OracleDate)"1999-DEC-01";

// Set a different DateFormat on the thread for ToString()
info.DateFormat = "MON DD YY";
OracleGlobalization.SetThreadInfo(info);

// Prints "DEC 01 99"
Console.WriteLine(date.ToString());
}
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125

OracleDate Properties

The OracleDate properties are listed in [Table 14–38](#).

Table 14–38 OracleDate Properties

| Properties | Description |
|-------------------------|---------------------------------------------------------------------------------|
| BinData | Gets an array of bytes that represents an Oracle DATE in Oracle internal format |
| Day | Gets the day component of an OracleDate method |
| IsNull | Indicates whether or not the current instance has a null value |
| Hour | Gets the hour component of an OracleDate |
| Minute | Gets the minute component of an OracleDate |
| Month | Gets the month component of an OracleDate |
| Second | Gets the second component of an OracleDate |
| Value | Gets the date and time that is stored in the OracleDate structure |
| Year | Gets the year component of an OracleDate |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

BinData

This property gets a array of bytes that represents an Oracle DATE in Oracle internal format.

Declaration

```
// C#
public byte[] BinData{get;}
```

Property Value

An array of bytes.

Exceptions

OracleNullValueException - OracleDate has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

Day

This property gets the day component of an OracleDate.

Declaration

```
// C#  
public int Day{get;}
```

Property Value

A number that represents the day. Range of Day is (1 to 31).

Exceptions

OracleNullValueException - OracleDate has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

IsNull

This property indicates whether or not the current instance has a null value.

Declaration

```
// C#  
public bool IsNull{get;}
```

Property Value

Returns true if the current instance has a null value; otherwise, returns false.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

Hour

This property gets the hour component of an OracleDate.

Declaration

```
// C#  
public int Hour {get;}
```

Property Value

A number that represents Hour. Range of Hour is (0 to 23).

Exceptions

OracleNullValueException - OracleDate has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

Minute

This property gets the minute component of an OracleDate.

Declaration

```
// C#  
public int Minute {get;}
```

Property Value

A number that represents Minute. Range of Minute is (0 to 59).

Exceptions

OracleNullValueException - OracleDate has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

Month

This property gets the month component of an OracleDate.

Declaration

```
// C#  
public int Month {get;}
```

Property Value

A number that represents Month. Range of Month is (1 to 12).

Exceptions

OracleNullValueException - OracleDate has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

Second

This property gets the second component of an OracleDate.

Declaration

```
// C#  
public int Second {get;}
```

Property Value

A number that represents Second. Range of Second is (0 to 59).

Exceptions

OracleNullValueException - OracleDate has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

Value

This property specifies the date and time that is stored in the OracleDate structure.

Declaration

```
// C#  
public DateTime Value {get;}
```

Property Value

A DateTime.

Exceptions

OracleNullValueException - OracleDate has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

Year

This property gets the year component of an OracleDate.

Declaration

```
// C#  
public int Year {get;}
```

Property Value

A number that represents Year. Range of Year is (-4712 to 9999).

Exceptions

OracleNullValueException - OracleDate has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

OracleDate Methods

The OracleDate methods are listed in [Table 14–39](#).

Table 14–39 OracleDate Methods

| Methods | Description |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------|
| CompareTo | Compares the current OracleDate instance to an object, and returns an integer that represents their relative values |
| Equals | Determines whether or not an object has the same date and time as the current OracleDate instance (Overloaded) |
| GetHashCode | Returns a hash code for the OracleDate instance |
| GetDaysBetween | Calculates the number of days between the current OracleDate instance and an OracleDate structure |
| GetType | Inherited from System.Object |
| ToOracleTimeStamp | Converts the current OracleDate structure to an OracleTimeStamp structure |
| ToString | Converts the current OracleDate structure to a string |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

CompareTo

This method compares the current OracleDate instance to an object, and returns an integer that represents their relative values.

Declaration

```
// C#
public int CompareTo(object obj);
```

Parameters

- *obj*
An object.

Return Value

The method returns:

- Less than zero: if the current OracleDate instance value is less than that of *obj*.
- Zero: if the current OracleDate instance and *obj* values are equal.
- Greater than zero: if the current OracleDate instance value is greater than *obj*.

Implements

IComparable

Exceptions

`ArgumentException` - The *obj* parameter is not an instance of `OracleDate`.

Remarks

The following rules apply to the behavior of this method.

- The comparison must be between `OracleDates`. For example, comparing an `OracleDate` instance with an `OracleBinary` instance is not allowed. When an `OracleDate` is compared with a different type, an `ArgumentException` is thrown.
- Any `OracleDate` that has a value compares greater than an `OracleDate` that has a null value.
- Two `OracleDates` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

Equals

This method determines whether or not an object has the same date and time as the current `OracleDate` instance.

Declaration

```
// C#  
public override bool Equals( object obj);
```

Parameters

- *obj*
An object.

Return Value

Returns `true` if *obj* has the same type as the current instance and represents the same date and time; otherwise returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleDate` that has a value compares greater than an `OracleDate` that has a null value.
- Two `OracleDates` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

GetHashCode

Overrides Object

This method returns a hash code for the OracleDate instance.

Declaration

```
// C#  
public override int GetHashCode();
```

Return Value

A number that represents the hash code.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

GetDaysBetween

This method calculates the number of days between the current OracleDate instance and the supplied OracleDate structure.

Declaration

```
// C#  
public int GetDaysBetween (OracleDate val);
```

Parameters

- *val*
An OracleDate structure.

Return Value

The number of days between the current OracleDate instance and the OracleDate structure.

Exceptions

OracleNullValueException - The current instance or the supplied OracleDate structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)

ToOracleTimeStamp

This method converts the current OracleDate structure to an OracleTimeStamp structure.

Declaration

```
// C#
public OracleTimeStamp ToOracleTimeStamp();
```

Return Value

An `OracleTimeStamp` structure.

Remarks

The returned `OracleTimeStamp` structure has date and time in the current instance.

If the `OracleDate` instance has a null value, the returned `OracleTimeStamp` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleDate Structure](#)
- [OracleDate Members](#)

ToString

Overrides `ValueType`

This method converts the current `OracleDate` structure to a string.

Declaration

```
// C#
public override string ToString();
```

Return Value

A string.

Remarks

The returned value is a string representation of the `OracleDate` in the format specified by the thread's `OracleGlobalization.DateFormat` property. The names and abbreviations used for months and days are in the language specified by the thread's `OracleGlobalization.DateLanguage` and `OracleGlobalization.Calendar` properties. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class ToStringSample
{
    static void Main(string[] args)
    {
        // Set the thread's DateFormat to a specific format
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.DateFormat = "YYYY-MON-DD";
        OracleGlobalization.SetThreadInfo(info);
    }
}
```

```
// Construct OracleDate from a string using the DateFormat specified
OracleDate date = (OracleDate)"1999-DEC-01";

// Set a different DateFormat on the thread for ToString()
info.DateFormat = "YYYY/MM/DD";
OracleGlobalization.SetThreadInfo(info);

// Prints "1999/12/01"
Console.WriteLine(date.ToString());
}
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDate Structure](#)
- [OracleDate Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125

OracleDecimal Structure

The `OracleDecimal` structure represents an Oracle `NUMBER` in the database or any Oracle numeric value.

Class Inheritance

`System.Object`

`System.ValueType`

`Oracle.DataAccess.Types.OracleDecimal`

Declaration

```
// C#
public struct OracleDecimal : IComparable, INullable, IXmlSerializable
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|-----------------------|--------------------------------------|---------------------------------------------|
| Assembly | <code>Oracle.DataAccess.dll</code> | <code>Oracle.ManagedDataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Types</code> | <code>Oracle.ManagedDataAccess.Types</code> |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

`OracleDecimal` can store up to 38 precision, while the .NET `Decimal` data type can only hold up to 28 precision. When accessing the `OracleDecimal.Value` property from an `OracleDecimal` that has a value greater than 28 precision, an exception is thrown. To retrieve the actual value of `OracleDecimal`, use the `OracleDecimal.ToString()` method. Another approach is to obtain the `OracleDecimal` value as a byte array in an internal Oracle `NUMBER` format through the `BinData` property.

Example

```
// C#

using System;
using Oracle.DataAccess.Types;

class OracleDecimalSample
{
    static void Main(string[] args)
    {
        // Illustrates the range of OracleDecimal vs. .NET decimal
        OracleDecimal decimal1 = OracleDecimal.MinValue;
        OracleDecimal decimal2 = OracleDecimal.MaxValue;
        OracleDecimal decimal3 = new OracleDecimal(decimal.MinValue);
        OracleDecimal decimal4 = new OracleDecimal(decimal.MaxValue);

        // Print the ranges
        Console.WriteLine("OracleDecimal can range from\n{0}\nto\n{1}\n",
```



```
decimal1, decimal2);  
Console.WriteLine(".NET decimal can range from\n{0}\nto\n{1}",  
decimal3, decimal4);  
}  
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Constructors](#)
- [OracleDecimal Static Fields](#)
- [OracleDecimal Static \(Comparison\) Methods](#)
- [OracleDecimal Static \(Manipulation\) Methods](#)
- [OracleDecimal Static \(Logarithmic\) Methods](#)
- [OracleDecimal Static \(Trigonometric\) Methods](#)
- [OracleDecimal Static \(Comparison\) Operators](#)
- [OracleDecimal Static Operators \(Conversion from .NET Type to OracleDecimal\)](#)
- [OracleDecimal Static Operators \(Conversion from OracleDecimal to .NET\)](#)
- [OracleDecimal Properties](#)
- [OracleDecimal Instance Methods](#)

OracleDecimal Members

OracleDecimal members are listed in the following tables:

OracleDecimal Constructors

OracleDecimal constructors are listed in [Table 14–40](#)

Table 14–40 OracleDecimal Constructors

| Constructor | Description |
|--------------------------------------------|---------------------------------------------------------------------|
| OracleDecimal Constructors | Instantiates a new instance of OracleDecimal structure (Overloaded) |

OracleDecimal Static Fields

The OracleDecimal static fields are listed in [Table 14–41](#).

Table 14–41 OracleDecimal Static Fields

| Field | Description |
|------------------------------|----------------------------------------------------------------------------------------------------|
| MaxPrecision | A constant representing the maximum precision, which is 38 |
| MaxScale | A constant representing the maximum scale, which is 127 |
| MaxValue | A constant representing the maximum value for this structure, which is $9.9\dots9 \times 10^{125}$ |
| MinScale | A constant representing the minimum scale, which is -84 |
| MinValue | A constant representing the minimum value for this structure, which is -1.0×10^{130} |
| NegativeOne | A constant representing the negative one value |
| Null | Represents a null value that can be assigned to an OracleDecimal instance |
| One | A constant representing the positive one value |
| Pi | A constant representing the numeric Pi value |
| Zero | A constant representing the zero value |

OracleDecimal Static (Comparison) Methods

The OracleDecimal static (comparison) methods are listed in [Table 14–42](#).

Table 14–42 OracleDecimal Static (Comparison) Methods

| Methods | Description |
|------------------------------------|--------------------------------------------------------------------------------------------|
| Equals | Determines if two OracleDecimal values are equal (Overloaded) |
| GreaterThan | Determines if the first of two OracleDecimal values is greater than the second |
| GreaterThanOrEqual | Determines if the first of two OracleDecimal values is greater than or equal to the second |
| LessThan | Determines if the first of two OracleDecimal values is less than the second |
| LessThanOrEqual | Determines if the first of two OracleDecimal values is less than or equal to the second. |

Table 14–42 (Cont.) OracleDecimal Static (Comparison) Methods

| Methods | Description |
|---------------------------|------------------------------------------------------|
| NotEquals | Determines if two OracleDecimal values are not equal |

OracleDecimal Static (Manipulation) Methods

The OracleDecimal static (manipulation) methods are listed in [Table 14–43](#).

Table 14–43 OracleDecimal Static (Manipulation) Methods

| Methods | Description |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Abs | Returns the absolute value of an OracleDecimal |
| Add | Adds two OracleDecimal structures |
| AdjustScale | Returns a new OracleDecimal with the specified number of digits and indicates whether or not to round or truncate the number if the scale is less than original |
| Ceiling | Returns a new OracleDecimal structure with its value set to the ceiling of an OracleDecimal structure |
| ConvertToPrecScale | Returns a new OracleDecimal structure with a new precision and scale |
| Divide | Divides one OracleDecimal value by another |
| Floor | Returns a new OracleDecimal structure with its value set to the floor of an OracleDecimal structure |
| Max | Returns the maximum value of the two supplied OracleDecimal structures |
| Min | Returns the minimum value of the two supplied OracleDecimal structures |
| Mod | Returns a new OracleDecimal structure with its value set to the modulus of two OracleDecimal structures |
| Multiply | Returns a new OracleDecimal structure with its value set to the result of multiplying two OracleDecimal structures |
| Negate | Returns a new OracleDecimal structure with its value set to the negation of the supplied OracleDecimal structure |
| Parse | Converts a string to an OracleDecimal |
| Round | Returns a new OracleDecimal structure with its value set to that of the supplied OracleDecimal structure and rounded off to the specified place |
| SetPrecision | Returns a new OracleDecimal structure with a new specified precision. |
| Shift | Returns a new OracleDecimal structure with its value set to that of the supplied OracleDecimal structure, and its decimal place shifted to the specified number of places to the right |
| Sign | Determines the sign of an OracleDecimal structure |
| Sqrt | Returns a new OracleDecimal structure with its value set to the square root of the supplied OracleDecimal structure |
| Subtract | Returns a new OracleDecimal structure with its value set to result of subtracting one OracleDecimal structure from another |
| Truncate | Truncates the OracleDecimal at a specified position |

OracleDecimal Static (Logarithmic) Methods

The OracleDecimal static (logarithmic) methods are listed in [Table 14-44](#).

Table 14-44 OracleDecimal Static (Logarithmic) Methods

| Methods | Description |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| Exp | Returns a new OracleDecimal structure with its value set to e raised to the supplied power |
| Log | Returns the supplied OracleDecimal structure with its value set to the logarithm of the supplied OracleDecimal structure (Overloaded) |
| Pow | Returns a new OracleDecimal structure with its value set to the supplied OracleDecimal structure raised to the supplied power (Overloaded) |

OracleDecimal Static (Trigonometric) Methods

The OracleDecimal static (trigonometric) methods are listed in [Table 14-45](#).

Table 14-45 OracleDecimal Static (Trigonometric) Methods

| Methods | Description |
|-----------------------|--------------------------------------------------------------------------------------------------------|
| Acos | Returns an angle in radians whose cosine is the supplied OracleDecimal structure |
| Asin | Returns an angle in radians whose sine is the supplied OracleDecimal structure |
| Atan | Returns an angle in radians whose tangent is the supplied OracleDecimal structure |
| Atan2 | Returns an angle in radians whose tangent is the quotient of the two supplied OracleDecimal structures |
| Cos | Returns the cosine of the supplied angle in radians |
| Sin | Returns the sine of the supplied angle in radians |
| Tan | Returns the tangent of the supplied angle in radians |
| Cosh | Returns the hyperbolic cosine of the supplied angle in radians |
| Sinh | Returns the hyperbolic sine of the supplied angle in radians |
| Tanh | Returns the hyperbolic tangent of the supplied angle in radians |

OracleDecimal Static (Comparison) Operators

The OracleDecimal static (comparison) operators are listed in [Table 14-46](#).

Table 14-46 OracleDecimal Static (Comparison) Operators

| Operator | Description |
|--------------------------------|--------------------------------------------------------------------------------------------|
| operator + | Adds two OracleDecimal values |
| operator / | Divides one OracleDecimal value by another |
| operator == | Determines if the two OracleDecimal values are equal |
| operator > | Determines if the first of two OracleDecimal values is greater than the second |
| operator >= | Determines if the first of two OracleDecimal values is greater than or equal to the second |

Table 14–46 (Cont.) OracleDecimal Static (Comparison) Operators

| Operator | Description |
|-----------------------------|----------------------------------------------------------------------------------------------------------|
| <code>operator !=</code> | Determines if the two OracleDecimal values are not equal |
| <code>operator <</code> | Determines if the first of two OracleDecimal values is less than the second |
| <code>operator <=</code> | Determines if the first of two OracleDecimal values is less than or equal to the second |
| <code>operator *</code> | Multiplies two OracleDecimal structures |
| <code>operator -</code> | Subtracts one OracleDecimal structure from another |
| <code>operator -</code> | Negates an OracleDecimal structure |
| <code>operator%</code> | Returns a new OracleDecimal structure with its value set to the modulus of two OracleDecimal structures. |

OracleDecimal Static Operators (Conversion from .NET Type to OracleDecimal)

The OracleDecimal static operators (Conversion from .NET Type to OracleDecimal) are listed in [Table 14–47](#).

Table 14–47 OracleDecimal Static Operators (Conversion from .NET Type to OracleDecimal)

| Operator | Description |
|----------------------------------------------|-----------------------------------------------------------------------|
| <code>implicit operator OracleDecimal</code> | Converts an instance value to an OracleDecimal structure (Overloaded) |
| <code>explicit operator OracleDecimal</code> | Converts an instance value to an OracleDecimal structure (Overloaded) |

OracleDecimal Static Operators (Conversion from OracleDecimal to .NET)

The OracleDecimal static operators (Conversion from OracleDecimal to .NET) are listed in [Table 14–48](#).

Table 14–48 OracleDecimal Static Operators (Conversion from OracleDecimal to .NET)

| Operator | Description |
|----------------------------------------|---------------------------------------------------------------|
| <code>explicit operator byte</code> | Returns the byte representation of the OracleDecimal value |
| <code>explicit operator decimal</code> | Returns the decimal representation of the OracleDecimal value |
| <code>explicit operator double</code> | Returns the double representation of the OracleDecimal value |
| <code>explicit operator short</code> | Returns the short representation of the OracleDecimal value |
| <code>explicit operator int</code> | Returns the int representation of the OracleDecimal value |
| <code>explicit operator long</code> | Returns the long representation of the OracleDecimal value |
| <code>explicit operator float</code> | Returns the float representation of the OracleDecimal value |

OracleDecimal Properties

The OracleDecimal properties are listed in [Table 14–49](#).

Table 14–49 OracleDecimal Properties

| Properties | Description |
|----------------------------|----------------------------------------------------------------------------------|
| BinData | Returns a byte array that represents the Oracle NUMBER in Oracle internal format |
| Format | Specifies the format for ToString() |
| IsInt | Indicates whether or not the current instance is an integer |
| IsNull | Indicates whether or not the current instance has a null value |
| IsPositive | Indicates whether or not the current instance is greater than 0 |
| IsZero | Indicates whether or not the current instance has a zero value |
| Value | Returns a decimal value |

OracleDecimal Instance Methods

The OracleDecimal instance methods are listed in [Table 14–50](#).

Table 14–50 OracleDecimal Instance Methods

| Method | Description |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CompareTo | Compares the current instance to the supplied object and returns an integer that represents their relative values |
| Equals | Determines whether or not an object is an instance of OracleDecimal, and whether or not the value of the object is equal to the current instance (Overloaded) |
| GetHashCode | Returns a hash code for the current instance |
| GetType | Inherited from System.Object |
| ToByte | Returns the byte representation of the current instance |
| ToDouble | Returns the double representation of the current instance |
| ToInt16 | Returns the Int16 representation of the current instance |
| ToInt32 | Returns the Int32 representation of the current instance |
| ToInt64 | Returns the Int64 representation of the current instance |
| ToSingle | Returns the Single representation of the current instance |
| ToString | Overloads Object.ToString() Returns the string representation of the current instance |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Structure](#)

OracleDecimal Constructors

The `OracleDecimal` constructors instantiate a new instance of the `OracleDecimal` structure.

Overload List:

- [OracleDecimal\(byte \[\]\)](#)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied byte array, which is in an Oracle `NUMBER` format.

- [OracleDecimal\(decimal\)](#)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied `Decimal` value.

- [OracleDecimal\(double\)](#)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied `double` value.

- [OracleDecimal\(int\)](#)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied `Int32` value.

- [OracleDecimal\(float\)](#)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied `Single` value.

- [OracleDecimal\(long\)](#)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied `Int64` value.

- [OracleDecimal\(string\)](#)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied `string` value.

- [OracleDecimal\(string, string\)](#)

This constructor creates a new instance of the `OracleDecimal` structure with the supplied `string` value and number format.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal(byte [])

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied byte array, which is in an Oracle `NUMBER` format.

Declaration

```
// C#  
public OracleDecimal(byte [] bytes);
```

Parameters

- *bytes*

A byte array that represents an Oracle NUMBER in an internal Oracle format.

Exceptions

ArgumentException - The *bytes* parameter is not in a internal Oracle NUMBER format or *bytes* has an invalid value.

ArgumentNullException - The *bytes* parameter is null.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal(decimal)

This constructor creates a new instance of the *OracleDecimal* structure and sets its value to the supplied *Decimal* value.

Declaration

```
// C#  
public OracleDecimal(decimal decX);
```

Parameters

- *decX*

The provided *Decimal* value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal(double)

This constructor creates a new instance of the *OracleDecimal* structure and sets its value to the supplied *double* value.

Declaration

```
// C#  
public OracleDecimal(double doubleX)
```

Parameters

- *doubleX*

The provided *double* value.

Exceptions

OverflowException - The value of the supplied *double* is greater than the maximum value or less than the minimum value of *OracleDecimal*.

Remarks

OracleDecimal contains the following values depending on the provided double value:

- `double.PositiveInfinity`: positive infinity value
- `double.NegativeInfinity`: negative infinity value.
- `double.NaN`: null value

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal(int)

This constructor creates a new instance of the OracleDecimal structure and sets its value to the supplied Int32 value.

Declaration

```
// C#  
public OracleDecimal(int intX);
```

Parameters

- *intX*

The provided Int32 value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal(float)

This constructor creates a new instance of the OracleDecimal structure and sets its value to the supplied Single value.

Declaration

```
// C#  
public OracleDecimal(float floatX);
```

Parameters

- *floatX*

The provided float value.

Remarks

OracleDecimal contains the following values depending on the provided float value:

`float.PositiveInfinity`: positive infinity value

`float.NegativeInfinity`: negative infinity value

`float.NaN`: null value

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal(long)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied `Int64` value.

Declaration

```
// C#  
public OracleDecimal(long longX);
```

Parameters

- *longX*
The provided `Int64` value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal(string)

This constructor creates a new instance of the `OracleDecimal` structure and sets its value to the supplied `string` value.

Declaration

```
// C#  
public OracleDecimal(string numStr);
```

Parameters

- *numStr*
The provided `string` value.

Exceptions

`ArgumentException` - The *numStr* parameter is an invalid string representation of an `OracleDecimal`.

`ArgumentNullException` - The *numStr* parameter is null.

`OverflowException` - The value of *numStr* is greater than the maximum value or less than the minimum value of `OracleDecimal`.

`input string format is incorrect` - The locale's numeric separator is a comma(,).

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125

OracleDecimal(string, string)

This constructor creates a new instance of the `OracleDecimal` structure with the supplied `string` value and number format.

Declaration

```
// C#  
public OracleDecimal(string numStr, string format);
```

Parameters

- `numStr`
The provided `string` value.
- `format`
The provided number format.

Exceptions

`ArgumentException` - The `numStr` parameter is an invalid `string` representation of an `OracleDecimal` or the `numStr` is not in the numeric format specified by `format`.

`ArgumentNullException` - The `numStr` parameter is null.

`OverflowException` - The value of `numStr` parameter is greater than the maximum value or less than the minimum value of `OracleDecimal`.

Remarks

If the numeric format includes decimal and group separators, then the provided `string` must use those characters defined by the `OracleGlobalization.NumericCharacters` of the thread.

If the numeric format includes the currency symbol, ISO currency symbol, or the dual currency symbol, then the provided `string` must use those symbols defined by the `OracleGlobalization.Currency`, `OracleGlobalization.ISOCurrency`, and `OracleGlobalization.DualCurrency` properties respectively.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
using Oracle.DataAccess.Types;  
  
class OracleDecimalSample  
{  
    static void Main(string[] args)
```

```
{
    // Set the nls parameters related to currency
    OracleGlobalization info = OracleGlobalization.GetClientInfo();
    info.Currency = "$";
    info.NumericCharacters = ".";
    OracleGlobalization.SetThreadInfo(info);

    // Construct an OracleDecimal using a valid numeric format
    OracleDecimal dec = new OracleDecimal("$2,222.22", "L9G999D99");

    // Print "$2,222.22"
    Console.WriteLine(dec.ToString());
}
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125

OracleDecimal Static Fields

The OracleDecimal static fields are listed in [Table 14–51](#).

Table 14–51 OracleDecimal Static Fields

| Field | Description |
|------------------------------|----------------------------------------------------------------------------------------------------|
| MaxPrecision | A constant representing the maximum precision, which is 38 |
| MaxScale | A constant representing the maximum scale, which is 127 |
| MaxValue | A constant representing the maximum value for this structure, which is $9.9\dots9 \times 10^{125}$ |
| MinScale | A constant representing the minimum scale, which is -84 |
| MinValue | A constant representing the minimum value for this structure, which is -1.0×10^{130} |
| NegativeOne | A constant representing the negative one value |
| Null | Represents a null value that can be assigned to an OracleDecimal instance |
| One | A constant representing the positive one value |
| Pi | A constant representing the numeric Pi value |
| Zero | A constant representing the zero value |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

MaxPrecision

This static field represents the maximum precision, which is 38.

Declaration

```
// C#
public static readonly byte MaxPrecision;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

MaxScale

This static field a constant representing the maximum scale, which is 127.

Declaration

```
// C#
public static readonly byte MaxScale;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

MaxValue

This static field indicates a constant representing the maximum value for this structure, which is $9.9\dots9 \times 10^{125}$ (38 nines followed by 88 zeroes).

Declaration

```
// C#  
public static readonly OracleDecimal MaxValue;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

MinScale

This static field indicates a constant representing the maximum scale, which is -84.

Declaration

```
// C#  
public static readonly int MinScale;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

MinValue

This static field indicates a constant representing the minimum value for this structure, which is -1.0×10^{130} .

Declaration

```
// C#  
public static readonly OracleDecimal MinValue;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

NegativeOne

This static field indicates a constant representing the negative one value.

Declaration

```
// C#  
public static readonly OracleDecimal NegativeOne;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Null

This static field represents a null value that can be assigned to an OracleDecimal instance.

Declaration

```
// C#  
public static readonly OracleDecimal Null;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

One

This static field indicates a constant representing the positive one value.

Declaration

```
// C#  
public static readonly OracleDecimal One;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Pi

This static field indicates a constant representing the numeric Pi value.

Declaration

```
// C#  
public static readonly OracleDecimal Pi;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Zero

This static field indicates a constant representing the zero value.

Declaration

```
// C#  
public static readonly OracleDecimal Zero;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal Static (Comparison) Methods

The OracleDecimal static (comparison) methods are listed in [Table 14–52](#).

Table 14–52 OracleDecimal Static (Comparison) Methods

| Methods | Description |
|------------------------------------|--------------------------------------------------------------------------------------------|
| Equals | Determines if two OracleDecimal values are equal (Overloaded) |
| GreaterThan | Determines if the first of two OracleDecimal values is greater than the second |
| GreaterThanOrEqual | Determines if the first of two OracleDecimal values is greater than or equal to the second |
| LessThan | Determines if the first of two OracleDecimal values is less than the second |
| LessThanOrEqual | Determines if the first of two OracleDecimal values is less than or equal to the second. |
| NotEquals | Determines if two OracleDecimal values are not equal |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Equals

This method determines if two OracleDecimal values are equal.

Declaration

```
// C#
public static bool Equals(OracleDecimal value1, OracleDecimal value2);
```

Parameters

- *value1*
The first OracleDecimal.
- *value2*
The second OracleDecimal.

Return Value

Returns true if two OracleDecimal values are equal; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleDecimal that has a value compares greater than an OracleDecimal that has a null value.
- Two OracleDecimals that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

GreaterThan

This method determines if the first of two `OracleDecimal` values is greater than the second.

Declaration

```
// C#  
public static bool GreaterThan(OracleDecimal value1, OracleDecimal value2);
```

Parameters

- *value1*
The first `OracleDecimal`.
- *value2*
The second `OracleDecimal`.

Return Value

Returns `true` if the first of two `OracleDecimal` values is greater than the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleDecimal` that has a value compares greater than an `OracleDecimal` that has a null value.
- Two `OracleDecimals` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

GreaterThanOrEqual

This method determines if the first of two `OracleDecimal` values is greater than or equal to the second.

Declaration

```
// C#  
public static bool GreaterThanOrEqual(OracleDecimal value1, OracleDecimal value2);
```

Parameters

- *value1*

The first OracleDecimal.

- *value2*

The second OracleDecimal.

Return Value

Returns true if the first of two OracleDecimal values is greater than or equal to the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleDecimal that has a value compares greater than an OracleDecimal that has a null value.
- Two OracleDecimals that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

LessThan

This method determines if the first of two OracleDecimal values is less than the second.

Declaration

```
// C#  
public static bool LessThan(OracleDecimal value1, OracleDecimal value2);
```

Parameters

- *value1*

The first OracleDecimal.

- *value2*

The second OracleDecimal.

Return Value

Returns true if the first of two OracleDecimal values is less than the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleDecimal that has a value compares greater than an OracleDecimal that has a null value.
- Two OracleDecimals that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

LessThanOrEqual

This method determines if the first of two `OracleDecimal` values is less than or equal to the second.

Declaration

```
// C#  
public static bool LessThanOrEqual(OracleDecimal value1, OracleDecimal value2);
```

Parameters

- *value1*
The first `OracleDecimal`.
- *value2*
The second `OracleDecimal`.

Return Value

Returns `true` if the first of two `OracleDecimal` values is less than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleDecimal` that has a value compares greater than an `OracleDecimal` that has a null value.
- Two `OracleDecimals` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

NotEquals

This method determines if two `OracleDecimal` values are not equal.

Declaration

```
// C#  
public static bool NotEquals(OracleDecimal value1, OracleDecimal value2);
```

Parameters

- *value1*
The first `OracleDecimal`.

- *value2*
The second OracleDecimal.

Return Value

Returns true if two OracleDecimal values are not equal; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleDecimal that has a value compares greater than an OracleDecimal that has a null value.
- Two OracleDecimals that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal Static (Manipulation) Methods

The OracleDecimal static (manipulation) methods are listed in [Table 14–53](#).

Table 14–53 OracleDecimal Static (Manipulation) Methods

| Methods | Description |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Abs | Returns the absolute value of an OracleDecimal |
| Add | Adds two OracleDecimal structures |
| AdjustScale | Returns a new OracleDecimal with the specified number of digits and indicates whether or not to round or truncate the number if the scale is less than original |
| Ceiling | Returns a new OracleDecimal structure with its value set to the ceiling of an OracleDecimal structure |
| ConvertToPrecScale | Returns a new OracleDecimal structure with a new precision and scale |
| Divide | Divides one OracleDecimal value by another |
| Floor | Returns a new OracleDecimal structure with its value set to the floor of an OracleDecimal structure |
| Max | Returns the maximum value of the two supplied OracleDecimal structures |
| Min | Returns the minimum value of the two supplied OracleDecimal structures |
| Mod | Returns a new OracleDecimal structure with its value set to the modulus of two OracleDecimal structures |
| Multiply | Returns a new OracleDecimal structure with its value set to the result of multiplying two OracleDecimal structures |
| Negate | Returns a new OracleDecimal structure with its value set to the negation of the supplied OracleDecimal structure |
| Parse | Converts a string to an OracleDecimal |
| Round | Returns a new OracleDecimal structure with its value set to that of the supplied OracleDecimal structure and rounded off to the specified place |
| SetPrecision | Returns a new OracleDecimal structure with a new specified precision. |
| Shift | Returns a new OracleDecimal structure with its value set to that of the supplied OracleDecimal structure, and its decimal place shifted to the specified number of places to the right |
| Sign | Determines the sign of an OracleDecimal structure |
| Sqrt | Returns a new OracleDecimal structure with its value set to the square root of the supplied OracleDecimal structure |
| Subtract | Returns a new OracleDecimal structure with its value set to result of subtracting one OracleDecimal structure from another |
| Truncate | Truncates the OracleDecimal at a specified position |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Abs

This method returns the absolute value of an OracleDecimal.

Declaration

```
// C#  
public static OracleDecimal Abs(OracleDecimal val);
```

Parameters

- *val*
An OracleDecimal.

Return Value

The absolute value of an OracleDecimal.

Remarks

If either argument has a null value, the returned OracleDecimal has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Add

This method adds two OracleDecimal structures.

Declaration

```
// C#  
public static OracleDecimal Add(OracleDecimal val1, OracleDecimal val2);
```

Parameters

- *val1*
The first OracleDecimal.
- *val2*
The second OracleDecimal.

Return Value

Returns an OracleDecimal structure.

Remarks

If either argument has a null value, the returned OracleDecimal has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

AdjustScale

This method returns a new `OracleDecimal` with the specified number of digits and indicates whether or not to round or truncate the number if the scale is less than the original.

Declaration

```
// C#
public static OracleDecimal AdjustScale(OracleDecimal val, int digits,
    bool fRound);
```

Parameters

- *val*
An `OracleDecimal`.
- *digits*
The number of digits.
- *fRound*
Indicates whether or not to round or truncate the number. Setting it to `true` rounds the number and setting it to `false` truncates the number.

Return Value

An `OracleDecimal`.

Remarks

If the supplied `OracleDecimal` has a null value, the returned `OracleDecimal` has a null value.

Example

```
// C#
using System;
using Oracle.DataAccess.Types;

class AdjustScaleSample
{
    static void Main(string[] args)
    {
        OracleDecimal dec1 = new OracleDecimal(5.555);

        // Adjust Scale to 2 with rounding off
        OracleDecimal dec2 = OracleDecimal.AdjustScale(dec1, 2, true);

        // Prints 5.56
        Console.WriteLine(dec2.ToString());

        // Adjust Scale to 2 with truncation
```



```
OracleDecimal dec3 = OracleDecimal.AdjustScale(dec1, 2, false);

// Prints 5.55
Console.WriteLine(dec3.ToString());
}
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Ceiling

This method returns a new `OracleDecimal` structure with its value set to the ceiling of the supplied `OracleDecimal`.

Declaration

```
// C#
public static OracleDecimal Ceiling(OracleDecimal val);
```

Parameters

- *val*
An `OracleDecimal`.

Return Value

A new `OracleDecimal` structure.

Remarks

If either argument has a null value, the returned `OracleDecimal` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

ConvertToPrecScale

This method returns a new `OracleDecimal` structure with a new precision and scale.

Declaration

```
// C#
public static OracleDecimal ConvertToPrecScale(OracleDecimal val
    int precision, int scale);
```

Parameters

- *val*
An `OracleDecimal` structure.

- *precision*
The precision. Range of precision is 1 to 38.
- *scale*
The number of digits to the right of the decimal point. Range of scale is -84 to 127.

Return Value

A new OracleDecimal structure.

Remarks

If the supplied OracleDecimal has a null value, the returned OracleDecimal has a null value.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Types;  
  
class ConvertToPrecScaleSample  
{  
    static void Main(string[] args)  
    {  
        OracleDecimal dec1 = new OracleDecimal(555.6666);  
  
        // Set the precision of od to 5 and scale to 2  
        OracleDecimal dec2 = OracleDecimal.ConvertToPrecScale(dec1,5,2);  
  
        // Prints 555.67  
        Console.WriteLine(dec2.ToString());  
  
        // Set the precision of od to 3 and scale to 0  
        OracleDecimal dec3 = OracleDecimal.ConvertToPrecScale(dec1,3,0);  
  
        // Prints 556  
        Console.WriteLine(dec3.ToString());  
    }  
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Divide

This method divides one OracleDecimal value by another.

Declaration

```
// C#  
public static OracleDecimal Divide(OracleDecimal val1, OracleDecimal val2);
```

Parameters

- *val1*
An OracleDecimal.
- *val2*
An OracleDecimal.

Return Value

A new OracleDecimal structure.

Remarks

If either argument has a null value, the returned OracleDecimal has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Floor

This method returns a new OracleDecimal structure with its value set to the floor of the supplied OracleDecimal structure.

Declaration

```
// C#  
public static OracleDecimal Floor(OracleDecimal val);
```

Parameters

- *val*
An OracleDecimal structure.

Return Value

A new OracleDecimal structure.

Remarks

If either argument has a null value, the returned OracleDecimal has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Max

This method returns the maximum value of the two supplied OracleDecimal structures.

Declaration

```
// C#  
public static OracleDecimal Max(OracleDecimal val1, OracleDecimal val2);
```

Parameters

- *val1*
An OracleDecimal structure.
- *val2*
An OracleDecimal structure.

Return Value

An OracleDecimal structure that has the greater value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Min

This method returns the minimum value of the two supplied OracleDecimal structures.

Declaration

```
// C#  
public static OracleDecimal Min(OracleDecimal val1, OracleDecimal val2);
```

Parameters

- *val1*
An OracleDecimal structure.
- *val2*
An OracleDecimal structure.

Return Value

An OracleDecimal structure that has the smaller value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Mod

This method returns a new OracleDecimal structure with its value set to the modulus of two OracleDecimal structures.

Declaration

```
// C#  
public static OracleDecimal Mod(OracleDecimal val1, OracleDecimal divider);
```

Parameters

- *val1*
An OracleDecimal structure.
- *divider*
An OracleDecimal structure.

Return Value

An OracleDecimal.

Remarks

If either argument has a null value, the returned OracleDecimal has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Multiply

This method returns a new OracleDecimal structure with its value set to the result of multiplying two OracleDecimal structures.

Declaration

```
// C#  
public static OracleDecimal Multiply(OracleDecimal val1, OracleDecimal val2);
```

Parameters

- *val1*
An OracleDecimal structure.
- *val2*
An OracleDecimal structure.

Return Value

A new OracleDecimal structure.

Remarks

If either argument has a null value, the returned OracleDecimal has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Negate

This method returns a new `OracleDecimal` structure with its value set to the negation of the supplied `OracleDecimal` structures.

Declaration

```
// C#  
public static OracleDecimal Negate(OracleDecimal val);
```

Parameters

- *val*
An `OracleDecimal` structure.

Return Value

A new `OracleDecimal` structure.

Remarks

If either argument has a null value, the returned `OracleDecimal` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Parse

This method converts a string to an `OracleDecimal`.

Declaration

```
// C#  
public static OracleDecimal Parse (string str);
```

Parameters

- *str*
The string being converted.

Return Value

A new `OracleDecimal` structure.

Exceptions

`ArgumentException` - The *numStr* parameter is an invalid string representation of an `OracleDecimal`.

`ArgumentNullException` - The *numStr* parameter is null.

`OverflowException` - The value of *numStr* is greater than the maximum value or less than the minimum value of `OracleDecimal`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125

Round

This method returns a new `OracleDecimal` structure with its value set to that of the supplied `OracleDecimal` structure and rounded off to the specified place.

Declaration

```
// C#  
public static OracleDecimal Round(OracleDecimal val, int decplace);
```

Parameters

- *val*
An `OracleDecimal` structure.
- *decplace*
The specified decimal place. If the value is positive, the function rounds the `OracleDecimal` structure to the right of the decimal point. If the value is negative, the function rounds to the left of the decimal point.

Return Value

An `OracleDecimal` structure.

Remarks

If the supplied `OracleDecimal` structure has a null value, the returned `OracleDecimal` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

SetPrecision

This method returns a new `OracleDecimal` structure with a new specified precision.

Declaration

```
// C#  
public static OracleDecimal SetPrecision(OracleDecimal val, int precision);
```

Parameters

- *val*

An OracleDecimal structure.

- *precision*

The specified precision. Range of precision is 1 to 38.

Return Value

An OracleDecimal structure.

Remarks

The returned OracleDecimal is rounded off if the specified precision is smaller than the precision of *val*.

If *val* has a null value, the returned OracleDecimal has a null value.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Types;  
  
class SetPrecisionSample  
{  
    static void Main(string[] args)  
    {  
        OracleDecimal dec1 = new OracleDecimal(555.6666);  
  
        // Set the precision of dec1 to 3  
        OracleDecimal dec2 = OracleDecimal.SetPrecision(dec1, 3);  
  
        // Prints 556  
        Console.WriteLine(dec2.ToString());  
  
        // Set the precision of dec1 to 4  
        OracleDecimal dec3 = OracleDecimal.SetPrecision(dec1, 4);  
  
        // Prints 555.7  
        Console.WriteLine(dec3.ToString());  
    }  
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Shift

This method returns a new OracleDecimal structure with its value set to that of the supplied OracleDecimal structure, and its decimal place shifted to the specified number of places to the right.

Declaration

```
// C#
```



```
public static OracleDecimal Shift(OracleDecimal val, int decplaces);
```

Parameters

- *val*
An OracleDecimal structure.
- *decplaces*
The specified number of places to be shifted.

Return Value

An OracleDecimal structure.

Remarks

If the supplied OracleDecimal structure has a null value, the returned OracleDecimal has a null value.

If *decplaces* is negative, the shift is to the left.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Sign

This method determines the sign of an OracleDecimal structure.

Declaration

```
// C#  
public static int Sign(OracleDecimal val);
```

Parameters

- *val*
An OracleDecimal structure.

Return Value

- -1: if the supplied OracleDecimal < 0
- 0: if the supplied OracleDecimal == 0
- 1: if the supplied OracleDecimal > 0

Exceptions

OracleNullValueException - The argument has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Sqrt

This method returns a new `OracleDecimal` structure with its value set to the square root of the supplied `OracleDecimal` structure.

Declaration

```
// C#  
public static OracleDecimal Sqrt(OracleDecimal val);
```

Parameters

- *val*
An `OracleDecimal` structure.

Return Value

An `OracleDecimal` structure.

Exceptions

`ArgumentOutOfRangeException` - The provided `OracleDecimal` structure is less than zero.

Remarks

If either argument has a null value, the returned `OracleDecimal` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Subtract

This method returns a new `OracleDecimal` structure with its value set to result of subtracting one `OracleDecimal` structure from another.

Declaration

```
// C#  
public static OracleDecimal Subtract(OracleDecimal val1, OracleDecimal val2);
```

Parameters

- *val1*
An `OracleDecimal` structure.
- *val2*
An `OracleDecimal` structure.

Return Value

An `OracleDecimal` structure.

Remarks

If either argument has a null value, the returned `OracleDecimal` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Truncate

This method truncates the `OracleDecimal` at a specified position.

Declaration

```
// C#  
public static OracleDecimal Truncate(OracleDecimal val, int pos);
```

Parameters

- *val*
An `OracleDecimal` structure.
- *pos*
The specified position. If the value is positive, the function truncates the `OracleDecimal` structure to the right of the decimal point. If the value is negative, it truncates the `OracleDecimal` structure to the left of the decimal point.

Return Value

An `OracleDecimal` structure.

Remarks

If the supplied `OracleDecimal` structure has a null value, the returned `OracleDecimal` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal Static (Logarithmic) Methods

The OracleDecimal static (logarithmic) methods are listed in [Table 14–54](#).

Table 14–54 OracleDecimal Static (Logarithmic) Methods

| Methods | Description |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| Exp | Returns a new OracleDecimal structure with its value set to e raised to the supplied power |
| Log | Returns the supplied OracleDecimal structure with its value set to the logarithm of the supplied OracleDecimal structure (Overloaded) |
| Pow | Returns a new OracleDecimal structure with its value set to the supplied OracleDecimal structure raised to the supplied power (Overloaded) |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Exp

This method returns a new OracleDecimal structure with its value set to e raised to the supplied OracleDecimal.

Declaration

```
// C#
public static OracleDecimal Exp(OracleDecimal val);
```

Parameters

- *val*
An OracleDecimal structure.

Return Value

An OracleDecimal structure.

Remarks

If either argument has a null value, the returned OracleDecimal has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Log

Log returns the supplied OracleDecimal structure with its value set to the logarithm of the supplied OracleDecimal structure.

Overload List:■ [Log\(OracleDecimal\)](#)

This method returns a new `OracleDecimal` structure with its value set to the natural logarithm (base e) of the supplied `OracleDecimal` structure.

■ [Log\(OracleDecimal, int\)](#)

This method returns the supplied `OracleDecimal` structure with its value set to the logarithm of the supplied `OracleDecimal` structure in the supplied base.

■ [Log\(OracleDecimal, OracleDecimal\)](#)

This method returns the supplied `OracleDecimal` structure with its value set to the logarithm of the supplied `OracleDecimal` structure in the supplied base.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Log(OracleDecimal)

This method returns a new `OracleDecimal` structure with its value set to the natural logarithm (base e) of the supplied `OracleDecimal` structure.

Declaration

```
// C#  
public static OracleDecimal Log(OracleDecimal val);
```

Parameters

- *val*

An `OracleDecimal` structure whose logarithm is to be calculated.

Return Value

Returns a new `OracleDecimal` structure with its value set to the natural logarithm (base e) of *val*.

Exceptions

`ArgumentOutOfRangeException` - The supplied `OracleDecimal` value is less than zero.

Remarks

If the supplied `OracleDecimal` structure has a null value, the returned `OracleDecimal` has a null value.

If the supplied `OracleDecimal` structure has zero value, the result is undefined, and the returned `OracleDecimal` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Log(OracleDecimal, int)

This method returns the supplied `OracleDecimal` structure with its value set to the logarithm of the supplied `OracleDecimal` structure in the supplied base.

Declaration

```
// C#  
public static OracleDecimal Log(OracleDecimal val, int logBase);
```

Parameters

- *val*
An `OracleDecimal` structure whose logarithm is to be calculated.
- *logBase*
An `int` that specifies the base of the logarithm.

Return Value

A new `OracleDecimal` structure with its value set to the logarithm of *val* in the supplied base.

Exceptions

`ArgumentOutOfRangeException` - Either argument is less than zero.

Remarks

If either argument has a null value, the returned `OracleDecimal` has a null value.

If both arguments have zero value, the result is undefined, and the returned `OracleDecimal` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Log(OracleDecimal, OracleDecimal)

This method returns the supplied `OracleDecimal` structure with its value set to the logarithm of the supplied `OracleDecimal` structure in the supplied base.

Declaration

```
// C#  
public static OracleDecimal Log(OracleDecimal val, OracleDecimal logBase);
```

Parameters

- *val*
An `OracleDecimal` structure whose logarithm is to be calculated.
- *logBase*
An `OracleDecimal` structure that specifies the base of the logarithm.

Return Value

Returns the logarithm of *val* in the supplied base.

Exceptions

`ArgumentOutOfRangeException` - Either the *val* or *logBase* parameter is less than zero.

Remarks

If either argument has a null value, the returned `OracleDecimal` has a null value.

If both arguments have zero value, the result is undefined, and the returned `OracleDecimal` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Pow

`Pow` returns a new `OracleDecimal` structure with its value set to the supplied `OracleDecimal` structure raised to the supplied power.

Overload List:

- [Pow\(OracleDecimal, int\)](#)

This method returns a new `OracleDecimal` structure with its value set to the supplied `OracleDecimal` value raised to the supplied `Int32` power.
- [Pow\(OracleDecimal, OracleDecimal\)](#)

This method returns a new `OracleDecimal` structure with its value set to the supplied `OracleDecimal` structure raised to the supplied `OracleDecimal` power.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Pow(OracleDecimal, int)

This method returns a new `OracleDecimal` structure with its value set to the supplied `OracleDecimal` value raised to the supplied `Int32` power.

Declaration

```
// C#  
public static OracleDecimal Pow(OracleDecimal val, int power);
```

Parameters

- *val*

An `OracleDecimal` structure.
- *power*

An int value that specifies the power.

Return Value

An OracleDecimal structure.

Remarks

If the supplied OracleDecimal structure has a null value, the returned OracleDecimal has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Pow(OracleDecimal, OracleDecimal)

This method returns a new OracleDecimal structure with its value set to the supplied OracleDecimal structure raised to the supplied OracleDecimal power.

Declaration

```
// C#  
public static OracleDecimal Pow(OracleDecimal val, OracleDecimal power);
```

Parameters

- *val*
An OracleDecimal structure.
- *power*
An OracleDecimal structure that specifies the power.

Return Value

An OracleDecimal structure.

Remarks

If the supplied OracleDecimal structure has a null value, the returned OracleDecimal has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal Static (Trigonometric) Methods

The OracleDecimal static (trigonometric) methods are listed in [Table 14-55](#).

Table 14-55 OracleDecimal Static (Trigonometric) Methods

| Methods | Description |
|-----------------------|--------------------------------------------------------------------------------------------------------|
| Acos | Returns an angle in radians whose cosine is the supplied OracleDecimal structure |
| Asin | Returns an angle in radians whose sine is the supplied OracleDecimal structure |
| Atan | Returns an angle in radians whose tangent is the supplied OracleDecimal structure |
| Atan2 | Returns an angle in radians whose tangent is the quotient of the two supplied OracleDecimal structures |
| Cos | Returns the cosine of the supplied angle in radians |
| Sin | Returns the sine of the supplied angle in radians |
| Tan | Returns the tangent of the supplied angle in radians |
| Cosh | Returns the hyperbolic cosine of the supplied angle in radians |
| Sinh | Returns the hyperbolic sine of the supplied angle in radians |
| Tanh | Returns the hyperbolic tangent of the supplied angle in radians |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Acos

This method returns an angle in radians whose cosine is the supplied OracleDecimal structure.

Declaration

```
// C#
public static OracleDecimal Acos(OracleDecimal val);
```

Parameters

- *val*
An OracleDecimal structure. Range is (-1 to 1).

Return Value

An OracleDecimal structure that represents an angle in radians.

Remarks

If either argument has a null value, the returned OracleDecimal has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Asin

This method returns an angle in radians whose sine is the supplied `OracleDecimal` structure.

Declaration

```
// C#  
public static OracleDecimal Asin(OracleDecimal val);
```

Parameters

- *val*
An `OracleDecimal` structure. Range is (-1 to 1).

Return Value

An `OracleDecimal` structure that represents an angle in radians.

Remarks

If either argument has a null value, the returned `OracleDecimal` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Atan

This method returns an angle in radians whose tangent is the supplied `OracleDecimal` structure

Declaration

```
// C#  
public static OracleDecimal Atan(OracleDecimal val);
```

Parameters

- *val*
An `OracleDecimal`.

Return Value

An `OracleDecimal` structure that represents an angle in radians.

Remarks

If the argument has a null value, the returned `OracleDecimal` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Atan2

This method returns an angle in radians whose tangent is the quotient of the two supplied OracleDecimal structures.

Declaration

```
// C#  
public static OracleDecimal Atan2(OracleDecimal val1, OracleDecimal val2);
```

Parameters

- *val1*
An OracleDecimal structure that represents the y-coordinate.
- *val2*
An OracleDecimal structure that represents the x-coordinate.

Return Value

An OracleDecimal structure that represents an angle in radians.

Remarks

If either argument has a null value, the returned OracleDecimal has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Cos

This method returns the cosine of the supplied angle in radians.

Declaration

```
// C#  
public static OracleDecimal Cos(OracleDecimal val);
```

Parameters

- *val*
An OracleDecimal structure that represents an angle in radians.

Return Value

An OracleDecimal instance.

Exceptions

`ArgumentOutOfRangeException` - The `val` parameter is positive or negative infinity.

Remarks

If either argument has a null value, the returned `OracleDecimal` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Sin

This method returns the sine of the supplied angle in radians.

Declaration

```
// C#  
public static OracleDecimal Sin(OracleDecimal val);
```

Parameters

- `val`
An `OracleDecimal` structure.

Return Value

An `OracleDecimal` structure that represents an angle in radians.

Exceptions

`ArgumentOutOfRangeException` - The `val` parameter is positive or negative infinity.

Remarks

If either argument has a null value, the returned `OracleDecimal` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Tan

This method returns the tangent of the supplied angle in radians.

Declaration

```
// C#  
public static OracleDecimal Tan(OracleDecimal val);
```

Parameters

- `val`
An `OracleDecimal` structure that represents an angle in radians.

Return Value

An OracleDecimal instance.

Exceptions

ArgumentOutOfRangeException - The *val* parameter is positive or negative infinity.

Remarks

If either argument has a null value, the returned OracleDecimal has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Cosh

This method returns the hyperbolic cosine of the supplied angle in radians.

Declaration

```
// C#  
public static OracleDecimal Cosh(OracleDecimal val);
```

Parameters

- *val*
An OracleDecimal structure that represents an angle in radians.

Return Value

An OracleDecimal instance.

Remarks

If either argument has a null value, the returned OracleDecimal has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Sinh

This method returns the hyperbolic sine of the supplied angle in radians.

Declaration

```
// C#  
public static OracleDecimal Sinh(OracleDecimal val);
```

Parameters

- *val*
An OracleDecimal structure that represents an angle in radians.

Return Value

An `OracleDecimal` instance.

Remarks

If either argument has a null value, the returned `OracleDecimal` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Tanh

This method returns the hyperbolic tangent of the supplied angle in radians.

Declaration

```
// C#  
public static OracleDecimal Tanh(OracleDecimal val);
```

Parameters

- *val*
An `OracleDecimal` structure that represents an angle in radians.

Return Value

An `OracleDecimal` instance.

Remarks

If either argument has a null value, the returned `OracleDecimal` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal Static (Comparison) Operators

The OracleDecimal static (comparison) operators are listed in [Table 14–56](#).

Table 14–56 OracleDecimal Static (Comparison) Operators

| Operator | Description |
|--------------------------------|----------------------------------------------------------------------------------------------------------|
| operator + | Adds two OracleDecimal values |
| operator / | Divides one OracleDecimal value by another |
| operator == | Determines if the two OracleDecimal values are equal |
| operator > | Determines if the first of two OracleDecimal values is greater than the second |
| operator >= | Determines if the first of two OracleDecimal values is greater than or equal to the second |
| operator != | Determines if the two OracleDecimal values are not equal |
| operator < | Determines if the first of two OracleDecimal values is less than the second |
| operator <= | Determines if the first of two OracleDecimal values is less than or equal to the second |
| operator * | Multiplies two OracleDecimal structures |
| operator - | Subtracts one OracleDecimal structure from another |
| operator - | Negates an OracleDecimal structure |
| operator% | Returns a new OracleDecimal structure with its value set to the modulus of two OracleDecimal structures. |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

operator +

This method adds two OracleDecimal values.

Declaration

```
// C#
public static OracleDecimal operator + (OracleDecimal val1, OracleDecimal val2);
```

Parameters

- *val1*
The first OracleDecimal.
- *val2*
The second OracleDecimal.

Return Value

An OracleDecimal structure.

Remarks

If either operand has a null value, the returned `OracleDecimal` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

operator /

This method divides one `OracleDecimal` value by another.

Declaration

```
/ C#  
public static OracleDecimal operator / (OracleDecimal val1, OracleDecimal val2)
```

Parameters

- *val1*
The first `OracleDecimal`.
- *val2*
The second `OracleDecimal`.

Return Value

An `OracleDecimal` structure.

Remarks

If either operand has a null value, the returned `OracleDecimal` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

operator ==

This method determines if two `OracleDecimal` values are equal.

Declaration

```
// C#  
public static bool operator == (OracleDecimal val1, OracleDecimal val2);
```

Parameters

- *val1*
The first `OracleDecimal`.
- *val2*
The second `OracleDecimal`.

Return Value

Returns true if their values are equal; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleDecimal that has a value compares greater than an OracleDecimal that has a null value.
- Two OracleDecimals that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

operator >

This method determines if the first of two OracleDecimal values is greater than the second.

Declaration

```
// C#  
public static bool operator > (OracleDecimal val1, OracleDecimal val2);
```

Parameters

- *val1*
The first OracleDecimal.
- *val2*
The second OracleDecimal.

Return Value

Returns true if the two OracleDecimal values are not equal; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleDecimal that has a value compares greater than an OracleDecimal that has a null value.
- Two OracleDecimals that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

operator >=

This method determines if the first of two OracleDecimal values is greater than or equal to the second.

Declaration

```
// C#  
public static bool operator >= (OracleDecimal val1, OracleDecimal val2);
```

Parameters

- *val1*
The first OracleDecimal.
- *val2*
The second OracleDecimal.

Return Value

Returns true if the first of two OracleDecimal values is greater than or equal to the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleDecimal that has a value compares greater than an OracleDecimal that has a null value.
- Two OracleDecimals that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

operator !=

This method determines if the first of two OracleDecimal values are not equal.

Declaration

```
// C#  
public static bool operator != (OracleDecimal val1, OracleDecimal val2);
```

Parameters

- *val1*
The first OracleDecimal.
- *val2*
The second OracleDecimal.

Return Value

Returns true if the two OracleDecimal values are not equal; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleDecimal` that has a value compares greater than an `OracleDecimal` that has a null value.
- Two `OracleDecimals` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

operator <

This method determines if the first of two `OracleDecimal` values is less than the second.

Declaration

```
// C#  
public static bool operator < (OracleDecimal val1, OracleDecimal val2);
```

Parameters

- *val1*
The first `OracleDecimal`.
- *val2*
The second `OracleDecimal`.

Return Value

Returns true if the first of two `OracleDecimal` values is less than the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleDecimal` that has a value compares greater than an `OracleDecimal` that has a null value.
- Two `OracleDecimals` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

operator <=

This method determines if the first of two `OracleDecimal` values is less than or equal to the second.

Declaration

```
// C#  
public static bool operator <= (OracleDecimal val1, OracleDecimal val2);
```

Parameters

- *val1*
The first OracleDecimal.
- *val2*
The second OracleDecimal.

Return Value

Returns true if the first of two OracleDecimal values is less than or equal to the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleDecimal that has a value compares greater than an OracleDecimal that has a null value.
- Two OracleDecimals that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

operator *

This method multiplies two OracleDecimal structures.

Declaration

```
// C#  
public static OracleDecimal operator * (OracleDecimal val1, OracleDecimal val2);
```

Parameters

- *val1*
The first OracleDecimal.
- *val2*
The second OracleDecimal.

Return Value

A new OracleDecimal structure.

Remarks

If either operand has a null value, the returned OracleDecimal has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

operator -

This method subtracts one OracleDecimal structure from another.

Declaration

```
// C#  
public static OracleDecimal operator - (OracleDecimal val1, OracleDecimal val2);
```

Parameters

- *val1*
The first OracleDecimal.
- *val2*
The second OracleDecimal.

Return Value

A new OracleDecimal structure.

Remarks

If either operand has a null value, the returned OracleDecimal has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

operator -

This method negates the supplied OracleDecimal structure.

Declaration

```
// C#  
public static OracleDecimal operator - (OracleDecimal val);
```

Parameters

- *val*
An OracleDecimal.

Return Value

A new OracleDecimal structure.

Remarks

If the supplied `OracleDecimal` structure has a null value, the returned `OracleDecimal` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

operator%

This method returns a new `OracleDecimal` structure with its value set to the modulus of two `OracleDecimal` structures.

Declaration

```
// C#  
public static OracleDecimal operator % (OracleDecimal val,  
    OracleDecimal divider);
```

Parameters

- *val*
An `OracleDecimal`.
- *divider*
An `OracleDecimal`.

Return Value

A new `OracleDecimal` structure.

Remarks

If either operand has a null value, the returned `OracleDecimal` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal Static Operators (Conversion from .NET Type to OracleDecimal)

The `OracleDecimal` static operators (Conversion from .NET Type to `OracleDecimal`) are listed in [Table 14–57](#).

Table 14–57 OracleDecimal Static Operators (Conversion from .NET Type to OracleDecimal)

| Operator | Description |
|-------------------------------------------------|------------------------------------------------------------------------------------|
| implicit operator OracleDecimal | Converts an instance value to an <code>OracleDecimal</code> structure (Overloaded) |
| explicit operator OracleDecimal | Converts an instance value to an <code>OracleDecimal</code> structure (Overloaded) |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

implicit operator OracleDecimal

`implicit operator OracleDecimal` returns the `OracleDecimal` representation of a value.

Overload List:

- [implicit operator OracleDecimal\(decimal\)](#)
This method returns the `OracleDecimal` representation of a decimal value.
- [implicit operator OracleDecimal\(int\)](#)
This method returns the `OracleDecimal` representation of an `int` value.
- [implicit operator OracleDecimal\(long\)](#)
This method returns the `OracleDecimal` representation of a long value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

implicit operator OracleDecimal(decimal)

This method returns the `OracleDecimal` representation of a decimal value.

Declaration

```
// C#
public static implicit operator OracleDecimal(decimal val);
```

Parameters

- `val`

A decimal value.

Return Value

An OracleDecimal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

implicit operator OracleDecimal(int)

This method returns the OracleDecimal representation of an int value.

Declaration

```
// C#  
public static implicit operator OracleDecimal(int val);
```

Parameters

- *val*
An int value.

Return Value

An OracleDecimal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

implicit operator OracleDecimal(long)

This method returns the OracleDecimal representation of a long value.

Declaration

```
// C#  
public static implicit operator OracleDecimal(long val);
```

Parameters

- *val*
A long value.

Return Value

An OracleDecimal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

explicit operator OracleDecimal

OracleDecimal returns the OracleDecimal representation of a value.

Overload List:

- [explicit operator OracleDecimal\(double\)](#)
This method returns the OracleDecimal representation of a double.
- [explicit operator OracleDecimal\(string\)](#)
This method returns the OracleDecimal representation of a string.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

explicit operator OracleDecimal(double)

This method returns the OracleDecimal representation of a double.

Declaration

```
// C#  
public static explicit operator OracleDecimal(double val);
```

Parameters

- *val*
A double.

Return Value

An OracleDecimal.

Exceptions

OverflowException - The value of the supplied double is greater than the maximum value of OracleDecimal or less than the minimum value of OracleDecimal.

Remarks

OracleDecimal contains the following values depending on the provided double value:

- `double.PositiveInfinity`: positive infinity value
- `double.NegativeInfinity`: negative infinity value.
- `double.NaN`: null value

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

explicit operator OracleDecimal(string)

This method returns the `OracleDecimal` representation of a string.

Declaration

```
// C#  
public static explicit operator OracleDecimal(string numStr);
```

Parameters

- *numStr*
A string that represents a numeric value.

Return Value

An `OracleDecimal`.

Exceptions

`ArgumentException` - The *numStr* parameter is an invalid string representation of an `OracleDecimal`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125

OracleDecimal Static Operators (Conversion from OracleDecimal to .NET)

The OracleDecimal static operators (Conversion from OracleDecimal to .NET) are listed in [Table 14–58](#).

Table 14–58 OracleDecimal Static Operators (Conversion from OracleDecimal to .NET)

| Operator | Description |
|-------------------------------------------|---------------------------------------------------------------|
| explicit operator byte | Returns the byte representation of the OracleDecimal value |
| explicit operator decimal | Returns the decimal representation of the OracleDecimal value |
| explicit operator double | Returns the double representation of the OracleDecimal value |
| explicit operator short | Returns the short representation of the OracleDecimal value |
| explicit operator int | Returns the int representation of the OracleDecimal value |
| explicit operator long | Returns the long representation of the OracleDecimal value |
| explicit operator float | Returns the float representation of the OracleDecimal value |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

explicit operator byte

This method returns the byte representation of the OracleDecimal value.

Declaration

```
// C#
public static explicit operator byte(OracleDecimal val);
```

Parameters

- *val*
An OracleDecimal structure.

Return Value

A byte.

Exceptions

OracleNullValueException - OracleDecimal has a null value.

OverflowException- The byte cannot represent the supplied OracleDecimal structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

explicit operator decimal

This method returns the decimal representation of the OracleDecimal value.

Declaration

```
// C#  
public static explicit operator decimal(OracleDecimal val);
```

Parameters

- *val*
An OracleDecimal structure.

Return Value

A decimal.

Exceptions

OracleNullValueException - The OracleDecimal has a null value.

OverflowException - The decimal cannot represent the supplied OracleDecimal structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

explicit operator double

This method returns the double representation of the OracleDecimal value.

Declaration

```
// C#  
public static explicit operator double(OracleDecimal val);
```

Parameters

- *val*
An OracleDecimal structure.

Return Value

A double.

Exceptions

OracleNullValueException - The OracleDecimal has a null value.

OverflowException - The double cannot represent the supplied OracleDecimal structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

explicit operator short

This method returns the short representation of the OracleDecimal value.

Declaration

```
// C#  
public static explicit operator short(OracleDecimal val);
```

Parameters

- *val*
An OracleDecimal structure.

Return Value

A short.

Exceptions

OracleNullValueException - The OracleDecimal has a null value.

OverflowException - The short cannot represent the supplied OracleDecimal structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

explicit operator int

This method returns the int representation of the OracleDecimal value.

Declaration

```
// C#  
public static explicit operator int(OracleDecimal val);
```

Parameters

- *val*
An OracleDecimal structure.

Return Value

An int.

Exceptions

OracleNullValueException - The OracleDecimal has a null value.

OverflowException - The int cannot represent the supplied OracleDecimal structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

explicit operator long

This method returns the long representation of the OracleDecimal value.

Declaration

```
// C#  
public static explicit operator long(OracleDecimal val);
```

Parameters

- *val*
An OracleDecimal structure.

Return Value

A long.

Exceptions

OracleNullValueException - The OracleDecimal has a null value.

OverflowException - The long cannot represent the supplied OracleDecimal structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

explicit operator float

This method returns the float representation of the OracleDecimal value.

Declaration

```
// C#  
public static explicit operator float(OracleDecimal val);
```

Parameters

- *val*
An OracleDecimal structure.

Return Value

A float.

Exceptions

OracleNullValueException - The OracleDecimal has a null value.

OverflowException - The float cannot represent the supplied OracleDecimal structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal Properties

The OracleDecimal properties are listed in [Table 14–59](#).

Table 14–59 OracleDecimal Properties

| Properties | Description |
|----------------------------|----------------------------------------------------------------------------------|
| BinData | Returns a byte array that represents the Oracle NUMBER in Oracle internal format |
| Format | Specifies the format for ToString() |
| IsInt | Indicates whether or not the current instance is an integer |
| IsNull | Indicates whether or not the current instance has a null value |
| IsPositive | Indicates whether or not the current instance is greater than 0 |
| IsZero | Indicates whether or not the current instance has a zero value |
| Value | Returns a decimal value |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

BinData

This property returns a byte array that represents the Oracle NUMBER in an internal Oracle format.

Declaration

```
// C#
public byte[] BinData {get;}
```

Property Value

A byte array that represents the Oracle NUMBER in an internal Oracle format.

Exceptions

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Format

This property specifies the format for ToString().

Declaration

```
// C#
```



```
public string Format {get; set;}
```

Property Value

The string which specifies the format.

Remarks

`Format` is used when `ToString()` is called on an instance of an `OracleDecimal`. It is useful if the `ToString()` method needs a specific currency symbol, group, or decimal separator as part of a string.

By default, this property is null which indicates that no special formatting is used.

The decimal and group separator characters are specified by the thread's `OracleGlobalization.NumericCharacters`.

The currency symbols are specified by the following thread properties:

- `OracleGlobalization.Currency`
- `OracleGlobalization.ISOCurrency`
- `OracleGlobalization.DualCurrency`

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125

IsInt

This property indicates whether or not the current instance is an integer value.

Declaration

```
// C#  
public bool IsInt {get;}
```

Property Value

A `bool` value that returns `true` if the current instance is an integer value; otherwise, returns `false`.

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

IsNull

This property indicates whether or not the current instance has a null value.

Declaration

```
// C#  
public bool IsNull {get;}
```

Property Value

A bool value that returns true if the current instance has a null value; otherwise, returns false.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

IsPositive

This property indicates whether or not the value of the current instance is greater than 0.

Declaration

```
// C#  
public bool IsPositive {get;}
```

Property Value

A bool value that returns true if the current instance is greater than 0; otherwise, returns false.

Exceptions

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

IsZero

This property indicates whether or not the current instance has a zero value.

Declaration

```
// C#  
public bool IsZero{get;}
```

Property Value

A bool value that returns true if the current instance has a zero value; otherwise, returns false.

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Value

This method returns a decimal value.

Declaration

```
// C#  
public decimal Value {get;}
```

Property Value

A decimal value.

Exceptions

`OracleNullValueException` - The current instance has a null value.

`OverflowException` - The decimal cannot represent the supplied `OracleDecimal` structure.

Remarks

Precision can be lost when the decimal value is obtained from an `OracleDecimal`. See Remarks under "[OracleDecimal Structure](#)" on page 14-106 for further information.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

OracleDecimal Instance Methods

The `OracleDecimal` instance methods are listed in [Table 14–60](#).

Table 14–60 OracleDecimal Instance Methods

| Method | Description |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CompareTo | Compares the current instance to the supplied object and returns an integer that represents their relative values |
| Equals | Determines whether or not an object is an instance of <code>OracleDecimal</code> , and whether or not the value of the object is equal to the current instance (Overloaded) |
| GetHashCode | Returns a hash code for the current instance |
| GetType | Inherited from <code>System.Object</code> |
| ToByte | Returns the <code>byte</code> representation of the current instance |
| ToDouble | Returns the <code>double</code> representation of the current instance |
| ToInt16 | Returns the <code>Int16</code> representation of the current instance |
| ToInt32 | Returns the <code>Int32</code> representation of the current instance |
| ToInt64 | Returns the <code>Int64</code> representation of the current instance |
| ToSingle | Returns the <code>Single</code> representation of the current instance |
| ToString | Overloads <code>Object.ToString()</code> Returns the <code>string</code> representation of the current instance |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

CompareTo

This method compares the current instance to the supplied object and returns an integer that represents their relative values.

Declaration

```
// C#
public int CompareTo(object obj);
```

Parameters

- *obj*
The supplied instance.

Return Value

The method returns a number:

- Less than zero: if the value of the current instance is less than *obj*.
- Zero: if the value of the current instance is equal to *obj*.

- Greater than zero: if the value of the current instance is greater than *obj*.

Implements

Comparable

Exceptions

ArgumentException - The parameter is not of type OracleDecimal.

Remarks

The following rules apply to the behavior of this method.

- The comparison must be between OracleDecimals. For example, comparing an OracleDecimal instance with an OracleBinary instance is not allowed. When an OracleDecimal is compared with a different type, an ArgumentException is thrown.
- Any OracleDecimal that has a value compares greater than an OracleDecimal that has a null value.
- Two OracleDecimals that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

Equals

Overrides Object

This method determines whether or not an object is an instance of OracleDecimal, and whether or not the value of the object is equal to the current instance.

Declaration

```
// C#
public override bool Equals(object obj);
```

Parameters

- *obj*
An OracleDecimal instance.

Return Value

Returns true if *obj* is an instance of OracleDecimal, and the value of *obj* is equal to the current instance; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleDecimal that has a value compares greater than an OracleDecimal that has a null value.
- Two OracleDecimals that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

GetHashCode

Overrides `Object`

This method returns a hash code for the current instance.

Declaration

```
// C#  
public override int GetHashCode();
```

Return Value

Returns a hash code.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

ToByte

This method returns the byte representation of the current instance.

Declaration

```
// C#  
public byte ToByte();
```

Return Value

A byte.

Exceptions

`OverflowException` - The byte cannot represent the current instance.

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

ToDouble

This method returns the double representation of the current instance.

Declaration

```
// C#  
public double ToDouble();
```

Return Value

A double.

Exceptions

OverflowException - The double cannot represent the current instance.

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

ToInt16

This method returns the Int16 representation of the current instance.

Declaration

```
// C#  
public short ToInt16();
```

Return Value

A short.

Exceptions

OverflowException - The short cannot represent the current instance.

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

ToInt32

This method returns the Int32 representation of the current instance.

Declaration

```
// C#  
public int ToInt32();
```

Return Value

An int.

Exceptions

OverflowException - The int cannot represent the current instance.

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

ToInt64

This method returns the Int64 representation of the current instance.

Declaration

```
// C#  
public long ToInt64();
```

Return Value

A long.

Exceptions

OverflowException - The long cannot represent the current instance.

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

ToSingle

This method returns the Single representation of the current instance.

Declaration

```
// C#  
public float ToSingle();
```

Return Value

A float.

Exceptions

OverflowException - The float cannot represent the current instance.

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)

ToString

Overrides `Object`

This method returns the string representation of the current instance.

Declaration

```
// C#  
public override string ToString();
```

Return Value

Returns the number in a string returns and a period (.) as a numeric separator.

Remarks

If the current instance has a null value, the returned string is "null".

The returned value is a string representation of an `OracleDecimal` in the numeric format specified by the `Format` property.

The decimal and group separator characters are specified by the thread's `OracleGlobalization.NumericCharacters`.

The currency symbols are specified by the following thread properties:

- `OracleGlobalization.Currency`
- `OracleGlobalization.ISOCurrency`
- `OracleGlobalization.DualCurrency`

If the numeric format is not specified, an Oracle default value is used.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleDecimal Members](#)
- [OracleDecimal Structure](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125

OracleIntervalDS Structure

The `OracleIntervalDS` structure represents the Oracle `INTERVAL DAY TO SECOND` data type to be stored in or retrieved from a database. Each `OracleIntervalDS` stores a period of time in term of days, hours, minutes, seconds, and fractional seconds.

Class Inheritance

`System.Object`

`System.ValueType`

`Oracle.DataAccess.Types.OracleIntervalDS`

Declaration

```
// C#
public struct OracleIntervalDS : IComparable, INullable, IXmlSerializable
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|-----------------------|--------------------------------------|---------------------------------------------|
| Assembly | <code>Oracle.DataAccess.dll</code> | <code>Oracle.ManagedDataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Types</code> | <code>Oracle.ManagedDataAccess.Types</code> |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#

using System;
using Oracle.DataAccess.Types;

class OracleIntervalDSSample
{
    static void Main()
    {
        OracleIntervalDS iDSMax = OracleIntervalDS.MaxValue;
        double totalDays = iDSMax.TotalDays;

        totalDays -= 1;
        OracleIntervalDS iDSMax_1 = new OracleIntervalDS(totalDays);

        // Calculate the difference
        OracleIntervalDS iDSDiff = iDSMax - iDSMax_1;

        // Prints "iDSDiff.ToString() = +000000000 23:59:59.999999999"
        Console.WriteLine("iDSDiff.ToString() = " + iDSDiff.ToString());
    }
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleIntervalDS Members](#)
- [OracleIntervalDS Constructors](#)
- [OracleIntervalDS Static Fields](#)
- [OracleIntervalDS Static Methods](#)
- [OracleIntervalDS Static Operators](#)
- [OracleIntervalDS Type Conversions](#)
- [OracleIntervalDS Properties](#)
- [OracleIntervalDS Methods](#)

OracleIntervalDS Members

OracleIntervalDS members are listed in the following tables:

OracleIntervalDS Constructors

OracleIntervalDS constructors are listed in [Table 14–61](#)

Table 14–61 OracleIntervalDS Constructors

| Constructor | Description |
|-----------------------------------------------|------------------------------------------------------------------------|
| OracleIntervalDS Constructors | Instantiates a new instance of OracleIntervalDS structure (Overloaded) |

OracleIntervalDS Static Fields

The OracleIntervalDS static fields are listed in [Table 14–62](#).

Table 14–62 OracleIntervalDS Static Fields

| Field | Description |
|--------------------------|------------------------------------------------------------------------------|
| MaxValue | Represents the maximum valid time interval for an OracleIntervalDS structure |
| MinValue | Represents the minimum valid time interval for an OracleIntervalDS structure |
| Null | Represents a null value that can be assigned to an OracleIntervalDS instance |
| Zero | Represents a zero value for an OracleIntervalDS structure |

OracleIntervalDS Static Methods

The OracleIntervalDS static methods are listed in [Table 14–63](#).

Table 14–63 OracleIntervalDS Static Methods

| Methods | Description |
|------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Equals | Determines whether or not two OracleIntervalDS values are equal (Overloaded) |
| GreaterThan | Determines whether or not one OracleIntervalDS value is greater than another |
| GreaterThanOrEqual | Determines whether or not one OracleIntervalDS value is greater than or equal to another |
| LessThan | Determines whether or not one OracleIntervalDS value is less than another |
| LessThanOrEqual | Determines whether or not one OracleIntervalDS value is less than or equal to another |
| NotEquals | Determines whether or not two OracleIntervalDS values are not equal |
| Parse | Returns an OracleIntervalDS structure and sets its value for time interval using a string |
| SetPrecision | Returns a new instance of an OracleIntervalDS with the specified day precision and fractional second precision |

OracleIntervalDS Static Operators

The OracleIntervalDS static operators are listed in [Table 14–64](#).

Table 14–64 OracleIntervalDS Static Operators

| Operator | Description |
|--------------------------------|------------------------------------------------------------------------------------------|
| operator + | Adds two OracleIntervalDS values |
| operator == | Determines whether or not two OracleIntervalDS values are equal |
| operator > | Determines whether or not one OracleIntervalDS value is greater than another |
| operator >= | Determines whether or not one OracleIntervalDS value is greater than or equal to another |
| operator != | Determines whether or not two OracleIntervalDS values are not equal |
| operator < | Determines whether or not one OracleIntervalDS value is less than another |
| operator <= | Determines whether or not one OracleIntervalDS value is less than or equal to another |
| operator - | Subtracts one OracleIntervalDS value from another |
| operator - | Negates an OracleIntervalDS structure |
| operator * | Multiplies an OracleIntervalDS value by a number |
| operator / | Divides an OracleIntervalDS value by a number |

OracleIntervalDS Type Conversions

The OracleIntervalDS type conversions are listed in [Table 14–65](#).

Table 14–65 OracleIntervalDS Type Conversions

| Operator | Description |
|----------------------------------------------------|----------------------------------------------------------------|
| explicit operator TimeSpan | Converts an OracleIntervalDS structure to a TimeSpan structure |
| explicit operator OracleIntervalDS | Converts a string to an OracleIntervalDS structure |
| implicit operator OracleIntervalDS | Converts a TimeSpan structure to an OracleIntervalDS structure |

OracleIntervalDS Properties

The OracleIntervalDS properties are listed in [Table 14–66](#).

Table 14–66 OracleIntervalDS Properties

| Properties | Description |
|-------------------------|-------------------------------------------------------------------------------------------------------|
| BinData | Returns an array of bytes that represents the Oracle INTERVAL DAY TO SECOND in Oracle internal format |
| Days | Gets the days component of an OracleIntervalDS |
| Hours | Gets the hours component of an OracleIntervalDS |

Table 14–66 (Cont.) OracleIntervalDS Properties

| Properties | Description |
|------------------------------|-----------------------------------------------------------------------------------------------------|
| IsNull | Indicates whether or not the current instance has a null value |
| Milliseconds | Gets the milliseconds component of an OracleIntervalDS |
| Minutes | Gets the minutes component of an OracleIntervalDS |
| Nanoseconds | Gets the nanoseconds component of an OracleIntervalDS |
| Seconds | Gets the seconds component of an OracleIntervalDS |
| TotalDays | Returns the total number, in days, that represent the time period in the OracleIntervalDS structure |
| Value | Specifies the time interval that is stored in the OracleIntervalDS structure |

OracleIntervalDS Methods

The OracleIntervalDS methods are listed in [Table 14–67](#).

Table 14–67 OracleIntervalDS Methods

| Methods | Description |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------|
| CompareTo | Compares the current OracleIntervalDS instance to an object, and returns an integer that represents their relative values |
| Equals | Determines whether or not the specified object has the same time interval as the current instance (Overloaded) |
| GetHashCode | Returns a hash code for the OracleIntervalDS instance |
| GetType | Inherited from System.Object |
| ToString | Converts the current OracleIntervalDS structure to a string |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)

OracleIntervalDS Constructors

OracleIntervalDS constructors create a new instance of the OracleIntervalDS structure.

Overload List:

- [OracleIntervalDS\(TimeSpan\)](#)
This constructor creates a new instance of the OracleIntervalDS structure and sets its value using a TimeSpan structure.
- [OracleIntervalDS\(string\)](#)
This constructor creates a new instance of the OracleIntervalDS structure and sets its value using a string that indicates a period of time.
- [OracleIntervalDS\(double\)](#)
This constructor creates a new instance of the OracleIntervalDS structure and sets its value using the total number of days.
- [OracleIntervalDS\(int, int, int, int, double\)](#)
This constructor creates a new instance of the OracleIntervalDS structure and sets its value using the supplied days, hours, minutes, seconds and milliseconds.
- [OracleIntervalDS\(int, int, int, int, int\)](#)
This constructor creates a new instance of the OracleIntervalDS structure and sets its value using the supplied days, hours, minutes, seconds, and nanoseconds.
- [OracleIntervalDS\(byte\[\] \)](#)
This constructor creates a new instance of the OracleIntervalDS structure and sets its value to the provided byte array, which is in an internal Oracle INTERVAL DAY TO SECOND format.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

OracleIntervalDS(TimeSpan)

This constructor creates a new instance of the OracleIntervalDS structure and sets its value using a TimeSpan structure.

Declaration

```
// C#
public OracleIntervalDS(TimeSpan ts);
```

Parameters

- *ts*
A TimeSpan structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

OracleIntervalDS(string)

This constructor creates a new instance of the `OracleIntervalDS` structure and sets its value using a string that indicates a period of time.

Declaration

```
// C#  
public OracleIntervalDS(string intervalStr);
```

Parameters

- *intervalStr*

A string representing the Oracle INTERVAL DAY TO SECOND.

Exceptions

`ArgumentException` - The *intervalStr* parameter is not in the valid format or has an invalid value.

`ArgumentNullException` - The *intervalStr* parameter is null.

Remarks

The value specified in the supplied *intervalStr* must be in Day HH:MI:SSxFF format.

Example

"1 2:3:4.99" means 1 day, 2 hours, 3 minutes, 4 seconds, and 990 milliseconds or 1 day, 2 hours, 3 minutes, 4 seconds, and 990000000 nanoseconds.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

OracleIntervalDS(double)

This constructor creates a new instance of the `OracleIntervalDS` structure and sets its value using the total number of days.

Declaration

```
// C#  
public OracleIntervalDS(double totalDays);
```

Parameters

- *totalDays*

The supplied total number of days for a time interval. Range of days is $-1000,000,000 < totalDays < 1000,000,000$.

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleIntervalDS`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

OracleIntervalDS(int, int, int, int, double)

This constructor creates a new instance of the `OracleIntervalDS` structure and sets its value using the supplied days, hours, minutes, seconds, and milliseconds.

Declaration

```
// C#
public OracleIntervalDS (int days, int hours, int minutes, int seconds,
    double milliSeconds);
```

Parameters

- *days*
The days provided. Range of day is (-999,999,999 to 999,999,999).
- *hours*
The hours provided. Range of hour is (-23 to 23).
- *minutes*
The minutes provided. Range of minute is (-59 to 59).
- *seconds*
The seconds provided. Range of second is (-59 to 59).
- *milliSeconds*
The milliseconds provided. Range of millisecond is (- 999.999999 to 999.999999).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleIntervalDS`.

Remarks

The sign of all the arguments must be the same.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

OracleIntervalDS(int, int, int, int, int)

This constructor creates a new instance of the `OracleIntervalDS` structure and sets its value using the supplied days, hours, minutes, seconds, and nanoseconds.

Declaration

```
// C#
public OracleIntervalDS (int days, int hours, int minutes, int seconds,
    int nanoseconds);
```

Parameters

- *days*
The days provided. Range of day is (-999,999,999 to 999,999,999).
- *hours*
The hours provided. Range of hour is (-23 to 23).
- *minutes*
The minutes provided. Range of minute is (-59 to 59).
- *seconds*
The seconds provided. Range of second is (-59 to 59).
- *nanoseconds*
The nanoseconds provided. Range of nanosecond is (-999,999,999 to 999,999,999)

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleIntervalDS`.

Remarks

The sign of all the arguments must be the same.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

OracleIntervalDS(byte[])

This constructor creates a new instance of the `OracleIntervalDS` structure and sets its value to the provided byte array, which is in an internal Oracle `INTERVAL DAY TO SECOND` format.

Declaration

```
// C#  
public OracleIntervalDS (byte[ ] bytes);
```

Parameters

- *bytes*

A byte array that is in an internal Oracle `INTERVAL DAY TO SECOND` format.

Exceptions

`ArgumentException` - *bytes* is not in internal Oracle `INTERVAL DAY TO SECOND` format, or *bytes* is not a valid Oracle `INTERVAL DAY TO SECOND`.

`ArgumentNullException` - *bytes* is null.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

OracleIntervalDS Static Fields

The OracleIntervalDS static fields are listed in [Table 14–68](#).

Table 14–68 OracleIntervalDS Static Fields

| Field | Description |
|--------------------------|------------------------------------------------------------------------------|
| MaxValue | Represents the maximum valid time interval for an OracleIntervalDS structure |
| MinValue | Represents the minimum valid time interval for an OracleIntervalDS structure |
| Null | Represents a null value that can be assigned to an OracleIntervalDS instance |
| Zero | Represents a zero value for an OracleIntervalDS structure |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

MaxValue

This static field represents the maximum value for an OracleIntervalDS structure.

Declaration

```
// C#
public static readonly OracleIntervalDS MaxValue;
```

Remarks

Maximum values:

- Day: 999999999
- hour: 23
- minute is 59
- second: 59
- nanosecond: 999999999

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

MinValue

This static field represents the minimum value for an OracleIntervalDS structure.

Declaration

```
// C#  
public static readonly OracleIntervalDS MinValue;
```

Remarks

Minimum values:

- Day: -999999999
- hour: -23
- minute: -59
- second: -59
- nanosecond: -999999999

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

Null

This static field represents a null value that can be assigned to an `OracleIntervalDS` instance.

Declaration

```
// C#  
public static readonly OracleIntervalDS Null;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

Zero

This static field represents a zero value for an `OracleIntervalDS` structure.

Declaration

```
// C#  
public static readonly OracleIntervalDS Zero;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

OracleIntervalDS Static Methods

The OracleIntervalDS static methods are listed in [Table 14–69](#).

Table 14–69 OracleIntervalDS Static Methods

| Methods | Description |
|------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Equals | Determines whether or not two OracleIntervalDS values are equal (Overloaded) |
| GreaterThan | Determines whether or not one OracleIntervalDS value is greater than another |
| GreaterThanOrEqual | Determines whether or not one OracleIntervalDS value is greater than or equal to another |
| LessThan | Determines whether or not one OracleIntervalDS value is less than another |
| LessThanOrEqual | Determines whether or not one OracleIntervalDS value is less than or equal to another |
| NotEquals | Determines whether or not two OracleIntervalDS values are not equal |
| Parse | Returns an OracleIntervalDS structure and sets its value for time interval using a string |
| SetPrecision | Returns a new instance of an OracleIntervalDS with the specified day precision and fractional second precision |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

Equals

This static method determines whether or not two OracleIntervalDS values are equal.

Declaration

```
// C#
public static bool Equals(OracleIntervalDS val1, OracleIntervalDS val2);
```

Parameters

- *val1*
The first OracleIntervalDS.
- *val2*
The second OracleIntervalDS.

Return Value

If the two OracleIntervalDS structures represent the same time interval, returns true; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalDS` that has a value compares greater than an `OracleIntervalDS` that has a null value.
- Two `OracleIntervalDS`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

GreaterThan

This static method determines whether or not the first of two `OracleIntervalDS` values is greater than the second.

Declaration

```
// C#
public static bool GreaterThan(OracleIntervalDS val1, OracleIntervalDS
    val2);
```

Parameters

- *val1*
The first `OracleIntervalDS`.
- *val2*
The second `OracleIntervalDS`.

Return Value

Returns `true` if the first of two `OracleIntervalDS` values is greater than the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalDS` that has a value compares greater than an `OracleIntervalDS` that has a null value.
- Two `OracleIntervalDS`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

GreaterThanOrEqual

This static method determines whether or not the first of two `OracleIntervalDS` values is greater than or equal to the second.

Declaration

```
// C#  
public static bool GreaterThanOrEqual(OracleIntervalDS val1,  
    OracleIntervalDS val2);
```

Parameters

- *val1*
The first OracleIntervalDS.
- *val2*
The second OracleIntervalDS.

Return Value

Returns true if the first of two OracleIntervalDS values is greater than or equal to the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleIntervalDS that has a value compares greater than an OracleIntervalDS that has a null value.
- Two OracleIntervalDSs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

LessThan

This static method determines whether or not the first of two OracleIntervalDS values is less than the second.

Declaration

```
// C#  
public static bool LessThan(OracleIntervalDS val1, OracleIntervalDS val2);
```

Parameters

- *val1*
The first OracleIntervalDS.
- *val2*
The second OracleIntervalDS.

Return Value

Returns true if the first of two OracleIntervalDS values is less than the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleIntervalDS that has a value compares greater than an OracleIntervalDS that has a null value.
- Two OracleIntervalDSs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

LessThanOrEqual

This static method determines whether or not the first of two OracleIntervalDS values is less than or equal to the second.

Declaration

```
// C#
public static bool LessThanOrEqual(OracleIntervalDS val1, OracleIntervalDS val2);
```

Parameters

- *val1*
The first OracleIntervalDS.
- *val2*
The second OracleIntervalDS.

Return Value

Returns true if the first of two OracleIntervalDS values is less than or equal to the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleIntervalDS that has a value compares greater than an OracleIntervalDS that has a null value.
- Two OracleIntervalDSs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

NotEquals

This static method determines whether or not two OracleIntervalDS values are not equal.

Declaration

```
// C#
public static bool NotEquals(OracleIntervalDS val1, OracleIntervalDS val2);
```

Parameters

- *val1*
The first OracleIntervalDS.
- *val2*
The second OracleIntervalDS.

Return Value

Returns true if two OracleIntervalDS values are not equal; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleIntervalDS that has a value compares greater than an OracleIntervalDS that has a null value.
- Two OracleIntervalDSs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

Parse

This static method returns an OracleIntervalDS instance and sets its value for time interval using a string.

Declaration

```
// C#  
public static OracleIntervalDS Parse(string intervalStr);
```

Parameters

- *intervalStr*
A string representing the Oracle INTERVAL DAY TO SECOND.

Return Value

Returns an OracleIntervalDS instance representing the time interval from the supplied string.

Exceptions

ArgumentException - The *intervalStr* parameter is not in the valid format or *intervalStr* has an invalid value.

ArgumentNullException - The *intervalStr* parameter is null.

Remarks

The value specified in *intervalStr* must be in Day HH:MI:SSxFF format.

Example

"1 2:3:4.99" means 1 day, 2 hours, 3 minutes, 4 seconds, and 990 milliseconds or 1 day, 2 hours, 3 minutes, 4 seconds, and 990000000 nanoseconds.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

SetPrecision

This static method returns a new instance of an `OracleIntervalDS` with the specified day precision and fractional second precision.

Declaration

```
// C#
public static OracleIntervalDS SetPrecision(OracleIntervalDS value1,
    int dayPrecision, int fracSecPrecision);
```

Parameters

- *value1*
An `OracleIntervalDS` structure.
- *dayPrecision*
The day precision provided. Range of day precision is (0 to 9).
- *fracSecPrecision*
The fractional second precision provided. Range of fractional second precision is (0 to 9).

Return Value

An `OracleIntervalDS` instance.

Exceptions

`ArgumentOutOfRangeException` - An argument value is out of the specified range.

Remarks

Depending on the value specified in the supplied *dayPrecision*, 0 or more leading zeros are displayed in the string returned by `ToString()`.

The value specified in the supplied *fracSecPrecision* is used to perform a rounding off operation on the supplied `OracleIntervalDS` value. Depending on this value, 0 or more trailing zeros are displayed in the string returned by `ToString()`.

Example

The `OracleIntervalDS` with a value of "1 2:3:4.99" results in the string "001 2:3:4.99000" when `SetPrecision()` is called, with the day precision set to 3 and fractional second precision set to 5.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

OracleIntervalDS Static Operators

The OracleIntervalDS static operators are listed in [Table 14–70](#).

Table 14–70 OracleIntervalDS Static Operators

| Operator | Description |
|--------------------------------|------------------------------------------------------------------------------------------|
| operator + | Adds two OracleIntervalDS values |
| operator == | Determines whether or not two OracleIntervalDS values are equal |
| operator > | Determines whether or not one OracleIntervalDS value is greater than another |
| operator >= | Determines whether or not one OracleIntervalDS value is greater than or equal to another |
| operator != | Determines whether or not two OracleIntervalDS values are not equal |
| operator < | Determines whether or not one OracleIntervalDS value is less than another |
| operator <= | Determines whether or not one OracleIntervalDS value is less than or equal to another |
| operator - | Subtracts one OracleIntervalDS value from another |
| operator - | Negates an OracleIntervalDS structure |
| operator * | Multiplies an OracleIntervalDS value by a number |
| operator / | Divides an OracleIntervalDS value by a number |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

operator +

This static operator adds two OracleIntervalDS values.

Declaration

```
// C#
public static OracleIntervalDS operator + (OracleIntervalDS val1,
    OracleIntervalDS val2);
```

Parameters

- *val1*
The first OracleIntervalDS.
- *val2*
The second OracleIntervalDS.

Return Value

An OracleIntervalDS.

Remarks

If either argument has a null value, the returned `OracleIntervalDS` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

operator ==

This static operator determines if two `OracleIntervalDS` values are equal.

Declaration

```
// C#  
public static bool operator == (OracleIntervalDS val1,  
    OracleIntervalDS val2);
```

Parameters

- *val1*
The first `OracleIntervalDS`.
- *val2*
The second `OracleIntervalDS`.

Return Value

Returns true if the two `OracleIntervalDS` values are the same; otherwise returns false.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalDS` that has a value compares greater than an `OracleIntervalDS` that has a null value.
- Two `OracleIntervalDS`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

operator >

This static operator determines if the first of two `OracleIntervalDS` values is greater than the second.

Declaration

```
// C#  
public static bool operator > (OracleIntervalDS val1,  
    OracleIntervalDS val2);
```

Parameters

- *val1*
The first OracleIntervalDS.
- *val2*
The second OracleIntervalDS.

Return Value

Returns true if one OracleIntervalDS value is greater than another; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleIntervalDS that has a value compares greater than an OracleIntervalDS that has a null value.
- Two OracleIntervalDSs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

operator >=

This static operator determines if the first of two OracleIntervalDS values is greater than or equal to the second.

Declaration

```
// C#
public static bool operator >= (OracleIntervalDS val1,
    OracleIntervalDS val2);
```

Parameters

- *val1*
The first OracleIntervalDS.
- *val2*
The second OracleIntervalDS.

Return Value

Returns true if the first of two OracleIntervalDS values is greater than or equal to the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleIntervalDS that has a value compares greater than an OracleIntervalDS that has a null value.
- Two OracleIntervalDSs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

operator !=

This static operator determines if the two `OracleIntervalDS` values are not equal.

Declaration

```
// C#
public static bool operator != (OracleIntervalDS val1,
    OracleIntervalDS val2);
```

Parameters

- *val1*
The first `OracleIntervalDS`.
- *val2*
The second `OracleIntervalDS`.

Return Value

Returns true if the two `OracleIntervalDS` values are not equal; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalDS` that has a value compares greater than an `OracleIntervalDS` that has a null value.
- Two `OracleIntervalDS`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

operator <

This static operator determines if the first of two `OracleIntervalDS` values is less than the second.

Declaration

```
// C#
public static bool operator < (OracleIntervalDS val1,
    OracleIntervalDS val2);
```

Parameters

- *val1*

The first OracleIntervalDS.

- *val2*

The second OracleIntervalDS.

Return Value

Returns true if the first of two OracleIntervalDS values is less than the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleIntervalDS that has a value compares greater than an OracleIntervalDS that has a null value.
- Two OracleIntervalDSs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

operator <=

This static operator determines if the first of two OracleIntervalDS values is less than or equal to the second.

Declaration

```
// C#
public static bool operator <= (OracleIntervalDS val1,
    OracleIntervalDS val2);
```

Parameters

- *val1*
The first OracleIntervalDS.
- *val2*
The second OracleIntervalDS.

Return Value

Returns true if the first of two OracleIntervalDS values is less than or equal to the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleIntervalDS that has a value compares greater than an OracleIntervalDS that has a null value.
- Two OracleIntervalDSs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

operator -

This static operator subtracts one OracleIntervalDS structure from another.

Declaration

```
// C#  
public static OracleIntervalDS operator - (OracleIntervalDS val1,  
    OracleIntervalDS val2);
```

Parameters

- *val1*
The first OracleIntervalDS.
- *val2*
The second OracleIntervalDS.

Return Value

An OracleIntervalDS structure.

Remarks

If either argument has a null value, the returned OracleIntervalDS structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

operator -

This static operator negates the supplied OracleIntervalDS structure.

Declaration

```
// C#  
public static OracleIntervalDS operator - (OracleIntervalDS val);
```

Parameters

- *val*
An OracleIntervalDS.

Return Value

An OracleIntervalDS structure.

Remarks

If the supplied `OracleIntervalDS` structure has a null value, the returned `OracleIntervalDS` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

operator *

This static operator multiplies an `OracleIntervalDS` value by a number.

Declaration

```
// C#
public static OracleIntervalDS operator * (OracleIntervalDS val1,
    int multiplier);
```

Parameters

- *val1*
The first `OracleIntervalDS`.
- *multiplier*
A multiplier.

Return Value

A new `OracleIntervalDS` instance.

Remarks

If the `OracleIntervalDS` structure has a null value, the returned `OracleIntervalDS` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

operator /

This static operator divides an `OracleIntervalDS` value by a number.

Declaration

```
// C#
public static OracleIntervalDS operator / (OracleIntervalDS val1,
    int divisor);
```

Parameters

- *val1*
The first `OracleIntervalDS`.

- *divisor*
A divisor.

Return Value

An `OracleIntervalDS` structure.

Remarks

If the `OracleIntervalDS` structure has a null value, the returned `OracleIntervalDS` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

OracleIntervalDS Type Conversions

The OracleIntervalDS type conversions are listed in [Table 14–71](#).

Table 14–71 OracleIntervalDS Type Conversions

| Operator | Description |
|----------------------------------------------------|----------------------------------------------------------------|
| explicit operator TimeSpan | Converts an OracleIntervalDS structure to a TimeSpan structure |
| explicit operator OracleIntervalDS | Converts a string to an OracleIntervalDS structure |
| implicit operator OracleIntervalDS | Converts a TimeSpan structure to an OracleIntervalDS structure |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

explicit operator TimeSpan

This type conversion operator converts an OracleIntervalDS structure to a TimeSpan structure.

Declaration

```
// C#
public static explicit operator TimeSpan(OracleIntervalDS val);
```

Parameters

- *val*
An OracleIntervalDS instance.

Return Value

A TimeSpan structure.

Exceptions

OracleNullValueException - The OracleIntervalDS structure has a null value.

Remarks

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

explicit operator OracleIntervalDS

This type conversion operator converts a string to an OracleIntervalDS structure.

Declaration

```
// C#  
public static explicit operator OracleIntervalDS (string intervalStr);
```

Parameters

- *intervalStr*

A string representation of an Oracle INTERVAL DAY TO SECOND.

Return Value

An OracleIntervalDS structure.

Exceptions

ArgumentException - The supplied *intervalStr* parameter is not in the correct format or has an invalid value.

ArgumentNullException - The *intervalStr* parameter is null.

Remarks

The returned OracleIntervalDS structure contains the same time interval represented by the supplied *intervalStr*. The value specified in the supplied *intervalStr* must be in Day HH:MI:SSxFF format.

Example

"1 2:3:4.99" means 1 day, 2 hours, 3 minutes 4 seconds and 990 milliseconds or 1 day, 2 hours, 3 minutes 4 seconds and 990000000 nanoseconds.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

implicit operator OracleIntervalDS

This type conversion operator converts a TimeSpan structure to an OracleIntervalDS structure.

Declaration

```
// C#  
public static implicit operator OracleIntervalDS(TimeSpan val);
```

Parameters

- *val*

A TimeSpan instance.

Return Value

An OracleIntervalDS structure.

Remarks

The returned OracleIntervalDS structure contains the same days, hours, seconds, and milliseconds as the supplied TimeSpan val.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

OracleIntervalDS Properties

The OracleIntervalDS properties are listed in [Table 14–72](#).

Table 14–72 OracleIntervalDS Properties

| Properties | Description |
|------------------------------|-------------------------------------------------------------------------------------------------------|
| BinData | Returns an array of bytes that represents the Oracle INTERVAL DAY TO SECOND in Oracle internal format |
| Days | Gets the days component of an OracleIntervalDS |
| Hours | Gets the hours component of an OracleIntervalDS |
| IsNull | Indicates whether or not the current instance has a null value |
| Milliseconds | Gets the milliseconds component of an OracleIntervalDS |
| Minutes | Gets the minutes component of an OracleIntervalDS |
| Nanoseconds | Gets the nanoseconds component of an OracleIntervalDS |
| Seconds | Gets the seconds component of an OracleIntervalDS |
| TotalDays | Returns the total number, in days, that represent the time period in the OracleIntervalDS structure |
| Value | Specifies the time interval that is stored in the OracleIntervalDS structure |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

BinData

This property returns an array of bytes that represents the Oracle INTERVAL DAY TO SECOND in Oracle internal format.

Declaration

```
// C#
public byte[] BinData {get;}
```

Property Value

A byte array that represents an Oracle INTERVAL DAY TO SECOND in Oracle internal format.

Exceptions

OracleNullValueException - The current instance has a null value.

Remarks

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

Days

This property gets the days component of an `OracleIntervalDS`.

Declaration

```
// C#  
public int Days {get;}
```

Property Value

An `int` representing the days component.

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

Hours

This property gets the hours component of an `OracleIntervalDS`.

Declaration

```
// C#  
public int Hours {get;}
```

Property Value

An `int` representing the hours component.

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

IsNull

This property indicates whether or not the current instance has a null value.

Declaration

```
// C#  
public bool IsNull {get;}
```

Property Value

Returns `true` if the current instance has a null value; otherwise, returns `false`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

Milliseconds

This property gets the milliseconds component of an `OracleIntervalDS`.

Declaration

```
// C#  
public double Milliseconds {get;}
```

Property Value

A `double` that represents milliseconds component.

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

Minutes

This property gets the minutes component of an `OracleIntervalDS`.

Declaration

```
// C#  
public int Minutes {get;}
```

Property Value

A `int` that represents minutes component.

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

Nanoseconds

This property gets the nanoseconds component of an `OracleIntervalDS`.

Declaration

```
// C#  
public int Nanoseconds {get;}
```

Property Value

An `int` that represents nanoseconds component.

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

Seconds

This property gets the seconds component of an `OracleIntervalDS`.

Declaration

```
// C#  
public int Seconds {get;}
```

Property Value

An `int` that represents seconds component.

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

TotalDays

This property returns the total number, in days, that represent the time period in the `OracleIntervalDS` structure.

Declaration

```
// C#  
public double TotalDays {get;}
```

Property Value

A double that represents the total number of days.

Exceptions

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

Value

This property specifies the time interval that is stored in the OracleIntervalDS structure.

Declaration

```
// C#  
public TimeSpan Value {get;}
```

Property Value

A time interval.

Exceptions

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

OracleIntervalDS Methods

The OracleIntervalDS methods are listed in [Table 14–73](#).

Table 14–73 OracleIntervalDS Methods

| Methods | Description |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------|
| CompareTo | Compares the current OracleIntervalDS instance to an object, and returns an integer that represents their relative values |
| Equals | Determines whether or not the specified object has the same time interval as the current instance (Overloaded) |
| GetHashCode | Returns a hash code for the OracleIntervalDS instance |
| GetType | Inherited from System.Object |
| ToString | Converts the current OracleIntervalDS structure to a string |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

CompareTo

This method compares the current OracleIntervalDS instance to an object, and returns an integer that represents their relative values.

Declaration

```
// C#
public int CompareTo(object obj);
```

Parameters

- *obj*
The object being compared to.

Return Value

The method returns:

- Less than zero: if the current OracleIntervalDS represents a shorter time interval than *obj*.
- Zero: if the current OracleIntervalDS and *obj* represent the same time interval.
- Greater than zero: if the current OracleIntervalDS represents a longer time interval than *obj*.

Implements

IComparable

Exceptions

ArgumentException - The *obj* parameter is not of type OracleIntervalDS.

Remarks

The following rules apply to the behavior of this method.

- The comparison must be between `OracleIntervalDS`s. For example, comparing an `OracleIntervalDS` instance with an `OracleBinary` instance is not allowed. When an `OracleIntervalDS` is compared with a different type, an `ArgumentException` is thrown.
- Any `OracleIntervalDS` that has a value compares greater than an `OracleIntervalDS` that has a null value.
- Two `OracleIntervalDS`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

Equals

This method determines whether or not the specified object has the same time interval as the current instance.

Declaration

```
// C#  
public override bool Equals(object obj);
```

Parameters

- *obj*
The specified object.

Return Value

Returns true if *obj* is of type `OracleIntervalDS` and has the same time interval as the current instance; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalDS` that has a value compares greater than an `OracleIntervalDS` that has a null value.
- Two `OracleIntervalDS`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

GetHashCode

Overrides `Object`

This method returns a hash code for the `OracleIntervalDS` instance.

Declaration

```
// C#  
public override int GetHashCode();
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

ToString

Overrides Object

This method converts the current OracleIntervalDS structure to a string.

Declaration

```
// C#  
public override string ToString();
```

Return Value

Returns a string.

Remarks

If the current instance has a null value, the returned string contains "null".

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalDS Structure](#)
- [OracleIntervalDS Members](#)

OracleIntervalYM Structure

The `OracleIntervalYM` structure represents the Oracle `INTERVAL YEAR TO MONTH` data type to be stored in or retrieved from a database. Each `OracleIntervalYM` stores a period of time in years and months.

Class Inheritance

`System.Object`

`System.ValueType`

`Oracle.DataAccess.Types.OracleIntervalYM`

Declaration

```
// C#
public struct OracleIntervalYM : IComparable
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|-----------------------|--------------------------------------|---------------------------------------------|
| Assembly | <code>Oracle.DataAccess.dll</code> | <code>Oracle.ManagedDataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Types</code> | <code>Oracle.ManagedDataAccess.Types</code> |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#

using System;
using Oracle.DataAccess.Types;

class OracleIntervalYMSample
{
    static void Main()
    {
        OracleIntervalYM iYMMax = OracleIntervalYM.MaxValue;
        double totalYears = iYMMax.TotalYears;

        totalYears -= 1;
        OracleIntervalYM iYMMax_1 = new OracleIntervalYM(totalYears);

        // Calculate the difference
        OracleIntervalYM iYMDiff = iYMMax - iYMMax_1;

        // Prints "iYMDiff.ToString() = +000000001-00"
        Console.WriteLine("iYMDiff.ToString() = " + iYMDiff.ToString());
    }
}
```


See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleIntervalYM Members](#)
- [OracleIntervalYM Constructors](#)
- [OracleIntervalYM Static Fields](#)
- [OracleIntervalYM Static Methods](#)
- [OracleIntervalYM Static Operators](#)
- [OracleIntervalYM Type Conversions](#)
- [OracleIntervalYM Properties](#)
- [OracleIntervalYM Methods](#)

OracleIntervalYM Members

OracleIntervalYM members are listed in the following tables:

OracleIntervalYM Constructors

OracleIntervalYM constructors are listed in [Table 14-74](#)

Table 14-74 OracleIntervalYM Constructors

| Constructor | Description |
|-----------------------------------------------|------------------------------------------------------------------------|
| OracleIntervalYM Constructors | Instantiates a new instance of OracleIntervalYM structure (Overloaded) |

OracleIntervalYM Static Fields

The OracleIntervalYM static fields are listed in [Table 14-75](#).

Table 14-75 OracleIntervalYM Static Fields

| Field | Description |
|--------------------------|------------------------------------------------------------------------------|
| MaxValue | Represents the maximum value for an OracleIntervalYM structure |
| MinValue | Represents the minimum value for an OracleIntervalYM structure |
| Null | Represents a null value that can be assigned to an OracleIntervalYM instance |
| Zero | Represents a zero value for an OracleIntervalYM structure |

OracleIntervalYM Static Methods

The OracleIntervalYM static methods are listed in [Table 14-76](#).

Table 14-76 OracleIntervalYM Static Methods

| Methods | Description |
|------------------------------------|-------------------------------------------------------------------------------------------|
| Equals | Determines whether or not two OracleIntervalYM values are equal (Overloaded) |
| GreaterThan | Determines whether or not one OracleIntervalYM value is greater than another |
| GreaterThanOrEqual | Determines whether or not one OracleIntervalYM value is greater than or equal to another |
| LessThan | Determines whether or not one OracleIntervalYM value is less than another |
| LessThanOrEqual | Determines whether or not one OracleIntervalYM value is less than or equal to another |
| NotEquals | Determines whether two OracleIntervalYM values are not equal |
| Parse | Returns an OracleIntervalYM structure and sets its value for time interval using a string |
| SetPrecision | Returns a new instance of an OracleIntervalYM with the specified year precision. |

OracleIntervalYM Static Operators

The OracleIntervalYM static operators are listed in [Table 14-77](#).

Table 14-77 OracleIntervalYM Static Operators

| Operator | Description |
|--------------------------------|------------------------------------------------------------------------------------------|
| operator + | Adds two OracleIntervalYM values |
| operator == | Determines whether or not two OracleIntervalYM values are equal |
| operator > | Determines whether or not one OracleIntervalYM value is greater than another |
| operator >= | Determines whether or not one OracleIntervalYM value is greater than or equal to another |
| operator != | Determines whether two OracleIntervalYM values are not equal |
| operator < | Determines whether or not one OracleIntervalYM value is less than another |
| operator <= | Determines whether or not one OracleIntervalYM value is less than or equal to another |
| operator - | Subtracts one OracleIntervalYM value from another |
| operator - | Negates an OracleIntervalYM structure |
| operator * | Multiplies an OracleIntervalYM value by a number |
| operator / | Divides an OracleIntervalYM value by a number |

OracleIntervalYM Type Conversions

The OracleIntervalYM conversions are listed in [Table 14-78](#).

Table 14-78 OracleIntervalYM Type Conversions

| Operator | Description |
|----------------------------------------------------|----------------------------------------------------------------|
| explicit operator long | Converts an OracleIntervalYM structure to a number |
| explicit operator OracleIntervalYM | Converts a string to an OracleIntervalYM structure |
| implicit operator OracleIntervalYM | Converts the number of months to an OracleIntervalYM structure |

OracleIntervalYM Properties

The OracleIntervalYM properties are listed in [Table 14-79](#).

Table 14-79 OracleIntervalYM Properties

| Properties | Description |
|-------------------------|----------------------------------------------------------------------------------------------------------|
| BinData | Returns an array of bytes that represents the Oracle INTERVAL YEAR TO MONTH in an Oracle internal format |
| IsNull | Indicates whether or not the current instance has a null value |

Table 14–79 (Cont.) OracleIntervalYM Properties

| Properties | Description |
|----------------------------|------------------------------------------------------------------------------------------------------------------|
| Months | Gets the months component of an OracleIntervalYM |
| TotalYears | Returns the total number, in years, that represents the period of time in the current OracleIntervalYM structure |
| Value | Specifies the total number of months that is stored in the OracleIntervalYM structure |
| Years | Gets the years component of an OracleIntervalYM |

OracleIntervalYM Methods

The OracleIntervalYM methods are listed in [Table 14–80](#).

Table 14–80 OracleIntervalYM Methods

| Methods | Description |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| CompareTo | Compares the current OracleIntervalYM instance to the supplied object, and returns an integer that represents their relative values |
| Equals | Determines whether or not the specified object has the same time interval as the current instance (Overloaded) |
| GetHashCode | Returns a hash code for the OracleIntervalYM instance |
| GetType | Inherited from System.Object |
| ToString | Converts the current OracleIntervalYM structure to a string |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)

OracleIntervalYM Constructors

The `OracleIntervalYM` constructors creates a new instance of the `OracleIntervalYM` structure.

Overload List:

- [OracleIntervalYM\(long\)](#)
This method creates a new instance of the `OracleIntervalYM` structure using the supplied total number of months for a period of time.
- [OracleIntervalYM\(string\)](#)
This method creates a new instance of the `OracleIntervalYM` structure and sets its value using the supplied string.
- [OracleIntervalYM\(double\)](#)
This method creates a new instance of the `OracleIntervalYM` structure and sets its value using the total number of years.
- [OracleIntervalYM\(int, int\)](#)
This method creates a new instance of the `OracleIntervalYM` structure and sets its value using years and months.
- [OracleIntervalYM\(byte\[\]\)](#)
This method creates a new instance of the `OracleIntervalYM` structure and sets its value to the provided byte array, which is in an internal Oracle `INTERVAL DAY TO SECOND` format.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

OracleIntervalYM(long)

This method creates a new instance of the `OracleIntervalYM` structure using the supplied total number of months for a period of time.

Declaration

```
// C#
public OracleIntervalYM (long totalMonths);
```

Parameters

- *totalMonths*
The number of total months for a time interval. Range is $-12,000,000,000 < totalMonths < 12,000,000,000$.

Exceptions

`ArgumentOutOfRangeException` - The *totalMonths* parameter is out of the specified range.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

OracleIntervalYM(string)

This method creates a new instance of the `OracleIntervalYM` structure and sets its value using the supplied string.

Declaration

```
// C#
public OracleIntervalYM (string intervalStr);
```

Parameters

- *intervalStr*

A string representing the Oracle INTERVAL YEAR TO MONTH.

Remarks

The value specified in the supplied *intervalStr* must be in Year-Month format.

Exceptions

`ArgumentException` - The *intervalStr* parameter is not in the valid format or *intervalStr* has an invalid value.

`ArgumentNullException` - The *intervalStr* parameter is null.

Example

"1-2" means 1 year and 2 months.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

OracleIntervalYM(double)

This method creates a new instance of the `OracleIntervalYM` structure and sets its value using the total number of years.

Declaration

```
// C#
public OracleIntervalYM (double totalYears);
```

Parameters

- *totalYears*

Number of total years. Range is $-1,000,000,000 < totalYears > 1,000,000,000$.

Exceptions

`ArgumentOutOfRangeException` - The *totalYears* parameter is out of the specified range.

`ArgumentException` - The *totalYears* parameter cannot be used to construct a valid `OracleIntervalYM`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

OracleIntervalYM(int, int)

This method creates a new instance of the `OracleIntervalYM` structure and sets its value using years and months.

Declaration

```
// C#
public OracleIntervalYM (int years, int months);
```

Parameters

- *years*
Number of years. Range of year is (-999,999,999 to 999,999,999).
- *months*
Number of months. Range of month is (-11 to 11).

Remarks

The sign of all the arguments must be the same.

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleIntervalYM`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

OracleIntervalYM(byte[])

This method creates a new instance of the `OracleIntervalYM` structure and sets its value to the provided byte array, which is in an internal Oracle `INTERVAL DAY TO SECOND` format.

Declaration

```
// C#  
public OracleIntervalYM (byte[] bytes);
```

Parameters

- *bytes*

A byte array that is in an internal Oracle INTERVAL YEAR TO MONTH format.

Exceptions

`ArgumentException` - The supplied byte array is not in an internal Oracle INTERVAL YEAR TO MONTH format or the supplied byte array has an invalid value.

`ArgumentNullException` - *bytes* is null.

Remarks

The supplied byte array must be in an internal Oracle INTERVAL YEAR TO MONTH format.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

OracleIntervalYM Static Fields

The OracleIntervalYM static fields are listed in [Table 14–81](#).

Table 14–81 OracleIntervalYM Static Fields

| Field | Description |
|--------------------------|------------------------------------------------------------------------------|
| MaxValue | Represents the maximum value for an OracleIntervalYM structure |
| MinValue | Represents the minimum value for an OracleIntervalYM structure |
| Null | Represents a null value that can be assigned to an OracleIntervalYM instance |
| Zero | Represents a zero value for an OracleIntervalYM structure |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

MaxValue

This static field represents the maximum value for an OracleIntervalYM structure.

Declaration

```
// C#
public static readonly OracleIntervalYM MaxValue;
```

Remarks

Year is 999999999 and Month is 11.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

MinValue

This static field represents the minimum value for an OracleIntervalYM structure.

Declaration

```
// C#
public static readonly OracleIntervalYM MinValue;
```

Remarks

Year is -999999999 and Month is -11.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

Null

This static field represents a null value that can be assigned to an `OracleIntervalYM` instance.

Declaration

```
// C#  
public static readonly OracleIntervalYM Null;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

Zero

This static field represents a zero value for an `OracleIntervalYM` structure.

Declaration

```
// C#  
public static readonly OracleIntervalDS Zero;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

OracleIntervalYM Static Methods

The OracleIntervalYM static methods are listed in [Table 14–82](#).

Table 14–82 OracleIntervalYM Static Methods

| Methods | Description |
|------------------------------------|-------------------------------------------------------------------------------------------|
| Equals | Determines whether or not two OracleIntervalYM values are equal (Overloaded) |
| GreaterThan | Determines whether or not one OracleIntervalYM value is greater than another |
| GreaterThanOrEqual | Determines whether or not one OracleIntervalYM value is greater than or equal to another |
| LessThan | Determines whether or not one OracleIntervalYM value is less than another |
| LessThanOrEqual | Determines whether or not one OracleIntervalYM value is less than or equal to another |
| NotEquals | Determines whether two OracleIntervalYM values are not equal |
| Parse | Returns an OracleIntervalYM structure and sets its value for time interval using a string |
| SetPrecision | Returns a new instance of an OracleIntervalYM with the specified year precision. |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

Equals

This static method determines whether or not two OracleIntervalYM values are equal.

Declaration

```
// C#
public static bool Equals(OracleIntervalYM val1, OracleIntervalYM val2);
```

Parameters

- *val1*
An OracleIntervalYM structure.
- *val2*
An OracleIntervalYM structure.

Return Value

Returns true if two OracleIntervalYM values represent the same time interval, otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleIntervalYM that has a value compares greater than an OracleIntervalYM that has a null value.
- Two OracleIntervalYMs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

GreaterThan

This static method determines whether or not the first of two OracleIntervalYM values is greater than the second.

Declaration

```
// C#  
public static bool GreaterThan(OracleIntervalYM val1, OracleIntervalYM val2);
```

Parameters

- *val1*
The first OracleIntervalYM.
- *val2*
The second OracleIntervalYM.

Return Value

Returns true if the first of two OracleIntervalYM values is greater than the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleIntervalYM that has a value compares greater than an OracleIntervalYM that has a null value.
- Two OracleIntervalYMs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

GreaterThanOrEqual

This static method determines whether or not the first of two OracleIntervalYM values is greater than or equal to the second.

Declaration

```
// C#  
public static bool GreaterThanOrEqual(OracleIntervalYM val1,
```

```
OracleIntervalYM val2);
```

Parameters

- *val1*
The first OracleIntervalYM.
- *val2*
The second OracleIntervalYM.

Return Value

Returns true if the first of two OracleIntervalYM values is greater than or equal to the second; otherwise returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleIntervalYM that has a value compares greater than an OracleIntervalYM that has a null value.
- Two OracleIntervalYMs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

LessThan

This static method determines whether or not the first of two OracleIntervalYM values is less than the second.

Declaration

```
// C#
public static bool LessThan(OracleIntervalYM val1, OracleIntervalYM val2);
```

Parameters

- *val1*
The first OracleIntervalYM.
- *val2*
The second OracleIntervalYM.

Return Value

Returns true if the first of two OracleIntervalYM values is less than the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleIntervalYM that has a value compares greater than an OracleIntervalYM that has a null value.

- Two OracleIntervalYMs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

LessThanOrEqual

This static method determines whether or not the first of two OracleIntervalYM values is less than or equal to the second.

Declaration

```
// C#  
public static bool LessThanOrEqual(OracleIntervalYM val1, OracleIntervalYM val2);
```

Parameters

- *val1*
The first OracleIntervalYM.
- *val2*
The second OracleIntervalYM.

Return Value

Returns true if the first of two OracleIntervalYM values is less than or equal to the second. Returns false otherwise.

Remarks

The following rules apply to the behavior of this method.

- Any OracleIntervalYM that has a value compares greater than an OracleIntervalYM that has a null value.
- Two OracleIntervalYMs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

NotEquals

This static method determines whether two OracleIntervalYM values are not equal.

Declaration

```
// C#  
public static bool NotEquals(OracleIntervalYM val1, OracleIntervalYM val2);
```

Parameters

- *val1*

The first OracleIntervalYM.

- *val2*

The second OracleIntervalYM.

Return Value

Returns true if two OracleIntervalYM values are not equal. Returns false otherwise.

Remarks

The following rules apply to the behavior of this method.

- Any OracleIntervalYM that has a value compares greater than an OracleIntervalYM that has a null value.
- Two OracleIntervalYMs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

Parse

This static method returns an OracleIntervalYM structure and sets its value for time interval using a string.

Declaration

```
// C#
public static OracleIntervalYM Parse (string intervalStr);
```

Parameters

- *intervalStr*
A string representing the Oracle INTERVAL YEAR TO MONTH.

Return Value

Returns an OracleIntervalYM structure.

Exceptions

ArgumentException - The *intervalStr* parameter is not in the valid format or *intervalStr* has an invalid value.

ArgumentNullException - The *intervalStr* parameter is null.

Remarks

The value specified in the supplied *intervalStr* must be in the Year-Month format.

Example

"1-2" means 1 year and 2 months.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

SetPrecision

This static method returns a new instance of an `OracleIntervalYM` with the specified year precision.

Declaration

```
// C#  
public static OracleIntervalYM SetPrecision(OracleIntervalYM value1,  
    int yearPrecision);
```

Parameters

- *value1*
An `OracleIntervalYM` structure.
- *yearPrecision*
The year precision provided. Range of year precision is (0 to 9).

Return Value

An `OracleIntervalDS` instance.

Exceptions

`ArgumentOutOfRangeException` - *yearPrecision* is out of the specified range.

Remarks

Depending on the value specified in the supplied *yearPrecision*, 0 or more leading zeros are displayed in the string returned by `ToString()`.

Example

An `OracleIntervalYM` with a value of "1-2" results in the string "001-2" when `SetPrecision()` is called with the year precision set to 3.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

OracleIntervalYM Static Operators

The OracleIntervalYM static operators are listed in [Table 14–83](#).

Table 14–83 OracleIntervalYM Static Operators

| Operator | Description |
|-----------------------------|------------------------------------------------------------------------------------------|
| <code>operator +</code> | Adds two OracleIntervalYM values |
| <code>operator ==</code> | Determines whether or not two OracleIntervalYM values are equal |
| <code>operator ></code> | Determines whether or not one OracleIntervalYM value is greater than another |
| <code>operator >=</code> | Determines whether or not one OracleIntervalYM value is greater than or equal to another |
| <code>operator !=</code> | Determines whether two OracleIntervalYM values are not equal |
| <code>operator <</code> | Determines whether or not one OracleIntervalYM value is less than another |
| <code>operator <=</code> | Determines whether or not one OracleIntervalYM value is less than or equal to another |
| <code>operator -</code> | Subtracts one OracleIntervalYM value from another |
| <code>operator -</code> | Negates an OracleIntervalYM structure |
| <code>operator *</code> | Multiplies an OracleIntervalYM value by a number |
| <code>operator /</code> | Divides an OracleIntervalYM value by a number |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

operator +

This static operator adds two OracleIntervalYM values.

Declaration

```
// C#
public static OracleIntervalYM operator + (OracleIntervalYM val1,
    OracleIntervalYM val2);
```

Parameters

- `val1`
The first OracleIntervalYM.
- `val2`
The second OracleIntervalYM.

Return Value

OracleIntervalYM

Remarks

If either argument has a null value, the returned `OracleIntervalYM` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

operator ==

This static operator determines if two `OracleIntervalYM` values are equal.

Declaration

```
// C#  
public static bool operator == (OracleIntervalYM val1, OracleIntervalYM val2);
```

Parameters

- *val1*
The first `OracleIntervalYM`.
- *val2*
The second `OracleIntervalYM`.

Return Value

Returns true if they are equal; otherwise returns false.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalYM` that has a value compares greater than an `OracleIntervalYM` that has a null value.
- Two `OracleIntervalYMs` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

operator >

This static operator determines if the first of two `OracleIntervalYM` values is greater than the second.

Declaration

```
// C#  
public static bool operator > (OracleIntervalYM val1, OracleIntervalYM val2);
```

Parameters

- *val1*
The first OracleIntervalYM.
- *val2*
The second OracleIntervalYM.

Return Value

Returns true if one OracleIntervalYM value is greater than another; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleIntervalYM that has a value compares greater than an OracleIntervalYM that has a null value.
- Two OracleIntervalYMs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

operator >=

This static operator determines if the first of two OracleIntervalYM values is greater than or equal to the second.

Declaration

```
// C#
public static bool operator >= (OracleIntervalYM val1, OracleIntervalYM val2);
```

Parameters

- *val1*
The first OracleIntervalYM.
- *val2*
The second OracleIntervalYM.

Return Value

Returns true if one OracleIntervalYM value is greater than or equal to another; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleIntervalYM that has a value compares greater than an OracleIntervalYM that has a null value.
- Two OracleIntervalYMs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

operator !=

This static operator determines whether two OracleIntervalYM values are not equal.

Declaration

```
// C#  
public static bool operator != (OracleIntervalYM val1, OracleIntervalYM val2)
```

Parameters

- *val1*
The first OracleIntervalYM.
- *val2*
The second OracleIntervalYM.

Return Value

Returns true if two OracleIntervalYM values are not equal; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleIntervalYM that has a value compares greater than an OracleIntervalYM that has a null value.
- Two OracleIntervalYMs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

operator <

This static operator determines if the first of two OracleIntervalYM values is less than the second.

Declaration

```
// C#  
public static bool operator < (OracleIntervalYM val1, OracleIntervalYM val2);
```

Parameters

- *val1*
The first OracleIntervalYM.
- *val2*

The second OracleIntervalYM.

Return Value

Returns true if the first of two OracleIntervalYM values is less than the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleIntervalYM that has a value compares greater than an OracleIntervalYM that has a null value.
- Two OracleIntervalYMs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

operator <=

This static operator determines if the first of two OracleIntervalYM values is less than or equal to the second.

Declaration

```
// C#
public static bool operator <= (OracleIntervalYM val1, OracleIntervalYM val2);
```

Parameters

- *val1*
The first OracleIntervalYM.
- *val2*
The second OracleIntervalYM.

Return Value

Returns true if the first of two OracleIntervalYM values is less than or equal to the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleIntervalYM that has a value compares greater than an OracleIntervalYM that has a null value.
- Two OracleIntervalYMs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

operator -

This static operator subtracts one OracleIntervalYM structure from another.

Declaration

```
// C#  
public static OracleIntervalYM operator - (OracleIntervalYM val1, OracleIntervalYM  
val2);
```

Parameters

- *val1*
The first OracleIntervalYM.
- *val2*
The second OracleIntervalYM.

Return Value

An OracleIntervalYM structure.

Remarks

If either argument has a null value, the returned OracleIntervalYM structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

operator -

This static operator negates an OracleIntervalYM structure.

Declaration

```
// C#  
public static OracleIntervalYM operator - (OracleIntervalYM val);
```

Parameters

- *val*
An OracleIntervalYM.

Return Value

An OracleIntervalYM structure.

Remarks

If the supplied `OracleIntervalYM` structure has a null value, the returned `OracleIntervalYM` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

operator *

This static operator multiplies an `OracleIntervalYM` value by a number.

Declaration

```
// C#
public static OracleIntervalYM operator * (OracleIntervalYM val1, int multiplier);
```

Parameters

- *val1*
The first `OracleIntervalYM`.
- *multiplier*
A multiplier.

Return Value

An `OracleIntervalYM` structure.

Remarks

If the supplied `OracleIntervalYM` structure has a null value, the returned `OracleIntervalYM` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

operator /

This static operator divides an `OracleIntervalYM` value by a number.

Declaration

```
// C#
public static OracleIntervalYM operator / (OracleIntervalYM val1, int divisor);
```

Parameters

- *val1*
The first `OracleIntervalYM`.
- *divisor*

A divisor.

Return Value

An `OracleIntervalYM` structure.

Remarks

If the supplied `OracleIntervalYM` structure has a null value, the returned `OracleIntervalYM` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

OracleIntervalYM Type Conversions

The OracleIntervalYM conversions are listed in [Table 14–84](#).

Table 14–84 OracleIntervalYM Type Conversions

| Operator | Description |
|----------------------------------------------------|----------------------------------------------------------------|
| explicit operator long | Converts an OracleIntervalYM structure to a number |
| explicit operator OracleIntervalYM | Converts a string to an OracleIntervalYM structure |
| implicit operator OracleIntervalYM | Converts the number of months to an OracleIntervalYM structure |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

explicit operator long

This type conversion operator converts an OracleIntervalYM to a number that represents the number of months in the time interval.

Declaration

```
// C#
public static explicit operator long (OracleIntervalYM val);
```

Parameters

- *val*
An OracleIntervalYM structure.

Return Value

A long number in months.

Exceptions

OracleNullValueException - The OracleIntervalYM structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

explicit operator OracleIntervalYM

This type conversion operator converts the string *intervalStr* to an OracleIntervalYM structure.

Declaration

```
// C#  
public static explicit operator OracleIntervalYM (string intervalStr);
```

Parameters

- *intervalStr*

A string representation of an Oracle INTERVAL YEAR TO MONTH.

Return Value

An OracleIntervalYM structure.

Exceptions

ArgumentException - The supplied *intervalStr* parameter is not in the correct format or has an invalid value.

ArgumentNullException - The *intervalStr* parameter is null.

Remarks

The returned OracleIntervalDS structure contains the same time interval represented by the supplied *intervalStr*. The value specified in the supplied *intervalStr* must be in Year-Month format.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

implicit operator OracleIntervalYM

This type conversion operator converts the total number of months as time interval to an OracleIntervalYM structure.

Declaration

```
// C#  
public static implicit operator OracleIntervalYM (long months);
```

Parameters

- *months*

The number of months to be converted. Range is $(-999,999,999 * 12) - 11 \leq months \leq (999,999,999 * 12) + 11$.

Return Value

An OracleIntervalYM structure.

Exceptions

ArgumentOutOfRangeException - The *months* parameter is out of the specified range.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

OracleIntervalYM Properties

The OracleIntervalYM properties are listed in [Table 14–85](#).

Table 14–85 OracleIntervalYM Properties

| Properties | Description |
|----------------------------|------------------------------------------------------------------------------------------------------------------|
| BinData | Returns an array of bytes that represents the Oracle INTERVAL YEAR TO MONTH in an Oracle internal format |
| IsNull | Indicates whether or not the current instance has a null value |
| Months | Gets the months component of an OracleIntervalYM |
| TotalYears | Returns the total number, in years, that represents the period of time in the current OracleIntervalYM structure |
| Value | Specifies the total number of months that is stored in the OracleIntervalYM structure |
| Years | Gets the years component of an OracleIntervalYM |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

BinData

This property returns an array of bytes that represents the Oracle INTERVAL YEAR TO MONTH in Oracle internal format.

Declaration

```
// C#
public byte[] BinData {get;}
```

Property Value

A byte array that represents an Oracle INTERVAL YEAR TO MONTH in Oracle internal format.

Exceptions

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

IsNull

This property indicates whether or not the value has a null value.

Declaration

```
// C#  
public bool IsNull {get;}
```

Property Value

Returns true if value has a null value; otherwise, returns false.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

Months

This property gets the months component of an OracleIntervalYM.

Declaration

```
// C#  
public int Months {get;}
```

Property Value

An int representing the months component.

Exceptions

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

TotalYears

This property returns the total number, in years, that represents the period of time in the current OracleIntervalYM structure.

Declaration

```
// C#  
public double TotalYears {get;}
```

Property Value

A double representing the total number of years.

Exceptions

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

Value

This property gets the total number of months that is stored in the `OracleIntervalYM` structure.

Declaration

```
// C#  
public long Value {get;}
```

Property Value

The total number of months representing the time interval.

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

Years

This property gets the years component of an `OracleIntervalYM`.

Declaration

```
// C#  
public int Years {get;}
```

Property Value

An `int` representing the years component.

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

OracleIntervalYM Methods

The OracleIntervalYM methods are listed in [Table 14–86](#).

Table 14–86 OracleIntervalYM Methods

| Methods | Description |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| CompareTo | Compares the current OracleIntervalYM instance to the supplied object, and returns an integer that represents their relative values |
| Equals | Determines whether or not the specified object has the same time interval as the current instance (Overloaded) |
| GetHashCode | Returns a hash code for the OracleIntervalYM instance |
| GetType | Inherited from System.Object |
| ToString | Converts the current OracleIntervalYM structure to a string |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

CompareTo

This method compares the current OracleIntervalYM instance to the supplied object, and returns an integer that represents their relative values.

Declaration

```
// C#
public int CompareTo(object obj);
```

Parameters

- *obj*
The supplied object.

Return Value

The method returns a number:

Less than zero: if the current OracleIntervalYM represents a shorter time interval than *obj*.

Zero: if the current OracleIntervalYM and *obj* represent the same time interval.

Greater than zero: if the current OracleIntervalYM represents a longer time interval than *obj*.

Implements

IComparable

Exceptions

ArgumentException - The *obj* parameter is not of type OracleIntervalYM.

Remarks

The following rules apply to the behavior of this method.

- The comparison must be between `OracleIntervalYMs`. For example, comparing an `OracleIntervalYM` instance with an `OracleBinary` instance is not allowed. When an `OracleIntervalYM` is compared with a different type, an `ArgumentException` is thrown.
- Any `OracleIntervalYM` that has a value compares greater than an `OracleIntervalYM` that has a null value.
- Two `OracleIntervalYMs` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

Equals

Overrides `Object`

This method determines whether or not the specified object has the same time interval as the current instance.

Declaration

```
// C#  
public override bool Equals(object obj);
```

Parameters

- *obj*
The supplied object.

Return Value

Returns `true` if the specified object instance is of type `OracleIntervalYM` and has the same time interval; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleIntervalYM` that has a value compares greater than an `OracleIntervalYM` that has a null value.
- Two `OracleIntervalYMs` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

GetHashCode

Overrides `Object`

This method returns a hash code for the `OracleIntervalYM` instance.

Declaration

```
// C#  
public override int GetHashCode();
```

Return Value

An `int` representing a hash code.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

ToString

Overrides `Object`

This method converts the current `OracleIntervalYM` structure to a string.

Declaration

```
// C#  
public override string ToString();
```

Return Value

A string that represents the current `OracleIntervalYM` structure.

Remarks

If the current instance has a null value, the returned string contain "null".

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleIntervalYM Structure](#)
- [OracleIntervalYM Members](#)

OracleString Structure

The `OracleString` structure represents a variable-length stream of characters to be stored in or retrieved from a database.

Class Inheritance

`System.Object`

`System.ValueType`

`Oracle.DataAccess.Types.OracleString`

Declaration

```
// C#  
public struct OracleString : IComparable, INullable, IXmlSerializable
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|--------------------------------------|---------------------------------------------|
| Assembly | <code>Oracle.DataAccess.dll</code> | <code>Oracle.ManagedDataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Types</code> | <code>Oracle.ManagedDataAccess.Types</code> |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Types;  
  
class OracleStringSample  
{  
    static void Main()  
    {  
        // Initialize OracleString structs  
        OracleString string1 = new OracleString("AAA");  
  
        // Display the string "AAA"  
        Console.WriteLine("{0} has length of {1}", string1, string1.Length);  
  
        // Contatenate characters to string1 until the length is 5  
        while (string1.Length < 5)  
            string1 = OracleString.Concat(string1, "a");  
  
        // Display the string of "AAAaa"  
        Console.WriteLine("{0} has length of {1}", string1, string1.Length);  
    }  
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleString Members](#)
- [OracleString Constructors](#)
- [OracleString Static Fields](#)
- [OracleString Static Methods](#)
- [OracleString Static Operators](#)
- [OracleString Type Conversions](#)
- [OracleString Properties](#)
- [OracleString Methods](#)

OracleString Members

OracleString members are listed in the following tables:

OracleString Constructors

OracleString constructors are listed in [Table 14–87](#)

Table 14–87 OracleString Constructors

| Constructor | Description |
|-------------------------------------------|--------------------------------------------------------------------|
| OracleString Constructors | Instantiates a new instance of OracleString structure (Overloaded) |

OracleString Static Fields

The OracleString static fields are listed in [Table 14–88](#).

Table 14–88 OracleString Static Fields

| Field | Description |
|----------------------|-------------------------------------------------------------------------------------------|
| Null | Represents a null value that can be assigned to an instance of the OracleString structure |

OracleString Static Methods

The OracleString static methods are listed in [Table 14–89](#).

Table 14–89 OracleString Static Methods

| Methods | Description |
|------------------------------------|------------------------------------------------------------------------------------------------------------|
| Concat | Concatenates two OracleString instances and returns a new OracleString instance that represents the result |
| Equals | Determines if two OracleString values are equal (Overloaded) |
| GreaterThan | Determines whether or not the first of two OracleString values is greater than the second |
| GreaterThanOrEqual | Determines whether or not the first of two OracleString values is greater than or equal to the second |
| LessThan | Determines whether or not the first of two OracleString values is less than the second |
| LessThanOrEqual | Determines whether or not the first of two OracleString values is less than or equal to the second |
| NotEquals | Determines whether two OracleString values are not equal |

OracleString Static Operators

The OracleString static operators are listed in [Table 14–90](#).

Table 14–90 OracleString Static Operators

| Operator | Description |
|--------------------------------|-------------------------------------------------------------------------------------------|
| operator + | Concatenates two OracleString values |
| operator == | Determines if two OracleString values are equal |
| operator > | Determines if the first of two OracleString values is greater than the second |
| operator >= | Determines if the first of two OracleString values is greater than or equal to the second |
| operator != | Determines if the two OracleString values are not equal |
| operator < | Determines if the first of two OracleString values is less than the second |
| operator <= | Determines if two OracleString values are not equal |

OracleString Type Conversions

The OracleString type conversions are listed in [Table 14–91](#).

Table 14–91 OracleString Type Conversions

| Operator | Description |
|------------------------------------------------|----------------------------------------------------------|
| explicit operator string | Converts the supplied OracleString to a string instance |
| implicit operator OracleString | Converts the supplied string to an OracleString instance |

OracleString Properties

The OracleString properties are listed in [Table 14–92](#).

Table 14–92 OracleString Properties

| Properties | Description |
|-------------------------------|-----------------------------------------------------------------------------------|
| IsCaseIgnored | Indicates whether or not case should be ignored when performing string comparison |
| IsNull | Indicates whether or not the current instance has a null value |
| Item | Obtains the particular character in an OracleString using an index. |
| Length | Returns the length of the OracleString |
| Value | Returns the string data that is stored in the OracleString structure. |

OracleString Methods

The OracleString methods are listed in [Table 14–93](#).

Table 14–93 OracleString Methods

| Methods | Description |
|-----------------------|-----------------------------------------------------|
| Clone | Returns a copy of the current OracleString instance |

Table 14–93 (Cont.) OracleString Methods

| Methods | Description |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| CompareTo | Compares the current <code>OracleString</code> instance to the supplied object, and returns an integer that represents their relative values |
| Equals | Determines whether or not an object has the same string value as the current <code>OracleString</code> structure (Overloaded) |
| GetHashCode | Returns a hash code for the <code>OracleString</code> instance |
| GetNonUnicodeBytes | Returns an array of bytes, containing the contents of the <code>OracleString</code> , in the client character set format |
| GetType | Inherited from <code>System.Object</code> |
| GetUnicodeBytes | Returns an array of bytes, containing the contents of the <code>OracleString</code> , in Unicode format |
| ToString | Converts the current <code>OracleString</code> instance to a string |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)

OracleString Constructors

The `OracleString` constructors create new instances of the `OracleString` structure.

Overload List:

- [OracleString\(string\)](#)

This constructor creates a new instance of the `OracleString` structure and sets its value using a string.

- [OracleString\(string, bool\)](#)

This constructor creates a new instance of the `OracleString` structure and sets its value using a string and specifies if case is ignored in comparison.

- [OracleString\(byte \[\], bool\)](#)

This constructor creates a new instance of the `OracleString` structure and sets its value using a byte array and specifies if the supplied byte array is Unicode encoded.

- [OracleString\(byte \[\], bool, bool\)](#)

This constructor creates a new instance of the `OracleString` structure and sets its value using a byte array and specifies the following: if the supplied byte array is Unicode encoded and if case is ignored in comparison.

- [OracleString\(byte \[\], int, int, bool\)](#)

This constructor creates a new instance of the `OracleString` structure and sets its value using a byte array, and specifies the following: the starting index in the byte array, the number of bytes to copy from the byte array, and if the supplied byte array is Unicode encoded.

- [OracleString\(byte \[\], int, int, bool, bool\)](#)

This constructor creates a new instance of the `OracleString` structure and sets its value using a byte array, and specifies the following: the starting index in the byte array, the number of bytes to copy from the byte array, if the supplied byte array is Unicode encoded, and if case is ignored in comparison.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

OracleString(string)

This constructor creates a new instance of the `OracleString` structure and sets its value using a string.

Declaration

```
// C#  
public OracleString(string data);
```

Parameters

- *data*

A string value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

OracleString(string, bool)

This constructor creates a new instance of the `OracleString` structure and sets its value using a string and specifies if case is ignored in comparison.

Declaration

```
// C#  
public OracleString(string data, bool isCaseIgnored);
```

Parameters

- *data*

A string value.

- *isCaseIgnored*

Specifies if case is ignored in comparison. Specifies `true` if case is to be ignored; otherwise, specifies `false`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

OracleString(byte [], bool)

This constructor creates a new instance of the `OracleString` structure and sets its value using a byte array and specifies if the supplied byte array is Unicode encoded.

Declaration

```
// C#  
public OracleString(byte[] data, bool fUnicode);
```

Parameters

- *data*

Byte array data for the new `OracleString`.

- *fUnicode*

Specifies if the supplied data is Unicode encoded. Specifies `true` if Unicode encoded; otherwise, `false`.

Exceptions

`ArgumentNullException` - The *data* parameter is null.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

OracleString(byte [], bool, bool)

This constructor creates a new instance of the `OracleString` structure and sets its value using a byte array and specifies the following: if the supplied byte array is Unicode encoded and if case is ignored in comparison.

Declaration

```
// C#  
public OracleString(byte[] data, bool fUnicode, bool isCaseIgnored);
```

Parameters

- *data*
Byte array data for the new `OracleString`.
- *fUnicode*
Specifies if the supplied data is Unicode encoded. Specifies true if Unicode encoded; otherwise, false.
- *isCaseIgnored*
Specifies if case is ignored in comparison. Specifies true if case is to be ignored; otherwise, specifies false.

Exceptions

`ArgumentNullException` - The *data* parameter is null.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

OracleString(byte [], int, int, bool)

This constructor creates a new instance of the `OracleString` structure and sets its value using a byte array, and specifies the following: the starting index in the byte array, the number of bytes to copy from the byte array, and if the supplied byte array is Unicode encoded.

Declaration

```
// C#  
public OracleString(byte[] data, int index, int count, bool fUnicode);
```

Parameters

- *data*
Byte array data for the new `OracleString`.

- *index*
The starting index to copy from *data*.
- *count*
The number of bytes to copy.
- *fUnicode*
Specifies if the supplied data is Unicode encoded. Specifies true if Unicode encoded; otherwise, false.

Exceptions

`ArgumentNullException` - The *data* parameter is null.

`ArgumentOutOfRangeException` - The *count* parameter is less than zero.

`IndexOutOfRangeException` - The *index* parameter is greater than or equal to the length of *data* or less than zero.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

OracleString(byte [], int, int, bool, bool)

This constructor creates a new instance of the `OracleString` structure and sets its value using a byte array, and specifies the following: the starting index in the byte array, the number of bytes to copy from the byte array, if the supplied byte array is Unicode encoded, and if case is ignored in comparison.

Declaration

```
// C#  
public OracleString(byte[] data, int index, int count, bool fUnicode,  
    bool isCaseIgnored);
```

Parameters

- *data*
Byte array data for the new `OracleString`.
- *index*
The starting index to copy from *data*.
- *count*
The number of bytes to copy.
- *fUnicode*
Specifies if the supplied data is Unicode encoded. Specifies true if Unicode encoded; otherwise, false.
- *isCaseIgnored*
Specifies if case is ignored in comparison. Specifies true if case is to be ignored; otherwise, specifies false.

Exceptions

ArgumentNullException - The *data* parameter is null.

ArgumentOutOfRangeException - The *count* parameter is less than zero.

IndexOutOfRangeException - The *index* parameter is greater than or equal to the length of *data* or less than zero.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

OracleString Static Fields

The `OracleString` static fields are listed in [Table 14–94](#).

Table 14–94 *OracleString Static Fields*

| Field | Description |
|----------------------|--------------------------------------------------------------------------------------------------------|
| Null | Represents a null value that can be assigned to an instance of the <code>OracleString</code> structure |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

Null

This static field represents a null value that can be assigned to an instance of the `OracleString` structure.

Declaration

```
// C#  
public static readonly OracleString Null;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

OracleString Static Methods

The OracleString static methods are listed in [Table 14–95](#).

Table 14–95 OracleString Static Methods

| Methods | Description |
|------------------------------------|------------------------------------------------------------------------------------------------------------|
| Concat | Concatenates two OracleString instances and returns a new OracleString instance that represents the result |
| Equals | Determines if two OracleString values are equal (Overloaded) |
| GreaterThan | Determines whether or not the first of two OracleString values is greater than the second |
| GreaterThanOrEqual | Determines whether or not the first of two OracleString values is greater than or equal to the second |
| LessThan | Determines whether or not the first of two OracleString values is less than the second |
| LessThanOrEqual | Determines whether or not the first of two OracleString values is less than or equal to the second |
| NotEquals | Determines whether two OracleString values are not equal |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

Concat

This static method concatenates two OracleString instances and returns a new OracleString instance that represents the result.

Declaration

```
// C#
public static OracleString Concat(OracleString str1, OracleString str2);
```

Parameters

- *str1*
The first OracleString.
- *str2*
The second OracleString.

Return Value

An OracleString.

Remarks

If either argument has a null value, the returned OracleString structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

Equals

Overloads `Object`

This static method determines whether or not the two `OracleStrings` being compared are equal.

Declaration

```
// C#  
public static bool Equals(OracleString str1, OracleString str2);
```

Parameters

- `str1`
The first `OracleString`.
- `str2`
The second `OracleString`.

Return Value

Returns `true` if the two `OracleStrings` being compared are equal; returns `false` otherwise.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

GreaterThan

This static method determines whether or not the first of two `OracleString` values is greater than the second.

Declaration

```
// C#  
public static bool GreaterThan(OracleString str1, OracleString str2);
```

Parameters

- *str1*
The first OracleString.
- *str2*
The second OracleString.

Return Value

Returns true if the first of two OracleStrings is greater than the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleString that has a value is greater than an OracleString that has a null value.
- Two OracleStrings that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

GreaterThanOrEqualTo

This static method determines whether or not the first of two OracleString values is greater than or equal to the second.

Declaration

```
// C#  
public static bool GreaterThanOrEqualTo(OracleString str1,  
    OracleString str2);
```

Parameters

- *str1*
The first OracleString.
- *str2*
The second OracleString.

Return Value

Returns true if the first of two OracleStrings is greater than or equal to the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleString that has a value is greater than an OracleString that has a null value.
- Two OracleStrings that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

LessThan

This static method determines whether or not the first of two `OracleString` values is less than the second.

Declaration

```
// C#  
public static bool LessThan(OracleString str1, OracleString str2);
```

Parameters

- *str1*
The first `OracleString`.
- *str2*
The second `OracleString`.

Return Value

Returns `true` if the first is less than the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

LessThanOrEqual

This static method determines whether or not the first of two `OracleString` values is less than or equal to the second.

Declaration

```
// C#  
public static bool LessThanOrEqual(OracleString str1, OracleString str2);
```

Parameters

- *str1*
The first `OracleString`.

- *str2*
The second `OracleString`.

Return Value

Returns `true` if the first is less than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

NotEquals

This static method determines whether two `OracleString` values are not equal.

Declaration

```
// C#  
public static bool NotEquals(OracleString str1, OracleString str2);
```

Parameters

- *str1*
The first `OracleString`.
- *str2*
The second `OracleString`.

Return Value

Returns `true` if the two `OracleString` instances are not equal; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

OracleString Static Operators

The OracleString static operators are listed in [Table 14–96](#).

Table 14–96 OracleString Static Operators

| Operator | Description |
|--------------------------------|-------------------------------------------------------------------------------------------|
| operator + | Concatenates two OracleString values |
| operator == | Determines if two OracleString values are equal |
| operator > | Determines if the first of two OracleString values is greater than the second |
| operator >= | Determines if the first of two OracleString values is greater than or equal to the second |
| operator != | Determines if the two OracleString values are not equal |
| operator < | Determines if the first of two OracleString values is less than the second |
| operator <= | Determines if two OracleString values are not equal |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

operator +

This static operator concatenates two OracleString values.

Declaration

```
// C#
public static OracleString operator + (OracleString value1, OracleString value2);
```

Parameters

- *value1*
The first OracleString.
- *value2*
The second OracleString.

Return Value

An OracleString.

Remarks

If either argument has a null value, the returned OracleString structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

operator ==

This static operator determines if two `OracleString` values are equal.

Declaration

```
// C#  
public static bool operator == (OracleString value1, OracleString value2);
```

Parameters

- *value1*
The first `OracleString`.
- *value2*
The second `OracleString`.

Return Value

Returns true if two `OracleString` values are equal; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

operator >

This static operator determines if the first of two `OracleString` values is greater than the second.

Declaration

```
// C#  
public static bool operator > (OracleString value1, OracleString value2);
```

Parameters

- *value1*
The first `OracleString`.
- *value2*

The second `OracleString`.

Return Value

Returns `true` if the first of two `OracleString` values is greater than the second; otherwise returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

operator >=

This static operator determines if the first of two `OracleString` values is greater than or equal to the second.

Declaration

```
// C#  
public static bool operator >= (OracleString value1, OracleString value2);
```

Parameters

- *value1*
The first `OracleString`.
- *value2*
The second `OracleString`.

Return Value

Returns `true` if the first of two `OracleString` values is greater than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

operator !=

This static operator determines if two `OracleString` values are not equal.

Declaration

```
// C#  
public static bool operator != (OracleString value1, OracleString value2);
```

Parameters

- *value1*
The first `OracleString`.
- *value2*
The second `OracleString`.

Return Value

Returns true if two `OracleString` values are not equal; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

operator <

This static operator determines if the first of two `OracleStrings` is less than the second.

Declaration

```
// C#  
public static bool operator < (OracleString value1, OracleString value2);
```

Parameters

- *value1*
The first `OracleString`.
- *value2*

The second `OracleString`.

Return Value

Returns `true` if the first of two `OracleStrings` is less than the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` has a null value.
- Two `OracleStrings` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleString Structure](#)
- [OracleString Members](#)

operator <=

This static operator determines if the first of two `OracleString` values is less than or equal to the second.

Declaration

```
// C#  
public static bool operator <= (OracleString value1, OracleString value1);
```

Parameters

- *value1*
The first `OracleString`.
- *value2*
The second `OracleString`.

Return Value

Returns `true` if the first of two `OracleString` values is less than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleString Structure](#)
- [OracleString Members](#)

OracleString Type Conversions

The OracleString type conversions are listed in [Table 14–97](#).

Table 14–97 OracleString Type Conversions

| Operator | Description |
|------------------------------------------------|----------------------------------------------------------|
| explicit operator string | Converts the supplied OracleString to a string instance |
| implicit operator OracleString | Converts the supplied string to an OracleString instance |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

explicit operator string

This type conversion operator converts the supplied OracleString to a string.

Declaration

```
//C#
public static explicit operator string (OracleString value1);
```

Parameters

- *value1*
The supplied OracleString.

Return Value

string

Exceptions

OracleNullValueException - The OracleString structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

implicit operator OracleString

This type conversion operator converts the supplied string to an OracleString.

Declaration

```
// C#
public static implicit operator OracleString (string value1);
```


Parameters

- *value1*
The supplied string.

Return Value

An `OracleString`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

OracleString Properties

The OracleString properties are listed in [Table 14–98](#).

Table 14–98 OracleString Properties

| Properties | Description |
|-------------------------------|-----------------------------------------------------------------------------------|
| IsCaseIgnored | Indicates whether or not case should be ignored when performing string comparison |
| IsNull | Indicates whether or not the current instance has a null value |
| Item | Obtains the particular character in an OracleString using an index. |
| Length | Returns the length of the OracleString |
| Value | Returns the string data that is stored in the OracleString structure. |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

IsCaseIgnored

This property indicates whether or not case should be ignored when performing string comparison.

Declaration

```
//C#
public bool IsCaseIgnored {get;set;}
```

Property Value

Returns true if string comparison must ignore case; otherwise false.

Remarks

Default value is true.

Example

```
// C#

using System;
using Oracle.DataAccess.Types;

class IsCaseIgnoredSample
{
    static void Main()
    {
        OracleString string1 = new OracleString("aAaAa");
        OracleString string2 = new OracleString("AaAaA");

        // Ignore case for comparisons
        string1.IsCaseIgnored = true;
        string2.IsCaseIgnored = true;
    }
}
```

```

// Same; Prints 0
Console.WriteLine(string1.CompareTo(string2));

// Make comparisons case sensitive
// Note that IsCaseIgnored must be set to false for both
// OracleStrings; otherwise an exception is thrown
string1.IsCaseIgnored = false;
string2.IsCaseIgnored = false;

// Different; Prints nonzero value
Console.WriteLine(string1.CompareTo(string2));
}
}

```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

IsNull

This property indicates whether or not the current instance contains a null value.

Declaration

```

// C#
public bool IsNull {get;}

```

Property Value

Returns true if the current instance contains has a null value; otherwise, returns false.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

Item

This property obtains the particular character in an OracleString using an index.

Declaration

```

// C#
public char Item {get;}

```

Property Value

A char value.

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

Length

This property returns the length of the `OracleString`.

Declaration

```
// C#  
public int Length {get;}
```

Property Value

A `int` value.

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

Value

This property returns the string data that is stored in the `OracleString`.

Declaration

```
// C#  
public string Value {get;}
```

Property Value

The stored string value

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

OracleString Methods

The OracleString methods are listed in [Table 14–99](#).

Table 14–99 OracleString Methods

| Methods | Description |
|------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Clone | Returns a copy of the current OracleString instance |
| CompareTo | Compares the current OracleString instance to the supplied object, and returns an integer that represents their relative values |
| Equals | Determines whether or not an object has the same string value as the current OracleString structure (Overloaded) |
| GetHashCode | Returns a hash code for the OracleString instance |
| GetNonUnicodeBytes | Returns an array of bytes, containing the contents of the OracleString, in the client character set format |
| GetType | Inherited from System.Object |
| GetUnicodeBytes | Returns an array of bytes, containing the contents of the OracleString, in Unicode format |
| ToString | Converts the current OracleString instance to a string |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

Clone

This method creates a copy of an OracleString instance.

Declaration

```
// C#
public OracleString Clone();
```

Return Value

An OracleString structure.

Remarks

The cloned object has the same property values as that of the object being cloned.

Example

```
// C#

using System;
using Oracle.DataAccess.Types;

class CloneSample
{
    static void Main()
    {
```

```
OracleString str1 = new OracleString("aAaAa");
OracleString str2 = str1.Clone();

// The OracleStrings are same; Prints 0
Console.WriteLine(str1.CompareTo(str2));
}
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

CompareTo

This method compares the current `OracleString` instance to the supplied object, and returns an integer that represents their relative values.

Declaration

```
// C#
public int CompareTo(object obj);
```

Parameters

- *obj*

The object being compared to the current instance.

Return Value

The method returns a number that is:

- Less than zero: if the current `OracleString` value is less than *obj*.
- Zero: if the current `OracleString` value is equal to *obj*.
- Greater than zero: if the current `OracleString` value is greater than *obj*.

Implements

`IComparable`

Exceptions

`ArgumentException` - The *obj* parameter is not of type `OracleString`.

Remarks

The following rules apply to the behavior of this method.

- The comparison must be between `OracleStrings`. For example, comparing an `OracleString` instance with an `OracleBinary` instance is not allowed. When an `OracleString` is compared with a different type, an `ArgumentException` is thrown.
- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

Equals

This method determines whether or not supplied object is an instance of `OracleString` and has the same values as the current `OracleString` instance.

Declaration

```
// C#  
public override bool Equals(object obj);
```

Parameters

- *obj*
An object being compared.

Return Value

Returns `true` if the supplied object is an instance of `OracleString` and has the same values as the current `OracleString` instance; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleString` that has a value is greater than an `OracleString` that has a null value.
- Two `OracleStrings` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

GetHashCode

Overrides `Object`

This method returns a hash code for the `OracleString` instance.

Declaration

```
// C#  
public override int GetHashCode();
```

Return Value

A number that represents the hash code.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

GetNonUnicodeBytes

This method returns an array of bytes, containing the contents of the `OracleString`, in the client character set format.

Declaration

```
// C#  
public byte[] GetNonUnicodeBytes();
```

Return Value

A byte array that contains the contents of the `OracleString` in the client character set format.

Remarks

If the current instance has a null value, an `OracleNullValueException` is thrown.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

GetUnicodeBytes

This method returns an array of bytes, containing the contents of the `OracleString` in Unicode format.

Declaration

```
// C#  
public byte[] GetUnicodeBytes();
```

Return Value

A byte array that contains the contents of the `OracleString` in Unicode format.

Remarks

If the current instance has a null value, an `OracleNullValueException` is thrown.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

ToString

Overrides Object

This method converts the current `OracleString` instance to a string.

Declaration

```
// C#  
public override string ToString();
```

Return Value

A string.

Remarks

If the current `OracleString` instance has a null value, the string contains "null".

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleString Structure](#)
- [OracleString Members](#)

OracleTimeStamp Structure

The `OracleTimeStamp` structure represents the Oracle `TIMESTAMP` data type to be stored in or retrieved from a database. Each `OracleTimeStamp` stores the following information: year, month, day, hour, minute, second, and nanosecond.

Class Inheritance

`System.Object`

`System.ValueType`

`Oracle.DataAccess.Types.OracleTimeStamp`

Declaration

```
// C#
public struct OracleTimeStamp : IComparable, INullable, IXmlSerializable
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|-----------------------|--------------------------------------|---------------------------------------------|
| Assembly | <code>Oracle.DataAccess.dll</code> | <code>Oracle.ManagedDataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Types</code> | <code>Oracle.ManagedDataAccess.Types</code> |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#

using System;
using Oracle.DataAccess.Types;

class OracleTimeStampSample
{
    static void Main()
    {
        OracleTimeStamp tsCurrent1 = OracleTimeStamp.GetSysDate();
        OracleTimeStamp tsCurrent2 = DateTime.Now;

        // Calculate the difference between tsCurrent1 and tsCurrent2
        OracleIntervalDS idsDiff = tsCurrent2.GetDaysBetween(tsCurrent1);

        // Calculate the difference using AddNanoseconds()
        int nanoDiff = 0;
        while (tsCurrent2 > tsCurrent1)
        {
            nanoDiff += 10;
            tsCurrent1 = tsCurrent1.AddNanoseconds(10);
        }
        Console.WriteLine("idsDiff.Nanoseconds = " + idsDiff.Nanoseconds);
        Console.WriteLine("nanoDiff = " + nanoDiff);
    }
}
```

```
}  
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleTimeStamp Members](#)
- [OracleTimeStamp Constructors](#)
- [OracleTimeStamp Static Fields](#)
- [OracleTimeStamp Static Methods](#)
- [OracleTimeStamp Static Operators](#)
- [OracleTimeStamp Static Type Conversions](#)
- [OracleTimeStamp Properties](#)
- [OracleTimeStamp Methods](#)

OracleTimeStamp Members

OracleTimeStamp members are listed in the following tables:

OracleTimeStamp Constructors

OracleTimeStamp constructors are listed in [Table 14–100](#)

Table 14–100 OracleTimeStamp Constructors

| Constructor | Description |
|----------------------------------------------|-----------------------------------------------------------------------|
| OracleTimeStamp Constructors | Instantiates a new instance of OracleTimeStamp structure (Overloaded) |

OracleTimeStamp Static Fields

The OracleTimeStamp static fields are listed in [Table 14–101](#).

Table 14–101 OracleTimeStamp Static Fields

| Field | Description |
|--------------------------|-------------------------------------------------------------------------------------------------------------------|
| MaxValue | Represents the maximum valid date for an OracleTimeStamp structure, which is December 31, 9999 23:59:59.999999999 |
| MinValue | Represents the minimum valid date for an OracleTimeStamp structure, which is January 1, -4712 0:0:0 |
| Null | Represents a null value that can be assigned to an instance of the OracleTimeStamp structure |

OracleTimeStamp Static Methods

The OracleTimeStamp static methods are listed in [Table 14–102](#).

Table 14–102 OracleTimeStamp Static Methods

| Methods | Description |
|------------------------------------|----------------------------------------------------------------------------------------------|
| Equals | Determines if two OracleTimeStamp values are equal (Overloaded) |
| GreaterThan | Determines if the first of two OracleTimeStamp values is greater than the second |
| GreaterThanOrEqual | Determines if the first of two OracleTimeStamp values is greater than or equal to the second |
| LessThan | Determines if the first of two OracleTimeStamp values is less than the second |
| LessThanOrEqual | Determines if the first of two OracleTimeStamp values is less than or equal to the second |
| NotEquals | Determines if two OracleTimeStamp values are not equal |
| GetSysDate | Gets an OracleTimeStamp structure that represents the current date and time |
| Parse | Gets an OracleTimeStamp structure and sets its value using the supplied string |

Table 14–102 (Cont.) OracleTimeStamp Static Methods

| Methods | Description |
|------------------------------|----------------------------------------------------------------------------------------------------------|
| SetPrecision | Returns a new instance of an <code>OracleTimeStamp</code> with the specified fractional second precision |

OracleTimeStamp Static Operators

The `OracleTimeStamp` static operators are listed in [Table 14–103](#).

Table 14–103 OracleTimeStamp Static Operators

| Operator | Description |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| operator + | Adds the supplied instance value to the supplied <code>OracleTimeStamp</code> and returns a new <code>OracleTimeStamp</code> structure (Overloaded) |
| operator == | Determines if two <code>OracleTimeStamp</code> values are equal |
| operator > | Determines if the first of two <code>OracleTimeStamp</code> values is greater than the second |
| operator >= | Determines if the first of two <code>OracleTimeStamp</code> values is greater than or equal to the second |
| operator != | Determines if the two <code>OracleTimeStamp</code> values are not equal |
| operator < | Determines if the first of two <code>OracleTimeStamp</code> values is less than the second |
| operator <= | Determines if the first of two <code>OracleTimeStamp</code> values is less than or equal to the second |
| operator - | Subtracts the supplied instance value from the supplied <code>OracleTimeStamp</code> and returns a new <code>OracleTimeStamp</code> structure (Overloaded) |

OracleTimeStamp Static Type Conversions

The `OracleTimeStamp` static type conversions are listed in [Table 14–104](#).

Table 14–104 OracleTimeStamp Static Type Conversions

| Operator | Description |
|---------------------------------------------------|--------------------------------------------------------------------------------------|
| explicit operator OracleTimeStamp | Converts an instance value to an <code>OracleTimeStamp</code> structure (Overloaded) |
| implicit operator OracleTimeStamp | Converts an instance value to an <code>OracleTimeStamp</code> structure (Overloaded) |
| explicit operator DateTime | Converts an <code>OracleTimeStamp</code> value to a <code>DateTime</code> structure |

OracleTimeStamp Properties

The `OracleTimeStamp` properties are listed in [Table 14–105](#).

Table 14–105 OracleTimeStamp Properties

| Properties | Description |
|-------------------------|-----------------------------------------------------------------------------------------------------|
| BinData | Returns an array of bytes that represents an <code>OracleTimeStamp</code> in Oracle internal format |

Table 14–105 (Cont.) OracleTimeStamp Properties

| Properties | Description |
|-------------|-----------------------------------------------------------------------------|
| Day | Specifies the day component of an OracleTimeStamp |
| IsNull | Indicates whether or not the OracleTimeStamp instance has a null value |
| Hour | Specifies the hour component of an OracleTimeStamp |
| Millisecond | Specifies the millisecond component of an OracleTimeStamp |
| Minute | Specifies the minute component of an OracleTimeStamp |
| Month | Specifies the month component of an OracleTimeStamp |
| Nanosecond | Specifies the nanosecond component of an OracleTimeStamp |
| Second | Specifies the second component of an OracleTimeStamp |
| Value | Specifies the date and time that is stored in the OracleTimeStamp structure |
| Year | Specifies the year component of an OracleTimeStamp |

OracleTimeStamp Methods

The OracleTimeStamp methods are listed in [Table 14–106](#).

Table 14–106 OracleTimeStamp Methods

| Methods | Description |
|-----------------|--------------------------------------------------------------------------------------------------------------------------|
| AddDays | Adds the supplied number of days to the current instance |
| AddHours | Adds the supplied number of hours to the current instance |
| AddMilliseconds | Adds the supplied number of milliseconds to the current instance |
| AddMinutes | Adds the supplied number of minutes to the current instance |
| AddMonths | Adds the supplied number of months to the current instance |
| AddNanoseconds | Adds the supplied number of nanoseconds to the current instance |
| AddSeconds | Adds the supplied number of seconds to the current instance |
| AddYears | Adds the supplied number of years to the current instance |
| CompareTo | Compares the current OracleTimeStamp instance to an object, and returns an integer that represents their relative values |

Table 14–106 (Cont.) OracleTimeStamp Methods

| Methods | Description |
|--------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Equals | Determines whether or not an object has the same date and time as the current <code>OracleTimeStamp</code> instance (Overloaded) |
| GetHashCode | Returns a hash code for the <code>OracleTimeStamp</code> instance |
| GetDaysBetween | Subtracts an <code>OracleTimeStamp</code> value from the current instance and returns an <code>OracleIntervalDS</code> that represents the time difference between the supplied <code>OracleTimeStamp</code> and the current instance |
| GetYearsBetween | Subtracts <code>value1</code> from the current instance and returns an <code>OracleIntervalYM</code> that represents the difference between <code>value1</code> and the current instance using <code>OracleIntervalYM</code> |
| GetType | Inherited from <code>System.Object</code> |
| ToOracleDate | Converts the current <code>OracleTimeStamp</code> structure to an <code>OracleDate</code> structure |
| ToOracleTimeStampLTZ | Converts the current <code>OracleTimeStamp</code> structure to an <code>OracleTimeStampLTZ</code> structure |
| ToOracleTimeStampTZ | Converts the current <code>OracleTimeStamp</code> structure to an <code>OracleTimeStampTZ</code> structure |
| ToString | Converts the current <code>OracleTimeStamp</code> structure to a string |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)

OracleTimeStamp Constructors

The `OracleTimeStamp` constructors create new instances of the `OracleTimeStamp` structure.

Overload List:

- [OracleTimeStamp\(DateTime\)](#)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date and time using the supplied `DateTime` value.
- [OracleTimeStamp\(string\)](#)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value using the supplied string.
- [OracleTimeStamp\(int, int, int\)](#)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date using year, month, and day.
- [OracleTimeStamp\(int, int, int, int, int, int\)](#)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date and time using year, month, day, hour, minute, and second.
- [OracleTimeStamp\(int, int, int, int, int, int, double\)](#)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date and time using year, month, day, hour, minute, second, and millisecond.
- [OracleTimeStamp\(int, int, int, int, int, int, int\)](#)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date and time using year, month, day, hour, minute, second, and nanosecond.
- [OracleTimeStamp\(byte \[\]\)](#)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value to the provided byte array, which is in the internal Oracle `TIMESTAMP` format.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

OracleTimeStamp(DateTime)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date and time using the supplied `DateTime` value.

Declaration

```
// C#  
public OracleTimeStamp (DateTime dt);
```


Parameters

- *dt*
The supplied DateTime value.

Exceptions

ArgumentException - The *dt* parameter cannot be used to construct a valid OracleTimeStamp.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

OracleTimeStamp(string)

This constructor creates a new instance of the OracleTimeStamp structure and sets its value using the supplied string.

Declaration

```
// C#
public OracleTimeStamp (string tsStr);
```

Parameters

- *tsStr*
A string that represents an Oracle TIMESTAMP.

Exceptions

ArgumentException - The *tsStr* value is an invalid string representation of an Oracle TIMESTAMP or the supplied *tsStr* is not in the timestamp format specified by the OracleGlobalization.TimeStampFormat property of the thread, which represents the Oracle NLS_TIMESTAMP_FORMAT parameter.

ArgumentNullException - The *tsStr* value is null.

Remarks

The names and abbreviations used for months and days are in the language specified by the DateLanguage and Calendar properties of the thread's OracleGlobalization object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#

using System;
using Oracle.DataAccess.Types;
using Oracle.DataAccess.Client;

class OracleTimeStampSample
{
    static void Main()
    {
        // Set the nls_timestamp_format for the OracleTimeStamp(string)
```

```
// constructor
OracleGlobalization info = OracleGlobalization.GetClientInfo();
info.TimeStampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
OracleGlobalization.SetThreadInfo(info);

// construct OracleTimeStamp from a string using the format specified.
OracleTimeStamp ts = new OracleTimeStamp("11-NOV-1999 11:02:33.444 AM");

// Set the nls_timestamp_format for the ToString() method
info.TimeStampFormat = "YYYY-MON-DD HH:MI:SS.FF AM";
OracleGlobalization.SetThreadInfo(info);

// Prints "1999-NOV-11 11:02:33.444000000 AM"
Console.WriteLine(ts.ToString());
}
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125
- *Oracle Database SQL Language Reference* for further information on date format elements

OracleTimeStamp(int, int, int)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date using year, month, and day.

Declaration

```
// C#
public OracleTimeStamp(int year, int month, int day);
```

Parameters

- *year*
The year provided. Range of year is (-4712 to 9999).
- *month*
The month provided. Range of month is (1 to 12).
- *day*
The day provided. Range of day is (1 to 31).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStamp` (that is, the day is out of range for the month).

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

OracleTimeStamp(int, int, int, int, int, int)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date and time using year, month, day, hour, minute, and second.

Declaration

```
// C#  
public OracleTimeStamp (int year, int month, int day, int hour,  
    int minute, int second);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).
- *month*
The month provided. Range of *month* is (1 to 12).
- *day*
The day provided. Range of *day* is (1 to 31).
- *hour*
The hour provided. Range of *hour* is (0 to 23).
- *minute*
The minute provided. Range of *minute* is (0 to 59).
- *second*
The second provided. Range of *second* is (0 to 59).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStamp` (that is, the day is out of range for the month).

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

OracleTimeStamp(int, int, int, int, int, int, double)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date and time using year, month, day, hour, minute, second, and millisecond.

Declaration

```
// C#  
public OracleTimeStamp(int year, int month, int day, int hour,  
    int minute, int second, double millisecond);
```

Parameters

- *year*
The year provided. Range of year is (-4712 to 9999).
- *month*
The month provided. Range of month is (1 to 12).
- *day*
The day provided. Range of day is (1 to 31).
- *hour*
The hour provided. Range of hour is (0 to 23).
- *minute*
The minute provided. Range of minute is (0 to 59).
- *second*
The second provided. Range of second is (0 to 59).
- *milliSeconds*
The milliseconds provided. Range of millisecond is (0 to 999.999999).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStamp` (that is, the day is out of range for the month).

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

OracleTimeStamp(int, int, int, int, int, int)

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value for date and time using year, month, day, hour, minute, second, and nanosecond.

Declaration

```
// C#  
public OracleTimeStamp (int year, int month, int day, int hour,
```

```
int minute, int second, int nanosecond);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).
- *month*
The month provided. Range of *month* is (1 to 12).
- *day*
The day provided. Range of *day* is (1 to 31).
- *hour*
The hour provided. Range of *hour* is (0 to 23).
- *minute*
The minute provided. Range of *minute* is (0 to 59).
- *second*
The second provided. Range of *second* is (0 to 59).
- *nanosecond*
The nanosecond provided. Range of *nanosecond* is (0 to 999999999).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStamp` (that is, the day is out of range for the month).

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

OracleTimeStamp(byte [])

This constructor creates a new instance of the `OracleTimeStamp` structure and sets its value to the provided byte array, which is in the internal Oracle `TIMESTAMP` format.

Declaration

```
// C#
public OracleTimeStamp (byte[] bytes);
```

Parameters

- *bytes*
A byte array that represents an Oracle `TIMESTAMP` in Oracle internal format.

Exceptions

`ArgumentException` - *bytes* is not in an internal Oracle `TIMESTAMP` format or *bytes* is not a valid Oracle `TIMESTAMP`.

`ArgumentNullException` - *bytes* is null.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

OracleTimeStamp Static Fields

The OracleTimeStamp static fields are listed in [Table 14–107](#).

Table 14–107 OracleTimeStamp Static Fields

| Field | Description |
|--------------------------|-------------------------------------------------------------------------------------------------------------------|
| MaxValue | Represents the maximum valid date for an OracleTimeStamp structure, which is December 31, 9999 23:59:59.999999999 |
| MinValue | Represents the minimum valid date for an OracleTimeStamp structure, which is January 1, -4712 0:0:0 |
| Null | Represents a null value that can be assigned to an instance of the OracleTimeStamp structure |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

MaxValue

This static field represents the maximum valid date and time for an OracleTimeStamp structure, which is December 31, 9999 23:59:59.999999999.

Declaration

```
// C#
public static readonly OraTimestamp MaxValue;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

MinValue

This static field represents the minimum valid date and time for an OracleTimeStamp structure, which is January 1, -4712 0:0:0.

Declaration

```
// C#
public static readonly OracleTimeStamp MinValue;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

Null

This static field represents a null value that can be assigned to an instance of the `OracleTimeStamp` structure.

Declaration

```
// C#  
public static readonly OracleTimeStamp Null;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

OracleTimeStamp Static Methods

The OracleTimeStamp static methods are listed in [Table 14–108](#).

Table 14–108 OracleTimeStamp Static Methods

| Methods | Description |
|------------------------------------|----------------------------------------------------------------------------------------------|
| Equals | Determines if two OracleTimeStamp values are equal (Overloaded) |
| GreaterThan | Determines if the first of two OracleTimeStamp values is greater than the second |
| GreaterThanOrEqual | Determines if the first of two OracleTimeStamp values is greater than or equal to the second |
| LessThan | Determines if the first of two OracleTimeStamp values is less than the second |
| LessThanOrEqual | Determines if the first of two OracleTimeStamp values is less than or equal to the second |
| NotEquals | Determines if two OracleTimeStamp values are not equal |
| GetSysDate | Gets an OracleTimeStamp structure that represents the current date and time |
| Parse | Gets an OracleTimeStamp structure and sets its value using the supplied string |
| SetPrecision | Returns a new instance of an OracleTimeStamp with the specified fractional second precision |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

Equals

This static method determines if two OracleTimeStamp values are equal.

Declaration

```
// C#
public static bool Equals(OracleTimeStamp value1, OracleTimeStamp value2);
```

Parameters

- *value1*
The first OracleTimeStamp.
- *value2*
The second OracleTimeStamp.

Return Value

Returns true if two OracleTimeStamp values are equal; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStamp` that has a value is greater than an `OracleTimeStamp` that has a null value.
- Two `OracleTimeStamps` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

GreaterThan

This static method determines if the first of two `OracleTimeStamp` values is greater than the second.

Declaration

```
// C#  
public static bool GreaterThan(OracleTimeStamp value1,  
    OracleTimeStamp value2);
```

Parameters

- *value1*
The first `OracleTimeStamp`.
- *value2*
The second `OracleTimeStamp`.

Return Value

Returns `true` if the first of two `OracleTimeStamp` values is greater than the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStamp` that has a value is greater than an `OracleTimeStamp` that has a null value.
- Two `OracleTimeStamps` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

GreaterThanOrEqual

This static method determines if the first of two `OracleTimeStamp` values is greater than or equal to the second.

Declaration

```
// C#  
public static bool GreaterThanOrEqual(OracleTimeStamp value1,  
    OracleTimeStamp value2);
```

Parameters

- *value1*
The first OracleTimeStamp.
- *value2*
The second OracleTimeStamp.

Return Value

Returns true if the first of two OracleTimeStamp values is greater than or equal to the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStamp that has a value is greater than an OracleTimeStamp that has a null value.
- Two OracleTimeStamps that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

LessThan

This static method determines if the first of two OracleTimeStamp values is less than the second.

Declaration

```
// C#  
public static bool LessThan(OracleTimeStamp value1,  
    OracleTimeStamp value2);
```

Parameters

- *value1*
The first OracleTimeStamp.
- *value2*
The second OracleTimeStamp.

Return Value

Returns true if the first of two OracleTimeStamp values is less than the second. Returns false otherwise.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStamp` that has a value is greater than an `OracleTimeStamp` that has a null value.
- Two `OracleTimeStamps` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

LessThanOrEqual

This static method determines if the first of two `OracleTimeStamp` values is less than or equal to the second.

Declaration

```
// C#  
public static bool LessThanOrEqual(OracleTimeStamp value1,  
    OracleTimeStamp value2);
```

Parameters

- *value1*
The first `OracleTimeStamp`.
- *value2*
The second `OracleTimeStamp`.

Return Value

Returns `true` if the first of two `OracleTimeStamp` values is less than or equal to the second. Returns `false` otherwise.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStamp` that has a value is greater than an `OracleTimeStamp` that has a null value.
- Two `OracleTimeStamps` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

NotEquals

This static method determines if two `OracleTimeStamp` values are not equal.

Declaration

```
// C#  
public static bool NotEquals(OracleTimeStamp value1,  
    OracleTimeStamp value2);
```

Parameters

- *value1*
The first OracleTimeStamp.
- *value2*
The second OracleTimeStamp.

Return Value

Returns true if two OracleTimeStamp values are not equal. Returns false otherwise.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStamp that has a value is greater than an OracleTimeStamp that has a null value.
- Two OracleTimeStamps that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

GetSysDate

This static method gets an OracleTimeStamp structure that represents the current date and time.

Declaration

```
// C#  
public static OracleTimeStamp GetSysDate();
```

Return Value

An OracleTimeStamp structure that represents the current date and time.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

Parse

This static method gets an OracleTimeStamp structure and sets its value using the supplied string.

Declaration

```
// C#
public static OracleTimeStamp Parse(string datetime);
```

Parameters

- *datetime*

A string that represents an Oracle `TIMESTAMP`.

Return Value

An `OracleTimeStamp` structure.

Exceptions

`ArgumentException` - The *tsStr* is an invalid string representation of an Oracle `TIMESTAMP` or the supplied *tsStr* is not in the timestamp format specified by the `OracleGlobalization.TimeStampFormat` property of the thread, which represents the Oracle `NLS_TIMESTAMP_FORMAT` parameter.

`ArgumentNullException` - The *tsStr* value is null.

Remarks

The names and abbreviations used for months and days are in the language specified by the `DateLanguage` and `Calendar` properties of the thread's `OracleGlobalization` object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#

using System;
using Oracle.DataAccess.Types;
using Oracle.DataAccess.Client;

class ParseSample
{
    static void Main()
    {
        // Set the nls_timestamp_format for the Parse() method
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.TimeStampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // construct OracleTimeStamp from a string using the format specified.
        OracleTimeStamp ts =
            OracleTimeStamp.Parse("11-NOV-1999 11:02:33.444 AM");

        // Set the nls_timestamp_format for the ToString() method
        info.TimeStampFormat = "YYYY-MON-DD HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // Prints "1999-NOV-11 11:02:33.444000000 AM"
        Console.WriteLine(ts.ToString());
    }
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125

SetPrecision

This static method returns a new instance of an `OracleTimeStamp` with the specified fractional second precision.

Declaration

```
// C#
public static OracleTimeStamp SetPrecision(OracleTimeStamp value1,
    int fracSecPrecision);
```

Parameters

- *value1*
The provided `OracleTimeStamp` object.
- *fracSecPrecision*
The fractional second precision provided. Range of fractional second precision is (0 to 9).

Return Value

An `OracleTimeStamp` structure with the specified fractional second precision.

Exceptions

`ArgumentOutOfRangeException` - *fracSecPrecision* is out of the specified range.

Remarks

The value specified in the supplied *fracSecPrecision* is used to perform a rounding off operation on the supplied `OracleTimeStamp` value. Depending on this value, 0 or more trailing zeros are displayed in the string returned by `ToString()`.

Example

The `OracleTimeStamp` with a value of "December 31, 9999 23:59:59.99" results in the string "December 31, 9999 23:59:59.99000" when `SetPrecision()` is called with the fractional second precision set to 5.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

OracleTimeStamp Static Operators

The OracleTimeStamp static operators are listed in [Table 14–109](#).

Table 14–109 OracleTimeStamp Static Operators

| Operator | Description |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| operator + | Adds the supplied instance value to the supplied OracleTimeStamp and returns a new OracleTimeStamp structure (Overloaded) |
| operator == | Determines if two OracleTimeStamp values are equal |
| operator > | Determines if the first of two OracleTimeStamp values is greater than the second |
| operator >= | Determines if the first of two OracleTimeStamp values is greater than or equal to the second |
| operator != | Determines if the two OracleTimeStamp values are not equal |
| operator < | Determines if the first of two OracleTimeStamp values is less than the second |
| operator <= | Determines if the first of two OracleTimeStamp values is less than or equal to the second |
| operator - | Subtracts the supplied instance value from the supplied OracleTimeStamp and returns a new OracleTimeStamp structure (Overloaded) |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

operator +

`operator+` adds the supplied object to the OracleTimeStamp and returns a new OracleTimeStamp structure.

Overload List:

- [operator + \(OracleTimeStamp, OracleIntervalDS\)](#)
This static operator adds the supplied OracleIntervalDS to the OracleTimeStamp and returns a new OracleTimeStamp structure.
- [operator + \(OracleTimeStamp, OracleIntervalYM\)](#)
This static operator adds the supplied OracleIntervalYM to the supplied OracleTimeStamp and returns a new OracleTimeStamp structure.
- [operator + \(OracleTimeStamp, TimeSpan\)](#)
This static operator adds the supplied TimeSpan to the supplied OracleTimeStamp and returns a new OracleTimeStamp structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

operator + (OracleTimeStamp, OracleIntervalDS)

This static operator adds the supplied `OracleIntervalDS` to the `OracleTimeStamp` and returns a new `OracleTimeStamp` structure.

Declaration

```
// C#  
public static operator + (OracleTimeStamp value1, OracleIntervalDS value2);
```

Parameters

- *value1*
An `OracleTimeStamp`.
- *value2*
An `OracleIntervalDS`.

Return Value

An `OracleTimeStamp`.

Remarks

If either parameter has a null value, the returned `OracleTimeStamp` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

operator + (OracleTimeStamp, OracleIntervalYM)

This static operator adds the supplied `OracleIntervalYM` to the supplied `OracleTimeStamp` and returns a new `OracleTimeStamp` structure.

Declaration

```
// C#  
public static operator + (OracleTimeStamp value1, OracleIntervalYM value2);
```

Parameters

- *value1*
An `OracleTimeStamp`.
- *value2*
An `OracleIntervalYM`.

Return Value

An OracleTimeStamp.

Remarks

If either parameter has a null value, the returned OracleTimeStamp has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

operator + (OracleTimeStamp, TimeSpan)

This static operator adds the supplied TimeSpan to the supplied OracleTimeStamp and returns a new OracleTimeStamp structure.

Declaration

```
// C#  
public static operator + (OracleTimeStamp value1, TimeSpan value2);
```

Parameters

- *value1*
An OracleTimeStamp.
- *value2*
A TimeSpan.

Return Value

An OracleTimeStamp.

Remarks

If the OracleTimeStamp instance has a null value, the returned OracleTimeStamp has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

operator ==

This static operator determines if two OracleTimeStamp values are equal.

Declaration

```
// C#  
public static bool operator == (OracleTimeStamp value1,  
    OracleTimeStamp value2);
```

Parameters

- *value1*
The first OracleTimeStamp.
- *value2*
The second OracleTimeStamp.

Return Value

Returns true if they are the same; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStamp that has a value is greater than an OracleTimeStamp that has a null value.
- Two OracleTimeStamps that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

operator >

This static operator determines if the first of two OracleTimeStamp values is greater than the second.

Declaration

```
// C#
public static bool operator > (OracleTimeStamp value1,
    OracleTimeStamp value2);
```

Parameters

- *value1*
The first OracleTimeStamp.
- *value2*
The second OracleTimeStamp.

Return Value

Returns true if the first OracleTimeStamp value is greater than the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStamp that has a value is greater than an OracleTimeStamp that has a null value.
- Two OracleTimeStamps that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

operator >=

This static operator determines if the first of two `OracleTimeStamp` values is greater than or equal to the second.

Declaration

```
// C#  
public static bool operator >= (OracleTimeStamp value1,  
    OracleTimeStamp value2);
```

Parameters

- *value1*
The first `OracleTimeStamp`.
- *value2*
The second `OracleTimeStamp`.

Return Value

Returns true if the first `OracleTimeStamp` is greater than or equal to the second; otherwise returns false.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStamp` that has a value is greater than an `OracleTimeStamp` that has a null value.
- Two `OracleTimeStamps` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

operator !=

This static operator determines if two `OracleTimeStamp` values are not equal.

Declaration

```
// C#  
public static bool operator != (OracleTimeStamp value1,  
    OracleTimeStamp value2);
```

Parameters

- *value1*

The first OracleTimeStamp.

- *value2*

The second OracleTimeStamp.

Return Value

Returns true if two OracleTimeStamp values are not equal; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStamp that has a value is greater than an OracleTimeStamp that has a null value.
- Two OracleTimeStamps that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

operator <

This static operator determines if the first of two OracleTimeStamp values is less than the second.

Declaration

```
// C#
public static bool operator < (OracleTimeStamp value1,
    OracleTimeStamp value2);
```

Parameters

- *value1*
The first OracleTimeStamp.
- *value2*
The second OracleTimeStamp.

Return Value

Returns true if the first OracleTimeStamp is less than the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStamp that has a value is greater than an OracleTimeStamp that has a null value.
- Two OracleTimeStamps that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

operator <=

This static operator determines if the first of two `OracleTimeStamp` values is less than or equal to the second.

Declaration

```
// C#  
public static bool operator <= (OracleTimeStamp value1,  
    OracleTimeStamp value2);
```

Parameters

- *value1*
The first `OracleTimeStamp`.
- *value2*
The second `OracleTimeStamp`.

Return Value

Returns true if the first `OracleTimeStamp` is less than or equal to the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStamp` that has a value is greater than an `OracleTimeStamp` that has a null value.
- Two `OracleTimeStamps` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

operator -

`operator-` subtracts the supplied value, from the supplied `OracleTimeStamp` value, and returns a new `OracleTimeStamp` structure.

Overload List:

- [operator - \(OracleTimeStamp, OracleIntervalDS\)](#)
This static operator subtracts the supplied `OracleIntervalDS` value, from the supplied `OracleTimeStamp` value, and return a new `OracleTimeStamp` structure.
- [operator - \(OracleTimeStamp, OracleIntervalYM\)](#)

This static operator subtracts the supplied `OracleIntervalYM` value, from the supplied `OracleTimeStamp` value, and returns a new `OracleTimeStamp` structure.

- [operator - \(OracleTimeStamp, TimeSpan\)](#)

This static operator subtracts the supplied `TimeSpan` value, from the supplied `OracleTimeStamp` value, and returns a new `OracleTimeStamp` structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

operator - (OracleTimeStamp, OracleIntervalDS)

This static operator subtracts the supplied `OracleIntervalDS` value, from the supplied `OracleTimeStamp` value, and return a new `OracleTimeStamp` structure.

Declaration

```
// C#  
public static operator - (OracleTimeStamp value1, OracleIntervalDS value2);
```

Parameters

- *value1*
An `OracleTimeStamp`.
- *value2*
An `OracleIntervalDS` instance.

Return Value

An `OracleTimeStamp` structure.

Remarks

If either parameter has a null value, the returned `OracleTimeStamp` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

operator - (OracleTimeStamp, OracleIntervalYM)

This static operator subtracts the supplied `OracleIntervalYM` value, from the supplied `OracleTimeStamp` value, and returns a new `OracleTimeStamp` structure.

Declaration

```
// C#  
public static operator - (OracleTimeStamp value1, OracleIntervalYM value2);
```

Parameters

- *value1*
An OracleTimeStamp.
- *value2*
An OracleIntervalYM instance.

Return Value

An OracleTimeStamp structure.

Remarks

If either parameter has a null value, the returned OracleTimeStamp has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

operator - (OracleTimeStamp, TimeSpan)

This static operator subtracts the supplied TimeSpan value, from the supplied OracleTimeStamp value, and returns a new OracleTimeStamp structure.

Declaration

```
// C#  
public static operator - (OracleTimeStamp value1, TimeSpan value2);
```

Parameters

- *value1*
An OracleTimeStamp.
- *value2*
A TimeSpan instance.

Return Value

An OracleTimeStamp structure.

Remarks

If the OracleTimeStamp instance has a null value, the returned OracleTimeStamp structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

OracleTimeStamp Static Type Conversions

The OracleTimeStamp static type conversions are listed in [Table 14–110](#).

Table 14–110 OracleTimeStamp Static Type Conversions

| Operator | Description |
|---------------------------------------------------|-------------------------------------------------------------------------|
| explicit operator OracleTimeStamp | Converts an instance value to an OracleTimeStamp structure (Overloaded) |
| implicit operator OracleTimeStamp | Converts an instance value to an OracleTimeStamp structure (Overloaded) |
| explicit operator DateTime | Converts an OracleTimeStamp value to a DateTime structure |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

explicit operator OracleTimeStamp

`explicit operator OracleTimeStamp` converts the supplied value to an OracleTimeStamp structure

Overload List:

- [explicit operator OracleTimeStamp\(OracleTimeStampLTZ\)](#)
This static type conversion operator converts an OracleTimeStampLTZ value to an OracleTimeStamp structure.
- [explicit operator OracleTimeStamp\(OracleTimeStampTZ\)](#)
This static type conversion operator converts an OracleTimeStampTZ value to an OracleTimeStamp structure.
- [explicit operator OracleTimeStamp\(string\)](#)
This static type conversion operator converts the supplied string to an OracleTimeStamp structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

explicit operator OracleTimeStamp(OracleTimeStampLTZ)

This static type conversion operator converts an OracleTimeStampLTZ value to an OracleTimeStamp structure.

Declaration

```
// C#
```

```
public static explicit operator OracleTimeStamp(OracleTimeStampLTZ value1);
```

Parameters

- *value1*
An OracleTimeStampLTZ instance.

Return Value

The returned OracleTimeStamp contains the date and time of the OracleTimeStampLTZ structure.

Remarks

If the OracleTimeStampLTZ structure has a null value, the returned OracleTimeStamp structure also has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

explicit operator OracleTimeStamp(OracleTimeStampTZ)

This static type conversion operator converts an OracleTimeStampTZ value to an OracleTimeStamp structure.

Declaration

```
// C#  
public static explicit operator OracleTimeStamp(OracleTimeStampTZ value1);
```

Parameters

- *value1*
An OracleTimeStampTZ instance.

Return Value

The returned OracleTimeStamp contains the date and time information from *value1*, but the time zone information from *value1* is truncated.

Remarks

If the OracleTimeStampTZ structure has a null value, the returned OracleTimeStamp structure also has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

explicit operator OracleTimeStamp(string)

This static type conversion operator converts the supplied string to an OracleTimeStamp structure.

Declaration

```
// C#
public static explicit operator OracleTimeStamp(string tsStr);
```

Parameters

- *tsStr*

A string representation of an Oracle TIMESTAMP.

Return Value

An OracleTimeStamp.

Exceptions

ArgumentException - The *tsStr* is an invalid string representation of an Oracle TIMESTAMP or the *tsStr* is not in the timestamp format specified by the thread's OracleGlobalization.TimeStampFormat property, which represents the Oracle NLS_TIMESTAMP_FORMAT parameter.

Remarks

The names and abbreviations used for months and days are in the language specified by the DateLanguage and Calendar properties of the thread's OracleGlobalization object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#

using System;
using Oracle.DataAccess.Types;
using Oracle.DataAccess.Client;

class OracleTimeStampSample
{
    static void Main()
    {
        // Set the nls_timestamp_format for the explicit
        // operator OracleTimeStamp(string)
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.TimeStampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // construct OracleTimeStamp from a string using the format specified.
        OracleTimeStamp ts = new OracleTimeStamp("11-NOV-1999 11:02:33.444 AM");

        // Set the nls_timestamp_format for the ToString method
        info.TimeStampFormat = "YYYY-MON-DD HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // Prints "1999-NOV-11 11:02:33.444000000 AM"
        Console.WriteLine(ts.ToString());
    }
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125
- *Oracle Database SQL Language Reference* for further information on datetime format elements

implicit operator OracleTimeStamp

This static type conversion operator converts a value to an `OracleTimeStamp` structure.

Overload List:

- [implicit operator OracleTimeStamp\(OracleDate\)](#)

This static type conversion operator converts an `OracleDate` value to an `OracleTimeStamp` structure.
- [implicit operator OracleTimeStamp\(DateTime\)](#)

This static type conversion operator converts a `DateTime` value to an `OracleTimeStamp` structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

implicit operator OracleTimeStamp(OracleDate)

This static type conversion operator converts an `OracleDate` value to an `OracleTimeStamp` structure.

Declaration

```
// C#  
public static implicit operator OracleTimeStamp (OracleDate value1);
```

Parameters

- *value1*

An `OracleDate` instance.

Return Value

An `OracleTimeStamp` structure that contains the date and time of the `OracleDate` structure, *value1*.

Remarks

If the `OracleDate` structure has a null value, the returned `OracleTimeStamp` structure also has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

implicit operator OracleTimeStamp(DateTime)

This static type conversion operator converts a `DateTime` value to an `OracleTimeStamp` structure.

Declaration

```
// C#  
public static implicit operator OracleTimeStamp(DateTime value);
```

Parameters

- *value*
A `DateTime` instance.

Return Value

An `OracleTimeStamp` structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

explicit operator DateTime

This static type conversion operator converts an `OracleTimeStamp` value to a `DateTime` structure.

Declaration

```
// C#  
public static explicit operator DateTime(OracleTimeStamp value1);
```

Parameters

- *value1*
An `OracleTimeStamp` instance.

Return Value

A `DateTime` containing the date and time in the current instance.

Exceptions

`OracleNullValueException` - The `OracleTimeStamp` structure has a null value.

Remarks

The precision of the `OracleTimeStamp` can be lost during the conversion.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

OracleTimeStamp Properties

The OracleTimeStamp properties are listed in [Table 14–111](#).

Table 14–111 OracleTimeStamp Properties

| Properties | Description |
|-----------------------------|------------------------------------------------------------------------------------------------------|
| BinData | Returns an array of bytes that represents an Oracle <code>TIMESTAMP</code> in Oracle internal format |
| Day | Specifies the day component of an OracleTimeStamp |
| IsNull | Indicates whether or not the OracleTimeStamp instance has a null value |
| Hour | Specifies the hour component of an OracleTimeStamp |
| Millisecond | Specifies the millisecond component of an OracleTimeStamp |
| Minute | Specifies the minute component of an OracleTimeStamp |
| Month | Specifies the month component of an OracleTimeStamp |
| Nanosecond | Specifies the nanosecond component of an OracleTimeStamp |
| Second | Specifies the second component of an OracleTimeStamp |
| Value | Specifies the date and time that is stored in the OracleTimeStamp structure |
| Year | Specifies the year component of an OracleTimeStamp |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

BinData

This property returns an array of bytes that represents an Oracle `TIMESTAMP` in Oracle internal format.

Declaration

```
// C#
public byte[] BinData {get;}
```

Property Value

A byte array that represents an Oracle `TIMESTAMP` in an internal format.

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

Day

This property specifies the day component of an `OracleTimeStamp`.

Declaration

```
// C#  
public int Day{get;}
```

Property Value

A number that represents the day. Range of `Day` is (1 to 31).

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

IsNull

This property indicates whether or not the current instance has a null value.

Declaration

```
// C#  
public bool IsNull{get;}
```

Property Value

Returns `true` if the current instance has a null value; otherwise, returns `false`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

Hour

This property specifies the hour component of an `OracleTimeStamp`.

Declaration

```
// C#  
public int Hour{get;}
```


Property Value

A number that represents the hour. Range of hour is (0 to 23).

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

Millisecond

This property gets the millisecond component of an `OracleTimeStamp`.

Declaration

```
// C#  
public double Millisecond{get;}
```

Property Value

A number that represents a millisecond. Range of `Millisecond` is (0 to 999.999999).

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

Minute

This property gets the minute component of an `OracleTimeStamp`.

Declaration

```
// C#  
public int Minute{get;}
```

Property Value

A number that represent a minute. Range of `Minute` is (0 to 59).

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

Month

This property gets the month component of an `OracleTimeStamp`.

Declaration

```
// C#  
public int Month{get;}
```

Property Value

A number that represents a month. Range of `Month` is (1 to 12).

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

Nanosecond

This property gets the nanosecond component of an `OracleTimeStamp`.

Declaration

```
// C#  
public int Nanosecond{get;}
```

Property Value

A number that represents a nanosecond. Range of `Nanosecond` is (0 to 999999999).

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

Second

This property gets the second component of an `OracleTimeStamp`.

Declaration

```
// C#
public int Second{get;}
```

Property Value

A number that represents a second. Range of Second is (0 to 59).

Exceptions

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

Value

This property specifies the date and time that is stored in the OracleTimeStamp structure.

Declaration

```
// C#
public DateTime Value{get;}
```

Property Value

A DateTime.

Exceptions

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

Year

This property gets the year component of an OracleTimeStamp.

Declaration

```
// C#
public int Year{get;}
```

Property Value

A number that represents a year. The range of Year is (-4712 to 9999).

Exceptions

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

OracleTimeStamp Methods

The OracleTimeStamp methods are listed in [Table 14–112](#).

Table 14–112 OracleTimeStamp Methods

| Methods | Description |
|--------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AddDays | Adds the supplied number of days to the current instance |
| AddHours | Adds the supplied number of hours to the current instance |
| AddMilliseconds | Adds the supplied number of milliseconds to the current instance |
| AddMinutes | Adds the supplied number of minutes to the current instance |
| AddMonths | Adds the supplied number of months to the current instance |
| AddNanoseconds | Adds the supplied number of nanoseconds to the current instance |
| AddSeconds | Adds the supplied number of seconds to the current instance |
| AddYears | Adds the supplied number of years to the current instance |
| CompareTo | Compares the current OracleTimeStamp instance to an object, and returns an integer that represents their relative values |
| Equals | Determines whether or not an object has the same date and time as the current OracleTimeStamp instance (Overloaded) |
| GetHashCode | Returns a hash code for the OracleTimeStamp instance |
| GetDaysBetween | Subtracts an OracleTimeStamp value from the current instance and returns an OracleIntervalDS that represents the time difference between the supplied OracleTimeStamp and the current instance |
| GetYearsBetween | Subtracts value1 from the current instance and returns an OracleIntervalYM that represents the difference between value1 and the current instance using OracleIntervalYM |
| GetType | Inherited from System.Object |
| ToOracleDate | Converts the current OracleTimeStamp structure to an OracleDate structure |
| ToOracleTimeStampLTZ | Converts the current OracleTimeStamp structure to an OracleTimeStampLTZ structure |
| ToOracleTimeStampTZ | Converts the current OracleTimeStamp structure to an OracleTimeStampTZ structure |
| ToString | Converts the current OracleTimeStamp structure to a string |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

AddDays

This method adds the supplied number of days to the current instance.

Declaration

```
// C#  
public OracleTimeStamp AddDays(double days);
```

Parameters

- *days*

The supplied number of days. Range is $(-1,000,000,000 < days < 1,000,000,000)$

Return Value

An OracleTimeStamp.

Exceptions

ArgumentOutOfRangeException - The argument value is out of the specified range.

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

AddHours

This method adds the supplied number of hours to the current instance.

Declaration

```
// C#  
public OracleTimeStamp AddHours(double hours);
```

Parameters

- *hours*

The supplied number of hours. Range is $(-24,000,000,000 < hours < 24,000,000,000)$.

Return Value

An OracleTimeStamp.

Exceptions

ArgumentOutOfRangeException - The argument value is out of the specified range.

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

AddMilliseconds

This method adds the supplied number of milliseconds to the current instance.

Declaration

```
// C#  
public OracleTimeStamp AddMilliseconds(double milliseconds);
```

Parameters

- *milliseconds*

The supplied number of milliseconds. Range is $(-8.64 * 1016 < milliseconds < 8.64 * 1016)$.

Return Value

An OracleTimeStamp.

Exceptions

ArgumentOutOfRangeException - The argument value is out of the specified range.

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

AddMinutes

This method adds the supplied number of minutes to the current instance.

Declaration

```
// C#  
public OracleTimeStamp AddMinutes(double minutes);
```

Parameters

- *minutes*

The supplied number of minutes. Range is $(-1,440,000,000,000 < minutes < 1,440,000,000,000)$.

Return Value

An OracleTimeStamp.

Exceptions

ArgumentOutOfRangeException - The argument value is out of the specified range.

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

AddMonths

This method adds the supplied number of months to the current instance.

Declaration

```
// C#  
public OracleTimeStamp AddMonths(long months);
```

Parameters

- *months*
The supplied number of months. Range is $(-12,000,000,000 < months < 12,000,000,000)$.

Return Value

An OracleTimeStamp.

Exceptions

ArgumentOutOfRangeException - The argument value is out of the specified range.

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

AddNanoseconds

This method adds the supplied number of nanoseconds to the current instance.

Declaration

```
// C#  
public OracleTimeStamp AddNanoseconds(long nanoseconds);
```

Parameters

- *nanoseconds*
The supplied number of nanoseconds.

Return Value

An OracleTimeStamp.

Exceptions

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

AddSeconds

This method adds the supplied number of seconds to the current instance.

Declaration

```
// C#  
public OracleTimeStamp AddSeconds(double seconds);
```

Parameters

- *seconds*

The supplied number of seconds. Range is $(-8.64 * 1013 < \text{seconds} < 8.64 * 1013)$.

Return Value

An `OracleTimeStamp`.

Exceptions

`ArgumentOutOfRangeException` - The argument value is out of the specified range.

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

AddYears

This method adds the supplied number of years to the current instance.

Declaration

```
// C#  
public OracleTimeStamp AddYears(int years);
```

Parameters

- *years*

The supplied number of years. Range is $(-999,999,999 \leq \text{years} \leq 999,999,999)$

Return Value

An `OracleTimeStamp`.

Exceptions

`ArgumentOutOfRangeException` - The argument value is out of the specified range.

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

CompareTo

This method compares the current `OracleTimeStamp` instance to an object, and returns an integer that represents their relative values.

Declaration

```
// C#  
public int CompareTo(object obj);
```

Parameters

- *obj*

The object being compared to the current `OracleTimeStamp` instance.

Return Value

The method returns a number that is:

Less than zero: if the current `OracleTimeStamp` instance value is less than that of *obj*.

Zero: if the current `OracleTimeStamp` instance and *obj* values are equal.

Greater than zero: if the current `OracleTimeStamp` instance value is greater than that of *obj*.

Implements

`IComparable`

Exceptions

`ArgumentException` - The *obj* parameter is not of type `OracleTimeStamp`.

Remarks

The following rules apply to the behavior of this method.

- The comparison must be between `OracleTimeStamps`. For example, comparing an `OracleTimeStamp` instance with an `OracleBinary` instance is not allowed. When an `OracleTimeStamp` is compared with a different type, an `ArgumentException` is thrown.
- Any `OracleTimeStamp` that has a value is greater than an `OracleTimeStamp` that has a null value.
- Two `OracleTimeStamps` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

Equals

Overrides `Object`

This method determines whether or not an object has the same date and time as the current `OracleTimeStamp` instance.

Declaration

```
// C#
public override bool Equals(object obj);
```

Parameters

- *obj*

The object being compared to the current OracleTimeStamp instance.

Return Value

Returns true if the *obj* is of type OracleTimeStamp and represents the same date and time; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStamp that has a value is greater than an OracleTimeStamp that has a null value.
- Two OracleTimeStamps that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

GetHashCode

Overrides Object

This method returns a hash code for the OracleTimeStamp instance.

Declaration

```
// C#
public override int GetHashCode();
```

Return Value

A number that represents the hash code.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

GetDaysBetween

This method subtracts an OracleTimeStamp value from the current instance and returns an OracleIntervalDS that represents the time difference between the supplied OracleTimeStamp structure and the current instance.

Declaration

```
// C#
```

```
public OracleIntervalDS GetDaysBetween(OracleTimeStamp value1);
```

Parameters

- *value1*

The OracleTimeStamp value being subtracted.

Return Value

An OracleIntervalDS that represents the interval between two OracleTimeStamp values.

Remarks

If either the current instance or the parameter has a null value, the returned OracleIntervalDS has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

GetYearsBetween

This method subtracts an OracleTimeStamp value from the current instance and returns an OracleIntervalYM that represents the time difference between the OracleTimeStamp value and the current instance.

Declaration

```
// C#  
public OracleIntervalYM GetYearsBetween(OracleTimeStamp value1);
```

Parameters

- *value1*

The OracleTimeStamp value being subtracted.

Return Value

An OracleIntervalYM that represents the interval between two OracleTimeStamp values.

Remarks

If either the current instance or the parameter has a null value, the returned OracleIntervalYM has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

ToOracleDate

This method converts the current `OracleTimeStamp` structure to an `OracleDate` structure.

Declaration

```
// C#  
public OracleDate ToOracleDate();
```

Return Value

The returned `OracleDate` contains the date and time in the current instance.

Remarks

The precision of the `OracleTimeStamp` value can be lost during the conversion.

If the value of the `OracleTimeStamp` has a null value, the value of the returned `OracleDate` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

ToOracleTimeStampLTZ

This method converts the current `OracleTimeStamp` structure to an `OracleTimeStampLTZ` structure.

Declaration

```
// C#  
public OracleTimeStampLTZ ToOracleTimeStampLTZ();
```

Return Value

The returned `OracleTimeStampLTZ` contains date and time in the current instance.

Remarks

If the value of the current instance has a null value, the value of the returned `OracleTimeStampLTZ` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)

ToOracleTimeStampTZ

This method converts the current `OracleTimeStamp` structure to an `OracleTimeStampTZ` structure.

Declaration

```
// C#
```

```
public OracleTimeStampTZ ToOracleTimeStampTZ();
```

Return Value

The returned `OracleTimeStampTZ` contains the date and time from the `OracleTimeStamp` and the time zone from the `OracleGlobalization.TimeZone` of the thread.

Remarks

If the value of the current instance has a null value, the value of the returned `OracleTimeStampTZ` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125

ToString

Overrides `Object`

This method converts the current `OracleTimeStamp` structure to a string.

Declaration

```
// C#  
public override string ToString();
```

Return Value

A string that represents the same date and time as the current `OracleTimeStamp` structure.

Remarks

The returned value is a string representation of an `OracleTimeStamp` in the format specified by the `OracleGlobalization.TimeStampFormat` property of the thread.

The names and abbreviations used for months and days are in the language specified by the `OracleGlobalization's DateLanguage` and `Calendar` properties of the thread. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Types;  
using Oracle.DataAccess.Client;  
  
class ToStringSample  
{  
    static void Main()  
    {
```

```
// Set the nls_timestamp_format for the OracleTimeStamp(string)
// constructor
OracleGlobalization info = OracleGlobalization.GetClientInfo();
info.TimeStampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
OracleGlobalization.SetThreadInfo(info);

// construct OracleTimeStamp from a string using the format specified.
OracleTimeStamp ts = new OracleTimeStamp("11-NOV-1999 11:02:33.444 AM");

// Set the nls_timestamp_format for the ToString() method
info.TimeStampFormat = "YYYY-MON-DD HH:MI:SS.FF AM";
OracleGlobalization.SetThreadInfo(info);

// Prints "1999-NOV-11 11:02:33.444000000 AM"
Console.WriteLine(ts.ToString());
}
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStamp Structure](#)
- [OracleTimeStamp Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125

OracleTimeStampLTZ Structure

The `OracleTimeStampLTZ` structure represents the Oracle `TIMESTAMP WITH LOCAL TIME ZONE` data type to be stored in or retrieved from a database. Each `OracleTimeStampLTZ` stores the following information: year, month, day, hour, minute, second, and nanosecond.

Class Inheritance

`System.Object`

`System.ValueType`

`Oracle.DataAccess.Types.OracleTimeStampLTZ`

Declaration

```
// C#
public struct OracleTimeStampLTZ : IComparable, INullable, IXmlSerializable
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|-----------------------|--------------------------------------|---------------------------------------------|
| Assembly | <code>Oracle.DataAccess.dll</code> | <code>Oracle.ManagedDataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Types</code> | <code>Oracle.ManagedDataAccess.Types</code> |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#

using System;
using Oracle.DataAccess.Types;
using Oracle.DataAccess.Client;

class OracleTimeStampLTZSample
{
    static void Main()
    {
        // Illustrates usage of OracleTimeStampLTZ
        // Display Local Time Zone Name
        Console.WriteLine("Local Time Zone Name = " +
            OracleTimeStampLTZ.GetLocalTimeZoneName());
        OracleTimeStampLTZ tsLocal1 = OracleTimeStampLTZ.GetSysDate();
        OracleTimeStampLTZ tsLocal2 = DateTime.Now;

        // Calculate the difference between tsLocal1 and tsLocal2
        OracleIntervalDS idsDiff = tsLocal2.GetDaysBetween(tsLocal1);

        // Calculate the difference using AddNanoseconds()
        int nanoDiff = 0;
        while (tsLocal2 > tsLocal1)
```



```
{
    nanoDiff += 10;
    tsLocal1 = tsLocal1.AddNanoseconds(10);
}
Console.WriteLine("idsDiff.Nanoseconds = " + idsDiff.Nanoseconds);
Console.WriteLine("nanoDiff = " + nanoDiff);
}
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleTimeStampLTZ Members](#)
- [OracleTimeStampLTZ Constructors](#)
- [OracleTimeStampLTZ Static Fields](#)
- [OracleTimeStampLTZ Static Methods](#)
- [OracleTimeStampLTZ Static Operators](#)
- [OracleTimeStampLTZ Static Type Conversions](#)
- [OracleTimeStampLTZ Properties](#)
- [OracleTimeStampLTZ Methods](#)

OracleTimeStampLTZ Members

OracleTimeStampLTZ members are listed in the following tables:

OracleTimeStampLTZ Constructors

OracleTimeStampLTZ constructors are listed in [Table 14–113](#)

Table 14–113 OracleTimeStampLTZConstructors

| Constructor | Description |
|-------------------------------------------------|--------------------------------------------------------------------------|
| OracleTimeStampLTZ Constructors | Instantiates a new instance of OracleTimeStampLTZ structure (Overloaded) |

OracleTimeStampLTZ Static Fields

The OracleTimeStampLTZ static fields are listed in [Table 14–114](#).

Table 14–114 OracleTimeStampLTZ Static Fields

| Field | Description |
|--------------------------|----------------------------------------------------------------------------------------------------------------------|
| MaxValue | Represents the maximum valid date for an OracleTimeStampLTZ structure, which is December 31, 9999 23:59:59.999999999 |
| MinValue | Represents the minimum valid date for an OracleTimeStampLTZ structure, which is January 1, -4712 0:0:0 |
| Null | Represents a null value that can be assigned to an instance of the OracleTimeStampLTZ structure |

OracleTimeStampLTZ Static Methods

The OracleTimeStampLTZ static methods are listed in [Table 14–115](#).

Table 14–115 OracleTimeStampLTZ Static Methods

| Methods | Description |
|----------------------------------------|-------------------------------------------------------------------------------------------------|
| Equals | Determines if two OracleTimeStampLTZ values are equal (Overloaded) |
| GetLocalTimeZoneName | Gets the client's local time zone name |
| GetLocalTimeZoneOffset | Gets the client's local time zone offset relative to UTC |
| GetSysDate | Gets an OracleTimeStampLTZ structure that represents the current date and time |
| GreaterThan | Determines if the first of two OracleTimeStampLTZ values is greater than the second |
| GreaterThanOrEqual | Determines if the first of two OracleTimeStampLTZ values is greater than or equal to the second |
| LessThan | Determines if the first of two OracleTimeStampLTZ values is less than the second |
| LessThanOrEqual | Determines if the first of two OracleTimeStampLTZ values is less than or equal to the second |
| NotEquals | Determines if two OracleTimeStampLTZ values are not equal |

Table 14–115 (Cont.) OracleTimeStampLTZ Static Methods

| Methods | Description |
|------------------------------|-----------------------------------------------------------------------------------------------------|
| Parse | Gets an OracleTimeStampLTZ structure and sets its value for date and time using the supplied string |
| SetPrecision | Returns a new instance of an OracleTimeStampLTZ with the specified fractional second precision |

OracleTimeStampLTZ Static Operators

The OracleTimeStampLTZ static operators are listed in [Table 14–116](#).

Table 14–116 OracleTimeStampLTZ Static Operators

| Operator | Description |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| operator + | Adds the supplied instance value to the supplied OracleTimeStampLTZ and returns a new OracleTimeStampLTZ structure (Overloaded) |
| operator == | Determines if two OracleTimeStampLTZ values are equal |
| operator > | Determines if the first of two OracleTimeStampLTZ values is greater than the second |
| operator >= | Determines if the first of two OracleTimeStampLTZ values is greater than or equal to the second |
| operator != | Determines if two OracleTimeStampLTZ values are not equal |
| operator < | Determines if the first of two OracleTimeStampLTZ values is less than the second |
| operator <= | Determines if the first of two OracleTimeStampLTZ values is less than or equal to the second |
| operator - | Subtracts the supplied instance value from the supplied OracleTimeStampLTZ and returns a new OracleTimeStampLTZ structure (Overloaded) |

OracleTimeStampLTZ Static Type Conversions

The OracleTimeStampLTZ static type conversions are listed in [Table 14–117](#).

Table 14–117 OracleTimeStampLTZ Static Type Conversions

| Operator | Description |
|------------------------------------------------------|----------------------------------------------------------------------------|
| explicit operator OracleTimeStampLTZ | Converts an instance value to an OracleTimeStampLTZ structure (Overloaded) |
| implicit operator OracleTimeStampLTZ | Converts an instance value to an OracleTimeStampLTZ structure (Overloaded) |
| explicit operator DateTime | Converts an OracleTimeStampLTZ value to a DateTime structure |

OracleTimeStampLTZ Properties

The OracleTimeStampLTZ properties are listed in [Table 14–118](#).

Table 14–118 OracleTimeStampLTZ Properties

| Properties | Description |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------|
| BinData | Returns an array of bytes that represents an Oracle <code>TIMESTAMP WITH LOCAL TIME ZONE</code> in Oracle internal format |
| Day | Specifies the day component of an <code>OracleTimeStampLTZ</code> |
| IsNull | Indicates whether or not the <code>OracleTimeStampLTZ</code> instance has a null value |
| Hour | Specifies the hour component of an <code>OracleTimeStampLTZ</code> |
| Millisecond | Specifies the millisecond component of an <code>OracleTimeStampLTZ</code> |
| Minute | Specifies the minute component of an <code>OracleTimeStampLTZ</code> |
| Month | Specifies the month component of an <code>OracleTimeStampLTZ</code> |
| Nanosecond | Specifies the nanosecond component of an <code>OracleTimeStampLTZ</code> |
| Second | Specifies the second component of an <code>OracleTimeStampLTZ</code> |
| Value | Specifies the date and time that is stored in the <code>OracleTimeStampLTZ</code> structure |
| Year | Specifies the year component of an <code>OracleTimeStampLTZ</code> |

OracleTimeStampLTZ Methods

The `OracleTimeStampLTZ` methods are listed in [Table 14–119](#).

Table 14–119 OracleTimeStampLTZ Methods

| Methods | Description |
|---------------------------------|------------------------------------------------------------------|
| AddDays | Adds the supplied number of days to the current instance |
| AddHours | Adds the supplied number of hours to the current instance |
| AddMilliseconds | Adds the supplied number of milliseconds to the current instance |
| AddMinutes | Adds the supplied number of minutes to the current instance |
| AddMonths | Adds the supplied number of months to the current instance |
| AddNanoseconds | Adds the supplied number of nanoseconds to the current instance |
| AddSeconds | Adds the supplied number of seconds to the current instance |
| AddYears | Adds the supplied number of years to the current instance |

Table 14–119 (Cont.) OracleTimeStampLTZ Methods

| Methods | Description |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| CompareTo | Compares the current <code>OracleTimeStampLTZ</code> instance to an object and returns an integer that represents their relative values |
| Equals | Determines whether or not an object has the same date and time as the current <code>OracleTimeStampLTZ</code> instance (Overloaded) |
| GetHashCode | Returns a hash code for the <code>OracleTimeStampLTZ</code> instance |
| GetDaysBetween | Subtracts an <code>OracleTimeStampLTZ</code> from the current instance and returns an <code>OracleIntervalDS</code> that represents the difference |
| GetYearsBetween | Subtracts an <code>OracleTimeStampLTZ</code> from the current instance and returns an <code>OracleIntervalYM</code> that represents the difference |
| GetType | Inherited from <code>System.Object</code> |
| ToOracleDate | Converts the current <code>OracleTimeStampLTZ</code> structure to an <code>OracleDate</code> structure |
| ToOracleTimeStamp | Converts the current <code>OracleTimeStampLTZ</code> structure to an <code>OracleTimeStamp</code> structure |
| ToOracleTimeStampTZ | Converts the current <code>OracleTimeStampLTZ</code> structure to an <code>OracleTimeStampTZ</code> structure |
| ToString | Converts the current <code>OracleTimeStampLTZ</code> structure to a string |
| ToUniversalTime | Converts the current local time to Coordinated Universal Time (UTC) |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)

OracleTimeStampLTZ Constructors

The `OracleTimeStampLTZ` constructors create new instances of the `OracleTimeStampLTZ` structure.

Overload List:

- [OracleTimeStampLTZ\(DateTime\)](#)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date and time using the supplied `DateTime` value.
- [OracleTimeStampLTZ\(string\)](#)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date and time using the supplied string.
- [OracleTimeStampLTZ\(int, int, int\)](#)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date using year, month, and day.
- [OracleTimeStampLTZ\(int, int, int, int, int, int\)](#)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date and time using year, month, day, hour, minute, and second.
- [OracleTimeStampLTZ\(int, int, int, int, int, int, double\)](#)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and millisecond.
- [OracleTimeStampLTZ\(int, int, int, int, int, int, int\)](#)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and nanosecond.
- [OracleTimeStampLTZ\(byte \[\]\)](#)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value to the provided byte array, which is in the internal Oracle `TIMESTAMP WITH LOCAL TIME ZONE` format.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

OracleTimeStampLTZ(DateTime)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date and time using the supplied `DateTime` value.

Declaration

```
// C#  
public OracleTimeStampLTZ (DateTime dt);
```

Parameters

- *dt*
The supplied DateTime value.

Exceptions

ArgumentException - The *dt* parameter cannot be used to construct a valid OracleTimeStampLTZ.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

OracleTimeStampLTZ(string)

This constructor creates a new instance of the OracleTimeStampLTZ structure and sets its value for date and time using the supplied string.

Declaration

```
// C#
public OracleTimeStampLTZ(string tsStr);
```

Parameters

- *tsStr*
A string that represents an Oracle TIMESTAMP WITH LOCAL TIME ZONE.

Exceptions

ArgumentException - The *tsStr* is an invalid string representation of an Oracle TIMESTAMP WITH LOCAL TIME ZONE or the supplied *tsStr* is not in the timestamp format specified by the OracleGlobalization.TimeStampFormat property of the thread, which represents the Oracle NLS_TIMESTAMP_FORMAT parameter.

ArgumentNullException - The *tsStr* value is null.

Remarks

The names and abbreviations used for months and days are in the language specified by the DateLanguage and Calendar properties of the thread's OracleGlobalization object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class OracleTimeStampLTZSample
{
    static void Main()
    {
        // Set the nls_timestamp_format for the OracleTimeStampLTZ(string)
```

```
// constructor
OracleGlobalization info = OracleGlobalization.GetClientInfo();
info.TimeStampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
OracleGlobalization.SetThreadInfo(info);

// construct OracleTimeStampLTZ from a string using the format
// specified.
OracleTimeStampLTZ ts =
    new OracleTimeStampLTZ("11-NOV-1999 11:02:33.444 AM");

// Set the nls_timestamp_format for the ToString() method
info.TimeStampFormat = "YYYY-MON-DD HH:MI:SS.FF AM";
OracleGlobalization.SetThreadInfo(info);

// Prints "1999-NOV-11 11:02:33.444000000 AM"
Console.WriteLine(ts.ToString());
}
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125
- *Oracle Database SQL Language Reference* for further information on date format elements

OracleTimeStampLTZ(int, int, int)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date using year, month, and day.

Declaration

```
// C#
public OracleTimeStampLTZ(int year, int month, int day);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).
- *month*
The month provided. Range of *month* is (1 to 12).
- *day*
The day provided. Range of *day* is (1 to 31).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampLTZ` (that is, the day is out of range for the month).

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

OracleTimeStampLTZ(int, int, int, int, int)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date and time using year, month, day, hour, minute, and second.

Declaration

```
// C#
public OracleTimeStampLTZ (int year, int month, int day, int hour,
    int minute, int second);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).
- *month*
The month provided. Range of *month* is (1 to 12).
- *day*
The day provided. Range of *day* is (1 to 31).
- *hour*
The hour provided. Range of *hour* is (0 to 23).
- *minute*
The minute provided. Range of *minute* is (0 to 59).
- *second*
The second provided. Range of *second* is (0 to 59).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampLTZ` (that is, the day is out of range for the month).

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

OracleTimeStampLTZ(int, int, int, int, int, int, double)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and millisecond.

Declaration

```
// C#  
public OracleTimeStampLTZ(int year, int month, int day, int hour, int minute, int second, double millisecond);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).
- *month*
The month provided. Range of *month* is (1 to 12).
- *day*
The day provided. Range of *day* is (1 to 31).
- *hour*
The hour provided. Range of *hour* is (0 to 23).
- *minute*
The minute provided. Range of *minute* is (0 to 59).
- *second*
The second provided. Range of *second* is (0 to 59).
- *milliSeconds*
The milliseconds provided. Range of *millisecond* is (0 to 999.999999).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampLTZ` (that is, the day is out of range for the month).

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

OracleTimeStampLTZ(int, int, int, int, int, int)

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and nanosecond.

Declaration

```
// C#
public OracleTimeStampLTZ (int year, int month, int day, int hour,
    int minute, int second, int nanosecond);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).
- *month*
The month provided. Range of *month* is (1 to 12).
- *day*
The day provided. Range of *day* is (1 to 31).
- *hour*
The hour provided. Range of *hour* is (0 to 23).
- *minute*
The minute provided. Range of *minute* is (0 to 59).
- *second*
The second provided. Range of *second* is (0 to 59).
- *nanosecond*
The nanosecond provided. Range of *nanosecond* is (0 to 999999999).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampLTZ` (that is, the day is out of range for the month).

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

OracleTimeStampLTZ(byte [])

This constructor creates a new instance of the `OracleTimeStampLTZ` structure and sets its value to the provided byte array, which is in the internal Oracle `TIMESTAMP WITH LOCAL TIME ZONE` format.

Declaration

```
// C#
public OracleTimeStampLTZ (byte[] bytes);
```

Parameters

- *bytes*

A byte array that represents an Oracle `TIMESTAMP WITH LOCAL TIME ZONE` in Oracle internal format.

Exceptions

`ArgumentException` - *bytes* is not in an internal Oracle `TIMESTAMP WITH LOCAL TIME ZONE` format or *bytes* is not a valid Oracle `TIMESTAMP WITH LOCAL TIME ZONE`.

`ArgumentNullException` - *bytes* is null.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

OracleTimeStampLTZ Static Fields

The OracleTimeStampLTZ static fields are listed in [Table 14–120](#).

Table 14–120 OracleTimeStampLTZ Static Fields

| Field | Description |
|--------------------------|----------------------------------------------------------------------------------------------------------------------|
| MaxValue | Represents the maximum valid date for an OracleTimeStampLTZ structure, which is December 31, 9999 23:59:59.999999999 |
| MinValue | Represents the minimum valid date for an OracleTimeStampLTZ structure, which is January 1, -4712 0:0:0 |
| Null | Represents a null value that can be assigned to an instance of the OracleTimeStampLTZ structure |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

MaxValue

This static field represents the maximum valid date for an OracleTimeStampLTZ structure, which is December 31, 9999 23:59:59.999999999.

Declaration

```
// C#
public static readonly OracleTimeStampLTZ MaxValue;
```

Remarks

This value is the maximum date and time in the client time zone.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

MinValue

This static field represents the minimum valid date for an OracleTimeStampLTZ structure, which is January 1, -4712 0:0:0.

Declaration

```
// C#
public static readonly OracleTimeStampLTZ MinValue;
```

Remarks

This value is the minimum date and time in the client time zone.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

Null

This static field represents a null value that can be assigned to an instance of the `OracleTimeStampLTZ` structure.

Declaration

```
// C#  
public static readonly OracleTimeStampLTZ Null;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

OracleTimeStampLTZ Static Methods

The OracleTimeStampLTZ static methods are listed in [Table 14–121](#).

Table 14–121 OracleTimeStampLTZ Static Methods

| Methods | Description |
|----------------------------------------|-----------------------------------------------------------------------------------------------------|
| Equals | Determines if two OracleTimeStampLTZ values are equal (Overloaded) |
| GetLocalTimeZoneName | Gets the client's local time zone name |
| GetLocalTimeZoneOffset | Gets the client's local time zone offset relative to UTC |
| GetSysDate | Gets an OracleTimeStampLTZ structure that represents the current date and time |
| GreaterThan | Determines if the first of two OracleTimeStampLTZ values is greater than the second |
| GreaterThanOrEqual | Determines if the first of two OracleTimeStampLTZ values is greater than or equal to the second |
| LessThan | Determines if the first of two OracleTimeStampLTZ values is less than the second |
| LessThanOrEqual | Determines if the first of two OracleTimeStampLTZ values is less than or equal to the second |
| NotEquals | Determines if two OracleTimeStampLTZ values are not equal |
| Parse | Gets an OracleTimeStampLTZ structure and sets its value for date and time using the supplied string |
| SetPrecision | Returns a new instance of an OracleTimeStampLTZ with the specified fractional second precision |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

Equals

This static method determines if two OracleTimeStampLTZ values are equal.

Declaration

```
// C#
public static bool Equals(OracleTimeStampLTZ value1,
    OracleTimeStampLTZ value2);
```

Parameters

- *value1*
The first OracleTimeStampLTZ.
- *value2*
The second OracleTimeStampLTZ.

Return Value

Returns true if two OracleTimeStampLTZ values are equal. Returns false otherwise.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStampLTZ that has a value is greater than an OracleTimeStampLTZ that has a null value.
- Two OracleTimeStampLTZs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

GetLocalTimeZoneName

This static method gets the client's local time zone name.

Declaration

```
// C#  
public static string GetLocalTimeZoneName();
```

Return Value

A string containing the local time zone.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

GetLocalTimeZoneOffset

This static method gets the client's local time zone offset relative to Coordinated Universal Time (UTC).

Declaration

```
// C#  
public static TimeSpan GetLocalTimeZoneOffset( );
```

Return Value

A TimeSpan structure containing the local time zone hours and time zone minutes.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

GetSysDate

This static method gets an `OracleTimeStampLTZ` structure that represents the current date and time.

Declaration

```
// C#  
public static OracleTimeStampLTZ GetSysDate();
```

Return Value

An `OracleTimeStampLTZ` structure that represents the current date and time.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

GreaterThan

This static method determines if the first of two `OracleTimeStampLTZ` values is greater than the second.

Declaration

```
// C#  
public static bool GreaterThan(OracleTimeStampLTZ value1,  
    OracleTimeStampLTZ value2);
```

Parameters

- *value1*
The first `OracleTimeStampLTZ`.
- *value2*
The second `OracleTimeStampLTZ`.

Return Value

Returns true if the first of two `OracleTimeStampLTZ` values is greater than the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampLTZ` that has a value is greater than an `OracleTimeStampLTZ` that has a null value.
- Two `OracleTimeStampLTZ`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

GreaterThanOrEqualTo

This static method determines if the first of two `OracleTimeStampLTZ` values is greater than or equal to the second.

Declaration

```
// C#
public static bool GreaterThanOrEqualTo(OracleTimeStampLTZ value1,
    OracleTimeStampLTZ value2);
```

Parameters

- *value1*
The first `OracleTimeStampLTZ`.
- *value2*
The second `OracleTimeStampLTZ`.

Return Value

Returns `true` if the first of two `OracleTimeStampLTZ` values is greater than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampLTZ` that has a value is greater than an `OracleTimeStampLTZ` that has a null value.
- Two `OracleTimeStampLTZ`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

LessThan

This static method determines if the first of two `OracleTimeStampLTZ` values is less than the second.

Declaration

```
// C#
public static bool LessThan(OracleTimeStampLTZ value1,
    OracleTimeStampLTZ value2);
```

Parameters

- *value1*
The first `OracleTimeStampLTZ`.
- *value2*
The second `OracleTimeStampLTZ`.

Return Value

Returns true if the first of two OracleTimeStampLTZ values is less than the second. Returns false otherwise.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStampLTZ that has a value is greater than an OracleTimeStampLTZ that has a null value.
- Two OracleTimeStampLTZs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

LessThanOrEqual

This static method determines if the first of two OracleTimeStampLTZ values is less than or equal to the second.

Declaration

```
// C#
public static bool LessThanOrEqual(OracleTimeStampLTZ value1,
    OracleTimeStampLTZ value2);
```

Parameters

- *value1*
The first OracleTimeStampLTZ.
- *value2*
The second OracleTimeStampLTZ.

Return Value

Returns true if the first of two OracleTimeStampLTZ values is less than or equal to the second. Returns false otherwise.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStampLTZ that has a value is greater than an OracleTimeStampLTZ that has a null value.
- Two OracleTimeStampLTZs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

NotEquals

This static method determines if two `OracleTimeStampLTZ` values are not equal.

Declaration

```
// C#  
public static bool NotEquals(OracleTimeStampLTZ value1,  
    OracleTimeStampLTZ value2);
```

Parameters

- *value1*
The first `OracleTimeStampLTZ`.
- *value2*
The second `OracleTimeStampLTZ`.

Return Value

Returns true if two `OracleTimeStampLTZ` values are not equal. Returns false otherwise.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampLTZ` that has a value is greater than an `OracleTimeStampLTZ` that has a null value.
- Two `OracleTimeStampLTZ`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

Parse

This static method creates an `OracleTimeStampLTZ` structure and sets its value using the supplied string.

Declaration

```
// C#  
public static OracleTimeStampLTZ Parse(string tsStr);
```

Parameters

- *tsStr*
A string that represents an Oracle `TIMESTAMP WITH LOCAL TIME ZONE`.

Return Value

An `OracleTimeStampLTZ` structure.

Exceptions

`ArgumentException` - The *tsStr* parameter is an invalid string representation of an Oracle `TIMESTAMP WITH LOCAL TIME ZONE` or the *tsStr* is not in the timestamp format

specified by the `OracleGlobalization.TimeStampFormat` property of the thread, which represents the Oracle `NLS_TIMESTAMP_FORMAT` parameter.

`ArgumentNullException` - The `tsStr` value is null.

Remarks

The names and abbreviations used for months and days are in the language specified by the `DateLanguage` and `Calendar` properties of the thread's `OracleGlobalization` object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#

using System;
using Oracle.DataAccess.Types;
using Oracle.DataAccess.Client;

class ParseSample
{
    static void Main()
    {
        // Set the nls_timestamp_format for the Parse() method
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.TimeStampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // construct OracleTimeStampLTZ from a string using the format specified.
        OracleTimeStampLTZ ts =
            OracleTimeStampLTZ.Parse("11-NOV-1999 11:02:33.444 AM");

        // Set the nls_timestamp_format for the ToString() method
        info.TimeStampFormat = "YYYY-MON-DD HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // Prints "1999-NOV-11 11:02:33.444000000 AM"
        Console.WriteLine(ts.ToString());
    }
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125

SetPrecision

This static method returns a new instance of an `OracleTimeStampLTZ` with the specified fractional second precision.

Declaration

```
// C#
```

```
public static OracleTimeStampLTZ SetPrecision(OracleTimeStampLTZ value1,  
int fracSecPrecision);
```

Parameters

- *value1*
The provided OracleTimeStampLTZ object.
- *fracSecPrecision*
The fractional second precision provided. Range of fractional second precision is (0 to 9).

Return Value

An OracleTimeStampLTZ structure with the specified fractional second precision

Exceptions

ArgumentOutOfRangeException - *fracSecPrecision* is out of the specified range.

Remarks

The value specified in the supplied *fracSecPrecision* parameter is used to perform a rounding off operation on the supplied OracleTimeStampLTZ value. Depending on this value, 0 or more trailing zeros are displayed in the string returned by ToString().

Example

The OracleTimeStampLTZ with a value of "December 31, 9999 23:59:59.99" results in the string "December 31, 9999 23:59:59.99000" when SetPrecision() is called with the fractional second precision set to 5.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

OracleTimeStampLTZ Static Operators

The OracleTimeStampLTZ static operators are listed in [Table 14–122](#).

Table 14–122 OracleTimeStampLTZ Static Operators

| Operator | Description |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| operator + | Adds the supplied instance value to the supplied OracleTimeStampLTZ and returns a new OracleTimeStampLTZ structure (Overloaded) |
| operator == | Determines if two OracleTimeStampLTZ values are equal |
| operator > | Determines if the first of two OracleTimeStampLTZ values is greater than the second |
| operator >= | Determines if the first of two OracleTimeStampLTZ values is greater than or equal to the second |
| operator != | Determines if two OracleTimeStampLTZ values are not equal |
| operator < | Determines if the first of two OracleTimeStampLTZ values is less than the second |
| operator <= | Determines if the first of two OracleTimeStampLTZ values is less than or equal to the second |
| operator - | Subtracts the supplied instance value from the supplied OracleTimeStampLTZ and returns a new OracleTimeStampLTZ structure (Overloaded) |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

operator +

`operator +` adds the supplied value to the supplied OracleTimeStampLTZ and returns a new OracleTimeStampLTZ structure.

Overload List:

- [operator + \(OracleTimeStampLTZ, OracleIntervalDS\)](#)
This static operator adds the supplied OracleIntervalDS to the supplied OracleTimeStampLTZ and returns a new OracleTimeStampLTZ structure.
- [operator + \(OracleTimeStampLTZ, OracleIntervalYM\)](#)
This static operator adds the supplied OracleIntervalYM to the supplied OracleTimeStampLTZ and returns a new OracleTimeStampLTZ structure.
- [operator + \(OracleTimeStampLTZ, TimeSpan\)](#)
This static operator adds the supplied TimeSpan to the supplied OracleTimeStampLTZ and returns a new OracleTimeStampLTZ structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

operator + (OracleTimeStampLTZ, OracleIntervalDS)

This static operator adds the supplied `OracleIntervalDS` to the supplied `OracleTimeStampLTZ` and returns a new `OracleTimeStampLTZ` structure.

Declaration

```
// C#  
public static operator +(OracleTimeStampLTZ value1,  
    OracleIntervalDS value2);
```

Parameters

- *value1*
An `OracleTimeStampLTZ`.
- *value2*
An `OracleIntervalDS`.

Return Value

An `OracleTimeStampLTZ`.

Remarks

If either parameter has a null value, the returned `OracleTimeStampLTZ` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

operator + (OracleTimeStampLTZ, OracleIntervalYM)

This static operator adds the supplied `OracleIntervalYM` to the supplied `OracleTimeStampLTZ` and returns a new `OracleTimeStampLTZ` structure.

Declaration

```
// C#  
public static operator +(OracleTimeStampLTZ value1,  
    OracleIntervalYM value2);
```

Parameters

- *value1*
An `OracleTimeStampLTZ`.
- *value2*

An `OracleIntervalYM`.

Return Value

An `OracleTimeStampLTZ`.

Remarks

If either parameter has a null value, the returned `OracleTimeStampLTZ` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

operator + (OracleTimeStampLTZ, TimeSpan)

This static operator adds the supplied `TimeSpan` to the supplied `OracleTimeStampLTZ` and returns a new `OracleTimeStampLTZ` structure.

Declaration

```
// C#
public static operator +(OracleTimeStampLTZ value1, TimeSpan value2);
```

Parameters

- *value1*
An `OracleTimeStampLTZ`.
- *value2*
A `TimeSpan`.

Return Value

An `OracleTimeStampLTZ`.

Remarks

If the `OracleTimeStampLTZ` instance has a null value, the returned `OracleTimeStampLTZ` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

operator ==

This static operator determines if two `OracleTimeStampLTZ` values are equal.

Declaration

```
// C#
public static bool operator ==(OracleTimeStampLTZ value1,
```

```
OracleTimeStampLTZ value2);
```

Parameters

- *value1*
The first OracleTimeStampLTZ.
- *value2*
The second OracleTimeStampLTZ.

Return Value

Returns true if they are the same; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStampLTZ that has a value is greater than an OracleTimeStampLTZ that has a null value.
- Two OracleTimeStampLTZs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

operator >

This static operator determines if the first of two OracleTimeStampLTZ values is greater than the second.

Declaration

```
// C#  
public static bool operator > (OracleTimeStampLTZ value1,  
    OracleTimeStampLTZ value2);
```

Parameters

- *value1*
The first OracleTimeStampLTZ.
- *value2*
The second OracleTimeStampLTZ.

Return Value

Returns true if the first OracleTimeStampLTZ value is greater than the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStampLTZ that has a value is greater than an OracleTimeStampLTZ that has a null value.

- Two OracleTimeStampLTZs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

operator >=

This static operator determines if the first of two OracleTimeStampLTZ values is greater than or equal to the second.

Declaration

```
// C#
public static bool operator >= (OracleTimeStampLTZ value1,
    OracleTimeStampLTZ value2);
```

Parameters

- value1*
An OracleTimeStampLTZ.
- value2*
The second OracleTimeStampLTZ.

Return Value

Returns true if the first OracleTimeStampLTZ is greater than or equal to the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStampLTZ that has a value is greater than an OracleTimeStampLTZ that has a null value.
- Two OracleTimeStampLTZs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

operator !=

This static operator determines if two OracleTimeStampLTZ values are not equal.

Declaration

```
// C#
public static bool operator != (OracleTimeStampLTZ value1,
    OracleTimeStampLTZ value2);
```

Parameters

- *value1*
The first OracleTimeStampLTZ.
- *value2*
The second OracleTimeStampLTZ.

Return Value

Returns true if two OracleTimeStampLTZ values are not equal; otherwise returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStampLTZ that has a value is greater than an OracleTimeStampLTZ that has a null value.
- Two OracleTimeStampLTZs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

operator <

This static operator determines if the first of two OracleTimeStampLTZ values is less than the second.

Declaration

```
// C#  
public static bool operator < (OracleTimeStampLTZ value1,  
    OracleTimeStampLTZ value2);
```

Parameters

- *value1*
The first OracleTimeStampLTZ.
- *value2*
The second OracleTimeStampLTZ.

Return Value

Returns true if the first OracleTimeStampLTZ is less than the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStampLTZ that has a value is greater than an OracleTimeStampLTZ that has a null value.
- Two OracleTimeStampLTZs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

operator <=

This static operator determines if the first of two `OracleTimeStampLTZ` values is less than or equal to the second.

Declaration

```
// C#
public static bool operator <= (OracleTimeStampLTZ value1,
    OracleTimeStampLTZ value2);
```

Parameters

- *value1*
The first `OracleTimeStampLTZ`.
- *value2*
The second `OracleTimeStampLTZ`.

Return Value

Returns true if the first `OracleTimeStampLTZ` is less than or equal to the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampLTZ` that has a value is greater than an `OracleTimeStampLTZ` that has a null value.
- Two `OracleTimeStampLTZ`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

operator -

`operator-` subtracts the supplied value, from the supplied `OracleTimeStampLTZ` value, and returns a new `OracleTimeStampLTZ` structure.

Overload List:

- [operator - \(OracleTimeStampLTZ, OracleIntervalDS\)](#)

This static operator subtracts the supplied `OracleIntervalDS` value, from the supplied `OracleTimeStampLTZ` value, and return a new `OracleTimeStampLTZ` structure.

- [operator - \(OracleTimeStampLTZ, OracleIntervalYM\)](#)

This static operator subtracts the supplied `OracleIntervalYM` value, from the supplied `OracleTimeStampLTZ` value, and returns a new `OracleTimeStampLTZ` structure.

- [operator - \(OracleTimeStampLTZ, TimeSpan\)](#)

This static operator subtracts the supplied `TimeSpan` value, from the supplied `OracleTimeStampLTZ` value, and returns a new `OracleTimeStampLTZ` structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

operator - (OracleTimeStampLTZ, OracleIntervalDS)

This static operator subtracts the supplied `OracleIntervalDS` value, from the supplied `OracleTimeStampLTZ` value, and return a new `OracleTimeStampLTZ` structure.

Declaration

```
// C#
public static operator - (OracleTimeStampLTZ value1,
    OracleIntervalDS value2);
```

Parameters

- *value1*
An `OracleTimeStampLTZ`.
- *value2*
An `OracleIntervalDS` instance.

Return Value

An `OracleTimeStampLTZ` structure.

Remarks

If either parameter has a null value, the returned `OracleTimeStampLTZ` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

operator - (OracleTimeStampLTZ, OracleIntervalYM)

This static operator subtracts the supplied `OracleIntervalYM` value, from the supplied `OracleTimeStampLTZ` value, and returns a new `OracleTimeStampLTZ` structure.

Declaration

```
// C#
public static operator - (OracleTimeStampLTZ value1,
    OracleIntervalYM value2);
```

Parameters

- *value1*
An OracleTimeStampLTZ.
- *value2*
An OracleIntervalYM.

Return Value

An OracleTimeStampLTZ structure.

Remarks

If either parameter has a null value, the returned OracleTimeStampLTZ has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

operator - (OracleTimeStampLTZ, TimeSpan)

This static operator subtracts the supplied TimeSpan value, from the supplied OracleTimeStampLTZ value, and returns a new OracleTimeStampLTZ structure.

Declaration

```
// C#
public static operator -(OracleTimeStampLTZ value1, TimeSpan value2);
```

Parameters

- *value1*
An OracleTimeStampLTZ.
- *value2*
A TimeSpan.

Return Value

An OracleTimeStampLTZ structure.

Remarks

If the OracleTimeStampLTZ instance has a null value, the returned OracleTimeStampLTZ structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

OracleTimeStampLTZ Static Type Conversions

The OracleTimeStampLTZ static type conversions are listed in [Table 14–123](#).

Table 14–123 OracleTimeStampLTZ Static Type Conversions

| Operator | Description |
|------------------------------------------------------|----------------------------------------------------------------------------|
| explicit operator OracleTimeStampLTZ | Converts an instance value to an OracleTimeStampLTZ structure (Overloaded) |
| implicit operator OracleTimeStampLTZ | Converts an instance value to an OracleTimeStampLTZ structure (Overloaded) |
| explicit operator DateTime | Converts an OracleTimeStampLTZ value to a DateTime structure |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

explicit operator OracleTimeStampLTZ

`explicit operator OracleTimeStampLTZ` converts the supplied value to an OracleTimeStampLTZ structure.

Overload List:

- [explicit operator OracleTimeStampLTZ\(OracleTimeStamp\)](#)
This static type conversion operator converts an OracleTimeStamp value to an OracleTimeStampLTZ structure.
- [explicit operator OracleTimeStampLTZ\(OracleTimeStampTZ\)](#)
This static type conversion operator converts an OracleTimeStampTZ value to an OracleTimeStampLTZ structure.
- [explicit operator OracleTimeStampLTZ\(string\)](#)
This static type conversion operator converts the supplied string to an OracleTimeStampLTZ structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

explicit operator OracleTimeStampLTZ(OracleTimeStamp)

This static type conversion operator converts an OracleTimeStamp value to an OracleTimeStampLTZ structure.

Declaration

```
// C#
```

```
public static explicit operator OracleTimeStampLTZ (OracleTimeStamp value1);
```

Parameters

- *value1*
An OracleTimeStamp.

Return Value

The OracleTimeStampLTZ structure contains the date and time of the OracleTimeStampTZ structure.

Remarks

If the OracleTimeStamp structure has a null value, the returned OracleTimeStampLTZ structure also has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

explicit operator OracleTimeStampLTZ(OracleTimeStampTZ)

This static type conversion operator converts an OracleTimeStampTZ value to an OracleTimeStampLTZ structure.

Declaration

```
// C#  
public static explicit operator OracleTimeStampLTZ  
    (OracleTimeStampTZ value1);
```

Parameters

- *value1*
An OracleTimeStampTZ instance.

Return Value

The OracleTimeStampLTZ structure contains the date and time in the OracleTimeStampTZ structure (which is normalized to the client local time zone).

Remarks

If the OracleTimeStampTZ structure has a null value, the returned OracleTimeStampLTZ structure also has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

explicit operator OracleTimeStampLTZ(string)

This static type conversion operator converts the supplied string to an OracleTimeStampLTZ structure.

Declaration

```
// C#
public static explicit operator OracleTimeStampLTZ (string tsStr);
```

Parameters

- *tsStr*

A string representation of an Oracle TIMESTAMP WITH LOCAL TIME ZONE.

Return Value

A OracleTimeStampLTZ.

Exceptions

ArgumentException - The *tsStr* parameter is an invalid string representation of an Oracle TIMESTAMP WITH LOCAL TIME ZONE or the *tsStr* is not in the timestamp format specified by the thread's OracleGlobalization.TimeStampFormat property, which represents the Oracle NLS_TIMESTAMP_FORMAT parameter.

Remarks

The names and abbreviations used for months and days are in the language specified by the DateLanguage and Calendar properties of the thread's OracleGlobalization object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#

using System;
using Oracle.DataAccess.Types;
using Oracle.DataAccess.Client;

class OracleTimeStampLTZSample
{
    static void Main()
    {
        // Set the nls_timestamp_format for the OracleTimeStampLTZ(string)
        // constructor
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.TimeStampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // construct OracleTimeStampLTZ from a string using the format specified.
        OracleTimeStampLTZ ts =
            new OracleTimeStampLTZ("11-NOV-1999 11:02:33.444 AM");

        // Set the nls_timestamp_format for the ToString() method
        info.TimeStampFormat = "YYYY-MON-DD HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // Prints "1999-NOV-11 11:02:33.444000000 AM"
        Console.WriteLine(ts.ToString());
    }
}
```

}

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125
- *Oracle Database SQL Language Reference* for further information on datetime format elements

implicit operator OracleTimeStampLTZ

implicit operator OracleTimeStampLTZ converts the supplied structure to an OracleTimeStampLTZ structure.

Overload List:

- [implicit operator OracleTimeStampLTZ\(OracleDate\)](#)

This static type conversion operator converts an OracleDate value to an OracleTimeStampLTZ structure.
- [implicit operator OracleTimeStampLTZ\(DateTime\)](#)

This static type conversion operator converts a DateTime structure to an OracleTimeStampLTZ structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

implicit operator OracleTimeStampLTZ(OracleDate)

This static type conversion operator converts an OracleDate value to an OracleTimeStampLTZ structure.

Declaration

```
// C#  
public static implicit operator OracleTimeStampLTZ(OracleDate value1);
```

Parameters

- *value1*
An OracleDate.

Return Value

The returned OracleTimeStampLTZ structure contains the date and time in the OracleDate structure.

Remarks

If the `OracleDate` structure has a null value, the returned `OracleTimeStampLTZ` structure also has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

implicit operator OracleTimeStampLTZ(DateTime)

This static type conversion operator converts a `DateTime` structure to an `OracleTimeStampLTZ` structure.

Declaration

```
// C#  
public static implicit operator OracleTimeStampLTZ(DateTime value1);
```

Parameters

- *value1*
A `DateTime` structure.

Return Value

An `OracleTimeStampLTZ` structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

explicit operator DateTime

This static type conversion operator converts an `OracleTimeStampLTZ` value to a `DateTime` structure.

Declaration

```
// C#  
public static explicit operator DateTime(OracleTimeStampLTZ value1);
```

Parameters

- *value1*
An `OracleTimeStampLTZ` instance.

Return Value

A `DateTime` that contains the date and time in the current instance.

Exceptions

`OracleNullValueException` - The `OracleTimeStampLTZ` structure has a null value.

Remarks

The precision of the `OracleTimeStampLTZ` value can be lost during the conversion.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

OracleTimeStampLTZ Properties

The OracleTimeStampLTZ properties are listed in [Table 14–124](#).

Table 14–124 OracleTimeStampLTZ Properties

| Properties | Description |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------|
| BinData | Returns an array of bytes that represents an Oracle <code>TIMESTAMP WITH LOCAL TIME ZONE</code> in Oracle internal format |
| Day | Specifies the day component of an OracleTimeStampLTZ |
| IsNull | Indicates whether or not the OracleTimeStampLTZ instance has a null value |
| Hour | Specifies the hour component of an OracleTimeStampLTZ |
| Millisecond | Specifies the millisecond component of an OracleTimeStampLTZ |
| Minute | Specifies the minute component of an OracleTimeStampLTZ |
| Month | Specifies the month component of an OracleTimeStampLTZ |
| Nanosecond | Specifies the nanosecond component of an OracleTimeStampLTZ |
| Second | Specifies the second component of an OracleTimeStampLTZ |
| Value | Specifies the date and time that is stored in the OracleTimeStampLTZ structure |
| Year | Specifies the year component of an OracleTimeStampLTZ |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

BinData

This property returns an array of bytes that represents an Oracle `TIMESTAMP WITH LOCAL TIME ZONE` in Oracle internal format.

Declaration

```
// C#
public byte[] BinData {get;}
```

Property Value

A byte array that represents an Oracle `TIMESTAMP WITH LOCAL TIME ZONE` internal format.

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

Day

This property specifies the day component of an `OracleTimeStampLTZ`.

Declaration

```
// C#  
public int Day{get;}
```

Property Value

A number that represents the day. Range of `Day` is (1 to 31).

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

IsNull

This property indicates whether or not the current instance has a null value.

Declaration

```
// C#  
public bool IsNull{get;}
```

Property Value

Returns `true` if the current instance contains a null value; otherwise, returns `false`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

Hour

This property specifies the hour component of an `OracleTimeStampLTZ`.

Declaration

```
// C#  
public int Hour{get;}
```


Property Value

A number that represents the hour. Range of Hour is (0 to 23).

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

Millisecond

This property gets the millisecond component of an `OracleTimeStampLTZ`.

Declaration

```
// C#  
public double Millisecond{get;}
```

Property Value

A number that represents a millisecond. Range of Millisecond is (0 to 999.999999)

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

Minute

This property gets the minute component of an `OracleTimeStampLTZ`.

Declaration

```
// C#  
public int Minute{get;}
```

Property Value

A number that represent a minute. Range of Minute is (0 to 59).

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

Month

This property gets the month component of an `OracleTimeStampLTZ`.

Declaration

```
// C#  
public int Month{get;}
```

Property Value

A number that represents a month. Range of `Month` is (1 to 12).

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

Nanosecond

This property gets the nanosecond component of an `OracleTimeStampLTZ`.

Declaration

```
// C#  
public int Nanosecond{get;}
```

Property Value

A number that represents a nanosecond. Range of `Nanosecond` is (0 to 999999999).

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

Second

This property gets the second component of an `OracleTimeStampLTZ`.

Declaration

```
// C#  
public int Second{get;}
```

Property Value

A number that represents a second. Range of Second is (0 to 59).

Exceptions

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

Value

This property specifies the date and time that is stored in the OracleTimeStampLTZ structure.

Declaration

```
// C#  
public DateTime Value{get;}
```

Property Value

A DateTime.

Exceptions

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

Year

This property gets the year component of an OracleTimeStampLTZ.

Declaration

```
// C#  
public int Year{get;}
```

Property Value

A number that represents a year. The range of Year is (-4712 to 9999).

Exceptions

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

OracleTimeStampLTZ Methods

The OracleTimeStampLTZ methods are listed in [Table 14–125](#).

Table 14–125 OracleTimeStampLTZ Methods

| Methods | Description |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| AddDays | Adds the supplied number of days to the current instance |
| AddHours | Adds the supplied number of hours to the current instance |
| AddMilliseconds | Adds the supplied number of milliseconds to the current instance |
| AddMinutes | Adds the supplied number of minutes to the current instance |
| AddMonths | Adds the supplied number of months to the current instance |
| AddNanoseconds | Adds the supplied number of nanoseconds to the current instance |
| AddSeconds | Adds the supplied number of seconds to the current instance |
| AddYears | Adds the supplied number of years to the current instance |
| CompareTo | Compares the current OracleTimeStampLTZ instance to an object and returns an integer that represents their relative values |
| Equals | Determines whether or not an object has the same date and time as the current OracleTimeStampLTZ instance (Overloaded) |
| GetHashCode | Returns a hash code for the OracleTimeStampLTZ instance |
| GetDaysBetween | Subtracts an OracleTimeStampLTZ from the current instance and returns an OracleIntervalDS that represents the difference |
| GetYearsBetween | Subtracts an OracleTimeStampLTZ from the current instance and returns an OracleIntervalYM that represents the difference |
| GetType | Inherited from System.Object |
| ToOracleDate | Converts the current OracleTimeStampLTZ structure to an OracleDate structure |
| ToOracleTimeStamp | Converts the current OracleTimeStampLTZ structure to an OracleTimeStamp structure |
| ToOracleTimeStampTZ | Converts the current OracleTimeStampLTZ structure to an OracleTimeStampTZ structure |
| ToString | Converts the current OracleTimeStampLTZ structure to a string |
| ToUniversalTime | Converts the current local time to Coordinated Universal Time (UTC) |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

AddDays

This method adds the supplied number of days to the current instance.

Declaration

```
// C#  
public OracleTimeStampLTZ AddDays(double days);
```

Parameters

- *days*
The supplied number of days. Range is $(-1,000,000,000 < days < 1,000,000,000)$

Return Value

An OracleTimeStampLTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

ArgumentOutOfRangeException - The argument value is out of the specified range.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

AddHours

This method adds the supplied number of hours to the current instance.

Declaration

```
// C#  
public OracleTimeStampLTZ AddHours(double hours);
```

Parameters

- *hours*
The supplied number of hours. Range is $(-24,000,000,000 < hours < 24,000,000,000)$.

Return Value

An OracleTimeStampLTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

ArgumentOutOfRangeException - The argument value is out of the specified range.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

AddMilliseconds

This method adds the supplied number of milliseconds to the current instance.

Declaration

```
// C#  
public OracleTimeStampLTZ AddMilliseconds(double milliseconds);
```

Parameters

- *milliseconds*

The supplied number of milliseconds. Range is $(-8.64 * 1016 < milliseconds < 8.64 * 1016)$.

Return Value

An OracleTimeStampLTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

ArgumentOutOfRangeException - The argument value is out of the specified range.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

AddMinutes

This method adds the supplied number of minutes to the current instance.

Declaration

```
// C#  
public OracleTimeStampLTZ AddMinutes(double minutes);
```

Parameters

- *minutes*

The supplied number of minutes. Range is $(-1,440,000,000,000 < minutes < 1,440,000,000,000)$.

Return Value

An OracleTimeStampLTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

ArgumentOutOfRangeException - The argument value is out of the specified range.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

AddMonths

This method adds the supplied number of months to the current instance.

Declaration

```
// C#  
public OracleTimeStampLTZ AddMonths(long months);
```

Parameters

- *months*
The supplied number of months. Range is (-12,000,000,000 < *months* < 12,000,000,000).

Return Value

An OracleTimeStampLTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

ArgumentOutOfRangeException - The argument value is out of the specified range.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

AddNanoseconds

This method adds the supplied number of nanoseconds to the current instance.

Declaration

```
// C#  
public OracleTimeStampLTZ AddNanoseconds(long nanoseconds);
```

Parameters

- *nanoseconds*
The supplied number of nanoseconds.

Return Value

An OracleTimeStampLTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

AddSeconds

This method adds the supplied number of seconds to the current instance.

Declaration

```
// C#  
public OracleTimeStampLTZ AddSeconds(double seconds);
```

Parameters

- *seconds*

The supplied number of seconds. Range is $(-8.64 * 1013 < seconds < 8.64 * 1013)$.

Return Value

An OracleTimeStampLTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

ArgumentOutOfRangeException - The argument value is out of the specified range.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

AddYears

This method adds the supplied number of years to the current instance

Declaration

```
// C#  
public OracleTimeStampLTZ AddYears(int years);
```

Parameters

- *years*

The supplied number of years. Range is $(-999,999,999 \leq years \leq 999,999,999)$

Return Value

An OracleTimeStampLTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

ArgumentOutOfRangeException - The argument value is out of the specified range.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

CompareTo

This method compares the current `OracleTimeStampLTZ` instance to an object, and returns an integer that represents their relative values.

Declaration

```
// C#  
public int CompareTo(object obj);
```

Parameters

- *obj*
The object being compared to the current `OracleTimeStampLTZ` instance.

Return Value

The method returns a number that is:

- Less than zero: if the current `OracleTimeStampLTZ` instance value is less than that of *obj*.
- Zero: if the current `OracleTimeStampLTZ` instance and *obj* values are equal.
- Greater than zero: if the current `OracleTimeStampLTZ` instance value is greater than that of *obj*.

Implements

`IComparable`

Exceptions

`ArgumentException` - The *obj* parameter is not of type `OracleTimeStampLTZ`.

Remarks

The following rules apply to the behavior of this method.

- The comparison must be between `OracleTimeStampLTZ`s. For example, comparing an `OracleTimeStampLTZ` instance with an `OracleBinary` instance is not allowed. When an `OracleTimeStampLTZ` is compared with a different type, an `ArgumentException` is thrown.
- Any `OracleTimeStampLTZ` that has a value is greater than an `OracleTimeStampLTZ` that has a null value.
- Two `OracleTimeStampLTZ`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

Equals

Overrides `Object`

This method determines whether or not an object has the same date and time as the current `OracleTimeStampLTZ` instance.

Declaration

```
// C#  
public override bool Equals(object obj);
```

Parameters

- *obj*

The object being compared to the current `OracleTimeStampLTZ` instance.

Return Value

Returns true if the *obj* is of type `OracleTimeStampLTZ` and represents the same date and time; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampLTZ` that has a value is greater than an `OracleTimeStampLTZ` that has a null value.
- Two `OracleTimeStampLTZ`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

GetHashCode

Overrides `Object`

This method returns a hash code for the `OracleTimeStampLTZ` instance.

Declaration

```
// C#  
public override int GetHashCode();
```

Return Value

A number that represents the hash code.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

GetDaysBetween

This method subtracts an `OracleTimeStampLTZ` value from the current instance and returns an `OracleIntervalDS` that represents the difference.

Declaration

```
// C#  
public OracleIntervalDS GetDaysBetween(OracleTimeStampLTZ value1);
```

Parameters

- *value1*
The `OracleTimeStampLTZ` value being subtracted.

Return Value

An `OracleIntervalDS` that represents the interval between two `OracleTimeStampLTZ` values.

Remarks

If either the current instance or the parameter has a null value, the returned `OracleIntervalDS` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

GetYearsBetween

This method subtracts an `OracleTimeStampLTZ` value from the current instance and returns an `OracleIntervalYM` that represents the time interval.

Declaration

```
// C#  
public OracleIntervalYM GetYearsBetween(OracleTimeStampLTZ value1);
```

Parameters

- *value1*
The `OracleTimeStampLTZ` value being subtracted.

Return Value

An `OracleIntervalYM` that represents the interval between two `OracleTimeStampLTZ` values.

Remarks

If either the current instance or the parameter has a null value, the returned `OracleIntervalYM` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

ToOracleDate

This method converts the current `OracleTimeStampLTZ` structure to an `OracleDate` structure.

Declaration

```
// C#  
public OracleDate ToOracleDate();
```

Return Value

The returned `OracleDate` structure contains the date and time in the current instance.

Remarks

The precision of the `OracleTimeStampLTZ` value can be lost during the conversion.

If the current instance has a null value, the value of the returned `OracleDate` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

ToOracleTimeStamp

This method converts the current `OracleTimeStampLTZ` structure to an `OracleTimeStamp` structure.

Declaration

```
// C#  
public OracleTimeStamp ToOracleTimeStamp();
```

Return Value

The returned `OracleTimeStamp` contains the date and time in the current instance.

Remarks

If the current instance has a null value, the value of the returned `OracleTimeStamp` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

ToOracleTimeStampTZ

This method converts the current `OracleTimeStampLTZ` structure to an `OracleTimeStampTZ` structure.

Declaration

```
// C#  
public OracleTimeStampTZ ToOracleTimeStampTZ();
```

Return Value

The returned `OracleTimeStampTZ` contains the date and time of the current instance, with the time zone set to the `OracleGlobalization.TimeZone` from the thread.

Remarks

If the current instance has a null value, the value of the returned `OracleTimeStampTZ` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125

ToString

Overrides `Object`

This method converts the current `OracleTimeStampLTZ` structure to a string.

Declaration

```
// C#  
public override string ToString();
```

Return Value

A string that represents the same date and time as the current `OracleTimeStampLTZ` structure.

Remarks

The returned value is a string representation of the `OracleTimeStampLTZ` in the format specified by the `OracleGlobalization.TimeStampFormat` property of the thread.

The names and abbreviations used for months and days are in the language specified by the `DateLanguage` and `Calendar` properties of the thread's `OracleGlobalization`

object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#

using System;
using Oracle.DataAccess.Types;
using Oracle.DataAccess.Client;

class ToStringSample
{
    static void Main()
    {
        // Set the nls_timestamp_format for the OracleTimeStampLTZ(string)
        // constructor
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.TimestampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // construct OracleTimeStampLTZ from a string using the format
        // specified.
        OracleTimeStampLTZ ts =
            new OracleTimeStampLTZ("11-NOV-1999 11:02:33.444 AM");

        // Set the nls_timestamp_format for the ToString() method
        info.TimestampFormat = "YYYY-MON-DD HH:MI:SS.FF AM";
        OracleGlobalization.SetThreadInfo(info);

        // Prints "1999-NOV-11 11:02:33.444000000 AM"
        Console.WriteLine(ts.ToString());
    }
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125

ToUniversalTime

This method converts the current local time to Coordinated Universal Time (UTC).

Declaration

```
// C#
public OracleTimeStampTZ ToUniversalTime();
```

Return Value

An OracleTimeStampTZ structure.

Remarks

If the current instance has a null value, the value of the returned `OracleTimeStampTZ` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampLTZ Structure](#)
- [OracleTimeStampLTZ Members](#)

OracleTimeStampTZ Structure

The `OracleTimeStampTZ` structure represents the Oracle `TIMESTAMP WITH TIME ZONE` data type to be stored in or retrieved from a database. Each `OracleTimeStampTZ` stores the following information: year, month, day, hour, minute, second, nanosecond, and time zone.

Class Inheritance

`System.Object`

`System.ValueType`

`Oracle.DataAccess.Types.OracleTimeStampTZ`

Declaration

```
// C#
public struct OracleTimeStampTZ : IComparable, INullable, IXmlSerializable
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|--------------------------------------|---------------------------------------------|
| Assembly | <code>Oracle.DataAccess.dll</code> | <code>Oracle.ManagedDataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Types</code> | <code>Oracle.ManagedDataAccess.Types</code> |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class OracleTimeStampTZSample
{
    static void Main()
    {
        // Set the nls parameters for the current thread
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.TimeZone = "US/Eastern";
        info.TimeStampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
        info.TimeStampTZFormat = "DD-MON-YYYY HH:MI:SS.FF AM TZR";
        OracleGlobalization.SetThreadInfo(info);

        // Create an OracleTimeStampTZ in US/Pacific time zone
        OracleTimeStampTZ tstz1=new OracleTimeStampTZ("11-NOV-1999 "+
            "11:02:33.444 AM US/Pacific");

        // Note that ToOracleTimeStampTZ uses the thread's time zone region,
        // "US/Eastern"
```

```
OracleTimeStamp ts = new OracleTimeStamp("11-NOV-1999 11:02:33.444 AM");
OracleTimeStampTZ tstz2 = ts.ToOracleTimeStampTZ();

// Calculate the difference between tstz1 and tstz2
OracleIntervalDS idsDiff = tstz1.GetDaysBetween(tstz2);

// Display information
Console.WriteLine("tstz1.TimeZone = " + tstz1.TimeZone);

// Prints "US/Pacific"
Console.WriteLine("tstz2.TimeZone = " + tstz2.TimeZone);

// Prints "US/Eastern"
Console.WriteLine("idsDiff.Hours = " + idsDiff.Hours); // Prints 3
Console.WriteLine("idsDiff.Minutes = " + idsDiff.Minutes); // Prints 0
}
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleTimeStampTZ Members](#)
- [OracleTimeStampTZ Constructors](#)
- [OracleTimeStampTZ Static Fields](#)
- [OracleTimeStampTZ Static Methods](#)
- [OracleTimeStampTZ Static Operators](#)
- [OracleTimeStampTZ Static Type Conversions](#)
- [OracleTimeStampTZ Properties](#)
- [OracleTimeStampTZ Methods](#)

OracleTimeStampTZ Members

OracleTimeStampTZ members are listed in the following tables:

OracleTimeStampTZ Constructors

OracleTimeStampTZ constructors are listed in [Table 14–126](#)

Table 14–126 OracleTimeStampTZ Constructors

| Constructor | Description |
|------------------------------------------------|-------------------------------------------------------------------------|
| OracleTimeStampTZ Constructors | Instantiates a new instance of OracleTimeStampTZ structure (Overloaded) |

OracleTimeStampTZ Static Fields

The OracleTimeStampTZ static fields are listed in [Table 14–127](#).

Table 14–127 OracleTimeStampTZ Static Fields

| Field | Description |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------|
| MaxValue | Represents the maximum valid date for an OracleTimeStampTZ structure in UTC, which is December 31, 999923:59:59.999999999 |
| MinValue | Represents the minimum valid date for an OracleTimeStampTZ structure in UTC, which is January 1, -4712 0:0:0 |
| Null | Represents a null value that can be assigned to an instance of the OracleTimeStampTZ structure |

OracleTimeStampTZ Static Methods

The OracleTimeStampTZ static methods are listed in [Table 14–128](#).

Table 14–128 OracleTimeStampTZ Static Methods

| Methods | Description |
|------------------------------------|----------------------------------------------------------------------------------------------------|
| Equals | Determines if two OracleTimeStampTZ values are equal (Overloaded) |
| GetSysDate | Gets an OracleTimeStampTZ structure that represents the current date and time |
| GreaterThan | Determines if the first of two OracleTimeStampTZ values is greater than the second |
| GreaterThanOrEqual | Determines if the first of two OracleTimeStampTZ values is greater than or equal to the second |
| LessThan | Determines if the first of two OracleTimeStampTZ values is less than the second |
| LessThanOrEqual | Determines if the first of two OracleTimeStampTZ values is less than or equal to the second |
| NotEquals | Determines if two OracleTimeStampTZ values are not equal |
| Parse | Gets an OracleTimeStampTZ structure and sets its value for date and time using the supplied string |

Table 14–128 (Cont.) OracleTimeStampTZ Static Methods

| Methods | Description |
|------------------------------|------------------------------------------------------------------------------------------------------------|
| SetPrecision | Returns a new instance of an <code>OracleTimeStampTZ</code> with the specified fractional second precision |

OracleTimeStampTZ Static Operators

The `OracleTimeStampTZ` static operators are listed in [Table 14–129](#).

Table 14–129 OracleTimeStampTZ Static Operators

| Operator | Description |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>operator +</code> | Adds the supplied instance value to the supplied <code>OracleTimeStampTZ</code> and returns a new <code>OracleTimeStampTZ</code> structure (Overloaded) |
| <code>operator ==</code> | Determines if two <code>OracleTimeStampTZ</code> values are equal |
| <code>operator ></code> | Determines if the first of two <code>OracleTimeStampTZ</code> values is greater than the second |
| <code>operator >=</code> | Determines if the first of two <code>OracleTimeStampTZ</code> values is greater than or equal to the second |
| <code>operator !=</code> | Determines if two <code>OracleTimeStampTZ</code> values are not equal |
| <code>operator <</code> | Determines if the first of two <code>OracleTimeStampTZ</code> values is less than the second |
| <code>operator <=</code> | Determines if the first of two <code>OracleTimeStampTZ</code> values is less than or equal to the second |
| <code>operator -</code> | Subtracts the supplied instance value from the supplied <code>OracleTimeStampTZ</code> and returns a new <code>OracleTimeStampTZ</code> structure (Overloaded) |

OracleTimeStampTZ Static Type Conversions

The `OracleTimeStampTZ` static type conversions are listed in [Table 14–130](#).

Table 14–130 OracleTimeStampTZ Static Type Conversions

| Operator | Description |
|--------------------------------------------------|----------------------------------------------------------------------------------------|
| <code>explicit operator OracleTimeStampTZ</code> | Converts an instance value to an <code>OracleTimeStampTZ</code> structure (Overloaded) |
| <code>implicit operator OracleTimeStampTZ</code> | Converts an instance value to an <code>OracleTimeStampTZ</code> structure (Overloaded) |
| <code>explicit operator DateTime</code> | Converts an <code>OracleTimeStampTZ</code> value to a <code>DateTime</code> structure |

OracleTimeStampTZ Properties

The `OracleTimeStampTZ` properties are listed in [Table 14–131](#).

Table 14–131 OracleTimeStampTZ Properties

| Properties | Description |
|-------------------------|---------------------------------------------------------------------------------------------------------------------|
| BinData | Returns an array of bytes that represents an Oracle <code>TIMESTAMP WITH TIME ZONE</code> in Oracle internal format |

Table 14–131 (Cont.) OracleTimeStampTZ Properties

| Properties | Description |
|-------------|------------------------------------------------------------------------------------------------------|
| Day | Specifies the day component of an OracleTimeStampTZ in the current time zone |
| IsNull | Indicates whether or not the current instance has a null value |
| Hour | Specifies the hour component of an OracleTimeStampTZ in the current time zone |
| Millisecond | Specifies the millisecond component of an OracleTimeStampTZ in the current time zone |
| Minute | Specifies the minute component of an OracleTimeStampTZ in the current time zone |
| Month | Specifies the month component of an OracleTimeStampTZ in the current time zone |
| Nanosecond | Specifies the nanosecond component of an OracleTimeStampTZ in the current time zone |
| Second | Specifies the second component of an OracleTimeStampTZ in the current time zone |
| TimeZone | Returns the time zone of the OracleTimeStampTZ instance |
| Value | Returns the date and time that is stored in the OracleTimeStampTZ structure in the current time zone |
| Year | Specifies the year component of an OracleTimeStampTZ |

OracleTimeStampTZ Methods

The OracleTimeStampTZ methods are listed in [Table 14–132](#).

Table 14–132 OracleTimeStampTZ Methods

| Methods | Description |
|-----------------|------------------------------------------------------------------|
| AddDays | Adds the supplied number of days to the current instance |
| AddHours | Adds the supplied number of hours to the current instance |
| AddMilliseconds | Adds the supplied number of milliseconds to the current instance |
| AddMinutes | Adds the supplied number of minutes to the current instance |
| AddMonths | Adds the supplied number of months to the current instance |
| AddNanoseconds | Adds the supplied number of nanoseconds to the current instance |
| AddSeconds | Adds the supplied number of seconds to the current instance |
| AddYears | Adds the supplied number of years to the current instance |

Table 14–132 (Cont.) OracleTimeStampTZ Methods

| Methods | Description |
|--------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| CompareTo | Compares the current <code>OracleTimeStampTZ</code> instance to an object, and returns an integer that represents their relative values |
| Equals | Determines whether or not an object has the same date and time as the current <code>OracleTimeStampTZ</code> instance |
| GetDaysBetween | Subtracts an <code>OracleTimeStampTZ</code> from the current instance and returns an <code>OracleIntervalDS</code> that represents the time interval |
| GetHashCode | Returns a hash code for the <code>OracleTimeStampTZ</code> instance |
| GetTimeZoneOffset | Gets the time zone information in hours and minutes of the current <code>OracleTimeStampTZ</code> |
| GetYearsBetween | Subtracts an <code>OracleTimeStampTZ</code> from the current instance and returns an <code>OracleIntervalYM</code> that represents the time interval |
| GetType | Inherited from <code>System.Object</code> |
| ToLocalTime | Converts the current <code>OracleTimeStampTZ</code> instance to local time |
| ToOracleDate | Converts the current <code>OracleTimeStampTZ</code> structure to an <code>OracleDate</code> structure |
| ToOracleTimeStampLTZ | Converts the current <code>OracleTimeStampTZ</code> structure to an <code>OracleTimeStampLTZ</code> structure |
| ToOracleTimeStamp | Converts the current <code>OracleTimeStampTZ</code> structure to an <code>OracleTimeStamp</code> structure |
| ToString | Converts the current <code>OracleTimeStampTZ</code> structure to a string |
| ToUniversalTime | Converts the current datetime to Coordinated Universal Time (UTC) |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)

OracleTimeStampTZ Constructors

The `OracleTimeStampTZ` constructors create new instances of the `OracleTimeStampTZ` structure.

Overload List:

- [OracleTimeStampTZ\(DateTime\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using the supplied `DateTime` value.
- [OracleTimeStampTZ\(DateTime, string\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using the supplied `DateTime` value and the supplied time zone data.
- [OracleTimeStampTZ\(string\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using the supplied string.
- [OracleTimeStampTZ\(int, int, int\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, and day.
- [OracleTimeStampTZ\(int, int, int, string\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, and time zone data.
- [OracleTimeStampTZ\(int, int, int, int, int, int\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, and second.
- [OracleTimeStampTZ\(int, int, int, int, int, int, string\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and time zone data.
- [OracleTimeStampTZ\(int, int, int, int, int, int, double\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and millisecond.
- [OracleTimeStampTZ\(int, int, int, int, int, int, double, string\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, millisecond, and time zone data.
- [OracleTimeStampTZ\(int, int, int, int, int, int, int\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and nanosecond.
- [OracleTimeStampTZ\(int, int, int, int, int, int, int, string\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, nanosecond, and time zone data.

- [OracleTimeStampTZ\(byte \[\]\)](#)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value to the provided byte array, that represents the internal Oracle `TIMESTAMP WITH TIME ZONE` format.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ(DateTime)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using the supplied `DateTime` value.

Declaration

```
// C#  
public OracleTimeStampTZ (DateTime dt);
```

Parameters

- *dt*
The supplied `DateTime` value.

Remarks

The time zone is set to the `OracleGlobalization.TimeZone` of the thread.

Exceptions

`ArgumentException` - The *dt* parameter cannot be used to construct a valid `OracleTimeStampTZ`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ(DateTime, string)

This constructor creates a new instance of the `OracleTimeStampTZ` structure with the supplied `DateTime` value and the time zone data.

Declaration

```
// C#  
public OracleTimeStampTZ (DateTime value1, string timeZone);
```


Parameters

- *value1*
The supplied DateTime value.
- *timeZone*
The time zone data provided.

Exceptions

ArgumentException - The argument values of the parameters cannot be used to construct a valid OracleTimeStampTZ.

Remarks

timeZone can be either an hour offset, for example, 7:00, or a valid time zone region name that is provided in V\$TIMEZONE_NAMES, such as US/Pacific. Time zone abbreviations are not supported.

If time zone is null, the OracleGlobalization.TimeZone of the thread is used.

Note: PST is a time zone region name as well as a time zone abbreviation; therefore it is accepted by OracleTimeStampTZ.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ(string)

This constructor creates a new instance of the OracleTimeStampTZ structure and sets its value for date and time using the supplied string.

Declaration

```
// C#
public OracleTimeStampTZ (string tsStr);
```

Parameters

- *tsStr*
A string that represents an Oracle TIMESTAMP WITH TIME ZONE.

Exceptions

ArgumentException - The *tsStr* is an invalid string representation of an Oracle TIMESTAMP WITH TIME ZONE or the *tsStr* is not in the timestamp format specified by the OracleGlobalization.TimeStampTZFormat property of the thread.

ArgumentNullException - The *tsStr* value is null.

Remarks

The names and abbreviations used for months and days are in the language specified by the DateLanguage and Calendar properties of the thread's OracleGlobalization

object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class OracleTimeStampTZSample
{
    static void Main()
    {
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.TimeStampTZFormat = "DD-MON-YYYY HH:MI:SS.FF AM TZR";
        OracleGlobalization.SetThreadInfo(info);

        // construct OracleTimeStampTZ from a string using the format specified.
        OracleTimeStampTZ tstz = new OracleTimeStampTZ("11-NOV-1999" +
            "11:02:33.444 AM US/Pacific");

        // Set the nls_timestamp_tz_format for the ToString() method
        info.TimeStampTZFormat = "YYYY-MON-DD HH:MI:SS.FF AM TZR";
        OracleGlobalization.SetThreadInfo(info);

        // Prints "1999-NOV-11 11:02:33.444000000 AM US/Pacific"
        Console.WriteLine(tstz.ToString());
    }
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125
- *Oracle Database SQL Language Reference* for further information on date format elements

OracleTimeStampTZ(int, int, int)

This constructor creates a new instance of the OracleTimeStampTZ structure and sets its value for date and time using year, month, and day.

Declaration

```
// C#
public OracleTimeStampTZ(int year, int month, int day);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).

- *month*
The month provided. Range of *month* is (1 to 12).
- *day*
The day provided. Range of *day* is (1 to 31).

Exceptions

ArgumentOutOfRangeException - The argument value for one or more of the parameters is out of the specified range.

ArgumentException - The argument values of the parameters cannot be used to construct a valid *OracleTimeStampTZ* (that is, the day is out of range for the month).

Remarks

The time zone is set to the *OracleGlobalization.TimeZone* of the thread.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ(int, int, int, string)

This constructor creates a new instance of the *OracleTimeStampTZ* structure and sets its value for date and time using year, month, day, and time zone data.

Declaration

```
// C#
public OracleTimeStampTZ(int year, int month, int day,
    string timeZone);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).
- *month*
The month provided. Range of *month* is (1 to 12).
- *day*
The day provided. Range of *day* is (1 to 31).
- *timeZone*
The time zone data provided.

Exceptions

ArgumentOutOfRangeException - The argument value for one or more of the parameters is out of the specified range.

ArgumentException - The argument values of the parameters cannot be used to construct a valid *OracleTimeStampTZ* (that is, the day is out of range for the month or the time zone is invalid).

Remarks

`timeZone` can be either an hour offset, for example, 7:00, or a valid time zone region name that is provided in `V$TIMEZONE_NAMES`, such as US/Pacific. Time zone abbreviations are not supported.

If time zone is null, the `OracleGlobalization.TimeZone` of the thread is used.

Note: PST is a time zone region name as well as a time zone abbreviation; therefore it is accepted by `OracleTimeStampTZ`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ(int, int, int, int, int, int)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, and second.

Declaration

```
// C#
public OracleTimeStampTZ(int year, int month, int day, int hour,
    int minute, int second);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).
- *month*
The month provided. Range of *month* is (1 to 12).
- *day*
The day provided. Range of *day* is (1 to 31).
- *hour*
The hour provided. Range of *hour* is (0 to 23).
- *minute*
The minute provided. Range of *minute* is (0 to 59).
- *second*
The second provided. Range of *second* is (0 to 59).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampTZ` (that is, the day is out of range for the month).

Remarks

The time zone is set to the `OracleGlobalization.TimeZone` of the thread.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ(int, int, int, int, int, int, string)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and time zone data.

Declaration

```
// C#  
public OracleTimeStampTZ (int year, int month, int day, int hour,  
    int minute, int second, string timeZone);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).
- *month*
The month provided. Range of *month* is (1 to 12).
- *day*
The day provided. Range of *day* is (1 to 31).
- *hour*
The hour provided. Range of *hour* is (0 to 23).
- *minute*
The minute provided. Range of *minute* is (0 to 59).
- *second*
The second provided. Range of *second* is (0 to 59).
- *timeZone*
The time zone data provided.

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampTZ` (that is, the day is out of range of the month or the time zone is invalid).

Remarks

`timeZone` can be either an hour offset, for example, 7:00, or a valid time zone region name that is provided in `V$TIMEZONE_NAMES`, such as US/Pacific. Time zone abbreviations are not supported.

If time zone is null, the `OracleGlobalization.TimeZone` of the thread is used.

Note: PST is a time zone region name as well as a time zone abbreviation; therefore it is accepted by `OracleTimeStampTZ`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ(int, int, int, int, int, int, double)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and millisecond.

Declaration

```
// C#
public OracleTimeStampTZ(int year, int month, int day, int hour,
    int minute, int second, double millisecond);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).
- *month*
The month provided. Range of *month* is (1 to 12).
- *day*
The day provided. Range of *day* is (1 to 31).
- *hour*
The hour provided. Range of *hour* is (0 to 23).
- *minute*
The minute provided. Range of *minute* is (0 to 59).
- *second*
The second provided. Range of *second* is (0 to 59).
- *millisecond*
The millisecond provided. Range of *millisecond* is (0 to 999.999999).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampTZ` (that is, the day is out of range for the month).

Remarks

The time zone is set to the `OracleGlobalization.TimeZone` of the thread.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ(int, int, int, int, int, int, double, string)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, millisecond, and time zone data.

Declaration

```
// C#
public OracleTimeStampTZ(int year, int month, int day, int hour,
    int minute, int second, double millisecond, string timeZone);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).
- *month*
The month provided. Range of *month* is (1 to 12).
- *day*
The day provided. Range of *day* is (1 to 31).
- *hour*
The hour provided. Range of *hour* is (0 to 23).
- *minute*
The minute provided. Range of *minute* is (0 to 59).
- *second*
The second provided. Range of *second* is (0 to 59).
- *millisecond*
The millisecond provided. Range of *millisecond* is (0 to 999.999999).
- *timeZone*
The time zone data provided.

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampTZ` (that is, the day is out of range for the month or the time zone is invalid).

Remarks

`timeZone` can be either an hour offset, for example, 7:00, or a valid time zone region name that is provided in `V$TIMEZONE_NAMES`, such as US/Pacific. Time zone abbreviations are not supported.

If time zone is null, the `OracleGlobalization.TimeZone` of the thread is used.

Note: PST is a time zone region name as well as a time zone abbreviation; therefore it is accepted by `OracleTimeStampTZ`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ(int, int, int, int, int, int, int)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, and nanosecond.

Declaration

```
// C#
public OracleTimeStampTZ(int year, int month, int day, int hour,
    int minute, int second, int nanosecond);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).
- *month*
The month provided. Range of *month* is (1 to 12).
- *day*
The day provided. Range of *day* is (1 to 31).
- *hour*
The hour provided. Range of *hour* is (0 to 23).
- *minute*
The minute provided. Range of *minute* is (0 to 59).
- *second*
The second provided. Range of *second* is (0 to 59).
- *nanosecond*
The nanosecond provided. Range of *nanosecond* is (0 to 999999999).

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampTZ` (that is, the day is out of range for the month).

Remarks

The time zone is set to the `OracleGlobalization.TimeZone` of the thread.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ(int, int, int, int, int, int, int, string)

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value for date and time using year, month, day, hour, minute, second, nanosecond, and time zone data.

Declaration

```
// C#
public OracleTimeStampTZ(int year, int month, int day, int hour,
    int minute, int second, int nanosecond, string timeZone);
```

Parameters

- *year*
The year provided. Range of *year* is (-4712 to 9999).
- *month*
The month provided. Range of *month* is (1 to 12).
- *day*
The day provided. Range of *day* is (1 to 31).
- *hour*
The hour provided. Range of *hour* is (0 to 23).
- *minute*
The minute provided. Range of *minute* is (0 to 59).
- *second*
The second provided. Range of *second* is (0 to 59).
- *nanosecond*
The nanosecond provided. Range of *nanosecond* is (0 to 999999999).
- *timeZone*
The time zone data provided.

Exceptions

`ArgumentOutOfRangeException` - The argument value for one or more of the parameters is out of the specified range.

`ArgumentException` - The argument values of the parameters cannot be used to construct a valid `OracleTimeStampTZ` (that is, the day is out of range for the month or the time zone is invalid).

Remarks

`timeZone` can be either an hour offset, for example, 7:00, or a valid time zone region name that is provided in `V$TIMEZONE_NAMES`, such as `US/Pacific`. Time zone abbreviations are not supported.

If time zone is null, the `OracleGlobalization.TimeZone` of the thread is used.

Note: PST is a time zone region name as well as a time zone abbreviation; therefore it is accepted by `OracleTimeStampTZ`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ(byte [])

This constructor creates a new instance of the `OracleTimeStampTZ` structure and sets its value to the provided byte array, that represents the internal Oracle `TIMESTAMP WITH TIME ZONE` format.

Declaration

```
// C#  
public OracleTimeStampLTZ (byte[] bytes);
```

Parameters

- *bytes*

The provided byte array that represents an Oracle `TIMESTAMP WITH TIME ZONE` in Oracle internal format.

Exceptions

`ArgumentException` - *bytes* is not in internal Oracle `TIMESTAMP WITH TIME ZONE` format or *bytes* is not a valid Oracle `TIMESTAMP WITH TIME ZONE`.

`ArgumentNullException` - *bytes* is null.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ Static Fields

The OracleTimeStampTZ static fields are listed in [Table 14–133](#).

Table 14–133 OracleTimeStampTZ Static Fields

| Field | Description |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------|
| MaxValue | Represents the maximum valid date for an OracleTimeStampTZ structure in UTC, which is December 31, 999923:59:59.999999999 |
| MinValue | Represents the minimum valid date for an OracleTimeStampTZ structure in UTC, which is January 1, -4712 0:0:0 |
| Null | Represents a null value that can be assigned to an instance of the OracleTimeStampTZ structure |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

MaxValue

This static field represents the maximum valid datetime time for an OracleTimeStampTZ structure in UTC, which is December 31, 999923:59:59.999999999.

Declaration

```
// C#
public static readonly OracleTimeStampTZ MaxValue;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

MinValue

This static field represents the minimum valid datetime for an OracleTimeStampTZ structure in UTC, which is January 1, -4712 0:0:0.

Declaration

```
// C#
public static readonly OracleTimeStampTZ MinValue;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

Null

This static field represents a null value that can be assigned to an instance of the `OracleTimeStampTZ` structure.

Declaration

```
// C#  
public static readonly OracleTimeStampTZ Null;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ Static Methods

The OracleTimeStampTZ static methods are listed in [Table 14–134](#).

Table 14–134 OracleTimeStampTZ Static Methods

| Methods | Description |
|------------------------------------|----------------------------------------------------------------------------------------------------|
| Equals | Determines if two OracleTimeStampTZ values are equal (Overloaded) |
| GetSysDate | Gets an OracleTimeStampTZ structure that represents the current date and time |
| GreaterThan | Determines if the first of two OracleTimeStampTZ values is greater than the second |
| GreaterThanOrEqual | Determines if the first of two OracleTimeStampTZ values is greater than or equal to the second |
| LessThan | Determines if the first of two OracleTimeStampTZ values is less than the second |
| LessThanOrEqual | Determines if the first of two OracleTimeStampTZ values is less than or equal to the second |
| NotEquals | Determines if two OracleTimeStampTZ values are not equal |
| Parse | Gets an OracleTimeStampTZ structure and sets its value for date and time using the supplied string |
| SetPrecision | Returns a new instance of an OracleTimeStampTZ with the specified fractional second precision |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

Equals

This static method determines if two OracleTimeStampTZ values are equal.

Declaration

```
// C#
public static bool Equals(OracleTimeStampTZ value1,
    OracleTimeStampTZ value2);
```

Parameters

- *value1*
The first OracleTimeStampTZ.
- *value2*
The second OracleTimeStampTZ.

Return Value

Returns true if two OracleTimeStampTZ values are equal. Returns false otherwise.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZ`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

GetSysDate

This static method gets an `OracleTimeStampTZ` structure that represents the current date and time.

Declaration

```
// C#
public static OracleTimeStampTZ GetSysDate();
```

Return Value

An `OracleTimeStampTZ` structure that represents the current date and time.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

GreaterThan

This static method determines if the first of two `OracleTimeStampTZ` values is greater than the second.

Declaration

```
// C#
public static bool GreaterThan(OracleTimeStampTZ value1,
    OracleTimeStampTZ value2);
```

Parameters

- *value1*
The first `OracleTimeStampTZ`.
- *value2*
The second `OracleTimeStampTZ`.

Return Value

Returns `true` if the first of two `OracleTimeStampTZ` values is greater than the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZ`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

GreaterThanOrEqualTo

This static method determines if the first of two `OracleTimeStampTZ` values is greater than or equal to the second.

Declaration

```
// C#
public static bool GreaterThanOrEqualTo(OracleTimeStampTZ value1,
    OracleTimeStampTZ value2);
```

Parameters

- *value1*
The first `OracleTimeStampTZ`.
- *value2*
The second `OracleTimeStampTZ`.

Return Value

Returns `true` if the first of two `OracleTimeStampTZ` values is greater than or equal to the second; otherwise, returns `false`.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZ`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

LessThan

This static method determines if the first of two `OracleTimeStampTZ` values is less than the second.

Declaration

```
// C#  
public static bool LessThan(OracleTimeStampTZ value1,  
    OracleTimeStampTZ value2);
```

Parameters

- *value1*
The first OracleTimeStampTZ.
- *value2*
The second OracleTimeStampTZ.

Return Value

Returns true if the first of two OracleTimeStampTZ values is less than the second. Returns false otherwise.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStampTZ that has a value is greater than an OracleTimeStampTZ that has a null value.
- Two OracleTimeStampTZs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

LessThanOrEqual

This static method determines if the first of two OracleTimeStampTZ values is less than or equal to the second.

Declaration

```
// C#  
public static bool LessThanOrEqual(OracleTimeStampTZ value1,  
    OracleTimeStampTZ value2);
```

Parameters

- *value1*
The first OracleTimeStampTZ.
- *value2*
The second OracleTimeStampTZ.

Return Value

Returns true if the first of two OracleTimeStampTZ values is less than or equal to the second. Returns false otherwise.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZ`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

NotEquals

This static method determines if two `OracleTimeStampTZ` values are not equal.

Declaration

```
// C#
public static bool NotEquals(OracleTimeStampTZ value1,
    OracleTimeStampTZ value2);
```

Parameters

- *value1*
The first `OracleTimeStampTZ`.
- *value2*
The second `OracleTimeStampTZ`.

Return Value

Returns true if two `OracleTimeStampTZ` values are not equal. Returns false otherwise.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZ`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

Parse

This static method returns an `OracleTimeStampTZ` structure and sets its value for date and time using the supplied string.

Declaration

```
// C#  
public static OracleTimeStampTZ Parse(string tsStr);
```

Parameters

- *tsStr*

A string that represents an Oracle `TIMESTAMP WITH TIME ZONE`.

Return Value

An `OracleTimeStampTZ` structure.

Exceptions

`ArgumentException` - The *tsStr* is an invalid string representation of an Oracle `TIMESTAMP WITH TIME ZONE` or the *tsStr* is not in the timestamp format specified by the `OracleGlobalization.TimeStampTZFormat` property of the thread, which represents the Oracle `NLS_TIMESTAMP_TZ_FORMAT` parameter.

`ArgumentNullException` - The *tsStr* value is null.

Remarks

The names and abbreviations used for months and days are in the language specified by the `DateLanguage` and `Calendar` properties of the thread's `OracleGlobalization` object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#  
  
using System;  
using Oracle.DataAccess.Client;  
using Oracle.DataAccess.Types;  
  
class ParseSample  
{  
    static void Main()  
    {  
        // Set the nls_timestamp_tz_format for the Parse() method  
        OracleGlobalization info = OracleGlobalization.GetClientInfo();  
        info.TimeStampTZFormat = "DD-MON-YYYY HH:MI:SS.FF AM TZR";  
        OracleGlobalization.SetThreadInfo(info);  
  
        // construct OracleTimeStampTZ from a string using the format specified.  
        OracleTimeStampTZ tstz = OracleTimeStampTZ.Parse("11-NOV-1999 " +  
            "11:02:33.444 AM US/Pacific");  
  
        // Set the nls_timestamp_tz_format for the ToString() method  
        info.TimeStampTZFormat = "YYYY-MON-DD HH:MI:SS.FF AM TZR";  
        OracleGlobalization.SetThreadInfo(info);  
  
        // Prints "1999-NOV-11 11:02:33.444000000 AM US/Pacific"  
        Console.WriteLine(tstz.ToString());  
    }  
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125

SetPrecision

This static method returns a new instance of an `OracleTimeStampTZ` with the specified fractional second precision.

Declaration

```
// C#
public static OracleTimeStampTZ SetPrecision(OracleTimeStampTZ value1,
    int fracSecPrecision);
```

Parameters

- *value1*
The provided `OracleTimeStampTZ` object.
- *fracSecPrecision*
The fractional second precision provided. Range of fractional second precision is (0 to 9).

Return Value

An `OracleTimeStampTZ` structure with the specified fractional second precision

Exceptions

`ArgumentOutOfRangeException` - *fracSecPrecision* is out of the specified range.

Remarks

The value specified in the supplied *fracSecPrecision* is used to perform a rounding off operation on the supplied `OracleTimeStampTZ` value. Depending on this value, 0 or more trailing zeros are displayed in the string returned by `ToString()`.

Example

The `OracleTimeStampTZ` with a value of "December 31, 9999 23:59:59.99 US/Pacific" results in the string "December 31, 9999 23:59:59.99000 US/Pacific" when `SetPrecision()` is called with the fractional second precision set to 5.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ Static Operators

The OracleTimeStampTZ static operators are listed in [Table 14–135](#).

Table 14–135 OracleTimeStampTZ Static Operators

| Operator | Description |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| operator + | Adds the supplied instance value to the supplied OracleTimeStampTZ and returns a new OracleTimeStampTZ structure (Overloaded) |
| operator == | Determines if two OracleTimeStampTZ values are equal |
| operator > | Determines if the first of two OracleTimeStampTZ values is greater than the second |
| operator >= | Determines if the first of two OracleTimeStampTZ values is greater than or equal to the second |
| operator != | Determines if two OracleTimeStampTZ values are not equal |
| operator < | Determines if the first of two OracleTimeStampTZ values is less than the second |
| operator <= | Determines if the first of two OracleTimeStampTZ values is less than or equal to the second |
| operator - | Subtracts the supplied instance value from the supplied OracleTimeStampTZ and returns a new OracleTimeStampTZ structure (Overloaded) |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

operator +

`operator+` adds the supplied structure to the supplied OracleTimeStampTZ and returns a new OracleTimeStampTZ structure.

Overload List:

- [operator +\(OracleTimeStampTZ, OracleIntervalDS\)](#)
This static operator adds the supplied OracleIntervalDS to the supplied OracleTimeStampTZ and returns a new OracleTimeStampTZ structure.
- [operator +\(OracleTimeStampTZ, OracleIntervalYM\)](#)
This static operator adds the supplied OracleIntervalYM to the supplied OracleTimeStampTZ and returns a new OracleTimeStampTZ structure.
- [operator +\(OracleTimeStampTZ, TimeSpan\)](#)
This static operator adds the supplied TimeSpan to the supplied OracleTimeStampTZ and returns a new OracleTimeStampTZ structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

operator +(OracleTimeStampTZ, OracleIntervalDS)

This static operator adds the supplied `OracleIntervalDS` to the supplied `OracleTimeStampTZ` and returns a new `OracleTimeStampTZ` structure.

Declaration

```
// C#
public static operator +(OracleTimeStampTZ value1,
    OracleIntervalDS value2);
```

Parameters

- *value1*
An `OracleTimeStampTZ`.
- *value2*
An `OracleIntervalDS`.

Return Value

An `OracleTimeStampTZ`.

Remarks

If either parameter has a null value, the returned `OracleTimeStampTZ` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

operator +(OracleTimeStampTZ, OracleIntervalYM)

This static operator adds the supplied `OracleIntervalYM` to the supplied `OracleTimeStampTZ` and returns a new `OracleTimeStampTZ` structure.

Declaration

```
// C#
public static operator +(OracleTimeStampTZ value1,
    OracleIntervalYM value2);
```

Parameters

- *value1*
An `OracleTimeStampTZ`.
- *value2*
An `OracleIntervalYM`.

Return Value

An OracleTimeStampTZ.

Remarks

If either parameter has a null value, the returned OracleTimeStampTZ has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

operator +(OracleTimeStampTZ, TimeSpan)

This static operator adds the supplied TimeSpan to the supplied OracleTimeStampTZ and returns a new OracleTimeStampTZ structure.

Declaration

```
// C#
public static operator +(OracleTimeStampTZ value1, TimeSpan value2);
```

Parameters

- *value1*
An OracleTimeStampTZ.
- *value2*
A TimeSpan.

Return Value

An OracleTimeStampTZ.

Remarks

If the OracleTimeStampTZ instance has a null value, the returned OracleTimeStampTZ has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

operator ==

This static operator determines if two OracleTimeStampTZ values are equal.

Declaration

```
// C#
public static bool operator ==(OracleTimeStampTZ value1,
    OracleTimeStampTZ value2);
```

Parameters

- *value1*
The first OracleTimeStampTZ.
- *value2*
The second OracleTimeStampTZ.

Return Value

Returns true if they are equal; otherwise returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStampTZ that has a value is greater than an OracleTimeStampTZ that has a null value.
- Two OracleTimeStampTZs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

operator >

This static operator determines if the first of two OracleTimeStampTZ values is greater than the second.

Declaration

```
// C#
public static bool operator > (OracleTimeStampTZ value1,
    OracleTimeStampTZ value2);
```

Parameters

- *value1*
The first OracleTimeStampTZ.
- *value2*
The second OracleTimeStampTZ.

Return Value

Returns true if the first OracleTimeStampTZ value is greater than the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStampTZ that has a value is greater than an OracleTimeStampTZ that has a null value.
- Two OracleTimeStampTZs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

operator >=

This static operator determines if the first of two `OracleTimeStampTZ` values is greater than or equal to the second.

Declaration

```
// C#
public static bool operator >= (OracleTimeStampTZ value1,
    OracleTimeStampTZ value2);
```

Parameters

- *value1*
The first `OracleTimeStampTZ`.
- *value2*
The second `OracleTimeStampTZ`.

Return Value

Returns true if the first `OracleTimeStampTZ` is greater than or equal to the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZ`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

operator !=

This static operator determines if two `OracleTimeStampTZ` values are not equal.

Declaration

```
// C#
public static bool operator != (OracleTimeStampTZ value1,
    OracleTimeStampTZ value2);
```

Parameters

- *value1*

The first OracleTimeStampTZ.

- *value2*

The second OracleTimeStampTZ.

Return Value

Returns true if two OracleTimeStampTZ values are not equal; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStampTZ that has a value is greater than an OracleTimeStampTZ that has a null value.
- Two OracleTimeStampTZs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

operator <

This static operator determines if the first of two OracleTimeStampTZ values is less than the second.

Declaration

```
// C#
public static bool operator < (OracleTimeStampTZ value1,
    OracleTimeStampTZ value2);
```

Parameters

- *value1*
The first OracleTimeStampTZ.
- *value2*
The second OracleTimeStampTZ.

Return Value

Returns true if the first OracleTimeStampTZ is less than the second; otherwise returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStampTZ that has a value is greater than an OracleTimeStampTZ that has a null value.
- Two OracleTimeStampTZs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

operator <=

This static operator determines if the first of two `OracleTimeStampTZ` values is less than or equal to the second.

Declaration

```
// C#  
public static bool operator <= (OracleTimeStampTZ value1,  
    OracleTimeStampTZ value2);
```

Parameters

- *value1*
The first `OracleTimeStampTZ`.
- *value2*
The second `OracleTimeStampTZ`.

Return Value

Returns true if the first `OracleTimeStampTZ` is less than or equal to the second; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZs` that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

operator -

`operator-` subtracts the supplied value, from the supplied `OracleTimeStampTZ` value, and returns a new `OracleTimeStampTZ` structure.

Overload List:

- [operator - \(OracleTimeStampTZ, OracleIntervalDS\)](#)
This static operator subtracts the supplied `OracleIntervalDS` value, from the supplied `OracleTimeStampTZ` value, and return a new `OracleTimeStampTZ` structure.

- [operator - \(OracleTimeStampTZ, OracleIntervalYM\)](#)

This static operator subtracts the supplied `OracleIntervalYM` value, from the supplied `OracleTimeStampTZ` value, and returns a new `OracleTimeStampTZ` structure.

- [operator - \(OracleTimeStampTZ value1, TimeSpan value2\)](#)

This static operator subtracts the supplied `TimeSpan` value, from the supplied `OracleTimeStampTZ` value, and returns a new `OracleTimeStampTZ` structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

operator - (OracleTimeStampTZ, OracleIntervalDS)

This static operator subtracts the supplied `OracleIntervalDS` value, from the supplied `OracleTimeStampTZ` value, and return a new `OracleTimeStampTZ` structure.

Declaration

```
// C#
public static operator - (OracleTimeStampTZ value1,
    OracleIntervalDS value2);
```

Parameters

- *value1*
An `OracleTimeStampTZ`.
- *value2*
An `OracleIntervalDS`.

Return Value

An `OracleTimeStampTZ` structure.

Remarks

If either parameter has a null value, the returned `OracleTimeStampTZ` has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

operator - (OracleTimeStampTZ, OracleIntervalYM)

This static operator subtracts the supplied `OracleIntervalYM` value, from the supplied `OracleTimeStampTZ` value, and returns a new `OracleTimeStampTZ` structure.

Declaration

```
// C#
```

```
public static operator - (OracleTimeStampTZ value1,  
    OracleIntervalYM value2);
```

Parameters

- *value1*
An OracleTimeStampTZ.
- *value2*
An OracleIntervalYM.

Return Value

An OracleTimeStampTZ structure.

Remarks

If either parameter has a null value, the returned OracleTimeStampTZ has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

operator - (OracleTimeStampTZ value1, TimeSpan value2)

This static operator subtracts the supplied TimeSpan value, from the supplied OracleTimeStampTZ value, and returns a new OracleTimeStampTZ structure.

Declaration

```
// C#  
public static operator - (OracleTimeStampTZ value1, TimeSpan value2);
```

Parameters

- *value1*
An OracleTimeStampTZ.
- *value2*
A TimeSpan.

Return Value

An OracleTimeStampTZ structure.

Remarks

If the OracleTimeStampTZ instance has a null value, the returned OracleTimeStampTZ structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ Static Type Conversions

The OracleTimeStampTZ static type conversions are listed in [Table 14–136](#).

Table 14–136 OracleTimeStampTZ Static Type Conversions

| Operator | Description |
|-----------------------------------------------------|--------------------------------------------------------------------------------------|
| explicit operator OracleTimeStampTZ | Converts an instance value to an OracleTimeStampTZ structure (Overloaded) |
| implicit operator OracleTimeStampTZ | Converts an instance value to an OracleTimeStampTZ structure (Overloaded) |
| explicit operator DateTime | Converts an OracleTimeStampTZ value to a DateTime structure in the current time zone |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

explicit operator OracleTimeStampTZ

`explicit operator OracleTimeStampTZ` converts an instance value to an OracleTimeStampTZ structure.

Overload List:

- [explicit operator OracleTimeStampTZ\(OracleTimeStamp\)](#)
This static type conversion operator converts an OracleTimeStamp value to an OracleTimeStampTZ structure.
- [explicit operator OracleTimeStampTZ\(OracleTimeStampLTZ\)](#)
This static type conversion operator converts an OracleTimeStampLTZ value to an OracleTimeStampTZ structure.
- [explicit operator OracleTimeStampTZ\(string\)](#)
This static type conversion operator converts the supplied string value to an OracleTimeStampTZ structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125

explicit operator OracleTimeStampTZ(OracleTimeStamp)

This static type conversion operator converts an OracleTimeStamp value to an OracleTimeStampTZ structure.

Declaration

```
// C#  
public static explicit operator OracleTimeStampTZ(OracleTimeStamp value1);
```

Parameters

- *value1*
An OracleTimeStamp.

Return Value

The returned OracleTimeStampTZ contains the date and time from the OracleTimeStamp and the time zone from the OracleGlobalization.TimeZone of the thread.

Remarks

The OracleGlobalization.TimeZone of the thread is used to convert from an OracleTimeStamp structure to an OracleTimeStampTZ structure.

If the OracleTimeStamp structure has a null value, the returned OracleTimeStampTZ structure also has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125

explicit operator OracleTimeStampTZ(OracleTimeStampLTZ)

This static type conversion operator converts an OracleTimeStampLTZ value to an OracleTimeStampTZ structure.

Declaration

```
// C#  
public static explicit operator OracleTimeStampTZ(OracleTimeStampLTZ value1);
```

Parameters

- *value1*
An OracleTimeStampLTZ.

Return Value

The returned OracleTimeStampTZ contains the date and time from the OracleTimeStampLTZ and the time zone from the OracleGlobalization.TimeZone of the thread.

Remarks

If the OracleTimeStampLTZ structure has a null value, the returned OracleTimeStampTZ structure also has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125

explicit operator OracleTimeStampTZ(string)

This static type conversion operator converts the supplied string value to an OracleTimeStampTZ structure.

Declaration

```
// C#
public static explicit operator OracleTimeStampTZ(string tsStr);
```

Parameters

- *tsStr*
A string representation of an Oracle TIMESTAMP WITH TIME ZONE.

Return Value

An OracleTimeStampTZ value.

Exceptions

ArgumentException - The *tsStr* is an invalid string representation of an Oracle TIMESTAMP WITH TIME ZONE. or the *tsStr* is not in the timestamp format specified by the thread's OracleGlobalization.TimeStampTZFormat property, which represents the Oracle NLS_TIMESTAMP_TZ_FORMAT parameter.

Remarks

The names and abbreviations used for months and days are in the language specified by the DateLanguage and Calendar properties of the thread's OracleGlobalization object. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class OracleTimeStampTZSample
{
    static void Main()
    {
        // Set the nls_timestamp_tz_format for the explicit operator
        // OracleTimeStampTZ(string)
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.TimeStampTZFormat = "DD-MON-YYYY HH:MI:SS.FF AM TZR";
        OracleGlobalization.SetThreadInfo(info);
    }
}
```

```
// construct OracleTimeStampTZ from a string using the format specified.
OracleTimeStampTZ tstz = new OracleTimeStampTZ("11-NOV-1999" +
    "11:02:33.444 AM US/Pacific");

// Set the nls_timestamp_tz_format for the ToString() method
info.TimestampTZFormat = "YYYY-MON-DD HH:MI:SS.FF AM TZR";
OracleGlobalization.SetThreadInfo(info);
Console.WriteLine(tstz.ToString());
}
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125

implicit operator OracleTimeStampTZ

implicit operator OracleTimeStampTZ converts a DateTime structure to an OracleTimeStampTZ structure.

Overload List:

- [implicit operator OracleTimeStampTZ\(OracleDate\)](#)

This static type conversion operator converts an OracleDate value to an OracleTimeStampTZ structure.

- [implicit operator OracleTimeStampTZ\(DateTime\)](#)

This static type conversion operator converts a DateTime structure to an OracleTimeStampTZ structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125

implicit operator OracleTimeStampTZ(OracleDate)

This static type conversion operator converts an OracleDate value to an OracleTimeStampTZ structure.

Declaration

```
// C#
public static implicit operator OracleTimeStampTZ(OracleDate value1);
```


Parameters

- *value1*
An OracleDate.

Return Value

The returned OracleTimeStampTZ contains the date and time from the OracleDate and the time zone from the OracleGlobalization.TimeZone of the thread.

Remarks

The OracleGlobalization.TimeZone of the thread is used to convert from an OracleDate to an OracleTimeStampTZ structure. If the OracleDate structure has a null value, the returned OracleTimeStampTZ structure also has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125

implicit operator OracleTimeStampTZ(DateTime)

This static type conversion operator converts a DateTime structure to an OracleTimeStampTZ structure.

Declaration

```
// C#  
public static implicit operator OracleTimeStampTZ (DateTime value1);
```

Parameters

- *value1*
A DateTime structure.

Return Value

The returned OracleTimeStampTZ contains the date and time from the DateTime and the time zone from the OracleGlobalization.TimeZone of the thread.

Remarks

The OracleGlobalization.TimeZone of the thread is used to convert from a DateTime to an OracleTimeStampTZ structure.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125

explicit operator DateTime

This static type conversion operator converts an `OracleTimeStampTZ` value to a `DateTime` structure and truncates the time zone information.

Declaration

```
// C#  
public static explicit operator DateTime(OracleTimeStampTZ value1);
```

Parameters

- *value1*
An `OracleTimeStampTZ`.

Return Value

A `DateTime` containing the date and time in the current instance, but with the time zone information in the current instance truncated.

Exceptions

`OracleNullValueException` - The `OracleTimeStampTZ` structure has a null value.

Remarks

The precision of the `OracleTimeStampTZ` value can be lost during the conversion, and the time zone information in the current instance is truncated

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ Properties

The OracleTimeStampTZ properties are listed in [Table 14–137](#).

Table 14–137 OracleTimeStampTZ Properties

| Properties | Description |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------|
| BinData | Returns an array of bytes that represents an Oracle <code>TIMESTAMP WITH TIME ZONE</code> in Oracle internal format |
| Day | Specifies the day component of an OracleTimeStampTZ in the current time zone |
| IsNull | Indicates whether or not the current instance has a null value |
| Hour | Specifies the hour component of an OracleTimeStampTZ in the current time zone |
| Millisecond | Specifies the millisecond component of an OracleTimeStampTZ in the current time zone |
| Minute | Specifies the minute component of an OracleTimeStampTZ in the current time zone |
| Month | Specifies the month component of an OracleTimeStampTZ in the current time zone |
| Nanosecond | Specifies the nanosecond component of an OracleTimeStampTZ in the current time zone |
| Second | Specifies the second component of an OracleTimeStampTZ in the current time zone |
| TimeZone | Returns the time zone of the OracleTimeStampTZ instance |
| Value | Returns the date and time that is stored in the OracleTimeStampTZ structure in the current time zone |
| Year | Specifies the year component of an OracleTimeStampTZ |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

BinData

This property returns an array of bytes that represents an Oracle `TIMESTAMP WITH TIME ZONE` in Oracle internal format.

Declaration

```
// C#
public byte[] BinData {get;}
```

Property Value

The provided byte array that represents an Oracle `TIMESTAMP WITH TIME ZONE` in Oracle internal format.

Exceptions

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

Day

This property specifies the day component of an OracleTimeStampTZ in the current time zone.

Declaration

```
// C#  
public int Day{get;}
```

Property Value

A number that represents the day. Range of Day is (1 to 31).

Exceptions

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

IsNull

This property indicates whether or not the current instance has a null value.

Declaration

```
// C#  
public bool IsNull{get;}
```

Property Value

Returns true if the current instance has a null value. Otherwise, returns false.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

Hour

This property specifies the hour component of an OracleTimeStampTZ in the current time zone.

Declaration

```
// C#  
public int Hour{get;}
```

Property Value

A number that represents the hour. Range of Hour is (0 to 23).

Exceptions

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

Millisecond

This property gets the millisecond component of an OracleTimeStampTZ in the current time zone.

Declaration

```
// C#  
public double Millisecond{get;}
```

Property Value

A number that represents a millisecond. Range of Millisecond is (0 to 999.999999)

Exceptions

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

Minute

This property gets the minute component of an OracleTimeStampTZ in the current time zone.

Declaration

```
// C#  
public int Minute{get;}
```

Property Value

A number that represent a minute. Range of Minute is (0 to 59).

Exceptions

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

Month

This property gets the month component of an `OracleTimeStampTZ` in the current time zone

Declaration

```
// C#  
public int Month{get;}
```

Property Value

A number that represents a month. Range of `Month` is (1 to 12).

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

Nanosecond

This property gets the nanosecond component of an `OracleTimeStampTZ` in the current time zone.

Declaration

```
// C#  
public int Nanosecond{get;}
```

Property Value

A number that represents a nanosecond. Range of `Nanosecond` is (0 to 999999999).

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

Second

This property gets the second component of an `OracleTimeStampTZ` in the current time zone.

Declaration

```
// C#  
public int Second{get;}
```

Property Value

A number that represents a second. Range of `Second` is (0 to 59).

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

TimeZone

This property returns the time zone of the `OracleTimeStampTZ` instance.

Declaration

```
// C#  
public string TimeZone{get;}
```

Property Value

A string that represents the time zone.

Remarks

If no time zone is specified in the constructor, this property is set to the thread's `OracleGlobalization.TimeZone` by default

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125

Value

This property returns the date and time that is stored in the `OracleTimeStampTZ` structure in the current time zone.

Declaration

```
// C#
```

```
public DateTime Value{get;}
```

Property Value

A `DateTime` in the current time zone.

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

Year

This property sets the year component of an `OracleTimeStampTZ` in the current time zone.

Declaration

```
// C#  
public int Year{get;}
```

Property Value

A number that represents a year. The range of `Year` is (-4712 to 9999).

Exceptions

`OracleNullValueException` - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

OracleTimeStampTZ Methods

The OracleTimeStampTZ methods are listed in [Table 14–138](#).

Table 14–138 OracleTimeStampTZ Methods

| Methods | Description |
|--------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| AddDays | Adds the supplied number of days to the current instance |
| AddHours | Adds the supplied number of hours to the current instance |
| AddMilliseconds | Adds the supplied number of milliseconds to the current instance |
| AddMinutes | Adds the supplied number of minutes to the current instance |
| AddMonths | Adds the supplied number of months to the current instance |
| AddNanoseconds | Adds the supplied number of nanoseconds to the current instance |
| AddSeconds | Adds the supplied number of seconds to the current instance |
| AddYears | Adds the supplied number of years to the current instance |
| CompareTo | Compares the current OracleTimeStampTZ instance to an object, and returns an integer that represents their relative values |
| Equals | Determines whether or not an object has the same date and time as the current OracleTimeStampTZ instance (Overloaded) |
| GetDaysBetween | Subtracts an OracleTimeStampTZ from the current instance and returns an OracleIntervalDS that represents the time interval |
| GetHashCode | Returns a hash code for the OracleTimeStampTZ instance |
| GetTimeZoneOffset | Gets the time zone information in hours and minutes of the current OracleTimeStampTZ |
| GetYearsBetween | Subtracts an OracleTimeStampTZ from the current instance and returns an OracleIntervalYM that represents the time interval |
| GetType | Inherited from System.Object |
| ToLocalTime | Converts the current OracleTimeStampTZ instance to local time |
| ToOracleDate | Converts the current OracleTimeStampTZ structure to an OracleDate structure |
| ToOracleTimeStampLTZ | Converts the current OracleTimeStampTZ structure to an OracleTimeStampLTZ structure |
| ToOracleTimeStamp | Converts the current OracleTimeStampTZ structure to an OracleTimeStamp structure |
| ToString | Converts the current OracleTimeStampTZ structure to a string |
| ToUniversalTime | Converts the current datetime to Coordinated Universal Time (UTC) |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

AddDays

This method adds the supplied number of days to the current instance.

Declaration

```
// C#  
public OracleTimeStampTZ AddDays(double days);
```

Parameters

- *days*
The supplied number of days. Range is $(-1,000,000,000 < days < 1,000,000,000)$

Return Value

An OracleTimeStampTZ.

Exceptions

OracleNullValueException - The current instance has a null value.
ArgumentOutOfRangeException - The argument value is out of the specified range.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

AddHours

This method adds the supplied number of hours to the current instance.

Declaration

```
// C#  
public OracleTimeStampTZ AddHours(double hours);
```

Parameters

- *hours*
The supplied number of hours. Range is $(-24,000,000,000 < hours < 24,000,000,000)$.

Return Value

An OracleTimeStampTZ.

Exceptions

OracleNullValueException - The current instance has a null value.
ArgumentOutOfRangeException - The argument value is out of the specified range.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

AddMilliseconds

This method adds the supplied number of milliseconds to the current instance.

Declaration

```
// C#  
public OracleTimeStampTZ AddMilliseconds(double milliseconds);
```

Parameters

- *milliseconds*

The supplied number of milliseconds. Range is $(-8.64 * 1016 < milliseconds < 8.64 * 1016)$.

Return Value

An OracleTimeStampTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

ArgumentOutOfRangeException - The argument value is out of the specified range.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

AddMinutes

This method adds the supplied number of minutes to the current instance.

Declaration

```
// C#  
public OracleTimeStampTZ AddMinutes(double minutes);
```

Parameters

- *minutes*

The supplied number of minutes. Range is $(-1,440,000,000,000 < minutes < 1,440,000,000,000)$.

Return Value

An OracleTimeStampTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

ArgumentOutOfRangeException - The argument value is out of the specified range.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

AddMonths

This method adds the supplied number of months to the current instance.

Declaration

```
// C#  
public OracleTimeStampTZ AddMonths(long months);
```

Parameters

- *months*
The supplied number of months. Range is (-12,000,000,000 < *months* < 12,000,000,000).

Return Value

An OracleTimeStampTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

ArgumentOutOfRangeException - The argument value is out of the specified range.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

AddNanoseconds

This method adds the supplied number of nanoseconds to the current instance.

Declaration

```
// C#  
public OracleTimeStampTZ AddNanoseconds(long nanoseconds);
```

Parameters

- *nanoseconds*
The supplied number of nanoseconds.

Return Value

An OracleTimeStampTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

AddSeconds

This method adds the supplied number of seconds to the current instance.

Declaration

```
// C#  
public OracleTimeStampTZ AddSeconds(double seconds);
```

Parameters

- *seconds*

The supplied number of seconds. Range is $(-8.64 * 1013 < seconds < 8.64 * 1013)$.

Return Value

An OracleTimeStampTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

ArgumentOutOfRangeException - The argument value is out of the specified range.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

AddYears

This method adds the supplied number of years to the current instance

Declaration

```
// C#  
public OracleTimeStampTZ AddYears(int years);
```

Parameters

- *years*

The supplied number of years. Range is $(-999,999,999 \leq years \leq 999,999,999)$.

Return Value

An OracleTimeStampTZ.

Exceptions

OracleNullValueException - The current instance has a null value.

ArgumentOutOfRangeException - The argument value is out of the specified range.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

CompareTo

This method compares the current `OracleTimeStampTZ` instance to an object, and returns an integer that represents their relative values.

Declaration

```
// C#  
public int CompareTo(object obj);
```

Parameters

- *obj*

The object being compared to the current `OracleTimeStampTZ` instance.

Return Value

The method returns a number that is:

Less than zero: if the current `OracleTimeStampTZ` instance value is less than that of *obj*.

Zero: if the current `OracleTimeStampTZ` instance and *obj* values are equal.

Greater than zero: if the current `OracleTimeStampTZ` instance value is greater than that of *obj*.

Implements

`IComparable`

Exceptions

`ArgumentException` - The *obj* is not of type `OracleTimeStampTZ`.

Remarks

The following rules apply to the behavior of this method.

- The comparison must be between `OracleTimeStampTZ`s. For example, comparing an `OracleTimeStampTZ` instance with an `OracleBinary` instance is not allowed. When an `OracleTimeStampTZ` is compared with a different type, an `ArgumentException` is thrown.
- Any `OracleTimeStampTZ` that has a value is greater than an `OracleTimeStampTZ` that has a null value.
- Two `OracleTimeStampTZ`s that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

Equals

Overrides Object

This method determines whether or not an object has the same date and time as the current OracleTimeStampTZ instance.

Declaration

```
// C#  
public override bool Equals(object obj);
```

Parameters

- *obj*

The object being compared to the current OracleTimeStampTZ instance.

Return Value

Returns true if the *obj* is of type OracleTimeStampTZ and represents the same date and time; otherwise, returns false.

Remarks

The following rules apply to the behavior of this method.

- Any OracleTimeStampTZ that has a value is greater than an OracleTimeStampTZ that has a null value.
- Two OracleTimeStampTZs that contain a null value are equal.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

GetDaysBetween

This method subtracts an OracleTimeStampTZ value from the current instance and returns an OracleIntervalDS that represents the time interval.

Declaration

```
// C#  
public OracleIntervalDS GetDaysBetween(OracleTimeStampTZ value1);
```

Parameters

- *value1*

The OracleTimeStampTZ value being subtracted.

Return Value

An OracleIntervalDS that represents the interval between two OracleTimeStampTZ values.

Remarks

If either the current instance or the parameter has a null value, the returned OracleIntervalDS has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

GetHashCode

Overrides Object

This method returns a hash code for the OracleTimeStampTZ instance.

Declaration

```
// C#  
public override int GetHashCode();
```

Return Value

A number that represents the hash code.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

GetTimeZoneOffset

This method gets the time zone portion in hours and minutes of the current OracleTimeStampTZ.

Declaration

```
// C#  
public TimeSpan GetTimeZoneOffset();
```

Return Value

A TimeSpan.

Exceptions

OracleNullValueException - The current instance has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

GetYearsBetween

This method subtracts an OracleTimeStampTZ value from the current instance and returns an OracleIntervalYM that represents the time interval.

Declaration

```
// C#
public OracleIntervalYM GetYearsBetween(OracleTimeStampTZ val);
```

Parameters

- *val*

The OracleTimeStampTZ value being subtracted.

Return Value

An OracleIntervalYM that represents the interval between two OracleTimeStampTZ values.

Remarks

If either the current instance or the parameter has a null value, the returned OracleIntervalYM has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

ToLocalTime

This method converts the current OracleTimeStampTZ instance to local time.

Declaration

```
// C#
public OracleTimeStampLTZ ToLocalTime();
```

Return Value

An OracleTimeStampLTZ that contains the date and time, which is normalized to the client local time zone, in the current instance.

Remarks

If the current instance has a null value, the returned OracleTimeStampLTZ has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

ToOracleDate

This method converts the current OracleTimeStampTZ structure to an OracleDate structure.

Declaration

```
// C#
```

```
public OracleDate ToOracleDate();
```

Return Value

The returned `OracleDate` contains the date and time in the current instance, but the time zone information in the current instance is truncated.

Remarks

The precision of the `OracleTimeStampTZ` value can be lost during the conversion, and the time zone information in the current instance is truncated.

If the current instance has a null value, the value of the returned `OracleDate` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

ToOracleTimeStampLTZ

This method converts the current `OracleTimeStampTZ` structure to an `OracleTimeStampLTZ` structure.

Declaration

```
// C#  
public OracleTimeStampLTZ ToOracleTimeStampLTZ();
```

Return Value

The returned `OracleTimeStampLTZ` structure contains the date and time, which is normalized to the client local time zone, in the current instance.

Remarks

If the value of the current instance has a null value, the value of the returned `OracleTimeStampLTZ` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

ToOracleTimeStamp

This method converts the current `OracleTimeStampTZ` structure to an `OracleTimeStamp` structure.

Declaration

```
// C#  
public OracleTimeStamp ToOracleTimeStamp();
```

Return Value

The returned `OracleTimeStamp` contains the date and time in the current instance, but the time zone information is truncated.

Remarks

If the value of the current instance has a null value, the value of the returned `OracleTimeStamp` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

ToString

Overrides `Object`

This method converts the current `OracleTimeStampTZ` structure to a string.

Declaration

```
// C#
public override string ToString();
```

Return Value

A string that represents the same date and time as the current `OracleTimeStampTZ` structure.

Remarks

The returned value is a string representation of an `OracleTimeStampTZ` in the format specified by the `OracleGlobalization.TimeStampTZFormat` property of the thread. The names and abbreviations used for months and days are in the language specified by the `OracleGlobalization.DateLanguage` and the `OracleGlobalization.Calendar` properties of the thread. If any of the thread's globalization properties are set to null or an empty string, the client computer's settings are used.

Example

```
// C#

using System;
using Oracle.DataAccess.Client;
using Oracle.DataAccess.Types;

class ToStringSample
{
    static void Main()
    {
        // Set the nls parameters for the current thread
        OracleGlobalization info = OracleGlobalization.GetClientInfo();
        info.TimeZone = "US/Eastern";
        info.TimeStampFormat = "DD-MON-YYYY HH:MI:SS.FF AM";
        info.TimeStampTZFormat = "DD-MON-YYYY HH:MI:SS.FF AM TZR";
        OracleGlobalization.SetThreadInfo(info);

        // Create an OracleTimeStampTZ in US/Pacific time zone
```

```
OracleTimeStampTZ tstz1=new OracleTimeStampTZ("11-NOV-1999 "+
    "11:02:33.444 AM US/Pacific");

// Note that ToOracleTimeStampTZ uses the thread's time zone region,
// "US/Eastern"
OracleTimeStamp ts = new OracleTimeStamp("11-NOV-1999 11:02:33.444 AM");
OracleTimeStampTZ tstz2 = ts.ToOracleTimeStampTZ();

// Calculate the difference between tstz1 and tstz2
OracleIntervalDS idsDiff = tstz1.GetDaysBetween(tstz2);

// Prints "US/Pacific"
Console.WriteLine("tstz1.TimeZone = " + tstz1.TimeZone);

// Prints "US/Eastern"
Console.WriteLine("tstz2.TimeZone = " + tstz2.TimeZone);

// Prints 3
Console.WriteLine("idsDiff.Hours = " + idsDiff.Hours);

// Prints 0
Console.WriteLine("idsDiff.Minutes = " + idsDiff.Minutes);
}
}
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)
- ["OracleGlobalization Class"](#) on page 10-2
- ["Globalization Support"](#) on page 3-125

ToUniversalTime

This method converts the current datetime to Coordinated Universal Time (UTC).

Declaration

```
// C#
public OracleTimeStampTZ ToUniversalTime();
```

Return Value

An `OracleTimeStampTZ` structure.

Remarks

If the current instance has a null value, the value of the returned `OracleTimeStampTZ` structure has a null value.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTimeStampTZ Structure](#)
- [OracleTimeStampTZ Members](#)

INullable Interface

The `INullable` interface is used to determine whether or not an ODP.NET type has a NULL value.

Declaration

```
// C#  
public interface INullable
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|---------------------------|--------------------------------|
| Assembly | Oracle.DataAccess.dll | Oracle.ManagedDataAccess.dll |
| Namespace | Oracle.DataAccess.Types | Oracle.ManagedDataAccess.Types |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [INullable Interface Members](#)
- [INullable Interface Properties](#)

INullable Interface Members

INullable members are listed in the following tables.

INullable Interface Properties

INullable interface properties are listed in [Table 14–139](#).

Table 14–139 *INullable Interface Properties*

| Public Property | Description |
|------------------------|------------------------------------------------------------|
| IsNull | Indicates whether or not the ODP.NET type has a NULL value |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [INullable Interface](#)

INullable Interface Properties

INullable interface properties are listed in [Table 14-139](#).

Table 14-140 *INullable Interface Properties*

| Public Property | Description |
|------------------------|------------------------------------------------------------|
| IsNull | Indicates whether or not the ODP.NET type has a NULL value |

IsNull

This property indicates whether or not the ODP.NET type has a NULL value.

Declaration

```
// C#  
bool IsNull {get;}
```

Property Value

Returns true if the ODP.NET type has a NULL value; otherwise, returns false.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [INullable Interface](#)
- [INullable Interface Members](#)

Oracle Data Provider for .NET Types Exceptions

This section covers the ODP.NET Types exceptions.

This chapter contains these topics:

- [OracleTypeException Class](#)
- [OracleNullValueException Class](#)
- [OracleTruncateException Class](#)

OracleTypeException Class

The `OracleTypeException` is the base exception class for handling exceptions that occur in the ODP.NET Types classes.

Class Inheritance

`System.Object`

`System.Exception`

`System.SystemException`

`Oracle.DataAccess.Types.OracleTypeException`

Declaration

```
// C#  
public class OracleTypeException : SystemException
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|--------------------------------------|---------------------------------------------|
| Assembly | <code>Oracle.DataAccess.dll</code> | <code>Oracle.ManagedDataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Types</code> | <code>Oracle.ManagedDataAccess.Types</code> |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleTypeException Members](#)
- [OracleTypeException Constructors](#)
- [OracleTypeException Static Methods](#)
- [OracleTypeException Properties](#)
- [OracleTypeException Methods](#)

OracleTypeException Members

OracleTypeException members are listed in the following tables.

OracleTypeException Constructors

The OracleTypeException constructors are listed in [Table 15-1](#).

Table 15-1 OracleTypeException Constructor

| Constructor | Description |
|--------------------------------------------------|----------------------------------------------------------------------|
| OracleTypeException Constructors | Creates a new instance of the OracleTypeException class (Overloaded) |

OracleTypeException Static Methods

The OracleTypeException static methods are listed in [Table 15-2](#).

Table 15-2 OracleTypeException Static Methods

| Methods | Description |
|---------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

OracleTypeException Properties

The OracleTypeException properties are listed in [Table 15-3](#).

Table 15-3 OracleTypeException Properties

| Properties | Description |
|-------------------------|------------------------------------------------------------------|
| HelpLink | Inherited from System.SystemException.Exception |
| InnerException | Inherited from System.SystemException.Exception |
| Message | Specifies the error messages that occur in the exception |
| Number | Specifies the error number that occurs in the exception |
| Source | Specifies the name of the data provider that generates the error |
| StackTrace | Inherited from System.SystemException.Exception |
| TargetSite | Inherited from System.SystemException.Exception |

OracleTypeException Methods

The OracleTypeException methods are listed in [Table 15-4](#).

Table 15-4 OracleTypeException Methods

| Methods | Description |
|------------------|-------------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |
| GetBaseException | Inherited from System.SystemException.Exception |

Table 15–4 (Cont.) OracleTypeException Methods

| Methods | Description |
|--------------------------|----------------------------------------------------|
| GetHashCode | Inherited from System.Object |
| GetObjectData | Inherited from System.SystemException.Exception |
| GetType | Inherited from System.Object |
| ToString | Returns the fully qualified name of this exception |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTypeException Class](#)

OracleTypeException Constructors

The `OracleTypeException` constructors create new instances of the `OracleTypeException` class.

Overload List:

- [OracleTypeException\(string\)](#)

This constructor creates a new instance of the `OracleTypeException` class with the specified error message, `errorMessage`.

- [OracleTypeException\(SerializationInfo, StreamingContext\)](#)

This constructor creates a new instance of the `OracleTypeException` class with the specified serialization information, `si`, and the specified streaming context, `sc`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)

OracleTypeException(string)

This constructor creates a new instance of the `OracleTypeException` class with the specified error message, `errorMessage`.

Declaration

```
// C#  
public OracleTypeException (string errorMessage);
```

Parameters

- `errorMessage`

The specified error message.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)

OracleTypeException(SerializationInfo, StreamingContext)

This constructor creates a new instance of the `OracleTypeException` class with the specified serialization information, `si`, and the specified streaming context, `sc`.

Declaration

```
// C#  
protected OracleTypeException (SerializationInfo si, StreamingContext sc);
```

Parameters

- `si`

The specified serialization information.

- *sc*

The specified streaming context.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)

OracleTypeException Static Methods

The OracleTypeException static methods are listed in [Table 15-5](#).

Table 15-5 OracleTypeException Static Methods

| Methods | Description |
|---------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)

OracleTypeException Properties

The OracleTypeException properties are listed in [Table 15–6](#).

Table 15–6 OracleTypeException Properties

| Properties | Description |
|-------------------------|------------------------------------------------------------------|
| HelpLink | Inherited from System.SystemException.Exception |
| InnerException | Inherited from System.SystemException.Exception |
| Message | Specifies the error messages that occur in the exception |
| Number | Specifies the error number that occurs in the exception |
| Source | Specifies the name of the data provider that generates the error |
| StackTrace | Inherited from System.SystemException.Exception |
| TargetSite | Inherited from System.SystemException.Exception |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)

Message

Overrides Exception

This property specifies the error messages that occur in the exception.

Declaration

```
// C#
public override string Message {get;}
```

Property Value

An error message.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)

Number

Overrides Exception

This property specifies the error number that occurs in the exception

Declaration

```
// C#
public override int Number {get;}
```


Property Value

An error number

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)

Source

Overrides Exception

This property specifies the name of the data provider that generates the error.

Declaration

```
// C#  
public override string Source {get;}
```

Property Value

Oracle Data Provider for .NET.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)

OracleTypeException Methods

The OracleTypeException methods are listed in [Table 15-7](#).

Table 15-7 OracleTypeException Methods

| Methods | Description |
|--------------------------|----------------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |
| GetBaseException | Inherited from System.SystemException.Exception |
| GetHashCode | Inherited from System.Object |
| GetObjectData | Inherited from System.SystemException.Exception |
| GetType | Inherited from System.Object |
| ToString | Returns the fully qualified name of this exception |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)

ToString

Overrides Exception

This method returns the fully qualified name of this exception, the error message in the Message property, the InnerException.ToString() message, and the stack trace.

Declaration

```
// C#  
public override string ToString();
```

Return Value

The fully qualified name of this exception.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTypeException Class](#)
- [OracleTypeException Members](#)

OracleNullValueException Class

The `OracleNullValueException` represents an exception that is thrown when trying to access an ODP.NET Types structure that has a null value.

Class Inheritance

`System.Object`

`System.Exception`

`System.SystemException`

`System.OracleTypeException`

`Oracle.DataAccess.Types.OracleNullValueException`

Declaration

```
// C#
public sealed class OracleNullValueException : OracleTypeException
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|--------------------------------------|---------------------------------------------|
| Assembly | <code>Oracle.DataAccess.dll</code> | <code>Oracle.ManagedDataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Types</code> | <code>Oracle.ManagedDataAccess.Types</code> |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleNullValueException Members](#)
- [OracleNullValueException Constructors](#)
- [OracleNullValueException Static Methods](#)
- [OracleNullValueException Properties](#)
- [OracleNullValueException Methods](#)

OracleNullValueException Members

OracleNullValueException members are listed in the following tables.

OracleNullValueException Constructors

The OracleNullValueException constructors are listed in [Table 15-8](#).

Table 15-8 OracleNullValueException Constructors

| Constructor | Description |
|-------------------------------------------------------|---------------------------------------------------------------------------|
| OracleNullValueException Constructors | Creates a new instance of the OracleNullValueException class (Overloaded) |

OracleNullValueException Static Methods

The OracleNullValueException static methods are listed in [Table 15-9](#).

Table 15-9 OracleNullValueException Static Methods

| Methods | Description |
|---------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

OracleNullValueException Properties

The OracleNullValueException properties are listed in [Table 15-10](#).

Table 15-10 OracleNullValueException Properties

| Properties | Description |
|----------------|-------------------------------------------------|
| HelpLink | Inherited from System.SystemException.Exception |
| InnerException | Inherited from System.SystemException.Exception |
| Message | Inherited from OracleTypeException |
| Source | Inherited from OracleTypeException |
| StackTrace | Inherited from System.SystemException.Exception |
| TargetSite | Inherited from System.SystemException.Exception |

OracleNullValueException Methods

The OracleNullValueException methods are listed in [Table 15-11](#).

Table 15-11 OracleNullValueException Methods

| Methods | Description |
|------------------|-------------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |
| GetBaseException | Inherited from System.SystemException.Exception |
| GetHashCode | Inherited from System.Object |
| GetObjectData | Inherited from System.SystemException.Exception |

Table 15–11 (Cont.) OracleNullValueException Methods

| Methods | Description |
|----------|------------------------------------|
| GetType | Inherited from System.Object |
| ToString | Inherited from OracleTypeException |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleNullValueException Class](#)

OracleNullValueException Constructors

The `OracleNullValueException` constructors create new instances of the `OracleNullValueException` class.

Overload List:

- [OracleNullValueException\(\)](#)
This constructor creates a new instance of the `OracleNullValueException` class with its default properties.
- [OracleNullValueException\(string\)](#)
This constructor creates a new instance of the `OracleNullValueException` class with the specified error message, `errorMessage`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleNullValueException Class](#)
- [OracleNullValueException Members](#)

OracleNullValueException()

This constructor creates a new instance of the `OracleNullValueException` class with its default properties.

Declaration

```
// C#  
public OracleNullValueException();
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleNullValueException Class](#)
- [OracleNullValueException Members](#)

OracleNullValueException(string)

This constructor creates a new instance of the `OracleNullValueException` class with the specified error message, `errorMessage`.

Declaration

```
// C#  
public OracleNullValueException (string errorMessage);
```

Parameters

- *errorMessage*
The specified error message.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleNullValueException Class](#)
- [OracleNullValueException Members](#)

OracleNullValueException Static Methods

The OracleNullValueException static methods are listed in [Table 15–12](#).

Table 15–12 OracleNullValueException Static Methods

| Methods | Description |
|---------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleNullValueException Class](#)
- [OracleNullValueException Members](#)

OracleNullValueException Properties

The OracleNullValueException properties are listed in [Table 15–13](#).

Table 15–13 OracleNullValueException Properties

| Properties | Description |
|----------------|-------------------------------------------------|
| HelpLink | Inherited from System.SystemException.Exception |
| InnerException | Inherited from System.SystemException.Exception |
| Message | Inherited from OracleTypeException |
| Source | Inherited from OracleTypeException |
| StackTrace | Inherited from System.SystemException.Exception |
| TargetSite | Inherited from System.SystemException.Exception |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleNullValueException Class](#)
- [OracleNullValueException Members](#)

OracleNullValueException Methods

The OracleNullValueException methods are listed in [Table 15-14](#).

Table 15-14 OracleNullValueException Methods

| Methods | Description |
|------------------|-------------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |
| GetBaseException | Inherited from System.SystemException.Exception |
| GetHashCode | Inherited from System.Object |
| GetObjectData | Inherited from System.SystemException.Exception |
| GetType | Inherited from System.Object |
| ToString | Inherited from OracleTypeException |

OracleTruncateException Class

The `OracleTruncateException` class represents an exception that is thrown when truncation in a `ODP.NET Types` class occurs.

Class Inheritance

`System.Object`

`System.Exception`

`System.SystemException`

`System.OracleTypeException`

`Oracle.DataAccess.Types.OracleTruncateException`

Declaration

```
// C#
public sealed class OracleTruncateException : OracleTypeException
```

Requirements

| Provider | ODP.NET, Unmanaged Driver | ODP.NET, Managed Driver |
|----------------|--------------------------------------|---------------------------------------------|
| Assembly | <code>Oracle.DataAccess.dll</code> | <code>Oracle.ManagedDataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Types</code> | <code>Oracle.ManagedDataAccess.Types</code> |
| .NET Framework | 3.5, 4.0, 4.5 | 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleTruncateException Members](#)
- [OracleTruncateException Constructors](#)
- [OracleTruncateException Static Methods](#)
- [OracleTruncateException Properties](#)
- [OracleTruncateException Methods](#)

OracleTruncateException Members

OracleTruncateException members are listed in the following tables.

OracleTruncateException Constructors

The OracleTruncateException constructors are listed in [Table 15–15](#).

Table 15–15 OracleTruncateException Constructors

| Constructor | Description |
|------------------------------------------------------|--------------------------------------------------------------------------|
| OracleTruncateException Constructors | Creates a new instance of the OracleTruncateException class (Overloaded) |

OracleTruncateException Static Methods

The OracleTruncateException static methods are listed in [Table 15–16](#).

Table 15–16 OracleTruncateException Static Methods

| Methods | Description |
|---------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

OracleTruncateException Properties

The OracleTruncateException properties are listed in [Table 15–17](#).

Table 15–17 OracleTruncateException Properties

| Properties | Description |
|----------------|-------------------------------------------------|
| HelpLink | Inherited from System.SystemException.Exception |
| InnerException | Inherited from System.SystemException.Exception |
| Message | Inherited from OracleTypeException |
| Source | Inherited from OracleTypeException |
| StackTrace | Inherited from System.SystemException.Exception |
| TargetSite | Inherited from System.SystemException.Exception |

OracleTruncateException Methods

The OracleTruncateException methods are listed in [Table 15–18](#).

Table 15–18 OracleTruncateException Methods

| Methods | Description |
|------------------|-------------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |
| GetBaseException | Inherited from System.SystemException.Exception |
| GetHashCode | Inherited from System.Object |
| GetObjectData | Inherited from System.SystemException.Exception |

Table 15–18 (Cont.) OracleTruncateException Methods

| Methods | Description |
|----------|------------------------------------|
| GetType | Inherited from System.Object |
| ToString | Inherited from OracleTypeException |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTruncateException Class](#)

OracleTruncateException Constructors

The `OracleTruncateException` constructors create new instances of the `OracleTruncateException` class

Overload List:

- [OracleTruncateException\(\)](#)
This constructor creates a new instance of the `OracleTruncateException` class with its default properties.
- [OracleTruncateException\(string\)](#)
This constructor creates a new instance of the `OracleTruncateException` class with the specified error message, `errorMessage`.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTruncateException Class](#)
- [OracleTruncateException Members](#)

OracleTruncateException()

This constructor creates a new instance of the `OracleTruncateException` class with its default properties.

Declaration

```
// C#  
public OracleTruncateException();
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTruncateException Class](#)
- [OracleTruncateException Members](#)

OracleTruncateException(string)

This constructor creates a new instance of the `OracleTruncateException` class with the specified error message, `errorMessage`.

Declaration

```
// C#  
public OracleTruncateException (string errorMessage);
```

Parameters

- *errorMessage*
The specified error message.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleTruncateException Class](#)
- [OracleTruncateException Members](#)

OracleTruncateException Static Methods

The OracleTruncateException static methods are listed in [Table 15–19](#).

Table 15–19 OracleTruncateException Static Methods

| Methods | Description |
|---------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTruncateException Class](#)
- [OracleTruncateException Members](#)

OracleTruncateException Properties

The OracleTruncateException properties are listed in [Table 15–20](#).

Table 15–20 OracleTruncateException Properties

| Properties | Description |
|----------------|-------------------------------------------------|
| HelpLink | Inherited from System.SystemException.Exception |
| InnerException | Inherited from System.SystemException.Exception |
| Message | Inherited from OracleTypeException |
| Source | Inherited from OracleTypeException |
| StackTrace | Inherited from System.SystemException.Exception |
| TargetSite | Inherited from System.SystemException.Exception |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTruncateException Class](#)
- [OracleTruncateException Members](#)

OracleTruncateException Methods

The OracleTruncateException methods are listed in [Table 15–21](#).

Table 15–21 OracleTruncateException Methods

| Methods | Description |
|------------------|-------------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |
| GetBaseException | Inherited from System.SystemException.Exception |
| GetHashCode | Inherited from System.Object |
| GetObjectData | Inherited from System.SystemException.Exception |
| GetType | Inherited from System.Object |
| ToString | Inherited from OracleTypeException |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleTruncateException Class](#)
- [OracleTruncateException Members](#)

Oracle Data Provider for .NET UDT-Related Classes

This chapter describes the object-related classes and interfaces in the Oracle Data Provider for .NET that provide support for Oracle user-defined data types (UDT).

Samples are provided in the `ORACLE_BASE\ORACLE_HOME\ODP.NET\Samples\UDT` directory.

- [OracleCustomTypeMappingAttribute Class](#)
- [OracleObjectMappingAttribute Class](#)
- [OracleArrayMappingAttribute Class](#)
- [IOracleCustomType Interface](#)
- [IOracleCustomTypeFactory Interface](#)
- [IOracleArrayTypeFactory Interface](#)
- [OracleUdt Class](#)
- [OracleRef Class](#)
- [OracleUdtFetchOption Enumeration](#)
- [OracleUdtStatus Enumeration](#)

OracleCustomTypeMappingAttribute Class

The `OracleCustomTypeMappingAttribute` class is used to mark a custom type factory class or struct with information that is used by ODP.NET when a custom type is used to represent an Oracle UDT.

Class Inheritance

`System.Object`

`System.Attribute`

`System.OracleCustomTypeMappingAttribute`

Declaration

```
// C#
[AttributeUsageAttribute(AttributeTargets.Class|AttributeTargets.Struct,
    AllowMultiple=false, Inherited=true)]
public sealed class OracleCustomTypeMappingAttribute : Attribute
```

Requirements

| | |
|-----------------------|--------------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | <code>Oracle.DataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Types</code> |
| .NET Framework | 3.5, 4.0, 4.5 |

Remarks

The `OracleCustomTypeMapping` attribute must be specified on the custom type factory class to indicate the Oracle UDT that the corresponding custom type represents. The Oracle UDT may be specified in the form `schema_name.type_name`.

For each Oracle UDT that the application uses, there must be a unique custom type factory, as follows:

- Oracle Object Types

The custom type factory must return a custom type that cannot be used to represent any other Oracle Object Type.
- Oracle Collection Types

The custom type factory may return a custom type that can be used by other Oracle Collection Types. This is common when an array type is used to represent an Oracle Collection, that is, when an `int []` is used to represent a collection of NUMBERS.

If the `OracleCustomTypeMappingAttribute` is not specified, then custom type mappings must be specified through an XML configuration file, for example, `app.config` for Windows applications or the `web.config` for web applications, and the `machine.config`

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleCustomTypeMappingAttribute Members](#)
- [OracleCustomTypeMappingAttribute Constructors](#)
- [OracleCustomTypeMappingAttribute Static Methods](#)
- [OracleCustomTypeMappingAttribute Methods](#)

OracleCustomTypeMappingAttribute Members

OracleCustomTypeMappingAttribute members are listed in the following tables.

OracleCustomTypeMappingAttribute Constructors

OracleCustomTypeMappingAttribute constructors are listed in [Table 16-1](#).

Table 16-1 OracleCustomTypeMappingAttribute Constructors

| Constructor | Description |
|---------------------------------------------------------------|-----------------------------------------------------------------------|
| OracleCustomTypeMappingAttribute Constructors | Instantiates a new instance of OracleCustomTypeMappingAttribute class |

OracleCustomTypeMappingAttribute Static Methods

OracleCustomTypeMappingAttribute static methods are listed in [Table 16-2](#).

Table 16-2 OracleCustomTypeMappingAttribute Static Methods

| Method | Description |
|---------------------|---------------------------------|
| Equals | Inherited from System.Attribute |
| GetCustomAttribute | Inherited from System.Attribute |
| GetCustomAttributes | Inherited from System.Attribute |
| IsDefined | Inherited from System.Attribute |
| ReferenceEquals | Inherited from System.Attribute |

OracleCustomTypeMappingAttribute Properties

OracleCustomTypeMappingAttribute properties are listed in [Table 16-3](#).

Table 16-3 OracleCustomTypeMappingAttribute Properties

| Property | Description |
|-----------------------------|---------------------------------------------------------------------------|
| UdtTypeName | Specifies the Oracle user-defined type name that the custom class maps to |
| TypeId | Inherited from System.Attribute |

OracleCustomTypeMappingAttribute Methods

OracleCustomTypeMappingAttribute methods are listed in [Table 16-4](#).

Table 16-4 OracleCustomTypeMappingAttribute Methods

| Method | Description |
|--------------------|---------------------------------|
| Equals | Inherited from System.Attribute |
| GetHashCode | Inherited from System.Attribute |
| GetType | Inherited from System.Attribute |
| IsDefaultAttribute | Inherited from System.Attribute |
| Match | Inherited from System.Attribute |
| ToString | Inherited from System.Attribute |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleCustomTypeMappingAttribute Class](#)

OracleCustomTypeMappingAttribute Constructors

OracleCustomTypeMappingAttribute constructors create new instances of the OracleCustomTypeMappingAttribute class.

Overload List:

- [OracleCustomTypeMappingAttribute\(string\)](#)

This constructor creates and initializes an OracleCustomTypeMappingAttribute using the specified Oracle user-defined type name.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleCustomTypeMappingAttribute Class](#)
- [OracleCustomTypeMappingAttribute Methods](#)

OracleCustomTypeMappingAttribute(string)

This constructor creates and initializes an OracleCustomTypeMappingAttribute using the specified Oracle user-defined type name.

Declaration

```
// C#  
public OracleCustomTypeMappingAttribute(string udtTypeName)
```

Parameters

- *udtTypeName*

The Oracle user-defined type name that the custom class maps to.

Remarks

The *udtTypeName* parameter is case-sensitive. The *udtTypeName* is specified in the form of *schema_name.type_name*.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleCustomTypeMappingAttribute Class](#)
- [OracleCustomTypeMappingAttribute Members](#)

OracleCustomTypeMappingAttribute Static Methods

OracleCustomTypeMappingAttribute static methods are listed in [Table 16–5](#).

Table 16–5 OracleCustomTypeMappingAttribute Static Methods

| Method | Description |
|---------------------|---------------------------------|
| Equals | Inherited from System.Attribute |
| GetCustomAttribute | Inherited from System.Attribute |
| GetCustomAttributes | Inherited from System.Attribute |
| IsDefined | Inherited from System.Attribute |
| ReferenceEquals | Inherited from System.Attribute |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleCustomTypeMappingAttribute Class](#)
- [OracleCustomTypeMappingAttribute Members](#)

OracleCustomTypeMappingAttribute Properties

OracleCustomTypeMappingAttribute properties are listed in [Table 16–6](#).

Table 16–6 OracleCustomTypeMappingAttribute Properties

| Property | Description |
|-----------------------------|---------------------------------------------------------------------------|
| UdtTypeName | Specifies the Oracle user-defined type name that the custom class maps to |
| TypeId | Inherited from <code>System.Attribute</code> |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleCustomTypeMappingAttribute Class](#)
- [OracleCustomTypeMappingAttribute Members](#)

UdtTypeName

This property specifies the Oracle user-defined type name that the custom class maps to.

Declaration

```
// C#  
public string UdtTypeName {get; set;}
```

Property Value

A string that represents an Oracle user-defined type name.

Remarks

UdtTypeName is case-sensitive. It is specified in the form of *schema_name.type_name*.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleCustomTypeMappingAttribute Class](#)
- [OracleCustomTypeMappingAttribute Members](#)

OracleCustomTypeMappingAttribute Methods

OracleCustomTypeMappingAttribute methods are listed in [Table 16-7](#).

Table 16-7 OracleCustomTypeMappingAttribute Methods

| Method | Description |
|--------------------|---------------------------------|
| Equals | Inherited from System.Attribute |
| GetHashCode | Inherited from System.Attribute |
| GetType | Inherited from System.Attribute |
| IsDefaultAttribute | Inherited from System.Attribute |
| Match | Inherited from System.Attribute |
| ToString | Inherited from System.Attribute |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleCustomTypeMappingAttribute Class](#)
- [OracleCustomTypeMappingAttribute Members](#)

OracleObjectMappingAttribute Class

The `OracleObjectMappingAttribute` class marks custom class fields or properties with information that ODP.NET uses when a custom type represents an Oracle Object type.

Class Inheritance

`System.Object`

`System.Attribute`

`System.OracleObjectMappingAttribute`

Declaration

```
// C#
[AttributeUsageAttribute(AttributeTargets.Field|AttributeTargets.Property,
AllowMultiple=false, Inherited=true)]
```

```
public sealed class OracleObjectMappingAttribute : Attribute
```

Requirements

| | |
|-----------------------|--------------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | <code>Oracle.DataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Types</code> |
| .NET Framework | 3.5, 4.0, 4.5 |

Remarks

The `OracleObjectMappingAttribute` is specified on members of a custom type that represent an Oracle object type. This attribute must specify the name or zero-based index of the attribute in the Oracle object that the custom class field or property maps to. This also allows the custom type to declare field or property names which differ from the Oracle Object type.

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleObjectMappingAttribute Members](#)
- [OracleObjectMappingAttribute Constructors](#)
- [OracleObjectMappingAttribute Static Methods](#)
- [OracleObjectMappingAttribute Properties](#)
- [OracleObjectMappingAttribute Methods](#)

OracleObjectMappingAttribute Members

OracleObjectMappingAttribute members are listed in the following tables.

OracleObjectMappingAttribute Constructors

OracleObjectMappingAttribute constructors are listed in [Table 16–8](#).

Table 16–8 OracleObjectMappingAttribute Constructors

| Constructor | Description |
|-----------------------------------------------------------|--------------------------------------------------------------------------------|
| OracleObjectMappingAttribute Constructors | Instantiates a new instance of OracleObjectMappingAttribute class (Overloaded) |

OracleObjectMappingAttribute Static Methods

OracleObjectMappingAttribute static methods are listed in [Table 16–9](#).

Table 16–9 OracleObjectMappingAttribute Static Methods

| Method | Description |
|---------------------|---------------------------------|
| Equals | Inherited from System.Attribute |
| GetCustomAttribute | Inherited from System.Attribute |
| GetCustomAttributes | Inherited from System.Attribute |
| IsDefined | Inherited from System.Attribute |
| ReferenceEquals | Inherited from System.Attribute |

OracleObjectMappingAttribute Properties

OracleObjectMappingAttribute properties are listed in [Table 16–10](#).

Table 16–10 OracleObjectMappingAttribute Properties

| Property | Description |
|--------------------------------|---------------------------------------------------------------------------|
| AttributeIndex | Specifies the index of the Oracle Object attribute that must be retrieved |
| AttributeName | Specifies the name of Oracle Object attribute that must be retrieved |
| TypeId | Inherited from System.Attribute |

OracleObjectMappingAttribute Methods

OracleObjectMappingAttribute methods are listed in [Table 16–11](#).

Table 16–11 OracleObjectMappingAttribute Methods

| Method | Description |
|--------------------|---------------------------------|
| Equals | Inherited from System.Attribute |
| GetHashCode | Inherited from System.Attribute |
| GetType | Inherited from System.Attribute |
| IsDefaultAttribute | Inherited from System.Attribute |
| Match | Inherited from System.Attribute |

Table 16–11 (Cont.) OracleObjectMappingAttribute Methods

| Method | Description |
|-----------------------|----------------------------------------------|
| <code>ToString</code> | Inherited from <code>System.Attribute</code> |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleObjectMappingAttribute Class](#)

OracleObjectMappingAttribute Constructors

OracleObjectMappingAttribute constructors create new instances of the OracleObjectMappingAttribute class.

Overload List:

- [OracleObjectMappingAttribute\(string\)](#)
This constructor creates and initializes an OracleObjectMappingAttribute object with the specified Oracle Object attribute name.
- [OracleObjectMappingAttribute\(int\)](#)
This constructor creates and initializes an OracleObjectMappingAttribute with the specified Oracle Object attribute index.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleObjectMappingAttribute Class](#)
- [OracleObjectMappingAttribute Members](#)

OracleObjectMappingAttribute(string)

This constructor creates and initializes an OracleObjectMappingAttribute object with the specified Oracle Object attribute name.

Declaration

```
// C#  
public OracleObjectMappingAttribute(string attrName);
```

Parameters

- *attrName*
The name of the Oracle Object attribute to map to.

Remarks

The *attrName* parameter is case-sensitive.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleObjectMappingAttribute Class](#)
- [OracleObjectMappingAttribute Members](#)

OracleObjectMappingAttribute(int)

This constructor creates and initializes an OracleObjectMappingAttribute object with the specified Oracle Object attribute index.

Declaration

```
// C#
```

```
public OracleObjectMappingAttribute(int attrIndex);
```

Parameters

- *attrIndex*

The zero-based index of the Oracle Object attribute to map to.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleObjectMappingAttribute Class](#)
- [OracleObjectMappingAttribute Members](#)

OracleObjectMappingAttribute Static Methods

OracleObjectMappingAttribute static methods are listed in [Table 16–12](#).

Table 16–12 OracleObjectMappingAttribute Static Method

| Method | Description |
|---------------------|---------------------------------|
| Equals | Inherited from System.Attribute |
| GetCustomAttribute | Inherited from System.Attribute |
| GetCustomAttributes | Inherited from System.Attribute |
| IsDefined | Inherited from System.Attribute |
| ReferenceEquals | Inherited from System.Attribute |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleObjectMappingAttribute Class](#)
- [OracleObjectMappingAttribute Members](#)

OracleObjectMappingAttribute Properties

OracleObjectMappingAttribute properties are listed in [Table 16–13](#).

Table 16–13 OracleObjectMappingAttribute Properties

| Property | Description |
|--------------------------------|---------------------------------------------------------------------------|
| AttributeIndex | Specifies the index of the Oracle Object attribute that must be retrieved |
| AttributeName | Specifies the name of the Oracle Object attribute that must be retrieved |
| TypeId | Inherited from System.Attribute |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleObjectMappingAttribute Class](#)
- [OracleObjectMappingAttribute Members](#)

AttributeIndex

This property specifies the index of the Oracle Object attribute that must be retrieved.

Declaration

```
// C#
public int AttributeIndex {get;}
```

Property Value

The zero-based index of an Oracle Object type attribute.

Remarks

The AttributeIndex property specifies the index of the Oracle Object type attribute that the custom class field or property maps to. This allows the custom class to declare fields or property names that differ from the Oracle object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleObjectMappingAttribute Class](#)
- [OracleObjectMappingAttribute Members](#)

AttributeName

This property specifies the name of the Oracle Object attribute that must be retrieved.

Declaration

```
// C#
public string AttributeName {get;}
```

Property Value

The name of an attribute of an Oracle Object type.

Remarks

The `AttributeName` property specifies name of the attribute in the Oracle Object type that the custom class field or property maps to. This allows the custom class to declare field or property names that differ from the Oracle object.

The specified attribute name is case-sensitive.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleObjectMappingAttribute Class](#)
- [OracleObjectMappingAttribute Members](#)

OracleObjectMappingAttribute Methods

OracleObjectMappingAttribute methods are listed in [Table 16–14](#).

Table 16–14 *OracleObjectMappingAttribute Methods*

| Method | Description |
|--------------------|---------------------------------|
| Equals | Inherited from System.Attribute |
| GetHashCode | Inherited from System.Attribute |
| GetType | Inherited from System.Attribute |
| IsDefaultAttribute | Inherited from System.Attribute |
| Match | Inherited from System.Attribute |
| ToString | Inherited from System.Attribute |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleObjectMappingAttribute Class](#)
- [OracleObjectMappingAttribute Members](#)

OracleArrayMappingAttribute Class

The `OracleArrayMappingAttribute` class is required to mark a custom class field or property with information that ODP.NET uses when a custom type represents an Oracle Collection type.

Class Inheritance

`System.Object`

`System.Attribute`

`System.OracleArrayMappingAttribute`

Declaration

```
[AttributeUsageAttribute(AttributeTargets.Field | AttributeTargets.Property,
AllowMultiple=false, Inherited=true)]
```

```
// C#
public sealed class OracleArrayMappingAttribute : Attribute
```

Requirements

| | |
|-----------------------|--------------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | <code>Oracle.DataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Types</code> |
| .NET Framework | 3.5, 4.0, 4.5 |

Remarks

An `OracleArrayMappingAttribute` object must be specified when a custom type represents an Oracle Collection. This attribute is applied only to the custom class member that stores the collection elements.

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleArrayMappingAttribute Members](#)
- [OracleArrayMappingAttribute Constructors](#)
- [OracleArrayMappingAttribute Static Methods](#)
- [OracleArrayMappingAttribute Properties](#)
- [OracleArrayMappingAttribute Methods](#)

OracleArrayMappingAttribute Members

OracleArrayMappingAttribute members are listed in the following tables.

OracleArrayMappingAttribute Constructors

OracleArrayMappingAttribute constructors are listed in [Table 16–15](#).

Table 16–15 OracleArrayMappingAttribute Constructors

| Constructor | Description |
|----------------------------------------------------------|-------------------------------------------------------------------------------|
| OracleArrayMappingAttribute Constructors | Instantiates a new instance of OracleArrayMappingAttribute class (Overloaded) |

OracleArrayMappingAttribute Static Methods

OracleArrayMappingAttribute static methods are listed in [Table 16–16](#).

Table 16–16 OracleArrayMappingAttribute Static Methods

| Method | Description |
|---------------------|---------------------------------|
| Equals | Inherited from System.Attribute |
| GetCustomAttribute | Inherited from System.Attribute |
| GetCustomAttributes | Inherited from System.Attribute |
| IsDefined | Inherited from System.Attribute |
| ReferenceEquals | Inherited from System.Attribute |

OracleArrayMappingAttribute Properties

OracleArrayMappingAttribute properties are listed in [Table 16–17](#).

Table 16–17 OracleArrayMappingAttribute Properties

| Property | Description |
|----------|---------------------------------|
| TypeId | Inherited from System.Attribute |

OracleArrayMappingAttribute Methods

OracleArrayMappingAttribute methods are listed in [Table 16–18](#).

Table 16–18 OracleArrayMappingAttribute Methods

| Method | Description |
|--------------------|---------------------------------|
| Equals | Inherited from System.Attribute |
| GetHashCode | Inherited from System.Attribute |
| GetType | Inherited from System.Attribute |
| IsDefaultAttribute | Inherited from System.Attribute |
| Match | Inherited from System.Attribute |
| ToString | Inherited from System.Attribute |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleArrayMappingAttribute Class](#)

OracleArrayMappingAttribute Constructors

OracleArrayMappingAttribute constructors create new instances of the OracleArrayMappingAttribute class.

Overload List:

- [OracleArrayMappingAttribute\(\)](#)

This constructor creates and initializes an OracleArrayMappingAttribute object.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleArrayMappingAttribute Class](#)
- [OracleArrayMappingAttribute Members](#)

OracleArrayMappingAttribute()

This constructor creates and initializes an OracleArrayMappingAttribute object.

Declaration

```
// C#  
public OracleArrayMappingAttribute();
```

Remarks

An OracleArrayMappingAttribute object must be applied when a custom class represents an Oracle Collection type, to specify the custom class field or property that stores the collection elements.

The OracleArrayMappingAttribute can be applied to only one field or property in the custom class.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleArrayMappingAttribute Class](#)
- [OracleArrayMappingAttribute Members](#)

OracleArrayMappingAttribute Static Methods

OracleArrayMappingAttribute static methods are listed in [Table 16–19](#).

Table 16–19 OracleArrayMappingAttribute Static Methods

| Method | Description |
|---------------------|---------------------------------|
| Equals | Inherited from System.Attribute |
| GetCustomAttribute | Inherited from System.Attribute |
| GetCustomAttributes | Inherited from System.Attribute |
| IsDefined | Inherited from System.Attribute |
| ReferenceEquals | Inherited from System.Attribute |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleArrayMappingAttribute Class](#)
- [OracleArrayMappingAttribute Members](#)

OracleArrayMappingAttribute Properties

OracleArrayMappingAttribute properties are listed in [Table 16–20](#).

Table 16–20 OracleArrayMappingAttribute Properties

| Property | Description |
|----------|---------------------------------|
| TypeId | Inherited from System.Attribute |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleArrayMappingAttribute Class](#)
- [OracleArrayMappingAttribute Members](#)

OracleArrayMappingAttribute Methods

OracleArrayMappingAttribute methods are listed in [Table 16–21](#).

Table 16–21 OracleArrayMappingAttribute Methods

| Method | Description |
|--------------------|---------------------------------|
| Equals | Inherited from System.Attribute |
| GetHashCode | Inherited from System.Attribute |
| GetType | Inherited from System.Attribute |
| IsDefaultAttribute | Inherited from System.Attribute |
| Match | Inherited from System.Attribute |
| ToString | Inherited from System.Attribute |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleArrayMappingAttribute Class](#)
- [OracleArrayMappingAttribute Members](#)

IOracleCustomType Interface

IOracleCustomType is an interface for converting between a Custom Type and an Oracle Object or Collection Type.

Declaration

```
// C#  
public interface IOracleCustomType
```

Requirements

| | |
|-----------------------|----------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | Oracle.DataAccess.dll |
| Namespace | Oracle.DataAccess.Types |
| .NET Framework | 3.5, 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [IOracleCustomType Members](#)
- [IOracleCustomType Interface Methods](#)

IOracleCustomType Members

IOracleCustomType members are listed in the following tables.

IOracleCustomType Interface Methods

IOracleCustomType interface methods are listed in [Table 16-22](#).

Table 16-22 *IOracleCustomType Interface Methods*

| Interface Method | Description |
|----------------------------------|--------------------------------------------------------------------------------|
| FromCustomObject | Returns the values that set the Oracle Object attributes |
| ToCustomObject | Provides the Oracle Object with the attribute values to set on the custom type |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [IOracleCustomType Interface](#)

IOracleCustomType Interface Methods

IOracleCustomType Interface methods are listed in [Table 16–23](#).

Table 16–23 *IOracleCustomType Interface Methods*

| Interface Method | Description |
|----------------------------------|--------------------------------------------------------------------------------|
| FromCustomObject | Returns the values that set the Oracle Object attributes |
| ToCustomObject | Provides the Oracle Object with the attribute values to set on the custom type |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [IOracleCustomType Interface](#)
- [IOracleCustomType Members](#)

FromCustomObject

This interface method creates an Oracle Object or Collection by setting the attribute or element values respectively on the specified Oracle UDT.

Declaration

```
// C#
void FromCustomObject(OracleConnection con, IntPtr pUdt);
```

Parameters

- *con*
An OracleConnection instance.
- *pUdt*
An opaque pointer to the Oracle Object or Collection to be created.

Remarks

The `FromCustomObject` method is used to build an Oracle Object or Collection from a custom object by setting attribute or element values respectively through the `OracleUdt.SetValue` method.

The `OracleUdt.SetValue` method is invoked as follows:

- Oracle Object Type
For a custom type that represents an Oracle Object Type, the `OracleUdt.SetValue` method must be invoked for each non-NULL attribute value that needs to be set.
- Oracle Collection Type
For a custom type that represents an Oracle Collection Type, a single call to `OracleUdt.SetValue` method specifies the collection element values.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [IOracleCustomType Interface](#)
- [IOracleCustomType Members](#)

ToCustomObject

This interface initializes a custom object using the specified Oracle UDT.

Declaration

```
// C#  
void ToCustomObject (OracleConnection con, IntPtr pUdt);
```

Parameters

- *con*
An OracleConnection instance.
- *pUdt*
An opaque pointer to the Oracle UDT.

Remarks

The ToCustomObject method is used to initialize a custom object from the specified Oracle Object or Collection by retrieving attribute or element values respectively through the OracleUdt.GetValue method.

The OracleUdt.GetValue method is invoked as follows:

- Oracle Object Type
For a custom type that represents an Oracle Object Type, the OracleUdt.GetValue method must be invoked for each attribute value to be retrieved.
- For a custom type that represents an Oracle Collection Type, a single call to OracleUdt.GetValue method retrieves the collection element values.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [IOracleCustomType Interface](#)
- [IOracleCustomType Members](#)

IOracleCustomTypeFactory Interface

The `IOracleCustomTypeFactory` interface is used by ODP.NET to create custom objects that represent Oracle Objects or Collections.

Declaration

```
// C#  
public interface IOracleCustomTypeFactory
```

Requirements

| | |
|-----------------------|--------------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | <code>Oracle.DataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Types</code> |
| .NET Framework | 3.5, 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [IOracleCustomTypeFactory Members](#)
- [IOracleCustomTypeFactory Interface Methods](#)

IOracleCustomTypeFactory Members

IOracleCustomTypeFactory members are listed in the following tables.

IOracleCustomTypeFactory Interface Methods

IOracleCustomTypeFactory interface methods are listed in [Table 16–24](#).

Table 16–24 *IOracleCustomTypeFactory Interface Methods*

| Public Method | Description |
|------------------------------|-------------------------------------------------------------------------|
| CreateObject | Returns a new custom object to represent an Oracle Object or Collection |

See Also:

- "[Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces](#)" on page 1-12
- [IOracleCustomTypeFactory Interface](#)

IOracleCustomTypeFactory Interface Methods

IOracleCustomTypeFactory Interface methods are listed in [Table 16–25](#).

Table 16–25 *IOracleCustomTypeFactory Interface Methods*

| Public Method | Description |
|------------------------------|-------------------------------------------------------------------------|
| CreateObject | Returns a new custom object to represent an Oracle Object or Collection |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [IOracleCustomTypeFactory Interface](#)
- [IOracleCustomTypeFactory Members](#)

CreateObject

This interface method returns a new custom object to represent an Oracle Object or Collection.

Declaration

```
// C#  
IOracleCustomType CreateObject();
```

Return Value

An `IOracleCustomType` object.

Remarks

The `CreateObject` method is used to create a new instance of a custom object to represent an Oracle Object or Collection.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [IOracleCustomTypeFactory Interface](#)
- [IOracleCustomTypeFactory Members](#)

IOracleArrayTypeFactory Interface

The `IOracleArrayTypeFactory` interface is used by ODP.NET to create arrays that represent Oracle Collections.

Declaration

```
// C#  
public interface IOracleArrayTypeFactory
```

Requirements

| | |
|-----------------------|----------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | Oracle.DataAccess.dll |
| Namespace | Oracle.DataAccess.Types |
| .NET Framework | 3.5, 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [IOracleArrayTypeFactory Members](#)
- [IOracleArrayTypeFactory Interface Methods](#)

IOracleArrayTypeFactory Members

IOracleArrayTypeFactory members are listed in the following tables.

IOracleArrayTypeFactory Interface Methods

IOracleArrayTypeFactory interface methods are listed in [Table 16–26](#).

Table 16–26 *IOracleArrayTypeFactory Interface Methods*

| Public Method | Description |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CreateArray | Returns a new array of the specified length to store Oracle Collection elements |
| CreateStatusArray | Returns a newly allocated <code>OracleUdtStatus</code> array of the specified length that will be used to store the null status of the collection elements |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [IOracleArrayTypeFactory Interface](#)

IOracleArrayTypeFactory Interface Methods

IOracleArrayTypeFactory Interface methods are listed in [Table 16–27](#).

Table 16–27 IOracleArrayTypeFactory Interface Methods

| Public Method | Description |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CreateArray | Returns a new array of the specified length to store Oracle Collection elements |
| CreateStatusArray | Returns a newly allocated <code>OracleUdtStatus</code> array of the specified length that will be used to store the null status of the collection elements |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [IOracleArrayTypeFactory Interface](#)
- [IOracleArrayTypeFactory Members](#)

CreateArray

This interface method returns a new array of the specified length to store Oracle Collection elements.

Declaration

```
// C#
Array CreateArray(int numElems);
```

Parameters

- *numElems*

The number of collection elements to be returned.

Return Value

A `System.Array` object.

Remarks

An Oracle Collection Type may be represented in either of the following ways:

- As an array of the appropriate type. The type must be able to represent a collection element.
- As a Custom Type that contains an array of the appropriate type.

In both cases, the `CreateArray` method creates an array of the specified length to store the collection elements.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [IOracleArrayTypeFactory Interface](#)
- [IOracleArrayTypeFactory Members](#)

CreateStatusArray

This method returns a newly allocated `OracleUdtStatus` array of the specified length that will be used to store the null status of the collection elements.

Declaration

```
// C#  
Array CreateStatusArray(int numElems);
```

Parameters

- `numElems`

The number of collection elements to be returned.

Return Value

A multi-dimensional `OracleUdtStatus` array as a `System.Array`.

Remarks

An Oracle Collection Type can be represented in the following ways:

- As an array of the appropriate type. The type must be able to represent a collection element.
- As a Custom Type that contains an array of the appropriate type.

In both cases, the `CreateStatusArray` method creates an `OracleUdtStatus` array of the specified length that stores the null status of the collection elements.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [IOracleArrayTypeFactory Interface](#)
- [IOracleArrayTypeFactory Members](#)
- ["OracleUdtFetchOption Enumeration"](#) on page 16-75

OracleUdt Class

The `OracleUdt` class defines static methods that are used when converting between Custom Types and Oracle UDTs and vice-versa.

Class Inheritance

`System.Object`

`System.OracleUdt`

Declaration

```
public sealed class OracleUdt
```

Requirements

| | |
|-----------------------|--------------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | <code>Oracle.DataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Types</code> |
| .NET Framework | 3.5, 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleUdt Members](#)
- [OracleUDT Static Methods](#)

OracleUdt Members

OracleUdt static methods are listed in [Table 16–28](#).

Table 16–28 OracleUdt Static Methods

| Static Method | Description |
|--------------------------|----------------------------------------------------------------------------------------------------|
| Equals | Inherited from <code>System.Object</code> |
| GetValue | Gets the attributes or elements from the specified Oracle UDT (Overloaded) |
| IsDBNull | Indicates whether or not the specified attribute being retrieved is <code>NULL</code> (Overloaded) |
| SetValue | Sets the attributes or elements on the specified Oracle UDT (Overloaded) |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleUdt Class](#)

OracleUDT Static Methods

OracleUDT methods are listed in [Table 16–29](#).

Table 16–29 OracleUdt Static Methods

| Static Method | Description |
|--------------------------|----------------------------------------------------------------------------------------------------|
| Equals | Inherited from <code>System.Object</code> |
| GetValue | Gets the attributes or elements from the specified Oracle UDT (Overloaded) |
| IsDBNull | Indicates whether or not the specified attribute being retrieved is <code>NULL</code> (Overloaded) |
| SetValue | Sets the attributes or elements on the specified Oracle UDT (Overloaded) |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleUdt Class](#)
- [OracleUdt Members](#)

GetValue

GetValue methods get the attributes or elements from the specified Oracle UDT.

Overload List:

- [GetValue\(OracleConnection, IntPtr, string\)](#)
This method gets the attributes or elements from the specified Oracle UDT, using the specified attribute name.
- [GetValue\(OracleConnection, IntPtr, int\)](#)
This method gets the attribute or elements from the specified Oracle UDT, using the specified index.
- [GetValue\(OracleConnection, IntPtr, string, out object\)](#)
This method returns either the elements of the specified collection attribute of the specified Oracle Object or the elements of the specified Oracle Collection.
- [GetValue\(OracleConnection, IntPtr, int, out object\)](#)
This method returns either the elements of the specified collection attribute of the specified Oracle Object or the elements of the specified Oracle Collection.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleUdt Class](#)
- ["OracleUdt Members"](#)

GetValue(OracleConnection, IntPtr, string)

This method gets the attributes or elements from the specified Oracle UDT, using the specified attribute name.

Declaration

```
public static object GetValue(OracleConnection con, IntPtr pUdt, string attrName);
```

Parameters

- *con*
An `OracleConnection` instance.
- *pUdt*
A pointer to an Oracle UDT.
- *attrName*
The case-sensitive name of the attribute to be retrieved. Null is specified for retrieving collection elements from a Custom Type that represents an Oracle Collection.

Return Value

An object representing the returned attribute or collection elements.

Exceptions

`ArgumentException` - The specified name is not a valid attribute name.

Remarks

The `IOracleCustomType.ToCustomObject` method invokes `OracleUdt.GetValue` method passing it the *con* and *pUdt* parameters. The `OracleUdt.GetValue` method returns these types of object:

- Oracle Object Type
For a Custom Type that represents an Oracle Object Type, the type returned for a specified attribute name is the type of the member in the custom class or struct that is mapped to the attribute using the `OracleObjectMappingAttribute` object.
- Oracle Collection Type
For a Custom Type that represents an Oracle Collection Type, the type returned is the type of the member in the custom class or struct to which the `OracleArrayMappingAttribute` object is applied.

In the case of NULL attribute values, the appropriate null representation of the type is returned. For example, for attributes that are represented as Custom Types and Provider Specific Types, the static `Null` property of the type is returned. For attributes that are represented as Nullable types, for example, `System.String` and `System.Array` Types, null is returned, and for all other remaining built-in types such as `Int32` and `DateTime` `DBNull.Value` is returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleUdt Class](#)
- [OracleUdt Members](#)
- ["OracleUdtFetchOption Enumeration"](#) on page 16-75

GetValue(OracleConnection, IntPtr, int)

This method gets the attribute or elements from the specified Oracle UDT, using the specified index.

Declaration

```
// C#  
public static object GetValue(OracleConnection con, IntPtr pUdt, int attrIndex,);
```

Parameters

- *con*
An OracleConnection instance.
- *pUdt*
A pointer to an Oracle UDT.
- *attrIndex*
The zero-based index of the attribute to be retrieved. For retrieving collection elements from a Custom Type that represents an Oracle Collection, zero must be specified.

Return Value

An object representing the returned attribute or collection elements.

Exceptions

ArgumentOutOfRangeException - The specified index is not a valid attribute index.

Remarks

The `IOracleCustomType.ToCustomObject` method invokes `OracleUdt.GetValue` method passing it the *con* and *pUdt* parameters. The `OracleUdt.GetValue` method returns these types of object:

- Oracle Object Type
For a Custom Type that represents an Oracle Object Type, the type returned for a specified attribute index is the type of the member in the custom class or struct that is mapped to the attribute using the `OracleObjectMappingAttribute` object.
- Oracle Collection Type
For a Custom Type that represents an Oracle Collection Type, the type returned is the type of the member in the custom class or struct to which the `OracleArrayMappingAttribute` object is applied.

In the case of NULL attribute values, the appropriate null representation of the type is returned. For example, for attributes that are represented as Custom Types and

Provider Specific Types, the static `Null` property of the type is returned. For attributes that are represented as Nullable types, for example, `System.String` and `System.Array` Types, null is returned, and for all other remaining built-in types such as `Int32` and `DateTime` `DBNull.Value` is returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleUdt Class](#)
- [OracleUdt Members](#)
- ["OracleUdtFetchOption Enumeration"](#) on page 16-75

GetValue(OracleConnection, IntPtr, string, out object)

This method returns either the elements of the specified collection attribute of the specified Oracle Object or the elements of the specified Oracle Collection.

Declaration

```
// C#
public static object GetValue(OracleConnection con, IntPtr pUdt, string attrName,
    out object statusArray);
```

Parameters

- *con*
An `OracleConnection` instance.
- *pUdt*
An opaque pointer to an Oracle UDT.
- *attrName*
The case-sensitive name of the attribute to be retrieved. Null must specified for retrieving collection elements from a Custom Type that represents an Oracle Collection.
- *statusArray* - The `OracleUdtStatus` array which returns the null status for the retrieved collection elements.

Return Value

An object representing the returned attribute or collection elements.

Exceptions

`ArgumentException` - The specified name is not a valid attribute name.

Remarks

The `IOracleCustomType.ToCustomObject` method invokes `OracleUdt.GetValue` method passing it the *con* and *pUdt* parameters. The `OracleUdt.GetValue` method returns these types of object:

- Oracle Object Type

For a Custom Type that represents an Oracle Object Type, the type returned for a specified attribute name is the type of the member in the custom class or struct that is mapped to the attribute using the `OracleObjectMappingAttribute` object.

- Oracle Collection Type

For a Custom Type that represents an Oracle Collection Type, the type returned is the type of the member in the custom class or struct to which the `OracleArrayMappingAttribute` object is applied.

In the case of NULL attribute values, the appropriate null representation of the type is returned. For example, for attributes that are represented as Custom Types and Provider Specific Types, the static `Null` property of the type is returned. For attributes that are represented as Nullable types, for example, `System.String` and `System.Array` Types, null is returned, and for all other remaining built-in types such as `Int32` and `DateTime` `DBNull.Value` is returned.

If the collection being returned is not NULL, the output `statusArray` parameter is populated with the null status for each of the collection elements.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleUdt Class](#)
- [OracleUdt Members](#)
- ["OracleUdtFetchOption Enumeration"](#) on page 16-75

GetValue(OracleConnection, IntPtr, int, out object)

This method returns either the elements of the specified collection attribute of the specified Oracle Object or the elements of the specified Oracle Collection.

Declaration

```
// C#
public static object GetValue(OracleConnection con, IntPtr pUdt, int attrIndex,
    out object statusArray);
```

Parameters

- `con`
An `OracleConnection` instance.
- `pUdt`
An opaque pointer to an Oracle UDT.
- `attrIndex`
The zero-based index of the attribute to be retrieved. For retrieving collection elements from a Custom Type that represents an Oracle Collection, 0 is specified.
- `statusArray`
The `OracleUdtStatus` array which returns the null status for the retrieved collection elements.

Return Value

An object representing the returned attribute or collection elements.

Exceptions

`ArgumentOutOfRangeException` - The specified index is not a valid attribute index.

Remarks

The `IOracleCustomType.ToCustomObject` method invokes `OracleUdt.GetValue` method passing it the `con` and `pUdt` parameters. The `OracleUdt.GetValue` method returns these types of object:

- Oracle Object Type

For a Custom Type that represents an Oracle Object Type, the type returned for a specified attribute index is the type of the member in the custom class or struct that is mapped to the attribute using the `OracleObjectMappingAttribute` object.

- Oracle Collection Type

For a Custom Type that represents an Oracle Collection Type, the type returned is the type of the member in the custom class or struct to which the `OracleArrayMappingAttribute` object is applied.

In the case of NULL attribute values, the appropriate null representation of the type is returned. For example, for attributes that are represented as Custom Types and Provider Specific Types, the static `Null` property of the type is returned. For attributes that are represented as Nullable types, for example, `System.String` and `System.Array` Types, null is returned, and for all other remaining built-in types such as `Int32` and `DateTime` `DBNull.Value` is returned.

If the collection being returned is not NULL, the output `statusArray` parameter is populated with the null status for each of the collection elements.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleUdt Class](#)
- [OracleUdt Members](#)
- ["OracleUdtFetchOption Enumeration"](#) on page 16-75

IsDBNull

`IsDBNull` methods indicate whether or not the specified attribute being retrieved is NULL.

Overload List:

- [IsDBNull\(OracleConnection, IntPtr, string\)](#)

This method indicates whether or not the attribute being retrieved, specified by `OracleConnection`, `pointer`, and attribute name, is NULL.

- [IsDBNull\(OracleConnection, IntPtr, int\)](#)

This method indicates whether or not the attribute being retrieved, specified by `OracleConnection`, `pointer`, and attribute index, is NULL.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleUdt Class](#)
- [OracleUdt Members](#)
- ["OracleUdtFetchOption Enumeration"](#) on page 16-75

IsDBNull(OracleConnection, IntPtr, string)

This method indicates whether or not the attribute being retrieved, specified by *OracleConnection*, *pointer*, and attribute name, is NULL.

Declaration

```
// C#
public static bool IsDBNull(OracleConnection con, IntPtr pUdt, string attrName);
```

Parameters

- *con*
An *OracleConnection* instance.
- *pUdt*
A pointer to an Oracle UDT.
- *attrName*
The case-sensitive name of the attribute.

Return Value

True if the specified attribute is NULL; otherwise, false.

Exceptions

ArgumentException - The specified name is not a valid attribute name.

Remarks

This method is invoked from the *IOracleCustomType.ToCustomObject* method. The *con* and *pUdt* parameter is passed from the *IOracleCustomType.ToCustomObject* method to the *OracleUdt.IsDBNull* method. The *attrName* parameter is case-sensitive.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleUdt Class](#)
- [OracleUdt Members](#)

IsDBNull(OracleConnection, IntPtr, int)

This method indicates whether or not the attribute being retrieved, specified by *OracleConnection*, *pointer*, and attribute index, is NULL.

Declaration

```
// C#  
public static bool IsDBNull(OracleConnection con, IntPtr pUdt, int attrIndex);
```

Parameters

- *con*
An `OracleConnection` instance.
- *pUdt*
An opaque pointer to an Oracle UDT.
- *attrIndex*
The zero-based index of the attribute.

Return Value

True if the specified attribute is NULL; otherwise, false.

Exceptions

`ArgumentOutOfRangeException` - The specified index is not a valid attribute index

Remarks

This method is invoked from the `IOracleCustomType.ToCustomObject` method. The *con* and *pUdt* parameter is passed from the `IOracleCustomType.ToCustomObject` method to the `OracleUdt.IsDBNull` method.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleUdt Class](#)
- [OracleUdt Members](#)

SetValue

`SetValue` methods set the attributes or elements on the specified Oracle UDT.

Overload List:

- [SetValue\(OracleConnection, IntPtr, string, object\)](#)
This method sets the attribute or elements on the specified Oracle UDT, using the specified attribute name and value.
- [SetValue\(OracleConnection, IntPtr, int, object\)](#)
This method sets the attribute or elements on the specified Oracle UDT, using the specified index and value.
- [SetValue\(OracleConnection, IntPtr, string, object, object\)](#)
This method sets either the specified collection attribute of the specified Oracle Object or elements of the specified Oracle Collection, to the specified value using the supplied null status of the collection elements.
- [SetValue\(OracleConnection, IntPtr, int, object, object\)](#)

This method sets either the specified collection attribute of the specified Oracle Object or elements of the specified Oracle Collection, to the specified value using the supplied null status of the collection elements.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleUdt Class](#)
- [OracleUdt Members](#)

SetValue(OracleConnection, IntPtr, string, object)

This method sets the attribute or elements on the specified Oracle UDT, using the specified attribute name and value.

Declaration

```
// C#
public static void SetValue(OracleConnection con, IntPtr pUdt, string attrName,
    object value);
```

Parameters

- *con*
An OracleConnection instance.
- *pUdt*
An opaque pointer to an Oracle UDT.
- *attrName*
The name of the attribute to be set. Specify null for setting collection elements from a Custom Type that represents an Oracle Collection.
- *value*
The attribute or collection value to be set.

Exceptions

ArgumentException - The specified value is not of the appropriate type.

Remarks

The `IOracleCustomType.FromCustomObject` method invokes `OracleUdt.SetValue` method passing it the *con* and *pUdt* parameters. The `OracleUdt.SetValue` method returns these types of object:

- Oracle Object Type
For a Custom Type that represents an Oracle Object Type, the type accepted for a specified attribute name is the type of the member in the custom class or struct that is mapped to the attribute using the `OracleObjectMappingAttribute` object.
- Oracle Collection Type
For a Custom Type that represents an Oracle Collection Type, the type accepted is the type of the member in the custom class or struct to which the `OracleArrayMappingAttribute` object is applied.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleUdt Class](#)
- ["OracleUdt Members"](#)

SetValue(OracleConnection, IntPtr, int, object)

This method sets the attribute or elements on the specified Oracle UDT, using the specified index and value.

Declaration

```
// C#  
public static void SetValue(OracleConnection con, IntPtr pUdt, int attrIndex,  
object value);
```

Parameters

- *con*
An OracleConnection instance.
- *pUdt*
An opaque pointer to an Oracle UDT.
- *attrIndex*
The index of the attribute to be set. Specify 0 for setting collection elements from a Custom Type that represents an Oracle Collection.
- *value*
The attribute or collection value to be set.

Exceptions

ArgumentException - The specified value is not of the appropriate type.

Remarks

The `IOracleCustomType.FromCustomObject` method invokes `OracleUdt.SetValue` method passing it the *con* and *pUdt* parameters. The `OracleUdt.SetValue` method returns these types of object:

- **Oracle Object Type**
For a Custom Type that represents an Oracle Object Type, the type accepted for a specified attribute index is the type of the member in the custom class or struct that is mapped to the attribute using the `OracleObjectMappingAttribute` object.
- **Oracle Collection Type**
For a Custom Type that represents an Oracle Collection Type, the type accepted is the type of the member in the custom class or struct to which the `OracleArrayMappingAttribute` object is applied.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleUdt Class](#)
- ["OracleUdt Members"](#)

SetValue(OracleConnection, IntPtr, string, object, object)

This method sets either the specified collection attribute of the specified Oracle Object or elements of the specified Oracle Collection, to the specified value using the supplied null status of the collection elements.

Declaration

```
// C#
public static void SetValue(OracleConnection con, IntPtr pUdt, string attrName,
    object value, object statusArray);
```

Parameters

- *con*
An OracleConnection instance.
- *pUdt*
An opaque pointer to an Oracle UDT.
- *attrName*
The name of the attribute to be set. Specify null for setting collection elements from a Custom Type that represents an Oracle Collection.
- *value*
The attribute or collection value to be set.
- *statusArray*
The null status for the collection elements.

Exceptions

ArgumentException - The specified value is not of the appropriate type.

Remarks

The `IOracleCustomType.FromCustomObject` method invokes `OracleUdt.SetValue` method passing it the *con* and *pUdt* parameters. The `OracleUdt.SetValue` method returns these types of object:

- Oracle Object Type
For a Custom Type that represents an Oracle Object Type, the type accepted for a specified attribute name is the type of the member in the custom class or struct that is mapped to the attribute using the `OracleObjectMappingAttribute` object.
- Oracle Collection Type
For a Custom Type that represents an Oracle Collection Type, the type accepted is the type of the member in the custom class or struct to which the `OracleArrayMappingAttribute` object is applied.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleUdt Class](#)
- ["OracleUdt Members"](#)

SetValue(OracleConnection, IntPtr, int, object, object)

This method sets either the specified collection attribute of the specified Oracle Object or elements of the specified Oracle Collection, to the specified value using the supplied null status of the collection elements.

Declaration

```
// C#
public static void SetValue(OracleConnection con, IntPtr pUdt, int attrIndex,
    object value, object statusArray);
```

Parameters

- *con*
An OracleConnection instance.
- *pUdt*
An opaque pointer to an Oracle UDT.
- *attrIndex*
The index of the attribute to be set. Specify 0 for setting collection elements from a Custom Type that represents an Oracle Collection.
- *value*
The attribute or collection value to be set.
- *statusArray*
The null status for the collection elements.

Exceptions

ArgumentException - The specified value is not of the appropriate type.

Remarks

The `IOracleCustomType.FromCustomObject` method invokes `OracleUdt.SetValue` method passing it the *con* and *pUdt* parameters. The `OracleUdt.SetValue` method returns these types of object:

- Oracle Object Type
For a Custom Type that represents an Oracle Object Type, the type accepted for a specified attribute index is the type of the member in the custom class or struct that is mapped to the attribute using the `OracleObjectMappingAttribute` object.
- Oracle Collection Type
For a Custom Type that represents an Oracle Collection Type, the type accepted is the type of the member in the custom class or struct to which the `OracleArrayMappingAttribute` object is applied.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleUdt Class](#)
- ["OracleUdt Members"](#)

OracleRef Class

An `OracleRef` instance represents an Oracle REF, which references a persistent, standalone, referenceable object that resides in the database. The `OracleRef` object provides methods to insert, update, and delete the Oracle REF.

Class Inheritance

`System.Object`

`System.MarshalByRefObject`

`Oracle.DataAccess.Types.OracleRef`

Declaration

```
// C#
public sealed class OracleRef : MarshalByRefObject, ICloneable, IDisposable,
    INullable
```

Requirements

| | |
|-----------------------|--------------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | <code>Oracle.DataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Types</code> |
| .NET Framework | 3.5, 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

If two or more `OracleRef` objects that refer to the same Oracle object in the database are retrieved through the same `OracleConnection`, then their operations on the referenced object must be synchronized.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleRef Members](#)
- [OracleRef Constructors](#)
- [OracleRef Static Methods](#)
- [OracleRef Instance Properties](#)
- [Oracle Ref Instance Methods](#)

OracleRef Members

OracleRef members are listed in the following tables.

OracleRef Constructors

OracleRef constructors are listed in [Table 16–30](#).

Table 16–30 OracleRef Constructors

| Constructor | Description |
|----------------------------------------|-------------------------------------------------------------|
| OracleRef Constructors | Instantiates a new instance of OracleRef class (Overloaded) |

OracleRef Static Fields

OracleRef static methods are listed in [Table 16–31](#)

Table 16–31 OracleRef Static Fields

| Static Field | Description |
|----------------------|-----------------------------------------------------------------------|
| Null | Represents a null value that can be assigned to an OracleRef instance |

OracleRef Static Methods

OracleRef static methods are listed in [Table 16–32](#).

Table 16–32 OracleRef Static Methods

| Method | Description |
|------------------------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

OracleRef Instance Properties

OracleRef instance properties are listed in [Table 16–33](#).

Table 16–33 OracleRef Instance Properties

| Property | Description |
|---------------------------------|-------------------------------------------------------------------------------|
| Connection | References the connection used by the OracleRef |
| HasChanges | References the connection used by the OracleRef |
| IsLocked | Indicates whether or not the REF is locked |
| IsNull | Indicates whether or not the Oracle REF is NULL |
| ObjectTableName | Returns the fully qualified object table name that is associated with the REF |
| Value | Returns a .NET representation of this Oracle REF |

OracleRef Instance Methods

OracleRef instance methods are listed in [Table 16–34](#).

Table 16–34 OracleRef Instance Methods

| Method | Description |
|-----------------------|----------------|
| Clone | Clones the REF |

Table 16–34 (Cont.) OracleRef Instance Methods

| Method | Description |
|------------------------------------------|------------------------------------------------------------------------------------------------------|
| Delete | Deletes the referenced object from the database |
| Dispose | Releases resources allocated for the <code>OracleRef</code> instance |
| <code>Equals</code> | Inherited from <code>System.Object</code> |
| Flush | Flushes changes made on the REF object to the database |
| GetCustomObject | Returns the object that the specified REF references as a custom type (Overloaded) |
| GetCustomObjectForUpdate | Returns the object that the specified REF references as a custom type (Overloaded) |
| <code>GetHashCode</code> | Inherited from <code>System.Object</code> |
| <code>GetType</code> | Inherited from <code>System.Object</code> |
| IsEqual | Compares two <code>OracleREF</code> objects |
| Lock | Locks the REF in the database |
| <code>ToString</code> | Inherited from <code>System.Object</code> |
| Update | Updates the object referenced by the specified REF in the database using the specified custom object |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRef Class](#)

OracleRef Constructors

OracleRef constructors instantiate new instances of OracleRef class.

Overload List:

- [OracleRef\(OracleConnection, string\)](#)

This constructor creates an instance of the OracleRef class with a connection and a HEX string that represents an REF instance in the database.

- [OracleRef\(OracleConnection, string, string\)](#)

This constructor creates an instance of the OracleRef class using the specified OracleConnection object, user-defined type name, and an object table name

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRef Class](#)
- [OracleRef Members](#)

OracleRef(OracleConnection, string)

This constructor creates an instance of the OracleRef class with a connection and a HEX string that represents an REF instance in the database.

Declaration

```
// C#  
public OracleRef(OracleConnection con, string hexStr);
```

Parameters

- *con*
An OracleConnection instance.
- *hexStr*
A HEX string that represents an REF instance in the database.

Exceptions

ArgumentException - The HEX string does not represent a valid REF in the database.

ArgumentNullException - The connection or HEX string is null.

InvalidOperationException - The OracleConnection object is not open.

Remarks

When an OracleRef instance is created, it is referenced to a specific table in the database.

The connection must be opened explicitly by the application. OracleRef does not open the connection implicitly.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

OracleRef(OracleConnection, string, string)

This constructor creates an instance of the `OracleRef` class using the specified `OracleConnection` object, user-defined type name, and an object table name.

Declaration

```
// C#  
public OracleRef(OracleConnection con, string udtTypeName, string objTabName);
```

Parameters

- *con*
An `OracleConnection` instance.
- *udtTypeName*
A user-defined type name.
- *objTabName*
An object table name.

Exceptions

`ArgumentException` - The object type name or the object table name is not valid.

`ArgumentNullException` - The object type name or the table name is null.

`InvalidOperationException` - The `OracleConnection` object is not open.

Remarks

When an `OracleRef` instance is created, this `OracleRef` instance is associated with the specific table in the database. In other words, it represents a persistent REF.

This constructor creates a reference to the object table. However, it does not cause any entries to be made in database tables until the object is flushed to the database, that is, until the `OracleRef.Flush` or the `OracleConnection.FlushCache` method is called on the `OracleRef` Connection. Therefore, any operation that attempts to operate on the database copy of the object before flushing the object, such as, lock the object or fetch the latest copy of the object from the database, results in an `OracleException`.

The connection must be opened explicitly by the application. `OracleRef` does not open the connection implicitly.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRef Class](#)
- [OracleRef Members](#)
- ["FlushCache"](#) on page 6-116

OracleRef Static Fields

OracleRef static fields are listed in [Table 16–35](#).

Table 16–35 OracleRef Static Fields

| Static Field | Description |
|----------------------|-----------------------------------------------------------------------|
| Null | Represents a null value that can be assigned to an OracleRef instance |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRef Class](#)
- [OracleRef Members](#)

Null

This static field represents a null value that can be assigned to an OracleRef instance.

Declaration

```
// C#  
public static readonly OracleRef Null;
```

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRef Class](#)
- [OracleRef Members](#)

OracleRef Static Methods

OracleRef static methods are listed in [Table 16–36](#).

Table 16–36 *OracleRef Static Methods*

| Method | Description |
|--------|-------------------------------------------|
| Equals | Inherited from System.Object (Overloaded) |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRef Class](#)
- [OracleRef Members](#)

OracleRef Instance Properties

OracleRef instance properties are listed in [Table 16–37](#).

Table 16–37 OracleRef Instance Properties

| Property | Description |
|---------------------------------|-------------------------------------------------------------------------------|
| Connection | References the connection used by the OracleRef |
| HasChanges | References the connection used by the OracleRef |
| IsLocked | Indicates whether or not the REF is locked |
| IsNull | Indicates whether or not the Oracle REF is NULL |
| ObjectTableName | Returns the fully qualified object table name that is associated with the REF |
| Value | Returns a .NET representation of this Oracle REF |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRef Class](#)
- [OracleRef Members](#)

Connection

This instance property references the connection used by the OracleRef.

Declaration

```
// C#
public OracleConnection Connection{get;}
```

Property Value

An OracleConnection object associated with the REF.

Exceptions

ObjectDisposedException - The object is already disposed.

Remarks

Once the Dispose method is invoked, this property is set to null.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRef Class](#)
- [OracleRef Members](#)

HasChanges

This instance property indicates whether or not the object referenced by the Oracle REF in the object cache has any changes that can be flushed to the database.

Declaration

```
// C#
public bool HasChanges {get;}
```

Property Value

Returns `true` if the object referenced by the Oracle REF in the object cache has any changes that can be flushed to the database; otherwise, returns `false`.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

This property returns `true` if a copy of the referenced object in the object cache is updated or deleted.

If there is no copy of the referenced object in the object cache, the latest copy of the referenced object in the database is cached in the object cache and `false` is returned.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

IsLocked

This instance property indicates whether or not the REF is locked.

Declaration

```
// C#
public bool IsLocked {get;}
```

Property Value

Returns `true` if the REF is locked; otherwise returns `false`.

Exceptions

`ObjectDisposedException` - The object is already disposed.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

IsNull

This instance property indicates whether or not the Oracle REF is NULL.

Declaration

```
// C#
```

```
public bool IsNull {get;}
```

Property Value

Returns true if the REF is NULL; otherwise, returns false.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

If the Oracle REF is NULL, this property returns true. Otherwise, it returns false.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

ObjectTableName

This instance property returns the fully-qualified object table name that is associated with the REF.

Declaration

```
// C#  
public string ObjectTableName{get;}
```

Property Value

A fully-qualified object table name that is associated with the REF.

Exceptions

`ObjectDisposedException` - The object is already disposed.

Remarks

The object table name is in the form *schema_Name.Table_Name*.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

Value

This instance property returns a .NET representation of this Oracle REF.

Declaration

```
// C#  
public string Value{get;}
```


Property Value

A .NET representation of the Oracle REF.

Exceptions

ObjectDisposedException - The object is already disposed.

Remarks

This property returns a HEX string that represents the REF.

The returned string can be used to create a new OracleRef instance by using the OracleRef(OracleConnection, string) constructor.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRef Class](#)
- [OracleRef Members](#)
- ["OracleRef\(OracleConnection, string\)"](#) on page 16-55

Oracle Ref Instance Methods

OracleRef instance methods are listed in [Table 16–38](#).

Table 16–38 OracleRef Instance Methods

| Method | Description |
|------------------------------------------|------------------------------------------------------------------------------------------------------|
| Clone | Clones the REF |
| Delete | Deletes the referenced object from the database |
| Dispose | Releases resources allocated for the OracleRef instance |
| Equals | Inherited from <code>System.Object</code> |
| Flush | Flushes changes made on the REF object to the database |
| GetCustomObject | Returns the object that the specified REF references as a custom type (Overloaded) |
| GetCustomObjectForUpdate | Returns the object that the specified REF references as a custom type (Overloaded) |
| GetHashCode | Inherited from <code>System.Object</code> |
| GetType | Inherited from <code>System.Object</code> |
| IsEqual | Compares two OracleREF objects |
| Lock | Locks the REF in the database |
| ToString | Inherited from <code>System.Object</code> |
| Update | Updates the object referenced by the specified REF in the database using the specified custom object |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRef Class](#)
- [OracleRef Members](#)

Clone

This instance method clones the REF.

Declaration

```
// C#
public OracleRef Clone();
```

Return Value

A clone of the current instance.

Implements

`ICloneable`

Exceptions

`InvalidOperationException` - The associated connection is not open.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

Delete

This method deletes the referenced object from the database.

Declaration

```
// C#  
public void Delete(bool bFlush);
```

Parameters

- *bFlush*
A `bool` that specifies whether or not the REF is flushed immediately.

Remarks

This method marks the specified REF for deletion.

Depending on whether the value of *bFlush* is set to `true` or `false`, the following occurs:

- `True`
The object referenced by the specified REF is deleted immediately from the database.

Before flushing objects, it is required that the application has explicitly started a transaction by executing the `BeginTransaction` method on the `OracleConnection` object. This is because if the object being flushed has not already been locked by the application, an exclusive lock is obtained implicitly for the object. The lock is only released when the transaction commits or rollbacks.
- `False`
The object referenced by the REF is not deleted immediately from the database, but only when a subsequent `Flush` method is invoked for the specified REF or the `FlushCache` method is invoked on the `OracleRef` or the `FlushCache` method is invoked on the `OracleRef` connection.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleRef Class](#)
- [OracleRef Members](#)
- `OracleConnection` ["FlushCache"](#) on page 6-116

Dispose

This instance method releases resources allocated for the `OracleRef` instance.

Declaration

```
// C#  
public void Dispose();
```

Implements

IDisposable

Remarks

The object cannot be reused after it is disposed. Although some properties can still be accessed, their values may not be up-to-date.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRef Class](#)
- [OracleRef Members](#)

Flush

This instance method flushes changes made on the REF object to the database, such as updates or deletes.

Declaration

```
// C#  
public void Flush();
```

Exceptions

InvalidOperationException - The associated connection is not open.

Remarks

Before flushing objects, it is required that the application has explicitly started a transaction by executing the `BeginTransaction` method on the `OracleConnection` object. This is because if the object being flushed has not already been locked by the application, an exclusive lock is obtained implicitly for the object. The lock is only released when the transaction commits or rollbacks.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRef Class](#)
- [OracleRef Members](#)

GetCustomObject

`GetCustomObject` methods return the object that the specified REF references as a custom type.

Overload List

- [GetCustomObject\(OracleUdtFetchOption\)](#)

This method returns the object that the specified REF references as a custom type using the specified fetch option.

- [GetCustomObject\(OracleUdtFetchOption, int\)](#)

This method returns the object that the specified REF references as a custom type using the specified fetch option and depth level.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRef Class](#)
- [OracleRef Members](#)

GetCustomObject(OracleUdtFetchOption)

This method returns the object that the specified REF references, as a custom type, using the specified fetch option.

Declaration

```
// C#
public object GetCustomObject(OracleUdtFetchOption fetchOption);
```

Parameters

- *fetchOption*
An OracleUdtFetchOption value.

Return Value

A custom object that represents the object that the specified REF references.

Exceptions

InvalidOperationException - The specified connection is not open, or a valid custom type has not been registered for the type of the referenced object.

Remarks

This method returns a custom type determined by the UDT mappings on the specified connection.

The connection must be opened explicitly by the application. This method does not open the connection implicitly.

The application can use the OracleUdtFetchOption method to control the copy of the Object that is returned according to the specified option:

- OracleUdtFetchOption.Cache option
If this option is specified, and there is a copy of the referenced object in the object cache, it is returned immediately. If no cached copy exists, the latest copy of the referenced object in the database is cached in the object cache and returned.
- OracleUdtFetchOption.Server option
If this option is specified, the latest copy of the referenced object from the database is cached in the object cache and returned. If a copy of the referenced object already exists in the cache, the latest copy overwrites the existing one.

- `OracleUdtFetchOption.TransactionCache` option

If this option is specified, and a copy of the referenced object is cached in the current transaction, the copy is returned. Otherwise, the latest copy of the referenced object from the database is cached in the object cache and returned. If a copy of the referenced object already exists in the cache, the latest copy overwrites the existing one.

Note that if a cached copy of the referenced object was modified before the current transaction began, that is, if the `OracleRef.HasChanges` property returns `true`, then the `Recent` option returns the cached copy of the referenced object. Outside of a transaction, the `Recent` option behaves like the `Any` option.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRef Class](#)
- [OracleRef Members](#)
- ["OracleUdtFetchOption Enumeration"](#) on page 16-75

GetCustomObject(OracleUdtFetchOption, int)

This method returns the object that the specified `REF` references, as a custom type, using the specified fetch option and depth level.

Declaration

```
// C#  
public object GetCustomObject(OracleUdtFetchOption fetchOption, int depthLevel);
```

Parameters

- *fetchOption*
An `OracleUdtFetchOption` value.
- *depthLevel*
The number of levels to be fetched for nested `REF` attributes.

Return Value

A custom object that represents the object that the specified `REF` references.

Exceptions

`InvalidOperationException` - The specified connection is not open, or a valid custom type has not been registered for the type of the referenced object.

Remarks

This method returns a custom type determined by the UDT mappings on the specified connection.

If the object that the `REF` references contains nested `REF` attributes, the *depthLevel* can be specified to optimize the subsequent object retrieval. The value of *depthLevel* determines the number of levels that are optimized.

For example, if the *depthLevel* is specified as two, the optimization is applied to all top-level nested REF attributes in the object being fetched and also to all nested REF attributes within the objects referenced by the top-level nested REF attributes.

The connection must be opened explicitly by the application. This method does not open the connection implicitly.

The application can use the `OracleUdtFetchOption` method to control the copy of the Object that is returned according to the specified option:

- `OracleUdtFetchOption.Cache` option
If this option is specified, and there is a copy of the referenced object in the object cache, it is returned immediately. If no cached copy exists, the latest copy of the referenced object in the database is cached in the object cache and returned.
- `OracleUdtFetchOption.Server` option
If this option is specified, the latest copy of the referenced object from the database is cached in the object cache and returned. If a copy of the referenced object already exists in the cache, the latest copy overwrites the existing one.
- `OracleUdtFetchOption.TransactionCache` option
If this option is specified, and a copy of the referenced object is cached in the current transaction, the copy is returned. Otherwise, the latest copy of the referenced object from the database is cached in the object cache and returned. If a copy of the referenced object already exists in the cache, the latest copy overwrites the existing one.

Note that if a cached copy of the referenced object was modified before the current transaction began, that is, if the `OracleRef.HasChanges` property returns `true`, then the `Recent` option returns the cached copy of the referenced object. Outside of a transaction, the `Recent` option behaves like the `Any` option.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRef Class](#)
- [OracleRef Members](#)
- ["OracleUdtFetchOption Enumeration"](#) on page 16-75

GetCustomObjectForUpdate

`GetCustomObjectForUpdate` methods return the object that the specified REF references as a custom type.

- `GetCustomObjectForUpdate(bool)`
This method locks the specified REF in the database and returns the object that the specified REF references as a custom type using the specified wait option.
- `GetCustomObjectForUpdate(bool, int)`
This method locks the specified REF in the database and returns the object that the specified REF references as a custom type using the specified wait option and depth level.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRef Class](#)
- [OracleRef Members](#)

GetCustomObjectForUpdate(bool)

This method locks the specified REF in the database and returns the object that the specified REF references, as a custom type, using the specified wait option.

Declaration

```
// C#  
public object GetCustomObjectForUpdate(bool bWait);
```

Parameters

- *bWait*
Specifies if the REF is to be locked with the no-wait option. If wait is set to true, this method invocation does not return until the REF is locked.

Return Value

A custom object that represents the object that the specified REF references.

Exceptions

InvalidOperationException - The specified connection is not open, or a valid custom type has not been registered for type of the referenced object.

OracleException - *bWait* is set to false, and the lock cannot be acquired.

Remarks

This method returns the latest copy of the referenced object, as a custom type, determined by the custom types registered on the *OracleRef* connection.

To be able to release the lock on the REF appropriately after flushing the REF using the *Flush* method on the *OracleRef* or *FlushCache* method on the *OracleConnection*, the application must commit or rollback the transaction. Therefore, it is required that, before invoking this method, a transaction is explicitly started by executing the *BeginTransaction* method on the *OracleConnection* object.

This method makes a network round-trip to lock the REF in the database. After this call, programmers can modify the associated row object exclusively. Then a call to the *Flush* method on the *OracleRef* or *FlushCache* method on the *OracleConnection* flushes the changes to the database.

If true is passed, this method blocks until the lock can be acquired. If false is passed, this method immediately returns. If the lock cannot be acquired, an *OracleException* is thrown.

The connection must be opened explicitly by the application. This method does not open the connection implicitly.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

GetCustomObjectForUpdate(bool, int)

This method locks the specified REF in the database and returns the object that the specified REF references, as a custom type, using the specified wait option and depth level

Declaration

```
public object GetCustomObjectForUpdate(bool bWait, int depthLevel);
```

Parameters

- *bWait*
A boolean value that specifies if the REF is to be locked with the no-wait option. If wait is set to true, this method invocation does not return until the REF is locked.
- *depthLevel*
The number of levels to be fetched for nested REF attributes.

Return Value

A custom object that represents the object that the specified REF references.

Exceptions

InvalidOperationException - The specified connection is not open, or a valid custom type has not been registered for type of the referenced object.

OracleException - *bWait* is set to false, and the lock cannot be acquired.

Remarks

This method returns the latest copy of the referenced object, as a custom type, determined by the custom types registered on the OracleRef connection.

To be able to release the lock on the REF appropriately after flushing the REF using the *Flush* method on the OracleRef or *FlushCache* method on the OracleConnection, the application must commit or rollback the transaction. Therefore, it is required that, before invoking this method, a transaction is explicitly started by executing the *BeginTransaction* method on the OracleConnection object.

This method makes a network round-trip to lock the REF in the database. After this call, programmers can modify the associated row object exclusively. Then a call to the *Flush* method on the OracleRef or *FlushCache* method on the OracleConnection flushes the changes to the database.

If true is passed, this method blocks until the lock can be acquired. If false is passed, this method immediately returns. If the lock cannot be acquired, an OracleException is thrown.

If the object that the REF references contains nested REF attributes, the *depthLevel* can be specified to optimize the subsequent object retrieval. The value of *depthLevel* determines the number of levels that are optimized.

For example, if the *depthLevel* is specified as 2, the optimization is applied to all top-level nested REF attributes in the object being fetched and also to all nested REF attributes within the objects referenced by the top-level nested REF attributes.

The connection must be opened explicitly by the application. This method does not open the connection implicitly.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

IsEqual

This instance method compares two OracleREF objects.

Declaration

```
// C#  
public bool IsEqual(OracleRef oraRef);
```

Parameters

- *oraRef*
The provided OracleRef object.

Return Value

bool

Remarks

This instance method returns true if the OracleRef instance and the OracleRef parameter both reference the same object. Otherwise, it returns false.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

Lock

This instance method locks the REF in the database.

Declaration

```
// C#  
public bool Lock(bool bWait);
```

Parameters

- *bWait*

Specifies if the lock is set to the no-wait option. If *bWait* is set to `true`, the method invocation does not return until the REF is locked.

Return Value

A boolean value that indicates whether or not the lock has been acquired.

Exceptions

`InvalidOperationException` - The associated connection is not open.

`ObjectDisposedException` - The object is already disposed.

Remarks

In order for the application to release the lock on the REF appropriately after the `Flush` invocation on the `OracleRef` or `FlushCache` methods, the application must commit or rollback the transaction. Therefore, it is required that, before invoking a lock on an `OracleRef` object, a transaction is explicitly started by executing the `BeginTransaction` method on the `OracleConnection` object.

This instance method makes a network round-trip to lock the REF in the database. After this call, programmers can modify the attribute values of the associated row object exclusively. Then a call to the `Flush` instance method on the `OracleRef` or `FlushCache` method on the `OracleConnection` flushes the changes to the database.

If `true` is passed, this method blocks, that is, does not return, until the lock is acquired. Consequently, the return value is always `true`.

If `false` is passed, this method immediately returns. The return value indicates `true` if the lock is acquired, and `false` if it is not.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

Update

This method updates the object referenced by the specified REF in the database using the specified custom object.

Declaration

```
// C#
public void Update(object customObject, bool bFlush);
```

Parameters

- *customObject*

The custom object used to update the referenced object.

- *bFlush*

A boolean that specifies if the changes must be flushed immediately. If *bFlush* is set to `true`, this method invocation flushes the changes immediately.

Exceptions

`InvalidOperationException` - The specified connection is not open or the custom object does not map to the type of referenced object.

Remarks

This method marks the specified `REF` for update. Depending on whether the value of `bFlush` is set to true or false, the following occurs:

- **True**

The object referenced by the specified `REF` is updated immediately in the database.

Before flushing objects, it is required that the application has explicitly started a transaction by executing the `BeginTransaction` method on the `OracleConnection` object. This is because if the object being flushed has not already been locked by the application, an exclusive lock is obtained implicitly for the object. The lock is only released when the transaction commits or rollbacks.

- **False**

The object referenced by the `REF` is not updated immediately in the database, but only when a subsequent `Flush` method is invoked for the specified `REF` or the `FlushCache` method is invoked for the specified connection.

The connection must be opened explicitly by the application. This method does not open the connection implicitly.

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

OracleUdtFetchOption Enumeration

OracleUdtFetchOption enumeration values specify how to retrieve a copy of the referenceable object.

Table 16–39 lists all the OracleUdtFetchOption enumeration values with a description of each enumerated value.

Table 16–39 OracleUdtFetchOption Enumeration Values

| Member Name | Description |
|------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Cache | If there is a copy of the referenced object in the object cache, it is returned immediately. If no cached copy exists, the latest copy of the referenced object in the database is cached in the object cache and returned. |
| Server | The latest copy of the referenced object from the database is cached in the object cache and returned. If a copy of the referenced object already exists in the cache, the latest copy overwrites the existing one. |
| TransactionCache | If a copy of the referenced object is cached in the current transaction, the copy is returned. Otherwise, the latest copy of the referenced object from the database is cached in the object cache and returned. If a copy of the referenced object already exists in the cache, the latest copy overwrites the existing one. Note that if a cached copy of the referenced object was modified before the current transaction began, that is, if the <code>OracleRef.HasChanges</code> property returns <code>true</code> , then the <code>Recent</code> option returns the cached copy of the referenced object. Outside of a transaction, the <code>Recent</code> option behaves like the <code>Any</code> option. |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces" on page 1-12](#)
- [OracleRef Class](#)
- [OracleRef Members](#)

OracleUdtStatus Enumeration

OracleUdtStatus enumeration values specify the status of an object attribute or collection element. An object attribute or a collection element can be a valid value or a null value.

[Table 16–40](#) lists all the OracleUdtStatus enumeration values with a description of each enumerated value:

Table 16–40 OracleUdtStatus Enumeration Values

| Member Name | Description |
|-------------|----------------------------------------------------------------------------------------|
| Null | Indicates that an object attribute or collection element is NULL. |
| NotNull | Indicates that a non-NULL value exists for the object attribute or collection element. |

See Also:

- ["Oracle.DataAccess.Types and Oracle.ManagedDataAccess.Types Namespaces"](#) on page 1-12
- [OracleRef Class](#)
- [OracleRef Members](#)

Oracle Data Provider for .NET Bulk Copy Classes

This chapter describes Oracle Data Provider for .NET support for Bulk Copy operations.

Note: Oracle Data Provider for .NET bulk copy operations do not support loading of UDT type columns.

This chapter includes the following topics:

- [OracleBulkCopy Class](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyOptions Enumeration](#)
- [OracleRowsCopiedEventHandler Delegate](#)
- [OracleRowsCopiedEventArgs Class](#)

OracleBulkCopy Class

An OracleBulkCopy object efficiently bulk loads or copies data into an Oracle table from another data source.

Class Inheritance

System.Object

System.OracleBulkCopy

Declaration

```
// C#  
public sealed class OracleBulkCopy : IDisposable
```

Requirements

| | |
|-----------------------|----------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | Oracle.DataAccess.dll |
| Namespace | Oracle.DataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

The OracleBulkCopy class can be used to write data to Oracle database tables only. However, the data source is not limited to Oracle databases; any data source can be used, as long as the data can be loaded to a DataTable instance or read with an IDataReader instance.

Bulk copy of string data to destination number column is currently not supported.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopy Members](#)
- [OracleBulkCopy Constructors](#)
- [OracleBulkCopy Properties](#)
- [OracleBulkCopy Public Methods](#)
- [OracleBulkCopy Events](#)

OracleBulkCopy Members

OracleBulkCopy members are listed in the following tables.

OracleBulkCopy Constructors

OracleBulkCopy constructors are listed in [Table 17-1](#).

Table 17-1 OracleBulkCopy Constructors

| Constructor | Description |
|---------------------------------------------|------------------------------------------------------------------------------|
| OracleBulkCopy Constructors | OracleBulkCopy constructors create new instances of the OracleBulkCopy class |

OracleBulkCopy Properties

OracleBulkCopy properties are listed in [Table 17-2](#).

Table 17-2 OracleBulkCopy Properties

| Property | Description |
|------------------------------------------|---------------------------------------------------------------------------------------------------------------|
| BatchSize | Specifies the number of rows to be sent as a batch to the database |
| BulkCopyOptions | Specifies the OracleBulkCopyOptions enumeration value that determines the behavior of the bulk copy operation |
| BulkCopyTimeout | Specifies the number of seconds allowed for the bulk copy operation to complete before it is aborted |
| ColumnMappings | Specifies the column mappings between the data source and destination table |
| Connection | Specifies the OracleConnection object that the Oracle database uses to perform the bulk copy operation |
| DestinationPartitionName | Specifies the database partition that the data is loaded into |
| DestinationTableName | Specifies the database table that the data is loaded in |
| NotifyAfter | Defines the number of rows to be processed before a notification event is generated |

OracleBulkCopy Public Methods

OracleBulkCopy public methods are listed in [Table 17-3](#).

Table 17-3 OracleBulkCopy Public Methods

| Method | Description |
|-------------------------------|----------------------------------------------------------|
| Close | Closes the OracleBulkCopy instance |
| Dispose | Releases any resources or memory allocated by the object |
| WriteToServer | Copies rows to a destination table |

OracleBulkCopy Events

OracleBulkCopy events are listed in [Table 17-4](#).

Table 17-4 OracleBulkCopy Events

| Event | Description |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| OracleRowsCopied | Triggered every time the number of rows specified by the <code>OracleBulkCopy.NotifyAfter</code> property has been processed |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleBulkCopy Class](#)

OracleBulkCopy Constructors

OracleBulkCopy constructors create new instances of the OracleBulkCopy class.

Overload List:

- [OracleBulkCopy\(OracleConnection\)](#)

This constructor instantiates a new instance of OracleBulkCopy class using the specified connection and default value for OracleBulkCopyOptions.

- [OracleBulkCopy\(string\)](#)

This constructor instantiates a new instance of OracleBulkCopy based on the supplied *connectionString* and default value for OracleBulkCopyOptions.

- [OracleBulkCopy\(OracleConnection, OracleBulkCopyOptions\)](#)

This constructor instantiates a new instance of OracleBulkCopy using the specified connection object and OracleBulkCopyOptions value.

- [OracleBulkCopy\(string, OracleBulkCopyOptions\)](#)

This constructor instantiates a new instance of OracleConnection based on the supplied *connectionString* and OracleBulkCopyOptions value.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

OracleBulkCopy(OracleConnection)

This constructor instantiates a new instance of OracleBulkCopy class using the specified connection and default OracleBulkCopyOptions enumeration values.

Declaration

```
// C#
public OracleBulkCopy(OracleConnection connection);
```

Parameters

- *connection*

The open instance of OracleConnection that performs the bulk copy operation.

Exceptions

ArgumentNullException - The connection parameter is null.

InvalidOperationException - The connection is not in the open state.

Remarks

The connection object passed to this constructor must be open. It remains open after the OracleBulkCopy instance is closed.

This constructor uses the default enumeration value OracleBulkCopyOptions.Default.

The `Connection` property is set to the supplied connection.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)
- ["OracleBulkCopyOptions Enumeration"](#) on page 17-46

OracleBulkCopy(string)

This constructor instantiates a new instance of the `OracleBulkCopy` class by first creating an `OracleConnection` object based on the supplied `connectionString`, then initializing the new `OracleBulkCopy` object with the `OracleConnection` object and `OracleBulkCopyOptions` default value.

Declaration

```
// C#
public OracleBulkCopy(string connectionString);
```

Parameters

- `connectionString`

The connection information used to connect to the Oracle database and perform the bulk copy operation.

Exception

`ArgumentNullException` - The `connectionString` parameter is null.

`ArgumentException` - The `connectionString` parameter is empty.

Remarks

The `WriteToServer` method opens the connection, if it is not already opened. The connection is automatically closed when the `OracleBulkCopy` instance is closed.

This constructor uses the default enumeration value `OracleBulkCopyOptions.Default`.

The `Connection` property is set to the `OracleConnection` object initialized using the supplied `connectionString`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)
- ["OracleBulkCopyOptions Enumeration"](#) on page 17-46

OracleBulkCopy(OracleConnection, OracleBulkCopyOptions)

This constructor instantiates a new instance of `OracleBulkCopy` using the specified connection object and `OracleBulkCopyOptions` value.

Declaration

```
// C#  
public OracleBulkCopy(OracleConnection connection, OracleBulkCopyOptions  
    copyOptions);
```

Parameters

- *connection*
The open instance of an `OracleConnection` object that performs the bulk copy operation.
- *copyOptions*
The combination of `OracleBulkCopyOptions` enumeration values that determine the behavior of the `OracleBulkCopy` object.

Exceptions

`ArgumentNullException` - The *connection* parameter is null.

`InvalidOperationException` - The connection is not in the open state.

Remarks

The connection passed to this constructor must be open. It remains open after the `OracleBulkCopy` instance is closed.

The `Connection` property is set to the supplied connection.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)
- ["OracleBulkCopyOptions Enumeration"](#) on page 17-46

OracleBulkCopy(string, OracleBulkCopyOptions)

This constructor instantiates a new instance of the `OracleBulkCopy` class by first creating an `OracleConnection` object based on the supplied *connectionString*, then initializing the new `OracleBulkCopy` object with the `OracleConnection` object and the supplied `OracleBulkCopyOptions` enumeration values.

Declaration

```
// C#  
public OracleBulkCopy(string connectionString, OracleBulkCopyOptions copyOptions);
```

Parameters

- *connectionString*
The connection information used to connect to the Oracle database to perform the bulk copy operation.
- *copyOptions*
The combination of `OracleBulkCopyOptions` enumeration values that determine the behavior of the bulk copy operation.

Exceptions

ArgumentNullException - The *connectionString* is null.

ArgumentException - The *connectionString* parameter is empty.

Remarks

The constructor uses the new instance of the `OracleConnection` class to initialize a new instance of the `OracleBulkCopy` class. The `OracleBulkCopy` instance behaves according to options supplied in the *copyOptions* parameter.

The connection is automatically closed when the `OracleBulkCopy` instance is closed.

The `Connection` property is set to an `OracleConnection` object initialized using the supplied *connectionString*.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)
- ["OracleBulkCopyOptions Enumeration"](#) on page 17-46

OracleBulkCopy Properties

OracleBulkCopy properties are listed in [Table 17-5](#).

Table 17-5 OracleBulkCopy Properties

| Property | Description |
|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| BatchSize | Specifies the number of rows to be sent as a batch to the database |
| BulkCopyOptions | Specifies the <code>OracleBulkCopyOptions</code> enumeration value that determines the behavior of the bulk copy operation |
| BulkCopyTimeout | Specifies the number of seconds allowed for the bulk copy operation to complete before it is aborted |
| ColumnMappings | Specifies the column mappings between the data source and destination table |
| Connection | Specifies the <code>OracleConnection</code> object that the Oracle database uses to perform the bulk copy operation |
| DestinationPartitionName | Specifies the database partition that the data is loaded into |
| DestinationTableName | Specifies the database table that the data is loaded in |
| NotifyAfter | Defines the number of rows to be processed before a notification event is generated |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

BatchSize

This property specifies the number of rows to be sent as a batch to the database.

Declaration

```
// C#
public int BatchSize {get; set;}
```

Property Value

An integer value for the number of rows to be sent to the database as a batch.

Exceptions

`ArgumentOutOfRangeException` - The batch size is less than zero.

Remarks

The default value is zero, indicating that the rows are not sent to the database in batches. The entire set of rows are sent in one single batch.

A large batch size reduces database round trips, but it can also consume large amounts of client side memory. Excessive memory consumption slows down overall machine performance and leads to errors if the process runs out of accessible memory. It is

recommended that client side memory is not consumed in excess. This can be done by reducing the batch size.

A batch is complete when `BatchSize` number of rows have been processed or there are no more rows to send to the database.

- If `BatchSize > 0` and the `UseInternalTransaction` bulk copy option is specified, each batch of the bulk copy operation occurs within a transaction. If the connection used to perform the bulk copy operation is already part of a transaction, an `InvalidOperationException` exception is raised.
- If `BatchSize > 0` and the `UseInternalTransaction` option is not specified, rows are sent to the database in batches of size `BatchSize`, but no transaction-related action is taken.

The `BatchSize` property can be set at any time. If a bulk copy is already in progress, the current batch size is determined by the previous batch size. Subsequent batches use the new batch size.

If the `BatchSize` property is initially zero and changes while a `WriteToServer` operation is in progress, that operation loads the data as a single batch. Any subsequent `WriteToServer` operations on the same `OracleBulkCopy` instance use the new `BatchSize`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)
- ["OracleBulkCopyOptions Enumeration"](#) on page 17-46

BulkCopyOptions

This property specifies the `OracleBulkCopyOptions` enumeration value that determines the behavior of the bulk copy option.

Declaration

```
// C#  
public OracleBulkCopyOptions BulkCopyOptions {get; set;}
```

Property Value

The `OracleBulkCopyOptions` enumeration object that defines the behavior of the bulk copy operation.

Exceptions

`ArgumentNullException` - The bulk copy options set is null.

Remarks

The default value of this property is `OracleBulkCopyOptions.Default` value. This property can be used to change the bulk copy options between the batches of a bulk copy operation.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)
- ["OracleBulkCopyOptions Enumeration"](#) on page 17-46

BulkCopyTimeout

This property specifies the number of seconds allowed for the bulk copy operation to complete before it is aborted.

Declaration

```
// C#
public int BulkCopyTimeout {get; set;}
```

Property Value

An integer value for the number of seconds after which the bulk copy operation times out.

Exceptions

`ArgumentOutOfRangeException` - The timeout value is set to less than zero.

Remarks

The default value is 30 seconds.

If `BatchSize>0`, rows that were sent to the database in the previous batches remain committed. The rows that are processed in the current batch are not sent to the database. If `BatchSize=0`, no rows are sent to the database.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

ColumnMappings

This property specifies the column mappings between the data source and destination table.

Declaration

```
// C#
public OracleBulkCopyColumnMappingCollection ColumnMappings {get;}
```

Property Value

The `OracleBulkCopyColumnMappingCollection` object that defines the column mapping between the source and destination table.

Remarks

The `ColumnMappings` collection is unnecessary if the data source and the destination table have the same number of columns, and the ordinal position of each source column matches the ordinal position of the corresponding destination column. However, if the column counts differ, or the ordinal positions are not consistent, the `ColumnMappings` collection must be used to ensure that data is copied into the correct columns.

During the execution of a bulk copy operation, this collection can be accessed, but it cannot be changed.

By default, this property specifies an empty collection of column mappings.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

Connection

This property specifies the `OracleConnection` object that the Oracle database uses to perform the bulk copy operation.

Declaration

```
// C#  
public OracleConnection Connection {get; }
```

Property Value

The `OracleConnection` object used for the bulk copy operations.

Remarks

This property gets the connection constructed by the `OracleBulkCopy`, if the `OracleBulkCopy` object is initialized using a connection string.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

DestinationPartitionName

This property specifies the database partition that the data is loaded into.

Declaration

```
// C#  
public string DestinationPartitionName {get; set;}
```

Property Value

A string value that identifies the destination partition name.

Remarks

If `DestinationPartitionName` is modified while a `WriteToServer` operation is running, the change does not affect the current operation. The new `DestinationPartitionName` value is used the next time a `WriteToServer` method is called.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

DestinationTableName

This property specifies the database table that the data is loaded into.

Declaration

```
// C#  
public string DestinationTableName {get; set;}
```

Property Value

A string value that identifies the destination table name.

Exceptions

`ArgumentNullException` - The destination table name set is null.

`ArgumentException` - The destination table name is empty.

Remarks

If `DestinationTableName` is modified while a `WriteToServer` operation is running, the change does not affect the current operation. The new `DestinationTableName` value is used the next time a `WriteToServer` method is called.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

NotifyAfter

This property defines the number of rows to be processed before a notification event is generated.

Declaration

```
// C#  
public int NotifyAfter {get; set;}
```

Property Value

An integer value that specifies the number of rows to be processed before the notification event is raised.

Exceptions

`ArgumentOutOfRangeException` - The property value is set to a number less than zero.

Remarks

The default value for this property is zero, to specify that no notifications events are to be generated.

This property can be retrieved in user interface components to display the progress of a bulk copy operation. The `NotifyAfter` property can be set at anytime, even during a bulk copy operation. The changes take effect for the next notification and any subsequent operations on the same instance.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

OracleBulkCopy Public Methods

OracleBulkCopy methods are listed in [Table 17–6](#).

Table 17–6 OracleBulkCopy Public Methods

| Method | Description |
|-------------------------------|----------------------------------------------------------|
| Close | Closes the OracleBulkCopy instance |
| Dispose | Releases any resources or memory allocated by the object |
| WriteToServer | Copies rows to a destination table |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

Close

This method closes the OracleBulkCopy instance.

Declaration

```
// C#
public void Close();
```

Exceptions

InvalidOperationException - The Close method was called from a OracleRowsCopied event.

Remarks

After the Close method is called on a OracleBulkCopy object, no other operation can succeed. Calls to the WriteToServer method throw an InvalidOperationException. The Close method closes the connection if the connection was opened by the OracleBulkCopy object, that is, if the OracleBulkCopy object was created by a constructor that takes a connection string.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

Dispose

This method releases any resources or memory allocated by the object.

Declaration

```
// C#
public void Dispose();
```

Implements

IDisposable

Remarks

After the `Dispose` method is called on the `OracleBulkCopy` object, no other operation can succeed. The connection is closed if the connection was opened by the `OracleBulkCopy` object, that is, if a constructor that takes a connection string created the `OracleBulkCopy` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

WriteToServer

`WriteToServer` copies rows to a destination table.

Overload List:

- [WriteToServer\(DataRow\[\]\)](#)

This method copies all rows from the supplied `DataRow` array to a destination table specified by the `DestinationTableName` property of the `OracleBulkCopy` object.
- [WriteToServer\(DataTable\)](#)

This method copies all rows in the supplied `DataTable` to a destination table specified by the `DestinationTableName` property of the `OracleBulkCopy` object.
- [WriteToServer\(IDataReader\)](#)

This method copies all rows in the supplied `IDataReader` to a destination table specified by the `DestinationTableName` property of the `OracleBulkCopy` object.
- [WriteToServer\(DataTable, DataRowState\)](#)

This method copies rows that match the supplied row state in the supplied `DataTable` to a destination table specified by the `DestinationTableName` property of the `OracleBulkCopy` object.
- [WriteToServer\(OracleRefCursor\)](#)

This method copies all rows from the specified `OracleRefCursor` to a destination table specified by the `DestinationTableName` property of the `OracleBulkCopy` object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

WriteToServer(DataRow[])

This method copies all rows from the supplied DataRow array to a destination table specified by the DestinationTableName property of the OracleBulkCopy object.

Declaration

```
// C#  
public void WriteToServer(DataRow[] rows);
```

Parameters

- *rows*
An array of DataRow objects to be copied to the destination table.

Exceptions

ArgumentNullException - The *rows* parameter is null.

InvalidOperationException - The connection is not in an open state.

Remarks

The ColumnMappings collection maps from the DataRow columns to the destination database table.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

WriteToServer(DataTable)

This method copies all rows in the supplied DataTable to a destination table specified by the DestinationTableName property of the OracleBulkCopy object.

Declaration

```
// C#  
public void WriteToServer(DataTable table);
```

Parameters

- *table*
The source DataTable containing rows to be copied to the destination table.

Exceptions

ArgumentNullException - The *table* parameter is null.

InvalidOperationException - The connection is not in an open state.

Remarks

All rows in the DataTable are copied to the destination table except those that have been deleted.

The `ColumnMappings` collection maps from the `DataTable` columns to the destination database table.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

WriteToServer(IDataReader)

This method copies all rows in the supplied `IDataReader` to a destination table specified by the `DestinationTableName` property of the `OracleBulkCopy` object.

Declaration

```
// C#  
public void WriteToServer(IDataReader reader);
```

Parameters

- *reader*

A `IDataReader` instance containing rows to be copied to the destination table.

Exceptions

`ArgumentNullException` - The *reader* parameter is null.

`InvalidOperationException` - The connection is not in an open state.

Remarks

The bulk copy operation starts with the next available row of the data reader. Typically, the *reader* returned by a call to the `ExecuteReader` method is passed to the `WriteToServer` method so that the next row becomes the first row. To copy multiple result sets, the application must call `NextResult` on the *reader* and then call the `WriteToServer` method again.

This `WriteToServer` method changes the state of the reader as it calls `reader.Read` internally to get the source rows. Thus, at the end of the `WriteToServer` operation, the *reader* is at the end of the result set.

The `ColumnMappings` collection maps from the data reader columns to the destination database table.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

WriteToServer(DataTable, DataRowState)

This method copies rows that match the supplied row state in the supplied `DataTable` to a destination table specified by the `DestinationTableName` property of the `OracleBulkCopy` object.

Declaration

```
// C#  
public void WriteToServer(DataTable table, DataRowState rowState);
```

Parameters

- *table*
A DataTable containing rows to be copied to the destination table.
- *rowState*
The DataRowState enumeration value. Only rows matching the row state are copied to the destination.

Exceptions

ArgumentNullException - The *table* or *rowState* parameter is null.

InvalidOperationException - The connection is not in an open state.

Remarks

Only rows in the DataTable that are in the state indicated in the *rowState* argument and have not been deleted are copied to the destination table.

The ColumnMappings collection maps from the DataTable columns to the destination database table.

DataRowState.Deleted is not supported and the behavior would be that all the rows except the deleted ones are copied.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

WriteToServer(OracleRefCursor)

This method copies all rows from the specified OracleRefCursor to a destination table specified by the DestinationTableName property of the OracleBulkCopy object.

Declaration

```
// C#  
public void WriteToServer(OracleRefCursor refCursor);
```

Parameters

- *refCursor*
An OracleRefCursor object containing rows to be copied to the destination table.

Exceptions

ArgumentNullException - The *refCursor* parameter is null

InvalidOperationException - The connection is not in an open state.

Remarks

The `ColumnMappings` collection maps from the `OracleRefCursor` columns to the destination database table.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

OracleBulkCopy Events

OracleBulkCopy events are listed in [Table 17-7](#).

Table 17-7 OracleBulkCopy Events

| Event | Description |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| OracleRowsCopied | Triggered every time the number of rows specified by the <code>OracleBulkCopy.NotifyAfter</code> property has been processed |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)

OracleRowsCopied

This event is triggered every time the number of rows specified by the `OracleBulkCopy.NotifyAfter` property has been processed.

Declaration

```
// C#
public event OracleRowsCopiedEventHandler OracleRowsCopied;
```

Exceptions

`InvalidOperationException` - The `Close` method is called inside this event.

Remarks

This event is raised when the number of rows specified by the `NotifyAfter` property has been processed. It does not imply that the rows have been sent to the database or committed.

To cancel the operation from this event, use the `Abort` property of `OracleRowsCopiedEventArgs` class.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleBulkCopy Class](#)
- [OracleBulkCopy Members](#)
- ["NotifyAfter"](#) on page 17-13

OracleBulkCopyColumnMapping Class

The `OracleBulkCopyColumnMapping` class defines the mapping between a column in the data source and a column in the destination database table.

Class Inheritance

`System.Object`

`System.OracleBulkCopyColumnMapping`

Declaration

```
// C#  
public sealed class OracleBulkCopyColumnMapping
```

Requirements

| | |
|-----------------------|---------------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | <code>Oracle.DataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Client</code> |
| .NET Framework | 3.5, 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

Column mappings define the mapping between data source and the target table.

It is not necessary to specify column mappings for all the columns in the data source. If a `ColumnMapping` is not specified, then, by default, columns are mapped based on the ordinal position. This succeeds only if the source and destination table schema match. If there is a mismatch, an `InvalidOperationException` is thrown.

All the mappings in a mapping collection must be by name or ordinal position.

Note: Oracle Data Provider for .NET makes one or more round-trips to the database to determine the column name if the mapping is specified by ordinal position. To avoid this performance overhead, specify the mapping by column name.

Example

```
// C#
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMapping Members](#)
- [OracleBulkCopyColumnMapping Constructors](#)
- [OracleBulkCopyColumnMapping Methods](#)
- [OracleBulkCopyColumnMapping Properties](#)

OracleBulkCopyColumnMapping Members

OracleBulkCopyColumnMapping members are listed in the following tables.

OracleBulkCopyColumnMapping Constructors

The OracleBulkCopyColumnMapping constructors are listed in [Table 17–8](#).

Table 17–8 OracleBulkCopyColumnMapping Constructors

| Constructor | Description |
|----------------------------------------------------------|---------------------------------------------------------------------|
| OracleBulkCopyColumnMapping Constructors | Instantiates new instances of the OracleBulkCopyColumnMapping class |

OracleBulkCopyColumnMapping Methods

The OracleBulkCopyColumnMapping method is listed in [Table 17–9](#).

Table 17–9 OracleBulkCopyColumnMapping Method

| Constructor | Description |
|---------------------------|-------------------------------------------------------------------------------------------------------------------|
| CompareTo | Compares the current instance to the supplied object and returns an integer that represents their relative values |

OracleBulkCopyColumnMapping Properties

The OracleBulkCopyColumnMapping properties are listed in [Table 17–10](#).

Table 17–10 OracleBulkCopyColumnMapping Properties

| Property | Description |
|------------------------------------|----------------------------------------------------------------------------------|
| DestinationColumn | Specifies the column name of the destination table that is being mapped |
| DestinationOrdinal | Specifies the column ordinal value of the destination table that is being mapped |
| SourceColumn | Specifies the column name of the data source that is being mapped |
| SourceOrdinal | Specifies the column ordinal value of the data source that is being mapped |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleBulkCopyColumnMapping Class](#)

OracleBulkCopyColumnMapping Constructors

OracleBulkCopyColumnMapping constructors instantiates new instances of the OracleBulkCopyColumnMapping class.

Overload List:

- [OracleBulkCopyColumnMapping\(\)](#)
This constructor instantiates a new instance of the OracleBulkCopyColumnMapping class
- [OracleBulkCopyColumnMapping\(int, int\)](#)
This constructor instantiates a new instance of the OracleBulkCopyColumnMapping class using the provided source column ordinal and destination column ordinal.
- [OracleBulkCopyColumnMapping\(int, string\)](#)
This constructor instantiates a new instance of the OracleBulkCopyColumnMapping class using the provided source column ordinal and destination column name.
- [OracleBulkCopyColumnMapping\(string, int\)](#)
This constructor instantiates a new instance of the OracleBulkCopyColumnMapping class using the provided source column name and destination column ordinal.
- [OracleBulkCopyColumnMapping\(string, string\)](#)
This constructor instantiates a new instance of the OracleBulkCopyColumnMapping class using the provided source column name and destination column name.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

OracleBulkCopyColumnMapping()

This constructor instantiates a new instance of the OracleBulkCopyColumnMapping class.

Declaration

```
// C#  
public OracleBulkCopyColumnMapping();
```

Remarks

Applications that use this constructor must define the source for the mapping using the `SourceColumn` or `SourceOrdinal` property, and must define the destination for the mapping using the `DestinationColumn` or `DestinationOrdinal` property.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

OracleBulkCopyColumnMapping(int, int)

This constructor instantiates a new instance of the `OracleBulkCopyColumnMapping` class using the provided source and destination column ordinal positions.

Declaration

```
// C#  
public OracleBulkCopyColumnMapping(int sourceColumnOrdinal,  
    int destinationOrdinal);
```

Parameters

- *sourceColumnOrdinal*
The ordinal position of the source column within the data source.
- *destinationOrdinal*
The ordinal position of the destination column within the destination table.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

OracleBulkCopyColumnMapping(int, string)

This constructor instantiates a new instance of the `OracleBulkCopyColumnMapping` class using the provided source column ordinal and destination column name.

Declaration

```
// C#  
public OracleBulkCopyColumnMapping(int sourceColumnOrdinal,  
    string destinationColumn);
```

Parameters

- *sourceColumnOrdinal*
The ordinal position of the source column within the data source.
- *destinationColumn*
The name of the destination column within the destination table.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

OracleBulkCopyColumnMapping(string, int)

This constructor instantiates a new instance of the `OracleBulkCopyColumnMapping` class using the provided source column name and destination column ordinal.

Declaration

```
// C#  
public OracleBulkCopyColumnMapping(string sourceColumn, int destinationOrdinal);
```

Parameters

- *sourceColumn*
The name of the source column within the data source.
- *destinationOrdinal*
The ordinal position of the destination column within the destination table.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

OracleBulkCopyColumnMapping(string, string)

This constructor instantiates a new instance of the `OracleBulkCopyColumnMapping` class using the provided source and destination column names.

Declaration

```
// C#  
public OracleBulkCopyColumnMapping(string sourceColumn, string destinationColumn);
```

Parameters

- *sourceColumn*
The name of the source column within the data source.
- *destinationColumn*
The name of the destination column within the destination table.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

OracleBulkCopyColumnMapping Methods

The `OracleBulkCopyColumnMapping` method is listed in [Table 17–11](#).

Table 17–11 *OracleBulkCopyColumnMapping Method*

| Property | Description |
|---------------------------|-------------------------------------------------------------------------------------------------------------------|
| CompareTo | Compares the current instance to the supplied object and returns an integer that represents their relative values |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

CompareTo

This method compares the current instance to the supplied object and returns an integer that represents their relative values.

Declaration

```
// C#
public int CompareTo(object obj);
```

Parameters

`obj` - The supplied instance.

Return Value

Less than zero: if the value of the current instance is less than `obj`.

Zero: if the value of the current instance is equal to `obj`.

Greater than zero: if the value of the current instance is greater than `obj`.

Implements

`IComparable`

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

OracleBulkCopyColumnMapping Properties

The OracleBulkCopyColumnMapping properties are listed in [Table 17–12](#).

Table 17–12 OracleBulkCopyColumnMapping Properties

| Property | Description |
|------------------------------------|----------------------------------------------------------------------------------|
| DestinationColumn | Specifies the column name of the destination table that is being mapped |
| DestinationOrdinal | Specifies the column ordinal value of the destination table that is being mapped |
| SourceColumn | Specifies the column name of the data source that is being mapped |
| SourceOrdinal | Specifies the column ordinal value of the data source that is being mapped |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

DestinationColumn

This property specifies the column name of the destination table that is being mapped.

Declaration

```
// C#
public string DestinationColumn {get; set;}
```

Property Value

A string value that represents the destination column name of the mapping.

Remarks

The DestinationColumn and DestinationOrdinal properties are mutually exclusive. The last value set takes precedence.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

DestinationOrdinal

This property specifies the column ordinal value of the destination table that is being mapped.

Declaration

```
// C#
```

```
public int DestinationOrdinal {get; set;}
```

Property Value

An integer value that represents the destination column ordinal of the mapping.

Exceptions

`IndexOutOfRangeException` - The destination ordinal is invalid.

Remarks

The `DestinationOrdinal` and `DestinationColumn` properties are mutually exclusive. The last value set takes precedence.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

SourceColumn

This property specifies the column name of the data source that is being mapped.

Declaration

```
// C#
public string SourceColumn {get; set;}
```

Property Value

A string value that represents the source column name of the mapping.

Remarks

The `SourceColumn` and `SourceOrdinal` properties are mutually exclusive. The last value set takes precedence.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

SourceOrdinal

This property specifies the column ordinal value of the data source that is being mapped.

Declaration

```
// C#
public int SourceOrdinal {get; set;}
```

Property Value

An integer value that represents the source column ordinal of the mapping.

Exceptions

`IndexOutOfRangeException` - The source ordinal is invalid.

Remarks

The `SourceOrdinal` and `SourceColumn` properties are mutually exclusive. The last value set takes precedence.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMapping Class](#)
- [OracleBulkCopyColumnMapping Members](#)

OracleBulkCopyColumnMappingCollection Class

The `OracleBulkCopyColumnMappingCollection` class represents a collection of `OracleBulkCopyColumnMapping` objects that are used to map columns in the data source to columns in a destination table.

Class Inheritance

`System.Object`

`System.CollectionBase`

`System.OracleBulkCopyColumnMappingCollection`

Declaration

```
// C#
public sealed class OracleBulkCopyColumnMappingCollection : CollectionBase
```

Requirements

| | |
|-----------------------|---------------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | <code>Oracle.DataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Client</code> |
| .NET Framework | 3.5, 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

Column mappings define the mapping between data source and the target table.

It is not necessary to specify column mappings for all the columns in the data source. If a `ColumnMapping` is not specified, then, by default, columns are mapped based on the ordinal position. This succeeds only if the source and destination table schema match. If there is a mismatch, an `InvalidOperationException` is thrown.

All the mappings in a mapping collection must be by name or ordinal position.

Note: Oracle Data Provider for .NET makes one or more round-trips to the database to determine the column name if the mapping is specified by ordinal position. To avoid this performance overhead, specify the mapping by column name.

Example

```
// C#
```

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)
- [OracleBulkCopyColumnMappingCollection Properties](#)
- [OracleBulkCopyColumnMappingCollection Public Methods](#)

OracleBulkCopyColumnMappingCollection Members

OracleBulkCopyColumnMappingCollection members are listed in the following tables.

OracleBulkCopyColumnMappingCollection Properties

The OracleBulkCopyColumnMappingCollection properties are listed in [Table 17–13](#).

Table 17–13 OracleBulkCopyColumnMappingCollection Properties

| Property | Description |
|-----------------------------|--------------------------------------------------------------------------------------|
| Item[index] | Gets or sets the OracleBulkCopyColumnMappingCollection object at the specified index |

OracleBulkCopyColumnMappingCollection Public Methods

The OracleBulkCopyColumnMappingCollection public methods are listed in [Table 17–14](#).

Table 17–14 OracleBulkCopyColumnMappingCollection Public Methods

| Public Method | Description |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| Add | Adds objects to the collection |
| Clear | Clears the contents of the collection |
| Contains | Returns a value indicating whether or not a specified OracleBulkCopyColumnMapping object exists in the collection |
| CopyTo | Copies the elements of the OracleBulkCopyColumnMappingCollection to an array of OracleBulkCopyColumnMapping items, starting at a specified index |
| IndexOf | Returns the index of the specified OracleBulkCopyColumnMapping object |
| Insert | Inserts a new OracleBulkCopyColumnMapping object in the collection, at the index specified. |
| Remove | Removes the specified OracleBulkCopyColumnMapping element from the OracleBulkCopyColumnMappingCollection. |
| RemoveAt | Removes the mapping from the collection at the specified index. |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleBulkCopyColumnMappingCollection Class](#)

OracleBulkCopyColumnMappingCollection Properties

The OracleBulkCopyColumnMappingCollection properties are listed in [Table 17–15](#).

Table 17–15 OracleBulkCopyColumnMappingCollection Properties

| Property | Description |
|-----------------------------|--------------------------------------------------------------------------------------|
| Item[index] | Gets or sets the OracleBulkCopyColumnMappingCollection object at the specified index |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

Item[index]

This property gets or sets the OracleBulkCopyColumnMapping object at the specified index.

Declaration

```
// C#
public OracleBulkCopyColumnMapping this[int index] {get;set;}
```

Parameters

- *index*

The zero-based index of the OracleBulkCopyColumnMapping being set or retrieved.

Property Value

An OracleBulkCopyColumnMapping object at the specified index.

Exceptions

IndexOutOfRangeException - The specified index does not exist.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

OracleBulkCopyColumnMappingCollection Public Methods

The `OracleBulkCopyColumnMappingCollection` public methods are listed in [Table 17–16](#).

Table 17–16 *OracleBulkCopyColumnMappingCollection Public Methods*

| Public Method | Description |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Add | Adds objects to the collection |
| Clear | Clears the contents of the collection |
| Contains | Returns a value indicating whether or not a specified <code>OracleBulkCopyColumnMapping</code> object exists in the collection |
| CopyTo | Copies the elements of the <code>OracleBulkCopyColumnMappingCollection</code> to an array of <code>OracleBulkCopyColumnMapping</code> items, starting at a specified index |
| IndexOf | Returns the index of the specified <code>OracleBulkCopyColumnMapping</code> object |
| Insert | Inserts a new <code>OracleBulkCopyColumnMapping</code> object in the collection, at the index specified. |
| Remove | Removes the specified <code>OracleBulkCopyColumnMapping</code> element from the <code>OracleBulkCopyColumnMappingCollection</code> . |
| RemoveAt | Removes the mapping from the collection at the specified index. |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

Add

Add methods add objects to the collection.

Overload List:

- [Add\(OracleBulkCopyColumnMapping\)](#)
This method adds the supplied `OracleBulkCopyColumnMapping` object to the collection.
- [Add\(int, int\)](#)
This method creates and adds an `OracleBulkCopyColumnMapping` object to the collection using the supplied source and destination column ordinal positions.
- [Add\(int, string\)](#)
This method creates and adds an `OracleBulkCopyColumnMapping` object to the collection using the supplied source column ordinal and destination column name.
- [Add\(string, int\)](#)
This method creates and adds an `OracleBulkCopyColumnMapping` object to the collection using the supplied source column name and destination column ordinal.

- [Add\(string, string\)](#)

This method creates and adds an `OracleBulkCopyColumnMapping` object to the collection using the supplied source and destination column names.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

Add(OracleBulkCopyColumnMapping)

This method adds the supplied `OracleBulkCopyColumnMapping` object to the collection.

Declaration

```
// C#  
public OracleBulkCopyColumnMapping Add(OracleBulkCopyColumnMapping  
    bulkCopyColumnMapping);
```

Parameters

- *bulkCopyColumnMapping*

The `OracleBulkCopyColumnMapping` object that describes the mapping to be added to the collection.

Exceptions

`InvalidOperationException` - The bulk copy operation is in progress.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

Add(int, int)

This method creates and adds an `OracleBulkCopyColumnMapping` object to the collection using the supplied source and destination column ordinal positions.

Declaration

```
// C#  
public OracleBulkCopyColumnMapping Add(int sourceColumnIndex,  
    int destinationColumnIndex);
```

Parameters

- *sourceColumnIndex*

The ordinal position of the source column within the data source.

- *destinationColumnIndex*

The ordinal position of the destination column within the destination table.

Exceptions

`InvalidOperationException` - The bulk copy operation is in progress.

Return Value

The newly created `OracleBulkCopyColumnMapping` object that was added to the collection.

Remarks

It is not necessary to specify column mappings for all the columns in the data source. If a `ColumnMapping` is not specified, then, by default, columns are mapped based on the ordinal position. This succeeds only if the source and destination table schema match. If there is a mismatch, an `InvalidOperationException` is thrown.

All the mappings in a mapping collection must be by name or ordinal position.

Note: Oracle Data Provider for .NET makes one or more round-trips to the database to determine the column name if the mapping is specified by ordinal position. To avoid this performance overhead, specify the mapping by column name.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

Add(int, string)

This method creates and adds an `OracleBulkCopyColumnMapping` object to the collection using the supplied source column ordinal and destination column name.

Declaration

```
// C#
public OracleBulkCopyColumnMapping Add(int sourceColumnIndex,
    string destinationColumn);
```

Parameters

- *sourceColumnIndex*
The ordinal position of the source column within the data source.
- *destinationColumn*
The name of the destination column within the destination table.

Exceptions

`InvalidOperationException` - The bulk copy operation is in progress.

Return Value

The newly created `OracleBulkCopyColumnMapping` object that was added to the collection.

Remarks

It is not necessary to specify column mappings for all the columns in the data source. If a `ColumnMapping` is not specified, then, by default, columns are mapped based on the ordinal position. This succeeds only if the source and destination table schema match. If there is a mismatch, an `InvalidOperationException` is thrown.

All the mappings in a mapping collection must be by name or ordinal position.

Note: Oracle Data Provider for .NET makes one or more round trips to the database to determine the column names if the mapping is specified by ordinal resulting in a performance overhead. Therefore, it is recommended to specify the mapping by column names.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

Add(string, int)

This method creates and adds an `OracleBulkCopyColumnMapping` object to the collection using the supplied source column name and destination column ordinal.

Declaration

```
// C#
public OracleBulkCopyColumnMapping Add(string sourceColumn,
    int destinationColumnIndex);
```

Parameters

- *sourceColumn*
The name of the source column within the data source.
- *destinationColumnIndex*
The ordinal position of the destination column within the destination table.

Return Value

The newly created `OracleBulkCopyColumnMapping` object that was added to the collection.

Exceptions

`InvalidOperationException` - The bulk copy operation is in progress.

Remarks

It is not necessary to specify column mappings for all the columns in the data source. If a `ColumnMapping` is not specified, then, by default, columns are mapped based on the ordinal position. This succeeds only if the source and destination table schema match. If there is a mismatch, an `InvalidOperationException` is thrown.

All the mappings in a mapping collection must be by name or ordinal position.

Note: Oracle Data Provider for .NET makes one or more round trips to the database to determine the column names if the mapping is specified by ordinal resulting in a performance overhead. Therefore, it is recommended to specify the mapping by column names.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

Add(string, string)

This method creates and adds an `OracleBulkCopyColumnMapping` object to the collection using the supplied source and destination column names.

Declaration

```
// C#
public OracleBulkCopyColumnMapping Add(string sourceColumn,
    string destinationColumn);
```

Parameters

- *sourceColumn*
The name of the source column within the data source.
- *destinationColumn*
The name of the destination column within the destination table.

Exceptions

`InvalidOperationException` - The bulk copy operation is in progress.

Return Value

The newly created `OracleBulkCopyColumnMapping` object that was added to the collection.

Remarks

It is not necessary to specify column mappings for all the columns in the data source. If a `ColumnMapping` is not specified, then, by default, columns are mapped based on the ordinal position. This succeeds only if the source and destination table schema match. If there is a mismatch, an `InvalidOperationException` is thrown.

All the mappings in a mapping collection must be by name or ordinal position.

Note: Oracle Data Provider for .NET makes one or more round-trips to the database to determine the column name if the mapping is specified by ordinal position. To avoid this performance overhead, specify the mapping by column name.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

Clear

This method clears the contents of the collection.

Declaration

```
// C#  
public void Clear();
```

Exceptions

`InvalidOperationException` - The bulk copy operation is in progress.

Remarks

The `Clear` method is most commonly used when an application uses a single `OracleBulkCopy` instance to process more than one bulk copy operation. If column mappings are created for one bulk copy operation, the `OracleBulkCopyColumnMappingCollection` must be cleared after the `WriteToServer` method invocation and before the next bulk copy is processed.

It is usually more efficient to perform several bulk copies using the same `OracleBulkCopy` instance than to use a separate `OracleBulkCopy` for each operation.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

Contains

This method returns a value indicating whether or not a specified `OracleBulkCopyColumnMapping` object exists in the collection.

Declaration

```
// C#  
public bool Contains(OracleBulkCopyColumnMapping value);
```

Parameters

- *value*
A valid `OracleBulkCopyColumnMapping` object.

Return Value

Returns `true` if the specified mapping exists in the collection; otherwise, returns `false`.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

CopyTo

This method copies the elements of the `OracleBulkCopyColumnMappingCollection` to an array of `OracleBulkCopyColumnMapping` items, starting at a specified index.

Declaration

```
// C#  
public void CopyTo(OracleBulkCopyColumnMapping[] array, int index);
```

Parameters

- *array*

The one-dimensional `OracleBulkCopyColumnMapping` array that is the destination for the elements copied from the `OracleBulkCopyColumnMappingCollection` object. The array must have zero-based indexing.

- *index*

The zero-based array index at which copying begins.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

IndexOf

This method returns the index of the specified `OracleBulkCopyColumnMapping` object.

Declaration

```
// C#  
public int IndexOf(OracleBulkCopyColumnMapping value);
```

Parameters

- *value*

The `OracleBulkCopyColumnMapping` object that is being returned.

Return Value

The zero-based index of the column mapping or -1 if the column mapping is not found in the collection.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

Insert

This method inserts a new `OracleBulkCopyColumnMapping` object in the collection, at the index specified.

Declaration

```
// C#  
public void Insert(int index, OracleBulkCopyColumnMapping value);
```

Parameters

- *index*
The integer value of the location within the `OracleBulkCopyColumnMappingCollection` at which the new `OracleBulkCopyColumnMapping` is inserted.
- *value*
The `OracleBulkCopyColumnMapping` object to be inserted in the collection.

Exceptions

`InvalidOperationException` - The bulk copy operation is in progress.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

Remove

This method removes the specified `OracleBulkCopyColumnMapping` element from the `OracleBulkCopyColumnMappingCollection`.

Declaration

```
// C#  
public void Remove(OracleBulkCopyColumnMapping value);
```

Parameters

- *value*
The `OracleBulkCopyColumnMapping` object to be removed from the collection.

Exceptions

`InvalidOperationException` - The bulk copy operation is in progress.

Remarks

The `Remove` method is most commonly used when a single `OracleBulkCopy` instance processes more than one bulk copy operation. If column mappings are created for one bulk copy operation, mappings that no longer apply must be removed after the `WriteToServer` method invocation and before mappings are defined for the next bulk copy. The `Clear` method can clear the entire collection, and the `Remove` and the `RemoveAt` methods can remove mappings individually.

It is usually more efficient to perform several bulk copies using the same `OracleBulkCopy` instance than to use a separate `OracleBulkCopy` for each operation.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

RemoveAt

This method removes the mapping from the collection at the specified index.

Declaration

```
// C#  
public void RemoveAt(int index);
```

Parameters

- *index*

The zero-based index of the `OracleBulkCopyColumnMapping` object to be removed from the collection.

Exceptions

`InvalidOperationException` - The bulk copy operation is in progress.

Remarks

The `RemoveAt` method is most commonly used when a single `OracleBulkCopy` instance is used to process more than one bulk copy operation. If column mappings are created for one bulk copy operation, mappings that no longer apply must be removed after the `WriteToServer` method invocation and before the mappings for the next bulk copy are defined. The `Clear` method can clear the entire collection, and the `Remove` and the `RemoveAt` methods can remove mappings individually.

It is usually more efficient to perform several bulk copies using the same `OracleBulkCopy` instance than to use a separate `OracleBulkCopy` for each operation.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleBulkCopyColumnMappingCollection Class](#)
- [OracleBulkCopyColumnMappingCollection Members](#)

OracleBulkCopyOptions Enumeration

The `OracleBulkCopyOptions` enumeration specifies the values that can be combined with an instance of the `OracleBulkCopy` class and used as options to determine its behavior and the behavior of the `WriteToServer` methods for that instance.

[Table 17-17](#) lists all the `OracleBulkCopyOptions` enumeration values with a description of each enumerated value.

Table 17-17 *OracleBulkCopyOptions Enumeration Members*

| Member Name | Description |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Default | Indicates that the default value for all options are to be used |
| UseInternalTransaction | Indicates that each batch of the bulk copy operation occurs within a transaction. If the connection used to perform the bulk copy operation is already part of a transaction, an <code>InvalidOperationException</code> exception is raised. If this member is not specified, <code>BatchSize</code> number of rows are sent to the database, without any transaction-related activity. |

Note: All bulk copy operations are agnostic of any local or distributed transaction created by the application.

Requirements

| | |
|----------------|---------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | Oracle.DataAccess.dll |
| Namespace | Oracle.DataAccess.Client |
| .NET Framework | 3.5, 4.0, 4.5 |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- `OracleBulkCopy` ["BulkCopyOptions"](#) on page 17-10

OracleRowsCopiedEventHandler Delegate

The `OracleRowsCopiedEventHandler` delegate represents the method that handles the `OracleRowsCopied` event of an `OracleBulkCopy` object.

Declaration

```
// C#
public delegate void OracleRowsCopiedEventHandler (object sender,
    OracleRowsCopiedEventArgs eventArgs);
```

Requirements

| | |
|-----------------------|---------------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | <code>Oracle.DataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Client</code> |
| .NET Framework | 3.5, 4.0, 4.5 |

Parameters

- *sender*
The source of the event.
- *eventArgs*
The `OracleRowsCopiedEventArgs` object that contains the event data.

Remarks

Event callbacks can be registered through this event delegate for applications that wish to be notified every time the number of rows specified by the `OracleBulkCopy.NotifyAfter` property has been processed.

If the event handler calls the `OracleBulkCopy.Close` method, an exception is generated, and the `OracleBulkCopy` object state does not change.

The event handler can also set the `OracleRowsCopiedEventArgs.Abort` property to `true` to indicate that the bulk copy operation must be aborted. If the bulk copy operation is part of an external transaction, an exception is generated and the transaction is not rolled back. The application is responsible for either committing or rolling back the external transaction.

If there is no external transaction, the internal transaction for the current batch of rows is automatically rolled back. However the previous batches of imported rows are unaffected, as their transactions have already been committed.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- ["OracleRowsCopied"](#) on page 21
- ["NotifyAfter"](#) on page 17-13

OracleRowsCopiedEventArgs Class

The `OracleRowsCopiedEventArgs` class represents the set of arguments passed as part of event data for the `OracleRowsCopied` event.

Class Inheritance

`System.Object`

`System.EventArgs`

`System.OracleRowsCopiedEventArgs`

Declaration

```
// C#  
public class OracleRowsCopiedEventArgs : EventArgs
```

Requirements

| | |
|-----------------------|---------------------------------------|
| Provider | ODP.NET, Unmanaged Driver |
| Assembly | <code>Oracle.DataAccess.dll</code> |
| Namespace | <code>Oracle.DataAccess.Client</code> |
| .NET Framework | 3.5, 4.0, 4.5 |

Thread Safety

All public static methods are thread-safe, although instance methods do not guarantee thread safety.

Remarks

Each time the number of rows represented by the `OracleBulkCopy.NotifyAfter` property is processed, the `OracleBulkCopy.OracleRowsCopied` event is raised, providing an `OracleRowsCopiedEventArgs` object that stores the event data.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleRowsCopiedEventArgs Members](#)
- [OracleRowsCopiedEventArgs Constructors](#)
- [OracleRowsCopiedEventArgs Properties](#)

OracleRowsCopiedEventArgs Members

OracleRowsCopiedEventArgs members are listed in the following tables.

OracleRowsCopiedEventArgs Constructors

OracleRowsCopiedEventArgs constructors are listed in [Table 17–18](#).

Table 17–18 OracleRowsCopiedEventArgs Constructors

| Constructor | Description |
|----------------------------------------------------------|----------------------------------------------------------------------------------------|
| OracleRowsCopiedEventArgs Constructors . | OracleRowsCopiedEventArgs creates new instances of the OracleRowsCopiedEventArgs class |

OracleRowsCopiedEventArgs Properties

OracleRowsCopiedEventArgs properties are listed in [Table 17–19](#).

Table 17–19 OracleRowsCopiedEventArgs Properties

| Property | Description |
|----------------------------|----------------------------------------------------------------------------------------------------|
| Abort | Retrieves or sets a value that indicates whether or not the bulk copy operation is aborted |
| RowsCopied | Retrieves a value that represents the number of rows copied during the current bulk copy operation |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleRowsCopiedEventArgs Class](#)

OracleRowsCopiedEventArgs Constructors

OracleRowsCopiedEventArgs creates new instances of the OracleRowsCopiedEventArgs class.

Overload List:

- [OracleRowsCopiedEventArgs\(long\)](#)

This constructor creates a new instance of the OracleRowsCopiedEventArgs object.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleRowsCopiedEventArgs Class](#)
- [OracleRowsCopiedEventArgs Members](#)

OracleRowsCopiedEventArgs(long)

This constructor creates a new instance of the OracleRowsCopiedEventArgs object.

Declaration

```
// C#  
public OracleRowsCopiedEventArgs(long rowsCopied);
```

Parameters

- *rowsCopied*

An Int64 value that indicates the number of rows copied during the current bulk copy operation.

Remarks

The value in the *rowsCopied* parameter is reset by each call to a WriteToServer method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleRowsCopiedEventArgs Class](#)
- [OracleRowsCopiedEventArgs Members](#)

OracleRowsCopiedEventArgs Properties

OracleRowsCopiedEventArgs properties are listed in [Table 17–20](#).

Table 17–20 OracleRowsCopiedEventArgs Properties

| Property | Description |
|----------------------------|----------------------------------------------------------------------------------------------------|
| Abort | Retrieves or sets a value that indicates whether or not the bulk copy operation is aborted |
| RowsCopied | Retrieves a value that represents the number of rows copied during the current bulk copy operation |

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleRowsCopiedEventArgs Class](#)
- [OracleRowsCopiedEventArgs Members](#)

Abort

This property retrieves or sets a value that indicates whether or not the bulk copy operation is aborted.

Declaration

```
// C#
public bool Abort{get; set;}
```

Property Value

Returns `true` if the bulk copy operation is to be aborted; otherwise, returns `false`.

Remarks

Set the `Abort` property to `true` to cancel the bulk copy operation.

If the `Close` method is called from `OracleRowsCopied`, an exception is generated, and the `OracleBulkCopy` object state does not change.

If the application does not create a transaction, the internal transaction corresponding to the current batch is automatically rolled back. However, changes related to previous batches within the bulk copy operation are retained, because the transactions in those batches are committed. This case is applicable only when `UseInternalTransaction` bulk copy option is chosen.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces"](#) on page 1-5
- [OracleRowsCopiedEventArgs Class](#)
- [OracleRowsCopiedEventArgs Members](#)

RowsCopied

This property retrieves a value that represents the number of rows copied during the current bulk copy operation.

Declaration

```
// C#  
public long RowsCopied {get;}
```

Property Value

An Int64 value that returns the number of rows copied.

Remarks

The value in the RowsCopied property is reset by each call to a WriteToServer method.

See Also:

- ["Oracle.DataAccess.Client and Oracle.ManagedDataAccess.Client Namespaces" on page 1-5](#)
- [OracleRowsCopiedEventArgs Class](#)
- [OracleRowsCopiedEventArgs Members](#)

Oracle Schema Collections

ODP.NET provides standard metadata collections as well as various Oracle database-specific metadata collections that can be retrieved through the `OracleConnection.GetSchema` API.

See Also:

- ["Schema Discovery"](#) on page 3-9
- ["GetSchema"](#) on page 6-118

This appendix contains the following topics:

- [Common Schema Collections](#)
- [ODP.NET-Specific Schema Collection](#)

Common Schema Collections

The common schema collections are available for all .NET Framework managed providers. ODP.NET supports the same common schema collections.

See Also: "Understanding the Common Schema Collections" in the MSDN Library

- [MetaDataCollections](#)
- [DataSourceInformation](#)
- [DataTypes](#)
- [Restrictions](#)
- [ReservedWords](#)

MetaDataCollections

[Table A-1](#) is a list of metadata collections that is available from the data source, such as tables, columns, indexes, and stored procedures.

Table A-1 *MetaDataCollections*

| Column Name | Data Type | Description |
|----------------|-----------|---------------------------------------------------------------------------------------|
| CollectionName | string | The name of the collection passed to the <code>GetSchema</code> method for retrieval. |

Table A-1 (Cont.) MetaDataCollections

| Column Name | Data Type | Description |
|-------------------------|-----------|-------------------------------------------------------------------|
| NumberOfRestrictions | int | Number of restrictions specified for the named collection. |
| NumberOfIdentifierParts | int | Number of parts in the composite identifier/database object name. |

DataSourceInformation

[Table A-2](#) lists DataSourceInformation information which may include these columns and possibly others.

Table A-2 DataSourceInformation

| Columns | Data Type | Description |
|-------------------------------------|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CompositeIdentifierSeparatorPattern | string | Separator for multipart names: @ \ . |
| DataSourceProductName | string | Database name: Oracle |
| DataSourceProductVersion | string | Database version. Note that this is the version of the database instance currently being accessed by DbConnection. |
| DataSourceProductVersionNormalized | string | A normalized DataSource version for easier comparison between different versions. For example: DataSource Version: 10.2.0.1.0 Normalized DataSource Version: 10.02.00.01.00 |
| GroupByBehavior | GroupByBehavior | An enumeration that indicates the relationship between the columns in a GROUP BY clause and the non-aggregated columns in a select list. |
| IdentifierPattern | string | Format for a valid identifier. |
| IdentifierCase | IdentifierCase | An enumeration that specifies whether or not to treat non-quoted identifiers as case sensitive. |
| OrderByColumnsInSelect | bool | A boolean that indicates whether or not the select list must contain the columns in an ORDER BY clause. |
| ParameterMarkerFormat | string | A string indicating whether or not parameter markers begin with a special character. |
| ParameterMarkerPattern | string | The format of a parameter marker. |
| ParameterNameMaxLength | int | Maximum length of a parameter. |
| ParameterNamePattern | string | The format for a valid parameter name. |
| QuotedIdentifierPattern | string | The format of a quoted identifier. |
| QuotedIdentifierCase | IdentifierCase | An enumeration that specifies whether or not to treat quote identifiers as case sensitive. |
| StringLiteralPattern | string | The format for a string literal. |
| SupportedJoinOperators | SupportedJoinOperators | An enumeration indicating the types of SQL join statements supported by the data source. |

DataTypes

Table A-3 lists DataTypes Collection information which may include these columns and possibly others.

Note: As an example, the description column includes complete information for the `TIMESTAMP WITH LOCAL TIME ZONE` data type.

Table A-3 *DataTypes*

| ColumnName | Data Type | Description |
|-----------------------|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| TypeName | string | The provider-specific data type name. Example: <code>TIMESTAMP WITH LOCAL TIME ZONE</code> |
| ProviderDbType | int | The provider-specific type value. Example: 124 |
| ColumnSize | long | The length of a non-numeric column or parameter. Example: 27 |
| CreateFormat | string | A format string that indicates how to add this column to a DDL statement. Example: <code>TIMESTAMP({0} WITH LOCAL TIME ZONE)</code> |
| CreateParameters | string | The parameters specified to create a column of this data type. Example: 8 |
| DataType | string | The .NET type for the data type. Example: <code>System.DateTime</code> |
| IsAutoIncrementable | bool | A boolean value that indicates whether or not this data type can be auto-incremented. Example: false |
| IsBestMatch | bool | A boolean value that indicates whether or not this data type is the best match to values in the <code>DataType</code> column. Example: false |
| IsCaseSensitive | bool | A boolean value that indicates whether or not this data type is case-sensitive. Example: false |
| IsFixedLength | bool | A boolean value that indicates whether or not this data type has a fixed length. Example: true |
| IsFixedPrecisionScale | bool | A boolean value that indicates whether or not this data type has a fixed precision and scale. Example: false |
| IsLong | bool | A boolean value that indicates whether or not this data type contains very long data. Example: false |

Table A-3 (Cont.) DataTypes

| ColumnName | Data Type | Description |
|----------------------|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IsNullable | bool | A boolean value that indicates whether or not this data type is nullable. Example: true |
| IsSearchable | bool | A boolean value that indicates whether or not the data type can be used in a WHERE clause with any operator, except the LIKE predicate. Example: true |
| IsSearchableWithLike | bool | A boolean value that indicates whether or not this data type can be used with the LIKE predicate. Example: false |
| IsUnsigned | bool | A boolean value that indicates whether or not the data type is unsigned. |
| MaximumScale | short | The maximum number of digits allowed to the right of the decimal point. |
| MinimumScale | short | The minimum number of digits allowed to the right of the decimal point. |
| IsConcurrencyType | bool | A boolean value that indicates whether or not the database updates the data type every time the row is changed and the value of the column differs from all previous values. Example: false |
| MinimumVersion | String | The earliest version of the database that can be used. Example: 09.00.00.00.00 |
| IsLiteralSupported | bool | A boolean value that indicates whether or not the data type can be expressed as a literal. Example: true |
| LiteralPrefix | string | The prefix of a specified literal. Example: TO_TIMESTAMP_TZ(|
| LiteralSuffix | string | The suffix of a specified literal. Example: ', 'YYYY-MM-DD HH24:MI:SS.FF') |

Restrictions

Table A-4 lists Restrictions, including the following columns.

Table A-4 Restrictions

| ColumnName | Data Type | Description |
|-------------------|-----------|----------------------------------------------------------|
| CollectionName | string | The collection that the restrictions apply to. |
| RestrictionName | string | The restriction name. |
| RestrictionNumber | int | A number that indicates the location of the restriction. |

ReservedWords

The `ReservedWords` collection exposes information about the words that are reserved by the database currently connected to ODP.NET.

[Table A-5](#) lists the `ReservedWords` Collection.

Table A-5 *ReservedWords*

| ColumnName | Data Type | Description |
|--------------|-----------|----------------------------------|
| ReservedWord | string | Provider-specific reserved words |

ODP.NET-Specific Schema Collection

Oracle Data Provider for .NET supports both the common schema collections described previously and the following Oracle-specific schema collections:

- [Tables](#)
- [Columns](#)
- [Views](#)
- [XMLSchema](#)
- [Users](#)
- [Synonyms](#)
- [Sequences](#)
- [Functions](#)
- [Procedures](#)
- [ProcedureParameters](#)
- [Arguments](#)
- [Packages](#)
- [PackageBodies](#)
- [JavaClasses](#)
- [Indexes](#)
- [IndexColumns](#)
- [PrimaryKeys](#)
- [ForeignKeys](#)
- [ForeignKeyColumns](#)
- [UniqueKeys](#)

Tables

[Table A-6](#) lists the column name, data type, and description of the `Tables` Schema Collection.

Table A-6 *Tables*

| Column Name | Data Type | Description |
|-------------|-----------|---------------------|
| OWNER | String | Owner of the Table. |

Table A-6 (Cont.) Tables

| Column Name | Data Type | Description |
|-------------|-----------|---------------------------------------------|
| TABLE_NAME | String | Name of the Table. |
| TYPE | String | Type of Table, for example, System or User. |

Columns

[Table A-7](#) lists the column name, data type, and description of the Columns Schema Collection .

Table A-7 Columns

| ColumnName | Data Type | Description |
|---------------|-----------|--------------------------------------------------------------------------------------------------------------|
| OWNER | String | Owner of the table or view. |
| TABLE_NAME | String | Name of the table or view. |
| COLUMN_NAME | String | Name of the column. |
| ID | Decimal | Sequence number of the column as created. |
| DATATYPE | String | Data type of the column. |
| LENGTH | Decimal | Length of the column in bytes. |
| PRECISION | Decimal | Decimal precision for NUMBER data type; binary precision for FLOAT data type, null for all other data types. |
| Scale | Decimal | Digits to right of decimal point in a number. |
| NULLABLE | String | Specifies whether or not a column allows NULLs. |
| CHAR_USED | String | Indicates whether the column uses BYTE length semantics (B) or CHAR length semantics (C). |
| LengthInChars | Decimal | Length of the column in characters. This value only applies to CHAR, VARCHAR2, NCHAR, and NVARCHAR2. |

Views

[Table A-8](#) lists the column name, data type, and description of the Views Schema Collection.

Table A-8 Views

| Column Name | Data Type | Description |
|------------------|-----------|-----------------------------------------------------|
| OWNER | String | Owner of the view. |
| VIEW_NAME | String | Name of the view. |
| TEXT_LENGTH | Decimal | Length of the view text. |
| TEXT | String | View text. |
| TYPE_TEXT_LENGTH | Decimal | Length of the type clause of the typed view. |
| TYPE_TEXT | String | Type clause of the typed view. |
| OID_TEXT_LENGTH | Decimal | Length of the WITH OID clause of the typed view. |
| OID_TEXT | String | WITH OID clause of the typed view. |
| VIEW_TYPE_OWNER | String | Owner of the view type if the view is a typed view. |

Table A–8 (Cont.) Views

| Column Name | Data Type | Description |
|----------------|-----------|-----------------------------------------------|
| VIEW_TYPE | String | Type of the view if the view is a typed view. |
| SUPERVIEW_NAME | String | Name of the superview. (Oracle9i or later) |

XMLSchema

[Table A–9](#) lists the column name, data type and description of the XMLSchema Schema Collection.

Note: This collection is only available with Oracle Database 10g and later.

Table A–9 XMLSchema

| Column Name | Data Type | Description |
|-----------------|-----------|-----------------------------------------------------------------|
| OWNER | String | Owner of the XML schema. |
| SCHEMA_URL | String | Schema URL of the XML schema. |
| LOCAL | String | Indicates whether the XML schema is local (YES) or global (NO). |
| SCHEMA | String | XML schema document. |
| INT_OBJNAME | String | Internal database object name for the schema. |
| QUAL_SCHEMA_URL | String | Fully qualified schema URL. |
| HIER_TYPE | String | Hierarchy type for the schema. |

Users

[Table A–10](#) lists the column name, data type and description of the Users Schema Collection.

Table A–10 Users

| Column Name | Data Type | Description |
|-------------|-----------|------------------------|
| NAME | String | Name of the user. |
| ID | Decimal | ID number of the user. |
| CREATEDATE | DateTime | User creation date. |

Synonyms

[Table A–11](#) lists the column name, data type and description of the Synonyms Schema Collection.

Table A–11 Synonyms

| Column Name | Data Type | Description |
|--------------|-----------|-----------------------|
| OWNER | String | Owner of the synonym. |
| SYNONYM_NAME | String | Name of the synonym. |

Table A–11 (Cont.) Synonyms

| Column Name | Data Type | Description |
|-------------|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TABLE_OWNER | String | Owner of the object referenced by the synonym. Although the column is called TABLE_OWNER, the object owned is not necessarily a table. It can be any general object such as a view, sequence, stored procedure, synonym, and so on. |
| TABLE_NAME | String | Name of the object referenced by the synonym. Although the column is called TABLE_NAME, the object does not necessarily have to be a table. It can be any general object such as a view, sequence, stored procedure, synonym, and so on. |
| DB_LINK | String | Name of the database link referenced, if any. |

Sequences

Table A–12 lists the column name, data type, and description of the Sequences Schema Collection.

Table A–12 Sequences

| Column Name | Data Type | Description |
|----------------|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SEQUENCE_OWNER | String | Name of the owner of the sequence. |
| SEQUENCE_NAME | String | Sequence name. |
| MIN_VALUE | Decimal | Minimum value of the sequence. |
| MAX_VALUE | Decimal | Maximum value of the sequence. |
| INCREMENT_BY | Decimal | Value by which sequence is incremented. |
| CYCLE_FLAG | String | Indicates if sequence wraps around on reaching limit. |
| ORDER_FLAG | String | Indicates if sequence numbers are generated in order. |
| CACHE_SIZE | Decimal | Number of sequence numbers to cache. |
| LAST_NUMBER | Decimal | Last sequence number written to disk. If a sequence uses caching, the number written to disk is the last number placed in the sequence cache. This number is likely to be greater than the last sequence number that was used. |

Functions

Table A–13 lists the column name, data type, and description of the Functions Schema Collection.

Table A–13 Functions

| Column Name | Data Type | Description |
|----------------|-----------|-------------------------------------------------|
| OWNER | String | Owner of the function. |
| OBJECT_NAME | String | Name of the function. |
| SUBOBJECT_NAME | String | Name of the subobject (for example, partition). |
| OBJECT_ID | Decimal | Dictionary object number of the function. |

Table A-13 (Cont.) Functions

| Column Name | Data Type | Description |
|----------------|-----------|------------------------------------------------------------------------------------------------------------------------------------|
| DATA_OBJECT_ID | Decimal | Dictionary object number of the segment that contains the function. |
| CREATED | DateTime | Timestamp for the creation of the function. |
| LAST_DDL_TIME | DateTime | Timestamp for the last modification of the function resulting from a DDL statement (including grants and revokes). |
| TIMESTAMP | String | Timestamp for the specification of the function (character data). |
| STATUS | String | Status of the function (VALID, INVALID, or N/A). |
| TEMPORARY | String | Whether or not the function is temporary (the current session can see only data that it placed in this object itself). |
| GENERATED | String | Indicates whether the name of this function is system generated (Y) or not (N). |
| SECONDARY | String | Whether or not this is a secondary object created by the <code>ODCIIndexCreate</code> method of the Oracle Data Cartridge (Y N). |

Procedures

Table A-14 lists the column name, data type, and description of the Procedures Schema Collection.

Table A-14 Procedures

| Column Name | Data Type | Description |
|----------------|-----------|------------------------------------------------------------------------------------------------------------------------------------|
| OWNER | String | Owner of the procedure. |
| OBJECT_NAME | String | Name of the procedure. |
| SUBOBJECT_NAME | String | Name of the subobject (for example, partition). |
| OBJECT_ID | Decimal | Dictionary object number of the procedure. |
| DATA_OBJECT_ID | Decimal | Dictionary object number of the segment that contains the procedure. |
| CREATED | DateTime | Timestamp for the creation of the procedure. |
| LAST_DDL_TIME | Decimal | Timestamp for the last modification of the procedure resulting from a DDL statement (including grants and revokes). |
| TIMESTAMP | String | Timestamp for the specification of the procedure (character data). |
| STATUS | String | Status of the procedure (VALID, INVALID, or N/A). |
| TEMPORARY | String | Whether or not the procedure is temporary (the current session can see only data that it placed in this object itself). |
| GENERATED | String | Indicates whether the name of this procedure is system generated (Y) or not (N). |
| SECONDARY | String | Whether or not this is a secondary object created by the <code>ODCIIndexCreate</code> method of the Oracle Data Cartridge (Y N). |

ProcedureParameters

[Table A–15](#) lists the column name, data type and description of the ProcedureParameters Schema Collection.

Table A–15 ProcedureParameters

| Column Name | Data Type | Description |
|--------------------|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OWNER | String | Owner of the object. |
| OBJECT_NAME | String | Name of the procedure or function. |
| PACKAGE_NAME | String | Name of the package. |
| OBJECT_ID | Decimal | Object number of the object. |
| OVERLOAD | String | Indicates the <i>n</i> th overloading ordered by its appearance in the source; otherwise, it is NULL. |
| SUBPROGRAM_ID | Decimal | Subprogram id for the procedure or function |
| ARGUMENT_NAME | String | If the argument is a scalar type, then the argument name is the name of the argument. A null argument name is used to denote a function return value. |
| POSITION | Decimal | If DATA_LEVEL is zero, then this column holds the position of this item in the argument list, or zero for a function return value. |
| SEQUENCE | Decimal | Defines the sequential order of the argument. Argument sequence starts from 1. |
| DATA_LEVEL | Decimal | Nesting depth of the argument for composite types. |
| DATA_TYPE | String | Data type of the argument. |
| DEFAULT_VALUE | String | Default value for the argument. |
| DEFAULT_LENGTH | Decimal | Length of the default value for the argument. |
| IN_OUT | String | Direction of the argument: [IN] [OUT] [IN/OUT]. |
| DATA_LENGTH | Decimal | Length of the column (in bytes). |
| DATA_PRECISION | Decimal | Length in decimal digits (NUMBER) or binary digits (FLOAT). |
| DATA_SCALE | Decimal | Digits to the right of the decimal point in a number. |
| RADIX | Decimal | Argument radix for a number. |
| CHARACTER_SET_NAME | String | Character set name for the argument. |
| TYPE_OWNER | String | Owner of the type of the argument. |
| TYPE_NAME | String | Name of the type of the argument. If the type is a package local type (that is, it is declared in a package specification), then this column displays the name of the package. |
| TYPE_SUBNAME | String | Displays the name of the type declared in the package identified in the TYPE_NAME column. Relevant only for package local types. |
| TYPE_LINK | String | Displays the database link that refers to the remote package. Relevant only for package local types when the package identified in the TYPE_NAME column is a remote package. |

Table A–15 (Cont.) ProcedureParameters

| Column Name | Data Type | Description |
|-------------|-----------|-----------------------------------------------------------------------------------------|
| PLS_TYPE | String | For numeric arguments, the name of the PL/SQL type of the argument. Otherwise, Null. |
| CHAR_LENGTH | Decimal | Character limit for string data types. |
| CHAR_USED | String | Indicates whether the byte limit (B) or character limit (C) is official for the string. |

Arguments

Table A–16 lists the column name, data type, and description of the Arguments Schema Collection.

Table A–16 Arguments

| Column Name | Data Type | Description |
|----------------|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| OWNER | String | Owner of the object. |
| PACKAGE_NAME | String | Name of the package. |
| OBJECT_NAME | String | Name of the procedure or function. |
| ARGUMENT_NAME | String | If the argument is a scalar type, then the argument name is the name of the argument. A null argument name is used to denote a function return value. |
| POSITION | Decimal | If DATA_LEVEL is zero, then this column holds the position of this item in the argument list, or zero for a function return value. |
| SEQUENCE | Decimal | Defines the sequential order of the argument. Argument sequence starts from 1. |
| DEFAULT_VALUE | String | Default value for the argument. |
| DEFAULT_LENGTH | Decimal | Length of the default value for the argument. |
| IN_OUT | String | Direction of the argument: [IN] [OUT] [IN/OUT]. |
| DATA_LENGTH | Decimal | Length of the column (in bytes). |
| DATA_PRECISION | Decimal | Length in decimal digits (NUMBER) or binary digits (FLOAT). |
| DATA_SCALE | Decimal | Digits to the right of the decimal point in a number. |
| DATA_TYPE | String | Data type of the argument. |
| CHAR_USED | String | Indicates whether the column uses BYTE length semantics (B) or CHAR length semantics (C). |

Packages

Table A–17 lists the column name, data type, and description of the Packages Schema Collection.

Table A–17 Packages

| Column Name | Data Type | Description |
|----------------|-----------|-------------------------------------------------|
| OWNER | String | Owner of the package. |
| OBJECT_NAME | String | Name of the package. |
| SUBOBJECT_NAME | String | Name of the subobject (for example, partition). |

Table A–17 (Cont.) Packages

| Column Name | Data Type | Description |
|----------------|-----------|------------------------------------------------------------------------------------------------------------------------------------|
| OBJECT_ID | Decimal | Dictionary object number of the package. |
| DATA_OBJECT_ID | Decimal | Dictionary object number of the segment that contains the package. |
| CREATED | DateTime | Timestamp for the creation of the package. |
| LAST_DDL_TIME | DateTime | Timestamp for the last modification of the package resulting from a DDL statement (including grants and revokes). |
| TIMESTAMP | String | Timestamp for the specification of the package (character data). |
| STATUS | String | Status of the package (VALID, INVALID, or N/A). |
| TEMPORARY | String | Whether or not the package is temporary (the current session can see only data that it placed in this object itself). |
| GENERATED | String | Indicates whether the name of this package was system generated (Y) or not (N). |
| SECONDARY | String | Whether or not this is a secondary object created by the <code>ODCIIndexCreate</code> method of the Oracle Data Cartridge (Y N). |

PackageBodies

[Table A–18](#) lists the column name, data type, and description of the PackageBodies Schema Collection.

Table A–18 PackageBodies

| Column Name | Data Type | Description |
|----------------|-----------|------------------------------------------------------------------------------------------------------------------------|
| OWNER | String | Owner of the package body. |
| OBJECT_NAME | String | Name of the package body. |
| SUBOBJECT_NAME | String | Name of the subobject (for example, partition). |
| OBJECT_ID | Decimal | Dictionary object number of the package body. |
| DATA_OBJECT_ID | Decimal | Dictionary object number of the segment that contains the package body. |
| CREATED | DateTime | Timestamp for the creation of the package body. |
| LAST_DDL_TIME | DateTime | Timestamp for the last modification of the package body resulting from a DDL statement (including grants and revokes). |
| TIMESTAMP | String | Timestamp for the specification of the package body (character data). |
| STATUS | String | Status of the package body (VALID, INVALID, or N/A). |
| TEMPORARY | String | Whether the package body is temporary (the current session can see only data that it placed in this object itself). |
| GENERATED | String | Indicates whether the name of this package body is system generated (Y) or not (N). |

Table A–18 (Cont.) PackageBodies

| Column Name | Data Type | Description |
|-------------|-----------|------------------------------------------------------------------------------------------------------------------------------------|
| SECONDARY | String | Whether or not this is a secondary object created by the <code>ODCIIndexCreate</code> method of the Oracle Data Cartridge (Y N). |

JavaClasses

[Table A–19](#) lists the column name, data type, and description of the JavaClasses Schema Collection.

Table A–19 JavaClasses

| Column Name | Data Type | Description |
|---------------|-----------|----------------------------------------------------------------------------------------------|
| OWNER | String | Owner of the Java class. |
| NAME | String | Name of the Java class. |
| MAJOR | Decimal | Major version number of the Java class, as defined in the JVM specification. |
| MINOR | Decimal | Minor version number of the Java class, as defined in the JVM specification. |
| KIND | String | Indicates whether the stored object is a Java class (CLASS) or a Java interface (INTERFACE). |
| ACCESSIBILITY | String | Accessibility of the Java class. |
| IS_INNER | String | Indicates whether this Java class is an inner class (YES) or not (NO). |
| IS_ABSTRACT | String | Indicates whether this Java class is an abstract class (YES) or not (NO). |
| IS_FINAL | String | Indicates whether this Java class is a final class (YES) or not (NO). |
| IS_DEBUG | String | Indicates whether this Java class contains debug information (YES) or not (NO). |
| SOURCE | String | Source designation of the Java class. |
| SUPER | String | Super class of this Java class. |
| OUTER | String | Outer class of this Java class if this Java class is an inner class. |

Indexes

[Table A–20](#) lists the column name, data type, and description of the Indexes Schema Collection.

Table A–20 Indexes

| Column Name | Data Type | Description |
|-------------|-----------|---------------------|
| OWNER | String | Owner of the index. |
| INDEX_NAME | String | Name of the index. |

Table A–20 (Cont.) Indexes

| Column Name | Data Type | Description |
|-----------------|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| INDEX_TYPE | String | Type of the index: <ul style="list-style-type: none"> ■ NORMAL ■ BITMAP ■ FUNCTION-BASED NORMAL ■ FUNCTION-BASED BITMAP ■ DOMAIN |
| TABLE_OWNER | String | Owner of the indexed object. |
| TABLE_NAME | String | Name of the indexed object. |
| TABLE_TYPE | String | Type of the indexed object (for example, TABLE or CLUSTER). |
| UNIQUENESS | String | Indicates whether the index is UNIQUE or NONUNIQUE. |
| COMPRESSION | String | Indicates whether index compression is enabled (ENABLED) or not (DISABLED). |
| PREFIX_LENGTH | Decimal | Number of columns in the prefix of the compression key. |
| TABLESPACE_NAME | String | Name of the tablespace containing the index. |
| INI_TRANS | Decimal | Initial number of transactions. |
| MAX_TRANS | Decimal | Maximum number of transactions. |
| INITIAL_EXTENT | Decimal | Size of the initial extent. |
| NEXT_EXTENT | Decimal | Size of secondary extents. |
| MIN_EXTENTS | Decimal | Minimum number of extents allowed in the segment. |
| MAX_EXTENTS | Decimal | Maximum number of extents allowed in the segment. |
| PCT_INCREASE | Decimal | Percentage increase in extent size. |
| PCT_THRESHOLD | Decimal | Threshold percentage of block space allowed per index entry. |
| INCLUDE_COLUMN | Decimal | Column ID of the last column to be included in index-organized table primary key (non-overflow) index. This column maps to the COLUMN_ID column of the *_TAB_COLUMNS data dictionary views. |
| FREELISTS | Decimal | Number of process freelists allocated to this segment. |
| FREELIST_GROUPS | Decimal | Number of freelist groups allocated to this segment. |
| PCT_FREE | Decimal | Minimum percentage of free space in a block. |
| LOGGING | String | Logging information. |
| BLEVEL | Decimal | B*-Tree level: depth of the index from its root block to its leaf blocks. A depth of 0 indicates that the root block and leaf block are the same. |
| LEAF_BLOCKS | Decimal | Number of leaf blocks in the index. |
| DISTINCT_KEYS | Decimal | Number of distinct indexed values. For indexes that enforce UNIQUE and PRIMARY KEY constraints, this value is the same as the number of rows in the table (USER_TABLES.NUM_ROWS). |

Table A-20 (Cont.) Indexes

| Column Name | Data Type | Description |
|-----------------------------|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AVG_LEAF_BLOCKS_ PER_KEY | Decimal | Average number of leaf blocks in which each distinct value in the index appears, rounded to the nearest integer. For indexes that enforce UNIQUE and PRIMARY KEY constraints, this value is always 1. |
| AVG_DATA_BLOCKS_ PER_KEY | Decimal | Average number of data blocks in the table that are pointed to by a distinct value in the index, rounded to the nearest integer. This statistic is the average number of data blocks that contain rows that contain a given value for the indexed columns. |
| CLUSTERING_FACTOR | Decimal | Indicates the amount of order of the rows in the table based on the values of the index. |
| STATUS | String | Indicates whether a nonpartitioned index is VALID or UNUSABLE. |
| NUM_ROWS | Decimal | Number of rows in the index. |
| SAMPLE_SIZE | Decimal | Size of the sample used to analyze the index. |
| LAST_ANALYZED | Date | Date on which this index was most recently analyzed. |
| DEGREE | String | Number of threads per instance for scanning the index. |
| INSTANCES | String | Number of instances across which the indexes to be scanned. |
| PARTITIONED | String | Indicates whether the index is partitioned (YES) or not (NO). |
| TEMPORARY | String | Indicates whether or not the index is on a temporary table. |
| GENERATED | String | Indicates whether the name of the index is system generated (Y) or not (N). |
| SECONDARY | String | Indicates whether the index is a secondary object created by the ODCIIndexCreate method of the Oracle Data Cartridge (Y) or not (N). |
| BUFFER_POOL | String | Name of the default buffer pool to be used for the index blocks. |
| USER_STATS | String | Indicates whether statistics were entered directly by the user (YES) or not (NO). |
| DURATION | String | Indicates the duration of a temporary table. |
| PCT_DIRECT_ACCESS | Decimal | For a secondary index on an index-organized table, the percentage of rows with VALID guess. |
| ITYP_OWNER | String | For a domain index, the owner of the index type. |
| ITYP_NAME | String | For a domain index, the name of the index type. |
| PARAMETERS | String | For a domain index, the parameter string. |
| GLOBAL_STATS | String | For partitioned indexes, indicates whether statistics are collected by analyzing the index as a whole (YES) or estimated from statistics on underlying index partitions and subpartitions (NO). |

Table A–20 (Cont.) Indexes

| Column Name | Data Type | Description |
|-------------------------|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DOMIDX_STATUS | String | Status of the domain index: <ul style="list-style-type: none"> ■ NULL - Index is not a domain index. ■ VALID - Index is a valid domain index. ■ IDX_TYP_INVLD - Index type of the domain index is invalid. |
| DOMIDX_OPSTATUS | String | Status of the operation on the domain index: <ul style="list-style-type: none"> ■ NULL - Index is not a domain index. ■ VALID - Operation performed without errors. ■ FAILED - Operation failed with an error. |
| FUNCIDX_STATUS | String | Status of a function-based index: <ul style="list-style-type: none"> ■ NULL - Index is not a function-based index. ■ ENABLED - Function-based index is enabled. ■ DISABLED - Function-based index is disabled. |
| JOIN_INDEX | String | Indicates whether the index is a join index (YES) or not (NO). |
| IOT_REDUNDANT_PKEY_ELIM | String | Indicates whether redundant primary key columns are eliminated from secondary indexes on index-organized tables (YES) or not (NO). |
| DROPPED | String | Indicates whether the index has been dropped and is in the recycle bin (YES) or not (NO); null for partitioned tables. |

IndexColumns

[Table A–21](#) lists the column name, data type, and description of the IndexColumns Schema Collection.

Table A–21 IndexColumns

| Column Name | Data Type | Description |
|-----------------|-----------|-------------------------------------------------------------|
| INDEX_OWNER | String | Owner of the index. |
| INDEX_NAME | String | Name of the index. |
| TABLE_OWNER | String | Owner of the table or cluster. |
| TABLE_NAME | String | Name of the table or cluster. |
| COLUMN_NAME | String | Column name or attribute of object type column. |
| COLUMN_POSITION | Decimal | Position of column or attribute within the index. |
| COLUMN_LENGTH | Decimal | Indexed length of the column. |
| DESCEND | String | Whether the column is sorted in descending order (Y/N). |
| CHAR_LENGTH | Decimal | Maximum codepoint length of the column. (Oracle9i or later) |

PrimaryKeys

[Table A–22](#) lists the column name, data type, and description of the PrimaryKeys Schema Collection.

Table A-22 PrimaryKeys

| Column Name | Data Type | Description |
|-------------------|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OWNER | String | Owner of the constraint definition. |
| CONSTRAINT_NAME | String | Name of the constraint definition. |
| TABLE_NAME | String | Name associated with the table (or view) with constraint definition. |
| SEARCH_CONDITION | String | Text of search condition for a check constraint. |
| R_OWNER | String | Owner of table referred to in a referential constraint. |
| R_CONSTRAINT_NAME | String | Name of the unique constraint definition for referenced table. |
| DELETE_RULE | String | Delete rule for a referential constraint (CASCADE or NO ACTION). |
| STATUS | String | Enforcement status of constraint (ENABLED or DISABLED). |
| DEFERRABLE | String | Whether or not the constraint is deferrable. |
| VALIDATED | String | Whether all data obeys the constraint (VALIDATED or NOT VALIDATED). |
| GENERATED | String | Whether the name of the constraint is user or system generated. |
| BAD | String | Indicates that this constraint specifies a century in an ambiguous manner. (Yes No) To avoid errors resulting from this ambiguity, rewrite the constraint using the TO_DATE function with a four-digit year. |
| RELY | String | Whether an enabled constraint is enforced or unenforced. |
| LAST_CHANGE | DateTime | When the constraint was last enabled or disabled. |
| INDEX_OWNER | String | Name of the user owning the index. (Oracle9i or later) |
| INDEX_NAME | String | Name of the index (only shown for unique and primary-key constraints). (Oracle9i or later) |

ForeignKeys

Table A-23 lists the column name, data type, and description of the ForeignKeys Schema Collection.

Table A-23 ForeignKeys

| Column Name | Data Type | Description |
|-----------------------------|-----------|----------------------------------------------------------------------|
| PRIMARY_KEY_CONSTRAINT_NAME | String | Name of the constraint definition. |
| PRIMARY_KEY_OWNER | String | Owner of the constraint definition. |
| PRIMARY_KEY_TABLE_NAME | String | Name associated with the table (or view) with constraint definition. |
| FOREIGN_KEY_OWNER | String | Owner of the constraint definition. |

Table A-23 (Cont.) ForeignKeys

| Column Name | Data Type | Description |
|-----------------------------|-----------|----------------------------------------------------------------------------|
| FOREIGN_KEY_CONSTRAINT_NAME | String | Name of the constraint definition. |
| FOREIGN_KEY_TABLE_NAME | String | Name associated with the table (or view) with constraint definition. |
| SEARCH_CONDITION | String | Text of search condition for a check constraint |
| R_OWNER | String | Owner of table referred to, in a referential constraint. |
| R_CONSTRAINT_NAME | String | Name of the unique constraint definition for referenced table. |
| DELETE_RULE | String | Delete rule for a referential constraint (CASCADE or NO ACTION). |
| STATUS | String | Enforcement status of constraint (ENABLED or DISABLED). |
| VALIDATED | String | Whether or not all data obeys the constraint (VALIDATED or NOT VALIDATED). |
| GENERATED | String | Whether the name of the constraint is user or system generated. |
| RELY | String | Whether an enabled constraint is enforced or unenforced. |
| LAST_CHANGE | DateTime | When the constraint was last enabled or disabled. |
| INDEX_OWNER | String | Name of the user owning the index. (Oracle9i or later) |
| INDEX_NAME | String | Name of the index. (Oracle9i or later) |

ForeignKeyColumns

[Table A-24](#) lists the column name, data type, and description of the ForeignKeyColumns Schema Collection.

Table A-24 ForeignKeyColumns

| Column Name | Data Type | Description |
|-----------------|-----------|---------------------------------------------------------------------------------------------------|
| OWNER | String | Owner of the constraint definition. |
| CONSTRAINT_NAME | String | Name of the constraint definition. |
| TABLE_NAME | String | Name of the table with constraint definition. |
| COLUMN_NAME | String | Name of the column or attribute of the object type column specified in the constraint definition. |
| POSITION | String | Original position of column or attribute in the definition of the object. |

UniqueKeys

[Table A-25](#) lists the column name, data type, and description of the UniqueKeys Schema Collection.

Table A-25 UniqueKeys

| Column Name | Data Type | Description |
|-------------------|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OWNER | String | Owner of the constraint definition. |
| CONSTRAINT_NAME | String | Name of the constraint definition. |
| TABLE_NAME | String | Name associated with the table (or view) with constraint definition. |
| SEARCH_CONDITION | String | Text of search condition for a check constraint. |
| R_OWNER | String | Owner of table referred to in a referential constraint. |
| R_CONSTRAINT_NAME | String | Name of the unique constraint definition for referenced table. |
| DELETE_RULE | String | Delete rule for a referential constraint (CASCADE or NO ACTION). |
| STATUS | String | Enforcement status of constraint (ENABLED or DISABLED). |
| DEFERRABLE | String | Whether or not the constraint is deferrable. |
| VALIDATED | String | Whether all data obeys the constraint (VALIDATED or NOT VALIDATED). |
| GENERATED | String | Whether the name of the constraint is user or system generated. |
| BAD | String | Indicates that this constraint specifies a century in an ambiguous manner. (Yes No) To avoid errors resulting from this ambiguity, rewrite the constraint using the TO_DATE function with a four-digit year. |
| RELY | String | Whether an enabled constraint is enforced or not. |
| LAST_CHANGE | String | When the constraint was last enabled or disabled. |
| INDEX_OWNER | String | Name of the user owning the index. (Oracle9i or later) |
| INDEX_NAME | String | Name of the index (only shown for unique and primary-key constraints). (Oracle9i or later) |

Mapping LINQ Canonical Functions and Oracle Functions

This appendix lists the Entity Framework canonical functions and the corresponding ODP.NET provider functions to which they map.

Aggregate Canonical Functions

| Canonical Function | Oracle Function |
|--------------------------------|------------------------------|
| <i>Avg (expression)</i> | <i>AVG (expression)</i> |
| <i>BigCount (expression)</i> | <i>COUNT (expression)</i> |
| <i>Count (expression)</i> | <i>COUNT (expression)</i> |
| <i>Max (expression)</i> | <i>MAX (expression)</i> |
| <i>Min (expression)</i> | <i>MIN (expression)</i> |
| <i>StDev (expression)</i> | <i>STDDEV (expression)</i> |
| <i>StDevP (expression)</i> | <i>STDEV (expression)</i> |
| <i>Sum (expression)</i> | <i>SUM (expression)</i> |
| <i>Var (expression)</i> | <i>VAR (expression)</i> |
| <i>VarP (expression)</i> | <i>VARP (expression)</i> |

Math Canonical Functions

| Canonical Function | Oracle Function |
|------------------------------------|-----------------------------------|
| <i>Abs (value)</i> | <i>ABS (value)</i> |
| <i>Ceiling (value)</i> | <i>CEIL (value)</i> |
| <i>Floor (value)</i> | <i>FLOOR (value)</i> |
| <i>Power (value , exponent)</i> | <i>POWER (value , exponent)</i> |
| <i>Round (value)</i> | <i>ROUND (value)</i> |
| <i>Round (value , digits)</i> | <i>ROUND (value , digits)</i> |
| <i>Truncate (value , digits)</i> | <i>TRUNC (value , digits)</i> |

String Canonical Functions

| Canonical Function | Oracle Function |
|-------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| Concat (<i>string1</i> , <i>string2</i>) | CONCAT(<i>string1</i> , <i>string2</i>) or (<i>string1</i> <i>string2</i>) |
| Contains(<i>string</i> , <i>target</i>) | INSTR(<i>string</i> , <i>target</i>) |
| EndsWith(<i>string</i> , <i>target</i>) | INSTR(REVERSE(<i>string</i>), REVERSE(<i>target</i>)) |
| Comparison operators (<i><</i> , <i><=</i> , <i>></i> , <i>>=</i> , <i><></i> , <i>!=</i>) | Comparison operators (<i><</i> , <i><=</i> , <i>></i> , <i>>=</i> , <i><></i> , <i>!=</i>) |
| IndexOf(<i>target</i> , <i>string</i>) | INSTR(<i>string2</i> , <i>target</i>) |
| Left (<i>string1</i> , <i>length</i>) | SUBSTR(<i>string1</i> , <i>length</i>) |
| Length (<i>string</i>) | LENGTH(<i>string</i>) |
| LTrim(<i>string</i>) | LTRIM(<i>string</i>) |
| Replace (<i>string1</i> , <i>string2</i> , <i>string3</i>) | REPLACE(<i>string1</i> , <i>string2</i> , <i>string3</i>) |
| Reverse (<i>string</i>) | REVERSE(string) |
| Right (<i>string</i> , <i>length</i>) | (CASE WHEN LENGTH(<i>string</i>) >= (<i>length</i>) THEN SUBSTR(<i>string</i>) ,-(<i>length</i>), <i>length</i>) ELSE <i>string</i> END) |
| RTrim(<i>string</i>) | RTRIM(<i>string</i>) |
| Substring (<i>string</i> , <i>start</i> , <i>length</i>) | SUBSTR((<i>string</i> , <i>start</i> , <i>length</i>) |
| StartsWith(<i>string</i> , <i>target</i>) | INSTR(<i>string</i> , <i>target</i>) |
| ToLower (<i>string</i>) | LOWER(<i>string</i>) |
| ToUpper(<i>string</i>) | UPPER |
| Trim (<i>string</i>) | LTRIM(RTRIM(<i>string</i>)) |

Date And Time Canonical Functions

| Canonical Function | Oracle Function |
|---------------------------------------------------------|----------------------------------|
| AddNanoseconds(<i>expression</i> , <i>number</i>) | (<i>expression</i>) + INTERVAL |
| AddMicroseconds(<i>expression</i> , <i>number</i>) | (<i>expression</i>) + INTERVAL |
| AddMilliseconds(<i>expression</i> , <i>number</i>) | (<i>expression</i>) + INTERVAL |
| AddSeconds(<i>expression</i> , <i>number</i>) | (<i>expression</i>) + INTERVAL |
| AddMinutes(<i>expression</i> , <i>number</i>) | (<i>expression</i>) + INTERVAL |
| AddHours(<i>expression</i> , <i>number</i>) | (<i>expression</i>) + INTERVAL |
| AddDays(<i>expression</i> , <i>number</i>) | (<i>expression</i>) + INTERVAL |
| AddMonths(<i>expression</i> , <i>number</i>) | (<i>expression</i>) + INTERVAL |
| AddYears(<i>expression</i> , <i>number</i>) | (<i>expression</i>) + INTERVAL |

| Canonical Function | Oracle Function |
|---------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| CreateDateTime(<i>year, month, day, hour, minute, second</i>) | TO_TIMESTAMP |
| CreateDateTimeOffset(<i>year, month, day, hour, minute, second, tzoffset</i>) | TO_TIMESTAMP_TZ |
| CreateTime(<i>hour, minute, second</i>) | Time literals are not supported in Oracle |
| CurrentDateTime() | LOCALTIMESTAMP |
| CurrentDateTimeOffset() | SYSTIMESTAMP |
| CurrentUtcDateTime() | SYS_EXTRACT_UTC (LOCALTIMESTAMP) |
| Day(<i>expression</i>) | EXTRACT(DAY FROM <i>expression</i>) |
| DayOfYear(<i>expression</i>) | TO_NUMBER(TO_CHAR(CAST(<i>expression</i> AS TIMESTAMP), 'DDD')) |
| DiffNanoseconds(<i>startExpression, endExpression</i>) | EXTRACT and arithmetic operations |
| DiffMilliseconds(<i>startExpression, endExpression</i>) | EXTRACT and arithmetic operations |
| DiffMicroseconds(<i>startExpression, endExpression</i>) | EXTRACT and arithmetic operations |
| DiffSeconds(<i>startExpression, endExpression</i>) | EXTRACT and arithmetic operations |
| DiffMinutes(<i>startExpression, endExpression</i>) | EXTRACT and arithmetic operations |
| DiffHours(<i>startExpression, endExpression</i>) | EXTRACT and arithmetic operations |
| DiffDays(<i>startExpression, endExpression</i>) | EXTRACT and arithmetic operations |
| DiffMonths(<i>startExpression, endExpression</i>) | EXTRACT and arithmetic operations |
| DiffYears(<i>startExpression, endExpression</i>) | EXTRACT and arithmetic operations |
|) | |
| Comparison operators | <, <=, >, >=, <>, != operators |
| (<, <=, >, >=, <>, !=) | |
| GetTotalOffsetMinutes(<i>datetimeoffset</i>) | (EXTRACT(TIMEZONE_HOUR FROM (<i>expression</i>))) * 60 + EXTRACT(TIMEZONE_MINUTE FROM(<i>expression</i>)) (Require multiple operations.) |
| Hour(<i>expression</i>) | EXTRACT(HOUR FROM <i>expression</i>) |
| Millisecond(<i>expression</i>) | NVL(TO_NUMBER(SUBSTR(TO_CHAR(CAST(<i>expression</i> AS TIMESTAMP), 'DD- MON-RR HH24:MI:SSXFF'), 20, 3)), 0) |
| Minute(<i>expression</i>) | EXTRACT(MINUTE FROM <i>expression</i>) |
| Month(<i>expression</i>) | EXTRACT(MONTH FROM <i>expression</i>) |
| Second(<i>expression</i>) | EXTRACT(SECOND FROM <i>expression</i>) |

| Canonical Function | Oracle Function |
|-----------------------------------|---------------------------------------|
| TruncateDate(<i>expression</i>) | TRUNC(<i>expression</i>) |
| Year(<i>expression</i>) | EXTRACT(YEAR FROM <i>expression</i>) |

Bitwise Canonical Functions

| Canonical Function | Oracle Function |
|----------------------------------------------|----------------------------------------------------------------------|
| BitWiseAnd (<i>value1</i> , <i>value2</i>) | BITAND(<i>value1</i> , <i>value2</i>) |
| BitWiseNot (<i>value</i>) | (0 - <i>value</i>) - 1 |
| BitWiseOr (<i>value1</i> , <i>value2</i>) | Value1 - BITAND(<i>value1</i> , <i>value2</i>) + <i>value2</i> |
| BitWiseXor (<i>value1</i> , <i>value2</i>) | Value1 - 2 * BITAND(<i>value1</i> , <i>value2</i>) + <i>value2</i> |

Other Canonical Functions

| Canonical Function | Oracle Function |
|---------------------------|------------------------|
| NewGuid() | SYS_GUID |

Glossary

assembly

Assembly is Microsoft's term for the module that is created when a DLL or .EXE is compiled by a .NET compiler.

BFILES

External binary files that exist outside the database tablespaces residing in the operating system. BFILES are referenced from the database semantics, and are also known as external LOBs.

Binary Large Object (BLOB)

A large object data type whose content consists of binary data. Additionally, this data is considered raw as its structure is not recognized by the database.

Character Large Object (CLOB)

The LOB data type whose value is composed of character data corresponding to the database character set. A CLOB may be indexed and searched by the Oracle Text search engine.

data provider

As the term is used with Oracle Data Provider for .NET, a data provider is the connected component in the ADO.NET model and transfers data between a data source and the DataSet.

DataSet

A DataSet is an in-memory copy of database data. The DataSet exists in memory without an active connection to the database.

dirty writes

Dirty writes means writing uncommitted or dirty data.

DDL

DDL refers to data definition language, which includes statements defining or changing data structure.

DOM

Document Object Model (DOM) is an application program interface (API) for HTML and XML documents. It defines the logical structure of documents and the way that a document is accessed and manipulated.

Extensible Stylesheet Language Transformation (XSLT)

The XSL W3C standard specification that defines a transformation language to convert one XML document into another.

flush

Flush or flushing refers to recording changes (that is, sending modified data) to the database.

Global Assembly Cache (GAC)

A cache for .NET assemblies.

goodness

The degree of load in the Oracle database. The lighter load is better and vice versa.

implicit database connection

The connection that is implicitly available from the context of the .NET stored procedure execution.

instantiate

A term used in object-based languages such as C# to refer to the creation of an object of a specific class.

invalidation message

The content of a change notification which indicates that the cache is now invalid

Large Object (LOB)

The class of SQL data type that is further divided into internal LOBs and external LOBs. Internal LOBs include BLOBs, CLOBs, and NLOBs while external LOBs include BFILES.

Microsoft .NET Framework Class Library

The Microsoft .NET Framework Class Library provides the classes for the .NET framework model.

namespace

- .NET:
A namespace is naming device for grouping related types. More than one namespace can be contained in an assembly.
- XML Documents:
A namespace describes a set of related element names or attributes within an XML document.

National Character Large Object (NCLOB)

The LOB data type whose value is composed of character data corresponding to the database national character set.

Oracle Net Services

The Oracle client/server communication software that offers transparent operation to Oracle tools or databases over any type of network protocol and operating system.

OracleDataReader

An `OracleDataReader` is a read-only, forward-only result set.

Oracle XML DB

Oracle XML DB is the name for a distinct group of technologies related to high-performance XML storage and retrieval that are available within the Oracle database. Oracle XML DB is not a separate server.

Oracle XML DB is based on the W3C XML data model.

PL/SQL

The Oracle procedural language extension to SQL.

primary key

The column or set of columns included in the definition of a table's PRIMARY KEY constraint.

reference semantics

Reference semantics indicates that assignment is to a reference (an address such as a pointer) rather than to a value. See [value semantics](#).

REF

A data type that encapsulates references to row objects of a specified object type.

result set

The output of a SQL query, consisting of one or more rows of data.

Safe Type Mapping

Safe Type Mapping allows the `OracleDataAdapter` to populate a `DataSet` with .NET type representations of Oracle data without any data or precision loss.

savepoint

A point in the workspace to which operations can be rolled back.

stored procedure

A stored procedure is a PL/SQL block that Oracle stores in the database and can be executed from an application.

Transparent Application Failover (TAF)

Transparent Application Failover is a runtime failover for high-availability environments. It enables client applications to automatically reconnect to the database if the connection fails. This reconnect happens automatically from within the Oracle Call Interface (OCI) library.

Unicode

Unicode is a universal encoded character set that enables information from any language to be stored using a single character set.

URL

URL (Universal Resource Locator).

value semantics

Value semantics indicates that assignment copies the value, not the reference or address (such as a pointer). See [reference semantics](#).

XPath

XML Path Language (XPath), based on a W3C recommendation, is a language for addressing parts of an XML document. It is designed to be used by both XSLT and XPointer. It can be used as a searching or query language as well as in hypertext linking.

A

- abstract data types, 3-90
- ADO, 1-4
- ADO.NET, 1-4, 3-103
- ADO.NET 1.x, 2-1
- ADO.NET 2.0, 2-5
 - base or DbCommon classes, 3-1
- ADO.NET 2.x, 2-1
- ADTs, 3-90
- Advanced Queuing support, lxiv
- app.config
 - setting performance counters, 3-14
- app.config file, 3-7
- AppDomain, 3-14
- application config, 2-9
- AQ support, lxiv
- array bind
 - OracleParameter, 3-46
- array bind operations, 3-45
 - ArrayBindCount, 6-23
 - ArrayBindIndex, 6-273
 - ArrayBindSize, 6-304, 6-305, 6-306, 6-330
 - ArrayBindStatus, 6-331
 - error handling, 3-46
- array binding, 3-45
- ArrayBindCount property, 6-23
- ArrayBindIndex property, 6-273
- ArrayBindSize property, 3-42, 3-46, 6-330
- ArrayBindStatus property, 3-42, 3-46, 6-331
- ASP.NET, 1-2
- assembly, 1-4
 - ODP.NET, 1-4

B

- batch processing, 3-48
- BatchUpdate
 - Microsoft Hotfix, 3-48
- behavior of ExecuteScalar method for REF CURSOR, 3-65
- BFILE, 3-75
- binding, 3-37
 - PL/SQL Associative Array, 3-42
- BLOB, 3-75
- bulk copy constraints, 3-105

- bulk copy feature, 3-105
 - restrictions, 3-105

C

- C#, Visual Basic .NET, C++ .NET, 1-1
- caching ODP.NET parameter contexts, lxvii
- callback support, 3-22
- case-sensitivity
 - column name mapping, 3-88
- change notification
 - ODP.NET support, 3-114
- change notification, Continuous Query Notification, 9-1
- characters with special meaning
 - in column data, 3-87
 - in table or view, 3-87
- characters with special meaning in XML, 3-82
- client applications, 1-1
- client globalization settings, 3-125, 3-128
- client identifier, 3-21
- CLOB, 3-75
- close calls, 2-32
- CLR, 1-2
- collection types, 3-91
- CollectionType property, 3-42
- column data
 - special characters in, 3-87
- CommandBehavior.SequentialAccess, 3-57
- commit transactions
 - changes to XML data, 3-90
- CommittableTransaction, 3-32
- Committed property, 6-304, 6-306
- configuration settings
 - UDTs, 3-104
- connect descriptor, 3-7
- connection dependency, 3-80
- connection pool
 - performance counters, 3-13
- connection pooling, 3-10
 - example, 3-11
 - management, 3-12
- Connection property, 3-76
- ConnectionString attributes, 3-10
 - Connection Lifetime, 3-5, 3-10, 3-11
 - Connection Timeout, 3-5, 3-10, 3-11

- Data Source, 3-5
- DBA Privilege, 3-5
- Decr Pool Size, 3-5, 3-10, 3-11
- Enlist, 3-5
- HA Events, 3-5, 3-10
- Incr Pool Size, 3-5, 3-10, 3-11
- Load Balancing, 3-5, 3-10
- Max Pool Size, 3-5, 3-10, 3-11
- Metadata Pooling, 3-5
- Min Pool Size, 3-5, 3-10, 3-11
- Password, 3-5
- Persist Security Info, 3-5
- Pooling, 3-5, 3-10, 3-11
- Proxy Password, 3-5, 3-19
- Proxy User Id, 3-5, 3-19
- Statement Cache Purge, 3-5
- Statement Cache Size, 3-5
- User Id, 3-5
- Validate Connection, 3-5, 3-10, 3-11
- ConnectionString property, 3-10, 3-11, 6-94
- Constraints property, 3-123
 - configuring, 3-124
- context connection, 5-2
- Continuous Query Notification, 3-112
 - best practices, 3-118
 - performance considerations, 3-118
- continuous query notification, 2-31, 3-114
 - ODP.NET support, 3-114
- controlling query reexecution, 3-122
- custom classes, 3-91
- custom type factories, 3-91
- custom type factory, 3-94
- custom type implementations
 - optional, 3-93
- custom type mapping, 3-94
- custom type mappings
 - specifying, 3-94
 - specifying with custom type factories, 3-94
 - specifying with XML, 3-94
 - using, 3-96
- custom types
 - converting to Oracle UDTS, 3-96
 - requirements, 3-92
- custom UDT classes, 3-91

D

- Data Guard, 3-24
- data loss, 3-119
- data manipulation
 - using XML, 3-86
- data source attribute, 3-7
- data source enumerators, 3-8
- database
 - changes to, 3-86
- database notification
 - port to listen, 2-31
- database shutdown, lxv
- database startup, lxv
- DataSet, 3-76

Index-2

- populating, 3-64
- populating from a REF CURSOR, 3-64
- populating with generic and custom objects, 3-103
- updating, 3-65
- updating to database, 3-123
- DataSet Fill, lxiv
- DataTable, 3-124
- Datatable properties, 3-123
- DBlinks, 5-2
- DbProviderFactories class, 2-5, 2-7, 3-1
- DbType
 - inference, 3-39
- debug tracing, 3-129
- default mapping
 - improving, 3-89
- dependent unmanaged DLL mismatch, 2-6
- direct path load, 3-105
- dispose calls, 2-32
- distributed transactions, 3-32
- documentation
 - .NET, 1-1
- Dynamic Enlistment, 3-21
- dynamic help, 1-1, 2-5, 2-7

E

- Easy Connect naming method, 3-8
- EDM type facets, 4-6
- EDM types
 - and Oracle data types, 4-2
- end-to-end tracing, lxvi, 3-21
- EnlistDistributedTransaction method, 3-21
- Entity Framework, lxi, 4-1
- enumeration type
 - OracleDbType, 3-37
- error handling, 3-46
- example
 - connection pooling, 3-11
- examples
 - documentation
 - readme file, 2-5, 2-8
- ExecuteNonQuery method, 3-65
- ExecuteScalar method, 3-65
- explicit user connections, 5-1
- EZCONNECT, 3-8

F

- failover, 3-22
 - registering an event handler, 3-22
- FailoverEvent Enumeration
 - description, 11-11
- FailoverReturnCode Enumeration
 - description, 11-12
- FailoverType Enumeration
 - description, 11-13
- Fast Application Notification (FAN), 3-25
- Fast Connection Failover (FCF), 3-27
- FCF, 3-28

features, 3-1
FetchSize property
 fine-tuning, 3-62
 setting at design time, 3-63
 setting at run time, 3-63
 using, 3-62
file locations, 2-5, 2-8

G

garbage collection, 2-32
GDS, 3-24
geographic data, 3-90
Global Assembly Cache (GAC), 2-5, 2-7
Global Data Services, 3-26
Global Data Services (GDS), 3-24
globalization settings, 3-125
 client, 3-125
 session, 3-126
 thread-based, 3-127
globalization support, 3-125
globalization-sensitive operations, 3-128
GoldenGate, 3-24
GUI access to ODP.NET, 1-2

H

HA Events, 3-5
HA events, 2-31
handling date and time format
 manipulating data in XML, 3-86
 retrieving queries in XML, 3-82
high availability, 3-24

I

implicit database connection, 5-1, 5-2, 5-3, 6-100
implicit REF CURSOR, lxi, 3-67
 bind and metadata, 3-67
 bindinfo, 3-69
 configuration, 3-71
 examples, 3-71
 usage, 3-73
improving default mapping, 3-89
inference from Value property, 3-40
inference of DbType and OracleDbType from Value, 3-40
inference of DbType from OracleDbType, 3-39
inference of OracleDbType from DbType, 3-40
inference of types, 3-39
InitialLOBFetchSize property, 3-58
InitialLONGFetchSize property, 3-57
input binding
 XMLType column, 3-81
insert triggers, 3-106
installation, 2-5, 2-7
 Oracle Data Provider for .NET, 2-5
 Oracle Data Provider for .NET, Manager Provider, 2-7
 XCopy class, 2-5, 2-7
integrated help, 2-5, 2-7

interference in OracleParameter class, 3-39
introduction, overview, 1-4
INullable Interface
 interface description, 14-455
 interface members, 14-456
 interface properties, 14-457
invalidation message, 3-114
 ensuring persistency of, 3-114
InvalidCastException, 3-54
IOracleArrayTypeFactory Interface
 interface description, 16-33
 interface members, 16-34
 interface methods, 16-35
IOracleCustomType Interface
 interface description, 16-26
 interface members, 16-27
 interface methods, 16-28
IOracleCustomTypeFactory Interface
 interface description, 16-30
 interface members, 16-31
 interface methods, 16-32

L

large binary datatypes, 3-75
large character datatypes, 3-75
limitations and restrictions, 5-2
LINQ to Entities, lxi, 4-1
Load Balancing, 3-5
load balancing, 2-31
LOB Connection property, 3-76
LOB retrieval, lxvii
LOBs
 temporary, 3-77
 updating, 3-77
LOBs updating, 3-76
local transactions, 3-32
location data, 3-90
logical transaction ID (LTXID), 3-29
LONG and LONG RAW datatypes, 3-75
LTXID, 3-29

M

machine.config, 2-9
machine.config file, 2-5, 2-7
metadata, 3-125
method invocation
 UDT, 3-104
Microsoft Common Language Runtime (CLR), 1-2
Microsoft Hotfix
 BatchUpdate, 3-48
Microsoft .NET Framework, 2-1
Microsoft .NET Framework Class Library, 1-4
Microsoft Transaction Server, 2-2
MTS, 2-2
multiple notification requests, 3-114
multiple tables
 changes to, 3-90

N

namespace

- Oracle.DataAccess.Types, 1-12
- native XML support, 3-78
- NCLOB, 3-75
- nested table types, 3-91
- .NET custom types, 3-90
- .NET Framework datatype, 3-52
- .NET languages, 1-1, 1-2
- .NET products and documentation, 1-1
- .NET stored procedures and functions, 5-1
- .NET Stream class, 3-76
- .NET type accessors, 3-54
- .NET Types
 - inference, 3-39
- notification framework, 3-114
- notification information
 - retrieving, 3-114
- notification process
 - flow, 3-116
- notification registration, 3-114
 - requirements of, 3-116
- NULL values
 - retrieving from column, 3-86
- number of rows fetched in round-trip
 - controlling, 3-62

O

- object data type support, 3-90
- object types, 3-91
- object-relational data, 3-85
 - saving changes from XML data, 3-90
- obtaining a REF CURSOR, 3-64
- obtaining an OracleRefCursor, 3-64
- obtaining data from an OracleDataReader, 3-53
- obtaining LOB data
 - InitialLOBFetchSize property, 3-58
- obtaining LONG and LONG RAW Data, 3-57
- OCI
 - statement caching, 3-48
- OData, lxii
- ODP.NET
 - installing, 2-5
- ODP.NET Configuration, 2-9
- ODP.NET LOB classes, 3-75
- ODP.NET Type accessors, 3-56
- ODP.NET Type classes, 3-52
- ODP.NET Type exceptions, 15-1
- ODP.NET Type structures, 3-52, 14-1
- ODP.NET Types, 3-52
 - overview, 3-52
- ODP.NET within a .NET stored procedure
 - limitations and restrictions, 5-2
 - transaction support, 5-3
 - unsupported SQL commands, 5-6
- ODP.NET XML Support, 3-78
- OnChangedEventArgs Class
 - instance properties, 9-34
 - members, 9-31

- static fields, 9-32
- static methods, 9-33
- OnChangeEventHandler Delegate
 - description, 9-40
- operating system authentication, 3-17
- Oracle Call Interface
 - statement caching, 3-48
- Oracle Data Provider for .NET
 - installing, 2-5
 - system requirements, 2-1
- Oracle Data Provider for .NET assembly, 1-4
- Oracle Data Provider for .NET, Managed Driver
 - installing, 2-7
- Oracle data types
 - and EDM types, 4-2
 - mapping and customizing, 4-12
- Oracle Database Extensions for .NET, 1-2, 5-1
- Oracle Developer Tools for Visual Studio, 1-2
- Oracle Label Security, 3-21
- Oracle native types, 3-52
 - supported by ODP.NET, 3-54
- Oracle Providers for ASP.NET, 1-2
- Oracle RAC, 3-24
- Oracle Real Application Clusters (Oracle RAC), 3-24
- Oracle Services for Microsoft Transaction Server, 2-2
- Oracle UDT attribute mappings, 3-97
- Oracle Universal Installer (OUI), 2-5, 2-7
- Oracle user-defined types, 3-90
- Oracle User-Defined Types (UDTs), 3-91
- Oracle Virtual Private Database (VPD), 3-21
- Oracle XML DB, 3-79
- OracleAQAgent
 - constructors, 12-4
- OracleAQAgent Class
 - constructors, 12-4
 - description, 12-2
 - members, 12-3, 12-38
 - properties, 12-6, 12-12
- OracleAQDequeueMode Enumeration
 - description, 12-84
- OracleAQDequeueOptions Class
 - constructor, 12-11
 - description, 12-8
 - members, 12-9
 - properties, 12-12
 - public methods, 12-18
- OracleAQEnqueueOptions Class
 - constructor, 12-21
 - description, 12-19
 - members, 12-20
 - properties, 12-22
 - public methods, 12-24
- OracleAQMessage Class
 - constructors, 12-27
 - description, 12-25
 - members, 12-26
 - properties, 12-29
- OracleAQMessageAvailableEventArgs Class
 - description, 12-37
 - members, 12-38

- properties, 12-40
- OracleAQMessageAvailableEventHandler Delegate
 - description, 12-47
- OracleAQMessageDeliveryMode Enumeration
 - description, 12-85
- OracleAQMessageState Enumeration
 - description, 12-86
- OracleAQMessageType Enumeration
 - description, 12-87
- OracleAQNavigationMode Enumeration
 - description, 12-88
- OracleAQNotificationGroupingType Enumeration
 - description, 12-89
- OracleAQNotificationType Enumeration
 - description, 12-90
- OracleAQQueue Class
 - constructors, 12-51
 - description, 12-48
 - events, 12-79
 - members, 12-49
 - properties, 12-58
 - public methods, 12-64
 - static methods, 12-51
- OracleAQVisibilityMode Enumeration
 - description, 12-91
- OracleArrayMappingAttribute Class
 - constructors, 16-22
 - description, 16-19
 - members, 16-20
 - methods, 16-25
 - properties, 16-24
 - static methods, 16-23
- OracleBFile Class
 - class description, 13-2
 - constructors, 13-8
 - instance methods, 13-20
 - instance properties, 13-13
 - members, 13-5
 - static fields, 13-10
 - static methods, 13-12
- OracleBinary Structure
 - constructor, 14-7
 - description, 14-2
 - instance methods, 14-26
 - members, 14-4
 - properties, 14-23
 - static fields, 14-8
 - static methods, 14-9
 - static operators, 14-15
 - static type conversion operators, 14-21
- OracleBlob Class
 - class description, 13-39
 - constructors, 13-45
 - instance methods, 13-56
 - instance properties, 13-50
 - members, 13-42
 - static fields, 13-47
 - static methods, 13-49
- OracleBulkCopy Class
 - class description, 17-2
- constructors, 17-5
- events, 17-21
- members, 17-3
- properties, 17-9
- public methods, 17-15
- OracleBulkCopyColumnMapping Class
 - class description, 17-22
 - constructors, 17-25
 - members, 17-24
 - properties, 17-29, 17-30
- OracleBulkCopyColumnMappingCollection Class
 - class description, 17-33
 - members, 17-35
 - properties, 17-36
 - public methods, 17-37
- OracleBulkCopyOptions Enumeration
 - description, 17-46
- OracleClientFactory, 2-5, 2-7
- OracleClientFactory Class
 - class description, 6-3
 - class members, 6-5
 - public methods, 6-8
 - public properties, 6-7
- OracleClientFactory class
 - instantiating, 3-1
- OracleClob Class
 - class description, 13-76
 - constructors, 13-82
 - instance methods, 13-94
 - instance properties, 13-87
 - members, 13-79
 - static fields, 13-84
 - static methods, 13-86
- OracleCollectionType Enumeration, 6-423
- OracleCommand
 - ArrayBindCount property, 3-45
 - constructors, 6-17
 - InitialLOBFetchSize property, 3-58
 - InitialLONGFetchSize property, 3-57
 - Transaction property, 3-32
- OracleCommand Class
 - ArrayBindCount, 6-23
 - class description, 6-12
 - ExecuteScalar method, 3-65
 - FetchSize property, 3-62
 - members, 6-14
 - properties, 6-20
 - public methods, 6-39, 12-18
 - RowSize property, 3-62
 - static methods, 6-19
- OracleCommand object, 3-32
- OracleCommand properties
 - ArrayBindCount, 3-45
- OracleCommand Transaction object, 3-32
- OracleCommandBuilder Class, 3-125
 - class description, 6-53
 - constructors, 6-58
 - events, 6-78
 - members, 6-56
 - properties, 6-64

- public methods, 6-69
- static methods, 6-60
- updating dataset, 3-123
- OracleConnection
 - ClearAllPools property, 3-12
 - ClearPool property, 3-12
 - ClientId property, 3-21
 - events, 6-130
- OracleConnection Class
 - class description, 6-79
 - constructors, 6-85
 - members, 6-81
 - obtaining a reference, 3-80
 - properties, 6-92
 - public methods, 6-107
 - static methods, 6-89
- OracleConnection class
 - GetSchema methods, 3-9
- OracleConnectionStringBuilder Class
 - class description, 6-134
 - class members, 6-137
 - constructors, 6-140
 - public methods, 6-157
 - public properties, 6-142
- OracleConnectionStringBuilder class
 - using, 3-7
- OracleConnectionType Enumeration
 - description, 6-422
- OracleCustomTypeMappingAttribute Class
 - constructors, 16-6
 - description, 16-2
 - members, 16-4
 - methods, 16-9
 - properties, 16-8
 - static methods, 16-7
- Oracle.DataAccess.Client namespace, 1-4
- Oracle.DataAccess.dll, 1-4
- Oracle.DataAccess.Types namespace, 1-4, 1-12
- OracleDataAdapter, 3-119
 - constructors, 6-165
 - members, 6-162
 - SafeMapping Property, 3-120
 - SelectCommand property, 3-64
- OracleDataAdapter Class, 6-160
 - events, 6-181
 - FillSchema method, 3-125
 - properties, 6-169
 - public methods, 6-176
 - SelectCommand property, 3-125
 - static methods, 6-168
- OracleDataAdapter class
 - FillSchema method, 3-124
 - Requery property, 3-122
 - SelectCommand property, 3-123
- OracleDataAdapter Safe Type Mapping, 3-119
- OracleDatabase Class
 - class description, 6-185
 - constructor, 6-188
 - members, 6-187
 - properties, 6-189
 - public methods, 6-190
 - Shutdown method, 6-191
 - Startup method, 6-194
- OracleDataReader, 3-53, 3-57
 - members, 6-200
 - retrieving UDTs from, 3-99
 - typed accessors, 3-54
- OracleDataReader Class
 - class description, 6-197
 - FetchSize property, 3-62
 - populating, 3-64
 - properties, 6-205
 - public methods, 6-217
 - static methods, 6-204
- OracleDataReader Class SchemaTable, 6-253
- OracleDataSource Enumerator class
 - using, 3-8
- OracleDataSourceEnumerator Class
 - class description, 6-263
 - class members, 6-265
 - public methods, 6-267
- OracleDate Structure
 - constructors, 14-74
 - description, 14-69
 - members, 14-71
 - methods, 14-101
 - properties, 14-96
 - static fields, 14-79
 - static methods, 14-81
 - static operators, 14-87
 - static type conversions, 14-92
- OracleDBShutdownMode Enumeration
 - description, 6-424
- OracleDBStartupMode Enumeration
 - description, 6-425
- OracleDbType
 - inference, 3-39
- OracleDbType Enumeration
 - description, 6-426
- OracleDbType enumeration, 3-39
- OracleDbType enumeration type, 3-37, 6-426
- OracleDecimal Structure
 - constructors, 14-113
 - description, 14-106
 - instance methods, 14-174
 - members, 14-108
 - properties, 14-170
 - static comparison methods, 14-123
 - static comparison operators, 14-153
 - static logarithmic methods, 14-142
 - static manipulation methods, 14-128
 - static operators, .NET Type to
 - OracleDecimal, 14-161
 - static operators, OracleDecimal to .NET, 14-165
 - static trigonometric methods, 14-147
- OracleDependency Class
 - change notification, 3-114
 - class description, 9-2
 - constructors, 9-5
 - Continuous Query Notification, 3-112

- events, 9-21
- instance methods, 9-18
- instance properties, 9-12
- members, 9-3
- static fields, 9-9
- static methods, 9-11
- OracleError Class
 - ArrayBindIndex, 6-273
 - class description, 6-269
 - members, 6-271
 - methods, 6-276
 - properties, 6-273
 - static methods, 6-272
- OracleErrorCollection
 - members, 6-279
 - properties, 6-281
 - public methods, 6-282
 - static methods, 6-280
- OracleErrorCollection Class, 6-277
- OracleException
 - members, 6-285
 - methods, 6-292
 - properties, 6-288
 - static methods, 6-287
- OracleException Class, 6-283
- OracleFailoverEventArgs
 - members, 11-5
 - properties, 11-7
 - public methods, 11-9
- OracleFailoverEventHandler Delegate
 - description, 11-10
- OracleGlobalization Class
 - class description, 10-2
 - members, 10-4
 - properties, 10-12
 - public methods, 10-22
- OracleHAEventArgs Class
 - description, 8-2
 - members, 8-3
 - properties, 8-4
- OracleHAEventHandler Delegate
 - description, 8-9
- OracleHAEventSource Enumeration
 - description, 8-10
- OracleHAEventStatus Enumeration
 - description, 8-11
- OracleIdentityType Enumeration
 - description, 6-428
- OracleInfoMessageEventArgs
 - members, 6-296
 - properties, 6-298
 - public methods, 6-300
 - static methods, 6-297
- OracleInfoMessageEventHandler Delegate, 6-301
- OracleIntervalDS Structure
 - constructors, 14-185
 - description, 14-180
 - members, 14-182
 - methods, 14-215
 - properties, 14-210
 - static methods, 14-192
 - static operators, 14-199
 - type conversions, 14-207
- OracleIntervalYM Structure
 - constructors, 14-223
 - description, 14-218
 - members, 14-220
 - methods, 14-229, 14-249
 - properties, 14-246
 - static fields, 14-227
 - static operators, 14-235
 - type conversions, 14-243
- OracleNotificationEventArgs Class
 - change notification, 3-114
 - class description, 9-30
 - instance methods, 9-39
- OracleNotificationInfo Enumeration
 - description, 9-44
- OracleNotificationRequest Class
 - change notification, 3-114
 - class description, 9-22
 - Continuous Query Notification, 3-112
 - instance methods, 9-29
 - instance properties, 9-25
 - members, 9-23
 - static methods, 9-24
- OracleNotificationSource Enumeration
 - description, 9-43
- OracleNotificationType Enumeration
 - description, 9-42
- OracleNullValueException Class
 - class description, 15-11
 - constructors, 15-14
 - members, 15-12
 - methods, 15-16, 15-18
 - properties, 15-17
- OracleObjectMappingAttribute Class
 - constructors, 16-13
 - description, 16-10
 - members, 16-11
 - methods, 16-18
 - properties, 16-16
 - static methods, 16-15
- OracleParameter
 - array bind properties, 3-46
 - ArrayBindSize property, 3-46, 6-304, 6-305, 6-306, 6-330
 - ArrayBindStatus property, 3-46, 6-331
 - constructors, 6-317
 - inferences of types, 3-39
 - members, 6-315
 - properties, 6-328
 - public methods, 6-345
 - static methods, 6-328
- OracleParameter array bind feature, 3-45
- OracleParameter Class, 6-313
 - Value, 3-40
- OracleParameter object, 3-37
 - OracleDbType enumerated values, 3-37
- OracleParameter property

- ArrayBindSize, 3-42
- ArrayBindStatus, 3-42
- CollectionType, 3-42
- Size, 3-42
- Value, 3-42
- OracleParameterCollection
 - members, 6-351
 - public methods, 6-357
 - static methods, 6-353
- OracleParameterCollection Class, 6-349
- OracleParameterStatus Enumeration
 - description, 6-429
- OracleParameterStatus enumeration type, 3-48, 6-429
- OraclePermission Class
 - constructor, 6-378
 - members, 6-376
 - public methods, 6-381
 - public properties, 6-380
 - static methods, 6-379
- Oraclepermission Class
 - description, 6-375
- OraclePermissionAttribute Class
 - constructor, 6-387
 - description, 6-384
 - members, 6-385
 - public methods, 6-390
 - public properties, 6-389
 - static methods, 6-388
- OracleRef Class
 - class description, 16-52
 - class members, 16-53
 - constructors, 16-55
 - instance methods, 16-64
 - instance properties, 16-60
 - static fields, 16-58
 - static methods, 16-59
- OracleRefCursor, 3-63
- OracleRefCursor Class
 - class description, 13-119
 - instance methods, 13-130
 - members, 13-122
 - populating from a REF CURSOR, 3-65
 - properties, 13-126
 - static methods, 13-124, 13-125
- OracleRowsCopiedEventArgs Class
 - class description, 17-48
 - constructors, 17-50
 - members, 17-49
 - properties, 17-51
- OracleRowsCopiedEventHandler Delegate
 - description, 17-47
- OracleRowUpdatedEventArgs
 - constructor, 6-394
 - members, 6-392
 - properties, 6-396
 - public methods, 6-397
 - static methods, 6-395
- OracleRowUpdatedEventArgs Class, 6-391
- OracleRowUpdatedEventHandler Delegate, 6-398
- OracleRowUpdatingEventArgs
 - constructor, 6-402
 - members, 6-400
 - properties, 6-404
 - public methods, 6-405
 - static methods, 6-403
- OracleRowUpdatingEventArgs Class, 6-399
- OracleRowUpdatingEventHandler Delegate, 6-406
- OracleString Structure
 - constructors, 14-257
 - description, 14-252
 - members, 14-254
 - methods, 14-279
 - properties, 14-276
 - static fields, 14-262
 - static methods, 14-263
 - static operators, 14-268
 - type conversions, 14-274
- OracleTimeStamp Structure
 - constructors, 14-290
 - description, 14-284
 - members, 14-286
 - methods, 14-327
 - properties, 14-321
 - static methods, 14-299
 - static operators, 14-306
 - static type conversions, 14-315
- OracleTimeStampLTZ Structure
 - constructors, 14-344
 - description, 14-338
 - members, 14-340
 - methods, 14-383
 - properties, 14-377
 - static fields, 14-351
 - static methods, 14-353
 - static operators, 14-361
 - static type conversions, 14-371
- OracleTimeStampTZ Structure
 - constructors, 14-401
 - description, 14-395
 - members, 14-397
 - methods, 14-443
 - properties, 14-437
 - static fields, 14-413
 - static methods, 14-415
 - static operators, 14-422
 - static type conversions, 14-431
- OracleTransaction
 - members, 6-410
 - properties, 6-412
 - public methods, 6-414
 - static methods, 6-411
- OracleTransaction Class
 - class description, 6-407
- OracleTruncateException Class
 - class description, 15-19
 - constructors, 15-22
 - members, 15-20
 - methods, 15-26
 - properties, 15-25

- static methods, 15-24
- OracleTypeException Class
 - class description, 15-2
 - constructors, 15-5
 - members, 15-3
 - properties, 15-8
 - static methods, 15-7
- OracleUdt Class
 - description, 16-37
 - members, 16-38
 - static methods, 16-39
- OracleUdtFetchOption Enumeration
 - description, 16-75
- OracleUdtStatus Enumeration
 - description, 16-76
- OracleXmlCommandType Enumeration, 7-2
- OracleXmlQueryProperties Class
 - class description, 7-3
 - constructors, 7-8
 - members, 7-7
 - properties, 7-9
 - public methods, 7-12
- OracleXmlSaveProperties Class, 7-13
 - constructors, 7-17
 - members, 7-16
 - properties, 7-18
 - public methods, 7-22
- OracleXmlStream Class
 - class description, 7-23
 - constructors, 7-26
 - instance methods, 7-32
 - instance properties, 7-28
 - members, 7-24
 - static methods, 7-27
- OracleXmlType Class, 3-80
 - class description, 7-38
 - constructors, 7-41
 - instance methods, 7-53
 - instance properties, 7-47
 - members, 7-39
 - static methods, 7-45
- outages, 3-28

P

- parameter binding, 3-37
- parameter binding with OracleParameter, 3-100
- parameter context caching, lxvii
- password expiration, 3-18
- passwords in code examples, liii
- performance, 3-24, 3-48
 - array binding, 3-45
 - connection pooling, 3-10
 - fine-tuning FetchSize, 3-62
 - number of rows fetched, 3-62
 - Obtaining LOB Data, 3-58
- performance counters
 - connection pool, 3-13
 - instance names of, 3-14
 - publishing, 3-13

- using .NET Configuration Entry, 3-14
- planned outage, 3-28
- PL/SQL Associative Array binding, 3-42
- PL/SQL Index-By Tables, 3-42
- PL/SQL language, 3-63
- PL/SQL REF CURSOR, 3-63
- PL/SQL REF CURSOR and OracleRefCursor, 3-63
- PLSQLAssociativeArray, 6-423
- pool size attributes
 - Oracle RAC, 3-28
- populating an OracleDataReader from a REF CURSOR, 3-64
- populating an OracleRefCursor from a REF CURSOR, 3-65
- populating the DataSet from a REF CURSOR, 3-64
- populating the DataSet with generic and custom objects, 3-103
- port
 - listen for database notifications, 2-31
- port number
 - defining listener, 3-114
- porting
 - client application to .NET stored procedure, 5-6
- preventing data loss, 3-119, 3-120
- preventing logical corruption, 3-29
- PrimaryKey property, 3-123
 - configuring, 3-124
- privileged connections, 3-18
- promotable transactions, lxiv, 3-32
- properties
 - ClientId property, 3-21
- provider factory classes, 3-1
- proxy authentication, 3-19

Q

- query result set
 - retrieving as XML, 3-82

R

- REF CURSOR
 - behavior of ExecuteScalar method, 3-65
 - implicit, lxii, 3-67
 - obtaining, 3-64
 - passing to stored procedure, 3-65
 - populating DataSet from, 3-64
 - populating from OracleDataReader, 3-64
- registry entries, 2-9
- release Oracle8i (8.1.7), 3-86
- release Oracle9i(9.0.x), 3-86
- Requery property, 3-122
- round-trip, 3-45
- RowSize property, 3-62
- runtime connection load balancing, 3-26

S

- Safe Type Mapping, 3-119
- SafeMapping Property, 3-120
- Samples, 1-18

- samples, 2-5, 2-8
 - UDT, 16-1
- saving change using an XML document, 3-88
- saving changes
 - using XML data, 3-86
- schema metadata
 - customizing metadata, 3-9
- SchemaTable, 6-253
- search order
 - unmanaged DLLs, 2-6
- SecureFiles, lxvii, 3-75
- security enhancements, lxv
- SelectCommand property, 3-64
- Self-Tuning, lxiv
- session globalization parameters, 3-128
- session globalization settings, 3-126
- Shutdown method, 6-191
- shutdown, database, lxv
- simple application, 1-17
- Size property, 3-42
- SQL commands
 - unsupported, 5-6
- Startup method, 6-194
- startup, database, lxv
- Statement Caching
 - connection string attributes, 3-49
 - methods and properties, 3-49
 - Statement Cache Purge, 3-48
 - Statement Cache Size, 3-48
- StatementCacheWithUdts, 3-104
- stored procedures and functions, 3-65, 5-1
- Stream class, 3-76
- support comparison
 - client application versus .NET stored procedure, 5-6
- SYSDBA privileges, 3-18
- SYSOPER privileges, 3-18
- system requirements
 - Oracle Data Provider for .NET, 2-1
- System.Transactions support, 3-32

T

- table or view
 - special characters in, 3-87
- TAF, 3-22
- TAF callback support, 3-22
- Temporary LOBs, 3-77
- thread globalization settings, 3-128
- Thread.Abort method, 2-32
- thread-based globalization settings, 3-127
- tips for ODP.NET, 2-32
- TNS alias, 3-7
- tracing
 - end-to-end, lxvi
- tracing attributes, 3-21
- Transaction Guard, 3-29
- Transaction object, 3-32
- Transaction property, 3-32
- transaction support, 5-3

- transactions
 - commit, 3-90
- TransactionScope, 3-32
- Transparent Application Failover (TAF), 3-22
- triggers, 3-106, 4-14
 - INSERT, 4-14
 - insert triggers, 3-106
- troubleshooting, 3-129
- typed OracleDataReader accessors, 3-54

U

- UDT
 - method invocation, 3-104
- UDT metadata retrieval from
 - OracleDataReader, 3-100
- UdtCacheSize, 3-104
- UDTs, 3-90
 - collection types, 3-91
 - configuration settings, 3-104
 - object types, 3-91
 - parameter binding with OracleParameter, 3-100
 - retrieving from OracleDataReader, 3-99
 - samples, 16-1
- UDTs (Oracle User-Defined Types), 3-91
- UdtTypeName property, 3-100
- unique columns, 3-57, 3-58
- unique constraint, 3-57, 3-58
- unique index, 3-57, 3-58
- UniqueConstraint, 3-124
- uniqueness
 - in updating DataSet to database, 3-123
- uniqueness in DataRows, 3-123
- unmanaged DLLs
 - mismatch, 2-6
 - search order, 2-6
- unmanged DLLs
 - config support, 2-6
- unsupported SQL commands, 5-6
- updating
 - LOBs, 3-76
 - updating a DataSet obtained from a REF CURSOR, 3-65
 - updating LOBs using a DataSet, 3-76
 - updating LOBs using ODP.NET LOB objects, 3-77
 - updating LOBs using OracleCommand and OracleParameter, 3-77
 - updating without PrimaryKey and Constraints, 3-125
- UserCallCompleted public read-only property, 6-305
- user-defined types, 3-90
- UserId public read-only property, 6-305
- using FetchSize property, 3-62

V

- Value property, 3-42
- VARRAY types, 3-91
- Virtual Private Database(VPD), 3-21

Visual Studio
documentation, 2-5, 2-7

W

WCF Data Services, lxii
web.config, 2-9
Windows registry, 2-17

X

XML
characters with special meaning, 3-82
data manipulation using, 3-86
XML data
saving changes using, 3-86
updating in OracleXmlType, 3-81
XML Database, 3-78
XML DB, 3-78, 3-79
XML element name
case-sensitivity in, 3-88
XML Element Name to Column Name
Mapping, 3-88
XML related classes, 7-1
XML related enumerations, 7-1
XML Support, 3-78
XML to specify custom type mappings, 3-95
XMLQuery, 3-79
XMLTable, 3-79
XMLType column
as a .NET String, 3-80
fetching into the DataSet, 3-80
updating with OracleCommand, 3-81
XMLType columns
setting to NULL, 3-81
XQUERY, 3-79
XQuery
support, 3-79
XQuery language, 3-79

