

Oracle® Process Manufacturing

Cost Management API User's Guide

Release 11i

Part No. A95270-02

January 2003

ORACLE™

Oracle Process Manufacturing Cost Management API User's Guide, Release 11i

Part No. A95270-02

Copyright © 2003 Oracle Corporation. All rights reserved.

Primary Author: Michele-Andrea Fields

The Programs (which include both the software and documentation) contain proprietary information of Oracle Corporation; they are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright, patent, and other intellectual and industrial property laws. Reverse engineering, disassembly, or decompilation of the Programs is prohibited.

Program Documentation is licensed for use solely to support the deployment of the Programs and not for any other purpose.

The information contained in this document is subject to change without notice. If you find any problems in the documentation, please report them to us in writing. Oracle Corporation does not warrant that this document is error free. Except as may be expressly permitted in your license agreement for these Programs, no part of these Programs may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, without the express written permission of Oracle Corporation.

If the Programs are delivered to the U.S. Government or anyone licensing or using the programs on behalf of the U.S. Government, the following notice is applicable:

Restricted Rights Notice Programs delivered subject to the DOD FAR Supplement are "commercial computer software" and use, duplication, and disclosure of the Programs, including documentation, shall be subject to the licensing restrictions set forth in the applicable Oracle license agreement. Otherwise, Programs delivered subject to the Federal Acquisition Regulations are "restricted computer software" and use, duplication, and disclosure of the Programs shall be subject to the restrictions in FAR 52.227-19, Commercial Computer Software - Restricted Rights (June, 1987). Oracle Corporation, 500 Oracle Parkway, Redwood City, CA 94065.

The Programs are not intended for use in any nuclear, aviation, mass transit, medical, or other inherently dangerous applications. It shall be the licensee's responsibility to take all appropriate fail-safe, backup, redundancy, and other measures to ensure the safe use of such applications if the Programs are used for such purposes, and Oracle Corporation disclaims liability for any damages caused by such use of the Programs.

Oracle is a registered trademark of Oracle Corporation. Other names may be trademarks of their respective owners.

Contents

Send Us Your Comments	vii
Preface.....	ix
Audience for This Guide.....	ix
How To Use This Guide	ix
Documentation Accessibility	x
Other Information Sources	x
Online Documentation.....	x
Related User's Guides.....	xi
Guides Related to All Products	xi
User Guides Related to This Product	xi
Installation and System Administration	xvi
Other Implementation Documentation.....	xviii
Training and Support.....	xix
Do Not Use Database Tools to Modify Oracle Applications Data.....	xx
About Oracle.....	xxi
Your Feedback	xxi
1 Cost Management APIs	
Introducing the Cost Management APIs.....	1-2
Basic Business Needs.....	1-2
Major Features.....	1-3
Item Cost APIs	1-4
Resource Cost APIs	1-4

Allocation Definition APIs	1-5
Burden Details APIs	1-5
Cost Management API Features	1-6
Cost Management API Support Policy	1-6
Oracle Applications Packages Supplied	1-7
Cost Management API Bill of Materials	1-7
2 Cost Management API Usage	
Calling the API Interface Code	2-1
Calling the API Code - Example	2-2
Wrapper logic	2-2
API Hints	2-4
Item Cost Example	2-5
3 Technical Overview	
Item Cost	3-1
Structure for Item Cost Public APIs	3-1
Resource Cost	3-3
Structure for Resource Cost Public APIs	3-3
Allocation Definition	3-4
Structure for Allocation Definition Public APIs	3-4
Burden Details	3-5
Structure for Burden Details Public APIs	3-5
Standard Parameters	3-6
4 Business Objects	
Item Cost	4-1
Cost Header Entity	4-2
This Level Cost Detail Entity	4-3
Lower Level Cost Detail Entity	4-4
Structure and Logic	4-5
Resource Cost	4-12
Resource Cost Entity	4-12
Structure and Logic	4-13

Allocation Definition	4-17
Allocation Definition Entity.....	4-17
Structure and Logic.....	4-18
Burden Details	4-22
Header Entity.....	4-22
Detail Entity.....	4-23
Structure and Logic.....	4-24

A Messages and Errors

Handling Messages	A-1
Interpreting Error Conditions	A-4
Understanding Error Messages	A-4

Index

Send Us Your Comments

Oracle Process Manufacturing Cost Management API User's Guide, Release 11i

Part No. A95270-02

Oracle Corporation welcomes your comments and suggestions on the quality and usefulness of this document. Your input is an important part of the information used for revision.

- Did you find any errors?
- Is the information clearly presented?
- Do you need more information? If so, where?
- Are the examples correct? Do you need more examples?
- What features did you like most?

If you find any errors or have any other suggestions for improvement, please indicate the document title and part number, and the chapter, section, and page number (if available). You can send comments to us in the following ways:

- FAX: 650-506-7200 Attn: Oracle Process Manufacturing
- Postal service:
Oracle Corporation
Oracle Process Manufacturing
500 Oracle Parkway
Redwood City, CA 94065
U.S.A.
- Electronic mail message to appsdoc@us.oracle.com

If you would like a reply, please give your name, address, telephone number, and (optionally) electronic mail address.

If you have problems with the software, please contact your local Oracle Support Services.

Audience for This Guide

Welcome to Release 11i of the *Oracle Process Manufacturing Cost Management API User's Guide*.

This guide assumes you have a working knowledge of the following:

- The principles and customary practices of your business area.
- *Oracle Process Manufacturing*

If you have never used *Oracle Process Manufacturing Cost Management APIs*, Oracle suggests you attend one or more of the *Oracle Process Manufacturing Cost Management APIs* training classes available through Oracle University.

- The Oracle Applications graphical user interface.

To learn more about the Oracle Applications graphical user interface, read the *Oracle Applications User's Guide*.

See Other Information Sources for more information about Oracle Applications product information.

How To Use This Guide

This guide contains the information you need to understand and use *Oracle Process Manufacturing*.

- Chapter 1 describes the Application Program Interfaces (APIs) that support external interfaces to the OPM Cost Management tables.
- Chapter 2 provides information on the usage and layout of the Cost Management APIs.
- Chapter 3 provides the relationships between Costing API table structure and its entities. Discusses Costing API business objects, the entity relationship diagram, business object interface design, creating a cost and importing cost data structures.
- Appendix A provides message handling, the interpretation of error conditions, and an understanding of error messages.

Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible, with good usability, to the disabled community. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Standards will continue to evolve over time, and Oracle Corporation is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be accessible to all of our customers. For additional information, visit the Oracle Accessibility Program Web site at <http://www.oracle.com/accessibility/>.

Accessibility of Code Examples in Documentation

JAWS, a Windows screen reader, may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, JAWS may not always read a line of text that consists solely of a bracket or brace.

Other Information Sources

You can choose from many sources of information, including online documentation, training, and support services, to increase your knowledge and understanding of *Oracle Process Manufacturing Cost Management APIs*.

If this guide refers you to other Oracle Applications documentation, use only the Release 11i versions of those guides.

Online Documentation

All Oracle Applications documentation is available online (HTML or PDF).

- **Online Help** - The new features section in the HTML help describes new features in 11i. This information is updated for each new release of *Oracle Process Manufacturing Cost Management APIs*. The new features section also includes information about any features that were not yet available when this guide was printed. For example, if your administrator has installed software from a mini-packs an upgrade, this document describes the new features. Online help patches are available on MetaLink.

- **11i Features Matrix** - This document lists new features available by patch and identifies any associated new documentation. The new features matrix document is available on MetaLink.
- **Readme File** - Refer to the readme file for patches that you have installed to learn about new documentation or documentation patches that you can download.

Related User's Guides

Oracle Process Manufacturing shares business and setup information with other Oracle Applications products. Therefore, you may want to refer to other user's guides when you set up and use *Oracle Process Manufacturing Cost Management APIs*.

You can read the guides online by choosing Library from the expandable menu on your HTML help window, by reading from the Oracle Applications Document Library CD included in your media pack, or by using a Web browser with a URL that your system administrator provides.

If you require printed guides, you can purchase them from the Oracle Store at <http://oraclestore.oracle.com>.

Guides Related to All Products

Oracle Applications User's Guide

This guide explains how to enter data, query, run reports, and navigate using the graphical user interface (GUI) available with this release of *Oracle Process Manufacturing Cost Management APIs* (and any other Oracle Applications products). This guide also includes information on setting user profiles, as well as running and reviewing reports and concurrent processes.

You can access this user's guide online by choosing "Getting Started with Oracle Applications" from any Oracle Applications help file.

User Guides Related to This Product

Accounting Setup User's Guide

The OPM Accounting Setup application is where users set up global accounting attributes about the way financial data will be collected by OPM. These attributes include such things as account keys, financial calendars, and account segments. Since OPM is closely integrated with Oracle General Ledger (GL), much of the

attributes are defined in the Oracle GL instead of OPM, and therefore, the windows are display only within OPM. The *Oracle Process Manufacturing Accounting Setup User's Guide* describes how to setup and use this application.

Cost Management User's Guide

The OPM Cost Management application is used by cost accountants to capture and review the manufacturing costs incurred in their process manufacturing businesses. The *Oracle Process Manufacturing Cost Management User's Guide* describes how to setup and use this application.

Manufacturing Accounting Controller User's Guide

The Manufacturing Accounting Controller application is where users define the impact of manufacturing events on financials. For example, event RCPT (Inventory Receipts) results in a debit to inventory, a credit to accrued accounts payable, a debit or a credit to purchase price variance, etc. These impacts are predefined in the Manufacturing Accounting Controller application so users may begin using OPM to collect financial data out-of-the-box, however, they may also be adjusted per your business needs. The *Oracle Process Manufacturing Manufacturing Accounting Controller User's Guide* describes how to setup and use this application.

Oracle Financials Integration User's Guide

Since OPM is closely integrated with Oracle General Ledger, financial data that is collected about the manufacturing processes must be transferred to the Oracle Financials applications. The OPM Oracle Financials Integration application is where users define how that data is transferred. For example, users define whether data is transferred real time or batched and transferred at intervals. The *Oracle Process Manufacturing Oracle Financials Integration User's Guide* describes how to setup and use this application.

Inventory Management User's Guide

The OPM Inventory Management application is where data about the items purchased for, consumed during, and created as a result of the manufacturing process are tracked. The *Oracle Process Manufacturing Inventory Management User's Guide* includes information to help you effectively work with the Oracle Process Manufacturing Inventory application.

Physical Inventory User's Guide

Performing physical inventory count is the most accurate way to get an accounting of all material quantities purchased, manufactured, and sold, and update your onhand quantities accordingly. The OPM Physical Inventory application automates and enables the physical inventory process. The *Oracle Process Manufacturing Physical Inventory User's Guide* describes how to setup and use this application.

Order Fulfillment User's Guide

The OPM Order Fulfillment application automates sales order entry to reduce order cycle time. Order Fulfillment enables order entry personnel to inform customers of scheduled delivery dates and pricing. The *Oracle Process Manufacturing Order Fulfillment User's Guide* describes how to setup and use this application.

Purchase Management User's Guide

OPM Purchase Management and Oracle Purchasing combine to provide an integrated solution for Process Manufacturing. Purchase orders are entered in Oracle Purchasing and received in OPM. Then, the receipts entered in OPM are sent to Oracle Purchasing. The *Oracle Process Manufacturing Purchase Management User's Guide* describes how to setup and use this integrated solution.

Using Oracle Order Management with Process Inventory Guide

Oracle Process Manufacturing and Oracle Order Management combine to provide an integrated solution for process manufacturers. The manufacturing process is tracked and handled within Oracle Process Manufacturing, while sales orders are taken and tracked in Oracle Order Management. Process attributes, such as dual UOM and lot control, are enabled depending on the inventory organization for the item on the sales order. Order Management accepts orders entered through Oracle Customer Relationship Management (CRM). Within CRM, orders can originate from TeleSales, Sales Online, and iStore, and are booked in Order Management, making the CRM suite of products available to Process customers, through Order Management. The *Oracle Order Management User's Guide* and *Using Oracle Order Management with Process Inventory Guide* describes how to setup and use this integrated solution.

Process Execution User's Guide

The OPM Process Execution application lets you track firm planned orders and production batches from incoming materials through finished goods. Seamlessly integrated to the Product Development application, Process Execution lets you convert firm planned orders to single or multiple production batches, allocate

ingredients, record actual ingredient usage, and then complete and close production batches. Production inquiries and preformatted reports help you optimize inventory costs while maintaining a high level of customer satisfaction with on-time delivery of high quality products. The *OPM Process Execution User's Guide* presents overviews of the tasks and responsibilities for the Production Supervisor and the Production Operator. It provides prerequisite setup in other applications, and details the windows, features, and functionality of the OPM Process Execution application.

Integration with Advanced Planning and Scheduling User's Guide

Oracle Process Manufacturing and Oracle Advanced Planning and Scheduling (APS) combine to provide an integrated solution for process manufacturers that can help increase planning efficiency. The integration provides for constraint-based planning, performance management, materials management by exception, mixed mode manufacturing that enables you to choose the best method to produce each of your products, and combine all of these methods within the same plant/company. The *Oracle Process Manufacturing Integration with Advanced Planning and Scheduling User's Guide* describes how to setup and use this application.

MPS/MRP and Forecasting User's Guide

The Oracle Process Manufacturing Material Requirements Planning (MRP) application provides long-term "views" of material demands and projected supply actions to satisfy those demands. The Master Production Scheduling (MPS) application lets you shorten that view to a much narrower and immediate time horizon, and see the immediate effects of demand and supply actions. The *Oracle Process Manufacturing MPS/MRP and Forecasting User's Guide* describes how to setup and use this application.

Capacity Planning User's Guide

The OPM Capacity Planning User's Guide describes the setup required to use OPM with the Oracle Applications Advanced Supply Chain Planning solutions. In addition, Resource setup, used by the OPM Production Execution and New Product Development applications, is also described.

Using Oracle Process Manufacturing with Oracle Manufacturing Scheduling

Oracle Process Manufacturing integrates with Oracle Manufacturing Scheduling to manage and utilize resources and materials. Through the Process Manufacturing application, you set up manufacturing, inventory, procurement and sales order data. Through the Manufacturing Scheduling application, you can optimize the

schedule based on resource and component constraints and user predefined priorities. Using different optimization objectives, you can tailor Manufacturing Scheduling to meet your needs.

Using Oracle Manufacturing Scheduling helps you improve productivity and efficiency on your shop floor. By optimally scheduling shop floor jobs, and being able to quickly react to unplanned constraints, you can lower manufacturing costs, increase resource utilization and efficiency, and increase customer satisfaction through improved on-time delivery. The *Using Oracle Process Manufacturing with Oracle Manufacturing Scheduling User's Guide* describes how to setup and use this integrated solution.

Product Development User's Guide

The Oracle Process Manufacturing Product Development application provides features to manage formula and laboratory work within the process manufacturing operation. It lets you manage multiple laboratory organizations and support varying product lines throughout the organization. You can characterize and simulate the technical properties of ingredients and their effects on formulas. You can optimize formulations before beginning expensive laboratory test batches. Product Development coordinates each development function and enables a rapid, enterprise-wide implementation of new products in your plants. The *Oracle Process Manufacturing Product Development User's Guide* describes how to setup and use this application.

Quality Management User's Guide

The Oracle Process Manufacturing Quality Management application provides features to test material sampled from inventory, production, or receipts from external suppliers. The application lets you enter specifications and control their use throughout the enterprise. Customized workflows and electronic record keeping automate plans for sampling, testing, and result processing. You can compare specifications to assist in regrading items, and match customer specifications. Aggregate test results and print statistical assessments on quality certificates. Several preformatted reports and inquiries help manage quality testing and reporting. The *Oracle Process Manufacturing Quality Management User's Guide* describes how to set up and use this application.

Regulatory Management User's Guide

The Oracle Process Manufacturing Regulatory Management application generates the Material Safety Data Sheets (MSDSs) required by authorities to accompany hazardous materials during shipping. You can create MSDSs from OPM Formula

Management with Regulatory or Production effectivities. The *Oracle Process Manufacturing Regulatory Management User's Guide* describes how to setup and use this application.

Implementation Guide

The *Oracle Process Manufacturing Implementation Guide* offers information on setup. That is, those tasks you must complete following the initial installation of the Oracle Process Manufacturing software. Any tasks that must be completed in order to use the system out-of-the-box are included in this manual.

System Administration User's Guide

Much of the System Administration duties are performed at the Oracle Applications level, and are therefore described in the *Oracle Applications System Administrator's Guide*. The *Oracle Process Manufacturing System Administration User's Guide* provides information on the few tasks that are specific to OPM. It offers information on performing OPM file purge and archive, and maintaining such things as responsibilities, units of measure, and organizations.

API User's Guides

Public Application Programming Interfaces (APIs) are available for use with different areas of the Oracle Process Manufacturing application. APIs make it possible to pass information into and out of the application, bypassing the user interface. Use of these APIs is documented in individual manuals such as the *Oracle Process Manufacturing Inventory API User's Guide*, *Oracle Process Manufacturing Process Execution API User's Guide*, *Oracle Process Manufacturing Product Development Formula API User's Guide*, *Oracle Process Manufacturing Product Development Recipe API User's Guide*, *Oracle Process Manufacturing Quality Management API User's Guide*, and the *Oracle Process Manufacturing Cost Management API User's Guide*. Additional API User's Guides are periodically added as additional public APIs are made available.

Installation and System Administration

Oracle Applications Concepts

This guide provides an introduction to the concepts, features, technology stack, architecture, and terminology for Oracle Applications Release 11i. It provides a useful first book to read before an installation of Oracle Applications. This guide

also introduces the concepts behind Applications-wide features such as Business Intelligence (BIS), languages and character sets, and Self-Service Web Applications.

Installing Oracle Applications

This guide provides instructions for managing the installation of Oracle Applications products. In Release 11*i*, much of the installation process is handled using Oracle Rapid Install, which minimizes the time to install Oracle Applications, the Oracle8 technology stack, and the Oracle8*i* Server technology stack by automating many of the required steps. This guide contains instructions for using Oracle Rapid Install and lists the tasks you need to perform to finish your installation. You should use this guide in conjunction with individual product user's guides and implementation guides.

Upgrading Oracle Applications

Refer to this guide if you are upgrading your Oracle Applications Release 10.7 or Release 11.0 products to Release 11*i*. This guide describes the upgrade process and lists database and product-specific upgrade tasks. You must be either at Release 10.7 (NCA, SmartClient, or character mode) or Release 11.0, to upgrade to Release 11*i*. You cannot upgrade to Release 11*i* directly from releases prior to 10.7.

Maintaining Oracle Applications

Use this guide to help you run the various AD utilities, such as AutoUpgrade, AutoPatch, AD Administration, AD Controller, AD Relink, License Manager, and others. It contains how-to steps, screenshots, and other information that you need to run the AD utilities. This guide also provides information on maintaining the Oracle applications file system and database.

Oracle Applications System Administrator's Guide

This guide provides planning and reference information for the Oracle Applications System Administrator. It contains information on how to define security, customize menus and online help, and manage concurrent processing.

Oracle Alert User's Guide

This guide explains how to define periodic and event alerts to monitor the status of your Oracle Applications data.

Oracle Applications Developer's Guide

This guide contains the coding standards followed by the Oracle Applications development staff. It describes the Oracle Application Object Library components needed to implement the Oracle Applications user interface described in the *Oracle Applications User Interface Standards for Forms-Based Products*. It also provides information to help you build your custom Oracle Forms Developer 6*i* forms so that they integrate with Oracle Applications.

Oracle Applications User Interface Standards for Forms-Based Products

This guide contains the user interface (UI) standards followed by the Oracle Applications development staff. It describes the UI for the Oracle Applications products and how to apply this UI to the design of an application built by using Oracle Forms.

Other Implementation Documentation

Oracle Applications Product Update Notes

Use this guide as a reference for upgrading an installation of Oracle Applications. It provides a history of the changes to individual Oracle Applications products between Release 11.0 and Release 11*i*. It includes new features, enhancements, and changes made to database objects, profile options, and seed data for this interval.

Multiple Reporting Currencies in Oracle Applications

If you use the Multiple Reporting Currencies feature to record transactions in more than one currency, use this manual before implementing *Oracle Process Manufacturing*. This manual details additional steps and setup considerations for implementing *Oracle Process Manufacturing* with this feature.

Multiple Organizations in Oracle Applications

This guide describes how to set up and use *Oracle Process Manufacturing* with Oracle Applications' Multiple Organization support feature, so you can define and support different organization structures when running a single installation of *Oracle Process Manufacturing*.

Oracle Workflow Guide

This guide explains how to define new workflow business processes as well as customize existing Oracle Applications-embedded workflow processes. You also use

this guide to complete the setup steps necessary for any Oracle Applications product that includes workflow-enabled processes.

Oracle Applications Flexfields Guide

This guide provides flexfields planning, setup and reference information for the *Oracle Process Manufacturing* implementation team, as well as for users responsible for the ongoing maintenance of Oracle Applications product data. This manual also provides information on creating custom reports on flexfields data.

Oracle eTechnical Reference Manuals

Each eTechnical Reference Manual (eTRM) contains database diagrams and a detailed description of database tables, forms, reports, and programs for a specific Oracle Applications product. This information helps you convert data from your existing applications, integrate Oracle Applications data with non-Oracle applications, and write custom reports for Oracle Applications products. Oracle eTRM is available on Metalink

Oracle Manufacturing APIs and Open Interfaces Manual

This manual contains up-to-date information about integrating with other Oracle Manufacturing applications and with your other systems. This documentation includes API's and open interfaces found in Oracle Manufacturing.

Oracle Order Management Suite APIs and Open Interfaces Manual

This manual contains up-to-date information about integrating with other Oracle Manufacturing applications and with your other systems. This documentation includes API's and open interfaces found in Oracle Order Management Suite.

Oracle Applications Message Reference Manual

This manual describes all Oracle Applications messages. This manual is available in HTML format on the documentation CD-ROM for Release 11i.

Training and Support

Training

Oracle offers a complete set of training courses to help you and your staff master *Oracle Process Manufacturing Cost Management APIs* and reach full productivity

quickly. These courses are organized into functional learning paths, so you take only those courses appropriate to your job or area of responsibility.

You have a choice of educational environments. You can attend courses offered by Oracle University at any one of our many Education Centers, you can arrange for our trainers to teach at your facility, or you can use Oracle Learning Network (OLN), Oracle University's online education utility. In addition, Oracle training professionals can tailor standard courses or develop custom courses to meet your needs. For example, you may want to use your organization structure, terminology, and data as examples in a customized training session delivered at your own facility.

Support

From on-site support to central support, our team of experienced professionals provides the help and information you need to keep *Oracle Process Manufacturing Cost Management APIs* working for you. This team includes your Technical Representative, Account Manager, and Oracle's large staff of consultants and support specialists with expertise in your business area, managing an Oracle8i server, and your hardware and software environment.

Do Not Use Database Tools to Modify Oracle Applications Data

Oracle STRONGLY RECOMMENDS that you never use SQL*Plus, Oracle Data Browser, database triggers, or any other tool to modify Oracle Applications data unless otherwise instructed.

Oracle provides powerful tools you can use to create, store, change, retrieve, and maintain information in an Oracle database. But if you use Oracle tools such as SQL*Plus to modify Oracle Applications data, you risk destroying the integrity of your data and you lose the ability to audit changes to your data.

Because Oracle Applications tables are interrelated, any change you make using Oracle Applications can update many tables at once. But when you modify Oracle Applications data using anything other than Oracle Applications, you may change a row in one table without making corresponding changes in related tables. If your tables get out of synchronization with each other, you risk retrieving erroneous information and you risk unpredictable results throughout Oracle Applications.

When you use Oracle Applications to modify your data, Oracle Applications automatically checks that your changes are valid. Oracle Applications also keeps track of who changes information. If you enter information into database tables using database tools, you may store invalid information. You also lose the ability to

track who has changed your information because SQL*Plus and other database tools do not keep a record of changes.

About Oracle

Oracle Corporation develops and markets an integrated line of software products for database management, applications development, decision support, and office automation, as well as Oracle Applications, an integrated suite of more than 160 software modules for financial management, supply chain management, manufacturing, project systems, human resources and customer relationship management.

Oracle products are available for mainframes, minicomputers, personal computers, network computers and personal digital assistants, allowing organizations to integrate different computers, different operating systems, different networks, and even different database management systems, into a single, unified computing and information resource.

Oracle is the world's leading supplier of software for information management, and the world's second largest software company. Oracle offers its database, tools, and applications products, along with related consulting, education, and support services, in over 145 countries around the world.

Your Feedback

Thank you for using *Oracle Process Manufacturing Cost Management APIs* and this user's guide.

Oracle values your comments and feedback. At the end of this guide is a Reader's Comment Form you can use to explain what you like or dislike about *Oracle Process Manufacturing Cost Management APIs* or this user's guide. Mail your comments to the following address or call us directly at (650) 506-7000.

Oracle Applications Documentation Manager
Oracle Corporation
500 Oracle Parkway
Redwood Shores, CA 94065
U.S.A.

Or, send electronic mail to **appsdoc_us@oracle.com**.

Cost Management APIs

This document describes the Application Program Interfaces (APIs) that support external interfaces to the Oracle Process Manufacturing (OPM) Cost Management tables. The topics discussed in this topic are:

- Introducing the Cost Management APIs
- Oracle Applications Packages Supplied
- Cost Management API Bill of Materials

Introducing the Cost Management APIs

Cost Management APIs allow you to import costing information from an existing cost management system into the Oracle Process Manufacturing Cost Management tables. When you import this information you can now include all pertinent information using a friendly tool that does not have cryptic IDs and system specific information. Cost Management APIs can process virtually all cost types. The interface insures that your imported costs contain the same detail as those you would enter manually on the OPM Cost Management window.

What's In This Document?

This document describes the basic business needs, major features, architecture, and components for the Insert, Update and Delete features for the Cost Management APIs. Much of the application is divided into module-specific objects that allow you to link OPM functionality into your own programs. The interfaces can make use of the standard functionality and logic implemented in the Cost Management module.

Cost Management APIs are currently written in PL/SQL which can be called by your own programs. To make use of these APIs, you must code your wrapper function that passes the appropriate parameters to the APIs. Your program will also be responsible for connecting to a database before calling an API function, and disconnecting from the database upon return. You may also choose to write log files before calling and after returning from a function. If there is a problem during execution of a call, the APIs return one of the following status codes:

- S for success
- E for error
- U unknown/unexpected status.

Basic Business Needs

These APIs allow users to have an Application Programming Interface (API) available for the maintenance of cost information for an Item and Resource. The purpose of these APIs is to provide a mechanism, in addition to an entry screen, through which users can manipulate cost information in the Oracle Process Manufacturing (OPM) application. The usage of this API will be multifold:

- Help new customers load bulk of item cost, resource cost, burden information, and allocation basis information into OPM from external systems bypassing laborious and error prone manual data entry.
- Enable existing customers to interface OPM with their custom applications.

- Allow a systematic approach to manipulate cost information in OPM without compromising any business rules or database constraints of OPM.

In addition to above, this APIs will also serve as a central place to satisfy the need for insert, update, or delete of cost information records in OPM from any source.

Following are some of the important characteristics that these APIs should have:

Code Re-Use

You should be able to maximize code reuse from all application development tools, including PL/SQL, Oracle Forms and Oracle Reports.

Ease of Integration

You should be able to integrate API's into other applications and enabling technology, such as Oracle Workflow Server, Oracle Internet Commerce & Oracle WebSystem, and Oracle EDI Gateway.

Insulation from Changes

You should be able to encapsulate the structure of schema to prevent changing schema structures from affecting other modules.

Consistent Behavior

You should be able to hide Object logic specific to a module from other modules, and to ensure that this logic is correctly invoked by other modules and customers.

Robust Validation

You should be able to fully validate all incoming information into Oracle Applications.

Major Features

In order to support requirements mentioned in “Basic Business Needs” section, new APIs will be developed supporting following functionality on business object - **Item Cost, Resource Cost, Allocation Definition, and Burden Details:**

Item Cost APIs

Insert Item Cost

This API will be used to insert new Item Cost record in OPM. It will help new customers of OPM load Item Cost information into OPM from external systems.

Update Item Cost

This API will be used to update Item Cost record for an existing Item. Using this API, user can update Item Cost in OPM.

Delete Item Cost

This API will be used to delete Item Cost record in OPM. Using this API, user can delete Item Cost record.

Retrieve Item Cost

This API will be used to retrieve Item Cost information from OPM. Using this API, user can retrieve Item Cost information from OPM to be used by external systems or for any other purpose.

Note: This reflects cost information directly from the cost details tables. This should not be used to reconcile subledger bookings or inventory valuations.

Resource Cost APIs

Insert Resource Cost

This API will be used to insert new Resource Cost record in OPM. It will help new customers of OPM load Resource Cost information into OPM from external systems.

Update Resource Cost

This API will be used to update Resource Cost record for an existing Resource. Using this API, user can update Resource Cost in OPM.

Delete Resource Cost

This API will be used to delete Resource Cost record in OPM. Using this API, user can delete Resource Cost record.

Retrieve Resource Cost

This API will be used to retrieve Resource Cost information from OPM. Using this API, user can retrieve Resource Cost information from OPM to be used by external systems or for any other purpose.

Allocation Definition APIs**Insert Allocation Definition**

This API will be used to insert new Allocation Definition record in OPM. It will help customers of OPM load allocation definition information into OPM from external systems.

Update Allocation Definition

This API will be used to update an existing Allocation Definition record. Using this API, user can update allocation definition in OPM.

Delete Allocation Definition

This API will be used to delete Allocation Definition record in OPM. Using this API, user can delete allocation definition record.

Burden Details APIs**Insert Burden Details**

This API will be used to insert new Burden Details in OPM. It will help new customers of OPM load Burden Details information into OPM from external systems.

Update Burden Details

This API will be used to update Burden Details for an existing item and resource. Using this API, user can update Burden Details in OPM.

Delete Burden Details

This API will be used to delete Burden Details record in OPM. Using this API, user can delete Burden Details record.

Retrieve Burden Details

This API will be used to retrieve Burden Details information from OPM. Using this API, user can retrieve Burden Details information from OPM to be used by external systems or for any other purpose.

Cost Management API Features

- „ Creating Updating and Deleting Information
- „ Proper Encapsulation
- „ Synchronous Processing Following the Business Hierarchy
- „ Detailed and Translatable Error Messages

Cost Management API Support Policy

Cost Management APIs are supported by Oracle. This means:

- „ Oracle will provide objects and libraries needed to use to the APIs and the documentation for their use.
- „ Oracle will ensure that the APIs function as designed.
- „ Oracle will not support customer generated programs that use the APIs.

Oracle Applications Packages Supplied

Cost Management APIs make use of the following standard Oracle Applications packages:

- FND_API - the standard Oracle Applications API version checking function. This is used by the stored procedure to check valid API version number and also contains constant variables such as TRUE and FALSE.
- FND_MESSAGE - the standard Oracle Applications messaging function. This is used by the stored procedure to report status and error handling.
- FND_PUB_MSG - the standard Oracle Applications message retrieval function, used to interrogate the procedure messages.

These packages are installed as part of the current release. Please refer to the *Oracle Applications Coding Standards* manual for additional details.

Cost Management API Bill of Materials

The following is a list of packages and files that are delivered with OPM Cost Management APIs. These must be on your system for your interface to compile and link properly.

Package Name	File Names	Description
GMF_ItemCost_PUB	GMFPCSTS.pls GMFPCSTB.pls	Public Cost Management package that the user defined function calls. The business API can be used for inserting, updating, deleting, or retrieving an item cost.
GMF_ResourceCost_PUB	GMFPRESS.pls GMFPCSTB.pls	Public Cost Management package that the user defined function calls. The business API can be used for inserting, updating, deleting, or retrieving a resource cost.
GMF_AllocationDefinition_PUB	GMFPALCS.pls GMFPCSTB.pls	Public Cost Management package that the user defined function calls. The business API can be used for inserting, updating, or deleting an allocation definition.
GMF_BurdenDetails_PUB	GMFPBRDS.pls GMFPBRDB.pls	Public Cost Management package that the user defined function calls. The business API can be used for inserting, updating, deleting, or retrieving a burden detail.

Cost Management API Usage

The Cost Management APIs are currently written in PL/SQL. To make use of these API's, you must code your interface or wrapper. Your program will also be responsible for connecting to a database before calling an API function. You may also choose to write log files before calling and after returning from an API function. Each function will return an error code in the parameter `x_return_status` which indicates whether the API was successful or failed. The values are as follows:

S - Successful

E - Expected error

U - Unexpected error

Calling the API Interface Code

The following are snippets from a sample wrapper (referred to as wrapper from here on) and are used to test the API code. Wrappers are written in PL/SQL Package. Wrappers can be written for each API and call the APIs directly from these wrappers. The source of data for the wrapper comes from an ASCII flat file. You will probably want to write a similar type of wrapper to call the API code.

These wrappers have following parameters :

`p_dir` IN VARCHAR2 - Working directory for input and output files.

`p_input_file` IN VARCHAR2 - Name of input file i.e., ASCII flat file with data

`p_output_file` IN VARCHAR2 - Name of output file

`p_delimiter` IN VARCHAR2 - Delimiter character

The ASCII flat file must be 'character delimited' (typically, but not necessarily, with a comma).

Calling the API Code - Example

This section details how to call the API code within the wrapper. The purpose of this is to explain how to call a standard OPM Cost Management APIs. Here Item Cost API is taken as an example. The wrapper package consists of a PL/SQL function named 'Create_Item_Cost' which returns VARCHAR2 indicating return status.

It is not critical how the data values get into your customized interface. What is dictated is the order in which those same data values get passed into the standard API calls.

Typically, wrappers goes through following steps for each item:

1. Load the data from the flat file into PL/SQL table or record.
2. Call the Item Cost API for each item.
3. Check the return status.
4. Retrieve the messages from the message stack and write them into a log file.

Wrapper logic

1. Lines 66-69, declares PL/SQL variables to hold the data coming from flat file. These variables gets passed to the public API, so that data type should correspond with the data types specified in the API specification.
2. Lines 125-132, get the first line from the flat file and extract the first value. In our case it is a type of the record. Following are the possible values:
 - 10 : Item Cost Header record
 - 20 : This Level record for the Item
 - 30 : Lower Level record for the Item.
3. Lines 143-261, populate the item details into PL/SQL tables based on the type of record.
4. Lines 263-281, error handling. If error is raised while populating header record then skip all the detail records. If in case of detail record then skip only that detail record and continue populating other detail records.
5. Lines 283-335, get the next line from the file and check type of record. Following scenarios may occur :
 - If the record type is of detail, then continue populating the record.

- If the record type is header record then call the public API for the previous Item Cost Detail already read.
 - If the fetch fails (i.e., end of file is reached - No_Data_Found error), then call the public API for the previous Item Cost Detail already read.
6. Lines 343-373, read all the messages from the message stack and write it into a log file.
 7. Lines 376-383, check the out parameter l_costcmpnt_ids PL/SQL table, if any records are inserted then get the information for what detail records have been inserted.
 8. Lines 385-389, check whether to continue the loop or not. If yes, then start over again from step 2.

API Hints

For performance improvement, NOCOPY hints have been added to the OUT parameters of the APIs. When an API has the same type of parameter defined as IN and OUT, you must pass in different variables. In addition, you must check the return status of the API (generally returned through `x_return_status` parameter) before looking at other OUT variables returned by the API. If the return status is not Success, then you must not use any of the OUT parameters passed back from the API.

For example, the `Get_Resource_Cost` API contains `p_resource_cost_rec` and `x_resource_cost_rec`:

```
PROCEDURE Get_Resource_Cost
( p_api_version IN NUMBER      ,
  p_init_msg_list IN VARCHAR2 := FND_API.G_FALSE ,
  x_return_status OUT NOCOPY VARCHAR2      ,
  x_msg_count OUT NOCOPY NUMBER      ,
  x_msg_data OUT NOCOPY VARCHAR2      ,
  p_resource_cost_rec IN Resource_Cost_Rec_Type ,
  x_resource_cost_rec OUT NOCOPY Resource_Cost_Rec_Type
);
```

Therefore, the call can be set up to read:

```
GMF_RESOURCECOST_PUB.get_resource_cost(
    (p_api_version => l_api_version,
     p_init_msg_list => l_init_msg_list,
     x_return_status => l_return_status,
     x_msg_count => l_msg_count,
     x_msg_data => l_msg_data,
     p_resource_cost_rec => l_resource_cost_rec,
     x_resource_cost_rec => l_resource_cost_rec );
```

In this example, `p_resource_cost_rec` and `x_resource_cost_rec` both have the variable `l_resource_cost_rec`. This gives an incorrect result because both the parameters cannot have the same variable.

You must set the call up so `p_resource_cost_rec` and `x_resource_cost_rec` have different variables:

```
GMF_RESOURCECOST_PUB.get_resource_cost(
    (p_api_version => l_api_version,
     p_init_msg_list => l_init_msg_list,
     x_return_status => l_return_status,
     x_msg_count => l_msg_count,
     x_msg_data => l_msg_data,
```

```
p_resource_cost_rec => l_resource_cost_rec_in,
x_resource_cost_rec => l_resource_cost_rec_out );
```

Item Cost Example

```

1
--+-----+
2  --| FUNCTION NAME
3  --|      Create_Item_Cost
4  --|
5  --| TYPE
6  --|      Public
7  --|
8  --| USAGE
9  --|      Create item Cost
10 --|
11 --| DESCRIPTION
12 --|      This is a PL/SQL wrapper function to call the
13 --|      Create_Item_Cost API.
14 --|      It reads item data from a flat file and outputs any error
15 --|      messages to a second flat file. It also generates a log file
16 --|      called gmf_api_cric_wrapper<session_id>.log in the p_dir directory.
17 --|
18 --| PARAMETERS
19 --|      p_dir          IN VARCHAR2          - Working directory for input
20 --|                                     and output files.
```

```
|
21 --|   p_input_file      IN VARCHAR2      - Name of input file
|
22 --|   p_output_file     IN VARCHAR2      - Name of output file
|
23 --|   p_delimiter       IN VARCHAR2      - Delimiter character
|
24 --|
|
25 --| RETURNS
|
26 --|   VARCHAR2 - 'S' All records processed successfully
|
27 --|                   'E' 1 or more records errored
|
28 --|                   'U' 1 or more record unexpected error
|
29 --|
|
30 --| HISTORY
|
31 --|
|
32
-----+
33 --Api end of comments
34
35 FUNCTION Create_Item_Cost
36 ( p_dir      IN VARCHAR2
37 , p_input_file IN VARCHAR2
38 , p_output_file IN VARCHAR2
39 , p_delimiter IN VARCHAR2
40 )
41 RETURN VARCHAR2
42 IS
43
44 /* Local variables */
45
46 l_status          VARCHAR2(11);
47 l_return_status   VARCHAR2(11) :=FND_API.G_RET_STS_SUCCESS;
48 l_count           NUMBER(10) ;
49 l_record_count    NUMBER(10) :=0;
50 l_loop_cnt        NUMBER(10) :=0;
51 l_dummy_cnt       NUMBER(10) :=0;
52 l_data            VARCHAR2(1000);
```

```
53
54 l_p_dir          VARCHAR2(150);
55 l_output_file    VARCHAR2(120);
56 l_outfile_handle UTL_FILE.FILE_TYPE;
57 l_input_file     VARCHAR2(120);
58 l_infile_handle  UTL_FILE.FILE_TYPE;
59 l_line           VARCHAR2(1000);
60 l_delimiter      VARCHAR(11);
61 l_log_dir        VARCHAR2(150);
62 l_log_name       VARCHAR2(120) := 'gmf_api_cric_wrapper';
63 l_log_handle     UTL_FILE.FILE_TYPE;
64 l_global_file    VARCHAR2(120);
65
66 l_header_rec     GMF_ItemCost_PUB.Header_Rec_Type;
67 l_this_lvl_tbl   GMF_ItemCost_PUB.This_Level_Dtl_Tbl_Type;
68 l_lower_lvl_tbl  GMF_ItemCost_PUB.Lower_Level_Dtl_Tbl_Type;
69 l_costcmpnt_ids  GMF_ItemCost_PUB.costcmpnt_ids_tbl_type;
70 l_idx            NUMBER(10);
71 l_idx1           NUMBER(10);
72 l_type           NUMBER(10);
73 l_continue       VARCHAR2(1) := 'Y' ;
74 l_skip_details   VARCHAR2(1) := 'N' ;
75
76 l_session_id     VARCHAR2(110);
77
78 BEGIN
79
80 /* Enable The Buffer */
81 DBMS_OUTPUT.ENABLE(1000000);
82
83 l_p_dir          :=p_dir;
84 l_input_file     :=p_input_file;
85 l_output_file    :=p_output_file;
86 l_delimiter      :=p_delimiter;
87 l_global_file    :=l_input_file;
88
89 /* Obtain The SessionId To Append To wrapper File Name. */
90
91 l_session_id := USERENV('sessionid');
92
93 l_log_name := CONCAT(l_log_name,l_session_id);
94 l_log_name := CONCAT(l_log_name, '.log');
95
96 /* Directory is now the same same as for the out file */
97 l_log_dir := p_dir;
```

```
98
99
100 /* Open The Wrapper File For Output And The Input File for Input. */
101
102 l_log_handle      :=UTL_FILE.FOPEN(l_log_dir, l_log_name, 'w');
103 l_infile_handle   :=UTL_FILE.FOPEN(l_p_dir, l_input_file, 'r');
104
105 /* Loop thru flat file and call Item Cost API */
106 DBMS_OUTPUT.PUT_LINE('Process Started at ' || to_char(SYSDATE,'DD-MON-YY
HH24:MI:SS'));
107 DBMS_OUTPUT.PUT_LINE('Input Directory ' || l_p_dir );
108 DBMS_OUTPUT.PUT_LINE('Input File      ' || l_input_file );
109 DBMS_OUTPUT.PUT_LINE('Delimiter      ' || l_delimiter );
110 DBMS_OUTPUT.PUT_LINE('Output File     ' || l_output_file );
111
112
113 DBMS_OUTPUT.PUT_LINE('Start Processing');
114 UTL_FILE.PUT_LINE(l_log_handle, 'Process Started at ' || to_
char(SYSDATE,'DD-MON-YY HH24:MI:SS'));
115
116 UTL_FILE.NEW_LINE(l_log_handle);
117 UTL_FILE.PUT_LINE(l_log_handle, 'Input Directory ' || l_p_dir );
118 UTL_FILE.PUT_LINE(l_log_handle, 'Input File      ' || l_input_file );
119 UTL_FILE.PUT_LINE(l_log_handle, 'Record Type     ' || l_delimiter );
120 UTL_FILE.PUT_LINE(l_log_handle, 'Output File     ' || l_output_file );
121
122 l_outfile_handle :=UTL_FILE.FOPEN(l_p_dir, l_output_file, 'w');
123
124 /* Get the first record from the file */
125 BEGIN
126     UTL_FILE.GET_LINE(l_infile_handle, l_line);
127     l_record_count  :=l_record_count+1;
128     l_type          := Get_Field(l_line,l_delimiter,1) ; -- 10 : header rec, 20 :
this level, 30 : lower level
129 EXCEPTION
130     WHEN NO_DATA_FOUND THEN
131         raise;
132 END;
133
134 /* Populate appropriate pl/sql record or table based on the type of record
*/
135 LOOP
136     BEGIN
137
138         UTL_FILE.PUT_LINE(l_log_handle, 'Reading Record...' || l_record_count
```

```

);
139     UTL_FILE.PUT_LINE(l_log_handle, 'Type      = ' || l_type) ;
140
141     /* Header record */
142
143     IF l_type = 10 THEN
144         -- empty the pl/sql tables to remove details of the previous item
145         -- and initialize the index
146         l_this_lvl_tbl.delete ;
147         l_lower_lvl_tbl.delete ;
148         l_costcmpnt_ids.delete;
149         l_skip_details := 'N' ;
150         l_idx := 0 ;
151         l_idx1 := 0 ;
152
153         l_header_rec.calendar_code := Get_Field(l_line,l_delimiter,2) ;
154         l_header_rec.period_code  := Get_Field(l_line,l_delimiter,3) ;
155         l_header_rec.cost_mthd_code := Get_Field(l_line,l_delimiter,4) ;
156         l_header_rec.whse_code     := Get_Field(l_line,l_delimiter,5) ;
157         l_header_rec.item_id       := Get_Field(l_line,l_delimiter,6) ;
158         l_header_rec.item_no       := Get_Field(l_line,l_delimiter,7) ;
159         l_header_rec.user_name     := Get_Field(l_line,l_delimiter,8) ;
160
161         UTL_FILE.PUT_LINE(l_log_handle, 'Type          = ' || l_type) ;
162         UTL_FILE.PUT_LINE(l_log_handle, 'calendar_code = ' || l_header_
rec.calendar_code) ;
163         UTL_FILE.PUT_LINE(l_log_handle, 'period_code  = ' || l_header_
rec.period_code) ;
164         UTL_FILE.PUT_LINE(l_log_handle, 'cost_mthd_code = ' || l_header_
rec.cost_mthd_code) ;
165         UTL_FILE.PUT_LINE(l_log_handle, 'whse_code    = ' || l_header_
rec.whse_code) ;
166         UTL_FILE.PUT_LINE(l_log_handle, 'item_id      = ' || l_header_
rec.item_id) ;
167         UTL_FILE.PUT_LINE(l_log_handle, 'item_no     = ' || l_header_
rec.item_no) ;
168         UTL_FILE.PUT_LINE(l_log_handle, 'user_name    = ' || l_header_
rec.user_name) ;
169
170     /* This Level Detail record. Skip details in case errors in loading
header record */
171     ELSIF l_type = 20 AND l_skip_details = 'Y' THEN
172         UTL_FILE.PUT_LINE(l_log_handle, 'Error : Skipping this record...');
173     ELSIF l_type = 20 AND l_skip_details = 'N' THEN
174         l_idx := l_idx + 1 ;

```

```
175      l_this_lvl_tbl(l_idx).cmpntcost_id      := Get_Field(l_line,l_
delimiter,2) ;
176      l_this_lvl_tbl(l_idx).cost_cmpntcls_id  := Get_Field(l_line,l_
delimiter,3) ;
177      l_this_lvl_tbl(l_idx).cost_cmpntcls_code := Get_Field(l_line,l_
delimiter,4) ;
178      l_this_lvl_tbl(l_idx).cost_analysis_code := Get_Field(l_line,l_
delimiter,5) ;
179      l_this_lvl_tbl(l_idx).cmpnt_cost       := Get_Field(l_line,l_
delimiter,6) ;
180      l_this_lvl_tbl(l_idx).burden_ind       := Get_Field(l_line,l_
delimiter,7) ;
181      l_this_lvl_tbl(l_idx).total_qty       := Get_Field(l_line,l_
delimiter,8) ;
182      l_this_lvl_tbl(l_idx).costcalc_orig   := Get_Field(l_line,l_
delimiter,9) ;
183      l_this_lvl_tbl(l_idx).rmcalc_type     := Get_Field(l_line,l_
delimiter,10) ;
184      l_this_lvl_tbl(l_idx).delete_mark     := Get_Field(l_line,l_
delimiter,11) ;
185      l_this_lvl_tbl(l_idx).attribute1      := Get_Field(l_line,l_
delimiter,12) ;
186      l_this_lvl_tbl(l_idx).attribute2      := Get_Field(l_line,l_
delimiter,13) ;
187      l_this_lvl_tbl(l_idx).attribute3      := Get_Field(l_line,l_
delimiter,14) ;
188      l_this_lvl_tbl(l_idx).attribute4      := Get_Field(l_line,l_
delimiter,15) ;
189      l_this_lvl_tbl(l_idx).attribute5      := Get_Field(l_line,l_
delimiter,16) ;
190      l_this_lvl_tbl(l_idx).attribute6      := Get_Field(l_line,l_
delimiter,17) ;
191      l_this_lvl_tbl(l_idx).attribute7      := Get_Field(l_line,l_
delimiter,18) ;
192      l_this_lvl_tbl(l_idx).attribute8      := Get_Field(l_line,l_
delimiter,19) ;
193      l_this_lvl_tbl(l_idx).attribute9      := Get_Field(l_line,l_
delimiter,20) ;
194      l_this_lvl_tbl(l_idx).attribute10     := Get_Field(l_line,l_
delimiter,21) ;
195      l_this_lvl_tbl(l_idx).attribute11     := Get_Field(l_line,l_
delimiter,22) ;
196      l_this_lvl_tbl(l_idx).attribute12     := Get_Field(l_line,l_
delimiter,23) ;
197      l_this_lvl_tbl(l_idx).attribute13     := Get_Field(l_line,l_
```

```

delimiter,24) ;
198     l_this_lvl_tbl(l_idx).attribute14      := Get_Field(l_line,l_
delimiter,25) ;
199     l_this_lvl_tbl(l_idx).attribute15      := Get_Field(l_line,l_
delimiter,26) ;
200     l_this_lvl_tbl(l_idx).attribute16      := Get_Field(l_line,l_
delimiter,27) ;
201     l_this_lvl_tbl(l_idx).attribute17      := Get_Field(l_line,l_
delimiter,28) ;
202     l_this_lvl_tbl(l_idx).attribute18      := Get_Field(l_line,l_
delimiter,29) ;
203     l_this_lvl_tbl(l_idx).attribute19      := Get_Field(l_line,l_
delimiter,30) ;
204     l_this_lvl_tbl(l_idx).attribute20      := Get_Field(l_line,l_
delimiter,31) ;
205     l_this_lvl_tbl(l_idx).attribute21      := Get_Field(l_line,l_
delimiter,32) ;
206     l_this_lvl_tbl(l_idx).attribute22      := Get_Field(l_line,l_
delimiter,33) ;
207     l_this_lvl_tbl(l_idx).attribute23      := Get_Field(l_line,l_
delimiter,34) ;
208     l_this_lvl_tbl(l_idx).attribute24      := Get_Field(l_line,l_
delimiter,35) ;
209     l_this_lvl_tbl(l_idx).attribute25      := Get_Field(l_line,l_
delimiter,36) ;
210     l_this_lvl_tbl(l_idx).attribute26      := Get_Field(l_line,l_
delimiter,37) ;
211     l_this_lvl_tbl(l_idx).attribute27      := Get_Field(l_line,l_
delimiter,38) ;
212     l_this_lvl_tbl(l_idx).attribute28      := Get_Field(l_line,l_
delimiter,39) ;
213     l_this_lvl_tbl(l_idx).attribute29      := Get_Field(l_line,l_
delimiter,40) ;
214     l_this_lvl_tbl(l_idx).attribute30      := Get_Field(l_line,l_
delimiter,41) ;
215     l_this_lvl_tbl(l_idx).attribute_category := Get_Field(l_line,l_
delimiter,42) ;
216
217     UTL_FILE.PUT_LINE(l_log_handle,'cmpntcost_id('||l_idx||')      = '
||
218     l_this_lvl_tbl(l_idx).cmpntcost_id) ;
219     UTL_FILE.PUT_LINE(l_log_handle,'cost_cmpntcls_id('||l_idx||')  = '
||
220     l_this_lvl_tbl(l_idx).cost_cmpntcls_id) ;
221     UTL_FILE.PUT_LINE(l_log_handle,'cost_cmpntcls_code('||l_idx||') = '||

```

```

222 l_this_lvl_tbl(l_idx).cost_cmpntcls_code) ;
223     UTL_FILE.PUT_LINE(l_log_handle,'cost_analysis_code('||l_idx||') = '||
224 l_this_lvl_tbl(l_idx).cost_analysis_code) ;
225     UTL_FILE.PUT_LINE(l_log_handle,'cmpnt_cost('||l_idx||')           = '
||
226     l_this_lvl_tbl(l_idx).cmpnt_cost) ;
227     UTL_FILE.PUT_LINE(l_log_handle,'burden_ind('||l_idx||')           = '
||
228     l_this_lvl_tbl(l_idx).burden_ind) ;
229     UTL_FILE.PUT_LINE(l_log_handle,'total_qty('||l_idx||')           = '
||
230     l_this_lvl_tbl(l_idx).total_qty) ;
231     UTL_FILE.PUT_LINE(l_log_handle,'costcalc_orig('||l_idx||')       = '
||
232     l_this_lvl_tbl(l_idx).costcalc_orig) ;
233     UTL_FILE.PUT_LINE(l_log_handle,'rmcalc_type('||l_idx||')         = '
||
234     l_this_lvl_tbl(l_idx).rmcalc_type) ;
235     UTL_FILE.PUT_LINE(l_log_handle,'delete_mark('||l_idx||')         = '
||
236     l_this_lvl_tbl(l_idx).delete_mark) ;
237
238     /* Lower Level Detail record. Skip details in case errors in loading
header record */
239     ELSIF l_type = 30 AND l_skip_details = 'Y' THEN
240         UTL_FILE.PUT_LINE(l_log_handle, 'Error : Skipping this record...');
241     ELSIF l_type = 30 AND l_skip_details = 'N' THEN
242         l_idx1 := l_idx1 + 1 ;
243         l_type                                := Get_Field(l_line,l_
delimiter,1) ;
244         l_lower_lvl_tbl(l_idx1).cmpntcost_id    := Get_Field(l_line,l_
delimiter,2) ;
245         l_lower_lvl_tbl(l_idx1).cost_cmpntcls_id := Get_Field(l_line,l_
delimiter,3) ;
246         l_lower_lvl_tbl(l_idx1).cost_cmpntcls_code := Get_Field(l_line,l_
delimiter,4) ;
247         l_lower_lvl_tbl(l_idx1).cost_analysis_code := Get_Field(l_line,l_
delimiter,5) ;
248         l_lower_lvl_tbl(l_idx1).cmpnt_cost      := Get_Field(l_line,l_
delimiter,6) ;
249
250         UTL_FILE.PUT_LINE(l_log_handle,'ll cmpntcost_id('||l_idx1||') =
' ||
251         l_lower_lvl_tbl(l_idx1).cmpntcost_id) ;
252         UTL_FILE.PUT_LINE(l_log_handle,'ll cost_cmpntcls_id('||l_idx1||') =

```

```

' ||
253         l_lower_lvl_tbl(l_idx1).cost_cmpntcls_id)      ;
254         UTL_FILE.PUT_LINE(l_log_handle,'ll cost_cmpntcls_code('||l_idx1||') =
' ||
255         l_lower_lvl_tbl(l_idx1).cost_cmpntcls_code) ;
256         UTL_FILE.PUT_LINE(l_log_handle,'ll cost_analysis_code('||l_idx1||') =
' ||
257         l_lower_lvl_tbl(l_idx1).cost_analysis_code) ;
258         UTL_FILE.PUT_LINE(l_log_handle,'ll cmpnt_cost('||l_idx1||')      =
' ||
259         l_lower_lvl_tbl(l_idx1).cmpnt_cost) ;
260
261     END IF ;
262
263     EXCEPTION
264     WHEN OTHERS THEN
265         /* in case of any errors log the error and continue with the next
record
266         * in case of header, skip all the detail record
267         * in case details, skip that particular record */
268
269         UTL_FILE.PUT_LINE(l_outfile_handle, 'Error : ' || to_char(SQLCODE) || '
' || SQLERRM);
270         UTL_FILE.PUT_LINE(l_log_handle, 'Error : '      || to_char(SQLCODE) || '
' || SQLERRM);
271
272     IF l_type = 10 THEN
273         l_skip_details := 'Y' ;
274         UTL_FILE.PUT_LINE(l_log_handle, 'Error : Skip detail records.');
```

275 ELSIF l_type = 20 THEN

276 l_this_lvl_tbl.delete(l_idx);

277 ELSIF l_type = 30 THEN

278 l_lower_lvl_tbl.delete(l_idx1);

279 END IF ;

280

281 END ;

282

283 BEGIN

284

285 UTL_FILE.GET_LINE(l_infile_handle, l_line);

286 l_record_count :=l_record_count+1;

287 UTL_FILE.NEW_LINE(l_log_handle);

288 l_type := Get_Field(l_line,l_delimiter,1) ; -- 10 : header rec, 20

: this level, 30 : lower level

289

```
290 EXCEPTION
291 /* End of file */
292 WHEN NO_DATA_FOUND THEN
293     IF l_skip_details = 'N' THEN
294
295         GMF_ItemCost_PUB.Create_Item_Cost
296         ( p_api_version      => 1.0
297         , p_init_msg_list    => FND_API.G_TRUE
298         , p_commit           => FND_API.G_TRUE
299
300         , x_return_status    => l_status
301         , x_msg_count        => l_count
302         , x_msg_data         => l_data
303
304         , p_header_rec       => l_header_rec
305         , p_this_level_dtl_tbl => l_this_lvl_tbl
306         , p_lower_level_dtl_Tbl => l_lower_lvl_tbl
307
308         , x_costcmpnt_ids    => l_costcmpnt_ids
309         );
310         l_continue := 'N' ;
311         goto GET_MSG_STACK ;
312     END IF ;
313 END;
314
315 IF (l_type = 10 AND l_record_count != 1 AND l_skip_details = 'N') THEN
316
317     DBMS_OUTPUT.PUT_LINE('Calling Create_Item_Cost API...');
318
319     GMF_ItemCost_PUB.Create_Item_Cost
320     ( p_api_version      => 1.0
321     , p_init_msg_list    => FND_API.G_TRUE
322     , p_commit           => FND_API.G_TRUE
323
324     , x_return_status    => l_status
325     , x_msg_count        => l_count
326     , x_msg_data         => l_data
327
328     , p_header_rec       => l_header_rec
329     , p_this_level_dtl_tbl => l_this_lvl_tbl
330     , p_lower_level_dtl_Tbl => l_lower_lvl_tbl
331
332     , x_costcmpnt_ids    => l_costcmpnt_ids
333     );
334     DBMS_OUTPUT.PUT_LINE('after API call. status := ' || l_status ||' cnt
```

```

:= ' || l_count );
335     END IF;
336
337     <<GET_MSG_STACK>>
338     NULL;
339
340     /* Check if any messages generated. If so then decode and */
341     /* output to error message flat file */
342
343     IF l_count > 0 THEN
344
345         l_loop_cnt :=1;
346         LOOP
347             FND_MSG_PUB.Get(
348                 p_msg_index   => l_loop_cnt,
349                 p_data        => l_data,
350                 p_encoded     => FND_API.G_FALSE,
351                 p_msg_index_out => l_dummy_cnt);
352
353             --DBMS_OUTPUT.PUT_LINE(l_data );
354             UTL_FILE.PUT_LINE(l_log_handle, l_data);
355
356             /* Update error status */
357             IF (l_status = 'U') THEN
358                 l_return_status :=l_status;
359             ELSIF (l_status = 'E' and l_return_status <> 'U') THEN
360                 l_return_status :=l_status;
361             ELSE
362                 l_return_status :=l_status;
363             END IF;
364
365             l_loop_cnt := l_loop_cnt + 1;
366             IF l_loop_cnt > l_count THEN
367                 EXIT;
368             END IF;
369
370         END LOOP; -- msg stack loop
371         l_count := 0 ;
372
373     END IF;-- if count of msg stack > 0
374
375     DBMS_OUTPUT.PUT_LINE('# of CostIds inserted : ' || l_costcmpnt_
ids.count);
376     FOR i in 1..l_costcmpnt_ids.count
377     LOOP

```

```
378     UTL_FILE.PUT_LINE(l_log_handle,
379     'CmpntClsId : '      || l_costcmpnt_ids(i).cost_cmpntcls_id ||
380     ' Analysis Code : ' || l_costcmpnt_ids(i).cost_analysis_code ||
381     ' Cost Level : '    || l_costcmpnt_ids(i).cost_level ||
382     ' CostId : '       || l_costcmpnt_ids(i).cmpntcost_id);
383 END LOOP ;
384
385 IF l_continue = 'N' THEN
386     EXIT ;
387 END IF ;
388
389 END LOOP;
390
391 UTL_FILE.NEW_LINE(l_log_handle);
392 UTL_FILE.PUT_LINE(l_log_handle, 'Process Completed at ' || to_
char(SYSDATE, 'DD-MON-YY HH24:MI:SS'));
393 UTL_FILE.FCLOSE_ALL;
394
395 RETURN l_return_status;
396
397 EXCEPTION
398 WHEN UTL_FILE.INVALID_OPERATION THEN
399     /* DBMS_OUTPUT.PUT_LINE('Invalid Operation For ' || l_global_file); */
400     UTL_FILE.FCLOSE_ALL;
401     RETURN l_return_status;
402
403 WHEN UTL_FILE.INVALID_PATH THEN
404     /* DBMS_OUTPUT.PUT_LINE('Invalid Path For      ' || l_global_file); */
405     UTL_FILE.FCLOSE_ALL;
406     RETURN l_return_status;
407
408 WHEN UTL_FILE.INVALID_MODE THEN
409     /* DBMS_OUTPUT.PUT_LINE('Invalid Mode For      ' || l_global_file); */
410     UTL_FILE.FCLOSE_ALL;
411     RETURN l_return_status;
412
413 WHEN UTL_FILE.INVALID_FILEHANDLE THEN
414     /* DBMS_OUTPUT.PUT_LINE('Invalid File Handle   ' || l_global_file); */
415     UTL_FILE.FCLOSE_ALL;
416     RETURN l_return_status;
417
418 WHEN UTL_FILE.WRITE_ERROR THEN
419     /* DBMS_OUTPUT.PUT_LINE('Invalid Write Error   ' || l_global_file); */
420     UTL_FILE.FCLOSE_ALL;
421     RETURN l_return_status;
```

```

422
423 WHEN UTL_FILE.READ_ERROR THEN
424     /* DBMS_OUTPUT.PUT_LINE('Invalid Read Error ' || l_global_file); */
425     UTL_FILE.FCLOSE_ALL;
426     RETURN l_return_status;
427
428 WHEN UTL_FILE.INTERNAL_ERROR THEN
429     /* DBMS_OUTPUT.PUT_LINE('Internal Error'); */
430     UTL_FILE.FCLOSE_ALL;
431     RETURN l_return_status;
432
433 WHEN OTHERS THEN
434     /* DBMS_OUTPUT.PUT_LINE('Other Error'); */
435     UTL_FILE.PUT_LINE(l_outfile_handle, 'Error : ' || to_char(SQLCODE) || ' '
436     || SQLERRM);
437     UTL_FILE.PUT_LINE(l_log_handle, 'Error : ' || to_char(SQLCODE) || ' ' ||
438     SQLERRM);
439     UTL_FILE.PUT_LINE(l_log_handle, 'Process Completed at ' || to_
440     char(SYSDATE, 'DD-MON-YY HH24:MI:SS'));
441     UTL_FILE.FCLOSE_ALL;
442     l_return_status := 'U' ;
443     RETURN l_return_status;
444
445
446 --+=====+
447 --| FUNCTION NAME
448 --|
449 --|   Get_Field
450 --|
451 --| TYPE
452 --|
453 --|   Public
454 --|
455 --| USAGE
456 --|
457 --|   Get value of field n from a delimited line of ASCII data
458 --|
459 --|

```

```
|
455 --| DESCRIPTION
|
456 --|   This utility function will return the value of a field from
|
457 --|   a delimited line of ASCII text
|
458 --|
|
459 --| PARAMETERS
|
460 --|   p_line           IN VARCHAR2       - line of data
|
461 --|   p_delimiter      IN VARCHAR2       - Delimiter character
|
462 --|   p_field_no      IN NUMBER         - Field occurrence to be
|
463 --|                                     returned
|
464 --|
|
465 --| RETURNS
|
466 --|   VARCHAR2         - Value of field
|
467 --|
|
468 --| HISTORY
|
469 --|
|
470
--+=====+
471 -- Api end of comments
472
473 FUNCTION Get_Field
474 ( p_line           IN VARCHAR2
475 , p_delimiter      IN VARCHAR2
476 , p_field_no      IN NUMBER
477 )
478 RETURN VARCHAR2
479 IS
480
481 /* Local variables */
482 l_start           NUMBER :=0;
```

```

483 l_end          NUMBER :=0;
484
485 BEGIN
486
487 /* Determine start position */
488 IF p_field_no = 1
489 THEN
490   l_start      :=0;
491 ELSE
492   l_start      :=INSTR(p_line,p_delimiter,1,(p_field_no - 1));
493   IF l_start   = 0
494   THEN
495     RETURN NULL;
496   END IF;
497 END IF;
498
499 /* Determine end position */
500 l_end          :=INSTR(p_line,p_delimiter,1,p_field_no);
501 IF l_end      = 0
502 THEN
503   l_end        := LENGTH(p_line) + 1;
504 END IF;
505
506 /* Extract the field data */
507 IF (l_end - l_start) = 1
508 THEN
509   RETURN NULL;
510 ELSE
511   RETURN SUBSTR(p_line,(l_start + 1),((l_end - l_start) - 1));
512 END IF;
513
514 EXCEPTION
515   WHEN OTHERS
516   THEN
517     RETURN NULL;
518
519 END Get_Field;
520
521
522 --+=====+
523 --| FUNCTION NAME
524 --|
525 --|   Get_Substring
526 --|

```

```
|
525 --| TYPE
|
526 --|   Public
|
527 --|
|
528 --| USAGE
|
529 --|   Get value of Sub-string from formatted ASCII data file record
|
530 --|
|
531 --| DESCRIPTION
|
532 --|   This utility function will return the value of a passed sub-string
|
533 --|   of a formatted ASCII data file record
|
534 --|
|
535 --| PARAMETERS
|
536 --|   p_substring          IN VARCHAR2          - substring data
|
537 --|
|
538 --| RETURNS
|
539 --|   VARCHAR2              - Value of field
|
540 --|
|
541 --| HISTORY
|
542 --|
|
543
--+=====+
544 -- Api end of comments
545
546 FUNCTION Get_Substring
547 ( p_substring    IN VARCHAR2
548 )
549 RETURN VARCHAR2
```

```
550 IS
551
552 /* Local variables */
553 l_string_value  VARCHAR2(200)  := ' ';
554
555 BEGIN
556
557 /* Determine start position */
558 l_string_value :=NVL(RTRIM(LTRIM(p_substring)),' ');
559
560 RETURN l_string_value;
561 EXCEPTION
562   WHEN OTHERS
563   THEN
564     RETURN ' ';
565
566 END Get_Substring;
```

Technical Overview

Item Cost

Each function on business object - Item Cost, is associated with a Public API, through which Item Cost details can be created, updated, deleted and retrieved from OPM.

The Public API will perform all validations necessary on input data supplied in order to prevent the flow of invalid data into OPM. In case of any validation errors the API stops the processing and returns an error status without finishing the remaining detail records. During the insert (i.e., after the validations to all detail records) if insert fails for any reason, then all the detail records for the item in process will not be inserted. After finishing validations on input data, public API will perform the required function by calling necessary routines.

According to API standards, the following are the names of file, package and procedures for Public APIs:

Structure for Item Cost Public APIs

Object Type	Name
Package Specification File	GMFPCSTS.pls
Package Body File	GMFPCSTB.pls
Package	GMF_ItemCost_PUB
Procedure - Create Item Cost	Create_Item_Cost
Procedure - Update Item Cost	Update_Item_Cost
Procedure - Delete Item Cost	Delete_Item_Cost

Object Type	Name
Procedure - Get Item Cost	Get_Item_Cost

Resource Cost

Each function on business object - Resource Cost, is associated with a Public API, through which Resource Cost details can be created, updated, deleted and retrieved from OPM.

The Public API will perform all validations necessary on input data supplied in order to prevent the flow of invalid data into OPM. In case of any validation errors that particular row will be skipped and the process will continue with the next Resource Cost record. During the insert (i.e., after the validations to all detail records) if insert fails for any reason, then Resource Cost record in process will not be inserted and process will continue with the next Resource Cost record. After finishing validations on input data, public API will perform the required function by calling necessary routines.

According to API standards, the following are the names of file, package and procedures for Public APIs:

Structure for Resource Cost Public APIs

Object Type	Name
Package Specification File	GMFPRESS.pls
Package Body File	GMFPRESB.pls
Package	GMF_ResourceCost_PUB
Procedure - Create Resource Cost	Create_Resource_Cost
Procedure - Update Resource Cost	Update_Resource_Cost
Procedure - Delete Resource Cost	Delete_Resource_Cost
Procedure - Get Resource Cost	Get_Resource_Cost

Allocation Definition

Each function on business object - Allocation Definition, is associated with a Public API, through which Allocation Definition details can be created, updated, deleted and retrieved from OPM.

The Public API will perform all validations necessary on input data supplied in order to prevent the flow of invalid data into OPM. In case of any validation errors that particular row will be skipped and the process will continue with the next Allocation Definition record. During the insert (i.e., after the validations to all detail records) if insert fails for any reason, then Allocation Definition record in process will not be inserted and process will continue with the next Allocation Definition record. After finishing validations on input data, public API will perform the required function by calling necessary routines.

According to API standards, the following are the names of file, package and procedures for Public APIs:

Structure for Allocation Definition Public APIs

Object Type	Name
Package Specification File	GMFPALCS.pls
Package Body File	GMFPALCB.pls
Package	GMF_AllocationDefinition_PUB
Procedure - Create Allocation Definition	Create_Allocation_Definition
Procedure - Update Allocation Definition	Update_Allocation_Definition
Procedure - Delete Allocation Definition	Delete_Allocation_Definition

Burden Details

Each function on business object - Burden Details, is associated with a Public API, through which Burden Details can be created, updated, deleted and retrieved from OPM.

The Public API will perform all validations necessary on input data supplied in order to prevent the flow of invalid data into OPM. In case of any validation errors the API stops the processing and returns an error status without finishing the remaining detail records. During the insert (i.e., after the validations to all detail records) if insert fails for any reason, then all the Burden Detail records for the item in process will not be inserted. After finishing validations on input data, public API will perform the required function by calling necessary routines.

According to API standards, the following are the names of file, package and procedures for Public APIs:

Structure for Burden Details Public APIs

Object Type	Name
Package Specification File	GMFPBRDS.pls
Package Body File	GMFPBRDB.pls
Package	GMF_BurdenDetails_PUB
Procedure - Create Burden Details	Create_Burden_Details
Procedure - Update Burden Details	Update_Burden_Details
Procedure - Delete Burden Details	Delete_Burden_Details

Standard Parameters

API standard parameters are a collection of parameters that are common to most APIs. The following paragraphs explain the standard parameters that will be used in APIs and their interpretation.

Some of the standard parameters apply to all APIs regardless of the nature of the business function they perform. For example, `p_api_version` and `x_return_status` will be included in all APIs.

On the other hand, some parameters are applicable for certain types of APIs and not applicable for other types. For example, `p_commit` is applicable for APIs that change the database state, and not applicable for read APIs.

Standard parameters will be included in all APIs whenever applicable.

Standard IN parameters:

- `p_api_version`
- `p_init_msg_list`
- `p_commit`
- `p_validation_level`

Standard OUT parameters:

- `x_return_status`
- `x_msg_count`
- `x_msg_data`

Parameter	Type	IN/OUT	Required	Validation
<code>p_api_version</code>	<code>varchar2</code>	IN	Y	Validates version compatibility. The version sent by the calling function is compared to the internal version of the API and an unexpected error (U) is generated if these do not match.
<code>p_init_msg_list</code>	<code>varchar2</code>	IN	N	Used to specify whether the message list should be initialized on entry to the API. It is an optional parameter, and if not supplied will default to <code>FND_API.G_FALSE</code> which means that the API will not initialize the message list.

Parameter	Type	IN/OUT	Required	Validation
p_commit	varchar2	IN	N	Used to specify whether the API should commit its work before returning to the calling function. If not supplied it will default to FND_API.G_FALSE.
x_return_status	varchar2	OUT	-	Specifies whether the API was successful or failed: 'S' Successful 'E' failed due to expected error 'U' failed due to unexpected error
x_msg_count	number	OUT	-	Specifies number of messages added to message list.
x_msg_data	varchar2	OUT	-	Returns the messages in an encoded format. These messages can then be processed by the standard message functions as defined in Business Object API Coding Standards Document.

Value-ID Conversion

IDs are usually used to represent primary and foreign entity keys, they are also used for internal processing of attributes. They are usually not meaningful to users and thus are usually hidden. Besides IDs, attributes may have values that represent them. Those values are usually meaningful to users and thus are used for display purposes. In general, API operates only on IDs.

Example :

An item is represented by an ID which is the NUMBER column ITEM_ID, this ID is its primary key and is used for all internal processing of the item. Besides this ID, an item is represented by a Value which is the VARCHAR2 column ITEM_NO, this value is the one displayed to users when they choose an item, thus an item can be identified by either its ID or its Value (in this case ITEM_NO).

The following set of rules are for the conversion process:

Either ID or Value, or both ID and Value can be passed to an API. But, when both the values are passed, ID based parameters takes precedence over value based parameters, i.e., if both parameters are passed, the value based parameter is ignored and the ID based parameter is used.

When both the Value and ID of an attribute are passed to an API, a message will be generated to inform the API caller that some of his/her input has been ignored.

This message isn't an error message. The API will then continue with its regular processing.

Each value has to resolve into one and only one ID. Failure to resolve a value into an ID (for any reason) is an error and will be associated with an error message. The API will then abort processing and return with a return status of error.

Business Objects

Item Cost

Item Cost specifies cost of a given Item. To understand how it is constructed, let's take an example that Item - A is made up of Item - B and Item - C.

Now, cost of an Item - A = Material Cost of an Item - B + Material Cost of an Item - C + Cost of Manufacturing Item - A from Item - B and Item - C

To better differentiate these costs, business object "Item Cost" is formatted in the following way:

Cost of an Item - A

- This Level Cost Detail (Cost of Manufacturing Item - A)
- Machine Cost, Labor Cost etc.
- Lower Level Cost Detail (Material Cost of an Item - B + Material Cost of an Item - C)
- Material Cost of components.

These means, business object "Item Cost" is made up of 3 entities, namely - Cost Header, This Level Cost Details, and Lower Level Cost Details.

Cost Header entity specifies Calendar, Period, Warehouse, Cost Method, and Item for which cost is defined. This Level Cost Detail entity specifies Cost Component Class and Analysis Code and exact cost in figures. Similarly, Lower Level Cost Detail entity specifies Cost Component Class and Analysis Code and exact cost in figures.

Cost Header Entity

The Cost header entity specifies attributes which identify what this cost information is about at the Parent Level. It specifies the following attributes of business object - Item Cost:

- n Calendar
- n Period
- n Cost Method
- n Warehouse
- n Item

Following is the definition of Header_Rec_Type:

Attribute	Required	Description
Calendar_code	Y	A valid Calendar Code must exist in cm_cldr_mst.
period_code	Y	A valid Period code must exist in cm_cldr_dtl and must not be closed. For UPDATE operation, the period must be open. If the period is open, then allow all the operations. If the period is frozen, only insert is allowed. No updates and deletes are allowed.
cost_mthd_code	Y	A valid Cost Method Code must exist in cm_mthd_mst.
whse_code	Y	A valid Warehouse Code must exist in ic_whse_mst.
item_id	N	Valid Item ID (Either item_id or item_no is required). Item ID/Item No must exist in ic_item_mst.
item_no	N	Valid Item No. (Either item_id or item_no is required). Item ID/Item No must exist in ic_item_mst.
user_name	Y	Valid Oracle Application's user name. User Name must exist in fnd_user.

This Level Cost Detail Entity

“This Level Cost Detail” entity specifies exact cost figure of a given cost component and analysis code. Along with that it also specifies other details which is very specific to OPM. Attributes of This Level Cost Detail entity are:

- Cost Component Class
- Analysis Code
- Component Cost
- Burden Indicator
- Rollover Indicator
- Total Quantity
- Cost Calculation Origin
- Raw Material Calculation Type
- Delete Mark
- Descriptive Flexfield Segment1 to Segment30
- Attribute Category

Following is the definition of This_Level_Dtl_Tbl_Type:

Attribute	Required	Description
cmpntcost_id	N	In case of “Insert”, this will be generated for each new record. Otherwise value supplied in this parameter will be used to locate unique cost detail record.
cost_cmpntcls_id	N	Valid Cost Component Class ID (Either cost_cmpntcls_id or cost_cmpntcls_code is required). Cost Component Class ID/ Cost Component Class Code must exist in cm_cmpnt_mst.
cost_cmpntcls_code	N	Valid Cost Component Class Code (Either cost_cmpntcls_id or cost_cmpntcls_code is required). Cost Component Class ID/ Cost Component Class Code must exist in cm_cmpnt_mst.
cost_analysis_code	Y	Valid Cost Analysis Code. Cost Analysis Code must exist in cm_alys_mst.
cmpnt_cost	Y	Component Cost must be a valid number.

Attribute	Required	Description
burden_ind	Y	Burden Indicator can be either 0 or 1. If Burden Indicator is 1 then Cost Component Class must have usage indicator = 2.
total_qty	N	Total transaction quantity used in calculating actual cost
costcalc_orig	N	This field is only a placeholder and value supplied by API caller will not be considered. For each new record created, this field will be set to 3 to indicate API origin.
Rmcalc_type	N	Raw Material Cost Calculation Type (Applicable only under actual costs, otherwise it is =0 1=PMAC, 2=PWAC, 3=PPAC, 4=LSTT, 5=LSTI)
Delete_mark	Y	Delete Mark must be either 0 or 1. Insert API will ignore the value sent. New records will always be created with Delete Mark set to 0. Record cannot be deleted using Update API (marked for purge), but can be undeleted.
attribute1-30	N	Descriptive Flexfield Segment. Attribute1 through Attribute30 and Attribute Category are optional and can have alphanumeric data.
attribute_category	N	Descriptive Flexfield Segment. Attribute1 through Attribute30 and Attribute Category are optional and can have alphanumeric data.

Lower Level Cost Detail Entity

Lower Level Cost Detail entity specifies exact cost figure of a given cost component and analysis code at lower level. Its attributes are:

- Cost Component Class
- Analysis Code
- Component Cost

Following is the definition of Lower_Level_Dtl_Tbl_Type:

Attribute	Required	Description
cmpntcost_id	N	In case of "Insert", this will be generated for each new record. Otherwise value supplied in this parameter will be used to locate unique cost detail record.
cost_cmpntcls_id	N	Valid Cost Component Class ID (Either cost_cmpntcls_id or cost_cmpntcls_code is required)
cost_cmpntcls_code	N	Valid Cost Component Class Code (Either cost_cmpntcls_id or cost_cmpntcls_code is required)
cost_analysis_code	Y	Valid Cost Analysis Code. Cost Analysis Code must exist in cm_alys_mst.
cmpnt_cost	Y	Component Cost must be a valid number.
delete_mark	Y	Standard 0=Active Record (Default), 1=Marked for (logical) Deletion.

Parameter - x_costcmpnt_ids (OUT)

This is a table type parameter, which has multiple records of newly generated surrogates for cost component records. API Caller will receive this OUT parameter with cost component IDs for each cost record both at this level and lower level. Following table explains how these IDs will be returned:

Attribute	Description
cost_cmpntcls_id	Cost Component Class ID
cost_analysis_code	Cost Analysis Code
cost_level	Cost Level where the record is created 0=This Level, 1=Lower Level
cmpntcost_id	Surrogate generated for combination of Cost Component Class ID+ Cost Analysis Code+Cost Level

Structure and Logic

This section explains structure and logic of public APIs for Item cost.

Package Specification - GMFPCSTS.pls

This file holds definition of all the variables, procedures and functions that will be available to users for use.

```
TYPE header_rec_type IS RECORD
(
  calendar_code      cm_cmpt_dtl.calendar_code%TYPE :=
, period_code       cm_cmpt_dtl.period_code%TYPE :=
, cost_mthd_code    cm_cmpt_dtl.cost_mthd_code%TYPE:=
, whse_code         cm_cmpt_dtl.whse_code%TYPE :=
, item_id           NUMBER :=
, item_no           ic_item_mst.item_no%TYPE :=
, user_name         fnd_user.user_name%TYPE :=
);

TYPE this_level_dtl_rec_type IS RECORD
(
  cmpntcost_id      NUMBER :=
, cost_cmpntcls_id  NUMBER :=
, cost_cmpntcls_code cm_cmpt_mst.cost_cmpntcls_code%TYPE:=
, cost_analysis_code cm_cmpt_dtl.cost_analysis_code%TYPE:=
, cmpnt_cost        NUMBER :=
, burden_ind        NUMBER :=
, total_qty         NUMBER :=
, costcalc_orig     NUMBER :=
, rmcalc_type       NUMBER :=
, delete_mark       NUMBER :=
, attribute1        cm_cmpt_dtl.attribute1%TYPE :=
...
, attribute30       cm_cmpt_dtl.attribute25%TYPE :=
, attribute_category cm_cmpt_dtl.attribute_category%TYPE:=
);

TYPE this_level_dtl_tbl_type IS TABLE OF this_level_dtl_rec_type
INDEX BY BINARY_INTEGER;

TYPE lower_level_dtl_rec_type IS RECORD
(
  cmpntcost_id      NUMBER :=
, cost_cmpntcls_id  NUMBER :=
, cost_cmpntcls_code cm_cmpt_mst.cost_cmpntcls_code%TYPE:=
, cost_analysis_code cm_cmpt_dtl.cost_analysis_code%TYPE:=
, cmpnt_cost        NUMBER :=
, delete_mark       NUMBER :=
);

TYPE lower_level_dtl_tbl_type IS TABLE OF lower_level_dtl_rec_type
INDEX BY BINARY_INTEGER;

TYPE costcmpnt_ids_rec_type IS RECORD
(
  cost_cmpntcls_id  NUMBER :=
, cost_analysis_code cm_cmpt_dtl.cost_analysis_code%TYPE:=
, cost_level        NUMBER :=
```

```

, cmpntcost_id      NUMBER                               :=
);

TYPE costcmpnt_ids_tbl_type IS TABLE OF costcmpnt_ids_rec_type
INDEX BY BINARY_INTEGER;

PROCEDURE Create_Item_Cost
(
  p_api_versionIN  NUMBER ,
  p_init_msg_listIN VARCHAR2 := FND_API.G_FALSE,
  p_commit IN      VARCHAR2 := FND_API.G_FALSE,

  x_return_statusOUT VARCHAR2,
  x_msg_countOUT     VARCHAR2,
  x_msg_dataOUT      VARCHAR2,

  p_header_recIN   Header_Rec_Type,
  p_this_level_dtl_tblIN This_Level_Dtl_Tbl_Type,
  p_lower_level_dtl_tblIN Lower_Level_Dtl_Tbl_Type,

  x_costcmpnt_idsOUT costcmpnt_ids_tbl_type
);

PROCEDURE Update_Item_Cost
(
  p_api_versionIN  NUMBER ,
  p_init_msg_listIN VARCHAR2 := FND_API.G_FALSE,
  p_commit IN      VARCHAR2 := FND_API.G_FALSE,

  x_return_statusOUT VARCHAR2,
  x_msg_countOUT     VARCHAR2,
  x_msg_dataOUT      VARCHAR2,

  p_header_recIN   Header_Rec_Type,
  p_this_level_dtl_tblIN This_Level_Dtl_Tbl_Type,
  p_lower_level_dtl_tblIN Lower_Level_Dtl_Tbl_Type
);

PROCEDURE Delete_Item_Cost
(
  p_api_versionIN  NUMBER ,
  p_init_msg_listIN VARCHAR2 := FND_API.G_FALSE,
  p_commit IN      VARCHAR2 := FND_API.G_FALSE,

  x_return_statusOUT VARCHAR2,
  x_msg_countOUT     VARCHAR2,
  x_msg_dataOUT      VARCHAR2,

  p_header_recIN   Header_Rec_Type,
  p_this_level_dtl_tblIN This_Level_Dtl_Tbl_Type,
  p_lower_level_dtl_tblIN Lower_Level_Dtl_Tbl_Type
);

```

```
);

PROCEDURE Get_Item_Cost
(
  p_api_version IN NUMBER ,
  p_init_msg_list IN VARCHAR2 := FND_API.G_FALSE,

  x_return_status OUT VARCHAR2,
  x_msg_count OUT VARCHAR2,
  x_msg_data OUT VARCHAR2,

  p_header_rec IN Header_Rec_Type,

  x_this_level_dtl_tbl OUT This_Level_Dtl_Tbl_Type,
  x_lower_level_dtl_tbl OUT Lower_Level_Dtl_Tbl_Type

);
```

Public Procedure Create_Item_Cost

Procedure Create_Item_Cost is used to insert component cost details of an Item. API caller needs to supply the data through the following three parameters :

p_header_rec Header level Information for Item Cost record

p_this_level_dtl_tbl This level cost details

p_lower_level_dtl_tbl Lower level cost details

Note: For details on above parameters please refer to the *Structure and Logic* topic in this guide.

The Public API will perform all validations necessary on input data supplied in order to prevent the flow of invalid data into OPM. After finishing validations on input data, public API will insert component cost details by calling necessary routines. API will generate surrogate key - cmpntcost_id for each component cost detail begin inserted. Also, API will return a parameter with cmpntcost_ids for each newly created component cost record.

Note: During validation process, if a detail record fails to go through all the validations then the API stops the processing and returns an error status without finishing the remaining detail records.

During the insert (i.e., after the validations to all detail records) if insert fails for any reason then all the detail records for the item in process will not be inserted. Error message will be given showing the details of the record for which insert failed.

Only one message will be given for number of rows successfully inserted for an Item.

Public Procedure Update_Item_Cost

Procedure Update_Item_Cost is used to update this level component cost of an Item. To update component cost of an item, API caller needs to specify attributes which uniquely classify the individual record to be updated. These attributes will be supplied through following two parameters along with the exact cost which needs to be updated:

p_header_rec Header level Information for Item Cost record

p_this_level_dtl_tbl This level cost details

p_lower_level_dtl_tbl Lower level cost details

Note: For details on above parameters please refer to the *Structure and Logic* topic in this guide.

Here second and third parameter holds surrogate - `cmpntcost_id` for the Item Cost record. If a valid value is supplied for this attribute then it will be used to identify the record to be updated, otherwise system will look at calendar, period, cost method code, warehouse code, and item id in the `p_header_rec` parameter as well as cost component class and analysis code in the `p_this_level_dtl_tbl` parameter to identify which record needs to be updated. Same is true for `p_lower_level_dtl_tbl` records.

Note: During validation process, if a detail record fails to go through all the validations then the API stops the processing and returns an error status without finishing the remaining detail records.

If the record is not found using either `cmpntcost_id` or using unique key then all the records for that item will not be updated. Error message will be given showing the details of the record for which update failed.

Only one message will be given for number of rows successfully updated for an Item.

If any column must be updated to NULL, then you must pass in `FND_API.G_MISS_CHAR`, `FND_API.G_MISS_NUM`, or `FND_API.G_MISS_DATE` variables to the API column values to update the column to NULL in the database.

Public Procedure Delete_Item_Cost

Procedure `Delete_Item_Cost` is used to delete this level component cost of an Item. To delete component cost of an item, API caller needs to specify attributes which uniquely classify the individual record to be deleted. These attributes will be supplied through following two parameters along with the exact cost which needs to be deleted:

`p_header_rec` Header level Information for Item Cost record

`p_this_level_dtl_tbl` This level cost details

`p_lower_level_dtl_tbl` Lower level cost details

Note: For details on above parameters please refer to the *Structure and Logic* topic in this guide.

Here second and third parameter holds surrogate - `cmpntcost_id` for the Item Cost record. If valid value is supplied for this attribute then it will be used to identify the record to be deleted, otherwise system will look at calendar, period, cost method code, warehouse code, and item id in the `p_header_rec` parameter as well as cost component class and analysis code in the `p_this_level_dtl_tbl` parameter to identify which record needs to be deleted. Same is true for `p_lower_level_dtl_tbl`.

Note: During validation process, if a detail record fails to go through all the validations then the API stops the processing and returns an error status without finishing the remaining detail records.

If the record is not found using either `cmpntcost_id` or using unique key then all the records for that item will not be deleted. Error message will be given showing the details of the record for which delete failed.

Only one message will be given for number of rows successfully deleted for an Item.

Public Procedure Get_Item_Cost

Procedure `Get_Item_Cost` is used to retrieve the cost of an Item. To retrieve component costs of an item, API caller needs to specify attributes which uniquely classify which item costs needs to be retrieved. These attributes will be supplied through following parameter:

`p_header_rec` Header level Information for Item Cost record

Note: For details on above parameters please refer to the *Structure and Logic* topic in this guide.

Item Costs will be returned back to caller using following OUT parameters:

`x_this_level_dtl_tbl` This level cost details

`x_lower_level_dtl_tbl` Lower level cost details

Resource Cost

Resource Cost specifies cost of a given resource per unit of usage. This cost will be added to product whenever it uses this resource in its manufacturing. Resource cost is defined for an Organization, for Calendar - Period and for a given Cost Method.

Resource Cost Entity

Resource Cost is fairly simple and it maps to single entity which we will call Resource Cost. Following are the attributes of this entity:

- „ Resource
- „ Organization
- „ Calendar
- „ Period
- „ Cost Method
- „ Usage Unit of Measure
- „ Nominal Cost
- „ Delete Mark

Following is the definition of Resource_Cost_Rec_Type:

Attribute	Required	Description
resources	Y	Valid Resource Code must exist in cr_src_mst
orgn_code	Y	Valid Organization Code must exist in sy_orgn_mst
calendar_code	Y	Valid Calendar Code must exist in cm_cldr_mst.
period_code	Y	Valid Period code must exist in cm_cldr_dtl and must not be closed.
cost_mthd_code	Y	Valid Cost Method Code must exist in cm_mthd_mst
usage_um	Y	Valid Unit of Measure must exist in sy_uoms_mst
nominal_cost	Y	Valid Number must be a number > 0
delete_mark	N	Either 0 or 1. (Default is 0)

Attribute	Required	Description
user_name	Y	Valid Oracle Application's user name. User name must exist in fnd_user

Structure and Logic

This section explains structure and logic of public APIs for Resource Cost.

Package Specification - GMFPRESS.pls

This file holds definition of all the variables, procedures and functions that will be available to users for use.

```

TYPE Resource_Cost_Rec_Type IS RECORD
(
  resources cm_rsrc_dtl.resources%TYPE      := ,
  orgn_code cm_rsrc_dtl.orgn_code%TYPE      := ,
  calendar_code cm_rsrc_dtl.calendar_code%TYPE := ,
  period_code cm_rsrc_dtl.period_code%TYPE  := ,
  cost_mthd_code cm_rsrc_dtl.cost_mthd_code%TYPE := ,
  usage_um cm_rsrc_dtl.usage_um%TYPE        := ,
  nominal_cost NUMBER                       := ,
  delete_mark cm_rsrc_dtl.delete_mark%TYPE  := ,
  user_name fnd_user.user_name%TYPE        :=
);

PROCEDURE Create_Resource_Cost
(
  p_api_version IN NUMBER ,
  p_init_msg_list IN VARCHAR2 := FND_API.G_FALSE,
  p_commit IN VARCHAR2 := FND_API.G_FALSE,

  x_return_status OUT VARCHAR2,
  x_msg_count OUT VARCHAR2,
  x_msg_data OUT VARCHAR2,

  p_resource_cost_rec IN Resource_Cost_Rec_Type
);

PROCEDURE Update_Resource_Cost
(
  p_api_version IN NUMBER ,
  p_init_msg_list IN VARCHAR2 := FND_API.G_FALSE,
  p_commit IN VARCHAR2 := FND_API.G_FALSE,

  x_return_status OUT VARCHAR2,
  x_msg_count OUT VARCHAR2,

```

```
x_msg_dataOUT VARCHAR2,

p_resource_cost_recIN Resource_Cost_Rec_Type
);

PROCEDURE Delete_Resource_Cost
(p_api_versionIN NUMBER ,
p_init_msg_list          IN VARCHAR2 := FND_API.G_FALSE,
p_commitIN VARCHAR2 := FND_API.G_FALSE,

x_return_statusOUT VARCHAR2,
x_msg_countOUT VARCHAR2,
x_msg_dataOUT VARCHAR2,

p_resource_cost_recIN Resource_Cost_Rec_Type
);

PROCEDURE Get_Resource_Cost
(p_api_versionIN NUMBER ,
p_init_msg_list          IN VARCHAR2 := FND_API.G_FALSE,

x_return_statusOUT VARCHAR2,
x_msg_countOUT VARCHAR2,
x_msg_dataOUT VARCHAR2,

p_resource_cost_recIN Resource_Cost_Rec_Type,
x_resource_cost_recOUT Resource_Cost_Rec_Type
);
```

Public Procedure Create_Resource_Cost

Procedure Create_Resource_Cost is used to insert resource cost details of an Item. API caller needs to supply the data through the following parameter :

p_resource_cost_rec Information for Resource Cost record

Note: For details on above parameters please refer to the *Structure and Logic* topic in this guide.

The Public API will perform all validations necessary on input data supplied in order to prevent the flow of invalid data into OPM. After finishing validations on input data, public API will insert resource cost details by calling necessary routines.

Public Procedure Update_Resource_Cost

Procedure Update_Resource_Cost is used to update nominal cost of a resource. To update nominal cost of a resource, API caller needs to specify attributes which uniquely classify the individual record to be updated. These attributes will be supplied through following parameter:

p_resource_cost_rec Information for Resource Cost record

Note: For details on above parameters please refer to the *Structure and Logic* topic in this guide.

If any column must be updated to NULL, then you must pass in FND_API.G_MISS_CHAR, FND_API.G_MISS_NUM, or FND_API.G_MISS_DATE variables to the API column values to update the column to NULL in the database.

Public Procedure Delete_Resource_Cost

Procedure Delete_Resource_Cost is used to delete a particular Resource Cost record from OPM. To delete Resource Cost record, API caller needs to specify attributes which uniquely classify the individual record to be deleted. These attributes will be supplied through following parameters:

p_resource_cost_rec Information for Resource Cost record

Note: For details on above parameters please refer to the *Structure and Logic* topic in this guide.

Public Procedure Get_Resource_Cost

Procedure Get_Resource_Cost is used to retrieve the cost of a Resource. To retrieve Resource Cost information, API caller needs to specify attributes which uniquely classify which Resource costs needs to be retrieved. These attributes will be supplied through following parameters:

p_resource_cost_rec Information for Resource Cost record

Note: For details on above parameters please refer to the *Structure and Logic* topic in this guide.

Resource Costs will be returned back to caller using following OUT parameters:

`x_resource_cost_rec` Information for Resource Cost record

Allocation Definition

Allocation Definition specifies information for an allocation code about the items to which expenses will be allocated, the allocation criteria based upon the basis account or fixed percent, and the cost component class bucket to which the allocated cost will go.

Allocation Definition Entity

Allocation Definition is fairly simple and it maps to single entity which we will call Allocation Definition. Following are the attributes of this entity:

- n Allocation Code
- n Allocation Method
- n Item No
- n Basis Account Key
- n Balance Type
- n Basis YTD PTD
- n Fixed Percent
- n Cost Component Class
- n Analysis Code
- n Warehouse Code
- n Delete Mark

Following is the definition of Allocation_Def_Rec_Type:

Attribute	Required	Description
alloc_id	Y	Surrogate for Allocation Code (Either alloc_id OR co_code + alloc_code is required.)
co_code	Y	Valid Company Code (Either alloc_id OR co_code + alloc_code is required.)
alloc_code	Y	Valid Allocation Code (Either alloc_id OR co_code + alloc_code is required.)
alloc_method	Y	Valid Allocation Method (Either 0 or 1)

Attribute	Required	Description
line_no	N	Surrogate for detail record. Only used in case of Update operation.
item_id	Y	Surrogate for Item No. (At least one of these two parameters is required.)
item_no	Y	valid Item No. (At least one of these two parameters is required.)
Basis_account_key	Y	A valid Basis Account Key (Used only when Allocation Method = 0).
balance_type	Y	Balance Type must be 0 = Statistical; 1 = Budget; or 2 = Actual. (Used only when Allocation Method = 0).
bas_ytd_ptd	Y	Basis YTP/PTD must be either 0 = Period To Date Basis Amount or 1 = Year To Date Basis Amount. (Used only when Allocation Method = 0).
fixed_percent	Y	Fixed percentage must be a valid number between 1 and 100 (Used only when Allocation Method = 1).
cmpntcls_id	Y	Surrogate for Cost Component Class (At least one of these two parameters is required.)
cost_cmpntcls_code	Y	Valid Cost Component Class (At least one of these two parameters is required.)
analysis_code	Y	Valid Analysis Code must exist in cm_alys_mst
whse_code	Y	Valid Warehouse Code must exists in ic_whse_mst
delete_mark	N	Either 0 or 1. (Default is 0)
user_name	Y	Valid Oracle Application's user name. User name must exists in fnd_user.

Structure and Logic

This section explains structure and logic of public APIs for Allocation Definition.

Package Specification - GMFPALCS.pls

This file holds definition of all the variables, procedures and functions that will be available to users for use.

```

TYPE Allocation_Definition_Rec_Type IS RECORD
(
  alloc_id          NUMBER                := ,
  alloc_code        gl_alloc_mst.alloc_code%TYPE := ,
  co_code           sy_orgn_mst.co_code%TYPE := ,
  alloc_method      NUMBER                := ,
  line_no           NUMBER                := ,
  item_id           NUMBER                := ,
  item_no           ic_item_mst.item_no%TYPE := ,
  basis_account_key gl_alloc_bas.basis_account_key%TYPE := ,
  balance_type      NUMBER                := ,
  bas_ytd_ptd       NUMBER                := ,
  fixed_percent     NUMBER                := ,
  cmpntcls_id       NUMBER                := ,
  cost_cmpntcls_code cm_cmpt_mst.cost_cmpntcls_code%TYPE := ,
  analysis_code     cm_alys_mst.cost_analysis_code%TYPE := ,
  whse_code         gl_alloc_bas.whse_code%TYPE := ,
  delete_mark       gl_alloc_bas.delete_mark%TYPE := ,
  user_name         fnd_user.user_name%TYPE :=
);

PROCEDURE Create_Allocation_Definition
(
  p_api_version IN NUMBER ,
  p_init_msg_list IN VARCHAR2 := FND_API.G_FALSE,
  p_commit IN VARCHAR2 := FND_API.G_FALSE,

  x_return_status OUT VARCHAR2,
  x_msg_count OUT VARCHAR2,
  x_msg_data OUT VARCHAR2,

  p_allocation_definition_rec IN Allocation_Definition_Rec_Type
);

PROCEDURE Update_Allocation_Definition
(
  p_api_version IN NUMBER ,
  p_init_msg_list IN VARCHAR2 := FND_API.G_FALSE,
  p_commit IN VARCHAR2 := FND_API.G_FALSE,

  x_return_status OUT VARCHAR2,
  x_msg_count OUT VARCHAR2,

```

```
x_msg_dataOUT VARCHAR2,  
  
p_allocation_definition_rec      IN Allocation_Definition_Rec_Type  
);  
  
PROCEDURE Delete_Allocation_Definition  
(  
    p_api_versionIN  NUMBER ,  
    p_init_msg_list  IN  VARCHAR2 := FND_API.G_FALSE,  
    p_commit IN  VARCHAR2 := FND_API.G_FALSE,  
  
    x_return_statusOUT VARCHAR2,  
    x_msg_countOUT VARCHAR2,  
    x_msg_dataOUT VARCHAR2,  
  
    p_allocation_definition_rec      IN Allocation_Definition_Rec_Type  
);
```

Public Procedure Create_Allocation_Definition

Procedure `Create_Allocation_Definition` is used to insert Allocation definition details. API caller needs to supply the data through the following parameter :

p_allocation_definition_rec Information for Allocation Definition record

Note: For details on above parameters please refer to the *Structure and Logic* topic in this guide.

The Public API will perform all validations necessary on input data supplied in order to prevent the flow of invalid data into OPM. After finishing validations on input data, public API will insert Allocation definition details by calling necessary routines.

Public Procedure Update_Allocation_Definition

Procedure `Update_Allocation_Definition` is used to update existing allocation definition record in OPM. To update allocation definition, API caller needs to specify attributes which uniquely classify the individual record to be updated. These attributes will be supplied through following parameter:

p_allocation_definition_rec Information for Allocation Definition record

Note: For details on above parameters please refer to the *Structure and Logic* topic in this guide.

Following are the attributes which will be used to uniquely identify which record needs to be updated:

- ALLOC_ID or ALLOC_CODE + CO_CODE
- LINE_NO

If any column must be updated to NULL, then you must pass in FND_API.G_MISS_CHAR, FND_API.G_MISS_NUM, or FND_API.G_MISS_DATE variables to the API column values to update the column to NULL in the database.

Public Procedure Delete_Allocation_Definition

Procedure Delete_Allocation_Definition is used to delete a particular Allocation Definition record from OPM. To delete Allocation Definition record, API caller needs to specify attributes which uniquely classify the individual record to be deleted. These attributes will be supplied through following parameters:

p_allocation_definition_rec Information for Allocation Definition record

Note: For details on above parameters please refer to the *Structure and Logic* topic in this guide.

Following are the attributes which will be used to uniquely identify which record needs to be deleted:

- ALLOC_ID or ALLOC_CODE + CO_CODE
- LINE_NO

Burden Details

Burden Details is used to setup and maintain standard resource burdens. A burden is a cost associated with a resource other than the resource usage assigned in the routing. Burden Cost will be added to the product cost whenever it uses the resource with which burden is associated. Burden is defined for an item, Organization, Warehouse, for Calendar - Period and for a given Cost Method.

Header Entity

Burden Details Header entity specifies attributes which identify what this burden details information is about at Parent Level. It specifies following attributes of business object - Burden Details:

- Organization
- Item
- Warehouse
- Calendar
- Period
- Cost Method

Following is the definition of Header_Rec_Type:

Attribute	Required	Description
orgn_code	Y	Valid Organization Code must exist in sy_orgn_mst
item_id	N	Valid Item ID must exist in ic_item_mst (Either item_id or item_no is required)
item_no	N	Valid Item No. must exist in ic_item_mst (Either item_id or item_no is required)
whse_code	Y	Valid Warehouse Code must exist in ic_whse_mst
Calendar_code	Y	Valid Calendar Code must exist in cm_cldr_mst
period_code	Y	Valid Period Code must exist in cm_cldr_dtl
cost_mthd_code	Y	Valid Cost Method Code must exist in cm_mthd_mst
user_name	Y	Valid Oracle Application's user name. User Name must exist in fnd_user.

Detail Entity

Detail Entity specifies exact resource with which burden will be associated along with component, analysis code, Burden Usage, Item Quantity and Item UOM. Along with that it also specifies lot other details which is very specific to OPM. Attributes of Burden Details - Detail Entity entity are:

- Resource
- Cost Component Class
- Analysis Code
- Burden Usage
- Item Quantity
- Item UOM
- Burden Quantity
- Burden UOM
- Base Currency Code
- Delete Mark

Following is the definition of This_Level_Dtl_Tbl_Type:

Attribute	Required	Description
burdenline_id	N	In case of "Insert", this will be generated for each new record. Otherwise value supplied in this parameter will be used to locate unique burden detail record.
resources	Y	Valid Resource Code must exist in cr_rsrc_mst
cost_cmpntcls_id	N	Cost Component Class ID/ Cost Component Class Code must exist in cm_cmpt_mst and must have usage indicator = 2 (Burden/Overhead).
cost_cmpntcls_code	N	Cost Component Class ID/ Cost Component Class Code must exist in cm_cmpt_mst and must have usage indicator = 2 (Burden/Overhead).
cost_analysis_code	Y	Valid Cost Analysis Code must exist in cm_alys_mst.
burden_usage	Y	Valid Number between 0.000000001 and 999999999.999999999

Attribute	Required	Description
item_qty	Y	Valid Number between 0.000000001 and 999999999.999999999
item_um	Y	Item UOM must be a valid Unit of Measure. Since this Item UOM can be any UOM, conversion factor should exist for this UOM and items actual UOM.
burden_qty	Y	Valid Number between 0.000000001 and 999999999.999999999
burden_um	Y	Burden UOM must be a valid Unit of Measure and Burden UOM type should be same as Resource UOM Type.
Delete_mark	Y	Delete Mark must be either 0 or 1. Insert API will ignore the value sent. New records will always be created with Delete Mark set to 0. Record cannot be deleted using Update API (marked for purge), but can be undeleted.

Parameter - x_burdenline_ids (OUT)

This is a table type parameter, which is having multiple records of newly generated surrogates for burden detail records. API Caller will receive this OUT parameter with BurdenLine IDs for each Burden Detail record. Following table explains how these IDs will be returned:

Attribute	Description
Resources	Resource used for the burden cost
cost_cmpntcls_id	Cost Component Class ID
cost_analysis_code	Cost Analysis Code
burdenline_id	Surrogate generated for combination of Resource+Cost Component Class ID+ Cost Analysis Code

Structure and Logic

This section explains structure and logic of public APIs for Burden Details.

Package Specification - GMFPBRDS.pls

This file holds definition of all the variables, procedures and functions that will be available to users for use.

```

TYPE Burden_Header_Rec_Type IS RECORD
(
  orgn_code      sy_orgn_mst.orgn_code%TYPE      := ,
  item_id        NUMBER                          := ,
  item_no        ic_item_mst.item_no%TYPE        := ,
  whse_code      cm_brdn_dtl.whse_code%TYPE      := ,
  calendar_code  cm_brdn_dtl.calendar_code%TYPE := ,
  period_code    cm_brdn_dtl.period_code%TYPE    := ,
  cost_mthd_code cm_brdn_dtl.cost_mthd_code%TYPE := ,
  user_name      fnd_user.user_name%TYPE        :=
);

TYPE Burden_Dtl_Rec_Type IS RECORD
(
  burdenline_id  NUMBER                          := ,
  resources       cr_rsrc_mst.resources%TYPE     := ,
  cost_cmpntcls_id NUMBER                        := ,
  cost_cmpntcls_codecm_cmpntcls_code%TYPE:=,
  cost_analysis_code cm_alys_mst.cost_analysis_code%TYPE:=,
  burden_usage   NUMBER                          := ,
  item_qty       NUMBER                          := ,
  item_um        cm_brdn_dtl.item_um%TYPE        := ,
  burden_qty     NUMBER                          := ,
  burden_um      cm_brdn_dtl.item_um%TYPE        := ,
  burden_factor  NUMBER                          := ,
  delete_mark    cm_brdn_dtl.delete_mark%TYPE    :=
);

TYPE Burden_Dtl_Tbl_Type IS TABLE OF Burden_Dtl_Rec_Type
INDEX BY BINARY_INTEGER;

TYPE Burdenline_Ids_Rec_Type IS RECORD
(
  resources       cm_rsrc_dtl.resources%TYPE     := ,
  cost_cmpntcls_id NUMBER                        := ,
  cost_analysis_code cm_brdn_dtl.cost_analysis_code%TYPE:=,
  burdenline_id  NUMBER                          :=
);

TYPE Burdenline_Ids_Tbl_Type IS TABLE OF Burdenline_Ids_Rec_Type

```

```

                                INDEX BY BINARY_INTEGER;
PROCEDURE Create_Burden_Details
(
    p_api_versionIN  NUMBER ,
    p_init_msg_list  IN  VARCHAR2 := FND_API.G_FALSE,
    p_commitIN  VARCHAR2 := FND_API.G_FALSE,

    x_return_statusOUT VARCHAR2,
    x_msg_countOUT VARCHAR2,
    x_msg_dataOUT VARCHAR2,

    p_header_recIN  Burden_Header_Rec_Type,
    p_dtl_tblIN  Burden_Dtl_Tbl_Type,

    x_burdenline_idsIN  Burdenline_Ids_Tbl_Type
);

PROCEDURE Update_Burden_Details
(
    p_api_versionIN  NUMBER ,
    p_init_msg_list  IN  VARCHAR2 := FND_API.G_FALSE,
    p_commitIN  VARCHAR2 := FND_API.G_FALSE,

    x_return_statusOUT VARCHAR2,
    x_msg_countOUT VARCHAR2,
    x_msg_dataOUT VARCHAR2,

    p_header_recIN  Burden_Header_Rec_Type,
    p_dtl_tblIN  Burden_Dtl_Tbl_Type,
);

PROCEDURE Delete_Burden_Details
(
    p_api_versionIN  NUMBER ,
    p_init_msg_list  IN  VARCHAR2 := FND_API.G_FALSE,
    p_commitIN  VARCHAR2 := FND_API.G_FALSE,

    x_return_statusOUT VARCHAR2,
    x_msg_countOUT VARCHAR2,
    x_msg_dataOUT VARCHAR2,

    p_header_recIN  Burden_Header_Rec_Type,
    p_dtl_tblIN  Burden_Dtl_Tbl_Type,
);

PROCEDURE Get_Item_Cost
(
    p_api_versionIN  NUMBER ,
    p_init_msg_list  IN  VARCHAR2 := FND_API.G_FALSE,

```

```
x_return_statusOUT VARCHAR2,  
x_msg_countOUT VARCHAR2,  
x_msg_dataOUT VARCHAR2,  
  
p_header_recIN Burden_Header_Rec_Type,  
  
x_dtl_tblOUT Burden_Dtl_Tbl_Type  
);
```

Public Procedure Create_Burden_Details

Procedure Create_Burden_Details is used to insert standard resource burdens. API caller needs to supply the data through the following parameter:

p_header_rec Header level Information for Burden Details record

p_dtl_tbl Detail level Information for Burden Details record

Note: For details on above parameters please refer to the *Structure and Logic* topic in this guide.

The Public API will perform all validations necessary on input data supplied in order to prevent the flow of invalid data into OPM. After finishing validations on input data, public API will insert burden details by calling necessary routines. API will generate surrogate key - `burdenline_id` for each burden details row begin inserted. Also, API will return a parameter with `burdenline_ids` for each newly created burden detail record.

Note: During validation process, if a detail record fails to go through all the validations then the API stops the processing and returns an error status without finishing the remaining detail records.

During the insert (i.e., after the validations to all detail records) if insert fails for any reason then all the detail records for the item in process will not be inserted. Error message will be given showing the details of the record for which insert failed.

Only one message will be given for number of rows successfully inserted for an Item.

Public Procedure Update_Burden_Details

Procedure Update_Burden_Details is used to update this level component cost of an Item. To update component cost of an item, API caller needs to specify attributes which uniquely classify the individual record to be updated. These attributes will be supplied through following two parameters along with the other details which needs to be updated:

p_header_rec Header level Information for Burden Details record

p_dtl_tbl Detail level Information for Burden Details record

Note: For details on above parameters please refer to the *Structure and Logic* topic in this guide.

Here second parameter holds surrogate - `burdenline_ids` for the Burden Cost record. If valid value is supplied for this attribute then it will be used to identify the record to be updated, otherwise system will look at Organization, Item, Warehouse, Calendar, Period and cost method code in the `p_header_rec` parameter as well as Resources, Cost Component Class and Analysis Code in the `p_dtl_tbl` parameter to identify which record needs to be updated.

Note: During validation process, if a detail record fails to go through all the validations then the API stops the processing and returns an error status without finishing the remaining detail records.

If the record is not found using either `cmpntcost_id` or using unique key then all the records for that item will not be updated. Error message will be given showing the details of the record for which update failed.

Only one message will be given for number of rows successfully updated.

If any column must be updated to NULL, then you must pass in `FND_API.G_MISS_CHAR`, `FND_API.G_MISS_NUM`, or `FND_API.G_MISS_DATE` variables to the API column values to update the column to NULL in the database.

Public Procedure Delete_Burden_Details

Procedure `Delete_Burden_Details` is used to delete burden details. To delete burden details, API caller needs to specify attributes which uniquely classify the individual record to be deleted. These attributes will be supplied through following two parameters along with the exact cost which needs to be deleted:

`p_header_rec` Header level Information for Burden Details record

`p_dtl_tbl` Detail level Information for Burden Details record

Note: For details on above parameters please refer to the *Structure and Logic* topic in this guide.

Here second parameter holds surrogate - `burdenline_id` for the burden details record. If valid value is supplied for this attribute then it will be used to identify the record to be deleted, otherwise system will look at organization, item, warehouse, calendar, period, and cost method code in the `p_header_rec` parameter as well as resources, cost component class and analysis code in the `p_dtl_tbl` parameter to identify which record needs to be deleted.

Note: During validation process, if a detail record fails to go through all the validations then only that particular detail record will be skipped/eliminated and process will continue with the next detail record.

If the record is not found using either `cmpntcost_id` or using unique key then all the records for that item will not be deleted. Error message will be given showing the details of the record for which delete failed.

Only one message will be given for number of rows successfully deleted.

Public Procedure Get_Burden_Details

Procedure `Get_Burden_Details` is used to retrieve burden details. To retrieve burden details, API caller needs to specify attributes which uniquely classify which burden details needs to be retrieved. These attributes will be supplied through following parameter:

`p_header_rec` Header level Information for Burden Details record

Note: For details on above parameters please refer to the *Structure and Logic* topic in this guide.

Burden Details will be returned back to caller using following OUT parameters:

`x_dtl_tbl` Burden details

Messages and Errors

This appendix covers:

- Handling Messages
- Interpreting Error Conditions
- Understanding Error Messages

Handling Messages

APIs put result messages into a message list. Programs calling APIs can then get the messages from the list and process them by either issuing them, loading them in a database table or writing them to a log file.

Messages are stored in an encoded format to enable API callers to find out message names by using the standard functions provided by the message dictionary. It also allows storing these messages in database tables and reporting off these tables in different languages.

The structure of the message list is not public. Neither API developers nor API callers can access this list except through calling the API message utility routines mentioned below.

The following utility functions are defined in the FND_MSG_PUB package, in the file AFASMSG.S.pls:

Initialize Initializes the API message list.

Add Adds a message to the API message list.

Get Gets a message from the API message list.

Count_Msg Returns the number of messages in the API message list.

Delete Deletes one or more messages from the API message list.

Reset Resets the index used in getting messages.

Count_And_Get Returns the number of messages in the API message list. If this number is one, it also returns the message data.

Refer to the documentation of these functions and procedures for usage information.

To add a message to the API message list, developers should use the regular message dictionary procedures `FND_MESSAGE.SET_NAME` and `FND_MESSAGE.SET_TOKEN` to set the message name and tokens on the message dictionary stack. They should then call `FND_MSG_PUB.Add` to fetch the messages off the message dictionary stack and add it to the API message list.

To get a message from the API message list, API callers should use the procedure `FND_MSG_PUB.Get`. This procedure operates in 5 different modes:

First Gets the first message in the API message list

Next Gets the next message in the API message list

Last Gets the last message in the API message list

Previous Gets the previous message in the API message list

Specific Gets a specific message from the API message list

For the sake of performance and reduction of the overall number of calls a program needs to make in order to execute an API. It is recommended that APIs provide their callers with the following information:

- message count
- message data

The message count holds the number of messages in the API message list. If this number is one, then message data holds the message in an encoded format.

<code>x_msg_count</code>	OUT	NUMBER
<code>x_msg_data</code>	OUT	TVARCHAR2

Example:

```

PROCEDURE Create_OrderLine
( p_api_version          INNUMBER,
  p_init_msg_listINVARCHAR2 := FND_API.G_FALSE,
p_commit      IN VARCHAR2 := FND_API.G_FALSE,
p_validation_levelIN NUMBER:=
FND_API.G_VALID_LEVEL_FULL,

x_return_statusOUTVARCHAR2 ,
x_msg_countOUTNUMBER,
x_msg_dataOUTVARCHAR2 ,

p_line_recINLine_Rec_Type
)
IS
l_api_version          CONSTANT NUMBER := 1.0;
l_api_name      CONSTANT VARCHAR2(30):= 'Create_OrderLine';
BEGIN
-- Standard begin of API savepoint
SAVEPOINTCreate_Line_PUB;
-- Standard call to check for call compatibility.
IF NOT FND_API.Compatible_API_Call ( l_api_version
                                     p_api_version
                                     l_api_name
                                     G_PKG_NAME
                                   )
THEN
RAISE FND_API.G_EXC_UNEXPECTED_ERROR;
END IF;
-- Check p_init_msg_list
IF FND_API.to_Boolean( p_init_msg_list ) THEN
FND_MSG_PUB.initialize;
END IF;
-- Initialize API return status to success
x_return_status := FND_API.G_RET_STS_SUCCESS;

Validate_Line
(l_return_status,
l_line_rec
);

Price_Line
(l_return_status,
l_line_rec
);

Insert_Line

```

```
(l_return_status,  
l_line_rec  
);  
  
IF FND_API.To_Boolean( p_commit ) THEN  
COMMIT WORK;  
END IF;  
-- Get message count and if 1, return message data.  
FND_MSG_PUB.Count_And_Get  
  ( p_count          =>      x_msg_count      ,  
    p_data           =>      x_msg_data      )  
);  
  
END Create_Line ;
```

Interpreting Error Conditions

The parameter `x_return_status` indicates whether the API was successful or failed. The values are as follows:

- S - Successful
- E - Expected error
- U - Unexpected error

Understanding Error Messages

These error messages will be output to the stored procedure message file, and can be monitored through the return `x_msg_count`. In conjunction with the `x_return_status`, this can be used to monitor the success or failure of the procedure call.

Displaying Errors in Languages Other than English

Language translation of error messages is determined by the environment variable `NLS_LANGUAGE`. If the message is not found in the required language, then the message will be retrieved in US English.

The following is a complete listing of Cost Management API Error Messages. Note that a message that is preceded with `Warning` is not a fatal API error, just a warning, and a message preceded with `Error` is a fatal API error.

Any uppercase word preceded by an ampersand (&) is a token, or placeholder, for an actual value that will be populated at runtime.

Message Name	Message Code
Error: Burden Details delete failed for Resource &RESOURCE, Component Class Id &CMPNTCLS_ID and Analysis Code &ALYS_CODE.	GMF_API_BRDN_DEL_FAILED_DTLS
Error: Either Allocation Id or combination of Allocation Code and Company Code is required.	GMF_API_ALLOC_DTL_REQ
Error: Allocation Method is required.	GMF_API_ALLOC_MTHD_REQ
Allocation Header. Allocation Id: &ALLOCATION_ID Allocation Code: &ALLOCATION_CODE Company: &COMPANY Item Id: &ITEM_ID Item No: &ITEM_NO Component Class Id: &CMPNT_CLASS_ID Component Class Id: &CMPNT_CLASS_CODE	GMF_API_ALLOCATION_HEADER
Error: Analysis Code is required.	GMF_API_ANALYSIS_CODE_REQ
Error: Balance Type is required.	GMF_API_BALANCE_TYPE_REQ
Error: Basis Account Key is required.	GMF_API_BAS_ACC_KEY_REQ
Error: YTD/PTD indicator for balance is required.	GMF_API_BAS_YTD_PTD_REQ
Error: Burden Details delete failed for Burden line Id &BURDENLINE_ID.	GMF_API_BRDN_DEL_FAILED_ID
Burden details not found for Resource &RESOURCE, Component Class Code &CMPNTCLS_CODE, Component Class Id &CMPNTCLS_ID, and Analysis Code &ALYS_CODE.	GMF_API_BRDN_DTL_NOT_FOUND
Error: Burden Details insert failed for Resource &RESOURCE, Component Class Id &CMPNTCLS_ID and Analysis Code &ALYS_CODE.	GMF_API_BRDN_INSERT_FAILED
Error: No Burden Details found to update for Resource &RESOURCE, Component Class Id &CMPNTCLS_ID and Analysis Code &ALYS_CODE.	GMF_API_BRDN_NOT_FOUND_FOR_DTL
Error: No Burden Details found to update for Burden Line Id &BURDENLINE_ID.	GMF_API_BRDN_NOT_FOUND_FOR_ID

Message Name	Message Code
UOM Conversion failed for resource &RESOURCES from Burden UOM &BURDEN_UM to Resource UOM &BURDEN_UM.	GMF_API_BRDN_UM_CONV_ERR
Error: Burden Details update failed for Resource &RESOURCE, Component Class Id &CMPNTCLS_ID and Analysis Code &ALYS_CODE.	GMF_API_BRDN_UPD_FAILED_DTLS
Error: Burden Details update failed for Burden line Id &BURDENLINE_ID.	GMF_API_BRDN_UPD_FAILED_ID
Burden Details Header. Organization: &ORGN Item Id: &ITEM_ID Item No: &ITEM_NO Warehouse: &WHSE Calendar: &CALENDAR Period: &PERIOD Cost Method: &COST_METHOD.	GMF_API_BURDEN_HEADER
Error: Burden Indicator is required.	GMF_API_BURDEN_IND_REQ
Error: Burden Quantity is required.	GMF_API_BURDEN_QTY_REQ
Error: Burden UOM is required.	GMF_API_BURDEN_UM_REQ
Error: Burden Indicator supplied is &BURDEN_IND, but Usage of the Cost Component Class &CMPNT_CLS is not burden detail.	GMF_API_BURDEN_USAGE_IND
Error: Burden Usage is required.	GMF_API_BURDEN_USAGE_REQ
Error: Calendar Code is required.	GMF_API_CALENDAR_CODE_REQ
Error: Record cannot be marked for purge using Update API.	GMF_API_CANT_MARK_FOR_PURGE
Error: Period &PERIOD_CODE for Calendar &CALENDAR_CODE is Closed.	GMF_API_CLOSED_PERIOD
Error: Component Cost is required.	GMF_API_CMPNT_COST_REQ
Error: Either Component Class Id or Component Class Code is required.	GMF_API_CMPNTCLS_ID_REQ
Error: Usage of Component Class &CMPNTCLS is not GL Expense Allocation.	GMF_API_CMPNTCLS_USG_NOT_ALC
Error: Usage of Component Class &CMPNTCLS_ID is not Burden (Overhead).	GMF_API_CMPNTCLS_USG_NOT_BRDN
Error: Cost Method Code is required.	GMF_API_COST_MTHD_CODE_REQ

Message Name	Message Code
Error: Item Cost details not found for Item Id &ITEM_ID, Warehouse &WHSE_CODE, Calendar &CALENDAR_CODE, Period &PERIOD_CODE, Cost Method &COST_MTHD, Component Class &CMPNTCLS_ID, Analysis Code &ANALYSIS_CODE and Cost Level &COST_LEVEL.	GMF_API_COST_ROWS_NOT_FOUND
DEBUG: &MSG	GMF_API_DEBUG
Error: No Burden Details found to delete for Resource &RESOURCE, Component Class Id &CMPNTCLS_ID and Analysis Code &ALYS_CODE.	GMF_API_DEL_BRDN_NOT_FOUND_DTL
Error: No Burden Details found to delete for Burden Line Id &BURDENLINE_ID.	GMF_API_DEL_BRDN_NOT_FOUND_ID
Error: No Component Cost Details found to delete for Component Class Id &CMPNTCLS_ID and Analysis Code &ALYS_CODE.	GMF_API_DEL_IC_NOT_FOUND_DTL
Error: No Component Cost Details found to delete for Component Cost Id &CMPNTCOST_ID.	GMF_API_DEL_IC_NOT_FOUND_ID
Error: Delete Mark is required.	GMF_API_DELETE_MARK_REQ
Error: Duplicate Item Cost details for Item Id &ITEM_ID, Warehouse &WHSE_CODE, Calendar &CALENDAR_CODE, Period &PERIOD_CODE, Cost Method &COST_MTHD, Component Class &CMPNTCLS_ID, Analysis Code &ANALYSIS_CODE and Cost Level &COST_LEVEL.	GMF_API_DUPLICATE_ITEM_COST
Error: Duplicate Resource Cost for Resource Code: &RESOURCES, Orgn: &ORGN_CODE, Calendar: &CALENDAR_CODE, Period: &PERIOD_CODE and Cost Method: &COST_MTHD_CODE.	GMF_API_DUPLICATE_RSRC_COST
Error: Percentage is required.	GMF_API_FIXED_PERCENT_REQ
Error: No Updates/Deletes allowed since Period &PERIOD_CODE for Calendar &CALENDAR_CODE is Frozen.	GMF_API_FROZEN_PERIOD

Message Name	Message Code
Error: Cannot insert new component details since Item &ITEM is frozen for Whse &WHSE, Calendar &CALENDAR, Period &PERIOD and Cost Method &COST_MTHD.	GMF_API_IC_CANNT_INSERT_CMPTS
Error: Component Cost delete failed for Component Class Id &CMPNTCLS_ID and Analysis Code &ALYS_CODE.	GMF_API_IC_DEL_FAILED_DTLS
Error: Component Cost delete failed for Component Cost Id &CMPNTCOST_ID.	GMF_API_IC_DEL_FAILED_ID
Error: Lower Level Component Cost insert failed for Component Class Id &CMPNTCLS_ID and Analysis Code &ALYS_CODE.	GMF_API_IC_LWRLVL_INS_FAILED
Error: This Level Component Cost insert failed for Component Class Id &CMPNTCLS_ID and Analysis Code &ALYS_CODE.	GMF_API_IC_THISLVL_INS_FAILED
Error: Component Cost update failed for Component Class Id &CMPNTCLS_ID and Analysis Code &ALYS_CODE.	GMF_API_IC_UPD_FAILED_DTLS
Error: Component Cost update failed for Component Cost Id &CMPNTCOST_ID.	GMF_API_IC_UPD_FAILED_ID
Warning: Allocation Code &ALLOC_CODE and Company Code &CO_CODE values are ignored since allocation Id is supplied.	GMF_API_IGNORE_ALLOC_CODE
Warning: Basis Amount fields are ignored since fixed percent is used for Allocation (Allocation Method is Fixed Percent).	GMF_API_IGNORE_BASIS
Warning: BurdenLine Id &BURDENLINE_ID is supplied and will be used to Update/Delete the record. Unique key combination of Organization, Item, Warehouse, Calendar, Period, Cost Method, Resource, Component Class and Analysis Code will be ignored.	GMF_API_IGNORE_BRDN_UNIQUE_KEY
Warning: Component Class Code &CMPNTCLS_CODE is ignored since Component Class Id is supplied.	GMF_API_IGNORE_CMPNTCLS_CODE
Warning: Fixed Percent &FIXED_PERCENT value is ignored since Alloc Percent Depends on Basis Amount (Allocation Method is Basis Type).	GMF_API_IGNORE_FIXED_PERCENT

Message Name	Message Code
Warning: Component Cost Id &CMPNTCOST_ID is supplied and will be used to Update/Delete the record. Unique key combination of Item, Warehouse, Calendar, Period, Cost Method, Component Class, Analysis Code and Cost Level will be ignored.	GMF_API_IGNORE_IC_UNIQUE_KEY
Warning: Item No &ITEM_NO is ignored since Item Id is supplied.	GMF_API_IGNORE_ITEM_NO
Warning: Lower level details cannot be updated or deleted hence ignored.	GMF_API_IGNORE_LOWER_LEVEL
Error: Invalid Accounting No in the Basis Account Key &BAS_ACC_KEY.	GMF_API_INVALID_ACCT_NO
Error: Invalid Accounting Unit in the Basis Account Key &BAS_ACC_KEY.	GMF_API_INVALID_ACCTG_UNIT
Error: Invalid combination of Allocation Code &ALLOC_CODE and Company &CO_CODE.	GMF_API_INVALID_ALLOC_CODE
Error: Allocation Method &ALLOC_METHOD not consistent with the existing method.	GMF_API_INVALID_ALLOC_DEF
Error: Invalid Allocation Id: &ALLOC_ID.	GMF_API_INVALID_ALLOC_ID
Error: Invalid Allocation Method: &ALLOC_METHOD.	GMF_API_INVALID_ALLOC_MTHD
Error: Invalid Analysis Code: &ANALYSIS_CODE.	GMF_API_INVALID_ANALYSIS_CODE
Error: Invalid Balance Type: &BALANCE_TYPE.	GMF_API_INVALID_BALANCE_TYPE
Error: Invalid Basis amount Indicator: &BAS_YTD_PTD.	GMF_API_INVALID_BAS_YTD_PTD
Invalid burden line id &BURDENLINE_ID passed.	GMF_API_INVALID_BRDN_LINE_ID
Error: Invalid Burden Indicator: &BURDEN_IND.	GMF_API_INVALID_BURDEN_IND
Error: Invalid Burden Quantity: &BURDEN_QTY (Should be between 0.000000001 and 999999999D99999999).	GMF_API_INVALID_BURDEN_QTY
Error: Invalid Burden UOM: &BURDEN_UM.	GMF_API_INVALID_BURDEN_UM

Message Name	Message Code
Error: Invalid Burden Usage: &BURDEN_USAGE (Should be between 0.00000001 and 999999999D99999999).	GMF_API_INVALID_BURDEN_USAGE
Error: Invalid Calendar Code: &CALENDAR_CODE.	GMF_API_INVALID_CALENDAR_CODE
Error: Component cost &CMPNT_COST should not be greater than 999,999,999.99999999.	GMF_API_INVALID_CMPNT_COST
Error: Invalid Component Class Code: &CMPNTCLS_CODE.	GMF_API_INVALID_CMPNTCLS_CODE
Error: Invalid Component Class Id: &CMPNTCLS_ID.	GMF_API_INVALID_CMPNTCLS_ID
Error: Invalid Cost Method Code: &COST_MTHD_CODE.	GMF_API_INVALID_COST_MTHD_CODE
Error: Invalid Delete Mark: &DELETE_MARK.	GMF_API_INVALID_DELETE_MARK
Error: Invalid Percentage: &FIXED_PERCENT (Should be 0 to 100).	GMF_API_INVALID_FIXED_PERCENT
Error: Invalid Item Id: &ITEM_ID.	GMF_API_INVALID_ITEM_ID
Error: Invalid Item No: &ITEM_NO.	GMF_API_INVALID_ITEM_NO
Error: Invalid Item Quantity: &ITEM_QTY (Should be between 0.00000001 and 999999999D99999999).	GMF_API_INVALID_ITEM_QTY
Error: Invalid Item UOM: &ITEM_UM.	GMF_API_INVALID_ITEM_UM
Error: Invalid Nominal Cost: &NOMINAL_COST (Should be between 0 and 999999999D99999999).	GMF_API_INVALID_NOMINAL_COST
Error: Invalid Organization Code: &ORGN_CODE.	GMF_API_INVALID_ORGN_CODE
Error: Invalid Period Code: &PERIOD_CODE for Calendar &CALENDAR_CODE.	GMF_API_INVALID_PERIOD_CODE
Error: Invalid Resource Code: &RESOURCES.	GMF_API_INVALID_RESOURCES
Error: For Actual Cost method, Raw Material Cost Calculation Type should be 1-PMAC, 2-PWAC, 3-PPAC, 4-LSTT or 5 -LSTI.	GMF_API_INVALID_RMCALC_TYPE
Error: Invalid Usage Unit of Measure: &USAGE_UM.	GMF_API_INVALID_USAGE_UM

Message Name	Message Code
Error: Invalid User name: &USER_NAME.	GMF_API_INVALID_USER_NAME
Error: Invalid Warehouse Code: &WHSE_CODE.	GMF_API_INVALID_WHSE_CODE
Error: Either Item Id or Item No is required.	GMF_API_ITEM_ID_REQ
Error: Item Quantity is required.	GMF_API_ITEM_QTY_REQ
Error: UOM conversion error for Item &ITEM_ID. Cannot convert quantity from current Item UOM &ITEM_UM to actual Item UOM &ITEM_ACT_UM.	GMF_API_ITEM_UM_CONV_ERR
Error: Item UOM is required.	GMF_API_ITEM_UM_REQ
Item Cost Header. Calendar: &CALENDAR Period: &PERIOD Cost Method: &COST_METHOD Warehouse: &WHSE Item Id: &ITEM_ID Item No: &ITEM_NO.	GMF_API_ITEMCOST_HEADER
Error: Line Number is required.	GMF_API_LINE_NO_REQ
Message: No rows deleted.	GMF_API_NO_ROWS_DEL
Error: No rows found to update/delete for Allocation Id &ALLOC_ID and Line No &LINE_NO.	GMF_API_NO_ROWS_FOUND
Message: No rows inserted.	GMF_API_NO_ROWS_INS
Message: No rows updated.	GMF_API_NO_ROWS_UPD
Error: Nominal Cost is required.	GMF_API_NOMINAL_COST_REQ
Error: Organization Code is required.	GMF_API_ORGN_CODE_REQ
Error: Period Code is required.	GMF_API_PERIOD_CODE_REQ
Resource Cost Header. Resource: &RESOURCES Organization: &ORGN Calendar: &CALENDAR Period: &PERIOD Cost Method: &COST_MTHD	GMF_API_RESOURCE_HEADER
Error: Resource Code is required.	GMF_API_RESOURCES_REQ
&NUM_ROWS row(s) deleted.	GMF_API_ROWS_DEL
&NUM_ROWS row(s) inserted.	GMF_API_ROWS_INS
&NUM_ROWS row(s) updated.	GMF_API_ROWS_UPD

Message Name	Message Code
Error: No rows found to update/delete for Resource &RESOURCES, Orgn &ORGN_CODE, Calendar &CALENDAR_CODE, Period &PERIOD_CODE and Cost Method &COST_MTHD_CODE.	GMF_API_RSRC_NO_ROWS_FOUND
Warning: Total Fixed Percentage for Allocation Id &ALLOC_ID is not equal to 100.	GMF_API_TOTAL_PCT_NOTHUNDRED
Error: Burden UOM &BURDEN_UM must be of the same type as the resource UOM &RESOURCE_UM.	GMF_API_UOM_SAMETYPE_REQ
Error: No Component Cost Details found to update for Component Class Id &CMPNTCLS_ID and Analysis Code &ALYS_CODE.	GMF_API_UPD_IC_NOT_FOUND_DTL
Error: No Component Cost Details found to update for Component Cost Id &CMPNTCOST_ID.	GMF_API_UPD_IC_NOT_FOUND_ID
Error: Usage Unit of Measure is required.	GMF_API_USAGE_UM_REQ
Error : Usage UOM &USAGE_UM must be of the same type as the resource UOM &RESOURCE_UM.	GMF_API_USAGE_UOM_SAMETYPE_REQ
User Name is required.	GMF_API_USER_NAME_REQ
Error: Warehouse Code is required.	GMF_API_WHSE_CODE_REQ

Glossary

Application Programming Interface (API)

A documented, supported method for communicating within or between modules.

Module

A module is a collection of one or more business objects and the associated transactions. A module publishes APIs for other modules and accesses other modules through their published API's. An example of a Module is Oracle Inventory.

Business Object

An independent item of significance in the business world. An example of a "Business Object" is a Sales Order.

Entity

An item of significance in the business world, that has no meaning without reference to a Business Object. An example of an Entity is a "Sales Order Header". A Sales Order Header is an entity of the business object "Sales Order".

Business Process API

An API that performs a transaction for the calling module, e.g., to hire an employee, enter an order, or cost a material movement transaction.

Public API

An API intended for use by all applications.; contrast to *Private API*.

Private API

An API intended for use by the owning module only.; contrast to *published API*.

Group API

An API intended for use by other authorized Oracle Applications modules.

Index

A

Allocation Definition, 1-3
 Allocation Definition Entity, 4-17
 Delete, 1-5
 Insert, 1-5
 Structure, 3-4
 Structure and Logic, 4-18
 Update, 1-5
Allocation Definition APIs, 1-5
API, 1-1, 1-2
Application Programming Interface (API), 1

B

Burden Details, 1-3
 Detail Entity, 4-23
 Header Entity, 4-22
 Insert, 1-5
 Retrieve, 1-6
 Structure, 3-5
 Structure and Logic, 4-24
 Update, 1-5
Burden Details APIs, 1-5
Business Object, 1
Business Objects, 4-1
 Allocation Definition, 4-17
 Burden Details, 4-22
 Item Cost, 4-1
 Resource Cost, 4-12
Business Process API, 1

C

Code Re-Use, 1-3
Consistent Behavior, 1-3

E

Ease of Integration, 1-3
Entity, 1

F

FND_API, 1-7
FND_API.G.FALSE, 3-6
FND_MESSAGE, 1-7
FND_PUB_MSG, 1-7
formula information, importing, 1-2

G

GMF_AllocationDefinition_PUB, 1-7, 3-4
GMF_BurdenDetails_PUB, 1-7, 3-5
GMF_ItemCost_PUB, 1-7, 3-1
GMF_ResourceCost_PUB, 1-7, 3-3
GMFPALCB.pls, 3-4
GMFPALCS.pls, 1-7, 3-4
GMFPBRDB.pls, 1-7, 3-5
GMFPBRDS.pls, 1-7, 3-5
GMFPCSTB.pls, 1-7, 3-1
GMFPCSTS.pls, 1-7, 3-1
GMFPRESB.pls, 3-3
GMFPRESS.pls, 1-7, 3-3
Group API, 2

I

importing formula information, 1-2
Insulation from Changes, 1-3
Item Cost, 1-3
 Cost Header Entity, 4-2
 Delete, 1-4
 Insert, 1-4
 Lower Level Cost Detail Entity, 4-4
 Retrieve, 1-4
 Structure, 3-1
 Structure and Logic, 4-5
 This Level Cost Detail Entity, 4-3
 Update, 1-4
Item Cost APIs, 1-4

M

message encoding, 3-7
message list initialization, 3-6
message list, specifying number of messages
 added, 3-7
Module, 1

P

p_allocation_definition_rec, 4-20
p_api_version, 3-6
p_commit, 3-7
p_dtl_tbl, 4-28, 4-29
p_header_rec, 4-9, 4-10, 4-11, 4-28, 4-29, 4-30
p_init_msg_list, 3-6
p_lower_level_dtl_tbl, 4-9, 4-10
p_resource_cost_rec, 4-15, 4-21
p_this_level_dtl_tbl, 4-9, 4-10
Package Specification - GMFPALCS.pls, 4-19
Package Specification - GMFPBRDS.pls, 4-25
Package Specification - GMFPCSTS.pls, 4-5
Package Specification - GMFPRESS.pls, 4-13
PL/SQL, 1-2
Private API, 1
processing standard message functions, 3-7
Public API, 1
Public Procedure Delete_Allocation_
 Definition, 4-21
Public Procedure Delete_Item_Cost, 4-10, 4-29

Public Procedure Delete_Resource_Cost, 4-15
Public Procedure Get_Burden_Details, 4-30
Public Procedure Get_Item_Cost, 4-11
Public Procedure Get_Resource_Cost, 4-15
Public Procedure Update_Allocation_
 Definition, 4-20
Public Procedure Update_Burden_Details, 4-28
Public Procedure Update_Item_Cost, 4-9
Public Procedure Update_Resource_Cost, 4-15

R

Resource Cost, 1-3
 Delete, 1-5
 Insert, 1-4
 Resource Cost Entity, 4-12
 Retrieve, 1-5
 Structure, 3-3
 Structure and Logic, 4-13
 Update, 1-4
Resource Cost APIs, 1-4
Robust Validation, 1-3

S

standard message function processing, 3-7
support policy, 1-6

T

Technical Overview, 3-1
 Allocation Definition, 3-4
 Burden Details, 3-5
 Item Cost, 3-1
 Resource Cost, 3-3

V

version compatibility, validation, 3-6

X

x_dtl_tbl, 4-30
x_lower_level_dtl_tbl, 4-11
x_msg_count, 3-7
x_msg_data, 3-7

x_resource_cost_rec, 4-16
x_return_status, 3-7
x_this_level_dtl_tbl, 4-11

