

Oracle® Application Server

Quick Installation Guide

10g Release 3 (10.1.3) for HP-UX Itanium

B28541-01

May 2006

ORACLE®

Copyright © 2006, Oracle. All rights reserved.

Primary Author: Brintha Bennet

The Programs (which include both the software and documentation) contain proprietary information; they are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright, patent, and other intellectual and industrial property laws. Reverse engineering, disassembly, or decompilation of the Programs, except to the extent required to obtain interoperability with other independently created software or as specified by law, is prohibited.

The information contained in this document is subject to change without notice. If you find any problems in the documentation, please report them to us in writing. This document is not warranted to be error-free. Except as may be expressly permitted in your license agreement for these Programs, no part of these Programs may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose.

If the Programs are delivered to the United States Government or anyone licensing or using the Programs on behalf of the United States Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the Programs, including documentation and technical data, shall be subject to the licensing restrictions set forth in the applicable Oracle license agreement, and, to the extent applicable, the additional rights set forth in FAR 52.227-19, Commercial Computer Software--Restricted Rights (June 1987). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

The Programs are not intended for use in any nuclear, aviation, mass transit, medical, or other inherently dangerous applications. It shall be the licensee's responsibility to take all appropriate fail-safe, backup, redundancy and other measures to ensure the safe use of such applications if the Programs are used for such purposes, and we disclaim liability for any damages caused by such use of the Programs.

Oracle, JD Edwards, PeopleSoft, and Siebel are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

The Programs may provide links to Web sites and access to content, products, and services from third parties. Oracle is not responsible for the availability of, or any content provided on, third-party Web sites. You bear all risks associated with the use of such content. If you choose to purchase any products or services from a third party, the relationship is directly between you and the third party. Oracle is not responsible for: (a) the quality of third-party products or services; or (b) fulfilling any of the terms of the agreement with the third party, including delivery of products or services and warranty obligations related to purchased products or services. Oracle is

not responsible for any loss or damage of any sort that you may incur from dealing with any third party.

1 Introduction

This guide describes how to install the following Oracle Application Server installation types:

- Basic Installation
- Advanced Installation: Integrated Web Server, J2EE Server and Process Management

Contents of this Guide

- [Section 2, "Documentation Accessibility"](#) on page 4
- [Section 3, "Installation Types Covered in this Guide"](#) on page 5
- [Section 4, "Requirements"](#) on page 7
- [Section 5, "Starting the Installer"](#) on page 18
- [Section 6, "Basic Installation"](#) on page 21
- [Section 7, "Advanced Installation"](#) on page 24
- [Section 8, "Accessing the Welcome Page"](#) on page 28
- [Section 9, "Additional Resources"](#) on page 29

2 Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible, with good usability, to the disabled community. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Accessibility standards will continue to evolve over time, and Oracle is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be accessible to all of our customers. For more information, visit the Oracle Accessibility Program Web site at <http://www.oracle.com/accessibility/>.

Accessibility of Code Examples in Documentation

Screen readers may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, some screen readers may not always read a line of text that consists solely of a bracket or brace.

Accessibility of Links to External Web Sites in Documentation

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations regarding the accessibility of these Web sites.

TTY Access to Oracle Support Services

Oracle provides dedicated Text Telephone (TTY) access to Oracle Support Services within the United States of America 24 hours a day, seven days a week. For TTY support, call 800.446.2398.

3 Installation Types Covered in this Guide

This guide is intended for users who want to install an Integrated Web Server, J2EE Server and Process Management in a single Oracle home. This install type provides the following components:

- Oracle HTTP Server

This is the Web server component of Oracle Application Server.

- Oracle Containers for J2EE

This component provides a complete Java 2 Enterprise Edition (J2EE) environment for developing Java applications.

- Oracle Enterprise Manager 10g Application Server Control

This component is used for Web-based management of Oracle Application Server.

- Oracle Process Manager and Notification Server

Integrated Web Server, J2EE Server and Process Management can be installed using the following install modes:

- **Basic Installation:** The basic (one-click) installation prompts you with questions on the initial installation screen, and then it proceeds to install the product without any further user interaction. The default values for all the components are used.
- **Advanced Installation:** The advanced installation provides you with a great degree of customization and flexibility, which enables installation of additional languages, port configuration options, and cluster configuration.

If you want more complex topologies, read the *Oracle Application Server Installation Guide* for complete installation instructions.

Before installing Oracle Application Server, you should read the *Oracle Application Server Release Notes* for the latest information.

4 Requirements

Check that your computer meets the minimum requirements:

- [Section 4.1, "Check System Requirements"](#)
- [Section 4.2, "Check Software Requirements"](#)
- [Section 4.3, "Check Kernel Parameters"](#)
- [Section 4.4, "Create an Operating System Group for the Inventory Directory"](#)
- [Section 4.5, "Create an Operating System User"](#)
- [Section 4.6, "Check Environment Variables"](#)

4.1 Check System Requirements

Your computer must meet the following requirements.

Operating Systems Supported

HP-UX 11i Version 2 (11.23) Itanium or higher

Other System Requirements

The following table shows other system requirements.

Table 1 *Minimum System Requirements*

Item	Minimum System Requirement
Memory	512 MB
Disk space	2.05 GB
Space in /tmp directory	400 MB
Swap space	1.5 GB

Complete the following steps to check these requirements:

1. To determine the physical RAM size, enter the following command:

```
# grep "Physical:" /var/adm/syslog/syslog.log
```

2. To determine the amount of free disk space, enter the following command:

```
prompt> dfbdf -k dir
```


Replace *dir* with the Oracle home directory or with the parent directory if the Oracle home directory does not exist yet. For example, if you plan to install Oracle Application Server in `/opt/oracle/OracleAS`, you can replace *dir* with `/opt/oracle` or `/opt/oracle/OracleAS`.

3. To determine the amount of available swap space, enter the following command:

```
# /usr/sbin/swapinfo -a
```

If necessary, see your operating system documentation for information on how to configure additional swap space.

4.2 Check Software Requirements

Check that the following software are installed on the system:

- HP-UX 11i Version 2 (11.23) Itanium or higher
- Patches for 11.23
 - BUNDLE11i B.11.23.0409.3 (Patch Bundle for HP-UX 11i v2 (B.11.23), September 2004)
 - PHSS_31850 (11.23 assembler patch)
 - PHSS_31851 (11.23 Integrity Unwind Library)

- PHSS_31854 (11.23 milli cumulative patch)
- PHSS_31855 (11.23 aC++ Runtime (IA: A.05.60, PA A.03.60))
- PHSS_33275 + PHSS_32213 (11.23 linker + fdp cumulative patch)
- PHSS_33276 (11.23 Math Library Cumulative Patch)

The following patches are required by JDK 1.5 or higher. JDK 1.5.0.03 is installed with this release. Refer to the HP Support site for a list of all JDK patches.

- PHCO_31553: pthread library cumulative patch
- PHKL_31500: 11.23 Sept04 base patch
- PHSS_34201: 11.23 Aries cumulative patch

The following patches are required if ANSI C and C++ are installed on the system:

- PHSS_33278: aC++ Compiler (A.06.02)
- PHSS_33277: HP C Compiler (A.06.02)
- PHSS_33279: u2comp/be patch

To ensure that the system meets these requirements, follow these steps:

1. To determine which version of HP-UX is installed, enter the following command:

```
# uname -a  
HP-UX hostname B.11.23 U ia64 1221911087  
unlimited-user license
```

In this example, the version of HP-UX 11i is 11.23.

2. To determine whether the bundle is installed, enter the following command:

```
# /usr/sbin/swlist | grep BUNDLE
```

If the bundle is not installed, download it from the following Web site and install it:

[http://www.software.hp.com/SUPPORT_ PLUS/gpk.html](http://www.software.hp.com/SUPPORT_PLUS/gpk.html)

3. To determine whether a bundle or product is installed, enter the following command:

```
# /usr/sbin/swlist -l product | more
```

If a required product is not installed, you must install it. See your operating system or software documentation for information on installing products.

4. To determine whether a patch is installed, enter a command similar to the following:

```
# /usr/sbin/swlist -l patch | grep PHKL_29198
```

Alternatively, to list all installed patches, enter the following command:

```
# /usr/sbin/swlist -l patch | more
```

If a required patch is not installed, download it from the following URL and install it:

<http://itresourcecenter.hp.com>

4.3 Check Kernel Parameters

The computers on which you plan to perform the installation require their kernel parameters to be set to the minimum values.

Complete the following tasks to set the kernel parameters for OracleAS Web Cache:

1. Start System Administration Manager (SAM) as the `root` user:

```
# /usr/sbin/sam
```

2. Choose the Kernel Configuration area, then choose the Configurable Parameters area.
3. Check the value for `maxfiles_lim` is at least 4096. If necessary, modify that value. See the SAM online help for more information on completing this step.
4. Exit from SAM.
5. If you modified the value, restart the system:

```
# /sbin/shutdown -r now
```

4.4 Create an Operating System Group for the Inventory Directory

If this is the first Oracle product to be installed on the computer, create an operating system group for the "inventory" directory. The installer creates files in the inventory directory to keep track of the Oracle products that are installed on the computer.

This guide uses the name `oinstall` for this group.

To create a local operating system group, `oinstall`, enter the following command:

```
# /usr/sbin/groupadd oinstall
```

In [Section 4.5, "Create an Operating System User"](#), you will create an operating system user, and set this group to be the user's primary group.

By having a separate group for the inventory directory, you allow different users to install Oracle products on the computer. Users need write permission for the inventory directory. They can achieve this by belonging to the `oinstall` group.

The default name of the inventory directory is `oraInventory`.

If you are unsure if there is already an inventory directory on the computer, look in the `oraInst.loc` file. This file lists the location of the inventory directory and the group who owns it. If the file does not exist, the computer does not have Oracle products installed on it.

4.5 Create an Operating System User

Create an operating system user to install and upgrade Oracle products. This guide refers to this user as the `oracle` user.

How to Create a User

To create the `oracle` operating system user as part of the `oinstall` group:

1. Enter the following command as the root user:

```
# /usr/sbin/useradd -g oinstall -G dba[,oper] oracle
```

In this command:

- The `-g` option specifies the primary group, which must be the Oracle Inventory group, for example `oinstall`
 - The `-G` option specifies the secondary groups, which must include the OSDBA group and if required, the OSOPER group, for example `dba` or `dba, oper`
2. Set the password for the `oracle` user by entering the following command and follow the instructions on screen:

```
# passwd oracle
```

For more information about operating system users and groups, see your operating system documentation or contact your system administrator.

4.6 Check Environment Variables

The operating system user who will be installing Oracle Application Server needs to set (or unset) the following environment variables.

Table 2 *Environment Variables*

Environment Variable	Set or Unset
ORACLE_HOME	Must not be set.
ORACLE_SID	Must not be set.
TNS_ADMIN	Must not be set.
PATH, CLASSPATH, and Shared Library Path	Must not contain references to directories in any Oracle home directories.
TMP and TMPDIR	Optional. If unset, defaults to /tmp.

4.6.1 Environment Variable Tips This section describes some things to look out for when setting environment variables:

- If you set environment variables in the `.profile` file, they might not be read. To ensure environment variables are set to the correct values, check their values in the shell where you will be running the installer.
- To check the value of environment variables, use the `env` command. This displays all the currently defined environment variables and their values.

```
% env
```

- If you use the `su` command to switch users (for example, switching from the root user to the `oracle` user), check the environment variables when you are the new user because the environment variables might not be passed to the new user. This can happen even if you run `su` with the `-` parameter (`su - user`).

```
# /* root user */  
# su - oracle  
% env
```

5 Starting the Installer

To start the installer:

1. Log in to the computer as a user who is a member of the Administrators group.
2. Insert the disk:
CD-ROM: Insert Oracle Application Server Disk 1.
DVD: Insert the Oracle Application Server DVD.
3. If your computer does not mount CD-ROMs or DVDs automatically, you need to set the mount point manually. See [Section 5.1, "Setting the Mount Point for the CD-ROM or DVD-ROM"](#) for steps on mounting the CD-ROM or DVD-ROM manually.
4. Log in as the `oracle` user.
5. Start up the installer:

Note:

- Be sure you are not logged in as the root user when you start the Oracle Universal Installer. The installer gives an error message if you try to run it as the root user.
 - Do not start the installation inside the `mount_point` directory. If you do, then you may not be able to eject the installation disk. The `cd` command below changes your current directory to your home directory.
-
-

CD-ROM:

```
prompt> cd  
prompt> mount_point/10.1.3disk1/runInstaller
```

DVD:

```
prompt> cd  
prompt> mount_point/application_server/runInstaller
```

This launches Oracle Universal Installer, through which you can install Oracle Application Server.

5.1 Setting the Mount Point for the CD-ROM or DVD-ROM

The Oracle Application Server CD-ROMs are in RockRidge format. The DVD-ROM is in DVD-ROM format.

To mount the first disk, follow these steps:

1. Insert Oracle Application Server disk 1 into the CD-ROM or DVD.
2. Create the `/SD_CDRM` directory if it does not already exist:

```
# /usr/bin/mkdir /SD_CDRM
```

3. Enter a command similar to the following:

```
# /usr/sbin/mount -F cdfs -o rr /dev/dsk/cxdyztz /SD_
CDROM
```

In the preceding example, `/SD_CDRM` is the disk mount point directory and `/dev/dsk/cxdyztz` is the device name for the disk device, for example `/dev/dsk/c0d2t0`.

6 Basic Installation

This section describes how to install Integrated Web Server, J2EE Server and Process Management using a basic installation. To install using a basic installation:

1. Start up the installer. See [Section 5, "Starting the Installer"](#) for details.
2. Oracle Application Server 10g 10.1.3.0.0 screen

Installation Directory: Enter the directory where you want to install Oracle Application Server.

Example:

```
/scratch/oracle/product/10.1.3/OracleAS
```

Basic Installation Mode: Select this option.

Installation Type: You cannot change the installation type in a basic installation.

Instance Name: The instance name identifies this Oracle Application Server instance. If you have more than one Oracle Application Server instance on the same host, the instances must have unique names.

Example: appserver

Administration Username: The administration username for Oracle Application Server instances is set to `oc4jadmin` and cannot be changed. To manage Oracle Application Server instances using Oracle Enterprise Manager, log in as the `oc4jadmin` user.

Administration Password and Confirm Password: Enter the password for the `oc4jadmin` user.

Example: `welcome1`

Click **Install**.

3. If this is the first Oracle product to be installed on this computer, the installer displays these additional screens:
 - a. Specify Inventory Directory and Credentials screen

Enter the full path of the inventory directory: Enter a full path to the inventory directory. This directory is different from the Oracle home directory for the product files.

Example: `/opt/oracle/orainventory`

Specify operating system group name: Select the operating system group that will have write permission for the inventory directory.

Example: `oinstall`

Click **Next**.

b. Run oraInstRoot.sh dialog

When prompted, run the `oraInstRoot.sh` script as the root user in a different shell. The script is located in the inventory directory.

After running the script, click **Continue**.

4. Run root.sh dialog

Note: do not run this script until you see the dialog.

In a different window, log in as the root user and run the `root.sh` script. The script is located in this instance's Oracle home directory.

After you have run the `root.sh` script, click **OK**.

5. Configuration Assistants screen

This screen displays the progress of configuration assistants, which configure Oracle Application Server components.

6. End of Installation screen

Click **Exit** to quit the installer.

7 Advanced Installation

This section describes how to install Integrated Web Server, J2EE Server and Process Management using an advanced installation. To install using an advanced installation:

1. Start up the installer. See [Section 5, "Starting the Installer"](#) for details.
2. Oracle Application Server 10g 10.1.3.0.0 screen

Installation Directory: Enter the directory where you want to install Oracle Application Server.

Example:

```
/scratch/oracle/product/10.1.3/OracleAS
```

Advanced Installation Mode: Select this option.

Click **Next**.

3. If this is the first Oracle product to be installed on this computer, the installer displays these additional screens:
 - a. Specify Inventory Directory and Credentials screen
Enter the full path of the inventory directory: Enter a full path to the inventory directory. This directory is different from the Oracle home directory for the product files.

Example: `/opt/oracle/oraInventory`

Specify operating system group name: Select the operating system group that will have write permission for the inventory directory.

Example: `oinstall`

Click **Next**.

b. Run oraInstRoot.sh dialog

When prompted, run the `oraInstRoot.sh` script as the root user in a different shell. The script is located in the inventory directory.

After running the script, click **Continue**.

4. Select Installation Type screen

Integrated Web Server, J2EE Server and Process Management: Select this option.

Click **Next**.

5. Specify Port Configuration Options screen

Select **Automatic**.

Click **Next**.

6. Administration Instance Settings screen

Select **Configure this as an Administration OC4J instance**.

Click **Next**.

7. Administration Settings screen

AS Instance Name: The instance name identifies this Oracle Application Server instance. If you have more than one Oracle Application Server instance on the same host, the instances must have unique names.

Example: appserver

Default OC4J Instance Administrator Account Username:

The administration username for Oracle Application Server instances is set to `oc4jadmin` and cannot be changed. To manage Oracle Application Server instances using Oracle Enterprise Manager, log in as the `oc4jadmin` user.

Administrator Account Password and Confirm Administrator Account Password: Enter the password for the `oc4jadmin` user.

Example: welcome1

OC4J Instance Name: The OC4J instance name identifies the default OC4J instance created by the installer.

Example: home

Click **Next**.

8. Cluster Topology Configuration screen

Deselect **Configure this instance to be part of an Oracle Application Server cluster topology**.

Click **Next**.

9. Summary screen

Verify your selections and click **Install**. The installer now installs the files.

10. Run root.sh dialog

Note: do not run this script until you see the dialog.

In a different window, log in as the root user and run the `root.sh` script. The script is located in this instance's Oracle home directory.

After you have run the `root.sh` script, click **OK**.

11. Configuration Assistants screen

This screen displays the progress of configuration assistants, which configure Oracle Application Server components.

12. End of Installation screen

Click **Exit** to quit the installer.

8 Accessing the Welcome Page

After installation, access the Oracle Application Server Welcome page to verify that the installation was successful. The URL for the Welcome page is:

`http://hostname.domainname:http_port`

You can locate the URL for accessing the Welcome Page on the End of Installation Screen text, which is stored in the following file:

`ORACLE_HOME/install/readme.txt`

The Welcome page provides links to these useful pages:

- New features in Oracle Application Server 10g Release 3 (10.1.3)
- Oracle Enterprise Manager Application Server Control ("Application Server Control"), which is a browser-based administrative tool

- Release Notes
- Quick Start
- Demos

9 Additional Resources

For more information, see these Oracle resources:

- Oracle Application Server Documentation Library CD-ROM
- Oracle Application Server platform-specific documentation on Oracle Application Server Disk 1 CD-ROM

Printed documentation is available for sale in the Oracle Store at <http://oraclestore.oracle.com>.

You can also contact your Oracle representative to purchase printed documentation.

To download free release notes, installation documentation, white papers, or other collateral, visit Oracle Technology Network (OTN). You must register online before using OTN; registration is free and can be done at <http://www.oracle.com/technology/membership/>.

If you already have a username and password for OTN, then you can go directly to the documentation section of OTN at <http://www.oracle.com/technology/documentation>.

9.1 Oracle Support Services

If you purchased Oracle Product Support, you can call Oracle Support Services for assistance. Oracle Support Services include phone assistance, version updates and access to our service offerings. You have access to phone support 24 hours a day, 7 days a week. In the U.S.A., you can call Product Support at **1-800-223-1711**.

Make sure you have your CSI (CPU Support Identifier) number ready when you call. Keep the CSI number for your records, because it is your key to Oracle Support Services. The Oracle Store sends the CSI number to you in an e-mail alert when it processes your order. If you do not have your CSI number and you are in the U.S.A., you can look up your CSI number by accessing our online Order Tracker which provides detailed order information. Go to the Oracle Store and click on Order Tracker located above the top navigation bar.

For Oracle Support Services locations outside the U.S.A., call your local support center for information on how to access support. To

find the local support center in your country, visit the Support Web Center at <http://www.oracle.com/support>.

At the Support Web Center you will find information on Oracle Support Services, such as:

- contact information
- instructions on how to access electronic services
- helpful Web sites
- Support Resources
- Oracle Support Portfolio
- Oracle Support Services news

With Oracle Product Support, you have round-the-clock access to Oracle*MetaLink*, Oracle Support Services premier Web support offering. Oracle*MetaLink* offers you access to installation assistance, product documentation, and a technical solution knowledge base.

It has technical forums, where you can post questions about your Oracle products and receive answers from Oracle Technical Support Analysts and other Oracle users. The questions and answers remain posted for the benefit of all users.

Oracle*MetaLink* options include:

- Technical Assistance Request (TAR) access
- patch downloads
- bug database query access
- product life-cycle information

You can access Oracle*MetaLink* at
<https://metalink.oracle.com>.

9.2 Version Updates

If you do not have a currently supported license, you can purchase the most recent version of an Oracle product from the Oracle Store at:

<http://oraclestore.oracle.com>

If you do have a currently supported license, you can place non-urgent requests for version update shipments through the iTAR feature on Oracle*MetaLink*. You will need to log the iTAR type as a U.S. Client Relations/Non-Technical Request.

You can also request Version Update shipments in the U.S.A. by calling Client Relations. When requesting a Version Update, provide the following information to the Client Relations Analyst:

- CSI number
- contact information
- platform
- product name
- shipping address
- version number of the product

Outside the U.S.A., call your local Oracle Support Center.

9.3 Premium Services

For information on our Premium Services, including onsite support, Oracle*GOLD*, remote services, and upgrade packages, visit the Support Web Center at

<http://www.oracle.com/support>

or call your Support Sales Representative in the U.S.A at **1-800-833-3536**.

9.4 Quick Reference

Resource	Contact Information or Web Site
Purchase additional products, full-use licenses, version updates, and documentation in the U.S.A.	http://oraclestore.oracle.com
Access technical resources for developers	http://www.oracle.com/technology
Access installation documentation	http://www.oracle.com/technology/documentation
Access information about technical support	http://www.oracle.com/support
Locate local Oracle Support Centers outside the U.S.A.	http://www.oracle.com/support
Locate local Oracle offices outside the U.S.A	http://www.oracle.com/global
Call Client Relations in the U.S.A	1-800-223-1711
Speak with your sales representative in the U.S.A.	1-800-ORACLE-1

Resource**Contact Information or Web Site**

TTY Access to technical support in the U.S.A.	1-800-446-2398
--	----------------
