

Retek® Merchandising System™

11.0.5

Installation Guide

Corporate Headquarters:

Retek Inc.
Retek on the Mall
950 Nicollet Mall
Minneapolis, MN 55403
USA
888.61.RETEK (toll free US)
Switchboard:
+1 612 587 5000
Fax:
+1 612 587 5100

European Headquarters:

Retek
110 Wigmore Street
London
W1U 3RW
United Kingdom
Switchboard:
+44 (0)20 7563 4600
Sales Enquiries:
+44 (0)20 7563 46 46
Fax:
+44 (0)20 7563 46 10

The software described in this documentation is furnished under a license agreement, is the confidential information of Retek Inc., and may be used only in accordance with the terms of the agreement.

No part of this documentation may be reproduced or transmitted in any form or by any means without the express written permission of Retek Inc., Retek on the Mall, 950 Nicollet Mall, Minneapolis, MN 55403, and the copyright notice may not be removed without the consent of Retek Inc. Information in this documentation is subject to change without notice.

Retek provides product documentation in a read-only-format to ensure content integrity. Retek Customer Support cannot support documentation that has been changed without Retek authorization.

The functionality described herein applies to this version, as reflected on the title page of this document, and to no other versions of software, including without limitation subsequent releases of the same software component. The functionality described herein will change from time to time with the release of new versions of software and Retek reserves the right to make such modifications at its absolute discretion.

Retek® Merchandising System™ is a trademark of Retek Inc. Retek and the Retek logo are registered trademarks of Retek Inc.

This unpublished work is protected by confidentiality agreement, and by trade secret, copyright, and other laws. In the event of publication, the following notice shall apply:

©2005 Retek Inc. All rights reserved.

All other product names mentioned are trademarks or registered trademarks of their respective owners and should be treated as such.

Printed in the United States of America.

Customer Support

Customer Support hours

Customer Support is available 7x24x365 via email, phone, and Web access.

Depending on the Support option chosen by a particular client (Standard, Plus, or Premium), the times that certain services are delivered may be restricted. Severity 1 (Critical) issues are addressed on a 7x24 basis and receive continuous attention until resolved, for all clients on active maintenance. Retek customers on active maintenance agreements may contact a global Customer Support representative in accordance with contract terms in one of the following ways.

Contact Method	Contact Information
E-mail	support@retek.com
Internet (ROCS)	rocs.retek.com
Phone	+1 612 587 5800
Mail	Retek Customer Support Retek on the Mall 950 Nicollet Mall Minneapolis, MN 55403

Toll free alternatives are also available in various regions of the world:

Australia	+1 800 555 923 (AU-Telstra) or +1 800 000 562 (AU-Optus)
-----------	--

France	0800 90 91 66
--------	---------------

Hong Kong	800 96 4262
-----------	-------------

Korea	00 308 13 1342
-------	----------------

United Kingdom	0800 917 2863
----------------	---------------

United States	+1 800 61 RETEK or 800 617 3835
---------------	---------------------------------

When contacting Customer Support, please provide:

- Product version and program/module name.
- Functional and technical description of the problem (include business impact).
- Detailed step-by-step instructions to recreate.
- Exact error message received.
- Screen shots of each step you take.

Contents

Chapter 1 –Database Installation Instructions 1

Mount CD-ROM on the Database Server	1
Loading RIB data	1
Update types	1
Update RMS tables.....	2
Update RMS database objects	2
Update data for RMS.....	2
Update Pricing tables.....	2
Update Pricing database objects.....	2
Update Pricing data	3
Validate all invalid objects	3
Update RETL for RDW	3
Compile RMS batch libraries and programs	3
Setting Environment Variables	4

Chapter 2 – Application Server Installation Instructions..... 7

Mount CD-ROM on the Database Server	7
Setup.....	7
Toolset.....	8
Forms.....	9
Help Files	10

Chapter 1 –Database Installation Instructions

Before you apply the RMS 11.0.5 patch:

- Make a backup of all your objects and database schema.
- Check that RMS 11.0.4 is installed.
- Review the enclosed RMS 11.0.5 Patch Release Notes (rms-1105-rn.pdf).
- Review each of the enclosed SIR documents.

Before copying over any files:

- Note whether customizations have been made to the module. If so, then the customizations must be reapplied over the new version of the module (or the fix may need to be applied to the custom version of the code).
- Copy the original files to a different directory before copying over them in case they need to be referred to at a later date.



Note: These instructions refer to RMS11DEV as the Oracle owning schema.

Mount CD-ROM on the Database Server

- 1 Copy the rms1105dbpatch.zip file from the CD /dbserverunix directory to a newly created staging directory on your UNIX server.
- 2 Unzip the file by entering:

```
unzip rms1105dbpatch.zip
```

Loading RIB data

- 1 Change directories to staging area/rib_objects11/xml.
- 2 Run the following command at the UNIX prompt:

```
sqlldr RMS11DEV/SCHEMA_PASSWORD control=rib_docatypes_rms.ctl
```
- 3 Check the log file rib_docatypes_rms.log for any errors.

Update types



Note: When running the scripts in this section the following errors may be encountered “ORA-04043 object XXXX does not exist”. These errors can be ignored. The errors are caused by dropping the item the script is about to create

- 1 Change directories to staging area/xml
- 2 Log into sqlplus as RMS11DEV and run the following command:

```
SQL> @patch1105xml.sql
```
- 3 Check the log file patch1105xml.log for any errors.

Update RMS tables

- 1 Change directories to staging area/dbcs
- 2 Log into sqlplus as RMS11DEV and run the following command:
SQL> @patch1105dbc.sql
- 3 Check the log file patch1105dbc.log for any errors.

Update RMS database objects

- 1 Change directories to staging area /db_objects
- 2 Log into sqlplus as RMS11DEV and run the following command:
SQL> @patch1105rms.sql
- 3 Check the log file patch1105rms.log for any errors.

Update data for RMS

 **Note:** When running the scripts in this section the following errors may be encountered “ERROR at line 1: ORA-28102: policy does not exist ORA-06512: at “SYS.DBMS_RLS”, line 308 ORA-06512: at line 1”. These errors can be ignored. The errors are caused by dropping the item the script is about to create

 **Note:** This script will also prompt for a role to add. The role added as a default in the RMS 11.0 release was developer.

- 1 Change directories to staging area /sqlplus
- 2 Log into sqlplus as RMS11DEV and run the following command:
SQL> @patch1105ctl.sql
- 3 Check the log file patch1105ctl.log for any errors.

Update Pricing tables

- 1 Change directories to staging area/pricing/dbcs
- 2 Log into sqlplus as RMS11DEV and run the following command:
SQL> @pricing1105dbc.sql
- 3 Check the log file pricing1105dbc.log for any errors.

Update Pricing database objects

- 1 Change directories to staging area /pricing/db_objects
- 2 Log into sqlplus as RMS11DEV and run the following command:
SQL> @pricing1105rms.sql
- 3 Check the log file pricing1105dbo.log for any errors.

Update Pricing data

- 1 Change directories to staging area/pricing/sqlplus
- 2 Log into sqlplus as RMS11DEV and run the following command:
SQL> @pricing1105ctl.sql
- 3 Check the log file pricing1105ctl.log for any errors.

Validate all invalid objects

 **Note:** Deadlocked objects may appear when running this script. This is expected. Run the script until no more invalid objects remain.

- 1 Change directories to INSTALL_DIR/utility
- 2 Log into sqlplus as RMS11DEV and run the following command:
SQL> @inv_obj_comp.sql
- 3 This script may need to be run more than once.

Update RETL for RDW

 **Note:** These steps only needs to be done if you are using RDW

- 1 Change directories to staging area /retlforRDW/rfx/etc
- 2 Copy all the files from this directory INSTALL_DIR/retlforRDW/rfx/etc
cp * INSTALL_DIR/retlforRDW/rfx/etc
- 3 Change directories to staging area /retlforRDW/rfx/schema
- 4 Copy all the files from this directory INSTALL_DIR/retlforRDW/rfx/schema
cp * INSTALL_DIR/retlforRDW/rfx/schema
- 5 Change directories to staging area /retlforRDW/rfx/src
- 6 Copy all the files from this directory INSTALL_DIR/retlforRDW/rfx/src
cp * INSTALL_DIR/retlforRDW/rfx/src

Compile RMS batch libraries and programs

 **Note:** Warning messages may appear during the compilation of the batch. These warnings can be ignored if the batch executables are successfully generated.

Setting Environment Variables

- 1 As the retek user, make sure the following variables are set:
 -  **Note:** INSTALL_DIR is the location where RMS 11 was installed.
 -  **Note:** Make sure the path for make, makedepend, and the compiler are in \$PATH environment variable.
 - MMHOME=INSTALL_DIR/rms
 - MMUSER=RMS Schema Owner
 - PASSWORD=RMS Schema Owner Password
 - ORACLE_HOME=Location of Oracle install
 - ORACLE_SID=The Oracle Sid for the RMS database
- 2 AIX only:
 - LIBPATH=\$ORACLE_HOME/lib:\$MMHOME/oracle/lib/bin:\$LDPATH
 - OBJECT_MODE=64
 - LINK_CTRN=L_PTHREADS_D7
- 3 HP only:
 - SHLIB_PATH=\$ORACLE_HOME/lib:\$MMHOME/oracle/lib/bin:\$SH_LIBPATH
- 4 Solaris only:
 - LD_LIBRARY_PATH=\$ORACLE_HOME/lib:\$MMHOME/oracle/lib/bin:\$LD_LIBRARY_PATH
- 5 Copy the files from staging area/batch/lib/src to INSTALL_DIR/rms/oracle/lib/src
- 6 Change directories to INSTALL_DIR/rms/oracle/lib/src and run the following commands
- 7 To make library dependencies

```
make -f retek.mk depend 2>&1 | tee libdpnd.log
```
- 8 Check the libdpnd.log file for errors
- 9 To make batch libraries

```
make -f retek.mk retek rms resa 2>&1 | tee libretek.log
```
- 10 Check the libretek.log file for errors
- 11 To install batch libraries

```
make -f retek.mk install
```
- 12 The batch libraries should now be in INSTALL_DIR/rms/oracle/lib/bin
- 13 Copy the files from staging are/batch/proc/src to INSTALL_DIR/rms/oracle/proc/src
- 14 Change directories to INSTALL_DIR/rms/oracle/proc/src and run the following commands
- 15 To make dependencies

```
make -f mts.mk rms-depend recs-depend rtm-depend resa-depend 2>&1 | tee srcdnpd.log
```

13 Check the srccpnd.log file for errors

14 To make batch programs

Because of an additional make command the following command must be run first

```
make -f rms.mk PRODUCT_PROCFLAGS=dynamic=ansi ditinsrt
```

To make the rest of the batch programs run the following command

```
make -f mts.mk rms-ALL recs-ALL resa-ALL rtm-ALL 2>&1 | tee  
srcall.log
```

15 Check the srcall.log file for errors

16 To install batch programs

```
make -f mts.mk rms-install recs-install resa-install rtm-install
```

17 The batch programs should now be in INSTALL_DIR/rms/oracle/proc/bin



Note: The following steps only need to be completed if Oracle Financials will be interfaced

18 To make FIF batch programs

19 To make the dependencies run this command

```
make -f mts.mk fif-depend
```

20 To make the batch program run this command

```
make -f mts.mk fif-ALL
```

21 To install batch programs

```
make -f mts.mk fif-install
```

22 The Oracle Financials Interface batch programs should now be in
INSTALL_DIR/rms/oracle/proc/bin

Chapter 2 – Application Server Installation Instructions



Note: INSTALL_DIR is the directory where the RMS 11.x files were extracted to. 9iAS10G_ORACLE_HOME is the location where Oracle 9iAS 10g Forms and Reports Services (9iAS 10g) was installed.

Mount CD-ROM on the Database Server

- 1 Copy the rms1105apppatch.zip file from the CD /appserverunix directory to a newly created staging directory on your UNIX server.
- 2 Unzip the file by entering:

```
unzip rms1105apppatch.zip
```

Setup

- 1 As the retek user, set the DISPLAY variable to the IP address plus “:0.0” (ie: 10.1.1.1:0.0) of the machine that is being used to perform the compilation from.
- 2 As the retek user, set the following variables:



Note: INSTALL_DIR is the location where RMS 11 was installed.



Note: 9iAS10G_ORACLE_HOME is the location where Oracle 9iAS 10g was installed.

```
ORACLE_HOME=9iAS10G_ORACLE_HOME
```

```
PATH=$ORACLE_HOME/bin:INSTALL_DIR/forms9i_scripts:$PATH
```

Solaris only:

```
LD_LIBRARY_PATH=$ORACLE_HOME/lib:$ORACLE_HOME/jdk/jre/lib/sparc:$ORACLE_HOME/jdk/jre/lib/sparc/native_threads
```

HP-UX only:

```
SHLIB_PATH=$ORACLE_HOME/lib32:$ORACLE_HOME/lib:$ORACLE_HOME/jdk/jre/lib/PA_RISC:$ORACLE_HOME/jdk/jre/lib/PA_RISC/server
```

AIX only:

```
LD_LIBRARY_PATH=$ORACLE_HOME/lib:$ORACLE_HOME/lib32:$ORACLE_HOME/jdk/jre/lib
```

```
LIBPATH=$LD_LIBRARY_PATH
```

All:

```
CLASSPATH=$ORACLE_HOME/jlib/debugger.jar:$ORACLE_HOME/jlib/utj90.jar:$ORACLE_HOME/jlib/ewt3.jar:$ORACLE_HOME/jlib/share.jar
```

```
FORMS90_BUILDER_CLASSPATH=$CLASSPATH
```

```
FORMS90_PATH=INSTALL_DIR/toolset/bin:INSTALL_DIR/rms/forms/bin:$ORACLE_HOME/forms90
```

```
REPORTS_PATH=INSTALL_DIR/rms/reports/bin:$ORACLE_HOME/forms90
```

Solaris/AIX only:

UP=<RMS schema owner>/<RMS schema password>@<RMS database>

HP-UX only:

UP=<RMS schema owner>/<RMS schema password>\@<RMS database>

Toolset

- 1 Copy all the files from staging area/toolset/src to INSTALL_DIR/toolset/src
- 2 Copy all libraries (*.pll files) in the INSTALL_DIR/toolset/src directory to the INSTALL_DIR/toolset/bin directory.
- 3 Change directories to INSTALL_DIR/toolset/bin.
- 4 Run f90plsqlconv_pll_stand45 to automatically attach the Forms 9i library rp2rro.dll to stand45.dll. This library must be attached to stand45.dll in order to run RMS reports.
- 5 Remove the newly created stand45.dll should it be created from running f90plsqlconv_pll_stand45
- 6 Run pl2plx9i_toolset to compile all Toolset .dll's.
- 7 Check to make sure that each .dll file has a corresponding .plx (to ensure that all .dll's compiled successfully). If a library fails to compile (there is no .plx file), it will have to be manually compiled with Oracle 9iDS 10g. See Appendix F of the RMS 11 Install Guide for manual compilation instructions
- 8 Remove all newly created .plx files.
- 9 Run fmb2fm9i_fmb (in INSTALL_DIR/toolset/bin) to compile the Toolset reference forms.
- 10 Remove all newly created fm_*.fmx files (reference forms should not have executable files).
- 11 Run fmb2fm9i (in INSTALL_DIR/toolset/bin) to generate Toolset runtime forms – .fmx's.
- 12 Check to make sure that each non-reference form (.fmb file) has a corresponding .fmx file. If a form fails to compile (there is no .fmx file), it will have to be manually compiled with Oracle 9iDS 10g. See Appendix F of the RMS 11 Install Guide for manual compilation instructions.



Note: Disregard fm_*.fmx files should they be created. These files should be removed. They should NOT exist in the INSTALL_DIR/toolset/bin directory.

- 13 Remove all non-reference form forms from INSTALL_DIR/toolset/bin; the following syntax will leave all reference forms (fm_*.fmb) in the bin directory, while removing all other forms:

```
> for PROG in `ls *.fmb | grep -v fm_`  
> do PROGNAME=`echo $PROG`  
> rm $PROGNAME  
> done
```
- 14 Copy all menus (*.mmx files) in the INSTALL_DIR/toolset/src directory to the INSTALL_DIR/toolset/bin directory.
- 15 Run mm2mm9i (in INSTALL_DIR/toolset/bin) to generate Toolset runtime menus – .mmx's.

- 16 Check to make sure that each .mmb file has a corresponding .mmx file. If a menu fails to compile (there is no .mmx file), it will have to be manually compiled with Oracle 9iDS 10g. See Appendix F of the RMS 11 Install Guide for manual compilation instructions.



Note: Should .err files be created by the compilation scripts above, these files are logs of the compilation process and can be removed.

- 17 Remove all .mmb files from INSTALL_DIR/toolset/bin.

Forms

- 1 Copy all the files from staging area/forms/src to INSTALL_DIR/rms/forms/src
- 2 Copy all libraries (.pll files) in the INSTALL_DIR/rms/forms/src directory to the directories to the INSTALL_DIR/rms/forms/bin directory.
- 3 Change directories to INSTALL_DIR/rms/forms/bin.
- 4 Run pll2plx9i_forms to compile all RMS .pll's.
- 5 Check to make sure that each .pll file has a corresponding .plx (to ensure that all .pll's compiled successfully). If a library fails to compile (there is no .plx file), it will have to be manually compiled with Oracle 9iDS 10g. See Appendix F of the RMS 11 Install Guide for manual compilation instructions
- 6 Remove all newly created .plx files.
- 7 Copy all forms (*.fmb files) in the INSTALL_DIR/rms/forms/src directory to the INSTALL_DIR/rms/forms/bin directory.
- 8 Run fmb2fmx9i_fm (in INSTALL_DIR/rms/forms/bin) to compile the RMS reference forms.
- 9 Remove all newly created fm_*.fmx files (reference forms should not have executable files).
- 10 Run fmb2fmx9i (in INSTALL_DIR/rms/forms/bin) to generate RMS runtime forms – .fmx's.
- 11 Check to make sure that each non-reference form .fmb file has a corresponding .fmx file. If a form fails to compile (there is no .fmx file), it will have to be manually compiled with Oracle 9iDS 10g. See Appendix F of the RMS 11 Install Guide for manual compilation instructions.



Note: Disregard fm_*.fmx files should they be created. These files should be removed. They should NOT exist in the INSTALL_DIR/rms/forms/bin directory.

- 12 Remove all non-reference form forms from INSTALL_DIR/rms/forms/bin; the following syntax will leave all reference forms (fm_*.fmb) in the bin directory, while removing all other forms:

```
> for PROG in `ls *.fmb | grep -v fm_`  
> do PROGNAME=`echo $PROG`  
> rm $PROGNAME  
> done
```

- 13 Copy all menus (*.mmb files) in the INSTALL_DIR/rms/forms/src directory to the INSTALL_DIR/rms/forms/bin directory.

- 14 Run mmb2mmx9i (in INSTALL_DIR/rms/forms/bin) to generate RMS runtime menus – .mmx's.

15 Check to make sure that each .mmb file has a corresponding .mmx file. If a form fails to compile (there is no .mmx file), it will have to be manually compiled with Oracle 9iDS 10g. See Appendix F of the RMS 11 Install Guide for manual compilation instructions.

16 Remove all .mmb files from INSTALL_DIR/rms/forms/bin.



Note: Should .err files be created by the compilation scripts above, these files are logs of the compilation process and can be removed.

Help Files

1 Change directories to INSTALL_DIR/web_html/helpfiles/english/rms and remove all existing help files

```
rm -rf *
```

2 Change directories to staging area/help

3 Copy all the files and folders from staging area/help to
INSTALL_DIR/web_html/helpfiles/english/rms

```
cp -R * INSTALL_DIR/web_html/helpfiles/english/rms
```