

**Oracle Retail® Merchandising
System™
10.1.12 French**

Installation Guide

Corporate Headquarters:

Oracle
950 Nicollet Mall
Minneapolis, MN 55403
USA
888.61.RETEK (toll free US)
Switchboard:
+1 612 587 5000
Fax:
+1 612 587 5100

European Headquarters:

Oracle
110 Wigmore Street
London
W1U 3RW
United Kingdom
Switchboard:
+44 (0)20 7563 4600
Sales Enquiries:
+44 (0)20 7563 46 46
Fax:
+44 (0)20 7563 46 10

The software described in this documentation is furnished under a license agreement, is the confidential information of Oracle Retail Inc., and may be used only in accordance with the terms of the agreement.

No part of this documentation may be reproduced or transmitted in any form or by any means without the express written permission of Oracle Customer Support, 950 Nicollet Mall, Minneapolis, MN 55403, and the copyright notice may not be removed without the consent of Oracle.

Information in this documentation is subject to change without notice.

Oracle Retail provides product documentation in a read-only-format to ensure content integrity. Oracle Customer Support cannot support documentation that has been changed without Oracle authorization.

The functionality described herein applies to this version, as reflected on the title page of this document, and to no other versions of software, including without limitation subsequent releases of the same software component. The functionality described herein will change from time to time with the release of new versions of software and Oracle reserves the right to make such modifications at its absolute discretion.

Oracle Retail® Merchandising System™ is a trademark of Oracle.

Oracle and the Oracle logo are registered trademarks of Oracle.

This unpublished work is protected by confidentiality agreement, and by trade secret, copyright, and other laws. In the event of publication, the following notice shall apply:

©2005 Oracle. All rights reserved.

All other product names mentioned are trademarks or registered trademarks of their respective owners and should be treated as such.

Printed in the United States of America.

Customer Support

Customer Support hours

Customer Support is available 7x24x365 via email, phone, and Web access.

Depending on the Support option chosen by a particular client (Standard, Plus, or Premium), the times that certain services are delivered may be restricted. Severity 1 (Critical) issues are addressed on a 7x24 basis and receive continuous attention until resolved, for all clients on active maintenance. Oracle customers on active maintenance agreements may contact a global Customer Support representative in accordance with contract terms in one of the following ways.

Contact Method	Contact Information
E-mail	support@retek.com
Internet (ROCS)	rocs.retek.com Oracle Retail's secure client Web site to update and view issues
Phone	+1 612 587 5800
Toll free alternatives are also available in various regions of the world:	
Australia	+1 800 555 923 (AU-Telstra) or +1 800 000 562 (AU-Optus)
France	0800 90 91 66
Hong Kong	800 96 4262
Korea	00 308 13 1342
United Kingdom	0800 917 2863
United States	+1 800 61 RETEK or 800 617 3835
Mail	Oracle Customer Support 950 Nicollet Mall Minneapolis, MN 55403

Toll free alternatives are also available in various regions of the world:

Australia	+1 800 555 923 (AU-Telstra) or +1 800 000 562 (AU-Optus)
-----------	--

France	0800 90 91 66
--------	---------------

Hong Kong	800 96 4262
-----------	-------------

Korea	00 308 13 1342
-------	----------------

United Kingdom	0800 917 2863
----------------	---------------

United States	+1 800 61 RETEK or 800 617 3835
---------------	---------------------------------

When contacting Customer Support, please provide:

- Product version and program/module name.
- Functional and technical description of the problem (include business impact).
- Detailed step-by-step instructions to recreate.
- Exact error message received.
- Screen shots of each step you take.

Contents

Chapter 1 – Database server installation instructions..... 1

Mount CD-ROM on the database server	1
Update XML	2
Update DDL.....	2
Update control tables	2
Update packages, stored procedures and functions	3
Update RMS RETL extracts	3
Recompile libraries and batch programs.....	3

Chapter 2 – Application Server installation instructions..... 5

Forms 6i installation instructions.....	5
Forms 9i Installation instructions.....	6
Forms.....	6

Chapter 1 – Database server installation instructions

Before you apply the RMS 10.1.12 French patch:

- Make a backup of all your objects and database schema.
- Check that RMS 10.1.11 French is installed.
- Review the enclosed RMS 10.1.12 patch Release Notes.
- Review each of the enclosed SIR documents.

Before copying over any files:

- Note whether customizations have been made to the module. If so, then the customizations must be reapplied over the new version of the module (or the fix may need to be applied to the custom version of the code).
- Copy the original files to a different directory before copying over them in case they need to be referred to at a later date.



Note: These instructions refer to rmsdev10 as the Oracle owning schema.

Mount CD-ROM on the database server

1. Mount the CD-ROM on your database server.
2. Copy the `rms10112frdbpatch.tar.z` file from the CD/dbserverunix directory to a newly created staging directory on your UNIX server.
3. Log in to UNIX.
4. Change directories to the staging directory.



Note: The tar file must have a `.Z` extension.

5. If the tar file has a “z” in lowercase, change it by typing:

```
mv rms10112frdbpatch.tar.z rms10112frdbpatch.tar.Z
```

6. Uncompress the tar file by entering:

```
uncompress rms10112frdbpatch.tar.Z
```

7. Untar the tar file by entering:

```
tar xvf rms10112frdbpatch.tar
```

Update XML

1. Change directories to <staging area>/xml.
2. Review and understand the scripts before running them.
3. If you have customized any objects, make modifications.
4. Log in to SQLPLUS as the rmsdev10 user.
5. Enter the following command:
SQL> @patch10112xml.sql
6. View the spool file patch10112xml.log when finished to verify that no errors were found.

Update DDL

1. Change directories to <staging area>/dbc.
2. Review and understand the scripts before running them.
3. If you have customized any objects, make modifications.
4. Log in to SQLPLUS as the rmsdev10 user.
5. Enter the following command:
SQL> @patch10112dbc.sql
6. View the spool file patch10112dbc.log when finished to verify that no errors were found.

Update control tables

1. On the server, change directories to <staging area>/sqlplus.
2. Log in to SQLPLUS as rmsdev10.
3. Enter the following command to update control tables:
SQL> @patch10112ctl.sql
4. View the spool file patch10112ctl.log when finished to verify that no errors were found.

Update packages, stored procedures and functions



Note: During revalidating, deadlocks may appear. This occurrence is normal because all objects should revalidate.

1. On the server, change directories to <staging area>/db_objects.
2. Log in to SQLPLUS as rmsdev10.
3. Enter the following command to update packages, procedures, and functions:
`SQL> @patch10112rms.sql`
4. Exit SQLPlus.
5. View the spool file patch10112rms.log when finished to verify that no errors were found.
6. After you have compiled all these objects, validate any objects that may have become invalid. You can do this by using the Oracle utility dbms_utility.compile_schema or the script, inv_obj_comp.sql, provided at <staging area>/utility. Run this script until there are no invalid objects.

Update RMS RETL extracts

1. On the server, change directories to <staging area>/retl/rfx/src
2. Copy files to INSTALL_DIR/retl/rfx/src
`cp * INSTALL_DIR/retl/rfx/src`
3. Change directories to <staging area>/retl/rfx/schema
4. Copy files to INSTALL_DIR/retl/rfx/schema
`cp * INSTALL_DIR/retl/rfx/schema`

Recompile libraries and batch programs

After the packages/procedures have been successfully compiled:

1. Copy the batch library from <staging area>/batch/lib/src into the applicable directories.
2. Copy the base RMS C programs from <staging area>/batch/proc/src into the appropriate directories.
3. Compile the batch library and base RMS C programs as directed in the RMS 10.1 Installation Guide.
4. Because of an addition to the make command, you must run the following command from INSTALL_DIR/rms/oracle/proc/src directory:
`make -f rms.mk PRODUCT_PROCFLAGS=dynamic=ansi ditinsrt`

Chapter 2 – Application Server installation instructions



Note: If customizations have been made to any libraries, forms, menus, or reports, make sure to back up these customizations so that they can be re-applied following the 10.1.12 patch upgrade.

Forms 6i installation instructions

1. Mount the CD-ROM on your UNIX application server.
2. Change directories to /appserverunix.
3. Copy the `rms10112frapppatch.tar.Z` file from the CD/appserverunix directory to a newly created staging directory on your UNIX application server.
4. Log in to UNIX.
5. Change directories to the staging directory.
 Note: The tar file must have a `.Z` extension.
6. If the tar file has a `Z` in lowercase, change it by typing:
`mv rms10112frapppatch.tar.Z rms10112frapppatch.tar.z`
7. Uncompress the tar file by entering:
`uncompress rms10112frapppatch.tar.Z`
8. Untar the tar file by entering:
`tar xvf rms10112frapppatch.tar`
9. Make sure your UNIX environment is set up properly to compile Oracle Forms (see the RMS 10.1 Installation Guide for more information).
10. Copy the RMS forms source code (*.fmb) located on UNIX in the `<staging area>/forms/src` to your UNIX Web forms src directory.
11. In the Web forms src directory, compile the RMS forms (*.fmb) as outlined in the RMS 10.1 Installation Guide, Appendix B.
12. Move all compiled forms (*.fmx) in the Web forms src directory to the bin directory.
13. The RMS forms server process and reports server process should be reloaded after the RMS 10.1.12 executables have been copied to the appropriate UNIX Web forms directories.

Forms 9i installation instructions



Note: If customizations have been made to any libraries, forms, menus, or reports, make sure to back up these customized modules so that they can be re-applied following the RMS 10.1.12 patch upgrade and prior to the Forms 9i upgrade. .

1. Mount the CD-ROM on your UNIX application server.
2. Change directories to /appserverunix.
3. Copy the `rms10112frapppatch.tar.Z` file from the CD /appserverunix directory to a newly created staging directory on your UNIX Application server.
4. Log in to UNIX.
5. Change directories to the staging directory.
 **Note:** The tar file must have a `.Z` extension.
6. If the tar file has a `Z` in lowercase, change it by typing:
`mv rms10112frapppatch.tar.Z rms10112frapppatch.tar.z`
7. Uncompress the tar file by entering:
`uncompress rms10112frapppatch.tar.z`
8. Untar the tar file by entering:
`tar xvf rms10112frapppatch.tar`
9. Make sure your UNIX environment is set up properly to compile Oracle Forms.

Forms

1. Change directories to <staging area>/forms/src
2. Copy files to `INSTALL_DIR/forms/src`.
3. Change directories to `INSTALL_DIR/forms/src`.
4. Run `fmb2fmx9i` to generate Forms 9i runtime forms (fmx)s. This script does not compile fmb(s).
5. Check to make sure that each .fmb file has a corresponding .fmx file. If a form fails to convert (there is no .fmx file), it will have to be manually compiled/converted with Forms Builder 9i (if 9iDS is installed); or contact Oracle Support if there is no means of manually compiling with Forms Builder.



Note: Disregard `fm_*.fmx` files should they be created. These files should be removed. They should **not** be copied to the `INSTALL_DIR/forms/bin` directory.

6. Move all newly created fmx files to the `INSTALL_DIR/forms/bin` directory.
 **Note:** Should .err files be created from the compilation scripts above, these files are logs of the compilation process and can be removed.