

Mapping and Simple Transformation Document

Related Mapping (copy from related mapping)

Mapping Name
RMS Transfer Detail
Add or Modify

Mapping Participants	
Application	RMS
Type	TsfDtlDesc.dtd

XML Tag Name	Included Mapping	Cardinality of included mapping	Table Name	Column Name	Data Type	Length	Permissible values and descriptions	Keys (pk)	Required? (yes/no)
tsf_no			TSFHEAD	TSF_NO	NUMBER	10	Contains the number that uniquely identifies the transfer within the system.	PK, FK1	Yes
doc_type			Generate	DOC_TYPE	VARCHAR2	1	'T'ransfer		
item			TSFDETAIL	ITEM	VARCHAR2	25	Unique alphanumeric value that identifies the item.	PK, FK1	Yes
physical_from_loc			Generated	PHYSICAL_FROM_LOC	NUMBER	10	This field contains the physical source location for the transfer.		
from_loc_type			Generated	FROM_LOC_TYPE	VARCHAR2	1	Generated based off of the from Location		
from_loc			TSFHEAD	FROM_LOC	NUMBER	10	This field contains the source location for the transfer.		
physical_to_loc			Generated	PHYSICAL_TO_LOC	NUMBER	10	This field contains the physical destination location for the transfer.		
to_loc_type			Generated	TO_LOC_TYPE	VARCHAR2	1	Generated based off of the to Location		
to_loc			TSFHEAD	TO_LOC	NUMBER	10	This field contains the destination location for the transfer. A virtual store can never have a transfer sent to it.		
tsf_qty			TSFDETAIL	TSF_QTY	NUMBER	(12,4)	This field contains the total quantity of the item reserved at the from location for this transfer.		Yes

Mapping and Simple Transformation Document

Related Mapping (copy from related mapping)

Mapping Name
RMS Transfer Detail
Add or Modify

Mapping Participants	
Application	RMS
Type	TsfDtlDesc.dtd

XML Tag Name	Included Mapping	Cardinality of included mapping	Table Name	Column Name	Data Type	Length	Permissible values and descriptions	Keys (pk)	Required? (yes/no)
price			Generated from PRICING_ATTRIB_SQL.GET_RETAIL - value in O_standard_unit_retail_loc	PRICE	NUMBER	(20,4)	Contains the price of the merchandise per standard UOM. Returned from call to PRICING_ATTRIB_SQL.GET_RETAIL.		No
selling_uom			Generated from PRICING_ATTRIB_SQL.GET_RETAIL - O_selling_uom_location	SELLING_UOM	VARCHAR2	4	Contains the selling UOM of the item. Returned from call to PRICING_ATTRIB_SQL.GET_RETAIL.		No
ticket_type_id			ITEM_TICKET	TICKET_TYPE_ID	NUMBER	4	Contains the receiving ticket type of the item. Retrieved from the ITEM_TICKET table.		No
priority			Always 1 now (reserved for use in the future)	PRIORITY	NUMBER	4	Always 1 now, should it be? 1-9999, 1 highest		

