

Oracle® Data Guard

Broker

11g Release 1 (11.1)

B28295-03

August 2008

Oracle Data Guard Broker, 11g Release 1 (11.1)

B28295-03

Copyright © 1999, 2008, Oracle. All rights reserved.

Primary Author: Kathy Rich

Contributors: Gary Allison, George Claborn, Sean Connolly, Jay Davison, Ray Dutcher, Mahesh Girkar, Michael Harvey, Nitin Karkhanis, Sadhana Kyathappala, Steve Lee, Jiangbin Luo, Venkat Maddali, Bob McGuirk, Ashish Ray, Vivian Schupmann, Lawrence To, Stephen Vivian, Hongjie Yang

The Programs (which include both the software and documentation) contain proprietary information; they are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright, patent, and other intellectual and industrial property laws. Reverse engineering, disassembly, or decompilation of the Programs, except to the extent required to obtain interoperability with other independently created software or as specified by law, is prohibited.

The information contained in this document is subject to change without notice. If you find any problems in the documentation, please report them to us in writing. This document is not warranted to be error-free. Except as may be expressly permitted in your license agreement for these Programs, no part of these Programs may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose.

If the Programs are delivered to the United States Government or anyone licensing or using the Programs on behalf of the United States Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the Programs, including documentation and technical data, shall be subject to the licensing restrictions set forth in the applicable Oracle license agreement, and, to the extent applicable, the additional rights set forth in FAR 52.227-19, Commercial Computer Software--Restricted Rights (June 1987). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

The Programs are not intended for use in any nuclear, aviation, mass transit, medical, or other inherently dangerous applications. It shall be the licensee's responsibility to take all appropriate fail-safe, backup, redundancy and other measures to ensure the safe use of such applications if the Programs are used for such purposes, and we disclaim liability for any damages caused by such use of the Programs.

Oracle, JD Edwards, PeopleSoft, and Siebel are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

The Programs may provide links to Web sites and access to content, products, and services from third parties. Oracle is not responsible for the availability of, or any content provided on, third-party Web sites. You bear all risks associated with the use of such content. If you choose to purchase any products or services from a third party, the relationship is directly between you and the third party. Oracle is not responsible for: (a) the quality of third-party products or services; or (b) fulfilling any of the terms of the agreement with the third party, including delivery of products or services and warranty obligations related to purchased products or services. Oracle is not responsible for any loss or damage of any sort that you may incur from dealing with any third party.

Contents

Preface	xv
Audience	xv
Documentation Accessibility	xv
Related Documents	xvi
Conventions	xvi
What's New in Oracle Data Guard Broker?	xvii
New Features in Data Guard Broker 11.1	xvii
1 Oracle Data Guard Broker Concepts	
1.1 Overview of Oracle Data Guard and the Broker	1-1
1.1.1 Data Guard Configurations and Broker Configurations	1-1
1.1.2 Oracle Data Guard Broker	1-2
1.2 Benefits of Data Guard Broker	1-3
1.3 Data Guard Broker Management Model	1-6
1.4 Data Guard Broker Components	1-7
1.5 Data Guard Broker User Interfaces	1-8
1.5.1 Oracle Enterprise Manager	1-8
1.5.2 Data Guard Command-Line Interface (DGMGRL)	1-9
1.6 Data Guard Monitor	1-10
1.6.1 Data Guard Monitor (DMON) Process	1-10
1.6.2 Configuration Management	1-11
1.6.3 Database Property Management	1-12
2 Oracle Data Guard Installation	
2.1 Oracle Data Guard Installation	2-1
2.2 Prerequisites	2-2
3 Managing Broker Configurations	
3.1 Configuration Support	3-1
3.2 Setting Up the Broker Configuration Files	3-3
3.2.1 Renaming the Broker Configuration Files	3-4
3.2.2 Managing Broker Configuration Files in an Oracle RAC Environment	3-4
3.2.2.1 Using Cluster File System (CFS) for Configuration Files	3-5

3.2.2.2	Using ASM Disk Groups for Configuration Files.....	3-5
3.2.2.3	Using Raw Devices for Configuration Files	3-6
3.3	Starting the Data Guard Broker	3-7
3.4	Management Cycle of a Broker Configuration.....	3-8
3.5	Enable and Disable Operations.....	3-10
3.6	Configuration Status.....	3-11

4 Managing Databases

4.1	Database Objects	4-1
4.2	Database States.....	4-1
4.2.1	Database State Transitions.....	4-3
4.3	Database Properties	4-4
4.3.1	Monitorable (Read-Only) Properties	4-5
4.3.2	Configurable (Changeable) Database Properties	4-6
4.4	Managing Redo Transport Services	4-7
4.4.1	Setting Up For Redo Transport.....	4-7
4.4.2	Managing Redo Transport Services for Data Protection Modes	4-8
4.4.3	Turning Redo Transport Services On and Off.....	4-8
4.4.4	Specifying Locations for Archived Redo Log Files.....	4-9
4.4.5	Other Redo Transport Settings	4-10
4.4.6	Redo Transport Services in an Oracle RAC Database Environment.....	4-10
4.5	Managing Log Apply Services.....	4-11
4.5.1	Managing Delayed Apply	4-12
4.5.2	Managing Parallel Apply with Redo Apply	4-12
4.5.3	Allocating Resources to SQL Apply.....	4-12
4.5.4	Managing SQL Apply Filtering	4-13
4.5.5	Managing SQL Apply Error Handling.....	4-13
4.5.6	Managing the DBA_LOGSTDBY_EVENTS Table	4-13
4.5.7	Apply Services in an Oracle RAC Database Environment.....	4-13
4.5.7.1	Selecting the Apply Instance.....	4-13
4.5.7.2	Apply Instance Failover.....	4-15
4.6	Managing Data Protection Modes.....	4-15
4.6.1	Setting the Protection Mode for Your Configuration.....	4-15
4.6.2	How the Protection Modes Influence Broker Operations.....	4-18
4.6.2.1	Upgrading or Downgrading the Current Protection Mode.....	4-18
4.6.2.2	Switchover Operations	4-19
4.6.2.3	Failover Operations.....	4-19
4.6.2.4	Disable and Enable Operations	4-20
4.6.2.5	Requirements For Removing a Database from the Configuration.....	4-20
4.6.2.6	Requirements On Other Operations.....	4-20
4.7	Managing Fast-Start Failover	4-21
4.7.1	Configure Properties to Tune Fast-Start Failover	4-21
4.7.2	Configure Conditions for Fast-start Failover.....	4-22
4.7.3	Application Initiated Fast-Start Failover	4-23
4.8	Managing Database Conversions	4-24
4.9	Database Status	4-24

5 Switchover and Failover Operations

5.1	Overview of Switchover and Failover in a Broker Environment	5-1
5.2	Choosing a Target Standby Database	5-2
5.2.1	Choosing a Target Standby Database for Switchover	5-2
5.2.2	Choosing a Target Standby Database for Failover	5-3
5.3	Switchover.....	5-3
5.3.1	Before You Perform a Switchover Operation	5-4
5.3.2	Starting a Switchover	5-5
5.3.3	How the Broker Performs a Switchover.....	5-5
5.4	Manual Failover	5-6
5.4.1	Complete and Immediate Manual Failovers	5-7
5.4.2	Performing a Manual Failover Operation.....	5-8
5.4.2.1	How the Broker Performs a Complete Failover Operation.....	5-9
5.4.2.2	How the Broker Performs an Immediate Failover Operation	5-11
5.4.3	Reenabling Disabled Databases After Failover or Switchover	5-11
5.4.3.1	How to Reinststate a Database	5-13
5.4.3.2	How to Re-create and Reenable a Disabled Database	5-14
5.5	Fast-Start Failover	5-14
5.5.1	Prerequisites for Enabling Fast-Start Failover	5-16
5.5.2	Enabling Fast-Start Failover	5-17
5.5.2.1	When Fast-Start Failover Is Enabled and the Observer Is Running	5-22
5.5.2.2	Restrictions When Fast-Start Failover is Enabled	5-24
5.5.2.3	Shutting Down the Primary Database When Fast-Start Failover Is Enabled ...	5-25
5.5.2.4	Performing Manual Role Changes When Fast-Start Failover Is Enabled	5-25
5.5.3	Directing a Fast-Start Failover From an Application.....	5-26
5.5.4	Viewing Fast-Start Failover Configuration Statistics and Status.....	5-26
5.5.4.1	V\$DATABASE View	5-27
5.5.4.2	V\$FS_FAILOVER_STATS View	5-29
5.5.5	Disabling Fast-Start Failover.....	5-29
5.5.6	Performance Considerations for Fast-Start Failover	5-32
5.5.7	Managing the Observer	5-33
5.5.7.1	Installing and Starting the Observer.....	5-34
5.5.7.2	Viewing Information About the Observer.....	5-34
5.5.7.3	What Happens if the Observer Fails?	5-35
5.5.7.4	Stopping the Observer	5-35
5.5.7.5	Moving the Observer to Another Computer	5-36
5.5.7.6	How the Observer Maintains Fast-Start Failover Configuration Information.	5-36
5.5.8	Reinstating the Former Primary Database in the Broker Configuration.....	5-37
5.5.8.1	Requirements	5-37
5.5.8.2	Restrictions on Reinstatement	5-37
5.5.8.3	How the Broker Handles a Failed Reinstatement.....	5-38
5.5.9	Shutting Down Databases In a Fast-Start Failover Environment.....	5-38

6 Scenarios Using Oracle Enterprise Manager

6.1	Scenario 1: Accessing the Data Guard User Interface	6-1
6.2	Scenario 2: Creating a Configuration or Adding an Additional Standby Database	6-4
6.3	Scenario 3: Adding an Existing RAC Standby Database.....	6-12

6.4	Scenario 4: Enabling Fast-Start Failover and the Observer.....	6-14
6.5	Scenario 5: Performing Routine Maintenance	6-20
6.5.1	Changing the State of a Database.....	6-20
6.5.2	Changing the Properties of a Database	6-21
6.5.3	Changing the Database Protection Mode.....	6-23
6.6	Scenario 6: Performing a Switchover Operation	6-25
6.7	Scenario 7: Invoking a Failover Manually.....	6-27
6.8	Scenario 8: Monitoring a Data Guard Configuration	6-30
6.8.1	Verifying a Broker Configuration	6-31
6.8.2	Viewing Log File Details.....	6-33
6.8.3	Monitoring Configuration Performance	6-34
6.9	Scenario 9: Using Metrics.....	6-36
6.9.1	Understanding the Data Guard Metrics.....	6-36
6.9.1.1	Fast-Start Failover Metrics.....	6-36
6.9.1.2	Data Guard Performance Metrics	6-36
6.9.1.3	Data Guard Status	6-36
6.9.2	Managing Data Guard Metrics	6-36
6.10	Scenario 10: Removing a Standby Database and Configuration	6-39
6.10.1	Remove a Standby Database.....	6-39
6.10.2	Remove the Data Guard Configuration	6-40

7 Scenarios Using the DGMGRL Command-Line Interface

7.1	Prerequisites for Getting Started	7-1
7.2	Scenario 1: Creating a Configuration.....	7-2
7.3	Scenario 2: Setting Database Properties.....	7-4
7.4	Scenario 3: Enabling the Configuration and Databases	7-6
7.5	Scenario 4: Setting the Configuration Protection Mode.....	7-7
7.6	Scenario 5: Enabling Fast-Start Failover and Starting the Observer.....	7-8
7.7	Scenario 6: Performing Routine Management Tasks.....	7-11
7.7.1	Changing Properties and States.....	7-11
7.7.1.1	Alter a Database Property	7-11
7.7.1.2	Alter the State of a Standby Database	7-11
7.7.1.3	Alter the State of a Primary Database.....	7-12
7.7.2	Disabling the Configuration and Databases.....	7-12
7.7.2.1	Disable a Configuration.....	7-12
7.7.2.2	Disable a Standby Database.....	7-12
7.7.3	Removing the Configuration or a Standby Database.....	7-13
7.8	Scenario 7: Performing a Switchover Operation	7-15
7.9	Scenario 8: Performing a Manual Failover Operation	7-18
7.10	Scenario 9: Reinstating a Failed Primary Database.....	7-19
7.11	Scenario 10: Converting a Physical Standby to a Snapshot Standby	7-21
7.12	Scenario 11: Monitoring a Data Guard Configuration	7-22

8 Data Guard Command-Line Interface Reference

8.1	Starting the Data Guard Command-Line Interface	8-1
8.1.1	DGMGRL Optional Parameters.....	8-1
8.1.2	DGMGRL Command Format and Parameters.....	8-3

8.1.3	DGMGRL Command Usage Notes.....	8-4
8.2	Exiting the Data Guard Command-Line Interface.....	8-5
	ADD DATABASE	8-6
	CONNECT	8-8
	CONVERT DATABASE.....	8-10
	CREATE CONFIGURATION	8-12
	DISABLE CONFIGURATION	8-14
	DISABLE DATABASE.....	8-15
	DISABLE FAST_START FAILOVER.....	8-16
	DISABLE FAST_START FAILOVER CONDITION.....	8-17
	EDIT CONFIGURATION (Property).....	8-18
	EDIT CONFIGURATION (Protection Mode).....	8-19
	EDIT DATABASE (Property).....	8-21
	EDIT DATABASE (Rename)	8-23
	EDIT DATABASE (State).....	8-24
	EDIT INSTANCE (AUTO PFILE).....	8-25
	EDIT INSTANCE (Property).....	8-26
	ENABLE CONFIGURATION	8-27
	ENABLE DATABASE	8-28
	ENABLE FAST_START FAILOVER	8-29
	ENABLE FAST_START FAILOVER CONDITION	8-31
	EXIT.....	8-32
	FAILOVER	8-33
	HELP	8-36
	QUIT	8-38
	REINSTATE DATABASE	8-39
	REMOVE CONFIGURATION	8-40
	REMOVE DATABASE	8-42
	REMOVE INSTANCE	8-44
	SHOW CONFIGURATION.....	8-45
	SHOW DATABASE	8-47
	SHOW FAST_START FAILOVER.....	8-50
	SHOW INSTANCE.....	8-51
	SHUTDOWN	8-53
	START OBSERVER.....	8-54
	STARTUP	8-56
	STOP OBSERVER.....	8-58
	SWITCHOVER	8-59

9 Database Properties

9.1	Monitored (Read-Only) Database Properties	9-1
9.1.1	InconsistentLogXptProps (Inconsistent Redo Transport Properties)	9-2

9.1.2	InconsistentProperties (Inconsistent Database Properties)	9-2
9.1.3	LogXptStatus (Redo Transport Status)	9-3
9.1.4	LsbyFailedTxnInfo (Logical Standby Failed Transaction Information).....	9-4
9.1.5	LsbyParameters (Logical Standby Parameters).....	9-4
9.1.6	LsbySkipTable (Logical Standby Skip Table)	9-4
9.1.7	LsbySkipTxnTable (SQL Apply Skip Transaction Table)	9-5
9.1.8	RecvQEntries (Receive Queue Entries).....	9-5
9.1.9	SendQEntries (Send Queue Entries)	9-6
9.1.10	StatusReport (Status Report).....	9-7
9.1.11	TopWaitEvents.....	9-8
9.2	Configurable Database Properties	9-8
9.2.1	AlternateLocation	9-10
9.2.2	ApplyInstanceTimeout	9-11
9.2.3	ApplyParallel.....	9-11
9.2.4	ArchiveLagTarget	9-12
9.2.5	Binding	9-12
9.2.6	BystandersFollowRoleChange	9-13
9.2.7	CommunicationTimeout.....	9-14
9.2.8	DbFileNameConvert	9-14
9.2.9	DelayMins	9-15
9.2.10	DGConnectIdentifier	9-16
9.2.11	FastStartFailoverAutoReinstate	9-17
9.2.12	FastStartFailoverLagLimit	9-17
9.2.13	FastStartFailoverPmyShutdown.....	9-18
9.2.14	FastStartFailoverTarget.....	9-19
9.2.15	FastStartFailoverThreshold	9-19
9.2.16	HostName	9-20
9.2.17	LogArchiveFormat	9-20
9.2.18	LogArchiveMaxProcesses.....	9-21
9.2.19	LogArchiveMinSucceedDest.....	9-21
9.2.20	LogArchiveTrace.....	9-22
9.2.21	LogFileNameConvert.....	9-23
9.2.22	LogShipping	9-23
9.2.23	LogXptMode	9-24
9.2.24	LsbyASkipCfgPr	9-25
9.2.25	LsbyASkipErrorCfgPr	9-25
9.2.26	LsbyASkipTxnCfgPr	9-26
9.2.27	LsbyDSkipCfgPr	9-27
9.2.28	LsbyDSkipErrorCfgPr	9-27
9.2.29	LsbyDSkipTxnCfgPr	9-28
9.2.30	LsbyMaxEventsRecorded	9-29
9.2.31	LsbyMaxSga.....	9-29
9.2.32	LsbyMaxServers	9-29
9.2.33	LsbyRecordAppliedDdl.....	9-30
9.2.34	LsbyRecordSkipDdl.....	9-30
9.2.35	LsbyRecordSkipErrors	9-31
9.2.36	LsbyPreserveCommitOrder	9-32

9.2.37	MaxConnections	9-32
9.2.38	MaxFailure	9-33
9.2.39	NetTimeout	9-33
9.2.40	ObserverConnectIdentifier	9-34
9.2.41	PreferredApplyInstance	9-34
9.2.42	RedoCompression	9-35
9.2.43	ReopenSecs	9-36
9.2.44	SidName	9-36
9.2.45	StandbyArchiveLocation	9-37
9.2.46	StandbyFileManagement	9-38

10 Troubleshooting Data Guard

10.1	Sources of Diagnostic Information	10-1
10.2	General Problems and Solutions	10-1
10.2.1	ORA-16596: Object Not Part of the Data Guard Broker Configuration	10-2
10.2.2	Redo Accumulating on the Primary Is Not Sent to Some Standby Databases	10-2
10.2.3	Many Log Files Are Received on a Standby Database But Not Applied	10-2
10.2.4	The Request Timed Out or Enterprise Manager Performance Is Sluggish	10-3
10.2.5	The Primary Database is Flashed Back	10-3
10.3	Troubleshooting Problems During a Switchover Operation	10-4
10.3.1	Failed Switchovers to Physical Standby Databases	10-4
10.3.1.1	Failure to Convert the Original Primary Database	10-4
10.3.1.2	Failure to Convert Target Physical Standby Database	10-5
10.3.1.3	Failure to Open New Primary Database	10-5
10.3.2	Failed Switchovers to Logical Standby Databases	10-6
10.3.2.1	Failure to Convert Original Primary Database	10-6
10.3.2.2	Failure to Convert Target Logical Standby Database	10-7
10.3.3	Additional Problems That May Occur During a Switchover Operation	10-7
10.4	Troubleshooting Problems During a Failover Operation	10-7
10.4.1	Failed Failovers to Physical Standby Databases	10-7
10.4.1.1	Failed Broker Complete Physical Failovers	10-7
10.4.1.2	Failed Broker Immediate Physical Failovers	10-8
10.4.2	Failed Failovers to Logical Standby Databases	10-8
10.5	Troubleshooting Problems with the Observer	10-8
10.5.1	Problems Starting the Observer	10-9
10.5.2	Problems Because the Observer Has Stopped	10-9
10.5.3	Capturing Observer Actions in the Observer Log File	10-10

A Changed and Deprecated Features

A.1	Changed Features	A-1
A.1.1	General Features That Changed	A-1
A.1.1.1	Changed Features in Release 11.1	A-1
A.1.1.2	Changed Features in Release 10.2	A-2
A.1.2	Changed Properties	A-2
A.1.2.1	Changed Properties in Release 11.1	A-2
A.1.2.2	Changed Properties in Release 10.2	A-2
A.1.3	Changed State Names	A-3

A.1.4	Changed DGMGRL Features in Release 10.2	A-4
A.2	Deprecated and Obsolete Features.....	A-4
A.2.1	Deprecated and Obsolete Features in Release 11.1.....	A-4
A.2.1.1	Deprecated and Obsolete Properties in Release 11.1	A-4
A.2.2	Deprecated and Obsolete Features in Release 10.2.....	A-4
A.2.2.1	Deprecated and Obsolete Properties in Release 10.2	A-5

B Data Guard Broker Upgrading and Downgrading

B.1	Upgrade from Release 9.2.0 to Release 11.1	B-1
B.2	Upgrade from Release 10. <i>n</i> to Release 11.1	B-2
B.3	Downgrade from Release 11.1	B-3

Glossary

Index

List of Examples

4-1	Using the SHOW DATABASE VERBOSE Command to Display Properties.....	4-5
4-2	Turn Off Redo Transport Services to All Standby Databases	4-9
4-3	Turn Off Redo Transport Services to a Specific Standby Database.....	4-9
7-1	Connecting to the Primary Database on the Local System	7-3
7-2	Connecting to the Primary Database on a Remote System.....	7-3
7-3	Altering a Database Property	7-11
7-4	Altering a Standby Database State	7-11
7-5	Disabling the Configuration and Primary Database	7-12
7-6	Disabling a Standby Database.....	7-13

List of Figures

1-1	Relationship of Objects Managed by the Data Guard Broker	1-7
1-2	Oracle Data Guard Broker	1-8
1-3	Databases With Broker (DMON) Processes.....	1-11
3-1	Oracle Data Guard Broker Configuration	3-3
3-2	Broker Configuration Setup in a CFS Area	3-5
3-3	Broker Configuration Setup with ASM	3-6
3-4	Broker Configuration Setup with Raw Devices	3-7
3-5	Life Cycle of a Broker Configuration and Its Databases	3-8
5-1	Relationship of Primary and Standby Databases and the Observer	5-16
5-2	The Observer in the Fast-Start Failover Environment.....	5-33
6-1	Create a Broker Configuration.....	6-2
6-2	Data Guard Overview Page	6-3
6-3	Add Standby Database Wizard - Introductory Page.....	6-5
6-4	Add Standby Database Wizard - Backup Type (Logical Standby Database)	6-6
6-5	Add Standby Database Wizard - Backup Type (Logical Standby Database)	6-6
6-6	Add Standby Database Wizard - Backup Options.....	6-7
6-7	Add Standby Database Wizard - Database Location.....	6-8
6-8	Add Standby Database Wizard - File Locations.....	6-9
6-9	Add Standby Database Wizard - Configuration	6-9
6-10	Add Standby Database Wizard - Review	6-10
6-11	Add Standby Database Wizard - Processing	6-11
6-12	Data Guard Overview Page - Creation in Progress	6-11
6-13	Adding an Existing RAC Standby Database to the Data Guard Configuration.....	6-12
6-14	Select an Existing Standby Database.....	6-13
6-15	Add Standby Database: Standby Configuration	6-13
6-16	Add Standby Database: Review	6-14
6-17	Fast-Start Failover Wizard: Configure	6-15
6-18	Fast-Start Failover Wizard: Set Observer	6-15
6-19	Fast-Start Failover Wizard: Enable Flashback Logging	6-16
6-20	Fast-Start Failover Wizard: Confirmation	6-17
6-21	Fast-Start Failover Wizard: Progress.....	6-17
6-22	Fast-Start Failover Is Successfully Enabled.....	6-18
6-23	Reinstating the Former Primary Database After a Fast-Start Failover.....	6-19
6-24	Alert Log Errors Page Showing That Fast-Start Failover Occurred	6-20
6-25	Changing the State or Properties of a Database	6-21
6-26	Standby Role Properties.....	6-22
6-27	Standby Advanced Properties	6-22
6-28	Common Properties.....	6-23
6-29	Change Protection Mode Page.....	6-23
6-30	Change Protection Mode - Standby Databases and Online Redo Log Files	6-24
6-31	Change Protection Mode - Process.....	6-24
6-32	Protection Mode Successfully Changed	6-25
6-33	Switchover Operation.....	6-25
6-34	Processing Page During Switchover	6-26
6-35	New Primary Database After Switchover	6-27
6-36	Data Guard Overview Page Showing ORA-16625 Error	6-28
6-37	Failover Confirmation Page	6-28
6-38	Failover Progress Page	6-29
6-39	Data Guard Overview Page After a Failover Operation Completes.....	6-30
6-40	Data Guard Overview Page Showing Observer Error	6-31
6-41	Verifying the Configuration	6-32
6-42	Results of the Verify Command.....	6-33
6-43	Viewing Log File Details.....	6-34
6-44	Performance Page	6-35

6-45	Data Guard Metrics	6-37
6-46	Alert Log Errors Page Showing the Observer Has Stopped.....	6-39
6-47	Removing a Standby Database	6-40
6-48	Removing a Data Guard Broker Configuration	6-40

List of Tables

1-1	Configuration Management With and Without the Broker	1-3
1-2	DGMGRL Commands	1-9
4-1	Database States and Descriptions	4-2
4-2	Data Guard Protection Modes and Requirements	4-17
5-1	Reenabling Disabled Databases After Failover or Switchover	5-12
5-2	FS_FAILOVER_STATUS Column of the V\$DATABASE View	5-27
5-3	FS_FAILOVER_OBSERVER_PRESENT Column of the V\$DATABASE View	5-34
6-1	Log File Details Page	6-33
8-1	Summary of DGMGRL Commands	8-3
8-2	Examples of Health Conditions	8-31
9-1	Configurable Properties	9-9
A-1	Changed Properties in Release 11.1	A-2
A-2	Changed Properties in Release 10.2	A-3
A-3	Database State Name Changes in Release 11.1	A-3
A-4	Deprecated and Obsolete Properties in Release 11.1	A-4
A-5	Deprecated and Obsolete Properties in Release 10.2	A-5

Preface

This document provides information about Oracle Data Guard Broker, a management and monitoring interface that helps you configure, monitor, and control an Oracle Data Guard broker configuration.

Audience

Oracle Data Guard Broker is intended for database administrators (DBAs) and system administrators who want to use the Oracle Data Guard broker to automate many of the tasks involved in configuring and monitoring an Oracle Data Guard configuration.

The discussions herein assume that readers are already familiar with Oracle Data Guard, Oracle Enterprise Manager, Oracle Real Application Clusters, and the network services provided by Oracle Net Services.

Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible, with good usability, to the disabled community. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Accessibility standards will continue to evolve over time, and Oracle is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be accessible to all of our customers. For more information, visit the Oracle Accessibility Program Web site at <http://www.oracle.com/accessibility/>.

Accessibility of Code Examples in Documentation

Screen readers may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, some screen readers may not always read a line of text that consists solely of a bracket or brace.

Accessibility of Links to External Web Sites in Documentation

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations regarding the accessibility of these Web sites.

TTY Access to Oracle Support Services

Oracle provides dedicated Text Telephone (TTY) access to Oracle Support Services within the United States of America 24 hours a day, 7 days a week. For TTY support, call 800.446.2398. Outside the United States, call +1.407.458.2479.

Related Documents

Refer to the following documentation for more information about Oracle Data Guard:

- *Oracle Data Guard Concepts and Administration.*
- Oracle release notes specific to your operating system.
- Oracle installation guide specific to your operating system.
- For more information about managing Oracle Data Guard through Oracle Enterprise Manager, see the online Help available with this graphical user interface. To access the online Help topics, click Help on the menu bar in Enterprise Manager.

Refer to the following documentation for information about related products:

- *Oracle Database Concepts*
- *Oracle Database Net Services Administrator's Guide*
- Oracle Enterprise Manager product documentation set
- *Oracle Real Application Clusters Administration and Deployment Guide*

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

What's New in Oracle Data Guard Broker?

This preface describes the new features added to Oracle Data Guard broker in Oracle Database 11g and provides links to additional information. For information about features that were introduced in earlier releases, refer to the documentation for those releases.

New Features in Data Guard Broker 11.1

This release provides the following new features:

- Fast-start failover enhancements

The following features increase the flexibility and manageability of customers' disaster-recovery configurations using Data Guard:

- Fast-start failover for a configuration operating in maximum performance mode

Allows fast-start failover to be enabled in a Data Guard broker configuration operating in maximum performance mode. The administrator can choose the maximum amount of data that may be lost if a fast-start failover is initiated.

- New DBMS_DG PL/SQL package

The DBMS_DG PL/SQL package allows applications to notify the observer process to initiate a fast-start failover to the target standby database.

- Fast-start failover for configurable conditions

Fast-start failover can be configured to occur when specific database conditions are detected. Certain conditions detectable through the database health-check mechanism and errors raised by the Oracle server (such as ORA errors) may be designated as conditions under which a fast-start failover should occur.

See Also:

- [Section 5.5, "Fast-Start Failover"](#)
- The DBMS_DG PL/SQL package in *Oracle Database PL/SQL Packages and Types Reference*

- Manageability enhancements

The following enhancements make it possible to use the Data Guard broker in a wider variety of disaster-recovery configurations:

- Support for snapshot standby databases

See Also: The DGMGRL [CONVERT DATABASE](#) command on page 8-10

- Support for Redo Apply on physical standby databases opened for read
- Improved support for redo transport options. Enables the administrator to specify a connect identifier for Redo Transport Services.
- Elimination of database downtime when changing the protection mode to and from maximum availability and maximum performance
- Allow a primary or logical standby database in a Data Guard Broker configuration to be mounted without having to be opened automatically
- The DGMGRL CLI `ADD DATABASE` command can import a pre-configured service attribute from a `LOG_ARCHIVE_DEST_n` parameter when adding a standby database to the configuration.
- Simplification of the database states managed by the broker. A primary database can be in either the `TRANSPORT-OFF` or `TRANSPORT-ON` state. A standby database can be in either the `APPLY-OFF` or `APPLY-ON` state.

- Compression of redo traffic over the network in a Data Guard configuration

This feature improves the network bandwidth utilization in a Data Guard configuration by compressing archived redo logs as they are transmitted over the network to standby databases, when the log is sent to satisfy a gap at a standby database.

See Also: [Section 9.2.42, "RedoCompression"](#) on page 9-35

- Better integration with the database recovery area because you can now specify `USE_DB_RECOVERY_FILE_DEST` as the value for the `AlternateLocation` and `StandbyArchiveLocation` database configurable properties.
- New Data Guard command-line interface (DGMGRL) commands include:
 - `CONVERT DATABASE TO [SNAPSHOT | PHYSICAL] STANDBY`
 - `DISABLE FAST_START FAILOVER CONDITION`
 - `ENABLE FAST_START FAILOVER CONDITION`
 - `SHOW FAST_START FAILOVER`

See Also: [Chapter 8, "Data Guard Command-Line Interface Reference"](#)

- New configurable properties include:
 - `DGConnectIdentifier` (replaces `InitialConnectIdentifier`)
 - `ObserverConnectIdentifier`
 - `RedoCompression`
- New configuration properties include:
 - `FastStartFailoverAutoReinstate`
 - `FastStartFailoverLagLimit`
 - `FastStartFailoverPmyShutdown`

- The `LsbyTxnConsistency` configurable database property has been renamed to `LsbyPreserveCommitOrder`
- New default of `ASYNC` for the `LogXptMode` configurable database property

See Also: [Chapter 9, "Database Properties"](#)

Oracle Data Guard Broker Concepts

This chapter describes the Oracle Data Guard broker, its architecture and components, and how it automates the creation, control, and monitoring of a Data Guard configuration. It contains the following topics:

- [Overview of Oracle Data Guard and the Broker](#)
- [Benefits of Data Guard Broker](#)
- [Data Guard Broker Management Model](#)
- [Data Guard Broker Components](#)
- [Data Guard Broker User Interfaces](#)
- [Data Guard Monitor](#)

See *Oracle Data Guard Concepts and Administration* for the definition of a Data Guard configuration and for complete information about Oracle Data Guard concepts and terminology.

1.1 Overview of Oracle Data Guard and the Broker

Oracle Data Guard ensures high availability, data protection, and disaster recovery for enterprise data. Data Guard provides a comprehensive set of services that create, maintain, manage, and monitor one or more standby databases to enable production Oracle databases to survive disasters and data corruptions. Data Guard maintains these standby databases as transactionally consistent copies of the primary database. If the primary database becomes unavailable because of a planned or an unplanned outage, Data Guard can switch any standby database to the production role, thus minimizing the downtime associated with the outage. Data Guard can be used with traditional backup, recovery, and cluster techniques, as well as the Flashback Database feature to provide a high level of data protection and data availability.

1.1.1 Data Guard Configurations and Broker Configurations

A *Data Guard configuration* consists of one primary database and up to nine standby databases. The databases in a Data Guard configuration are connected by Oracle Net and may be dispersed geographically. There are no restrictions on where the databases are located as long as they can communicate with each other. For example, you can have a standby database on the same system as the primary database, along with two standby databases on another system.

The Data Guard broker logically groups these primary and standby databases into a *broker configuration* that allows the broker to manage and monitor them together as an integrated unit. You can manage a broker configuration using either the Oracle

Enterprise Manager graphical user interface or the Data Guard command-line interface.

1.1.2 Oracle Data Guard Broker

The Oracle Data Guard broker is a distributed management framework that automates and centralizes the creation, maintenance, and monitoring of Data Guard configurations. The following list describes some of the operations the broker automates and simplifies:

- Creating Data Guard configurations that incorporate a primary database, a new or existing (physical, logical, or snapshot) standby database, redo transport services, and log apply services, where any of the databases could be Oracle Real Application Clusters (RAC) databases.
- Adding additional new or existing (physical, snapshot, logical, RAC or non-RAC) standby databases to an existing Data Guard configuration, for a total of one primary database, and from 1 to 9 standby databases in the same configuration.
- Managing an entire Data Guard configuration, including all databases, redo transport services, and log apply services, through a client connection to any database in the configuration.
- Managing the protection mode for the broker configuration.
- Invoking switchover or failover with a single command to initiate and control complex role changes across all databases in the configuration.
- Configuring failover to occur automatically upon loss of the primary database, increasing availability without manual intervention.
- Monitoring the status of the entire configuration, capturing diagnostic information, reporting statistics such as the redo apply rate and the redo generation rate, and detecting problems quickly with centralized monitoring, testing, and performance tools.

You can perform all management operations locally or remotely through the broker's easy-to-use interfaces: the Data Guard management pages in Oracle Enterprise Manager, which is the broker's graphical user interface (GUI), and the Data Guard command-line interface called DGMGRL.

These interfaces simplify the configuration and management of a Data Guard configuration. [Table 1-1](#) provides a comparison of configuration management using the broker's interfaces and using SQL*Plus.

Table 1–1 Configuration Management With and Without the Broker

	With the Broker	Without the Broker
General	Provides primary and standby database management as one unified configuration.	You must manage the primary and standby databases separately.
Standby Database Creation	Provides the Enterprise Manager wizards that automate and simplify the steps required to create a configuration with an Oracle database on each site, including creating the standby control file, online redo log files, datafiles, and server parameter files.	You must manually: <ul style="list-style-type: none"> ▪ Copy the database files to the standby database. ▪ Create a control file on the standby database. ▪ Create server parameter or initialization parameter files on the standby database.
Configuration and Management	Enables you to configure and manage multiple databases from a single location and automatically unifies all of the databases in the broker configuration.	You must manually: <ul style="list-style-type: none"> ▪ Set up redo transport services and log apply services on each database in the configuration. ▪ Manage the primary database and standby databases individually.
Control	<ul style="list-style-type: none"> ▪ Automatically set up redo transport services and log apply services. Simplify management of these services, especially in an Oracle RAC environment. ▪ Simplifies switchovers and failovers by allowing you to invoke them through a single command. ▪ Automates failover by allowing the broker to determine if failover is necessary and to initiate failover to a specified target standby database, with no need for DBA intervention and with either no loss of data or with a configurable amount of data loss. ▪ Integrates Cluster Ready Services (CRS)¹ and instance management over database role transitions. ▪ Provides mouse-driven database state changes and a unified presentation of configuration and database status. ▪ Provides mouse-driven property changes. 	You must manually: <ul style="list-style-type: none"> ▪ Use multiple SQL*Plus statements to manage the database. ▪ Coordinate sequences of multiple commands across multiple database sites to execute switchover and failover operations. ▪ Coordinate sequences of multiple commands to manage services and instances during role transitions.
Monitoring	<ul style="list-style-type: none"> ▪ Provides continuous monitoring of the configuration health, database health, and other runtime parameters. ▪ Provides a unified updated status and detailed reports. ▪ Provides integration with Oracle Enterprise Manager events. 	You must manually: <ul style="list-style-type: none"> ▪ Monitor the status and runtime parameters using fixed views on each database—there is no unified view of status for all of the databases in the configuration. ▪ Provide a custom method for monitoring Oracle Enterprise Manager events.

¹ Cluster Ready Services (CRS) are part of Oracle Clusterware.

1.2 Benefits of Data Guard Broker

The broker's interfaces improve usability and centralize management and monitoring of the Data Guard configuration. Available as a feature of the Enterprise Edition and Personal Edition of the Oracle database, the broker is also integrated with the Oracle

database and Oracle Enterprise Manager. These broker attributes result in the following benefits:

Disaster protection: By automating many of the manual tasks required to configure and monitor a Data Guard configuration, the broker enhances the high availability, data protection, and disaster protection capabilities that are inherent in Oracle Data Guard. Access is possible through a client to any system in the Data Guard configuration, eliminating any single point of failure. If the primary database fails, the broker automates the process for any one of the standby databases to replace the primary database and take over production processing. The database availability that Data Guard provides makes it easier to protect your data.

Higher availability and scalability with Oracle Real Application Clusters (RAC)

Databases: While Oracle Data Guard broker enhances disaster protection by maintaining transactionally consistent copies of the primary database, Data Guard, configured with Oracle high availability solutions such as Oracle Real Application Clusters (RAC) databases, further enhances the availability and scalability of any given copy of that database. The *intrasite* high availability of an Oracle RAC database complements the *intersite* protection that is provided by Data Guard broker.

Consider that you have a cluster system hosting a primary Oracle RAC database comprised of multiple instances sharing access to that database. Further consider that an unplanned failure has occurred. From a Data Guard broker perspective, the primary database remains available as long as at least one instance of the clustered database continues to be available for transporting redo data to the standby databases. Oracle Clusterware manages the availability of instances of an Oracle RAC database. Cluster Ready Services (CRS), a subset of Oracle Clusterware, works to rapidly recover failed instances to keep the primary database available. If CRS is unable to recover a failed instance, the broker continues to run automatically with one less instance. If the last instance of the primary database fails, the broker provides a way to fail over to a specified standby database. If the last instance of the primary database fails, and fast-start failover is enabled, the broker can continue to provide high availability by automatically failing over to a pre-determined standby database.

The broker is integrated with CRS so that database role changes occur smoothly and seamlessly. This is especially apparent in the case of a planned role switchover (for example, when a physical standby database is directed to take over the primary role while the former primary database assumes the role of standby). The broker and CRS work together to temporarily suspend service availability on the primary database, accomplish the actual role change for both databases during which CRS works with the broker to properly restart the instances as necessary, and then start services defined on the new primary database. The broker manages the underlying Data Guard configuration and its database roles while CRS manages service availability that depends upon those roles. Applications that rely on CRS for managing service availability will see only a temporary suspension of service as the role change occurs in the Data Guard configuration.

Note that while CRS helps to maintain the availability of the individual instances of an Oracle RAC database, the broker coordinates actions that maintain one or more physical or logical copies of the database across multiple geographically dispersed locations to provide disaster protection. Together, the broker and Oracle Clusterware provide a strong foundation for Oracle's high-availability architecture.

See Also: *Oracle Real Application Clusters Administration and Deployment Guide* for information about Oracle Clusterware and CRS

Automated creation of a Data Guard configuration: The broker helps you to logically define and create a Data Guard configuration consisting of a primary database and (physical or logical, snapshot, RAC or non-RAC) standby databases. The broker automatically communicates between the databases in a Data Guard configuration using Oracle Net Services. The databases can be local or remote, connected by a LAN or geographically dispersed over a WAN.

Oracle Enterprise Manager provides a wizard that automates the complex tasks involved in creating a broker configuration, including:

- Adding an existing standby database, or a new standby database created from existing backups taken through Enterprise Manager
- Configuring the standby control file, server parameter file, and datafiles
- Initializing communication with the standby databases
- Creating standby redo log files
- Enabling Flashback Database if you plan to use fast-start failover

Although DGMGRL cannot automatically create a new standby database, you can use DGMGRL commands to configure and monitor an existing standby database, including those created using Enterprise Manager.

Easy configuration of additional standby databases: After you create a Data Guard configuration consisting of a primary and a standby database, you can add up to eight new or existing, physical, snapshot, or logical standby databases to each Data Guard configuration. Oracle Enterprise Manager provides an Add Standby Database wizard to guide you through the process of adding more databases. It also makes all Oracle Net Services configuration changes necessary to support redo transport services and log apply services across the configuration.

Simplified, centralized, and extended management: You can issue commands to manage many aspects of the broker configuration. These include:

- Simplify the management of all components of the configuration, including the primary and standby databases, redo transport services, and log apply services.
- Coordinate database state transitions and update database properties dynamically with the broker recording the changes in a broker configuration file that includes profiles of all the databases in the configuration. The broker propagates the changes to all databases in the configuration and their server parameter files.
- Simplify the control of the configuration protection modes (to maximize protection, to maximize availability, or to maximize performance).
- Invoke the Enterprise Manager verify operation to ensure that redo transport services and log apply services are configured and functioning properly.

Simplified switchover and failover operations: The broker simplifies switchovers and failovers by allowing you to invoke them using a single key click in Oracle Enterprise Manager or a single command at the DGMGRL command-line interface (referred to in this documentation as *manual failover*). For *lights-out administration*, you can enable fast-start failover to allow the broker to determine if a failover is necessary and to initiate the failover to a pre-specified target standby database automatically, with no need for DBA intervention. Fast-start failover can be configured to occur with no data loss or with a configurable amount of data loss.

Fast-start failover allows you to increase availability with less need for manual intervention, thereby reducing management costs. Manual failover gives you control

over exactly when a failover occurs and to which target standby database. Regardless of the method you choose, the broker coordinates the role transition on all databases in the configuration. Once failover is complete, the broker posts the `DB_DOWN` event to notify applications that the new primary is available.

Note that you can use the `DBMS_DG` PL/SQL package to enable an application to initiate a fast-start failover when it encounters specific conditions. See [Section 4.7.3](#) for more information.

Only one command is required to initiate complex role changes for switchover or failover operations across all databases in the configuration. The broker automates switchover and failover to a specified standby database in the broker configuration. Enterprise Manager enables you to select a new primary database from a set of viable standby databases (enabled and running, with normal status). The `DGMGRL SWITCHOVER` and `FAILOVER` commands only require you to specify the target standby database before automatically initiating and completing the many steps in switchover or failover operations across the multiple databases in the configuration.

Built-in monitoring and alert and control mechanisms: The broker provides built-in validation that monitors the *health* of all of the databases in the configuration. From any system in the configuration connected to any database, you can capture diagnostic information and detect obvious and subtle problems quickly with centralized monitoring, testing, and performance tools. Both Enterprise Manager and `DGMGRL` retrieve a complete configuration view of the progress of redo transport services on the primary database and the progress of Redo Apply or SQL Apply on the standby database.

The ability to monitor local and remote databases and respond to events is significantly enhanced by the broker's health check mechanism and tight integration with the Oracle Enterprise Manager event management system.

Transparent to application: Use of the broker is possible for any database because the broker works transparently with applications; no application code changes are required to accommodate a configuration that you manage with the broker.

See Also: *Oracle Data Guard Concepts and Administration* for a complete description of the discrete steps that comprise the creation of standby databases and the other monitoring and control operations that have been automated or simplified by the broker

1.3 Data Guard Broker Management Model

The broker simplifies the management of a Data Guard environment by performing operations on the following logical objects:

- Configuration of databases
- A single database


The broker supports one or more Data Guard configurations, each of which includes a profile for the primary database and each standby database. A supported broker configuration consists of:

- A **configuration** object, which is a named collection of database profiles. A database **profile** is a description of a database object including its current state, current status, and properties. The configuration object profiles one primary database and its standby databases that can include a mix of physical, snapshot, and logical standby databases. The databases of a given configuration are typically distributed across multiple host systems.

- **Database** objects, corresponding to primary or standby databases. The broker uses a database object's profile to manage and control the state of a single database on a given system. The database object may be comprised of one or more instance objects if this is an Oracle RAC database.
- **Instance** objects. The broker treats a database as a collection of one or more named instances. The broker automatically discovers the instances and associates them with their database.

Figure 1–1 shows the relationship of these objects.

Figure 1–1 Relationship of Objects Managed by the Data Guard Broker



See also: [Chapter 3](#), [Chapter 4](#), and [Chapter 5](#) for more information about managing configuration and database objects

1.4 Data Guard Broker Components


The Oracle Data Guard broker consists of the following components:

- [Oracle Enterprise Manager](#)
- [Data Guard Command-Line Interface \(DGMGRL\)](#)
- [Data Guard Monitor](#)

Oracle Enterprise Manager and the Data Guard command-line interface (DGMGRL) are the broker client interfaces that help you define and manage a configuration consisting of a collection of primary and standby databases. DGMGRL also includes commands to create an **observer**, a process that facilitates fast-start failover. [Section 1.5](#) describes these interfaces in more detail.

The Data Guard monitor is the broker server-side component that is integrated with the Oracle database. Data Guard monitor is composed of several processes, including the DMON process, and broker configuration files that allow you to control the databases of that configuration, modify their behavior at runtime, monitor the overall health of the configuration, and provide notification of other operational characteristics. [Section 1.6](#) describes the Data Guard monitor in more detail.

Figure 1–2 shows these components of the broker.

Figure 1–2 Oracle Data Guard Broker

1.5 Data Guard Broker User Interfaces

You can use either of the broker's user interfaces to create a broker configuration and to control and monitor the configuration. The following sections describe the broker's user interfaces:

- [Oracle Enterprise Manager](#)
- [Data Guard Command-Line Interface \(DGMGRL\)](#)

1.5.1 Oracle Enterprise Manager

Oracle Enterprise Manager works with the Data Guard monitor to automate and simplify the management of a Data Guard configuration.

With Enterprise Manager, the complex operations of creating and managing standby databases are simplified through Data Guard management pages and wizards, including:

- An Add Standby Database wizard that helps you to create a broker configuration, if one does not already exist, having a primary database and a local or remote standby database. The wizard can create a physical, snapshot, or logical standby database or import an existing physical, snapshot, or logical (RAC or non-RAC) standby database. If the wizard creates a physical, snapshot, or logical standby database, the wizard also automates the creation of the standby control file, server parameter file, online and standby redo log files, and the standby datafiles.
- A switchover operation that helps you switch roles between the primary database and a standby database.
- A failover operation that changes one of the standby databases to the role of a primary database.
- Performance tools and graphs that help you monitor and tune redo transport services and log apply services.
- Property pages that allow you to set database properties on any database and, if applicable, the settings are immediately propagated to all other databases and server parameter files in the configuration.
- Event reporting through e-mail.

In addition, it makes all Oracle Net Services configuration changes necessary to support redo transport services and log apply services.

See Also: [Chapter 6, "Scenarios Using Oracle Enterprise Manager"](#)

1.5.2 Data Guard Command-Line Interface (DGMGRL)

The Data Guard command-line interface (DGMGRL) enables you to control and monitor a Data Guard configuration from the DGMGRL prompt or within scripts. You can perform most of the activities required to manage and monitor the databases in the configuration using DGMGRL commands.

DGMGRL also includes commands to create an observer process that continuously monitors the primary and target standby databases and evaluates whether failover is necessary, and then initiates a fast-start failover when conditions warrant.

[Table 1–2](#) lists the DGMGRL commands.

Table 1–2 DGMGRL Commands

Command	Description
ADD	Adds a standby database to the broker configuration
CONNECT	Connects to an Oracle instance
CONVERT	Converts a database between a physical standby database and a snapshot standby database
CREATE	Creates a broker configuration
DISABLE	Disables a configuration, a database, fast-start failover, or a fast-start failover condition
EDIT	Edits a configuration, database, or instance
ENABLE	Enables a configuration, a database, fast-start failover, or a fast-start failover condition
EXIT	Exits the program
FAILOVER	Changes a standby database to be the primary database
HELP	Displays description and syntax for individual commands
QUIT	Exits the program
REINSTATE	Changes a database marked for reinstatement into a viable standby database
REM	Comment to be ignored by DGMGRL
REMOVE	Removes a configuration, database, or instance
SHOW	Displays information about a configuration, database, instance, or fast-start failover
SHUTDOWN	Shuts down a currently running Oracle instance
START	Starts the fast-start failover observer
STARTUP	Starts an Oracle database instance
STOP	Stops the fast-start failover observer
SWITCHOVER	Switches roles between the primary database and a standby database

See Also: [Chapter 8](#) for complete reference information for the Data Guard command-line interface

1.6 Data Guard Monitor

The configuration, control, and monitoring functions of the broker are implemented by server-side software and configuration files that are maintained for each database that the broker manages. The software is called the Data Guard monitor.

The following sections describe how the Data Guard monitor interacts with the Oracle database and with remote Data Guard monitors to manage the broker configuration.

1.6.1 Data Guard Monitor (DMON) Process

The Data Guard monitor process (DMON) is an Oracle background process that runs for every database instance that is managed by the broker. When you start the Data Guard broker, a DMON process is created.


See Also: [Section 3.3](#) on page 3-7 for information on starting the broker

Whether you use Oracle Enterprise Manager or DGMGRL to manage a database, the DMON process is the server-side component that interacts with the local database and the DMON processes of the other databases to perform the requested function. The DMON process is also responsible for monitoring the health of the broker configuration and for ensuring that every database has a consistent description of the configuration.

See Also: *Oracle Database Concepts* for more information about the memory structures and processes that are used with an Oracle database

[Figure 1–3](#) shows the broker's DMON process as one of several background processes that constitute an instance of the Oracle database. Each database instance shown in the figure has its own DMON process.

Figure 1–3 Databases With Broker (DMON) Processes



The zigzag arrow in the center of [Figure 1–3](#) represents the two-way Oracle Net Services communication channel that exists between the DMON processes of two databases in the same broker configuration.

This two-way communication channel is used to pass requests between databases and to monitor the health of all of the databases in the broker configuration.

1.6.2 Configuration Management

The broker's DMON process persistently maintains profiles about all database objects in the broker configuration in a binary **configuration file**. A copy of this file is maintained by the DMON process for each of the databases that belong to the broker configuration. If it is an Oracle RAC database, each database's copy of the file is shared by all instances of the database.

This configuration file contains profiles that describe the states and properties of the databases in the configuration. For example, the file records the databases that are part of the configuration, the roles and properties of each of the databases, and the state of each database in the configuration.

The configuration data is managed transparently by the DMON process to ensure that the configuration information is kept consistent across all of the databases. The broker uses the data in the configuration file to configure and start the databases, control each database's behavior, and provide information to DGMGRL and Oracle Enterprise Manager.

See Also: [Section 4.3](#) on page 4-4 for more information

Whenever you add databases to a broker configuration, or make a change to an existing database's properties, each DMON process records the new information in its copy of the configuration file.

1.6.3 Database Property Management

Associated with each database are various properties that the DMON process uses to control the database's behavior. The properties are recorded in the configuration file as a part of the database's object profile that is stored there. Many database properties are used to control database initialization parameters related to the Data Guard environment.

To ensure that the broker can update the values of parameters in both the database itself and in the configuration file, you must use a server parameter file to control static and dynamic initialization parameters. The use of a server parameter file gives the broker a mechanism that allows it to reconcile property values selected by the database administrator (DBA) when using the broker with any related initialization parameter values recorded in the server parameter file.

When you set values for database properties in the broker configuration, the broker records the change in the configuration file and propagates the change to all of the databases in the Data Guard configuration.

Note: The broker supports both the default and nondefault server parameter file filenames. If you use a nondefault server parameter filename, the initialization parameter file must include the complete filename and location of the server parameter file. If this is an Oracle RAC database, there must be one nondefault server parameter file for all instances.

See Also: [Section 4.3.2](#) on page 4-6 for more information

Oracle Data Guard Installation

This chapter includes the following topics:

- [Oracle Data Guard Installation](#)
- [Prerequisites](#)

See Also: [Appendix B](#) for help with upgrading the Oracle databases and Oracle Enterprise Manager in a Data Guard broker configuration

2.1 Oracle Data Guard Installation

Oracle Data Guard is included with the Enterprise Edition of the Oracle database software. You can manage a Data Guard configuration by using either SQL*Plus, the Data Guard broker's command-line interface (DGMGRL), or Oracle Enterprise Manager 10g Grid Control.

To use DGMGRL, the best practice is to install the Oracle Enterprise Edition or Personal Edition database software on each location you expect to include in broker configurations. You must install Oracle Enterprise Manager 10g Grid Control to use the Enterprise Manager Web-based user interface for Data Guard.

In addition, to use fast-start failover you must install DGMGRL and run the observer software. Oracle recommends running the observer on a computer system that is separate from the primary and standby systems. To install DGMGRL on the observer computer, use one of the methods described in the following list:

- Install the complete Oracle Client Administrator by choosing the `Administrator` option from Oracle Universal Installer.

This installation includes DGMGRL but it does not include the Oracle Enterprise Manager agent. This allows you to manage the observer using DGMGRL commands but not Oracle Enterprise Manager.

- Install the full Oracle Database 11g software kit.

This installation includes DGMGRL and the Oracle Enterprise Manager agent, allowing you to manage the observer using Oracle Enterprise Manager or DGMGRL commands.

Note: The observer can be run from any platform that supports it, and that platform can be different from the platform of the primary or target standby database.

2.2 Prerequisites

The following conditions must be true before you can use the broker:

- The primary and standby databases must be running Oracle Database 11g (11.1) and each can be installed in either a single-instance or multi-instance environment. The database must be licensed for Oracle Enterprise Edition or Personal Edition.
- You must use a server parameter file (SPFILE) to ensure the broker can persistently reconcile values between broker properties and any related initialization parameter values. See [Section 4.3.2](#) for more information.
- The value of the `DG_BROKER_START` initialization parameter must be set to `TRUE`. See [Section 3.3](#) for more information. (Enterprise Manager sets this parameter automatically.)
- If any of the databases in the configuration is an Oracle RAC database, you must set up the `DG_BROKER_CONFIG_FILEn` initialization parameters for that database such that they point to the same shared files for all instances of that database. The shared files could be files on a cluster file system, if available, on raw devices, or stored using Automatic Storage Management (ASM).

See Also: Configuration file information in [Section 1.6.2](#). Also, see [Section 3.2](#) for details about setting up the broker configuration file, and [Section 3.2.2.3](#) for details about sizing the raw devices.

- Oracle Net Services network files must be set up on the primary database and on the standby database if you configure an existing standby database into the broker configuration. Otherwise, Enterprise Manager automatically sets up the network files when it creates a standby database.
- The connect identifier that you specify for each database in a broker configuration, using the `DGConnectIdentifier` property, must:
 - Allow all other databases in the configuration to reach it.
 - Allow all instances of an Oracle RAC database to be reached.
 - Specify a service that all instances dynamically register with the listeners so that connect-time failover on an Oracle RAC database is possible.
 - Have failover attributes set to allow the primary database's Redo Transport Services to continue shipping redo data to an Oracle RAC standby database, even if the receiving instance of that standby database has failed.
- To enable DGMGRL to restart instances during the course of broker operations, a service with a specific name must be statically registered with the local listener of each instance. A static service registration is also required to enable the observer to restart instances as part of automatic reinstatement of the old primary database after Fast-Start Failover has occurred. The value for the `GLOBAL_DBNAME` attribute must be set to a concatenation of `db_unique_name_DGMGRL.db_domain`. For example, in the `LISTENER.ORA` file:

```
LISTENER = (DESCRIPTION =
  (ADDRESS_LIST = (ADDRESS = (PROTOCOL = tcp) (HOST = host_name)
    (PORT = port_num)))
  SID_LIST_LISTENER = (SID_LIST = (SID_DESC = (SID_NAME = sid_name)
    (GLOBAL_DBNAME = db_unique_name_DGMGRL.db_domain)
    (ORACLE_HOME = oracle_home)))
```

- The primary database must be opened in ARCHIVELOG mode.
- You must set the COMPATIBLE initialization parameter to 10.2.0.1.0 or higher for both the primary and standby databases. However, if you want to take advantage of new Oracle Database 11g features, set the COMPATIBLE parameter to 11.0.0 on all databases within the Data Guard configuration.

Ensure the COMPATIBLE initialization parameter is set to the same value on both the primary and standby databases. If the values differ, redo transport services may be unable to transmit redo data from the primary database to the standby databases.

- Select and configure a redo transport authentication method, as described in *Oracle Data Guard Concepts and Administration*.

See Also:

- [Section 3.3](#) for more information about preparing and starting Oracle Data Guard broker
- *Oracle Data Guard Concepts and Administration* for more information about setting up network files
- *Oracle Database Net Services Administrator's Guide*

Managing Broker Configurations

This chapter discusses the following topics:

- [Configuration Support](#)
- [Setting Up the Broker Configuration Files](#)
- [Starting the Data Guard Broker](#)
- [Management Cycle of a Broker Configuration](#)
- [Enable and Disable Operations](#)
- [Configuration Status](#)

3.1 Configuration Support

The broker enables you to logically define a Data Guard configuration, consisting of a primary database and one or more standby databases. With the broker, you define a **broker configuration** that is a *logical* grouping of the databases, including redo transport services and log apply services. At the DBA's discretion, the broker controls the logical objects in the configuration, modifies their behavior at runtime, monitors the overall health of the configuration, and reports any health and other operational characteristics up through the Oracle Enterprise Management notification mechanisms if you are using Oracle Enterprise Manager, or through `SHOW` commands if you are using `DGMGRL`.

The broker supports Data Guard configurations consisting of a primary database, and up to nine standby databases that are either local to, or, remote from, the primary database. Any of those databases can be an Oracle Real Application Clusters (RAC) database.

A supported Data Guard configuration contains the following components:

- A (RAC or non-RAC) primary database
- From one to nine physical, snapshot, or logical (RAC or non-RAC) standby databases
- Physical systems that host the primary and standby databases
- Oracle Net Services network configuration that defines a connection between the databases
- Standby (archived redo log files) destination parameters and configuration properties
- Redo transport services that transmit the redo data from the primary database to the standby databases

- Log apply services that apply redo data to the standby databases from the archived redo log files or standby redo log files

The Data Guard log apply services update standby databases with redo data that is transmitted automatically from the primary database by redo transport services. The archived redo log files and standby redo log files contain all of the database changes except for *unrecoverable* or *unlogged* changes. On physical standby databases, Redo Apply applies the redo data to stay transactionally consistent with the primary database. On logical standby databases, SQL Apply applies the redo data to stay transactionally consistent with the primary database. On snapshot standby databases, the redo data is received but not applied until the snapshot standby database is converted back to a physical standby database.

The broker's Data Guard monitor (DMON) process configures and maintains the broker configuration as a group of objects that you can manage and monitor as a single unit. Thus, when you enter a command that affects multiple databases, the DMON process:

- Carries out your request on the primary database
- Coordinates with the DMON process for each of the other databases, as required for your request
- Updates the configuration file on the local system
- Communicates with the DMON process for each of the other databases to update their copies of the configuration file

Through the DMON process, you can configure, monitor, and control the databases and the configuration together as a unit. If you disable the configuration, broker management of all of the databases in the configuration is also disabled. If you later enable the configuration, broker management is enabled for each database in the configuration.


[Figure 3-1](#) shows a broker configuration with a primary database and physical standby database.

On the primary database, the figure shows the redo transport services in addition to the following main components: the primary database, DMON, the online redo log files, and the archived redo log files. The figure also shows standby redo log files in outline form on the primary side; the standby redo logs are outlined to indicate they are currently inactive but have been configured in preparation for a switchover to the standby role.

The physical standby database includes the following components: a standby database, log apply services, DMON, archived redo log files, and standby redo log files. The online redo log files on the physical standby database are outlined to indicate they are currently inactive but have been configured in preparation for a switchover to the primary role.

See Also: *Oracle Data Guard Concepts and Administration* for more information about physical, snapshot, and logical standby databases

Figure 3–1 Oracle Data Guard Broker Configuration



3.2 Setting Up the Broker Configuration Files

Two copies of the configuration file are maintained for each database so as to always have a record of the last known *valid* state of the configuration. When the broker is started for the first time, the configuration files are automatically created and named using a default path name and filename that is operating-system specific. You can override this default path name and filename by setting the following initialization parameters for that database:

```
DG_BROKER_CONFIG_FILE1
DG_BROKER_CONFIG_FILE2
```

Note the following restrictions when setting the `DG_BROKER_CONFIG_FILE1` and `DG_BROKER_CONFIG_FILE2` initialization parameters:

- These parameters can only be set or changed when the Data Guard broker is not running (`DG_BROKER_START=FALSE`).
- These parameters must specify a raw device, ASM file, or cluster file system file that is shared for all Oracle RAC instances.

The Data Guard Broker works with databases that use either Oracle managed or user managed datafiles. These datafiles can reside on raw devices, a file system or an ASM disk group. The following section contains these topics:

- [Renaming the Broker Configuration Files](#)
- [Managing Broker Configuration Files in an Oracle RAC Environment](#)

3.2.1 Renaming the Broker Configuration Files

You can change the configuration filenames dynamically by issuing the `ALTER SYSTEM SQL` statement. However, you cannot alter these parameters when the broker's `DMON` process is running. To change the names of these configuration files for a given database, perform the following steps:

1. Disable the broker configuration using the `DGMGRL DISABLE` command. See [Section 3.5](#) on page 3-10.
2. Stop the Data Guard broker `DMON` process using the following SQL statement:

```
SQL> ALTER SYSTEM SET DG_BROKER_START=FALSE;
```

3. Change the configuration filenames for the database:

```
SQL> ALTER SYSTEM SET DG_BROKER_CONFIG_FILE1=filespec1;  
SQL> ALTER SYSTEM SET DG_BROKER_CONFIG_FILE2=filespec2;
```

Note: If the broker is managing an Oracle RAC database, the value of `DG_BROKER_CONFIG_FILE1` and the value of `DG_BROKER_CONFIG_FILE2` for each of the instances must point to the same set of physical files.

4. The method of moving the files depends upon where they currently reside and where you want to move them to:
 - If the files reside on an operating file system, use operating system commands to move the files to their new location.
 - If the files reside on raw devices, manually transfer the files to their new location.
 - If the old or new location is an ASM disk group, use the `DBMS_FILE_TRANSFER.COPY_FILE` function to transfer the files to their new location.

5. Restart the Data Guard broker `DMON` process, as follows:

```
SQL> ALTER SYSTEM SET DG_BROKER_START=TRUE;
```

6. Enable the broker configuration using the `DGMGRL ENABLE` command or the Enable operation in the Data Guard management pages of the Enterprise Manager.

3.2.2 Managing Broker Configuration Files in an Oracle RAC Environment

If the broker is managing an Oracle RAC database, the value of `DG_BROKER_CONFIG_FILE1` and the value of `DG_BROKER_CONFIG_FILE2` for each of the instances must point to the same set of physical files. In other words, all instances of the database must reference the same set of configuration files. The configuration files can be deployed using one of the following methods:

- [Using Cluster File System \(CFS\) for Configuration Files](#)


- Using ASM Disk Groups for Configuration Files
- Using Raw Devices for Configuration Files

3.2.2.1 Using Cluster File System (CFS) for Configuration Files

If cluster file system (CFS) is available, and the configuration files reside there, the `DG_BROKER_CONFIG_FILE n` parameters on all of the instances must be set to these files including the path to the CFS area. [Figure 3–2](#) shows the set up for the broker configuration files on CFS. In this scenario, the parameters and value for all instances would be:

```
DG_BROKER_CONFIG_FILE1=$ORACLE_BASE/admin/db_unique_name/dr1db_unique_name.dat
DG_BROKER_CONFIG_FILE2=$ORACLE_BASE/admin/db_unique_name/dr2db_unique_name.dat
```


Figure 3–2 Broker Configuration Setup in a CFS Area



3.2.2.2 Using ASM Disk Groups for Configuration Files

The broker's configuration files can also reside on an ASM disk group. [Figure 3–3](#) shows the setup for the broker configuration files on ASM devices. In this scenario, the parameters and values would be specified, as follows:

```
ALTER SYSTEM SET DG_BROKER_CONFIG_FILE1 = '+DG/DIRECTORY/DR1.DAT' SCOPE=BOTH;
ALTER SYSTEM SET DG_BROKER_CONFIG_FILE2 = '+DG/DIRECTORY/DR2.DAT' SCOPE=BOTH;
```

Figure 3–3 Broker Configuration Setup with ASM


Because the configuration files must be explicitly named by the user, these configuration files are not Oracle Managed Files (OMF).

To create the broker's configuration files on an ASM disk group, set the `DG_BROKER_CONFIG_FILE1` and `DG_BROKER_CONFIG_FILE2` initialization parameters to a string value that includes the name of an existing ASM disk group, an existing directory in that disk group, and the name of the configuration file itself.

3.2.2.3 Using Raw Devices for Configuration Files

If CFS is not available and you are not using ASM, the files must be on raw devices. In this case, the parameter values on each of the instances must point to the raw devices. [Figure 3–4](#) shows the set up for the broker configuration files on raw devices. On a UNIX system, you would set this up similar to the following on each node:

```
% ln -s /dev/rds/c1t2d3s5 dr1inst1.dat
% ln -s /dev/rds/c1t2d3s6 dr2inst2.dat
```

Figure 3–4 Broker Configuration Setup with Raw Devices

If the broker configuration files need to be on raw devices, set up two additional raw devices of 1MB each. Set up the value of the `DG_BROKER_CONFIG_FILE1` and `DG_BROKER_CONFIG_FILE2` parameters to point to the raw devices. A 1MB configuration file will accommodate 10 databases with a total of 45 instances between them.

You may need a larger device if the number of instances for this configuration exceeds 45 instances. You will need 15KB for each additional instance.

3.3 Starting the Data Guard Broker

After setting up the configuration files, the `DG_BROKER_START` initialization parameter must be set to `TRUE` for each database to start the `DMON` processes.

By default, the `DG_BROKER_START` initialization parameter is set to `FALSE`. However, you can set the value in the following ways:

- If you are using Oracle Enterprise Manager, it automatically sets the `DG_BROKER_START` initialization parameter to `TRUE` for new standby databases that it creates.
- If you are using `DGMGRL`, you must explicitly set the `DG_BROKER_START` initialization parameter to `TRUE`; otherwise, the broker will not start. You can set the `DG_BROKER_START` initialization parameter with the following SQL statement:

```
SQL> ALTER SYSTEM SET DG_BROKER_START=TRUE;
```

```
System altered.
```

```
SQL> SHOW PARAMETER DG_BROKER_START
```

NAME	TYPE	VALUE

dg_broker_start	boolean	TRUE


Whether you use Enterprise Manager or `DGMGRL`, set the value of the `DG_BROKER_START` initialization parameter to `TRUE` in the server parameter file on each primary

and standby database. Doing so ensures that Data Guard Broker will start automatically the next time you start any instance of the database.

3.4 Management Cycle of a Broker Configuration

The broker helps you to create a new configuration or manage an existing configuration. [Figure 3-5](#) shows the life cycle of a broker configuration.

Figure 3-5 *Life Cycle of a Broker Configuration and Its Databases*



Create the Broker Configuration

When using Enterprise Manager, the Add Standby Database wizard can either add an existing (RAC or non-RAC) standby database into the configuration or create a new (RAC or non-RAC) standby database and add it to the configuration. The standby database can be a physical, logical, or snapshot database.

When using DGMGRL, the primary database and a standby database must already exist. You construct the standby database from backups of the primary database control files and datafiles, and then prepare it for recovery.

See Also: [Chapter 6](#) and [Chapter 7](#) that describe the preparation requirements if you are using Enterprise Manager or DGMGRL, respectively

Enable the Broker Configuration

A Data Guard configuration must be enabled to be managed or monitored by the broker. Conversely, you disable a configuration if you no longer want to manage it with the broker. When you disable a configuration, broker management of all of its databases is also disabled.

Note: You can enable or disable the configuration using DGMGRL. You cannot disable the configuration using Enterprise Manager. You can enable the configuration using Enterprise Manager in the event that it was previously disabled using DGMGRL.

A broker configuration, when first created using Enterprise Manager, is automatically enabled as soon as the Add Standby Database wizard completes.

A broker configuration, when first created using DGMGRL, is in a disabled condition. This means its constituent databases are not yet under active control of the broker. When you finish configuring the databases into a broker configuration with DGMGRL, you must enable the configuration to allow the broker to manage the configuration.

You can enable:

- The entire configuration, including all of its databases
- An individual standby database

You can easily disable a database if a problem occurs such that it cannot function properly in a broker configuration. Note that you cannot disable the primary database. You must disable the entire configuration to disable the primary database.

You may also want to disable a configuration temporarily, and then change some properties in the broker configuration without affecting the actual database properties. The changed properties will take effect when the configuration is enabled again for management by the broker.

Make Role Changes Within the Broker Configuration, As Needed

At any time, you can issue a single command to change the roles of the databases in the configuration. If some event renders the primary database unusable, you can fail over one of the standby databases to become the new primary database.

In addition, planned downtime for maintenance can be reduced because you can quickly switch over production processing from the current primary database to a standby database, and then switch back again after the planned maintenance.

See Also: [Chapter 5](#) for more information about role changes

Make State Changes to the Databases, As Needed

When you enable a configuration for the first time, the broker, by default, starts redo transport services on the primary and starts log apply services on the standby (except for a snapshot standby).

At any time, you can issue a single command through Enterprise Manager or DGMGRL to change the state of the database. For example, you could bring the primary database into a `TRANSPORT-OFF` state to temporarily stop sending redo data to the standby databases. Then, you could issue another command to resume sending redo data to the standby databases.

See Also: [Chapter 4](#) for more information about database state changes

Update Database Properties, As Needed

The broker enables you to set database properties, some of which correspond to database initialization parameters. You can change these properties to dynamically control such things as redo transport, standby file management, log apply, and to support the overall configuration protection mode. The broker records the changes in the broker configuration file for each database in the Data Guard configuration and propagates the changes to the related initialization parameters in the server parameter files, if needed.

See Also: [Chapter 4](#) and [Chapter 9](#) for complete information about database properties

Set Data Protection Modes, As Needed

The broker enables you to set the data protection mode for the configuration. You can configure the protection mode to maximize data protection, maximize availability, or maximize performance.

See Also: [Section 4.6](#) for information about managing data protection modes

Monitor the Configuration

You can check the health of the configuration, display and update the properties of the databases, and set Oracle Enterprise Manager events.

Enterprise Manager also provides a dynamic performance page that automatically and dynamically refreshes chart data and status at specified intervals. The performance chart shows a graphical summary of how far behind and how much redo data is being generated and applied.

See Also: [Chapter 6](#) and [Chapter 7](#) for scenarios that show examples using Enterprise Manager and DGMGRL, respectively

3.5 Enable and Disable Operations

A key concept of management with the broker is the notion of enabling and disabling broker management of the databases in a broker configuration. The enable and disable operations are defined for databases that were incorporated into a broker configuration; you cannot perform these broker operations on databases that are not part of the broker configuration. This is because when you enable or disable a database in the broker configuration, you are effectively enabling or disabling the ability of the broker to:

- Manage and monitor the specified database
- Manage the profile information in the broker configuration file for each database

However, disabling a broker configuration does not affect current services and operations in the actual Data Guard configuration. For example, when you disable a broker configuration, redo transport services and log apply services in the Data Guard configuration continue to function unchanged, but you can no longer manage them through the broker interfaces.

In addition, disabling a database *does not* remove or delete its profile from the broker configuration file. You can still change the properties of a disabled database and later reen able your ability to manage with the broker using the DGMGRL `ENABLE CONFIGURATION` or `ENABLE DATABASE` commands, or the Enable option in the Data Guard management pages of Enterprise Manager.

Caution: If you disable broker management of a standby database in the broker configuration, that standby database cannot be used by the broker as a failover target in the event of loss of the primary database.

Disabling broker management of the configuration may be useful to do even though you are removing the broker's ability to monitor and control the databases. For example, it may be advantageous to disable a configuration temporarily in order to change one or more properties in the broker configuration all at the same time. When you change properties in a disabled configuration, it does not affect the actual database properties underneath because the changes are not applied to the running database until you reenables the configuration. For example, you might want to change the overall configuration protection mode and the redo transport services properties on a disabled configuration so that all changes are applied to the configuration at the same time upon the next enable operation.

See Also: [Section 4.6.2, "How the Protection Modes Influence Broker Operations"](#)

3.6 Configuration Status

A configuration status reveals the overall health of the configuration. Status of the configuration is acquired from the status of all of its databases.

The following list describes the possible status modes for a configuration:

- **Success**

The configuration, including all of the databases configured in it, is operating as specified by the user without any warnings or errors.
- **Warning**

One or more of the databases in the configuration are not operating as specified by the user. To obtain more information, use the `DGMGRL SHOW DATABASE <db-unique-name> StatusReport` command or the Enterprise Manager display to locate each database and examine its status to reveal the source of the problem.
- **Error**

One or more of the databases in the configuration failed or may no longer be operating as specified by the user. To obtain more information, use the `DGMGRL SHOW DATABASE <db-unique-name> StatusReport` command or the Enterprise Manager display to locate each database and examine its status to reveal the source of the problem.
- **Unknown/Disabled**

Broker management of the configuration is disabled and the broker is not monitoring the status of the databases in the configuration.

Managing Databases

This chapter describes managing the states and properties that are specific to the database. It contains the following topics:

- [Database Objects](#)
- [Database States](#)
- [Database Properties](#)
- [Managing Redo Transport Services](#)
- [Managing Log Apply Services](#)
- [Managing Data Protection Modes](#)
- [Managing Fast-Start Failover](#)
- [Managing Database Conversions](#)
- [Database Status](#)

4.1 Database Objects

The broker manages database objects. A database object corresponds to a primary or standby database. The broker uses each object's profile to manage and monitor the state of a single database.

The broker distinguishes between physical, snapshot, and logical standby databases. These databases are configured with profiles having states and properties that are appropriate for their standby types.

4.2 Database States

When a configuration is enabled, its databases can be in one of several states that direct the behavior of Data Guard, for example transmitting redo data or applying redo data. The broker does not manage the state of the database (that is, mounted or opened). [Table 4-1](#) describes the various database states.

Table 4–1 Database States and Descriptions

Database Role	State Name	Description
Primary	TRANSPORT-ON	<p>Redo transport services are set up to transmit redo data to the standby databases when the primary database is open for read/write access.</p> <p>If this is an Oracle RAC database, all instances open in read/write mode will have redo transport services running.</p> <p>This is the default state for a primary database when it is enabled for the first time.</p>
Primary	TRANSPORT-OFF	<p>Redo transport services are stopped on the primary database.</p> <p>If this is an Oracle RAC database, redo transport services are not running on any instances.</p>
Physical standby	APPLY-ON	<p>Redo Apply is started on a physical standby database.</p> <p>If the standby database is an Oracle RAC database, the broker starts Redo Apply on exactly one standby instance, called the apply instance. If this instance fails, the broker automatically chooses another instance that is either mounted or open read-only. This new instance then becomes the apply instance.</p> <p>This is the default state for a physical standby database when it is enabled for the first time.</p> <p>If a license for the Oracle Active Data Guard option has been purchased, a physical standby database can be open while Redo Apply is active. This capability is known as real-time query. See <i>Oracle Data Guard Concepts and Administration</i> for more details.</p>
Physical standby	APPLY-OFF	<p>Redo Apply is stopped.</p> <p>If this is an Oracle RAC database, there is no instance running Apply Services until you change the database state to APPLY-ON.</p>
Snapshot standby	APPLY-OFF	<p>Redo data is received from the primary database but is not applied. The database is opened for read/write access.</p>
Logical standby	APPLY-ON	<p>SQL Apply is started on the logical standby database when it is opened and the logical standby database guard is on.</p> <p>If this is an Oracle RAC database, SQL Apply is running on one instance, the apply instance. If this instance fails, the broker automatically chooses another open instance. This new instance becomes the apply instance.</p> <p>This is the default state for a logical standby database when it is enabled for the first time.</p>

Table 4–1 (Cont.) Database States and Descriptions

Database Role	State Name	Description
Logical standby	APPLY-OFF	SQL Apply is not running on the logical standby database. The logical standby database guard is on. If this is an Oracle RAC database, there is no instance running SQL Apply until you change the state to APPLY-ON.

4.2.1 Database State Transitions

You can use the `DGMGRL EDIT DATABASE` command to explicitly change the state of a database. For example, the `EDIT DATABASE` command in the following example changes the state of the `North_Sales` database to `TRANSPORT-OFF`.

```
DGMGRL> EDIT DATABASE 'North_Sales' SET STATE='TRANSPORT-OFF';
Succeeded.
```

See Also: [Chapter 8](#) for complete information about the `EDIT DATABASE` command. See [Chapter 6](#) for examples of performing state transitions using Enterprise Manager.

The following sections describe in more detail the possible state transitions for primary and standby databases.

Primary database state transitions

When transitioning the primary database to the `TRANSPORT-ON` state, the broker sets up redo transport services to all broker-managed standby databases using the redo transport-related properties of the standby databases (see [Section 4.4](#) for the list of all redo transport-related properties). Redo transport services setup is done by setting the `LOG_ARCHIVE_DEST_n` and `LOG_ARCHIVE_DEST_STATE_n` initialization parameters on the primary database, and the `LOG_ARCHIVE_CONFIG` initialization parameter on all databases (primary or standby). If necessary, the broker also sets up the data protection mode of the database to match the protection mode recorded in the broker configuration file. Finally, if the database is open, the broker switches a log for each thread to initiate redo transport services.

When transitioning the primary database to the `TRANSPORT-OFF` state, the broker turns off redo transport services to all broker-managed standby databases by resetting the `LOG_ARCHIVE_DEST_STATE_n` initialization parameter. Transmission of redo data to all broker-managed standby databases is stopped. Log files continue to be archived at the primary database.

If the primary database is an Oracle RAC database, the broker configures redo transport services on all primary instances with the exact same settings.

See Also: [Section 4.4](#) for more details on managing redo transport services

Physical standby database state transitions

When transitioning a physical standby database to the `APPLY-ON` state, the broker starts Redo Apply with options specified by the redo apply-related properties (see [Section 4.5](#) for the property list). If the standby database is an Oracle RAC database, the broker starts Redo Apply on one standby instance, called the apply instance.

If a license for the Oracle Active Data Guard option has been purchased, a physical standby database can be open while Redo Apply is active. This capability is known as real-time query. See *Oracle Data Guard Concepts and Administration* for more details.

Note: The apply instance must be open before starting redo apply if any other instance is open.

When transitioning to the APPLY-OFF state, the broker stops Redo Apply.

Snapshot standby database state transitions

A snapshot standby database in a broker configuration is in the APPLY-OFF state. The snapshot standby database can be converted to a physical standby database, at which time it will enter the APPLY-ON state.

Logical standby database state transitions

When transitioning a logical standby database to the APPLY-ON state, the broker will wait until the database is open, and then enable the database guard to prevent modifications to tables in the logical standby database, and start SQL Apply with options specified by the log apply-related properties. If the logical standby database is an Oracle RAC database, the broker starts SQL Apply on one standby instance, the apply instance.

When transitioning to the APPLY-OFF state, the broker stops SQL Apply.

See Also:

- [Section 4.5](#) on page 4-11 for information about managing SQL Apply
- *Oracle Data Guard Concepts and Administration* for information about the database guard

4.3 Database Properties

There are two types of database properties: monitorable and configurable. Both monitorable and configurable properties can be further divided into those properties that have database scope and those having instance scope.

- Monitorable property values can be viewed only when the associated database object is enabled.

Monitorable properties allow you to view run-time information related to database objects, but you cannot change the values of these properties.

- Configurable property values can be viewed and dynamically updated.

Configurable properties affect the operation or configuration of the broker. You can change the value of these properties using DGMGRL or Enterprise Manager. You can edit properties if the configuration and its databases are enabled or disabled. However, if the database is disabled, the new property value will not take effect until you enable the configuration or database, as appropriate.

See Also: [Chapter 9](#) for a detailed list of all database properties

To see these properties, you can use the DGMGRL `SHOW` command or Edit Properties page in Enterprise Manager. [Example 4-1](#) uses the `SHOW DATABASE VERBOSE` command to display information about the `North_Sales` database.

Example 4-1 Using the SHOW DATABASE VERBOSE Command to Display Properties

```
DGMGRL> SHOW DATABASE VERBOSE North_Sales;

Database
Name:          North_Sales
Role:          PRIMARY
Enabled:       NO
Intended State: TRANSPORT-ON
Instance(s):
  sales1

Properties:
  DGConnectIdentifier          = 'North_Sales.foo.com'
  ObserverConnectIdentifier    = ''
  LogXptMode                   = 'ASYNC'
  DelayMins                    = '0'
  Binding                      = 'OPTIONAL'
  MaxFailure                   = '0'
  MaxConnections               = '1'
  ReopenSecs                   = '300'
  NetTimeout                   = '30'
  RedoCompression             = 'DISABLE'
  LogShipping                   = 'ON'
  PreferredApplyInstance       = ''
  ApplyInstanceTimeout         = '0'
  ApplyParallel                = 'AUTO'
  StandbyFileManagement        = 'AUTO'
  ArchiveLagTarget             = '0'
  LogArchiveMaxProcesses       = '5'
  LogArchiveMinSucceedDest     = '1'
  DbFileNameConvert            = 'dbs/bt, dbs/t'
  LogFileNameConvert           = 'dbs/bt, dbs/t'
  FastStartFailoverTarget      = ''
  StatusReport                 = '(monitor)'
  InconsistentProperties        = '(monitor)'
  InconsistentLogXptProps      = '(monitor)'
  SendQEntries                 = '(monitor)'
  LogXptStatus                 = '(monitor)'
  RecvQEntries                 = '(monitor)'
  HostName                     = 'stacm29'
  SidName                      = 'b2'
  StandbyArchiveLocation       = '/archfs/arch/'
  AlternateLocation            = ''
  LogArchiveTrace              = '8191'
  LogArchiveFormat             = 'db1r_%d_%t_%s_%r.arc'
  LatestLog                    = '(monitor)'
  TopWaitEvents                = '(monitor)'
```

Current status for "North_Sales":
DISABLED

See Also: [Chapter 8](#) for complete information about the DGMGRL command-line interface

4.3.1 Monitorable (Read-Only) Properties

Monitorable database properties allow you to view information related to the database, but you cannot change the values of these properties. These properties can be very helpful when you are trying to diagnose problems in the broker configuration.

For example, you can view the `InconsistentLogXptProps` monitorable database property to determine where there is a discrepancy in redo transport services properties between the broker configuration file and the actual value currently used by the database.

You can list all monitorable database properties using the `DGMGRL SHOW DATABASE VERBOSE` command. Use the `SHOW DATABASE` command to obtain more details about a particular property. For example, the following shows the `InconsistentLogXptProps` property:

```
DGMGRL> SHOW DATABASE 'North_Sales' 'InconsistentLogXptProps';
INCONSISTENT LOG TRANSPORT PROPERTIES
```

INSTANCE_NAME	STANDBY_NAME	PROPERTY_NAME	MEMORY_VALUE	BROKER_VALUE
sales1	DR_Sales	DelayMins	30	10

Enterprise Manager displays the information obtained from these properties on the Edit Properties page.

4.3.2 Configurable (Changeable) Database Properties

Configurable database properties affect the operation or configuration of the database. When you use `DGMGRL` or Enterprise Manager to create a primary database object and import existing standby databases into a new broker configuration, the property values are initially imported from the database settings.

You can update many property values when the database is either disabled or enabled. When a new database is added into the configuration, the broker connects to the database and imports initial values for the database properties from the current database settings. For example:

```
DGMGRL> SHOW DATABASE 'North_Sales' 'ArchiveLagTarget';
ArchiveLagTarget = '0'
```

```
DGMGRL> EDIT DATABASE 'North_Sales' SET PROPERTY 'ArchiveLagTarget'=1200;
Property "ArchiveLagTarget" updated
```

```
DGMGRL> SHOW DATABASE 'North_Sales' 'ArchiveLagTarget';
ArchiveLagTarget = '1200'
```

When the configuration is enabled, the broker keeps the database property values in the broker configuration file consistent with the values being used in the database. For those that are related to initialization parameter properties, the broker maintains the consistency among the value in the broker configuration file, the current database value, and the initialization parameter value in the server parameter file, as follows:

- For dynamic parameters, the broker keeps the value of the database parameter consistent in the system global area (SGA) for the instance, in the broker configuration file, and in the server parameter file.
- For static parameters and properties, the database parameter value in the system global area (SGA) for the instances may temporarily differ from what is in the broker configuration file and in the server parameter file. Typically, the database value becomes the same as the server parameter file value and the broker configuration file value the next time the database instance is stopped and restarted.

Even when the configuration is disabled, you can update database property values through the broker. The broker retains the property settings (without validating the

values) and updates the database initialization parameters in the server parameter file and the settings in memory the next time you enable the broker configuration.

Note: Even though you can change a property value when the configuration is disabled, the change does not take effect on the database unless the configuration is enabled. Also note that some property values can only be changed in the disabled state.

4.4 Managing Redo Transport Services

To manage redo transport services, you specify the following set of configurable database properties on each standby database:

- `DGConnectIdentifier`
- `AlternateLocation`
- `Binding`
- `LogShipping`
- `LogXptMode`
- `MaxFailure`
- `NetTimeout`
- `RedoCompression`
- `ReopenSecs`
- `StandbyArchiveLocation`

You can use these properties to specify how the broker configures redo transport services for the standby database. The actual redo transport setup, such as setting the `LOG_ARCHIVE_DEST_n` initialization parameter, is carried out by the broker on the primary database (except for the `StandbyArchiveLocation` property). If changing the property requires that you change the `LOG_ARCHIVE_DEST_n` initialization parameter attributes, the broker forces a log switch on each thread so that the new setting is adopted immediately by the primary database.

You may also preset these properties on the primary database in preparation for it to be switched over to a standby database.

4.4.1 Setting Up For Redo Transport

Redo data is transported to a standby database using Oracle Net. An Oracle Net service name is specified with the `SERVICE` attribute of the `LOG_ARCHIVE_DEST_n` initialization parameter and is used to transmit redo data to the standby database. The Oracle Net service name is translated into a connect descriptor that contains the information necessary for connecting to the standby database.

The `SERVICE` attribute can be set or changed by using the `DGConnectIdentifier` configurable database property. The `DGConnectIdentifier` property is set when a database is first added to the configuration. Its initial value is the connect identifier that is specified in the optional `CONNECT IDENTIFIER IS` clause of the `ADD DATABASE` command. If that optional clause is not specified, the initial value of the `DGConnectIdentifier` property is extracted from the `SERVICE` attribute of the `LOG_ARCHIVE_DEST_n` initialization parameter whose `DB_UNIQUE_NAME` attribute matches the `DB_UNIQUE_NAME` of the database specified in the `ADD DATABASE` command.

The `DGConnectIdentifier` property value is also used to set up the `FAL_SERVER` and `FAL_CLIENT` initialization parameters. If the `DGConnectIdentifier` property for any database is changed, `SERVICE` attribute of the corresponding `LOG_ARCHIVE_DEST_n` initialization parameter will also be changed. In addition the `FAL_SERVER` and `FAL_CLIENT` initialization parameters will also be updated.

4.4.2 Managing Redo Transport Services for Data Protection Modes

[Section 4.6](#) describes how the broker handles data protection modes. As a part of the overall configuration protection mode, you must ensure that redo transport services are also properly set up for the data protection mode that you choose.

You use the `LogXptMode` configurable database property to set the `SYNC` or `ASYNC` mode for redo transport services. See [Table 4-2](#) for additional information about protection modes and redo transport services.

The values for the `LogXptMode` property are described in the following list:

SYNC

Configures redo transport services for this standby database using the `SYNC` and `AFFIRM` attributes of the `LOG_ARCHIVE_DEST_n` initialization parameter. This mode, along with standby redo log files, is required for configurations operating in either maximum protection mode or maximum availability mode. This redo transport service enables the highest grade of data protection to the primary database, but also can incur a higher performance impact.

ASYNC

Configures redo transport services for this standby database using the `ASYNC` and `NOAFFIRM` attributes of the `LOG_ARCHIVE_DEST_n` initialization parameter. This mode, along with standby redo log files, enables a moderate grade of protection to the primary database, and lower performance impact.

4.4.3 Turning Redo Transport Services On and Off

Turn redo transport services on and off by setting the state of the primary database. Setting the primary database state to `TRANSPORT-ON` starts redo transport services to the standby databases, and setting the primary database state to `TRANSPORT-OFF` stops redo transport services to all the standby database.

Note: Oracle does not recommend turning off redo transport services to all standby databases. This increases the risk of data loss if the primary database fails.

Turn redo transport services on and off to an individual standby database using the `LogShipping` configurable database property on the standby database. The `LogShipping` property accepts values `ON` and `OFF`. If you set the `LogShipping` property to `OFF` for a standby database, redo transport services to this standby database are turned off, while redo transport services to other databases are not affected. You can set `LogShipping` to `ON` to turn back on redo transport services to the standby database.

The relationship between setting the primary database state and setting the `LogShipping` property is as follows:

- If the primary database state is set to `TRANSPORT-OFF`, redo transport services to all the standby databases are stopped regardless of the `LogShipping` property values of the individual standby databases.
- If the primary database state is set to `TRANSPORT-ON`, redo transport services to each standby database are determined by the `LogShipping` property of that database.

[Example 4-2](#) and [Example 4-3](#) show how to turn off redo transport services in two different scenarios.

Example 4-2 Turn Off Redo Transport Services to All Standby Databases

```
DGMGRL> EDIT DATABASE 'North_Sales' SET STATE="TRANSPORT-OFF";
Succeeded.
DGMGRL> SHOW DATABASE 'North_Sales';
```

```
Database
Name:          North_Sales
Role:          PRIMARY
Enabled:       YES
Intended State: TRANSPORT-OFF
Instance(s):
sales1
```

```
Current status for "North_Sales":
SUCCESS
```

Example 4-3 Turn Off Redo Transport Services to a Specific Standby Database

```
DGMGRL> EDIT DATABASE 'DR_Sales' SET PROPERTY 'LogShipping'='OFF';
Property "LogShipping" updated

DGMGRL> SHOW DATABASE 'DR_Sales' 'LogShipping';
LogShipping = 'OFF'
```

4.4.4 Specifying Locations for Archived Redo Log Files

You can set up locations on the standby database to store the archived redo log files to be used by log apply services on the standby database. This is done by setting the `StandbyArchiveLocation` and `AlternateLocation` configurable database properties on the standby database.

`StandbyArchiveLocation` specifies a standby location where the archived redo log files will be stored. The broker only manages the location to store archived redo log files received from the primary database. For archived redo log files generated locally when the database is either the primary database or a logical standby database, you need to set up local destinations directly through the `LOG_ARCHIVE_DEST_n` initialization parameter. The broker allows the value of `StandbyArchiveLocation` to be the same as the location you set up for locally generated logs, in which case the broker sets up the `VALID_FOR` attribute of the destination appropriately so that it can be used for both the archived redo log files received from the primary database and archived redo log files generated locally.

Note: On a logical standby database, Oracle recommends that the `LOCATION` attribute of the `LOG_ARCHIVE_DEST_n` initialization parameter for the local destination be different from the value of either the `StandbyArchiveLocation` or `AlternateLocation` property unless you are using database recovery area.

You can also set up an alternate location to store archived redo log files on the standby using the `AlternateLocation` property on the standby database. This is useful for avoiding disk capacity problems or disk errors when archiving the online redo log files on the standby database. `AlternateLocation` specifies a standby location where the archived redo log files will be stored if the location specified by the `StandbyArchiveLocation` fails. The broker sets up the alternate location properly using the `ALTERNATE` attribute of the `LOG_ARCHIVE_DEST_n` initialization parameter.

Note: You can use the database recovery area to store archived redo log files on the standby. In such a case, the value of the `StandbyArchiveLocation` or `AlternateLocation` properties can be set to `USE_DB_RECOVERY_FILE_DEST`.

4.4.5 Other Redo Transport Settings

You can use the `Binding`, `MaxFailure`, `MaxConnections`, `NetTimeout`, `RedoCompression`, and `ReopenSecs` configurable database properties to tune the performance of redo transport services and to set up redo transport services failure policies. These properties correspond to attributes on the `LOG_ARCHIVE_DEST_n` initialization parameter.

When creating a new standby database, the broker sets these properties with default values. When importing an existing standby database, the broker imports existing settings corresponding to these properties if it finds a match between the service string of a current destination and the connect identifier that was specified when the database was added to the configuration. If that fails, it finds a match between the `db_unique_name` of a current destination and the name that was specified when the database was added to the configuration.

For most cases, the default values or the imported values should be sufficient for normal operations. If for some reason you need to change these property values, you can use `DGMGRL` commands to set up these properties. Enterprise Manager does not provide an interface for modifying these properties.

See Also: [Chapter 9](#) for complete information about these database properties

4.4.6 Redo Transport Services in an Oracle RAC Database Environment

If the primary database is an Oracle RAC database, the broker ensures that redo transport services are identical on each of the primary database instances. Each instance has the same remote destinations, and for each remote destination, all instances are set up the same in terms of redo transport service, performance related settings, and so on. If an instance has different settings, the broker raises a health check warning on that particular instance

Settings relative to redo transport services are saved in the broker configuration file as properties. When you update a redo transport-related property on a standby database,

the corresponding change is also made automatically by the broker to the `LOG_ARCHIVE_DEST_n` initialization parameter on all of the primary database instances. If a new instance comes up on the primary database, the broker sets up redo transport services for the new instance using the redo transport-related properties of all the standby databases currently being managed by the broker. After the new instance is opened for activity, all archived redo log files generated on this instance will begin to transmit to the standby databases.

See also: *Oracle Data Guard Concepts and Administration* for additional information about the `LOG_ARCHIVE_DEST_n` initialization parameter

4.5 Managing Log Apply Services

You can manage Redo Apply and SQL Apply on physical and logical standby databases through the following log apply-related configurable database properties:

- Properties common to Redo Apply and SQL Apply
 - `ApplyInstanceTimeout`
 - `DelayMins`
 - `PreferredApplyInstance`
- Properties specific to Redo Apply
 - `ApplyParallel`
- Properties specific to SQL Apply
 - `LsbyASkipTxnCfgr`
 - `LsbyDSkipTxnCfgr`
 - `LsbyASkipCfgr`
 - `LsbyDSkipCfgr`
 - `LsbyASkipErrorCfgr`
 - `LsbyDSkipErrorCfgr`
 - `LsbyMaxEventsRecorded`
 - `LsbyPreserveCommitOrder`
 - `LsbyRecordSkipErrors`
 - `LsbyRecordSkipDdl`
 - `LsbyRecordAppliedDdl`
 - `LsbyMaxSga`
 - `LsbyMaxServers`

There are some properties related to SQL Apply that, if changed, may require a restart of SQL Apply if the current database state is `APPLY-ON`. See the information in [Chapter 9](#) about properties related to SQL Apply, to determine which ones require SQL Apply to be restarted.

If the current database state is `APPLY-OFF`, the property changes will take effect the next time the database state is changed to `APPLY-ON`.

4.5.1 Managing Delayed Apply

You can set up Apply Services so that the application of redo to the standby database is delayed. This allows the standby database to lag behind the primary database, and if a user error (for example, dropping a table) occurs during this window of time, the standby database will still contain the correct data that can be transmitted back to the primary database to repair the data.

By default, no delay is configured and the redo data is applied on a standby database as soon as possible. If the standby database has standby redo logs configured, the broker will enable real-time apply. When Redo Apply and SQL Apply apply redo in real time, the redo data is recovered directly from the standby redo log files as they are being filled. This means that the standby database does not have to wait for the log files to be archived before applying redo data from the archived redo log files. This minimizes the transactional lag between the primary and the standby.

Use the `DelayMins` configurable database property to specify the number of minutes that log apply services must wait before applying redo data to the standby database. Note that only log apply services on the standby database are delayed. Redo transport services on the primary database are not delayed, thus the primary database data is still well protected by the standby database.

Caution: Because the broker automatically enables real-time apply on standby databases, Oracle recommends that you configure all databases to use Flashback Database.

4.5.2 Managing Parallel Apply with Redo Apply

For Redo Apply, you can configure whether multiple parallel processes are used to apply redo data received from the primary database by using the `ApplyParallel` configurable database property. Parallelism is enabled by default, which means Redo Apply automatically chooses the optimal number of parallel processes based on the number of CPUs in the system. (This is equivalent to setting the `ApplyParallel` property to `AUTO`.) You can disable parallelism by setting the `ApplyParallel` property to `NO`.

Note: The `ApplyParallel` configurable database property is not displayed on the Edit Properties page of Enterprise Manager.

See Also: The `ApplyParallel` property in [Section 9.2.3, "ApplyParallel"](#)

4.5.3 Allocating Resources to SQL Apply

You can control how much SGA memory is available for SQL Apply. This can be set using the `LsbyMaxSga` configurable database property.

To control the number of parallel query servers used by SQL Apply, you can use the `LsbyMaxServers` configurable database property.

You can control the trade off between SQL Apply performance and the commit order of transactions. The `LsbyPreserveCommitOrder` configurable database property controls whether transactions are committed on the logical standby database in the exact same order in which they were committed on the primary database. Preserving commit order may affect performance.

See Also: [Section 9.2.31, "LsbyMaxSga"](#) and [Section 9.2.32, "LsbyMaxServers"](#)

4.5.4 Managing SQL Apply Filtering

One of the benefits of a logical standby database is to allow control of what to apply and what not to apply. This is done by setting up SQL Apply filters. The granularity of the filtering ranges from a specific transaction to database objects to a particular class of SQL statement on a particular schema.

To add a SQL Apply filter in Data Guard broker, use the `LsbyASkip*` configurable database properties (for example, `LsbyASkipTxnCfgPr` or `LsbyASkipCfgPr`). To delete a previously added SQL Apply filter, use the `LsbyDSkip*` configurable database properties (for example, `LsbyDSkipTxnCfgPr` or `LsbyDSkipCfgPr`).

See Also: [Chapter 9](#) for information on these properties

4.5.5 Managing SQL Apply Error Handling

You can fine-tune SQL Apply to handle apply errors on a specified set of SQL statements on particular schemas. When such SQL Apply errors are encountered, Data Guard can either skip the error to continue SQL Apply or call a specified stored procedure at the time when the error is encountered.

To add this error handling capability, use the `LsbyASkipErrorCfgPr` configurable database property. To delete a previously added error handling specification, use the `LsbyDSkipErrorCfgPr` configurable database property.

Changing these properties results in restarting SQL Apply if the current database state is `APPLY-ON`. If the current database state is `APPLY-OFF`, the property changes take effect the next time the database state is changed to `APPLY-ON`.

4.5.6 Managing the DBA_LOGSTDBY_EVENTS Table

The `DBA_LOGSTDBY_EVENTS` table records important events that affect SQL Apply. Because every logical standby database might have a different interest in the set of events to be recorded in this table, Data Guard provides a means to control the event recording. From the Data Guard broker, you can use the `LsbyRecord*` configurable database properties (for example, `LsbyRecordSkipDdl` or `LsbyRecordSkipErrors`) to control recording of a particular set of events. The value of these properties are either `TRUE` or `FALSE`, indicating the turning on or off of the event recording.

4.5.7 Apply Services in an Oracle RAC Database Environment

If a standby database is an Oracle RAC database, only one instance of the RAC database can have log apply services running at any time. This instance is called the **apply instance**. If the apply instance fails, the broker automatically moves log apply services to a different instance; this is called **apply instance failover**.

4.5.7.1 Selecting the Apply Instance

Note: The information in this section is not applicable to snapshot standby databases.

If you have no preference which instance is to be the apply instance in an Oracle RAC standby database, the broker randomly picks an apply instance. If you want to select a particular instance as the apply instance, there are two methods to do this.

- The first method is to pick an apply instance before there is an apply instance running in the RAC standby database. To do so, set the value of the `PreferredApplyInstance` configurable database property to the name of the instance (see the `SidName` property) you prefer to be the apply instance. The broker starts log apply services on the instance specified by the `PreferredApplyInstance` property when no apply instance is yet selected in the RAC standby database. This could be the case before you enable the standby database for the first time, or if the apply instance just failed and the broker is about to do an apply instance failover, or if the RAC database is currently the primary and you want to specify its apply instance in preparation for a switchover. Once the apply instance is selected and, as long as the apply instance is still running, the broker disregards the value of the `PreferredApplyInstance` property even if you change it.
- The second method is to change the apply instance when the apply instance is already selected and is running. To change the apply instance, issue the `DGMGRL SET STATE` command to set the standby database state to `APPLY-ON`, with a specific apply instance argument. The `SET STATE` command will update the `PreferredApplyInstance` property to the new apply instance value, and then move log apply services to the new instance. For example, use `DGMGRL SHOW` command to show the available instances for the standby database, then issue the `EDIT DATABASE` command to move log apply services to the new instance:

```
DGMGRL> SHOW DATABASE 'DR_Sales' ;
Database
Name:          DR_Sales
Role:          PHYSICAL STANDBY
Enabled:       YES
Intended State: APPLY-ON
Instance(s):
  dr_sales1 (apply instance)
  dr_sales2

Current status for "DR_Sales":
SUCCESS

DGMGRL> EDIT DATABASE 'DR_Sales' SET STATE='APPLY-ON' WITH APPLY
INSTANCE="dr_sales2";
Succeeded.
DGMGRL> SHOW DATABASE 'DR_Sales' 'PreferredApplyInstance';
  PreferredApplyInstance = 'dr_sales2'

DGMGRL> SHOW DATABASE 'DR_Sales' ;
Database
Name:          DR_Sales
Role:          PHYSICAL STANDBY
Enabled:       YES
Intended State: APPLY-ON
Instance(s):
  dr_sales1
  dr_sales2 (apply instance)

Current status for "DR_Sales":
SUCCESS
```

Ensure that the new apply instance is running when the command is issued. Otherwise, the apply instance remains the same.

Once the apply instance is selected, the broker keeps apply instance information in the broker configuration file so that even if the standby database is shut down and restarted, the broker still selects the same instance to start log apply services. The apply instance remains unchanged until changed by the user or it fails for any reason and the broker decides to do an apply instance failover.

4.5.7.2 Apply Instance Failover

To tolerate a failure of the apply instance, the broker leverages the availability of the RAC standby database by automatically failing over log apply services to a different standby instance. The apply instance failover capability provided by the broker enhances data protection.

To set up apply instance failover, set the `ApplyInstanceTimeout` configurable database property to specify the time period that the broker will wait after detecting an apply instance failure and before initiating an apply instance failover. To select an appropriate timeout value, you need to consider:

- If there is another mechanism in the cluster that will try to recover the failed apply instance.
- How long your business can tolerate not applying redo data on the standby database.
- The overhead associated with moving the log apply services to a different instance. The overhead may include retransmitting, from the primary database, all log files accumulated on the failed apply instance that have not been applied if those log files are not saved in a shared file system that can be accessed from other standby instances.

The broker default value of the `ApplyInstanceTimeout` property is 0 seconds, indicating that apply instance failover should occur immediately upon detection of the failure of the current apply instance.

After the broker initiates an apply instance failover, the broker selects a new apply instance according to the following rule: if the `PreferredApplyInstance` property indicates an instance that is currently running, select it as the new apply instance; otherwise pick a random instance that is currently running to be the new apply instance.

4.6 Managing Data Protection Modes

The broker can simplify the process of setting up your configuration for any of the different grades of data protection: maximum protection, maximum availability, or maximum performance.

This section contains the following topics to help you configure the proper protection for your configuration:

- [Section 4.6.1, "Setting the Protection Mode for Your Configuration"](#)
- [Section 4.6.2, "How the Protection Modes Influence Broker Operations"](#)

4.6.1 Setting the Protection Mode for Your Configuration

To set the protection mode, perform the following steps:

Step 1 Determine which data protection mode you want to use.

Each data protection mode provides a different balance of data protection, data availability, and database performance. To select the data protection mode that meets the needs of your business, carefully consider your data protection requirements and the performance expectations of your users.

Note: The maximum protection and maximum availability modes cannot be used if the only standby database in a configuration is a snapshot standby.

Maximum Availability This protection mode provides the highest level of data protection that is possible without compromising the availability of a primary database. Transactions do not commit until all redo data needed to recover those transactions has been written to the online redo log and to at least one synchronized standby database. If the primary database cannot write its redo stream to at least one synchronized standby database, it operates as if it were in maximum performance mode to preserve primary database availability until it is again able to write its redo stream to a synchronized standby database.

This mode ensures that no data loss will occur if the primary database fails, but only if a second fault does not prevent a complete set of redo data from being sent from the primary database to at least one standby database.

You can enable fast-start failover if the protection mode is maximum availability.

Maximum Performance This protection mode provides the highest level of data protection that is possible without affecting the performance of a primary database. This is accomplished by allowing transactions to commit as soon as all redo data generated by those transactions has been written to the online log. Redo data is also written to one or more standby databases, but this is done asynchronously with respect to transaction commitment, so primary database performance is unaffected by delays in writing redo data to the standby database(s).

This protection mode offers slightly less data protection than maximum availability mode and has minimal impact on primary database performance.

This is the default protection mode.

Maximum Protection This protection mode ensures that zero data loss occurs if a primary database fails. To provide this level of protection, the redo data needed to recover a transaction must be written to both the online redo log and to at least one synchronized standby database before the transaction commits. To ensure that data loss cannot occur, the primary database will shut down, rather than continue processing transactions, if it cannot write its redo stream to at least one synchronized standby database.

Because this data protection mode prioritizes data protection over primary database availability, Oracle recommends that a minimum of two standby databases be used to protect a primary database that runs in maximum protection mode to prevent a single standby database failure from causing the primary database to shut down.

See Also:

- [Section 5.5](#) for information on fast-start failover
- *Oracle Data Guard Concepts and Administration* for complete information about data protection modes

Step 2 Set up standby redo log files.

You must add standby redo log files on all standby databases, regardless of the protection mode you are using. Also, Oracle recommends you add standby redo log files on the primary database in preparation for a future switchover or failover. Standby redo log files are required on the primary database if you want to enable fast-start failover.

Enterprise Manager automatically prompts you to select one or more standby databases in the configuration and sets up standby redo log (SRL) files on them and on the primary database in preparation for a future role change.

See Also: If you are using the DGMGRL command-line interface, follow the instructions in *Oracle Data Guard Concepts and Administration* to configure standby redo log files. Also, see [Section 6.5.3](#) for additional information about changing the database protection mode.

Step 3 Set the LogXptMode configurable database property, if necessary.

If the data protection mode requires that you change the redo transport service used by any of the standby databases, change the setting of the `LogXptMode` configurable database property appropriately on each standby database. See [Section 4.4](#) for more information about setting the redo transport service. [Table 4–2](#) shows the protection modes and the corresponding redo transport service.

Enterprise Manager automatically specifies the correct redo transport service on the primary database in preparation for a future switchover. See [Section 6.5.3](#) for additional information about changing the database protection mode.

Table 4–2 Data Guard Protection Modes and Requirements

Protection Mode	Redo Transport	Standby Redo Log Files Needed?	Usable with Fast-Start Failover?
MAXPROTECTION	SYNC	Yes	No
MAXAVAILABILITY	SYNC	Yes	Yes
MAXPERFORMANCE	ASYNC	Yes	Yes

Step 4 Set the protection mode.

Set the protection mode using DGMGRL commands or Enterprise Manager.

With DGMGRL:

1. Use the `EDIT DATABASE (property)` command and specify the standby database whose redo transport service should be changed to correspond to the protection mode you plan to set. For example, if you plan to set the overall Data Guard configuration to operate in maximum availability mode, you must use the `EDIT DATABASE` command to set the `SYNC` mode for redo transport services. For example:

```
DGMGRL> EDIT DATABASE 'DR_Sales' SET PROPERTY 'LogXptMode'='SYNC';
```

Do this also for the primary database or another standby database in the configuration to ensure that it can support the chosen protection mode after a switchover.

2. Use the `EDIT CONFIGURATION SET PROTECTION MODE AS protection-mode` command to set the overall configuration protection mode. For example:

```
DGMGRL> EDIT CONFIGURATION SET PROTECTION MODE AS MAXAVAILABILITY;
```

See [Section 7.5](#) for a DGMGRL scenario showing how to set the protection mode.

With Enterprise Manager:

1. On the Data Guard overview page, click the link to the right of the Protection Mode label.
2. Select Maximum Protection, Maximum Availability, or Maximum Performance and click Continue.
3. If prompted, log in to the database with SYSDBA privileges and click Login.
4. Select one or more standby databases to support the protection mode that you selected. If standby redo log files are needed, verify the names of the log files. Click OK.
5. On the Confirmation page, click Yes.

See [Section 6.5.3](#) for a scenario showing how to set the protection mode.

After you upgrade the protection mode using either DGMGRL or Enterprise Manager, the primary database will be restarted automatically if you are upgrading to maximum protection mode. The primary database need not be restarted following a downgrade of the protection mode.

4.6.2 How the Protection Modes Influence Broker Operations

This section describes how operations such as switchover, failover, disabling, or enabling the Data Guard configuration can have an effect on the configuration's protection mode and redo transport services. This section contains the following sections:

- [Upgrading or Downgrading the Current Protection Mode](#)
- [Switchover Operations](#)
- [Failover Operations](#)
- [Disable and Enable Operations](#)
- [Requirements For Removing a Database from the Configuration](#)
- [Requirements On Other Operations](#)

4.6.2.1 Upgrading or Downgrading the Current Protection Mode

No restart is necessary when you upgrade the current Data Guard protection mode to maximum availability or when you downgrade the current Data Guard protection mode. Follow these recommendations when upgrading or downgrading the Data Guard protection mode:

- When upgrading the protection mode, upgrade the redo transport service before you upgrade the overall protection mode. (Enterprise Manager does this for you. See [Section 6.5.3](#) for information.) At the time when you change the protection mode or reset the redo transport service of a standby database, the broker verifies that there is at least one standby database in the configuration that can support the desired grade of protection. If not, then the broker does not change the protection mode and returns an error.
- When downgrading the protection mode, downgrade the protection mode first and then change the redo transport service (if necessary). The broker will disallow

a change of the redo transport service if doing so invalidates the current overall protection mode.

If you upgrade the protection mode from the maximum performance mode, the broker ensures that there is at least one standby database whose `LogXptMode` configurable database property is set to `SYNC`. Additionally, for upgrades to maximum protection mode, the broker ensures there are no gaps in the redo data on the standby database. If there are no standby databases in the configuration that meet these requirements, the request to upgrade the protection mode is rejected with an error.

The protection mode cannot be changed if fast-start failover is enabled.

WARNING: The primary database will be shut down and restarted if you upgrade the protection mode to maximum protection.

4.6.2.2 Switchover Operations

A switchover does not change the overall Data Guard protection mode. The protection mode remains the same as it was before the switchover.

This requires that there be a standby database that is properly configured to support the current protection mode once the switchover completes. This can be either another standby database in the configuration or the current primary database that will become a standby database after the switchover completes.

Before you perform a switchover, if necessary, you can add standby redo log files and set the redo transport service on the current primary database, or on another standby database in the configuration, to the `SYNC` or `ASYNC` mode that is required to support the Data Guard protection mode. Then, when the switchover begins:

- The broker verifies the presence of standby redo log files and the redo transport service setting on each standby database and on the current primary database.
- The broker verifies there are no gaps in the redo data present on the target standby database.

If the verification is successful, the switchover continues; otherwise, the switchover fails, and the database roles and the broker configuration files remain unchanged.

WARNING: The broker will shut down and restart the primary database if the target of the switchover is a physical standby database.

See Also: [Section 5.3](#) for more information about switchovers

4.6.2.3 Failover Operations

After you perform a manual failover, the Data Guard protection mode is downgraded to maximum performance mode if the protection mode was at maximum protection. You can upgrade the protection mode later, if necessary. If the protection mode was at maximum availability, it remains at maximum availability. The redo transport services of the standby databases remain unchanged.

If fast-start failover occurs, the broker preserves the protection mode that was in effect just prior to the fast-start failover.

See Also: [Section 5.4](#) and [Section 5.5](#) for more information about manual failover and fast-start failover, respectively

4.6.2.4 Disable and Enable Operations

When you disable broker management of a standby database, the broker checks to see if the overall protection mode can still be satisfied by any of the remaining standby databases. If not, the broker rejects the disable operation. Otherwise, the broker allows the disable operation to proceed as long as fast-start failover is not enabled. If it is enabled, the broker allows the disable operation to proceed only if the standby database is not the target standby database for fast-start failovers.

Caution: If you disable broker management of a standby database in the broker configuration, that standby database cannot be used by the broker as a failover target in the event of loss of the primary database.

After a standby database is successfully disabled, you can change the redo transport service for that database and the broker will record the change in the broker configuration file. The change will not affect the overall protection mode because it is guaranteed that at least one of the enabled standby databases already satisfies the overall protection mode requirement.

As long as fast-start failover is not enabled, you can disable the entire configuration regardless of the protection mode. You cannot disable the configuration if fast-start failover is enabled. See [Section 5.5.2.2, "Restrictions When Fast-Start Failover is Enabled"](#) for more information.

If the entire configuration is disabled, you can change any broker settings, including the redo transport services of the standby databases and the protection mode of the configuration. The broker saves the changes in the broker configuration file, but the changes will not be made to the database itself.

When enabling broker management of the entire configuration, the broker first checks to see if the protection mode will be satisfied by the redo transport services of the standby databases that will be enabled. If not, the enable operation fails and the configuration remains disabled. Otherwise, the enable operation successfully enables the configuration, and the broker enables the database using the settings saved in the broker configuration file.

4.6.2.5 Requirements For Removing a Database from the Configuration

When removing a standby database from the broker configuration, the broker checks to see if the protection mode will still be satisfied. The operation fails if:

- Removing the database compromises the protection mode
- Fast-start failover is enabled and you try to remove the standby database that is the target of the fast-start failover

You can remove the configuration at any time, unless fast-start failover is enabled.

4.6.2.6 Requirements On Other Operations

Some operations that take place in a broker configuration, especially operations related to redo transport services, can affect the overall protection mode. These operations include:

- Stopping redo transport services on the primary database
- Stopping redo transport services to individual standby databases

- Downgrading the `LogXptMode` configurable database property from `SYNC` to `ASYNC` on the only standby database that supports a configuration operating in maximum availability mode or maximum protection mode

Before any of these operations can proceed, the broker checks to see if the protection mode will be supported by the redo transport service settings on the standby databases after the operation completes. If not, the broker fails the operation and returns an error.

4.7 Managing Fast-Start Failover

For *lights out administration*, you can enable **fast-start failover** to allow the broker to determine if a failover is necessary and to initiate a failover to a pre-specified target standby database, with either no data loss or a configurable amount of data loss. In addition, you can specify under which conditions or errors you want a failover to be initiated. Oracle also provides the `DBMS_DG` PL/SQL package to allow an application to request a fast-start failover.

The following configuration properties are used to control the behavior of fast-start failover:

- `FastStartFailoverThreshold`
- `FastStartFailoverPmyShutdown`
- `FastStartFailoverLagLimit`
- `FastStartFailoverAutoReinstate`
- `FastStartFailoverTarget`

You can also use Oracle Enterprise Manager or the `DGMGRL ENABLE FAST_START FAILOVER CONDITION` and `Enterprise DISABLE FAST_START FAILOVER CONDITION` commands to specify conditions for which a fast-start failover should occur.

4.7.1 Configure Properties to Tune Fast-Start Failover

The configurable properties for fast-start failover include:

- `FastStartFailoverThreshold`
Set the `FastStartFailoverThreshold` configuration property to specify the number of seconds you want the observer and target standby database to wait (after detecting the primary database is unavailable) before initiating a failover. See [Section 5.5.2, "Enabling Fast-Start Failover"](#) on page 5-17 for more information and an example.
- `FastStartFailoverPmyShutdown`
The `FastStartFailoverPmyShutdown` configuration property controls whether the primary database will shut down if redo generation has been stalled (`FS_FAILOVER_STATUS` column of `V$DATABASE` contains a value of `STALLED`) and the primary database has lost connectivity with the observer and target standby database for longer than the number of seconds specified by the `FastStartFailoverThreshold` configuration property. The default value for `FastStartFailoverPmyShutdown` is `TRUE`.

Note: The primary database is always shut down if a user configurable fast-start failover condition is detected or if an application initiated a fast-start failover by calling the `DBMS_DG.INITIATE_FS_FAILOVER` function.

- `FastStartFailoverLagLimit`

The fast-start failover feature can be configured on databases operating in maximum performance mode. Destinations that receive redo in `ASync` mode will be acceptable fast-start failover target standby databases, and these destinations can lag the primary in terms of redo received and applied. A configurable time-based limit can be specified through the `FastStartFailoverLagLimit` configuration property. If the standby database's applied redo point is within this many seconds of the primary's redo generation point, a fast-start failover will be allowed. If its applied point lags beyond this limit, a fast-start failover is not allowed. The `FastStartFailoverLagLimit` configuration property is not used if fast-start failover is enabled when the configuration is operating in maximum availability mode.

An `ASync` destination is only a valid fast-start failover target in a configuration operating in maximum performance mode. If the user wishes to change protection mode or change the destination to `sync`, he must first disable fast-start failover. Likewise, changing the protection mode from `MAXAVAILABILITY` to `MAXPERFORMANCE` will require first disabling fast-start failover and changing the `LogXptMode` property of the primary and target standby to `ASync`.

Reinstatement of an old primary will be possible after a fast-start failover to an `ASync` target standby. If the observer rediscovers the old primary, it will automatically reinstate the old primary and any redo generated within the specified lag will be lost.

See Also: [Chapter 9, "Database Properties"](#) for more information

- `FastStartFailoverAutoReinstate`

The `FastStartFailoverAutoReinstate` configuration property controls whether the former primary database is automatically reinstated if a fast-start failover occurred because the primary database crashed or was stalled for longer than `FastStartFailoverThreshold` seconds. The default value for `FastStartFailoverAutoReinstate` is `TRUE`.

If you want to perform diagnostic or repair work after failover has completed, you can avoid an automatic reinstatement by setting the `FastStartFailoverAutoReinstate` configuration property to `FALSE`.

Note: The former primary database is never automatically reinstated if a fast-start failover occurred because a user configurable fast-start failover condition was detected or because an application initiated a fast-start failover by calling the `DBMS_DG.INITIATE_FS_FAILOVER` function.

4.7.2 Configure Conditions for Fast-start Failover

By default, a fast-start failover is done when neither the observer nor the standby can reach the primary after the configured time threshold

(`FastStartFailoverThreshold`) has passed. There are also other conditions under which you might want a fast-start failover to occur.

The configurable conditions fall into two classes: those detected through the database health-check mechanism and those detected through errors raised by the Oracle server (such as ORA errors). When a specified condition occurs, the observer will initiate a fast-start failover without waiting for `FastStartFailoverThreshold` to expire, assuming the standby is in a valid state to accept a failover.

Each condition may be enabled or disabled individually. The Data Guard configuration persists all user specified configurable fast-start failover conditions in the broker configuration file.

The observer will detect when the primary database has signaled any of the enabled health-check conditions and will immediately initiate a fast-start failover, assuming the standby is in a valid fast-start failover state (observed and either synchronized or within lag limits) to accept a failover.

For specified Oracle ORA-Error conditions, the primary database will notify the observer if the error is signaled and the observer will immediately initiate a fast-start failover, assuming the standby is in a valid fast-start failover state (observed and either synchronized or within lag limits) to accept a failover.

Note: The primary database will shut down and the observer will not attempt to automatically reinstate the former primary database.

See Also:

- Oracle Enterprise Manager online help
- [ENABLE FAST_START FAILOVER CONDITION](#) on page 8-31
- [DISABLE FAST_START FAILOVER CONDITION](#) on page 8-17

4.7.3 Application Initiated Fast-Start Failover

Use the `DBMS_DG` PL/SQL package to enable an application to initiate a fast-start failover when it encounters specific conditions. When a condition uniquely known to the application is detected, it may call the `DBMS_DG.INITIATE_FS_FAILOVER` procedure, thus alerting the primary database that it wants a fast-start failover to occur immediately. The primary database will notify the observer of this and the observer will immediately initiate a fast-start failover, assuming the standby is in a valid fast-start failover state (observed and either synchronized or within lag limits) to accept a failover.

If the configuration is not failable, the `DBMS_DG.INITIATE_FS_FAILOVER` procedure will return an ORA error number (not signal an exception) informing the caller that a fast-start could not be performed.

Note: The primary database will shut down and the observer will not attempt to automatically reinstate the former primary database.

See Also: *Oracle Database PL/SQL Packages and Types Reference* for more information about the `DBMS_DG` package

4.8 Managing Database Conversions

You can use the `DGMGRL CONVERT DATABASE` command to convert a physical standby database to a snapshot standby database. A snapshot standby database is a fully updatable standby database that is created by converting a physical standby database into a snapshot standby database.

Like a physical or logical standby database, a snapshot standby database receives and archives redo data from a primary database. However, unlike a physical or logical standby database, a snapshot standby database does not apply the redo data that it receives. The redo data received by a snapshot standby database is not applied until the snapshot standby is converted back into a physical standby database, after first discarding any local updates made to the snapshot standby database.

To convert a physical standby database to a snapshot standby database you must have Flashback Database enabled. The following example shows how to convert a physical standby database to a snapshot standby database:

```
DGMGRL> CONVERT DATABASE 'DR_Sales' TO SNAPSHOT STANDBY;
```

When you are ready to convert the snapshot back into a physical standby, use the `DGMGRL CONVERT DATABASE` command as follows:

```
DGMGRL> CONVERT DATABASE 'DR_Sales' TO PHYSICAL STANDBY;
```

4.9 Database Status

Database status reveals the health of the database. In general, the broker checks the health of a database by verifying if the actual database state and settings match with those described in the broker configuration file. This is done by checking if any component of the Data Guard configuration is functioning incorrectly (for example, if redo transport services have an error), and by checking if other required database settings are correctly set (for example, if the server parameter files are available and if the `ARCHIVELOG` mode is turned on). The following is a detailed list of what is being checked by the broker on a primary database and a standby database.

On a primary database, the health check determines whether the following conditions are met:

- Database is in the state specified by the user, as recorded in the broker configuration file
- Database is in the correct data protection mode
- Database is using a server parameter file
- Database is in the `ARCHIVELOG` mode
- Database guard is turned off
- Supplemental logging is turned on when there is a logical standby database in the configuration
- Redo transport services do not have any errors
- Database settings match those specified by the broker configurable properties
- Redo transport settings match those specified by the redo transport-related properties of the standby databases
- Current data protection level is consistent with configured data protection mode

On a standby database, the health check determines whether the following conditions are met:

- Database is in the state specified by the user, as recorded in the broker configuration file
- Database is using a server parameter file
- Database settings match those specified by the broker configurable properties
- Database guard is turned on when the database is a logical standby database
- Primary and target standby databases are synchronized or within lag limits if fast-start failover is enabled

The following monitorable database properties can be used to query the database status:

- `StatusReport`
- `LogXptStatus`
- `InconsistentProperties`
- `InconsistentLogXptProps`

Note: These properties are directly accessed through the DGMGRL command-line interface. Enterprise Manager rearranges the values of these properties for presentation in the GUI.

The `StatusReport` monitorable database property provides a list of all health check problems the broker detected for a database during a health check. This is usually the first property you use to check the database status. In the following example, you see three items reported by the `StatusReport` property.

```
DGMGRL> SHOW DATABASE 'North_Sales' 'StatusReport';
STATUS REPORT
      INSTANCE_NAME  SEVERITY ERROR_TEXT
      sales1          ERROR ORA-16737: the redo transport service for standby
database "North_Sales" has an error
      sales2          ERROR ORA-16737: the redo transport service for standby
database "North_Sales" has an error
      sales2          WARNING ORA-16715: redo transport-related property
MaxFailure of standby "North_Sales" is inconsistent
```

To further check the details about the database status, you can use the `LogXptStatus`, `InconsistentProperties`, and `InconsistentLogXptProps` monitorable database properties. `LogXptStatus` lists all log transport errors detected on all instances of the primary database. `InconsistentProperties` lists all properties that have inconsistent values between the broker configuration file and the database settings. `InconsistentLogXptProps` lists all redo transport-related properties of standby databases that have inconsistent values between the broker configuration file and the redo transport settings. For example, the output of `StatusReport` (in the previous example) shows two problems: some redo transport services errors and an inconsistent redo transport-related property.

Issue the following `SHOW DATABASE` commands to obtain further details about the problems.

```
DGMGRL> SHOW DATABASE 'North_Sales' 'LogXptStatus';
REDO TRANSPORT STATUS
PRIMARY_INSTANCE_NAME STANDBY_DATABASE_NAME STATUS
```

Database Status

```
sales1          DR_Sales          ORA-12514: TNS:listener could not resolve SERVICE_NAME
                  given in connect descriptor
sales2          DR_Sales          ORA-12514: TNS:listener could not resolve SERVICE_NAME
                  given in connect descriptor
```

```
DGMGRL> SHOW DATABASE 'North_Sales' 'InconsistentLogXptProps';
```

```
INCONSISTENT REDO TRANSPORT PROPERTIES
```

INSTANCE_NAME	STANDBY_NAME	PROPERTY_NAME	MEMORY_VALUE	BROKER_VALUE
sales2	DR_Sales	MaxFailure	9	0

See Also: [Chapter 9](#) for detailed information about database properties

Switchover and Failover Operations

This chapter describes how the broker manages databases during switchover and failover. It contains the following topics:

- [Overview of Switchover and Failover in a Broker Environment](#)
- [Choosing a Target Standby Database](#)
- [Switchover](#)
- [Manual Failover](#)
- [Fast-Start Failover](#)

5.1 Overview of Switchover and Failover in a Broker Environment

An Oracle database operates in one of two roles: primary or standby. Data Guard helps you change the role of a database using either a switchover or a failover:

- A **switchover** is a role reversal between the primary database and one of its standby databases. A switchover guarantees no data loss and is typically done for planned maintenance of the primary system. During a switchover, the primary database transitions to a standby role, and the standby database transitions to the primary role.
- A **failover** is done when the primary database (all instances of an Oracle RAC primary database) fails or has become unreachable and one of the standby databases is transitioned to take over the primary role. Failover should be performed when the primary database cannot be recovered in a timely manner. Failover may or may not result in data loss depending on the protection mode in effect at the time of the failover.

Without the broker, you perform role transitions by first determining if a role transition is necessary and then issuing a series of SQL statements (as described in *Oracle Data Guard Concepts and Administration*). The broker simplifies switchovers and failovers by allowing you to invoke them using a single key click in Oracle Enterprise Manager or a single command in the DGMGRL command-line interface (referred to in this documentation as *manual failover*). Moreover, you can enable fast-start failover to fail over automatically when the conditions for fast-start failover are met. When fast-start failover is enabled, the broker determines if a failover is necessary and initiates the failover to the specified target standby database automatically, with no need for DBA intervention.

Fast-start failover allows you to increase availability with less need for manual intervention, thereby reducing management costs. Manual failover gives you control over exactly when a failover occurs and to which target standby database. Regardless

of the method you choose, the broker coordinates the role transition on all databases in the configuration.

When the database is opened for the first time after a role transition, the `DB_ROLE_CHANGE` system event fires. You can write a trigger that is associated with this system event to manage tasks after a role change occurs. See the table of system events in the *Oracle Database PL/SQL Language Reference* for more details. After a failover, the broker posts the Fast Application Notification (FAN) `OCI DATABASE_DOWN` event in addition to firing the `DB_ROLE_CHANGE` system event. You can use both events to, for example, help user applications locate services on the new primary database.

5.2 Choosing a Target Standby Database

There are many factors to take into consideration when selecting a standby database to be the next primary database after a switchover or a failover. You need to consider all of the options at the time you are building your Data Guard configuration, including factors such as the characteristics of physical standbys versus logical standbys versus snapshot standbys, the network latency to your standby database sites, the computing capabilities at a future primary database site, and so on.

Note: A snapshot standby cannot be the target of a switchover or fast-start failover operation. You can, however, perform a manual failover to a snapshot standby.

For switchovers, understanding all of the factors can simplify the choice of which standby database to consider as your new primary database. In disaster situations where a failover is necessary, you may be more limited in which standby database is the best one to pick up the failed primary database's activities. The following sections provide guidelines to help you choose a target standby database.

Note: For fast-start failover, you must pre-select the target standby database that will be used. [Section 5.5](#) provides more information about fast-start failover.

5.2.1 Choosing a Target Standby Database for Switchover

When performing a switchover in a configuration whose standby databases are all of the same type (all physical or all logical standby databases), choose the standby database that has the least amount of unapplied redo. By choosing the standby database with the least amount of unapplied redo, you can minimize the overall time it takes to complete the switchover operation. For example:

- Using DGMGRL, you can do this by examining the `RecvQEntries` monitorable database property of each standby database in the configuration. For example, connect to one of the databases in the configuration and issue the `SHOW DATABASE database_name RecvQEntries` command. (When the standby is keeping up, this property will return no rows.)
- Using Enterprise Manager, you can view the value of the `ApplyLag` column for each standby database in the `Standby Databases` section of the Data Guard Overview Page.

If the configuration contains both physical and logical standby databases, consider choosing a physical standby database (that has the least amount of unapplied redo) to be the target standby database. A switchover to a physical standby database is

preferable because all databases in the configuration will be available as standby databases to the new primary database after the switchover operation completes. Whereas a switchover to a logical standby database will invalidate and disable all of the physical and snapshot standby databases in the configuration. You will then need to reenble the physical standby databases from a backup of the new primary database before you can reenble them.

You cannot perform a switchover to a snapshot standby database unless you first convert it back to a physical standby database.

Note: If the Data Guard configuration is operating in maximum protection mode, the broker does not allow a switchover to occur to a logical standby database. The configuration must be operating in either maximum availability mode or maximum performance mode in order to be able to switch over to a logical standby database.

5.2.2 Choosing a Target Standby Database for Failover

When performing a failover in a configuration whose standbys are all of the same type, choose the standby database that has the most redo data archived to it. By choosing the standby database that has the most amount of redo data archived to it, you can minimize the amount of data loss and in some cases, incur no data loss at all.

If the configuration contains physical, snapshot, and logical standby databases, consider choosing a physical standby database as the target standby database. A failover to a physical standby database is preferable because it is likely that all standby databases in the configuration will still be available as standby databases to the new primary database after the failover operation completes.

You may failover to a snapshot standby database. However failing over to a snapshot standby database will require more time because the broker must first convert it back to a physical standby database. After the conversion, the broker will start Redo Apply to apply accumulated redo data, before failing the database over to the primary role. Because the broker performs the failover after converting the snapshot standby database to a physical standby database, it is likely that all standby databases in the configuration will still be available as standby databases to the new primary database after the failover operation completes.

A failover to a logical standby database requires that all other standby databases be reenbled from a copy of the new primary database after the failover completes. In addition, a logical standby database may contain only a subset of the data present in the primary database. (For example, if the `DBMS_LOGSTDBY.SKIP` procedure was used to specify which database operations done on the primary database will not be applied to the logical standby database.)

However, there may be exceptions to the recommendation to choose a physical standby database as the target standby database. For example, if the physical standby database is lagging behind the logical standby database (the physical standby database was running with a log apply delay via the `DelayMins` configurable database property) and your business requires minimum downtime, consider selecting the logical standby database as the failover target.

5.3 Switchover

You can switch a database from the primary role to the standby role, as well as from standby to primary. This is known as a database switchover, because the standby

database that you specify becomes the primary database, and the original primary database becomes a standby database, with no loss of data.

Whenever possible, you should switch over to a physical standby database:

- If the switchover transitions a physical standby database to the primary role, then:
 - The original primary database will be switched to a physical standby role.
 - The online redo log files will be continuously archived from the new primary database to all standby databases in the configuration.
 - The original primary database will be restarted as a part of the switchover operation.

Standby databases not involved in the switchover will continue operating in the state they were in before the switchover occurred and will automatically begin applying redo data received from the new primary database.

- If the switchover transitions a logical standby database to the primary role, then:
 - The original primary database will be switched to a logical standby role.
 - Neither the primary database nor the logical standby database needs to be restarted after the switchover completes.

Other logical standby databases in the broker configuration that were not involved in the switchover will remain viable after the switchover. There is no need to restart any databases. All physical and snapshot standby databases will be disabled after a switchover to a logical standby database.

Switchover to a logical standby database is disallowed when the configuration is operating in maximum protection mode.

WARNING: Switching over to a logical standby database results in the snapshot and physical standby databases in the broker configuration being disabled by the broker, making these databases no longer viable as standby databases. [Section 5.4.3](#) describes how to restore their viability as standby databases.

5.3.1 Before You Perform a Switchover Operation

Consider the following points before you begin a switchover:

- When you start a switchover, the broker verifies that at least one standby database, including the primary database that is about to be transitioned to the standby role, is configured to support the overall protection mode (maximum protection, maximum availability, or maximum performance) after the switchover is completed.
- Prepare the primary database in advance for its possible future role as a standby database in the context of the overall protection mode (see [Section 4.6](#)). Such preparation includes:
 - Ensuring that standby redo log files are configured on the primary database.
 - Presetting configurable database properties related to redo transport services, such as `LogXptMode`, `NetTimeout`, `StandbyArchiveLocation`, and `AlternateLocation`. For more details about managing redo transport services using configurable database properties, see [Section 4.4](#).

- Presetting configurable database properties related to log apply services, such as `DeLayMins`. For more details about managing log apply services using configurable properties, see [Section 4.5](#).
- For each temporary table, verifying that temporary files associated with that table on the primary database also exist on the standby database.

Note that the broker does not use the properties to set up redo transport services and log apply services until you actually switch over the primary database to the standby role. Thus, the validity of the values of these properties is not verified until after the switchover. Once you set these properties, their values persist through role changes during switchover and failover.

- If fast-start failover is enabled in either maximum availability or maximum performance mode, a switchover can be performed only to the pre-specified target standby database and only if the standby database is synchronized with the primary database. For information about enabling fast-start failover, see [Section 5.5.2](#).

After a switchover completes, the broker preserves the overall Data Guard protection mode as part of the switchover process by keeping the protection mode at the same protection level (maximum protection, maximum availability, or maximum performance) it was at before the switchover. Also, the network transmission mode (`SYNC` or `ASYNC`) for transporting redo to other standby databases not involved in the switchover does not change after a switchover. Log apply services on all other standby databases not involved in the switchover automatically begin applying redo data received from the new primary database.

If there are physical or snapshot standby databases in the configuration and the switchover occurs to a logical standby database, you need to re-create those databases from a copy of the new primary database and then reenable those databases, as described in [Section 5.4.3](#).

5.3.2 Starting a Switchover

The act of switching roles should be a well-planned activity. The primary and standby databases involved in the switchover should have as small a redo lag as possible. *Oracle Data Guard Concepts and Administration* provides information about setting up the databases in preparation of a switchover.

To start a switchover using Enterprise Manager, select the standby database that you want to change to the primary role and click **Switchover**. When using DGMGRL, you need to issue only one `SWITCHOVER` command to specify the name of the standby database that you want to change into the primary role.

The broker controls the rest of the switchover, as described in [Section 5.3.3](#).

5.3.3 How the Broker Performs a Switchover

Once you start the switchover, the broker:

1. Verifies that the primary and the target standby databases are in the following states:
 - a. The primary database is enabled and is in the `TRANSPORT-ON` state.
 - b. The target standby database is enabled and is in the `APPLY-ON` state.

The broker allows the switchover to proceed as long as there are no errors for the primary database and the standby database that you selected to participate in the

switchover operation. Errors occurring for any other standby databases not involved in the switchover will not impede the switchover.

2. Shuts down all instances except one.

If you are switching over to a physical standby database and either it or the primary database is a RAC database, the broker keeps only one instance running on both databases and shuts down all other instances before it continues the switchover. For an Oracle RAC physical standby, the broker ensures that the apply instance is the only instance running. If the other instances on either database cannot be shut down, the switchover fails and you must manually shut down those other instances and issue the switchover command again. It is also important that you do not start any new instances during the switchover. If you must manually shut down the instances on the physical standby database, do not shut down the apply instance.

No instances will be shut down if switching over to a logical standby database. You cannot switch over to a snapshot standby database.

3. Switches roles between the primary and standby databases.

The broker first converts the original primary database to run in the standby role. Then, the broker transitions the target standby database to the primary role. If any errors occur during either conversion, the broker stops the switchover. See [Section 10.3, "Troubleshooting Problems During a Switchover Operation"](#) for more information.

4. Updates the broker configuration file to record the change in roles.

Because the configuration file profiles all database objects in the configuration, this ensures that each database will run in the correct role and state should it be restarted later for any reason.

5. Restarts the new standby (former primary) database if the switchover occurs with a physical standby database, and Redo Apply begins applying redo data from the new primary database. If this is an Oracle RAC physical standby database, the broker directs CRS to restart the instances that were shut down prior to the switchover. In a configuration operating in maximum protection mode, the new primary database will also be restarted.
6. The new primary database is opened in read/write mode and redo transport services are started. If this is an Oracle RAC physical standby database, the broker restarts the instances that it shut down prior to the switchover.

The broker verifies the state and status of the databases to ensure that the switchover transitioned the databases to their new role correctly. Standby databases not involved in the switchover and not disabled by the broker after the switchover will continue operating in the state they were in before the switchover. Redo Apply and SQL Apply on all other standby databases not involved in the switchover automatically begin applying redo data from the new primary database.

5.4 Manual Failover

You can convert a standby database to a primary database when the original primary database fails and there is no possibility of recovering the primary database in a timely manner. This is known as a **manual failover**. There may or may not be data loss depending upon whether your primary and target standby databases were synchronized at the time of the primary database failure. The word *manual* is used to contrast this type of failover with a fast-start failover (described in [Section 5.5](#)).

Note: You can perform a manual failover even if fast-start failover is enabled. See [Section 5.5.2.4](#) for more information.

The following sections describe how to perform manual failovers:

- [Section 5.4.1, "Complete and Immediate Manual Failovers"](#)
- [Section 5.4.2, "Performing a Manual Failover Operation"](#)
- [Section 5.4.3, "Reenabling Disabled Databases After Failover or Switchover"](#)

5.4.1 Complete and Immediate Manual Failovers

Using Enterprise Manager or DGMGRL, you can perform either a *complete* (recommended) or an *immediate* failover:

- A *complete* failover is the recommended and default failover option. It automatically recovers the maximum amount of redo data for the protection mode the configuration is operating in. A complete failover also attempts to avoid disabling any standby databases that were not the target of the failover, so that they may continue serving as standby databases to the new primary database.

Whether or not standby databases that were not the target of failover (bystander standby databases) are disabled depends upon how much redo data they have applied relative to the failover target and the standby type of the failover target:

- If the failover target is a physical or snapshot standby database, the original primary database must be reenabled in order to be a standby database for the new primary database. In addition, some standby databases may be disabled by the broker during the failover if the broker detects that they have applied redo beyond where the new primary database had applied. Any database that was disabled by the broker must be reenabled using the steps described in [Section 5.4.3](#).

Note that if failover was performed on a snapshot standby database, the old primary must be reenabled as a physical standby database.

- If the failover target is a logical standby database, the original primary database and all standby databases in the configuration (that were not the target of the failover) will be disabled and must be reenabled to act as standby databases for the new primary database. Any database that was disabled by the broker must be reenabled using the steps described in [Section 5.4.3](#).

If any of the databases that were disabled as part of a failover have flashback enabled, they can be reinstated using the DGMGRL `REINSTATE` command or the Reinstatement button in Enterprise Manager.

During a complete failover, the broker performs the failover steps described in [Section 5.4.2.1](#).

- An *immediate* failover is the fastest type of failover. However, no additional data is applied on the standby database once you invoke the failover. Another consequence of immediate failover is that you must also reenable the original primary database and all other standby databases not involved in the failover before they can serve as standby databases to the new primary database. [Section 5.4.3](#) describes how to do this. During an immediate failover, the broker performs the failover steps described in [Section 5.4.2.2](#).

Caution: Always try to perform a complete failover first. Only when a complete failover is unsuccessful should you perform an immediate failover. Depending on the destination attributes of redo transport services, a complete failover can occur without any data loss, while an immediate failover usually results in data loss.

5.4.2 Performing a Manual Failover Operation

After determining that there is no possibility of recovering the primary database in a timely manner, ensure that the primary database is shut down and then begin the failover operation.

The steps in this section describe how to perform a manual failover. Depending on the failover and the types of standby databases involved, some of the databases may need to be restarted or reenabled. The instructions guide you through the appropriate steps for each type of situation.

Step 1 Determine which of the available standby databases is the best target for the failover.

Follow the guidelines described in [Section 5.2, "Choosing a Target Standby Database"](#).

Step 2 Start the failover.

Using Enterprise Manager or DGMGRL, perform either a *complete* (recommended) or an *immediate* failover.

Manual Failover Using Enterprise Manager:

On the Data Guard Overview Page in Enterprise Manager, select the standby database that you want to change to the primary role and click **Failover**. Then, on the Failover Confirmation Page, click **Yes** to invoke the default Complete failover option.

See Also: [Section 6.7, "Scenario 7: Invoking a Failover Manually"](#) on page 6-27

Manual Failover Using DGMGRL:

On the target standby database, issue the `FAILOVER` command to invoke a complete failover, specifying the name of the standby database that you want to change into the primary role:

```
DGMGRL> FAILOVER TO database-name [IMMEDIATE];
```

See Also:

- [Section 7.9, "Scenario 8: Performing a Manual Failover Operation"](#) on page 7-18
- [FAILOVER](#) on page 8-33

If the target standby database is an Oracle RAC physical or snapshot standby database, the broker will direct CRS to shut down all instances except the apply instance before it continues the failover. If the other instances cannot be shut down, the failover fails. In this case, you must manually shut down all instances except the apply instance and issue the `FAILOVER` command again. It is also important that you do not start any new instances during the failover. The broker will direct CRS to restart instances that were shut down prior to the failover.

No instances will be shut down if failing over to a logical standby database.

Step 3 Reset the protection mode.

After a manual failover (complete or immediate), the overall Data Guard protection mode is handled as follows:

- If the protection mode was at maximum protection, it is reset to maximum performance. You can upgrade the protection mode later, if necessary, as described in [Section 4.6.1](#).
- If the protection mode was at maximum availability, it remains at maximum availability.

Note: If you perform a manual failover when fast-start failover is enabled:

- The failover can only be performed to the pre-selected target standby database.
 - The broker preserves the protection mode at the maximum availability level (which is the mode it was operating in before the failover occurred).
-

Step 4 Re-establish a disaster-recovery configuration.

To maintain a viable disaster-recovery solution in the event of another disaster, you may need to perform the additional steps described in [Section 5.4.3](#) to:

- Reinstall the original primary database to act as a standby database in the new configuration.
- Reinstall or re-create standby databases in the configuration that were disabled by the broker.

After a complete failover finishes, any standby database not involved in the failover that is not viable as a standby for the new primary database will be disabled by the broker. This can happen for either of these reasons:

- The broker detects that the standby database has applied redo data beyond what has been applied on the new primary database.

For instance, this could happen if a standby database not involved in the failover has applied more redo data than the new primary database itself has applied. The standby database must be reenabled or reinstated before it can serve as a standby for the new primary database.

- The failover was to a logical standby database, the broker disables all of the (physical, snapshot, and logical) standby databases in the configuration that were not involved in the failover. They must be reenabled before they can serve as standby to the new primary database.

5.4.2.1 How the Broker Performs a Complete Failover Operation

Once you start a complete failover, the broker:

1. Verifies that the target standby database is enabled. If the database is not enabled, you will not be able to perform a failover to this database. If the target is an Oracle RAC physical or snapshot standby database, the broker the broker directs CRS to shut down all instances except the apply instance.
2. Waits for the target standby database to finish applying any unapplied redo data before stopping Redo Apply (if the target is a physical standby database) or SQL Apply (if the target is a logical standby database).

If the target is a snapshot standby database, the broker first converts the database back to a physical standby and then starts Redo Apply to apply all the accumulated redo before completing the failover and opening the database as a primary database.

3. Transitions the target standby database into the primary database role, as follows:
 - a. Opens the new primary database in read/write mode.
 - b. Determines whether or not any standby databases that did not participate in the failover operation have applied redo data beyond the new primary database, and thus need to be reenabled.

If a standby database not involved in the failover is not disabled by the broker during this failover, it will remain in the state it was in before the failover. For example, if a physical standby database was in the `APPLY-OFF` state, it will remain in the `APPLY-OFF` state.

By default the broker always determines whether bystander standby databases will be viable standby databases for the new primary when performing a complete failover. If you want the broker to skip this viability check of bystander standby databases during a complete failover, thus decreasing the overall failover time, set the `BystandersFollowRoleChange` configuration property to `NONE`.

When this property is set to `NONE`, the broker will disable all bystander standby databases without checking whether they have applied more redo data than the new primary database. You will have to manually reenable the standby databases after failover has completed. Use the `SHOW CONFIGURATION BystandersFollowRoleChange` command to see the value of this property. The default value is `ALL`.

This property also affects whether the broker skips viability checks of bystander standby databases when a fast-start failover occurs.

- c. Starts redo transport services to begin transmitting redo data to all standby databases not involved in the failover and that were not disabled.

Note: Standby databases not directly involved in a failover may be disabled by the broker during the failover, and they must be reenabled in the configuration before they can serve as standby databases to the new primary database. Oracle recommends configuring Flashback Database on every database so that if failover occurs to a physical standby database, you can more easily reinstate any disabled physical standby databases. However, if failover occurs to a logical standby database, all (physical, snapshot, and logical) standby databases will be disabled by the broker. In this case, Flashback Database cannot be used to reinstate databases.

4. If the target is an Oracle RAC physical or snapshot standby database, the broker directs CRS to restart all instances that it shut down prior to the failover.

The broker allows the failover to proceed as long as there are no errors for the standby database that you selected to participate in the failover. Errors occurring for any standby databases not involved in the failover will not stop the failover. If you initiated a complete failover and it fails, you might need to use immediate failover.

5.4.2.2 How the Broker Performs an Immediate Failover Operation

Once you start an immediate failover, the broker:

1. Verifies that the target standby database is enabled. If the standby database is not enabled for management by the broker, then the failover cannot occur.
2. Stops Redo Apply or SQL Apply on the standby database immediately, without waiting until all available redo data has been applied. This may result in data loss.
3. Transitions the target standby database into the primary role, opens the new primary database in read/write mode, and starts redo transport services.

After an immediate failover completes, all the standby databases in the configuration, regardless of their type, are disabled. They must be reenabled before they can serve as standby database to the new primary database. See [Section 5.4.3](#) for information.

The broker allows the failover to proceed as long as there are no errors for the standby database that you selected to participate in the failover.

5.4.3 Reenabling Disabled Databases After Failover or Switchover

To restore your original disaster-recovery solution after switchover to a logical standby database or after failover to any standby database, you may need to perform additional steps.

Databases that have been disabled after a role transition are not *removed* from the broker configuration, but they are disabled in the sense that the databases are no longer managed by the broker.

To reenable broker management of these databases, you must reinstate or re-create the databases using one of the following procedures:

- If a database can be reinstated, the database will show the following status after a complete failover:

```
ORA-16661: the standby database needs to be reinstated
```

Reinstate the database using the DGMGRL `REINSTATE DATABASE` command or the `reinst` option in Enterprise Manager, as described in [Section 5.4.3.1, "How to Reinstate a Database"](#) on page 5-13.

- If a database must be re-created from a copy of the new primary database, it will have the following status:

```
ORA-16795: the standby database needs to be re-created
```

Re-create the standby database from a copy of the primary database and then reenable it. The procedures for creating a standby database are documented in *Oracle Data Guard Concepts and Administration*. See [Section 5.4.3.2, "How to Re-create and Reenable a Disabled Database"](#) on page 5-14 for more information.

Note: Any database that was disabled while multiple role changes were performed cannot be reinstated. You must re-create the database manually and then reenable the database in the broker configuration.

Whether you reinstate or re-create a database depends on if you performed a switchover or failover and on the type of standby database that was the target of the operation.

The following table describes how to reenoble disabled databases based on the type of role transition that was performed. The status value associated with databases that are disabled after a switchover or failover will also guide you in choosing which procedure to use. These status values can be viewed in the output from the `DGMGRL SHOW DATABASE` or on the Data Guard Overview page in Enterprise Manager.

Table 5–1 Reenabling Disabled Databases After Failover or Switchover

Role Transition (Switchover or Failover)	Reenabling a Failed Primary Database	Reenabling the Standby Databases Not Involved in the Role Transition
Switchover to a physical standby database	No action is required.	No action is required.
Switchover to a logical standby database	No action is required.	All physical and snapshot standby databases will be disabled and must be re-created from a copy of the new primary database. Logical standby databases will not be disabled.
Switchover to a snapshot standby database	Not supported.	Not supported.
Complete failover to a physical standby database	The broker disables the failed primary database during the failover operation. You can reinstate the database if Flashback Database was enabled prior to the failover and there are sufficient flashback logs on the failed primary database. Otherwise, you must re-create the primary database from a copy of the new primary database.	Physical standby databases that were disabled during failover can be reinstated if Flashback Database was enabled prior to failover and there are sufficient flashback logs on the physical standby database. Otherwise, the physical standby databases must be re-created from a copy of the new primary database. Logical and snapshot standby databases disabled during failover must be re-created from a copy of the new primary database.
Complete failover to a logical standby database	The broker disables the failed primary database during the failover. You can reinstate the database if Flashback Database was enabled prior to failover and there are sufficient flashback logs on the failed primary database. Otherwise, re-create the primary database from a copy of the new primary database.	The broker disables all standby databases not involved in the failover. You must re-create the databases from a copy of the new primary database.

Table 5–1 (Cont.) Reenabling Disabled Databases After Failover or Switchover

Role Transition (Switchover or Failover)	Reenabling a Failed Primary Database	Reenabling the Standby Databases Not Involved in the Role Transition
Complete failover to a snapshot standby database	The broker disables the failed primary database during the failover operation. You can reinstate the database if Flashback Database was enabled prior to the failover and there are sufficient flashback logs on the failed primary database. Otherwise, you must re-create the primary database from a copy of the new primary database.	Physical standby databases that were disabled during failover can be reinstated if Flashback Database was enabled prior to failover and there are sufficient flashback logs on the physical standby database. Otherwise, the physical standby databases must be re-created from a copy of the new primary database. Logical and snapshot standby databases disabled during failover must be re-created from a copy of the new primary database.
Immediate failover to either a physical, snapshot, or logical standby database	The broker disables the failed primary database during failover. You must re-create the database from a copy of the new primary database.	The broker disables all standby databases not involved in the failover. You must re-create the databases from a copy of the new primary database.

The following sections describe how to reinstate or reenab a database.

5.4.3.1 How to Reinstate a Database

You can use the broker's `REINSTATE` command to reenab the failed primary database after performing a complete failover to either a physical, snapshot, or logical standby database. You can also use the broker's `REINSTATE` command to reenab any physical standby databases that were not the target of the failover operation but were disabled during a complete failover to a physical standby database.

Databases that can be reinstated will have the following status value:

```
ORA-16661: the standby database needs to be reinstated
```

For the `REINSTATE` command to succeed, Flashback Database must have been enabled on the database prior to the failover and there must be sufficient flashback logs on that database. In addition, the database to be reinstated and the new primary database must have network connectivity.

To reinstate a database:

1. Restart the database to the mounted state
2. Connect to the new primary database
3. Use Enterprise Manager or DGMGRL to reinstate the database

When reinstating a failed primary database, the broker reenables it as a standby database of the same type (physical or logical standby database) as the old standby database. When reinstating physical standby databases that were disabled during a failover, the broker reenables them as physical standby databases to the new primary database.

Reinstatement Using Enterprise Manager

On the Data Guard Overview page, click the `Database must be reinstated` link. This brings up the General Properties page that provides a Reinstatement button. After you click the Reinstatement button, Enterprise Manager begins reinstating the database.

When the process is complete, the database will be enabled as a standby database to the new primary database, and Enterprise Manager displays the Data Guard Overview page.

Reinstatement Using DGMGRL

Issue the following command while connected to any database in the broker configuration, except the database that is to be reinstated:

```
DGMGRL> REINSTATE DATABASE db_unique_name;
```

The newly reinstated standby database will begin serving as standby database to the new primary database. If the database is not reinstated successfully, then you must reenoble it from a copy of the new primary database, as described in [Section 5.4.3.2](#).

5.4.3.2 How to Re-create and Reenable a Disabled Database

If you performed a failover or switchover that requires you to re-create the failed primary database or standby databases that were disabled during the role transition, follow the procedures in *Oracle Data Guard Concepts and Administration*.

Note that if you are re-creating the old primary database, it must be created as the standby type of the old standby database. For example, if the old standby was a physical standby, then the old primary must be re-created as a physical standby. It can then be properly enabled.

After the database has been re-created, enable broker management of the re-created standby database by using the `DGMGRL ENABLE DATABASE` command.

5.5 Fast-Start Failover

Fast-start failover allows the broker to automatically fail over to a previously chosen standby database in the event of loss of the primary database. Fast-start failover quickly and reliably fails over the target standby database to the primary database role, without requiring you to perform any manual steps to invoke the failover. Fast-start failover can be used only in a broker configuration and can be configured only through DGMGRL or Enterprise Manager.

Either maximum availability mode or maximum performance mode can be used with fast-start failover. Maximum availability mode provides an automatic failover environment guaranteed to lose no data. Maximum performance mode provides an automatic failover environment guaranteed to lose no more than the amount of data (in seconds) specified by the `FastStartFailoverLagLimit` configuration property. This property indicates the maximum amount of data loss that is permissible in order for an automatic failover to occur. It is only used when fast-start failover is enabled and the configuration is operating in maximum performance mode.

Once fast-start failover is enabled, the broker will ensure that fast-start failover is only possible when the configured data loss guarantee can be upheld. If the configured data loss guarantee cannot be upheld, redo generation on the primary database will be stalled. To avoid a prolonged stall, either the observer or target standby database may allow the primary database to continue redo generation after first recording that a fast-start failover cannot happen.

The broker will restore the ability to automatically failover once the configured data loss guarantee is restored. For a configuration that is operating in maximum

availability mode, this occurs once the target standby database has received all missing redo data. For a configuration that is operating in maximum performance mode, this occurs once the target standby database's redo applied point is no longer lagging the primary database's redo generation point by the value specified by the `FastStartFailoverLagLimit` configuration property.


This section describes how to enable fast-start failover and an **observer** site that monitors the fast-start failover environment. The observer is a separate OCI client-side component that runs on a different computer from the primary and standby databases and monitors the availability of the primary database. The observer is described in more detail in [Section 5.5.7](#).

Once the observer is started, no further user interaction is required. If both the observer and designated standby database lose connectivity with the primary database for longer than the number of seconds specified by the `FastStartFailoverThreshold` configuration property, the observer will initiate a fast-start failover to the standby database. In addition, the primary database will shut down if it perceives a loss of connectivity for a period longer than `FastStartFailoverThreshold` seconds, if the `FastStartFailoverPmyShutdown` configuration property is set to `TRUE`. After the failover completes, the former primary database is automatically reinstated as a standby database when a connection to it is reestablished, if the `FastStartFailoverAutoReinstate` configuration property is set to `TRUE`.

Note: The `FastStartFailoverPmyShutdown` and `FastStartFailoverAutoReinstate` configuration properties do not affect whether the former primary database is shut down and automatically reinstated, respectively, when a fast-start failover occurs if either a user configurable fast-start failover condition is detected or if an application initiated a fast-start failover by calling the `DBMS_DG.INITIATE_FS_FAILOVER` function. In these cases, the former primary database is always shut down and never automatically reinstated.

[Figure 5–1](#) shows the relationships between the primary database, target standby database, and the observer during fast-start failover:

- **Before Fast-Start Failover:** Data Guard is operating in a steady state, with the primary database transmitting redo data to the target standby database and the observer monitoring the state of the entire configuration.
- **FastStart Failover Ensues:** Disaster strikes the primary database and its network connections to both the observer and the target standby database are lost. Upon detecting the break in communication, the observer attempts to reestablish a connection with the primary database for the amount of time defined by the `FastStartFailoverThreshold` property before initiating a fast-start failover. If the observer is unable to regain a connection to the primary database within the specified time, and the target standby database is ready for fast-start failover, then fast-start failover ensues.
- **After Fast-Start Failover:** The fast-start failover has completed and the target standby database is running in the primary database role. After the former primary database has been repaired, the observer reestablishes its connection to that database and reinstates it as a new standby database. The new primary database starts transmitting redo data to the new standby database.

Figure 5–1 Relationship of Primary and Standby Databases and the Observer

The following sections describe these topics:

- [Prerequisites for Enabling Fast-Start Failover](#)
- [Enabling Fast-Start Failover](#)
- [Viewing Fast-Start Failover Configuration Statistics and Status](#)
- [Disabling Fast-Start Failover](#)
- [Performance Considerations for Fast-Start Failover](#)
- [Managing the Observer](#)
- [Reinstating the Former Primary Database in the Broker Configuration](#)
- [Shutting Down Databases In a Fast-Start Failover Environment](#)

5.5.1 Prerequisites for Enabling Fast-Start Failover

The following prerequisites must be met before the broker allows you to enable fast-start failover:

- Ensure the broker configuration is operating in either maximum availability mode or maximum performance mode.
See [Section 4.6.1](#) for information about configuring the protection mode, standby redo logs, and the `LogXptMode` property.
- Ensure that the standby database you choose to be the target of fast-start failover has its `LogXptMode` property set to `SYNC` if you wish to enable fast-start failover in maximum availability mode, or to `ASYN` if you wish to enable fast-start failover in maximum performance mode. The current primary database must have its `LogXptMode` property set accordingly and must have standby redo logs configured.

- Enable Flashback Database and set up a flash recovery area on both the primary database and the target standby database.
See *Oracle Database Backup and Recovery User's Guide*.
- Install the DGMGRL command-line interface on the observer computer as described in [Section 2.1](#).
- Configure the `TNSNAMES.ORA` file on the observer system so that the observer is able to connect to the primary database and the pre-selected target standby database.
- Create static service names so that the observer can automatically restart a database as part of reinstatement. See [Section 2.2, "Prerequisites"](#) for more information.

5.5.2 Enabling Fast-Start Failover

You can enable fast-start failover from any site while connected to any database in the broker configuration. Enabling fast-start failover does not trigger a failover. Instead, it allows the observer to begin observing the primary and standby databases and initiate a fast-start failover should conditions warrant a failover.

Perform the following steps to enable fast-start failover and start the observer. The steps assume that you are connected as `SYS` and that a primary and standby database are already set up in a broker configuration.

Step 1 Determine which of the available standby databases is the best target for the failover.

Follow the guidelines described in [Section 5.2, "Choosing a Target Standby Database"](#).

Step 2 Specify the target standby database with the `FastStartFailoverTarget` configuration property.

You can specify only one target standby database when setting the `FastStartFailoverTarget` configuration property on the current primary database:

- If there is only one standby database in the configuration, you can skip this step and continue with Step 3. The broker will automatically set the `FastStartFailoverTarget` property on the primary and standby databases to point to each other as their respective target during a failover.
- If there is more than one standby database in the configuration, you must explicitly set the `FastStartFailoverTarget` property on the primary database and your chosen target standby database to point to each other for the purpose of defining which standby database will be the target of a fast-start failover. For example:

```
DGMGRL> EDIT DATABASE 'North_Sales' SET PROPERTY FastStartFailoverTarget = 'DR_Sales';
DGMGRL> EDIT DATABASE 'DR_Sales' SET PROPERTY FastStartFailoverTarget = 'North_Sales';
```

In this example, the current primary database, `North_Sales`, specifies `DR_Sales` as its failover target, and the target standby database, `DR_Sales`, specifies the current primary database as its target. When `DR_Sales` becomes the primary database it must have a standby target to which it can fail over.

Note: To change the `FastStartFailoverTarget` property to point to a different standby database, disable fast-start failover, set the `FastStartFailoverTarget` property, and reenables fast-start failover.

See [Section 9.2.14, "FastStartFailoverTarget"](#) for more information about this property.

Step 3 Determine the protection mode you want

Fast-start failover can be enabled for either maximum availability mode or maximum performance mode. If you cannot tolerate any loss of data, then ensure that the configuration protection mode is set to maximum availability. To do this, the `LogXptMode` configurable database property for both the primary and target standby database must be set to `SYNC`. Then set the configuration protection mode to maximum availability. For example:

```
DGMGRL> EDIT DATABASE 'North_Sales' SET PROPERTY LogXptMode=SYNC;
DGMGRL> EDIT DATABASE 'DR_Sales' SET PROPERTY LogXptMode=SYNC;
DGMGRL> EDIT CONFIGURATION SET PROTECTION MODE AS MaxAvailability;
```

If you are more concerned about the performance of the primary database than a minimal loss of data, consider enabling fast-start failover when the configuration protection mode is set to maximum performance. In this mode you will need to consider how much data loss is acceptable in terms of seconds and set the `FastStartFailoverLagLimit` configuration property accordingly. This property specifies the amount of data, in seconds, that the target standby database can lag behind the primary database in terms of redo applied. If the standby database's redo applied point is within that many seconds of the primary database's redo generation point, a fast-start failover will be allowed. The `FastStartFailoverLagLimit` configuration property is only used by the broker when enabling fast-start failover for configurations operating in maximum performance mode. The default value is 30 seconds and the lowest possible value is 10 seconds.

In addition to setting the configuration protection mode to maximum performance, you will also need to ensure that the `LogXptMode` configurable database property for both the primary and target standby database is set to `ASYNC`. For example:

```
DGMGRL> EDIT DATABASE 'North_Sales' SET PROPERTY LogXptMode=ASYNC;
DGMGRL> EDIT DATABASE 'DR_Sales' SET PROPERTY LogXptMode=ASYNC;
DGMGRL> EDIT CONFIGURATION SET PROTECTION MODE AS MaxPerformance;
DGMGRL> EDIT CONFIGURATION SET PROPERTY FastStartFailoverLagLimit=45;
```

Step 4 Set the `FastStartFailoverThreshold` configuration property.

Fast-start failover will occur if both the observer and the target standby database lose connection to the primary database for the period of time specified by the `FastStartFailoverThreshold` configuration property.

Set the `FastStartFailoverThreshold` property to specify the number of seconds you want the observer and target standby database to wait (after detecting the primary database is unavailable) before initiating a failover. For example:

```
DGMGRL> EDIT CONFIGURATION SET PROPERTY FastStartFailoverThreshold = 45;
```

This is a configuration-level property. The default value for the `FastStartFailoverThreshold` property is 30 seconds and the lowest possible value is 6 seconds. If you have an Oracle RAC primary database, consider specifying a

higher value to minimize the possibility of a false failover in the event of an instance failure.

The time interval starts when the observer first loses its connection to the primary database. If the observer is unable to regain a connection to the primary database within the specified time, then the observer begins a fast-start failover provided the standby database is ready to fail over. Although the default value of 30 seconds is typically adequate for detecting outages and failures on most configurations, you can adjust failover sensitivity with this property to decrease the probability of false failovers in a temporarily unstable environment.

If the `FastStartFailoverPmyShutdown` configuration property is set to `TRUE`, the primary database will shut down after `FastStartFailoverThreshold` seconds has elapsed if redo generation has been stalled and the primary database is unable to reestablish connectivity with either the observer or target standby database.

Note that the `FastStartFailoverThreshold` property can be changed even when fast-start failover is enabled.

See Also: [Section 9.2.15](#) for reference information about the `FastStartFailoverThreshold` property

Step 5 Set other database properties (optional).

You can optionally set the database properties described in the following table:

Property Name	Description	Default Value
<code>FastStartFailoverPmyShutdown</code>	<p>This configuration property causes the primary database to shut down if fast-start failover is enabled and <code>V\$DATABASE.FS_FAILOVER_STATUS</code> indicates the primary has been <code>STALLED</code> for longer than <code>FastStartFailoverThreshold</code> seconds. A value of <code>TRUE</code> helps to ensure that an isolated primary database cannot satisfy user queries.</p> <p>This property cannot be used to prevent the primary database from shutting down if a fast-start failover occurred because a user configuration condition was detected or was requested by an application by calling the <code>DBMS_DG.INITIATE_FS_FAILOVER</code> function.</p>	<code>TRUE</code>
<code>FastStartFailoverLagLimit</code>	<p>This configuration property establishes an acceptable limit, in seconds, that the standby is allowed to fall behind the primary in terms of redo applied, beyond which a fast-start failover will not be allowed. The lowest possible value is 10 seconds.</p> <p>This property is used when fast-start failover is enabled and the configuration is operating in maximum performance mode.</p>	30 seconds
<code>FastStartFailoverAutoReinstate</code>	<p>This configuration property causes the former primary database to be automatically reinstated if a fast-start failover was initiated because the primary database was either isolated or had crashed. To prevent automatic reinstatement of the former primary database in these cases, set this configuration property to <code>FALSE</code>. The broker never automatically reinstates the former primary database if a fast-start failover was initiated because a user configuration condition was detected or was requested by an application calling the <code>DBMS_DG.INITIATE_FS_FAILOVER</code> function.</p>	<code>TRUE</code>

Property Name	Description	Default Value
<code>ObserverConnectIdentifier</code>	This configurable database property is used to specify how the observer should connect to and monitor the primary and standby database. Set this property for the primary and target standby database if you want the observer to use a different connect identifier than that used to ship redo data (that is, the connect identifier specified by the <code>DGConnectIdentifier</code> property).	Observer uses the value of the <code>DGConnectIdentifier</code> configurable property to connect to and monitor the primary and target standby databases.

Step 6 Enable additional fast-start failover conditions (optional)

By default, a fast-start failover is done when both the observer and the standby cannot reach the primary after the configured time threshold (`FastStartFailoverThreshold`) has passed.

You can optionally indicate the database health conditions that should cause fast-start failover to occur. These conditions are described in the following table:

Health Condition	Description	Enabled by Default
Datafile Offline	A datafile is offline because of a write error.	Yes
Corrupted Dictionary	Dictionary corruption of a critical database object. Currently, this state can be detected only when the database is open	Yes
Corrupted Controlfile	Controlfile is permanently damaged because of a disk failure.	Yes
Inaccessible Logfile	LGWR is unable to write to any member of the log group because on an I/O error	No
Stuck Archiver	Archiver is unable to archive a redo log because the device is full or unavailable.	No

In Oracle RAC configurations, the Inaccessible Logfile and Stuck Archiver health conditions may only be applicable to a single instance. Careful consideration should be given before enabling fast-start failover for either of these conditions because doing so will supersede availability options provided by CRS.

You can also specify errors raised by the Oracle server (ORA errors) as conditions for which fast-start failover should occur.

You can specify particular conditions for which a fast-start failover should occur using either Oracle Enterprise Manager or the `DGMGRL ENABLE FAST_START FAILOVER CONDITION` and `DISABLE FAST_START FAILOVER CONDITION` commands.

Step 7 Enable fast-start failover.

Use the Enterprise Manager Fast-Start Failover wizard or the `DGMGRL ENABLE FAST_START FAILOVER` command to enable fast-start failover. To enable fast-start failover, both the primary and target standby databases must be running and have connectivity, and satisfy all of the prerequisite conditions listed in [Section 5.5.1](#).

Enable Fast-Start Failover Using Enterprise Manager

To enable fast-start failover in Enterprise Manager, use the Fast-Start Failover wizard. On the Data Guard Overview Page next to the "Fast-Start Failover" status field, click

Disabled to invoke the Fast-Start Failover Page. Then, on the Fast-Start Failover Change Mode Page, click Enabled. Enterprise Manager will start the observer. Then, on the Fast-Start Failover Configure Page, select the standby database that should be the target of a failover. See [Section 5.2, "Choosing a Target Standby Database"](#) for helpful advice. This page will not allow you to alter the protection mode. Rather, fast-start failover will be enabled in accordance with the current protection mode. If the currently configured mode is maximum protection, Enterprise Manager will downgrade the mode to maximum availability.

See Also: [Section 6.4, "Scenario 4: Enabling Fast-Start Failover and the Observer"](#) for an example of the fast-start failover wizard

Enable Fast-Start Failover Using DGMGRL

To enable fast-start failover with DGMGRL, issue the `ENABLE FAST_START FAILOVER` command while connected to any database in the broker configuration, including on the observer computer. For example:

```
DGMGRL> ENABLE FAST_START FAILOVER;
Enabled.
```

See Also:

- [ENABLE FAST_START FAILOVER](#) on page 8-29
- [Section 7.6, "Scenario 5: Enabling Fast-Start Failover and Starting the Observer"](#) on page 7-8

Note: Administration at the target standby site should be as comprehensive as that at the primary site because the standby database may assume the primary role without prior notice. Staff support, hardware and software, security (both software and site), network connections, and bandwidth should be equivalent at both sites.

Step 8 Start the Observer.

The primary database must be running in order to start the observer.

You can start the observer before or after you enable fast-start failover. However, it is recommended that you have the observer running whenever you have fast-start failover enabled. If fast-start failover is enabled, the observer immediately begins monitoring the status and connections to the primary and target standby databases.

Starting the Observer Using Enterprise Manager

If the Enterprise Manager agent is installed on the observer computer, it automatically starts the observer when you enable fast-start failover through Enterprise Manager. If the agent is not present, you must start the observer manually using the following instructions for the DGMGRL command-line interface.

Starting the Observer Using DGMGRL

To start the observer with DGMGRL, issue the following command on the observer computer:

```
DGMGRL> START OBSERVER;
```

The observer is a continuously executing process that is created when the `START OBSERVER` command is issued. Thus, the command-line prompt on the observer

computer does not return until you issue the `STOP OBSERVER` command from another DGMGRL session. To issue commands and interact with the broker configuration, you must connect through another DGMGRL client session.

See the [START OBSERVER](#) command on page 8-54 for more information.

Step 9 Verify the fast-start failover environment.

To verify the readiness of the fast-start failover configuration, issue the DGMGRL `SHOW CONFIGURATION VERBOSE` command or the `SHOW FAST_START FAILOVER` command on the primary database. For example:

```
DGMGRL> SHOW FAST_START FAILOVER;
```

```
Fast-Start Failover: ENABLED
Threshold:          60 seconds
Target:            DR_Sales
Observer:          observer.foo.com
Lag Limit:         30 seconds (not in use)
Shutdown Primary: TRUE
Auto-reinstate:    TRUE
```

```
Configurable Failover Conditions
Health Conditions:
  Corrupted Controlfile      YES
  Corrupted Dictionary       YES
  Inaccessible Logfile       NO
  Stuck Archiver             NO
  Datafile Offline          YES
```

```
Oracle Error Conditions:
(none)
```

The following sections provide more information about the fast-start failover environment:

- [When Fast-Start Failover Is Enabled and the Observer Is Running](#)
- [Restrictions When Fast-Start Failover is Enabled](#)
- [Shutting Down the Primary Database When Fast-Start Failover Is Enabled](#)
- [Performing Manual Role Changes When Fast-Start Failover Is Enabled](#)

5.5.2.1 When Fast-Start Failover Is Enabled and the Observer Is Running

Once you enable fast-start failover and start the observer, the observer continuously monitors the environment to ensure the primary database is available. This section lists the steps the observer takes to determine if fast-start failover is needed and then performs one, if necessary.

Step 1 Monitor the environment to ensure the primary database is available.

The following list describes some of the conditions with the primary database, system, or site that could cause the observer to attempt a fast-start failover:

- The primary database loses its connections with both the observer and target standby database
- Instance failures

If a single-instance primary database (either RAC or non-RAC), or if all instances of an Oracle RAC primary database fail, the observer attempts a fast-start failover.

- Shutdown abort

If a single-instance primary database (either RAC or nonRAC), or if all instances of an Oracle RAC primary database are shut down with the `ABORT` option, the observer attempts a fast-start failover. Fast-start failover will not be attempted for the other types of database shutdown (`NORMAL`, `IMMEDIATE`, `TRANSACTIONAL`).
- User-configurable condition

If the observer determines that any of the user-configurable conditions has been detected, the observer attempts a fast-start failover.
- Application calls to `DBMS_DG.INITIATE_FS_FAILOVER`

If an application has called this function and it has received a status of `SUCCESS`, the observer attempts a fast-start failover.

Except for the user-configurable conditions and application initiated fast-start failover, the observer attempts to reconnect to the primary database within the time specified by the `FastStartFailoverThreshold` configuration property before attempting a fast-start failover. When a user-configurable condition has been detected or an application initiated fast-start failover has occurred, the observer initiates a fast-start failover immediately, without waiting for the amount of time specified by the `FastStartFailoverThreshold` property to expire.

Step 2 Reconnect within the time specified by `FastStartFailoverThreshold`.

If the observer detects an availability problem with the primary database, the observer typically attempts to reconnect to the primary database within the time specified by the `FastStartFailoverThreshold` configuration property. The `FastStartFailoverThreshold` time interval starts when the observer first detects there might be a failure with the primary database.

The time interval specified by the `FastStartFailoverThreshold` property is ignored if the observer detects that a user-configurable condition has occurred or if a fast-start failover has been requested by the `DBMS_DG.INITIATE_FS_FAILOVER` function.

If the primary database is an Oracle Real Application Clusters (RAC) database, the observer will attempt to connect to one of the remaining primary instances. Fast-start failover will not occur unless all instances comprising the RAC primary database are perceived to have failed. The observer uses the value specified by either the `DGConnectIdentifier` or `ObserverConnectIdentifier` configurable database properties to connect to the primary and fast-start failover target standby databases. The value specified for either of these properties should allow the observer to connect to any instance of an Oracle RAC database.

Step 3 Verify the target standby database is ready for failover.

If fast-start failover is initiated, the observer verifies the target standby database is ready to fail over to the primary database role.

Fast-start failover *cannot* occur if:

- Fast-start failover is no longer enabled
- The observer cannot connect to the target standby database

See Also: [Section 5.5.7.3, "What Happens if the Observer Fails?"](#) if the observer is not running

- The observer and the target standby database are inconsistent with regard to the current state of the broker configuration
- The observer is not running
- If the protection mode is maximum availability and the target standby database was not synchronized with the primary database at the time the primary database failed
- If the protection mode is maximum performance and the apply point of the target standby database lags the redo generation point of the primary database by more than the amount specified by the `FastStartFailoverLagLimit` configuration property at the time the primary database failed
- The target standby database has contact with the primary database
- The `FS_FAILOVER_STATUS` column in the `V$DATABASE` view for the target standby database displays a reason why fast-start failover cannot occur
- A manual failover is already in progress. See [Section 5.4](#) for complete information about manual failovers.
- The primary database was shut down without using the `ABORT` option

Step 4 Initiate a fast-start failover.

If the target standby database is ready for failover, the observer immediately invokes a fast-start failover. The observer directs the target standby database to fail over to the primary database role. If failover is not possible for some reason, the observer will continue checking whether the standby database is ready to fail over. But it will also continue trying to reconnect to the primary database indefinitely. If it reconnects to the primary database before the standby agrees to fail over, the observer will stop attempting to initiate a fast-start failover.

Step 5 Reinstate the former primary database as a new standby database.

After the fast-start failover completes successfully, the observer will attempt to reinstate the former primary database as a new standby database when a connection to the former primary database is reestablished, and the `FastStartFailoverAutoReinstate` configuration property is set to `TRUE`. If the `FastStartFailoverPmyShutdown` configuration property is set to `TRUE`, the former primary database will have been automatically shut down and must be manually restarted before the observer can attempt to reinstate it.

Note that these properties only affect whether primary shutdown and automatic reinstatement are performed if a fast-start failover occurs because the primary crashed or was isolated from the observer and target standby database.

See Also: [Section 5.5.8](#) for more information about reinstatement

5.5.2.2 Restrictions When Fast-Start Failover is Enabled

When fast-start failover is enabled, you cannot:

- Change:
 - The configuration protection mode
 - The `LogXptMode` configurable database property on the primary or target standby databases
 - The `FastStartFailoverTarget` configuration property on the primary or target standby databases

- Disable or delete:
 - The broker configuration
 - The standby database that is the target of fast-start failover
- Perform a manual failover:
 - Unless the conditions listed in [Section 5.5.2.4](#) have been met
 - To a standby database that is not configured as the fast-start failover target

To determine if the configuration is ready for fast-start failover to occur, issue the `DGMGRL SHOW DATABASE <target-standby-database> StatusReport` command, or query the `V$DATABASE` view on either the primary or target standby databases. The column value for `V$DATABASE.FS_FAILOVER_STATUS` will be `SYNCHRONIZED` in a configuration operating in maximum availability mode, and it will be `TARGET UNDER LAG LIMIT` in a configuration operating in maximum performance mode when ready to fast-start failover. The `FS_FAILOVER_OBSERVER_PRESENT` column displays `YES` for the target standby database.

- Perform a switchover to a standby database that is not configured as the fast-start failover target
- Perform a switchover to the target standby database in a configuration operating in maximum availability mode, unless the standby database is synchronized with the primary database
- Perform a switchover to the target standby database in a configuration operating in maximum performance mode, unless the standby database is within the lag limit of the primary database
- Attempt to open the primary database, or the following error may be returned:

```
ORA-16649: possible failover to another database prevents this database being opened
```

This error may return if the fast-start failover validity check fails or does not complete in under two minutes.

5.5.2.3 Shutting Down the Primary Database When Fast-Start Failover Is Enabled

Fast-start failover will not be triggered if the primary or standby database is shut down normally (using `SHUTDOWN NORMAL`, `SHUTDOWN IMMEDIATE`, or `SHUTDOWN TRANSACTIONAL`). A normal shutdown will prevent fast-start failover until the primary database and standby database are connected and communicating again.

5.5.2.4 Performing Manual Role Changes When Fast-Start Failover Is Enabled

If fast-start failover is enabled you can still perform a switchover or a manual failover as long as the following conditions are met:

- The role change is directed to the same standby database that was specified with the `FastStartFailoverTarget` configuration property
- The target standby database is synchronized with the primary database if it is a configuration operating in maximum availability mode, or the target standby database is within the lag limit if it is a configuration operating in maximum performance mode
- For manual failover, the observer is started and communicating with the target standby database

Note: You can disable fast-start failover if necessary, by using the `FORCE` option. See [Section 5.5.5, "Disabling Fast-Start Failover"](#).

See Also: [Section 5.3](#) and [Section 5.4](#) for more information about switchovers and manual failovers, respectively

5.5.3 Directing a Fast-Start Failover From an Application

You can use the `DBMS_DG` PL/SQL package to allow an application to direct a fast-start failover when it encounters specific conditions. When a serious condition uniquely known to the application is detected, it may call the `DBMS_DG.INITIATE_FS_FAILOVER` function, thus alerting the primary database that it wants a fast-start failover to occur immediately. The primary database will notify the observer of this and the observer will immediately initiate a fast-start failover, assuming the standby is ready for failover. Once the observer has initiated a fast-start failover, the primary database will shut down automatically. The observer will not attempt to reinstate the former primary database.

If the configuration is not failable, the `DBMS_DG.INITIATE_FS_FAILOVER` function will return an ORA error number (not signal an exception) informing the caller that a fast-start failover could not be performed.

Note: The application should use caution when calling this function because the observer will initiate failover to the target standby database.

See Also: *Oracle Database PL/SQL Packages and Types Reference* for more information about the `DBMS_DG` package

5.5.4 Viewing Fast-Start Failover Configuration Statistics and Status

To verify the observer is started and the configuration is ready for fast-start failover, you can issue the `DGMGRL SHOW DATABASE <target-standby-database> StatusReport` command or query the `V$DATABASE` view on the target standby database.

You can also query the `V$FS_FAILOVER_STATS` view to display statistics about fast-start failover occurring on the system.

The rest of this section provides examples of using `DGMGRL SHOW` commands to display fast-start failover information and includes sections describing the following views:

- [V\\$DATABASE View](#)
- [V\\$FS_FAILOVER_STATS View](#)

Example 1 SHOW FAST-START FAILOVER

The `DGMGRL SHOW FAST-START FAILOVER` command displays all the fast-start failover related information. For example:

```
DGMGRL> SHOW FAST_START FAILOVER;
```

```
Fast-Start Failover: ENABLED
Threshold:           60 seconds
Target:              DR_Sales
```

```

Observer:          observer.foo.com
Lag Limit:         30 seconds (not in use)
Shutdown Primary: TRUE
Auto-reinstate:   TRUE

```

Configurable Failover Conditions

```

Health Conditions:
  Corrupted Controlfile      YES
  Corrupted Dictionary       YES
  Inaccessible Logfile       NO
  Stuck Archiver             NO
  Datafile Offline          YES

```

```

Oracle Error Conditions:
  (none)

```

Example 2 SHOW CONFIGURATION VERBOSE

The following example shows the fast-start failover information for the DRSolution configuration:

```
DGMGRL> SHOW CONFIGURATION VERBOSE;
```

Configuration

```

Name:              DRSolution
Enabled:           YES
Protection Mode:   MaxAvailability
Databases:
  North_Sales - Primary database
  DR_Sales    - Physical standby database
               - Fast-Start Failover target

```

Fast-Start Failover: ENABLED

```

Threshold:         60 seconds
Target:            DR_Sales
Observer:          observer.foo.com
Lag Limit:         30 seconds (not in use)
Shutdown Primary: TRUE
Auto-reinstate:   TRUE

```

```

Current status for "DRSolution":
SUCCESS

```

5.5.4.1 V\$DATABASE View

You can query the V\$DATABASE view to verify the observer is started and the configuration is ready for fast-start failover. When querying the V\$DATABASE view, pay special attention to the FS_FAILOVER_STATUS column that can contain the values described in [Table 5-2](#). Also pay attention to the FS_FAILOVER_OBSERVER_PRESENT column which indicates whether the observer is running and actively pinging the database.

Table 5-2 FS_FAILOVER_STATUS Column of the V\$DATABASE View

Column Value	Description	Fast-Start Failover ...
BYSTANDER	Fast-start failover is enabled, but this standby database is not the target of the fast-start failover. The database cannot provide fast-start failover status information.	Is enabled
DISABLED	Fast-start failover is disabled.	Is not possible

Table 5–2 (Cont.) FS_FAILOVER_STATUS Column of the V\$DATABASE View

Column Value	Description	Fast-Start Failover ...
LOADING DICTIONARY	Displays only on a logical standby database that has not yet completed loading a copy of the primary database's data dictionary.	Is not possible
PRIMARY UNOBSERVED	Displays only on the target standby database when it is SYNCHRONIZED with or is TARGET UNDER LAG LIMIT of the primary database, has connectivity to the observer, but the primary database does not have a connection to the observer.	Is not possible
REINSTATE FAILED	Reinstatement of the failed primary database as a new standby database failed. See Section 10.1 for details about the broker's <code>drac*</code> log files.	Has completed
REINSTATE IN PROGRESS	Reinstatement of the failed primary database as a new standby database is in progress.	Has completed
REINSTATE REQUIRED	The failed primary database requires reinstatement as a new standby database to the new primary. The observer automatically starts the reinstatement process. REINSTATE REQUIRED is present only after fast-start failover has occurred and shows only on the new primary database.	Has completed
STALLED	<p>Displays on the primary database after loss of connectivity to the target standby database and the change to the UNSYNCHRONIZED state (maximum availability mode) or to the TARGET OVER LAG LIMIT state (maximum performance mode) cannot be confirmed by either the target standby database or the observer. Note that the value of the <code>FastStartFailoverPmyShutdown</code> configuration property must be FALSE for the primary to stall indefinitely under these conditions. With a value of TRUE for this property, the primary will shut down after being stalled for the number of seconds specified by the <code>FastStartFailoverThreshold</code> property.</p> <p>It shuts down or stalls because it is likely a failover has occurred.</p> <p>Note: this state also occurs on the primary during startup when fast-start failover is possible and neither the target standby database nor the observer are present to confirm it is okay to continue opening the database.</p>	Is possible
TARGET OVER LAG LIMIT	Displays if the standby database's redo applied point lags the primary database's redo generation point by more than the number of seconds specified by the <code>FastStartFailoverLagLimit</code> configuration property and the configuration is operating in maximum performance mode.	Is not possible

Table 5–2 (Cont.) FS_FAILOVER_STATUS Column of the V\$DATABASE View

Column Value	Description	Fast-Start Failover ...
TARGET UNDER LAG LIMIT	Displays if the standby database's redo applied point does not lag the primary database's redo generation point by more than the number of seconds specified by the <code>FastStartFailoverLagLimit</code> configuration property and the configuration is operating in maximum performance mode.	Is possible
SUSPENDED	Displays only on the target standby database when either the primary or target standby database was shut down in a controlled fashion (using the <code>NORMAL</code> , <code>IMMEDIATE</code> , or <code>TRANSACTIONAL</code> , options, but not the <code>ABORT</code> option). Fast-start failover is inhibited in this case. <code>SUSPENDED</code> is cleared when connectivity with the primary database is restored.	Is not possible
SYNCHRONIZED	Displays when the primary and target standby databases are synchronized and the configuration is operating in maximum availability mode.	Is possible if the target standby database displays <code>SYNCHRONIZED</code> and the <code>FS_FAILOVER_OBSERVER_PRESENT</code> column displays <code>YES</code>
UNSYNCHRONIZED	Displays when the target standby database does not have all of the primary database redo data and the configuration is operating in maximum availability mode.	Is not possible

5.5.4.2 V\$FS_FAILOVER_STATS View

Because fast-start failovers are fully automated and can occur at any time, it is useful to query this view on the primary database to display statistics about fast-start failovers that have occurred on the system, including:

- `LAST_FAILOVER_TIME` that shows the timestamp of last fast-start failover
- `LAST_FAILOVER_REASON` that shows the reason for the last fast-start failover

The following is an example of querying the `V$FS_FAILOVER_STATS` view:

```
SQL> SELECT LAST_FAILOVER_TIME, LAST_FAILOVER_REASON FROM V$FS_FAILOVER_STATS;

LAST_FAILOVER_TIME
-----
LAST_FAILOVER_REASON
-----
02/13/2007 16:53:10
Primary Disconnected
```

5.5.5 Disabling Fast-Start Failover

Disabling fast-start failover prevents the observer from initiating a failover to the target standby database. In this case, manual failover may still be possible. See [Section 5.4](#) for information about manual failover.

Note: Disabling fast-start failover does not stop the observer. To stop the observer, see [Section 5.5.7.4, "Stopping the Observer"](#).

To disable fast-start failover, use the Fast-Start Failover wizard in Enterprise Manager or the `DGMGRL DISABLE FAST_START FAILOVER [FORCE]` command. The `FORCE` option disables fast-start failover on the database to which you are connected even when errors occur. Whether or not you need the `FORCE` option depends mostly on if the primary and target standby database have network connectivity:

- If the primary and target standby database have network connectivity, and the database to which you are connected has network connectivity with the primary database, the `FORCE` option has no effect. Simply use `DISABLE FAST_START FAILOVER`. This method will disable fast-start failover on all databases in the broker configuration.

If errors occur during the disable operation, the broker returns an error message and stops the disable operation.

- If the primary and target standby databases do not have network connectivity or if the database to which you are connected does not have network connectivity with the primary database, consider using `DISABLE FAST_START FAILOVER` *with* the `FORCE` option.

The broker may not be able to disable fast-start failover on all databases in the broker configuration when you issue the `DISABLE FAST_START FAILOVER FORCE` command. As a result, there is no guarantee that the observer will not perform a fast-start failover to the target standby database if the observer determines that conditions warrant a failover. The following list indicates the extent to which fast-start failover is disabled in the broker configuration when the `DISABLE FAST_START FAILOVER FORCE` command is issued on the primary database, target standby database, and a standby database that is not the fast-start failover target.

If you issue this command on:

- The target standby database when it does not have connectivity with the primary database, fast-start failover is disabled only on the target standby database. In this case, the observer cannot perform a fast-start failover even if conditions warrant a failover. Disabling fast-start failover with the `FORCE` option when connected to the target standby database guarantees that fast-start failover will not occur.

When the primary database and the target standby database regain network connectivity, the broker will disable fast-start failover for the entire broker configuration.

- The primary database, the primary database attempts to disable fast-start failover on as many databases in the configuration with which it has a network connection. If the primary database does not have connectivity with the target standby database, fast-start failover remains enabled on the target standby database and the observer may still attempt a fast-start failover if conditions warrant a failover.

Caution: This action may result in two databases in the configuration simultaneously assuming the primary database role should fast-start failover occur. For this reason, you should first issue this command on the target standby database.

- Another standby database that does not have connectivity with the primary database, fast-start failover is disabled for this database. Because fast-start failover was not disabled on the target standby database, the observer may

still attempt a fast-start failover to the target standby database should conditions warrant a failover.

When the primary database and the (non-target) standby database regain network connectivity, the broker will propagate its current fast-start failover setting (ENABLED or DISABLED) to the non-target standby.

Caution: When you are experiencing network disconnections and you issue the `DISABLE FAST_START FAILOVER FORCE` command on the primary database or a standby database that does not have connectivity with the primary database, fast-start failover may not be disabled for all databases in the broker configuration. As a result the observer may still initiate fast-start failover to the target standby database, if conditions warrant a failover. This may result in two databases in the configuration simultaneously assuming the primary database role.

Conditions Requiring the FORCE Option

Disabling fast-start failover without the `FORCE` option can succeed only if the database on which the command is issued has a network connection with the primary database and if the primary database and target standby database have a network connection. This is the recommended method for disabling fast-start failover.

However, there may be situations in which you must disable fast-start failover when the primary database and the target standby database do not have a network connection, or the database on which you issued the disable fast-start failover command does not have a network connection to the primary database. In cases where there is a lost network connection, be aware that the observer may attempt a fast-start failover to the target standby database if conditions warrant a failover.

The `FORCE` option may be the preferred method for disabling fast-start failover when:

- A network outage isolates the primary database from the observer and the target standby database, while the databases are ready to failover.

In this case, the primary database stalls and prevents any further transactions from committing because a fast-start failover may have occurred while it was isolated. If you expect the network to be disconnected for a long time and you need to make the primary database available, first confirm that a fast-start failover has not occurred to the target standby database. Then, disable fast-start failover with the `FORCE` option on the primary database.

If possible, confirm that fast-start failover has not occurred to the target standby database prior to disabling fast-start failover with the `FORCE` option on the primary database.

Caution: This action may result in two databases in the configuration simultaneously assuming the primary database role. This can be avoided by first disabling fast-start failover with the `FORCE` option on the target standby.

- You want to conduct a manual failover to any standby database in the configuration (for example, because a failure occurred on the primary database at a time when the primary and target standby database were not ready to failover).

In this case fast-start failover cannot occur because the databases are not ready to failover. You cannot perform a manual failover to the target standby database for the same reason. To proceed, you must first disable fast-start failover using the `FORCE` option, and then perform a manual failover.

Caution: This action will result in loss of data and the possibility of two databases in the configuration simultaneously assuming the primary database role. This can be avoided by first disabling fast-start failover with the `FORCE` option on the target standby.

- A fast-start failover to the target standby database fails.
If the failover fails for any reason, it could leave the target standby database inoperable, regardless of whether the target standby database is ready to failover. If there is another standby database that is available for failover, you can perform a manual failover to that standby database after you first disable fast-start failover using the `FORCE` option on that standby database.
- You want to prevent fast-start failover from occurring because the primary database will resume service soon.
In this case, disable fast-start failover using the `FORCE` option on the target standby database. Once the primary database regains connectivity with the target standby database, fast-start failover will be disabled for all the databases in the configuration.

Disabling Fast-Start Failover Using Enterprise Manager

Click **Disable** in the Fast-Start Failover wizard. Then, click **Continue** to proceed to the next page. See the Enterprise Manager online Help system for more information.

Disabling Fast-Start Failover Using DGMGRL

Issue the `DISABLE FAST_START FAILOVER` command or the `DISABLE FAST_START FAILOVER FORCE` command. See the "[DISABLE FAST_START FAILOVER](#)" command in [Chapter 8](#) for more information.

5.5.6 Performance Considerations for Fast-Start Failover

Consider the following recommendations to obtain better performance when using fast-start failover:

- The failover time is dependent upon whether the target standby database (physical or logical standby database) has applied all of the redo data it has received from the primary database.
- Enabling fast-start failover in a configuration operating in maximum performance mode provides better overall performance on the primary database because redo data is sent asynchronously to the target standby database. Note that this does not guarantee no data will be lost.
- Fast-start failover is faster when you take steps to optimize recovery so that the application of redo data to the standby database is kept up to date with the primary database's rate of redo application. To optimize the log apply rate:
 - Do not configure the `DelayMins` configurable database property to delay applying archived redo log files to the standby database (see [Section 4.5](#) for more information).


- See *Oracle Data Guard Concepts and Administration* for information about tuning the log apply rate for a physical standby database.
- See the *Oracle Maximum Availability Architecture* white papers at:
<http://otn.oracle.com/deploy/availability/>
- When setting the `FastStartFailoverLagLimit` configuration property, consider these tradeoffs between performance and potential data-loss:
 - A low lag limit will minimize data loss but may impact the performance of the primary database.
 - A high lag limit may lead to more data loss but may lessen the performance impact of the primary database.

5.5.7 Managing the Observer

The observer is integrated in the DGMGRL client-side component of the broker and typically runs on a different computer from the primary or standby databases and from the computer where you manage the broker configuration. The observer continuously monitors the fast-start failover environment to ensure the primary database is available (described in [Section 5.5.2.1](#)). The observer's main purpose is to enhance high availability and *lights out* computing by reducing the human intervention required by the manual failover process that can add minutes or hours to downtime.

You can manage the observer through either the Data Guard Overview pages in Oracle Enterprise Manager or using DGMGRL commands. [Figure 5–2](#) shows the observer monitoring a fast-start failover configuration.

Figure 5–2 The Observer in the Fast-Start Failover Environment



The following sections provide information about managing the observer:

- [Installing and Starting the Observer](#)
- [Viewing Information About the Observer](#)
- [What Happens if the Observer Fails?](#)
- [Stopping the Observer](#)
- [Moving the Observer to Another Computer](#)

- [How the Observer Maintains Fast-Start Failover Configuration Information](#)

5.5.7.1 Installing and Starting the Observer

The observer should be installed and run on a computer system that is separate from the primary and standby systems. Installing and starting the observer is an integral part of using fast-start failover and is described in detail in these sections:

- [Section 2.1](#) describes installing Oracle Database Enterprise Edition or Oracle Personal Edition on the observer system.
- [Section 5.5.2](#) describes how to start the observer as a part of the step-by-step process to enable fast-start failover. Examples for starting the observer through Oracle Enterprise Manager and DGMGRL are included in [Section 6.4](#) and [Section 7.6](#), respectively.

There can be only one observer monitoring the broker configuration. If you attempt to start another one, the broker returns the following error message:

```
ORA-16647: could not start more than one observer
```

To start the observer, you must be able to login to DGMGRL as `SYS`. The observer is an OCI client that connects to the primary and target standby databases using the same `SYS` credentials you used when you connected to the Data Guard configuration with DGMGRL.

5.5.7.2 Viewing Information About the Observer

You can find information about the observer by querying the following columns in the `V$DATABASE` view:

- `FS_FAILOVER_OBSERVER_HOST` shows the name of the computer on which the observer is running
- `FS_FAILOVER_OBSERVER_PRESENT` shows whether or not the observer is connected to the local database

Table 5–3 FS_FAILOVER_OBSERVER_PRESENT Column of the V\$DATABASE View

Column Value ¹	Description
YES	Observer is currently connected to the local database
NO	Observer is not connected to the local database

¹ This value is consistent across instances in an Oracle Real Applications Clusters (RAC) environment. That is, if the observer is connected to any instance in the RAC, all instances will show a value of `YES`.

For example, to determine if fast-start failover can occur, the `FS_FAILOVER_STATUS` column displays either `SYNCHRONIZED` or `TARGET UNDER LAG LIMIT` and the `FS_FAILOVER_OBSERVER_PRESENT` column displays `YES` for the target standby database. For example:

Database	FS_FAILOVER_STATUS	Protection Mode	FS_FAILOVER_OBSERVER_PRESENT
Primary	SYNCHRONIZED	Maximum Availability	YES
Standby	SYNCHRONIZED	Maximum Availability	YES

Database	FS_FAILOVER_STATUS	Protection Mode	FS_FAILOVER_OBSERVER_PRESENT
Primary	TARGET UNDER LAG LIMIT	Maximum Performance	YES
Standby	TARGET UNDER LAG LIMIT	Maximum Performance	YES

In the following example, assume the network between the primary database and the observer has failed. In this case, the `FS_FAILOVER_STATUS` and `FS_FAILOVER_OBSERVER_PRESENT` columns will appear as shown in the following table and fast-start failover will not occur:

Database	FS_FAILOVER_STATUS	FS_FAILOVER_OBSERVER_PRESENT
Primary	SYNCHRONIZED	NO
Standby	PRIMARY UNOBSERVED	YES

5.5.7.3 What Happens if the Observer Fails?

If the primary and target standby databases stay connected but the connection to the observer is lost, then the broker reports that the configuration is not observed. The configuration and database status report that the observer is not running and return one of the following status messages:

```
ORA-16658: unobserved fast-start failover configuration
ORA-16820: fast-start failover observer is no longer observing this database
```

While the configuration is in the unobserved state, fast-start failover cannot happen. Therefore, the primary database can continue processing transactions, even if the target standby database fails. The configuration status returns the `SUCCESS` status after the observer reestablishes its connection to the primary database, which then notifies the target standby database.

See Also: [Section 5.5.4, "Viewing Fast-Start Failover Configuration Statistics and Status"](#)

5.5.7.4 Stopping the Observer

You may want to stop the observer when you no longer want to use fast-start failover (see [Section 5.5.5, "Disabling Fast-Start Failover"](#)) or if you want to move the observer to a different host machine (see [Section 5.5.7.5, "Moving the Observer to Another Computer"](#)).

To stop the observer when fast-start failover *is enabled*, the primary database and target standby database must be connected and communicating with each other. Stopping the observer does not disable the fast-start failover. However, fast-start failover cannot occur when the target standby database is in the unobserved state.

To stop the observer when fast-start failover *is not enabled*, the primary database must be running.

You can stop the observer while connected to any database in the broker configuration that has network connectivity to the primary database, as follows:

- Using Enterprise Manager

Choose the **Stop Observer** option on the first page of the fast-start failover wizard and click **Continue** at the bottom of the page. See the Enterprise Manager online help system for more information.

- Using DGMGRL

Issue the following command:

```
DGMGRL> STOP OBSERVER;
```

See the [STOP OBSERVER](#) command on page 8-58 for more information.

Note: The observer does not stop immediately when you issue `STOP OBSERVER` command. When the broker receives the `STOP OBSERVER` request, it informs the observer the next time the observer contacts the broker.

5.5.7.5 Moving the Observer to Another Computer

To move the observer to another computer:

1. Stop the observer from any computer system in the broker configuration, as described in [Section 5.5.7.4](#).
2. Start the observer on the new computer system, as described in Step 8 of [Section 5.5.2](#).

There is no need to disable fast-start failover when you move the observer.

5.5.7.6 How the Observer Maintains Fast-Start Failover Configuration Information

The observer persistently maintains information about the fast-start failover configuration in a binary file created in the working directory where you started the observer. By default, the observer creates this file in the current working directory when it is started and names the file `fsfo.dat`. This file contains connect identifiers to both the primary and the target standby databases.

Ensure this file cannot be read by unauthorized users.

Once the observer is started, you cannot change the file's name and location. However, you can change the name or the location of the file if you start the observer using the `DGMGRL START OBSERVER` command and include the `FILE` qualifier. See the [START OBSERVER](#) command on page 8-54 for more information.

Note: If the observer is stopped abnormally (for example, by typing `CTRL/C`), restart it and reference the existing `fsfo.dat` file with the `FILE` qualifier.

If you want to use one Oracle home to start multiple observers, with each observer monitoring a different fast-start failover configuration, use the `FILE` qualifier to specify a unique observer configuration file location for each configuration to be monitored. If you want to capture any logging generated by the observer, use the `LOGFILE` option and ensure that file name is unique as well. For example:

```
% dgmgrl -logfile $ORACLE_HOME/rdbms/log/config1.log
DGMGRL> CONNECT /@primary1;
DGMGRL> START OBSERVER FILE=$ORACLE_HOME/dbs/config1.dat;

% dgmgrl -logfile $ORACLE_HOME/rdbms/log/config2.log
```

```
DGMGRL> CONNECT /@primary2;
DGMGRL> START OBSERVER FILE=$ORACLE_HOME/dbs/config2.dat;
```

5.5.8 Reinstating the Former Primary Database in the Broker Configuration

If a fast-start failover was initiated because the primary database had crashed or lost connectivity with the observer and target standby database, the observer automatically attempts to *reinst*ate the former primary database as a standby database, if the `FastStartFailoverAutoReinst` configuration property is set to `TRUE`. **Reinstatement** restores high availability to the broker configuration so that, in the event of a failure of the new primary database, another fast-start failover can occur. The reinstated database acts as the fast-start failover target for the new primary database, making a subsequent fast-start failover possible. The new standby database is a viable target of a failover when it begins receiving redo data received from the new primary database.

To allow the observer to automatically reinstate the former primary database, the database must be started and mounted, but it cannot be opened. The broker reinstates the database as a standby database of the same type as the former standby database of the new primary database.

If the former primary database cannot be reinstated automatically, you can manually reinstate it using either the DGMGRL `REINSTATE` command or Enterprise Manager. Step-by-step instructions for manual reinstatement are described in [Section 5.4.3](#).

5.5.8.1 Requirements

Reinstatement is supported only after failover in a broker configuration. It also requires Flashback Database to be enabled on both the primary and target standby databases. [Section 5.5.1](#) provides complete information about all of the fast-start failover and reinstatement requirements.

5.5.8.2 Restrictions on Reinstatement

The broker cannot automatically reinstate the former primary database if:

- A fast-start failover occurred because a user-configurable condition was detected or was requested by an application by calling the `DBMS_DG.INITIATE_FS_FAILOVER` function.
- `FastStartFailoverAutoReinst` is set to `FALSE`
- Another failover or switchover occurred *after* the fast-start failover completed but *before* the former primary database restarted
- Fast-start failover was disabled
- The observer cannot connect to the former primary database
- The former primary database cannot connect to the new primary database
- The former primary database and the new primary database are not configured in the same fast-start failover environment
- The former primary database was disabled because of a manual failover when fast-start failover was disabled

Note: Standby databases that are disabled during switchover, manual failover, or fast-start failover will not be automatically reinstated.

If automatic reinstatement fails, the broker will log errors and the former primary database will remain in the mounted state. At this point, you can either:

- Disable fast-start failover (described in [Section 5.5.5](#)) and attempt to open the former primary database
- Manually reinstate the former primary database, as described in [Section 5.4.3](#)

5.5.8.3 How the Broker Handles a Failed Reinstatement

If a failure occurs once a reinstatement operation (automatic or manual) is underway, the broker logs the appropriate information in the broker configuration files and "broker log" files. The former primary database is disabled. Most in-progress failures cannot be restarted (for example, archived redo log file corruption on the primary database). You must manually reenable the database as a standby database.

See Also: [Section 5.4.3.2, "How to Re-create and Reenable a Disabled Database"](#)

5.5.9 Shutting Down Databases In a Fast-Start Failover Environment

Perform the following steps if you need to shut down the primary or standby databases:

1. Shut down the observer and wait for the `FS_FAILOVER_OBSERVER_PRESENT` column in the `V$DATABASE` fixed view to contain the value "NO" for both the primary and target standby databases. This ensures that a fast-start failover will not occur while you are shutting down the primary database.
2. Shut down the primary database and the target standby database using either `DGMGRL SHUTDOWN` command or the SQL*Plus `SHUTDOWN` statement.

When restarting the databases, you may restart them in any order. When both databases have been restarted, you may restart the observer.

Scenarios Using Oracle Enterprise Manager

This chapter describes the Data Guard Broker graphical user interface (GUI) provided in Oracle Enterprise Manager Grid Control 10.2. This is the latest currently available broker interface in Enterprise Manager. You can use it to create, manage, and monitor an Oracle Database 11g release 1 (11.1) Data Guard configuration.

This chapter contains the following scenarios:

- [Scenario 1: Accessing the Data Guard User Interface](#)
- [Scenario 2: Creating a Configuration or Adding an Additional Standby Database](#)
- [Scenario 3: Adding an Existing RAC Standby Database](#)
- [Scenario 4: Enabling Fast-Start Failover and the Observer](#)
- [Scenario 5: Performing Routine Maintenance](#)
- [Scenario 6: Performing a Switchover Operation](#)
- [Scenario 7: Invoking a Failover Manually](#)
- [Scenario 8: Monitoring a Data Guard Configuration](#)
- [Scenario 9: Using Metrics](#)
- [Scenario 10: Removing a Standby Database and Configuration](#)

6.1 Scenario 1: Accessing the Data Guard User Interface

Access the Data Guard Web pages through the Oracle Enterprise Manager Grid Control using the following steps:

Note: Oracle Enterprise Manager Grid Control provides access to the complete set of Data Guard 10.2 features. Limited monitoring-only Data Guard functionality is available in Enterprise Manager Database Control.

1. Click the **Targets** tab to go to the Targets page.
2. Click **Databases** to go to the Databases page.
3. On the Databases page, you see a listing of all discovered databases. In this scenario, the primary database, North_Sales, has already been discovered. Click the North_Sales database to go to the primary database home page.
4. Click **Administration**.

- In the High Availability section under Data Guard, click **Setup and Manage** and log in.

Note: If you log in as a user with SYSDBA privileges, you will have access to all Data Guard functionality, including all monitoring and management features. If you log in as a non-SYSDBA user, you will have access to monitoring functions only; features such as standby creation, switchover, and failover will not be available.

If the primary database is not already in a broker configuration, clicking **Setup and Manage** in Step 5 will go to the page shown in [Figure 6–1](#). This screenshot shows information presented on the All Targets tab, containing graphs for all targets discovered for the cluster. From the list of managed targets, you can quickly assess the availability of the targets and click any graph to drill down for more information.

Figure 6–1 Create a Broker Configuration

The screenshot shows the Oracle Enterprise Manager 10g Grid Control interface. The top navigation bar includes 'Home', 'Targets', 'Deployments', 'Alerts', 'Policies', 'Jobs', and 'Reports'. The 'All Targets' tab is selected. The breadcrumb trail shows 'Host: north.foo.com > Database Instance: West_Sales >'. The page is logged in as 'SYS'. There are two main sections: 'Information' and 'Confirmation'. The 'Information' section states that the database is not configured with Data Guard broker and provides a link to 'Add Standby Database'. The 'Confirmation' section states that the Data Guard configuration has been removed. Below these is a 'Data Guard' section with a 'Data Guard Broker' subsection, which describes the broker as a distributed management framework and lists its advantages: integrated support for Oracle Real Application Clusters, easy creation and management of physical and logical standby databases, automated switchover and failover operations, and built-in monitoring, alert, and control capabilities.

If the primary database is already part of a broker configuration, clicking **Setup and Manage** in Step 5 will go to the Data Guard Overview page as shown in [Figure 6–2](#).

Figure 6–2 Data Guard Overview Page

ORACLE Enterprise Manager 10g Grid Control

Setup Preferences Help Logout

Home Targets Deployments Alerts Policies Jobs Reports

Databases | Hosts | Web Applications | Services | Systems | Groups | All Targets

Host: north.foo.com > Database Instance: North_Sales > Logged in As SYS

Data Guard

Page Refreshed May 26, 2005 3:05:15 PM EDT View Data Real Time: Manual Refresh

Overview

- Data Guard Status: **Normal**
- Protection Mode: **Maximum Performance**
- Fast-Start Failover: **Disabled**

Primary Database

- Name: **North_Sales**
- Host: **north**
- Data Guard Status: **Normal**
- Current Log: **32**
- Properties: **Edit**

Standby Progress Summary

The transport lag is the time difference between the primary last update and the standby last received redo. The apply lag is the time difference between the primary last update and the standby last applied redo.

seconds	DR_Sales
4	Transport Lag
12	Apply Lag

Standby Databases

Edit Remove Switchover Failover Add Standby Database

Select	Name	Host	Data Guard Status	Role	Last Received Log	Last Applied Log	Estimated Failover Time
<input checked="" type="radio"/>	DR_Sales	north	Normal	Physical Standby	31	31	0 seconds

Performance

- Performance Overview
- Log File Details

Additional Administration

- Verify
- Remove Data Guard Configuration

On the Data Guard Overview page, you can:

- Edit the protection mode—click **Protection Mode** in the Data Guard Overview section to view the current protection mode setting and, if necessary, change the protection mode.
- Enable Fast-Start Failover—click **Disabled** to invoke the Fast-Start Failover wizard that will guide you through the process of enabling fast-start failover and the observer.
- View a summary of standby progress—this chart shows the amount of data that each standby database has not yet received and applied.
- Retrieve information about the primary database—click **Name**, **Host**, **Status**, **Current Log**, or **Properties (Edit)** to view pertinent information about the primary database.

If you click Status or **Edit**, you are taken to the Edit Properties page where you can view and change the current state or properties of the primary database.

- View or change information on the standby databases:
 - Add a standby database to the broker configuration—click **Add Standby Database** to add a physical or logical standby database.
 - Change the state or properties—click **Edit** to go to the Edit Properties page to view and change the current state or properties of the standby database.
 - Discontinue Data Guard broker control—click **Remove** to remove the selected standby database from Data Guard broker control.
 - Switch the role from standby to primary—click **Switchover** to switch the database roles from standby to primary.

- Transition the standby database to the role of primary database— click **Failover** when a catastrophic failure occurs on the primary database, and there is no possibility of recovering the primary database in a timely manner. The target standby database assumes the primary role, and the failed primary database is disabled by the broker. See [Section 5.4.3](#) for steps to reenable the failed primary database as a standby database to the new primary database.
- View performance information for the configuration and status of online redo log files for each standby database:
 - Click **Performance Overview** to view information about data archived and applied, a summary of standby progress, and a summary of log services.
 - Click **Log File Details** to view the status of online redo log files that were generated on the primary database but not received by the standby, and for online redo log files that were received but not applied to the standby database
- Perform additional administrative activities:
 - Click **Verify** to check the protection mode and properties, confirm that standby redo log files are present, and verify log switch.
 - Click **Remove Data Guard Configuration** to remove the broker configuration from Data Guard broker control.
- Search for information about any Enterprise Manager topic—Click **Help** to display the Welcome to Oracle Data Guard help topic. Once in the online Help system, you can use the Contents page or Search page to locate help topics of interest.

6.2 Scenario 2: Creating a Configuration or Adding an Additional Standby Database

Creating a broker configuration is the first thing you must do before you can manage and monitor the databases. Enterprise Manager provides the Add Standby Database wizard to create a broker configuration that includes a primary database and one or more standby databases. This scenarios shows how to use the Add Standby Database wizard later to add a logical standby database to a broker configuration that already has one physical standby database (DR_Sales). To start the Add Standby Database wizard, click **Add Standby Database** on the Data Guard Overview page.

After clicking **Add Standby Database**, you can select one of the following options:


- Create a new physical standby database (single-instance only)
- Create a new logical standby database (single-instance only)
- Manage an existing standby database with Data Guard broker
- Create a primary database backup only

You will need to connect to the primary database using SYSDBA credentials, if you are not yet connected.

See Also: *Oracle Data Guard Concepts and Administration* for the steps about how to create an Oracle RAC standby database

[Figure 6–3](#) show the introductory page of the create configuration process.

Figure 6–3 Add Standby Database Wizard - Introductory Page



The Add Standby Database wizard takes you through the following steps:

1. Determine the backup type.
2. Set up the backup options.
3. Select the Oracle home in which to create the standby database.
4. Set up the location for standby database files.
5. Provide standby database configuration parameters.
6. Review the information before clicking Finish.

The following steps assume a broker configuration already exist with one primary database and one physical standby database, and creates a new logical standby database. It shows how the wizard takes you through additional steps to select the Oracle home for the database and to copy datafiles to the standby database.


Step 1 Determine the backup type.

Enterprise Manager uses Oracle Recovery Manager (RMAN) to create a single-instance standby database from a new or existing backup of the primary database. You can select one of two backup operations to use for the standby database creation:

- Perform a live backup of the primary database
- Use an existing backup of the primary database

Figure 6–4 shows Step 1 of 6 of the configuration process if you are adding a logical standby database.


Figure 6–4 Add Standby Database Wizard - Backup Type (Logical Standby Database)



You can click **Cancel** to terminate the current process and begin again at the introductory page of the Add Standby Database wizard.

Figure 6–5 shows additional screen content that appears when you are adding a logical standby database.

Figure 6–5 Add Standby Database Wizard - Backup Type (Logical Standby Database)



Step 2 Set up the backup options.

A working directory is needed to store the primary database backup files. It can optionally be retained and used to create additional standby databases in the future. Specify a location on the primary host in which the working directory can be created.

Primary host credentials are required for this step. Enter the credentials of the owner of the primary database Oracle server installation. These credentials can be saved by checking the box marked Save as Preferred Credential.

You can click **Cancel** to terminate the current process and begin again at the introductory page of the Add Standby Database wizard.

Figure 6–6 shows Step 2 of 6 of the configuration process.

Figure 6–6 Add Standby Database Wizard - Backup Options

ORACLE Enterprise Manager 10g
Grid Control

Setup Preferences Help Logout

Home Targets Deployments Alerts Policies Jobs Reports

Databases | Hosts | Web Applications | Services | Systems | Groups | All Targets

Backup Type Backup Options Database Location File Locations Configuration Review

Add Standby Database: Backup Options

Primary Database **North_Sales** Cancel Back Step 2 of 6 Next

Primary Host **north.foo.com**

Backup Files Directory

Specify a location on the primary host where a directory can be created to store the primary database backup files.
 TIP The directory can optionally be retained for future standby database creations.

* Backup Files Directory Location

Subdirectory dg2_13 will be created at this location.

Compress the backup datafiles in the working directory
 Compression reduces backup file size and transfer time, but it may also slow down datafile backup and restoration.

Delete directory dg2_13 after standby database creation. Minimum disk space required is 810 MB.
 This option requires only enough disk space to contain a backup of the largest datafile.

Retain directory dg2_13 for a future standby database creation. Minimum disk space required is 1180 MB.
 This option requires enough disk space to contain a full database backup.

Primary Host Credentials

Enter the credentials of the user who owns the primary database Oracle server installation.

* Username

* Password

Save as Preferred Credential

Cancel Back Step 2 of 6 Next

Step 3 Select the Oracle home in which to create the standby database.

The standby database can be created in any Oracle home that was discovered by Oracle Enterprise Manager. Only Oracle homes on hosts that match the operating system of the primary host are shown. You must select a discovered Oracle home and provide a unique instance name for the standby database. Standby host credentials are required to continue.

Figure 6–7 shows Step 3 of 6 of the configuration process.

Figure 6–7 Add Standby Database Wizard - Database Location

ORACLE Enterprise Manager 10g
Grid Control

Setup Preferences Help Logout

Home Targets Deployments Alerts Policies Jobs Reports

Databases | Hosts | Web Applications | Services | Systems | Groups | All Targets

Backup Type Backup Options Database Location File Locations Configuration Review

Add Standby Database: Database Location

Primary Database **North_Sales** Primary Host **north.foo.com** Step 3 of 6

Standby Database

* Instance Name
The instance name (also referred to as the SID) must be unique on the standby host.

Database Storage
Choose whether the database files will be put on a conventional file system or on raw devices.

Standby Host Credentials

Enter the credentials of the user who owns the Oracle installation in the Oracle Home selected below.

* Username
* Password

Standby Database Location

The standby database can be created in any Oracle Home that has been discovered by Enterprise Manager. Only Oracle Homes on hosts that match the operating system of the primary host are shown. Select the Oracle Home in which to create the standby database.

Search For Host

Select	Host	Oracle Home	Oracle Server Version	Operating System	Operating System Version
<input checked="" type="radio"/>	north	/user1/oracle	10.2.0.1.0	Red Hat Enterprise Linux AS release 3 (Taroon Update 4)	2.4.21

Step 3 of 6

Step 4 Set up the location for standby database files.

Part of the create broker configuration process involves making the datafiles for the primary database available to the standby host. You have the option of customizing the location for the standby database files. Standby host credentials are required to continue. The following list describes your options:

- Specify the backup file access method

Choose the method by which you want to make the primary database backup files accessible to the standby host. The two options are:

 - Transfer files from the primary host working directory to a standby host working directory
 - Directly access the primary host working directory location from the standby host using a network path name
- Specify the standby database file location

Choose the locations for the standby database files. You have two options:

 - Convert to Oracle OFA (Optimal Flexible Architecture)
 - Keep file names and locations the same as the primary database
- Specify the network configuration file location

Data Guard will add configuration information for the standby database to the network configuration files (listener.ora and tnsnames.ora) in the specified directory on the standby host.

You can click **Cancel** to terminate the current process and begin again at the introductory page of the Add Standby Database wizard.

Figure 6–8 shows Step 4 of the configuration process.

Figure 6–8 Add Standby Database Wizard - File Locations

ORACLE Enterprise Manager 10g
Grid Control

Setup Preferences Help Logout

Home Targets Deployments Alerts Policies Jobs Reports

Databases | Hosts | Web Applications | Services | Systems | Groups | All Targets

Backup Type Backup Options Database Location **File Locations** Configuration Review

Add Standby Database: File Locations

Primary Database **North_Sales** Step 4 of 6

Primary Host **north.foo.com**

Standby Host **north.foo.com**

Standby Database File Locations

Since the primary and standby databases are on the same host, the standby database files will be placed into an Oracle Optimal Flexible Architecture (OFA) directory structure. Click 'Customize' to modify individual file names.

Total Disk Space Required **1180 MB**

Network Configuration File Location

Data Guard will add configuration information for the standby database to the network configuration files (listener.ora and tnsnames.ora) in the specified directory on the standby host.

* Configuration File Location Step 4 of 6

Step 5 Provide standby database configuration parameters.

Standby database configuration parameters must be set. These parameters include the database name, database unique name, target name, and standby archive location. The standby archive location can be a regular directory or a flash recovery area. The default values are based on corresponding primary database settings.

You can click **Cancel** to terminate the current process and begin again at the introductory page of the Add Standby Database wizard.

Figure 6–9 shows Step 5 of 6 of the configuration process.

Figure 6–9 Add Standby Database Wizard - Configuration

ORACLE Enterprise Manager 10g
Grid Control

Setup Preferences Help Logout

Home Targets Deployments Alerts Policies Jobs Reports

Databases | Hosts | Web Applications | Services | Systems | Groups | All Targets

Backup Type Backup Options Database Location File Locations **Configuration** Review

Add Standby Database: Configuration

Primary Database **North_Sales** Step 5 of 6

Primary Host **north.foo.com**

Standby Host **north.foo.com**

The following standby database parameters must be set. The default values are based on corresponding primary database settings.

* Database Name
This name will be used for the standby database db_name parameter.

* Database Unique Name
This name will be used for the standby database DB_UNIQUE_NAME parameter. It must be unique within the Data Guard configuration.

* Target Name
This name will be used by Enterprise Manager for the new standby database and will appear in the database targets list. Oracle recommends that this name be the same as the Database Unique Name. The standby database target will be configured with SYSDBA monitoring credentials. If you do not want Enterprise Manager to use SYSDBA credentials for monitoring, change the credentials using the Configure Database wizard. See the help for more information.

* Standby Archive Location Step 5 of 6
Archived redo log files received from the primary database will be put in this location, and will be automatically deleted after they are no longer needed.


Step 6 Review the information before clicking Finish.

The Add Standby Database wizard allows one last review of the data you input for the configuration and standby database. Click **Finish** when you are certain all of the information is correct.

You can click **Cancel** to terminate the current process and begin again at the introductory page of the Add Standby Database wizard.

Figure 6–10 shows Step 6 of 6 of the configuration process.


Figure 6–10 Add Standby Database Wizard - Review



By clicking Standby Database Storage, you can see additional information about all the standby database file locations.

Once you click Finish, the standby database creation process runs as an Oracle Enterprise Manager job. You can cancel the standby creation at any point before the job submission. Figure 6–11 shows the standby database creation process.


Figure 6–11 Add Standby Database Wizard - Processing



After the job is submitted, you will be returned to the Data Guard Overview page. In the Status column of the Standby Databases table, you will see *Creation in progress* listed. If you click that link, you can monitor the progress of the standby database creation. Figure 6–12 shows the Data Guard Overview page with this link.

To add additional standby databases after the initial creation of the configuration, click **Add Standby Database** to run the Add Standby Database wizard again.

Figure 6–12 Data Guard Overview Page - Creation in Progress




6.3 Scenario 3: Adding an Existing RAC Standby Database

Although the Add Standby Database wizard will not create an Oracle RAC standby database, you can add an existing RAC standby database into a Data Guard configuration. Click **Add Standby Database** to run the Add Standby Database wizard and select **Add an existing standby database**.

Figure 6–13 shows the Add Standby Database introductory page.

Figure 6–13 Adding an Existing RAC Standby Database to the Data Guard Configuration



The Add Standby Database wizard takes you through the following steps:

1. [Select an existing standby database.](#)
2. [Set the standby archive location setting.](#)
3. [Review the configuration settings.](#)

Step 1 Select an existing standby database.

In this step, select the RAC standby database you want to add to the configuration. All discovered databases in your environment (both RAC and non-RAC databases) will be shown in the list. In the example shown in Figure 6–14 (Step 1 of 3), one of the databases in the list (RAC10g) is an Oracle RAC standby database.

You can click Cancel at any time to terminate the current process and begin again at the introductory page of the Add Standby Database wizard.

If you wish to continue, click **Next**.

Figure 6–14 Select an Existing Standby Database

ORACLE Enterprise Manager 10g
Grid Control

Setup Preferences Help Logout

Home Targets Deployments Alerts Policies Jobs Reports

Databases | Hosts | Web Applications | Services | Systems | Groups | All Targets

Select Existing Standby Database Standby Configuration Review

Add Standby Database: Select Existing Standby Database

Cancel Step 1 of 3 Next

Select an existing standby database to add to the configuration. The database you choose must have been created from the primary database and must be configured to function as a standby database.

Only databases that match the operating system (SunOS) of the primary database are listed in the table.

Select Database	Host/Cluster
<input type="radio"/> DR1	drlab3
<input checked="" type="radio"/> RAC10g	drcluster

ORACLE Enterprise Manager 10g
Grid Control

Setup Preferences Help Logout

Home Targets Deployments Alerts Policies Jobs Reports

Databases | Hosts | Web Applications | Services | Systems | Groups | All Targets

Host: north.foo.com > Database Instance: West Sales > Data Guard > Logged in As SYS

Cancel Step 1 of 3 Next

Step 2 Set the standby archive location setting.

You can optionally change the Standby Archive Location setting of the existing standby cluster database, as shown in Figure 6–15 (Step 2 of 3).

If you wish to continue, click **Next**.

Figure 6–15 Add Standby Database: Standby Configuration

ORACLE Enterprise Manager 10g
Grid Control

Setup Preferences Help Logout

Home Targets Deployments Alerts Policies Jobs Reports

Databases | Hosts | Web Applications | Services | Systems | Groups | All Targets

Select Existing Standby Database Standby Configuration Review

Add Standby Database: Standby Configuration

Cancel Back Step 2 of 3 Next

Optionally change the following standby database parameters.

* Standby Archive Location
Location on the standby host for archived redo logs.

Cancel Back Step 2 of 3 Next


Step 3 Review the configuration settings.

Review the data for the configuration and standby database, as shown in Figure 6–16 (Step 3 of 3).

You can click **Cancel** to terminate the current process and begin again at the introductory page of the Add Standby Database wizard.

If you wish to complete the operation, click **Finish**.

Figure 6–16 Add Standby Database: Review



6.4 Scenario 4: Enabling Fast-Start Failover and the Observer

You can enable fast-start failover from any site, including the observer site, while connected to any database in the broker configuration. Enabling fast-start failover does not trigger a failover. Instead, it allows the observer to begin observing the primary and standby databases and initiate a fast-start failover should conditions warrant a failover.

This section describes the steps to enable fast-start failover and the observer:

1. [Invoke the Fast-Start Failover wizard.](#)
2. [Configure the target database and fast-start failover properties.](#)
3. [Enable Flashback Database.](#)
4. [Confirm that you want to enable fast-start failover.](#)

Step 1 Invoke the Fast-Start Failover wizard.

On the Data Guard Overview Page next to the "Fast-Start Failover" status field, click **Disabled** to invoke the Fast-Start Failover wizard.

Step 2 Configure the target database and fast-start failover properties.

On the Fast-Start Failover Configure Page:

- Select the standby database that you choose to be the target of fast-start failover and set fast-start failover properties. The example shown in [Figure 6–17](#) chooses DR_Sales, a physical standby database, to be the target standby database.

See Also: [Section 5.2](#) for helpful advice on determining which standby database will make the best target for a failover

Figure 6–17 Fast-Start Failover Wizard: Configure

ORACLE Enterprise Manager 10g
Grid Control

Setup Preferences Help Logout

Home Targets Deployments Alerts Policies Jobs Reports

Databases Hosts Web Applications Services Systems Groups All Targets

Host: north.foo.com > Database Instance: West_Sales > Data Guard > Logged in As SYS

Fast-Start Failover: Configure Cancel Continue

TIP The configuration will be automatically upgraded to Maximum Availability mode and the primary database will be restarted.

Target Database Selection
Select a standby database to be the fast-start failover target. The log transport mode for the selected database will be set to SYNC (if not currently set to SYNC).

Select Name	Role	Log Transport Mode
<input checked="" type="radio"/> DR_Sales	Physical Standby	ASYN
<input type="radio"/> West_Sales	Logical Standby	ASYN

Properties
Fast-start failover requires a Data Guard observer process. For highest availability, Oracle recommends that the observer be on a separate host from the primary and standby databases.

TIP Fast-start failover can be enabled without starting the observer, but cannot actually take place until the observer is running.

Observer Location **Not Set** Set Observer
There is currently no observer for this configuration, nor has one been specified.

Fast-Start Failover Threshold seconds
Amount of time the primary database must be out of contact with the observer and the standby database before a fast-start failover is initiated.

Cancel Continue

- Click **Set Observer** to specify the system on which the observer will run and the Oracle home:
 - If an observer is not currently defined, the Observer Host and Home fields are blank. You can directly edit the Observer Host and Home fields (in which case the specified host must already be discovered by Enterprise Manager), or you can choose from the list of discovered hosts and their Oracle Homes provided by Enterprise Manager. If you leave the Observer Host and Home fields blank, you may still configure fast-start failover, but you must then manually start an observer for fast-start failover to be ready for fast-start failover.
 - If an observer host and home is already known to Enterprise Manager, the Observer Host field displays those values when the Set Observer page is displayed. You can change the observer location, in which case the current observer will be stopped and Enterprise Manager will run a remote operation to start the new observer on the specified host.

Figure 6–18 shows the Set Observer page.

Figure 6–18 Fast-Start Failover Wizard: Set Observer

ORACLE Enterprise Manager 10g
Grid Control

Setup Preferences Help Logout

Home Targets Deployments Alerts Policies Jobs Reports

Databases Hosts Web Applications Services Systems Groups All Targets

Logged in As SYS

Fast-Start Failover: Set Observer Cancel OK

There is currently no observer for this configuration. Select the discovered host and Oracle Home where Enterprise Manager will start the observer.

TIP Fast-start failover can be enabled without starting the observer, but cannot actually take place until the observer is running.

Observer Host

Observer Oracle Home

Cancel OK

Note: When running the observer through Enterprise Manager Grid Control, output from the observer is written to the following log file:

ORACLE_HOME\rdbms\log\dgmgrl<pid>.log

In the example, ORACLE_HOME is the home you specified in Grid Control for the observer, and <pid> is the process ID for DGMGRL.

- Set the **FastStartFailoverThreshold** configuration property to specify the number of seconds you want the observer and target standby database to wait (after detecting the primary database is unavailable) before initiating a failover


See Also: [Section 9.2.15](#) for more information about the FastStartFailoverThreshold configuration property

- Click **Continue**.

Step 3 Enable Flashback Database.


The next page of the Fast-Start Failover wizard enables flashback logging on the primary and standby databases. If either the primary database or the target standby database does not have flashback logging enabled, the page shown in [Figure 6–19](#) will display. On this page you can specify the flash recovery area location, flash recovery area size, and flashback retention time for each database for which flashback logging must be activated.

Figure 6–19 Fast-Start Failover Wizard: Enable Flashback Logging



Step 4 Confirm that you want to enable fast-start failover.


Enterprise Manager displays the Confirmation page shown in [Figure 6–20](#) to verify that you want to start fast-start failover.

Figure 6–20 Fast-Start Failover Wizard: Confirmation

If you click **Yes** to continue with an enable operation, the Enterprise Manager processing page shown in [Figure 6–21](#) displays. The processing page provides a progress bar and a list of the steps that are being undertaken during the enable operation. The fast-start failover wizard performs the following steps:

1. Creates standby redo log files on the primary and standby databases
2. Upgrades the protection mode to Maximum Availability, if required
3. Restarts the primary and standby databases, if required
4. Enables fast-start failover
5. Starts the observer process

Some steps may not be performed. For example, because fast-start failover requires the Data Guard configuration be operating in either maximum availability mode or maximum performance mode, this scenario includes the Changing Protection Mode step to upgrade the configuration's protection mode from maximum performance to maximum availability.

Figure 6–21 Fast-Start Failover Wizard: Progress

When the operation completes, Enterprise Manager displays the Data Guard Overview page that shows an Enabled status along with the Observer Host.

[Figure 6–22](#) shows how, in this scenario, fast-start failover is "Enabled to DR_Sales." If you were to click this status field, the Fast-Start Failover wizard would be invoked again to lead you through the steps to disable fast-start failover.

Figure 6–22 Fast-Start Failover Is Successfully Enabled

ORACLE Enterprise Manager 10g Grid Control [Setup](#) [Preferences](#) [Help](#) [Logout](#)

[Home](#) **[Targets](#)** [Deployments](#) [Alerts](#) [Policies](#) [Jobs](#) [Reports](#)

Databases | Hosts | Web Applications | Services | Systems | Groups | **All Targets**

Host: north.foo.com > Database Instance: North_Sales > Logged in As SYS

Information
The fast-start failover mode has been successfully changed.

Data Guard
Page Refreshed June 8, 2005 2:44:45 PM EDT View Data Real Time: Manual Refresh

Overview

- Data Guard Status ✔ **Normal**
- Protection Mode [Maximum Availability](#)
- Fast-Start Failover [Enabled to DR_Sales](#)
- Observer Location **north**

Primary Database

- Name [North_Sales](#)
- Host [north](#)
- Data Guard Status ✔ **Normal**
- Current Log [174](#)
- Properties [Edit](#)

Standby Progress Summary

The transport lag is the time difference between the primary last update and the standby last received redo. The apply lag is the time difference between the primary last update and the standby last applied redo.

Database	Transport Lag (seconds)	Apply Lag (seconds)
DR_Sales	0	0
West_Sales	3	35

Standby Databases [Add Standby Database](#)

Select	Name	Host	Data Guard Status	Role	Last Received Log	Last Applied Log	Estimated Failover Time
<input checked="" type="radio"/>	DR_Sales	north	✔ Normal	Physical Standby	173	173	0 seconds
<input type="radio"/>	West_Sales	north	✔ Normal	Logical Standby	173	173	0 seconds

Performance

[Performance Overview](#)
[Log File Details](#)

Additional Administration

[Verify](#)
[Remove Data Guard Configuration](#)

Once fast-start failover and the observer are enabled, the observer continuously monitors the environment to ensure the primary database is available. If the observer detects a problem, the observer attempts to reconnect to the primary database within the time specified by the `FastStartFailoverThreshold` property. If the problem is not remedied in that time and the target standby database is ready for failover, the observer immediately invokes a fast-start failover. Because a fast-start failover is automatic and fast, you may not be aware it has happened until you notice that reinstatement is needed or is already occurring.

Figure 6–23 shows an example of the warning message that shows when a reinstatement is needed.

Figure 6–23 Reinstating the Former Primary Database After a Fast-Start Failover

Overview

- Data Guard Status: **Warning**
- Protection Mode: [Maximum Availability \(Unsynchronized\)](#)
- Fast-Start Failover: [Enabled to DR_Sales \(Not Ready\)](#)
- Observer Location: **north**

Primary Database

- Name: [North_Sales](#)
- Host: [north](#)
- Data Guard Status: **Warning** [ORA-16817: unsynchronized Fast-Start Failover configuration](#)
- Current Log: [187](#)
- Properties: [Edit](#)

Standby Progress Summary

The transport lag is the time difference between the primary last update and the standby last received redo. The apply lag is the time difference between the primary last update and the standby last applied redo.

0.0 0.5 1.0

No data is currently available.

Standby Databases

[Add Standby Database](#)

Select	Name	Host	Data Guard Status	Role	Last Received Log	Last Applied Log	Estimated Failover Time
<input checked="" type="radio"/>	DR_Sales	north	Warning Database must be reinstated	Physical Standby	n/a	n/a	n/a
<input type="radio"/>	West_Sales	north	Normal	Logical Standby	186	186	n/a

Performance

- [Performance Overview](#)
- [Log File Details](#)

Additional Administration

- [Verify](#)
- [Remove Data Guard Configuration](#)

You can also obtain information about your fast-start failover environment by looking at the metrics in the Alert Log Errors page. This page enables you to view a list of log entries containing errors. To see database alerts, navigate to the Database Home page and choose the **Alert Log** link from the Diagnostic Summary section. The errors are listed in a table that includes a severity level and time stamp for each row. The Category column provides a description of the category type of the error. You can filter the list using View Data to display a day's, week's, or month's worth of data.

Figure 6–24 shows an example of the Alert Log Errors page for the North_Sales database after a fast-start failover occurred.

Figure 6–24 Alert Log Errors Page Showing That Fast-Start Failover Occurred

Database Instance: North_Sales

Home Performance Administration Maintenance

Latest Data Collected From Target Jun 8, 2005 3:20:27 PM EDT Refresh View Data Automatically (60 sec)

General

↑ Shutdown Black Out

Status Up
 Up Since Jun 8, 2005 3:02:31 PM EDT
 Instance Name dg2
 Version 10.2.0.1.0
 Host north.foo.com
 Listener listener

[View All Properties](#)

Host CPU

Load 0.25 Paging 0.00

Active Sessions

Maximum CPU 2

Diagnostic Summary

ADDM Findings 0
 Alert Log Jun 8, 2005 3:17:50 PM

Space Summary

Database Size (GB) 1,086
 Problem Tablespaces 0
 Segment Advisor 0
 Recommendations 0
 Space Violations 6
 Dump Area Used (%) 63

High Availability

Data Guard Physical Standby
 Primary Database DR_Sales
 Instance Recovery Time (sec) 31
 Last Backup n/a
 Usable Flash Recovery Area (%) 83.04
 Flashback Time Jun 6, 2005 11:02:59 PM

Alerts

Category All Go Critical 1 Warning 4

Severity	Category	Name	Message	Alert Triggered
✘	Data Guard Fast-Start Failover	Fast-Start Failover Occurred	A fast-start failover occurred at 2005-06-08 15:17:57.	Jun 8, 2005 3:18:37 PM
⚠	Response	State	The database status is MOUNTED.	Jun 8, 2005 3:04:40 PM
⚠	Waits by Wait Class	Database Time Spent Waiting (%)	Metrics "Database Time Spent Waiting (%)" is at 61.93074 for event class "Other"	Jun 8, 2005 2:41:15 PM
⚠	User Audit	Audited User	User SYS logged on from stadj30.us.oracle.com.	Jun 6, 2005 7:41:58 AM

See Also: [Section 5.5](#) for complete information about fast-start failovers, the observer, and reinstating the failed primary database

6.5 Scenario 5: Performing Routine Maintenance

Enterprise Manager simplifies some of the routine maintenance tasks you must perform in the configuration. The following examples, provided in the following sections, show:

- [Changing the State of a Database](#)
- [Changing the Properties of a Database](#)
- [Changing the Database Protection Mode](#)

6.5.1 Changing the State of a Database

This section describes how to set the standby database to Log Apply Off.

To change the state of the standby database to Log Apply Off, follow these steps:

1. From the Data Guard Overview page, select the standby database you want to change to the Log Apply Off state.
2. Click **Edit** to go to the Edit Properties page.
3. Select **Log Apply Off**.
4. Click **Apply**.
5. When the process completes, a message indicating success is returned.

Figure 6–25 shows the Edit Properties page where you can change the state of a database.

Figure 6–25 Changing the State or Properties of a Database



When you change the state of the standby database to Log Apply Off, it stops Redo Apply (or SQL Apply for logical standby databases) from applying the redo data to the standby database. However, redo transport services on the primary database are unaffected; the standby database continues to receive redo data from the primary database.

After completing your maintenance tasks, you can follow the same sequence of steps to bring the database online again.

6.5.2 Changing the Properties of a Database

Enterprise Manager divides the database properties into primary, standby, and common properties.

To view or change properties:

1. Click either **Edit** from the Primary Database section or click **Edit** from the Standby Databases section of the Data Guard Overview page.
2. Click one of the following:
 - Standby Role Properties
 - Common Properties
3. Make the appropriate change and click **Apply**.
4. When the process completes, a message indicating success is returned.


Figure 6–26 shows properties specific to the standby database.

Figure 6–26 Standby Role Properties



By clicking **Show Advanced Properties**, you can view additional properties specific to the standby database, as shown in [Figure 6–27](#).

Figure 6–27 Standby Advanced Properties



[Figure 6–28](#) shows properties common to both the primary database and the standby database.

Figure 6–28 Common Properties

ORACLE Enterprise Manager 10g
Grid Control

Setup Preferences Help Logout

Home Targets Deployments Alerts Policies Jobs Reports

Databases | Hosts | Web Applications | Services | Systems | Groups | All Targets

Host: north.foo.com > Database Instance: DR_Sales > Data Guard > Logged in As SYS

Edit Standby Database Properties: North_Sales

Revert Apply

General Standby Role Properties **Common Properties**

TIP Common properties are not role specific and are always in effect. Any modified common properties will take effect immediately.

Log Archive Max Processes
Number of archiver processes to be used.

Log Archive Trace
Level of tracing output generated by Data Guard processes.

General Standby Role Properties **Common Properties**

Revert Apply

6.5.3 Changing the Database Protection Mode

You can change the broker configuration's overall protection mode with Enterprise Manager.

When the configuration was first created it was placed in the maximum performance mode by default. This section describes the process for upgrading to the maximum protection mode. The maximum protection mode guarantees that no data loss will occur if the primary database fails.

To set the maximum protection mode:

1. Click **Maximum Performance** under the Overview section on the Data Guard Overview page.
2. Select **Maximum Protection** and click **Continue**.

Figure 6–29 shows the Edit Protection Mode page.

Figure 6–29 Change Protection Mode Page

ORACLE Enterprise Manager 10g
Grid Control

Setup Preferences Help Logout

Home Targets Deployments Alerts Policies Jobs Reports

Databases | Hosts | Web Applications | Services | Systems | Groups | All Targets

Host: north.foo.com > Database Instance: DR_Sales > Data Guard > Logged in As SYS

Change Protection Mode: Select Mode

Cancel Continue

Data Guard provides multiple protection modes. Higher protection modes reduce data loss but may affect performance of the primary database. When changing to Maximum Protection or Maximum Availability, a SYSDBA connection is required to the primary database and all standby databases to determine if standby redo log files are needed.

TIP Upgrading the protection mode requires a restart of the primary database.

Maximum Protection
Provides the highest level of data protection. No data will be lost. Possible primary database downtime if connectivity to the standby database is lost. Requires the SYNC log transport mode to be set on at least one standby database.

Maximum Availability
Provides very high data protection. No primary database downtime if connectivity to the standby database is lost but data may diverge. Requires the SYNC log transport mode to be set on at least one standby database.

Maximum Performance
No performance impact on the primary database. Provides high data protection with the ASYNC log transport mode. Can also be used with the ARCH log transport mode.


Cancel Continue

3. Select one or more of the standby databases listed in Figure 6–30 that you want to support the maximum protection mode. The redo transport service (and

LogXptMode configurable database property) will automatically be set to SYNC for the primary database and the selected standby databases.


Data Guard broker automatically determines the correct number and size of standby redo log files needed for all databases in the configuration and adds those log files using the directory locations you specify. Click **Continue** to go on.

Figure 6–30 Change Protection Mode - Standby Databases and Online Redo Log Files



4. Confirm that you want to change the protection mode. Click **Yes** to continue or **No** to cancel. This scenario assumes you are accepting the change by clicking **Yes**. Then, the Edit Protection Mode Processing page is displayed, as shown in Figure 6–31.

Figure 6–31 Change Protection Mode - Process



5. Once the protection mode is successfully updated, the Data Guard Overview page is displayed as shown in Figure 6–32.

Figure 6–32 Protection Mode Successfully Changed

ORACLE Enterprise Manager 10g
Grid Control

Setup Preferences Help Logout

Home Targets Deployments Alerts Policies Jobs Reports

Databases | Hosts | Web Applications | Services | Systems | Groups | All Targets

Host: north.foo.com > Database Instance: DR_Sales > Logged in As SYS

Information
The protection mode has been successfully changed and the primary database has been restarted.

Data Guard
Page Refreshed May 27, 2005 5:36:38 PM EDT View Data Real Time: Manual Refresh

Overview

Data Guard Status	✓ Normal
Protection Mode	Maximum Protection
Fast-Start Failover	Disabled

Primary Database

Name	DR_Sales
Host	north
Data Guard Status	✓ Normal
Current Log	45
Properties	Edit

Standby Progress Summary
The transport lag is the time difference between the primary last update and the standby last received redo. The apply lag is the time difference between the primary last update and the standby last applied redo.

seconds

North_Sales

Legend: Transport Lag (blue), Apply Lag (green)

Standby Databases

Edit Remove Switchover Failover Add Standby Database

Select Name	Host	Data Guard Status	Role	Last Received Log	Last Applied Log	Estimated Failover Time
North_Sales	north	✓ Normal	Physical Standby	44	44	0 seconds

6.6 Scenario 6: Performing a Switchover Operation

There may be occasions when you might want to perform a switchover between the primary database and standby databases. This scenario steps you through the process of using the switchover operation to switch roles between the primary database and a standby database.

To execute a switchover, perform the following steps:

1. Select the standby database that you want to become the primary database.
2. Click **Switchover**.
3. Click **Yes** to continue with the switchover. Click **No** to cancel.

Figure 6–33 shows the Switchover Confirmation page.

Figure 6–33 Switchover Operation

ORACLE Enterprise Manager 10g
Grid Control

Setup Preferences Help Logout

Home Targets Deployments Alerts Policies Jobs Reports

Databases | Hosts | Web Applications | Services | Systems | Groups | All Targets

Logged in As SYS

Confirmation: Switchover to DR_Sales

A switchover will cause the primary and standby databases to switch roles. Since DR_Sales is a physical standby database, the primary and standby databases will be shut down and restarted. The switchover operation cannot be cancelled.

Any active sessions connected to the primary database will be closed automatically during the switchover operation.
[Browse Primary Database Sessions](#)

TIP Standby databases not involved in the switchover will continue to function normally after the switchover.

Are you sure you want to switchover to DR_Sales?

No Yes

The Switchover operation performs the following steps:

1. Ensures that the primary database and standby database are not currently in an error status condition and verifies that broker management of the primary database is enabled and running.
2. If the switchover target is a physical standby database, you can view any active user sessions connected to the primary using the Browse Primary Database Sessions link. These sessions will be closed automatically during the switchover.
3. Performs the switchover by first changing the primary database to the standby role, and then the standby database to the primary role, displaying a progress indicator as the switchover progresses.
4. If the switchover target is a physical standby database, both it and the primary database will be restarted.

Figure 6–34 shows the Processing page during the switchover.

Figure 6–34 Processing Page During Switchover




Figure 6–35 shows the Data Guard Overview page after a successful switchover.

Figure 6–35 New Primary Database After Switchover

ORACLE Enterprise Manager 10g
Grid Control

Setup Preferences Help Logout

Home Targets Deployments Alerts Policies Jobs Reports

Databases | Hosts | Web Applications | Services | Systems | Groups | All Targets

Host: north.foo.com > Database Instance: DR_Sales > Logged in As SYS

Information
Switchover completed successfully.

Data Guard
Page Refreshed May 29, 2005 1:34:47 PM EDT View Data Real Time: Manual Refresh

Overview

Data Guard Status	✓ Normal
Protection Mode	Maximum Protection
Fast-Start Failover	Disabled

Primary Database

Name	DR_Sales
Host	north
Data Guard Status	✓ Normal
Current Log	n/a
Properties	Edit

Standby Progress Summary

The transport lag is the time difference between the primary last update and the standby last received redo. The apply lag is the time difference between the primary last update and the standby last applied redo.

Standby Databases

Edit Remove Switchover Failover Add Standby Database

Select	Name	Host	Data Guard Status	Role	Last Received Log	Last Applied Log	Estimated Failover Time
<input checked="" type="radio"/>	North_Sales	north	✓ Normal	Physical Standby	n/a	n/a	0 seconds

Performance
Performance Overview
Log File Details


Additional Administration
Verify
Remove Data Guard Configuration

6.7 Scenario 7: Invoking a Failover Manually

This scenario steps you through the process of using the Failover operation to transition one of the physical standby databases, in this case DR_Sales, into the primary role. You should perform a failover only in the event of a software or system failure that results in the loss of the primary database. The failed primary database is disabled by the broker and must be reenabled, and the standby database assumes the primary database role. See Section 5.4.3 for steps to reenable the failed primary database as a standby database to the new primary database.

In Figure 6–36 the Data Guard Overview page shows the ORA-16625 error status that indicates problems accessing the primary database.


Figure 6–36 Data Guard Overview Page Showing ORA-16625 Error



To transition DR_Sales into the primary role, select DR_Sales in the Standby Databases table and click **Failover**.

Figure 6–37 shows the Failover Confirmation page.

Figure 6–37 Failover Confirmation Page



If you determine that a failure occurred on the primary database and there is no possibility of recovering the primary database in a timely manner, you can start the Failover operation. In configurations with both physical and logical standby databases, Oracle recommends using the physical standby database as the failover target because it will allow the logical standby database to continue to function as a logical standby to the new primary database. If the failover is made to the logical


standby, any physical standbys in the configuration will need to be re-created from a backup of the new primary database.

The Failover operation enables you to choose one of the following two types of failover operations:

- Complete—attempts to minimize data loss by applying all available redo on the standby database.
- Immediate—no additional data will be applied on the standby database; data may be lost. This is the fastest type of failover.

Figure 6–38 shows the progress of the failover operation.

Figure 6–38 Failover Progress Page



ORACLE Enterprise Manager 10g
Grid Control

Setup Preferences Help Logout

Home Targets Deployments Alerts Policies Jobs Reports

Databases | Hosts | Web Applications | Services | Systems | Groups | All Targets

Logged in As SYS

Processing: Failover

Failing over to DR_Sales

This process will take some time. The page will automatically forward to the overview page upon completion. Click on the alert log link to view progress details in a new browser window. View alert log: [North_Sales DR_Sales](#)

Performing failover.
 Restarting primary database.
 Waiting for failover to complete.

TIP This process cannot be cancelled. It will continue even if the browser window is closed.

During the failover, the selected standby database transitions into the primary role. If the failover target is a physical standby database, it is restarted. When completed, the Data Guard Overview page reflects the updated configuration, as shown in Figure 6–39.

Figure 6–39 Data Guard Overview Page After a Failover Operation Completes

ORACLE Enterprise Manager 10g Grid Control

Setup Preferences Help Logout

Home Targets Deployments Alerts Policies Jobs Reports

Databases | Hosts | Web Applications | Services | Systems | Groups | All Targets

Host: north.foo.com > Database Instance: DR_Sales > Logged in As SYS

Information
Failover completed successfully.

Data Guard
Page Refreshed May 29, 2005 6:40:11 PM EDT View Data Real Time: Manual Refresh

Overview
 Data Guard Status **Normal**
 Protection Mode [Maximum Performance](#)
 Fast-Start Failover [Disabled](#)

Primary Database
 Name [DR_Sales](#)
 Host [north](#)
 Data Guard Status **Normal**
 Current Log [n/a](#)
 Properties [Edit](#)

Standby Progress Summary
 The transport lag is the time difference between the primary last update and the standby last received redo.
 The apply lag is the time difference between the primary last update and the standby last applied redo.

1.0
0.5
0.0
No data is currently available.

Standby Databases [Add Standby Database](#)

Select	Name	Host	Data Guard Status	Role	Last Received Log	Last Applied Log	Estimated Failover Time
<input checked="" type="radio"/>	North_Sales	north	Database must be reinstated	Physical Standby	n/a	n/a	n/a

Performance [Performance Overview](#) [Log File Details](#)

Additional Administration
[Verify](#)
[Remove Data Guard Configuration](#)

In the figure, the Data Guard Status column indicates that the original primary database (North_Sales) is disabled and can no longer be managed through Enterprise Manager until it has been reenabled as a physical standby database.

See Also: [Section 5.4.3](#) for more information about post-failover steps to reenable databases

6.8 Scenario 8: Monitoring a Data Guard Configuration

Enterprise Manager provides ways to monitor the status of a configuration as well as the online redo log file activity of the primary and standby databases. At the most basic level, the Data Guard Overview page for the configuration not only displays information about the configuration, but it also includes summary information about its databases.

Note: You can access the monitoring functions of Data Guard even if you are logged in as a non-SYSDBA user. However, all management features, such as standby creation, switchover, and failover, require a SYSDBA connection.

For example, the summary information on the Data Guard Overview page shows the status for all of the databases in the configuration. If you want more information about why Redo Apply or SQL Apply are off for a specific standby database, select the Status link of the database in the Standby Databases table and view the property pages. Any Data Guard specific database properties that are incorrect, inconsistent, or known to be in conflict with other parameters will be flagged with a warning in the Edit Properties page for the database. A variety of icons indicating the status condition can appear next to the Status link. A green check mark appears if the primary database is


functioning normally; a yellow triangle containing an exclamation mark appears if there is a warning; and a red X appears if there is an error condition.

- To check the primary database status, select Status under the Primary Database section of the Data Guard Overview page.
- To check the status of a standby database listed in the Standby Databases table, select the link under the Status column.

For example, a yellow warning icon may display the message "A yellow warning indicates an inconsistent property has been detected. The value for this property is inconsistent between Data Guard and the database, Data Guard and the server parameter file, or Data Guard and both the database and server parameter file."

Figure 6–40 shows the Data Guard Overview page in the case where the configuration has returned an error because the observer is no longer observing the fast-start failover configuration.

Figure 6–40 Data Guard Overview Page Showing Observer Error



The following sections provide information on ways to monitor the status and health of a configuration:

- Section 6.8.1, "Verifying a Broker Configuration"
- Section 6.8.2, "Viewing Log File Details"
- Section 6.8.3, "Monitoring Configuration Performance"

6.8.1 Verifying a Broker Configuration

Another way to quickly check the overall health of a broker configuration is to run the Verify operation. The Verify operation performs a series of validation checks on the

broker configuration, including a health check of each database in the configuration. The checks include:

1. Shows the current data protection mode setting, including the current redo transport service settings for each database and whether or not the standby redo log files are configured properly. If standby redo log files are needed for any database, the Verify results will allow you to automatically configure them.
2. Validates each database for the current status.
3. Performs a log switch on the primary database and then verifies that the log file was applied on each standby database.
4. Shows the results of the Verify operation, including errors, if any. The Verify operation completes successfully if there are no errors and an online redo log file was successfully applied to at least one standby database.
5. Shows any databases or RAC instances that are not discovered. Undiscovered databases and instances could prevent a failover or switchover from completing successfully.
6. Detects inconsistencies between database properties and their corresponding values in the database itself. It also provides a mechanism for resolving these inconsistencies.

Note: You can click **Cancel** at any time to stop the Verify operation.

To verify the configuration, click **Verify** under the Additional Administration section of the Data Guard Overview page. See [Figure 6–41](#). The Verify command displays a progress indicator. When the Verify operation completes successfully, the broker configuration is healthy, guarding the data, and ready for a switchover or failover.

Figure 6–41 Verifying the Configuration

ORACLE Enterprise Manager 10g
Grid Control

Setup Preferences Help Logout

Home Targets Deployments Alerts Policies Jobs Reports

Databases | Hosts | Web Applications | Services | Systems | Groups | All Targets

Logged in As SYS

Processing: Verify

Verify checks various standby database settings.

The results of the verify will be shown upon completion. You can click Cancel to stop processing at any time.


- ✓ Initializing
- ✓ Switching current log
- ✓ Performing health check
- ✓ Updating Data Guard information
- ➔ Verifying protection mode
- Checking standby redo log files
- Checking Data Guard status
- Checking properties
- Verifying log switch
- Saving detailed results

Cancel

When the Verify operation completes successfully, the broker configuration is healthy, guarding the data and ready for a switchover or failover operation. The Verify processing page can be canceled at any time.

Figure 6–42 shows the results after the successful completion of the Verify operation.

Figure 6–42 Results of the Verify Command



6.8.2 Viewing Log File Details

For each standby database in the configuration, there is a table that shows the status of archived redo log files that were generated on the primary database but not received by the standby database, and for archived redo log files that were received but not applied to the standby database. This Log File Details page is useful to determine log file information when redo transport or log apply services are stopped. Under normal operations, each standby table is empty.

For example, if redo transport services go offline unexpectedly, the primary database continues to generate archived redo log files, but redo transport services will not send the archived redo log files to the standby databases. You can view the Log File Details page to find out which log files have not yet been received for each standby database.

On the Log File Details page, there is a *Primary Current Log* entry that indicates the log sequence number of the current log file on the primary.

For each standby database, redo transport and log apply information is displayed to help diagnose any log file buildup. Table 6–1 describes the columns for the standby table:

Table 6–1 Log File Details Page

Column Title	Description
Log	The log sequence number.
Status	The status of the log file.
Not Received	The log file has not been received.
Not Applied	The log file has not been applied.
First Change # (SCN)	The first system change number.

Table 6–1 (Cont.) Log File Details Page

Column Title	Description
Last Change # (SCN)	The last system change number.
Size (KB)	The size, in kilobytes, of the log file.
Time Generated	The time when the log file was generated.
Time Completed	The time at which the log file was completed.

Click **Log File Details** from the Data Guard Overview page to see the page shown in Figure 6–43.

Figure 6–43 Viewing Log File Details

The screenshot shows the Oracle Enterprise Manager 10g interface. At the top, there are navigation tabs for Home, Targets, Deployments, Alerts, Policies, Jobs, and Reports. Below this is a breadcrumb trail: Host: north.foo.com > Database Instance: West_Sales > Data Guard >. The page title is "Log File Details". A status bar indicates "Page Refreshed Jun 5, 2005 10:45:27 PM EDT".

A descriptive paragraph states: "A table is shown below for each standby database in the configuration, listing redo log files that have not been received by the standby database and redo log files that have been received but not applied to the standby database. Related log transport and apply information is also displayed for diagnostic purposes." Below this, it says "Primary Current Log 146".

DR_Sales

Log Transport Services: On
Log Transport Status: Normal
Log Apply Services Status: Off
Apply Delay (minutes): 0
Normal, Log Apply Off

Log Status	ResetLogs ID #	First Change # (SCN)	Last Change # (SCN)	Size (KB)	Time Generated	Time Completed
144 Partially Applied	559311340	666888	667390	155	Jun 5, 2005 10:27:17 PM	Jun 5, 2005 10:44:21 PM
145 Not Applied	559311340	667390	667409	4	Jun 5, 2005 10:44:21 PM	Jun 5, 2005 10:45:07 PM

West_Sales

Log Transport Services: On
Log Transport Status: Normal
Log Apply Services Status: Off
Apply Delay (minutes): 0
Normal, Log Apply Off

Log Status	ResetLogs ID #	First Change # (SCN)	Last Change # (SCN)	Size (KB)	Time Generated	Time Completed
145 Partially Applied	559311340	667390	667409	5	Jun 5, 2005 10:44:21 PM	Jun 5, 2005 10:45:07 PM

6.8.3 Monitoring Configuration Performance


For more in-depth performance and monitoring, you can display detailed performance statistics for a broker configuration using performance charts that provide a graphical summary of all online redo log file activity in the configuration. The charts are refreshed based on a collection interval (the rate at which data is sampled from the primary database) that you can specify. The default collection interval is 30 seconds, which can be changed. See the online Help for detailed information about performance sampling rates.

The Performance Overview page collects performance related information from all of the databases in the configuration. All charts are represented by metrics. Typically, the charts show two hours worth of data. You can click any chart to view historical data (for example, 24 hours a day, 7 days a week, 31 days a month). Rates are calculated by

determining the amount of redo (applied or generated) divided by the collection interval (default is 1 minute for the performance page, 5 minutes for metrics).

- Redo Generation Rate -- This chart shows the redo generation rate (KB/sec) on the primary.
- Lag Times -- Shows the Transport Lag (the approximate number seconds of redo not yet available on the standby database) and Apply Lag (The approximate number of seconds the standby is behind the primary database).
- Apply Rate -- Displays the standby apply rate (KB/sec). The Current Redo Generation Rate shows the last value. The Apply Rate When Active value (last 3 logs, KB/sec) shows the actual apply rate when averaged over the last three log files.
- Test Application -- The test application is a built in application which will generate a workload on the primary database. This is an easy way view the performance metrics when the primary database is under a load.
- Overview -- Shows the primary database name and status. Click the status link to view the historical summary of the status metric. Note: the status on the performance page is shown directly from the status metric which runs at 5 minute collection intervals. The status on the Data Guard Overview Page is always updated on every refresh.

Figure 6–44 Performance Page



The Performance Overview page begins charting information as soon as the page is displayed. Data will not be collected for any offline or disabled databases.

6.9 Scenario 9: Using Metrics

Oracle Enterprise Manager automatically monitors the status and redo log file activity on the primary and standby databases. The following list shows the Data Guard metrics:

- Data Guard Fast-Start Failover:
 - Fast-Start Failover Occurred
 - Fast-Start Failover SCN
 - Fast-Start Failover Time
- Data Guard Performance
 - Apply Lag (seconds)
 - Estimated Failover Time (seconds)
 - Redo Apply Rate (KB/second)
 - Transport Lag (seconds)
- Data Guard Status

You can set up Email Services to notify you through your e-mail if any of the metrics are triggered.

See Also: Enterprise Manager help and documentation for more information about registering metrics and using Email Services

6.9.1 Understanding the Data Guard Metrics

The following sections provide additional information about the Data Guard metrics.

6.9.1.1 Fast-Start Failover Metrics

When fast-start failover is enabled, these metrics will generate a critical alert on the new primary database (old standby) if a fast-start failover occurs.

6.9.1.2 Data Guard Performance Metrics

The Data Guard performance metrics provide alerts for performance related to redo log activity in the configuration.

6.9.1.3 Data Guard Status

The Data Guard Status metric checks the status of each database in the broker configuration and triggers a warning or critical alert if necessary.

6.9.2 Managing Data Guard Metrics

The example in this section describes Data Guard metrics and how to set up for notification through e-mail when a metric is triggered. Take the following steps to manage Data Guard metrics:

1. [Set up to receive metric notification by e-mail.](#)
2. [View the All Metrics page.](#)

3. [Set or change metric thresholds for Data Guard thresholds.](#)
4. [View triggered metrics.](#)

Step 1 Set up to receive metric notification by e-mail.

You can set up the Notification Methods to notify you through e-mail if any of the metrics are triggered. To set up Notification Methods, take the following steps:

1. Click **Setup** at the bottom of the Database Home page.
2. Click **Notification Methods** on the Setup page.
3. Set up the required mail server information.

See Also: Oracle Enterprise Manager documentation and help for a complete description of Email Services

Step 2 View the All Metrics page.

You can view all of the metrics for Oracle Enterprise Manager, including Data Guard, by clicking All Metrics at the bottom of the Database Home page.

Figure 6–45 shows the All Metrics page for the primary database with the Data Guard metrics expanded.

Figure 6–45 Data Guard Metrics

ORACLE Enterprise Manager 10g
Grid Control

Home Targets Deployments Alerts Policies Jobs Reports

Databases | Hosts | Web Applications | Services | Systems | Groups | All Targets

Database Instance: North_Sales >

All Metrics

Collected From Target Jun 5, 2005 11:34:43 PM EDT

Expand All | Collapse All

Metrics	Thresholds	Collection Schedule	Upload Interval	Last Upload
North_Sales				
Alert Log	Some	Every 15 Minutes	Every Collection	Jun 2, 2005 11:11:26 AM
Alert Log Content	None	Real-time Only	n/a	n/a
Alert Log Error Status	All	Every 15 Minutes	Every Collection	Jun 5, 2005 11:20:57 PM
Archive Area	Some	Every 15 Minutes	Every Collection	-
Audit Files Directory Permission	None	Real-time Only	n/a	n/a
Audit Trail	None	Real-time Only	n/a	n/a
Background Dump Directory Permission	None	Real-time Only	n/a	n/a
Control Files Permission	None	Real-time Only	n/a	n/a
Core Dump Directory Permission	None	Real-time Only	n/a	n/a
Data Files Permission	None	Real-time Only	n/a	n/a
Data Guard Fast-Start Failover	Some	Every 5 Minutes	Every Collection	Jun 5, 2005 11:32:40 PM
Fast-Start Failover Occurred	Set			
Fast-Start Failover SCN	Not Set			
Fast-Start Failover Time	Not Set			
Data Guard Performance	None	Every 5 Minutes	Every Collection	Jun 5, 2005 11:32:40 PM
Redo Generation Rate (KB/second)	Not Set			
Data Guard Status	All	Every 5 Minutes	Every Collection	Jun 5, 2005 11:32:40 PM
Data Guard Status	Set			
Database Files	None	Every 5 Minutes	Every Collection	Jun 5, 2005 11:25:38 PM
Database Job Status	All	Every 5 Minutes	On Alert	Jun 5, 2005 9:53:57 PM
Database Limits	Some	Every 5 Minutes	Every Collection	Jun 5, 2005 11:32:38 PM
Database Link with Hard Coded Password	None	Real-time Only	n/a	n/a
Database Services	None	Every 15 Minutes	Every Collection	Jun 5, 2005 11:24:38 PM
Database Users With Tablespace Quota	None	Real-time Only	n/a	n/a
Database Users with Access on	None	Real-time Only	n/a	n/a

Step 3 Set or change metric thresholds for Data Guard thresholds.

The following Data Guard metrics can be changed on the Metrics and Policy Settings page.

■ Data Guard Fast-Start Failover

When Fast-Start Failover is enabled, these metrics will generate a critical alert on the new primary database (old standby) if a fast-start failover occurs:

- **Fast-Start Failover Occurred:** Indicates that a fast-start failover has occurred. The value is 0 if fast-start failover has not occurred, and 1 if fast-start failover has occurred.
- **Fast-Start Failover SCN:** Shows the SCN when a fast-start failover occurred. The fast-start failover SCN must be initialized to a value before the metric will alert.
- **Fast-Start Failover Time:** Shows the time when a fast-start failover occurred.

■ Data Guard Performance

All charts on the Performance Overview page are represented by the following metrics.

- **Apply Lag (seconds):** Shows the approximate number of seconds the standby is behind the primary database.
- **Estimated Failover Time (seconds):** The approximate number of seconds required to fail over to this standby database. This accounts for the startup time, if necessary, plus the remaining time required to apply all the available redo on the standby. If a bounce is not required, it is only the remaining apply time.
- **Redo Apply Rate (KB/second):** Displays the Redo Apply Rate in KB/second on this standby database.
- **Transport Lag (seconds):** Shows the approximate number seconds of redo not yet available on the standby database.

■ Data Guard Status

If the Data Guard Status metric contains Warning, a warning alert is triggered. If the metric contains Error, a critical alert is triggered.


See Also: Oracle Enterprise Manager online Help for a information about setting metrics

Step 4 View triggered metrics.

If a metric condition is triggered or a threshold value is exceeded, an alert is issued. Click **Data Guard Status**, **Data Guard Performance**, or **Data Guard Fast-Start Failover** on the All Metrics page to view triggered metrics.

[Figure 6–46](#) shows the Alert Log Errors page for the North_Sales database. It provides an example of what is shown when the Data Guard Fast-Start Failover metric triggers after a problem with the observer is detected in the configuration. The table shows the status of each database in the configuration. The status of the primary database shows the ORA-16820 error.

Figure 6–46 Alert Log Errors Page Showing the Observer Has Stopped



Because Email Services was set up, DBAs are also notified by an e-mail message. After a metric condition is fixed, the metric is cleared automatically.

6.10 Scenario 10: Removing a Standby Database and Configuration

You can remove a standby database or broker configuration so that it is no longer controlled by the Data Guard broker.

6.10.1 Remove a Standby Database


Removing a standby database from Data Guard broker control does not permanently delete the database itself. This operation permanently removes the profile of the standby database from the broker configuration file.

By default, the standby destination is also removed from the primary database so that log files are no longer archived to that standby database.

Caution: The Oracle9i Data Guard Manager default was to preserve the standby destination on the primary database.

To remove a standby database from the broker configuration, click **Remove** in the Standby Databases section of the Data Guard Overview page. Enterprise Manager will ask you to confirm that you really want to remove the standby database from the configuration. Click **Yes** to continue or **No** to cancel.


Figure 6–47 shows removing a standby database.

Figure 6–47 Removing a Standby Database

6.10.2 Remove the Data Guard Configuration

To remove the broker configuration, you must be connected to the configuration through the primary database. Click **Remove Data Guard Configuration** under the Additional Administration section. Enterprise Manager will ask you to confirm that you want to remove the configuration. Click **Yes** to continue or **No** to cancel.

Figure 6–48 shows removing a Data Guard broker configuration.

Figure 6–48 Removing a Data Guard Broker Configuration

When you choose this option, Enterprise Manager removes (deletes) the selected broker configuration permanently. When you permanently remove a configuration, the remove operation:

- Does not affect the underlying operations of the standby databases or log apply services if you check the box to preserve all standby destinations. Operations such as redo transport services and log apply services continue to run; however, these services are no longer manageable through Enterprise Manager.
- By default, all standby database profiles are removed from the broker configuration, and redo transport services to all standby databases in the configuration are stopped.
- Destroys all broker configuration profile information maintained for each database; the configuration is then unknown to the broker and can no longer be managed from Enterprise Manager.

Although the configuration information is not recoverable once you delete a broker configuration permanently, you can easily re-create the configuration with the Add Standby Database wizard.

Scenarios Using the DGMGRL Command-Line Interface

This chapter describes the prerequisites for getting started using the Data Guard command-line interface (DGMGRL). It also describes scenarios that demonstrate how to use DGMGRL to create, manage, and monitor a broker configuration.

This chapter contains the following sections:

- [Prerequisites for Getting Started](#)
- [Scenario 1: Creating a Configuration](#)
- [Scenario 2: Setting Database Properties](#)
- [Scenario 3: Enabling the Configuration and Databases](#)
- [Scenario 4: Setting the Configuration Protection Mode](#)
- [Scenario 5: Enabling Fast-Start Failover and Starting the Observer](#)
- [Scenario 6: Performing Routine Management Tasks](#)
- [Scenario 7: Performing a Switchover Operation](#)
- [Scenario 8: Performing a Manual Failover Operation](#)
- [Scenario 9: Reinstating a Failed Primary Database](#)
- [Scenario 10: Converting a Physical Standby to a Snapshot Standby](#)
- [Scenario 11: Monitoring a Data Guard Configuration](#)

7.1 Prerequisites for Getting Started

One of the prerequisites for using DGMGRL is that a primary database and any standby databases must already exist. The `DG_BROKER_START` initialization parameter must be set to `TRUE` for all databases in the configuration. You must use a server parameter file with the broker (see [Section 2.1](#) and [Section 8.1.3](#)).

Convert the initialization parameter files (PFILE) on both primary and standby databases into server parameter files (SPFILE), if necessary. Use the following SQL*Plus command:

```
CREATE SPFILE FROM PFILE='pfilename';
```

If an instance was not started with a server parameter file, then you must shut down the instance and restart it using the server parameter file.

After starting the Oracle instance, set the `DG_BROKER_START=TRUE` initialization parameter using the SQL `ALTER SYSTEM` statement. The parameter value will be

saved in the server parameter file. The next time you start the Oracle instance, the broker is started automatically, and you do not need to issue the SQL `ALTER SYSTEM` statement again.

See Also: *Oracle Database Administrator's Guide* for detailed information about creating server parameter files

The following assumptions are made for the scenarios in this chapter:

- TCP/IP is used to connect to primary and standby databases.
- The standby database has been created from backups of the primary database control files and datafiles as described in the *Oracle Data Guard Concepts and Administration*.
- The scenarios in this chapter assume the following broker configuration:
 - The configuration name is `DRSolution`.
 - The database unique name (`DB_UNIQUE_NAME`) of the primary database is `North_Sales`.
 - The database unique name (`DB_UNIQUE_NAME`) of the remote standby database is `DR_Sales`.
 - The protection mode is maximum performance mode.
 - There are standby redo log files and the transport mode is `ASYNC`.
 - The standby database is a physical standby database.

7.2 Scenario 1: Creating a Configuration

This section provides examples that create a broker configuration named `DRSolution` that includes a primary and standby database named `North_Sales` and `DR_Sales`.

The following steps show how to create a configuration and add one physical standby database.

Step 1 Invoke DGMGRL.

To start DGMGRL, enter `dgmgrl` at the command-line prompt on a system where Oracle Data Guard is installed:

```
$ dgmgrl

DGMGRL for Linux: Version 11.1.0.7.0 - Production

Copyright (c) 2000, 2005, Oracle. All rights reserved.

Welcome to DGMGRL, type "help" for information.

DGMGRL>
```

Step 2 Connect to the primary database.

Before you specify any command (other than the `HELP`, `EXIT`, or `QUIT`), you must first connect to the primary database using the DGMGRL `CONNECT` command.

The account from which you connect to the database (`SYS` in this example) must have `SYSDBA` privileges on the primary and standby databases.

Note: You do not have to include `AS SYSDBA` on the `CONNECT` command because `SYSDBA` is the default setting for this command.

The following examples show two variations of the `CONNECT` command. [Example 7-1](#) shows how to connect to the default database on the local system, and [Example 7-2](#) includes the Oracle Net Services connect identifier (`North_Sales.foo.com`) to make a connection to a database located on a remote system. In both examples, you are prompted for a password.

Example 7-1 Connecting to the Primary Database on the Local System

```
DGMGRL> CONNECT sys;
Password: password
Connected.
```

Example 7-2 Connecting to the Primary Database on a Remote System

```
DGMGRL> CONNECT sys@North_Sales.foo.com;
Password: password
Connected.
```

Step 3 Create the broker configuration.

To create the broker configuration, you first define the configuration including a profile for the primary database, which in this case is called `North_Sales`. In a later command, you will add a profile for the standby database, `DR_Sales`.

Note: The names for the primary and standby databases must match their database unique names. Fetch these from their `DB_UNIQUE_NAME` initialization parameter as follows:

```
SQL> SHOW PARAMETER DB_UNIQUE_NAME;
```

Use the `CREATE CONFIGURATION` command to create the `DRSolution` configuration and define the primary database, `North_Sales`:

```
DGMGRL> CREATE CONFIGURATION 'DRSolution' AS
> PRIMARY DATABASE IS 'North_Sales'
> CONNECT IDENTIFIER IS North_Sales.foo.com;
```

DGMGRL returns the following information:

```
Configuration "DRSolution" created with primary database "North_Sales"
```

The name `North_Sales` is the value of this database's `DB_UNIQUE_NAME` initialization parameter.

Step 4 Show the configuration information.

Use the `SHOW CONFIGURATION` command to display a brief summary of the configuration:

```
DGMGRL> SHOW CONFIGURATION;
```

DGMGRL returns the following information:

```
Configuration
Name:                DRSolution
Enabled:             NO
```

```
Protection Mode:      MaxPerformance
Databases:
  North_Sales - Primary database
```

```
Fast-Start Failover: DISABLED
```

```
Current status for "DRSolution":
DISABLED
```

Step 5 Add a standby database to the configuration.

To add a standby database to the `DRSolution` configuration, use the `ADD DATABASE` command to create a broker configuration profile for the standby database.

The following command defines `DR_Sales` as a standby database, which is the standby database associated with the primary database called `North_Sales`:

```
DGMGRL> ADD DATABASE 'DR_Sales' AS
> CONNECT IDENTIFIER IS DR_Sales.foo.com;
```

DGMGRL returns the following information:

```
Database "DR_Sales" added
```

The name `DR_Sales` is the value of the database's `DB_UNIQUE_NAME` initialization parameter.

Use the `SHOW CONFIGURATION` command to verify that the `DR_Sales` database was added to the `DRSolution` configuration:

```
DGMGRL> SHOW CONFIGURATION;
```

DGMGRL returns the following information:

```
Configuration
Name:          DRSolution
Enabled:       NO
Protection Mode:  MaxPerformance
Databases:
  North_Sales - Primary database
  DR_Sales    - Physical standby database

Fast-Start Failover: DISABLED

Current status for "DRSolution":
DISABLED
```

7.3 Scenario 2: Setting Database Properties

After you create the configuration with DGMGRL, you can set database properties at any time. For example, the following statements set the `LogArchiveFormat` and `StandbyArchiveLocation` configurable database properties for the `DR_Sales` standby database:

```
DGMGRL> EDIT DATABASE 'DR_Sales' SET PROPERTY 'LogArchiveFormat'='log_%t_%s_%r_%d.arc';
Property "LogArchiveFormat" updated.

DGMGRL> EDIT DATABASE 'DR_Sales' SET PROPERTY 'StandbyArchiveLocation'='/archfs/arch/';
Property "StandbyArchiveLocation" updated.
```

Use the `SHOW DATABASE VERBOSE` command to view all properties and their values for a database. The following example shows the properties for the `DR_Sales` database.

```
DGMGRL> SHOW DATABASE VERBOSE 'DR_Sales';

Database
Name:          DR_Sales
Role:          PHYSICAL STANDBY
Enabled:       NO
Intended State: APPLY-ON
Instance(s):
  dr_sales1

Properties:
  DGConnectIdentifier          = 'DR_Sales.foo.com'
  ObserverConnectIdentifier    = ''
  LogXptMode                   = 'ASYNC'
  DelayMins                    = '0'
  Binding                      = 'OPTIONAL'
  MaxFailure                   = '0'
  MaxConnections               = '1'
  ReopenSecs                   = '300'
  NetTimeout                   = '30'
  RedoCompression              = 'DISABLE'
  LogShipping                   = 'ON'
  PreferredApplyInstance       = ''
  ApplyInstanceTimeout         = '0'
  ApplyParallel                = 'AUTO'
  StandbyFileManagement        = 'AUTO'
  ArchiveLagTarget              = '0'
  LogArchiveMaxProcesses       = '5'
  LogArchiveMinSucceedDest     = '1'
  DbFileNameConvert            = 'dbs/t, dbs/bt'
  LogFileNameConvert           = 'dbs/t, dbs/bt'
  FastStartFailoverTarget      = ''
  StatusReport                  = '(monitor)'
  InconsistentProperties        = '(monitor)'
  InconsistentLogXptProps      = '(monitor)'
  SendQEntries                  = '(monitor)'
  LogXptStatus                  = '(monitor)'
  RecvQEntries                  = '(monitor)'
  HostName                      = 'dr_sales.foo.com'
  SidName                       = 'dr_sales1'
  StandbyArchiveLocation        = '/archfs/arch'
  AlternateLocation             = ''
  LogArchiveTrace                = '8191'
  LogArchiveFormat              = 'db2r_%d_%t_%s_%r.arc'
  LatestLog                     = '(monitor)'
  TopWaitEvents                 = '(monitor)'

Current status for "DR_Sales":
DISABLED
```

If broker management of the database is enabled, setting a database property value causes the underlying parameter value to be changed in the corresponding database, and the value for the changed parameter is reflected in the server parameter file. Thus, if the database is shut down and restarted outside of Oracle Enterprise Manager and DGMGRL (such as from the SQL*Plus interface), the database uses the new parameter values from the updated server parameter file when it starts. However, you should not

make changes to the redo transport services initialization parameters through SQL statements. Doing so will cause an inconsistency between the database and the broker.

Note: The database properties are typically displayed in mixed-case (for example, `LogArchiveFormat`) typeface to help you visually differentiate database properties (from the corresponding initialization parameter, SQL statement, or PL/SQL procedure), which are typically documented in `UPPERCASE` typeface. However, the commands to manage properties are not case sensitive; you can issue commands in uppercase, lowercase, or mixed-case.

You can change a property if the database is enabled or disabled. However, if the database is disabled when you change a property, the change does not take effect until the database is enabled.

7.4 Scenario 3: Enabling the Configuration and Databases

So far, the `DRSolution` configuration is disabled, which means it is not under the control of the Data Guard broker. When you finish configuring the databases into a broker configuration and setting any necessary database properties, you must enable the configuration to allow the Data Guard broker to manage it.

You can enable:

- The entire configuration, including all of its databases
- A standby database

Enable the entire configuration.

You can enable the entire configuration, including all of the databases, with the following command:

```
DGMGRL> ENABLE CONFIGURATION;  
Enabled.
```

Show the configuration.

Use the `SHOW` command to verify that the configuration and its databases were successfully enabled:

```
DGMGRL> SHOW CONFIGURATION;
```

DGMGRL returns the following information:

```
Configuration  
Name:                DRSolution  
Enabled:          YES  
Protection Mode:     MaxPerformance  
Databases:  
  North_Sales - Primary database  
  DR_Sales    - Physical standby database  
  
Fast-Start Failover: DISABLED  
  
Current status for "DRSolution":  
SUCCESS
```


Enable the database.

This step is unnecessary except if the standby database was previously disabled with the `DISABLE DATABASE` command. Normally, enabling the configuration also enables the standby database.

```
DGMGRL> ENABLE DATABASE 'DR_Sales';
Enabled.
```

Show the database.

```
DGMGRL> SHOW DATABASE 'DR_Sales';
```

```
Database
Name:          DR_Sales
Role:          PHYSICAL STANDBY
Enabled:     YES
Intended State: APPLY-ON
Instance(s):
  dr_sales1
```

```
Current status for "DR_Sales":
SUCCESS
```

7.5 Scenario 4: Setting the Configuration Protection Mode

You can change the protection mode of the configuration at any time. However, it is best if you do this when there is no activity occurring in the configuration if you are moving to the maximum protection or maximum availability modes.

Note: If the protection mode to be set is maximum protection mode, the broker automatically restarts the primary database.

This scenario sets the protection mode of the configuration to the `MAXAVAILABILITY` mode. Note that this protection mode requires that there be at least one standby database configured to use standby redo log files, with its `LogXptMode` configurable database property set to `SYNC`.

Step 1 Configure standby redo log files, if necessary.

Because you will be setting the protection mode to the `MAXAVAILABILITY` mode, it is important to ensure that sufficient standby redo log files are configured on the standby database.

Step 2 Set the LogXptMode configurable database property appropriately.

Use the `EDIT DATABASE (property)` command on the standby database to set the redo transport service that corresponds to the protection mode you plan to set. If the protection mode to be set is `MAXAVAILABILITY`, it is required that the redo transport service of at least one standby database is set to `SYNC`. For example:

```
DGMGRL> EDIT DATABASE 'DR_Sales' SET PROPERTY 'LogXptMode'='SYNC';
Property "LogXptMode" updated
```

The broker will not allow this command to succeed unless the standby database is configured with standby redo log files in the configuration.

Step 3 Change the overall protection mode for the configuration.

Use the `EDIT CONFIGURATION` command to upgrade the broker configuration to the `MAXAVAILABILITY` protection mode:

```
DGMGRL> EDIT CONFIGURATION SET PROTECTION MODE AS MAXAVAILABILITY;  
Succeeded.
```

If the configuration is disabled when you enter this command, the actual protection mode change is not applied until you enable the configuration with the `ENABLE CONFIGURATION` command. The broker will not allow you to enable the configuration if it does not find a standby database in the configuration that can support the requirements of the protection mode.

Step 4 Verify the protection mode was changed.

Use the `SHOW CONFIGURATION` command to display the current protection mode for the configuration:

```
DGMGRL> SHOW CONFIGURATION;  
  
Configuration  
Name:                DRSolution  
Enabled:             YES  
Protection Mode:    MaxAvailability  
Databases:  
  North_Sales - Primary database  
  DR_Sales    - Physical standby database  
  
Fast-Start Failover: DISABLED  
  
Current status for "DRSolution":  
SUCCESS
```

See Also: [Section 4.6, "Managing Data Protection Modes"](#) on page 4-15

7.6 Scenario 5: Enabling Fast-Start Failover and Starting the Observer

You can enable fast-start failover from any site, including the observer site, while connected to any database in the broker configuration. Enabling fast-start failover does not trigger a failover. Instead, it allows the observer to begin observing the primary and standby databases and initiate a fast-start failover should conditions warrant a failover.

This section describes the steps to enable fast-start failover and start the observer where the configuration property mode is to be set to:

- [Ensure standby redo logs are configured on the primary and target standby databases.](#)
- [Ensure the LogXptMode Property is set to SYNC.](#)
- [Set the FastStartFailoverTarget configuration property.](#)
- [Upgrade the protection mode to MAXAVAILABILITY, if necessary.](#)
- [Enable Flashback Database on the primary and target standby databases, if necessary.](#)
- [Start the observer.](#)
- [Enable fast start failover.](#)

- [Verify the fast-start failover configuration.](#)

Step 1 Ensure standby redo logs are configured on the primary and target standby databases.

Standby redo logs must be configured on the primary and standby databases. You must stop log apply services prior to configuring standby redo logs.

See Also: *Oracle Data Guard Concepts and Administration* for instructions on configuring standby redo log files

Step 2 Ensure the LogXptMode Property is set to SYNC.

The LogXptMode configurable database property must be set to SYNC on the primary and target standby databases.

To set the redo transport service that corresponds to the protection mode you plan to set, use the EDIT DATABASE (property) command on the primary and target standby databases. For example, if the protection mode to be set is MAXAVAILABILITY, you must set the LogXptMode property to SYNC on the primary database and on the target standby database, as shown in the following examples:

```
DGMGRL> EDIT DATABASE 'North_Sales' SET PROPERTY 'LogXptMode'='SYNC';
Property "LogXptMode" updated
```

```
DGMGRL> EDIT DATABASE 'DR_Sales' SET PROPERTY 'LogXptMode'='SYNC';
Property "LogXptMode" updated
```

The broker does not allow these commands to succeed unless the databases are configured with standby redo log files.

Step 3 Set the FastStartFailoverTarget configuration property.

If you have two or more standby databases, set up the FastStartFailoverTarget configuration property on the primary database to indicate the desired target standby database. For example:

```
DGMGRL> EDIT DATABASE 'North_Sales' SET PROPERTY FastStartFailoverTarget='DR_
Sales';
Property "FastStartFailoverTarget" updated
```

Step 4 Upgrade the protection mode to MAXAVAILABILITY, if necessary.

If it is necessary to upgrade the protection mode, use the following DGMGRL EDIT CONFIGURATION command. For example:

```
DGMGRL> EDIT CONFIGURATION SET PROTECTION MODE AS MAXAVAILABILITY;
```

Step 5 Enable Flashback Database on the primary and target standby databases, if necessary.

If it is not already enabled on the primary and standby databases, enable Flashback Database by issuing the following statements on each database:

```
ALTER SYSTEM SET UNDO_RETENTION=3600 SCOPE=SPFILE;
ALTER SYSTEM SET UNDO_MANAGEMENT='AUTO' SCOPE=SPFILE;
SHUTDOWN IMMEDIATE;
STARTUP MOUNT;
SHOW PARAMETER UNDO;
ALTER SYSTEM SET DB_FLASHBACK_RETENTION_TARGET=4320 SCOPE=BOTH;
ALTER DATABASE ARCHIVELOG;
ALTER SYSTEM SET db_recovery_file_dest_size=<size>;
```

```
ALTER SYSTEM SET db_recovery_file_dest=<directory-specification>;
ALTER DATABASE FLASHBACK ON;
ALTER DATABASE OPEN;
```

Ensure the `UNDO_RETENTION` and `DB_FLASHBACK_RETENTION_TARGET` initialization parameters are set to sufficiently large values so that reinstatement is still possible after a prolonged outage.

Step 6 Start the observer.

Start the observer by logging into the observer computer and running `DGMGRL`. Connect to the configuration as `SYS` and then issue the `START OBSERVER` command. Note that the command does not return; that is you will not get `DGMGRL` prompt after issuing the command.

```
DGMGRL> CONNECT sys@North_Sales.foo.com;
Password: password
Connected.
DGMGRL> START OBSERVER;
Observer started
```

When starting the observer interactively, Oracle recommends that connection credentials be supplied as a command parameter to the `DGMGRL CONNECT` command, as shown in the example, rather than as a command line parameter to the `DGMGRL` command. This practice prevents other users on the system from using a utility (for example, the UNIX `ps` utility) to display the connection credentials.

When starting the observer from a script, Oracle recommends that you use a method that supports `'connect /'`, so that database connection credentials do not have to be embedded within the script. If you choose to use a client-side Oracle Wallet as a secure external password store (see *Oracle Database Advanced Security Administrator's Guide*), be sure to add credentials for both the primary and fast-start failover target standby databases. The database connect string that you specify when adding the credentials for each database must match the `ObserverConnectIdentifier` or `DGConnectIdentifier` configurable database property.

Step 7 Enable fast start failover.

You can enable fast-start failover while connected to any database system in the broker configuration. For example:

```
DGMGRL> ENABLE FAST_START FAILOVER;
Enabled.
```

Step 8 Verify the fast-start failover configuration.

Use the `SHOW FAST_START FAILOVER` command to display the fast-start failover settings:

```
DGMGRL> SHOW FAST_START FAILOVER;

Fast-Start Failover: ENABLED
  Threshold:          30 seconds
  Target:             DR_Sales
  Observer:           observer.foo.com
  Lag Limit:          30 seconds (not in use)
  Shutdown Primary:  TRUE
  Auto-reinstate:     TRUE

Configurable Failover Conditions
Health Conditions:
```

Corrupted Controlfile	YES
Corrupted Dictionary	YES
Inaccessible Logfile	NO
Stuck Archiver	NO
Datafile Offline	YES

Oracle Error Conditions:
(none)

7.7 Scenario 6: Performing Routine Management Tasks

There may be situations in which you want to change the state or properties of the databases in a broker configuration to perform routine maintenance on one or more databases. You might also need to temporarily disable broker management of databases in a configuration.

7.7.1 Changing Properties and States

As you monitor the configuration, you might need to dynamically modify the states of the databases or their properties. The following sections show how to change the state or properties of the databases in the configuration.

7.7.1.1 Alter a Database Property

You can modify the values of database properties at any time—if the database is enabled or disabled.

[Example 7–3](#) shows how to use the `EDIT DATABASE` command to change the `LogArchiveTrace` configurable database property to the value 127 for the `North_Sales` database.

Example 7–3 Altering a Database Property

```
DGMGRL> EDIT DATABASE 'North_Sales' SET PROPERTY 'LogArchiveTrace'='127';
```

DGMGRL returns the following message to indicate that the `LogArchiveTrace` property was updated successfully in the Data Guard configuration file:

```
Property "LogArchiveTrace" updated
```

If the configuration is currently disabled, the database does not use the new property value until you enable the broker configuration with the `ENABLE CONFIGURATION` command.

7.7.1.2 Alter the State of a Standby Database

You might want to temporarily stop Redo Apply on a physical standby. To change the state of the standby database to `APPLY-OFF`, enter the `EDIT DATABASE` command as shown in [Example 7–4](#).

Example 7–4 Altering a Standby Database State

```
DGMGRL> EDIT DATABASE 'DR_Sales' SET STATE='APPLY-OFF';
Succeeded.
```

Redo data is still being received when you put the physical standby database in the `APPLY-OFF` state.

7.7.1.3 Alter the State of a Primary Database

You might want to stop the transmittal of redo data to the standby database. To change the state of the primary database to accommodate this, use the following command:

```
DGMGRL> EDIT DATABASE North_Sales SET STATE=TRANSPORT-OFF;
```

Succeeded.

To change the state of the primary database back to TRANSPORT-ON, do the following:

```
DGMGRL> EDIT DATABASE North_Sales SET STATE=TRANSPORT-ON;
```

Succeeded.

7.7.2 Disabling the Configuration and Databases

When you disable the broker configuration or any of its databases, you are disabling the broker's management of those objects and are effectively removing your ability to use DGMGRL to manage and monitor the disabled object. However, disabling the broker's management of a broker configuration does not affect the actual operation of the underlying Data Guard configuration or the databases. For example, the redo transport services and log apply services in the Data Guard configuration continue to function unchanged, but you can no longer manage them.

7.7.2.1 Disable a Configuration

You must use the `DISABLE CONFIGURATION` command to disable management of the entire broker configuration including the primary database as shown in [Example 7-5](#).

Example 7-5 Disabling the Configuration and Primary Database

```
DGMGRL> DISABLE CONFIGURATION;
```

The only way to disable broker management of the primary database is to use the `DISABLE CONFIGURATION` command; the `DISABLE DATABASE` command only disables management of a standby database.

Note: If you disable management of a configuration while connected to the standby database, you must connect to the primary database to reenble the configuration.

Disabling the broker's management of an object *does not* remove its profile from the broker configuration file. You can reenble your ability to use DGMGRL (or Enterprise Manager) to manage the object by entering the appropriate `ENABLE CONFIGURATION` or `ENABLE DATABASE` command.

7.7.2.2 Disable a Standby Database

You use the `DISABLE DATABASE` command when you temporarily do not want the broker to manage and monitor a standby database.

You can explicitly disable broker management of a standby database to prevent it from being enabled when the rest of the configuration is enabled. [Example 7-6](#) shows how to disable the `DR_Sales` standby database.

Example 7–6 Disabling a Standby Database

```
DGMGRL> DISABLE DATABASE 'DR_Sales';  
Disabled.
```

Note: You cannot disable a standby database from the configuration if fast-start failover is enabled and the database to be disabled is the target standby database.

Note: If you disable management of a standby database while connected to that standby database, you must connect to the primary database or another enabled standby database to reenable broker-management of the standby database.

Caution: If you disable broker management of a standby database in the broker configuration, that standby database cannot be used by the broker as a failover target in the event of loss of the primary database.

When operating under either maximum protection mode or maximum availability mode, the broker prevents you from disabling the last standby database that supports the protection mode.

7.7.3 Removing the Configuration or a Standby Database

When you use either the `REMOVE CONFIGURATION` or `REMOVE DATABASE` command, you effectively delete the configuration or standby database profile from the broker configuration file, removing the ability of the Data Guard broker to manage the configuration or the standby database, respectively.

A remove operation with the `PRESERVE DESTINATIONS` clause *does not* remove or delete the actual Data Guard configuration underneath, nor does it affect the operation of the actual Data Guard configuration and its databases.

Caution: After you use the `REMOVE CONFIGURATION` or `REMOVE DATABASE` command, you cannot recover the configuration or database profile that was deleted from the broker configuration file. You must go through the steps in [Section 7.2](#) as necessary, to create a broker configuration that can be managed with DGMGRL (or the Enterprise Manager).

Note: You cannot remove a standby database from the configuration if fast-start failover is enabled and the database to be removed is the target standby database.

Step 1 Remove a standby database from the configuration.

When you use the `REMOVE DATABASE` command, broker management and monitoring of the database ceases and the database's profile is deleted from the broker configuration file:

```
DGMGRL> SHOW CONFIGURATION;

Configuration
Name:                DRSolution
Enabled:             YES
Protection Mode:     MaxPerformance
Databases:
  North_Sales - Primary database
  DR_Sales    - Physical standby database

Fast-Start Failover: DISABLED

Current status for "DRSolution":
SUCCESS
```

DGMGRL returns the following message to indicate the command successfully removed the `DR_Sales` database information from the Data Guard configuration file:

```
DGMGRL> REMOVE DATABASE 'DR_Sales';
Removed database "DR_Sales" from the configuration
```

```
DGMGRL> SHOW CONFIGURATION;

Configuration
Name:                DRSolution
Enabled:             YES
Protection Mode:     MaxPerformance
Databases:
  North_Sales - Primary database

Fast-Start Failover: DISABLED

Current status for "DRSolution":
SUCCESS
```

When operating under either maximum protection mode or maximum availability mode, the broker prevents you from deleting the last standby database that supports the protection mode.

Step 2 Remove the broker configuration.

Use the following command to remove the entire configuration from management and monitoring by the broker:

```
DGMGRL> REMOVE CONFIGURATION;
```

Note: You cannot remove the configuration if fast-start failover is enabled.

DGMGRL returns the following message to indicate the command successfully removed all of the configuration information from the Data Guard configuration file:

```
Removed configuration
```



```
DGMGRL> SHOW CONFIGURATION;
Error: ORA-16532: Data Guard broker configuration does not exist

Configuration details cannot be determined by DGMGRL
```

7.8 Scenario 7: Performing a Switchover Operation

You can switch the role of the primary database and a standby database using the `SWITCHOVER` command. Before you issue the `SWITCHOVER` command, you must ensure:

- The state of the primary and standby databases are `TRANSPORT-ON` and `APPLY-ON`, respectively.
- All participating databases are in good health, without any errors or warnings present.
- The standby database properties were set on the primary database, so that the primary database can function correctly when transitioning to a standby database (shown in the following examples in boldface type).
- Standby redo log files on the primary database are set up, and the `LogXptMode` configurable database property is set to `SYNC` if the configuration is operating in either maximum availability mode or maximum protection mode.
- If fast-start failover is enabled, you can perform a switchover only to the standby database that was specified as the target standby database.

Step 1 Check the primary database.

Use the `SHOW DATABASE VERBOSE` command to check the state, health, and properties of the primary database, as follows:

```
DGMGRL> SHOW DATABASE VERBOSE 'North_Sales';

Database
Name:          North_Sales
Role:          PRIMARY
Enabled:       YES
Intended State: TRANSPORT-ON
Instance(s):
  sales1

Properties:
  DGConnectIdentifier          = 'North_Sales.foo.com'
  ObserverConnectIdentifier    = ''
  LogXptMode                   = 'SYNC'
  DelayMins                    = '0'
  Binding                      = 'OPTIONAL'
  MaxFailure                   = '0'
  MaxConnections               = '1'
  ReopenSecs                   = '300'
  NetTimeout                   = '30'
  RedoCompression             = 'DISABLE'
  LogShipping                  = 'ON'
  PreferredApplyInstance       = ''
  ApplyInstanceTimeout         = '0'
  ApplyParallel                = 'AUTO'
  StandbyFileManagement        = 'AUTO'
  ArchiveLagTarget             = '0'
  LogArchiveMaxProcesses       = '5'
```

```

LogArchiveMinSucceedDest      = '1'
DbFileNameConvert           = 'dbs/bt, dbs/t'
LogFileNameConvert         = 'dbs/bt, dbs/t'
FastStartFailoverTarget      = 'DR_Sales'
StatusReport                  = '(monitor)'
InconsistentProperties        = '(monitor)'
InconsistentLogXptProps      = '(monitor)'
SendQEntries                  = '(monitor)'
LogXptStatus                  = '(monitor)'
RecvQEntries                  = '(monitor)'
HostName                      = 'North_Sales.foo.com'
SidName                      = 'sales1'
StandbyArchiveLocation     = '/archfs/arch/'
AlternateLocation             = ''
LogArchiveTrace               = '8191'
LogArchiveFormat           = 'db1r_%d_%t_%s_%r.arc'
LatestLog                    = '(monitor)'
TopWaitEvents                 = '(monitor)'

```

```

Current status for "North_Sales":
SUCCESS

```

In particular, you should examine the boldface properties and the current status of the primary database. See [Chapter 4](#) for information about managing databases.

Step 2 Check the standby database that is the target of the switchover.

Use the `SHOW DATABASE VERBOSE` command to check the state, health, and properties of the standby database that is the target of the switchover. For example:

```
DGMGRL> SHOW DATABASE VERBOSE 'DR_Sales';
```

```

Database
Name:          DR_Sales
Role:          PHYSICAL STANDBY
Enabled:       NO
Intended State: APPLY-ON
Instance(s):
  dr_sales1

Properties:
DGConnectIdentifier      = 'DR_Sales.foo.com'
ObserverConnectIdentifier = ''
LogXptMode              = 'SYNC'
DelayMins                = '0'
Binding                  = 'OPTIONAL'
MaxFailure                = '0'
MaxConnections           = '1'
ReopenSecs               = '300'
NetTimeout               = '30'
RedoCompression          = 'DISABLE'
LogShipping               = 'ON'
PreferredApplyInstance   = ''
ApplyInstanceTimeout     = '0'
ApplyParallel            = 'AUTO'
StandbyFileManagement    = 'AUTO'
ArchiveLagTarget         = '0'
LogArchiveMaxProcesses   = '5'
LogArchiveMinSucceedDest = '1'
DbFileNameConvert       = 'dbs/t, dbs/bt'
LogFileNameConvert     = 'dbs/t, dbs/bt'

```

```

FastStartFailoverTarget      = ''
StatusReport                 = '(monitor)'
InconsistentProperties        = '(monitor)'
InconsistentLogXptProps      = '(monitor)'
SendQEntries                 = '(monitor)'
LogXptStatus                 = '(monitor)'
RecvQEntries                 = '(monitor)'
HostName                     = 'dr_sales.foo.com'
SidName                      = 'dr_sales1'
StandbyArchiveLocation      = '/archfs/arch'
AlternateLocation            = ''
LogArchiveTrace              = '8191'
LogArchiveFormat           = 'db2r_%d_%t_%s_%r.arc'
LatestLog                   = '(monitor)'
TopWaitEvents                = '(monitor)'

```

```

Current status for "DR_Sales":
SUCCESS

```

In particular, you should examine the current status of the database.

Step 3 Issue the switchover command.

Issue the SWITCHOVER command to swap the roles of the primary and standby databases. The following example shows how the broker automatically shuts down and restarts the old primary database as a part of the switchover. (See the usage notes in [Section 8.1.3](#) for information about how to set up the broker environment so that DGMGRL can automatically restart the primary and standby databases for you.)

```

DGMGRL> switchover to 'DR_Sales';
Performing switchover NOW, please wait...
New primary database "DR_Sales" is opening...
Operation requires shutdown of instance "sales1" on database "North_Sales"
Shutting down instance "sales1"...
ORA-01109: database not open

Database dismounted.
ORACLE instance shut down.
Operation requires startup of instance "sales1" on database "North_Sales"
Starting instance "sales1"...
ORACLE instance started.
Database mounted.
Switchover succeeded, new primary is "DR_Sales"

```

After the switchover completes, use the SHOW CONFIGURATION and SHOW DATABASE commands to verify that the switchover operation was successful.

Step 4 Show the configuration.

Issue the SHOW CONFIGURATION command to verify that the switchover was successful.

```

DGMGRL> SHOW CONFIGURATION;

Configuration
Name:          DRSolution
Enabled:       YES
Protection Mode:  MaxAvailability
Databases:
  DR_Sales     - Primary database
  North_Sales  - Physical standby database

```

- Fast-Start Failover target

Fast-Start Failover: ENABLED

Current status for "DRSolution":
SUCCESS

7.9 Scenario 8: Performing a Manual Failover Operation

You invoke a failover operation in response to an emergency situation, usually when the primary database cannot be accessed or is unavailable. See [Section 5.2](#) before you fail over to decide which standby database should be the target of the failover. The following scenario describes a failover to the remote database called DR_Sales.

Note: If fast-start failover is enabled, you can perform a manual failover only to the standby database that was specified as the target of a fast-start failover and only when the observer is running.

If you want to perform a manual failover to a standby database that is not the fast-start failover target standby database, you must first disable fast-start failover using the `FORCE` option on the standby database you want to fail over. See [Section 5.5.5, "Disabling Fast-Start Failover"](#) for more information about the `FORCE` option.

Step 1 Connect to the target standby database.

To perform the failover operation, you must connect to the standby database to which you want to fail over to as a user that has the `SYSDBA` privilege. For example:

```
DGMGRL> CONNECT sys@DR_Sales.foo.com;
Password: password
Connected.
```

Step 2 Issue the failover command.

Now you can issue the failover command to make the target standby database the new primary database for the configuration. Note that after the failover completes, the original primary database cannot be used as a standby database of the new primary database unless it is reenabled (as described in [Section 5.4.3](#)).

Step 3 Show the configuration.

Issue the `SHOW CONFIGURATION` command to verify the failover.

```
DGMGRL> SHOW CONFIGURATION;

Configuration
Name:                DRSolution
Enabled:             YES
Protection Mode:    MaxAvailability
Databases:
  DR_Sales           - Primary database
  North_Sales        - Physical standby database (disabled)

Fast-Start Failover: DISABLED

Current status for "DRSolution":
Warning: ORA-16608: one or more databases have warnings
```

Note that in this example, the configuration was operating in maximum availability mode. The protection mode was preserved after the failover. The configuration also has a warning status. If you show the `StatusReport` monitorable database property of the new primary, you will see that the warning is the result of not having an enabled physical standby database. As a result, the warning status indicates that the protection level of the configuration is not the same as the configured mode.

Step 4 Show StatusReport property of the new primary database.

```
DGMGRL> SHOW DATABASE 'DR_Sales' StatusReport;
STATUS REPORT
      INSTANCE_NAME  SEVERITY ERROR_TEXT
                *    WARNING ORA-16629: database reports a different protection
level from the protection mode
```

Step 5 Show the database.

Issue the `SHOW DATABASE` command to see that the former (failed) primary database was disabled by the broker as a consequence of the failover. It must be reenabled (as described in [Section 5.4.3](#)).

```
DGMGRL> SHOW DATABASE 'North_Sales';

Database
Name:          North_Sales
Role:          PHYSICAL STANDBY
Enabled:       NO
Intended State: APPLY-ON
Instance(s):
sales1

Current status for "North_Sales":
Error: ORA-16661: the standby database needs to be reinstated
```

7.10 Scenario 9: Reinstating a Failed Primary Database

If your primary database had been configured with Flashback Database, you can easily reinstate the failed primary database as a standby database of the new primary database. The failed primary database will be reinstated as a standby type that matches the old standby database. For example, if you failed over to a physical standby database, the old primary will be reinstated as a physical standby database.

To reinstate the failed primary database, start it to the mounted state. Then run `DGMGRL`, connect to the new primary database and reinstate the old primary database.

Step 1 Restart the Old Primary Database.

```
% sqlplus sys as sysdba
Enter password: password

SQL> STARTUP MOUNT;
ORACLE instance started.

Total System Global Area 234364928 bytes
Fixed Size                 1296352 bytes
Variable Size              209717280 bytes
Database Buffers           16777216 bytes
Redo Buffers                6574080 bytes
Database mounted.
```

Step 2 Reinstat the old primary database.

```
% dgmgrl connect sys
Password: password
Connected.
DGMGRL> REINSTATE DATABASE 'North_Sales';
Reinstating database "North_Sales", please wait...
Operation requires shutdown of instance "sales1" on database "North_Sales"
Shutting down instance "sales1"...
ORA-01109: database not open

Database dismounted.
ORACLE instance shut down.
Operation requires startup of instance "sales1" on database "North_Sales"
Starting instance "sales1"...
ORACLE instance started.
Database mounted.
Continuing to reinstate database "North_Sales" ...
Reinstatement of database "North_Sales" succeeded
```

After the primary has been reinstated, issue the `SHOW CONFIGURATION` and `SHOW DATABASE` commands to confirm that the old primary has been successfully reinstated.

Step 3 Show the Configuration and Databases.

```
DGMGRL> SHOW CONFIGURATION;

Configuration
Name:          DRSolution
Enabled:       YES
Protection Mode: MaxAvailability
Databases:
  DR_Sales     - Primary database
  North_Sales  - Physical standby database

Fast-Start Failover: DISABLED

Current status for "DRSolution":
SUCCESS

DGMGRL> SHOW DATABASE 'DR_Sales';

Database
Name:          DR_Sales
Role:          PRIMARY
Enabled:       YES
Intended State: TRANSPORT-ON
Instance(s):
  dr_sales1

Current status for "DR_Sales":
SUCCESS

DGMGRL> SHOW DATABASE 'North_Sales';

Database
Name:          North_Sales
Role:          PHYSICAL STANDBY
Enabled:       YES
Intended State: APPLY-ON
```

```
Instance(s):
  sales1

Current status for "North_Sales":
SUCCESS
```

7.11 Scenario 10: Converting a Physical Standby to a Snapshot Standby

If you have a physical standby database that you would like to convert to a snapshot standby database, use the `DGMGRL CONVERT DATABASE` command. Redo data will continue to be received by the database while it is operating as a snapshot standby database, but it will not be applied until the snapshot standby is converted back into a physical standby database.

Note that the Flashback Database feature is required to create a snapshot standby database. If Flashback database is disabled, it is automatically enabled during conversion to a snapshot standby database. The broker automatically restarts the database to the mounted state if it had been opened with Flashback Database disabled. No user action is required.

```
DGMGRL> CONVERT DATABASE 'DR_Sales' to SNAPSHOT STANDBY;
Converting database "DR_Sales" to a Snapshot Standby database, please wait...
Database "DR_Sales" converted successfully
```

```
DGMGRL> SHOW CONFIGURATION;
Configuration
Name: DRSolution
Enabled: YES
Protection Mode: MaxPerformance
Databases:
North_Sales - Primary database
DR_Sales - Snapshot standby database
Fast-Start Failover: DISABLED
Current status for "DRSolution":
SUCCESS
```

When you are ready to revert the database back to a physical standby database, use the `DGMGRL CONVERT DATABASE` command again as follows. Any updates made to the database while it was operating as a snapshot standby database will be discarded. All accumulated redo data will be applied by Redo Apply services after the database is converted back to a physical standby database.

```
DGMGRL> CONVERT DATABASE 'DR_Sales' to PHYSICAL STANDBY;
Converting database "DR_Sales" to a Physical Standby database, please wait...
Operation requires shutdown of instance "dr_sales1" on database "DR_Sales"
Shutting down instance "dr_sales1"...
Database closed.
Database dismounted.
ORACLE instance shut down.
Operation requires startup of instance "dr_sales1" on database "DR_Sales"
Starting instance "dr_sales1"...
ORACLE instance started.
Database mounted.
Continuing to convert database "DR_Sales" ...
Operation requires shutdown of instance "dr_sales1" on database "DR_Sales"
Shutting down instance "dr_sales1"...
ORA-01109: database not open
Database dismounted.
ORACLE instance shut down.
Operation requires startup of instance "dr_sales1" on database "DR_Sales"
```

```
Starting instance "dr_sales1"...  
ORACLE instance started.  
Database mounted.  
Database "DR_Sales" converted successfully
```

7.12 Scenario 11: Monitoring a Data Guard Configuration

The scenario in this section demonstrates how to use the `SHOW` command and monitorable database properties to identify and resolve a failure situation.

Step 1 Check the configuration status.

The status of the broker configuration is an aggregated status of all databases and instances in the broker configuration. You can check the configuration status first to determine whether or not any further action needs to be taken. If the configuration status is `SUCCESS`, everything in the broker configuration is working fine. However, if you see the following error, it means something is wrong in the configuration:

```
DGMGRL> SHOW CONFIGURATION;  
Configuration  
Name:                DRSolution  
Enabled:             NO  
Protection Mode:    MaxPerformance  
Fast-Start Failover: DISABLED  
Databases:  
  North_Sales - Primary database  
  DR_Sales    - Physical standby database
```

```
Current status for "DRSolution":  
Warning: ORA-16607: one or more databases have failed
```

In this case, you need to continue on to Step 2 to determine the actual failure.

Step 2 Check the database status.

To identify which database has the failure, you need to go through all of the databases in the configuration one by one. In this example, the error happens to be on the primary database `North_Sales`:

```
DGMGRL> SHOW DATABASE 'North_Sales';
```

The command returns the following output:

```
Database  
Name:                North_Sales  
Role:                PRIMARY  
Enabled:             YES  
Intended State:     TRANSPORT-ON  
Instance(s):  
  sales1
```

```
Current status for "North_Sales":  
Error: ORA-16810: multiple errors or warnings detected for the database
```

Step 3 Check the StatusReport monitorable database property.

When you see message `ORA-16810`, you can use the `StatusReport` monitorable database property to identify each of the errors or warnings:

```
DGMGRL> SHOW DATABASE 'North_Sales' 'StatusReport';  
STATUS REPORT  
  INSTANCE_NAME  SEVERITY  ERROR_TEXT
```



```

sales1      ERROR ORA-16737: the redo transport service for
standby "DR_Sales" has an error
sales1      WARNING ORA-16714: the value of property
LogArchiveTrace is inconsistent with the database setting
sales1      WARNING ORA-16715: redo transport-related property
ReopenSecs of standby database "DR_Sales" is inconsistent

```

Step 4 Check the LogXptStatus monitorable database property.

You see error ORA-16737 in the previous status report in Step 3. To identify the exact log transport error, you can use LogXptStatus monitorable database property:

```

DGMGRL> SHOW DATABASE 'North_Sales' 'LogXptStatus';
LOG TRANSPORT STATUS
PRIMARY_INSTANCE_NAME STANDBY_DATABASE_NAME          STATUS
sales1                DR_Sales ORA-12541: TNS:no listener

```

Now you know the exact reason why redo transport services failed. To fix this error, start the listener for the physical standby database DR_Sales.

Step 5 Check the InconsistentProperties monitorable database property.

You also see warning ORA-16714 reported in Step 3. To identify the inconsistent values for property LogArchiveTrace, you can use the InconsistentProperties monitorable database property:

```

DGMGRL> SHOW DATABASE 'North_Sales' 'InconsistentProperties';

INCONSISTENT PROPERTIES
INSTANCE_NAME  PROPERTY_NAME  MEMORY_VALUE  SPFILE_VALUE  BROKER_VALUE
sales1        LogArchiveTrace    255           0             0

```

It seems that the current database memory value (255) is different from both the server parameter file (SPFILE) value (0) and Data Guard broker's property value (0). If you decide the database memory value is correct, you can update Data Guard broker's property value using the following command:

```

DGMGRL> EDIT DATABASE 'North_Sales' SET PROPERTY 'LogArchiveTrace'=255;
Property "LogArchiveTrace" updated

```

In the previous command, Data Guard broker also updates the spfile value for you so that value for LogArchiveTrace is kept consistent.

Step 6 Check the InconsistentLogXptProps monitorable database property.

Another warning you see in the status report returned in Step 3 is ORA-16715. To identify the inconsistent values for the redo transport configurable database property, ReopenSecs, you can use the InconsistentLogXptProps monitorable database property.

```

DGMGRL> SHOW DATABASE 'North_Sales' 'InconsistentLogXptProps';

INCONSISTENT LOG TRANSPORT PROPERTIES
INSTANCE_NAME  STANDBY_NAME  PROPERTY_NAME  MEMORY_VALUE  BROKER_VALUE
sales1        DR_Sales      ReopenSecs    600           300

```

The current database memory value (600) is different from the Data Guard broker's property value (300). If you think the broker's property value is correct, you can fix the inconsistency by re-editing the property of the standby database with the same value, as shown in the following example:

```

DGMGRL> EDIT DATABASE 'DR_Sales' SET PROPERTY 'ReopenSecs'=300;
Property "ReopenSecs" updated

```

You can also reenble the standby database or reset the primary database state to `TRANSPORT-ON` to fix the inconsistency, but re-editing the property is the simplest.

Data Guard Command-Line Interface Reference

The Data Guard command-line interface (DGMGRL) enables you to manage a Data Guard broker configuration and its databases directly from the command line, or from batch programs or scripts. You can use the Data Guard command-line interface as an alternative to Oracle Enterprise Manager for managing a Data Guard configuration.

This chapter contains the following sections, which provide reference information for the Data Guard command-line interface:

- [Starting the Data Guard Command-Line Interface](#)
- [Exiting the Data Guard Command-Line Interface](#)

8.1 Starting the Data Guard Command-Line Interface

To run DGMGRL, you must have SYSDBA privileges.

Start the command-line interface by entering `dgmgrl` at the command-line prompt on a system where Oracle is installed:

```
% dgmgrl

DGMGRL for Linux: Version 11.1.0.7.0 - Production

Copyright (c) 2000, 2005, Oracle. All rights reserved.

Welcome to DGMGRL, type "help" for information.

DGMGRL>
```

8.1.1 DGMGRL Optional Parameters

You can supply optional parameters on the command line to indicate how you want the Data Guard command-line interface to display output such as command prompts, banners, and messages.

Additionally, a single command mode is available. In this mode, DGMGRL executes one command and exits upon the completion of the command. The exit code is the result of the command. If the exit code is 0, the command completed successfully. Otherwise, there was an error.

The command line of DGMGRL appears as follows:

```
% dgmgrl [<options>] [<logon> [<command>] ]
```

Specify any of the following keywords when you invoke the DGMGRL command-line interface:

- `<options>` can be one of the following choices:
 - `-echo`
Displays command input and output to the default display device. If you do not use this parameter, only the output from the command is displayed.
 - `-logfile <file-spec> "<dgmgrl-command>"`
Specifies a file into which you can capture the actions of the DGMGRL command-line interface. This is particularly useful when DGMGRL is being invoked to serve as the fast-start failover *observer*. See the ["START OBSERVER"](#) command for more information.

See Also:

- The ["START OBSERVER"](#) command
- [Section 10.5.3, "Capturing Observer Actions in the Observer Log File"](#)
- `-silent`
Suppresses the display of the DGMGRL (`DGMGRL>`) command prompt on your default display device. This option is useful if you are directing the command output to a file or to another display tool.
- `<logon>` is:
 - `username [@connect-identifier]`
To connect to the database, enter a username and optionally, a `connect-identifier`. You will then be prompted for a password. The `connect-identifier` is a fully specified connect descriptor or a name to be resolved by an Oracle naming method (for example, TNS).

WARNING: Including a password on the command line when invoking DGMGRL is a security risk. This risk can be avoided either by omitting the password when invoking DGMGRL and entering it when prompted, or by using an external authentication method.

- You can connect as `'/'` when using operating-system authentication (remote database restarts will not work), SSL, or database credentials stored in a wallet.
- `<command>` is a single command.

For example:

```
% dgmgrl sys/ "show database 'North_Sales'"
Password: password
```

The following subsections specify the command format that you enter at the `DGMGRL>` command prompt.

8.1.2 DGMGRL Command Format and Parameters

The DGMGRL commands allow you to create and maintain one broker configuration at a time. A broker configuration can consist of a primary database and up to 9 standby databases.

After you invoke the command-line interface, you can enter any of the DGMGRL commands listed in [Table 8–1](#). Each command and its associated parameters are described in detail in later sections of this chapter.

Table 8–1 Summary of DGMGRL Commands

Command	Effect
ADD DATABASE	Adds a new standby database profile to the existing broker configuration.
CONNECT	Connects to the specified database using the specified username.
CONVERT DATABASE	Converts the specified database to either a snapshot standby database or a physical standby database.
CREATE CONFIGURATION	Creates a broker configuration and adds a primary database profile to the configuration.
DISABLE CONFIGURATION	Disables broker management of a configuration so that the configuration and all of its databases are no longer managed by the broker.
DISABLE DATABASE	Disables broker management of the named standby database.
DISABLE FAST_START FAILOVER	Disables fast-start failover.
DISABLE FAST_START FAILOVER CONDITION	Allows a user to remove conditions for which a fast-start failover should be performed.
EDIT CONFIGURATION (Property)	Changes the value of a property for the broker configuration.
EDIT CONFIGURATION (Protection Mode)	Changes the current protection mode setting for the broker configuration.
EDIT DATABASE (Property)	Changes the value of a property for the named database.
EDIT DATABASE (Rename)	Changes the name used by the broker to refer to the specified database.
EDIT DATABASE (State)	Changes the state of the specified database.
EDIT INSTANCE (AUTO PFILE)	Sets the name of the initialization parameter file for the specified instance.
EDIT INSTANCE (Property)	Changes the value of a property for the specified instance.
ENABLE CONFIGURATION	Enables broker management of the broker configuration and all of its databases.
ENABLE DATABASE	Enables broker management of the specified database.
ENABLE FAST_START FAILOVER	Enables the broker to automatically failover from the primary database to a target standby database.
ENABLE FAST_START FAILOVER CONDITION	Allows a user to add conditions for which a fast-start failover should be performed.
EXIT	Exits the Data Guard command-line interface.
FAILOVER	Performs a database failover operation in which the standby database, to which DGMGRL is currently connected, fails over to the role of primary database.

Table 8–1 (Cont.) Summary of DGMGRL Commands

Command	Effect
HELP	Displays online help for the Data Guard command-line interface.
QUIT	Quits the Data Guard command-line interface.
REINSTATE DATABASE	Reinstates the database after a failover.
REMOVE CONFIGURATION	Removes the broker configuration including all of its database profiles from the broker configuration file.
REMOVE DATABASE	Removes the specified standby database profile from the broker configuration.
REMOVE INSTANCE	Removes knowledge of an instance from an existing database profile in the broker configuration.
SHOW CONFIGURATION	Displays information about the broker configuration.
SHOW DATABASE	Displays information about the specified database.
SHOW FAST_START FAILOVER	Displays all fast-start failover related information.
SHOW INSTANCE	Displays information about the specified instance.
SHUTDOWN	Shuts down a currently running Oracle database.
START OBSERVER	Starts the observer.
STARTUP	Starts an Oracle instance with the same options as SQL*Plus, including mounting and opening a database.
STOP OBSERVER	Stops the observer.
SWITCHOVER	Performs a switchover operation in which the current primary database becomes a standby database, and the specified standby database becomes the primary database.

8.1.3 DGMGRL Command Usage Notes

To use DGMGRL, the following must be true:

- The `DG_BROKER_START` dynamic initialization parameter is set to `TRUE`.
- To enable broker operations that require restarting instances without manual intervention, Oracle Net Services must be configured on each of the hosts that contain the primary and standby database instances. Specifically, the `listener.ora` file must contain static configuration information about the instance. The `GLOBAL_DBNAME` attribute must be set to `db_unique_name_DGMGRL.db_domain`. See [Section 2.2](#) for additional information.
- The Connect Identifier used while creating the configuration or adding a database, must be resolvable from any of the hosts in the configuration.

See Also: [Chapter 7](#) for more information about preparing and starting Oracle Data Guard broker. See the *Oracle Database Administrator's Guide* for more information about setting up the network files and listener on the standby database.

- You must have `SYSDBA` privileges to use the Data Guard command-line interface. Do not include `AS SYSDBA` on the `CONNECT` command because `SYSDBA` is the default setting for this command.

- If you specify more than one option on the command, you can specify the options in any order.
- A semicolon is required at the end of each DGMGRL command.
- Characters specified in a DGMGRL command string value are interpreted as lowercase characters, unless enclosed in double (") or single (') quotation marks. For example, database and DatAbaSe are equivalent, but "database" and "DatAbaSe" are not.
- You can use the backslash (\) to escape a single quotation mark ('), a double quotation mark ("), and the backslash character (\) itself if these characters appear in a character string.
- Some operations on a broker configuration may require that one or more databases be shut down and restarted. In most cases, DGMGRL will automatically shut down and restart a given database for you if the following are true:
 - The *instance-name* is the SID (this applies to Enterprise Manager as well as DGMGRL).
 - The broker must be able to connect to the database using the same credentials given in the last CONNECT command, even if the last CONNECT command was used to connect to another database.

Command Examples

Example 1

This example demonstrates how to connect to the DGMGRL command-line interface on a local system.

```
% dgmgrl

DGMGRL for Linux: Version 11.1.0.7.0 - Production

Copyright (c) 2000, 2005, Oracle. All rights reserved.

Welcome to DGMGRL, type "help" for information.

DGMGRL> CONNECT sys;
Password: password
Connected.
```

Example 2

This example demonstrates how to connect to the Data Guard (DGMGRL) command-line interface on a remote system.

```
DGMGRL> CONNECT sys@remote-stby;
Password: password
Connected.
```

8.2 Exiting the Data Guard Command-Line Interface

When you are done working with the command-line interface and want to return to the operating system, enter the EXIT or QUIT command at the DGMGRL command prompt. For example:

```
DGMGRL> EXIT;
```

ADD DATABASE

Creates a new standby database profile and adds it to the existing broker configuration. The `AS CONNECT IDENTIFIER` clause is optional. If you do not specify this clause, the broker will search the `LOG_ARCHIVE_DEST_n` initialization parameters on the primary database for an entry that corresponds to the database being added.

The `MAINTAINED AS` clause allows you the option of specifying the standby database type. Otherwise, the broker automatically determines whether the standby database type is a physical, logical, or snapshot standby database.

Format

```
ADD DATABASE database-name
[AS CONNECT IDENTIFIER IS connect-identifier]
```

Command Parameters

database-name

The name that will be used by the broker to refer to this standby database. It must match (case-insensitive) the value of the corresponding database `DB_UNIQUE_NAME` initialization parameter.

connect-identifier

A fully specified connect descriptor or a name to be resolved by an Oracle Net Services naming method (for example, TNS). The value you specify is also used as the initial value of the `DGConnectIdentifier` configurable database property. If you do not specify this option, the broker will search the primary database `LOG_ARCHIVE_DEST_n` parameters for a corresponding entry to the standby database and use its `SERVICE` value for the connect-identifier.

Usage Notes

- To issue this command, you must connect to the primary database or to an enabled standby database that is already in the configuration.
- The broker uses the specified `connect-identifier` to communicate with the specified database from other databases. Therefore, you must ensure that the `connect-identifier` can be used to address the specified database from all databases in your configuration. For example, if you use `tnsnames.ora` files to resolve the `connect-identifier`, you must ensure it will be resolved to the same connect descriptor in all `tnsnames.ora` files and the resulting connect descriptor can be used to reach the database specified in this `ADD DATABASE` command. If the database that is being added is an Oracle RAC database, the `connect-identifier` provided here must reach all instances of the RAC, preferably with `FAILOVER` attributes set.

See Also: *Oracle Database Net Services Administrator's Guide*

- If the connection cannot be made, the broker does not add the new database to the configuration.
- The `MAINTAINED AS` clause is deprecated in this release. The broker will determine standby database type automatically.

Command Example

Example 1

The following example shows how to add a database named DR_Sales.

```
DGMGRL> ADD DATABASE DR_Sales AS CONNECT IDENTIFIER IS DR_Sales.foo.com;  
Database "DR_Sales" added
```

CONNECT

Connects a given username to the specified database.

Format

```
CONNECT username [@connect-identifier];
```

Command Parameters

username

Represents the username with which you want to connect to the database. You will be prompted for a password after you enter a username and optionally, a connect-identifier.

connect-identifier

This parameter is optional. It consists of the Oracle Net Services connect identifier of the database to which you want to connect. The exact syntax depends upon the Oracle Net Services communications protocol your Oracle installation uses.

Usage Notes

- The username and password must be valid for the database to which you are trying to connect. The username you specify must have the SYSDBA privilege. You do not have to include AS SYSDBA on the CONNECT command because SYSDBA is the default setting for this command.
- If the CONNECT command returns an error, check to see that you specified a valid connect-identifier.

Command Examples

Example 1

This example connects to the default database on the local system.

```
DGMGRL> CONNECT sys;  
Password: password  
Connected.
```

Example 2

This example connects to a remote database whose connect-identifier is North_Sales.foo.com.

```
DGMGRL> CONNECT sys@North_Sales.foo.com;  
Password: password  
Connected.
```

Example 3

This example connects to a database using CONNECT '/' so that connection credentials are not visible on the command line:

```
DGMGRL> CONNECT /@North_Sales.foo.com;
```

You must set up Oracle Wallet to use CONNECT '/'. By setting up Oracle Wallet, you can write a script to securely start and run the observer as a background job without specifying database credentials in the script.

See Also: *Oracle Database Advanced Security Administrator's Guide* for more information about Oracle Wallet

CONVERT DATABASE

Converts a physical standby database to a snapshot standby database, or reverts the snapshot standby database back to a physical standby database.

A snapshot standby database is a fully updatable standby database that is created by converting a physical standby database into a snapshot standby database. Like a physical or logical standby database, a snapshot standby database receives and archives redo data from a primary database. Unlike a physical or logical standby database, a snapshot standby database does not apply the redo data that it receives. The redo data received by a snapshot standby database is not applied until the snapshot standby is converted back into a physical standby database, after first discarding any local updates made to the snapshot standby database.

A snapshot standby database is best used in scenarios that require a temporary, updatable snapshot of a physical standby database. Note that because redo data received by a snapshot standby database is not applied until it is converted back into a physical standby, the time needed to perform a role transition is directly proportional to the amount of redo data that needs to be applied.

See *Oracle Data Guard Concepts and Administration* for additional information about snapshot standby databases.

Format

```
CONVERT DATABASE db_unique_name TO {SNAPSHOT | PHYSICAL} STANDBY;
```

Usage Notes

- A physical standby database cannot be converted to a snapshot standby database if it is the target of a fast-start failover. The ORA-16420: Fast-Start Failover (FSFO) target cannot be converted to snapshot standby error will be returned.
- Use the DGMGRL [ADD DATABASE](#) command to import an existing snapshot standby database into a Data Guard broker configuration.
- A snapshot standby database cannot be the target of a switchover or a fast-start failover.
- A snapshot standby database can be the target of a manual failover if fast-start failover is disabled.
- You can use the SHOW CONFIGURATION or SHOW DATABASE command to verify the conversion result. For example:

```
DGMGRL> SHOW CONFIGURATION;

Configuration
Name:          DRSolution
Enabled:       YES
Protection Mode:  MaxPerformance
Databases:
  North_Sales  - Primary database
  DR_Sales     - Snapshot standby database

Fast-Start Failover: DISABLED
Current status for "DRSolution":
SUCCESS
```

- After a snapshot standby database is converted back to a physical standby database, it will be in the default state for a physical standby database, APPLY-ON.

Command Examples

Example 1

Issue the following to convert a physical standby database to a snapshot standby database:

```
DGMGRL> CONVERT DATABASE 'DR_Sales' to SNAPSHOT STANDBY;
Converting database "DR_Sales" to a Snapshot Standby database, please wait...
Database "DR_Sales" converted successfully
```

Example 2

Issue the following to convert the snapshot standby database back to a physical standby database:

```
DGMGRL> CONVERT DATABASE 'DR_Sales' to PHYSICAL STANDBY;
Converting database "DR_Sales" to a Physical Standby database, please wait...
Operation requires shutdown of instance "dr_sales1" on database "DR_Sales"
Shutting down instance "dr_sales1"...
Database closed.
Database dismounted.
ORACLE instance shut down.
Operation requires startup of instance "dr_sales1" on database "DR_Sales"
Starting instance "dr_sales1"...
ORACLE instance started.
Database mounted.
Continuing to convert database "DR_Sales" ...
Operation requires shutdown of instance "dr_sales1" on database "DR_Sales"
Shutting down instance "dr_sales1"...
ORA-01109: database not open

Database dismounted.
ORACLE instance shut down.
Operation requires startup of instance "dr_sales1" on database "DR_Sales"
Starting instance "dr_sales1"...
ORACLE instance started.
Database mounted.
Database "DR_Sales" converted successfully
```

CREATE CONFIGURATION

Creates a new broker configuration and adds a primary database profile to the configuration.

Format

```
CREATE CONFIGURATION configuration-name AS  
PRIMARY DATABASE IS database-name  
CONNECT IDENTIFIER IS connect-identifier;
```

Command Parameters

configuration-name

A user-friendly name for the configuration you are creating. Valid names contain any alphanumeric characters. If spaces are included in the name, the name must be enclosed in double or single quotation marks. The name must consist of 30 or fewer bytes.

database-name

The name that will be used by the broker to refer to the primary database. It must match (case-insensitive) the value of the corresponding database `DB_UNIQUE_NAME` initialization parameter.

connect-identifier

A fully specified connect descriptor or a name to be resolved by an Oracle Net Services naming method (for example, TNS). The value you specify is also used as the initial value of the `DGConnectIdentifier` configurable database property.

Usage Notes

- A broker configuration is a named collection of one or more databases that you want to manage as a group. You must specify a value for each of the command parameters. There are no default values.
- You must connect to the primary database to issue this command.
- The broker uses the specified `connect-identifier` to communicate with the specified database from other databases. Therefore, you must ensure that the `connect-identifier` can be used to address the specified database from all other databases in your configuration. For example, if you use `tnsnames.ora` files to resolve the `connect-identifier`, you must ensure it will be resolved to the same connect descriptor in all `tnsnames.ora` files and the resulting connect descriptor can be used to reach the primary database specified in this `CREATE CONFIGURATION` command.
- To add standby databases after you create the broker configuration, use the [ADD DATABASE](#) command.

Command Example

Example 1

The following example creates a new broker configuration named `DRSolution` with a primary database named `North_Sales`.

```
DGMGRL> CREATE CONFIGURATION 'DRSolution' AS
> PRIMARY DATABASE IS 'North_Sales'
> CONNECT IDENTIFIER IS North_Sales.foo.com;
Configuration "DRSolution" created with primary database "North_Sales"
```

DISABLE CONFIGURATION

Disables broker management of a configuration so that the configuration and all of its databases are no longer managed by the broker.

Format

```
DISABLE CONFIGURATION;
```

Command Parameters

None.

Usage Notes

- A disabled configuration and all of its constituent databases are no longer managed by the broker.
- The only way to disable broker management of the primary database is to use the `DISABLE CONFIGURATION` command.
- This command does not remove the broker configuration from the configuration file. See the [REMOVE CONFIGURATION](#) command for more information about removing the configuration.
- You can edit database properties and modify the configuration's protection mode while the configuration is disabled. However, any changes made to properties or to the protection mode will not take effect until the configuration is enabled.
- This command cannot be executed if fast-start failover is enabled.

Command Example

Example 1

The following example disables management of the broker configuration and all of its databases.

```
DGMGRL> DISABLE CONFIGURATION;  
Disabled.
```


DISABLE DATABASE

Disables broker management of the named standby database. This means that broker directed state changes will be disallowed for this database, and the broker will not monitor the database for health status or for monitorable database properties.

Format

```
DISABLE DATABASE database-name;
```

Command Parameter

database-name

Name of the standby database to be disabled.

Usage Notes

- You cannot specify the name of a primary database.
- Use the `DISABLE CONFIGURATION` command to disable the primary and all standby databases.
- If the sole standby database is disabled, you have no failover option. This standby database is not viable for failover until it is reenabled.
- This command cannot be used to disable the fast-start failover target database when fast-start failover is enabled.

Command Example

Example 1

The following example shows how to disable a database named `DR_Sales`.

```
DGMGRL> DISABLE DATABASE 'DR_Sales';  
Disabled.
```

DISABLE FAST_START FAILOVER

Disables fast-start failover and prevents the observer from initiating a failover to the target standby database. See [Section 5.5.5, "Disabling Fast-Start Failover"](#) for additional information.

Format

```
DISABLE FAST_START FAILOVER [ FORCE ];
```

Command Parameters

None.

Usage Notes

- If the primary and target standby database have a network connection, use `DISABLE FAST_START FAILOVER` *without* the `FORCE` option to disable fast-start failover on all databases in the broker configuration. If errors occur during the disable operation, the broker returns an error message and stops the disable operation. You may need to reissue the `DISABLE FAST_START FAILOVER` command with the `FORCE` option to override the error conditions and disable fast-start failover on the database to which you are connected. See [Section 5.5.5, "Disabling Fast-Start Failover"](#) for more information.
- Use `DISABLE FAST_START FAILOVER` *with* the `FORCE` option when the network between the primary and target standby databases is disconnected or when the database upon which the command is received does not have a connection with the primary database. The `FORCE` option disables fast-start failover on the database to which you are connected, even when errors occur.
- Disabling fast-start failover with the `FORCE` option on a primary database that is disconnected from the observer and the target standby database does not prevent the observer from initiating a fast-start failover to the target standby database.
- You can disable fast-start failover while connected to any database in the broker configuration.
- If disabled by force at the target standby database and the connection subsequently resumes with the primary database, fast-start failover is disabled on all databases in the configuration.
- Disabling fast-start failover with the `FORCE` option will disable fast-start failover on the target standby database if there is network connectivity between both databases.

Command Example

Example 1

The following example shows how to disable fast-start failover.

```
DGMGRL> DISABLE FAST_START FAILOVER;  
Disabled.
```

DISABLE FAST_START FAILOVER CONDITION

Allows a user to remove conditions for which a fast-start failover should be performed.

Format

```
DISABLE FAST_START FAILOVER CONDITION value;
```

Command Parameters

value

Possible values are those described in the `SHOW FAST_START FAILOVER` command as Health Conditions or Oracle error numbers.

Usage Notes

An error will be raised if the condition is not recognized. If the condition has not been set, no error will be raised.

Command Example

Example 1

```
DISABLE FAST_START FAILOVER CONDITION "Corrupted Controlfile";
```

This specifies that the detection of a corrupted controlfile does not automatically initiate an immediate fast-start failover.

Example 2

```
DISABLE FAST_START FAILOVER CONDITION 27102;
```

This specifies that the ORA-27102 error does not automatically initiate an immediate fast-start failover.

EDIT CONFIGURATION (Property)

Changes the value of a property for the broker configuration.

Format

```
EDIT CONFIGURATION SET PROPERTY property-name = value;
```

Command Parameter

property-name

The name of a configuration property.

value

The new value for the property.

See Also: [Chapter 4](#) and [Chapter 9](#) for information about configuration properties

Usage Notes

- Issue this command while connected to the primary database or to any standby database in the broker configuration having connectivity to the primary database.
- Use the `SHOW CONFIGURATION` command to display the current property information for the configuration.

Command Example

Example 1

The following example shows how to set the `FastStartFailoverThreshold` configuration property to 90 seconds.

```
DGMGRL> EDIT CONFIGURATION SET PROPERTY FastStartFailoverThresdhold=90;
```

EDIT CONFIGURATION (Protection Mode)

Edits the current protection mode setting for the broker configuration.

Format

EDIT CONFIGURATION SET PROTECTION MODE AS *protection-mode*;

Command Parameter

protection-mode

The data protection mode in which you want the configuration to run when the configuration is enabled. The possible protection modes are:

MAXPROTECTION
MAXAVAILABILITY
MAXPERFORMANCE

Usage Notes

- Before you use the `EDIT CONFIGURATION` command to set the protection mode to either the `MAXPROTECTION` or `MAXAVAILABILITY` mode, ensure that at least one standby database has its `LogXptMode` configurable database property set to `SYNC`.
- The following table shows the configuration protection modes and the minimum corresponding settings for redo transport services:

Protection Mode	Redo Transport	Standby Redo Log Files Needed?	Usable with Fast-Start Failover?
MAXPROTECTION	SYNC	Yes	No
MAXAVAILABILITY	SYNC	Yes	Yes
MAXPERFORMANCE	ASync	Yes	Yes

The default protection mode for the configuration is `MAXPERFORMANCE`.

See Also: [Chapter 4](#) for more information about the protection modes and redo transport services

- `MAXAVAILABILITY` or `MAXPERFORMANCE` is required in order to enable fast-start failover.
- This command cannot be executed if fast-start failover is enabled.
- After you change the protection mode, the broker will automatically restart the primary database, if necessary.
- Use the `SHOW CONFIGURATION` command to display the current protection mode for the configuration.

```
DGMGR> SHOW CONFIGURATION;
```

```
Configuration
Name:                DRSolution
Enabled:             YES
Protection Mode:     MaxPerformance
```

```
Databases:
  North_Sales - Primary database
  DR_Sales    - Physical standby database
```

```
Fast-Start Failover: DISABLED
```

```
Current status for "DRSolution":
SUCCESS
```

If broker management of the configuration is disabled when you enter the `EDIT CONFIGURATION` command, the protection mode of the configuration does not take effect until the next time you enable the configuration with the [ENABLE CONFIGURATION](#) command.

Command Example

Example 1

The following example shows how to upgrade the broker configuration to the `MAXAVAILABILITY` protection mode.

Verify that standby redo log files are configured on the standby database and that the redo transport service is set to `SYNC`, for example:

```
DGMGRL> EDIT DATABASE 'DR_Sales' SET PROPERTY 'LogXptMode'='SYNC';
Property "LogXptMode" updated
```

```
DGMGRL> EDIT CONFIGURATION SET PROTECTION MODE AS MAXAVAILABILITY;
Succeeded.
```

EDIT DATABASE (Property)

Changes the value of a property for the named database.

Format

```
EDIT DATABASE database-name
SET PROPERTY property-name = value;
```

Command Parameters

database-name

The name of the database for which you want to change a property value.

property-name

The name of an existing database-specific property. If this is an Oracle RAC database, this property change affects all instances of the database.

See Also: [Chapter 4](#) and [Chapter 9](#) for information about properties.

value

The new value for the property.

Caution: This command can be used to change the value of a per-instance property if and only if just one instance is known by the broker for the named database. An attempt to use this command to change a per-instance property when the broker knows of multiple instances of the database will be rejected. It is recommended to only use `EDIT INSTANCE (property)` to change the value of a per-instance property.

Command Examples

Example 1

Edit a configurable database property at the database level.

```
DGMGRL> EDIT DATABASE 'North_Sales' SET PROPERTY 'ArchiveLagTarget'=1200;
Property "ArchiveLagTarget" updated
```

Example 2

Edit a configurable database property of a non-RAC database, at the instance level.

```
DGMGRL> EDIT DATABASE 'DR_Sales' SET PROPERTY
> 'StandbyArchiveLocation'='/archfs/arch/';
Property "StandbyArchiveLocation" updated
```

Example 3

Edit an instance level property of an Oracle RAC database. This will not succeed because it is not clear to which instance the property change should be applied.

```
DGMGRL> EDIT DATABASE 'North_Sales' SET PROPERTY
> 'StandbyArchiveLocation'='/archfs/arch/';
```

Error: ORA-16587: ambiguous object specified to Data Guard broker

Failed.

EDIT DATABASE (Rename)

Changes the name used by the broker to refer to the specified database, as recorded in that database's profile in the broker configuration.

Format

```
EDIT DATABASE database-name  
  RENAME TO new-database-name;
```

Command Parameters

database-name

The name of the database that you want to change.

new-database-name

The name of the new database.

Usage Notes

- Use this command to track changes to the DB_UNIQUE_NAME initialization parameter for this database.

Caution: The *database-name* must always match the value for that database's DB_UNIQUE_NAME initialization parameter.

- This command can only be done when broker management of the database that you are renaming is disabled.

Command Example

Example 1

The following example shows how to edit and rename a database.

```
DGMGRL> DISABLE DATABASE 'DR_Sales_typo';  
Disabled.
```

```
DGMGRL> EDIT DATABASE 'DR_Sales_typo' RENAME TO 'DR_Sales';  
Succeeded.
```

```
DGMGRL> ENABLE DATABASE 'DR_Sales';  
Enabled.
```

EDIT DATABASE (State)

Changes the state of the specified database.

Format

```
EDIT DATABASE database-name  
SET STATE = state  
[WITH APPLY INSTANCE = instance-name];
```

Command Parameters

database-name

The name of the database for which you want to change the state.

state

The state in which you want the database to be running. The possible states are:

TRANSPORT-ON (primary database only)
TRANSPORT-OFF (primary database only)
APPLY-ON (physical or logical standby database only)
APPLY-OFF (physical or logical standby database only)

instance-name

The name of the instance you want to become the apply instance if this is an Oracle RAC standby database.

Usage Notes

- If the target state is `APPLY-ON` and this database is currently a physical or logical standby database, the optional `WITH APPLY INSTANCE` clause specifies which instance will become the apply instance.
- If the target state is not `APPLY-ON` or if the database is currently in the primary role, the `WITH APPLY INSTANCE` clause is ignored even if it is specified.
- You cannot change the state of a snapshot standby database.
- All instances of an Oracle RAC database are affected by this database state change.

Command Example

The following examples show how to change the state of a database.

Example 1

```
DGMGRL> EDIT DATABASE 'DR_Sales' SET STATE='APPLY-ON';  
Succeeded.
```

EDIT INSTANCE (AUTO PFILE)

Sets the name of the initialization parameter file for the specified instance.

Format

```
EDIT INSTANCE instance-name
      [ON DATABASE database-name]
      SET AUTO PFILE [= { initialization-file | OFF }];
```

Command Parameters

instance-name

The name of the instance (SID) for which you want to specify its initialization parameter file.

database-name

The name of the database to which the *instance-name* is associated.

initialization-file

Executes the startup operation for the instance when a subsequent broker operation requires the instance to be started automatically. If SET AUTO PFILE is set to OFF, automatic restart of that instance is disabled. When a subsequent operation needs to start that instance, you must start it manually. If you do not specify SET AUTO PFILE for the instance, the automatic startup operation looks for the initialization parameter file at the default location.

Usage Notes

- The *instance-name* can be unique across the configuration. If *instance-name* is not unique, you must specify both the *database-name* and the *instance-name* to fully identify the instance.
- SET AUTO PFILE is valid only for the duration of the current DGMGRL session. You must specify SET AUTO PFILE again if you quit and reenter DGMGRL.

Command Example

Example 1

The following example shows how to edit an instance of a database.

```
DGMGRL> EDIT INSTANCE 'dr_sales1' ON DATABASE 'DR_Sales'
> SET AUTO PFILE='initsales1.ora';
Instance 'dr_sales1' updated
```

EDIT INSTANCE (Property)

Changes the value of a property for the specified instance.

Format

```
EDIT INSTANCE instance-name
[ON DATABASE database-name]
SET PROPERTY property-name = value;
```

Command Parameters

instance-name

The name of the instance (SID) for which you want to change a per-instance property value.

database-name

The name of the database to which the *instance-name* is associated.

property-name

The name of the per-instance property for which you want to set a new value.

See Also: [Chapter 4](#) and [Chapter 9](#) for information about properties.

value

The new value for the property.

Usage Notes

- The *instance-name* can be unique across the configuration. If *instance-name* is not unique, you must specify both the *database-name* and the *instance-name* to fully identify the instance.
- This command cannot be used to change a database-specific property.

Command Examples

Example 1

Edit an instance level property.

```
DGMGRL> EDIT INSTANCE 'sales1' ON DATABASE 'North_Sales'
> SET PROPERTY 'StandbyArchiveLocation'='/archfs/arch/';
Property "StandbyArchiveLocation" updated.
```

Example 2

Edit a database level property. This will not be allowed.

```
DGMGRL> EDIT INSTANCE 'sales1' ON DATABASE 'North_Sales'
> SET PROPERTY 'LogXptMode'='SYNC';
Error: ORA-16586: could not edit database property through instance
Failed.
```

ENABLE CONFIGURATION

Enables the broker to actively manage the broker configuration including all of its databases.

Format

```
ENABLE CONFIGURATION;
```

Command Parameters

None.

Usage Notes

- Use this command to enable broker management of the primary database and all standby databases, if these standby database are not explicitly disabled by the user.
- By default, broker management of the configuration's databases is enabled in the `TRANSPORT-ON` state with redo transport services turned on at the primary database and `APPLY-ON` with log apply services started at the standby databases. You can change the state of a database using the [EDIT DATABASE \(State\)](#) command, but not when the database or the entire configuration is disabled.
- Use the [SHOW CONFIGURATION](#) command to display information about the configuration.

Command Example

Example 1

The following example enables management of a broker configuration.

```
DGMGRL> ENABLE CONFIGURATION;  
Enabled.
```

ENABLE DATABASE

Enables broker management of the specified standby database.

Caution: Do not issue the `ENABLE DATABASE` command on a standby database that needs to be reinstated. See [Section 5.4.3](#) for more details.

Format

`ENABLE DATABASE database-name;`

Command Parameter

database-name

The name of the standby database for which you want to enable broker management.

Usage Notes

- A standby database may have been disabled by the broker as a consequence of a prior failover or switchover operation. See [Section 5.4.3](#) to understand how the database can be reenabled.
- By default, broker management of the physical or logical standby database is enabled in the `APPLY-ON` state with log apply services enabled. You can change the state of the standby database using the [EDIT DATABASE \(State\)](#) command, but only when the database is enabled.
- Use the [SHOW DATABASE](#) command to display information about the database.
- For an Oracle RAC database, only one instance is required to be started and mounted for this command to succeed.

Command Example

Example 1

The following example shows how to enable a database named `DR_Sales`.

```
DGMGRL> ENABLE DATABASE 'DR_Sales';  
Enabled.
```

ENABLE FAST_START FAILOVER

Enables the broker to fail over to a specifically-chosen standby database in the event of loss of the primary database, without requiring you to perform any manual steps to invoke the failover. See [Section 5.5.2, "Enabling Fast-Start Failover"](#) for complete information.

Format

```
ENABLE FAST_START FAILOVER;
```

Command Parameters

None.

Usage Notes

- The prerequisites described in [Section 5.5.1](#) must be met before you issue this command to enable fast-start failover.
- Issuing the `ENABLE FAST_START FAILOVER` command does not trigger a failover, it only allows the observer to monitor the configuration and initiate fast-start failover if conditions warrant a failover.
- You can enable fast-start failover while connected to any database in the broker configuration.
- If you do not start the observer after you have enabled fast-start failover, the `ORA-16819` warning displays for the primary and target standby databases. For example:

```
DGMGRL> SHOW DATABASE 'North_Sales';
Database
  Name:          North_Sales
  Role:          PRIMARY
  Enabled:       YES
  Intended State:  TRANSPORT-ON
  Instance(s):
    sales1
```

```
Current status for "North_Sales":
Warning: ORA-16819: fastsStart failover observer not started
```

- To enable fast-start failover for a broker configuration with multiple standby databases, the `FastStartFailoverTarget` configuration property on the primary database must be set to point to the desired target standby database. Both the primary database and the target standby database must have:
 - Standby redo logs configured
 - Either the `LogXptMode` configurable database property set to `SYNC` and protection mode set to `MAXAVAILABILITY`, or the `LogXptMode` property set to `ASYNCR` and the protection mode set to `MAXPERFORMANCE`
 - Flashback Database enabled on both the primary and standby databases
 Step 2 in [Section 5.5.2](#) and [Section 9.2.14](#) provide more information about the `FastStartFailoverTarget` configuration property.

- Once you have enabled fast-start failover, you must comply with the restrictions described in [Section 5.5.2.2, "Restrictions When Fast-Start Failover is Enabled"](#).

Command Example

Example 1

The following example enables fast-start failover.

```
DGMGRL> ENABLE FAST_START FAILOVER;  
Enabled.
```

Example 2

The following example shows that fast-start failover was successfully enabled when the configuration is operating in maximum performance mode.

```
DGMGRL> SHOW FAST_START FAILOVER;  
  
Fast-Start Failover: ENABLED  
Threshold:           30 seconds  
Target:              DR_Sales  
Observer:            (none)  
Lag Limit:           30 seconds  
Shutdown Primary:   TRUE  
Auto-reinstate:     TRUE  
  
Configurable Failover Conditions  
Health Conditions:  
  Corrupted Controlfile      YES  
  Corrupted Dictionary       YES  
  Inaccessible Logfile       NO  
  Stuck Archiver             NO  
  Datafile Offline           YES  
  
Oracle Error Conditions:  
(none)
```


ENABLE FAST_START FAILOVER CONDITION

Specifies additional conditions for which a fast-start failover should be performed.

Format

ENABLE FAST_START FAILOVER CONDITION *value*;

Command Parameters

value

Possible values are those described in the `SHOW FAST_START FAILOVER` command as Health Conditions or Oracle error numbers.

Usage Notes

- Possible values are the set maintained by the database health-check facility or a number corresponding to any ORA-xxxx error.
- While the conditions maintained by the health-check facility are subject to change in the future, some common examples are shown in [Table 8-2](#):

Table 8-2 Examples of Health Conditions

Health Condition	Description
"Datafile Offline"	Data file offline due to a write error.
"Corrupted Controlfile"	Corrupted controlfile.
"Corrupted Dictionary"	Dictionary corruption of a critical database object.
"Inaccessible Logfile"	LGWR is unable to write to any member of a log group due to an I/O error.
"Stuck Archiver"	Archiver is unable to archive a redo log because device is full or unavailable.

The following are enabled by default: "Datafile Offline," "Corrupted Controlfile," and "Corrupted Dictionary." An error will be raised if the specified value is not recognized. If the condition has already been set, no error will be raised.

- You can display these configurable conditions with the `SHOW FAST_START FAILOVER` command.

Command Example

Example 1

```
ENABLE FAST_START FAILOVER CONDITION "Corrupted Controlfile";
```

This specifies that a fast-start failover should be done if a corrupted controlfile is detected.

Example 2

```
ENABLE FAST_START FAILOVER CONDITION 27102;
```

This specifies that a fast-start failover should be done if an ORA-27102 error is raised.

EXIT

Exits (quits) the command-line interface.

Format

EXIT;

Command Parameters

None.

Usage Notes

- This command has the same effect as the [QUIT](#) command.
- A database connection is not required to execute this command. However, if you are connected, this command breaks the connection.

Command Example

Example 1

The following example demonstrates how to exit (quit) the command-line interface.

```
DGMGRL> EXIT;
```

FAILOVER

Invokes a failover that transitions the named (target) standby database into the role of a primary database. This type of failover is referred to as *manual failover*. See [Section 5.4, "Manual Failover"](#) for more information.

Note: Because a failover results in a transition of a standby database to the primary role, it should be performed when the primary database has failed or is unreachable and cannot be recovered in a timely manner. Failover may or may not result in data loss depending on the protection mode in effect at the time of the failover and whether the target standby database was synchronized with the primary database.

Use the `SWITCHOVER` command if the primary database has not failed and you want the current primary database and a standby database to switch roles with no data loss.

Format

```
FAILOVER TO database-name  
[ IMMEDIATE ];
```

Command Parameters

database-name

The name of a physical, logical, or snapshot standby database that you want to fail over to the primary database role.

Usage Notes

- The specified standby database must be enabled before the primary database fails. However, an enabled standby database that was shut down can be a candidate for the failover operation. In this case, restart the standby database using `DGMGRL STARTUP` command, then issue the `FAILOVER` command.
- The failover operates on the specified standby database and changes its role to a primary database. Any other standby databases not involved in the failover remain in the standby role.
- Before you issue the `FAILOVER` command, verify that you are connected to the standby database that will become the new primary database. If necessary, issue a `CONNECT` command to connect to the standby database to which you want to failover.
- If the `FAILOVER` command is issued without any options, the standby database chosen as the failover target applies all unapplied redo it has received before changing to the primary role. This is referred to as a complete failover.
- If the standby database that you want to fail over to the primary role is an Oracle RAC database, the broker will shut down all of the instances except the apply instance before it continues the failover operation. See [Section 5.4.3](#) for details.
- If you are failing over to an Oracle RAC physical standby database, only one instance can be running when performing failover. Once failover has completed,

the broker will automatically restart all other instances. The instance upon which failover was performed does not require a restart. No instance restarts are required if you are failing over to a single instance physical standby database.

No instance restarts are required if you are failing over to a logical standby database (either Oracle RAC or single instance).

If you are failing over to an Oracle RAC snapshot standby database, all but one instance will be shut down before starting failover. After failover has completed, the last instance will be restarted and opened. The broker will restart all other instances once the instance upon which failover was performed has opened. If you are failing over to a single-instance snapshot standby database, the instance must be restarted before the database can be opened.

- If the broker configuration is operating in maximum protection mode, a manual failover operation will force the protection mode to be maximum performance. The redo transport service settings are unaffected. You need to restore the desired protection mode for the resulting configuration after the failover operation.

Note: With fast-start failover, the broker preserves the protection mode at the same level in which it was operating before the failover.

- If the `FAILOVER` command is issued with the `IMMEDIATE` option, no attempt is made to apply any unapplied redo that has been received. This option more likely results in lost application data even when standby redo log files are configured on the standby database. Additionally, any remaining standby databases in the configuration cannot function as such until they are reenabled. See [Section 5.4.3](#) for more information about reenabling databases.
- You can perform a manual failover or set up the broker to perform a fast-start failover. See the [ENABLE FAST_START FAILOVER](#) command for information about allowing the broker to automatically invoke failover, when conditions warrant a failover.
- If fast-start failover is enabled, you can perform a *complete* manual failover only to the target standby database and only if the target standby database is synchronized with, or within the lag limit of, the primary database, and only when the observer is started. You cannot perform an *immediate* manual failover when fast-start failover is enabled.
- If Flashback Database was enabled on the former (failed) primary database prior to the failover, the former primary database can be reinstated using the broker's `REINSTATE` command (see the [REINSTATE DATABASE](#) command on page 8-39).

If failover was performed to a physical standby database, any other physical standby databases that were disabled by the failover can be reinstated if Flashback Database was enabled on the standby database and there are sufficient flashback logs available. See [Section 5.4.3, "Reenabling Disabled Databases After Failover or Switchover"](#) for step-by-step instructions.

- The original primary database can only participate in the configuration as a standby database after it is reenabled.

Caution: You should shut down the original primary database if it still has any active instances running prior to failing over.

See Also: [Section 5.4.3](#) about reenabling the original primary database so that it could serve as a standby database to the primary database

Command Examples

Example 1

The following example performs a failover in which the standby database, DR_Sales, transitions to the primary role:

```
DGMGRL> FAILOVER TO 'DR_Sales';
Performing failover NOW, please wait...
Failover succeeded, new primary is "DR_Sales"

DGMGRL> SHOW CONFIGURATION;

Configuration
Name:                DRSolution
Enabled:             YES
Protection Mode:    MaxPerformance
Databases:
  DR_Sales          - Primary database
  North_Sales      - Physical standby database (disabled)

Fast-Start Failover: DISABLED

Current status for "DRSolution":
SUCCESS
```

HELP

Displays online help for the Data Guard command-line interface.

Format

```
HELP [topic];
```

Command Parameter

topic

The topic for which you want to display help information. If you do not specify a topic, the command lists all of the topics and the format. Valid topics are:

```
ADD
CONNECT
CONVERT
CREATE
DISABLE
EDIT
ENABLE
EXIT
FAILOVER
HELP
QUIT
REINSTATE
REM
REMOVE
SHOW
SHUTDOWN
START
STARTUP
STOP
SWITCHOVER
```

Usage Note

- A database connection is not required to execute this command.

Command Examples

Example 1

The following example gets help on the EDIT commands.

```
DGMGRL> HELP EDIT
```

```
Edit a configuration, database or instance
```

```
Syntax:
```

```
EDIT CONFIGURATION SET PROTECTION MODE AS
    {MaxProtection|MaxAvailability|MaxPerformance};
EDIT CONFIGURATION SET PROPERTY <property name> = <value>;

EDIT DATABASE <database name> SET PROPERTY <property name> = <value>;
```

```
EDIT DATABASE <database name> RENAME TO <new database name>;

EDIT DATABASE <database name> SET STATE = <state>
  [WITH APPLY INSTANCE = <instance name>];

EDIT INSTANCE <instance name> [ON DATABASE <database name>]
  SET AUTO PFILE [ = {<initialization file path>|OFF} ];

EDIT INSTANCE <instance name> [ON DATABASE <database name>]
  SET PROPERTY <property name> = <value>;
```

QUIT

Quits (exits) the Data Guard command-line interface.

Format

QUIT;

Command Parameters

None.

Usage Notes

- This command has the same effect as the [EXIT](#) command.
- A database connection is not required to execute this command. However, if you are connected, this command breaks the connection.

Command Example

Example 1

The following example shows how to quit (exit) the command-line interface.

```
DGMGRL> QUIT;
```

REINSTATE DATABASE

Reinstates a database as a new standby database in the broker configuration for the current primary database.

Format

```
REINSTATE DATABASE database-name;
```

Command Parameter

database-name

The name of the database that is to be reinstated in the broker configuration.

Usage Notes

- If the conditions for reinstatement described in [Section 5.5.8](#) are not satisfied, the reinstatement will fail with an appropriate error status and the specified database will remain disabled.
- If the *database-name* specified is that of the old primary and fast-start failover is enabled, the old primary database will be reinstated as a standby to the new primary, and the fast-start failover environment will be updated to reflect the availability of the new standby database. It will accept redo data from the new primary database and be the target of a fast-start failover should the new primary database fail. Reinstatement occurs automatically if the observer is running unless the `FastStartFailoverAutoReinstate` configuration property is set to `FALSE`.
- This command does not require that fast-start failover be enabled. It can be used to reinstate an old primary database after a complete manual failover has been performed. It can also be used to reinstate a physical standby database that had been disabled because of a complete failover to a physical standby database.
- Issue this command while connected to any database in the broker configuration, except the database that is to be reinstated.

Command Examples

Example 1

The following example reinstates the `DR_Sales` database as a standby database in the broker configuration.

```
DGMGRL> REINSTATE DATABASE 'North_Sales';
Reinstating database "North_Sales", please wait...
Operation requires shutdown of instance "sales1" on database "North_Sales"
Shutting down instance "sales1"...
ORA-01109: database not open

Database dismounted.
ORACLE instance shut down.
Operation requires startup of instance "sales1" on database "North_Sales"
Starting instance "sales1"...
ORACLE instance started.
Database mounted.
Continuing to reinstate database "North_Sales" ...
Reinstatement of database "North_Sales" succeeded
```

REMOVE CONFIGURATION

Removes all of the broker configuration information, including all database profiles, from the Data Guard broker configuration file, and terminates broker management of all of the databases associated with the broker configuration.

Caution: When you use the `REMOVE CONFIGURATION` command, all profile information is deleted from the Data Guard broker configuration file and cannot be recovered.

Format

```
REMOVE CONFIGURATION [ PRESERVE DESTINATIONS ];
```

Command Parameters

None.

Usage Notes

- When you remove a broker configuration, management of all of the databases associated with that configuration is disabled.
- By default, the command removes the corresponding broker settings of the `LOG_ARCHIVE_DEST_n` initialization parameter on the primary database and the `LOG_ARCHIVE_CONFIG` initialization parameters on all databases in the configuration. To preserve these settings, use the `PRESERVE DESTINATIONS` option.
- This command does not remove or affect the actual primary or standby database instances, databases, datafiles, control files, initialization parameter files, server parameter files, or log files of the underlying Data Guard configuration.
- You cannot remove the configuration when fast-start failover is enabled.

Command Example

The following examples show a successful and an unsuccessful `REMOVE CONFIGURATION` command.

Example 1 Successful REMOVE CONFIGURATION Command

The following command shows how to remove configuration information from the configuration file.

```
DGMGRL> REMOVE CONFIGURATION;
Removed configuration
DGMGRL> SHOW CONFIGURATION;
Error: ORA-16532: Data Guard broker configuration does not exist
```

Configuration details cannot be determined by DGMGRL

Example 2 Unsuccessful REMOVE CONFIGURATION Command

The following command is unsuccessful because fast-start failover is enabled.

```
DGMGRL> REMOVE CONFIGURATION;
Error: ORA-16654: Fast-Start Failover was enabled
```

Failed.

```
DGMGRL> SHOW CONFIGURATION;
```

```
Configuration
```

```
Name:                DRSolution
Enabled:             YES
Protection Mode:     MaxAvailability
Databases:
  DR_Sales           - Primary database
  North_Sales        - Physical standby database
                    - Fast-Start Failover target
```

```
Fast-Start Failover: ENABLED
```

```
Current status for "DRSolution":
SUCCESS
```

REMOVE DATABASE

Removes the specified standby database's profile from the broker configuration and terminates broker management of the standby database.

Caution: When you use the `REMOVE DATABASE` command, the database's profile information is deleted from the broker configuration file and cannot be recovered.

Format

```
REMOVE DATABASE database-name [ PRESERVE DESTINATIONS ];
```

Command Parameter

database-name

The name of the standby database whose profile you want to remove from the broker configuration.

Usage Note

- An error is returned if you specify the name of the primary database in the broker configuration.
- By default, the command removed the corresponding broker settings of the `LOG_ARCHIVE_DEST_n` initialization parameter on the primary database and the `LOG_ARCHIVE_CONFIG` initialization parameter on all databases in the configuration. To preserve these settings, use the `PRESERVE DESTINATIONS` option.
- This command cannot be executed if fast-start failover is enabled and *database-name* specifies the name of the target standby database.

Command Example

Example 1

The following example shows how to remove a database from the Data Guard broker configuration.

```
DGMGRL> SHOW CONFIGURATION;
```

```
Configuration
Name:                DRSolution
Enabled:             YES
Protection Mode:     MaxPerformance
Databases:
  North_Sales - Primary database
  DR_Sales    - Physical standby database
```

```
Fast-Start Failover: DISABLED
```

```
Current status for "DRSolution":
SUCCESS
```

```
DGMGRL> REMOVE DATABASE 'DR_Sales';
Removed database "DR_Sales" from the configuration
```

```
DGMGRL> SHOW CONFIGURATION;

Configuration
Name:          DRSolution
Enabled:       YES
Protection Mode:  MaxPerformance
Databases:
  North_Sales  - Primary database

Fast-Start Failover: DISABLED

Current status for "DRSolution":
SUCCESS
```

REMOVE INSTANCE

Removes an instance from an existing database profile in the broker configuration.

Format

```
REMOVE INSTANCE instance-name  
[ON DATABASE database-name];
```

Command Parameters

instance-name

The name of the instance (SID) that you want to remove from the broker configuration.

database-name

The name of the database to which the *instance-name* is associated.

Usage Notes

- In an Oracle RAC database, the broker automatically adds started instances into the corresponding database profile. However, the broker may not automatically remove instances from the database profile. The `REMOVE INSTANCE` command can be used to manually remove any instance that no longer exists from the database profile.
- The *instance-name* can be unique across the configuration. If *instance-name* is not unique, you must specify both the *database-name* and the *instance-name* to fully identify the instance.
- This command is rejected for an instance that is currently active in the broker configuration.
- This command is rejected if this is the only instance currently associated with a database profile.

Command Example

Example 1

The following example shows how to remove an instance of the database.

```
DGMGRL> REMOVE INSTANCE 'dr_sales3' ON DATABASE 'DR_Sales';  
Removed instance "dr_sales3" from the database "DR_Sales"
```

SHOW CONFIGURATION

Displays a summary and status of the broker configuration. The summary lists all databases included in the broker configuration and other information pertaining to the broker configuration itself, including the fast-start failover status.

Format

```
SHOW CONFIGURATION [VERBOSE | property-name];
```

Command Parameters

property-name

The name of the property for which you want to display summary information.

See [Chapter 9, "Database Properties"](#) for complete information about properties.

Usage Notes

- Use the `SHOW CONFIGURATION VERBOSE` command (or the `SHOW FAST_START FAILOVER` command) to show the properties related to fast-start failover.
- You can optionally specify either `VERBOSE` or `property-name`, but not both.

Command Examples

Example 1 Showing a Summary of the DRSolution Configuration

The following example provides a summary of the `DRSolution` configuration for which fast-start failover is disabled.

```
DGMGRL> SHOW CONFIGURATION;

Configuration
Name:                DRSolution
Enabled:             YES
Protection Mode:    MaxPerformance
Databases:
  North_Sales - Primary database
  DR_Sales   - Physical standby database

Fast-Start Failover: DISABLED

Current status for "DRSolution":
SUCCESS
```

Example 2 Verifying the Readiness of Fast-Start Failover

The following example verifies the readiness of a configuration for which fast-start failover is enabled:

```
DGMGRL> SHOW CONFIGURATION VERBOSE;

Configuration
Name:                DRSolution
Enabled:             YES
Protection Mode:    MaxAvailability
Databases:
  North_Sales - Primary database
  DR_Sales   - Physical standby database
```

- Fast-Start Failover target

Fast-Start Failover: ENABLED
Threshold: 30 seconds
Target: DR_SALES
Observer: (none)
Lag Limit: 30 seconds (not in use)
Shutdown Primary: TRUE
Auto-reinstate: TRUE

Current status for "DRSolution":
SUCCESS

SHOW DATABASE

Displays information or property values of the specified database and its instances.

Format

```
SHOW DATABASE database-name [VERBOSE | property-name];
```

Command Parameters

database-name

The name of the database for which you want to display information.

property-name

The name of the property for which you want to display a value.

See Also: [Chapter 4](#) and [Chapter 9](#) for information about properties.

Usage Notes

- The `SHOW DATABASE` command shows a brief summary of the database. `SHOW DATABASE VERBOSE` shows properties of the database in addition to the brief summary. They both show the status of the database.
- The `SHOW DATABASE VERBOSE` command shows database-specific properties and instance-specific properties. For a non-RAC database, the values of the instance-specific properties are those of the only instance of the database. For an Oracle RAC database, the values of the instance-specific properties will not be shown, although the property names are still listed. To see the instance-specific values of these properties, use the `SHOW INSTANCE` command.
- The properties that the `SHOW DATABASE VERBOSE` command shows depend on the database role and the configuration composition:
 - For the primary database, properties specific to physical or snapshot standby databases are shown only if there is at least one physical or snapshot standby database in the configuration. The properties specific to logical standby databases are shown only if there is at least one logical standby database in the configuration.
 - For physical and snapshot standby databases, properties specific to logical standby databases are not shown.
 - For logical standby databases, properties specific to physical and snapshot standby databases are not shown.
- This command is rejected if you use the `SHOW DATABASE property-name` command to show an instance-specific property in an Oracle RAC database.

Command Examples

Example 1

Shows database information in an abbreviated format.

```
DGMGR> SHOW DATABASE 'DR_Sales';
```

```

Database
Name:          DR_Sales
Role:          PHYSICAL STANDBY
Enabled:       YES
Intended State: APPLY-ON
Instance(s):
  dr_sales1

```

```

Current status for "DR_Sales":
SUCCESS

```

Example 2

Shows database information in an extended format.

```
DGMGRL> SHOW DATABASE VERBOSE 'DR_Sales';
```

```

Database
Name:          DR_Sales
Role:          PHYSICAL STANDBY
Enabled:       NO
Intended State: APPLY-ON
Instance(s):
  dr_sales1

Properties:
  DGConnectIdentifier          = 'DR_Sales.foo.com'
  ObserverConnectIdentifier    = ''
  LogXptMode                   = 'ASYNC'
  DelayMins                    = '0'
  Binding                      = 'OPTIONAL'
  MaxFailure                   = '0'
  MaxConnections               = '1'
  ReopenSecs                   = '300'
  NetTimeout                   = '30'
  RedoCompression              = 'DISABLE'
  LogShipping                   = 'ON'
  PreferredApplyInstance       = ''
  ApplyInstanceTimeout         = '0'
  ApplyParallel                = 'AUTO'
  StandbyFileManagement        = 'AUTO'
  ArchiveLagTarget             = '0'
  LogArchiveMaxProcesses       = '5'
  LogArchiveMinSucceedDest     = '1'
  DbFileNameConvert            = 'dbs/t, dbs/bt'
  LogFileNameConvert           = 'dbs/t, dbs/bt'
  FastStartFailoverTarget      = ''
  StatusReport                 = '(monitor)'
  InconsistentProperties        = '(monitor)'
  InconsistentLogXptProps      = '(monitor)'
  SendQEntries                 = '(monitor)'
  LogXptStatus                 = '(monitor)'
  RecvQEntries                 = '(monitor)'
  HostName                     = 'dr_sales.foo.com'
  SidName                      = 'dr_sales1'
  StandbyArchiveLocation        = '/archfs/arch'
  AlternateLocation            = ''
  LogArchiveTrace              = '8191'
  LogArchiveFormat              = 'db2r_%d_%t_%s_%r.arc'
  LatestLog                    = '(monitor)'
  TopWaitEvents                = '(monitor)'

```

```
Current status for "DR_Sales":  
SUCCESS
```

SHOW FAST_START FAILOVER

Displays all fast-start failover related information.

Format

```
SHOW FAST_START FAILOVER;
```

COMMAND PARAMETERS

None.

Usage Notes

The `SHOW FAST_START FAILOVER` command shows a summary of the fast-start failover configuration.

Command Example

```
DGMGRL> SHOW FAST_START FAILOVER;
```

```
Fast-Start Failover: DISABLED
```

```
Threshold:          30 seconds
Target:             (none)
Observer:           (none)
Lag Limit:          30 seconds
Shutdown Primary:  TRUE
Auto-reinstate:    TRUE
```

```
Configurable Failover Conditions
```

```
Health Conditions:
```

```
Corrupted Controlfile      YES
Corrupted Dictionary       YES
Inaccessible Logfile       NO
Stuck Archiver             NO
Datafile Offline           YES
```

```
Oracle Error Conditions:
```

```
ORA-27102: out of memory
```

SHOW INSTANCE

Displays information or property value of the specified instance.

Format

```
SHOW INSTANCE instance-name [VERBOSE | property-name]  
[ON DATABASE database-name];
```

Command Parameters

instance-name

The name of the instance for which you want to display information.

property-name

The name of the property for which you want to display a value.

See Also: [Chapter 4](#) and [Chapter 9](#) for information about configuration properties.

database-name

The name of the database to which is associated the instance for which you want to show information.

Usage Notes

- The `SHOW INSTANCE` command shows a brief summary of the instance. `SHOW INSTANCE VERBOSE` shows properties of the instance in addition to the brief summary. They both show the status of the instance.
- The `SHOW INSTANCE VERBOSE` command only shows instance-specific properties.
- The properties that the `SHOW INSTANCE VERBOSE` command shows depend on the database role and the configuration composition:
 - For instances of the primary database, properties specific to physical or snapshot standby instances are shown only if there is at least one physical or snapshot standby database in the configuration. The properties specific to logical standby instances are shown only if there is at least one logical standby database in the configuration.
 - For instances of physical or snapshot standby databases, properties specific to logical standby instances are not shown.
 - For instances of logical standby databases, properties specific to physical and snapshot standby instances are not shown.
- The *instance-name* can be unique across the configuration. If *instance-name* is not unique, you must specify both the *database-name* and the *instance-name* to fully identify the instance.

Command Example

Example 1

The following example shows information about a specific instance of a database.

```
DGMGRL> SHOW INSTANCE sales1;
```

```
Instance 'sales1' of database 'North_Sales'  
Host Name:      north.foo.com
```

```
Current status for "sales1":  
SUCCESS
```

Example 2

Shows instance information in an extended format.

```
DGMGRL> SHOW INSTANCE VERBOSE sales1;
```

```
Instance 'sales1' of database 'North_Sales'  
Host Name:      north.foo.com  
PFILE:
```

```
Properties:  
HostName          = 'north.foo.com'  
SidName           = 'sales1'  
StandbyArchiveLocation = '/archfs/arch'  
AlternateLocation = ''  
LogArchiveTrace   = '255'  
LogArchiveFormat  = 'r_%d_%t_%s_%r.arc'  
LsbyMaxSga        = '0'  
LsbyMaxServers    = '0'  
LatestLog         = '(monitor)'  
TopWaitEvents     = '(monitor)'
```

```
Current status for "sales1":  
SUCCESS
```

SHUTDOWN

Shuts down a currently running Oracle instance.

Format

```
SHUTDOWN [ ABORT | IMMEDIATE | NORMAL ];
```

Command Parameters

None.

Usage Notes

- Using the `SHUTDOWN` command with no arguments is equivalent to using the `SHUTDOWN NORMAL` command.
- The following list describes the options to the `SHUTDOWN` command:

- `ABORT`

Proceeds with the fastest possible shutdown of the database without waiting for calls to complete or for users to disconnect from the database.

Uncommitted transactions are not rolled back. Client SQL statements being processed are terminated. All users connected to the database are implicitly disconnected, and the next database startup will require instance recovery. You must use this option if a background process terminates abnormally.

Caution: If you use the `ABORT` option on the primary database when fast-start failover is enabled and the observer is running, a fast-start failover may ensue. Use the `IMMEDIATE` or `NORMAL` option to prevent an unexpected fast-start failover from occurring.

- `IMMEDIATE`

Does not wait for current calls to complete or users to disconnect from the database. Further connections are prohibited. The database is closed and dismounted. The instance is shut down, and no instance recovery is required on the next database startup.

- `NORMAL`

This is the default option. The process waits for users to disconnect from the database. Further connections are prohibited. The database is closed and dismounted. The instance is shut down, and no instance recovery is required on the next database startup.

Command Example

Example 1

The following command shuts down the primary database in normal mode.

```
DGMGRL > SHUTDOWN;
```

```
Database closed.
```

```
Database dismounted.
```

```
Oracle instance shut down.
```

START OBSERVER

Starts the fast-start failover observer.

Format

```
START OBSERVER [ FILE=observer_configuration_filename];
```

Command Parameters

observer_configuration_filename

Specifies an explicit directory path and file name on the observer computer.

Usage Notes

- The Oracle Client Administrator kit, or the full Oracle Database Enterprise Edition or Oracle Personal Edition kit must be installed on the observer computer to monitor a broker configuration for which fast-start failover is to be enabled. See [Section 5.5.1](#) for more information.
- The `START OBSERVER` command must be issued on the observer computer. Once the observer is successfully started, control is not returned to the user until the observer is stopped (for example, by issuing the `STOP OBSERVER` command from a different client connection). If you want to perform further interaction with the broker configuration, you must connect through another client.
- The observer runs autonomously once it has been successfully started. For this reason, it is recommended that when invoking DGMGRL for the purpose of issuing the `START OBSERVER` command, specify the `-logfile` optional parameter on the command line so that output generated while acting as the observer is not lost. See [Section 8.1.1](#) for more information about this parameter and see [Section 10.5.3](#) for an example use of the `-logfile` option.
- If a directory path is not specified with the `FILE` parameter, the observer searches the current working directory for the `fsfo.dat` file. If an `fsfo.dat` file is not found and this is the first time the `START OBSERVER` command is issued, the observer creates a `fsfo.dat` file.
- The primary and target standby database `DB_UNIQUE_NAME` initialization parameter and connect identifiers are stored in the `fsfo.dat` configuration file. Oracle recommends you ensure this file is protected from unauthorized access.
- Fast-start failover does not need to be enabled before you issue this command.
 - If fast-start failover is enabled, the observer will retrieve primary and target standby connect identifiers from the broker configuration and begin monitoring the configuration.
 - If fast-start failover is not enabled, the observer continually monitors for when fast-start failover is enabled.
- Only the primary database needs to be running when you issue this command; the standby database that will be the target of a fast-start failover does not need to be running.
- If the observer is stopped:
 - Because the `STOP OBSERVER` command was issued, you can issue the `START OBSERVER` command on any computer to restart the observer.

- For any reason other than because the `STOP OBSERVER` command was issued, you must issue the `START OBSERVER` command on the same observer computer where it was started originally, with the observer configuration file used when the observer had first been started.
- If an observer is already running, the `START OBSERVER` command fails and returns one of the following errors:


```
ORA-16647: could not start more than one observer
DGM-16954: unable to open and lock the Observer configuration file
```
- If the primary and target standby databases stay connected but they lose the connection to the observer, then the primary database goes into an unobserved state. This state is reported by the broker's health check capability.
- Use the `SHOW FAST_START FAILOVER` command, the `SHOW CONFIGURATION VERBOSE` command, or query the `FS_FAILOVER_*` columns in the `V$DATABASE` view on the primary database to see the status of the observer and its host computer.

Command Examples

Example 1

The following example shows how to start the observer.

```
DGMGRL> CONNECT sys@North_Sales.foo.com;
Password: password
Connected.
DGMGRL> START OBSERVER;
Observer started
```

Example 2

The following example shows how to start the observer using `CONNECT '/'` so that connection credentials are not visible on the command line:

```
DGMGRL> CONNECT /@North_Sales.foo.com;
DGMGRL> START OBSERVER;
Observer started.
```

You must set up Oracle Wallet to use `CONNECT '/'`. By setting up Oracle Wallet, you can write a script to securely start and run the observer as a background job without specifying database credentials in the script. When using Oracle Wallet as a secure external password store, be sure to add credentials for both the primary and fast-start failover target standby databases. The database connect string that you specify when adding the credentials for each database must match the `ObserverConnectIdentifier` or `DGConnectIdentifier` configurable database property.

See Also: *Oracle Database Advanced Security Administrator's Guide* for more information about Oracle Wallet

STARTUP

Starts an Oracle database instance with any of the following options:

- **FORCE**: shuts down the current Oracle instance in the `SHUTDOWN ABORT` mode before restarting it.
- **RESTRICT**: allows only Oracle users with the `RESTRICTED SESSION` system privilege to connect to the instance.
- **PFILE**: specifies the `PFILE` initialization parameter file to be used when the database instance is started.
- **MOUNT**: mounts the specified database without opening it.
- **OPEN**: mounts and opens the specified database.
- **NOMOUNT**: starts the specified database instance without mounting the database.

Format

```
STARTUP
  [FORCE]
  [RESTRICT]
  [PFILE=filename]
  [MOUNT | OPEN [open-options] | NOMOUNT];
```

Command Parameters

filename

The name of the initialization parameter file to be used when starting the database instance. If you do not specify the `PFILE` parameter option, then the default server parameter file (specific to your operating system) is used.

open-options

The mode of access in which you want the specified database to start. The possible modes are:

```
READ ONLY
READ WRITE
```

Usage Notes

- Using the `STARTUP` command with no arguments is equivalent to using the `STARTUP OPEN` command.
- If you do not use the `FORCE` clause when you use the `STARTUP` command and the current database instance is running, an error results. The `FORCE` clause is useful when you are debugging or when error conditions are occurring. Otherwise, it should not be used.
- Use the `RESTRICT` clause to allow only Oracle users with the `RESTRICTED SESSION` system privilege to connect to the instance. Later, you can use the `ALTER SYSTEM` command through `SQL*Plus` to disable the restricted session feature.
- If you do not use the `PFILE` clause to specify the initialization parameter file, the `STARTUP` command uses the default server parameter file, if it exists. Otherwise,

the `STARTUP` command uses the default initialization parameter file. The default files are platform specific.

See your operating system-specific documentation for more information about the default parameter files.

- Use the `OPEN` clause to mount and open the specified database.
- The `NOMOUNT` clause starts the database instance without mounting the database. You cannot use the `NOMOUNT` clause with the `MOUNT` or `OPEN` options.

Command Examples

Example 1

The following examples show two different methods for starting a database instance. Each command starts a database instance using the standard parameter file, mounts the default database in exclusive mode, and opens the database.

```
DGMGRL> STARTUP;  
DGMGRL> STARTUP OPEN;
```

Example 2

The following command shuts down the current instance, immediately restarts it without mounting or opening the database, and allows only users with restricted session privileges to connect to it.

```
DGMGRL > STARTUP FORCE RESTRICT NOMOUNT;
```

Example 3

The following command starts an instance using the parameter file `testparm` without mounting the database.

```
DGMGRL > STARTUP PFILE=testparm NOMOUNT;
```

Example 4

The following example starts and mounts a database instance, but does not open it.

```
DGMGRL> STARTUP MOUNT;
```

STOP OBSERVER

Stops the fast-start failover observer.

Format

```
STOP OBSERVER;
```

Command Parameters

None.

Usage Notes

- You can issue this command while connected to any database in the broker configuration.
- This command does not disable fast-start failover.
- Fast-start failover does not need to be enabled when you issue this command.
- If fast-start failover *is enabled* when you issue the `STOP OBSERVER` command, then the primary and standby databases must be connected and communicating with each other. Otherwise the following error is returned:

```
ORA-16636 fast-start failover target standby in error state, cannot stop observer
```

- If fast-start failover *is not enabled* when you issue the `STOP OBSERVER` command, then only the primary database must be running when you stop the observer.
- The observer does not stop immediately when the `STOP OBSERVER` command is issued. The observer does not discover it has been stopped until the next time the observer contacts the broker.

As soon as you have issued the `STOP OBSERVER` command, you may enter the `START OBSERVER` command again on any computer. You can start a new observer right away, even if the old observer has not yet discovered it was stopped. Any attempt to restart the old observer will fail, because a new observer has been started for the broker configuration.

Command Examples

Example 1

The following example stops the observer.

```
DGMGRL> STOP OBSERVER;
```

SWITCHOVER

A switchover operation is a planned transition in which the primary database exchanges roles with one of the standby databases. When you issue the `SWITCHOVER` command, the current primary database becomes a standby database, and the specified standby database becomes the primary database.

Format

```
SWITCHOVER TO database-name;
```

Command Parameter

database-name

The name of the standby database you want to change to the primary database role.

Usage Notes

- If fast-start failover is enabled, you may switch over only to the target standby database.
- The broker verifies that the primary and standby databases are in the following states before starting the switchover:
 - The primary database must be enabled and in the `TRANSPORT-ON` state so redo transport services are started.
 - The standby database must be enabled and in the `APPLY-ON` state, with log apply services started.
- The broker allows the switchover to proceed as long as there are no redo transport services errors for the standby database that you selected to participate in the switchover. However, errors occurring for any other standby database not involved in the switchover will not prevent the switchover from proceeding.
- Switchover to a logical standby database is not allowed when the configuration is operating in maximum protection mode.
- If the broker configuration is operating in either maximum protection mode or maximum availability mode, the switchover maintains the protection mode even after the operation (described in [Section 5.3.1](#)). The switchover will not be allowed if the mode cannot be maintained because the target standby database of the switchover was the only standby that satisfied the protection mode requirement.
- If the standby database that is assuming the primary role is a physical standby database, then the old primary database will be restarted after the switchover completes. If the standby database is a logical standby database, then neither the primary database nor the logical standby database is restarted.
- If the standby database that is assuming the primary role is a physical standby database, then the original primary becomes a physical standby database.
- If the standby database that is assuming the primary role is a logical standby database, then the original primary becomes a logical standby database.
- If the standby database you want to switch to the primary role is an Oracle RAC physical standby database, the broker will shut down all instances except the apply instance on the physical standby database, and all but one instance on an

Oracle RAC primary database, before it continues the switchover. See [Section 5.3](#) for details.

- You cannot switchover to a snapshot standby database.
- If the standby database that is assuming the primary role is a logical standby database and there are physical standby databases in the configuration, after the switchover, the physical standby databases will be disabled.

Caution: For this reason, Oracle generally recommends that you specify your physical standby database for switchover instead of your logical standby database. If you must switch over to your logical standby database, see [Section 5.4.3](#) to reenable your physical standby database.

Command Examples

Example 1

The following example shows a successful switchover in which the physical standby database, DR_Sales, transitions into the primary role.

```
DGMGRL> switchover to 'DR_Sales';
Performing switchover NOW, please wait...
New primary database "DR_Sales" is opening...
Operation requires shutdown of instance "sales1" on database "North_Sales"
Shutting down instance "sales1"...
ORA-01109: database not open

Database dismounted.
ORACLE instance shut down.
Operation requires startup of instance "sales1" on database "North_Sales"
Starting instance "sales1"...
ORACLE instance started.
Database mounted.
Switchover succeeded, new primary is "DR_Sales"
```

Example 2

If you connect to the database using operating system authentication, you can use any username and password to connect. However, DGMGRL may not be able to shut down and start up the primary and standby database automatically because it cannot remotely authenticate itself.

The following example shows a switchover that succeeded but returns an error because DGMGRL cannot shut down and start up the primary and standby databases.

```
DGMGRL> connect /
Connected.
DGMGRL> SWITCHOVER TO 'DR_Sales';
Performing switchover NOW, please wait...
New primary database "DR_Sales" is opening...
Operation requires shutdown of instance "sales1" on database "North_Sales"
Shutting down instance "sales1"...
ORA-01031: insufficient privileges

You are no longer connected to ORACLE
Please connect again.
Unable to shut down instance "sales1"
You must shut down instance "sales1" manually
```

Operation requires startup of instance "sales1" on database "North_Sales"
You must start instance "sales1" manually
Switchover succeeded, new primary is "DR_Sales"

Note: For DGMGRL to restart instances automatically, you must connect to the database using the same credentials given in the last CONNECT command, even if the last CONNECT command was used to connect to another database.

You must manually issue the [SHUTDOWN](#) and [STARTUP](#) commands to restart the new primary and any standby instances that may have been shut down.

Database Properties

Database properties help you to view and control the behavior of databases, redo transport services, and log apply services in a broker configuration.

This chapter discusses the following topics:

- [Monitorable \(Read-Only\) Database Properties](#)
- [Configurable Database Properties](#)

The scope of some properties is said to be database-wide. If the database (primary or standby) is an Oracle RAC database consisting of multiple instances, the value of such a property applies uniformly across all of the instances of that database. The scope of other properties is said to be instance-specific. Such a property exists for all instances of the RAC database, but its value may differ from one specific instance to another.

Note: This chapter presents properties primarily from the point of view of the Data Guard command-line interface (DGMGRL). Using DGMGRL, the properties described in this chapter may be viewed or modified using discrete DGMGRL commands.

Enterprise Manager explicitly presents some of these properties on the Edit Properties page. Information from other properties may be implicitly incorporated into other Web pages displayed by Enterprise Manager. Each property's description in this chapter indicates how Enterprise Manager presents that property.

9.1 Monitorable (Read-Only) Database Properties

Monitorable database properties allow you to view information related to the database or the instance, but you cannot change the values of these properties. You can view all of the monitorable properties using the DGMGRL `SHOW` commands.

Note: Information for monitorable properties can be seen only when broker management of the database is enabled. Enterprise Manager displays the information obtained from these properties on the Property page.

If the database is an Oracle RAC database, the output values of some properties may also show instance-specific information. For example if the primary database is an Oracle RAC database, `LogXptStatus` may show `Instance1` transmitting redo data to `Standby2` has an error and `Instance2` transmitting redo data to `Standby4` has an error.

The following sections describe the monitorable database properties:

- [InconsistentLogXptProps \(Inconsistent Redo Transport Properties\)](#)
- [InconsistentProperties \(Inconsistent Database Properties\)](#)
- [LogXptStatus \(Redo Transport Status\)](#)
- [LsbyFailedTxnInfo \(Logical Standby Failed Transaction Information\)](#)
- [LsbyParameters \(Logical Standby Parameters\)](#)
- [LsbySkipTable \(Logical Standby Skip Table\)](#)
- [LsbySkipTxnTable \(SQL Apply Skip Transaction Table\)](#)
- [RecvQEntries \(Receive Queue Entries\)](#)
- [SendQEntries \(Send Queue Entries\)](#)
- [StatusReport \(Status Report\)](#)
- [TopWaitEvents](#)

9.1.1 InconsistentLogXptProps (Inconsistent Redo Transport Properties)

The `InconsistentLogXptProps` monitorable database property returns a table that shows all properties related to redo transport services whose values are inconsistent between the broker configuration file and the runtime value in the database.

Although the properties reported in this table are database-level properties, the inconsistency is reported on an instance-level basis. A database-specific property only ensures that there is one value in the broker's configuration file for all instances sharing the database, but the runtime values among the instances can be different. This means that a database-specific property may be inconsistent only on some instances.

This property pertains to the primary database. The table contains the following columns:

- `INSTANCE_NAME`
The value identifying the SID for the instance.
- `STANDBY_NAME`
The database unique name (`DB_UNIQUE_NAME`) of the standby database to which this redo transport services property pertains.
- `PROPERTY_NAME`
The name of the redo transport services property with an inconsistent value.
- `MEMORY_VALUE`
The runtime value being used in the database.
- `BROKER_VALUE`
The value of the redo transport services property saved in the broker configuration file.

9.1.2 InconsistentProperties (Inconsistent Database Properties)

The `InconsistentProperties` monitorable database property returns a table that shows all database properties whose values contained in the broker configuration file

are inconsistent with the values in the corresponding server parameter file or the runtime values in the database.

The properties reported in this table can be either database-specific properties or instance-specific properties. A database-specific property only ensures that there is one value in the broker's configuration file for all instances sharing the database, but the runtime memory values or SPFILE values among the instances can be different. This means that a database-specific property may be inconsistent only on some instances.

Each individual database has this property. The table contains the following columns:

- `INSTANCE_NAME`
The value identifying the SID for the instance.
- `PROPERTY_NAME`
The name of the database property with the inconsistent value.
- `MEMORY_VALUE`
The corresponding runtime value being used in the database.
- `SPFILE_VALUE`
The corresponding value saved in the server parameter file (SPFILE).
- `BROKER_VALUE`
The value of the database property saved in the broker configuration file.

9.1.3 LogXptStatus (Redo Transport Status)

The `LogXptStatus` monitorable database property returns a table that contains the error status of redo transport services for each of the enabled standby databases. This property pertains to the primary database.

The table contains the following columns:

- `PRIMARY_INSTANCE_NAME`
The value identifying the SID for the instance on the primary database.
- `STANDBY_DATABASE_NAME`
The database unique name (`DB_UNIQUE_NAME`) of the standby database.
- `ERROR`
The text of the redo transport error. If there is no error, the field is empty.

Each entry in the table indicates the status of redo transport services on one primary instance to one standby database.

The error status can be an empty string, which indicates there is no error.

In the following example, the `STATUS` from `DR_Sales` is empty because there is no error for the `DR_Sales` destination. The `South_Report` destination returned the `ORA-01034` message.

```
DGMGR> SHOW DATABASE 'North_Sales' 'LogXptStatus' ;
LOG TRANSPORT STATUS
PRIMARY_INSTANCE_NAME STANDBY_DATABASE_NAME          STATUS
                    sales1                DR_Sales
                    sales1                South_Report    ORA-01034: ORACLE not available
```

9.1.4 LsbyFailedTxnInfo (Logical Standby Failed Transaction Information)

The `LsbyFailedTxnInfo` monitorable database property identifies a failed transaction that caused log apply services to stop. This property contains a string with the following values from the `DBA_LOGSTDBY_EVENTS` view:

- `XIDUSN`: Transaction ID undo segment number
- `XIDSLT`: Transaction ID slot number
- `XIDSQN`: Transaction ID sequence number
- `STATUS_CODE`: Status (or Oracle error code) belonging to the `STATUS` message
- `STATUS`: Description of the current activity of the process or the reason why log apply services stopped

The transaction IDs and status information are separated by a string of number signs (###).

This property pertains to a logical standby database.

9.1.5 LsbyParameters (Logical Standby Parameters)

The `LsbyParameters` monitorable database property contains a string that identifies the value of `MAX_SGA` (maximum system global area) and `MAX_SERVERS` (maximum number of parallel query servers) specifically reserved for log apply services. These values are separated by a string of number signs (###) in the `LsbyParameters` property.

This property pertains to a logical standby database.

9.1.6 LsbySkipTable (Logical Standby Skip Table)

The `LsbySkipTable` monitorable database property lists the SQL Apply skip specifications. These skip specifications specify filters for SQL Apply to skip applying a certain class of online redo log files on the logical standby database. This property returns a table with the following columns from the `DBA_LOGSTDBY_SKIP` view:

- `ERROR`
Indicates if the statement should be skipped (Y) or if errors should be returned for the statement (N)
- `STATEMENT_OPT`
Indicates the type of statement that should be skipped
- `SCHEMA`
The schema name for which this skip option should be used
- `NAME`
Name of the object for which this skip option should be used
- `PROCEDURE`
Name of the stored procedure to execute when processing the skip option

This property pertains to a logical standby database.

9.1.7 LsbySkipTxnTable (SQL Apply Skip Transaction Table)

The `LsbySkipTxnTable` monitorable database property lists the skip settings chosen. This property returns a table with following columns:

- `XIDUSN`: Transaction ID undo segment number
- `XIDSLT`: Transaction ID slot number
- `XIDSQN`: Transaction ID sequence number
- `ACTIVE`: Description of the current activity of the process or the reason why SQL Apply stopped

This property pertains to SQL Apply.

9.1.8 RecvQEntries (Receive Queue Entries)

The `RecvQEntries` monitorable database property returns a table indicating all log files that were received by the standby database but have not yet been applied. If no rows are returned, it implies all log files received have been applied. This property pertains to a standby database.

The table contains the following columns in the order shown:

- `STATUS`

The `STATUS` column is set to one of the following values for a log file on a logical standby database:

- `NOT_APPLIED`: No redo records in this log file have been applied.
- `PARTIALLY_APPLIED`: Some of the redo records in this log file have been applied while others have not.
- `COMMITTED_TRANSACTIONS_APPLIED`: This status value only applies to a logical standby database. All redo records belonging to the committed transactions have been applied. Redo records belonging to uncommitted transactions have not been read by LogMiner and may still be needed when the transactions are committed in the future. Therefore, it is not safe yet to discard this online redo log file.

- `RESETLOGS_ID`

Resetlogs identifier associated with the archived redo log file

- `THREAD`

The redo thread number

- `LOG_SEQ`

The online redo log file sequence number

- `TIME_GENERATED`

The first time when the online redo log file was written to the primary database

- `TIME_COMPLETED`

The next time when the log file was archived on the primary database (corresponds to the `NEXT_CHANGE#` column)

- `FIRST_CHANGE#`

First change number in the archived redo log file

- `NEXT_CHANGE#`

First change in the next log file

- SIZE (KBs)

The SIZE of the online redo log file in kilobytes

For example:

```
DGMGRL> SHOW DATABASE 'DR_Sales' 'RecvQEntries' ;
          STATUS      RESETLOGS_ID      THREAD
LOG_SEQ   TIME_GENERATED    TIME_COMPLETED    FIRST_CHANGE#
NEXT_CHANGE#  SIZE (KBs)
          NOT_APPLIED      497198843          1              5
06/20/2003 14:55:38 06/20/2003 16:31:26      202138
210718          7364
          NOT_APPLIED      497198843          1              6
06/20/2003 16:31:26 06/20/2003 16:31:39      210718
210753          13
          NOT_APPLIED      497198843          1              7
06/20/2003 16:31:39 06/20/2003 16:31:54      210753
210758          1
          NOT_APPLIED      497198843          1              8
06/20/2003 16:31:54 06/20/2003 16:31:59      210758
210789          11
```

Note: Enterprise Manager displays this information on the Log File Details page.

9.1.9 SendQEntries (Send Queue Entries)

The `SendQEntries` monitorable database property returns a table that shows all log files on the primary database that were not successfully archived to one or more standby databases. This property pertains to the primary database.

The table contains the following columns:

- STANDBY_NAME

The value can be empty or it can contain the database unique name (`DB_UNIQUE_NAME`) of a standby database. If empty, the `STATUS` column will contain a value of `CURRENT` or `NOT_ARCHIVED`.

- STATUS

The `STATUS` column is set to one of the following values:

- `CURRENT`: A log file to which online redo is currently being written.
- `NOT_ARCHIVED`: A completed online redo log file that has not been archived locally.
- `ARCHIVED`: A completed log file that has been archived locally but has not been transmitted to the standby database specified in the `STANDBY_NAME` column.

The table contains exactly one row with the value of `STATUS=CURRENT`. There can be multiple rows with the value `STATUS=ARCHIVED` or `STATUS=NOT_ARCHIVED`.

- RESETLOGS_ID

Resetlogs identifier associated with the archived redo log file

- THREAD

The redo thread number.

- LOG_SEQ

The log sequence number. Multiple rows may have the same LOG_SEQ value (for different STANDBY_NAME values).

- TIME_GENERATED

The first time when the online redo log file was written to the primary database.

- TIME_COMPLETED

The next time when the log file was archived on the primary database (corresponds to the NEXT_CHANGE# column).

- FIRST_CHANGE#

First change number in the archived redo log file.

- NEXT_CHANGE#

First change in the next log file.

- SIZE (KBs)

The SIZE of the online redo log file in kilobytes.

For example, the following shows output from a SHOW DATABASE command:

```
DGMGRL> SHOW DATABASE 'North_Sales' 'SendQEntries' ;
PRIMARY_SEND_QUEUE
      STANDBY_NAME      STATUS      RESETLOGS_ID
THREAD      LOG_SEQ      TIME_GENERATED      TIME_COMPLETED
FIRST_CHANGE#      NEXT_CHANGE#      SIZE (KBs)
DR_Sales  ARCHIVED      497198843
1          9 06/20/2003 16:31:59 06/20/2003 16:39:57
210789      211411      186
DR_Sales  ARCHIVED      497198843
1          10 06/20/2003 16:39:57 06/20/2003 16:40:01
211411      211415      1
DR_Sales  ARCHIVED      497198843
1          11 06/20/2003 16:40:01 06/20/2003 16:40:07
211415      211418      1
                                CURRENT      497198843
1          12 06/20/2003 16:40:07
211418      211418      1
```

Note: Enterprise Manager displays this information on the Log File Details page.

9.1.10 StatusReport (Status Report)

The StatusReport monitorable database property returns a table that provides a list of errors or warnings about the status of the database. In an Oracle RAC database environment, it also includes the status of all running instances. Each individual database has this property. The table contains the following columns in the order shown:

- INSTANCE_NAME

The value identifying the SID for the instance.

- ERROR_TEXT

Formatted error text.

- SEVERITY

The severity of the error message. The value is either WARNING or ERROR.

For example, the following shows output from a SHOW DATABASE command:

```
DGMGRL> SHOW DATABASE 'North_Sales' 'StatusReport' ;
STATUS REPORT
      INSTANCE_NAME  SEVERITY ERROR_TEXT
      sales1         ERROR ORA-16737: the redo transport service for
standby "DR_Sales" has an error
                *   ERROR ORA-16745: unable to add DB_UNIQUE_NAME DR_Sales
into the DG_CONFIG list because it is full
```

9.1.11 TopWaitEvents

The TopWaitEvents monitorable database property specifies the 5 events with the longest waiting time in the specified instance. The events and their waiting time are retrieved from V\$SYSTEM_EVENT. Each instance in the configuration has this property. This property is an instance level monitorable property. The table contains the following columns in the order shown:

- Event

The system wait event.

- Wait Time

The total amount of time waited for this event in hundredths of a second.

The following example shows output from a SHOW INSTANCE command:

```
DGMGRL> SHOW INSTANCE sales1 'TopWaitEvents';
TOP SYSTEM WAIT EVENTS
      Event                Wait Time
      rdbms ipc message    671350
SQL*Net message from client 62390
      pmon timer           47897
      Queue Monitor Wait   43016
      wakeup time manager  38508
```

9.2 Configurable Database Properties

Configurable database properties control the behavior of databases in a broker configuration. You can view and dynamically update the values of these properties using either DGMGRL or Enterprise Manager. However, some properties can only be updated through DGMGRL.

In most cases, the configurable database property is said to have **database scope**; meaning the value you set for the property applies uniformly to each instance of the database. However, in a few cases, the configurable database property is said to have **instance scope**; meaning, for a multiple-instance database environment, it is possible that the values of some particular properties may differ from one instance of the database to the next. [Table 9–1](#) lists each configurable database property and indicates if the scope of the property is database-wide or instance-specific. If the Scope column contains:

- Database—The value of the property is database wide, not instance or configuration specific.

- Instance—The value of the property is instance specific, not database or configuration specific.
- Configuration—The value of the property is configuration wide, not instance or database specific.

Table 9–1 Configurable Properties

Configurable Property Name	Scope	Pertains To
AlternateLocation	Instance	Redo transport services
ApplyInstanceTimeout	Database	Redo Apply and SQL Apply
ApplyParallel	Database	Redo Apply
ArchiveLagTarget	Database	Redo transport services
Binding	Database	Redo transport services
BystandersFollowRoleChange	Configuration	Fast-start failover
CommunicationTimeout	Configuration	Redo transport services
DbFileNameConvert	Database	Redo transport services
DelayMins	Database	Redo Apply and SQL Apply
DGConnectIdentifier	Database	Broker communication, Redo transport services
FastStartFailoverAutoReinstate	Configuration	Fast-start failover
FastStartFailoverLagLimit	Configuration	Fast-start failover
FastStartFailoverPmyShutdown	Configuration	Fast-start failover
FastStartFailoverTarget	Database	Fast-start failover
FastStartFailoverThreshold	Configuration	Fast-start failover
HostName	Instance	Instance identification
LogArchiveFormat	Instance	Redo transport services
LogArchiveMaxProcesses	Database	Redo transport services
LogArchiveMinSucceedDest	Database	Redo transport services
LogArchiveTrace	Instance	Diagnosis
LogFileNameConvert	Database	Redo transport services
LogShipping	Database	Redo transport services
LogXptMode	Database	Redo transport services
LsbyASkipCfgPr	Database	SQL Apply
LsbyASkipErrorCfgPr	Database	SQL Apply
LsbyASkipTxnCfgPr	Database	SQL Apply
LsbyDSkipCfgPr	Database	SQL Apply
LsbyDSkipErrorCfgPr	Database	SQL Apply
LsbyDSkipTxnCfgPr	Database	SQL Apply
LsbyMaxEventsRecorded	Database	SQL Apply
LsbyMaxSga	Instance	SQL Apply
LsbyMaxServers	Instance	SQL Apply
LsbyPreserveCommitOrder	Database	SQL Apply

Table 9–1 (Cont.) Configurable Properties

Configurable Property Name	Scope	Pertains To
LsbyRecordAppliedDdl	Database	SQL Apply
LsbyRecordSkipDdl	Database	SQL Apply
LsbyRecordSkipErrors	Database	SQL Apply
MaxConnections	Database	Redo transport services
MaxFailure	Database	Redo transport services
NetTimeout	Database	Redo transport services
ObserverConnectIdentifier	Database	Fast-start failover
PreferredApplyInstance	Database	Redo Apply and SQL Apply
RedoCompression	Database	Redo transport services
ReopenSecs	Database	Redo transport services
SidName	Instance	Instance identification
StandbyArchiveLocation	Instance	Redo transport services
StandbyFileManagement	Database	Redo Apply and SQL Apply

See Also: [Chapter 4](#) for more information about database property management

Note: When a broker configuration with its primary database is created and standby databases are added to the configuration, the broker imports existing settings from the databases to set many of the properties. If importing an existing setting fails, or if a property value is not imported, then the broker uses a broker default value. The default values and whether or not a property is imported is indicated within each property description.

9.2.1 AlternateLocation

The `AlternateLocation` configurable database property specifies an alternate disk location to store the archived redo log files in the standby when the location specified by the `StandbyArchiveLocation` configurable database property fails. The property has an instance scope, and the location it specifies has to be accessible by the instance.

Category	Description
Datatype	String
Valid values	Directory specification on system where the standby instance is located
Broker default	Empty string
Imported?	No
Parameter class	Dynamic
Role	Standby ¹
Standby type	Physical, logical, or snapshot

Category	Description
Corresponds to	<ul style="list-style-type: none"> ■ On the standby instance, the <code>LOCATION</code> attribute for the <code>LOG_ARCHIVE_DEST_n</code> initialization parameter that represents an alternate destination of the local destination that matches the configurable database property <code>StandbyArchiveLocation</code> ■ On the primary database, the <code>TEMPLATE</code> attribute for the <code>LOG_ARCHIVE_DEST_n</code> initialization parameter that represents an alternate destination
Scope	Instance
Enterprise Manager name	<code>Alternate Standby Location</code>

¹ Although this property is set for the standby instance, it is indirectly related to redo transport services for the primary database. The broker sets up both an alternate local destination on the standby instance and an alternate remote destination on the primary database.

Note: On a logical standby database, Oracle recommends the `LOCATION` attribute of the `LOG_ARCHIVE_DEST_n` initialization parameter for the local destination be different from the value of `AlternateLocation` configurable database property.

9.2.2 ApplyInstanceTimeout

The `ApplyInstanceTimeout` configurable database property specifies the number of seconds the broker waits after detecting the current apply instance failed before initiating the apply instance failover.

Category	Description
Datatype	Integer
Valid values	≥ 0 (seconds)
Broker default	0 (results in immediate apply instance failover)
Imported?	No
Parameter class	Not applicable
Role	Standby
Standby type	Physical or logical
Corresponds to	Not applicable
Scope	Database
Enterprise Manager name	Not applicable

9.2.3 ApplyParallel

The `ApplyParallel` configurable database property specifies whether Redo Apply should use multiple processes to apply redo data to the physical standby database. If Redo Apply is shut off, then setting the property has no immediate effect. However, when Redo Apply is running again, the value of the property is used to determine the parallel apply behavior of Redo Apply.

Category	Description
Datatype	String
Valid values	<ul style="list-style-type: none"> ▪ AUTO—the number of parallel processes used for Redo Apply is automatically determined by Oracle based on the number of CPUs that the system has. ▪ NO--no parallel apply
Broker default	AUTO
Imported?	No
Parameter class	Not applicable
Role	Standby
Standby type	Physical
Corresponds to	<ul style="list-style-type: none"> ▪ AUTO corresponds to the PARALLEL clause of the ALTER DATABASE RECOVER MANAGED STANDBY DATABASE statement ▪ NO corresponds to the NOPARALLEL clause of the ALTER DATABASE RECOVER MANAGED STANDBY DATABASE statement
Scope	Database
Enterprise Manager name	Not applicable

9.2.4 ArchiveLagTarget

The `ArchiveLagTarget` configurable database property limits the amount of data that can be lost and effectively increases the availability of the standby database by forcing a log switch after the amount of time you specify (in seconds) elapses. That way, the standby database will not miss redo records generated from a time range longer than the value set for the `ARCHIVE_LAG_TARGET` initialization parameter.

Category	Description
Datatype	Number
Valid values	Seconds (either 0 seconds, or any number from 60 to 7200 seconds)
Broker default	0 (disabled)
Imported?	Yes, from the <code>ARCHIVE_LAG_TARGET</code> initialization parameter
Parameter class	Dynamic
Role	Primary
Standby type	Not applicable
Corresponds to	<code>ARCHIVE_LAG_TARGET=seconds</code> initialization parameter
Scope	Database
Enterprise Manager name	Archive Lag Target

9.2.5 Binding

The `Binding` configurable database property specifies whether the standby destination is `MANDATORY` or `OPTIONAL`.

Category	Description
Datatype	String
Valid values	<ul style="list-style-type: none"> ■ MANDATORY You can specify a policy for reuse of online redo log files using the MANDATORY value. If the archiving operation of a mandatory destination fails, online redo log files cannot be overwritten. ■ OPTIONAL You can specify a policy for reuse of online redo log files using the OPTIONAL value. If the archiving operation of an optional destination fails, the online redo log files are overwritten.
Broker default	OPTIONAL
Imported?	Yes, from the BINDING column of the V\$ARCHIVE_DEST view of the primary database
Parameter class	Dynamic
Role	Standby ¹
Standby type	Physical, logical, or snapshot
Corresponds to	<ul style="list-style-type: none"> ■ MANDATORY and OPTIONAL attributes for the LOG_ARCHIVE_DEST_n initialization parameter of the primary database ■ BINDING column of the V\$ARCHIVE_DEST view of the primary database
Scope	Database
Enterprise Manager name	Not applicable

¹ Although this property is set for the standby database, it is indirectly related to the redo transport services for the primary database. The broker propagates the setting you specify on the standby database to the corresponding attributes of the LOG_ARCHIVE_DEST_n value of the primary database.

9.2.6 BystandersFollowRoleChange

The `BystandersFollowRoleChange` configuration property allows the user to decide whether the broker should determine whether bystander standby databases will be viable standby databases for the new primary database as part of performing a complete failover. Setting the property to `ALL` directs the broker to evaluate and detect each standby database that can be a viable standby database to the new primary database, as part of failover processing. Setting the property to `NONE` directs the broker to perform failover without evaluating standby database viability. This option decreases the processing time for failover, but disables broker management of all databases in the configuration. If fast-start failover is enabled, the observer will automatically reinstate and enable the standby databases after failover has completed. Otherwise you will have to manually reenable the standby databases after failover has completed.

Category	Description
Datatype	String
Valid value	ALL or NONE
Broker default	ALL
Imported?	No
Parameter class	Not applicable

Category	Description
Role	Primary and standby
Standby type	Not applicable
Corresponds to	Not applicable
Scope	Broker configuration. This property will be consumed by broker on the database that is the target of a complete failover.
Enterprise Manager name	Not applicable

9.2.7 CommunicationTimeout

The `CommunicationTimeout` configuration property allows you to decide how many seconds the broker should wait before timing out its network communication between databases in the configuration. A value of zero indicates that a network communication should never be timed out.

Category	Description
Datatype	Integer
Valid values	≥ 0
Broker default	180 seconds
Imported?	No
Parameter class	Not applicable
Role	Primary and standby
Standby type	Not applicable
Corresponds to	Not applicable
Scope	Broker configuration. This property will be consumed by broker on all databases in the configuration.
Enterprise manager name	Not applicable

9.2.8 DbFileNameConvert

The `DbFileNameConvert` configurable database property distinguishes standby datafile filenames from primary datafile filenames. You must set this property on all standby databases. If you add a datafile to the primary database, this property converts the datafile name on the primary database to the datafile on the standby database.

This property is used in the following situations:

- At standby mount time, it is used to rename primary datafile filenames to standby datafile filenames if the datafile file path on the standby system is different from the primary database system.
- When a new data file is created on the primary database, a corresponding new data file will be created on the standby database if the `StandbyFileManagement` configurable database property is set to `'AUTO'`. Oracle uses the data-file file-path mapping information from the `DbFileNameConvert` property to determine the standby file path of the new

standby data file. If the `StandbyFileManagement` property is set to 'MANUAL', you must add a corresponding file to the standby database.

Category	Description
Datatype	String
Valid values	<p>Set the value of this property to a list of string pairs:</p> <ol style="list-style-type: none"> 1. The first string is the substring found in the datafile names on the primary database. 2. The second string is the substring found in the datafile names on the standby database. <p>For example, ('string1', 'string2', 'string3', 'string4', ...)</p> <p>Where:</p> <ul style="list-style-type: none"> ▪ string1 is the substring of the primary database filename. ▪ string2 is the substring of the standby database filename. ▪ string3 is the substring of the primary database filename. ▪ string4 is the substring of the standby database filename.
Broker default	Empty string
Imported?	Yes, from the <code>DB_FILE_NAME_CONVERT</code> initialization parameter
Parameter class	Static
Role	Standby
Standby type	Physical
Corresponds to	<code>DB_FILE_NAME_CONVERT</code> initialization parameter
Scope	Database
Enterprise Manager name	DB File Name Convert

9.2.9 DelayMins

The `DelayMins` configurable database property specifies the number of minutes log apply services will delay applying the archived redo log data on the standby database. When the `DelayMins` property is set to the default value of 0 minutes, log apply services apply redo data as soon as possible.

If the `DelayMins` property is set to 0, start log apply services as follows:

- Start Redo Apply on physical standby databases using the following SQL statement:

```
ALTER DATABASE RECOVER MANAGED STANDBY DATABASE USING CURRENT LOGFILE;
```

- Start SQL Apply on logical standby databases using the following SQL statement:

```
ALTER DATABASE START LOGICAL STANDBY APPLY IMMEDIATE;
```

Category	Description
Datatype	Integer
Valid values	>=0 (minutes)
Broker default	0

Category	Description
Imported?	Yes, from the <code>DELAY_MINS</code> column of the <code>V\$ARCHIVE_DEST</code> view of the primary database
Parameter class	Dynamic
Role	Standby ¹
Standby type	Physical and logical
Corresponds to	<ul style="list-style-type: none"> ■ <code>DELAY</code> attribute for the <code>LOG_ARCHIVE_DEST_n</code> initialization parameter of the primary database ■ <code>DELAY_MINS</code> column of the <code>V\$ARCHIVE_DEST</code> view of the primary database ■ Options used to start Redo Apply and SQL Apply
Scope	Database
Enterprise Manager name	Apply Delay (mins)

¹ Although this property is set for the standby database, it is indirectly related to the redo transport services for the primary database. The broker propagates the setting you specify on the standby database to the corresponding attributes of the `LOG_ARCHIVE_DEST_n` value of the primary database.

9.2.10 DGConnectIdentifier

The `DGConnectIdentifier` configurable database property specifies the connection identifier the broker uses when making connections to a database. If using `DGMGRL`, you supply the value when you enter the `CREATE CONFIGURATION` or `ADD DATABASE` command. If using Enterprise Manager, the value is supplied automatically. If this is an Oracle RAC database, the value must:

- Allow all instances of an Oracle RAC database to be reached.
- Specify a service that all instances dynamically register with the listeners so that connect-time failover on an Oracle RAC database is possible.
- Have failover attributes set to allow for redo transport to allow the primary database's Redo Transport Services to continue shipping redo data to an Oracle RAC standby database, even if the receiving instance of that standby database has failed.

The value of this property is specified in the `SERVICE` attribute of the `LOG_ARCHIVE_DEST_n` parameter when the broker configures redo transport services on the primary database.

Category	Description
Datatype	String
Valid values	A connect identifier that can be used to connect to this database
Broker default	Not applicable
Imported?	No
Parameter class	Not applicable
Role	Primary and standby
Standby type	Physical, logical, or snapshot
Corresponds to	<code>SERVICE_NAME</code> attribute of the <code>LOG_ARCHIVE_DEST_n</code> initialization parameter of the primary database

Category	Description
Scope	Database
Enterprise Manager name	Not applicable

Note: Prior to Oracle Database release 11.1, the `DGConnectIdentifier` configurable database property was known as the `InitialConnectIdentifier` property. When upgrading a 10g configuration to Oracle Database release 11.1, the `InitialConnectIdentifier` value will be retained as the new `DGConnectIdentifier` value for that database.

If this is an Oracle RAC database, then before the upgrade, you must ensure that the `InitialConnectIdentifier` meets the criteria just listed for `DGConnectIdentifier`.

See Also: *Oracle Database Net Services Administrator's Guide*

9.2.11 FastStartFailoverAutoReinstate

The `FastStartFailoverAutoReinstate` configuration property causes the former primary database to be automatically reinstated if a fast-start failover was initiated because the primary database was either isolated or had crashed. To prevent automatic reinstatement of the former primary database in these cases, set this configuration property to `FALSE`. The broker never automatically reinstates the former primary database if a fast-start failover was initiated because a user configuration condition was detected or was requested by an application calling the `DBMS_DG.INITIATE_FS_FAILOVER` function.

Category	Description
Datatype	Boolean
Valid value	TRUE or FALSE
Broker default	TRUE
Imported?	No
Parameter class	Not applicable
Role	Primary and standby
Standby type	Not applicable
Corresponds to	Not applicable
Scope	Broker configuration. This property will be consumed by the observer after fast-start failover has been enabled.
Enterprise Manager name	Automatically Reinstate Primary

9.2.12 FastStartFailoverLagLimit

The `FastStartFailoverLagLimit` configuration property establishes an acceptable limit, in seconds, that the standby is allowed to fall behind the primary in

terms of redo applied, beyond which a fast-start failover will not be allowed. The lowest possible value is 10 seconds.

This property is used when fast-start failover is enabled and the configuration is operating in maximum performance mode.

Category	Description
Datatype	Integer
Valid value	Integral number of seconds. Must be greater than, or equal to, 10.
Broker default	30 seconds
Imported?	No
Parameter class	Not applicable
Role	Primary and standby
Standby type	Not applicable
Corresponds to	Not applicable
Scope	Broker configuration. This property will be consumed by the observer after fast-start failover has been enabled.
Enterprise Manager name	Lag Limit

9.2.13 FastStartFailoverPmyShutdown

The `FastStartFailoverPmyShutdown` configuration property causes the primary database to shut down if fast-start failover is enabled and `V$DATABASE.FS_FAILOVER_STATUS` indicates the primary has been `STALLED` for longer than `FastStartFailoverThreshold` seconds. A value of `TRUE` helps to ensure that an isolated primary database cannot satisfy user queries.

This property cannot be used to prevent the primary database from shutting down if a fast-start failover occurred because a user configuration condition was detected or was requested by an application by calling the `DBMS_DG.INITIATE_FS_FAILOVER` function.

Category	Description
Datatype	Boolean
Valid value	TRUE or FALSE
Broker default	TRUE
Imported?	No
Parameter class	Not applicable
Role	Primary and standby
Standby type	Not applicable
Corresponds to	Not applicable
Scope	Broker configuration. This property will be consumed by the observer after fast-start failover has been enabled.
Enterprise Manager name	Automatically Shutdown Primary

9.2.14 FastStartFailoverTarget

The `FastStartFailoverTarget` configuration property specifies the `DB_UNIQUE_NAME` of the database that will be the target of a fast-start failover when this database is the primary database. See Step 2 in [Section 5.5.2](#) for more information about setting this property.

Category	Description
Datatype	String
Valid value	<code>DB_UNIQUE_NAME</code> of the database that is the target of the fast-start failover.
Broker default	If only one physical or logical standby database exists, then the broker selects that as the default value for this property on the primary database when fast-start failover is enabled. If more than one physical or logical standby database exists, you must specify the <code>FastStartFailoverTarget</code> value explicitly, prior to enabling fast-start failover. For the target standby database, the broker automatically selects the current primary database as the value for this property when fast-start failover is enabled.
Imported?	No
Parameter class	Not applicable
Role	Primary or standby
Standby type	Physical or logical
Corresponds to	Not applicable
Scope	Database
Enterprise Manager name	Enterprise Manager displays the value for the current primary database on the Data Guard Overview page, along with whether or not fast-start failover has been enabled.

9.2.15 FastStartFailoverThreshold

The `FastStartFailoverThreshold` configuration property defines the number of seconds the observer attempts to reconnect to the primary database before initiating a fast-start failover to the target standby database. The time interval starts when the observer first loses connection with the primary database. If the observer is unable to regain a connection to the primary database within the specified time, then the observer initiates a fast-start failover. See Step 4 in [Section 5.5.2](#) for more information about setting this property. The observer ignores the threshold completely if a configurable fast-start condition is detected or an application has requested that fast-start failover be initiated.

Category	Description
Datatype	Integer
Valid value	Integral number of seconds. Must be greater than, or equal to, 6.
Broker default	30 seconds
Imported?	No
Parameter class	Not applicable
Role	Target standby database that is about to fail over to the primary role

Category	Description
Standby type	Not applicable
Corresponds to	Not applicable
Scope	Broker configuration. This property will be consumed by the observer after fast-start failover has been enabled.
Enterprise Manager name	Oracle Enterprise Manager presents this as "Failover Threshold" on the Data Guard Overview page.

9.2.16 HostName

The `HostName` configurable database property specifies the name of the host on which the instance that is specified by `SidName` configurable database property is running. You can update this property only when broker management of the database is disabled. You should only update the value when the host is renamed, in which case you need to disable broker management of the database, update the `HostName` property to match with the new host name, and then reenable broker management of the database.

Note: If the instance that is specified by the `SidName` property is started on a different host than was specified by `HostName`, the broker updates the value in `HostName` to match the actual name of the host, and broker management of the database may proceed.

Category	Description
Datatype	String
Valid values	Name of the host on which the instance is running
Broker default	Not applicable
Imported?	Yes
Parameter class	Not applicable
Role	Primary and standby
Standby type	Physical, logical, or snapshot
Corresponds to	<code>HOST_NAME</code> column of the <code>V\$INSTANCE</code> view
Scope	Instance
Enterprise Manager name	Not applicable

9.2.17 LogArchiveFormat

The `LogArchiveFormat` configurable database property specifies the format for filenames of archived redo log files using a database ID (`%d`), thread (`%t`), sequence number (`%s`), and resetlogs ID (`%r`).

Category	Description
Datatype	String
Valid values	<code>%d_%t_%s_%r</code>
Broker default	Empty string

Category	Description
Imported?	Yes, from the LOG_ARCHIVE_FORMAT initialization parameter on the primary database
Parameter class	Static
Role	Primary and standby
Standby type	Physical, logical, or snapshot
Corresponds to	LOG_ARCHIVE_FORMAT initialization parameter
Scope	Instance
Enterprise Manager name	Not applicable

9.2.18 LogArchiveMaxProcesses

The LogArchiveMaxProcesses configurable database property specifies the initial number of archiver processes (ARC*n*) the Oracle database invokes. The actual number of archiver processes in use may increase subsequently based on the archiving workload.

Category	Description
Datatype	Integer
Valid values	1 to 30
Broker default	4
Imported?	Yes, from the LOG_ARCHIVE_MAX_PROCESSES initialization parameter
Parameter class	Dynamic
Role	Primary and standby
Standby type	Physical, logical, or snapshot
Corresponds to	LOG_ARCHIVE_MAX_PROCESSES initialization parameter
Scope	Database
Enterprise Manager name	Archiver Processes

9.2.19 LogArchiveMinSucceedDest

The LogArchiveMinSucceedDest configurable database property controls when online redo log files are available for reuse. For the online redo log files to be available for reuse, archiving must succeed to a minimum number of destinations.

Category	Description
Datatype	Integer
Valid values	1 to 10
Broker default	1
Imported?	Yes, from the LOG_ARCHIVE_MIN_SUCCEED_DEST initialization parameter
Parameter class	Dynamic

Category	Description
Role	Primary
Standby type	Not applicable
Corresponds to	LOG_ARCHIVE_MIN_SUCCEED_DEST initialization parameter
Scope	Database
Enterprise Manager name	Not applicable

9.2.20 LogArchiveTrace

Set the `LogArchiveTrace` configurable database property to an integer value to see the progression of the archiving of online redo log files on the primary and the standby databases. The Oracle database writes an audit trail of the archived redo log files received from the primary database into process trace files.

Category	Description
Datatype	Integer
Valid values	<p>A valid value is the sum of any combination of any of the following values:</p> <ul style="list-style-type: none"> 0: Disable archive redo log tracing 1: Track archiving of online redo log file 2: Track archiving status of each archive redo log destination 4: Track archiving operational phase 8: Track ARCHIVELOG destination activity 16: Track detailed ARCHIVELOG destination activity 32: Track ARCHIVELOG destination parameter modifications 64: Track ARCn process state activity 128: Track FAL (fetch archive log) server related activities 256: Tracks RFS Logical Client 512: Tracks LGWR redo shipping network activity 1024: Tracks RFS physical client 2048: Tracks RFS/ARCn ping heartbeat 4096: Tracks real-time apply activity 8192: Tracks Redo Apply (media recovery or physical standby)
Broker default	255
Imported?	Yes, from the LOG_ARCHIVE_TRACE initialization parameter
Parameter class	Dynamic
Role	Primary and standby
Standby type	Physical, logical, or snapshot
Corresponds to	LOG_ARCHIVE_TRACE initialization parameter
Scope	Instance
Enterprise Manager name	Log Archive Trace

9.2.21 LogFileNameConvert

The `LogFileNameConvert` configurable database property converts the filename of an online redo log file on the primary database to the filename of a corresponding online redo log file on the standby database.

Category	Description
Datatype	String
Valid values	<p>Set the value of this property to a list of an even number of string pairs, separated by commas.</p> <ol style="list-style-type: none"> 1. The first string is the substring found in the datafile names on the primary database. 2. The second string is the substring found in the datafile names on the standby database. <p>For example, ('string1', 'string2', 'string3', 'string4', ...)</p> <p>Where:</p> <ul style="list-style-type: none"> ▪ string1 is the substring of the primary database filename. ▪ string2 is the substring of the standby database filename. ▪ string3 is the substring of the primary database filename. ▪ string4 is the substring of the standby database filename.
Broker default	Empty string
Imported?	Yes, from the <code>LOG_FILE_NAME_CONVERT</code> initialization parameter
Parameter class	Static
Role	Standby
Standby type	Physical
Corresponds to	<code>LOG_FILE_NAME_CONVERT</code> initialization parameter
Scope	Database
Enterprise Manager name	Log File Name Convert

9.2.22 LogShipping

The `LogShipping` configurable database property specifies whether or not redo transport services can send archived redo log files to the particular standby database. The broker uses the value of the `LogShipping` property only when the primary database is in the `TRANSPORT-ON` state:

- If the primary database is in the `TRANSPORT-OFF` state, then redo transport services to all standby databases are disabled, regardless of whether or not the `LogShipping` property is set to `ON` or `OFF`.
- If the primary database is in the `TRANSPORT-ON` state and the value of the `LogShipping` property is `ON`, then redo transport services are enabled to send archived redo data to the particular standby database. If the `LogShipping` property is `OFF`, then redo transport services are disabled to send archived redo data to the particular standby database.

Category	Description
Datatype	String

Category	Description
Valid values	ON or OFF
Broker default	ON
Imported?	No
Parameter class	Dynamic
Role	Standby ¹
Standby type	Physical, logical, or snapshot
Corresponds to	ENABLE and DEFER values for the LOG_ARCHIVE_DEST_STATE_1 initialization parameter of the primary database
Scope	Database
Enterprise Manager name	Log Shipping

¹ Although this property is set for the standby database, it is indirectly related to the redo transport services for the primary database. The broker propagates the setting you specify on the standby database to the corresponding attributes of the LOG_ARCHIVE_DEST_1 value of the primary database.

9.2.23 LogXptMode

The LogXptMode configurable database property enables you to set the redo transport service. You set the redo transport services on each standby database to one of the following modes:

- SYNC

Configures redo transport services for this standby database using the SYNC and AFFIRM attributes of the LOG_ARCHIVE_DEST_1 initialization parameter. Standby redo log files are required. This mode is required for the maximum protection or maximum availability data protection modes. This redo transport service enables the highest grade of data protection to the primary database, but also incurs the highest performance impact.

- ASYNC

Configures redo transport services for this standby database using the ASYNC and NOAFFIRM attributes of the LOG_ARCHIVE_DEST_1 initialization parameter. Standby redo log files are required. This mode enables a moderate grade of data protection to the primary database, and incurs a lower performance impact than SYNC.

Category	Description
Datatype	String
Valid values	SYNC or ASYNC
Broker default	ASYNC
Imported?	Yes, from the ARCHIVER, TRANSMIT_MODE, and AFFIRM columns of V\$ARCHIVE_DEST view of the primary database
Parameter class	Dynamic
Role	Standby ¹
Standby type	Physical, logical, or snapshot

Category	Description
Corresponds to	<ul style="list-style-type: none"> SYNC, ASYNC, AFFIRM, and NOAFFIRM attributes for the LOG_ARCHIVE_DEST_n initialization parameter of the primary database ARCHIVER, TRANSMIT_MODE, and AFFIRM columns of V\$ARCHIVE_DEST view of the primary database
Scope	Database
Enterprise Manager name	Redo Transport Service

¹ Although this property is set for the standby database, it is indirectly related to the redo transport services for the primary database. The broker propagates the setting you specify on the standby database to the corresponding attributes of the LOG_ARCHIVE_DEST_n value of the primary database.

See Also: [Chapter 4](#) for more information about setting data protection modes for redo transport services

9.2.24 LsbyASkipCfgPr

The `LsbyASkipCfgPr` configurable database property provides a way to add a skip specification to SQL Apply to control the apply service to skip (ignore) SQL statements that you do not want to apply to the logical standby database. The `SKIP` operation:

- Sets the criteria for identifying the SQL statements that will not be applied to the standby database
- Specifies any additional processing that will be done, if necessary

Specifying a value for this property has no effect and will be ignored if management of the standby database is disabled.

Category	Description
Datatype	String
Valid values	A valid set of arguments to the <code>DBMS_LOGSTDBY.SKIP</code> procedure
Broker default	Empty string
Imported?	No
Parameter class	Dynamic; SQL Apply does not require restart
Role	Standby
Standby type	Logical
Corresponds to	<code>DBMS_LOGSTDBY.SKIP</code> procedure
Scope	Database
Enterprise Manager name	Add Skip Table Entries

See Also: *Oracle Database PL/SQL Packages and Types Reference*

9.2.25 LsbyASkipErrorCfgPr

The `LsbyASkipErrorCfgPr` configurable database property adds a skip error specification to SQL Apply. It provides criteria to determine if an error should cause

SQL Apply to stop. All errors to be skipped are stored in system tables that describe how exceptions should be handled.

Specifying a value for this property has no effect and will be ignored if management of the standby database is disabled.

Category	Description
Datatype	String
Valid values	A valid set of arguments to the <code>DBMS_LOGSTDBY.SKIP_ERROR</code> procedure. The string must contain comma separators between the arguments.
Broker default	Empty string
Imported?	No
Parameter class	Dynamic; SQL Apply does not require restart
Role	Standby
Standby type	Logical
Corresponds to	<code>DBMS_LOGSTDBY.SKIP_ERROR</code> procedure
Scope	Database
Enterprise Manager name	Add Skip Table Entries

See Also: *Oracle Database PL/SQL Packages and Types Reference*

9.2.26 LsbyASkipTxnCfgPr

The `LsbyASkipTxnCfgPr` configurable database property skips over a transaction that caused SQL Apply to stop applying transactions to the logical standby database. This property enables you to specify the transaction ID (`XIDSN` NUMBER) of the problematic transaction that you want SQL Apply to ignore. Before you restart SQL Apply, you should issue a SQL transaction that will correctly update the logical standby database in place of the skipped transaction. Applying a compensating transaction will help keep the logical standby database transactionally consistent with the primary database.

Specifying a value for this property has no effect and will be ignored if management of the standby database is disabled.

Category	Description
Datatype	String
Valid values	A valid set of arguments to the <code>DBMS_LOGSTDBY.SKIP_TRANSACTION</code> procedure. Use comma separators between the arguments.
Broker default	Empty string
Imported?	No
Parameter class	Dynamic; SQL Apply does not require restart
Role	Standby
Standby type	Logical
Corresponds to	<code>DBMS_LOGSTDBY.SKIP_TRANSACTION</code> procedure

Category	Description
Scope	Database
Enterprise Manager name	Skip Edit Properties

Note: Enterprise Manager indirectly supports skipping a transaction using the Skip Edit Properties page.

See Also: *Oracle Database PL/SQL Packages and Types Reference*

9.2.27 LsbyDSkipCfgPr

The `LsbyDSkipCfgPr` configurable database property deletes an existing skip specification from SQL Apply. It reverses or removes the actions of the `LsbyASkipCfgPr` property by finding the record, matching all the parameters, and removing the record from the system table. The match must be exact, and multiple skip actions can be removed only by a matching number of unskip actions. You cannot remove multiple skip actions by using wildcard characters as a value to this property.

Specifying a value for this property has no effect and will be ignored if management of the standby database is disabled.

Category	Description
Datatype	String
Valid Values	A valid set of arguments to the <code>DBMS_LOGSTDBY.UNSKIP</code> procedure
Broker Default	Empty string
Imported?	No
Parameter Class	Dynamic; SQL Apply does not require restart
Role	Standby
Standby type	Logical
Corresponds to	<code>DBMS_LOGSTDBY.UNSKIP</code> procedure
Scope	Database
Enterprise Manager name	Remove Skip Table Entries

See Also: *Oracle Database PL/SQL Packages and Types Reference*

9.2.28 LsbyDSkipErrorCfgPr

The `LsbyDSkipErrorCfgPr` configurable database property deletes an existing skip error specification from SQL Apply. It reverses or removes the actions of the `LsbyASkipErrorCfgPr` property by finding the record, matching all of the parameters and removing the record from the system table. The match must be exact, and multiple skip actions can be removed only by a matching number of unskip actions. You cannot remove multiple skip actions by using wildcard characters as a value to this property.

Specifying a value for this property has no effect and will be ignored if management of the standby database is disabled.

Category	Description
Datatype	String
Valid values	A valid set of arguments to the <code>DBMS_LOGSTDBY.UNSKIP_ERROR</code> procedure. The string must contain comma separators between the arguments.
Broker default	Empty string
Imported?	No
Parameter class	Dynamic; SQL Apply does not require restart
Role	Standby
Standby type	Logical
Corresponds to	<code>DBMS_LOGSTDBY.UNSKIP_ERROR</code> procedure
Scope	Database
Enterprise Manager name	Remove Skip Table Entries

See Also: *Oracle Database PL/SQL Packages and Types Reference*

9.2.29 LsbyDSkipTxnCfgPr

The `LsbyDSkipTxnCfgPr` configurable database property reverses or removes the actions of the `LsbyASkipTxnCfgPr` property. The transaction IDs must match exactly, and multiple skip transaction actions can be removed only by a matching number of unskip transaction actions. You cannot remove multiple skip transaction actions by using wildcard characters as a value to this property.

Specifying a value for this property has no effect and will be ignored if management of the standby database is disabled.

Category	Description
Datatype	String
Valid values	A valid set of arguments to the <code>DBMS_LOGSTDBY.UNSKIP_TRANSACTION</code> procedure
Broker default	Empty string
Imported?	No
Parameter class	Dynamic; SQL Apply does not require restart
Role	Standby
Standby type	Logical
Corresponds to	<code>DBMS_LOGSTDBY.UNSKIP_TRANSACTION</code> procedure
Scope	Database
Enterprise Manager name	Not applicable

See Also: *Oracle Database PL/SQL Packages and Types Reference*

9.2.30 LsbyMaxEventsRecorded

The `LsbyMaxEventsRecorded` configurable database property specifies the number of events that will be stored in the `DBA_LOGSTDBY_EVENTS` table, which stores logical standby event information.

Category	Description
Datatype	Integer
Valid values	>=0
Broker default	0
Imported?	Yes, from the <code>MAX_EVENTS_RECORDED</code> row of <code>SYSTEM.LOGSTDBY\$PARAMETERS</code>
Parameter class	Dynamic; SQL Apply does not require restart
Role	Standby
Standby type	Logical
Corresponds to	<code>DBMS_LOGSTDBY.APPLY_SET('MAX_EVENTS_RECORDED')</code> and the <code>DBMS_LOGSTDBY.APPLY_UNSET('MAX_EVENTS_RECORDED')</code> procedures
Scope	Database
Enterprise Manager name	Max Events Recorded

9.2.31 LsbyMaxSga

The `LsbyMaxSga` configurable database property specifies the number of megabytes for the allocation of SQL Apply cache in the system global area (SGA). If the value is 0, SQL Apply uses one quarter of the value set for the `SHARED_POOL_SIZE` initialization parameter.

Category	Description
Datatype	Integer
Valid values	>=0
Broker default	0
Imported?	Yes, from the <code>MAX_SGA</code> row of <code>SYSTEM.LOGSTDBY\$PARAMETERS</code>
Parameter class	Dynamic; SQL Apply does not require restart
Role	Standby
Standby type	Logical
Corresponds to	<code>DBMS_LOGSTDBY.APPLY_SET('MAX_SGA')</code> and the <code>DBMS_LOGSTDBY.APPLY_UNSET('MAX_SGA')</code> procedures
Scope	Instance
Enterprise Manager name	Max SGA (MB)

9.2.32 LsbyMaxServers

The `LsbyMaxServers` configurable database property specifies the number of parallel query servers specifically reserved for SQL Apply. If the value is 0, SQL Apply uses all available parallel query servers to read the log files and apply changes.

Category	Description
Datatype	Integer
Valid values	>=0
Broker default	0
Imported?	Yes, from the MAX_SERVERS row of SYSTEM.LOGSTDBY\$PARAMETERS
Parameter class	Dynamic; SQL Apply does not require restart
Role	Standby
Standby type	Logical
Corresponds to	DBMS_LOGSTDBY.APPLY_SET('MAX_SERVERS') and the DBMS_LOGSTDBY.APPLY_UNSET('MAX_SERVERS') procedures
Scope	Instance
Enterprise Manager name	Max Servers

9.2.33 LsbyRecordAppliedDdl

The `LsbyRecordAppliedDdl` configurable database property controls whether or not SQL statements that were applied to the logical standby database are recorded in the `DBA_LOGSTDBY_EVENTS` table. Specify one of the following values:

- `TRUE`: DDL statements applied to the logical standby database are recorded in the `DBA_LOGSTDBY_EVENTS` table. This is the default setting.
- `FALSE`: Applied DDL statements are not recorded.

Category	Description
Datatype	String
Valid values	TRUE or FALSE
Broker default	TRUE
Imported?	Yes, from the RECORD_APPLIED_DDL row of SYSTEM.LOGSTDBY\$PARAMETERS
Parameter class	Dynamic; SQL Apply does not require restart
Role	Standby
Standby type	Logical
Corresponds to	DBMS_LOGSTDBY.APPLY_SET('RECORD_APPLIED_DDL') and the DBMS_LOGSTDBY.APPLY_UNSET('RECORD_APPLIED_DDL') procedures
Scope	Database
Enterprise Manager name	Record Applied DDL

9.2.34 LsbyRecordSkipDdl

The `LsbyRecordSkipDdl` configurable database property controls whether or not skipped DDL statements are recorded in the `DBA_LOGSTDBY_EVENTS` table. Specify one of the following values:

- TRUE: Skipped DDL statements are recorded in the DBA_LOGSTDBY_EVENTS table. This is the default setting.
- FALSE: Skipped DDL statements are not recorded in the DBA_LOGSTDBY_EVENTS table.

Category	Description
Datatype	String
Valid values	TRUE or FALSE
Broker default	TRUE
Imported?	Yes, from the RECORD_SKIP_DDL row of SYSTEM.LOGSTDBY\$PARAMETERS
Parameter class	Dynamic; SQL Apply does not require restart
Role	Standby
Standby type	Logical
Corresponds to	DBMS_LOGSTDBY.APPLY_SET('RECORD_SKIP_DDL') and the DBMS_LOGSTDBY.APPLY_UNSET('RECORD_SKIP_DDL') procedures
Scope	Database
Enterprise Manager name	Record Skip DDL

9.2.35 LsbyRecordSkipErrors

The `LsbyRecordSkipErrors` configurable database property controls whether or not skipped errors (as described by the `DBMS_LOGSTDBY.SKIP_ERROR` procedure) are recorded in the `DBA_LOGSTDBY_EVENTS` table. Specify one of the following values:

- TRUE: Skipped errors are recorded in the DBA_LOGSTDBY_EVENTS table.
- FALSE: Skipped errors are not recorded in the DBA_LOGSTDBY_EVENTS table.

Category	Description
Datatype	String
Valid values	TRUE or FALSE
Broker default	TRUE
Imported?	Yes, from the RECORD_SKIP_ERRORS row of SYSTEM.LOGSTDBY\$PARAMETERS
Parameter class	Dynamic; SQL Apply does not require restart
Role	Standby
Standby type	Logical
Corresponds to	DBMS_LOGSTDBY.APPLY_SET('RECORD_SKIP_ERRORS') and the DBMS_LOGSTDBY.APPLY_UNSET('RECORD_SKIP_ERRORS') procedures
Scope	Database
Enterprise Manager name	Record Skip Errors

9.2.36 LsbyPreserveCommitOrder

The `LsbyPreserveCommitOrder` configurable database property controls whether transactions are committed on the logical standby database in the exact same order in which they were committed on the primary database. Specify one of the following values:

- `TRUE`: Transactions are applied to the logical standby database in the exact order in which they were committed on the primary database.
- `FALSE`: Transactions containing non-overlapping sets of rows may be committed in a different order than they were committed on the primary database.

Category	Description
Datatype	String
Valid values	TRUE or FALSE
Broker default	TRUE
Imported?	Yes, from the <code>PRESERVE_COMMIT_ORDER</code> row of <code>SYSTEM.LOGSTDBY\$PARAMETERS</code>
Parameter class	Static; SQL Apply requires restart
Role	Standby
Standby type	Logical
Corresponds to	<code>DBMS_LOGSTDBY.APPLY_SET('PRESERVE_COMMIT_ORDER')</code> and <code>DBMS_LOGSTDBY.APPLY_UNSET('PRESERVE_COMMIT_ORDER')</code> procedures
Scope	Database
Enterprise Manager name	Preserve Commit Order

9.2.37 MaxConnections

The `MaxConnections` configurable database property specifies how many `ARCn` processes will be used in parallel to transmit redo data from a single archived redo log on the primary database to the archived redo log at the remote site. If the `MaxConnections` property is set to a nonzero value, redo transport services use multiple `ARCn` processes to transmit redo data to archived redo log files at the remote destinations.

Category	Description
Datatype	Integer
Valid values	≥ 0
Broker default	5
Imported?	Yes, from the <code>MAX_CONNECTIONS</code> column of the <code>V\$ARCHIVE_DEST</code> view for the primary database.
Parameter class	Dynamic
Role	Standby
Standby type	Physical, logical, or snapshot

Category	Description
Corresponds to	<ul style="list-style-type: none"> ▪ LOG_ARCHIVE_MAX_PROCESSES initialization parameter¹ ▪ MAX_CONNECTIONS attribute for the LOG_ARCHIVE_DEST_<i>n</i> initialization parameter of the primary database ▪ MAX_CONNECTIONS column of the V\$ARCHIVE_DEST view of the primary database

¹ The LOG_ARCHIVE_MAX_PROCESSES initialization parameter affects the actual number of ARC*n* processes used by an instance.

9.2.38 MaxFailure

The `MaxFailure` configurable database property specifies the maximum number of contiguous archiving failures before the redo transport services stop trying to transport archived redo log files to the standby database. A value of zero indicates that an unlimited number of failures are allowed.

Category	Description
Datatype	Integer
Valid values	>=0
Broker default	0
Imported?	Yes, from the MAX_FAILURE column of V\$ARCHIVE_DEST view of the primary database
Parameter class	Dynamic
Role	Standby ¹
Standby type	Physical, logical, or snapshot
Corresponds to	<ul style="list-style-type: none"> ▪ MAX_FAILURE attribute for the LOG_ARCHIVE_DEST_<i>n</i> initialization parameter of the primary database ▪ MAX_FAILURE column of the V\$ARCHIVE_DEST view of the primary database
Scope	Database
Enterprise Manager name	Not applicable

¹ Although this property is set for the standby database, it is indirectly related to the redo transport services for the primary database. The broker propagates the setting you specify on the standby database to the corresponding attributes of the LOG_ARCHIVE_DEST_*n* value of the primary database.

9.2.39 NetTimeout

The `NetTimeout` configurable database property specifies the number of seconds the LGWR waits for Oracle Net Services to respond to a LGWR request. It is used to bypass the long connection timeout in TCP. This property is only used when the `LogXptMode` configurable database property of the same database is set to `SYNC` or `ASYNC`.

Category	Description
Datatype	Integer
Valid values	0, 15 to 1200
Broker default	30

Category	Description
Imported?	Yes, from the <code>NET_TIMEOUT</code> column of <code>V\$ARCHIVE_DEST</code> view of the primary database
Parameter class	Dynamic
Role	Primary and Standby
Standby type	Physical, logical, or snapshot
Corresponds to	<ul style="list-style-type: none"> ■ <code>NET_TIMEOUT</code> attribute of the <code>LOG_ARCHIVE_DEST_n</code> initialization parameter of the primary database ■ <code>NET_TIMEOUT</code> column of <code>V\$ARCHIVE_DEST</code> view of the primary database
Scope	Database
Enterprise Manager name	Not applicable

9.2.40 ObserverConnectIdentifier

The `ObserverConnectIdentifier` configurable database property specifies a connect identifier that can be used by the observer to connect to this database. This can pertain only to the primary database, or to the target standby database when fast-start failover is enabled.

Category	Description
Datatype	String
Valid Values	A connect identifier that observer can use to connect to this database
Broker Default	Empty String ¹
Imported?	No
Parameter Class	Not applicable
Role	Primary and Standby
Standby Type	Physical or logical
Corresponds to	Not applicable
Scope	Database
Enterprise Manager name	Observer Connect Identifier

¹ When this is Empty String (not set by the user), the connect identifier specified by this database's `DGConnectIdentifier` property will be used by the observer.

9.2.41 PreferredApplyInstance

The `PreferredApplyInstance` configurable database property indicates that a particular instance is the preferred choice for serving log apply services. It is only used when the database is a standby RAC database. The value could be an empty string (default) which means the broker chooses the apply instance.

Category	Description
Datatype	String
Valid Values	The instance name (SID) or empty string

Category	Description
Broker Default	Empty string
Imported?	No
Parameter Class	Not applicable
Role	Standby
Standby Type	Physical or logical
Corresponds to	Not applicable
Scope	Database
Enterprise Manager name	Apply Instance

See Also: [Section 4.5.7](#) for more information

9.2.42 RedoCompression

The `RedoCompression` configurable database property is used to specify whether redo data is transmitted to a standby database in compressed form or uncompressed form when resolving redo data gaps.

Note: Redo transport compression is a feature of the Oracle Advanced Compression option. You must purchase a license for this option before using the redo transport compression feature.

Category	Description
Datatype	String
Valid value	DISABLE or ENABLE
Broker Default	DISABLE
Imported?	Yes, from the <code>COMPRESSION</code> column of the <code>V\$ARCHIVE_DEST</code> view of the primary database
Parameter class	Dynamic
Role	Standby ¹
Standby type	Physical, logical, or snapshot
Corresponds to	<ul style="list-style-type: none"> ▪ <code>COMPRESSION</code> attribute for the <code>LOG_ARCHIVE_DEST_n</code> initialization parameter of the primary database ▪ <code>COMPRESSION</code> column of the <code>V\$ARCHIVE_DEST</code> view of the primary database
Scope	Database
Enterprise Manager name	Not applicable

¹ Although this property is set for the standby database, it is indirectly related to the redo transport services for the primary database. The broker propagates the setting you specify on the standby database to the corresponding attributes of the `LOG_ARCHIVE_DEST_n` value of the primary database.

9.2.43 ReopenSecs

The `ReopenSecs` configurable database property specifies the minimum number of seconds before the archiver process (`ARCn`, foreground, or log writer process) should try again to access a previously failed destination.

Category	Description
Datatype	Integer
Valid values	>=0 seconds
Broker default	300
Imported?	Yes, from the <code>REOPEN_SECS</code> column of <code>V\$ARCHIVE_DEST</code> view of the primary database
Parameter class	Dynamic
Role	Standby ¹
Standby type	Physical, logical, or snapshot
Corresponds to	<ul style="list-style-type: none"> ■ <code>REOPEN</code> attribute for the <code>LOG_ARCHIVE_DEST_n</code> initialization parameter of the primary database ■ <code>REOPEN_SECS</code> column of the <code>V\$ARCHIVE_DEST</code> view of the primary database
Scope	Database
Enterprise Manager name	Not applicable

¹ Although this property is set for the standby database, it is indirectly related to the redo transport services for the primary database. The broker propagates the setting you specify on the standby database to the corresponding attributes of the `LOG_ARCHIVE_DEST_n` value of the primary database.

9.2.44 SidName

The `SidName` configurable database property specifies the SID of the instance. The property can only be updated when broker management of the database is disabled. You should only update the value when the SID is changed, in which case you need to disable broker management of the database, update the `SidName` property to match with the new SID, and reenale broker management of the database.

Note: If no existing instance object in the broker configuration, for the database object whose name matches this instance's `db_unique_name`, has a `SidName` property with a value that matches this instance's actual SID, then the broker will create a new instance object for this database that has this instance's `db_unique_name`. See [Section 1.3, "Data Guard Broker Management Model"](#) for more information.

Category	Description
Datatype	String
Valid values	SID of the instance
Broker default	Not applicable
Imported?	Yes

Category	Description
Parameter class	Not applicable
Role	Primary and standby
Standby type	Physical, logical, or snapshot
Corresponds to	INSTANCE_NAME column of the V\$INSTANCE view
Scope	Instance
Enterprise Manager name	Not applicable

9.2.45 StandbyArchiveLocation

The `StandbyArchiveLocation` configurable database property specifies the location of archived redo log files arriving from a primary database. Oracle recommends that you always explicitly set the value.

Category	Description
Datatype	String
Valid values	Nonempty file specification of the location of archived redo log files on the standby database. Use <code>DB_RECOVERY_FILE_DEST</code> if database recovery area is desired.
Broker default	<code>dgsby_db_unique_name</code>
Imported?	Yes, from the <code>DESTINATION</code> column of the <code>V\$ARCHIVE_DEST</code> fixed view of the standby database where the destination is a local destination and where the <code>VALID_FOR</code> attribute is compatible with the string <code>(STANDBY_ROLE, STANDBY_LOGFILE)</code> ; if no such destination exists, import is from the <code>STANDBY_ARCHIVE_DEST</code> initialization parameter. Note that the <code>STANDBY_ARCHIVE_DEST</code> parameter has been deprecated and is supported for backward compatibility only.
Parameter class	Dynamic
Role	Standby
Standby type	Physical, logical, or snapshot
Corresponds to	<ul style="list-style-type: none"> ▪ <code>LOCATION</code> attribute of the <code>LOG_ARCHIVE_DEST_n</code> initialization parameter of the standby database with <code>VALID_FOR</code> compatible with <code>(STANDBY_ROLE, STANDBY_LOGFILE)</code> ▪ <code>DESTINATION</code> column of the <code>V\$ARCHIVE_DEST</code> view of the standby database
Scope	Instance
Enterprise Manager name	Standby Archive Location

Note: On a logical standby database, Oracle recommends the `LOCATION` attribute of the `LOG_ARCHIVE_DEST_n` initialization parameter for the local destination be different from the value of `StandbyArchiveLocation` property, unless you are using database recovery area.

9.2.46 StandbyFileManagement

The `StandbyFileManagement` configurable database property affects how the add datafile operation on the primary database is applied on the standby database. If this property is set to `AUTO`, in conjunction with valid settings in the `DbFileNameConvert` configurable database property, a corresponding new datafile is automatically created on the standby database. The location of this new standby datafile is determined by the value of the `DbFileNameConvert` property.

If this property is set to `MANUAL`, you have to create the correct new datafile on the standby database manually.

Category	Description
Datatype	String
Valid values	<code>AUTO</code> or <code>MANUAL</code>
Broker default	<code>AUTO</code>
Imported?	Yes, from the <code>STANDBY_FILE_MANAGEMENT</code> initialization parameter
Parameter class	Dynamic
Role	Standby
Standby type	Physical, logical, or snapshot
Corresponds to	<code>STANDBY_FILE_MANAGEMENT</code> initialization parameter
Scope	Database
Enterprise Manager name	Not applicable

Troubleshooting Data Guard

This chapter describes various errors and how to solve them. It contains the following topics:

- [Sources of Diagnostic Information](#)
- [General Problems and Solutions](#)
- [Troubleshooting Problems During a Switchover Operation](#)
- [Troubleshooting Problems During a Failover Operation](#)
- [Troubleshooting Problems with the Observer](#)

10.1 Sources of Diagnostic Information

The Data Guard broker provides information about its activities in several forms:

- Database status information (see [Section 4.9](#))
- Oracle alert log files

The broker records key information in the alert log file for each database. You can check the alert log files for such information when troubleshooting Data Guard.

- Data Guard "broker log files"

For each database in a broker configuration, the broker DMON process records important behavior and status information in a "broker log file," useful in diagnosing Data Guard failures.

The broker log file is created in the same directory as the alert log and is named `drc<$ORACLE_SID>.log`.

10.2 General Problems and Solutions

This section describes general problems and solutions. This section contains the following topics:

- [ORA-16596: Object Not Part of the Data Guard Broker Configuration](#)
- [Redo Accumulating on the Primary Is Not Sent to Some Standby Databases](#)
- [Many Log Files Are Received on a Standby Database But Not Applied](#)
- [The Primary Database is Flashed Back](#)

10.2.1 ORA-16596: Object Not Part of the Data Guard Broker Configuration

A request was issued to the broker, but the database instance through which you have connected is no longer a part of the broker configuration. You may see this error when the broker fails to locate a broker configuration profile for the database upon which it is running.

Solution Reconnect to the configuration through another database that you know is part of the broker configuration. Confirm that a database exists in the broker configuration that has a name that matches the `db_unique_name` value of the database that returned the ORA-16596 error.

This problem can also occur if you attempt to enable a configuration, but the broker configuration file for one of its databases was accidentally removed or is outdated. In this case, remove the database from the broker configuration, manually delete the configuration file for that standby database (not for the primary database), and try again to enable the configuration. After the configuration is enabled, to create a new database profile for the previously deleted standby database, you can either use the Enterprise Manager Add Standby Database wizard and choose the Add existing standby database option, or you can use the DGMGRL command-line interface and issue the `ADD DATABASE` command.

10.2.2 Redo Accumulating on the Primary Is Not Sent to Some Standby Databases

By viewing the Log File Details page in Enterprise Manager, you have determined that log files are accumulating on the primary database and are not being archived to some of the standby databases in the broker configuration.

Solution To narrow down the problem, do the following:

- Verify that the state of the primary database is in the `TRANSPORT-ON` state (not `TRANSPORT-OFF`).
- Verify that the value of the `LogShipping` configurable database property of the standby database in question is `ON`.
- Check the status of the redo transport services on the primary database using the `LogXptStatus` monitorable database property. If redo transport services have an error, then use the error message to determine further checking and resolution action. For example:
 - If the error indicates the standby database is not available, you need to restart the standby database.
 - If the error indicates no listener, you need to restart the listener.
 - If the error indicates the standby database has no local destination, you need to set up a standby location to store archived redo log files from the primary database.

10.2.3 Many Log Files Are Received on a Standby Database But Not Applied

By viewing the Performance page or Log File Details page in Enterprise Manager, you have determined that the standby database accumulates too many log files without applying them.

Solution There are many possible reasons why archived redo log files might not be applied to the standby database. Investigate why the log files are building up and rule out the valid reasons.

If the current status of the standby database is not normal:

- Determine whether or not the log apply services might be unexpectedly stopped. See the ORA-16766 (for physical standby databases) or ORA-16768 (for logical standby databases) error description and solution statement for more help.
- If this is a logical standby database, check to see if a failed transaction has occurred.
- If you want to suppress the error while you investigate the problem, you can temporarily disable broker management of the database.

See Also: [Chapter 8](#) for additional information about disabling the database using the DGMGRL command-line interface

If the current status of the standby database is normal:

- Verify the state of the standby database is `APPLY-ON` (not in the `APPLY-OFF` state).
- Verify the state of the primary database is `TRANSPORT-ON` (not in the `TRANSPORT-OFF` state).

See Also: [Chapter 9](#) for additional information about the `LogShipping` configurable database property

- Check to see if log files are building up because the value of the `DelayMins` property is set too large. (Log apply services will delay applying the archived redo log files on the standby database for the number of minutes specified.)

See Also: [Chapter 9](#) for additional information about the `DelayMins` configurable database property

- If you cannot see any errors, compare the archive rate to the apply rate on the Performance page in Enterprise Manager to see if the apply rate is lower than the archive rate.

10.2.4 The Request Timed Out or Enterprise Manager Performance Is Sluggish

If the broker requests are not completing within the normal timeout parameters, try the following actions to solve the problem:

1. Verify the network is operating appropriately.
2. Try to ping all of the nodes in the configuration.
3. Try reconnecting through another database to retry the operation.
4. Run the `VERIFY` command from the configuration to see which broker is busy. The output from the `VERIFY` command should show why, or at least on which database, the broker is not able to process the requests.

10.2.5 The Primary Database is Flashed Back

If the primary database is flashed back, the standby databases in the configuration must be also be flashed back or reenabled to be viable targets for switchovers or failovers. The broker will report errors for the standby databases if the primary database has been flashed back.

For more information about restoring the viability of a standby database that was disabled by the broker, see [Section 5.4.3](#).

10.3 Troubleshooting Problems During a Switchover Operation

If the switchover fails due to problems with the configuration, the broker reports any problems it encounters in the alert log files or in the broker log files (see [Section 10.1](#)). In general, you can choose another database for the switchover or restore the configuration to its pre-switchover state and then retry the switchover. The following subsections describe how to recover from the most common problems.

If fast-start failover is enabled, the broker does not allow switchover to any standby database except to the target standby database. In addition, switchover to the target standby database is allowed only when the value of the `FS_FAILOVER_STATUS` column in the `V$DATABASE` view on the target standby database is either `READY` or `SUSPENDED`.

See Also: [Section 5.5.2.1, "When Fast-Start Failover Is Enabled and the Observer Is Running"](#)

10.3.1 Failed Switchovers to Physical Standby Databases

Examine the alert and DRC log files on the original primary and the target standby databases to determine the cause of the failure. The following sections describe the steps necessary to recover from a failed switchover to a physical standby, based on the types of errors contained in the log files:

- [Failure to Convert the Original Primary Database](#)
- [Failure to Convert Target Physical Standby Database](#)
- [Failure to Open New Primary Database](#)

10.3.1.1 Failure to Convert the Original Primary Database

If the broker switchover failed and the `DATABASE_ROLE` column of the `V$DATABASE` view contains a value of `PRIMARY`, take the following steps:

1. Disable fast-start failover if it is enabled.
2. If the old primary database has been closed, open it.
3. Correct the errors reported in the alert and DRC log files.
4. Retry the broker switchover.
5. Reenable fast-start failover if it was disabled in Step 1.

If the `DATABASE_ROLE` column of `V$DATABASE` contains a value of `PHYSICAL STANDBY`, then you can perform either one of the following procedures:

1. Disable fast-start failover if it is enabled.
2. Connect to the new physical standby database (original primary database) and disable the broker configuration.
3. Restart the new physical standby database.
4. Use the `ALTER DATABASE SWITCHOVER TO PRIMARY DATABASE SQL` statement to convert the new physical standby database back into a primary database.
5. Open the new primary database.
6. Reenable the broker configuration.
7. Reenable fast-start failover if it was disabled in step 1.

8. Reattempt the broker switchover.

OR

1. Disable fast-start failover if it is enabled.
2. Connect to the new physical standby database (original primary database) and remove the broker configuration.
3. Connect to target standby database.
4. Use the `ALTER DATABASE SWITCHOVER TO PRIMARY DATABASE SQL` statement to complete the switchover to the target physical standby.
5. Open the new primary database.
6. Shut down and restart the new physical standby database.
7. Connect to the new primary database and re-create the broker configuration.
8. Enable the broker configuration.
9. Reenable fast-start failover if it was disabled in step 1.

10.3.1.2 Failure to Convert Target Physical Standby Database

If the broker switchover failed and the `DATABASE_ROLE` column of the `V$DATABASE` view on the target physical standby database contains a value of `PHYSICAL STANDBY`, take the following steps:

1. Disable fast-start failover if it is enabled.
2. Check the alert and DRC log files to see what caused the switchover to fail and correct it. Once the problem has been corrected you can perform either one of the following procedures:
 - a. Connect to the new physical standby database and disable the configuration.
 - b. Shut down and restart the new physical standby.
 - c. Use the `ALTER DATABASE SWITCHOVER TO PRIMARY DATABASE SQL` statement to convert the new physical standby database back into a primary database.
 - d. Reenable the configuration.
 - e. Reattempt the switchover.

OR

- a. Connect to the new physical standby database (original primary database) and remove the broker configuration.
- b. Use the `ALTER DATABASE SWITCHOVER TO PRIMARY DATABASE SQL` statement to complete the switchover to the target physical standby.
- c. Shut down and restart the new physical standby.
- d. Connect to the new primary database and re-create the broker configuration.
- e. Enable the broker configuration.
3. Reenable fast-start failover if it was disabled in Step 1.

10.3.1.3 Failure to Open New Primary Database

If the broker switchover failed because the new primary database could not be opened, follow these steps:

1. Disable fast-start failover if it is enabled.
2. Connect to the new physical standby database (original primary database) and remove the broker configuration.
3. Check the new primary database's alert log file to see what prevented the database from opening and correct it, and then open the database.
4. Shut down and restart the new physical standby database.
5. Connect to the new primary database and re-create the broker configuration.
6. Enable the broker configuration.
7. Reenable fast-start failover if it was disabled in Step 1.

10.3.2 Failed Switchovers to Logical Standby Databases

Examine the alert and DRC log files on the original primary and the target standby databases to determine the cause of the failure. The following sections describe the steps necessary to recover from a failed switchover to a logical standby, based on the types of errors contained in the log files:

- [Failure to Convert Original Primary Database](#)
- [Failure to Convert Target Logical Standby Database](#)

10.3.2.1 Failure to Convert Original Primary Database

If the broker switchover failed because there was an error converting the primary database, take the following steps:

1. Disable fast-start failover if it is enabled.
2. Disable the broker configuration.
3. Take the corrective actions described in *Oracle Data Guard Concepts and Administration*.

If after taking corrective action, you have:

- Restored the original primary database to the primary role, take the following steps:
 - a. Reenable the broker configuration.
 - b. Retry the broker switchover.
 - Manually switched over the target logical standby to a primary database, take the following steps:
 - a. Connect to the original primary database and remove the broker configuration.
 - b. Connect to the target logical standby database and convert it to a primary database using the `ALTER DATABASE COMMIT TO SWITCHOVER TO PRIMARY SQL` statement.
 - c. Connect to the new primary database and re-create the broker configuration.
 - d. Enable the broker configuration.
4. Enable fast-start failover if it was disabled in step 1.

10.3.2.2 Failure to Convert Target Logical Standby Database

If the broker switchover failed and the `DATABASE_ROLE` column of the `V$DATABASE` view contains a value of `PRIMARY`, or if the column contains a value of `LOGICAL STANDBY` and you intend to complete the switchover, follow these steps:

1. Disable fast-start failover if it is enabled.
2. Connect to the target logical standby database and disable the broker configuration.
3. Take the corrective actions described in *Oracle Data Guard Concepts and Administration*.
4. Reenable the broker configuration.
5. Enable fast-start failover if it was disabled in step 1.

10.3.3 Additional Problems That May Occur During a Switchover Operation

Problem: The broker switchover fails due to problems with redo transport services.

Solution: Verify the state and status of the primary and standby database by viewing its information on the Data Guard Overview page or through `DGMGRL CLI SHOW DATABASE` commands.

Then run the Verify operation after the switchover completes to examine the alert log file of the new primary database and to verify the status of the configuration.

See Also:

- [Chapter 6](#) for additional information about the Data Guard Overview page
- [Section 6.8.1](#) for additional information about verifying the configuration

Problem: The switchover may fail during verification checks done by Data Guard broker (for example, redo transport services might return errors on a database that is involved in the switchover).

Solution: Choose another database for the switchover or fix the problem by transporting the archived redo log files.

10.4 Troubleshooting Problems During a Failover Operation

Although it is possible for a failover to stop, it is unlikely. If an error occurs, it is likely to happen when the standby database is transitioning to the primary role. Use these guidelines to fix the problem and continue the broker failover.

10.4.1 Failed Failovers to Physical Standby Databases

Use the steps below to recover from a failed broker failover to a physical standby database.

10.4.1.1 Failed Broker Complete Physical Failovers

Examine the alert and DRC log files on the target standby database to determine the cause of the failure and correct the problem. If the `ALTER DATABASE RECOVER`

MANAGED STANDBY DATABASE FINISH SQL statement returned an error, or if the statement completes successfully but the database could not be converted to a primary database, follow these steps:

1. Connect to the target standby database and disable fast-start failover using the FORCE option if it is enabled.
2. Then you can either:
 - Connect to another physical standby database and attempt a broker complete failover.
 - Perform a broker immediate failover to the target physical standby database.
3. Reinstall the original primary database and any bystander physical standby databases that are disabled with a status of reinstatement required (ORA-16661).
4. Reenable fast-start failover if it was disabled in step 1.

10.4.1.2 Failed Broker Immediate Physical Failovers

Examine the alert and DRC log files on the target standby database to determine the cause of the failure and correct the problem. If the problem can be corrected, retry the broker immediate failover. Otherwise connect to another physical standby database and attempt either a broker complete or immediate failover.

10.4.2 Failed Failovers to Logical Standby Databases

1. Examine the alert and DRC log files on the target standby database to determine the cause of the failure and correct the problem.
2. Connect to the target standby database and disable fast-start failover using the FORCE option if it is enabled.
3. Retry the broker failover.
4. Reinstall the old primary database. All bystander standby databases will be re-created from a copy of the new primary database.
5. Reenable fast-start failover if it was disabled in step 1.

If broker failover continues to fail, you should stop the broker on all databases in the Data Guard configuration (set the DG_BROKER_START initialization parameter to FALSE). Remove the Data Guard broker configuration files from all databases. Attempt a manual failover using the guidelines for role transitions in *Oracle Data Guard Concepts and Administration*.

Note: You can enable or disable the broker configuration using DGMGRL ENABLE CONFIGURATION and DISABLE CONFIGURATION commands. You cannot disable the configuration using the Enterprise Manager. You can only enable the configuration using Enterprise Manager if it was previously disabled using DGMGRL.

10.5 Troubleshooting Problems with the Observer

The observer continuously monitors the fast-start failover environment to ensure the primary database is available. Installing and starting the observer is an integral part of using fast-start failover. The following sections describe techniques for troubleshooting the observer:

- [Problems Starting the Observer](#)
- [Problems Because the Observer Has Stopped](#)
- [Capturing Observer Actions in the Observer Log File](#)

10.5.1 Problems Starting the Observer

Only one observer can be observing the broker configuration at any given time. If you attempt to start a second observer, one of the following errors is returned:

```
ORA-16647: could not start more than one observer
DGM-16954: Unable to open and lock the Observer configuration file
```

Use the `DGMGRL SHOW CONFIGURATION VERBOSE` command to determine the location of the observer that is currently associated with the broker configuration.

```
DGMGRL> SHOW CONFIGURATION VERBOSE;
Configuration
Name:                DRSolution
Enabled:             YES
Protection Mode:    MaxAvailability
Databases:
  North_Sales - Primary database
  DR_Sales    - Physical standby database
               - Fast-Start Failover target

Fast-Start Failover: ENABLED
Threshold:          30 seconds
Target:             DR_Sales
Observer:        o_host
Lag Limit:          30 seconds (not in use)
Shutdown Primary:  TRUE
Auto-reinstate:    TRUE

Current status for "DRSolution":
SUCCESS
```

10.5.2 Problems Because the Observer Has Stopped

If the observer host machine crashes, the broker configuration is no longer observed and fast-start failover is no longer possible. In this case, you may have to move the observer to a new host if the original host machine cannot be repaired in a timely fashion. To move the observer, you must stop allowing the first observer to observe this broker configuration, and then start a new observer on another host.

1. Issue the `DGMGRL STOP OBSERVER` command to sever the link between the original observer and the broker configuration:

```
DGMGRL> STOP OBSERVER;
Done.
```

2. Issue the `DGMGRL SHOW CONFIGURATION VERBOSE` and the `SHOW DATABASE` commands to verify that the configuration is no longer being observed:

```
DGMGRL> SHOW CONFIGURATION VERBOSE;
Configuration
Name:                DRSolution
Enabled:             YES
Protection Mode:    MaxAvailability
Databases:
  North_Sales - Primary database
```

```

DR_Sales      - Physical standby database
               - Fast-Start Failover target

Fast-Start Failover: ENABLED
Threshold:      30 seconds
Target:        DR_Sales
Observer:    (none)
Lag Limit:     30 seconds (not in use)
Shutdown Primary: TRUE
Auto-reinstate: TRUE

Current status for "DRSolution":
Warning: ORA-16608: one or more databases have warnings

DGMGRL> SHOW DATABASE 'North_Sales';

Database
Name:          North_Sales
Role:          PRIMARY
Enabled:       YES
Intended State: TRANSPORT-ON
Instance(s):
  sales1

Current status for "DR_Sales"
Error: ORA-16658: unobserved fast-start failover configuration

```

3. Note that you do not need to issue the DGMGRL `SHOW` commands to verify that the observer has actually stopped. Successful completion of the DGMGRL `STOP OBSERVER` command will allow a new observer to become associated with the configuration.

10.5.3 Capturing Observer Actions in the Observer Log File

You can use the DGMGRL `-logfile` option to start the observer, so that all of the troubleshooting actions performed in [Section 10.5.1](#) can be captured in a file. For example:

```
% dgmgrl -logfile observer.log / "start observer"
```

All the observer output is then recorded in a file named `observer.log` in the current working directory where you issued the DGMGRL command.

Note that this is not only useful for troubleshooting problems with the observer, but also for troubleshooting problems with fast-start failover in general.

Changed and Deprecated Features

This appendix describes the Data Guard broker features that were changed, deprecated, or made obsolete. This appendix provides the following sections:

- [Changed Features](#)
- [Deprecated and Obsolete Features](#)

A.1 Changed Features

This section contains information about Data Guard broker features that were changed:

- [General Features That Changed](#)
- [Changed Properties](#)
- [Changed State Names](#)
- [Changed DGMGRL Features in Release 10.2](#)

A.1.1 General Features That Changed

The following sections list features that have changed:

- [Changed Features in Release 11.1](#)
- [Changed Features in Release 10.2](#)

A.1.1.1 Changed Features in Release 11.1

- Changed database startup behavior.

The Data Guard broker honors the startup option specified by the database administrator. This removes the current requirement that databases belonging in a Data Guard configuration only be mounted. Previously, a primary or a logical standby database would be opened even if the DBA had only mounted it, but this will no longer happen. This also means that Data Guard actions will not start taking place until the database is opened in the case of a primary or a logical standby database. The DBA must explicitly open the database.

- Database States and descriptions have changed.

See [Table A-3, "Database State Name Changes in Release 11.1"](#)

- The `ADD DATABASE CONNECT IDENTIFIER IS` clause is now optional if a pre-existing standby is being added to the configuration.

A.1.1.2 Changed Features in Release 10.2

- Changed failover behavior

After failover to a logical standby database, the broker disables all standby databases in the configuration that were not directly involved in the failover. The disabled databases must be reenabled before they can serve as standby to the new primary database. Previously, failover to a logical standby database resulted in the broker disabling only physical standby databases.
- Changed behavior for the `DelayMins` configurable database property

When the `DelayMins` property is set to 0, log apply services apply redo data to the standby database as soon as possible, including using real-time apply if the standby database is configured with standby redo logs.

Additionally, if you specified the `DelayMins` and `RealTimeApply` properties on your release 10.1 database, the delay behavior might change unexpectedly. This is due to the `RealTimeApply` property being deprecated in release 10.2

For example, if your release 10.1 database had the `DelayMins` property set to a nonzero value and the `RealTimeApply` property set to `YES`, the delay setting was ignored because the real-time apply setting overrides any delay settings. However, because in release 10.2 the `RealTimeApply` property is deprecated, the release 10.2 database will no longer be affected by the `RealTimeApply` property and the application of redo according to the time specified by the `DelayMins` property may be unexpectedly delayed.

A.1.2 Changed Properties

The following sections list properties that have changed:

- [Changed Properties in Release 11.1](#)
- [Changed Properties in Release 10.2](#)

A.1.2.1 Changed Properties in Release 11.1

The following properties were changed in release 11.1:

Table A-1 *Changed Properties in Release 11.1*

Property Name	Description of Change
<code>InitialConnectIdentifier</code>	<p>This property has been changed to <code>DGConnectIdentifier</code>. The value of <code>DGConnectIdentifier</code> will be used for all Data Guard network traffic, all of the time.</p> <p>When upgrading a 10g configuration to Oracle Database release 11.1, the <code>InitialConnectIdentifier</code> value will be retained as the new <code>DGConnectIdentifier</code> value for that database. Before the upgrade, you must ensure that the <code>InitialConnectIdentifier</code> will reach all instances if this is an Oracle RAC database.</p>
<code>LsbyTxnConsistency</code>	This property has been changed to <code>LsbyPreserveCommitOrder</code>

A.1.2.2 Changed Properties in Release 10.2

The following properties were changed in release 10.2:

Table A-2 Changed Properties in Release 10.2

Property Name	Description of Change
ApplyInstanceTimeout	The default value has changed from 120 seconds to 0 seconds.
ApplyParallel (configurable property)	<ul style="list-style-type: none"> ■ New default value is AUTO ■ Can no longer specify the number of processes to use for Redo Apply
DelayMins	<p>Using this property is the preferred method for delaying the application of redo data to a standby database. If you set DelayMins property to 0:</p> <ul style="list-style-type: none"> ■ Any previously configured DelayMins setting will be ignored. ■ The standby database will apply redo data as soon as possible, including using real-time apply if the standby database is configured with standby redo logs. <p>If you have more than one physical standby database in the configuration, Oracle recommends using Flashback Database after a failing over to a physical standby databases. You can use Flashback Database to reinstate any physical standby databases that were disabled but were not the target of the failover.</p>
LogArchiveMaxProcesses	Range of valid values is now from 1 to 30 (was from 1 to 10)
LsbyTxnConsistency	Now imports the value of PRESERVE_COMMIT_ORDER from SYSTEM.LOGSTDBY\$PARAMETERS instead of TRANSACTION_CONSISTENCY
NetTimeout	The default value has changed from 30 seconds to 180 seconds.

A.1.3 Changed State Names

Table A-3 shows the database state names that changed in Release 11.1:

Table A-3 Database State Name Changes in Release 11.1

Database Type	State Name Prior to Oracle Database 11.1	New State Name as of Oracle Database 11.1
Primary	ONLINE	TRANSPORT-ON
Primary	LOG-TRANSPORT-OFF	TRANSPORT-OFF
Physical standby	ONLINE	APPLY-ON
Physical standby	LOG-APPLY-OFF	APPLY-OFF
Physical standby	READ-ONLY	None ¹
Logical standby	ONLINE	APPLY-ON
Logical standby	LOG-APPLY-OFF	APPLY-OFF
All	OFFLINE	None ²

¹ Prior to Release 11.1, the READ-ONLY state allowed a physical standby database to be opened read-only. In Release 11.1, this database state has been deprecated because a physical standby database can apply redo while opened read-only. Therefore this state change operation through the broker is no longer necessary.

² This database state has been deprecated. You can shut down a database using either the SQL*Plus SHUTDOWN command or the DGMGRL SHUTDOWN command.

See Also: [Section 4.2, "Database States"](#)

A.1.4 Changed DGMGRL Features in Release 10.2

Data Guard command-line interface (DGMGRL) commands that changed in Oracle Database 10g (10.2) include:

- `FAILOVER`
- `EDIT CONFIGURATION`
- `EDIT DATABASE`
- `SHOW CONFIGURATION`

See Also: [Chapter 8, "Data Guard Command-Line Interface Reference"](#)

A.2 Deprecated and Obsolete Features

The following sections list features that have been deprecated or made obsolete:

- [Deprecated and Obsolete Features in Release 11.1](#)
- [Deprecated and Obsolete Features in Release 10.2](#)

A.2.1 Deprecated and Obsolete Features in Release 11.1

This section contains information about Data Guard broker features that were deprecated or are obsolete.

- Deprecated database properties include:
 - `LocalListenerAddress`
 - The `READ-ONLY` state for physical standby databases has been deprecated
 - The `OFFLINE` and `ONLINE` states have been deprecated
- The `ADD DATABASE . . . MAINTAINED AS {PHYSICAL|LOGICAL}` statement is deprecated. Specifically, the `MAINTAINED AS` clause of `ADD DATABASE` command is deprecated. The broker now automatically finds out the standby database type.

A.2.1.1 Deprecated and Obsolete Properties in Release 11.1

Table A-4 *Deprecated and Obsolete Properties in Release 11.1*

Deprecated Property	Replacement Property (if any)
<code>LsbyTxnConsistency</code>	<code>LsbyPreserveCommitOrder</code>

A.2.2 Deprecated and Obsolete Features in Release 10.2

This section contains information about Data Guard broker features that were deprecated or are obsolete.

A.2.2.1 Deprecated and Obsolete Properties in Release 10.2

Table A-5 *Deprecated and Obsolete Properties in Release 10.2*

Deprecated Property	Replacement Property (if any)
ApplyNext	No replacement.
ApplyNoDelay	Set the DelayMins property to zero (0).
AsyncBlocks	None. Specifying the number of blocks is no longer necessary. The transport mode is determined <i>automatically</i> by redo transport services, based on the protection mode defined for the Data Guard configuration.
RealTimeApply	Set the DelayMins property to zero (0).

Data Guard Broker Upgrading and Downgrading

This appendix guides you through the process of upgrading or downgrading the Oracle databases and Oracle Enterprise Manager in a broker configuration. It contains the following topics:

- [Section B.1, "Upgrade from Release 9.2.0 to Release 11.1"](#)
- [Section B.2, "Upgrade from Release 10.n to Release 11.1"](#)
- [Section B.3, "Downgrade from Release 11.1"](#)

See Also: [Chapter 2, "Oracle Data Guard Installation"](#)

B.1 Upgrade from Release 9.2.0 to Release 11.1

If you are currently running an Oracle Data Guard release 9.2.0 configuration, you must upgrade to Oracle Database release 11.1, and re-create the broker configuration, as follows:

1. Delete (remove) the release 9.2.0 broker configuration using Data Guard Manager or DGMGRL release 9.2.0. For example, the DGMGRL `REMOVE CONFIGURATION` command can be used.
2. If using DGMGRL, clear the `LOG_ARCHIVE_DEST_n` initialization parameter settings by using the `ALTER SYSTEM SET LOG_ARCHIVE_DEST_n=" " SQL*Plus` command.
3. Upgrade the database software to Oracle release 11.1. See the Oracle Database installation documentation that is appropriate for your operating system.
4. If you are using Oracle Enterprise Manager and Data Guard Manager release 9.2.0, you must upgrade to Oracle Enterprise Manager release 10.2 to manage a broker configuration running Oracle Data Guard release 11.1. Data Guard Manager release 9.2.0 is not compatible with Oracle Data Guard release 11.1.
5. If you are using DGMGRL release 9.2.0, you must upgrade to Data Guard command-line interface release 11.1:
 - DGMGRL release 9.2.0 is not compatible with Oracle Data Guard release 11.1.

Note: Existing Oracle9i command-line scripts are supported in Oracle Database 11.1 for non-RAC databases. See [Appendix A](#) for information about deprecated commands.

- DGMGRL release 11.1 is not compatible with Oracle Data Guard release 9.2.0.

Note: Oracle Database 11.1 command-line scripts are not supported in Oracle9i.

6. Invoke Enterprise Manager or the DGMGRL command-line interface, and re-create the broker configuration.

B.2 Upgrade from Release 10.n to Release 11.1

If you are currently running an Oracle Data Guard release 10.n configuration, you can upgrade the database software to Oracle release 11.1 using the Oracle Database installation documentation that is appropriate for your operating system.

Step 1 Disable fast-start failover if it is enabled.

Issue the following DGMGRL command to disable fast-start failover:

```
DGMGRL> DISABLE FAST_START FAILOVER;
```

Step 2 Shut down the 10.n Data Guard broker.

Disable the broker's management of the configuration and then stop the broker. For example:

1. Issue the following DGMGRL command to disable the broker's active management of the databases in the Data Guard configuration:

```
DGMGRL> DISABLE CONFIGURATION;
```

2. Issue the following SQL*Plus statement to stop the broker:

```
SQL> ALTER SYSTEM SET DG_BROKER_START=FALSE;
```

Step 3 Make a copy of the current broker configuration files.

Make a copy of the current broker configuration files, as indicated by the following initialization parameters: `DG_BROKER_CONFIG_FILE1` and `DG_BROKER_CONFIG_FILE2`.

Step 4 Upgrade the Oracle Database software to release 11.1.

For step-by-step upgrade instructions, see the Oracle Database installation documentation that is appropriate for your operating system.

To upgrade Oracle Enterprise Manager Grid Control or DGMGRL, consider the following:

- If you are running Oracle Enterprise Manager Grid Control release 10.n, you can use it to manage a broker configuration running Oracle Data Guard release 11.1.
- If you are using DGMGRL release 10.n, you must upgrade to Data Guard command-line interface release 11.1 to manage a broker configuration running Oracle Data Guard release 11.1.

Note: Existing release 10.*n* DGMGRL command-line scripts are supported by the DGMGRL command-line interface available in release 11.1.

Release 11.1 DGMGRL command-line scripts are not guaranteed to be supported by Oracle Database release 10.*n*.

Step 5 Start the broker.

After the upgrade, start the release 11.1 Data Guard Broker. For example:

1. Issue the following SQL*Plus statements to start the broker:

```
SQL> ALTER SYSTEM SET DG_BROKER_START=TRUE;
```

2. Issue the following DGMGRL command to enable the broker's active management of the databases in the Data Guard configuration:

```
DGMGRL> ENABLE CONFIGURATION
```

The first time the release 11.1 broker starts, it will detect the existence of the release 10.*n* broker configuration files and automatically upgrade them to include any new properties that were introduced in release 11.1 (for example, the fast-start failover properties). This automatic conversion is transparent, permanent, and occurs only once.

See Also: [Appendix A, "Changed and Deprecated Features"](#)

B.3 Downgrade from Release 11.1

If you have upgraded to release 11.1 and want to downgrade to your prior release, you must downgrade the database release and re-create the broker configuration as follows:

1. Delete (remove) the release 11.1 broker configuration using Enterprise Manager or DGMGRL release 11.1. For example, the DGMGRL `REMOVE CONFIGURATION` command can be used.
2. Downgrade the Oracle Database software to the prior Oracle release. See the Oracle Database documentation that is appropriate for your operating system.
3. You can downgrade the Data Guard broker to release 10.*n*, as follows:
 - If you are confident that you made no changes to your broker configuration after upgrading to release 11.1, you can copy the broker configuration files that you created during the upgrade procedure (described in [Section B.2](#)). Then, invoke Enterprise Manager or the DGMGRL command-line interface and reenable the broker configuration as it existed at the time you made that copy.
 - Alternatively, you can invoke Enterprise Manager or the DGMGRL command-line interface to re-create the broker configuration.
4. You can downgrade the Data Guard broker to Oracle release 9.2.0, as follows:
 - If you were using Enterprise Manager, you can continue to use the Oracle Enterprise Manager release 10.2 to manage your 9.2.0 broker configuration. You can also downgrade to the Data Guard Manager by re-installing Oracle Enterprise Manager release 9.2.0.

- Invoke Enterprise Manager, the Data Guard Manager, or the DGMGRL command-line interface and re-create the broker configuration.

Glossary

apply instance

In an Oracle Real Application Clusters (RAC) databases environment, the apply instance is the one instance applying archived redo data to a standby database.

broker

A distributed management framework that automates and simplifies most of the complex operations required to create, control, and monitor a Data Guard configuration.

broker configuration

A logical grouping of the primary and standby databases (including redo transport services and log apply services) of a Data Guard configuration.

See also [Data Guard configuration](#).

configuration object

A named collection of database objects. It is an abstraction of a Data Guard configuration.

database guard

The database guard controls whether or not modifications can be made to the tables in a logical standby database.

database object

A named object that corresponds to a primary or standby database in a Data Guard configuration. The broker uses this object to manage and control the state of a single database and to associate properties with the database.

Data Guard command-line interface

The Data Guard command-line interface (DGMGRL) enables you to control and monitor a Data Guard configuration from the DGMGRL prompt or within scripts.

Data Guard configuration

A distributed computing system that prevents or minimizes losses due to unplanned events (for example, human errors, environmental disasters, or data corruption) as well as to planned downtime (such as for routine maintenance tasks).

See also [broker configuration](#).

Data Guard environment

The physical configuration of the primary and standby databases. The environment depends on many factors, including the:

- Number of standby databases associated with a primary database
- Number of host systems used by the databases
- Directory structures of the machines used by the databases
- Network configuration
- Redo transport services
- Log apply services

The Data Guard environment can be managed manually by a DBA, automatically using Enterprise Manager or the Data Guard command-line interface (DGMGRL) or a combination of all of these.

default state

The initial runtime state in which the database object will run when you enable broker management of the configuration. The actual default state can vary depending on the role (primary or standby) in which the database is running.

See also [intended state](#).

failover

Failover changes a standby database into the role of a primary database and disables the old primary database.

See also [fast-start failover](#) and [manual failover](#).

fast-start failover

Enables a failover *automatically* when the primary database becomes unavailable. When fast-start failover is enabled, the broker determines if a failover is necessary and automatically, quickly, and reliably fails over to a designated standby without requiring that you perform any manual steps to invoke the failover.

See also [manual failover](#).

instance object

A named object; a database object is a collection of one or more named instance objects. The broker uses this object to manage and control the state of the database with which the instance is associated, and to associate instance-specific properties with this instance of the database.

intended state

The runtime state of a database object while it is enabled for management by the broker.

See also [default state](#).

lights out computing

Refers to computing equipment or software whose operations are automated, requiring little to no intervention by human administrators.

The term "lights out" originated from when computing centers were located in one room and contained a number of servers that were kept under lock and key and in the

dark. Under normal operation, the room was not entered by human administrators, and all operations in the room were automated.

logical standby database

A logical standby database takes standard Oracle archived redo log files, transforms them back into SQL transactions, and then applies them to an open standby database. Although changes can be applied concurrently with end-user access, the tables being maintained through regenerated SQL transactions allow read-only access to users of the logical standby database. Because the database is open to allow application of reconstructed SQL transactions, it is physically different from the primary database. The database tables can have different indexes and physical characteristics from their primary database peers, but the tables must maintain logical consistency from an application access perspective, to fulfill their role as a standby data source.

manual failover

A failover that is initiated by the DBA who first determines a failover is necessary and then invokes one by clicking `FAILOVER` in Enterprise Manager or by issuing the `DGMGRL FAILOVER` command. The word *manual* is used to contrast this type of failover with a fast-start failover.

See also [fast-start failover](#).

observer

A DGMGRL client that continuously monitors the primary and target standby databases, evaluates whether failover is necessary, and initiates a fast-start failover when conditions warrant.

physical standby database

A physical standby database is an exact copy of a primary database. While the primary database is open and active, a physical standby database uses Redo Apply Services to apply redo data received from the primary database. Redo Apply Services can run on a physical standby database instance that is mounted. If a license for the Oracle Active Data Guard option has been purchased, Redo Apply Services can also run on a physical standby database instance that is open. See *Oracle Data Guard Concepts and Administration* for more details.

primary database

A production database from which one or more standby databases is created and maintained. Every standby database is associated with one and only one primary database. A single primary database can, however, support multiple standby databases. The Data Guard broker monitor (DMON) maintains the master copy of the binary configuration file with the primary database, ensuring that each standby database's copy of the file is kept up to date as changes are made.

The broker refers to this database using the value in the `DB_UNIQUE_NAME` initialization parameter which is defined to be globally unique.

profiles

The description of a database object including its current state (on or off), properties, and current status (for example, its health). This description is maintained persistently by the broker in its binary configuration file.

read-only mode

A mode in which a database can be opened that allows queries, but disallows modifications.

A physical standby database can be opened read-only so that queries may be performed. If a license for the Oracle Active Data Guard option has been purchased, a physical standby database can be open while redo apply is active. This capability is known as real-time query. See *Oracle Data Guard Concepts and Administration* for more details.

Redo Apply

A physical standby database is kept synchronized with the primary database through Redo Apply, which recovers the redo data received from the primary database and applies the redo to the physical standby database.

SQL Apply

A logical standby database is kept synchronized with the primary database through SQL Apply, which transforms the data in the redo received from the primary database into SQL statements and then executes the SQL statements on the standby database.

standby database

A copy of a primary database created using a backup of your primary database. Standby databases are kept synchronized with the primary database by applying archived redo data over time from the primary database to each standby database. The standby database can take over processing from the primary database, providing nearly continuous database availability. A standby database has its own server parameter file, control file, and datafiles. It also has a copy of the broker's configuration file, kept up to date at the direction of the DMON process running in the primary database instance.

The broker refers to a standby database by its globally unique name that is stored in its `DB_UNIQUE_NAME` initialization parameter.

See also [logical standby database](#) and [physical standby database](#).

A

- Add Standby Database wizard
 - creating a broker configuration, 3-8, 6-4
 - creating a standby database, 6-4
 - definition, 1-8
 - introduction, 1-8
- adding
 - an existing RAC standby database, 6-12
 - standby database to the broker configuration, 7-4
- ALTER SYSTEM statement
 - starting the broker, 7-1
- altering
 - properties
 - database, 7-11
 - states
 - database, 7-11, 7-12
- AlternateLocation property, 9-10
 - setting log apply services, 4-9
- application integration, 1-6
- apply errors
 - managing, 4-13
- apply instance, 4-13
 - failover, 4-13
 - PreferredApplyInstance property, 4-14
 - selecting, 4-14
- ApplyInstanceTimeout property, 4-15, 9-11
- ApplyParallel property, 4-12, 9-11
- architecture
 - Data Guard broker, 1-7
- ARCHIVE_LAG_TARGET initialization parameter
 - setting in a broker configuration, 9-12
- archived redo logs
 - destination and configuration parameters, 3-1
 - in a Data Guard configuration, 3-2
 - primary database setup, 2-3
- ArchiveLagTarget property, 9-12
- ASYNC redo transport service, 4-8
- Automatic Storage Management (ASM)
 - creating a standby database that uses, 2-2
- suppressing from DGMGRL command-line
 - interface output, 8-1
- before you perform a switchover, 5-4
- before you use DGMGRL, 7-1
- benefits
 - Data Guard broker, 1-3
 - high availability, 1-4
 - scalability, 1-4
 - with Real Application Clusters, 1-4
- binary configuration file, 1-11
- Binding property, 9-12
- broker
 - components, 1-7
 - configuration, 1-1
 - Data Guard configuration file, 1-12
 - drc* log files, 10-1
 - installation, 2-2
 - introduction, 1-2
 - managing databases, 4-1
 - user interfaces, 1-8
- broker configurations
 - add an existing RAC standby database, 6-12
 - benefits, 1-3
 - changing roles, 3-9
 - components, 3-1
 - creating, 6-4, 7-2, 8-12
 - Data Guard configuration file, 1-10
 - database objects, 1-7
 - database profiles, 1-6
 - disabling databases, 3-10, 8-14
 - effects of removing metadata from, 8-40
 - enabling, 7-6, 8-27
 - enabling databases, 3-9, 3-10, 7-6, 8-27
 - enabling fast-start failover, 8-29
 - health, 1-10, 3-11
 - instance objects, 1-7
 - life cycle, 3-8
 - management, 1-6, 1-8, 1-9, 1-11
 - monitoring, 6-30, 7-22
 - objects, 1-6
 - Oracle Net Services configuration, 1-5, 1-8
 - overview, 3-1
 - properties, 4-4
 - protection modes, 8-19
 - removing, 6-40
 - setting protection mode, 4-15

B

- background processes
 - DMON, 1-10
- banners

- status modes, 3-11
- supported, 1-6, 3-1
- verifying, 6-31

BystandersFollowRoleChange property, 9-13

C

CFS

See cluster file system

changed features, A-1

changing

properties

- databases in a broker configuration, 3-10, 4-6

- of a database in a broker configuration, 6-21

protection mode

- of a database in a broker configuration, 6-23

roles

- within the broker configuration, 3-9

states

- databases in a broker configuration, 4-3

- of a standby database in a broker

 - configuration, 6-20

- of databases in a broker configuration, 7-11

See also editing

cluster file system (CFS)

- broker configuration files, 3-5

Cluster Ready Services (CRS), 1-4

command prompts

- suppressing from DGMGRL command-line

 - interface output, 8-1

command-line interface

See Data Guard command-line interface (DGMGRL)

CommunicationTimeout property, 9-14

COMPATIBLE initialization parameter

- requirements for setting, 2-3

complete failover, 5-7, 8-33

- reinstating disabled databases, 5-13

components

- broker, 1-7

- Data Guard configuration, 3-1

configurable properties, 4-4

- AlternateLocation, 9-10

- ApplyInstanceTimeout, 9-11

- ApplyParallel, 9-11

- ArchiveLagTarget, 9-12

- Binding, 9-12

- CommunicationTimeout, 9-14

- database, 4-6, 9-8

- DbFileNameConvert, 9-14

- DelayMins, 9-15

- DGConnectIdentifier, 9-16

- FastStartFailoverAutoReinstate, 9-17

- FastStartFailoverLagLimit, 9-17

- FastStartFailoverPmyShutdown, 9-18

- FastStartFailoverTarget, 9-19

- FastStartFailoverThreshold, 9-19

- LogArchiveFormat, 9-20

- LogArchiveMaxProcesses, 9-21

- LogArchiveMinSucceedDest, 9-21

- LogArchiveTrace, 9-22

- LogFileNameConvert, 9-23

- LogShipping, 9-23

- LogXptMode, 9-24

- LsbyASkipCfgPr, 9-25

- LsbyASkipErrorCfgPr, 9-25

- LsbyASkipTxnCfgPr, 9-26

- LsbyDSkipCfgPr, 9-27

- LsbyDSkipErrorCfgPr, 9-27

- LsbyDSkipTxnCfgPr, 9-28

- LsbyMaxEventsRecorded, 9-29

- LsbyMaxServers, 9-29

- LsbyMaxSga, 9-29

- LsbyPreserveCommitOrder, 9-32

- LsbyRecordAppliedDdl, 9-30

- LsbyRecordSkipDdl, 9-30

- LsbyRecordSkipErrors, 9-31

- managing redo transport services, 4-7

- MaxConnections, 9-32

- MaxFailure, 9-33

- NetTimeout, 9-33

- PreferredApplyInstance, 9-34

- RedoCompression, 9-35

- ReopenSecs, 9-36

- SidName, 9-36

- StandbyArchiveLocation, 9-37

- StandbyFileManagement, 9-38

- TopWaitEvents, 9-8

configuration files

- fast-start failover configuration (fsfo.dat)

 - file, 5-36

- See Also* Data Guard configuration file

configuration properties

- BystandersFollowRoleChange, 9-13

CONNECT command, 7-3, 8-8

connecting

- privileges required for Data Guard broker

 - configurations, 8-4

- starting the observer, 7-10

- to the primary database, 7-2

controlling

- available SGA memory, 4-12

- transaction commit order, 4-12

CREATE CONFIGURATION command, 7-3, 8-12

creating

- a broker configuration, 6-4, 7-2, 7-3, 8-12

 - with the Add Standby Database wizard, 3-8

- a standby database, 3-8, 6-4

D

Data Guard

- troubleshooting, 10-1

Data Guard broker

- changed features, A-1

- deprecated features, A-1

- integration with Oracle Enterprise Manager, 6-1

- See Also* broker

Data Guard command-line interface

- commands, 1-9

- ENABLE FAST_START FAILOVER, 8-29
 - SET STATE, 4-14
- DG_BROKER_START initialization
 - parameter, 2-2
- enabling a database, 7-6
- introduction, 1-2, 1-9
- Data Guard command-line interface (DGMGRL)
 - banners from output, 8-1
 - commands
 - CONNECT, 8-8
 - CREATE CONFIGURATION, 8-12
 - DISABLE CONFIGURATION, 8-14
 - DISABLE DATABASE, 8-15
 - DISABLE FAST_START FAILOVER, 5-30, 8-16
 - DISABLE FAST_START FAILOVER CONDITION, 8-17
 - EDIT CONFIGURATION (property), 8-18
 - EDIT CONFIGURATION (protection mode), 8-19
 - EDIT DATABASE (property), 8-21
 - EDIT DATABASE (rename), 8-23
 - EDIT DATABASE (state), 8-24
 - EDIT INSTANCE (AUTO PFILE), 8-25
 - EDIT INSTANCE (property), 8-26
 - ENABLE CONFIGURATION, 8-27
 - ENABLE DATABASE, 8-28
 - ENABLE FAST_START FAILOVER CONDITION, 8-31
 - EXIT, 8-32
 - FAILOVER, 7-18
 - HELP, 8-36
 - QUIT, 8-38
 - REMOVE CONFIGURATION, 8-40
 - REMOVE DATABASE, 8-42
 - REMOVE INSTANCE, 8-44
 - SHOW CONFIGURATION, 8-45
 - SHOW DATABASE, 8-47
 - SHOW FAST_START FAILOVER, 8-50
 - SHOW INSTANCE, 8-51
 - SHUTDOWN, 8-53
 - STARTUP, 8-56
 - SWITCHOVER, 7-15, 8-59
 - creating a configuration, 7-2
 - DG_BROKER_START initialization
 - parameter, 8-4
 - enabling the configuration, 7-6
 - FSFO.DAT file creation, 8-54
 - monitoring broker configurations, 7-22
 - performing routine management tasks, 7-11
 - prerequisites, 7-1
 - setting critical database properties, 7-4
 - setting up standby redo log files, 4-17
 - single command mode, 8-1
 - starting, 7-2, 8-1
 - stopping, 8-5
 - string values, 8-5
 - summary of commands, 8-3
 - suppressing command prompts, 8-1
- Data Guard configuration file
 - for a RAC database, 3-4
 - in a CFS area, 3-5
 - inconsistent values from server parameter file, 9-2
 - on a raw device, 3-6
 - relationship to DMON process, 1-10
 - renaming, 1-11
 - setting up, 3-3
- Data Guard configurations
 - automated creation of, 1-5
 - background, 3-2
 - supported, 3-1
- Data Guard Fast-Start Failover metrics
 - understanding, 6-36
- Data Guard monitor (DMON), 1-10
 - interaction with the Oracle database, 1-10
 - maintaining configuration data, 1-11
 - managing objects, 3-2, 3-9, 7-6
 - Oracle database background processes, 1-10
 - overview, 1-10
 - removing objects, 7-13
 - starting with the DG_BROKER_START parameter, 3-7
 - two-way network communication, 1-11
- Data Guard Performance metric
 - understanding, 6-36
- Data Guard Status metric
 - understanding, 6-36
- data protection modes
 - See* protection modes
- database resources
 - monitoring, 1-6
- databases
 - changing the state of, 7-11
 - connecting to, 7-2
 - creating and adding to a broker
 - configuration, 1-8
 - dependencies, 4-1
 - disabling management of, 8-14
 - during
 - fast-start failover, 5-14
 - manual failover, 5-6
 - switchover, 5-3
 - enabling, 7-6
 - health, 4-24
 - installation for broker management, 2-2
 - monitorable database properties, 4-5, 9-1 to 9-7
 - network setup, 1-11, 2-2
 - objects, 1-6
 - definition, 1-7
 - in a broker configuration, 1-7
 - prerequisites for broker configurations, 2-2
 - properties, 1-8, 4-6, 9-8 to 9-38
 - property management, 1-12
 - reenabling after a role transition, 5-11
 - removing
 - from a broker configuration, 7-14
 - restarting
 - after fast-start failover, 5-38
 - shutting down

- effect on fast-start failover, 5-23, 5-25, 5-38
- states, 4-1
 - dependencies, 4-1
 - transitions, 4-3
- status, 4-24
- DB_FILE_NAME_CONVERT initialization parameter
 - initialization parameters
 - setting DB_FILE_NAME_CONVERT in a broker configuration, 9-14
- db_unique_name_DGMGRL static service name
 - registering, 2-2
- DBA_LOGSTDBY_EVENTS table
 - managing, 4-13
- DbFileNameConvert property, 9-14
- delaying
 - application of redo data with DelayMins property, 4-12
- DelayMins property, 9-15
 - delaying log apply services, 4-12
- deprecated features, A-1
- destinations
 - archived redo log file parameters, 3-1
 - viewing the LogXptStatus property, 9-3
- DG_BROKER_CONFIG_FILEn file, 1-11, 3-4
 - in a CFS area, 3-5
 - on a raw device, 3-6
- DG_BROKER_START initialization parameter, 2-2, 7-1, 8-4
- DGConnectIdentifier property, 9-16
- DGMGRL commands
 - FAILOVER, 8-33
 - SWITCHOVER, 8-59
- diagnostic information
 - sources, 10-1
- DISABLE CONFIGURATION command, 8-14
 - example, 7-12
- DISABLE DATABASE command, 8-15
 - example, 7-13
- DISABLE FAST_START FAILOVER command, 5-30, 8-16
- DISABLE FAST_START FAILOVER CONDITION command, 8-17
- disabling
 - broker configuration, 7-12, 8-14
 - broker management of standby database, 8-15
 - databases, 3-10, 7-12
 - fast-start failover, 5-29, 8-16
 - on a standby database, 5-30
 - See also* each DISABLE command
- disaster protection
 - benefits, 1-4
- displaying
 - configuration information, 8-45
 - help for DGMGRL commands, 8-36
 - help for Enterprise Manager, 6-4
 - properties, 4-4
- distributed management framework, 1-2
- DMON
 - See* Data Guard monitor (DMON)
- downgrading

- Data Guard, B-3
- Oracle Enterprise Manager, B-3
 - protection mode, 4-18
- drc* log files
 - broker diagnostic information, 10-1
 - during reinstatement, 5-28
 - recording failed reinstatement, 5-38

E

- EDIT CONFIGURATION (Property) command, 8-18
- EDIT CONFIGURATION (protection mode) command, 8-19
- EDIT DATABASE (property) command, 8-21
 - example, 7-11
- EDIT DATABASE (rename) command, 8-23
- EDIT DATABASE (state) command, 8-24
 - example, 7-11
- EDIT INSTANCE (AUTO PFILE) command, 8-25
- EDIT INSTANCE (property) command, 8-26
- editing
 - configurable properties, 8-18
 - database instance, 8-25, 8-26
 - database name, 8-23
 - database properties, 8-21
 - database state, 8-24
 - protection modes, 8-19
- effect of switchovers on, 5-6
- e-mail
 - reporting events, 1-8
- ENABLE CONFIGURATION command, 7-6, 8-27
- ENABLE DATABASE command, 8-28
- ENABLE FAST_START FAILOVER command, 8-29
- ENABLE FAST_START FAILOVER CONDITION command, 8-31
- enabling
 - broker configuration, 3-9, 7-6
 - databases in a broker configuration, 3-10
 - fast-start failover, 5-16, 5-20, 6-14
 - See also* each ENABLE command
- Enterprise Edition database
 - installation, 2-1
- Enterprise Manager
 - adding an existing RAC standby database, 6-12
 - changing
 - database properties, 6-21
 - database protection mode, 6-23
 - database state, 6-20
 - creating
 - a configuration, 6-4
 - a standby database, 6-4
 - Fast-Start Failover wizard
 - disabling fast-start failover, 5-30
 - managing metrics, 6-36
 - monitoring
 - broker configurations, 6-30
 - configuration performance, 6-34
 - performing
 - fast-start failover, 6-14
 - manual failover, 6-27

- routine maintenance, 6-20
 - switchover, 6-25
- removing
 - broker configuration, 6-40
 - standby database, 6-39
- starting, 6-1
- using metrics, 6-36
- verifying a broker configuration, 6-31
- viewing log file details, 6-33
- wizards
 - automate standby database creation, 1-3
- error messages
 - ORA-16795, 5-11
- error status, 3-11
- events
 - managing
 - in a logical standby database, 4-13
 - monitoring with Oracle Enterprise Manager, 1-3
 - Oracle Enterprise Manager, 1-6
 - reporting, 1-8
 - responding to, 1-6
- EXIT command, 8-32
 - See also* QUIT command

F

- failover
 - failing over to a standby database, 8-33
 - Oracle Enterprise Manager, 1-8
- FAILOVER command, 7-18, 8-33
- failovers
 - and FastStartFailoverTarget property, 7-9
 - benefits, 1-5
 - broker tasks, 5-9
 - choosing a target standby database, 5-2
 - complete, 5-8, 5-9
 - defined, 5-1
 - fast-start failover, 5-25
 - effect on data protection mode, 5-16
 - V\$DATABASE, 5-27
 - immediate, 5-11
 - managing, 5-1
 - fast-start, 5-14
 - manual, 5-6
 - manual
 - complete option, 5-7
 - effect on data protection mode, 5-9
 - immediate option, 5-7
 - reenabling disabled databases after, 5-10, 5-11
 - scenario
 - fast-start failover, 6-14
 - manual failover, 6-27
 - starting manually, 5-8
 - using DGMGRL, 7-18
- failures
 - observer, 5-35
- fast-start failover, 5-1
 - conditions resulting in, 5-22
 - configuration information in the fsfo.dat file, 5-36
 - defined, 5-14

- DGMGRL client as the observer, 1-9
 - disabling, 5-29, 5-30
 - to perform manual failover, 5-31
 - enabling, 5-20, 6-14, 8-29
 - instance failures, 5-22
 - monitoring by the observer, 5-22
 - observer monitoring, 5-22
 - observer overview, 5-15
 - performing manual failovers when enabled, 5-25
 - performing switchover when enabled, 5-25
 - querying V\$DATABASE, 5-25
 - reinstating the former primary database, 5-37
 - requirements, 5-16
 - restarting databases after shut down, 5-38
 - setting the FastStartFailoverTarget property, 5-17, 7-9
 - setting the FastStartFailoverThreshold property, 5-18, 6-16
 - shutdown abort, 5-23, 5-25
 - shutting down databases, 5-38
 - to RAC database instances, 5-23
 - unobserved, 5-35
 - verifying the environment, 5-22
 - viewing failover configuration statistics, 5-27
- FastStartFailoverAutoReinstate property, 9-17
- FastStartFailoverLagLimit property, 9-17
- FastStartFailoverPmyShutdown property, 9-18
- FastStartFailoverTarget property, 9-19
 - setting, 5-17, 7-9
- FastStartFailoverThreshold property, 9-19
 - conditions causing fast-start failover, 5-22
 - setting, 5-18, 6-16
- files
 - naming the server parameter file, 1-12
- Flashback Database
 - reinstating databases, 5-13
 - use after failover, 5-10
- flashback logs
 - reinstating a failed primary database, 5-13
- FORCE option
 - disabling fast-start failover, 5-30, 8-16
 - performing a manual failover, 5-31
- FS_FAILOVER_OBSERVER_HOST column
 - of V\$DATABASE view, 5-34
- FS_FAILOVER_OBSERVER_PRESENT column
 - of V\$DATABASE view, 5-34
- FS_FAILOVER_STATUS column
 - of V\$DATABASE view
 - failed reinstatement, 5-28
- FSFO.DAT file
 - overview, 5-36
 - START OBSERVER command, 8-54

G

- global service names
 - registering, 2-2
- GLOBAL_DBNAME attribute
 - setting, 2-2

H

- health check, 1-6
 - monitoring, 1-10, 1-11
 - on primary database, 4-24
 - on standby database, 4-25
 - revealed by configuration status, 3-11
 - StatusReport property, 4-25
- HELP command, 8-36
- high availability
 - benefits, 1-4
 - levels of data protection, 4-15, 9-24
 - LogXptMode property, 9-24
 - restoring after fast-start failover, 5-37

I

- immediate failover, 5-7, 8-33
- InconsistentProperties property, 9-2
- increased scalability
 - benefits, 1-4
- initialization parameters
 - COMPATIBLE, 2-3
 - database configurable properties, 4-6
 - DG_BROKER_CONFIG_FILEn, 3-4
 - DG_BROKER_START, 2-2, 7-1
 - dynamic, 4-6
 - inconsistent, 9-2
 - LOG_ARCHIVE_DEST_n, 4-10
 - static, 4-6
 - See also* server parameter file, 2-2
- installation
 - ARCHIVELOG mode setup, 2-3
 - Data Guard, 2-1
 - Oracle Enterprise Manager, 2-1
 - Oracle Instant Client, 2-1, 8-54
 - prerequisites, 2-2
- instances
 - failures, 5-22
 - objects
 - in a broker configuration, 1-7
 - removing, 8-17, 8-31, 8-44
 - restarting during the course of broker operations, 2-2
 - shutting down, 8-53
 - starting, 8-56
- intended state
 - configuration health check, 3-11
- invoking
 - the Data Guard command-line interface, 7-2

L

- life cycle of a broker configuration, 3-8
- LISTENER.ORA file
 - registering global service names, 2-2
- local listener
 - statically registering services with, 2-2
- log apply services
 - and apply instance failover, 4-13
 - and parallel apply, 4-12

- apply instance, 4-13
- configuring, 1-5, 1-8
- Data Guard configuration, 3-2
- delayed application of redo data, 4-12
- delaying, 9-15
- in a RAC database, 4-13
- managing, 4-11
- selecting the apply instance, 4-14
- verifying, 1-5
- log files
 - broker, 5-38
 - FSFO.DAT
 - creating, 8-54
 - viewing, 6-33
- LOG_ARCHIVE_DEST_n initialization parameter
 - setting redo transport services, 4-10
 - setting the DELAY attribute, 9-15
 - setting the ENABLE and DEFER attributes, 9-23
 - setting the MANDATORY or OPTIONAL attributes, 9-12
- LOG_ARCHIVE_FORMAT initialization parameter, 9-20
- LOG_ARCHIVE_MAX_PROCESSES initialization parameter, 9-21
- LOG_ARCHIVE_MIN_SUCCEED initialization parameter, 9-21
- LOG_ARCHIVE_TRACE initialization parameter
 - setting LogArchiveTrace property, 9-22
- LOG_FILE_NAME_CONVERT initialization parameter
 - setting LogFileNameConvert property, 9-23
- LogArchiveFormat property, 9-20
- LogArchiveMaxProcesses property, 9-21
- LogArchiveMinSucceedDest property, 9-21
- LogArchiveTrace property, 9-22
- LogFileNameConvert property, 9-23
- logical standby databases
 - and SQL Apply error handling, 4-13
 - and SQL Apply filters, 4-13
 - managing events, 4-13
 - SQL Apply, 4-12
 - state transitions, 4-4
 - switchover to the primary role, 5-4
- LogShipping property, 9-23
- LogXptMode property, 9-24
- LogXptStatus property, 9-3
- LsbyASkipCfgPr property, 9-25
- LsbyASkipErrorCfgPr property, 4-13, 9-25
- LsbyASkipTxnCfgPr property, 9-26
- LsbyDSkipCfgPr property, 9-27
- LsbyDSkipErrorCfgPr property, 4-13, 9-27
- LsbyDSkipTxnCfgPr property, 9-28
- LsbyFailedTxnInfo property, 9-4
- LsbyMaxEventsRecorded property, 9-29
- LsbyMaxServers property, 9-29
- LsbyMaxSga property, 4-12, 9-29
- LsbyParameters property, 9-4
- LsbyPreserveCommitOrder property, 4-12, 9-32
- LsbyRecordAppliedDdl property, 9-30
- LsbyRecordSkipDdl property, 9-30

lsbyRecordSkipErrors property, 9-31
lsbySkipTable property, 9-4
lsbySkipTxnTable property, 9-5

M

management
 benefits, 1-5
 model, 1-6
 Oracle Enterprise Manager, 1-8
managing
 a broker configuration, 3-1, 7-1
 apply errors, 4-13
 Data Guard metrics, 6-36
 databases, 4-1
 DBA_LOGSTDBY_EVENTS table, 4-13
 events
 in a logical standby database, 4-13
 fast-start failover, 5-14
 local operations, 1-2
 log apply services, 4-11
 manual failover, 5-6
 objects in a broker configuration, 1-7
 parallel apply in a physical standby
 database, 4-12
 remote operations, 1-2
 roles, 5-1
 fast-start failover, 5-14
 manual failover, 5-6
 switchover, 5-3
 switchover, 5-3
MANDATORY attribute
 set with the Binding property, 9-12
manual failover, 1-5, 5-1
 complete option, 5-7
 effect on protection modes, 4-19
 immediate option, 5-7
 performing when fast-start failover is
 enabled, 5-25, 5-31
 starting, 5-8
manual role changes
 performing when fast-start failover is
 enabled, 5-25
MaxConnections property, 9-32
MaxFailure property, 9-33
maximize availability, 1-5, 3-10, 9-24
maximize data protection, 1-5, 3-10, 9-24
maximize performance, 1-5, 3-10, 9-24
maximum availability
 data protection mode, 4-16
maximum performance
 data protection mode, 4-16
maximum protection
 data protection mode, 4-16
metrics
 Data Guard Fast-Start Failover, 6-36
 Data Guard Performance, 6-36
 Data Guard Status, 6-36
 managing, 6-36
 using, 6-36

monitorable properties, 4-4
 database, 4-5
 InconsistentProperties, 9-2
 LogXptStatus, 9-3
 lsbyFailedTxnInfo, 9-4
 lsbyParameters, 9-4
 lsbySkipTable, 9-4
 lsbySkipTxnTable, 9-5
 RecvQEntries, 9-5
 SendQEntries, 9-6
 StatusReport, 9-7
monitoring
 broker configurations, 1-10, 6-30, 7-1, 7-22
 configuration performance, 6-34
 local and remote databases, 1-6
 observer
 fast-start failover environment, 5-22
 Oracle Enterprise Manager performance
 page, 3-10
 through the command-line interface, 1-9

N

NetTimeout property, 9-33
networks
 Data Guard configuration, 3-1
 setting up files, 2-2
 two-way communication, 1-11
normal status, 3-11

O

objects
 broker configuration, 1-6, 3-2
 disabling, 7-12
 properties for databases, 1-12
 relationship, 1-7
observer, 5-15
 and FastStartFailoverThreshold property, 5-18,
 6-16
 connecting to the configuration, 7-10
 connection to the local computer, 5-34
 detecting
 database shutdown, 5-23, 5-25
 instance failures, 5-22
 failures, 5-35
 finding host machine name, 5-34
 installing Oracle Instant Client kit, 2-1, 8-54
 lost connection, 5-35
 maintaining fast-start failover configuration
 information, 5-36
 monitoring, 5-22
 shutting down, 5-38
 using Oracle Wallet for connection
 credentials, 8-8
operations
 complete failover, 8-33
 disable broker management
 effect on protection modes, 4-20
 downgrade

- effect on protection modes, 4-18
- effect on protection modes, 4-18
- enable broker management
 - effect on protection modes, 4-20
- failover, 7-18
- fast-start failover scenario, 6-14
- immediate failover, 8-33
- manual failover
 - effect on protection modes, 4-19
- manual failover scenario, 6-27
- removing a database from the configuration
 - effect on protection modes, 4-20
- OPTIONAL attribute
 - set with the Binding property, 9-12
- ORA-16661 message
 - reinstating a database, 5-11, 5-13
- ORA-16795 message
 - re-creating a database, 5-11
- Oracle Clusterware
 - and instances of a RAC database, 1-4
 - integration with Data Guard broker, 1-4
 - recover failed instances, 1-4
- Oracle Enterprise Manager, 1-8
 - Add Standby Database wizard, 1-8
 - database property pages, 1-8
 - downgrading, B-3
 - event management system, 1-6
 - integration, 1-8
 - integration with the Data Guard monitor, 1-8
 - introduction, 1-2, 1-7
 - making Oracle Net Services configuration
 - changes, 1-5, 1-8
 - monitoring events, 1-3
 - performance tools and graphs, 1-8
 - setting up standby redo log files, 4-17
 - upgrading, B-1
 - wizards
 - creating standby databases, 1-8
- Oracle Instant Client
 - installing, 2-1, 8-54
- Oracle Managed Files (OMF)
 - creating a standby database that uses, 2-2
- Oracle Net Services
 - configuration changes, 1-5, 1-8
 - installation prerequisites, 2-2
 - supported configuration, 3-1
 - two-way communication, 1-11
- Oracle Universal Installer
 - installing Oracle Instant Client, 2-1, 8-54
- Oracle Wallet
 - starting the observer, 8-8

P

- parallel apply
 - and log apply services, 4-12
 - managing in a physical standby database, 4-12
- performance
 - Enterprise Manager tools, 6-34
 - Oracle Enterprise Manager tools, 1-8

- physical standby databases
 - managing parallel apply, 4-12
 - state transitions, 4-3
 - switchover to the primary role, 5-4
- PreferredApplyInstance property, 4-14, 9-34
- prerequisites
 - installation, 2-2
 - switchover, 5-4
- primary database
 - ARCHIVELOG mode, 2-3
 - configuration, 3-1
 - connecting to, 7-2
 - constructing a standby database, 3-8, 7-2
 - Data Guard configuration, 3-1
 - during failover, 1-8
 - during switchover, 5-6
 - failed
 - reenabling, 5-12
 - Flashback Database, 5-13
 - health check, 4-24
 - preparing for switchover, 5-4
 - reinstating
 - REINSTATEMENT command
 - how to reinstate a database, 5-13
 - reinstating after a fast-start failover, 5-37
 - shutting down when fast-start failover is
 - enabled, 5-38
 - standby redo log files on, 4-17
 - state transitions, 4-3
 - switching over to the standby role, 8-59
- processes
 - DMON, 1-10
 - Oracle database, 1-10
- properties, 4-6
 - AlternateLocation, 4-9
 - ApplyInstanceTimeout, 4-15
 - ApplyParallel, 4-12
 - configurable, 4-4
 - database, 4-4
 - DelayMins, 4-12
 - LsbyASkipErrorCfgPr, 4-13
 - LsbyDSkipErrorCfgPr, 4-13
 - LsbyMaxSga, 4-12
 - LsbyPreserveCommitOrder, 4-12
 - managing, 1-12
 - monitorable, 4-4
 - PreferredApplyInstance, 4-14
 - setting, 3-10, 6-21, 7-4
 - in server parameter file, 1-12, 2-2
 - StandbyArchiveLocation, 4-9
 - StatusReport, 4-25
- property pages
 - database, 1-8
- protection modes
 - after a failover, 4-19, 5-9, 5-16
 - benefits, 1-5
 - configuration, 8-19
 - downgrading, 4-18
 - of a database
 - changing in a broker configuration, 6-23

- redo transport services setup, 9-24
- setting for a broker configuration, 4-15
- updating, 3-10
- upgrading, 4-18

Q

- QUIT command, 8-38
 - See also* EXIT command

R

- raw devices
 - and broker configuration files, 3-6
 - sizing, 3-7
- Real Application Clusters
 - adding to a broker configuration, 6-12
 - and log apply services, 4-13
 - and setting the apply instance, 4-14
 - availability of instances with Oracle Clusterware, 1-4
 - benefits, 1-4
 - Cluster Ready Services (CRS), 1-4
 - fast-start failover, 5-23
 - observer behavior in, 5-23
 - observer connection to instances, 5-34
- RecvQEntries property, 9-5
- Redo Apply, 3-2, 5-6
- redo transport services
 - ASYNC mode, 4-8, 9-24
 - configuring, 1-5, 1-8
 - data protection modes, 9-24
 - Data Guard configuration, 3-1
 - LogShipping property, 9-23
 - managing, 4-7
 - SYNC mode, 4-8, 9-24
 - tuning, 4-10
 - turning off, 4-9
 - turning on, 4-8
 - verifying, 1-5
- RedoCompression property, 9-35
- reenabling
 - a database after failover or switchover, 5-11
- registering
 - db_unique_name_DGMGRL service name, 2-2
- reinstatement, 5-37
 - disabled databases, 5-13
 - failure logged in broker drc* log files, 5-28
 - Flashback Database requirement, 5-13
 - flashback logs requirement, 5-13
 - how to, 5-13
 - logged in broker log files, 5-38
 - ORA-16661 message, 5-11, 5-13
 - requires standby redo log files, 4-17
 - using DGMGRL
 - DGMGRL
 - reinstating a database, 5-14
 - using Enterprise Manager, 5-13
- REINSTATEMENT command, 5-13
- relationship

- objects in a broker configuration, 1-7
- REMOVE CONFIGURATION command, 8-40
 - example, 7-14
- REMOVE DATABASE command, 8-42
- REMOVE INSTANCE command, 8-44
- removing
 - a standby database, 4-20
 - broker configurations, 6-40
 - See each* REMOVE command
 - standby databases, 6-39
- ReopenSecs property, 9-36
- requests
 - passing between sites, 1-11
- requirements
 - for enabling fast-start failover, 5-16
- restarting
 - databases
 - when fast-start failover is enabled, 5-38
 - instances, 2-2
- role transitions
 - changing, 3-9
 - managing, 5-1
 - fast-start failover, 5-14
 - manual failover, 5-6
 - switchover, 5-3
 - reenabling databases after, 5-12

S

- scenarios
 - switchover, 6-25
- scripts
 - using Data Guard command-line interface (DGMGRL), 8-1
- selecting the apply instance, 4-14
- SendQEntries property, 9-6
- server parameter file
 - broker property management, 1-12, 2-2
 - filenames, 1-12
 - inconsistent values from Data Guard configuration file, 9-3
- server-side software, 1-10
- service names
 - registering
 - db_unique_name_DGMGRL, 2-2
- SET STATE command
 - and setting the apply instance, 4-14
- setting
 - configuration protection mode, 4-15
 - database properties, 7-4
 - log apply services, 4-9
 - redo transport services, 4-10
- SGA memory
 - and SQL Apply, 4-12
- SHOW CONFIGURATION command, 7-3, 7-4, 7-6, 8-45
- SHOW CONFIGURATION VERBOSE
 - example, 5-27
- SHOW DATABASE command, 8-47
- SHOW DATABASE VERBOSE command

- displaying properties, 4-4
- SHOW FAST-START FAILOVER command
 - example, 5-26
- SHOW INSTANCE command, 8-51
- SHOW SHOW FAST_START FAILOVER
 - command, 8-50
- showing
 - See each SHOW command
- shutdown
 - FS_FAILOVER_OBSERVER_PRESENT
 - view, 5-38
- shutdown abort, 5-23
 - effect on fast-start failover, 5-25
- SHUTDOWN command, 8-53
- shutting down an Oracle instance, 8-53
- SidName property, 9-36
- single command mode
 - for Data Guard command-line interface, 8-1
- SQL Apply, 3-2
 - and logical standby databases, 4-12
 - effect of switchovers on, 5-6
 - error handling
 - and logical standby databases, 4-13
 - filters
 - and logical standby databases, 4-13
- standby databases
 - changing the state of, 6-20
 - choosing a target standby database, 5-2
 - constructing from backups, 3-8, 7-2
 - creating, 1-8, 6-4
 - if primary database uses ASM or OMF, 2-2
 - Data Guard configuration, 3-1
 - health check, 4-25
 - not involved in a switchover, 5-6
 - reenabling after failover, 5-10
 - reinstating, 5-13
 - removing, 4-20, 6-39, 8-42
 - require standby redo log files, 4-17
 - shutting down when fast-start failover is
 - enabled, 5-38
 - specifying the location of archived redo logs, 4-9
 - switching over to the primary role, 8-59
- standby redo log files
 - setting up, 4-17
 - setting up with DGMGRL, 4-17
- StandbyArchiveLocation property, 9-37
 - setting log apply services, 4-9
- StandbyFileManagement property, 9-38
- START OBSERVER command
 - fast-start failover configuration file
 - (fsfo.dat), 5-36
- starting
 - Data Guard command-line interface
 - (DGMGRL), 7-2, 8-1
 - Data Guard monitor (DMON), 3-7
 - Data Guard Web pages in Enterprise
 - Manager, 6-1
 - manual failover, 5-8
 - Oracle instance, 8-56
 - switchover, 5-5
- STARTUP command, 8-56
- state transitions
 - effect on database states, 4-3
 - logical standby database, 4-4
 - physical standby database, 4-3
 - primary database, 4-3
- states, 3-10
 - changing, 7-11
 - database, 4-1
 - database transitions, 4-3
 - logical standby database
 - APPLY-OFF, 4-3
 - APPLY-ON, 4-2
 - of a standby database
 - changing in a broker configuration, 6-20
 - physical standby database
 - APPLY-OFF, 4-2
 - APPLY-ON, 4-2
 - primary database
 - TRANSPORT-OFF, 4-2
 - TRANSPORT-ON, 4-2
- status
 - configuration, 3-11
 - health check on primary database, 4-24
 - health check on standby database, 4-25
 - health of the database, 4-24
 - intended state of a configuration, 3-11
 - using metrics, 6-36
- status messages
 - ORA-16661, 5-11
 - ORA-16795, 5-11
- StatusReport property, 4-25, 9-7
- string values
 - Data Guard command-line interface, 8-5
- supported broker configuration, 1-6
- SWITCHOVER command, 7-15, 8-59
- switchovers
 - benefits, 1-5
 - broker tasks, 5-5
 - choosing a target standby database, 5-2
 - DGMGRL SWITCHOVER command, 7-15
 - effect on
 - database startup, 8-59
 - primary database, 5-6
 - protection modes, 4-19
 - standby databases not involved in the
 - switchover, 5-6
 - managing, 5-1, 5-3
 - overview, 5-1
 - Oracle Enterprise Manager, 1-8
 - performing when fast-start failover is
 - enabled, 5-25
 - preparing the primary database, 5-4
 - prerequisites, 5-4
 - reenabling disabled standby databases, 5-11
 - reinstating a database after, 5-11
 - scenario
 - Oracle Enterprise Manager, 6-25
 - starting, 5-5
 - transitioning

- a logical standby database to the primary role, 5-4
 - a physical standby database to the primary role, 5-4
- using the DGMGRL SWITCHOVER command, 8-59
- SYNC redo transport mode, 4-8
- SYSDBA privileges, 7-2
 - to connect to the database, 8-4

T

- target standby database
 - choosing, 5-2
 - disabling fast-start failover on, 5-30
 - setting with the FastStartFailoverTarget property, 5-17, 7-9
- TopWaitEvents property, 9-8
- transaction commit order
 - controlling, 4-12
- TRANSPORT-OFF state
 - LogShipping property setting, 9-23
- TRANSPORT-ON state
 - setting LogShipping property, 9-23
- troubleshooting
 - Data Guard, 10-1
 - diagnostics logged in broker drc* log files, 10-1
- tuning
 - redo transport services, 4-10
- two-way communication channel, 1-11

U

- understanding metrics, 6-36
- unobserved configuration, 5-35
- updating configuration properties, 4-4
- upgrading
 - Data Guard, B-1, B-2
 - Oracle Enterprise Manager, B-1
 - protection mode, 4-18
- user interfaces
 - overview, 1-8

V

- V\$DATABASE view
 - fast-start failover columns, 5-25, 5-27
 - FS_FAILOVER_OBSERVER_HOST column, 5-34
 - FS_FAILOVER_OBSERVER_PRESENT column, 5-34
 - when shutting down databases, 5-38
 - verifying
 - fast-start failover environment, 5-22
 - viewing
 - fast-start failover statistics, 5-27
- V\$FS_FAILOVER_STATS view, 5-29
- verifying
 - a broker configuration, 6-31
 - fast-start failover environment, 5-22
- viewing
 - log file details, 6-33

- property information about databases, 4-5, 9-1

W

- warning status, 3-11
- wizards
 - Add Standby Database, 1-8, 6-4

